

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286242

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Xu; Hu et al.

SECONDARY BATTERY, BATTERY MODULE, AND DEVICE USING SECONDARY BATTERY AS POWER SUPPLY

Abstract

This application provides a secondary battery, a battery module, and a device using a secondary battery as a power supply. The secondary battery includes an electrode assembly, a cap assembly, and current collection members. The electrode assembly includes a main body and tabs that extend from the main body. The cap assembly includes a cap plate, electrode terminals, and an insulation baffle. The electrode terminals are disposed on the cap plate. The insulation baffle is connected to a side of the cap plate, where the side is close to the main body. The current collection members are at least partly located between the insulation baffle and the main body, and each of the current collection members includes a tab connection portion connected to one of the tabs. The insulation baffle contains a first recess.

Inventors: Xu; Hu (Ningde, CN), Chen; Yuanbao (Ningde, CN), Xu; Long (Ningde, CN), Dong; Jiao (Ningde, CN)

Applicant: CONTEMPORARY AMPEREX TECHNOLOGY (HONK KONG) LIMITED
(Hong Kong, CN)

Family ID: 72621522

Appl. No.: 19/216760

Filed: May 23, 2025

Foreign Application Priority Data

CN

202020306566.8

Mar. 12, 2020

Related U.S. Application Data

parent US continuation 17826466 20220527 parent-grant-document US 12347890 child US 19216760

parent WO continuation PCT/CN2020/141780 20201230 PENDING child US 17826466

Publication Classification

Int. Cl.: **H01M50/533** (20210101); **H01M50/204** (20210101); **H01M50/249** (20210101); **H01M50/547** (20210101); **H01M50/59** (20210101)

U.S. Cl.:

CPC **H01M50/533** (20210101); **H01M50/204** (20210101); **H01M50/249** (20210101); **H01M50/547** (20210101); **H01M50/59** (20210101); H01M2220/20 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 17/826,466, filed on May 27, 2022, which is a continuation of International Application No. PCT/CN2020/141780, filed on Dec. 30, 2020, which claims priority to Chinese Patent Application No. 202020306566.8, filed on Mar. 12, 2020. The disclosures of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

[0002] This application relates to the field of batteries, and in particular, to a secondary battery, a battery module, and a device using a secondary battery as a power supply.

BACKGROUND

[0003] A secondary battery such as a lithium-ion battery is widely used in electronic devices such as a mobile phone and a notebook computer by virtue of a high energy density and environmental friendliness. In recent years, in order to cope with environmental issues, gasoline price issues, and energy storage issues, the application of lithium-ion batteries has been rapidly expanded to hybrid electric vehicles, ships, and energy storage systems.

[0004] A secondary battery includes an electrode assembly, a cap assembly, and current collection members. The electrode assembly includes a main body and tabs extending from the main body. The cap assembly includes a cap plate, an insulation baffle, and electrode terminals. Each of the current collection members connects a tab and an electrode terminal. The insulation baffle is connected between the cap plate and the current collection members, thereby reducing short-circuit risks caused by a contact between the current collection members and the cap plate.

[0005] However, the insulation baffle occupies space inside the secondary battery and reduces the energy density of the secondary battery.

SUMMARY

[0006] In view of the problems in the background technologies, an objective of this application is to provide a secondary battery, a battery module, and a device using a secondary battery as a power supply to increase an energy density and reduce short-circuit risks.

[0007] To achieve the foregoing objective, this application provides a secondary battery. The secondary battery includes an electrode assembly, a cap assembly, and current collection members. The electrode assembly includes a main body and tabs that extend from the main body. The cap assembly includes a cap plate, electrode terminals, and an insulation baffle. The electrode terminals are disposed on the cap plate. The insulation baffle is connected to a side of the cap plate, where the side is close to the main body. The current collection members are at least partly located between

the insulation baffle and the main body. Each of the current collection members includes a tab connection portion connected to one of the tabs. The insulation baffle contains a first recess. The first recess is recessed against a lower surface of the insulation baffle away from the main body, and the tab connection portion is at least partly accommodated in the first recess.

[0008] In a secondary battery according to some embodiments, the current collection member further includes a terminal connection portion. The terminal connection portion is connected to the electrode terminals. Both the terminal connection portion and the tab connection portion are flat plate structures. The tab connection portion is farther away from the main body than the terminal connection portion.

[0009] In a secondary battery according to some embodiments, the tab is connected to a side of the tab connection portion, where the side is close to the main body.

[0010] In a secondary battery according to some embodiments, a gap exists between the tab connection portion and a bottom face of the first recess.

[0011] In a secondary battery according to some embodiments, the current collection member further includes a tilt portion. The tilt portion is connected between the terminal connection portion and the tab connection portion. The tilt portion tilts against the terminal connection portion away from the main body.

[0012] In a secondary battery according to some embodiments, the terminal connection portion is parallel to the tab connection portion.

[0013] In a secondary battery according to some embodiments, the terminal connection portion includes a fixing region and a fuse region. The fixing region is connected to the electrode terminals. The fuse region is connected between the fixing region and the tilt portion.

[0014] In a secondary battery according to some embodiments, the current collection member further includes an insulation strip that wraps around the fuse region. A part of the insulation strip is accommodated in the first recess. A surface that is of the insulation strip and that is away from the main body is closer to the main body than a surface that is of the tab connection portion and that is away from the main body.

[0015] This application further provides a battery module. The battery module includes the secondary battery described above. The secondary battery is plural in number.

[0016] This application further provides a device using a secondary battery as a power supply. The device includes the secondary battery described above.

[0017] Beneficial effects of this application are as follows: By disposing the first recess, this application downsizes the insulation baffle, reduces the space occupied by the insulation baffle in the secondary battery, and increases the energy density of the secondary battery. The tab connection portion is at least partly accommodated in the first recess, thereby increasing a distance between the tab connection portion and the main body, providing more space for the tabs, reducing the risks of inserting the tabs into the main body, avoiding short circuits, and improving safety performance.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0018] To describe the technical solutions in the embodiments of this application more clearly, the following outlines the drawings used in the embodiments of this application. Evidently, the drawings outlined below are merely a part of embodiments of this application. A person of ordinary skill in the art may derive other drawings from the outlined drawings without making any creative efforts.

[0019] FIG. 1 is a schematic diagram of a device using a secondary battery as a power supply according to some embodiments;

[0020] FIG. 2 is a schematic diagram of a battery module according to some embodiments;

[0021] FIG. **3** is a schematic diagram of a secondary battery according to some embodiments;
[0022] FIG. **4** is an exploded view of the secondary battery shown in FIG. **3**;
[0023] FIG. **5** is a sectional view of an electrode assembly of a secondary battery according to some embodiments;
[0024] FIG. **6** is a top view of a secondary battery according to some embodiments;
[0025] FIG. **7** is a sectional view of the secondary battery shown in FIG. **6** and sectioned along an A-A line;
[0026] FIG. **8** is a locally enlarged view of a part indicated by a box in FIG. **7**;
[0027] FIG. **9** is a sectional view of the secondary battery shown in FIG. **6** and sectioned along a B-B line;
[0028] FIG. **10** is a locally enlarged view of a part indicated by a box in FIG. **9**;
[0029] FIG. **11** is a schematic diagram of a cap assembly and a current collection member according to some embodiments;
[0030] FIG. **12** is a schematic diagram of an insulation baffle according to some embodiments;
[0031] FIG. **13** is another schematic diagram of an insulation baffle according to some embodiments;
[0032] FIG. **14** is a schematic diagram of a current collection member according to some embodiments;
[0033] FIG. **15** is a schematic diagram of a current collection member according to other embodiments; and
[0034] FIG. **16** is a schematic diagram of a current collection member according to still other embodiments.

[0035] The drawings are not drawn to scale.

REFERENCE NUMERALS

[0036] **1**: Electrode assembly; [0037] **11**: Main body; [0038] **12**: Tab; [0039] **121**: First part; [0040] **122**: Second part; [0041] **13**: Positive electrode plate; [0042] **14**: Negative electrode plate; [0043] **15**: Separator; [0044] **2**: Housing; [0045] **3**: Top cover assembly; [0046] **31**: Top cover plate; [0047] **311**: Exhaust hole; [0048] **32**: Electrode terminal; [0049] **33**: Insulation baffle; [0050] **331**: Lower surface; [0051] **332**: First recess; [0052] **333**: First bulge; [0053] **334**: Upper surface; [0054] **335**: Second recess; [0055] **336**: Second bulge; [0056] **34**: Rupture disk; [0057] **4**: Current collection member; [0058] **41**: Terminal connection portion; [0059] **411**: Fixing region; [0060] **412**: Fuse region; [0061] **413**: Fuse hole; [0062] **42**: Tab connection portion; [0063] **421**: Connection sub-portion; [0064] **422**: Confluence portion; [0065] **43**: Tilt portion; [0066] **44**: Insulation strip; [0067] **1000**: Secondary battery; [0068] X: Length direction; [0069] Y: Thickness direction; and [0070] Z: Height direction.

DETAILED DESCRIPTION OF EMBODIMENTS

[0071] The following gives a more detailed description of implementations of this application with reference to accompanying drawings and embodiments. The detailed description of the following embodiments and the accompanying drawings are intended to exemplarily describe the principles of this application, but not to limit the scope of this application. Therefore, this application is not limited to the described embodiments.

[0072] In the description of this application, unless otherwise specified, “a plurality of” means two or more; the terms such as “upper”, “lower”, “left”, “right”, “inner”, and “outer” indicating a direction or a position relationship are merely intended for ease or brevity of description of this application, but do not indicate or imply that the device or component referred to must be located in the specified direction or constructed or operated in the specified direction. Therefore, such terms shall not be understood as a limitation on this application. In addition, the terms “first”, “second”, and “third” are merely intended for descriptive purposes, but are not intended to indicate or imply relative importance. “Perpendicular” is not exactly perpendicular, but within an error tolerance range. “Parallel” is not exactly parallel, but within an error tolerance range.

[0073] The directional terms appearing in the following description indicate the directions shown in the drawings, but are not intended to limit specific structures in this application. In the context of this application, unless otherwise expressly specified, the terms “mount”, “concatenate”, and “connect” are understood in a broad sense. For example, a “connection” may be a fixed connection, a detachable connection, or an integrated connection, and may be a direct connection or an indirect connection implemented through an intermediary. A person of ordinary skill in the art can understand the specific meanings of the terms in this application according to specific situations.

[0074] This application provides a device using a secondary battery as a power supply. The device is an electric vehicle, a hybrid electric vehicle, a ship, or the like. Referring to FIG. 1, in some embodiments, the device is an electric vehicle. The electric vehicle is a battery electric vehicle, or a hybrid electric vehicle, or a range-extended electric vehicle. The electric vehicle includes a chassis, a body, and an electrical drive system. The electrical drive system includes a drive module and a power module. The drive module includes structures such as a motor, a mechanical transmission mechanism, and wheels. The power module includes a plurality of secondary batteries. The power module uses the motor and the mechanical transmission mechanism to drive the wheels to rotate, thereby driving the electric vehicle to move. The secondary battery is a lead-acid battery, a nickel-cadmium battery, a nickel-hydrogen battery or a lithium-ion battery. In some optional embodiments, the secondary battery is a lithium-ion battery.

[0075] This application further provides a battery module. Referring to FIG. 2, the battery module includes a plurality of secondary batteries **1000**. In some embodiments, the plurality of secondary batteries **1000** are arranged sequentially. The battery module further includes two end plates and two side plates. The two end plates are located at two ends of the plurality of secondary batteries **1000** along an arrangement direction respectively. The two side plates are located at two sides of the plurality of secondary batteries **1000** respectively. The two end plates and the two side plates are connected together to form a quasi-rectangular frame structure. The frame structure supports and fixes the plurality of secondary batteries **1000**.

[0076] This application further provides a secondary battery. Referring to FIG. 3 and FIG. 4, a secondary battery according to some embodiments includes an electrode assembly **1**, a housing **2**, a cap assembly **3**, and current collection members **4**.

[0077] The electrode assembly **1** is a core member for the secondary battery to implement functions of charging and discharging. The electrode assembly **1** includes a positive electrode plate **13**, a negative electrode plate **14**, and a separator **15** that separates the positive electrode plate **13** from the negative electrode plate **14**. In some embodiments, referring to FIG. 5, the positive electrode plate **13**, the separator **15**, and the negative electrode plate **14** are sequentially stacked and wound into a whole. In other embodiments, the positive electrode plate **13** and the negative electrode plate **14** are both sheet-like structures and are alternately stacked along a thickness direction thereof.

[0078] The positive electrode plate **13** includes a positive current collector and a positive active material layer coated on a surface of the positive current collector. The positive current collector contains a positive coating region and a positive blank region. The positive coating region is overlaid with the positive active material layer, and the positive blank region is not overlaid with the positive active material layer. The negative electrode plate **14** includes a negative current collector and a negative active material layer coated on a surface of the negative current collector. The negative current collector contains a negative coating region and a negative blank region. The negative coating region is overlaid with the negative active material layer, and the negative blank region is not overlaid with the negative active material layer.

[0079] In some embodiments, the positive current collector is an aluminum foil, and the positive active material layer contains lithium manganate, lithium iron phosphate, or a ternary material. The negative current collector is a copper foil, and the negative active material layer contains graphite or silicon.

[0080] Referring to FIG. 4, as seen from the appearance of the electrode assembly 1, the electrode assembly 1 includes a main body 11 and tabs 12 extending from the main body 11. The main body 11 includes a positive coating region, a positive active material layer, a negative coating region, a negative active material layer, and a separator 15. There are two tabs 12: a positive tab and a negative tab. The positive tab includes a plurality of positive blank regions stacked together, and the negative tab includes a plurality of negative blank regions stacked together.

[0081] In some embodiments, referring to FIG. 4, the housing 2 is in a hexahedral shape. In other embodiments, the housing 2 is in a cylindrical shape or other shapes. A cavity is formed inside the housing 2 to accommodate the electrode assembly 1 and an electrolytic solution. The housing 2 forms an opening at one end, and the electrode assembly 1 can be placed into the inner cavity of the housing 2 through the opening. In some embodiments, the housing 2 is made of a conductive metal material such as aluminum or aluminum alloy.

[0082] The cap assembly 3 includes a cap plate 31 and electrode terminals 32 disposed on the cap plate 31. The size of the cap plate 31 fits the size of the opening of the housing 2. In some embodiments, the cap plate 31 is a conductive metal plate. The cap plate 31 is connected to the housing 2 by welding and covers the opening of the housing 2. A communicating electrode lead-out hole is disposed on the cap plate 31. The electrode lead-out hole is configured to lead electrical energy of the electrode assembly 1 inside the housing 2 to the outside of the cap plate 31. In some embodiments, the electrode terminals 32 pass through the electrode lead-out hole of the cap plate 31 and are exposed outside the secondary battery.

[0083] There are two electrode terminals 32: a positive terminal and a negative terminal. The positive terminal is electrically connected to the positive tab, and the negative terminal is electrically connected to the negative tab.

[0084] In some embodiments, the cap plate 31 contains a communicating exhaust hole 311. The cap assembly 3 further includes a rupture disk 34. The rupture disk 34 is disposed on the cap plate 31 and seals the exhaust hole 311. The rupture disk 34 contains a fragile region. When the electrode assembly 1 generates a large amount of gas due to overcharging, a short circuit, or other reasons, air pressure inside the secondary battery increases and bursts the rupture disk 34 in the fragile region. The gas is expelled out of the secondary battery through the exhaust hole 311, thereby preventing the secondary battery from exploding.

[0085] The secondary battery according to some embodiments further includes current collection members 4. There are two current collection members 4. One current collection member 4 connects the positive terminal and the positive tab, and the other current collection member 4 connects the negative terminal and the negative tab.

[0086] To prevent the cap plate 31 from electrically connecting the positive tab and the negative tab and to reduce short-circuit risks, the cap assembly 3 according to some embodiments further includes an insulation baffle 33. The insulation baffle 33 is disposed at a side of the cap plate 31 and connected to the cap plate 31, where the side is close to the main body 11.

[0087] The current collection members 4 are at least partly located between the insulation baffle 33 and the main body 11. The insulation baffle 33 can separate the current collection members 4 from the cap plate 31, thereby avoiding a direct contact between the current collection members 4 and the cap plate 31 and reducing short-circuit risks.

[0088] In some embodiments, referring to FIG. 8 and FIG. 14 to FIG. 16, each of the current collection members 4 includes a terminal connection portion 41 and a tab connection portion 42. The terminal connection portion 41 is connected to the electrode terminals 32, and the tab connection portion 42 is connected to one of the tabs 12. The tab connection portion 42 is connected to the tab 12 by welding or by other means, and the terminal connection portion 41 is connected to the electrode terminals 32 by welding or other means.

[0089] Referring to FIG. 7 to FIG. 12, the insulation baffle 33 contains a first recess 332. The first recess 332 is recessed against a lower surface 331 of the insulation baffle 33 away from the main

body **11**. The lower surface **331** of the insulation baffle **33** is oriented toward the main body **11** and is approximately flat. The tab connection portion **42** is at least partly accommodated in the first recess **332**.

[0090] By disposing the first recess **332**, this application downsizes the insulation baffle **33**, reduces the space occupied by the insulation baffle **33** in the secondary battery, and increases the energy density of the secondary battery. The tab connection portion **42** is at least partly accommodated in the first recess **332**, thereby increasing a distance between the tab connection portion **42** and the main body **11**, providing more space for the tabs **12**, reducing the risks of inserting the tabs **12** into the main body **11**, avoiding short circuits, and improving safety performance.

[0091] Referring to FIG. **10**, a tab **12** according to some embodiments includes a first part **121** and a second part **122**. The first part **121** extends from the main body **11**. The second part **122** is connected to one end that is of the first part **121** and that is away from the main body **11**, and is bent against the first part **121**. The second part **122** is welded to the tab connection portion **42**. An end that is of the second part **122** and that is away from the first part **121** may be bent downward. If a distance between the tab connection portion **42** and the main body **11** is too small, the end of the second part **122** is likely to be inserted into the main body **11** to cause a short-circuit risk. However, by disposing the first recess **332**, this application increases the distance between the tab connection portion **42** and the main body **11**, thereby increasing the spacing between the second part **122** and the main body **11** and reducing the risks of inserting the second part **122** into the main body **11**.

[0092] In some embodiments, referring to FIG. **14** to FIG. **16**, both the terminal connection portion **41** and the tab connection portion **42** are flat plate structures. Referring to FIG. **8**, the electrode terminals **32** are located at a side of the terminal connection portion **41** without being connected to the tabs **12**, where the side is away from the main body **11**. Therefore, in contrast with the tab connection portion **42**, the distance between the terminal connection portion **41** and the main body **11** may be smaller. In other words, the tab connection portion **42** is farther away from the main body **11** than the terminal connection portion **41**.

[0093] In some embodiments, referring to FIG. **10**, the tab **12** is connected to a side of the tab connection portion **42**, where the side is close to the main body **11**, so as to simplify the welding between the tab **12** and the tab connection portion **42** as well as the welding between the terminal connection portion **41** and the electrode terminals **32**. In addition, if the tab **12** is connected to a side that is of the tab connection portion **42** and that is far away from the main body **11**, the first recess **332** needs to be fairly deep in order to accommodate the tab connection portion **42**. This will reduce the insulation performance of the insulation baffle **33**.

[0094] In some embodiments, referring to FIG. **10**, a gap exists between the tab connection portion **42** and a bottom face of the first recess **332**. By disposing the gap, the assembly of the current collection member **4** and the cap assembly **3** can be simplified. If the tab connection portion **42** fits snugly with the bottom face of the first recess **332**, then in assembling the current collection member **4** and the cap assembly **3**, the current collection member **4** needs to fit snugly with both the bottom face of the electrode terminals **32** and the bottom face of the first recess **332**. Due to process errors, it is difficult to ensure that the current collection member **4** fits well with both bottom faces. Therefore, in this application, a gap is reserved between the tab connection portion **42** and the bottom face of the first recess **332**, so that it is enough to ensure that the current collection member **4** fits snugly with the bottom face of the electrode terminals **32**. In addition, when the secondary battery vibrates, the tab connection portion **42** can release the stress between the tab **12** and the current collection member **4** through elastic deformation, thereby reducing the risk of rupturing the tab **12**.

[0095] In some embodiments, referring to FIG. **8** and FIG. **14** to FIG. **16**, the current collection member **4** further includes a tilt portion **43**. The tilt portion **43** is connected between the terminal connection portion **41** and the tab connection portion **42**. The tilt portion **43** tilts against the

terminal connection portion **41** away from the main body **11**. By disposing the tilt portion **43**, the spacing between the tab connection portion **42** and the main body **11** is increased.

[0096] In some embodiments, the terminal connection portion **41** is parallel to the tab connection portion **42**. Both the terminal connection portion **41** and the tab connection portion **42** are approximately perpendicular to a height direction Z of the secondary battery.

[0097] In some embodiments, referring to FIG. **15**, the terminal connection portion **41** includes a fixing region **411** and a fuse region **412**. The fixing region **411** is connected to the electrode terminals **32**. The fuse region **412** is connected between the fixing region **411** and the tilt portion **43**. The fuse region **412** is set to work in this way: when the secondary battery is short-circuited, the fuse region **412** blows out to cut off the circuit. In contrast with other parts of the current collection member **4**, a passage area of the fuse region **412** is smaller. When the secondary battery is short-circuited, the current on the current collection member **4** increases sharply. When a large current passes through the fuse region **412**, heat is generated and blows out the fuse region, thereby cutting off the circuit and reducing safety risks such as fire or explosion of the secondary battery.

[0098] In some embodiments, referring to FIG. **15**, a via hole is disposed on the terminal connection portion **41**. The fuse region **412** includes two fuse sub-regions. The two fuse sub-regions are located at two sides of the via hole respectively. In other embodiments, a groove is disposed on the terminal connection portion **41**. The fuse region **412** is located at one side of the groove along a thickness direction of the terminal connection portion **41**. In still other embodiments, two notches are disposed on the terminal connection portion **41**. The two notches are located at two sides of the fuse region **412** respectively. By disposing the via hole, the groove, or the notches, this application can reduce the passage area of the fuse region **412**, thereby implementing the safety protection function of the fuse region **412**.

[0099] In some embodiments, referring to FIG. **16**, the current collection member **4** further includes an insulation strip **44** that wraps around the fuse region **412**. When the fuse region **412** blows out, the current collection member **4** is partitioned into two parts. The insulation strip **44** can join the two partitioned parts to avoid relative movement of the two partitioned parts, and prevent the two parts of the current collection member **4** from being lap-jointed again. In some embodiments, a part of the insulation strip **44** is inserted into the via hole of the terminal connection portion **41** and separates the fixing region **411** from the tilt portion **43**.

[0100] In some embodiments, a part of the insulation strip **44** is accommodated in the first recess **332**. In a plane perpendicular to the thickness direction of the terminal connection portion **41**, a projection of the insulation strip **44** is located in a projection of a peripheral wall of the first recess **332**. A part of the insulation strip **44** is accommodated in the first recess **332**, thereby making full use of the first recess **332**, saving space, and increasing the energy density of the secondary battery.

[0101] In some embodiments, a surface that is of the insulation strip **44** and that is away from the main body **11** is closer to the main body **11** than a surface that is of the tab connection portion **42** and that is away from the main body **11**. If the surface that is of the insulation strip **44** and that is away from the main body **11** is farther away from the main body **11** than the surface that is of the tab connection portion **42** and that is away from the main body **11**, the first recess **332** needs to be deeper in order to accommodate the insulation strip **44**, thereby impairing the insulation performance of the insulation baffle **33**.

[0102] In some embodiments, referring to FIG. **11** and FIG. **12**, the insulation baffle **33** further contains a first bulge **333** protruding against the lower surface **331**. The terminal connection portion **41** is located at a side that is of the first bulge **333** and that is close to the main body **11**. The tilt portion **43** is located at a side of the first bulge **333** along the length direction X of the secondary battery. By disposing the first bulge **333**, a height difference between the terminal connection portion **41** and the tab connection portion **42** in the height direction Z of the secondary battery can be increased, thereby reducing the risks of lap-jointing the tab **12** to the terminal connection portion **41**, and avoiding failure of the safety protection function of fuse region **412**.

[0103] In some embodiments, referring to FIG. 13, the insulation baffle 33 contains an upper surface 334 oriented toward the cap plate 31 and a second recess 335 recessed against the upper surface 334. In a plane perpendicular to the thickness direction of the insulation baffle 33, a projection of the rupture disk 34 is located in a projection of a boundary of the second recess 335. Referring to FIG. 8, by disposing the second recess 335, the spacing between the rupture disk 34 and the insulation baffle 33 can be reduced, thereby preventing the insulation baffle 33 from squeezing the rupture disk 34 when deformed, and preventing the rupture disk 34 from being ruptured by the insulation baffle 33.

[0104] Along the thickness direction of the insulation baffle 33, the first recess 332 does not overlap the second recess 335, thereby avoiding communication between the first recess 332 and the second recess 335 while ensuring a sufficient depth of both the first recess 332 and the second recess 335.

[0105] In some embodiments, referring to FIG. 8 and FIG. 11 to FIG. 13, the insulation baffle 33 further includes a second bulge 336. Along a direction close to the main body 11, the second bulge 336 protrudes against the first bulge 333. The second bulge 336 abuts on the main body 11 to reduce vibration of the main body 11 and reduce the risks of rupturing the tab 12. In an optional embodiment, there are a plurality of second bulges 336.

[0106] Although this application has been described with reference to exemplary embodiments, various improvements may be made to the embodiments without departing from the scope of this application, and the components therein may be replaced with equivalents. Particularly, to the extent that no structural conflict exists, various technical features mentioned in various embodiments can be combined in any manner. This application is not limited to the specific embodiments disclosed herein, but includes all technical solutions falling within the scope of the claims.

Claims

1. A secondary battery, comprising: an electrode assembly, wherein the electrode assembly comprises a main body and tabs extending from the main body; a cap assembly, wherein the cap assembly comprises a cap plate, electrode terminals, and an insulation baffle, the electrode terminals are disposed on the cap plate, and the insulation baffle is connected to a side of the cap plate, wherein the side is close to the main body; and current collection members, wherein the current collection members are at least partly located between the insulation baffle and the main body, and each of the current collection members comprises a tab connection portion connected to one of the tabs and a terminal connection portion, wherein the insulation baffle contains a first recess, a first bulge and a second bulge, wherein the first recess is recessed against a lower surface of the insulation baffle away from the main body, and the tab connection portion is at least partly accommodated in the first recess; wherein the first bulge protrudes against the lower surface, and along the thickness direction of the insulation baffle, the terminal connection portion is located on a side of the first bulge, wherein the side is close to the main body; wherein along a direction close to the main body, the second bulge protrudes against the first bulge.
2. The secondary battery according to claim 1, wherein the terminal connection portion is connected to the electrode terminals, both the terminal connection portion and the tab connection portion are flat plate structures, and the tab connection portion is farther away from the main body than the terminal connection portion.
3. The secondary battery according to claim 1, wherein the tab is connected to a side of the tab connection portion, wherein the side is close to the main body.
4. The secondary battery according to claim 1, wherein a gap exists between the tab connection portion and a bottom face of the first recess.
5. The secondary battery according to claim 2, wherein the current collection member further

comprises a tilt portion, wherein the tilt portion is connected between the terminal connection portion and the tab connection portion, and the tilt portion tilts against the terminal connection portion away from the main body.

6. The secondary battery according to claim 2, wherein the terminal connection portion is parallel to the tab connection portion.

7. The secondary battery according to claim 5, wherein the terminal connection portion comprises a fixing region and a fuse region, the fixing region is connected to the electrode terminals, and the fuse region is connected between the fixing region and the tilt portion.

8. The secondary battery according to claim 7, wherein the current collection member further comprises an insulation strip that wraps around the fuse region; and a part of the insulation strip is accommodated in the first recess, and a surface that is of the insulation strip and that is away from the main body is closer to the main body than a surface that is of the tab connection portion and that is away from the main body.

9. A battery module, comprising a secondary battery, wherein the secondary battery is plural in number and the secondary battery comprises: an electrode assembly, wherein the electrode assembly comprises a main body and tabs extending from the main body; a cap assembly, wherein the cap assembly comprises a cap plate, electrode terminals, and an insulation baffle, the electrode terminals are disposed on the cap plate, and the insulation baffle is connected to a side of the cap plate, wherein the side is close to the main body; and current collection members, wherein the current collection members are at least partly located between the insulation baffle and the main body, and each of the current collection members comprises a tab connection portion connected to one of the tabs, and a terminal connection portion, wherein the insulation baffle contains a first recess, a first bulge and a second bulge, wherein the first recess is recessed against a lower surface of the insulation baffle away from the main body, and the tab connection portion is at least partly accommodated in the first recess; wherein the first bulge protrudes against the lower surface, and along the thickness direction of the insulation baffle, the terminal connection portion is located on a side of the first bulge, wherein the side is close to the main body; wherein along a direction close to the main body, the second bulge protrudes against the first bulge.

10. A device using a secondary battery as a power supply, wherein the device comprises the secondary battery, and the secondary battery comprises: an electrode assembly, wherein the electrode assembly comprises a main body and tabs extending from the main body; a cap assembly, wherein the cap assembly comprises a cap plate, electrode terminals, and an insulation baffle, the electrode terminals are disposed on the cap plate, and the insulation baffle is connected to a side of the cap plate, wherein the side is close to the main body; and current collection members, wherein the current collection members are at least partly located between the insulation baffle and the main body, and each of the current collection members comprises a tab connection portion connected to one of the tabs and a terminal connection portion, wherein the insulation baffle contains a first recess, a first bulge and a second bulge, wherein the first recess is recessed against a lower surface of the insulation baffle away from the main body, and the tab connection portion is at least partly accommodated in the first recess; wherein the first bulge protrudes against the lower surface, and along the thickness direction of the insulation baffle, the terminal connection portion is located on a side of the first bulge, wherein the side is close to the main body; wherein along a direction close to the main body, the second bulge protrudes against the first bulge.
