

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286426

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

CHEN; Guangquan et al.

ELECTRIC ASSEMBLY AND VEHICLE HAVING THE SAME

Abstract

An electric assembly includes a box assembly, a motor, and a transmission. A mounting plate is disposed in the box assembly, and the mounting plate divides a space within the box assembly into a motor holding cavity and a transmission holding cavity. The motor is disposed in the motor holding cavity. The transmission is disposed in the transmission holding cavity, and the motor is power-coupled to the transmission such that the motor and the transmission are directly integrated through the box assembly without external connection of the motor and the transmission. The mounting plate is a monolithically integral part of the box assembly.

Inventors: CHEN; Guangquan (Shenzhen, CN), CHEN; Daqi (Shenzhen, CN), LIU; Chunlei (Shenzhen, CN), JING; Shuanghong (Shenzhen, CN)

Applicant: BYD COMPANY LIMITED (SHENZHEN, CN)

Family ID: 67549192

Appl. No.: 19/216586

Filed: May 22, 2025

Foreign Application Priority Data

CN	201810146302.8	Feb. 12, 2018
CN	201820254974.6	Feb. 12, 2018

Related U.S. Application Data

parent US continuation 18654993 20240503 parent-grant-document US 12348104 child US 19216586

parent US continuation 18110267 20230215 parent-grant-document US 12021434 child US 18654993

parent US continuation 16969400 20200812 parent-grant-document US 11735974 WO continuation PCT/CN2019/073413 20190128 child US 18110267

Publication Classification

Int. Cl.: **H02K5/12** (20060101); **F16H57/04** (20100101); **H02K5/20** (20060101); **H02K7/00** (20060101); **H02K7/116** (20060101)

U.S. Cl.:

CPC **H02K5/12** (20130101); **F16H57/04** (20130101); **H02K5/20** (20130101); **H02K7/006** (20130101); **H02K7/116** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. patent application Ser. No. 18/654,993 filed on May 3, 2024, which is a continuation application of U.S. patent application Ser. No. 18/110,267 filed on Feb. 15, 2023, now U.S. Pat. No. 12,021,434, which is a continuation application of U.S. patent application Ser. No. 16/969,400, filed on Aug. 12, 2020, now U.S. Pat. No. 11,735,974, which is a national phase entry under 35 U.S.C. § 371 of International Application No. PCT/CN2019/073413, filed on Jan. 28, 2019, which is based on and claims priority to and benefits of Chinese Patent Applications Nos. 201810146302.8 and 201820254974.6, both filed on Feb. 12, 2018. The content of all of the above-identified applications is incorporated herein by reference in their entireties.

FIELD

[0002] This application relates to the field of vehicle manufacturing technologies and, specifically, to an electric assembly and a vehicle having the electric assembly.

BACKGROUND

[0003] A motor assembly, a transmission assembly and a controller assembly individually disposed are used in a vehicle in the related art. The motor assembly and the transmission assembly are connected together through a bolt. Box assemblies at connection locations have relatively large wall thicknesses and waste space, there are many and bulky components, the loss is high, each assembly occupies a relatively large space, the structure is insufficiently compact, mounting and maintenance are difficult, costs are relative relatively high, and the entire mass is large, which affects the endurance capability of the entire vehicle.

SUMMARY

[0004] The present disclosure aims to resolve at least one of the technical problems existing in the prior art. For this purpose, the present disclosure proposes an electric assembly, where the electric assembly has advantages such as a compact structure and a good cooling effect.

[0005] The present disclosure further provides a vehicle having the electric assembly.

[0006] To achieve the foregoing objective, according to an embodiment of a first aspect of the present disclosure, an electric assembly is proposed. The electric assembly includes: a box assembly, where an mounting plate is disposed in the box assembly, and the mounting plate divides a space within the box assembly into a motor holding cavity and a transmission holding cavity; a motor, where the motor is disposed in the motor holding cavity; a transmission, where the transmission is disposed in the transmission holding cavity, and the motor is power-coupled to the transmission such that the motor and the transmission are directly integrated through the box assembly without external connection of the motor and the transmission, where the mounting plate is a monolithically integral part of the box assembly.

[0007] Additionally, the electric assembly according to the foregoing embodiments of the present disclosure may further have the following additional technical characteristics.

[0008] According to an embodiment of the present disclosure, the transmission holding cavity is configured to contain a cooling lubricating liquid to cool the box assembly, and the cooling lubricating liquid cools the box assembly through the mounting plate.

[0009] According to an embodiment of the present disclosure, a distance between the motor and the mounting plate is less than a preset distance such that the mounting plate cools the motor.

[0010] According to an embodiment of the present disclosure, at least one of a surface of the mounting plate facing the motor and a surface of the mounting plate facing the transmission is provided with ribs.

[0011] According to an embodiment of the present disclosure, the ribs divide a space between the mounting plate and the motor into a plurality of cavities.

[0012] According to an embodiment of the present disclosure, the ribs include an annular rib extending along a circumferential direction of the motor.

[0013] According to an embodiment of the present disclosure, the ribs include a plurality of strip-shaped ribs extending along a radial direction of the motor, and the strip-shaped ribs are spaced apart along a circumferential direction of the mounting plate.

[0014] According to an embodiment of the present disclosure, heights of the strip-shaped ribs relative to the mounting plate gradually decrease from a center portion of the mounting plate to a periphery portion of the mounting plate.

[0015] According to an embodiment of the present disclosure, the box assembly includes a transmission box and a motor box, the transmission box includes a front box and a rear box, the motor box includes a motor housing and a motor backend cover, the front box and the motor housing are disposed adjacent to each other, and the mounting plate is a part of the front box or a part of the motor housing.

[0016] According to an embodiment of the present disclosure, the front box and the motor housing are integrally formed or detachably connected.

[0017] According to an embodiment of the present disclosure, the box assembly includes a transmission box and a motor box, the transmission box includes a front box and a rear box, the motor box includes a motor frontend cover, a motor housing and a motor backend cover, and the mounting plate is a part of the front box or a part of the motor frontend cover.

[0018] According to an embodiment of the present disclosure, the electric assembly further includes a controller, where the controller is mounted outside the box assembly and fixedly connected to the box assembly.

[0019] According to an embodiment of the present disclosure, the electric assembly further includes a conductive sheet, where the conductive sheet connects to the controller and the motor.

[0020] According to an embodiment of a second aspect of the present disclosure, a vehicle is proposed. The vehicle includes the electric assembly according to the embodiment of the first aspect of the present disclosure.

[0021] In the vehicle according to an embodiment of the present disclosure, the electric assembly according to the first aspect of the present disclosure is used, where the electric assembly has advantages such as a compact structure and a good cooling effect.

[0022] The additional aspects and advantages of the present disclosure will be provided in the following description, and some of the additional aspects and advantages will become clear in the following description or be understood through practice of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] The foregoing and/or additional aspects and advantages of the present disclosure become more obvious and easily understood in descriptions of the embodiments with reference to the

following accompanying drawings.

[0024] FIG. **1** is a schematic structural diagram of an electric assembly according to an embodiment of the present disclosure;

[0025] FIG. **2** is a local cross-sectional view of an electric assembly according to an embodiment of the present disclosure;

[0026] FIG. **3** is an enlarged diagram of a location D in FIG. **2**;

[0027] FIG. **4** is an exploded view of an electric assembly according to an embodiment of the present disclosure;

[0028] FIG. **5** is an exploded view of a box assembly of an electric assembly according to an embodiment of the present disclosure;

[0029] FIG. **6** is a schematic local structural diagram of an electric assembly according to an embodiment of the present disclosure;

[0030] FIG. **7** is a local cross-sectional view of an electric assembly according to an embodiment of the present disclosure;

[0031] FIG. **8** is a local cross-sectional view of an electric assembly according to another embodiment of the present disclosure;

[0032] FIG. **9** is a schematic structural diagram of an electric assembly according to an embodiment of the present disclosure;

[0033] FIG. **10** is a schematic structural diagram of an electric assembly according to an embodiment of the present disclosure;

[0034] FIG. **11** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure;

[0035] FIG. **12** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure;

[0036] FIG. **13** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure;

[0037] FIG. **14** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure;

[0038] FIG. **15** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure;

[0039] FIG. **16** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure;

[0040] FIG. **17** is an enlarged diagram of a location A in FIG. **15**;

[0041] FIG. **18** is an exploded view of an electric assembly according to an embodiment of the present disclosure;

[0042] FIG. **19** is a schematic structural diagram of an oil pump of an electric assembly according to an embodiment of the present disclosure;

[0043] FIG. **20** is a schematic local structural diagram of an electric assembly according to an embodiment of the present disclosure;

[0044] FIG. **21** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure;

[0045] FIG. **22** is a schematic local structural diagram of an electric assembly according to another embodiment of the present disclosure; and

[0046] FIG. **23** is a schematic structural diagram of a vehicle according to an embodiment of the present disclosure.

[0047] Reference numerals of the accompanying drawing: electric assembly **1**; conductive member **10**; conductive sheet **20**; box assembly **100**; transmission box **101**; motor box **102**; motor holding cavity **110**; transmission holding cavity **120**; mounting plate **160**; strip-shaped rib **161**; cavity **162**; annular rib **163**; motor **200**; transmission **400**; oil pump **13**; mounting seat **135**; spindle **134**; driving gear **131**; front box **180**; rear box **190**; motor housing **140**; motor backed cover **150**; motor

frontend cover **170**; first connection rib **181**; second connection rib **182**; third connection rib **183**; controller **500**; conductive sheet **20**; positioning insert **206**; motor body **203**; leading wire **2031**; connection device **204**; supporting plate **205**; leading wire **2031**; motor connection end **2212**; shaft via-hole **130**; reinforcing rib **141**; motor shaft **210**; outer spline **211**; main shaft **300**; shaft hole **310**; inner spline **311**; oil baffle **320**; oil storage cavity **330**; seal retainer ring **340**; air vent **350**; first gear **410**; second gear **420**; third gear **430**; differential assembly **440**; transmission shaft **450**; first bearing **510**; second bearing **520**; third bearing **530**; fourth bearing **540**; vehicle **11**.

DETAILED DESCRIPTION

[0048] The following describes exemplary embodiments of the present disclosure in detail.

Examples of the embodiments are shown in the accompanying drawings. The same or similar elements and the elements having same or similar functions are denoted by like reference numerals throughout the descriptions. The following embodiments described with reference to the accompanying drawings are exemplary, and are only to describe the present disclosure and cannot be construed as a limitation to the present disclosure.

[0049] An electric assembly **1** according to an embodiment of the present disclosure is described below with reference to the accompanying drawings.

[0050] As shown in FIG. **1** to FIG. **23**, the electric assembly **1** according to one embodiment of the present disclosure includes a box assembly **100**, a motor **200**, a transmission **400** and a cooling lubricating liquid.

[0051] A mounting plate **160** is disposed in the box assembly **100**, and the mounting plate **160** divides a space within the box assembly **100** into a motor holding cavity **110** and a transmission holding cavity **120** that are arranged along an axial direction of a motor shaft **210**. The motor **200** is disposed in the motor holding cavity **110**. The transmission **400** is disposed in the transmission holding cavity **120**, and the motor **200** is power-coupled to the transmission **400**. The cooling lubricating liquid fills the transmission holding cavity **120** and cools the box assembly **100**.

[0052] In the electric assembly **1** according to one embodiment of the present disclosure, the motor **200** and the transmission **400** are disposed in the box assembly **100**. Compared with the motor assembly in the related art in which the front box of the transmission and the frontend cover of the motor are connected, the motor **200** and the transmission **400** share a box assembly **100**, to implement the integrated design of the electric assembly **1**, which not only may leave out a structure in which a plurality of box assemblies **100** are disposed, but also may leave out a bolt required to connect the motor assembly and the transmission assembly, so as to simplify the structure of the electric assembly **1**, reduce the part quantity of the electric assembly **1**, improve the integration level of the electric assembly **1**, and improve the production efficiency of the electric assembly **1**.

[0053] Moreover, the motor **200** and the transmission **400** share a box assembly **100**. Compared with the related art in which the motor assembly and the transmission assembly are individually disposed, space may be saved, to help shorten an axial distance of the electric assembly **1**, so that the structure of the electric assembly **1** is compact and proper, thereby improving the space utilization of the electric assembly **1**, and facilitating the disposition of the electric assembly **1**; and facilitating mounting and repair of the electric assembly **1**, and helping improve reliability and stability of the electric assembly **1**.

[0054] Moreover, the motor **200** and the transmission **400** share a box assembly **100**, and therefore components used for integration of the motor **200** and the transmission **400** may be reduced, thereby helping reduce the weight of the electric assembly **1**. For example, when the electric assembly **1** is applied to a vehicle **11**, the entire weight of the vehicle **11** may be reduced, thereby helping reduce costs of the vehicle **11**, reducing the energy loss of the vehicle **11**, improving the operating efficiency of the vehicle **11**, and improving the endurance capability of the vehicle **11**.

[0055] Moreover, the box assembly **100** is disposed, the mounting plate **160** is disposed in the box assembly **100**, and clamping needs to be performed only once during assembly, to facilitate

assembly and forming of the electric assembly **1**, help reduce the error of the electric assembly **1**, facilitate mounting and disposition of the motor **200** and the transmission **400**, improve coaxiality and radial mounting accuracy of the motor **200** and the transmission **400**, and help improve the operating performance of the electric assembly **1**.

[0056] Further, the cooling lubricating liquid fills the transmission holding cavity **120** and the cooling lubricating liquid may cool the box assembly **100**. In this way, the transmission **400** may be cooled by using the cooling lubricating liquid, to help control the temperature range of the transmission **400** and ensure the normal operating performance of the transmission **400**. Because the cooling lubricating liquid may cool the box assembly **100** at the same time, the temperature range of the box assembly **100** may be controlled to make the box assembly **100** stably run within a proper temperature range, and the motor **200** in the box assembly **100** may be further cooled through the box assembly **100**, thereby helping improve the entire heat dissipation performance of the electric assembly **1** and improve the operating reliability and stability of the electric assembly **1**.

[0057] Because the cooling lubricating liquid may cool the box assembly **100**, and compared with the cooling manner for the electric assembly in the related art, the cooling lubricating liquid not only may cool the transmission **400** but also may cool the box assembly **100**, the electric assembly **1** may be fully cooled by the cooling lubricating liquid, and the cooling evenness throughout the electric assembly **1** may be improved, to enhance the cooling effect of the electric assembly **1** and improve the cooling reliability of the electric assembly **1**.

[0058] Therefore, the electric assembly **1** according to one embodiment of the present disclosure has advantages such as a compact structure and a good cooling effect.

[0059] An electric assembly **1** according to an embodiment of the present disclosure is described below with reference to the accompanying drawings.

[0060] In some specific embodiments of the present disclosure, as shown in FIG. **1** to FIG. **23**, the electric assembly **1** according to one embodiment of the present disclosure includes a box assembly **100**, a motor **200**, a transmission **400** and a cooling lubricating liquid.

[0061] Specifically, the mounting plate **160** is constructed as a part of the box assembly **100**, and the cooling lubricating liquid cools the box assembly **100** through the mounting plate **160**. In this way, the disposition of the mounting plate **160** is facilitated, and heat may be transferred through the mounting plate **160**, to improve the entire cooling effect of the electric assembly **1**. For example, the mounting plate **160** may be cooled through the cooling lubricating liquid in the transmission holding cavity **120**, and the box assembly **100** transfers heat through the mounting plate **160**, to further cool the motor housing **140**, thereby cooling the motor **200** in the motor housing **140**.

[0062] According to an embodiment of the present disclosure, the mounting plate **160** is constructed as a part of a front box **180**, and because lubricating liquid in the transmission cools the front box **180**, the mounting plate **160** and the box assembly **100**, for example, a motor housing **140** and a transmission box **101** may also be cooled. For example, the cavities **162** are formed between the ribs of the mounting plate **160**, and therefore, the air flowing through the cavities **162** is also cooled accordingly, and the motor **200** may be cooled by using the air flowing through the cavities **162**, to help improve the heat dissipation performance of the electric assembly **1**. In short, the lubricating liquid passing through the transmission **400** may cool the motor housing **140** and the housing of the transmission **400** at the same time.

[0063] According to another embodiment of the present disclosure, the mounting plate **160** is constructed as a part of the motor housing **140**, and because lubricating liquid in the motor cools the motor housing **140**, and may also cool the mounting plate **160** and transfer heat through the mounting plate **160**, so that the transmission box **101** may also be cooled, thereby cooling the box assembly **100** and improving the entire cooling effect of the electric assembly **1**. In short, the lubricating liquid passing through the motor **200** may also cool the motor housing **140** and the transmission **400** at the same time.

[0064] In an embodiment, as shown in FIG. 19, the electric assembly 1 further includes an oil pump 13, where the oil pump 13 is disposed on the box assembly 100 and configured to transport the cooling lubricating liquid in the transmission holding cavity 120 to the transmission 400 and the mounting plate 160. In this way, the cooling lubricating liquid may be driven by using the oil pump 13 to flow in the box assembly 100, and the cooling lubricating liquid is transported to the mounting plate 160, to help cool the mounting plate 160. Further, the box assembly 100 transfers heat through the mounting plate 160, to help cool the motor housing 140, thereby cooling the motor 200 in the motor housing 140, further improving the cooling effect of the transmission 400 and the mounting plate 160, and cooling the motor 200 through the mounting plate 160, so as to further improve the entire cooling effect of the electric assembly 1.

[0065] Specifically, the motor housing 140 may be provided with a motor cooling liquid passage that may cool the motor 200, the motor housing 140 is sleeved over the periphery of a stator, so as to have cooling and heat dissipation effects on the stator, and the mounting plate 160 is disposed on a side of an end of the motor 200, to mainly perform cooling and heat dissipation on the end and a coil of the motor 200, thereby fully cooling the motor 200. The two cooling manners have respective focuses, to jointly achieve a full cooling effect. On the other hand, the transmission 400 is cooled through the motor cooling liquid of the motor 200, and meanwhile the lubricating cooling liquid of the transmission 400 cools the motor 200, to reinforce the cooling effect on the electric assembly 1 through a combination of the two, thereby jointly achieving a full cooling effect on the electric assembly 1.

[0066] In an embodiment of the present disclosure, as shown in FIG. 20, the oil pump 13 is mounted in the box assembly 100, and the oil pump 13 is in transmission connection to the transmission 400 and is driven by the transmission 400. In this way, the oil pump 13 is driven by the transmission 400 to transport the cooling lubricating liquid to the transmission 400, and oil line disposition of the electric assembly 1 may be facilitated, to help the electric assembly 1 be more fully lubricated and cooled.

[0067] Furthermore, the transmission 400 is lubricated by using the oil pump 13, and the electric assembly 1 does not have a high requirement on space arrangement of a gear shaft. Even if the gear shaft is arranged higher than an oil liquid surface, key parts can still be lubricated in time. Therefore, an arrangement angle of the electric assembly 1 on the entire vehicle is broader, a proper mounting angle of the power assembly may be obtained through adjustment according to the arrangement of the entire vehicle, and the adaptability is relatively high.

[0068] Moreover, the oil pump 13 is driven through the transmission 400 to run, no additional power (for example, motor) needs to be disposed to drive the oil pump 13, the structure is simple, and the adaptability is good; and the amount of the cooling lubricating liquid may be adjusted according to the vehicle speed, and the lubricating efficiency is relatively high.

[0069] Furthermore, as shown in FIG. 19, the oil pump 13 has a mounting seat 135, and the oil pump 13 is mounted on an inner wall of the transmission holding cavity 120 through the mounting seat 135. Specifically, the mounting seat 135 is disposed on the bottom of the oil pump 13, the mounting seat 135 is provided with a mounting hole, and a bolt is inserted into the mounting hole and is in threaded connection to the inner wall of the transmission box 101, so that the fixing effect of the oil pump 13 and the inner wall of the transmission box 101 is good. Moreover, the oil pump 13 is disposed in the transmission 400, transmission may be performed by using power in the electric assembly 1, and no external space is occupied.

[0070] Specifically, as shown in FIG. 19, the oil pump 13 includes a spindle 134, where the spindle 134 is connected to a driving gear 131, the driving gear 131 is in transmission connection to the transmission 400, and the oil pump 13 is in transmission connection to the driving gear 131 through the spindle 134 and is driven by the driving gear 131. Therefore, the rotation effect of the driving gear 131 is more stable. In this way, the driving gear 131 on the oil pump 13 may drive the spindle 134 to rotate to make the oil pump 13 pump oil. Therefore, no additional motor needs to be

disposed to drive the oil pump **13**, and the displacement of the oil pump **13** depends on the rotational speed of a driven gear. When the vehicle speed is higher, that is, the rotational speed of the driven gear is also higher, the displacement of the oil pump **13** is also larger, and the lubricating effect of the transmission **400** does not become poorer as the vehicle speed becomes higher; and when the vehicle speed is relatively low, that is, the rotational speed of the driven gear is relatively low, the transmission **400** requires a relatively small amount of the cooling lubricating liquid, and the displacement of the oil pump **13** is also low accordingly, to further improve the lubricating efficiency on the transmission **400**.

[0071] More specifically, the oil pump **13** is in transmission connection to the driving gear **131** through the spindle **134**. While the driving gear **131** is rotating, the spindle **134** is driven to rotate, and the spindle **134** is connected to a gear or paddle in the oil pump **13**, thereby driving the gear or paddle in the oil pump **13** to rotate.

[0072] The driving gear **131** may be a metal gear or non-metal gear, and a most lightweight gear may be selected according to an actual requirement. Therefore, the rotation effect of the driving gear **131** is more stable. The oil pump **13** may be a gear pump, and the spindle **134** may drive the gear in the oil pump **13** to rotate, so that the low-pressure cooling lubricating liquid sucked into the oil pump **13** becomes high-pressure oil discharged from the oil pump **13**; or the oil pump **13** may be a paddle pump, and the spindle **134** may drive a paddle wheel in the oil pump **13** to rotate, to increase the pressure of the cooling lubricating liquid. The oil pump **13** of the electric assembly **1** in one embodiment of the present disclosure refers to a device that can transport the cooling lubricating liquid to each key part of the transmission **400**.

[0073] Specifically, the electric assembly **1** further includes an oil transportation pipe, where the oil pump **13** transports the cooling lubricating liquid in the transmission holding cavity **120** to the mounting plate **160** through the oil transportation pipe. In this way, it is convenient to smoothly transport the cooling lubricating liquid, improve the transport capability and cooling effect of the cooling lubricating liquid, further transport the cooling lubricating liquid to the mounting plate **160**, and cool the mounting plate **160**. Further, the box assembly **100** transfers heat through the mounting plate **160**, and it is further convenient to cool the entire box assembly **100**.

[0074] More specifically, the oil pump transports the cooling lubricating liquid in the transmission holding cavity to the mounting plate and at least one gear location and/or at least one bearing location and/or at least one meshing location through the oil transportation pipe. In other words, the oil pump **13** may transport the cooling lubricating liquid to at least one of the gear location, the bearing location and the meshing location through the oil transportation pipe. The oil transportation pipe transports the cooling lubricating liquid in the transmission box **101** to the oil pump **13**, and then the oil pump **13** transports the cooling lubricating liquid to a driving bearing location, a driving gear, and a meshing location and a transmission bearing location of a first transmission gear. It may be understood that, the transporting, by the oil transportation pipe, the cooling lubricating liquid to a part of a speed change mechanism **12** is merely to better understand the present disclosure, but cannot be understood as a limitation on the present disclosure.

[0075] According to another embodiment of the present disclosure, as shown in FIG. **21** and FIG. **22**, the oil pump **13** is mounted outside the box assembly **100**. In this way, a case in which the oil pump **13** is disposed to affect the internal structure of the box assembly **100** may be avoided, to improve the disposition flexibility of the oil pump **13**. Moreover, a requirement of a key part such as a bearing or a gear on lubrication may be met, and the lubricating effect is good.

[0076] Specifically, the oil pump **13** is driven through an external motor or driven through a transmission mechanism of the transmission **400**. In this way, power may be provided for the oil pump **13**, and the disposition flexibility of the oil pump **13** is improved, to help the oil pump **13** transport the cooling lubricating liquid, and help further improve the cooling performance of the electric assembly **1**.

[0077] In an embodiment, an oil guiding passage making the transmission holding cavity **120** and

the oil pump **13** be in communication with each other is disposed in a wall of the box assembly **100**. Specifically, the oil guiding passage is formed in the wall of the box assembly **100** in a punching manner. In this way, it is convenient to smoothly transport the cooling lubricating liquid, and it is convenient for the cooling lubricating liquid to perform heat dissipation and temperature reduction on the electric assembly **1**. Particularly, it may be convenient to lubricate the bearing and the spline. For example, the oil guiding passage may be extended to the bearing or spline location, to directly transport the cooling lubricating liquid to the bearing or spline location, thereby avoiding a case in which injection of the oil liquid affects the cooling and lubricating effects.

[0078] Specifically, the oil pump **13** transports the cooling lubricating liquid in the transmission holding cavity **120** to the mounting plate **160** and at least one gear location and/or at least one bearing location and/or at least one meshing location through the oil guiding passage. Specifically, the oil pump **13** may transport the cooling lubricating liquid to at least one of the gear location, the bearing location and the meshing location through the oil guiding passage. In this way, it is not only further convenient to transport the cooling lubricating liquid to the mounting plate **160**, to help the cooling lubricating liquid cool the mounting plate **160** and help transfer heat through the mounting plate **160**, but also convenient to improve the lubricating performance of the at least one of the gear location, the bearing location and the meshing location, to help the electric assembly **1** smoothly operate and help improve the reliability and stability of the electric assembly **1**.

[0079] In an embodiment, a distance between the motor **200** and the mounting plate **160** is less than a preset distance. It should be understood herein that, the preset distance is a maximum distance making the mounting plate **160** cool the motor **200**, and a person skilled in the art may learn the preset distance through the rated voltage and rated current of the electric assembly **1**. For example, the distance between the motor **200** and the mounting plate **160** may be less than 10 millimeters, and is preferably 7.5 millimeters. Because the motor is close to the mounting plate **160**, the motor **200** and the mounting plate **160** may be cooled at a short distance between each other, and after the mounting plate **160** is cooled, the motor **200** can be quickly cooled. In an embodiment, as shown in FIG. **9** and FIG. **10**, a surface of the mounting plate **160** facing the motor **200** and/or the transmission **400** is provided with ribs. Because the ribs enhance the rigidity of the box assembly **100** and improve the natural frequency, resonance may be prevented from occurring in the electric assembly **1**, to reduce the noise of the electric assembly **1**. In this way, the contact area between the cooling lubricating liquid and the mounting plate **160** may be increased, so that the cooling lubricating liquid cools the mounting plate **160** more fully.

[0080] Specifically, during rotation of the motor **200**, a stress is transferred to the box assembly **100** through a bearing, and ribs are added to the box assembly **100**, to help increase rigidity and strength of the box assembly **100**, prevent the box assembly **100** from being in contact with a coil of the motor **200**, prevent components of the motor **200** from being damaged, and further improve operating reliability and stability of the motor **200**.

[0081] Further, the ribs divide a space between the mounting plate **160** and the motor **200** into a plurality of cavities **162**. In this way, forming of the cavities **162** is facilitated, so as to cool the motor **200** by using air passing through the cavities **162**.

[0082] According to an embodiment of the present disclosure, as shown in FIG. **12**, the ribs include an annular rib **163** extending along a circumferential direction of the motor **200**. In this way, rigidity and strength of the box assembly **100** may be improved, the structure stability of the box assembly **100** may be improved, and the heat dissipation capability and the cooling effect of the box assembly **100** may be improved.

[0083] According to another embodiment of the present disclosure, as shown in FIG. **10**, the ribs include strip-shaped ribs **161** extending along a radial direction of the motor **200**, there are a plurality of strip-shaped ribs **161** and the plurality of strip-shaped ribs **161** are spaced apart along a circumferential direction of the mounting plate **160**. In this way, a more even force may be applied to the box assembly **100**, to further help improve rigidity and strength of the box assembly **100**,

further help improve noise reduction performance and heat dissipation performance of the electric assembly **1**, and improve the cooling effect of the electric assembly **1**.

[0084] According to another embodiment of the present disclosure, the ribs include an annular rib **163** extending along a circumferential direction of the motor **200** and strip-shaped ribs **161** extending along a radial direction of the motor **200**, there are a plurality of strip-shaped ribs **161** and the plurality of strip-shaped ribs **161** are spaced apart along a circumferential direction of the mounting plate **160**. In this way, rigidity and strength of the box assembly **100** along the circumferential direction and the radial direction of the motor **200** may be improved at the same time, thereby improving the structure reliability of the box assembly **100**, further improving the heat dissipation area of the box assembly **100**, and improving heat dissipation and cooling performance of the electric assembly **1**.

[0085] Specifically, heights of the strip-shaped ribs **161** relative to the mounting plate **160** gradually decrease from a center portion of the mounting plate to a periphery portion of the mounting plate. In this way, the disposition space of the strip-shaped ribs **161** may be reduced, to prevent the strip-shaped ribs **161** from occupying excessive space in the box assembly **100**, and further facilitate mounting and disposition of the motor **200** and the transmission **400**. On the other hand, the heights of the strip-shaped ribs **161** relative to the mounting plate **160** gradually decrease from a center portion of the mounting plate to a periphery portion of the mounting plate, and the center portion has a largest height, and may bear a high strength load formed by a bearing on the box assembly **100**.

[0086] According to an embodiment of the present disclosure, the box assembly **100** includes a transmission box **101** and a motor box **102**, the transmission box **101** includes a front box **180** and a rear box **190**, the motor box **102** includes a motor housing **140** and a motor backend cover **150**, the front box **180** and the motor housing **140** are disposed adjacent to each other, and the mounting plate **160** is constructed as a part of the front box **180** or a part of the motor housing **140**. In this way, it is convenient for the electric assembly **1** to become a three-segment structure, forming of the transmission holding cavity **120** and the motor holding cavity **110** is facilitated, and mounting and dismounting of the electric assembly **1** are facilitated. Moreover, the mounting plate **160** is a part of the front box **180** or a part of the motor housing **140**, and the mounting plate **160** is integrated on the box assembly **100**, so that the structure of the box assembly **100** may be made more proper and compact, and the mounting plate **160** may be cooled by the lubricating liquid of the transmission **400**, thereby improving the lubricating and cooling effect of the mounting plate **160**.

[0087] Further, the front box **180** and the motor housing **140** are integrally formed or detachably connected. In this way, the electric assembly **1** may be a three-segment structure, to facilitate the disposition of the motor **200** and the transmission **400**.

[0088] According to another embodiment of the present disclosure, as shown in FIG. **9** and FIG. **10**, the box assembly **100** includes a transmission box **101** and a motor box **102**, the transmission box **101** includes a front box **180** and a rear box **190**, the motor box **102** includes a motor frontend cover **170**, a motor housing **140** and a motor backend cover **150**, and the mounting plate **160** is constructed as a part of the front box **180** or a part of the motor frontend cover **170**. In this way, it is convenient for the electric assembly **1** to become a three-segment structure, forming of the transmission holding cavity **120** and the motor holding cavity **110** is facilitated, and mounting and dismounting of the electric assembly **1** are facilitated. Moreover, the mounting plate **160** is a part of the front box **180** or a part of the motor housing **140**, and the mounting plate **160** is integrated on the box assembly **100**, so that the structure of the box assembly **100** may be made more proper and compact, and the mounting plate **160** may be cooled by the lubricating liquid of the transmission **400**, thereby improving the lubricating and cooling effect of the mounting plate **160**.

[0089] According to an embodiment of the present disclosure, as shown in FIG. **2**, the motor housing **140**, the motor frontend cover **170** and the front box **180** are integrally formed or each two

of the motor housing **140**, the motor frontend cover **170** and the front box **180** are detachably connected. In this way, the structure flexibility of the box assembly may be improved, to facilitate optimization of the structure of the box assembly **100**, facilitate reduction of the weight of the box assembly **100**, and improve the endurance capability of the electric assembly **1**.

[0090] According to another embodiment of the present disclosure, the motor frontend cover **170** and the front box **180** are integrally formed, and the motor housing **140** and the motor frontend cover **170** are detachably connected. In this way, simplification of the assembly process of the box assembly **100** is facilitated, thereby improving the assembly efficiency of the box assembly **100**.

[0091] According to another embodiment of the present disclosure, the motor frontend cover **170** and the motor housing **140** are integrally formed, and the motor frontend cover **170** and the front box **180** are detachably connected. In this way, mutual separation between the transmission box **101** and motor box **102** is facilitated, to help improve the structure flexibility of the box assembly **100**.

[0092] According to another embodiment of the present disclosure, the motor housing **140** is connected to the motor frontend cover **170** through a bolt, the motor frontend cover **170** is connected to the front box **180** through a bolt, and the motor housing **140** is connected to the motor backend cover **150** through a bolt. In this way, machining and forming of the motor housing **140**, the motor frontend cover **170**, the front box **180** and the rear box **190** are facilitated, so as to simplify the forming process. The motor housing **140** the front box **180** the rear box **190** the motor backend cover **150** the motor housing **140** the front box **180** the rear box **190** the motor backend cover **150** the motor housing **140** the front box **180** the motor housing **140**. Because each of the motor frontend cover **170**, the motor housing **140** and the motor backend cover **150** is detachable, the length of the motor **200** may be adjusted. For example, the length of the motor housing **140** as a standard member may be individually adjusted, thereby improving the structure flexibility and the application range of the motor **200**.

[0093] Specifically, as shown in FIG. **9**, one or more of a first connection rib **181**, a second connection rib **182** and a third connection rib **183** are connected between an outer surface of the front box **180** and an outer surface of the motor housing **140**, the first connection rib **181** is connected between (an up-down direction is shown by an arrow A in FIG. **9**) an upper end face of the motor housing **140** and an upper end face of the front box **180**, the second connection rib **182** is connected between a lower end face of the motor housing **140** and a lower end face of the front box **180**, and the third connection rib **183** is located between the first connection rib **181** and the second connection rib **182**. In this way, the strength of connection between the front box **180** and the motor housing **140** may be reinforced, to avoid a case in which a point with weak strength occurs in a connection location between the front box **180** and the motor housing **140** to cause deformation or damage, thereby improving the entire structure performance of the box assembly **100**.

[0094] In an embodiment, as shown in FIG. **3**, the transmission **400** includes a main shaft **300**, the main shaft **300** is power-coupled to a motor shaft **210** of the motor **200**, at least one of the motor shaft **210** and the main shaft **300** is threaded through a shaft via-hole **130** and is connected to the other one, and the main shaft **300** is connected to the motor shaft **210** of the motor **200** through splines. In this way, direct transmission between the motor shaft **210** and the main shaft **300** is facilitated, and an additional transmission structure may be left out, to further simplify the structure of the electric assembly **1**, improve the integration level of the electric assembly **1**, help transfer power outputted by the motor **200** to the transmission **400** in time, help improve the transmission efficiency of the electric assembly **1**, and help improve timeliness and accuracy of power transmission of the electric assembly **1**. In this way, the main shaft **300** and the motor shaft **210** may be fixed and positioned by using splines, to prevent relative rotation from occurring between the main shaft **300** and the motor shaft **210**, facilitate reliable transmission of the electric assembly **1**, and help ensure transmission efficiency of the electric assembly **1**. In this way, another structure connecting the main shaft **300** and the motor shaft **210** may be left out, thereby further simplifying

the structure of the electric assembly **1**, and improving the integration level of the electric assembly **1**, and because the main shaft **300** and the motor shaft **210** are sleeved over each other, the shaft spacing of the electric assembly **1** is further shortened, so as to further control the size of the electric assembly **1** in the axial direction of the motor shaft **210**.

[0095] Further, as shown in FIG. 2, the main shaft **300** is provided with a shaft hole **310**, an inner circumferential surface of the shaft hole **310** is provided with inner splines **311**, an outer circumferential surface of the motor shaft **210** is provided with outer splines **211**, the motor shaft **210** of the motor **200** is matched in the shaft hole **310** and the inner splines **311** match the outer splines **211**. In this way, machining of the inner splines **311** is facilitated, to help improve machining precision of the inner splines **311**. Through the matching between the inner splines **311** and the outer splines **211**, transmission connection between the main shaft **300** and the motor shaft **210** may be implemented, and reliable positioning between the main shaft **300** and the motor shaft **210** may be implemented, to further prevent relative rotation from occurring between the main shaft **300** and the motor shaft **210**. Moreover, the motor **200** is a three-segment motor, the main shaft **300** and the motor shaft **210** are sleeved over each other, and the length of the motor **200** may be adjusted according to a requirement, to help change torque and power of the motor **200**, and help improve compatibility of the motor **200**.

[0096] Specifically, the shaft hole **310** runs through the main shaft **300** along an axial direction of the main shaft **300**, an oil baffle **320** is matched in the shaft hole **310**, the oil baffle **320**, an inner circumferential wall of the shaft hole **310** and the motor shaft **210** jointly define an oil storage cavity **330**, the oil storage cavity **330** is filled with lubricating oil, and the oil baffle **320** is provided with an air vent **350**. In this way, the disposition of the lubricating oil is facilitated, and the lubricating oil in the shaft hole **310** can be effectively prevented from leaking, to play a role of protecting a spline lubricating system. In this way, the main shaft **300** may have an oil storage function, the splines may be lubricated and cooled, the air vent **350** may discharge generated gas at the right time, and the disposition of the shaft hole **310** running through along the axial direction of the main shaft **300** may avoid a case in which gas exists in the shaft hole **310** to affect mounting of the motor shaft **210** and the main shaft **300**.

[0097] More specifically, a seal retainer ring is matched between the oil baffle **320** and the shaft hole **310** and between the outer circumferential surface of the motor shaft **210** and the inner circumferential surface of the shaft hole **310**. In this way, it is convenient to seal the oil storage cavity **330**, and the lubricating oil in the oil storage cavity **330** may be prevented from leaking, thereby improving the seal effect of the oil storage cavity **330**.

[0098] Specifically, as shown in FIG. 2, the electric assembly **1** further includes a plurality of bearings, and the plurality of bearings are respectively sleeved over the motor shaft **210** and the main shaft **300** and are spaced apart along the axial direction of the motor shaft **210** and the main shaft **300**. In this way, smooth rotation of the motor shaft **210** and the main shaft **300** is facilitated, to help improve reliability and accuracy of rotation of the motor shaft **210** and the main shaft **300**.

[0099] According to an embodiment of the present disclosure, as shown in FIG. 8, the plurality of bearings include a first bearing **510**, a second bearing **520** and a third bearing **530**, the first bearing **510** and the second bearing **520** are respectively disposed adjacent to two ends of the main shaft **300**, and the third bearing **530** is disposed adjacent to one end of the motor shaft **210** far away from the main shaft **300**. In this way, the disposition of the motor shaft **210** and the main shaft **300** is facilitated, to further facilitate smooth rotation of the motor shaft **210** and the main shaft **300**, and the quantity of the bearings may be reduced, to reduce costs of the electric assembly **1**.

[0100] Specifically, the third bearing **530** is disposed between one end of the motor shaft **210** far away from the transmission **400** and the box assembly **100**, the first bearing **510** is disposed between one end of the main shaft **300** far away from the motor **200** and the box assembly **100**, and the second bearing **520** is disposed between at least one of one end of the motor **200** close to the main shaft **300** and one end of the main shaft **300** close to the motor shaft **210** and the box

assembly **100**. In this way, the force applied to the motor shaft **210** and the main shaft **300** may be more balanced, to help improve the operating performance of the electric assembly **1**.

[0101] In an embodiment, the second bearing **520** is sleeved over the main shaft **300** and is located on an overlap between the main shaft **300** and the motor shaft **210** in the axial direction. In this way, the second bearing **520** may be used for supporting the main shaft **300** and the motor shaft **210**, to ensure the disposition reliability of the main shaft **300** and the motor shaft **210**. Because the overlap between the main shaft **300** and the motor shaft **210** in the axial direction is a place on which rotation forms stress concentration, effective supporting of the second bearing **520** may prevent the main shaft **300** and the motor shaft **210** from being broken, thereby improving the operating performance of the main shaft **300** and the motor shaft **210**.

[0102] According to another embodiment of the present disclosure, as shown in FIG. 7, the electric assembly **1** further includes a fourth bearing **540**, where the fourth bearing **540** is sleeved over the motor shaft **210** and is located between the motor shaft **210** and the motor housing. In this way, the fourth bearing **540** may be used for reinforcing supporting on the motor shaft **210**, thereby further improving the disposition reliability of the motor shaft **210**.

[0103] Specifically, the fourth bearing **540** is located between the main shaft **300** and a stator of the motor **200** in the axial direction of the motor shaft **210**. In this way, the force applied to the main shaft **300** and the motor **200** may be more even, to help improve reliability and stability of power transfer between the main shaft **300** and the motor **200**.

[0104] In an embodiment, as shown in FIG. 11, an outer surface of the motor housing **140** is provided with reinforcing ribs **141** arranged along the outer surface of the motor housing **140**. In this way, it is convenient to improve the strength of the motor housing **140**, and the surface area of the motor housing **140** may be increased, thereby improving the heat dissipation performance of the motor housing **140**.

[0105] Specifically, after the motor backend cover **150** is dismounted, the transmission holding cavity **120** may be opened. In this way, it may be convenient to replace and maintain the transmission **400**.

[0106] Further, an end face of the motor holding cavity **110** far away from one end of the transmission holding cavity **120** may be opened, and after the motor **200** is mounted to the box assembly **100**, the motor backend cover **150** covers the motor holding cavity **110**.

[0107] In an embodiment, the motor housing **140** and the motor backend cover **150** are mounted through bolts and the front box **180** and the rear box **190** are mounted through bolts. In this way, reliability and stability of the fixed connection between the motor housing **140** and the motor backend cover **150** and between the front box **180** and the rear box **190** may be ensured, and when the electric assembly **1** has a fault, the box assembly **100** may be quickly dismounted, to further facilitate maintenance of the electric assembly **1**.

[0108] Specifically, as shown in FIG. 2, the first bearing **510** is located on the motor backend cover **150**, the second bearing **520** and the fourth bearing **540** are respectively disposed at two ends of the shaft via-hole **130**, and the third bearing **530** is located on an end face of the motor holding cavity **110** far away from the transmission holding cavity **120**. In this way, the force applied to the main shaft **300** and the motor **200** may be more even, to further help improve the structure stability of the electric assembly **1**.

[0109] More specifically, the main shaft **300** is provided with a first main shaft positioning slot and a second main shaft positioning slot, the first bearing **510** is matched in the first main shaft positioning slot, and the second bearing **520** is matched in the second main shaft positioning slot. The motor shaft **210** is provided with a third motor shaft positioning slot and a fourth motor shaft positioning slot, the third bearing **530** is matched in the third motor shaft positioning slot, and the fourth bearing **540** is matched in the fourth motor shaft positioning slot. The box assembly **100** is provided with box positioning slots matching the bearings. In this way, the positioning slots may be used for positioning the bearings, to facilitate reliable disposition of the bearings, and help improve

location accuracy of the bearings.

[0110] In an embodiment, the electric assembly **1** can be directly mounted to the chassis of the vehicle **11** through a suspension mounting point on the box assembly **100**. In this way, mounting of the electric assembly **1** is further facilitated, improvement of the mounting efficiency of the vehicle **11** is facilitated, and the mounting costs of the vehicle **11** are reduced.

[0111] Specifically, as shown in FIG. **6**, the transmission **400** includes a differential assembly **440**, a first gear **410**, a second gear **420**, a third gear **430** and a transmission shaft **450**, the first gear **410** is sleeved over the main shaft **300**, the second gear **420** and the third gear **430** are sleeved over the transmission shaft **450**, the first gear **410** is meshed with the second gear **420**, and the third gear **430** is meshed with the differential assembly **440**. In this way, it is convenient for the transmission **400** to implement speed change transmission.

[0112] In an embodiment, as shown in FIG. **1**, the box assembly **100** includes the cylindrical motor housing **140** and the front box assembly **180** of the transmission connected to the motor housing **140**, the motor holding cavity **110** is disposed in the motor housing **140**, the transmission holding cavity **120** is disposed between the front box **180** and the rear box **190**, and the box of the transmission protrudes outward from the outer circumferential surface of the motor housing **140**. In this way, it is convenient for the box assembly **100** to protect the electric assembly **1**.

[0113] Specifically, as shown in FIG. **6**, the axial line of the motor shaft **210** is parallel to those of the main shaft **300**, the transmission shaft **450** and the differential assembly **440**. In this way, it is convenient for the electric assembly **1** to smoothly transfer power.

[0114] In an embodiment, the electric assembly **1** further includes a controller **500**, where the controller **500** is mounted outside the box assembly **100** and fixedly connected to the box assembly **100**. In this way, the integral disposition of the controller **500** is facilitated, and an external three-phase line disposed between the controller **500** and the motor **200** may be left out, to facilitate optimization of the structure of the electric assembly **1**, reduce costs of the electric assembly **1**, prevent mounting of the external three-phase line from affecting the seal effect of the electric assembly **1**, prevent electric leakage from occurring in the electric assembly **1**, improve the operating efficiency of the electric assembly **1**, improve the anti-interference capability of the electric assembly **1**, and reduce the fault rate of the electric assembly **1**.

[0115] According to an embodiment of the present disclosure, as shown in FIG. **13**, the electric assembly **1** further includes a conductive sheet **20**, where the conductive sheet **20** is configured to connect the controller **500** and the motor **200**. For example, the conductive sheet **20** has a controller connection end and a motor connection end, the controller connection end is used for connecting to the controller **500**, for example, connecting to a three-phase line of the controller **500**, the motor connection end is used for connecting to the motor **200**, for example, connecting to a three-phase line of the motor **200**, and the conductive sheet **20** is fixed to the controller **500** through a bolt. In this way, external three-phase lines and connection bases may be left out, the length of the three-phase lines is reduced, the connection base structure is left out, and costs are reduced.

[0116] Specifically, the motor **200** includes a motor body **203** and a connection device **204**, the connection device **204** is mounted on the motor body **203**, the motor body **203** has a plurality of leading wires **2031**, the connection device **204** includes a plurality of conductive sheets **20**, and the plurality of conductive sheets **20** are respectively connected to the corresponding leading wires **2031**, where the conductive sheet **20** has a controller connection end, and the controller connection end of the conductive sheet **20** is used for directly connecting to the controller **500**.

[0117] In other words, the controller **500** is directly connected to the controller connection end at one end of the conductive sheet **20**, and the other end of the conductive sheet **20** is connected to the leading wire **2031** of the motor body **203** (the leading wire may be a leading wire of a motor winding). In this way, the controller **500** may control the motor body **203**, and the connection between the motor controller **100** and the motor body **203** through the conductive sheet **20** may make the entire structure of the motor **200** more compact.

[0118] In some embodiments, the connection device **204** further includes a supporting plate **205**, the supporting plate **205** is relatively fixedly mounted on the motor body **203**, the supporting plate **205** is provided with a positioning insert **206**, two ends of the positioning insert **206** respectively stretch out of two opposite side surfaces on the supporting plate **205**, a part of the conductive sheet **20** is inserted into the positioning insert **206**, and the controller connection end of the conductive sheet **20** stretches out of the positioning insert **206**. In other words, the supporting plate **205** is fixedly mounted on the motor body **203**, the positioning insert **206** stretches out of two sides of the supporting plate **205**, the conductive sheet **20** is inserted into the positioning insert **206**, and two ends of the conductive sheet partially stretch out of the positioning insert **206** and are used for respectively connecting to the leading wire **2031** and the controller connection end, where the positioning insert **206** provides supporting and positioning for the conductive sheet **20**.

[0119] Further, the plurality of conductive sheets **20** are disposed side by side and spaced apart from each other. It may be understood that, the plurality of conductive sheets **20** spaced apart from each other may prevent a case of short-circuit or confused connection from occurring.

[0120] That is to say, motor connection ends of conductive members **10** are connected to the conductive sheets **20** in a one-to-one correspondence, the conductive member **10** and the conductive sheet **20** are electrically connected, and the conductive member **10** and the conductive sheet **20** are directly connected without a conducting wire or another connection device. In this way, the line of the electric assembly **1** may be shortened, thereby improving the anti-interference capability, and greatly saving the space.

[0121] In an embodiment, the conductive member **10** and the conductive sheet **20** are in screw connection. The screw connection is self-locking connection, the connection is stable and not easy to be loose, and dismounting is convenient. Certainly, the foregoing embodiment is only schematic, and cannot be understood as a limitation on the protection scope of the present disclosure. For example, the conductive member **10** and the conductive sheet **20** may be in insertion connection, sticking connection, welding connection, riveting connection or the like.

[0122] According to another embodiment of the present disclosure, as shown in FIG. **16**, the electric assembly **1** further includes a conductive sheet **20**, where the conductive sheet **20** is stuck in the controller **500** or the conductive sheet **20** is fixed to the controller **500** through a bolt. The conductive sheet **20** has a controller connection end and a motor connection end, the controller connection end is used for connecting to the controller **500**, for example, connecting to a three-phase line of the controller **500**, the motor connection end is used for connecting to the motor **200**, for example, a three-phase line of the motor **200**, and the conductive sheet **20** is stuck in the controller **500**. In this way, dismounting and mounting of the conductive sheet **20** are facilitated, external three-phase lines and connection bases may be left out, the length of the three-phase lines is reduced, the connection base structure is left out, and costs are reduced.

[0123] Specifically, the electric assembly **1** includes a motor **200** and a controller **500**. The motor **200** includes a motor body **203** and a connection device **204**, the connection device **204** is mounted on the motor body **203**, the motor body **203** has a plurality of leading wires **2031**, the connection device **204** includes a plurality of conductive sheets **20**, and the plurality of conductive sheets **20** are respectively connected to the corresponding leading wires **2031**, where the conductive sheet **20** has a controller connection end. The motor controller **100** is mounted on the motor **200**, the motor controller **100** has a conductive member **10**, and the conductive member **10** has a power supply connection end used for connecting to a power supply and a motor connection end **2212** used for directly connecting to the motor **200**, where one of the motor connection end **2212** of the conductive member **10** and the controller connection end of the conductive sheet has an insertion structure and the other one and the insertion structure are in insertion connection.

[0124] In other words, the power supply connection end of the conductive member **10** is connected to the power supply, and the motor connection end **2212** of the conductive member **10** and the controller connection end of the conductive sheet **20** are connected. That is to say, the motor

controller **100** is directly connected to the controller connection end at one end of the conductive sheet **20**, and the other end of the conductive sheet **20** is connected to the leading wire **2031** of the motor body **203** (the leading wire **2031** may be a leading wire of a motor winding). In this way, the motor controller **100** may control the motor body **203**, and the connection between the motor controller **100** and the motor body **203** through the conductive sheet **20** may make the entire structure of the motor **200** more compact.

[0125] Moreover, the motor connection end **2212** of the conductive member **10** and the conductive sheet **20** of the motor **200** are connected through an insertion structure. It may be understood that, compared with an insulation line wiring manner, the insertion connection manner is simpler, procedures are simplified, and the time is saved. Moreover, when a bumping case is encountered, integrity of the conductive sheet **20** of the motor may be ensured, and occurrence of cases such as bending the conductive sheet **20** and breaking the conductive sheet **20** is reduced.

[0126] That is to say, motor connection ends **2212** of conductive members **10** are connected to the conductive sheets **20** in a one-to-one correspondence, the conductive member **10** and the conductive sheet **20** are electrically connected, and the conductive member **10** and the conductive sheet **20** are directly connected without a conducting wire or another connection device. In this way, the line of the electric assembly **1** may be shortened, thereby improving the anti-interference capability, and greatly saving the space.

[0127] In some embodiments, the conductive sheet **20** is provided with a stop groove, the insertion structure is provided with a stop protrusion, and the stop protrusion is properly buckled into the stop groove. When the insertion structure and the conductive sheet **20** are connected, the stop protrusion matches the stop groove. In this way, the contact area between an insertion sheet **2211** and the conductive sheet **20** may be increased, and the insertion sheet **2211** may be prevented from transiently departing from the conductive sheet **20** during vibration, to prevent a case of undesired contact from occurring.

[0128] A vehicle **11** according to an embodiment of the present disclosure is described below. The vehicle **11** according to one embodiment of the present disclosure includes the electric assembly **1** according to the foregoing embodiment of the present disclosure.

[0129] In the vehicle **11** according to one embodiment of the present disclosure, the electric assembly **1** according to one embodiment of the present disclosure is used, where the electric assembly has advantages such as a compact structure and a good cooling effect.

[0130] Other configurations and operations of the vehicle **11** according to the embodiments of the present disclosure are known to those of ordinary skill in the art and will not be described in detail herein.

[0131] In the description of the present disclosure, it should be understood that, orientations or position relationships indicated by terms such as “center”, “longitudinal”, “transverse”, “length”, “width”, “thickness”, “up”, “down”, “front”, “rear”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inner”, “outer”, “clockwise”, “counterclockwise”, “axial”, “radial”, and “circumferential” are orientations or position relationship shown based on the accompanying drawings, and are merely used for describing the present disclosure and simplifying the description, rather than indicating or implying that the apparatus or element should have a particular orientation or be constructed and operated in a particular orientation, and therefore, should not be construed as a limitation on the present disclosure. Moreover, features modified by “first” and “second” may explicitly or implicitly include one or more features. In descriptions of the present disclosure, “a plurality of” means two or more, unless otherwise stated.

[0132] In the descriptions of the present disclosure, it should be noted that, unless otherwise clearly specified and defined, terms such as “mounting”, “interconnection”, and “connection” shall be understood in a broad sense, for example, may be a fixing connection, a detachable connection, an integral connection, a mechanical connection, an electrical connection, a direct connection, an indirect connection by using an intermediate medium, and communication between interiors of two

components. A person of ordinary skill in the art may understand specific meanings of the foregoing terms in the present disclosure according to a specific situation.

[0133] In the descriptions of this specification, descriptions such as reference terms “an embodiment”, “some embodiments”, “exemplary embodiment”, “example”, “specific example”, or “some examples” indicate that specific features, structures, materials, or characteristics described with reference to embodiments or examples are included in at least one embodiment or example of the present disclosure. In this specification, exemplary descriptions of the foregoing terms do not necessarily refer to a same embodiment or example. In addition, the described specific feature, structure, material, or characteristic may be combined in a proper manner in any one or more embodiments or examples.

[0134] Although the disclosed embodiments of the present disclosure have been shown and described, a person skilled in the art can understand that the above embodiments cannot be construed to limit the present disclosure, and changes, alternatives, and modifications can be made in the embodiments without departing from the principle and the purpose of the present disclosure.

Claims

1. An electric assembly, comprising: a box assembly, wherein a mounting plate is disposed in the box assembly, and the mounting plate divides a space within the box assembly into a motor holding cavity and a transmission holding cavity; a motor, wherein the motor is disposed in the motor holding cavity and comprises a motor shaft; and a transmission, wherein the transmission is disposed in the transmission holding cavity, the transmission comprises a main shaft having a first gear disposed around the main shaft, the motor is power-coupled to the transmission through the motor shaft coupling with the main shaft at an overlapping region of the motor shaft and the main shaft, and a bearing is disposed at the overlapping region, wherein the transmission further includes a second gear, a third gear, and a differential assembly, the first gear is power-coupled to the second gear, the second gear is power-coupled and coaxial to the third gear, the differential assembly has a fourth gear disposed around the differential assembly, and the third gear is power-coupled to the differential assembly via the fourth gear, wherein a first connection line is a connection line between a center of the first gear and a center of the second gear, a second connection line is a connection line between the center of the second gear and a center of the differential assembly, and the first connection line is in an obtuse angle with the second connection line, and wherein the bearing comprises a first bearing, a second bearing, and a third bearing, the first bearing and the second bearing are respectively disposed adjacent to two ends of the main shaft, and the third bearing is disposed adjacent to one end of the motor shaft away from the main shaft.
2. The electric assembly according to claim 1, wherein an axis of the main shaft is offset from and parallel to an axis of the differential assembly.
3. The electric assembly according to claim 1, wherein a diameter of the fourth gear is greater than a diameter of the third gear, and a diameter of the second gear is greater than a diameter of the first gear.
4. The electric assembly according to claim 3, wherein the third bearing is disposed between one end of the motor shaft away from the transmission and the box assembly, the first bearing is disposed between a first end of the main shaft away from the motor and the box assembly, and the second bearing is disposed between at least one of one end of the motor close to the main shaft and a second end of the main shaft close to the motor shaft and the box assembly, the second bearing is disposed around the main shaft and is located on the overlapping region between the main shaft and the motor shaft in an axial direction of the main shaft.
5. The electric assembly according to claim 1, wherein the motor and the transmission are directly integrated through the box assembly without an external connection of the motor and the transmission.

6. The electric assembly according to claim 1, wherein the transmission holding cavity is configured to contain a cooling lubricating liquid to cool the box assembly, and the cooling lubricating liquid cools the box assembly through the mounting plate.
7. The electric assembly according to claim 6, wherein a distance between the motor and the mounting plate is less than a preset distance such that the mounting plate cools the motor.
8. The electric assembly according to claim 1, wherein the box assembly comprises a transmission box and a motor box, the transmission box comprises a front box and a rear box, the motor box comprises a motor housing and a motor backend cover, the front box and the motor housing are disposed adjacent to each other, and the mounting plate is a part of the front box or a part of the motor housing.
9. The electric assembly according to claim 6, the bearing is disposed between the main shaft and the motor housing.
10. The electric assembly according to claim 1, wherein: the box assembly comprises a transmission box and a motor box, the transmission box comprises a front box and a rear box, the motor box comprises a motor frontend cover, a motor housing, and a motor backend cover, and the mounting plate is a part of the front box or a part of the motor frontend cover.
11. The electric assembly according to claim 1, further comprising: a conductive sheet and a controller, the conductive sheet connects to the controller and the motor.
12. The electric assembly according to claim 11, wherein the controller is mounted outside the box assembly and fixedly connected to the box assembly.
13. The electric assembly according to claim 9, wherein reinforcing ribs are disposed along an outer surface of the motor housing.
14. A vehicle, comprising an electric assembly, wherein the electric assembly comprises: a box assembly, wherein a mounting plate is disposed in the box assembly, and the mounting plate divides a space within the box assembly into a motor holding cavity and a transmission holding cavity; a motor, wherein the motor is disposed in the motor holding cavity and comprises a motor shaft; and a transmission, wherein the transmission is disposed in the transmission holding cavity, the transmission comprises a main shaft having a first gear disposed around the main shaft, the motor is power-coupled to the transmission through the motor shaft coupling with the main shaft at an overlapping region of the motor shaft and the main shaft, and a bearing is disposed at the overlapping region, wherein the transmission further includes a second gear, a third gear, and a differential assembly, the first gear is power-coupled to the second gear, the second gear is power-coupled and coaxial to the third gear, the differential assembly has a fourth gear disposed around the differential assembly, and the third gear is power-coupled to the differential assembly via the fourth gear, wherein a first connection line is a connection line between a center of the first gear and a center of the second gear, a second connection line is a connection line between the center of the second gear and a center of the differential assembly, and the first connection line is in an obtuse angle with the second connection line, and wherein the bearing comprises a first bearing, a second bearing, and a third bearing, the first bearing and the second bearing are respectively disposed adjacent to two ends of the main shaft, and the third bearing is disposed adjacent to one end of the motor shaft away from the main shaft.
15. The vehicle according to claim 14, wherein an axis of the main shaft is offset from and parallel to an axis of the differential assembly.
16. The vehicle according to claim 14, wherein a diameter of the fourth gear is greater than a diameter of the third gear, and a diameter of the second gear is greater than a diameter of the first gear.
17. The vehicle according to claim 16, wherein the third bearing is disposed between one end of the motor shaft away from the transmission and the box assembly, the first bearing is disposed between a first end of the main shaft away from the motor and the box assembly, and the second bearing is disposed between at least one of one end of the motor close to the main shaft and a second end of

the main shaft close to the motor shaft and the box assembly, the second bearing is disposed around the main shaft and is located on the overlapping region between the main shaft and the motor shaft in an axial direction of the main shaft.

18. The vehicle according to claim 14, wherein the box assembly comprises a motor box, the motor box comprises a motor housing, and reinforcing ribs are disposed along an outer surface of the motor housing.

19. The vehicle according to claim 14, wherein the motor and the transmission are directly integrated through the box assembly without an external connection of the motor and the transmission.

20. The vehicle according to claim 14, wherein the transmission holding cavity is configured to contain a cooling lubricating liquid to cool the box assembly, and the cooling lubricating liquid cools the box assembly through the mounting plate.
