

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287061

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

HONG; Jiyeon et al.

HUB DEVICE, MULTI-DEVICE SYSTEM INCLUDING THE HUB DEVICE AND PLURALITY OF DEVICES, AND OPERATING METHOD OF THE HUB DEVICE AND MULTI-DEVICE SYSTEM

Abstract

A method, performed by a hub device, of storing a voice assistant model for controlling a device includes receiving information about a first device connected to the hub device, requesting a voice assistant server to update a device determination model stored in the hub device; receiving the updated device determination model from the voice assistant server and storing the received updated device determination model; requesting, from the voice assistant server, information about a function determination model corresponding to the first device; receiving the information about the function determination model corresponding to the first device from the voice assistant server, and determining whether to store the function determination model in the hub device based on the received information; and based on the function determination model being determined to be stored in the hub device, storing, in the hub device, the function determination model corresponding to the first device.

Inventors: HONG; Jiyeon (Suwon-si, KR), KO; Hyeonmok (Suwon-si, KR), CHOI; Sungja (Suwon-si, KR), PAEON; Changho (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008620820

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 19/217756

Filed: May 23, 2025

Foreign Application Priority Data

KR 10-2019-0138767

Nov. 01, 2019

KR 10-20200065181

May. 29, 2020

Related U.S. Application Data

parent US continuation 18397357 20231227 parent-grant-document US 12335550 child US 19217756
parent US continuation 17085565 20201030 parent-grant-document US 11930230 child US 18397357

Publication Classification

Int. Cl.: **H04N21/258** (20110101); **H04N21/236** (20110101); **H04N21/24** (20110101);
H04N21/262 (20110101)

U.S. Cl.:

CPC **H04N21/25891** (20130101); **H04N21/236** (20130101); **H04N21/24** (20130101);
H04N21/262 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. patent application Ser. No. 18/397,357, filed Dec. 27, 2023 (allowed), which is a continuation application of U.S. patent application Ser. No. 17/085,565, filed on Oct. 30, 2020 (now U.S. Pat. No. 11,930,230, issued on Mar. 12, 2024), in the U.S. Patent and Trademark Office, which claims priority to Korean Patent Application No. 10-2019-0138767, filed on Nov. 1, 2019, and Korean Patent Application No. 10-2020-0065181, filed on May 29, 2020, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

[0002] The disclosure relates to a hub device including: an artificial intelligence (AI) model for determining an operation-performing device for performing an operation according to a user's intention based on a voice input received from the user; and an AI model for controlling an operation performed by the determined operation-performing device, in a multi-device environment including the hub device and a plurality of devices, a multi-device system, and an operating method of the hub device and the multi-device system.

2. Description of Related Art

[0003] As multimedia technology and network technology have developed, users may receive various services by using devices. In particular, with the development of voice recognition technology, a user may input a voice (e.g., an utterance) to a device and may receive a response message to the input voice through a service providing agent.

[0004] However, in a multi-device system such as a home network environment including a plurality of devices, when a user wants to receive a service by using a device other than a client device that interacts through a voice input or the like, the user has to inconveniently select a device to provide the service. In particular, because types of services that may be provided by the plurality of devices are different, there is a demand for technology capable of recognizing an intention included in the voice input of the user and effectively providing a corresponding service.

[0005] In order to recognize an intention based on a voice input of a user, artificial intelligence (AI)

technology may be used, and rule-based natural language understanding (NLU) technology may also be used. When a voice input of a user is received through a hub device, because the hub device may not directly select a device for providing a service according to the voice input and has to control the device by using a separate voice assistant service-providing server, the user has to pay network usage fees, and because the voice assistant service-providing server is used, a response speed is reduced. In order to solve the above problems, the hub device may adopt an on-device model method by which a voice assistant model for controlling the device for providing the service based on the voice input is stored in an internal memory. However, when the on-device model method is used, the voice assistant model may not be stored due to a capacity of the internal memory of the hub device, a random-access memory (RAM) residual capacity, a processing speed, or the like.

SUMMARY

[0006] Provided is a multi-device system including the hub device and a plurality of devices, and an operating method of the hub device and the multi-device system, and more particularly, to a hub device that receives a voice input of a user and stores, in an internal memory of the hub device, at least some of a voice assistant model that automatically determines a device for performing an operation according to the user's intention based on the received voice input and a voice assistant model that provides pieces of information required to perform a service according to the determined device, a multi-device system, and an operating method of the hub device and the multi-device system.

[0007] According to an aspect of the disclosure, a method, performed by a hub device, of storing a voice assistant model for controlling a device includes receiving information about a first device connected to the hub device, and after receiving the information about the first device, requesting a voice assistant server to update a device determination model stored in the hub device; receiving the updated device determination model from the voice assistant server and storing the received updated device determination model; requesting, from the voice assistant server, information about a function determination model corresponding to the first device; receiving the information about the function determination model corresponding to the first device from the voice assistant server, and determining whether to store the function determination model in the hub device based on the received information; and based on the function determination model being determined to be stored in the hub device, storing, in the hub device, the function determination model corresponding to the first device.

[0008] The method may further include, based on the function determination model being determined not to be stored in the hub device, receiving access information of the function determination model corresponding to the first device.

[0009] The access information may include at least one of identification information of the voice assistant server in which the function determination model corresponding to the first device is stored, position information, Internet protocol address information, a media access control address, application programming interface information accessible to the function determination model in the voice assistant server, a use language of the function determination model, or identification information of the first device.

[0010] The determining whether to store the function determination model in the hub device may include determining whether to store the function determination model based on a resource state of the hub device and the information about the function determination model corresponding to the first device.

[0011] The hub device may be selected by the voice assistant server based on resource state information about each of a plurality of devices pre-registered according to a user account.

[0012] The method may further include selecting at least one hub device candidate from among a plurality of devices pre-registered in an Internet of things (IoT) server according to a user account logged into the hub device; selecting one device from among the least one hub device candidate

based on use history information and performance information of each of the at least one hub device candidate; and changing the hub device by replacing the hub device with the selected one device from among the at least one hub device candidate.

[0013] The selecting of the at least one hub device candidate may include selecting the at least one hub device candidate from among the plurality of devices pre-registered in the IoT server based on at least one of consistency of power supply, computing power, or a power consumption amount of each of the plurality of devices pre-registered in the IoT server.

[0014] The selecting of the one device from among the at least one hub device candidate may include obtaining information about a frequency of use of each of the hub device and the at least one hub device candidate, by analyzing a use history log database stored in the hub device; obtaining information about an utterance processing time of each of the hub device and the at least one hub device candidate, by analyzing a performance history log database stored in the hub device; and selecting a device for replacing the hub device, based on the information about the frequency of use and the information about the utterance processing time of each of the hub device and the at least one hub device candidate.

[0015] The selecting of the at least one hub device candidate from among the plurality of devices pre-registered in an IoT server may be performed after the receiving of the information about the first device connected to the hub device.

[0016] The method may further include receiving a user input that selects one of the plurality of devices pre-registered in the IoT server according to the user account logged into the hub device; and selecting the one device of the plurality of devices pre-registered in the IoT server based on the user input as the hub device.

[0017] According to another aspect of the disclosure, a hub device for storing a voice assistant model for controlling a device may include a communication interface configured to perform data communication with at least one of a plurality of devices, a voice assistant server, or an Internet of things (IoT) server; a memory configured to store a program comprising one or more instructions; and a processor configured to execute the one or more instructions of the program stored in the memory to: receive information about a first device connected to the hub device, upon receiving the information about the first device, request the voice assistant server to update a device determination model stored in the memory, and control the communication interface to receive the updated device determination model from the voice assistant server; store the received updated device determination model in the memory; request, from the voice assistant server, information about a function determination model corresponding to the first device, and control the communication interface to receive the information about the function determination model corresponding to the first device from the voice assistant server; determine whether to store the function determination model in the hub device based on the received information; and based on the function determination model being determined to be stored in the hub device, store the function determination model corresponding to the first device in the memory.

[0018] The processor may be further configured to execute the one or more instructions to, based on the function determination model being determined not to be stored in the hub device, control the communication interface to receive access information of the function determination model corresponding to the first device.

[0019] The access information may include at least one of identification information of the voice assistant server in which the function determination model corresponding to the first device is stored, position information, Internet protocol address information, a media access control address, application programming interface information accessible to the function determination model in the voice assistant server, a use language of the function determination model, or identification information of the first device.

[0020] The processor may be further configured to execute the one or more instructions to determine whether to store the function determination model in the memory, based on a resource

state of the hub device and the information about the function determination model corresponding to the first device.

[0021] The hub device may be selected by the voice assistant server, based on resource state information about each of a plurality of devices pre-registered according to a user account.

[0022] The processor may be further configured to execute the one or more instructions to select at least one hub device candidate from among a plurality of devices pre-registered in the IoT server according to a user account logged into the hub device, select one device from among the at least one hub device candidate based on use history information and performance information of each of the at least one hub device candidate, and change the hub device by replacing the hub device with the selected on device from among the at least one hub device candidate.

[0023] The processor may be further configured to execute the one or more instructions to select the at least one hub device candidate from among the plurality of devices pre-registered in the IoT server based on at least one of consistency of power supply, computing power, or a power consumption amount of each of the plurality of devices pre-registered in the IoT server.

[0024] The device may further include a use history log database storing information about a frequency of use of each of the hub device and the at least one hub device candidate; and a performance history log database storing information about an utterance processing time of each of the hub device and the at least one hub device candidate.

[0025] The processor may be further configured to execute the one or more instructions to: obtain the information about the frequency of use of each of the hub device and the at least one hub device candidate by analyzing the use history log database; obtain the information about the utterance processing time of each of the hub device and the at least one hub device candidate by analyzing the performance history log database; and select a device for replacing the hub device, based on the information about the frequency of use and the information about the utterance processing time of each of the hub device and the at least one hub device candidate.

[0026] The device may further include a voice inputter configured to receive a voice input of a user that selects one of the plurality of devices pre-registered in the IoT server according to the user account logged into the hub device. The processor may be further configured to execute the one or more instructions to convert the voice input of the user received from the voice inputter into text by performing automatic speech recognition (ASR), and select the one device of the plurality of devices pre-registered in the IoT server according to the voice input of the user as the hub device by interpreting the text by using a natural language understanding (NLU) model.

[0027] According to another aspect of the disclosure, a method, performed by a voice assistant server and a hub device, of storing a voice assistant model for controlling a device may include, after receiving information about a first device, requesting, by the hub device, the voice assistant server to update a device determination model stored in the hub device; based on receiving a request to update the device determination model, updating, by the voice assistant server, the device determination model of the hub device; receiving, by the hub device, the updated device determination model from the voice assistant server and storing the received updated device determination model; requesting, by the hub device, information about a function determination model corresponding to the first device from the voice assistant server; obtaining, by the voice assistant server, the information about the function determination model corresponding to the first device; transmitting, by the voice assistant server, the information about the function determination model to the hub device; receiving, by the hub device, the information about the function determination model corresponding to the first device from the voice assistant server; and determining, by the hub device, whether to store the function determination model in the hub device based on the received information.

[0028] The method may further include, based on the function determination model being determined to be stored in the hub device, storing, by the hub device, the function determination model corresponding to the first device.

[0029] The method may further include, based on the function determination model being determined not to be stored in the hub device, requesting, by the hub device, access information of the function determination model corresponding to the first device from the voice assistant server.

[0030] The access information may include at least one of identification information of the voice assistant server in which the function determination model corresponding to the first device is stored, position information, Internet protocol address information, a media access control address, application programming interface information accessible to the function determination model in the voice assistant server, a use language of the function determination model, or identification information of the first device.

[0031] The hub device may be selected by the voice assistant server, based on resource state information about each of a plurality of devices pre-registered according to a user account.

[0032] According to another aspect of the disclosure, a system may include a hub device and a voice assistant server. The hub device may include a communication interface configured to perform data communication with the voice assistant server; a memory configured to store a program comprising one or more instructions; and a processor configured to execute the one or more instructions of the program stored in the memory to: control the communication interface to receive information about a first device and request the voice assistant server to update a device determination model pre-stored in the memory; receive the updated device determination model from the voice assistant server, and store the received updated device determination model in the memory; request, from the voice assistant server, information about a function determination model corresponding to the first device, and control the communication interface to receive the information about the function determination model corresponding to the first device from the voice assistant server; and determine whether to store the function determination model in the hub device based on the received information. The voice assistant server may be configured to, based on a request to update the device determination model being received from the hub device, update the device determination model pre-stored in the hub device, obtain the information about the function determination model corresponding to the first device, and transmit the obtained information to the hub device.

[0033] The processor may be further configured to execute the one or more instructions to, based on the function determination model being determined to be stored in the hub device, store the function determination model corresponding to the first device in the memory.

[0034] The processor may be further configured to execute the one or more instructions to, based on the function determination model being determined not to be stored in the hub device, request, from the voice assistant server, access information of the function determination model corresponding to the first device, and control the communication interface to receive the access information from the voice assistant server.

[0035] The access information may include at least one of identification information of the voice assistant server in which the function determination model corresponding to the first device is stored, position information, Internet protocol address information, a media access control address, application programming interface information accessible to the function determination model in the voice assistant server, a use language of the function determination model, or identification information of the first device.

[0036] The hub device may be selected by the voice assistant server, based on resource state information about each of a plurality of devices pre-registered according to a user account.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0037] The above and other aspects and features of certain embodiments of the present disclosure

will be more apparent from the following description taken in conjunction with the accompanying drawings, in which like reference numerals denote like structural elements, and in which:

[0038] FIG. 1 is a block diagram of a multi-device system including a hub device, a voice assistant server, an Internet of things (IoT) server, and a plurality of devices, according to an embodiment;

[0039] FIG. 2 is a block diagram of a hub device according to an embodiment;

[0040] FIG. 3 is a block diagram of a voice assistant server according to an embodiment;

[0041] FIG. 4 is a block diagram of an IoT server according to an embodiment;

[0042] FIG. 5 is a block diagram of a plurality of devices according to an embodiment;

[0043] FIG. 6 is a flowchart of a method, performed by a hub device, of receiving and storing at least some of voice assistant models from a voice assistant server, according to an embodiment;

[0044] FIG. 7 is a flowchart of a method, performed by a hub device, of determining whether to store a function determination model based on information of the function determination model received from the voice assistant server, according to an embodiment;

[0045] FIG. 8 is a flowchart of a method, performed by a hub device, of controlling an operation of a new device based on a voice input of a user, according to an embodiment;

[0046] FIG. 9 is a flowchart of an operating method of a hub device, a voice assistant server, an IoT server, and a new device, according to an embodiment;

[0047] FIG. 10 is a flowchart of an operating method of a hub device and a new device, according to an embodiment;

[0048] FIG. 11 is a flowchart of an operating method of a hub device, a voice assistant server, an IoT server, and a new device, according to an embodiment;

[0049] FIG. 12A is a conceptual diagram of a hub device and a listener device, according to an embodiment;

[0050] FIG. 12B is a conceptual diagram of a hub device and a second device, according to an embodiment;

[0051] FIG. 13 is a block diagram of a hub device according to an embodiment;

[0052] FIG. 14 is a flowchart of an operating method of a hub device according to an embodiment;

[0053] FIG. 15 is a flowchart of an operating method of a hub device according to an embodiment;

[0054] FIG. 16 is a flowchart of an operating method of a hub device according to an embodiment;

[0055] FIG. 17 is a diagram of a multi-device system environment including a hub device, a voice assistant server, and a plurality of devices according to an embodiment;

[0056] FIG. 18A is a diagram of a voice assistant model executable by the hub device and the voice assistant server, according to an embodiment; and

[0057] FIG. 18B is a diagram of a voice assistant model executable by the hub device and the voice assistant server, according to an embodiment.

DETAILED DESCRIPTION

[0058] Although the terms used herein are selected from among common terms that are currently widely used in consideration of their functions in the disclosure, the terms may vary according the intention of one of ordinary skill in the art, a precedent, or the advent of new technology. Also, in particular cases, the terms are discretionally selected by the applicant of the disclosure, and the meaning of those terms will be described in detail in the corresponding part of the detailed description. Therefore, the terms used herein are not merely designations of the terms, but the terms are defined based on the meaning of the terms and content throughout the disclosure.

[0059] As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms including technical and scientific terms used herein may have the same meaning as commonly understood by one of ordinary skill in the art to which the disclosure belongs.

[0060] Throughout the disclosure, the expression “at least one of a, b or c” indicates only a, only b, only c, both a and b, both a and c, both b and c, all of a, b, and c, or variations thereof.

[0061] Throughout the present application, when a part “includes” an element, it is to be

understood that the part additionally includes other elements rather than excluding other elements as long as there is no particular opposing recitation. Also, the terms such as “. . . unit,” “. . . module,” or the like used herein indicate a unit, which processes at least one function or operation, and the unit may be implemented as hardware or software, or a combination of hardware and software.

[0062] The expression “configured to (or set to)” used herein may be replaced with, for example, “suitable for,” “having the capacity to,” “designed to,” “adapted to,” “made to,” or “capable of” according to cases. The expression “configured to (or set to)” may not necessarily mean “specifically designed to” in hardware. Instead, in some cases, the expression “system configured to . . .” may mean that the system is “capable of . . .” along with other devices or parts. For example, “a processor configured to (or set to) perform A, B, and C” may refer to a dedicated processor (e.g., an embedded processor) for performing a corresponding operation, or a general-purpose processor (e.g., a central processing unit (CPU) or an application processor (AP)) capable of performing a corresponding operation by executing one or more software programs stored in a memory.

[0063] A ‘first natural language understanding (NLU) model’ used herein is a model trained to analyze text converted from a voice input and determine an operation-performing device based on an analysis result. The first NLU model may be used to determine an intent by interpreting the text and determine the operation-performing device based on the intent.

[0064] A ‘second NLU model’ used herein is a model trained to analyze text related to a specific device. The second NLU model may be a model trained to obtain operation information about an operation to be performed by the specific device by interpreting at least part of the text. A storage capacity of the second NLU model may be greater than a storage capacity of the first NLU model.

[0065] A ‘voice assistant model’ used herein may include a device determination model and a function determination model. A ‘device determination model’ is a model trained to determine an operation-performing device from among a plurality of devices pre-registered according to a user account, based on a text analysis result of a first NLU model. The device determination model may include the first NLU model. A ‘function determination model’ is a model used to obtain operation information about detailed operations for performing an operation according to a determined function of a device and a relationship between the detailed operations. The function determination model may include a second NLU model and an action plan management model.

[0066] An ‘action plan management model’ used herein may be a model trained to manage operation information related to a detailed operation of a device in order to generate detailed operations to be performed by an operation-performing device and an execution order of the detailed operations. The action plan management model may manage operation information about detailed operations of devices according to device types and a relationship between the detailed operations.

[0067] An ‘intent’ used herein is information indicating a user's intention determined by interpreting text. The intent that is information indicating the user's utterance intention may be information indicating an operation of an operation-performing device requested by the user. The intent may be determined by interpreting the text by using an NLU model. For example, when the text converted from a voice input of the user is “play the movie Avengers on TV”, the intent may be “content playback”. Alternatively, when the text converted from a voice input of the user is “lower the air conditioner temperature to 18° C.”, the intent may be “temperature control”.

[0068] The intent may include not only the information indicating the user's utterance intention (hereinafter, referred to as intention information) but also a numerical value corresponding to the information indicating the user's intention. The numerical value may indicate a probability that the text is related to information indicating a specific intention. After the text is interpreted by using the NLU model, when a plurality of pieces of intention information indicating the user's intention are obtained, intention information having a largest numerical value from among a plurality of

numerical values corresponding to the plurality of pieces of intention information may be determined as the intent.

[0069] The term ‘operation’ of a device used herein may refer to at least one action performed by the device when the device executes a specific function. The operation may indicate at least one action performed by the device when the device executes an application. For example, the operation may indicate, for example, video playback, music playback, email creation, weather information reception, news information display, game play, and photography performed when the device executes the application. However, the operation is not limited to the above examples.

[0070] The operation of the device may be performed based on information about a detailed operation output from an action plan management model. The device may perform at least one action by executing a function corresponding to the detailed operation output from the action plan management model. The device may store instructions for executing the function corresponding to the detailed operation, and when the detailed operation is determined, the device may determine instructions corresponding to the detailed operation and may execute a specific function by executing the instructions.

[0071] Also, the device may store instructions for executing an application corresponding to the detailed operation. The instructions for executing the application may include instructions for executing the application itself and instructions for executing a detailed function constituting the application. When the detailed operations is determined, the device may execute the application by executing the instructions for executing the application corresponding to the detailed operation, and may execute the detailed function by executing the instructions for executing the detailed function of the application corresponding to the detailed operation.

[0072] ‘Operation information’ used herein may be information related to detailed operations to be determined by a device, a relationship between each of the detailed operations and another detailed operation, and an execution order of the detailed operations. The relationship between each of the detailed operations and another detailed operation includes, when a first operation is to be executed, information about a second operation that has to be executed before the first operation is executed. For example, when an operation to be performed is “music playback”, “power on” may be another detailed operation that has to be executed before “music playback” is performed. The operation information may include, but is not limited to, functions to be executed by an operation-performing device to perform a specific operation, an execution order of the functions, an input value required to execute the functions, and an output value output as an execution result of the functions.

[0073] The term ‘operation-performing device’ used herein refers to a device determined to perform an operation based on an intent obtained from text from among a plurality of devices. The text may be analyzed by using a first NLU model, and the operation-performing device may be determined based on an analysis result. The operation-performing device may perform at least one action by executing a function corresponding to a detailed operation output from an action plan management model. The operation-performing device may perform an operation based on operation information.

[0074] An ‘Internet of things (IoT) server’ used herein is a server that obtains, stores, and manages device information about each of a plurality of devices. The IoT server may obtain, determine, or generate a control command for controlling the device by using the stored device information. The IoT server may transmit the control command to the device determined to perform an operation based on operation information. The IoT server may be implemented as, but not limited to, a hardware device independent of a ‘server’ of the disclosure. The IoT server may be an element of a ‘voice assistant server’ of the disclosure, or may be a server designed to be classified as software.

[0075] Hereinafter, embodiments of the disclosure will be described in detail with reference to the attached drawings in order to enable one of ordinary skill in the art to easily embody and practice the disclosure. The disclosure may, however, be embodied in many different forms and should not

be construed as being limited to the embodiments of the disclosure set forth herein.

[0076] Reference will now be made in detail to embodiments of the disclosure, examples of which are illustrated in the accompanying drawings.

[0077] FIG. 1 is a block diagram of a multi-device system including a hub device **1000**, a voice assistant server **2000**, an IoT server **3000**, and a plurality of devices **4000** according to an embodiment.

[0078] In FIG. 1, for convenience of explanation, only essential elements for describing operations of the hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and the plurality of devices **4000** are illustrated. Elements included in the hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and the plurality of devices **4000** are not limited to those illustrated in FIG. 1.

[0079] Reference numerals S1 through S16 marked by arrows in FIG. 1 denote data movement, transmission, and reception between a plurality of entities through a network. Numbers attached to the English letter S in S1 through S16 are for identification and are not related to an order of data movement, transmission, and reception.

[0080] Referring to FIG. 1, the hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and the plurality of devices **4000** may be connected to one another by using a wired or wireless communication method and may perform communication. In an embodiment, the hub device **1000** and the plurality of devices **4000** may be directly connected to each other through a communication network, but the disclosure is not limited thereto. The hub device **1000** and the plurality of devices **4000** may be connected to the voice assistant server **2000**, and the hub device **1000** may be connected to the plurality of devices **4000** through the voice assistant server **2000**. Also, the hub device **1000** and the plurality of devices **4000** may be connected to the IoT server **3000**. In another embodiment, each of the hub device **1000** and the plurality of devices **4000** may be connected to the voice assistant server **2000** through a communication network, and may be connected to the IoT server **3000** through the voice assistant server **2000**.

[0081] The hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and the plurality of devices **4000** may be connected through a local area network (LAN), a wide area network (WAN), a value-added network (VAN), a mobile radio communication network, a satellite communication network, or a combination thereof. Examples of the wireless communication method may include, but are not limited to, Wi-Fi, Bluetooth, Bluetooth low energy (BLE), Zigbee, Wi-Fi Direct (WFD), Ultra-wideband (UWB), Infrared Data Association (IrDA), and Near-Field Communication (NFC).

[0082] The hub device **1000** is a device that receives a voice input of a user and controls at least one of the plurality of devices **4000** based on the received voice input. The hub device **1000** may be a listener device that receives the voice input from the user. For example, the hub device **1000** may be, but is not limited to, a voice assistant speaker.

[0083] The hub device **1000** may be selected by the voice assistant server **2000**, based on resource state information about each of a plurality of devices pre-registered in the IoT server **3000** according to a user account.

[0084] At least one of the plurality of devices **4000** may be an operation-performing device that performs a specific operation by receiving a control command of the hub device **1000** or the IoT server **3000**. The plurality of devices **4000** may be devices that are logged in by using the same user account as a user account of the hub device **1000** and are pre-registered in the IoT server **3000** by using the user account of the hub device **1000**. However, the disclosure is not limited thereto, and the plurality of devices **4000** may include a new device **4300** newly registered in the IoT server **3000** according to the user account. The new device **4300** may be a device that is newly obtained by the user of the hub device **1000**, and is registered in the IoT server **3000** by being logged in by using the same user account as that of the hub device **1000** and other devices (e.g., a first device **4100** and a second device **4200**).

[0085] At least one of the plurality of devices **4000** may receive the control command from the IoT server **3000** (**S12**, **S14**, and **S16**), or may receive at least part of text converted from the voice input from the hub device **1000** (**S3** and **S5**). At least one of the plurality of devices **4000** may receive the control command from the IoT server **3000** (**S12**, **S14**, and **S16**) without receiving the at least part of the text from the hub device **1000**.

[0086] The hub device **1000** may include a device determination model **1340** that determines a device for performing an operation based on the voice input of the user. The device determination model **1340** may determine an operation-performing device from among the plurality of devices **4000** that are registered according to the user account. In an embodiment, the hub device **1000** may receive, from the voice assistant server **2000**, device information including at least one of identification information of each of the plurality of devices **4000** (e.g., device id information), a device type of each of the plurality of devices **4000**, a function execution capability of each of the plurality of devices **4000**, position information, or state information (**S2**). The hub device **1000** may determine the device for performing the operation according to the voice input of the user from among the plurality of devices **4000** based on the received device information, by using data about the device determination model **1340**.

[0087] In another embodiment, the hub device **1000** may directly receive, from a plurality of devices, device information including at least one of identification information of each of the plurality of devices **4000** (e.g., device id information), a device type of each of the plurality of devices **4000**, a function execution capability of each of the plurality of devices **4000**, position information, or state information. The hub device **1000** may identify a plurality of devices connected to an access point connected to the hub device **1000**, and may obtain the device information by requesting the identified plurality of devices for the device information. In this case, the plurality of devices may include a SW module configured to transmit the device information according to a request of the hub device **1000**. Also, the hub device **1000** may obtain the device information by receiving the device information transmitted by the plurality of devices. In this case, the plurality of devices may include a SW module configured to identify the hub device **1000** connected to the access point connected to the plurality of devices and a SW module configured to transmit the device information to the identified hub device **1000**.

[0088] When the hub device **1000** obtains information about a new device (first device) connected to the hub device **1000**, the hub device **1000** may request the voice assistant server **2000** to update a device determination model stored in the hub device **1000**. In an embodiment, the hub device **1000** may analyze text related to the new device from a voice input of the user based on device information of the new device received from the IoT server **3000**, and may transmit a query signal for requesting to update the device determination model stored in a memory **1300** (see FIG. 2) to the voice assistant server **2000** to determine the new device as an operation-performing device. In this case, the hub device **1000** may transmit at least user account information and identification information of the hub device **1000** (e.g., id information of the hub device **1000**) along with the query signal to the voice assistant server **2000**.

[0089] The hub device **1000** receives the updated device determination model from the voice assistant server **2000** in response to the request of the hub device **1000**, and stores the received updated device determination model. In an embodiment, the hub device **1000** may analyze the voice input of the user about the new device, may download the updated device determination model from the voice assistant server **2000** to determine the new device as an operation-performing device as an analysis result, and may store the updated device determination model in the memory **1300** (see FIG. 2) inside the hub device **1000**.

[0090] Also, a function determination model corresponding to the operation-performing device determined by the hub device **1000** may be stored in the memory **1300** (see FIG. 2) of the hub device **1000**, may be stored in the operation-performing device itself, or may be stored in a memory **2300** (see FIG. 3) of the voice assistant server **2000**. The memory **1300** of the hub device **1000** is a

nonvolatile memory. The nonvolatile memory refers to a memory medium that may store and retain information even when power is not supplied and may use stored information when power is supplied, and may include at least one of, for example, a flash memory, a hard disk, a solid state drive (SSD), a multimedia card micro type, a card-type memory (e.g., an SD or XD memory), a read-only memory (ROM), a magnetic memory, a magnetic disk, or an optical disk. The term 'function determination model' corresponding to each device refers to a model used to obtain operation information about detailed operations for performing an operation according to a determined function of the device and a relationship between the detailed operations.

[0091] The hub device **1000** may monitor resource states of the hub device **1000** and the plurality of devices **4000** and may obtain resource state information, by using a resource tracking module **1350**. The resource state information includes information related to usage states of processors **1200**, **4120**, **4220**, and **4320** and memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**. The resource state information may include at least one of, for example, residual capacity, average RAM usage capacity, or average processor occupancy information of the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**. The resource tracking module **1350** may provide the obtained resource state information to a function determination model management module **1360**.

[0092] The hub device **1000** may determine whether to store and process a function determination model **1370** in the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**, by using the function determination model management module **1360**. When there are a plurality of function determination models **1370**, the hub device **1000** may determine whether to store and process each of the plurality of function determination models **1370** in the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**. The function determination model management module **1360** may compare information (e.g., capacity information) of a function determination model received from the voice assistant server **2000** with the resource state information received from the resource tracking module **1350** and may analyze the compared information. The function determination model management module **1360** may determine whether to download the function determination model from the voice assistant server **2000** and store the function determination model in the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**, by using a comparison/analysis result.

[0093] In an embodiment, based on the function determination model management module **1360** determines to download the function determination model from the voice assistant server **2000** and store the function determination model in the memory **1300**, the hub device **1000** may transmit a query for requesting the voice assistant server **2000** to transmit the function determination model, may receive the function determination model from the voice assistant server **2000**, and may store the function determination model in the memory **1300**.

[0094] In another embodiment, based on the function determination model management module **1360** determining to download the function determination model from the voice assistant server **2000** and store the function determination model in the memory **4130**, **4230**, or **4330** of at least one of the plurality of devices **4000** other than the hub device **1000**, the hub device **1000** may transmit a query for requesting the voice assistant server **2000** to transmit the function determination model, may receive the function determination model from the voice assistant server **2000**, and may transmit the function determination model to at least one of the plurality of devices **4000**. The voice assistant server **2000** may transmit the function determination model to at least one of the plurality of devices **4000** other than the hub device **1000**.

[0095] In another embodiment, based on the function determination model management module **1360** determining not to download the function determination model from the voice assistant server **2000**, the hub device **1000** may receive access information of the function determination model pre-stored in the voice assistant server **2000** and may store the received access information in a function determination model information database **1362**.

[0096] The function determination model information database **1362** may store capacity information and access information of a function determination model corresponding to a device that is newly registered or is registered by using the same user account as that of the hub device **1000** from among a plurality of function determination models **2362**, **2364**, **2366**, and **2368** that are pre-stored in the voice assistant server **2000**. The access information may include at least one of identification information (e.g., server id) of the voice assistant server **2000** storing each function determination model, position information, Internet protocol (IP) address information, a media access control (MAC) address, application programming interface (API) information accessible to each function determination model in the voice assistant server **2000**, a use language of each function determination model, or identification information of a corresponding device.

[0097] In an embodiment, when a new device is registered by using the user account, the hub device **1000** receives information (e.g., capacity information) about a function determination model corresponding to the new device from the voice assistant server **2000**, by using the function determination model management module **1360**. The hub device **1000** may determine whether to download the function determination model from the voice assistant server **2000** and store the function determination model in the memory **1300** (see FIG. 2), based on the received information about the function determination model. Based on the function determination model being determined to be stored in the memory **1300**, the hub device **1000** may download the function determination model corresponding to the new device from the voice assistant server **2000** and may store the function determination model in the memory **1300**. Based on the function determination model being determined not to be stored, the hub device **1000** may store access information of the function determination model corresponding to the new device in the function determination model information database **1362**.

[0098] The hub device **1000** may determine a function of the hub device **1000** itself, and may store a first function determination model **1372** for performing an operation according to the determined function and a second function determination model **1374** corresponding to at least one of the plurality of devices **4000**. For example, when the hub device **1000** is a voice assistant speaker, the hub device **1000** may store the first function determination model **1372** (e.g., speaker function determination model) used to obtain operation information about detailed operations for performing a function of the hub device **1000** and a relationship between the detailed operations. Alternatively, the hub device **1000** may store the second function determination model **1374** (e.g., TV function determination model) used to obtain operation information about detailed operations corresponding to a TV and a relationship between the detailed operations. The TV may be a device pre-registered in the IoT server **3000** by using the same user account as the user account of the hub device **1000**.

[0099] The first function determination model **1372** (e.g., speaker function determination model) and the second function determination model **1374** (e.g., TV function determination model) may respectively include second NLU models **1372a** and **1374a** and action plan management models **1372b** and **1374b**. The second NLU models **1372a** and **1374a** and the action plan management models **1372b** and **1374b** will be described in detail with reference to FIG. 2.

[0100] The voice assistant server **2000** may determine an operation-performing device for performing an operation intended by the user, based on text received from the hub device **1000**. The voice assistant server **2000** may receive user account information from the hub device **1000** (S1). When the voice assistant server **2000** receives the user account information from the hub device **1000**, the voice assistant server **2000** may transmit, to the IoT server **3000**, a query for requesting device information about the plurality of devices **4000** that are pre-registered according to the received user account information (S9), and may receive the device information about the plurality of devices **4000** from the IoT server **3000** (S10). The device information may include at least one of identification information (e.g., device id information) of each of the plurality of devices **4000**, a device type of each of the plurality of devices **4000**, a function execution capability

of each of the plurality of devices **4000**, position information, or state information. The voice assistant server **2000** may transmit the device information received from the IoT server **3000** to the hub device **1000** (S2).

[0101] The voice assistant server **2000** may include a device determination model **2330**, a voice assistant model update module **2340**, an on-device model update module **2350**, and the plurality of function determination models **2362**, **2364**, **2366**, and **2368**. The voice assistant server **2000** may select a function determination model corresponding to at least part of the text received from the hub device **1000** from among the plurality of function determination models **2362**, **2364**, **2366**, and **2368** by using the device determination model **2330**, and may obtain operation information for performing an operation of the operation-performing device by using the selected function determination model. The voice assistant server **2000** may transmit the operation information to the IoT server **3000** (S9).

[0102] The voice assistant server **2000** may update a voice assistant model, by using the voice assistant model update module **2340**. When a new device is newly registered by using a user account in the IoT server **3000** or a new function is added to an existing device, the voice assistant server **2000** may update the device determination model **2330** and the function determination model **2368** by using the voice assistant model update module **2340**. For example, when the function determination model **2364** corresponding to the second device **4200** is updated, for example, when a function of the second device **4200** is added or changed, the voice assistant model update module **2340** may update the device determination model **2330** to a new model through learning or the like so that the device determination model **2330** determines the second device **4200** as an operation-performing device related to the updated function by interpreting the updated function. In an embodiment, the voice assistant model update module **2340** may update a first NLU model **2332** to a new model through learning or the like so that the first NLU model **2332** of the device determination model **2330** interprets text related to the newly updated function.

[0103] For example, when the new device **4300** is registered by using a user account in the IoT server **3000**, the voice assistant model update module **2340** may receive identification information of the new device **4300** and the function determination model **2368** corresponding to the new device **4300** from the IoT server **3000**, and may additionally store the received function determination model **2368** in the function determination models **2362**, **2364**, and **2366** in the memory **2300** (see FIG. 3). The voice assistant model update module **2340** may update the device determination model **2330** to a new model through learning or the like so that the device determination model **2330** interprets an intent from text and determines the new device **4300** as an operation-performing device related to the intent as an interpretation result. In an embodiment, the voice assistant model update module **2340** may update the first NLU model **2332** to a new model through learning or the like so that the first NLU model **2332** of the device determination model **2330** interprets text related to the new device **4300**.

[0104] The voice assistant server **2000** may train voice assistant models according to user accounts by using the on-device model update module **2350**, and may determine whether to transmit at least some of voice assistant models updated through learning to the hub device **1000**. In another embodiment, the voice assistant server **2000** may determine to transmit at least some of the voice assistant models updated through learning to at least one of the plurality of devices **4000** other than the hub device **1000**. The on-device model update module **2350** may include an on-device model information database **2352** that stores configuration information of the voice assistant models according to user accounts. The on-device model information database **2352** may store at least one of, for example, user account information, identification information about a plurality of devices registered according to user accounts, identification information of a function determination model corresponding to each of the plurality of devices, version information of the function determination model, version information of a device determination model, or information about a device type that may be determined by the device determination model as an operation-performing device.

[0105] When the voice assistant server **2000** determines to transmit the updated device determination model **2330** to the hub device **1000** by using the on-device model update module **2350**, the voice assistant server **2000** may transmit the updated device determination model **2330** to the hub device **1000** through a communication interface **2100** (see FIG. 3) (S2). In an embodiment, when the voice assistant server **2000** receives a signal for requesting to transmit the function determination model **2368** corresponding to the new device from the hub device **1000** (S1), the voice assistant server **2000** may transmit the function determination model **2368** corresponding to the new device to the hub device **1000** by using the on-device model update module **2350** (S2). In another embodiment, the voice assistant server **2000** may transmit the function determination model **2368** corresponding to the new device to at least one of the plurality of devices **4000** by using the on-device model update module **2350**.

[0106] Each of the plurality of function determination models **2362**, **2364**, **2366**, and **2368** stored in the voice assistant server **2000** will be described in detail with reference to FIG. 3.

[0107] The IoT server **3000** may be connected through a network, and may store information about the plurality of devices **4000** that are pre-registered by using the user account of the hub device **1000**. In an embodiment, the IoT server **3000** may receive at least one of user account information used to log into each of the plurality of devices **4000**, identification information (e.g., device id information) of each of the plurality of devices **4000**, a device type of each of the plurality of devices **4000**, or function execution capability information of each of the plurality of devices **4000** (S11, S13, and S15). In an embodiment, the IoT server **3000** may receive state information about power on/off of each of the plurality of devices **4000** or an operation that is being executed from the plurality of devices **4000** (S11, S13, and S15). The IoT server **3000** may store the device information and the state information received from the plurality of devices **4000**.

[0108] The IoT server **3000** may transmit the device information and the state information received from each of the plurality of devices **4000** to the voice assistant server **2000** (S10).

[0109] The IoT server **3000** may generate a control command readable and executable by the operation-performing device based on the operation information received from the voice assistant server **2000**. The IoT server **3000** may transmit the control command to the device determined as the operation-performing device from among the plurality of devices **4000** (S12, S14, and S16).

[0110] Elements of the IoT server **3000** will be described in detail with reference to FIG. 4.

[0111] In FIG. 1, the plurality of devices **4000** may include the first device **4100**, the second device **4200**, and the new device **4300**. Although the first device **4100** is an air conditioner, the second device **4200** is a TV, and the new device **4300** is an air purifier in FIG. 1, the disclosure is not limited thereto. The plurality of devices **4000** may include not only an air conditioner, a TV, and an air purifier, but also a home appliance such as a robot cleaner, a washing machine, an oven, a microwave oven, a scale, a refrigerator, or an electronic picture frame and a mobile device such as a smartphone, a tablet personal computer (PC), a mobile phone, a video phone, an e-book reader, a desktop PC, a laptop PC, a netbook computer, a workstation, a server, a personal digital assistant (PDA), a portable multimedia player (PMP), an MP3 player, a mobile medical device, a camera, or a wearable device.

[0112] At least one of the plurality of devices **4000** itself may store a function determination model. For example, the memory **4130** of the first device **4100** may store a function determination model **4132** used to obtain operation information about detailed operations needed for the first device **4100** to perform an operation determined from a voice input of the user and a relationship between the detailed operations and generate a control command based on the operation information.

[0113] Each of the second device **4200** and the new device **4300** from among the plurality of devices **4000** does not store a function determination model. However, the disclosure is not limited thereto. In an embodiment, a function determination model corresponding to the new device **4300** may be stored in an internal memory of the new device **4300** itself.

[0114] At least one of the plurality of devices **4000** may transmit information about whether the

device itself stores a function determination device corresponding to each of the plurality of devices **4000** to the hub device **1000** (S4, S6, and S8).

[0115] FIG. 2 is a block diagram of the hub device **1000** according to an embodiment.

[0116] The hub device **1000** is a device that receives a voice input of a user and controls at least one of the plurality of devices **4000** based on the received voice input. The hub device **1000** may be a listener device that receives the voice input from the user.

[0117] Referring to FIG. 2, the hub device **1000** may include at least a microphone **1100**, the processor **1200**, the memory **1300**, and a communication interface **1400**. The hub device **1000** may receive the voice input (e.g., the user's utterance) from the user through the microphone **1100**, and may obtain a voice signal from the received voice input. In an embodiment, the processor **1200** of the hub device **1000** may convert a sound received through the microphone **1100** into an acoustic signal, and may obtain the voice signal by removing noise (e.g., a non-voice component) from the acoustic signal.

[0118] Although not shown in FIG. 2, the hub device **1000** may include a voice recognition module having a function of detecting a designated voice input (e.g., a wake-up input such as 'Hi, Bixby' or 'OK, Google') or a function of pre-processing the voice signal obtained from part of the voice input.

[0119] The processor **1200** may execute one or more instructions of a program stored in the memory **1300**. The processor **1200** may include hardware components that perform arithmetic, logic, and input/output operations and signal processing. The processor **1200** may include at least one of, but not limited to, a central processing unit, a microprocessor, a graphics processing unit, an application-specific integrated circuit (ASIC), a digital signal processor (DSP), a digital signal processing device (DSPD), a programmable logic device (PLD), or a field programmable gate array (FPGA).

[0120] A program including instructions for controlling the plurality of devices **4000** based on the voice input of the user received through the microphone **1100** may be stored in the memory **1300**. Instructions and program code readable by the processor **1200** may be stored in the memory **1300**. In the following embodiments, the processor **1200** may be implemented by executing the instructions or the code stored in the memory.

[0121] The memory **1300** may store data about an automatic speech recognition (ASR) module **1310**, data about a natural language generation (NLG) module **1320**, data about a text-to-speech (TTS) module **1330**, data about the device determination model **1340**, data about the resource tracking module **1350**, data about the function determination model management module **1360**, and data corresponding to each of a plurality of function determination models **1370**.

[0122] The memory **1300** may include a nonvolatile memory. The memory **1300** may include at least one type of storage medium from among, for example, a flash memory type, a hard disk type, a solid state drive (SSD), a multimedia card micro type, a card-type memory (e.g., an SD or XD memory), a random-access memory (RAM), a static random-access memory (SRAM), a read-only memory (ROM), an electrically erasable programmable read-only memory (EEPROM), a programmable read-only memory (PROM), a magnetic memory, a magnetic disk, and an optical disk.

[0123] The processor **1200** may convert the voice signal received through the microphone **1100** into text by performing automatic speech recognition (ASR) by using the data about the ASR module **1310** stored in the memory **1300**.

[0124] The processor **1200** may analyze the text by using the data about the device determination model **1340** stored in the memory **1300** and may determine an operation-performing device from among the plurality of devices **4000** based on an analysis result of the text. The device determination model **1340** may include a first NLU model **1342**. In an embodiment, the processor **1200** may analyze the text by using data about the first NLU model **1342** included in the device determination model **1340**, and may determine the operation-performing device for performing an

operation according to the user's intention from among the plurality of devices **4000** based on an analysis result of the text.

[0125] The first NLU model **1342** is a model trained to analyze the text converted from the voice input and determine the operation-performing device based on an analysis result. The first NLU model **1342** may be used to determine an intent by interpreting the text and determine the operation-performing device based on the intent.

[0126] In an embodiment, the processor **1200** may parse the text in units of morphemes, words, or phrases by using the data about the first NLU model **1342** stored in the memory **1300**, and may infer the meaning of a word extracted from the parsed text by using linguistic features (e.g., grammatical constituents) of the morphemes, words, or phrases. The processor **1200** may compare the inferred meaning of the word with pre-defined intents provided by the first NLU model **1342** and may determine an intent corresponding to the inferred meaning of the word.

[0127] The processor **1200** may determine a device related to the intent recognized from the text as the operation-performing device, based on a matching model for determining a relation between the intent and the device. In an embodiment, the matching model may be included in the data about the device determination model **1340** stored in the memory **1300** and may be obtained through learning through a rule-based system, but the disclosure is not limited thereto.

[0128] In an embodiment, the processor **1200** may obtain a plurality of numerical values indicating relation degrees between the intent and the plurality of devices **4000** by applying the matching model to the intent, and may determine a device having a largest numerical value from among the obtained plurality of numerical values as a final operation-performing device. For example, when the intent is related to each of the first device **4100** (see FIG. 1) and the second device **4200** (see FIG. 1), the processor **1200** may obtain a first numerical value indicating a relation degree between the intent and the first device **4100** and a second numerical value indicating a relation degree between the intent and the second device **4200**, and may determine the first device **4100** having a larger numerical value from among the first numerical value and the second numerical value as an operation-performing device.

[0129] For example, when the hub device **1000** receives a voice input of the user saying "lower the set temperature 2° C. because it is hot" from the user, the processor **1200** may perform ASR of converting the voice input into text by using data about the ASR module **1310** and may obtain an intent corresponding to 'set temperature adjustment' by analyzing the converted text by using the data related to the first NLU model **1342**. The processor **1200** may obtain a first numerical value indicating a relation degree between the intent of 'set temperature adjustment' and the first device **4100** that is an air conditioner, a second numerical value indicating a relation degree between the intent of 'set temperature adjustment' and the second device **4200** that is a TV, and a third numerical value indicating a relation degree between the intent of 'set temperature adjustment' and the new device **4300** (see FIG. 1) that is an air purifier, by applying the matching model. The processor **1200** may determine the first device **4100** as an operation-performing device related to 'set temperature adjustment' by using the first numerical value that is a largest value from among the obtained numerical values.

[0130] As another example, when the hub device **1000** receives a voice input of the user saying "play the movie Avengers" from the user, the processor **1200** may analyze text converted from the voice input and may obtain an intent corresponding to 'content playback'. The processor **1200** may determine the second device **4200** as an operation-performing device related to 'content playback', based on second numerical value information that is a largest value from among a first numerical value indicating a relation degree between the intent of 'content playback' and the first device **4100** that is an air conditioner, a second numerical value indicating a relation degree between the intent of 'content playback' and the second device **4200** that is a TV, and a third numerical value indicating a relation degree between the intent of 'content playback' and the new device **4300** that is an air purifier calculated by using the matching model.

[0131] However, the disclosure is not limited to the above examples, and the processor **1200** may arrange, in an ascending order, numerical values indicating relation degrees between an intent and a plurality of devices and may determine a pre-determined number of devices as operation-performing devices. In an embodiment, the processor **1200** may determine a device whose numerical value indicating a relation degree is equal to or greater than a certain threshold value as an operation-performing device related to an intent. In this case, a plurality of devices may be determined as operation-performing devices.

[0132] Although the processor **1200** may train the matching model between an intent and an operation-performing device by using, for example, a rule-based system, the disclosure is not limited thereto. An artificial intelligence (AI) model used by the processor **1200** may be, for example, a neural network-based system (e.g., a convolution neural network (CNN) or a recurrent neural network (RNN)), a support-vector machine (SVM), linear regression, logistic regression, Naïve Bayes, a random forest, a decision tree, or a k-nearest neighbor algorithm. Alternatively, the AI model may be a combination of the above examples or any of other AI models. AI models used by the processor **1200** may be stored in the device determination model **1340**.

[0133] The device determination model **1340** stored in the memory **1300** of the hub device **1000** may determine an operation-performing device from among the plurality of devices **4000** that are registered according to a user account of the hub device **1000**. The hub device **1000** may receive device information about each of the plurality of devices **4000** from the voice assistant server **2000**, by using the communication interface **1400**. The device information may include at least one of, for example, identification information (e.g., device id information) of each of the plurality of devices **4000**, a device type of each of the plurality of devices **4000**, a function execution capability of each of the plurality of devices **4000**, position information, or state information. The processor **1200** may determine a device for performing an operation according to an intent from among the plurality of devices **4000** based on the device information, by using the data about the device determination model **1340** stored in the memory **1300**.

[0134] In an embodiment, the processor **1200** may analyze numerical values indicating relation degrees between the intent and the plurality of devices **4000** that are pre-registered by using the same user account as the user account of the hub device **1000** by using the device determination model **1340**, and may determine a device having a largest value from among the numerical values indicating the relation degrees between the intent and the plurality of devices **4000** as an operation-performing device.

[0135] Because the device determination model **1340** is configured to determine an operation-performing device by using only the plurality of devices **4000** that are logged in and registered by using the same user account as that of the hub device **1000** as device candidates, there is a technical effect in that the amount of calculation performed by the processor **1200** in order to determine a relation degree with the intent may be reduced to be less than that of a processor **2200** (see FIG. 3) of the voice assistant server **2000**. Also, due to the reduction in the amount of calculation, a processing time required to determine the operation-performing device may be reduced, and thus a response speed may be improved.

[0136] In an embodiment, the processor **1200** may obtain a name of a device from text by using the first NLU model **1342**, and may determine an operation-performing device based on the name of the device by using the data about the device determination model **1340** stored in the memory **1300**. In an embodiment, the processor **1200** may extract a common name related to the device and a word or a phrase regarding an installation position of the device from the text by using the first NLU model **1342**, and may determine the operation-performing device based on the extracted common name and installation position of the device. For example, when text converted from a voice input is “play the movie Avengers on TV”, the processor **1200** may parse the text in units of words or phrases by using the first NLU model **1342**, and may recognize the name of the device corresponding to ‘TV’ by comparing a word or a phrase with pre-stored words or phrases. The

processor **1200** may determine the second device **4200**, which is logged in by using the same account as the user account of the hub device **1000** and is a TV from among the plurality of devices **4000** connected to the hub device **1000**, as an operation-performing device.

[0137] The natural language generation (NLG) module **1320** may be used to provide a response message during an interaction between the hub device **1000** and the user. For example, the processor **1200** may generate a response message such as “I will play the movie on TV” or “I will lower the set temperature of the air conditioner by 2° C.” by using the NLG module **1320**. The response message generated by the NLG module **1320** may be a message including text.

[0138] When there exist a plurality of operation-performing devices determined by the processor **1200** or there exist a plurality of devices having similar relation degrees with an intent, the NLG module **1320** may store data used to generate a query message for determining a specific operation-performing device. In an embodiment, the processor **1200** may generate a query message for selecting one operation-performing device from among a plurality of device candidates by using the data about the NLG module **1320**. The query message may be a message for requesting a response from the user regarding which one of the plurality of device candidates is to be determined as an operation-performing device.

[0139] The TTS module **1330** may convert a response message or a query message including text generated by the NLG module **1320** into an audio signal. In an embodiment, the processor **1200** may control a response message or a query message including text to be converted into an audio signal by using data about the TTS module **1330** and to be transmitted through a speaker. In an embodiment, the hub device **1000** may receive a notification message indicating an execution result of an operation from an operation-performing device. In this case, the notification information may include text, and the processor **1200** may convert the notification message including text into an audio signal by using the data about the TTS module **1330**. The processor **1200** may output the notification message converted into the audio signal through the speaker.

[0140] When the hub device **1000** obtains information about a new device connected to the hub device **1000**, the hub device **1000** requests the voice assistant server **2000** to update a device determination model stored in the hub device **1000**. In an embodiment, the hub device **1000** may analyze text related to the new device from the voice input of the user based on device information of the new device (e.g., identification information of the new device and type information of the new device) received from the IoT server **3000**, and may transmit a query signal for requesting to update a device determination model pre-stored in the memory **1300** (see FIG. 2) to the voice assistant server **2000** to determine the new device as an operation-performing device. In this case, the hub device **1000** may transmit at least user account information and identification information of the hub device **1000** (e.g., id information of the hub device **1000**) along with the query signal to the voice assistant server **2000**.

[0141] In another embodiment, the hub device **1000** may receive the device information of the new device (e.g., identification information of the new device and type information of the new device) from the new device. In this case, the hub device **1000** may transmit the query signal for requesting to update the device determination model pre-stored in the hub device **1000**, based on the device information of the new device received from the new device.

[0142] In response to a request of the hub device **1000**, the hub device **1000** receives the updated device determination model from the voice assistant server **2000** and stores the received updated device determination model. In an embodiment, the hub device **1000** may analyze the voice input of the user about the new device, may download the updated device determination model from the voice assistant server **2000** to determine the new device as an operation-performing device as an analysis result, and may store the updated device determination model in the memory **1300** (see FIG. 2) in the hub device **1000**. An operation of requesting to update a device determination model and receiving and storing the updated device determination model may be performed by a separate software module. Alternatively, this operation may be performed by the function determination

model management module **1360**.

[0143] The resource tracking module **1350** is a module that monitors resource states of elements, for example, the processors **1200**, **4120**, **4220**, and **4230** and the memories **1300**, **4130**, **4230**, and **4330**, of the hub device **1000** and the plurality of devices **4000** and obtains resource state information. The resource state information is information indicating usage states of the processors **1200**, **4120**, **4220**, and **4320** and the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**. The resource state information may include at least one of, for example, residual capacity, average RAM usage capacity, or average processor occupancy information of the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**. In an embodiment, the hub device **1000** may monitor periodically or in real time at least one of an average processing speed of the processors **1200**, **4120**, **4220**, and **4320**, a residual capacity of the memories **1300**, **4130**, **4230**, and **4330**, or an average RAM residual capacity, by using the resource tracking module **1350**. The resource tracking module **1350** may provide resource state information obtained through monitoring to the function determination model management module **1360**.

[0144] The function determination model management module **1360** may determine whether to store and process the function determination model **1370** in the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**. When a plurality of function determination models **1370** are provided, the function determination model management module **1360** may determine whether to respectively store and process the plurality of function determination models **1370** in the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices. The function determination model management module **1360** may determine which one of the memories **1300**, **4130**, **4230**, **4330** of the hub device **1000** and the plurality of devices **4000** is to be used to store the function determination model **1370**.

[0145] The function determination model management module **1360** may compare and analyze information of a function determination model (e.g., capacity information of the function determination model) received from the voice assistant server **2000** (see FIG. 1) with the resource state information received from the resource tracking module **1350**. The function determination model management module **1360** may download the function determination model from the voice assistant server **2000** and may determine whether to store the downloaded function determination model in the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**, by using a comparison/analysis result. In an embodiment, the function determination model management module **1360** may determine whether to store a function determination model corresponding to the new device **4300** (see FIG. 1) received from the voice assistant server **2000** in the memories **1300**, **4130**, **4230**, and **4330**. In an embodiment, the function determination model management module **1360** may analyze a residual capacity and an occupancy of the processors **1200**, **4120**, **4220**, and **4320** and the memories **1300**, **4130**, **4230**, and **4330** according to a usage pattern of the hub device **1000** and the plurality of devices **4000**, based on the resource state information obtained from the resource tracking module **1350**. For example, when the user frequently plays music or video content through the hub device **1000**, decoding continuously occurs, and thus an occupancy of the processor **1200** through calculation may be high and a RAM residual capacity may be low. In another embodiment, when the user performs only a simple operation such as an operation of asking about weather information by using one of the plurality of devices **4000**, an occupancy of the processors **4120**, **4220**, and **4320** may not be high and a residual capacity of the memories **4130**, **4230**, and **4330** may be large. The function determination model management module **1360** of the hub device **1000** may determine whether to store a function determination model in the memory **1300** of the hub device **1000** or the memories **4130**, **4230**, and **4310** of the plurality of devices **4000**, by comparing the resource state information of the processors **1200**, **4120**, **4220**, and **4320** and the memories **1300**, **4130**, **4230**, and **4330** with information of the function determination model. The information of the function determination

model may include at least one of capacity information of the function determination model, RAM occupancy information used to read the function determination model, or information about a simulated processing time required for the processors **1200**, **4120**, **4220**, and **4320** to obtain operation information through detailed operations according to a function and an order of the detailed operations by reading the function determination model.

[0146] In an embodiment, the hub device **1000** may perform a simulation to compare a residual capacity of the memories **1300**, **4130**, **4230**, and **4330** with capacity information of the received function determination model, based on the information of the function determination model received from the voice assistant server **2000**, by using data about the function determination model management module **1360**. In an embodiment, the hub device **1000** may perform a simulation to compare an average residual capacity of a RAM connected to the processors **1200**, **4120**, **4220**, and **4320** with a RAM capacity used to process the function determination model, by using the data about the function determination model management module **1360**. In an embodiment, the hub device **1000** may simulate a processing time required to process the function determination model considering an average processing speed of the processor **1200**, by using the data about the function determination model management module **1360**.

[0147] In an embodiment, when a difference between a residual capacity of the memory **1300** and a capacity of the function determination model is less than a preset threshold value, the function determination model management module **1360** may determine not to store the function determination model in the memory **1300**. In an embodiment, when a simulated processing time of the function determination model is greater than a preset threshold time, the function determination model management module **1360** may determine not to store the function determination model in the memory **1300**. A detailed method, performed by the hub device **1000**, of determining whether to store the function determination model in the memory **1300** by using the data about the function determination model management module **1360** will be described below in detail with reference to FIG. 7.

[0148] In another embodiment, the function determination model management module **1360** may analyze characteristics of the function determination model corresponding to the new device **4300**. The characteristics of the function determination model are analyzed based on detailed information about a function determined to be performed by the device. The detailed information about the function may include the name of the function, a detailed description of the function, resources required to perform the function (e.g., a memory amount and a processing speed), an application required to perform the function, and a type of content subjected to the function. The function determination model management module **1360** obtains the detailed information about the function, and analyzes the characteristics of the function determination model, according to a pre-stored voice assistant usage pattern of the user, one or more pre-determined rules, and a type according to sensitive information that is pre-input by the user.

[0149] The characteristics of the function determination model include a minimum time required for a device to perform a function and output a result through the device or another peripheral device, and the required minimum time may be determined by a pre-determined rule. For example, the hub device **1000** may store information indicating that a default minimum time for a function of power on/off of the device is 0.1 ms, and a default minimum time for a function of searching and playing video content in the device is 1 s. In addition, when a device through which the user inputs a voice and a device that is subjected to the function are different from each other, the hub device **1000** may store a rule indicating that 0.5 ms is added to the default minimum time.

[0150] Also, the characteristics of the function determination model include whether a function is similar to a function frequently used by the user by considering a voice assistant usage pattern of the user. For example, the hub device **1000** may store usage pattern information indicating that the hub device **1000** plays music once every two days. In this case, it may be determined that the function determination model of the new device includes a function related to music playback by

using detailed information about a function included in the function determination model of the new device and the function is identical to a function performed by the user once every two days. [0151] Also, the characteristics of the function determination model may include whether to use sensitive information of the user to perform the function, and the sensitive information of the user may be determined according to a pre-determined rule or may be determined according to a type of the sensitive information that is pre-input by the user. For example, when the function determination model of the new device has a function of obtaining schedule information and registering the schedule information in a calendar application, the hub device **1000** determines whether the schedule information is the sensitive information of the user. The hub device **1000** may determine that the schedule information is the sensitive information of the user, according to the type of the sensitive information that is pre-input by the user.

[0152] The function determination model management module **1360** may determine whether to download the function determination model corresponding to the new device, by analyzing the characteristics of the function determination model. For example, as a result of analysis of the characteristics of the function determination model, when a minimum time required to perform some of functions included in the function determination model and output a result is equal to or less than a certain time, the function determination model management module **1360** may determine to download the function determination model to the hub device **1000** or the new device.

[0153] As another example, as a result of analysis of the characteristics of the function determination model, when it is determined that some of functions included in the function determination model are similar to a function frequently used by the user, the function determination model management module **1360** may determine to download the function determination model to the hub device **1000** or the new device. As another example, as a result of analysis of the characteristics of the function determination model, when it is determined that some of functions included in the function determination model use sensitive information of the user, the function determination model management module **1360** may determine to download the function determination model to the hub device **1000** or the new device.

[0154] As another example, the function determination model management module **1360** may obtain manufacturer or model name information of the new device, and may determine whether to download the function determination model corresponding to the new device according to the manufacturer or model name information. The hub device **1000** may pre-store data about whether to download a function determination model for each manufacturer or model name. When it is determined by using the pre-stored data that the manufacturer or model name information of the new device is designated to download the function determination model, the hub device **1000** may determine to download the function determination model. Also, when manufacturer information of the hub device **1000** and the manufacturer information of the new device are compared with each other and are determined to be identical to each other, the hub device **1000** may determine to download the function determination model corresponding to the new device.

[0155] In another embodiment, the function determination model management module **1360** may obtain the manufacturer or model name information of the new device, and when the function determination model corresponding to the new device is downloaded according to the manufacturer or model name information, the function determination model management module **1360** may also download a data adaptor module (not shown) along with the function determination model. The data adaptor module (not shown) refers to a software (SW) module that converts output data of the voice assistant server into data processable by the IoT server to link the voice assistant server and the IoT server. In an embodiment, the data adaptor module may determine a similarity between data obtained by a device from the outside and data stored inside the device, and may convert the data obtained from the outside into data most similar thereto. The conversion of the data may be performed based on a database including pairs of data before conversion and after conversion. In this case, the data adaptor module determines a similarity between the data obtained from the

outside and the data before conversion, and identifies data, from among the data before conversion, most similar to the data obtained from the outside. The data adaptor module identifies corresponding data after conversion by using the identified data before conversion, and outputs the identified data after conversion. In another embodiment, the data adaptor module may convert the data obtained from the outside by using a data conversion model instead of the database.

Alternatively, the data adaptor module may use both the database and the data conversion model.

[0156] Data processable by the IoT server may be the same type of data as data received by at least one of a plurality of devices from the IoT server and used to perform a specific function. Also, the data adaptor module may perform an operation of converting output data of the IoT server into data processable by the voice assistant server. The data processable by the voice assistant server may be the same type of data as information about at least one of the plurality of devices received by the hub device **1000** from the voice assistant server.

[0157] For example, output data of the voice assistant server includes information about a detailed operation, and output data of the IoT server includes device information including at least one of identification information of a device, a device type, a function execution capability, position information, or state information. When the hub device **1000** downloads the data adaptor module to the hub device **1000**, the data adaptor module (not shown) converts output data of the hub device **1000** to link the hub device and the new device. In detail, the data adaptor module converts output data of the function determination model into data processable by the new device, to link the function determination model downloaded to the hub device **1000** and a SW module (not shown) for executing the detailed operation stored in the new device. Also, when the hub device **1000** receives device information about the new device from the new device, the data adaptor module converts the received device information into data processable by the hub device **1000**.

[0158] The data adaptor module may be configured to correspond to a manufacturer or a model name of the new device. In this case, the voice assistant server may store a data adaptor module for each manufacturer or model name, and may store a plurality of data adaptor modules. The hub device **1000** may request the voice assistant server for a data adaptor module corresponding to the new device, based on manufacturer or model name information of the new device. Also, even when there is no request of the hub device **1000**, the voice assistant server may transmit the data adaptor module corresponding to the new device to the hub device **1000** based on the manufacturer or model name information of the new device obtained from the IoT server.

[0159] In an embodiment, when the function determination model management module **1360** determines to download the function determination model from the voice assistant server **2000** and store the function determination model in the memory **1300**, the hub device **1000** may transmit a query for requesting to transmit the function determination model to the voice assistant server **2000**, may receive the function determination model from the voice assistant server **2000**, and may store the function determination model in the memory **1300**. In this case, the hub device **1000** may request the voice assistant server for the data adaptor module corresponding to the new device, based on the manufacturer or model name information of the new device. The data adaptor module (not shown) converts output data of the function determination model downloaded and stored in the hub device **1000** into data processable by the new device.

[0160] In another embodiment, when the function determination model management module **1360** determines not to download the function determination model from the voice assistant server **2000**, the hub device **1000** may receive access information of the function determination model pre-stored in the voice assistant server **2000** and may store the received access information in the function determination model information database **1362**. The access information may include at least one of identification information (e.g., server id) of the voice assistant server **2000** (see FIG. **1**), position information, Internet protocol (IP) address information, a media access control (MAC) address, application programming interface (API) information accessible to each function determination model in the voice assistant server **2000**, a use language of each function

determination model, or identification information of the new device.

[0161] In an embodiment, when the new device is registered by using a user account, the hub device **1000** may receive, from the voice assistant server **2000**, information (e.g., capacity information) about the function determination model corresponding to the new device by using data about the function determination model management module **1360**, may download the function determination model from the voice assistant server **2000** based on the received information about the function determination model, and may determine whether to store the function determination model in the memory **1300**. When the function determination model is determined to be stored in the memory **1300**, the hub device **1000** may download the function determination model corresponding to the new device from the voice assistant server **2000** and may store the function determination model in the memory **1300**. When the function determination model is determined not to be stored, the hub device **1000** may store access information of the function determination model corresponding to the new device in the function determination model information database **1362**.

[0162] The hub device **1000** may determine a function of the hub device **1000** itself, and may store the first function determination model **1372** for performing an operation according to the determined function and the second function determination model **1374** corresponding to at least one of the plurality of devices **4000** (see FIG. 1). The term ‘function determination model corresponding to an operation-performing device’ refers to a model used to obtain operation information about detailed operations for performing an operation according to a determined function of the operation-performing device and a relationship between the detailed operations. In an embodiment, the first function determination model **1372** and the second function determination model **1374** stored in the memory **1300** of the hub device **1000** may respectively correspond to a plurality of devices that are logged in by using the same account as the user account and are connected to the hub device **1000** through a network.

[0163] For example, the first function determination model **1372** may be a model used to obtain operation information about detailed operations for performing an operation according to a function of the first device **4100** (see FIG. 1) and a relationship between the detailed operations. In an embodiment, the first function determination model **1372** may be, but is not limited to, a model used to obtain operation information according to a function of the hub device **1000**. Likewise, the second function determination model **1374** may be a model used to obtain operation information about detailed operations for performing an operation according to a function of the second device **4200** (see FIG. 1) and a relationship between the detailed operations.

[0164] The first function determination model **1372** and the second function determination model **1374** may respectively include second NLU models **1372a** and **1374a** configured to analyze at least part of text and obtain operation information about an operation to be performed by the determined operation-performing device based on an analysis result of the at least part of the text. The first function determination model **1372** and the second function determination model **1374** may respectively include action plan management models **1372b** and **1374b** configured to manage operation information related to a detailed operation of a device to generate detailed operations to be performed by the device and an execution order of the detailed operations. The action plan management models **1372b** and **1374b** may manage operation information about detailed operations of devices according devices and a relationship between the detailed operations. The action plan management models **1372b** and **1374b** may plan detailed operations to be performed by a device and an execution order of the detailed operations, based on an analysis result of at least part of text.

[0165] The processor **1200** may obtain operation information about an operation to be performed by the operation-performing device by using the function determination model corresponding to the operation-performing device stored in the memory **1300**, for example, the second NLU model **1374a** of the second function determination model **1374** that is a TV function determination model. The second NLU model **1374a** that is a model specialized for a specific device (e.g., a TV) may be

an AI model trained to obtain an intent related to a device corresponding to an operation-performing device determined by the first NLU model **1342** and corresponding to text. Also, the second NLU model **1374a** may be a model trained to determine an operation of the device related to the user's intention by interpreting the text. The operation may refer to at least one action performed by the device when the device executes a specific function. The operation may indicate at least one action performed by the device when the device executes an application.

[0166] In an embodiment, the processor **1200** may analyze the text by using the second NLU model **1374a** of the second function determination model **1374** corresponding to the determined operation-performing device (e.g., a TV). The processor **1200** may parse text in units of morphemes, words, or phrases by using the second NLU model **1374a**, may recognize the meaning of a morpheme, a word, or a phrase parsed through grammatical or semantic analysis, and may determine an intent and parameters by matching the recognized meaning to pre-defined words. The 'parameters' used herein refer to variable information for determining detailed operations of an operation-performing device related to the intent. For example, when text transmitted to the second function determination model **1374** is "play the movie Avengers on TV", an intent may be 'content playback' and parameters may be 'the movie Avengers' that is information about content to be played.

[0167] The processor **1200** may obtain operation information about at least one detailed operation related to the intent and the parameters, by using the action plan management model **1374b** of the second function determination model **1374**. The action plan management module **1374b** may manage information about detailed operations of devices according to devices and a relationship between the detailed operations. The processor **1200** may plan detailed operations to be performed by an operation-performing device (e.g., a TV) and an execution order of the detailed operations based on the intent and the parameters by using the action plan management module **1374b**, and may obtain operation information. The operation information may be information related to detailed operations to be performed by a device and an execution order of the detailed operations. The operation information may include information related to detailed operations to be performed by a device, a relationship between each of the detailed operations and another detailed operation, and an execution order of the detailed operations. The operation information may include, but is not limited to, functions to be executed by an operation-performing device to perform a specific operation, an execution order of the functions, an input value required to execute the functions, and an output value output as an execution result of the functions.

[0168] The processor **1200** may generate a control command for controlling the operation-performing device based on the operation information. The control command refers to instructions readable and executable by the operation-performing device so that the operation-performing device performs the detailed operations included in the operation information. In this case, the processor **1200** has to receive a control command conversion module for converting operation information into a control command from the IoT server **3000** through the communication interface **1400**. In an embodiment, the processor **1200** may transmit a query for requesting to transmit the control command conversion module for converting operation information about an operation-performing device into a control command to the IoT server **3000**, may receive the control command conversion module from the IoT server **3000**, and may store the control command conversion module in the memory **1300**, by controlling the communication interface **1400**. However, the disclosure is not limited thereto, and the control command conversion module corresponding to the operation-performing device may be pre-stored in the memory **1300**.

[0169] The processor **1200** may control the communication interface **1400** to transmit the generated control command to the operation-performing device.

[0170] The communication interface **1400** may perform data communication with the voice assistant server **2000**, the IoT server **3000**, and the plurality of devices **4000**. The communication interface **1400** may perform data communication with the voice assistant server **2000**, the IoT

server **3000**, and the plurality of devices **4000** by using at least one of data communication methods including wired LAN, wireless LAN, Wi-Fi, Bluetooth, Zigbee, Wi-Fi Direct (WFD), Infrared Data Association (IrDA), Bluetooth low energy (BLE), Near-Field Communication (NFC), Wireless Broadband Internet (Wibro), World Interoperability for Microwave Access (WiMAX), Shared Wireless Access Protocol (SWAP), Wireless Gigabit Alliance (WiGig), or Radio-Frequency (RF) communication.

[0171] In an embodiment, the processor **1200** may receive device information about the new device **4300** (see FIG. 1) that is logged in and newly registered in the IoT server **3000** (see FIG. 1) by using the same account as the user account of the hub device **1000**, through the communication interface **1400**. The processor **1200** may receive the device information about the new device **4300** by using the communication interface **1400** from the IoT server **3000**, but the disclosure is not limited thereto. The IoT server **3000** may transmit the device information and user account information about the new device **4300** that is newly registered by using the user account to the voice assistant server **2000** (see FIG. 1), and the processor **1200** of the hub device **1000** may control the communication interface **1400** to receive the device information of the new device **4300** from the voice assistant server **2000**.

[0172] The processor **1200** may request the voice assistant server **2000** to update the device determination model **1340** stored in the memory **1300** through the communication interface **1400**, and may receive the updated device determination model **1340** from the voice assistant server **2000**. When the new device **4300** is newly registered by using the user account in the IoT server **3000**, the voice assistant server **2000** may update the device determination model **2330** (see FIG. 1) and the function determination model **2368** (see FIG. 1). In this case, the processor **1200** may transmit, to the voice assistant server **2000**, a query for inquiring about whether there exists the updated device determination model **2330** for device determination of the new device **43000**, and when there exists the updated device determination model **2330**, the processor **1200** may control the communication interface **1400** to transmit a signal for requesting to transmit the updated device determination model **2330** to the hub device **1000**.

[0173] The processor **1200** may analyze text about the new device **4300** from the voice assistant server **2000** through the communication interface **1400**, may receive the device determination model **2300** updated to determine the new device **4300** as an operation-performing device, and may store the received device determination model **2330** in the memory **1300**.

[0174] The processor **1200** may transmit a query for requesting information about the function determination model corresponding to the new device **4300** to the voice assistant server **2000**, through the communication interface **1400**. The information of the function determination model corresponding to the new device **4300** may include at least one of, for example, capacity information or access information of the function determination model to obtain information related to detailed operations performed by the new device **4300**, a relationship between each of the detailed operations and another detailed operation, and an execution order of the detailed operations. The processor **1200** may control the communication interface **1400** to download the function determination model from the voice assistant server **2000** or to receive only the access information of the function determination model, based on determination made by the function determination model management module **1360** as to whether to store the function determination model corresponding to the new device **4300**.

[0175] In FIGS. 1 and 2, when the new device **4300** is logged in by using account information of the same user as the user of the hub device **1000** and is registered by using the user account, or when a new function is added to an existing device, the hub device **1000** may download the updated device determination model **2330** (see FIG. 1) from the voice assistant server **2000** and may store the updated device determination model **2330** in the memory **1300**, and may determine whether to download a function determination model corresponding to the new device **4300** or an updated function determination model corresponding to the existing device and store the

downloaded function determination model in the memory **1300** based on resource state information in the hub device **1000**. In general, when the hub device **1000** determines an operation-performing device and obtains operation information about the operation-performing device, a processing speed may be higher than that when the voice assistant server **2000** performs the processes, and network usage fees for accessing the voice assistant server **2000** may be reduced. However, a resource problem may occur in storing all updated function determination models in the memory **1300** of the hub device **1000** itself. Therefore, according to an embodiment, because the updated device determination model is downloaded from the voice assistant server **2000** and stored in the memory **1300** but whether to download the updated function determination model and the function determination model corresponding to the new device **4300** is determined after resources of the hub device **1000** itself are reviewed, a resource problem may be solved and a processing speed of a voice command may be increased.

[0176] FIG. 3 is a block of the voice assistant server **2000** according to an embodiment.

[0177] The voice assistant server **2000** is a server that receives text converted from a voice input of a user from the hub device **1000**, determines an operation-performing device based on the received text, and obtains operation information by using a function determination model corresponding to the operation-performing device.

[0178] Referring to FIG. 3, the voice assistant server **2000** may include at least the communication interface **2100**, the processor **2200**, and the memory **2300**.

[0179] The communication interface **2100** of the voice assistant server **2000** may receive, from the IoT server **3000**, device information including at least one of identification information (e.g., device id information) of each of the plurality of devices **4000** (see FIG. 1), a device type of each of the plurality of devices **4000**, a function execution capability of each of the plurality of devices **4000**, position information, or state information, by performing data communication with the IoT server **3000** (see FIG. 1). In an embodiment, the voice assistant server **2000** may receive user account information using which the new device **4300** is registered and device information about the new device **4300** from the IoT server **3000** through the communication interface **2100**. The voice assistant server **2000** may receive user account information from the hub device **1000** through the communication interface **2100**, and may transmit device information about the plurality of devices **4000** registered according to the received user account information to the hub device **1000**. In an embodiment, the voice assistant server **2000** may transmit the updated device determination model **2330** to the hub device **1000**, through the communication interface **2100**. In an embodiment, the voice assistant server **2000** may transmit information of the function determination model **2368** corresponding to the new device **4300** to the hub device **1000** or may transmit the function determination model **2368** itself to the hub device **1000**, through the communication interface **2100**.

[0180] In another embodiment, when the function determination model **2368** corresponding to the new device **4300** is determined by the function determination model management module **1360** (see FIG. 2) of the hub device **1000** to be transmitted to one of the plurality of devices **4000** other than the hub device **1000**, the voice assistant server **2000** may receive a query including identification information about the determined device and a signal indicating to transmit the function determination model from the hub device **1000** through the communication interface **2100** and may transmit the function determination model **2368** to the determined device in response to the received query.

[0181] The processor **2200** and the memory **2300** of the voice assistant server **2000** may perform functions that are the same as or similar to those of the processor **1200** (see FIG. 2) and the memory **1300** (see FIG. 2) of the hub device **1000** (see FIG. 2). Accordingly, the same description of the processor **2200** and the memory **2300** of the voice assistant server **2000** as that made for the processor **1200** and the memory **1300** of the hub device **1000** is not provided.

[0182] Data about an ASR module **2310**, data about an NLG module **2320**, data about the device

determination model **2330**, data about the voice assistant model update module **2340**, data about the on-device model update module **2350**, and data corresponding to each of a plurality of function determination models **2360** may be stored in the memory **2300** of the voice assistant server **2000**. The memory **2300** of the voice assistant server **2000** may store the plurality of function determination models **2360** corresponding to a plurality of devices related to a plurality of different user accounts, instead of the plurality of function determination models **1370** (see FIG. 2) stored in the memory **1300** of the hub device **1000**. Also, the plurality of function determination models **2360** for more types of devices than the plurality of function determination models **1370** stored in the memory **1300** of the hub device **1000** may be stored in the memory **2300** of the voice assistant server **2000**. A total capacity of the plurality of function determination models **2360** stored in the memory **2300** of the voice assistant server **2000** may be greater than a capacity of the plurality of function determination models **1370** stored in the memory **1300** of the hub device **1000**.

[0183] When at least part of text is received from the hub device **1000**, the communication interface **2100** of the voice assistant server **2000** may transmit the received at least part of the text to the processor **2200**, and the processor **2200** may analyze the at least part of the text by using the first NLU model **2332** stored in the memory **2300**. The processor **2200** may determine an operation-performing device related to the at least part of the text based on an analysis result, by using the device determination model **2330** stored in the memory **2300**. The processor **2200** may select a function determination model corresponding to the operation-performing device from among a plurality of function determination models stored in the memory **2300**, and may obtain operation information about detailed operations for performing a function of the operation-performing device and a relationship between the detailed operations by using the selected function determination model.

[0184] For example, when it is determined that the operation-performing device is the first device **4100** that is an air conditioner, the processor **2200** may analyze the at least part of the text by using a second NLU model **2362a** of the function determination model **2362** corresponding to the air conditioner, and may obtain operation information by planning detailed operations to be performed by a device and an execution order of the detailed operations by using an action plan management model **2362b**.

[0185] For example, when the voice assistant server **2000** receives text corresponding to 'raise the temperature 1° C.' from the hub device **1000**, the voice assistant server **2000** determines the air conditioner as an operation-performing device through the device determination model **2330**. Next, the voice assistant server **2000** may select the function determination model **2362** corresponding to the air conditioner from among the plurality of function determination models **2360**, may analyze the text by using data about the second NLU model **2362a** of the selected function determination model **2362**, and may obtain operation information for performing a temperature control operation based on a text analysis result by using data about the action plan management model **2362b**.

[0186] For example, when the voice assistant server **2000** receives text corresponding to 'change the channel' from the hub device **1000**, the voice assistant server **2000** determines a TV as an operation-performing device through the device determination model **2330**. Next, the voice assistant server **2000** may select the function determination model **2364** corresponding to the TV from among the plurality of function determination models **2360**, may analyze the text by using data about a second NLU model **2364a** of the selected function determination model **2364**, and may obtain operation information for performing a channel change operation based on a text analysis result by using data about an action plan management model **2364b**.

[0187] The voice assistant server **2000** may update a voice assistant model, by using the voice assistant model update module **2340** stored in the memory **2300**. When the new device **4300** (see FIG. 1) is newly registered by using a user account in the IoT server **3000** or a new function is added to an existing device, the voice assistant server **2000** may receive a user account and device information of the new device **4300** that is registered by using the user account from the IoT server

3000 through the communication interface **2100**. The voice assistant server **2000** may update the device determination model **2330** and the function determination model **2368** corresponding to the new device **4300** by using the voice assistant model update module **2340**.

[0188] For example, when the function determination model **2364** corresponding to the second device **4200** is updated, for example, when a function of the second device **4200** (see FIG. 1) is added or changed, the voice assistant model update module **2340** may update the device determination model **2330** to a new model through learning or the like so that the device determination model **2330** determines the second device **4200** as an operation-performing device related to the updated function by interpreting the updated function. In an embodiment, the voice assistant model update module **2340** may update the first NLU model **2332** to a new model through learning or the like so that the first NLU model **2332** of the device determination model **2330** interprets text related to the newly updated function.

[0189] For example, when the new device **4300** is registered by using a user account in the IoT server **3000**, the voice assistant model update module **2340** may receive identification information of the new device **4300** and the function determination model **2368** corresponding to the new device **4300** from the IoT server **3000** and may additionally store the received function determination model **2368** in the function determination models **2362**, **2364**, and **2366** in the memory **2300**. The voice assistant model update module **2340** may update the device determination model **2330** to a new model through learning or the like so that the device determination model **2330** interprets an intent from text and determines the new device **4300** as an operation-performing device related to the intent as an interpretation result. In an embodiment, the voice assistant model update module **2340** may update the first NLU model **2332** to a new model through learning or the like so that the first NLU model **2332** of the device determination model **2330** interprets text related to the new device **4300**.

[0190] The voice assistant server **2000** may train voice assistant models according to user accounts by using the on-device model update module **2350**, and may determine whether to transmit at least some of the voice assistant models updated through learning to the hub device **1000** (see FIG. 2). In another embodiment, the voice assistant server **2000** may determine to transmit at least some of the updated voice assistant models to at least one of the plurality of devices **4000** by using the on-device model update module **2350**.

[0191] The on-device model update module **2350** may include the on-device model information database **2352** that stores configuration information of the voice assistant models according to user accounts. The on-device model information database **2352** may store at least one of, for example, user account information, identification information about a plurality of devices registered according to user accounts, identification information of a function determination model corresponding to each of the plurality of devices, version information of the function determination model, version information of a device determination model, or information about a device type that may be determined by the device determination model as an operation-performing device.

[0192] In an embodiment, the voice assistant server **2000** may determine to transmit the updated device determination model **2330** to the hub device **1000** (see FIG. 2), by using the on-device model update module **2350**. In an embodiment, the voice assistant server **2000** may transmit the updated device determination model **2330** to the hub device **1000** through the communication interface **2100**. In another embodiment, the voice assistant server **2000** may transmit the updated device determination model **2330** to at least one of the plurality of devices **4000** through the communication interface **2100**.

[0193] In another embodiment, the voice assistant server **2000** receives a query signal for updating a device determination model pre-stored in the hub device **1000** along with information about a new device connected to the hub device **1000** from the hub device **1000**. In this case, the voice assistant server **2000** may also receive at least user account information and identification information of the hub device **1000** (e.g., id information of the hub device **1000**) along with the

query signal from the hub device **1000**. The on-device model update module **2350** of the voice assistant server **2000** may update the device determination model pre-stored in the hub device **1000** by using at least the received account information and the information about the new device received from the hub device **1000**.

[0194] Updating of the device determination model is similar to updating of the device determination model **2330** of the voice assistant server **2000**. That is, the on-device model update module **2350** may update the device determination model of the hub device **1000** to a new model through learning or the like so that the device determination model of the hub device **1000** interprets an intent from text and determines the new device **4300** as an operation-performing device related to the intent as an interpretation result. In an embodiment, the on-device model update module **2350** may update a first NLU model to a new model through learning or the like so that the first NLU model of the device determination model of the hub device **1000** interprets text related to the new device **4300**. Updating of a model will be described below in more detail with reference to FIGS. **18A** and **18B**.

[0195] In an embodiment, the voice assistant server **2000** may receive a signal for requesting to transmit the function determination model **2368** corresponding to the new device **4300** from the hub device **1000**. When the signal for requesting to transmit the function determination model **2368** corresponding to the new device **4300** is received, the voice assistant server **2000** may transmit the function determination model **2368** corresponding to the new device **4300** to the hub device **1000** by using the on-device model update module **2350**.

[0196] The voice assistant server **2000** may include a data adaptor module (not shown). The data adaptor module (not shown) refers to a software (SW) module that converts output data of the voice assistant server **2000** into data processable by the IoT server **3000** to link the voice assistant server **2000** and the IoT server **3000**. The voice assistant server **2000** may store a data adaptor module for each manufacturer or model name, and may include a plurality of data adaptor modules. The voice assistant server **2000** may transmit a data adaptor module corresponding to the new device to the hub device **1000** in response to a request of the hub device **1000**. In an embodiment, even when there is no request of the hub device **1000**, the voice assistant server **2000** may transmit the data adaptor module corresponding to the new device to the hub device **1000** based on manufacturer or model name information of the new device obtained from the IoT server **3000**.

[0197] In another embodiment, the voice assistant server **2000** may receive a query for requesting to transmit the function determination model **2368** corresponding to the new device **4300** to one of the plurality of devices **4000** from the hub device **1000**. In this case, the voice assistant server **2000** may receive identification information (e.g., device id) about one of the plurality of devices **4000** along with the query. The voice assistant server **2000** may transmit the function determination model **2368** corresponding to the new device to the device determined according to received device information from among the plurality of devices **4000**, by using the on-device model update module **2350**.

[0198] FIG. **4** is a block diagram of the IoT server **3000** according to an embodiment.

[0199] The IoT server **3000** is a server that obtains, stores, and manages device information about each of the plurality of devices **4000** (see FIG. **1**). The IoT server **3000** may obtain, determine, or generate a control command for controlling a device by using the stored device information. Although the IoT server **3000** is implemented as an independent hardware device separate from the voice assistant server **2000** in FIG. **1**, the disclosure is not limited thereto. In an embodiment, the IoT server **3000** may be an element of the voice assistant server **2000** (see FIG. **1**), or may be a server designed to be classified as software.

[0200] Referring to FIG. **4**, the IoT server **3000** may include at least a communication interface **3100**, a processor **3200**, and a memory **3300**.

[0201] The IoT server **3000** may be connected via a network to the voice assistant server **2000** or an operation-performing device through the communication interface **3100**, and may receive or

transmit data. The IoT server **3000** may transmit data stored in the memory **3300** to the voice assistant server **2000** or the operation-performing device through the communication interface **3100** under the control of the processor **3200**. Also, the IoT server **3000** may receive data from the voice assistant server **2000** or the operation-performing device through the communication interface **3100** under the control of the processor **3200**.

[0202] In an embodiment, the communication interface **3100** may receive device information including at least one of device identification information (e.g., device id information), function execution capability information, position information, or state information from each of the plurality of devices **4000** (see FIG. 1). In an embodiment, the communication interface **3100** may receive user account information from each of the plurality of devices **4000**. Also, the communication interface **3100** may receive information about power on/off or an operation that is being performed from the plurality of devices **4000**. The communication interface **3100** may provide the received device information to the memory **3300**.

[0203] In an embodiment, the communication interface **3100** may receive user account information using which the new device **4300** is logged in and device information about the new device **4300** from the new device **4300** (see FIG. 1).

[0204] In an embodiment, the communication interface **3100** may transmit the user account information of the new device **4300** and the device information of the new device **4300** registered by using a user account to the voice assistant server **2000** (see FIG. 1), under the control of the processor **3200**.

[0205] The processor **3200** may store the device information about each of the plurality of devices **4000** received through the communication interface **3100** in the memory **3300**. In an embodiment, the memory **3300** may classify the device information according to the user account information received from the plurality of devices **4000** and may store the classified device information in the form of a lookup table (LUT).

[0206] The processor **3200** may store, in the memory **3300**, the device information about the new device and the user account information used to log into the new device **4300**, which are received through the communication interface **3100**. In an embodiment, the processor **3200** may store the device information of the new device **4300**, for example, at least one of identification information (e.g., id information) of the new device **4300**, function execution capability information, position information, or state information, in the user account information corresponding to the new device **4300** in the memory **3300** in the form of a lookup table.

[0207] In an embodiment, the communication interface **3100** may receive a query for requesting the user account information and the device information about the plurality of devices **4000** that are pre-registered by using the user account information from the voice assistant server **2000**. In response to the received query, the processor **3200** may obtain, from the memory **3300**, the device information about the plurality of devices **4000** that are pre-registered by using a user account in response to the received query, and may control the communication interface **3100** to transmit the obtained device information to the voice assistant server **2000**.

[0208] In an embodiment, the communication interface **3100** may receive a query for requesting the device information about the new device **4300** that is newly registered by using the user account information from the voice assistant server **2000**. In this case, the processor **3200** may control the communication interface **3100** to transmit the device information about the new device **4300** that is newly registered by using the user account to the voice assistant server **2000** in response to the received query.

[0209] The processor **3200** may control the communication interface **3100** to transmit a control command to the operation-performing device determined to perform an operation, based on operation information received from the voice assistant server **2000**.

[0210] The IoT server **3000** may receive an operation execution result according to the control command through the communication interface **3100** from the operation-performing device.

[0211] FIG. 5 is a block diagram of the plurality of devices **4000** according to an embodiment.

[0212] The plurality of devices **4000** may be devices that are controlled by the hub device **1000** (see FIG. 1) or the IoT server **3000** (see FIG. 1). In an embodiment, the plurality of devices **4000** may be executor devices that execute an operation based on a control command received from the hub device **1000** or the IoT server **3000**.

[0213] Referring to FIG. 5, the plurality of devices **4000** may include the first device **4100**, the second device **4200**, and the new device **4300**. However, the disclosure is not limited thereto, and in an embodiment, the plurality of devices **4000** may include only the first device **4100** and the second device **4200** that are pre-registered, and may not include the new device **4300**.

[0214] The new device **4300** may be a device that is newly obtained by a user of the hub device **1000**, and is registered in the IoT server **3000** (see FIG. 1) by being logged in by using the same user account as that of other pre-registered devices **4100** and **4200**.

[0215] Although the first device **4100** is an air conditioner, the second device **4200** is a TV, and the new device **4300** is an air purifier of FIG. 5, the disclosure is not limited thereto. The plurality of devices **4000** are not limited to device types illustrated in FIG. 5.

[0216] Although each of the first device **4100**, the second device **4200**, and the new device **4300** includes only a processor, a memory, and a communication interface in FIG. 5, this is for convenience of explanation. In FIG. 5, elements required for each of the plurality of devices **4000** to execute an operation based on a control command are not shown in FIG. 5.

[0217] Some of the plurality of devices **4000** may store function determination models. In FIG. 5, the first device **4100** may include a communication interface **4110**, a processor **4120**, and the memory **4130**, and the function determination model **4132** may be stored in the memory **4130**. The function determination model **4132** stored in the first device **4100** may be a model used to obtain operation information about detailed operations for performing an operation of the first device **4100** and a relationship between the detailed operations. The function determination model **4132** may include an NLU model **4134** configured to analyze at least part of text received from the hub device **1000** or the IoT server **3000** and obtain operation information about an operation to be performed by the first device **4100** based on an analysis result of the at least part of the text. The function determination model **4132** may include an action plan management model **4136** configured to manage operation information related to a detailed operation of a device in order to generate detailed operations to be performed by the first device **4100** and an execution order of the detailed operations. The action plan management model **4136** may plan the detailed operations to be performed by the first device **4100** and the execution order of the detailed operations, based on an analysis result of the at least part of the text.

[0218] The second device **4200** may include a communication interface **4210**, the processor **4220**, and the memory **4230**. The new device **4300** may include a communication interface **4310**, the processor **4320**, and a memory **4330**. Each of the second device **4200** and the new device **4300** does not store a function determination model, unlike the first device **4100**. Each of the second device **4200** and the new device **4300** does not receive at least part of text from the hub device **1000** (see FIG. 1) or the IoT server **3000** (see FIG. 1). Each of the second device **4200** and the new device **4300** may receive a control command from the hub device **1000** or the IoT server **3000**, and may execute an operation based on the received control command.

[0219] However, this is for convenience of explanation, and the disclosure is not limited thereto. In an embodiment, the new device **4300** itself may include a function determination model for obtaining operation information about detailed operations for executing an operation of the new device **4300**, a relationship between the detailed operations, and an execution order of the detailed operations.

[0220] The plurality of devices **4000** may transmit user account information and device information to the IoT server **3000** by using the communication interfaces **4110**, **4210**, and **4310**. The device information may include at least one of, for example, identification information (e.g.,

device id information) of each of the plurality of devices **4000**, a device type of each of the plurality of devices **4000**, a function execution capability of each of the plurality of devices **4000**, position information, or state information.

[0221] In an embodiment, at least one of the plurality of devices **4000** may include an updated function determination model for an added, changed, or removed function. For example, when a 'no-wind function (new function)' is added to the first device **4100**, the function determination model **4132** stored in the memory **4130** of the first device **4100** may be updated. When the function determination model **4132** of the first device **4100** is updated, the first device **4100** may transmit information about the updated function determination model **4132** to the IoT server **3000** by using the communication interface **4110**.

[0222] The new device **4300** may transmit user account information of a user who logs in to the new device **4300** and device information to the IoT server **3000** through the communication interface **4310**. In an embodiment, the new device **4300** may transmit information about whether the new device **4300** itself includes a function determination model to the IoT server **3000**, by using the communication interface **4310**.

[0223] In an embodiment, the plurality of devices **4000** may transmit, to the hub device **1000** (see FIG. 1), user account information, information about whether each of the plurality of devices **4000** itself stores a device determination model, and information about whether each of the plurality of devices **4000** itself stores a function determination model, by using the communication interfaces **4110**, **4210**, and **4310**.

[0224] FIG. 6 is a flowchart of a method, performed by the hub device **1000**, of receiving and storing at least some of voice assistant models from the voice assistant server **2000** according to an embodiment.

[0225] In operation **S610**, the hub device **1000** receives information of a new device connected to the hub device **1000**. In an embodiment, the hub device **1000** may receive device information about the new device that is logged in by using the same user account as that of the hub device **1000** and is newly registered in the IoT server **3000** (see FIG. 1) by using the user account. The new device may be a device that is newly obtained by a user of the hub device **1000** through purchase or ownership transfer and is registered in the IoT server **3000** by being logged in by using the same user account as that of the hub device **1000**. The device information of the new device received by the hub device **1000** may include at least one of, for example, identification information (e.g., device id information) of the new device, a device type of the new device, function execution capability information of the new device, or position information. In an embodiment, the hub device **1000** may receive state information about power on/off of the new device or an operation that is being currently executed.

[0226] The hub device **1000** may receive the device information of the new device from the IoT server **3000**. However, the disclosure is not limited thereto, and the hub device **1000** may receive the device information of the new device from the voice assistant server **2000** (see FIG. 1).

[0227] In operation **S620**, the hub device **1000** requests the voice assistant server **2000** to update a device determination model stored in the hub device **1000**. In an embodiment, the hub device **1000** may transmit a query signal for requesting to update a device determination model pre-stored in the memory **1300** (see FIG. 2) to the voice assistant server **2000** so that the hub device **1000** analyzes text related to the new device from a voice input of the user based on the device information of the new device received in operation **S610** and determines the new device as an operation-performing device. In this case, the hub device **1000** may transmit user account information of the new device and identification information of the hub device **1000** (e.g., id information of the hub device **1000**) along with the query signal to the voice assistant server **2000**.

[0228] In operation **S630**, the hub device **1000** receives and stores the updated device determination model from the voice assistant server **2000**. In an embodiment, the hub device **1000** may analyze the voice input of the user related to the new device, may download the updated

device determination model from the voice assistant server **2000** to determine the new device as an operation-performing device as an analysis result, and may store the updated device determination model in the memory **1300** (see FIG. 2) in the hub device **1000**.

[0229] In operation **S640**, the hub device **1000** requests the voice assistant server **2000** for information of a function determination model corresponding to the new device and receives the information of the function determination model corresponding to the new device from the voice assistant server **2000**. In an embodiment, when the hub device **1000** requests the information of the function determination model corresponding to the new device, the hub device **1000** may transmit identification information (e.g., device id) of the hub device **1000** and the new device and user account information to the voice assistant server **2000**.

[0230] The function determination model corresponding to the new device is a model for, when the new device is determined as an operation-performing device, obtaining information related to detailed operations to be performed by the new device, a relationship between each of the detailed operations and another detailed operation, and an execution order of the detailed operations. The information of the function determination model may include at least one of, for example, capacity information of a file constituting the function determination model corresponding to the new device, RAM occupancy information used to read the function determination model, or information about a simulated processing time required for the processor **1200** (see FIG. 2) of the hub device **1000** to obtain operation information through detailed operations according to a function and an order of the detailed operations by reading the function determination model.

[0231] In operation **S650**, the hub device **1000** determines whether to store the function determination model corresponding to the new device in the hub device **1000**, based on the received information of the function determination model corresponding to the new device. In an embodiment, the hub device **1000** may determine whether to store the function determination model corresponding to the new device in the memory **1300** by monitoring resource states of the processor **1200** (see FIG. 2) and the memory **1300** (see FIG. 2) and comparing and analyzing resource state information and the information of the function determination model corresponding to the new device. The resource state information that is information indicating usage states of the processors **1200**, **4120**, **4220**, and **4320** and the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000** may include at least one of, for example, residual capacity, average RAM usage capacity, or average processor occupancy information of the memories **1300**, **4130**, **4230**, and **4330** of the hub device **1000** and the plurality of devices **4000**.

[0232] In an embodiment, the hub device **1000** may determine whether to download the function determination model corresponding to the new device from the voice assistant server **2000** and store the downloaded function determination model in the memory **1300** by monitoring in real time or periodically at least one of an average processing speed of the processor **1200**, a residual capacity of the memory **1300**, or an average RAM residual capacity and comparing monitoring result information with the information of the function determination model corresponding to the new device.

[0233] In another embodiment, the hub device **1000** may monitor resource state information of each of the plurality of devices **4000** (see FIG. 5) and may obtain the resource state information of each of the plurality of devices **4000**. The resource state information of the plurality of devices **4000** that is information related to usage states of the processors **4120**, **4220**, and **4320** (see FIG. 5) and the memories **1300**, **4130**, **4230**, and **4330** (see FIG. 5) may include at least one of residual capacity, average RAM usage capacity, or average processor occupancy information of the memories **4130**, **4230**, and **4330**. The hub device **1000** may determine whether to store the function determination model corresponding to the new device in at least one of the plurality of devices **4000**, based on the resource state information. The hub device **1000** may compare and analyze the information of the function determination model and the resource state information of each of the plurality of devices **4000**, and may determine which one of the memories **4130**, **4230**, and **4330** of

the plurality of devices **4000** is to be used to store the function determination model corresponding to the new device based on a comparison/analysis result.

[0234] In operation **S650**, a specific process, performed by the hub device **1000**, of determining whether to store the function determination model corresponding to the new device will be described below in detail with reference to FIG. 7.

[0235] When the function determination model corresponding to the new device is determined to be stored (operation **S660**), the hub device **1000** receives the function determination model corresponding to the new device from the voice assistant server **2000** and stores the function determination model in the memory **1300** (see FIG. 2). Because the function determination model corresponding to the new device is stored in the memory **1300** in the hub device **1000**, when the new device is determined as an operation-performing device, the hub device **1000** may obtain information about detailed operations about the new device, a relationship between the detailed operations, and an execution order of the detailed operations even without accessing the voice assistant server **2000**. Accordingly, a time being consumed to access the voice assistant server **2000** and network usage fees may be prevented and a processing speed may be increased. Also, when a network may not be used, for example, when a wireless communication network may not be used or Wi-Fi communication may not be used, the hub device **1000** itself may obtain operation information about the new device.

[0236] Although the function determination model corresponding to the new device is stored in the memory **1300** of the hub device **1000** in operation **S660**, the disclosure is not limited thereto. When the hub device **1000** determines to store the function determination model corresponding to the new device in at least one of the plurality of devices **4000** based on the resource state information of each of the plurality of devices **4000** in operation **S650**, in operation **S660**, the hub device **1000** may receive the function determination model from the voice assistant server **2000** and may transmit the function determination model to the determined device.

[0237] In another embodiment, the hub device **1000** may transmit device information (e.g., device id) of the device determined to store the function determination model corresponding to the new device to the voice assistant server **2000**. In this case, the voice assistant server **2000** may transmit the determined function determination model corresponding to the new device, based on the device information.

[0238] When the function determination model corresponding to the new device is determined not to be stored (operation **S670**), the hub device **1000** receives access information of the function determination model corresponding to the new device from the voice assistant server **2000**. The access information may include at least one of, for example, identification information (e.g., server id) of the voice assistant server **2000** storing the function determination model corresponding to the new device, position information, IP address information, a MAC address, application programming interface (API) information accessible to the function determination model in the voice assistant server **2000**, a use language of the function determination model, or identification information of the device. The hub device **1000** may store the received access information in the function determination model information database **1362** (see FIG. 2) in the memory **1300**. Because the access information is stored in the memory **1300**, the hub device **1000** may access the voice assistant server **2000** by using the access information even without storing the function determination model corresponding to the new device itself, and may obtain information about detailed operations about the new device, a relationship between the detailed operations, and an execution order of the detailed operations by using the function determination model corresponding to the new device stored in the voice assistant server **2000**.

[0239] FIG. 7 is a flowchart of a method, performed by the hub device **1000**, of determining whether to store a function determination model based on information of the function determination model received from the voice assistant server **2000** according to an embodiment. FIG. 7 is a detailed flowchart of operation **S650** of FIG. 6. Operations **S710**, **S712**, and **S714** of

FIG. 7 may be performed after operation S640 of FIG. 6.

[0240] In operation S710, the hub device **1000** identifies a residual capacity of a flash memory in the hub device **1000**. The flash memory may be a storage medium that stores an updated device determination model and at least one function determination model in the hub device **1000**. In an embodiment, the hub device **1000** may include a hard disk type, a solid state drive (SSD), or a card-type external memory (e.g., an SD or XD memory), instead of a flash memory type, as a storage medium.

[0241] In operation S712, the hub device **1000** identifies an average RAM residual capacity. The average RAM residual capacity indicates an average available RAM capacity, excluding an RAM capacity used by at least one application executed by the hub device **1000** to provide a service or at least one application executed in the background to receive a push notification or the like.

[0242] In operation S714, the hub device **1000** identifies an average processing speed. The hub device **1000** may identify an average processing speed of the processor **1200** (see FIG. 2). The average processing speed indicates an average computation speed at which the processor **1200** performs a function, for example, a function of executing at least one application, a function of converting a voice input of a user into text by performing ASR, or a function of determining an operation-performing device related to the text by using a device determination model.

[0243] Operations S710, S712, and S714 in which a resource state of the hub device **1000** is monitored and resource state information is obtained may be performed by the processor **1200** by using the resource tracking module **1350** stored in the memory **1300** (see FIG. 2). Operations S710, S712, and S714 may be performed in real time or periodically.

[0244] Although operations S710, S712, and S714 may be simultaneously performed, the disclosure is not limited thereto.

[0245] Operations S710, S712, and S714 may not be all performed, and at least one of operations S710, S712, and S714 may be performed. When one of operations S710, S712, and S714 is not performed, operations subsequent to the operation may also not be performed. For example, when operation S710 is not performed, operation S720 that is subsequent to operation S710 may not be performed.

[0246] Although operations S710, S712, and S714 respectively identify an internal flash memory residual capacity of the hub device **1000**, an average RAM residual capacity of the hub device **1000**, and an average processing speed of the hub device **1000**, the disclosure is not limited thereto. In an embodiment, operations S710, S712, and S714 may respectively monitor a flash memory residual capacity, an average RAM residual capacity, and an average processing speed of the plurality of devices **4000** (see FIG. 5) other than the hub device **1000**.

[0247] In operation S720, the hub device **1000** compares the flash memory residual capacity with received information about a function determination model. The information of the function determination model received in operation S640 may include at least one of capacity information of a file constituting the function determination model, RAM occupancy information used to read the function determination model, or information about a simulated processing time required for the processor **1200** (see FIG. 2) of the hub device **1000** to obtain operation information through detailed operations according to a function and an order of the detailed operations by reading the function determination model. The hub device **1000** may compare the flash memory residual capacity with the capacity information of the file constituting the function determination model. In an embodiment, the hub device **1000** may compare the flash memory residual capacity of each of the plurality of devices **4000** with the capacity information of the function determination model.

[0248] In operation S722, the hub device **1000** simulates an operation of the function determination model considering the RAM residual capacity. In an embodiment, the hub device **1000** may simulate a RAM occupancy capacity used by the processor **1200** to read and execute instructions written in a programming language included in the function determination model, by comparing the average RAM residual capacity identified in operation S712 with the RAM occupancy information

in the information of the function determination model received in operation S640. In an embodiment, the hub device **1000** may simulate an operation of the function determination model considering the RAM residual capacity of each of the plurality of devices **4000**.

[0249] In operation S724, the hub device **1000** simulates an operation of the function determination model considering the average processing speed. In one embodiment, the hub device **1000** may simulate a processing speed for reading the function determination model and obtaining operation information through detailed operations and an order of the detailed operations according to a read function, by comparing the average processing speed identified in operation S714 with the information about the simulated processing time in the information of the function determination model received in operation S640. In an embodiment, the hub device **1000** may simulate an operation of the function determination model considering the average processing speed of each of the processors **4120**, **4220**, and **4320** of the plurality of devices **4000**.

[0250] In operation S730, the hub device **1000** determines whether a difference between the memory residual capacity and the capacity of the function determination model is greater than a preset threshold value of a memory residual capacity. In an embodiment, the hub device **1000** may calculate a difference value between the flash memory residual capacity and the capacity information of the file constituting the function determination model. The capacity information of the file constituting the function determination model may be obtained from the information of the function determination model received in operation S640. In an embodiment, the hub device **1000** may compare the calculated difference value with the preset threshold value of the memory residual capacity, and may determine whether the calculated difference value is greater than the preset threshold value as a comparison result.

[0251] When it is determined that the difference value between the flash memory residual capacity and the capacity of the function determination model is greater than the preset threshold value of the memory residual capacity (operation S740), the hub device **1000** determines whether the simulated processing time of the function determination model is less than a preset threshold value of a processing time. In an embodiment, the hub device **1000** may obtain information about the simulated processing time of the function determination model from the information of the function determination model received in operation S640. The hub device **1000** may compare the obtained simulated processing time of the function determination model with the preset threshold value of the processing time, and may determine whether the simulated processing time of the function determination model is less than the preset threshold value as a comparison result.

[0252] When it is determined that the difference value between the flash memory residual capacity and the capacity of the function determination model is less than the preset threshold value of the memory residual capacity (operation S670), the hub device **1000** receives access information of the function determination model corresponding to a new device from the voice assistant server **2000**.

[0253] When it is determined that the simulated processing time of the function determination model is less than the preset threshold value of the processing time (operation S660), the hub device **1000** may receive the function determination model corresponding to the new device from the voice assistant server **2000** and may store the function determination model in an internal memory.

[0254] When it is determined that the simulated processing time of the function determination model is greater than the preset threshold value of the processing time (operation S670), the hub device **1000** receives the access information of the function determination model corresponding to the new device from the voice assistant server **2000**.

[0255] FIG. 8 is a flowchart of a method, performed by the hub device **1000**, of controlling an operation of a new device based on a voice input of a user according to an embodiment. FIG. 8 includes a series of operations performed after operation S660 of FIGS. 6 and 7. Operation S810 of FIG. 8 is an operation after the hub device **1000** receives a function determination model corresponding to a new device from the voice assistant server **2000** (see FIG. 1) and stores the

received function determination model corresponding to the new device in an internal memory.

[0256] In operation **S810**, the hub device **1000** requests the IoT server **3000** (see FIG. 1) for a control command conversion module to convert operation information about the new device into a control command. The operation information about the new device that is information obtained by interpreting a voice input of a user by using the function determination model corresponding to the new device may be information related to detailed operations to be performed by the new device, a relationship between each of the detailed operations and another detailed operation, and an execution order of the detailed operations. The control command conversion module may be a module for converting the operation information into instructions or a set of instructions readable or executable by the new device so that the new device performs the detailed operations included in the operation information obtained by the hub device **1000**. In an embodiment, the hub device **1000** may transmit a query for requesting identification information of the new device (e.g., id of the new device) and the control command conversion module to the IoT server **3000**.

[0257] In operation **S820**, the hub device **1000** receives the control command conversion module for the new device from the IoT server **3000**. In an embodiment, the hub device **1000** may store the received control command conversion module in the memory **1300** (see FIG. 2).

[0258] In operation **S830**, the hub device **1000** receives the voice input of the user. In an embodiment, the hub device **1000** may receive the voice input (e.g., the user's utterance) from the user through the microphone **1100** (see FIG. 2), and may obtain a voice signal from the received voice input. In an embodiment, the processor **1200** (see FIG. 2) of the hub device **1000** may convert a sound received through the microphone **1100** into an acoustic signal, and may obtain the voice signal by removing noise (e.g., a non-voice component) from the acoustic signal.

[0259] In operation **S840**, the hub device **1000** converts the received voice input into text, by performing automatic speech recognition (ASR). In an embodiment, the processor **1200** of the hub device **1000** may perform ASR that converts the voice signal into computer-readable text by using a pre-defined model such as an acoustic model (AM) or a language model (LM). When the hub device **1000** receives the acoustic signal from which noise is not removed, the processor **1200** may obtain the voice signal by removing noise from the received acoustic signal and may perform ASR on the voice signal.

[0260] In operation **S850**, the hub device analyzes the text by using an updated device determination model, and determines the new device as an operation-performing device related to the analyzed text. In an embodiment, the processor **1200** of the hub device **1000** may analyze the text by using an updated first NLU model included in the updated device determination model, and may determine the new device as an operation-performing device for performing an operation according to the user's intention from among a plurality of devices based on an analysis result of the text. The plurality of devices refer to devices that are logged in by using the same user account as that of the hub device **1000** and are connected to the hub device **1000** through a network. The plurality of devices may be devices that are registered in an IoT server by using the same user account as that of the hub device **1000**.

[0261] The first NLU model is a model trained to analyze the text converted from the voice input and determine the operation-performing device based on an analysis result. The first NLU model may be used to determine an intent by interpreting the text and determine the operation-performing device based on the intent. The hub device **1000** may parse the text in units of morphemes, words, or phrases by using the first NLU model, and may infer the meaning of a word extracted from the parsed text by using linguistic features (e.g., grammatical constituents) of the morphemes, words, or phrases. The processor **1200** may compare the inferred meaning of the word with pre-defined intents provided by the first NLU model and may determine an intent corresponding to the inferred meaning of the word.

[0262] The hub device **1000** may determine a device related to the intent recognized from the text as the operation-performing device, based on a matching model for determining a relation between

the intent and the device. In an embodiment, the matching model may be obtained through learning through a rule-based system, but the disclosure is not limited thereto.

[0263] In an embodiment, the hub device **1000** may obtain a plurality of numerical values indicating relation degrees between the intent and the plurality of devices by applying the matching model to the intent, and may determine a device having a largest value from among the obtained plurality of numerical values as a final operation-performing device. For example, when the intent is related to each of a first device and a second device, the hub device **1000** may obtain a first numerical value indicating a relation degree between the intent and the first device and a second numerical value indicating a relation degree between the intent and the second device, and may determine the first device having a larger numerical value from among the first numerical value and the second numerical value as the operation-performing device.

[0264] Although the hub device **1000** may train the matching model between the intent and the operation-performing device by using, for example, a rule-based system, the disclosure is not limited thereto. An AI model used by the hub device **1000** may be, for example, a neural network-based system (e.g., a convolution neural network (CNN) or a recurrent neural network (RNN)), a support-vector machine (SVM), linear regression, logistic regression, Naïve Bayes, a random forest, a decision tree, or a k-nearest neighbor algorithm. Alternatively, the AI model may be a combination of the above examples or any of other AI models.

[0265] The updated device determination model may be a model trained to determine an operation-performing device from among the plurality of devices that are pre-registered and the new device that is newly registered according to a user account of the hub device **1000**. In an embodiment, the updated device determination model may be a model updated through learning or the like to analyze text about the new device, obtain an intent as an analysis result of the text, and determine the new device as an operation-performing device based on the obtained intent.

[0266] The updated device determination model may analyze and calculate a numerical value indicating a relation degree between the intent obtained from the text and each of the new device that is newly registered by being logged in by using the same user account as the user account of the hub device **1000** and the plurality of pre-registered devices, and may determine a device having a largest numerical value as an operation-performing device.

[0267] In an embodiment, the hub device **1000** may receive device information about each of the new device that is newly registered according to the user account and the plurality of pre-registered devices from the voice assistant server **2000** (see FIG. 1). The device information may include at least one of, for example, identification information (e.g., device id information) of each of the new device and the plurality of devices, a device type, a function execution capability, position information, or state information. The hub device **1000** may determine a device for performing an operation according to the intent from among the new device and the plurality of devices based on the received device information. In an embodiment, the hub device **1000** may determine the new device as an operation-performing device by analyzing the text by using the updated device determination model.

[0268] In operation **S860**, the hub device **1000** provides at least part of the text to the function determination model corresponding to the new device stored in then internal memory. Although not shown in FIG. 8, in operation **S860**, the hub device **1000** may select the function determination model corresponding to the new device from among one or more function determination models pre-stored in the internal memory. The ‘function determination model corresponding to the new device’ refers to a model used to obtain operation information about detailed operations for performing an operation according to a function determined by the new device determined as an operation-performing device, a relationship between the detailed operations, and an execution order of the detailed operations.

[0269] The hub device **1000** provides at least part of the text to the selected function determination model. In an embodiment, the processor **1200** (see FIG. 2) of the hub device **1000** may provide at

least part of the text, instead of the whole of the text, to the selected function determination model. For example, when the new device is an air purifier and text converted from a voice input is “execute the deodorization mode in the air purifier”, a name of an operation-performing device is specified in the phrase ‘in the air purifier’, and thus the phrase ‘in the air purifier’ may be unnecessary information for the function determination model corresponding to the new device. The processor **1200** may parse the text in units of words or phrases by using the updated first NLU model, may recognize a word or a phrase specifying a name, a common name, or an installation position of a device, and may provide part of the text other than the recognized word or phrase to the function determination model.

[0270] In operation **S870**, the hub device **1000** obtains operation information about an operation to be performed by the new device by interpreting the at least part of the text by using the function determination model corresponding to the new device. In an embodiment, the processor **1200** (see FIG. 2) of the hub device **1000** may analyze the at least part of the text by using a second NLU model included in the function determination model corresponding to the new device. The processor **1200** may parse the text in units of morphemes, words, or phrases by using the second NLU model, may recognize the meaning of a morpheme, a word, or a phrase parsed through grammatical or semantic analysis, and may determine an intent and parameters by matching the recognized meaning to pre-defined words. The ‘parameters’ used herein refer to variable information for determining detailed operations of an operation-performing device related to the intent. When text provided to the function determination model corresponding to the new device is “execute the deodorization mode”, an intent may be ‘operation mode execution’ and parameters may be a ‘deodorization mode’ that is a mode to be performed.

[0271] The processor **1200** (see FIG. 2) may obtain operation information about at least one detailed operation related the intent and the parameters, by using an action plan management module of the function determination model corresponding to the new device. The action plan management module may manage information about detailed operations of the new device determined as an operation-performing device and a relationship between the detailed operations. The processor **1200** may plan detailed operations to be performed by the new device and an execution order of the detailed operations based on the intent and the parameters by using the action plan management module, and thus may obtain operation information.

[0272] The operation information may be information related to detailed operations to be performed by the new device and an execution order of the detailed operations. The operation information may include information related to detailed operations to be performed by the new device, a relationship between each of the detailed operations and another detailed operation, and an execution order of the detailed operations. The operation information may include, but is not limited to, functions to be executed by the new device to perform a specific operation, an execution order of the functions, an input value required to execute the functions, and an output value output as an execution result of the functions.

[0273] In operation **S880**, the hub device **1000** obtains a control command based on the obtained operation information. The control command refers to instructions or a set of instructions readable or executable by the new device so that the new device performs the detailed operations included in the operation information.

[0274] FIG. 9 is a flowchart of an operating method of the hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and the new device **4300** according to an embodiment.

[0275] FIG. 9 illustrates operations of entities in a multi-device system environment including the hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and an operation-performing device **4000a**. Referring to FIG. 9, the hub device **1000** may include the ASR module **1310**, the NLG module **1320**, the TTS module **1330**, the device determination model **1340**, the resource tracking module **1350**, and the function determination model management module **1360**. In FIG. 9, the hub device **1000** may not store a function determination model, or may not store a function

determination model corresponding to a new device.

[0276] The ASR module **1310**, the NLG module **1320**, the TTS module **1330**, the device determination model **1340**, the resource tracking module **1350**, and the function determination model management module **1360** of FIG. **9** are the same as those illustrated in FIG. **2**, and thus a repeated explanation will be omitted.

[0277] The voice assistant server **2000** may store the device determination model **2330**, the voice assistant model update module **2340**, the on-device model update module **2350**, and the plurality of function determination models **2362**, **2364**, and **2368**. For example, the function determination model **2362** that is a first function determination model and is stored in the voice assistant server **2000** may be a model used to determine a function of an air conditioner and obtain operation information about detailed operations related to the determined function and a relationship between the detailed operations. For example, the function determination model **2364** that is a second function determination model may be a model used to determine a function of a TV and obtain operation information about detailed operations related to the determined function and a relationship between the detailed operations, and the function determination model **2368** may be a model used to determine a function of an air purifier that is a new device and obtain operation information about detailed operations related to the determined function and a relationship between the detailed operations.

[0278] In FIG. **9**, it may be determined that the operation-performing device **4000a** is an 'air purifier' that is the new device **4300**, and the function determination model **2368** corresponding to the air purifier may be stored in the voice assistant server **2000**.

[0279] In operation **S910**, the new device **4300** transmits device information and user account information of the new device **4300** to the IoT server **3000**. When a user of the hub device **1000** obtains the new device **4300**, turns on the new device **4300**, and then logs on to the new device **4300** by inputting a user account, the new device **4300** may transmit the user account information and the device information obtained during a login process to the IoT server **3000**. The device information transmitted to the IoT server **3000** may include at least one of, for example, identification information of the new device (e.g., id information of the new device **4300**), a device type of the new device **4300**, function execution capability information of the new device **4300**, position information, or state information.

[0280] In operation **S920**, the IoT server **3000** registers the new device **4300** by using the received user account. The IoT server **3000** may classify and register a plurality of devices according to user accounts.

[0281] The new device **4300** (or first device) may refer to a device that is newly obtained by the same user as the user of the hub device **1000** and is registered in the IoT server **3000** by being logged in by using the same user account as that of the hub device **1000**.

[0282] In operation **S922**, the IoT server **3000** transmits the user account information and the device information of the new device **4300** registered by using the user account to the voice assistant server **2000**.

[0283] In operation **S930**, the IoT server **3000** transmits the device information of the new device **4300** to the hub device **1000**. The IoT server **3000** may identify the hub device **1000** that is pre-registered by using the received user account, and may transmit the device information of the new device **4300** to the identified hub device **1000**.

[0284] In operation **S932**, the voice assistant server **2000** transmits the device information of the new device **4300** to the hub device **1000**. The voice assistant server **2000** may identify the hub device **1000** that is pre-registered by using the user account received from the IoT server **3000**, and may transmit the device information of the new device **4300** to the identified hub device **1000**.

[0285] In operation **S940**, the hub device **1000** determines whether the device determination model **1340** needs to be updated. In an embodiment, the hub device **1000** may determine whether the device determination model **1340** stored in the memory **1300** (see FIG. **2**) may determine the new

device **4300** as an operation-performing device from a voice input of the user. For example, the hub device **1000** may analyze text converted from the voice input of the user by using the first NLU model **1342** included in the device determination model **1340**, and may determine whether utterance data for obtaining an intent related to a function of the new device **4300** is included.

[0286] When it is determined that the device determination model **1340** related to the new device **4300** does not need to be updated (operation **S944**), the hub device **1000** determines an operation-performing device by using the device determination model **1340**. In operation **S944**, the device determination model **1340** that is a model pre-stored in the memory **1300** (see FIG. 2) before the hub device **1000** receives the device information of the new device **4300** may obtain an intent related to the new device **4300** from the text even without a separate updating process and may determine the new device **4300** as an operation-performing device based on the obtained intent.

[0287] When it is determined that the device determination model **1340** related to the new device **4300** needs to be updated (operation **S942**), the hub device **1000** transmits user account information, identification information of the hub device **1000**, and a query for requesting to update a device determination model to the voice assistant server **2000**.

[0288] In operation **S950**, the voice assistant server **2000** updates the device determination model **2330** by using the device information of the new device **4300**. The voice assistant server **2000** may update the device determination model **2330** to a new model by using the voice assistant model update module **2340** through learning or the like so that the device determination model **2330** interprets the intent from the text based on the received device information of the new device **4300** and determines the new device **4300** as an operation-performing device related to the intent as an interpretation result. In an embodiment, the voice assistant model update module **2340** may update a first NLU model to a new model through learning or the like so that the first NLU model of the device determination model **2330** interprets the text related to the new device **4300**.

[0289] In operation **S952**, the voice assistant server **2000** provides the updated device determination model **2330** to the hub device **1000**. In an embodiment, the voice assistant server **2000** may transmit at least one file constituting the updated device determination model **2330** to the hub device **1000**.

[0290] In operation **S960**, the hub device **1000** stores the updated device determination model **2330** in the memory **1300** (see FIG. 2). In an embodiment, the updated device determination model **2330** received from the voice assistant server **2000** may replace the device determination model **1340** pre-stored in the hub device **1000** by using overwriting.

[0291] In operation **S970**, the voice assistant server **2000** obtains function determination model information corresponding to the new device **4300**, by using the device information of the new device **4300**. In an embodiment, the voice assistant server **2000** may obtain the function determination model **2368** corresponding to the new device **4300** by using the device information of the new device **4300** received from the IoT server **3000** in operation **S922**, and may store the obtained function determination model **2368** in the memory **2300** (see FIG. 3) in addition to the function determination models **2362** and **2364**.

[0292] In operation **S972**, the voice assistant server **2000** provides information of the function determination model corresponding to the new device **4300** to the hub device **1000**. The information of the function determination model may include at least one of, for example, capacity information of the function determination model **2368**, RAM occupancy information used to read the function determination model **2368**, or information about a simulated processing time required for the processor **1200** (see FIG. 2) of the hub device **1000** to obtain operation information through detailed operations according to a function and an order of the detailed operations by reading the function determination model **2368**.

[0293] In operation **S980**, the hub device **1000** identifies a capacity of the function determination model **2368** from the information of the function determination model corresponding to the new device **4300**. In an embodiment, the hub device **1000** may identify a capacity of at least one file

constituting the function determination model **2368** from the information of the function determination model received from the voice assistant server **2000**. However, the disclosure is not limited thereto, and the hub device **1000** may identify RAM occupancy information used to read the function determination model **2368** from the information of the function determination model and information about the simulated processing time required for the processor **1200** (see FIG. 2) of the hub device **1000** to read the function determination model **2368**.

[0294] In operation **S990**, the hub device **1000** determines whether to store the function determination model **2368** corresponding to the new device **4300** in the memory **1300** (see FIG. 2) in the hub device **1000**, based on the received information of the function determination model **2368** corresponding to the new device **4300**. Operation **S990** is the same as operation **S650** of FIG. 7 (including operations **S710** through **S740**), and thus a repeated explanation will be omitted.

[0295] FIG. **10** is a flowchart of an operating method of the hub device **1000** and the new device **4300** according to an embodiment.

[0296] FIG. **10** is a flowchart showing operations of entities in a multi-device system environment including the hub device **1000** and the new device **4300** after step {circle around (a)} of FIG. **9**. Step {circle around (a)} of FIG. **9** indicates a state where it is determined that the hub device **1000** stores the function determination model **2368** corresponding to the new device **4300** in the hub device **1000**.

[0297] In operation **S1010**, the hub device **1000** may download the function determination model **2368** corresponding to the new device **4300** from the voice assistant server **2000** and may store the function determination model **2368** in the memory **1300** (see FIG. 2). Referring to FIG. **10**, the hub device **1000** may include a new device function determination model **1378**. In operation **S1010**, the hub device **1000** may transmit a query for requesting to transmit the function determination model **2368** corresponding to the new device **4300** to the voice assistant server **2000**, may download the function determination model **2368** from the voice assistant server **2000**, and may store the function determination model **2368** in the memory **1300**. The new device function determination model **1378** included in the hub device **1000** may be the same as the function determination model **2368** corresponding to the new device **4300** received from the voice assistant server **2000**.

[0298] In operation **S1020**, the hub device **1000** receives a voice input of a user.

[0299] In operation **S1030**, the hub device **1000** converts the received voice input into text by performing ASR.

[0300] In operation **S1040**, the hub device **1000** analyzes the text by using the updated device determination model **1340** and determines the new device **4300** as an operation-performing device related to the analyzed text.

[0301] In operation **S1050**, the hub device **1000** provides at least part of the text to the new device function determination model **1378** stored in the memory **1300**.

[0302] In operation **S1060**, the hub device **1000** obtains operation information about an operation to be performed by the new device **4300**, by interpreting the at least part of the text by using the new device function determination model **1378**.

[0303] Operations **S1020** through **S1060** are the same as operations **S830** through **S870** of FIG. **8**, and thus a repeated explanation will be omitted.

[0304] In operation **S1062**, the hub device **1000** transmits the operation information by using identification information of the new device **4300**. In an embodiment, the hub device **1000** may identify the new device **4300** by using the identification information of the new device **4300**, for example, id information of the new device **4300**, and may transmit the operation information to the identified new device **4300**.

[0305] In operation **S1070**, the new device **4300** obtains a control command based on the obtained operation information. In operation **S1070**, the new device **4300** itself may include a control command conversion module for converting the operation information into a control command. The new device **4300** may convert the operation information into instructions or a set of

instructions readable or executable by the new device **4300** by using the control command conversion module.

[0306] In operation **S1080**, the new device **4300** executes an operation according to the obtained control command.

[0307] In an embodiment, after executing the operation, the new device **4300** may transmit information about an operation execution result to the hub device **1000**. However, the disclosure is not limited thereto, and the new device **4300** may transmit the information about the operation execution result to the IoT server **3000** (see FIG. 1).

[0308] FIG. **11** is a flowchart of an operating method of the hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and the new device **4300** according to an embodiment.

[0309] FIG. **11** is a flowchart showing operations of entities in a multi-device system environment including the hub device **1000**, the voice assistant server **2000**, the IoT server **3000**, and the new device **4300** after step @ of FIG. **9**. Step {circle around (b)} of FIG. **9** indicates a state where the hub device **1000** does not store the function determination model **2368** corresponding to the new device **4300** in the hub device **1000**. Unlike the hub device **1000** of FIG. **10**, the hub device **1000** of FIG. **11** does not include the new device function determination model **1378** because, in step {circle around (b)}, it is determined that the function determination model **2368** corresponding to the new device **4300** is not stored in the memory **1300** (see FIG. 2).

[0310] In operation **S1110**, the hub device **1000** transmits a query for requesting the voice assistant server **2000** for access information of the function determination model **2368** corresponding to the new device **4300**. The access information may include at least one of, for example, identification information (e.g., server id) of the voice assistant server **2000** storing the function determination model **2368** corresponding to the new device **4300**, position information, IP address information, a MAC address, application programming interface (API) information accessible to the function determination model **2368** in the voice assistant server **2000**, a use language of the function determination model **2368**, or identification information of the corresponding new device **4300**. In operation **S1110**, the hub device **1000** may transmit identification information and user account information of the hub device **1000** to the voice assistant server **2000**.

[0311] In operation **S1120**, the voice assistant server **2000** obtains the access information of the function determination model **2368** corresponding to the new device **4300**.

[0312] In operation **S1122**, the voice assistant server **2000** transmits the access information of the function determination model **2368** corresponding to the new device **4300** to the hub device **1000**.

[0313] In operation **S1130**, the hub device **1000** stores the received access information in the memory **1300** (see FIG. 2).

[0314] In operation **S1140**, the hub device **1000** receives a voice input of a user.

[0315] In operation **S1150**, the hub device **1000** converts the received voice input into text by performing ASR.

[0316] In operation **S1160**, the hub device **1000** analyzes the text by using the updated device determination model **1340** and determines the new device **4300** as an operation-performing device corresponding to the analyzed text.

[0317] Operations **S1140** through **S1160** are the same as operations **S830** through **S850** of FIG. **8**, and thus a repeated explanation will be omitted.

[0318] In operation **S1162**, the hub device **1000** transmits at least part of the text to the function determination model **2368** corresponding to the new device **4300** based on the access information. In an embodiment, the hub device **1000** may identify the voice assistant server **2000** storing the function determination model **2368** at least one of the identification information (e.g., server id) of the voice assistant server **2000** storing the function determination model **2368** corresponding to the new device **4300**, the position information, the IP address information, the MAC address, the API information accessible to the function determination model **2368** in the voice assistant server **2000**, the use language of the function determination model **2368**, or the identification information of the

new device **4300**, and may transmit the at least part of the text to the function determination model **2368** of the voice assistant server **2000**.

[0319] In operation **S1170**, the voice assistant server **2000** obtains operation information about an operation to be performed by the new device **4300** by interpreting the at least part of the text by using the function determination model **2368** corresponding to the new device **4300**. In an embodiment, the voice assistant server **2000** selects the function determination model **2368** corresponding to the new device **4300** from among the plurality of function determination models **2362**, **2364**, and **2368**, interprets the text by using an NLU model **2368a** of the selected function determination model **2368**, and determines an intent based on an analysis result. The voice assistant server **2000** may analyze the at least part of the text received from the hub device **1000**, by using the NLU model **2368a** of the function determination model **2368**. The NLU model **2368a** that is an AI model trained to interpret the text related to the new device **4300** may be a model trained to determine an intent and parameters related to an operation intended by the user. The NLU model **2368a** may be a model trained to determine a function related to a type of the new device **4300** when the text is input.

[0320] In an embodiment, the voice assistant server **2000** may parse the at least part of the text in units of words or phrases by using the NLU model **2368a**, may infer the meaning of a word extracted from the parsed text by using linguistic features (e.g., grammatical elements) of parsed morphemes, words, or phrases, and may obtain an intent and parameters from the text by matching the inferred meaning to pre-defined intents and parameters. In an embodiment, the voice assistant server **2000** may determine only the intent from the at least part of the text.

[0321] The voice assistant server **2000** obtains operation information about an operation to be performed by the new device **4300** based on the intent. In an embodiment, the voice assistant server **2000** plans the operation information to be performed by the new device **4300** based on the intent and the parameters, by using an action plan management module **2368b** of the function determination model **2368**. The action plan management module **2368b** may interpret operations to be performed by the new device **4300** based on the intent and the parameters. The action plan management module **2368b** may select detailed operations related to the interpreted operations from among operations of devices that are pre-stored, and may plan an execution order of the selected detailed operations. The action plan management module **2368b** may obtain operation information about a detailed operation to be performed by the new device **4300** by using a planning result.

[0322] In operation **S1172**, the voice assistant server **2000** transmits the obtained operation information and the identification information of the new device **4300** to the IoT server **3000**.

[0323] In operation **S1180**, the IoT server **3000** obtains a control command based on the identification information of the new device **4300** and the received operation information. The IoT server **3000** may include a database in which control commands and operation information for a plurality of devices are stored. In an embodiment, the IoT server **3000** may select a control command for controlling detailed operations of the new device **4300** based on the identification information of the new device **4300**, from among the control commands related to the plurality of devices pre-stored in the database.

[0324] In operation **S1182**, the IoT server **3000** transmits the control command to the new device **4300** by using the identification information of the new device **4300**.

[0325] In operation **S1190**, the new device **4300** executes operations corresponding to the control command, according to the received control command.

[0326] In an embodiment, after executing the operations, the new device **4300** may transmit information about an operation execution result to the IoT server **3000**.

[0327] FIG. **12A** is a conceptual diagram showing operations of a hub device and a listener device according to an embodiment;

[0328] Arrows in FIG. **12A** indicate movement, transmission, and reception of data including a

voice signal and text between a first device **4100a** and a second device **4200a**. Circled numbers indicate an order of operations.

[0329] The first device **4100a** and the second device **4200a** may be connected to each other by using a wired or wireless communication method and may perform communication. In an embodiment, the first device **4100a** and the second device **4200a** may be directly connected to each other through a communication network, but the disclosure is not limited thereto. In an embodiment, the first device **4100a** and the second device **4200a** may be connected to the voice assistant server **2000** (see FIG. 3), and may be connected to each other through the voice assistant server **2000**.

[0330] Referring to FIG. 12A, the first device **4100a** may be a listener device that receives a voice input from a user, and the second device **4200b** may be a hub device that determines an operation-performing device by interpreting the voice input and controls the determined operation-performing device to perform an operation. For example, the first device **4100a** may be an air conditioner, and the second device **4200a** may be a TV.

[0331] The first device **4100a** may be a listener device that receives a voice input including an utterance from the user. The listener device may be a device that only receives a voice input from the user, but the disclosure is not limited thereto. In an embodiment, the listener device may be an operation-performing device that performs an operation related to a specific function by receiving a control command from the hub device (the second device **4200a** in FIG. 12A).

[0332] In an embodiment, the listener device may receive a voice input related to a function performed by the listener device from the user. For example, the first device **4100a** receives a voice input such as “lower the air conditioner temperature to 20° C.” from the user (step {circle around (1)}).

[0333] In an embodiment, the first device **4100a** may convert a sound received through a microphone into an acoustic signal, and may obtain a voice signal by removing noise (e.g., a non-voice component) from the acoustic signal.

[0334] The second device **4100a** transmits the voice signal to the second device **4200a** that is a hub device (step {circle around (2)}).

[0335] The second device **4200a** that is a hub device receives the voice signal from the first device **4100a**, converts the voice signal into text, and determines the listener device as an operation-performing device by interpreting the text (step {circle around (3)}). In an embodiment, the second device **4200a** may convert the voice signal into the text, by performing automatic speech recognition (ASR) by using data of an ASR module that is pre-stored in a memory. The second device **4200a** may detect an intent from the text by interpreting the text by using a device determination model that is pre-stored in the memory, and may determine a device for performing an operation corresponding to the detected intent. In FIG. 12A, the second device **4200a** may determine the first device **4100a** as an operation-performing device.

[0336] A function determination model corresponding to the operation-performing device determined by the second device **4200a** that is a hub device may be pre-stored in the memory of the hub device, may be stored in the first device **4100a** itself that is determined as the operation-performing device, or may be stored in the memory **2300** (see FIG. 3) of the voice assistant server **2000** (see FIG. 3). A ‘function determination model’ corresponding to each device is a model used to obtain operation information about detailed operations for performing an operation according to a determined function of the device and a relationship between the detailed operations.

[0337] In FIG. 12A, the function determination model corresponding to the first device **4100a** may be pre-stored in the memory of the first device **4100a**. For example, the first device **4100a** may store the function determination model **4132** (see FIG. 5) used to obtain operation information about detailed operations corresponding to an air conditioner and a relationship between the detailed operations.

[0338] The second device **4200a** that is a hub device provides the text to the function determination

model of the listener device (step {circle around (4)}).

[0339] The first device **4100a** executes an operation by interpreting the received text (step {circle around (5)}). In an embodiment, the first device **4100a** may analyze at least part of the text by using the NLU model **4134** (see FIG. 5) included in the function determination model **4132**, and may obtain operation information about an operation to be performed by the first device **4100a** based on an analysis result of the at least part of the text. The function determination model **4132** may include the action plan management module **4136** (see FIG. 5) configured to manage operation information related to a detailed operation of a device in order to generate detailed operations to be performed by the first device **4100a** and an execution order of the detailed operations. The action plan management module **4136** may manage operation information about detailed operations executed by the first device **4100a** and a relationship between the detailed operations. The action plan management module **4136** may plan detailed operations to be performed by the first device **4100a** and an execution order of the detailed operations, based on an analysis result of the at least part of the text. The first device **4100a** may plan the detailed operations and the execution order of the detailed operations based on an analysis result of the at least part of the text by the function determination model **4132**, and may execute an operation based on a planning result.

[0340] FIG. 12B is a conceptual diagram showing operations of a hub device and a second device according to an embodiment.

[0341] Arrows of FIG. 12B indicate movement, transmission, and reception of data including a voice signal and text between a first device **4100b** and a second device **4200b**. Circled numbers indicate an order of operations.

[0342] Like in FIG. 12A, the first device **4100b** and the second device **4200b** of FIG. 12B may be connected to each other by using a wired or wireless communication method and may perform data communication.

[0343] Referring to FIG. 12B, the first device **4100b** may be a listener device that receives a voice input from a user, and may be a hub device that determines an operation-performing device by interpreting the received voice input and controls the determined operation-performing device to perform an operation.

[0344] In FIG. 12B, the first device **4100b** receives a voice input such as “lower the air conditioner temperature to 20° C.” from the user (step {circle around (1)}).

[0345] The first device **4100b** determines a hub device as an operation-performing device by interpreting the voice input and executes an operation (step {circle around (2)}). A method by which the first device **4100b** that is a hub device converts a voice input into text, determines an operation-performing device by interpreting the converted text, obtains operation information for performing an operation of the operation-performing device, and executes an operation based on the obtained operation information is the same as a method of the first device **4100a** of FIG. 12A, and thus a repeated explanation will be omitted.

[0346] In FIGS. 12A and 12B, operation-performing devices related to an utterance intention for an operation executed by the user through a specific device, for example, an intent for an operation of lowering a set temperature of an air conditioner, are both the first device **4100a** and **4100b**.

However, because the first device **4100a** is a listener device in FIG. 12A, the first device **4100a** may not determine an operation-performing device by directly interpreting a voice input, and thus a process of transmitting a voice signal to the second device **4200a** that is a hub device and receiving text from the second device **4200a** is further required. However, because the first device **4100b** is a hub device in FIG. 12B, an unnecessary process of transmitting a voice signal to the second device **4200b** or receiving text from the second device **4200b** is omitted. Accordingly, in FIG. 12B, a latency may be less than that in FIG. 12, and an utterance processing time may be less than that in FIG. 12A. An ‘utterance processing time’ refers to a time from when a user's utterance is received to when operation execution is completed. In an embodiment, an utterance processing time may

refer to a time from when a user's utterance is received to when an operation execution completion message is output.

[0347] In an embodiment, a device that is more frequently used by a user among a plurality of device and requires a short utterance processing time may be determined as a hub device. Also, when there is a first device that is more frequently used by a user than a second device currently used as a hub device and requires a short utterance processing time, the hub device may be changed by being replaced with the first device. In FIGS. 12A and 12B, because a frequency of using an air conditioner in the summer increases and thus a frequency of utterance related to air conditioner control increases, considering a frequency of use and an utterance processing time, the second device **4200a** that is a TV may no longer be used as a hub device and the first device **4100b** that is an air conditioner (see FIG. 12B) may be used instead as a hub device, to reduce a latency. Also, a hub device may be replaced with another device in an exceptional situation where the hub device may not operate normally, such as a device currently used as the hub device is turned off or network connection is lost, to flexibly cope with the exceptional situation.

[0348] In an embodiment, a hub device may be periodically changed by periodically obtaining information about an utterance processing time and a frequency of use of each of a plurality of devices periodically according to a preset time interval and comparing an utterance processing time and a frequency of use of a device currently used as the hub device with the obtained information.

[0349] FIG. 13 is a block diagram of a hub device **1002** according to an embodiment.

[0350] The hub device **1002** is a device that receives a voice input of a user and controls at least one of the plurality of devices **4000** based on the received voice input. The hub device **1002** may be a listener device that receives the voice input from the user.

[0351] Referring to FIG. 13, the hub device **1002** may include at least the microphone **1100**, the processor **1200**, the memory **1300**, and the communication interface **1400**. The microphone **1100**, the processor **1200**, and the communication interface **1400** from among elements of the hub device **1002** are respectively the same as those illustrated in FIG. 2, and thus a repeated explanation will be omitted.

[0352] The memory **1300** may store data about the ASR module **1310**, data about the NLG module **1320**, data about the TTS module **1330**, data about the device determination model **1340**, data about the resource tracking module **1350**, data about the function determination model management module **1360**, data about the plurality of function determination models **1370**, and data about a hub device determination module **1380**. The ASR module **1310**, the NLG module **1320**, the TTS module **1330**, the device determination model **1340**, the resource tracking module **1350**, the function determination model management modules **1360**, and the plurality of function determination models **1370** are the same as those illustrated in FIG. 2, and thus a repeated explanation will be omitted.

[0353] The hub device determination module **1380** is a module configured to determine, as a hub device, one of the hub device **1002** and the plurality of devices **4000** (see FIG. 5) pre-registered in the IoT server **3000** (see FIG. 4) according to a user account logged into the hub device **1002**. The hub device determination module **1380** may include data, instructions, or program code configured to select at least one hub device candidate from among the plurality of devices **4000**, determine one device from among the at least one hub device candidate based on use history information and performance information of each of the at least one hub device candidate, and change a hub device by replacing the current hub device **1002** with the determined device.

[0354] The processor **1200** may select at least one hub device candidate from among the plurality of devices **4000** by using data or program code about the hub device determination module **1380**. In an embodiment, the processor **1200** may obtain at least one information from among consistency of power supply, computing power, or a power consumption amount of each of the plurality of devices **4000** by using the data or program code about the hub device determination module **1380**, and may select at least one hub device candidate from among the plurality of devices **4000** based

on at least one of consistency of power supply, the computing power, or the power consumption amount. Consistency of power supply refers to whether the power supplied to each of the plurality of device **400** is constant and continuous.

[0355] The processor **1200** may obtain use history information and performance information of each of at least one hub device candidate by using the data or program code about the hub device determination module **1380**, and may determine one device from among the at least one hub device candidate based on the obtained use history information and performance information. The processor **1200** may change a hub device by replacing the current hub device **1002** with the determined device. For example, when the current hub device **1002** is a TV, the processor **1200** may determine an air conditioner from among the plurality of devices **4000** as a new hub device by using data about the hub device determination module **1380**, and may change the hub device **1002** by replacing a TV that is the current hub device **1002** with the air conditioner.

[0356] The hub device determination module **1380** may include a use history log database **1382** and a device performance history database **1384**. Although the use history log database **1382** and the device performance history database **1384** are included in the hub device determination module **1380** in FIG. 13, the disclosure is not limited thereto. In an embodiment, the use history log database **1382** and the device performance history database **1384** may not be included in the hub device determination module **1380**, and may be stored in the memory **1300**.

[0357] In another embodiment, at least one of the use history log database **1382** or the device performance history database **1384** may not be included in the hub device **1002**, and may include an external database. In this case, the hub device **1002** may access at least one of the use history log database **1382** or the device performance history database **1384** through a network.

[0358] The use history log database **1382** is a database storing information about a frequency of use and a recent use history of each of the hub device **1002** and the plurality of devices **4000** in the form of a log. The use history log database **1382** may store, in the form of a log, at least one data from among a frequency at which each of the hub device **1002** and the plurality of devices **4000** is used by a user as a listener device, a frequency at which each of the hub device **1002** and the plurality of devices **4000** is used as an operation-performing device, a recent use history in which each of the hub device **1002** and the plurality of devices **4000** is used as a listener device, or a recent use history in which each of the hub device **1002** and the plurality of devices **4000** is used as an operation-performing device. The use history log database **1382** may store, for example, a voice input frequently received from the user or text converted from the voice input.

[0359] The device performance history database **1384** is a database storing performance history information of each of the hub device **1002** and the plurality of devices **4000** in the form of a log. The device performance history database **1384** may store, for example, data about an utterance processing time of each of the hub device **1002** and the plurality of devices **4000** in the form of a log. An ‘utterance processing time’ refers to a time from when a device receives a user's utterance to when operation execution is completed. In an embodiment, an utterance processing time may refer to a time from when a user's utterance is received to when an operation execution completion message is output. An utterance processing time is inversely proportional to the performance of a device. For example, as an utterance processing time decreases, the performance of a device increases.

[0360] In an embodiment, the hub device **1002** may obtain information about a simulation result of an utterance processing time from each of the plurality of devices **4000**. In an embodiment, each of the plurality of devices **4000** may determine an operation-performing device by interpreting text of a user's utterance such as “lower the air conditioner temperature to 20° C.” or “play the movie the Avengers on TV”, may obtain operation information about an operation to be performed by the determined operation-performing device, may generate a control command by using the obtained operation information, and may simulate an utterance processing time required for the operation-performing device to execute an operation based on the generated control command. In an

embodiment, each of the plurality of devices **4000** may simulate an utterance processing time by using a background process. The ‘background process’ refers to a process executed by the device itself in a background environment without user intervention. Each of the plurality of devices **4000** may transmit a simulation result to the hub device **1002**. The hub device **1002** may store the simulation result of the utterance processing time obtained from each of the plurality of devices **4000** in the device performance history database **1384**.

[0361] The processor **1200** may obtain information about a frequency of use of each of the hub device **1002** and at least one device candidate, by analyzing the use history log database **1382** by using the data or program code of the hub device determination module **1380**. Also, the processor **1200** may obtain information about a utterance processing time of each of the hub device **1002** and the at least one hub device candidate, by analyzing the device performance history database **1384** by using the data or program code of the hub device determination module **1380**. The processor **1200** may determine a device for replacing the current hub device **1002** based on the information about the frequency of use and the information about the utterance processing time of each of the hub device **1002** and the at least one hub device candidate. The processor **1200** may change the hub device **1002** to a second device, by replacing a first device used as the current hub device **1002** with the newly determined second device by using the data or program code of the hub device determination module **1380**. A method by which the processor **1200** changes the hub device **1002** based on the information about the frequency of use and the information about the utterance processing time will be described in detail with reference to FIG. **15**.

[0362] However, the disclosure is not limited to the processor **1200** that changes the hub device **1002** based on the information about the frequency of use and the information about the utterance processing time. In an embodiment, the hub device **1002** may receive a user input that selects one of the plurality of devices **4000**, and may determine the selected device as a hub device based on the received user input. For example, the hub device **1002** may receive a voice input of a user that selects one of the plurality of devices **4000** through the microphone **1100**, and the processor **1200** may convert the voice input into text by using data of the ASR module **1310** and may identify the device intended by the user by interpreting the text by using data of the first NLU model **1342**. The processor **1200** may change a hub device to the identified device.

[0363] FIG. **14** is a flowchart of an operating method of the hub device **1002** according to an embodiment.

[0364] In operation **S1410**, the hub device **1002** selects at least one hub device candidate from among a plurality of devices **4000** (see FIG. **5**) that are pre-registered according to a user account. In an embodiment, the hub device **1002** may obtain at least one information from among consistency of power supply, computing power, or a power consumption amount of each of the plurality of devices **4000** that are pre-registered in the IoT server **3000** (see FIG. **4**) according to a user account logged into the hub device **1002** and are connected through a network to the hub device **1002**, and may determine at least one hub device candidate from among the plurality of devices **4000** based on at least one of consistency of power supply, the computing power, or the power consumption amount.

[0365] In operation **S1420**, the hub device **1002** determines one device from among the at least one hub device candidate, based on use history information and performance information of each of the at least one hub device candidate.

[0366] In an embodiment, the hub device **1002** may obtain information about a frequency of use of each of the hub device **1002** and the at least one hub device candidate by analyzing the use history log database **1382** (see FIG. **13**) stored in the memory **1300** (see FIG. **13**). The hub device **1002** may obtain at least one use history information from, for example, a frequency at which each of the hub device **1002** and the at least one hub device candidate is used by a user as a listener device, a frequency at which each of the hub device **1002** and the at least one hub device candidate is used as an operation-performing device, a recent use history in which each of the hub device **1002** and the

at least one hub device candidate is used as a listener device, and a recent use history in which each of the hub device **1002** and the at least one hub device candidate is used as an operation-performing device, from the use history log database **1382**.

[0367] In an embodiment, the hub device **1002** may obtain performance history information of each of the hub device **1002** and the at least one hub device candidate by analyzing the device performance history database **1384** (see FIG. **13**) stored in the memory **1300**. The hub device **1002** may obtain, for example, information about an utterance processing time of each of the hub device **1002** and the at least one hub device candidate from the device performance history database **1384**. An 'utterance processing time' refers to a time from when a user's utterance is received to when operation execution is completed. In an embodiment, an utterance processing time may refer to a time from when a user's utterance is received to when an operation execution completion message is output.

[0368] In an embodiment, the hub device **1002** may determine one device for replacing the hub device **1002** from among the at least one hub device candidate, by comparing frequency of use and utterance processing time of the at least one hub device candidate with a frequency of use and an utterance processing time of the current hub device **1002**. For example, the hub device **1002** may determine one device from among the at least one hub device candidate, by comparing a largest value from among a frequency of use of the at least one hub device candidate with the frequency of use of the current hub device **1002** and comparing a smallest value from among an utterance processing time of the at least one hub device candidate with the utterance processing time of the current hub device **1002**. A detailed method of determining one device from among the at least one hub device candidate will be described below in detail with reference to operations **S1510** through **S1550** of FIG. **15**.

[0369] In operation **S1430**, the hub device **1002** changes the hub device **1002** by replacing the current hub device **1002** with the determined device. For example, when the current hub device **1002** is a TV, the hub device **1002** may change the hub device **1002** by replacing the TV with an air conditioner that is determined from among the at least one hub device candidate.

[0370] FIG. **15** is a flowchart of an operating method of the hub device **1002** according to an embodiment.

[0371] Operations **S1510** through **S1550** of FIG. **15** are detailed operations of operation **S1420** of FIG. **14**. Operation **S1510** of FIG. **15** is performed after operation **S1410** of FIG. **14**.

[0372] In operation **S1510**, the hub device **1002** obtains information about a frequency of use of each of the hub device **1002** and at least one hub device candidate, by analyzing the use history log database **1382** (see FIG. **13**). In an embodiment, the processor **1200** (see FIG. **13**) of the hub device **1002** may access the use history log database **1382** stored in the memory **1300** (see FIG. **13**), and may obtain information about a frequency of use including at least one of a frequency at which each of the hub device **1002** and the at least one hub device candidate is used by a user as a listener device or a frequency at which each of the hub device **1002** and the at least one hub device candidate is used as an operation-performing device by analyzing the use history log database **1382**. Also, the processor **1200** may obtain information about a recent use history including at least one of a recent use history in which each of the hub device **1002** and the at least one hub device candidate is used as a listener device or a recent use history in which each of the hub device **1002** and the at least one hub device candidate is used as an operation-performing device by analyzing the use history log database **1382**.

[0373] In operation **S1520**, the hub device **1002** compares a frequency of use of the current hub device **1002** with a largest value from among a frequency of use of the at least one hub device candidate, and determines whether the frequency of use of the hub device **1002** is equal to or less than the largest value from among the frequency of use of the at least one hub device candidate. When there is only one hub device candidate, the hub device **1002** may determine whether a frequency of use of a device used as the current hub device **1002** is less than a frequency of use of

the hub device candidate.

[0374] When it is determined that the frequency of use of the device used as the current hub device **1002** is less than the largest value from among the frequency of use of the at least one hub device candidate (operation **S1530**), the hub device **1002** obtains information about an utterance processing time of each of the hub device **1002** and the at least one hub device candidate by analyzing the device performance history database **1384** (see FIG. **13**). In an embodiment, the processor **1200** may access the device performance history database **1384** stored in the memory **1300**, and may obtain the information about the utterance processing time of each of the hub device **1002** and the at least one hub device candidate by analyzing the device performance history database **1384**. An ‘utterance processing time’ refers to a time from when a device receives a user’s utterance to when operation execution is completed. In an embodiment, an utterance processing time may refer to a time from a time when a user’s utterance is received to a time when an operation execution completion message is output. An utterance processing time is inversely proportional to the performance of a device. For example, as an utterance processing time decreases, the performance of a device increases.

[0375] In operation **S1540**, the hub device **1002** determines whether the utterance processing time of the current hub device **1002** is equal to or greater than a smallest value from among the utterance processing time of the at least one hub device candidate by comparing the utterance processing time of the device used as the current hub device **1002** with the smallest value from among the utterance processing time of the at least one hub device candidate. When there is only one hub device candidate, the hub device **1002** may determine whether the utterance processing time of the device used as the current hub device **1002** is greater than an utterance processing time of the hub device candidate.

[0376] When it is determined that the utterance processing time of the device used as the current hub device **1002** is greater than the smallest value from among the utterance processing time of the at least one hub device candidate (operation **S1550**), the hub device **1002** may determine a device for replacing the hub device **1002** based on information about a frequency of use and information about a utterance processing time of the at least one hub device candidate. In an embodiment, the hub device **1002** may determine a device having a largest frequency at which the device is used as at least one of a listener device or an operation-performing device from among the at least one hub device candidate and requiring a shortest utterance processing time as a device for replacing the hub device **1002**. In one embodiment, although the hub device **1002** considers both a frequency of use and an utterance processing time together, the hub device **1002** may place a greater weight on the frequency of use to determine a device for replacing the hub device **1002**. For example, the hub device **1002** may first select one or more devices having a large frequency of use from among the at least one hub device candidate, and then may determine a device having a shortest utterance processing time from among the selected one or more devices.

[0377] However, the disclosure is not limited thereto, and the hub device **1002** may first select one or more devices requiring an utterance processing time less than a preset threshold time from among the at least one hub device candidate, and then may determine a device having a largest frequency of use from among the selected one or more devices.

[0378] In operation **S1430**, the hub device **1002** changes a hub device by replacing the device used as the current hub device **1002** with the determined device.

[0379] In operation **S1520**, when the frequency of use of the current hub device is greater than the largest value from among the frequency of use of the at least one hub device candidate (operation **S1440**), the device used as the current hub device **1002** is maintained as a hub device. Likewise, in operation **S1540**, when the utterance processing time of the current hub device **1002** is equal to or less than the smallest value from among the utterance processing time of the at least one hub device candidate (operation **S1440**), the device used as the current hub device **1002** is maintained as a hub device. When the frequency of use of the device used as the current hub device **1002** is greater than

a frequency of use of another device and the utterance processing time of the device used as the current hub device **1002** is less than an utterance processing time of the device, a hub device does not need to be changed, and thus the device used as the hub device **1002** is maintained.

[0380] FIG. **16** is a flowchart of an operating method of the hub device **1002** according to an embodiment.

[0381] Operations **S1610** through **S1690** of FIG. **16** are operations performed between operations **S610** and **S620** of FIG. **6**. Operation **S1610** is the same as operation **S610** of FIG. **6**. After operations **S1630**, **S1652**, **S1680**, and **S1682** are performed, operation **S620** is performed.

[0382] In operation **S1610**, the hub device **1002** receives device information of a new device registered according to a user account from the IoT server **3000** (see FIG. **4**). The new device refers to a device that is newly obtained by a user of the hub device **1002** through purchase or ownership transfer, and is registered in the IoT server **3000** by being logged in by using the same user account as that of the hub device **1002**. The device information of the new device received by the hub device **1002** may include at least one of, for example, identification information (e.g., device id information) of the new device, a device type of the new device, function execution capability information of the new device, or position information. In an embodiment, the hub device **1000** may receive state information about power on/off of the new device or an operation that is being currently executed.

[0383] The hub device **1002** may receive the device information of the new device from the IoT server **3000**. However, the disclosure is not limited thereto, and the hub device **1002** may receive the device information of the new device from the voice assistant server **2000** (see FIG. **2**).

[0384] In operation **S1620**, the hub device **1002** determines whether there exists a hub device from among a plurality of devices that are pre-registered by using the user account. In an embodiment, the hub device **1002** may be determined by the voice assistant server **2000** (see FIG. **3**) based on resource state information of the plurality of devices pre-registered in the IoT server **3000** according to the same user account as the user account logged into the hub device **1002**. In an embodiment, the hub device may be a device including the device determination model **1340** (see FIG. **2**) from among the plurality of devices and capable of determining an operation-performing device by interpreting a voice input received from the user.

[0385] When it is determined that there does not exist a hub device from among the plurality of devices (operation **S1630**), the new device is determined as the hub device **1002**.

[0386] When it is determined that there exists the hub device **1002** from among the plurality of devices (operation **S1640**), the hub device **1002** selects a hub device candidate based on constant power supply, computing power, and a power consumption amount from among the plurality of devices pre-registered by using the user account. In an embodiment, the hub device **1002** may determine one or more hub device candidates from among the plurality of devices. Operation **S1640** is the same as operation **S1410** of FIG. **14**, and thus a repeated explanation will be omitted.

[0387] In operation **S1650**, the hub device **1002** determines whether a voice input for requesting to change the hub device is received from the user. For example, when a device used as the current hub device **1002** is a TV, the hub device **1002** may receive a voice input for requesting to change a hub device such as “change the air conditioner as a hub device”. However, the disclosure is not limited to reception of a voice input, and the hub device **1002** may receive, from the user, an input through a manipulation device such as a mouse or a keyboard or a touch input which changes a hub device by replacing the device used as the current hub device **1002** as the new device.

[0388] When the voice input for requesting to change the hub device is received (operation **S1652**), the hub device **1002** determines a device for replacing the hub device **1002** based on the received voice input. The hub device **1002** may convert the voice input into text, may identify a name or a type of the device intended by the user by interpreting the text by using an NLU model, and may determine the identified device as a device for replacing the hub device **1002**. In an embodiment, the processor **1200** (see FIG. **13**) of the hub device **1002** may convert the received voice input into

the text by using data or program code about the ASR module **1310** (see FIG. **13**), may parse the text in units of words or phrases by using data or the program code about the first NLU model **1342** (see FIG. **13**), may recognize a word or a phrase specifying a name of the device, a common name, or an installation position of a device, and may identify the device from the recognized word or phrase. The hub device **1002** may determine the identified device as the device for replacing the hub device **1002**.

[0389] When the voice input for requesting to change the hub device is not received from the user (operation **S1660**), the hub device **1002** obtains information about an utterance processing time of each of the hub device **1002** and at least one hub device candidate by analyzing the device performance history database **1384** (see FIG. **13**).

[0390] In operation **S1670**, the hub device **1002** determines whether the utterance processing time of the current hub device **1002** is greater than a smallest value from among the utterance processing time of the at least one hub device candidate by comparing an utterance processing time of the device used as the current hub device **1002** with the smallest value from among the utterance processing time of the at least one hub device candidate.

[0391] Operations **S1660** and **S1670** are respectively the same as operations **S1530** and **S1540** of FIG. **15**, and thus a repeated explanation will be omitted.

[0392] When the utterance processing time of the device used as the current hub device **1002** is equal to or less than the smallest value from among the utterance processing time of the at least one hub device candidate (operation **S1680**), the device used as the current hub device **1002** is determined as the hub device **1002**.

[0393] When it is determined that the utterance processing time of the device used as the current hub device **1002** is greater than the smallest value from among the utterance processing time of the at least one hub device candidate (operation **S1682**), the hub device **1002** determines a device for replacing the hub device **1002** based on information about the utterance processing time of the at least one hub device candidate. In an embodiment, the hub device **1002** may determine a device having a shortest utterance processing time from among the at least one hub device candidate as the device for replacing the hub device **1002**.

[0394] In operation **S620**, the determined hub device **1002** request the voice assistant server **2000** to update the device determination model **1340** (see FIG. **13**) stored in the hub device **1002**.

[0395] FIG. **17** is a diagram of a network environment including the hub device **1000**, the plurality of devices **4000**, and the voice assistant server **2000** according to an embodiment.

[0396] Referring to FIG. **17**, the hub device **1000**, the plurality of devices **4000**, the voice assistant server **2000**, and the IoT server **3000** may be connected by using a wired or wireless communication method, and may perform communication. In an embodiment, the hub device **1000** and the plurality of devices **4000** may be directly connected to each other through a communication network, but the disclosure is not limited thereto.

[0397] The hub device **1000** and the plurality of devices **4000** may be connected to the voice assistant server **2000**, and the hub device **1000** may be connected to the plurality of devices **4000** through a server. Also, the hub device **1000** and the plurality of devices **4000** may be connected to the IoT server **3000**. In another embodiment, each of the hub device **1000** and the plurality of devices **4000** may be connected to the voice assistant server **2000** through a communication network, and may be connected to the IoT server **3000** through the voice assistant server **2000**. In another embodiment, the hub device **1000** may be connected to the plurality of devices **4000**, and the hub device **1000** may be connected to the plurality of devices **4000** through one or more nearby access points. Also, the hub device **1000** may be connected to the plurality of devices **4000** in a state where the hub device **1000** is connected to the voice assistant server **2000** or the IoT server **3000**.

[0398] The hub device **1000**, the plurality of devices **4000**, the voice assistant server **2000**, and the IoT server **3000** may be connected through a local area network (LAN), a wide area network

(WAN), a value-added network (VAN), a mobile radio communication network, a satellite communication network, or a combination thereof. Examples of the wireless communication method may include, but are not limited to, Wi-Fi, Bluetooth, Bluetooth low energy (BLE), Zigbee, Wi-Fi Direct (WFD), Ultra-wideband (UWB), Infrared Data Association (IrDA), and Near-Field Communication (NFC).

[0399] In an embodiment, the hub device **1000** may receive a voice input of a user. At least one of the plurality of devices **4000** may be a target device that receives a control command of the voice assistant server **2000** and/or the IoT server **3000** and performs a specific operation. At least one of the plurality of devices **4000** may be controlled to perform a specific operation based on the voice input of the user received by the hub device **1000**. In an embodiment, at least one of the plurality of devices **4000** may receive a control command from the hub device **1000**, without receiving a control command from the voice assistant server **2000** and/or the IoT server **3000**.

[0400] The hub device **1000** may receive a voice input (e.g., an utterance) from the user. In an embodiment, the hub device **1000** may include an ASR model. In an embodiment, the hub device **1000** may include an ASR model having a limited function. For example, the hub device **1000** may include an ASR model having a function of detecting a designated voice input (e.g., a wake-up input such as 'Hi, Bixby' or 'OK, Google') or a function of pre-processing a voice signal obtained from part of a voice input. Although the hub device **1000** is an AI speaker in FIG. 17, the disclosure is not limited thereto. In an embodiment, one of the plurality of devices **4000** may be the hub device **1000**. Also, the hub device **1000** may include a first NLU model, a second NLU model, and an NLG model. In this case, the hub device **1000** may receive a voice input of the user through a microphone, or may receive a voice input of the user from at least one of the plurality of devices **4000**. When a voice input of the user is received, the hub device **1000** may process the voice input of the user by using the ASR model, the first NLU model, the second NLU model, and the NLG model, and may provide a response to the voice input of the user.

[0401] The hub device **1000** may determine a type of the target device for performing an operation intended by the user, based on the received voice signal. The hub device **1000** may receive a voice signal that is an analog signal, and may convert a voice part into computer-readable text by performing automatic speech recognition (ASR). The hub device **1000** may interpret the text by using a first NLU model and may determine the target device based on an interpretation result. The hub device **1000** may determine at least one of the plurality of devices **4000** as the target device. The hub device **1000** may select a second NLU model corresponding to the determined target device from among a plurality of stored second NLU models. The hub device **1000** may determine an operation to be performed by the target device requested by the user by using the selected second NLU model. When it is determined that there is no second NLU model corresponding to the determined target device from among the plurality of stored second NLU models, the hub device **1000** may transmit at least part of the text to at least one of the plurality of devices **4000** or the voice assistant server **2000**. The hub device **1000** transmits information about the determined operation to the target device so that the determined target device executes the determined operation.

[0402] The hub device **1000** may receive information of the plurality of devices **4000** from the IoT server **3000**. The hub device **1000** may determine the target device by using the received information of the plurality of devices **4000**. Also, the hub device **1000** may control the target device to execute the determined operation, by using the IoT server **3000** as a relay server for transmitting the information about the determined operation.

[0403] The hub device **1000** may receive a voice input of the user through the microphone, and may transmit the received voice input to the voice assistant server **2000**. In an embodiment, the hub device **1000** may obtain a voice signal from the received voice input, and may transmit the voice signal to the voice assistant server **2000**.

[0404] In FIG. 17, the plurality of devices **4000** include, but are not limited to, the first device **4100**

that is an air conditioner, the second device **4200** that is a TV, the new device **4300** that is a washing machine, and a fourth device **4400** that is a refrigerator. For example, the plurality of devices **4000** may include at least one of a smartphone, a tablet personal computer (PC), a mobile phone, a video phone, an e-book reader, a desktop PC, a laptop PC, a netbook computer, a workstation, a server, a personal digital assistant (PDA), a portable multimedia player (PMP), an MP3 player, a mobile medical device, a camera, or a wearable device. In an embodiment, the plurality of devices **4000** may be home appliances. The home appliances may include at least one of a TV, a digital video disk (DVD) player, an audio device, a refrigerator, an air conditioner, a cleaner, an oven, a microwave oven, a washing machine, an air purifier, a set-top box, a home automation control panel, a security control panel, a game console, an electronic key, a camcorder, or an electronic picture frame.

[0405] The voice assistant server **2000** may determine a type of the target device for performing an operation intended by the user, based on the received voice signal. The voice assistant server **2000** may receive a voice signal that is an analog signal from the hub device **1000**, and may convert a voice part into computer-readable text by performing automatic speech recognition (ASR). The voice assistant server **2000** may interpret the text by using a first NLU model, and may determine the target device based on an interpretation result. Also, the voice assistant server **2000** may receive at least part of the text and information about the target device determined by the hub device **1000** from the hub device **1000**. In this case, the hub device **1000** converts the voice signal into text by using an ASR model and a first NLU model of the hub device **1000**, and determines the target device by interpreting the text. Also, the hub device **1000** transmits at least part of the text and information about the determined target device to the voice assistant server **2000**.

[0406] The voice assistant server **2000** may determine an operation to be performed by the target device requested by the user by using a second NLU model corresponding to the determined target device. The voice assistant server **2000** may receive information of the plurality of devices **4000** from the IoT server **3000**. The voice assistant server **2000** may determine the target device by using the received information of the plurality of devices **4000**. Also, the voice assistant server **2000** may control the target device to execute the determined operation by using the IoT server **3000** as a relay server for transmitting information about the determined operation. The IoT server **3000** may store the information about the plurality of devices **4000** that are connected through a network and are pre-registered. In an embodiment, the IoT server **3000** may store at least one of identification information (e.g., device id information) of the plurality of devices **4000**, a device type of each of the plurality of devices **4000**, or function execution capability information of each of the plurality of devices **4000**.

[0407] In an embodiment, the IoT server **3000** may store state information about power on/off of each of the plurality of devices **4000** or an operation that is being executed. The IoT server **3000** may transmit a control command for executing the determined operation to the target device from among the plurality of devices **4000**. The IoT server **3000** may receive the information about the determined target device and the information about the determined operation from the voice assistant server **2000**, and may transmit the control command to the target device based on the received information.

[0408] FIGS. **18A** and **18B** are diagrams of a voice assistant model **200** executable by the hub device **1000** and the voice assistant server **2000** according to an embodiment.

[0409] Referring to FIGS. **18A** and **18B**, the voice assistant model **200** is implemented as software. The voice assistant model **200** may be configured to determine a user's intention from a voice input of the user and control a target device related to the user's intention. When a device controlled through the voice assistant model **200** is added, the voice assistant model **200** may include a first assistant model **200a** configured to update an existing model to a new model through learning or the like and a second assistant model **200b** configured to add a model corresponding to the added device to the existing model.

[0410] The first assistant model **200a** is a model that determines the target device related to the user's intention by analyzing the voice input of the user. The first assistant model **200a** may include an ASR model **202**, an NLG model **204**, a first NLU model **300a**, and a device determination model **310**. In an embodiment, the device determination model **310** may include the first NLU model **300a**. In another embodiment, the device determination model **310** and the first NLU model **300a** may be configured as separate elements.

[0411] The device determination model **310** is a model for performing an operation of determining the target device by using an analysis result of the first NLU model **300a**. The device determination model **310** may include a plurality of detailed models, and one of the plurality of detailed models may be the first NLU model **300a**. The first NLU model **300a** or the device determination model **310** may be an AI model.

[0412] When a device controlled through the voice assistant model **200** is added, the first assistant model **200a** may update at least the device determination model **310** and the first NLU model **300a** through learning. The learning may refer to learning using both training data used to train an existing device determination model and a first NLU model and additional training data related to the added device. Also, the learning may refer to updating the device determination model and the first NLU model by using only the additional training data related to the added device.

[0413] The second assistant model **200b** that is a model specialized for a specific device is a model that determines an operation to be performed by the target device corresponding to the voice input of the user from among a plurality of operations performable by the specific device. In FIG. **18A**, the second assistant model **200b** may include a plurality of second NLU models **300b**, an NLG model **206**, and an action plan management module **210**. The plurality of second NLU models **300b** may respectively correspond to a plurality of different devices. The second NLU model, the NLG model, and the action plan management model may be models implemented through a rule-based system. In an embodiment, the second NLU model, the NLG model, and the action plan management model may be AI models. A plurality of second NLU models may be elements of a plurality of function determination models.

[0414] When a device controlled through the voice assistant model **200** is added, the second assistant model **200b** may be configured to add a second NLU model corresponding to the added device. That is, the second assistant model **200b** may further include a second NLU model corresponding to the added device in addition to the existing plurality of second NLU models **300b**. In this case, the second assistant model **200b** may be configured to select a second NLU model corresponding to the determined target device, from among the plurality of second NLU models including the added second NLU model, by using information about the target device determined through the first assistant model **200a**.

[0415] Referring to FIG. **18B**, the second assistant model **200b** may include a plurality of action plan management models and a plurality of NLG models. In FIG. **18B**, the plurality of second NLU models included in the second assistant model **200b** may respectively correspond to the second NLU models **300b** of FIG. **18A**, each of the plurality of NLG models included in the second assistant model **200b** may correspond to the NLG model **206** of FIG. **18A**, and each of the plurality of action plan management models included in the second assistant model **200b** may correspond to the action plan management model **210** of FIG. **18A**.

[0416] In FIG. **18B**, the plurality of action plan management models may be configured to respectively correspond to the plurality of second NLU models. Also, the plurality of NLG models may be configured to respectively correspond to the plurality of second NLU models. In another embodiment, one NLG model may be configured to correspond to the plurality of second NLU models, and one action plan management model may be configured to correspond to the plurality of second NLU models.

[0417] In FIG. **18B**, when a device controlled through the voice assistant model **200** is added, the second assistant model **200b** may be configured to add a second NLU model, an NLG model, and

an action plan management model corresponding to the added device.

[0418] In FIG. **18B**, when a device controlled through the voice assistant model **200** is added, the first NLU model **300a** may be configured to be updated to a new model through learning or the like. Also, when the device determination model **310** includes the first NLU model **300a**, the device determination model **310** may be configured so that an existing model is entirely updated to a new model through learning or the like when a device controlled through the voice assistant model **200** is added. The first NLU model **300a** or the device determination model **310** may be an AI model. The learning may refer to learning using both training data used to train an existing device determination model and a first NLU model and additional training data related to the added device. Also, the learning may refer to updating the device determination model and the first NLU model by using only the additional training data related to the added device.

[0419] In FIG. **18B**, when a device controlled through the voice assistant model **200** is added, the second assistant model **200b** may be updated by adding a second NLU model, an NLG model, and an action plan management model corresponding to the added device to an existing model. The second NLU model, the NLG model, and the action plan management model may be models implemented through a rule-based system.

[0420] In FIG. **18B**, the second NLU model, the NLG model, and the action plan management model may be AI models. The second NLU model, the NLG model, and the action plan management model may each be managed as one device according to a corresponding device. In this case, the second assistant model **200b** may include a plurality of second assistant models **200b-1**, **200b-2**, and **200b-3** respectively corresponding to a plurality of devices. For example, a second NLU model corresponding to a TV, an NLG model corresponding to the TV, and an action plan management model corresponding to the TV may be managed as the second assistant model **200b-1** corresponding to the TV. Also, a second NLU model corresponding to a speaker, an NLG model corresponding to the speaker, and an action plan management model corresponding to the speaker may be managed as the second assistant model **200b-2** corresponding to the speaker. Also, a second NLU model corresponding to a refrigerator, an NLG model corresponding to the refrigerator, and an action plan management model corresponding to the refrigerator may be managed as the second assistant model **200b-3** corresponding to the refrigerator.

[0421] When a device controlled through the voice assistant model **200** is added, the second assistant model **200b** may be configured to add a second assistant model corresponding to the added device. That is, the second assistant model **200b** may further include the second assistant model corresponding to the added device in addition to the existing plurality of second assistant models **200b-1** through **200b-3**. In this case, the second assistant model **200b** may be configured to select a second assistant model corresponding to the determined target device, from among the plurality of second assistant models including the second assistant model corresponding to the added device, by using information about the target device determined by the first assistant model **200a**.

[0422] A program executed by the hub device **1000**, the voice assistant server **2000**, and the plurality of devices **4000** according to the disclosure may be realized as hardware components, software components, and/or a combination of hardware components and software components. The program may be executed by any system capable of executing computer-readable instructions.

[0423] Software may include a computer program, code, instructions, or a combination of one or more thereof, and may configure a processing device to operate as required or separately or collectively command the processing device.

[0424] Software may be implemented in a computer program that includes instructions stored in a computer-readable storage medium. Computer-readable storage media may include, for example, magnetic storage media (e.g., ROM, RAM, floppy disks, hard disks, etc.) and optical reading media (e.g., compact disk (CD)-ROM, DVD, etc.). The computer-readable recording media may be distributed in computer systems connected in a network and may store and execute computer-

readable code in a distributed fashion. The media may be computer-readable, may be stored in a memory, and may be executed by a processor.

[0425] The computer-readable storage media may be provided in the form of non-transitory storage media. Here, 'non-transitory' means that the storage medium does not include a signal and is tangible, but does not distinguish whether data is stored semi-permanently or temporarily on the storage medium.

[0426] Further, the program according to the embodiments may be provided in a computer program product. The computer program product is a product purchasable between a seller and a purchaser.

[0427] The computer program product may include a software program and a computer-readable storage medium in which the software program is stored. For example, the computer program product may include a software program-type product (e.g., a downloadable application) electronically distributed by a manufacturer of a device or electronic markets (e.g., Google Play™ store, App Store, etc.). For electronic distribution, at least a portion of the software program may be stored in storage media or temporarily generated. In this case, the storage media may be a server of the manufacturer, a server of the electronic market, or a storage medium of a relay server temporarily storing the software program.

[0428] The computer program product may include a storage medium of a server or a storage medium of a device in a system including the server and the device. Alternatively, when there is a third device (e.g., a smartphone) connected with the server or the device for communication, the computer program product may include a storage medium of the third device. Alternatively, the computer program product may include a software program itself transmitted to the device or the third device from the server or to the device from the third device.

[0429] In this case, one of the server, the device, and the third device may perform a method according to the embodiments by executing the computer program product. Alternatively, at least two of the server, the device, and the third device may perform the method according to the embodiments in a distributed fashion by executing the computer program product.

[0430] For example, the server (e.g., an IoT server or a voice assistant server) may execute the computer program product stored in the server and control the device connected with the server for communication to perform the method according to the embodiments.

[0431] As another example, the third device may execute the computer program product and control the device connected to the third device for communication to perform the method according to the embodiments.

[0432] When the third device executes the computer program product, the third device may download the computer program product from the server and execute the downloaded computer program product. Alternatively, the third device may execute the computer program product provided in a free-loaded state and perform the method according to the embodiments.

[0433] Although the embodiments of the disclosure have been described by the limited embodiments of the disclosure and the drawings as described above, various modifications and variations are possible by one of ordinary skill in the art from the above description. For example, the described techniques may be performed in a different order from the described method, and/or elements of the described computer system, module, etc. may be combined or integrated in a different form from the described method, or may be replaced or substituted by other elements or equivalents to achieve appropriate results.

Claims

1. A hub device comprising: a communication interface; memory configured to store a program comprising one or more instructions; and at least one processor configured to execute the one or more instructions of the program stored in the memory to: receive, through the communication interface, from an Internet of Things (IoT) server, device information of at least one hub device

candidate from among a plurality of devices pre-registered in the IoT server according to a user account of a user, obtain use history information and performance information of each of the at least one hub device candidate based on the device information, determine a device candidate from among the at least one hub device candidate, based on the use history information and the performance information of each of the at least one hub device candidate, and determine the device candidate as a new hub device that is to perform operations of the hub device.

2. The hub device of claim 1, wherein the at least one processor is further configured to execute the one or more instructions to: obtain, by analyzing a use history log database stored in the memory, the use history information about a frequency of use of each of the hub device and the at least one hub device candidate, and determine whether to change the hub device to the determined new hub device based on the obtained use history information.

3. The hub device of claim 2, wherein the use history information comprises at least one of a frequency at which each of the hub device and the at least one hub device candidate is used by the user as a listener device, a frequency at which each of the hub device and the at least one hub device candidate is used as an operation-performing device, a recent use history in which each of the hub device and the at least one hub device candidate is used as the listener device, and a recent use history in which each of the hub device and the at least one hub device candidate is used as the operation-performing device.

4. The hub device of claim 2, wherein the at least one processor is further configured to execute the one or more instructions to: identify a frequency of use of each of the hub device and the at least one hub device candidate, compare the frequency of use of the hub device with a largest value from among the frequency of use of the at least one hub device candidate, and determine whether to change the hub device to the determined new device based on a result of the comparison.

5. The hub device of claim 1, wherein the at least one processor is further configured to execute the one or more instructions to: obtain, by analyzing a device performance history database stored in the memory, utterance processing time information of each of the hub device and the at least one hub device candidate, and determine whether to change the hub device to the determined new hub device based on the obtained utterance processing time information.

6. The hub device of claim 5, wherein the utterance processing time information comprises information about time between a first time point when an utterance of the user is received by each of the hub device and the at least one hub device candidate and a second time point when an operation executed by each of the hub device and the at least one hub device candidate is completed.

7. The hub device of claim 5, wherein the at least one processor is further configured to execute the one or more instructions to: identify, based on the utterance processing time information, an utterance processing time of the hub device and an utterance processing time of each of the at least one hub device candidate, compare the utterance processing time of the hub device with a smallest value from among the utterance processing time of each of the at least one hub device candidate, and determine whether to change the hub device to the determined new hub device based on a result of the comparison.

8. The hub device of claim 1, wherein the at least one processor is further configured to execute the one or more instructions to: select the at least one hub device candidate from among the plurality of devices pre-registered in the IoT server based on at least one of constancy of power supply, computing power, or a power consumption amount of each of the plurality of devices pre-registered in the IoT server.

9. The hub device of claim 1 further comprises: a user input interface configured to receive a user input of the user that selects a device from among the plurality of devices pre-registered in the IoT server according to the user account logged into the hub device, wherein the at least one processor is further configured to execute the one or more instructions to: determine the device determined by the user input received through the user input interface as the new hub device.

- 10.** The hub device of claim 1, wherein the at least one processor is further configured to execute the one or more instructions to change the hub device to the new hub device periodically according to a preset time interval.
- 11.** A method performed by a hub device, the method comprising: receiving, from an Internet of Things (IoT) server, device information of at least one hub device candidate from among a plurality of devices pre-registered in the IoT server according to a user account; obtaining use history information and performance information of each of the at least one hub device candidate based on the device information; determining a device candidate from among the at least one hub device candidate, based on the use history information and the performance information of each of the at least one hub device candidate; and determining the device candidate as a new hub device that is to perform operations of the hub device.
- 12.** The method of claim 11, wherein the obtaining of the use history information and the performance information of each of the at least one hub device candidate comprises obtaining, by analyzing a use history log database stored in the memory, the use history information about a frequency of use of each of the hub device and the at least one hub device candidate, and wherein the method further comprises: determining whether to change the hub device to the determined new hub device based on the obtained use history information.
- 13.** The method of claim 12, wherein the use history information comprises at least one of a frequency at which each of the hub device and the at least one hub device candidate is used by the user as a listener device, a frequency at which each of the hub device and the at least one hub device candidate is used as an operation-performing device, a recent use history in which each of the hub device and the at least one hub device candidate is used as the listener device, and a recent use history in which each of the hub device and the at least one hub device candidate is used as the operation-performing device.
- 14.** The method of claim 12, wherein the determining whether to change the hub device comprises: identifying a frequency of use of each of the hub device and the at least one hub device candidate; comparing the frequency of use of the hub device with a largest value from among the frequency of use of the at least one hub device candidate; and determining whether to change the hub device to the determined new hub device based on a result of the comparison.
- 15.** The method of claim 11, wherein the obtaining of the use history information and the performance information of each of the at least one hub device candidate comprises obtaining, by analyzing a device performance history database stored in the memory, utterance processing time information of each of the hub device and at least one hub device candidate, and wherein the method further comprises: determining whether to change the hub device the determined new hub device based on the obtained utterance processing time information.
- 16.** The method of claim 15, wherein the utterance processing time information comprises information about time between a first time point when an utterance of the user is received by each of the hub device and at least one hub device candidate and a second time point when an operation executed by each of the hub device and at least one hub device candidate is completed.
- 17.** The method of claim 15, wherein determining whether to change the hub device comprises: identifying, based on the utterance processing time information, an utterance processing time of the hub device and an utterance processing time of each of the at least one hub device candidate; comparing the utterance processing time of the hub device with a smallest value from among the utterance processing time of each of the at least one hub device candidate; and determining whether to change the hub device to the determined new hub device based on a result of the comparison.
- 18.** The method of claim 11 further comprises: selecting the at least one hub device candidate from among the plurality of devices pre-registered in the IoT server based on at least one of constancy of power supply, computing power, or a power consumption amount of each of the plurality of devices pre-registered in the IoT server.
- 19.** The method of claim 11 further comprises: receiving a user input of the user that selects device

from among the plurality of devices pre-registered in the IoT server according to the user account logged into the hub device; and determining the device determined by the user input received through the user input interface as the new hub device, changing the hub device to the determined new hub device by the user input.

20. A computer program product comprising a computer-readable storage medium, the computer-readable storage medium comprising instructions readable by a hub device to perform: receiving, from an Internet of Things (IoT) server, device information of at least one hub device candidate from among a plurality of devices pre-registered in the IoT server according to a user account; obtaining use history information and performance information of each of the at least one hub device candidate based on the device information; determining a device candidate from among the at least one hub device candidate, based on the use history information and the performance information of each of the at least one hub device candidate; and determining the device candidate as a new hub device that is to perform operations of the hub device.
