

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402919
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Artaki; Alexander et al.

Orthopedic derotation devices and methods of installation thereof

Abstract

Embodiments herein are generally directed to derotation systems, apparatuses, and components thereof that can be used in spinal derotation procedures, as well as methods of installation. The derotation systems may include a plurality of derotation towers and clamp members.

Inventors: Artaki; Alexander (Philadelphia, PA), Pham; Khiem (Chalfont, PA), Cahill; Doug (Lititz, PA), Lawson; Stephan (Philadelphia, PA), Zweizig; Michael (Fleetwood, PA), Leff; David (Philadelphia, PA), Ingahalikar; Aditya (Pune, IN)

Applicant: GLOBUS MEDICAL, INC. (Audubon, PA)

Family ID: 84489854

Assignee: Globus Medical, Inc. (Audubon, PA)

Appl. No.: 18/161972

Filed: January 31, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230172642 A1	Jun. 08, 2023

Related U.S. Application Data

continuation parent-doc US 16871362 20200511 US 11602379 child-doc US 18161972
continuation parent-doc US 16015770 20180622 US 10687867 20200323 child-doc US 16871362
continuation parent-doc US 15598572 20170518 US 10028771 20180724 child-doc US 16015770
continuation parent-doc US 14665273 20150323 US 9681899 20170620 child-doc US 15598572

Publication Classification

Int. Cl.: A61B17/70 (20060101)

U.S. Cl.:

CPC A61B17/7047 (20130101); A61B17/708 (20130101);

Field of Classification Search

CPC: A61B (17/7047); A61B (17/708)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5984865	12/1998	Farley et al.	N/A	N/A
6083225	12/1999	Winslow	N/A	N/A
D462245	12/2001	Friedman et al.	N/A	N/A
7794464	12/2009	Bridwell	N/A	N/A
7951168	12/2010	Chao et al.	N/A	N/A
7951175	12/2010	Chao	N/A	N/A
8007516	12/2010	Chao	N/A	N/A
8038699	12/2010	Cohen	N/A	N/A
8043343	12/2010	Miller et al.	N/A	N/A
8123751	12/2011	Shluzas	N/A	N/A
8162952	12/2011	Cohen	N/A	N/A
8221474	12/2011	Bridwell	N/A	N/A
8277453	12/2011	Kave	N/A	N/A
8353826	12/2012	Weiman	N/A	N/A
8465529	12/2012	Choi	N/A	N/A
8472944	12/2012	Shah	N/A	N/A
8491588	12/2012	Wall	N/A	N/A
8512343	12/2012	Dziedzic	N/A	N/A
8540718	12/2012	Dauster	N/A	N/A
8551141	12/2012	Gephart	N/A	N/A
8603094	12/2012	Walker	N/A	N/A
8608746	12/2012	Kolb	N/A	N/A
8679128	12/2013	Seelig	N/A	N/A
8709044	12/2013	Chao	N/A	N/A
8764756	12/2013	Jones	N/A	N/A
8845640	12/2013	McLean	N/A	N/A
8986349	12/2014	German	606/279	A61B 17/7037
10687867	12/2019	Artaki	N/A	A61B 17/7077
2006/0200132	12/2005	Chao	606/279	A61B 17/7077
2007/0213596	12/2006	Hamada	N/A	N/A
2008/0294206	12/2007	Choi	606/301	A61B 17/7077
2009/0124861	12/2008	Fetzer	N/A	N/A
2009/0228053	12/2008	Kolb et al.	N/A	N/A
2010/0113885	12/2009	McBride et al.	N/A	N/A
2010/0212460	12/2009	Buss	81/57.39	A61B 17/7091

2011/0077689	12/2010	Mickiewicz	N/A	N/A
2011/0196426	12/2010	Peukert et al.	N/A	N/A
2012/0029580	12/2011	Solitario, Jr.	606/86A	A61B 17/7002
2012/0035668	12/2011	Manninen	N/A	N/A
2012/0203279	12/2011	Walters	N/A	N/A
2013/0096624	12/2012	Di Lauro	606/279	A61B 17/7032
2013/0211453	12/2012	Lenke	N/A	N/A
2013/0245694	12/2012	Choi	N/A	N/A
2014/0039556	12/2013	Rutschmann	N/A	N/A
2014/0039567	12/2013	Hoefer	N/A	N/A
2014/0046372	12/2013	Ibrahim	N/A	N/A
2014/0100618	12/2013	Kolb	N/A	N/A
2014/0114354	12/2013	May	N/A	N/A
2014/0163617	12/2013	Boachie-Adjei	N/A	N/A
2014/0188182	12/2013	Chao et al.	N/A	N/A
2014/0194939	12/2013	Seelig	N/A	N/A
2014/0277170	12/2013	Barrett	N/A	N/A
2014/0316475	12/2013	Parikh	606/86A	A61B 17/7086

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2353530	12/2010	EP	N/A
2010527650	12/2009	JP	N/A
2011514830	12/2010	JP	N/A
2014534009	12/2013	JP	N/A

Primary Examiner: Plionis; Nicholas J

Background/Summary

REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of U.S. patent application Ser. No. 16/871,362, filed May 11, 2020 (published as U.S. Pat. Pub. No. 2021-0346063 and U.S. Pat. Pub. No. 2022-0401132), which is a continuation of U.S. patent application Ser. No. 16/015,770, filed on Jun. 22, 2018, now U.S. Pat. No. 10,687,867, which is a continuation of U.S. Ser. No. 15/598,572, filed May 18, 2017, now U.S. Pat. No. 10,028,771, which is a continuation application of U.S. Ser. No. 14/665,273, filed Mar. 23, 2015, now U.S. Pat. No. 9,681,899, all of which are hereby incorporated by reference in their entireties for all purposes.

FIELD OF THE INVENTION

(1) The present disclosure relates to orthopedic derotation devices and methods used to install these devices.

BACKGROUND OF THE INVENTION

(2) Many types of spinal irregularities can cause pain, limit range of motion, or injure the nervous system within the spinal column. These irregularities can result from, without limitation, trauma, tumor, disc degeneration, and disease. One general example of a spinal irregularity is an abnormal curvature of the spine, for example, as exhibited with scoliosis, kyphosis, and/or lordosis. Scoliosis, a side-to-side curvature of the spine, can affect the dimensions of an individual's chest area, thereby impacting performance of internal organs such as the lungs and heart.

(3) Treatment of irregular spinal curvatures can include, for example, reducing the severity and

preventing further progression of the irregularity through physical therapy, bracing, and/or surgery. Surgical procedures can include realigning or correcting the curvature of the spine and optionally placing one or more rods alongside thereof to maintain the alignment.

SUMMARY OF THE INVENTION

(4) Some embodiments herein are directed to a derotation system that can include first, second, and third derotation towers, wherein each derotation tower comprises a proximal derotation tube coupled to a distal engagement assembly that is configured to engage an anchor member; first and second clamp members, wherein each clamp member is configured to receive at least two derotation tubes; and a handle assembly configured to engage one of the clamp members; wherein the first clamp member is configured to couple the first and second derotation tubes along a first axis and the second clamp member is configured to couple the first and third derotation tubes along a second axis that is skewed relative to the first axis.

(5) Other embodiments herein are directed to a derotation system that can include a plurality of derotation towers, wherein each derotation tower comprises a derotation tube; a plurality of clamp members each having a longitudinal axis, wherein each clamp member is configured to engage at least two derotation tubes; and a handle assembly configured to engage one of the clamp members; wherein, when the clamp members are engaged with the derotation tubes, the longitudinal axes of at least two clamp members are skewed.

(6) Yet other embodiments herein are directed to a derotation kit that can include a plurality of derotation towers, wherein each derotation tower comprises a proximal derotation tube; a plurality of clamp members, wherein each clamp member is configured to engage at least two derotation tubes; a plurality of handle assemblies, wherein each handle assembly is configured to engage a clamp member; and a plurality of countertorque devices, wherein each countertorque device is configured to engage at least one derotation apparatus.

(7) Some embodiments herein are directed to a method of installing a derotation system that can include engaging a plurality of derotation towers with a plurality of anchor members, wherein each derotation tower comprises a proximal derotation tube coupled to a distal engagement assembly; clamping a first clamp member around a first group of at least two derotation tubes along a first axis; clamping a second clamp member around a second group of at least two derotation tubes along a second axis, wherein the second axis is skewed relative to the first axis; coupling a handle assembly to one of the first and second clamp members; and applying force to the handle assembly to adjust a position of at least one derotation tower.

(8) Other embodiments herein are directed to a method of installing a derotation system that can include engaging a plurality of derotation towers with a plurality of anchor members to thereby push at least one elongate rod into engagement with the anchor members, wherein each derotation tower comprises a proximal derotation tube coupled to a distal engagement assembly; clamping a first clamp member around a first group of at least two derotation tubes along a first axis; clamping a second clamp member around a second group of at least two derotation tubes along a second axis, wherein the second axis is skewed relative to the first axis; coupling a handle assembly to one of the first and second clamp members; and applying force to the handle assembly to adjust a position of at least one derotation tower.

(9) Still other embodiments herein are directed to a method of installing a derotation system that can include providing a plurality of anchor members and a plurality of derotation towers; engaging each derotation tower with a different anchor member; clamping each derotation tower to at least two other derotation towers along first and second axes that are skewed relative to each other; and applying force to the system to adjust a position thereof.

(10) Further areas of applicability of the present disclosure will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating certain embodiments, are intended for purposes of illustration only and are not intended to limit the scope of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present disclosure will become more fully understood from the detailed description and the accompanying drawings, wherein:
- (2) FIG. 1 illustrates a perspective view of a derotation system as described herein;
- (3) FIG. 2 illustrates a perspective view of a derotation tube and a distal engagement assembly as described herein;
- (4) FIG. 3 illustrates a perspective view of a clamp member and three derotation towers as described herein;
- (5) FIGS. 4A-B illustrate perspective views of derotation towers as described herein;
- (6) FIG. 4C illustrates a cross-sectional view of the locking mechanism of the derotation tower illustrated in FIG. 4B;
- (7) FIG. 5A illustrates a perspective view of a derotation tower that includes a rod reducer assembly as described herein;
- (8) FIG. 5B illustrates the coupling mechanism of components of the rod reducer assembly illustrated in FIG. 5A;
- (9) FIGS. 5C-D illustrate perspective views of derotation towers that each include a rod reducer assembly as described herein;
- (10) FIG. 6A illustrates a perspective view of a clamp member as described herein;
- (11) FIGS. 6B-D illustrate perspective views of a clamp member transitioning from an unlocked to a locked configuration as described herein;
- (12) FIG. 7 illustrates a perspective view of a handle assembly coupled to a clamp member and a countertorque device coupled to a derotation tower as described herein;
- (13) FIG. 8 illustrates a handle assembly as described herein;
- (14) FIG. 9 illustrates a countertorque device as described herein; and
- (15) FIG. 10 illustrates a perspective view of an alternative clamp member.

DETAILED DESCRIPTION

(16) In some procedures to treat irregular spinal curvatures, a surgeon or other user may attach bone anchors to select vertebrae of the spine. A rod can be inserted through the bone anchors to adjust or maintain the relative positions of the vertebrae, thereby promoting correction of the curvature. A mechanical force can be used to deliver the rod to the bone anchors in a process that may be referred to as reduction. In some instances, a locking member, such as a set screw or locking cap, can be coupled with the bone anchor to retain the rod therein. In addition to adjusting for curvature, the angular rotation of one or more vertebrae relative to other vertebrae can be adjusted. This process can involve rotating the anchors and/or rods via tube members and can be referred to as derotation. Accordingly, described herein are derotation systems and components thereof that can be advantageously used to manipulate and/or adjust the rotational angle of one or more vertebrae.

(17) Components of all of the systems and devices disclosed herein can be made of materials known to those skilled in the art, including metals (e.g., titanium), metal alloys (e.g., stainless steel, titanium alloys, and/or cobalt-chromium alloys), ceramics, polymers (e.g., poly ether ether ketone (PEEK), polyphenylene sulfone (PPSU), polysulfone (PSU), polycarbonate (PC), polyetherimide (PEI), polypropylene (PP), polyacetals, or mixtures or co-polymers thereof), allograft, and/or combinations thereof. In some embodiments, the systems and devices may include radiolucent and/or radiopaque materials. In some embodiments, the systems and devices may be formed of silicone rubber. In other embodiments, one or more components may be coated with a bone growth-enhancing material, such as hydroxyapatite. The components can also be machined and/or manufactured using techniques known to those skilled in the art. For example, polymeric

components may be injection-molded or blow-molded.

(18) Embodiments herein are directed to derotation systems that can include one or more derotation towers and/or clamp members. The clamp members may be configured to couple, clamp, and/or link the derotation towers together to form the derotation system. In some embodiments, the derotation systems can additionally include one or more handle assemblies and/or countertorque devices. Advantageously, those skilled in the art may appreciate that the derotation systems of the present disclosure may include any combination of any embodiments of derotation towers, clamp members, handle assemblies, and/or countertorque devices described herein. The derotation systems may be configured to adjust the curvature and/or rotation of a patient's spine in a derotation procedure, as described herein. In some embodiments, the derotation systems may also be configured to reduce a rod, e.g., to push a rod into engagement with an anchor member, such as a tulip head or pedicle screw. The derotation towers may advantageously be cannulated to allow passage of a fastener, such as a set screw or locking cap, therethrough. In use, after the spine is derotated, the fastener may be passed through the derotation tower to couple with an anchor member, thereby securing the anchor member to a rod and/or at a particular angle.

(19) The derotation towers described herein can each include a proximal derotation tube coupled to and/or extending from a distal engagement assembly. The derotation tube can include a longitudinal axis and a variable (e.g., angled, non-smooth, abrasive, roughened, increased-friction, coarse, grainy, sandblasted, knurled, texturized, bumpy, ridged, toothed, and/or irregular) transverse (e.g., circumferential) outer surface thereabout. The derotation tube can include a cannula extending entirely therethrough along the longitudinal axis thereof. The longitudinal axis can be a straight or curved line. The distal engagement assembly can be configured to engage an anchor member (e.g., a bone anchor such as a pedicle screw or hook, alone or in combination with a housing, such as a tulip head, and/or an elongate rod). The systems disclosed herein can include a plurality of derotation towers, e.g., 2, 3, 4, 5, 6, 7, 8, or more towers. In some embodiments, the systems disclosed herein can include at least first, second, and third derotation towers.

(20) Turning now to FIG. 1, some embodiments herein are directed to a derotation system **100** that can include one or more derotation towers, such as derotation tower **2**, and one or more clamp members, such as clamp member **4**. As illustrated in FIG. 2, derotation tower **2** can include a proximal derotation tube **6** and a distal engagement assembly **8**. The proximal derotation tube **6** can include a longitudinal axis **9** and a variable transverse outer surface thereabout. As illustrated in FIG. 2, the derotation tube **6** can include a plurality of angled surfaces **10**. In some embodiments, the derotation tube **6** can include six angled surfaces (e.g., can include a hexagonal outer surface or transverse outer cross-section). In other embodiments, the derotation tube **6** can include 3, 4, 5, 6, 7, 8 or more angled surfaces. In some embodiments, the derotation tube **6** can include first and second rotatable members **12**, **14**. The first and second rotatable members **12**, **14** can be positioned in series along the longitudinal axis **9**. Each of the first and second rotatable members **12**, **14** can include a variable outer surface. For example, each of the first and second rotatable members **12**, **14** can include a hexagonal outer surface or transverse outer cross-section. The first and second rotatable members **12**, **14** may be advantageously configured to rotate relative to each other. In some embodiments, the derotation tube **6** can further include a locking member configured to lock the rotational orientation of the first and/or second rotatable members **12**, **14**. Advantageously, the first and second rotatable members **12**, **14** can be configured to each couple to a clamp member along a different axis, as illustrated in FIG. 1. Each rotatable member **12**, **14** can be rotated individually to adjust and/or accommodate the orientation of the clamp member.

(21) An alternative embodiment of a proximal derotation tube is proximal derotation tube **16**, illustrated in FIG. 3. Derotation tube **16** can include a longitudinal axis **18** and a variable transverse outer surface thereabout. In these embodiments, derotation tube **16** may be a unitary (e.g., one-piece) tube. As illustrated in FIG. 3, at least a section of the variable transverse outer surface of the derotation tube **16** can include roughening and/or texturizing (e.g., knurling). In some

embodiments, derotation tube **16** may be referred to as a knurled tube.

(22) In some embodiments, the proximal derotation tube and the distal engagement assembly, or a component thereof, may form a unitary body. In other embodiments, the proximal derotation tube may be reversibly or irreversibly coupled to the distal engagement assembly. For example, in some embodiments the proximal derotation tube may be welded to the distal engagement assembly. In other embodiments, the proximal derotation tube may be clipped, threaded, snapped, bolted, and/or otherwise coupled to the distal engagement assembly. In embodiments where the distal engagement assembly includes two or more components (e.g., an inner sheath and an outer sheath), the proximal derotation tube may be coupled with any of the components.

(23) One embodiment of a distal engagement assembly, distal engagement assembly **20**, is illustrated in FIG. **4A**. The distal engagement assembly **20** can include an outer sleeve **22** slideably disposed over an inner sleeve **24**. The inner sleeve **24** can include a distal end **26** configured to engage an anchor member **28**. As illustrated in FIG. **4A**, the distal end **26** of the inner sleeve **24** can include two tips **30**, **32** separated by a longitudinal slot **34**. Each tip **30**, **32** may also include a beveled protrusion (not shown) extending radially outwards and that may be configured to engage an inner surface of the outer sleeve **22**.

(24) The outer sleeve **22** may include a channel **38** at a proximal end having an enlarged proximal opening **34** and an enlarged distal opening **36**. The proximal opening **34** and the distal opening **36** may each have a width that is greater than that of an intermediate portion **35** therebetween. For example, the channel **38** may be generally “I”-shaped. As illustrated in FIG. **4A**, the channel **38** may pass entirely through the outer sleeve **22** in a transverse direction. In some embodiments, the proximal end of the outer sleeve **22** may also include one, two, or more flat exterior sections. In some embodiments, the outer sleeve **22** can include two parallel flat exterior sections (e.g., two parallel walls). The flat exterior sections may be configured to couple with one or more installation tools, such as a countertorque device, described further herein.

(25) The distal engagement assembly **20** can also include an actuator **40**. Actuator **40** may be coupled to a stop **42**. The stop **42** may be sized to fit within the enlarged proximal and distal openings **34**, **36**, but not within the intermediate portion **35**. In use, when the actuator **40** is depressed, the distal engagement assembly **20** may transition between an unlocked position and a locked position, wherein in the locked position the distal engagement assembly **20** is coupled (e.g., secured) to and/or engaged with the anchor member **28**. In the locked position, illustrated in FIG. **4A**, the stop **42** may be positioned within the proximal opening **34** and the outer sleeve **22** may engage the beveled protrusion (not shown) on each tip **30**, **32**. In this position, the outer sleeve **22** may be applying a radial force on the beveled protrusions, causing the slot **34** to compress, bringing the tips **30**, **32** together to clamp the anchor member **28** therebetween. To transition to the unlocked position, e.g., to disengage the distal engagement assembly **20** from the anchor member **28**, the actuator **40** may be depressed (e.g., squeezed), disengaging the stop **42** from the proximal opening **34**. The outer sleeve **22** may then be translated proximally until the beveled protrusions are uncovered and the stop **42** is aligned with the distal opening **36**. The actuator **40** may then be released to allow the stop **42** to be retained within the distal opening **36**. To transition to the locked position, e.g., to engage the distal engagement assembly **20** with the anchor member **28**, the actuator **40** may be depressed (e.g., squeezed), disengaging the stop **42** from the distal opening **36**. The outer sleeve **22** may then be translated distally until the beveled protrusions are covered and the stop **42** is aligned with the proximal opening **34**. The actuator **40** may then be released to allow the stop **42** to be retained within the proximal opening **34**.

(26) Another embodiment of a distal engagement assembly, distal engagement assembly **44**, is illustrated in FIGS. **4B-C**. The distal engagement assembly **44** can include an outer sleeve **46** slideably disposed over an inner sleeve **48**. The inner sleeve **48** can include a distal end **50** configured to engage an anchor member (not shown). As illustrated in FIG. **4B**, the distal end **50** of the inner sleeve **48** can include two tips **52**, **54** separated by a longitudinal slot **56**. Each tip **52**, **54**

may also include a protrusion **58, 60** extending radially outwards and that may be configured to engage an inner surface of the outer sleeve **46**. The inner sleeve **48** may also include a proximal end **62**, illustrated in FIG. **4C**. The proximal end **62** may include a circumferential groove **64** on an outer surface thereof. The circumferential groove **64** may be configured to receive a retaining ring **66** therein. As illustrated in FIG. **4C**, the retaining ring **66** may be configured to be disposed between the inner sleeve **48** and the outer sleeve **46**. In some embodiments, the retaining ring **66** may be compressible and/or compliant.

(27) The outer sleeve **46** may include a distal end **68** and a proximal end **70**, as illustrated in FIGS. **4B-C**. The distal end **68** may be configured to engage the protrusions **58, 60** of the inner sleeve **48**. The proximal end **70** may include a distal circumferential groove **72** and a proximal circumferential groove **74**, both extending along an inner surface thereof. As illustrated in FIG. **4B**, the proximal end **70** may also include at least one or more concave gripping surfaces **76, 78**. Each concave gripping surface **76, 78** may include an engagement or friction-increasing feature, such as ridges, teeth, knurling, and/or sandblasting. In some embodiments, the proximal end **70** may also include one, two, or more flat exterior sections. In some embodiments, the proximal end **70** can include two parallel flat exterior sections (e.g., two parallel walls). The flat exterior sections may be configured to couple with one or more installation tools, such as a countertorque device, described further herein.

(28) In use, the distal engagement assembly **44** may transition between an unlocked position and a locked position, wherein in the locked position the distal engagement assembly **44** is coupled (e.g., secured) to and/or engaged with an anchor member (not shown). Although not illustrated, those skilled in the art may appreciate that an anchor member (e.g., a bone screw engaged with a housing and/or a rod) may be positioned between the tips **52, 54** prior to transitioning the distal engagement assembly from the unlocked position to the locked position. In the unlocked position, illustrated in FIG. **4B-C**, the protrusions **58, 60** at the distal end **50** of the inner sleeve **48** may be exposed (e.g., not engaged with the outer sleeve **46**). Additionally, the retaining ring **66** may rest within the groove **64** on the proximal end **62** of the inner sleeve **48** and the distal groove **72** on the proximal end **70** of the outer sleeve **46**. In some embodiments, the groove can be circumferential or rectangular. The retaining ring **66** may inhibit the outer sleeve **46** from translating axially. To transition to the locked position, e.g., to engage the distal engagement assembly **44** with the anchor member, a user may grasp the concave gripping surfaces **76, 78** and translate or slide the outer sleeve **46** distally. The retaining ring **66** may be pushed and/or compressed into the circumferential groove **64**, allowing the outer sleeve **46** to translate or slide. The outer sleeve **46** may continue to translate distally until the retaining ring **66** is aligned with the proximal groove **74** and the distal end **68** of the outer sleeve **46** has engaged the protrusions **58, 60**. When the retaining ring **66** is aligned with the proximal groove **74**, it may move and/or expand into the proximal groove **74**, thereby inhibiting the outer sleeve **46** from translating axially. In this position, the distal end **68** of the outer sleeve **46** may be applying a radial force on the protrusions **58, 60**, causing the slot **56** to compress, bringing the tips **52, 54** together to clamp the anchor member (not shown) therebetween.

(29) In some embodiments, the distal engagement assembly may include a rod reducer assembly which be configured to reduce a rod engaged with an anchor member (e.g., may be configured to urge a rod towards the anchor member or portion thereof). Some embodiments may include rod reducer assembly **80**, illustrated in FIG. **5A**. Rod reducer assembly **80** may include a connector member **82** and a clip reducer **84** configured to be reversibly coupled with the connector member **82**. The rod reducer assembly **80** may also include a threaded driver (not shown).

(30) The connector member **82** may be a generally tubular body having a cannula extending longitudinally therethrough. The connector member **82** may include a proximal end **83** that is coupled to the derotation tube **16**. The proximal end **83** may also include a collar **96**. The collar **96** may be generally cylindrical with two flat exterior sections **94, 95** (e.g., two parallel walls). The flat exterior sections **94, 95** may be configured to couple with one or more installation tools, such

as a countertorque device, described further herein. The connector member **82** may include a first cantilevered tab **86** and a symmetrical second cantilevered tab **88** on an opposite side of the connector member **82**, as illustrated in FIG. 5B. The tabs may protrude radially outward from an outer surface of the connector member **82** as well as inward from an inner surface thereof. As illustrated in FIG. 5A, rod reducer assembly **80** may also include a handle member **90** having a cannula extending longitudinally therethrough and two arms **92**, **93** extending transversely therefrom. The connector member **82** may be received within the cannula of the handle member **90**. The handle member **90** may have an inner surface configured to engage an outer surface of the tabs **86**, **88**. The handle member **90** may be coupled to the proximal end **83** of the connector member **82** by a spring member **97**, such as a compression spring.

(31) The clip reducer **84** may be cannulated and may include a distal end **98** configured to engage anchor member **28**. As illustrated in FIG. 5A, the distal end **98** can include two tips **104**, **106** separated by a longitudinal slot **108**. The clip reducer **84** may be configured to receive the anchor member **28** between the two tips **104**, **106**. Each tip **104**, **106** may also include a protrusion (not shown) extending radially outwards and that may be configured to engage an inner surface of a reduction member **102**. The reduction member **102** may be slideably engaged with the clip reducer **84**. The reduction member **102** may be a tubular member having a cannula extending therethrough, and may include a distally-extending tip **110**. In some embodiments, the reduction member **102** may be generally chevron- or V-shaped when viewed from a side. The tip **110** may include a partially-circular (e.g., concave) cut-out configured to engage, nest, or abut a cylindrical rod. The clip reducer **84** may be received within the cannula of the reduction member **102**. The reduction member **102** may be configured to slide longitudinally (e.g., distally and/or proximally) along the clip reducer **84**. The clip reducer **84** may also include a proximal end **112**, as illustrated in FIG. 5B. The proximal end **112** may include depressions or recesses **114**, **116** that can be configured to receive at least a portion of tabs **86**, **88** therein. The rod reducer assembly **80** may further include an elongate threaded driver (not shown). The driver may be configured to engage and/or actuate the reduction member **102**.

(32) In use, the connector member **82** may be coupled with the clip reducer **84** as follows. The arms **92**, **93** of the handle member **90** may be grasped and the handle member **90** pulled proximally towards the collar **96** to compress the spring member **97** and release the tabs **86**, **88**. The proximal end **112** of the clip reducer **84** may be inserted into a distal end of the connector member **82** until the recesses **114**, **116** are aligned with the tabs **86**, **88**. The arms **92** of the handle member **90** may then be released, thereby releasing the spring member **96** and causing the handle **90** to return to its distal position. The inner surface of the handle **90** may engage the tabs **86**, **88**, pushing them radially inwards and into the recesses **114**, **116**. The handle **90** may retain the tabs **86**, **88** within the recesses **114**, **116** and may thereby inhibit the connector member **82** from disengaging from the clip reducer **84**.

(33) To engage rod reducer assembly **80** with an anchor member, the distal end **98** of the clip reducer **84** may be positioned or placed around at least a portion of the anchor member **28**. The clip reducer **84** may be placed around anchor member **28** before or after coupling with the connector member **82**. Although not illustrated in FIG. 5A, those skilled in the art may appreciate that, in use, anchor member **28** may include an elongate rod resting in the U-shaped opening thereof. To reduce the rod, e.g., to urge the rod into closer and/or secure engagement with the anchor member **28**, the threaded driver or screw may be threaded through the clip reducer **84**. Rotation of the threaded driver, which is in engagement with the reduction member **102**, can cause the reduction member **102** to translate distally. As the reduction member **102** translates distally, it may apply a radial force on the tips **104**, **106**, compressing the slot **108** and causing the tips **104**, **106** to clamp the anchor member **28** therebetween. The threaded driver may urge the reduction member **102** to translate distally until it abuts the elongate rod (not shown) and urges or pushes the elongate rod into engagement with the anchor member **28**.

(34) FIG. 5C illustrates another embodiment of a rod reducer assembly. Rod reducer assembly **118** may include a clip reducer **120** and a threaded driver **122**. The clip reducer **120** can include a proximal end **124** and a distal end **126**. The clip reducer **120** may be coupled to derotation tube **16** at the proximal end **124**. The proximal end **124** may also include one, two, or more flat exterior sections **138**. In some embodiments, the proximal end **124** can include two parallel flat exterior sections (e.g., two parallel walls). The flat exterior sections **138** may be configured to couple with one or more installation tools, such as a countertorque device, described further herein. The distal end **126** may include two tips **128**, **130** separated by a longitudinal slot **132**. The rod reducer assembly **118** may also include a reduction member **134** that is slideably engaged with the clip reducer **120**. The reduction member **134** may be a tubular member having a cannula extending therethrough, and may include a distally-extending tip **136**. In some embodiments, the reduction member **134** may be generally chevron- or V-shaped when viewed from a side. The tip **136** may include a partially-circular (e.g., concave) cut-out configured to engage or abut a cylindrical rod. The clip reducer **120** may be received within the cannula of the reduction member **134**. The reduction member **134** may be configured to translate or slide longitudinally (e.g., distally and/or proximally) along the clip reducer **120**.

(35) The threaded driver **122** may be configured to be received within the cannula of the clip reducer **120** and may be configured to engage the reduction member **134**. To engage rod reducer assembly **118** with an anchor member, the distal end **126** or a portion thereof may be placed or positioned around an anchor member. In use, the tips **128**, **130** may be placed around an anchor member that may include, for example, a housing and a fastener (e.g., a pedicle screw or hook) therein. An elongate rod may also be placed or positioned at or within the housing. To reduce the rod, e.g., to urge the rod into closer engagement with the anchor member, the threaded driver **122** may be inserted (e.g., threaded) through the clip reducer **120** from a proximal end of the derotation tube **16** and into engagement with the reduction member **134**. The threaded driver **122** may actuate the reduction member **134**, causing it to translate distally. As the reduction member **134** translates distally, it may apply a radial force on the tips **128**, **130**, compressing the slot **132** and causing the tips **128**, **130** to clamp the anchor member therebetween. The threaded driver **122** may urge the reduction member **134** to translate distally until it abuts the elongate rod (not shown) and urges or pushes the elongate rod into engagement with the anchor member.

(36) FIG. 5D illustrates another embodiment of a rod reduction assembly. Rod reduction assembly **140** can include an inner sleeve **142**, an outer sleeve **144**, and a rotatable handle **146**. The inner sleeve **142** may include a proximal end **148** and a distal end **150**. The proximal end **148** may be configured to couple with derotation tube **16**. The inner sleeve **142** may be configured to engage anchor member **28**. In some embodiments, the distal end **150** can include two or more tips **152**, **154** (e.g., four or more) separated by a longitudinal slot **156**. The inner sleeve **142** may be configured to receive the anchor member **28** between the two tips **152**, **154**. Each tip **152**, **154** may also include a protrusion (not shown) extending radially outwards and that may be configured to engage an inner surface of the outer sleeve **144**.

(37) The outer sleeve **144** may be slideably disposed over the inner sleeve **142** and may be configured to reduce an elongate rod (not shown). The outer sleeve **144** may include a proximal end **158** and a distal end **160**. The distal end **160** may include a distal tip **162** having a partially-circular (e.g., concave) cut-out configured to engage, nest, or abut a cylindrical rod. The proximal end **158** may include one, two, or more flat exterior sections. In some embodiments, the proximal end **158** can include two parallel flat exterior sections (e.g., two parallel walls). The flat exterior sections may be configured to couple with one or more installation tools, such as a countertorque device, described further herein. The proximal end **158** may be engaged or coupled with the rotatable handle **146**. The rotatable handle **146** may be configured to actuate the outer sleeve **144**.

(38) To engage rod reducer assembly **140** with anchor member **28**, the distal end **150** or a portion thereof may be placed or positioned around the anchor member **28**. In use, the tips **152**, **154** may be

placed around anchor member **28** (e.g., a tulip head or other housing). Although not illustrated in FIG. 5D, those skilled in the art may appreciate that, in use, anchor member **28** may include an elongate rod resting in the U-shaped opening thereof. To reduce the rod, e.g., to urge the rod into closer and/or secure engagement with the anchor member **28**, the rotatable handle **146** may be rotated (e.g., threaded onto the inner sleeve **142**) to actuate the outer sleeve **144**, thereby urging and/or pushing the outer sleeve **144** in a distal direction. As the outer sleeve **144** translates distally, it may apply a radial force on the tips **152**, **154**, compressing the slot **156** and causing the tips **152**, **154** to clamp the anchor member **28** therebetween. The rotatable handle **146** may continue to rotate, urging the outer sleeve **144** to translate distally until it abuts the elongate rod (not shown) and urges or pushes the elongate rod into engagement with the anchor member **28**.

(39) The derotation systems disclosed herein may also include first, second, or more clamp members. In some embodiments, each clamp member may be configured to engage, couple, and/or receive (e.g., clamp) at least two derotation towers or portions thereof (e.g., proximal derotation tube and/or distal engagement assembly). For example, each clamp member may be configured to engage, couple, and/or receive (e.g., clamp) at least two derotation tubes. Thus, the derotation systems described herein may include a plurality of clamp members and derotation tubes. Any combination of embodiments of clamp members, derotation towers, and/or derotation tubes may be used in the derotation systems described herein. In some embodiments that include a plurality of (e.g., two or more) clamp members engaged with a plurality of derotation tubes, the longitudinal axes of at least two clamp members may be skewed (e.g., the longitudinal axes would intersect if in the same plane). In some embodiments, the derotation system can include at least three (e.g., first, second, and third) derotation towers and at least two (e.g., first and second) clamp members. In these embodiments, the first clamp member may be configured to couple two (e.g., first and second) derotation tubes along a first axis and the second clamp member may be configured to couple two (e.g., first and third) derotation tubes along a second axis, wherein the second axis is skewed relative to the first axis (e.g., the first and second axes would intersect if in the same plane). In other embodiments, the clamp members may be configured to engage each derotation tower in the system with at least a first adjacent derotation tower along a first axis and at least a second adjacent derotation tower along a second axis, wherein the second axis is skewed relative to the first axis. One such example is illustrated in FIG. 1.

(40) FIG. 6A illustrates one embodiment of a clamp member. Clamp member **164** can include a first elongate arm **166** and a second elongate arm **168**. The first elongate arm **166** can be coupled to an actuator assembly **170** and the second elongate arm can include a receiving portion **172** extending therefrom. Clamp member **164** can also include a first end **174** and a second end **188**, wherein the first and second arms **166**, **168** may be coupled together at the first end **174**. Clamp member **164** may include a longitudinal axis that extends between the first and second ends **174**, **188**.

(41) The first arm **166** can include an inner surface **184** and an outer surface **186**, wherein the inner surface **184** is closer to the second arm **168** and the outer surface **186** is farther from the second arm **168**. As illustrated in FIG. 6A, the term “inner surface” can refer to a surface attached to the first arm **166**, as well as to the direct surface of the first arm **166**. The inner surface **184** can advantageously include a retaining (e.g., friction-increasing) feature. In some embodiments, the inner surface **184** may include a variable surface feature, and may be, for example, angled, non-smooth, abrasive, roughened, increased-friction, coarse, grainy, sandblasted, knurled, texturized, bumpy, ridged, toothed, and/or irregular. As illustrated in FIG. 6A, the retaining feature of the inner surface **184** can include knurling. In other embodiments, the retaining feature may be soft, compressive, and/or compliant. For example, the retaining feature may be a polymeric (e.g., silicone) surface. In yet other embodiments, the retaining feature can include a scalloped surface, e.g., a plurality of indentations, wherein each indentation is configured to nest a portion of a derotation apparatus therein. The second arm **168** can also have an inner surface having some or all

of the same features as the inner surface **184**. As illustrated with respect to the second arm **168**, in some embodiments the outer surface of either or both arms can include a plurality of curved depressions or indentations **192**.

(42) The first and second elongate arms **166**, **168** may be pivotably coupled at the first end **174** of the clamp member **164**. The first and second elongate arms **166**, **168** may also be coupled to a spring member, such as a cantilever or torsion spring, at the first end **174**. Thus, in use, when the arms **166**, **168** are pulled apart and subsequently released, the spring member may pull the arms **166**, **168** back towards each other.

(43) The receiving portion **172** can include a receptacle **176** therein. At least a portion of the actuator assembly **170** may be configured to be reversibly received within the receptacle **176**. In some embodiments, the receptacle **176** can be open on one side and can be, for example, a U-shaped channel or opening. In other embodiments, the receptacle may be a forked opening (e.g., may include two tines defining a channel therebetween). In yet other embodiments, the receptacle can include a tapered opening, e.g., such that the width of the opening of the receptacle is less than the diameter of the receptacle. In some embodiments, the receptacle **176** may have a constant diameter or width as measured longitudinally from the inner surface to the outer surface of the second arm **168**. For example, the receptacle **176** may generally have the shape of a cylindrical segment. In other embodiments, the receptacle **176** may have a variable diameter or width. For example, the receptacle **176** may be tapered (e.g., conical or frustoconical). In some embodiments, the receptacle **176** can include a countersink configured to nest a portion of the actuator assembly **170** (e.g., head member **182**) therein.

(44) The actuator assembly **170** can include a threaded rod **178** and a threaded nut **180**. The threaded nut **180** can be generally cylindrical and can include a threaded passageway configured to mate with the threaded rod **178**. In some embodiments, the threaded nut **180** can include a gripping surface. For example, as illustrated in FIG. 6A, the threaded nut **180** can be texturized and can include a plurality of alternating ridges and valleys. In some embodiments, the threaded nut **180** can be coupled to a head member **182**. The head member **182** can be configured to be received (e.g., locked) within the receptacle **176**. The head member **182** may be configured to rotate within the receptacle **176**.

(45) In some embodiments, the head member **182** may be distal to the threaded nut **180**, as illustrated in FIG. 6A. In other embodiments, for example, as illustrated in FIG. 1, clamp member **165** may include a threaded nut **181** that is distal to the head member **183**. Those skilled in the art may appreciate that, except as otherwise described herein, clamp member **165** may include the same features as clamp member **164**. FIG. 10 shows an alternative embodiment of an assembly whereby the threaded nut **180** is positioned on an outer surface of the actuator assembly **170**.

(46) In some embodiments, the actuator assembly **170** may be pivotably coupled to the first elongate arm **166**, for example, at the second end **188** of the clamp member **164**. The actuator assembly **170** may be configured to pivot about a pin **190**, and in some embodiments, may be configured to pivot by approximately 90 degrees relative to the first elongate arm **166**. The actuator assembly **170** may be configured to pivot between a closed position and an open position. In the closed position, the actuator assembly **170** may be generally perpendicular to the first elongate arm **166**, and/or at least a portion of the actuator assembly **170** may be received within the receptacle **176**. In some embodiments, in the closed position, the threaded nut **180** may be configured to be received between the first and second elongate arms **166**, **168**. In other embodiments, for example, as illustrated in FIG. 1, when in the closed position, the threaded nut **181** may be configured to be outside of both the first and second elongate arms **167**, **169**. In the open position, the actuator assembly **170** may be generally parallel to the first elongate arm **166**. In some embodiments, the clamp member **164** may further include a spring member, such as a cantilever or torsion spring, that may be coupled to the first elongate arm **166** and the actuator assembly **170**. In use, when the actuator assembly **170** is pulled or urged to the open position and released, the spring member may

apply force on the actuator assembly **170** to pivot or return the actuator assembly **170** towards the closed position (e.g., towards the receptacle **176**, relative to the first elongate arm **166**).

(47) The clamp member **164** may be configured to clamp, couple, engage, and/or secure at least two derotation towers. In use, the clamp member **164** may be pulled open by pivoting the actuator assembly **170** to the open position and pulling, urging, and/or pivoting the first and second arms **166**, **168** apart. The clamp member **164** may then be placed around at least two derotation towers (e.g., around two or more proximal derotation tubes). For example, the at least two derotation tubes may be placed between the first and second arms **166**, **168**. Advantageously, the retaining surfaces on the derotation tubes and/or inner surfaces of the first and second arms **166**, **168** may retain or increase friction between the members. The first and second arms **166**, **168** may be brought together and the actuator assembly **170** may be pivoted towards the receptacle **176** to the closed position, with at least a portion of the actuator assembly **170** (e.g., the head member **182**) inserted into and/or received within the receptacle **176**. The derotation towers may be clamped within the clamp member **164** by threading the nut **180** along the rod **178**. The head member **182**, which may be captured within the receptacle **176** of the second arm **168**, may urge the second arm **168** towards the first arm **166** to reduce a distance between the first and second arms **166**, **168** at the second end **188** of the clamp member **164**. The head member **182** may rest within a countersink of the receptacle **176**, thereby inhibiting the second arm **168** from being released.

(48) Turning to FIGS. **6B-D**, an alternative embodiment of a clamp member is illustrated. Clamp member **194** can include a first elongate arm **196** and a second elongate arm **198**. The first elongate arm **196** can be coupled to an actuator assembly **202** and the second elongate arm can include a receiving portion **204** extending therefrom. Clamp member **194** can also include a first end **206** and a second end **208**. The first and second arms **196**, **198** may be coupled together at the first end **206**, for example, by a hinge member **207**. Clamp member **194** may include a longitudinal axis that extends between the first and second ends **206**, **208**.

(49) The first arm **196** can include an inner surface **210** and an outer surface **212**, wherein the inner surface **210** is closer to the second arm **198** and the outer surface is farther from the second arm **198**. The term “inner surface” can refer to a surface attached to the first arm **196**, as well as to the direct surface of the first arm **196**. The inner surface **210** can advantageously include a retaining (e.g., friction-increasing) feature. In some embodiments, the inner surface **210** may include a variable surface feature, and may be, for example, angled, non-smooth, abrasive, roughened, increased-friction, coarse, grainy, sandblasted, knurled, texturized, bumpy, ridged, toothed, and/or irregular. In other embodiments, the retaining feature may be soft, compressive, and/or compliant. For example, the retaining feature may be a polymeric (e.g., silicone) surface. In yet other embodiments, the retaining feature can include a scalloped surface, e.g., a plurality of indentations, wherein each indentation is configured to nest a portion of a derotation apparatus therein, as illustrated in FIGS. **6B-D**. The second arm **198** can also have an inner surface having some or all of the same features as the inner surface **210**. In some embodiments, the outer surface of the first and/or second arms may also include a retaining feature. For example, in some embodiments the outer surface of either or both arms can include a plurality of curved depressions or indentations (not shown).

(50) The first and second elongate arms **196**, **198** may be pivotably coupled at the first end **202** of the clamp member **194**. The first and second elongate arms **196**, **198** may also be coupled to a spring member, such as a cantilever or torsion spring, at the first end **206**. Thus, in use, when the arms **196**, **198** are pulled apart and subsequently released, the spring member may pull the arms **196**, **198** back towards each other.

(51) As illustrated in FIGS. **6B-D**, the receiving portion **204** may extend at an oblique angle (e.g., greater than 90 degrees) relative to the second elongate arm **198**. In other embodiments, the receiving portion **204** may be perpendicular to the second elongate arm **198**. The receiving portion **204** can include a receptacle **214** therein. At least a portion of the actuator assembly **202** may be

configured to be reversibly received within the receptacle **214**. As illustrated in FIG. 6B, the receptacle **214** can be open on one side and can be, for example, a U-shaped channel or opening. In other embodiments, the receptacle may be a forked opening (e.g., may include two tines defining a channel therebetween). In yet other embodiments, the receptacle can include a tapered opening, e.g., such that the width of the opening of the receptacle is less than the diameter of the receptacle. In some embodiments, the receptacle **214** may have a constant diameter or width as measured longitudinally from the inner surface to the outer surface of the second arm **198**. In other embodiments, the receptacle **214** may have a variable diameter or width. For example, the receptacle **214** may be tapered (e.g., conical or frustoconical). In some embodiments, the receptacle **214** can include a countersink configured to nest a portion of the actuator assembly **202** (e.g., nut **218**) therein.

(52) The actuator assembly **202** can include a threaded rod **216** and a threaded nut **218**. The threaded nut **218** can be generally cylindrical and can include a threaded passageway configured to mate with the threaded rod **216**. In some embodiments, the threaded nut **218** can include a gripping surface, such as a plurality of alternating ridges and valleys. As illustrated in FIGS. 6B-D, the threaded nut **218** can include two gripping wings, and may be referred to as a wing nut. In some embodiments, the threaded nut **218** can be coupled to a head member (not shown), as described herein with respect to clamp member **164**.

(53) As illustrated in FIGS. 6B-D, the threaded rod **216** may be coupled (e.g., affixed, connected, and/or attached) to the first arm **196**. The threaded rod **216** may have an axis that is generally parallel to a length of the first arm **196**. The threaded rod **216** may have a length that is greater than a width of the second arm **198**. As described herein, the threaded rod **216** may be configured to be reversibly received within the receptacle **214** of the second arm **198**.

(54) The clamp member **194** may be configured to clamp, couple, engage, and/or secure at least two derotation towers. In use, the first and second arms **196**, **198** may be pulled, urged, and/or pivoted apart and placed around two or more derotation towers (e.g., around two or more proximal derotation tubes), as illustrated in FIG. 6B. For example, the at least two derotation tubes may be placed between the first and second arms **196**, **198**. Advantageously, the derotation tubes may nest within and/or against the scalloped features on the inner surfaces of the first and second arms **196**, **198**. The first and second arms **196**, **198** may be brought together so that the threaded rod **216** of the first arm **196** is received within the receptacle **214** of the second arm **198**, as illustrated in FIG. 6C. The derotation towers may be clamped within the clamp member **194** by threading the nut **218** along the rod **216** towards the first end **206** of the clamp member **194**, as illustrated in FIG. 6D. As the nut **218** moves along the rod **216**, it may exert pressure on the receiving portion **204**. In embodiments where the receiving portion **204** is obliquely angled, applying pressure on the receiving portion **204** may cause the second arm **198** to pivot towards the first arm **196**, thereby clamping the derotation towers therebetween and/or reducing a distance between the first and second arms **196**, **198** at the second end **208** of the clamp member **194**. The threaded nut **218** may nest within a countersink of the receptacle **214**, thereby inhibiting the second arm **198** from being released.

(55) Derotation systems described herein may also include a handle assembly **300**, as illustrated in FIGS. 7-8. The handle assembly **300** may be configured to engage or couple with any of the clamp members disclosed herein (e.g., clamp member **164**, clamp member **165**, and/or clamp member **194**). In some embodiments, the handle assembly **300** may be configured to engage or couple with a single clamp member. In use, the handle assembly **300** may be configured to transmit force to the spine through the derotation system as part of a derotation procedure. As illustrated in FIG. 8, the handle assembly **300** can include an elongate member **302** and a plate member **304**. The elongate member **302** may be rotatably coupled to (e.g., may be configured to rotate within) the plate member **304**. The elongate member can include a proximal handle-engaging portion **306**, a first leg **310**, and a cylindrical body **308** therebetween. The elongate member **302** may be configured to

rotate about longitudinal axis **312**. The handle-engaging portion **306** can include a circumferential, rounded groove **314** and/or an angled proximal head **316**. As illustrated in FIG. **8**, the angled proximal head **316** can include four beveled walls and can include, for example, a generally square or rectangular transverse cross-section. The handle-engaging portion **306** can be configured to couple with a handle **318**, as illustrated in FIG. **7**. In use, the handle **318** can be grasped by a user to apply force to the derotation system.

(56) As illustrated in FIG. **8**, the first leg can include an eccentrically-shaped member **320** and/or a distal lip **322** extending therefrom. The eccentrically-shaped member **320** may have a length, as measured along the longitudinal axis **312**, which is greater than or equal to a height of a clamp member. The eccentrically-shaped member **320** may have a transverse area that is greater than that of the cylindrical body **308** of the elongate member **302**. When viewed along the longitudinal axis **312**, the eccentrically-shaped member **320** may have an area that is not equally distributed around the longitudinal axis **312**. In some embodiments, the eccentrically-shaped member **320** may have a non-circular and/or non-symmetrical transverse cross-section. For example, the eccentrically-shaped member **320** may be elliptical, ovular, and/or egg-shaped. The eccentrically-shaped member **320** may be referred to herein as a cam member. The distal lip **322** may have a transverse area that is greater than that of the cylindrical body **308** and/or the eccentrically-shaped member **320**. When viewed along the longitudinal axis **312**, the distal lip **322** may have an area that is not equally distributed around the longitudinal axis **312**. Both the eccentrically-shaped member **320** and the distal lip **322** may extend radially beyond the cylindrical body **308** at some points along a circumference of the cylindrical body **308**. As illustrated in FIG. **8**, the elongate member **302** may generally include a first, unlocked section or portion **324** where the cylindrical body **308**, eccentrically-shaped member **320**, and lip **322** are aligned (e.g., flush), and a second, unlocked section or portion **326** where the cylindrical body **308**, eccentrically-shaped member **320**, and lip **322** are staggered (e.g., the eccentrically-shaped member **320** and the lip **322** may each extend radially outward relative to the cylindrical body **308**). The elongate member **302** may be configured to rotate between a locked and unlocked configuration. In the unlocked configuration, illustrated in FIG. **8**, the unlocked portion of the elongate member **302** may be facing inwards (e.g., towards the second leg **330**, described herein) and the locked portion may be facing outwards (e.g., away from the second leg **330**). In the locked configuration, the unlocked portion of the elongate member **302** may be facing outwards and the locked portion may be facing inwards.

(57) As illustrated in FIG. **8**, the plate member **304** can include a body **328** and a second leg **330**. The handle assembly **300** may be configured to receive a clamp member between the first and second legs **310**, **330**. The body **328** of the plate member **304** may be generally flat and/or planar. The body **328** may include a receptacle **332** configured to receive the elongate member **302** therethrough. The second leg **330** may extend perpendicularly or orthogonally from the plate member **304**. In some embodiments, the second leg **330** may be affixed or attached to the body **328**. In other embodiments, the plate member **304** may be a unitary structure. The second leg **330** may be cylindrical.

(58) In use, a clamp member may be positioned between the first and second legs **310**, **330** when the handle assembly **300** is in the unlocked configuration (e.g., the unlocked portion of the elongate member **302** is facing inwards). To couple the handle assembly **300** to the clamp member, the elongate member **302** may be rotated to the locked configuration. The portion of the eccentrically-shaped member **320** that extends radially beyond the cylindrical body **308** may rotate into engagement with the clamp member to secure it in a friction fit between the first and second legs **310**, **330**. Additionally, the portion of the lip **322** that extends radially beyond the cylindrical body **308** may rotate to a position below the clamp member, further securing the engagement between the clamp member and the handle assembly **300**.

(59) Derotation systems described herein may also include a countertorque device **400**, as illustrated in FIGS. **7** and **9**. The countertorque device **400** may be generally flat and/or planar. As

illustrated in FIG. 9, the countertorque device **400** can include an elongate body **402** having first and second prongs **404**, **406** extending distally therefrom. The first and second prongs **404**, **406** can define a channel or cavity **412** therebetween. The cavity **412** can include a curved section **408** and a linear, straight, and/or flat section **410**. As illustrated in FIG. 9, the linear section **410** may be distal to the curved section **408**. The cavity **412** can also include a mouth or opening **416** that may be wider than the curved and/or linear sections **408**, **410**, as measured between the first and second prongs **404**, **406**. A proximal section of the elongate body **402** may include an angular hole **414** passing from a top surface to a bottom surface thereof. As illustrated in FIG. 9, the angular hole **414** may have four walls and can be generally square or rectangular. In other embodiments, the angular hole may have a different number of walls, such as 3, 4, 5, 6, 7, or 8, and may be, for example, triangular, rectangular, pentagonal, hexagonal, heptagonal, or octagonal. The angular hole **414** may be configured to receive and engage the angular head **316** of the handle assembly **300**. In some embodiments, the elongate body **402** may be generally hollow. For example, as illustrated in FIG. 9, the elongate body **402** may include an elongate hole **418** passing from the top surface to the bottom surface thereof.

(60) In use, a derotation tower may be positioned between first and second prongs **404**, **406** and within in the cavity **412**, as illustrated in FIG. 7. The flat section **410** of the cavity may align with flat section(s) on the derotation towers. The countertorque device **400** may be grasped by a user to prevent a moment from being transferred to an overall construct and/or patient

(61) Some embodiments herein are directed to methods of installing the derotation towers and systems described herein. These methods can include providing a plurality of anchor members and derotation towers and/or engaging one or more derotation towers with one or more anchor members as described herein. In some embodiments, each derotation tower can be engaged with a separate and/or different anchor member (e.g., each anchor member may be engaged with only one derotation tower). Each derotation tower can include a proximal derotation tube (e.g., proximal derotation tube **6** or **16**) coupled to a distal engagement assembly (e.g., distal engagement assembly **8**, **20**, or **44**, or rod reducer assembly **80**, **118**, or **140**). As described herein, the anchor member can include an anchor or fastener, such as a pedicle screw or hook, and a housing, such as a tulip head. The anchor or fastener may be at least partially received within the housing. The anchor member may include an elongate rod associated therewith. For example, the elongate rod may be disposed within a channel on the housing. Each derotation tower may be engaged with a separate anchor member. In some embodiments, a plurality of derotation towers may be engaged with a plurality of anchor members.

(62) In some embodiments, one or more derotation towers can include a distal engagement assembly, such as distal engagement assembly **20** or **44**, as illustrated in FIGS. 4A-C. As described herein, these assemblies may include an outer sleeve (e.g., outer sleeve **22** or **46**) slideably disposed over an inner sleeve (e.g., inner sleeve **24** or **48**). As described herein, in these embodiments, the step of engaging the derotation tower with the anchor member can include positioning the inner sleeve around at least a portion of the anchor member (e.g., the housing) and translating the outer sleeve distally.

(63) In some embodiments, one or more derotation towers can include a distal engagement assembly that includes a rod reducer assembly, such as rod reducer assembly **80**, **118**, or **140**, as illustrated in FIGS. 5A-D. In these embodiments, the derotation tower may be configured to urge an elongate rod into engagement with an anchor member. For example, in embodiments where the anchor member includes a housing having a rod-receiving channel, the derotation tower may be configured to urge the elongate rod distally into the channel. In these embodiments, the step of engaging a plurality of derotation towers with a plurality of anchor members may include pushing or urging at least one elongate rod into engagement with the anchor members.

(64) In some embodiments, the derotation tower may include a distal engagement assembly that includes rod reducer assembly **80**, illustrated in FIGS. 5A-B. As described herein, in these

embodiments, the rod reducer assembly **80** may include a connector member **82**, a clip reducer **84** reversibly coupled with the connector member **82** and comprising a reduction member **102** and a distal end **98**, and a threaded driver. The step of engaging the derotation tower with an anchor member (e.g., anchor member **28**) can include positioning the distal end **98** around at least a portion of the anchor member (e.g., the housing) and threading the threaded driver through the clip reducer **84** to actuate the reduction member **102**.

(65) In some embodiments, the derotation tower may include a distal engagement assembly that includes rod reducer assembly **118**, illustrated in FIG. 5C. As described herein, in these embodiments, the rod reducer assembly **118** may include a clip reducer **120** and a threaded driver **122**. The clip reducer **120** can include a reduction member **134** and a distal end **126**. The step of engaging the derotation tower with an anchor member can include positioning the distal end **126** around at least a portion of the anchor member (e.g., the housing) and threading the threaded driver **122** through the clip reducer **120** to actuate the reduction member **134**.

(66) In some embodiments, the derotation tower may include a distal engagement assembly that include rod reducer assembly **140**, illustrated in FIG. 5D. As described herein, in these embodiments, the rod reducer assembly **140** may include an inner sleeve **142**, an outer sleeve **144** slideably disposed over the inner sleeve **142**, and a rotatable handle **146** configured to actuate the outer sleeve **144**. The step of engaging the derotation tower with an anchor member (e.g., anchor member **28**) can include positioning the distal end **150** around at least a portion of the anchor member (e.g., the housing) and rotating the rotatable handle **146** to actuate the outer sleeve **144**.

(67) Methods of installing the derotation systems described herein may also include placing, clamping, and/or securing a first clamp member around a first group of at least two derotation tubes (e.g., first and second derotation tubes) of at least two derotation towers (e.g., first and second derotation towers) along a first axis, to thereby couple together the derotation tubes. In some embodiments, the first axis may be a longitudinal axis or a latitudinal axis. In other embodiments, the first axis may be a medial-lateral or cephalad-caudal (e.g., superior-inferior) axis. Any combinations of the clamp members described herein, e.g., clamp member **164**, **165**, and/or **194**, can be used as the first clamp member in the derotation systems of the present disclosure. As described herein, the first clamp member may include a first elongate arm coupled to an actuator assembly and a second elongate arm having a receiving portion extending therefrom, wherein the actuator assembly includes a threaded rod and a threaded nut. The step of clamping the first clamp member around the first group of at least two derotation tubes can include opening the first clamp member by pivoting apart the first and second elongate arms, placing the first group of at least two derotation tubes between the first and second elongate arms, inserting at least a portion of the actuator assembly of the first arm into a receptacle in the receiving portion of the second arm, and threading the nut on the rod to reduce a distance between the first and second elongate arms at a second end of the first clamp member.

(68) Methods of installing the derotation systems described herein may also include placing, clamping, and/or securing a second clamp member around a second group of at least two derotation tubes (e.g., first and third derotation tubes) of at least two derotation towers (e.g., first and third derotation towers) along a second axis, to thereby couple together the derotation tubes. Any combinations of the clamp members described herein, e.g., clamp member **164**, **165**, and/or **194**, can be used as the second clamp member in the derotation systems of the present disclosure. The second clamp member can be placed, clamped, and/or secured around the second group of derotation tubes according to the method described herein of placing, clamping, and/or securing the first clamp member around the first group of derotation tubes. As illustrated in FIG. 1, a second clamp member may be positioned on a derotation tower distal to a first clamp member, or vice versa.

(69) In some embodiments, the second axis may be a longitudinal axis or a latitudinal axis. In other embodiments, the second axis may be a medial-lateral or cephalad-caudal (e.g., superior-inferior)

axis. Advantageously, the second axis may be skewed relative to the first axis (e.g., the first and second axes would intersect if in the same plane). For example, the first axis can be a longitudinal axis and the second axis can be a latitudinal axis, or vice versa. In another example, the first axis can be a medial-lateral axis and the second axis can be a cephalad-caudal axis, or vice versa. In some embodiments, if in the same plane, the first and second axes would be perpendicular and/or orthogonal.

(70) In some embodiments, one derotation tube (e.g., a single derotation tower), such as the first derotation tube, may be a member of both the first and second groups of derotation tubes. Thus, the first and second clamp members may overlap on the one derotation tube. Additionally, the one derotation tube may link the first and second groups together to assemble a derotation system, which may be referred to herein as a unified (e.g., interconnected) derotation system construct. In some embodiments, at least two or more derotation tubes (e.g., derotation towers) in the system can be coupled or clamped to at least two other derotation towers using at least two different clamp members. In some embodiments, each derotation tower in the system can be coupled or clamped to at least two other derotation towers along two different, skewed axes and using at least two different clamp members.

(71) Some embodiments can include clamping each derotation tower to at least two other derotation towers along first and second axes, respectively, for example, as illustrated in FIG. 1. For example, in a system including at least first, second, and third derotation towers, the first derotation tower can be coupled or clamped to the second derotation tower along the first axis, and can be coupled or clamped to the third derotation tower along the second axis. The first and second axes may be skewed relative to each other. In these embodiments, the step of clamping each derotation tower to at least two other derotation towers can include clamping at least two (e.g., first and second) clamp members around each derotation tower. The first clamp member may extend along the first axis and the second clamp member may extend along the second axis. In some embodiments, each derotation tower can be clamped to an adjacent ipsilateral derotation tower and an adjacent contralateral derotation tower. Thus, those skilled in the art may appreciate that the derotation systems of the present disclosure can include any number of derotation towers and/or clamp members. As illustrated in FIG. 1, for example, in some embodiments the derotation system can include eight derotation towers and six clamp members.

(72) In use, the derotation towers may be engaged with a plurality of anchor members along two sides of a patient's spine. Advantageously, each derotation tower may be clamped to at least one derotation tower on the same side of the spine (e.g., ipsilaterally) and at least one on the opposite side of the spine (e.g., contralaterally). In some embodiments, each derotation tower may be coupled or clamped to at least two other derotation towers along two different, skewed axes. Advantageously, this can provide the derotation system with stability, as compared to a system that may only allow coupling of some towers, for example, on a single side of the spine, and can thereby enable a user to effectively apply controlled force during a derotation procedure.

(73) Those skilled in the art may appreciate that the derotation towers and/or systems described herein may be used to treat a spinal irregularity, such as an irregular curvature (e.g., scoliosis), for example, in a derotation procedure. In a derotation procedure, a derotation system may be installed as described herein along a patient's spine adjacent to the spinal irregularity. As described herein, the system may include a plurality of derotation towers installed along both sides of the patient's spine and coupled together via clamp members either ipsilaterally and/or contralaterally. In some embodiments, the system can include a plurality of derotation towers coupled together with clamp members in both medial-lateral and cephalad-caudal directions.

(74) Methods described herein can optionally include coupling a handle assembly (e.g., handle assembly **300**) to one of the first and second clamp members (e.g., clamp member **164**, **165**, or **194**). As described herein, handle assembly **300** can include an elongate member **302** rotatably coupled to a plate member **304**, wherein the elongate member **302** can include a first leg **310** that

can include an eccentrically-shaped member **320** and/or a distal lip **322**. This step can include positioning the clamp member widthwise between the first and second legs **310**, **330** of the handle assembly **300**. For example, the first arm of the clamp member may be adjacent the first leg of the handle assembly and the second arm may be adjacent the second leg, or vice versa. In some embodiments, the clamp member, for example, as illustrated in FIG. **6A** with respect to clamp member **164**, can include a plurality of curved depressions or indentations **192**. In these embodiments, the first and second legs **310**, **330** of the handle assembly **300** may nest within these depressions or indentations **192**. Advantageously, this feature may encourage a secure engagement between these components. The step of coupling the handle assembly to the clamp member can also include locking and/or securing the handle assembly to the clamp member. This step can include rotating the first leg, for example, from an unlocked configuration to a locked configuration as described herein, to thereby engage the eccentrically-shaped member **320** with the clamp member. In embodiments that include distal lip **322**, the step of rotating the first leg **310** can also include rotating the distal lip **322** towards the second leg **330** and/or towards (e.g., under) the clamp member. The clamp member may thereby be retained, held, and/or positioned between the body **328** and the distal lip **322** of the handle assembly **300**.

(75) In some embodiments, a handle (e.g., handle **318**) can be coupled to the handle assembly **300**. In some embodiments, this step may be performed prior to coupling the handle assembly **300** to one of the clamp members. For example, this step may be performed prior to locking the handle assembly **300**, e.g., prior to rotating the first leg **310** from the unlocked configuration to the locked configuration. In these embodiments, the step of coupling the handle assembly **300** with the handle **318** can include inserting at least a portion of the proximal handle-engaging portion **306** into a socket in the handle. The handle **318** can be grasped by a user to apply force to the handle assembly **300**. Thus, the step of rotating the first leg **310** can include rotating or turning the handle **318** to apply torque to the first leg **310**. In some embodiments, the handle assembly **300** and the handle **318** can be connected or coupled via a quick-connect coupling. In other embodiments, the handle **318** can include a compressible member configured to be retained within the circumferential groove **314** on the proximal handle-engaging portion **306**.

(76) Methods herein can also include applying force to the handle assembly **300**, e.g., by applying force to the handle **316**, to adjust a position (e.g., angle and/or orientation) of at least one derotation tower. As the derotation tower may be coupled to an anchor member, this step can also include adjusting a position of the anchor member. Advantageously, because multiple (e.g., all) derotation towers may be coupled together in the derotation system, force applied to the handle assembly **300** may be distributed throughout the entire system to adjust a position thereof. In embodiments where each derotation tower is coupled to at least two different towers in two different directions, the derotation system may advantageously configured to sturdily receive and distribute force evenly therethrough. In a spinal derotation procedure, a user may apply force to the handle to adjust and/or correct the curvature and/or rotation of a patient's spine.

(77) Some methods may also include coupling and/or securing the anchor member (e.g., a pedicle screw and/or housing) with a fastener (e.g., a set screw or locking cap). In these embodiments, the fastener may be passed longitudinally and/or axially through the derotation tower to the anchor member. A countertorque device (e.g., countertorque device **400**) may be engaged with the derotation tower. For example, this may include positioning the derotation tower within the cavity **412** (e.g., between the first and second prongs **404**, **406**) of the countertorque device **400**. In embodiments where the derotation tower includes one or more flat exterior sections as described herein, this step can include aligning the flat exterior sections with the linear or straight section **410** of the cavity **412**. In embodiments where the derotation tower includes a flattened section having two parallel walls, this step can include aligning the two parallel walls with the linear or straight section **410** of the cavity **412**.

(78) Subsequently, an elongate driver may be passed longitudinally and/or axially through the

derotation tower to engage the fastener. Force may be applied to the driver while the countertorque device **400** is engaged with the derotation tower to couple the fastener member to the anchor member (e.g., to thread a set screw into a housing or tulip head). In some embodiments, an elongate rod may be associated with the anchor member. For example, an elongate rod may be disposed within a channel on a housing of the anchor member. In these embodiments, applying force to the driver, while the countertorque device **400** is engaged with the derotation tower, may also result in securing the anchor member to the elongate rod and/or securing an angle of the anchor member relative to the elongate rod. Those skilled in the art may appreciate that the countertorque device may advantageously allow the driver and fastener to rotate while preventing or inhibiting the derotation tower and/or anchor member from rotating.

(79) Some methods may also include disengaging the handle assembly **300** from the clamp member. This step can include placing the angled proximal head **316** of the handle assembly **300** into the angular hole **414** of the countertorque device **400** and applying force to the countertorque device to unlock the handle assembly **300** by rotating the eccentrically-shaped member **320** and/or distal lip **322** out of engagement with the clamp member (e.g., to rotate the eccentrically-shaped member **320** from the locked configuration to the unlocked configuration).

(80) Some embodiments herein are directed to a kit that can include any combination of the devices and components described herein. For example, some embodiments can include a plurality of derotation towers, a plurality of clamp members, a plurality of handle assemblies, and/or a plurality of countertorque devices. Multiple variants of derotation towers, clamp members, handle assemblies, and/or countertorque devices can also be included in a single kit. Furthermore, the kit can include a variety of different sizes of each device. The kit can additionally include one or more other devices, tools, and/or materials configured for use in conjunction with the derotation system or its components. For example, a kit may include one or more handles, fasteners (e.g., pedicle screws or hooks), housings (e.g., tulip heads), elongate rods, set screws, locking caps and/or drivers. In some embodiments, for example, where the kit does not include a derotation tower configured for rod reduction, the kit may additionally include a rod reducer. In other embodiments, the kit can include one or more additional instruments configured for use during the installation procedure, such as a probe, forceps, inserter, retractor, distractor, compressor, and/or rod bender. In yet other embodiments, the kit can include one or more additional implants, such as an intervertebral cage, plate, transverse rod connector, and/or bone graft material. In yet other embodiments, the systems described above can be used with various fusion devices (spacers, plates, rods) and prosthetic devices.

(81) The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims. Although individual embodiments are discussed herein, the invention covers all combinations of all those embodiments.

Claims

1. A method of derotation comprising: providing a derotation system, the derotation system including: first and second derotation towers, wherein each derotation tower comprises a proximal derotation tube coupled to a distal engagement assembly that is configured to engage an anchor member; a clamp member configured to receive the first and second derotation towers, the clamp member having an inner surface including an engagement feature, and the engagement feature is configured to engage an outer surface of the first or second derotation tower, wherein the engagement feature is a plurality of non-deformable, non-movable concave engagement surfaces positioned on the inner surface of the clamp member, and each of the plurality of engagement surfaces is configured to engage an outer surface of the first or second derotation tower, wherein

the clamp member includes a first elongate arm coupled to a threaded rod and a nut, the clamp member further including a second elongate arm having an obliquely angled receiving portion extending therefrom, wherein the first and second elongate arms are pivotably coupled at a first end of the clamp member, wherein when the threaded rod is received in the obliquely angled receiving portion and the nut is actuated the second elongate arm pivots toward the first elongate arm due to the obliquely angled receiving portion to clamp the first and second derotation towers; and a handle assembly configured to engage the clamp member, engaging the first derotation tower with a first anchor member; engaging the second derotation tower with a second anchor member; clamping the first and second derotation towers with the clamp member; and applying a force to adjust a position of at least one of the first and second derotation towers.

2. The method of claim 1, wherein each derotation tube comprises a longitudinal axis and a variable transverse outer surface thereabout.

3. The method of claim 2, wherein the variable transverse outer surface comprises a plurality of angled surfaces.

4. The method of claim 2, wherein at least one derotation tube comprises first and second rotatable members in series along the longitudinal axis.

5. The method of claim 2, wherein the variable transverse outer surface comprises a knurled surface.

6. The method of claim 1, wherein the distal engagement assembly comprises an outer sleeve slideably disposed over an inner sleeve, wherein the inner sleeve comprises a distal end configured to engage the anchor member.

7. The method of claim 6, wherein the outer sleeve comprises at least two concave gripping surfaces.

8. The method of claim 1, wherein the distal engagement assembly comprises a rod reducer assembly, wherein the rod reducer assembly is configured to reduce a rod engaged with the anchor member.

9. The method of claim 8, wherein the rod reducer assembly includes: a connector member; a clip reducer configured to be reversibly coupled with the connector member and comprising a reduction member and a distal end configured to engage the anchor member; and a threaded driver configured to actuate the reduction member.

10. The method of claim 8, wherein the rod reducer assembly includes: a clip reducer comprising a translatable reduction member and a distal end configured to engage the anchor member; and a threaded driver configured to actuate the reduction member.

11. The method of claim 8, wherein the rod reducer assembly includes an inner sleeve comprising a distal end configured to engage the anchor member; an outer sleeve slideably disposed over the inner sleeve and configured to reduce the rod; and a rotatable handle configured to actuate the outer sleeve.

12. The method of claim 1, wherein an inner surface of each of the first and second elongate arms comprises a retaining feature selected from the group consisting of a knurled surface, a polymeric surface, and a scalloped surface.

13. The method of claim 1, wherein an actuator assembly is pivotably coupled to the first elongate arm.

14. The method of claim 1, wherein the derotation system further includes a cantilever spring coupled to the first elongate arm and an actuator assembly.

15. A method of derotation comprising: providing a derotation system, the derotation system including: a plurality of derotation towers, wherein each derotation tower comprises a derotation tube; a plurality of clamp members each having a longitudinal axis, wherein each clamp member is configured to engage at least two derotation tubes, each clamp member having an inner surface including an engagement feature, and the engagement feature is configured to engage an outer surface of the plurality of derotation towers, wherein the engagement feature is a plurality of non-

deformable, non-movable concave engagement surfaces positioned on the inner surface of each clamp member, and each of the plurality of engagement surfaces is configured to engage an outer surface of one of the plurality of derotation tubes, wherein each clamp member includes a first elongate arm coupled to a threaded rod and a nut, each clamp member further including a second elongate arm having an obliquely angled receiving portion extending therefrom, wherein the first and second elongate arms are pivotably coupled at a first end of the each clamp member, wherein when the threaded rod is received in the obliquely angled receiving portion and the nut is actuated the second elongate arm pivots toward the first elongate arm due to the obliquely angled receiving portion to clamp the plurality of derotation towers; and a handle assembly configured to engage one of the plurality of clamp members, engaging each derotation tower with an anchor member; clamping each derotation tower with one of the plurality of clamp members; and applying a force to adjust a position of at least one of the plurality of derotation towers.

16. The method of claim 15, wherein the handle assembly comprises an elongate member rotatably coupled to a plate member, wherein: the elongate member comprises a proximal handle-engaging portion, a first leg, and a cylindrical body therebetween; and the plate member comprises a body and a second leg extending orthogonally therefrom.

17. The method of claim 16, wherein the handle assembly is configured to receive one of the clamp members between the first and second legs.

18. The method of claim 15, further comprising a counter-torque device comprising an elongate body having first and second prongs extending distally therefrom and defining a cavity therebetween, wherein the cavity comprises a curved section and a linear section.
