

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404921
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Palaskar; Ram et al.

Systems and devices for controlling sensing plate lash in a lock detection mechanism for electronic locking differentials

Abstract

The present disclosure relates to an electronic locking differential gear mechanism having a lock detection mechanism for sensing and indication of a locked and unlocked state of the locking mechanism. The electronic locking differential gear mechanism includes an electronic stator which, when activated, rotates a ramped collar about an axis of the mechanism. The ramps of the ramped collar axially displace a plurality of push rods, which displace a locking collar and cause it to engage with a locker gear, placing the mechanism in a locked state. A sensor assembly detects the displacement of a sensing plate which is displaced along with the push rods, and thereby senses whether the mechanism is in a locked or unlocked state. Anti-rotation lugs interact with a tab of the sensor assembly to prevent rotation of the sensing plate relative to other components.

Inventors:	Palaskar; Ram (Pune, IN), More; Prajwal (Pune, IN), Dube; Piyush (Nagpur, IN), Edler; Andrew N. (Homer, MI)
Applicant:	Eaton Intelligent Power Limited (Dublin, IE)
Family ID:	85037126
Assignee:	Eaton Intelligent Power Limited (Dublin, IE)
Appl. No.:	18/727444
Filed (or PCT Filed):	January 10, 2023
PCT No.:	PCT/EP2023/025003
PCT Pub. No.:	WO2023/131580
PCT Pub. Date:	July 13, 2023

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

IN 202211001214 Jan. 10, 2022

Publication Classification

Int. Cl.: F16H48/34 (20120101); F16H48/38 (20120101)

U.S. Cl.:

CPC F16H48/34 (20130101); F16H48/38 (20130101);

Field of Classification Search

CPC: F16H (48/34); F16H (48/24); F16H (2048/343); F16H (48/20-2048/346)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6966863	12/2004	Teraoka	475/154	H02K 7/108
7264568	12/2006	Ludwig	475/233	F16H 48/295
7572202	12/2008	Donofrio	475/233	F16H 48/24
7862462	12/2010	Fusegi	N/A	N/A
9556945	12/2016	Fox	N/A	F16H 48/22
9625026	12/2016	Cochren et al.	N/A	N/A
9657827	12/2016	Gopal et al.	N/A	N/A
9933060	12/2017	Cochren et al.	N/A	N/A
9989140	12/2017	Onitake	N/A	F16H 48/24
10036658	12/2017	Hernandez-Oliver	N/A	G01D 11/245
10215268	12/2018	Creech	N/A	G01D 5/147
10920866	12/2020	Gostin, Jr. et al.	N/A	N/A
11326679	12/2021	Borgaonkar et al.	N/A	N/A
11396935	12/2021	Allen	N/A	N/A
11867270	12/2023	Welling	N/A	F16H 48/40
2007/0197338	12/2006	Fusegi	N/A	N/A
2015/0133254	12/2014	Fox	N/A	N/A
2019/0226566	12/2018	Hillman et al.	N/A	N/A
2019/0383378	12/2018	Surve et al.	N/A	N/A
2020/0116245	12/2019	Fritz et al.	N/A	N/A
2021/0131542	12/2020	Allen	N/A	N/A
2024/0426372	12/2023	Palaskar	N/A	F16H 48/34

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
210003771	12/2019	CN	N/A
1 908 621	12/2007	EP	N/A
2004208460	12/2003	JP	N/A

2007/069042	12/2006	WO	N/A
2013/176866	12/2012	WO	N/A
2014/116802	12/2013	WO	N/A
2015/060890	12/2014	WO	N/A
2015/060890	12/2014	WO	N/A
2017/100550	12/2016	WO	N/A
2018/057437	12/2017	WO	N/A
2018/232262	12/2017	WO	N/A
2019/238272	12/2018	WO	N/A
2020/094252	12/2019	WO	N/A
2020/144090	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/EP2023/025003 mailed Mar. 24, 2023. cited by applicant

Primary Examiner: Estremsky; Sherry L

Attorney, Agent or Firm: Merchant & Gould P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

(1) This application is a National Stage Application of PCT/EP2023/025003, filed on Jan. 10, 2023, which claims priority to India Application No. 202211001214, titled SYSTEMS AND DEVICES FOR CONTROLLING SENSING PLATE LASH IN A LOCK DETECTION MECHANISM FOR ELECTRONIC LOCKING DIFFERENTIALS, filed on Jan. 10, 2022, the disclosure of which is hereby incorporated by reference in their entireties. To the extent appropriate, a claim of priority is made to each of the above disclosed applications.

BACKGROUND OF THE INVENTION

(2) Vehicle drivetrains may include differential mechanisms which include gear sets that allow torque to be applied differently to wheels of the same axle during operation of the vehicle. In some instances, it may be desired to include a locking mechanism in the differential so that all torque is delivered equally to both wheels of the axle. Locking differentials, including electronic locking differentials, are generally known in the art. For locking differentials, it may be desirable to have a detection structure on such mechanisms to determine the locking state of the differential and provide the locking state to the operator of a vehicle.

SUMMARY

(3) In some aspects, a locking mechanism is included in the differential mechanism so that all available torque is delivered equally to both wheels of the axle, locking both wheels in synchronous rotation with each other. A detection structure on such a locking mechanism to determine the locking state of the differential and provide the locking state to the operator of a vehicle may provide useful benefits to the driver, including ensuring that the locking mechanism is functioning properly, and monitoring vehicle performance and status for safe vehicle operations.

(4) Accordingly, the present application describes, in an example aspect, a differential assembly comprising a first housing; a first half-axle output; a second half-axle output; a power input location; a gear set; an electrically activated locking assembly; and a sensor assembly. In an aspect, the gear set is disposed within the first housing and operably connects the first half-axle output, the

second half-axle output, and the power input location together. In an aspect, the electrically activated locking assembly includes a second housing mounted to the first housing and is operable between a locked position, in which the first and second axle outputs are prevented from rotating relative to each other, and an unlocked position, in which the first and second half-axle outputs are enabled to rotate relative to each other. In an aspect, the sensor assembly includes a position sensing plate and a position sensor, the position sensing plate being coupled to the locking assembly such that operation of the locking assembly between the locked and unlocked positions causes axial movement of the position sensing plate and such that the position sensing plate is non-rotatable with respect to the second housing, and the position sensor is configured to measure an axial position of the position sensing plate.

(5) In an aspect, the locking assembly includes a stator mounted within the second housing, a rotatable ramped collar actuated by the stator, a plurality of push rods axially displaceable by rotation of the ramped collar, and a locking collar axially displaceable by movement of the plurality of push rods, where in the locked position, the locking collar is engaged with a locker gear of the gear set, and where in the unlocked position, the locking collar is disengaged with the locker gear.

(6) In an aspect, the ramped collar is located axially between the stator and the position sensing plate.

(7) In an aspect, the position sensing plate is secured to the plurality of push rods.

(8) In an aspect, one or more of the plurality of push rods includes a groove for receiving an edge portion of the position sensing plate. In an aspect, the edge portion defines a central aperture of the position sensing plate.

(9) In an aspect, the position sensing plate is secured to the plurality of push rods with one or more fasteners. In an aspect, the one or more fasteners are snap rings.

(10) In an aspect, the position sensing plate includes an axially extending tab and the position sensor is configured to sense movement of the axially extending tab.

(11) In an aspect, the sensor assembly includes a sensor target mounted to the axially extending tab.

(12) In an aspect, the position sensor is a magnetic-type position sensor that is spaced from the position sensing plate.

(13) In an example aspect, a lock detection mechanism for a differential assembly comprises a locking element of the differential assembly; one or more push rods displaceable along an axis of the differential assembly, connected at a first end to a locking collar of the locking element and in contact at a second end with a ramped collar; a position sensing plate axially displaceable along the axis, wherein the position sensing plate is displaceable by the one or more push rods; and a sensor assembly to detect a status of the locking element, wherein the sensor assembly detects a displacement of the position sensing plate. In an aspect, the locking element is operable between a locked state and an unlocked state. In an aspect, the ramped collar is rotatable about the axis. In an aspect, the ramped collar comprises one or more ramp valleys and one or more ramp peaks. In an aspect, the one or more push rods are displaceable by the one or more ramp valleys and one or more ramp peaks.

(14) In an aspect, the lock detection mechanism further comprises a sensor of the sensor assembly; and a tab of the sensor assembly. In an aspect, the tab is connected to the position sensing plate at a first end. In an aspect, the tab is displaceable by the position sensing plate along the axis. In an aspect, the tab is connected to a sensor target at a second end. In an aspect, a position of the sensor target is detectable by the sensor.

(15) In an aspect, the sensor is a magnetic-type position sensor that is spaced from the position sensing plate.

(16) In an aspect, the position sensing plate comprises a notch, and at least a portion of the tab fits within the notch.

(17) In an aspect, the position sensing plate comprises one or more recessed portions, and each of the one or more recessed portions receives a portion of one of the one or more push rods.

- (18) In an aspect, each of the one or more push rods includes a groove receiving the respective recessed portion of the position sensing plate and at least one snap-ring on at least one side of the position sensing plate.
- (19) In an aspect, the ramped collar is rotatable by an electronic actuator mechanism.
- (20) An example method of detecting a locked state of a differential assembly, comprises rotating, about an axis of a differential assembly, a ramped collar ramp plate; displacing a push rod along the axis (the push rod in contact with the ramped collar at a first end) by the rotation of the ramped collar; displacing a locking collar of a locking element along the axis by the displacement of the push rod, where the locking collar is connected to the push rod at a second end; displacing a position sensing plate along the axis, by the displacement of the push rod; and sensing, by a sensor assembly, an axial displacement of the position sensing plate.
- (21) In an aspect, the method further comprises displacing a tab along the axis, by the displacement of the position sensing plate, where the tab is connected at a first end to the position sensing plate; detecting a position of a second end of the tab by a sensor of the sensor assembly; and indicating a status of the locking element.
- (22) In an example aspect, a lock detection arrangement for a differential assembly comprises: a sensor assembly including a position sensing plate and a position sensor, the position sensing plate being configured for connection to a locking element of the differential assembly and axially displaceable with reference to the position sensor between a locked state of the locking element and an unlocked state of the locking element; and a pair of anti-rotation lugs between which a first tab structure of the position sensing plate extends, the pair of anti-rotation lugs preventing rotation of the position sensing plate.
- (23) In an aspect, the pair of anti-rotation lugs are parallel with each other.
- (24) In an aspect, the side surfaces of the first tab structure are parallel to the pair of anti-rotation lugs when the sensing plate is centered between the pair of anti-rotation lugs.
- (25) In an aspect, each of the pair of anti-rotation lugs has a cylindrical shape.
- (26) In an aspect, the lock detection arrangement further comprises: a second pair of anti-rotation lugs opposite the first pair of anti-rotation lugs; and a second tab structure opposite the first tab structure and extending between the second pair of anti-rotation lugs.
- (27) In an example aspect, a differential assembly comprises: a differential including a gear set disposed within a housing and operably coupling a power input location to a first half-axle output and a second half-axle output; an electrically activated locking assembly operable between a locked position, in which the first and second axle half-axle outputs are prevented from rotating relative to each other, and an unlocked position, in which the first and second half-axle outputs are enabled to rotate relative to each other; a sensor assembly including a position sensing plate and a position sensor, the position sensing plate being operably coupled to the locking assembly and axially displaceable with reference to the position sensor between the locked and unlocked positions of the locking assembly; and a pair of anti-rotation lugs between which a first tab structure of the position sensing plate extends, the pair of anti-rotation lugs preventing rotation of the position sensing plate.
- (28) In an aspect, the pair of anti-rotation lugs are parallel with each other.
- (29) In an aspect, the side surfaces of the first tab structure are parallel to the pair of anti-rotation lugs when the first tab structure is centered between the pair of anti-rotation lugs.
- (30) In an aspect, each of the pair of anti-rotation lugs has a cylindrical shape.
- (31) In an aspect, the differential assembly further comprises: a second pair of anti-rotation lugs opposite the first pair of anti-rotation lugs; and a second tab structure opposite the first tab structure and extending between the second pair of anti-rotation lugs.
- (32) This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Non-limiting and non-exhaustive examples are described with reference to the following Figures.
- (2) FIG. 1 illustrates a perspective view of an electronic locking differential gear mechanism, constructed in accordance with principles of this disclosure, according to an example.
- (3) FIG. 2 illustrates a perspective view of the electronic locking differential gear mechanism of FIG. 1, with a housing removed, according to an example.
- (4) FIG. 3 illustrates a left-side view of the electronic locking differential gear mechanism of FIG. 1, according to an example.
- (5) FIG. 4 illustrates a cross-sectional view of the electronic locking differential gear mechanism of FIG. 2, along the plane indicated in FIG. 3, according to an example.
- (6) FIG. 5 illustrates a front-perspective exploded view of the electronic locking differential gear mechanism of FIG. 2, according to an example.
- (7) FIG. 6 illustrates a rear-perspective exploded view of the electronic locking differential gear mechanism of FIG. 2, according to an example.
- (8) FIG. 7 illustrates a perspective view of a sensor assembly for an electronic locking differential gear mechanism, constructed in accordance with principles of this disclosure, according to an example.
- (9) FIG. 8 illustrates an exploded view of the sensor assembly of FIG. 7, according to an example.
- (10) FIG. 9 illustrates a side view of a sensing plate for the sensor assembly of FIG. 7, according to an example.
- (11) FIG. 10 illustrates a front view of the electronic locking differential gear mechanism of FIG. 2, in an unlocked state, according to an example.
- (12) FIG. 10A illustrates a front view of an alternate embodiment of the electronic locking differential gear mechanism of FIG. 10, in an unlocked state, with two snap rings engaged with each push rod, according to an example.
- (13) FIG. 11 illustrates a front view of the electronic locking differential gear mechanism of FIG. 2, in a locked state, according to an example.
- (14) FIG. 12 illustrates a schematic view of a vehicle within which the electronic locking differential gear mechanism may be used.
- (15) FIG. 13 illustrates a top view of a portion of the electronic locking differential gear mechanism of FIG. 1, including the sensing plate and anti-rotation lugs, according to an example.
- (16) FIG. 14 illustrates a close-up front view of a portion of the sensor assembly of FIG. 7, including the sensing plate and anti-rotation lugs, according to an example.
- (17) FIG. 15 illustrates a close-up front view of the sensing plate and anti-rotation lugs, illustrating an example embodiment with a distance between each side of the sensing plate and the anti-rotation lug it faces, according to an example.

DETAILED DESCRIPTION

(18) In the following detailed description, references are made to the accompanying drawings that form a part hereof, and in which are shown, by way of illustrations, specific embodiments, or examples. These aspects may be combined, other aspects may be utilized, and structural changes may be made without departing from the present disclosure. Examples may be practiced as methods, systems, or devices. The following detailed description is therefore not to be taken in a limiting sense, and the scope of the present disclosure is defined by the appended claims and their equivalents.

(19) Vehicle drivetrains may include differential mechanisms which include gear sets **50** that allow torque to be applied differently to wheels of the same axle during operation of the vehicle. In some

aspects, a driveshaft transferring torque from an engine or motor may, via a drive pinion gear, transfer torque to a ring gear of a transmission (for example, mounted to a flange of the transmission) by engagement with the ring gear. This ring gear is in a meshing engagement with a plurality of inner pinion gears (or spider gears) **52**. In an aspect, the inner pinion gears **52** are in a meshing engagement with two side gears **54, 56**, each side gear additionally having internal splines **58, 60** corresponding to a half-axle output. In an aspect, the ring gear is located outside of a case or housing, and the gear set (which operably connects the half-axle outputs and the power input location (driveshaft) together), including the inner pinion gears **52** and side gears **54, 56**, are located within the case/housing.

(20) In some aspects, a locking mechanism is included in the differential mechanism so that all available torque is delivered equally to both wheels of the axle, locking both wheels in synchronous rotation with each other. In some aspects, the locking mechanism is moved between a locked state and an unlocked state by an electrical action. In some aspects, the electrical action includes an electric stator. In some aspects, a driver or other user of a vehicle may trigger the electrical locking mechanism by way of a button, switch, or similar interactive device.

(21) Referring to FIG. **12**, an example vehicle driveline is shown in accordance with the above description and disclosure and within which the disclosed electronic locking differential gear assembly **10** may be used. As shown, the vehicle driveline is provided with a power plant **106**, such as an internal combustion engine or electric motor, a transmission **107**, a power transfer unit **108** that are operatively connected at the front of the vehicle to transmit torque directly to a front left axle **100**, and front right axle **101** such that wheels **102** and **103** receive torque to provide traction to the vehicle via wheel hubs **115** and **116**. Via mechanisms in the power transfer unit **108**, such as a hypoid gear and pinion, the drive shaft **109** receives torque and transmits it to the rear of the vehicle. As shown, an all-wheel drive coupling **120** connects to the drive shaft **109**, and a rear drive unit **110** may house the disclosed locking differential assembly **10** within a rear differential assembly. As discussed further herein, the locking differential assembly **10** may be operated in either an open or locked mode. In the open mode, the left rear wheel **113**, via wheel hub **117** and left rear axle **111**, can spin at a speed that is different from the right wheel **114**. Likewise, the right rear wheel **114**, via wheel hub **118** and right rear axle **112**, can spin at a different speed than left rear wheel **113**. In the locked mode, both left and right rear wheels **113** and **114** receive the same torque because the left and right rear axle **111** and **112** are locked together to prevent relative rotation via internal components in the rear differential. An example of a differential mechanism is described in further detail in U.S. Pat. No. 9,657,827 B2, the entire disclosure of which, except for any definitions, disclaimers, disavowals, and inconsistencies, is incorporated herein by reference.

(22) Referring now to the Figures, there is shown an electronic locking differential gear mechanism (e.g., differential assembly) **10** that includes cam/ramp actuated direct acting electronic locking capability. The gear set **50** of the electronic locking differential gear mechanism **10** is located within a case **20** (refer to FIG. **1**), and in some examples, torque may be transferred to the gear set **50** via a ring gear mounted to a flange **23**. Accordingly, the flange **23** may be referred to as a power input location.

(23) In an aspect, an electric actuator mechanism (e.g., electrically actuated locking assembly or locking element) **12** of the electronic locking differential gear mechanism **10** includes a stator housing **40**. The stator housing **40** is mounted to case (e.g., housing) **20**. The stator housing **40** is operable between a locked position, in which first and second half-axle outputs are prevented from rotating relative to each other, and an unlocked position, in which the first and second half-axle outputs are enabled to rotate relative to each other. Stator housing **40** includes an electric stator **16**, which, in some aspects, causes a ramped collar **18** to be rotationally actuated in relation to the stator housing **40**. In an aspect, ramped collar **18** rotates about an axis **2**.

(24) Referring to FIG. **10-11**, in an aspect, ramped collar **18** includes one or more ramps (for example, one or more locations axially where it has a greater or lesser length). Ramped collar **18**

includes one or more ramp valleys **17**, where the axial length of the ramped collar **18** is the least. Ramped collar **18** includes one or more ramp peaks **19**, where the axial length of the ramped collar **18** is the greatest.

(25) Electric actuator mechanism **12** includes at least one actuating push rod **14**. Although three push rods **14** are depicted in the example embodiments of the Figures, other embodiments may include more than three push rods **14** or fewer than three push rods **14**. Push rods **14** are operably coupled to electric stator **16** via the ramped collar **18**. In some aspects, push rods **14** may be generally cylindrical or rod-like in shape. Push rods **14** contact ramped collar **18** at an end of the push rods **14**. In some aspects, push rods **14** pass through the case **20** in a bore, and do not rotate with relation to the case **20**.

(26) Push rods **14** are coupled to a locking collar **24**. In some examples, push rods **14** are coupled to locking collar **24** via press fit design, threaded connection, or any suitable fastening or attachment means.

(27) Push rods **14** are axially displaceable along (parallel to) the axis X of the differential assembly **10**. Push rods **14** are axially displaceable by the rotation of the ramped collar **18**. Locking collar **24** is axially displaceable by the displaced movement of the push rods **14**. By use of the term axial or axially displaceable, it is meant to define a direction that is parallel to the longitudinal axis X of the differential assembly **10**. Locking collar **24** includes teeth **26** formed on an inner diameter of the (28) locking collar **24**, which selectively engage with external teeth **27** of a locker gear **28**. When the teeth **26** of locking collar **24** engage with the external teeth **27** of locker gear **28**, the electronic locking differential gear mechanism **10** is placed into a locked position. When the teeth **26** of locking collar **24** are disengaged from the external teeth **27** of locker gear **28**, the electronic locking differential gear mechanism **10** is placed into an unlocked position.

(29) The locking collar **24** is disposed within a cavity defined at an outer boundary by the gear case **20** and defined at an inner boundary by the locker gear **28**.

(30) In some aspects, the locking collar **24** is biased to a disengaged or unlocked position by a spring or other biasing force member.

(31) In an aspect, each of the push rods **14**, in contact with ramped collar **18** at an end, is at an initial position (corresponding to an unlocked state) with its end in contact with a ramp valley **17**. As ramp collar **18** is rotated about axis **2**, each of the push rods **14** is displaced axially toward locker gear **28**, as the end in contact with ramped collar **18** is moved to a maximally displaced position in contact with a ramp peak **19** (corresponding to a locked state). This displaces locking collar **24** toward locker gear **28**, allowing teeth **26** and external teeth **27** to engage.

(32) The electronic locking differential gear mechanism **10** includes a sensor assembly **32** to determine the locking state/status (for example, locked or unlocked) of the electronic locking differential gear mechanism **10**. The sensor assembly **32** includes at least a sensing plate **34** (e.g., position sensing plate). Sensing plate **34** is axially displaceable along the axis **2**. Sensing plate **34** is axially displaceable by at least one of the push rods **14**.

(33) Sensing plate **34** is attached/secured to at least one of the push rods **14**. In an aspect, one or more of the push rods **14** includes a groove **15** for receiving an inner edge portion **37** of the sensing plate **34**. In an aspect, the sensing plate **34** is attached to a push rod **14** using one or more fasteners. In an aspect, the sensing plate **34** is attached to a push rod **14** using one or more snap rings **36**. In an aspect, the sensing plate **34** is attached to a push rod **14** using a step (for example, of a groove **15**) on one side of the push rod **14**. In an aspect, the sensing plate **34** is attached to a push rod **14** using a step of groove **15** and a snap ring **36** (on a side of the sensing plate **34** opposite the step). In an aspect, the sensing plate **34** is attached to a push rod **14** by sitting within groove **15** and having a snap ring **36** on either side of the sensing plate **34** (refer to FIG. **10A**). In an aspect, groove **15** and/or one or more snap rings **36** retain the sensing plate **34** relative to the push rod **14**. Other types of fasteners may also be used.

(34) In an aspect, sensing plate **34** includes one or more recesses **33**. Recesses **33** are located on the

inner edge portion **37** of sensing plate **34**. In some aspects, the number of recesses **33** equals the number of push rods **14**. In some aspects, recesses **33** are semi-circular (or another segment of a circle) in nature. In some aspects, each of the recesses **33** engage with (for example, receive) at least a portion of an outer surface of one of the push rods **14**. In some aspects, each of recesses **33** may engage with one of the push rods **14** at a groove **15**. In some aspects, each of recesses **33** facilitate the assembly of sensing plate **34** with push rod **14**. Once inserted, sensing plate **34** may be rotated within the groove **15**, and then one or more snap rings **36** may be added to the assembly to retain the sensing plate **34**.

(35) In an aspect, the inner edge portion **37** of sensing plate **34** defines a central aperture **39** of the sensing plate **34**.

(36) Sensing plate **34** is thereby coupled to the electric actuator mechanism (e.g., locking assembly) **12** such that operation of the locking assembly **12** between the locked and unlocked positions causes axial movement of the sensing plate **34**.

(37) Sensing plate **34** is coupled to the electric actuator mechanism (e.g., locking assembly) **12** such that sensing plate **34** is non-rotatable with respect to the stator housing.

(38) In an aspect, the ramped collar **18** is located axially between the electric stator **16** and the sensing plate **34**.

(39) The sensor assembly **32** includes sensor electronics **38**. Sensor electronics **38** include a position sensor configured to measure an axial position of the sensing plate **34** (e.g., detects a displacement of the sensing plate **34**). In an example, sensor assembly **32** is attached or mounted to the stator housing **40** by any appropriate means of attachment. Various sensor types may be utilized including, magnetic-type sensors such as Hall-effect sensors. In an aspect, the sensor is spaced from the sensor tab **42**, discussed below, of the sensing plate **34** such that the sensor does not physically contact the axially displaceable sensor tab **42**. Accordingly, the sensor assembly **32** may be referred to as a non-contacting sensor assembly. In an embodiment, a linear variable differential transformer (LVDT) sensor may be utilized.

(40) In an aspect, the sensor assembly **32** includes a sensor tab (or sensor bracket) **42**. Sensor tab **42** is displaceable by the sensing plate **34** along axis X. Sensor tab **42** extends axially from the sensing plate **34** in a direction away from the locker gear **28**. In an aspect, sensor tab **42** has a substantially L-shaped cross section, with the shorter base length of the L-shape contacting a surface of the sensing plate **34** opposite of the sensor electronics. In an aspect, sensor tab **42** is attached to the sensing plate **34**. Sensor tab **42** may be attached to, mounted on, or fastened to sensing plate **34** by any means, including by welding, the use of adhesives, or the use of fasteners. In another aspect, sensor tab **42** and sensing plate **34** may be integrally formed as a single component. In an aspect, sensing plate **34** includes a notch **35**. In some embodiments, at least a portion of tab **42** may engage with (for example, sit in or fit in) notch **35**.

(41) In an aspect, sensor tab **42** includes a sensor target **44** attached to or mounted thereon. The sensor tab **42** is positioned adjacent to the sensor electronics **38** to determine axial movement of the sensor plate **34**. In an aspect, a position of the sensor target **44** is detectable by the sensor assembly. In an aspect, the sensor target **44** is a magnet and the sensor electronics **38** are configured to detect a magnetic field of the sensor target **44**.

(42) In an aspect, stator housing **40** includes anti-rotation lugs or tabs **46**, **47** formed or attached thereon. The sensor tab **42** is positioned between the anti-rotation lugs or tabs **46**, thereby preventing rotation of the sensing plate **34** relative to the stator housing **40**. To further provide anti-rotation capability, an additional extension or tab structure **43** is shown as being part of or secured to the sensing plate **34** and located oppositely from the sensor tab **42**. The tab structure **43** interacts with lugs **47** to prevent rotation of the sensing plate **34**. By providing two such structures, the anti-rotation forces at tabs **42**, **43** are balanced such that an undesirable torque exerted on the sensing plate **34** by the lugs is reduced or eliminated. As with sensor tab **42** and sensing plate **34**, the tab structure **43** may also be attached to, mounted on, or fastened to sensing plate **34** by any means,

including by welding, the use of adhesives, or the use of fasteners, or may be integrally formed as a single component with the sensing plate.

(43) In an aspect, anti-rotation lugs **46** (and, in some examples, lugs **47**) are oriented parallel to each other and perpendicular to upper surface **60** of the sensor tab **42**. Refer to FIGS. **13** and **14**. A center point of each of the anti-rotation tabs **46** defines an axis Y. Each of the vertical axes Y are parallel to each other and orthogonal to the axis X. Each of the axes Y are at an oblique angle to a radial line extending from axis X.

(44) As discussed above, sensor tab **42** is positioned between the anti-rotation lugs **46**, thereby preventing rotation of the sensing plate **34** relative to the stator housing **40** during movement of the sensing plate **34**. In the depicted embodiment, the anti-rotation lugs **46** define parallel vertical surfaces that face and are parallel to side surfaces **62**, **64** of sensor tab **42** (for example, when the sensing plate **34** is centered between the pair of anti-rotation lugs **46**) such that, when an anti-rotation lug **46** contacts a side surface **62** or **64**, contact is maximized between the vertical surface of the anti-rotation lug **46** and the side surface **62** or **64**. In this way, the anti-rotation lugs **46** cooperate to mitigate lash experienced by the sensor tab **42** during movement of the sensing plate **34**. The mitigation of lash may result in improved position of the sensing plate **34** and a more accurate sensor assembly **32**.

(45) In an example, where axis X is oriented substantially horizontal, the anti-rotation lugs **46** may be oriented in a substantially vertical position (with axes Y substantially vertical).

(46) The anti-rotation lugs **46** may be fastened, adhered, welded, or integrated into (e.g., via casting, molding, machining) the stator housing **40**. In some examples, the anti-rotation lugs **46** (and lugs **47**) may be of cylindrical, rectangular prism, or other suitable shape.

(47) In some examples, the diameter of each anti-rotation lug **46** may be about 6.0 mm, with tolerances of about ± 0.2 mm. In some examples, the diameter of each anti-rotation lug **46** may be from about 4.0 mm to about 8.0 mm. In some examples, the diameter of each anti-rotation lug **46** may be from about 5.0 mm to about 7.0 mm. In some examples, the diameter of each anti-rotation lug **46** may be from about 5.5 mm to about 6.5 mm.

(48) In some examples, the width of sensor tab **42** (as measured between the side surfaces **62** and **64** where they face (and potentially contact) the anti-rotation lugs **46**) may be about 12.3 mm, with tolerances of about ± 0.1 mm. In some examples, the width of sensor tab **42** may be from about 10.0 mm to about 14.0 mm. In some examples, the width of sensor tab **42** may be from about 11.0 mm to about 13.0 mm. In some examples, the width of sensor tab **42** may be from about 12.0 mm to about 12.6 mm.

(49) In an aspect, the vertical surfaces of one or both of the anti-rotation lugs **46** contact the side surfaces **62**, **64**. In an example, a gap distance exists between one or both of the anti-rotation lugs **46** and the side surfaces **62**, **64**. Refer to FIG. **15**. A gap distance D1 may exist between one of the anti-rotation lugs **46** and side surface **62**. A gap distance D2 may exist between one of the anti-rotation lugs **46** and side surface **64**. In some examples, gap distances D1 and D2 are equal. In some examples, gap distances D1 and D2 are unequal.

(50) In some examples, the width of each of gap distances D1 and D2 vary over time as the electronic locking differential gear mechanism **10** operates. If the width of gap distance D1 or D2 varies to 0 mm, then there is contact between the vertical surface of the respective the anti-rotation lug **46** the respective side surface **62** or **64**. This contact prevents rotation of the sensing plate **34** relative to the stator housing **40**.

(51) In some examples, the total lash or total play (the sum of the gap distances D1 and D2) may be about 0.3 mm. In some examples, the total lash may be between about 0.2 mm to about 0.4 mm. In some examples, the total lash may be between about 0.15 mm to about 0.5 mm.

(52) In some examples, anti-rotation lug **46** may have analogous dimensions and orientations to anti-rotation lugs **46**. In some examples, tab structure **43** may have analogous dimensions and orientations to sensor tab **42**.

(53) In an example use, the electric actuator mechanism **12** is in a normal, unlocked status. Refer to FIG. **10**. For example, it may be biased to an unlocked state by a spring or biasing element. In the unlocked state, locking collar **24** is moved axially away from engagement with locker gear **28**.

(54) Upon activation/energizing (which may be in response to a control signal from a control module or may be actuated in response to activation of a switch by a user) of the electric stator **16**, the ramped collar **18** is rotated about axis **2**, and at least one push rod **14** is displaced axially. As shown at FIGS. **5** and **6**, a bearing assembly **17** can be provided between the stator **16** and collar **18** to facilitate relative movement between the two components. Locking collar **24** is moved by the displacement of the one or more push rods **14** to engage with the locker gear **28**, which causes the locking of the electronic locking differential gear mechanism **10**. Refer to FIG. **11**.

(55) Sensing plate **34** is displaced axially with the push rods **14** and correspondingly the sensor tab **42** with the sensor target **44** is displaced relative to the sensor electronics **38**. The position sensor senses/detects the axial displacement of the sensor target **44** (and therefore the displacement of the sensing plate **34**).

(56) A signal is thereby produced that indicates that the electronic locking differential gear mechanism **10** is in a locked condition. The status can then be indicated to a user of the vehicle, in some aspects.

(57) In some aspects, after the electric stator **16** is de-energized, the electronic locking differential gear mechanism **10** is returned to an unlocked position (for example, by a biasing element or spring). The sensing plate **34** moves with the push rods **14** (and correspondingly the sensor tab **42** with the sensor target **44** moves relative to the sensor electronics **38**). A signal is thereby produced that indicates that the differential **10** is in an un-locked condition. The status can then be indicated to a user of the vehicle, in some aspects.

(58) For the purposes of this application, terms such as “left,” “right,” “front,” “back,” “upper,” “lower,” “upward,” and “downward” are intended to be descriptive with reference to and in relation to the orientation shown in the Figures for clarity and are not meant to be limiting, but the examples as practiced and included in the scope of the claims may include examples where the systems and devices are in a different orientation.

(59) While particular uses of the technology have been illustrated and discussed above, the disclosed technology can be used with a variety of environments in accordance with many examples of the technology. The above discussion is not meant to suggest that the disclosed technology is only suitable for implementation within the environments shown and described above. For examples, while certain technologies described herein were primarily described in the context of sealed battery cases, technologies disclosed herein are applicable to sealed components generally.

(60) This disclosure described some aspects of the present technology with reference to the accompanying drawings, in which only some of the possible aspects were shown. Other aspects can, however, be embodied in many different forms and should not be construed as limited to the aspects set forth herein. Rather, these aspects were provided so that this disclosure was thorough and complete and fully conveyed the scope of the possible aspects to those skilled in the art.

(61) As should be appreciated, the various aspects described with respect to the Figures herein are not intended to limit the technology to the particular aspects described. Accordingly, additional configurations can be used to practice the technology herein and/or some aspects described can be excluded without departing from the methods and systems disclosed herein.

(62) Similarly, where operations of a process are disclosed, those operations are described for purposes of illustrating the present technology and are not intended to limit the disclosure to a particular sequence of operations. For example, the operations can be performed in differing order, two or more operations can be performed concurrently, additional operations can be performed, and disclosed operations can be excluded without departing from the present disclosure. Further, each operation can be accomplished via one or more sub-operations. The disclosed processes can be

repeated.

(63) Although specific aspects were described herein, the scope of the technology is not limited to those specific aspects. One skilled in the art will recognize other aspects or improvements that are within the scope of the present technology. Therefore, the specific structure, acts, or operations are disclosed only as illustrative aspects. The scope of the technology is defined by the following claims and any equivalents therein.

Claims

1. A differential assembly comprising: a) a first housing; b) a first half-axle output; c) a second half-axle output; d) a power input location; e) a gear set disposed within the first housing and operably connecting the first half-axle output, the second half-axle output, and the power input location together; f) an electrically activated locking assembly including a second housing mounted to the first housing and being operable between a locked position, in which the first and second half-axle outputs are prevented from rotating relative to each other, and an unlocked position, in which the first and second half-axle outputs are enabled to rotate relative to each other, the locking assembly including a first pair of anti-rotation members extending from the second housing; g) a sensor assembly including a position sensing plate defining a first axially extending tab supporting a sensor target of a position sensor, the position sensing plate being coupled to the locking assembly such that operation of the locking assembly between the locked and unlocked positions causes axial movement of the position sensing plate, the first axially extending tab being located between the first pair of anti-rotation members such that the position sensing plate is non-rotatable with respect to the second housing, the position sensor being configured to measure an axial position of the position sensing plate.
2. The differential assembly of claim 1, wherein the position sensor is configured to sense movement of the axially extending tab.
3. The differential assembly of claim 2, wherein the position sensor is a magnetic-type position sensor that is spaced from the position sensing plate.
4. The differential assembly of claim 1, wherein the first pair of anti-rotation members includes first and second members that are parallel to each other.
5. The differential assembly of claim 1, wherein the first pair of anti-rotation members includes first cylindrical lug and second cylindrical lug.
6. The differential assembly of claim 1, further comprising: a second pair of anti-rotation members located oppositely from the first pair of anti-rotation members; and a second axially extending tab located oppositely from the first axially extending tab and extending between the second pair of anti-rotation members.
7. A lock detection mechanism for a differential assembly, the lock detection mechanism comprising: a locking element of the differential assembly, operable between a locked state and an unlocked state; one or more push rods displaceable in a direction parallel to an axis of the differential assembly, connected at a first end to a locking collar of the locking element and in contact at a second end with a ramped collar, wherein: the ramped collar is rotatable about the axis, the ramped collar comprises one or more ramp valleys and one or more ramp peaks, and the one or more push rods are displaceable by the one or more ramp valleys and one or more ramp peaks; a position sensing plate axially displaceable along the axis, wherein the position sensing plate is displaceable by the one or more push rods; and a sensor assembly including a sensor to detect a status of the locking element, wherein the sensor assembly detects a displacement of a sensor target supported by an axially extending tab of the position sensing plate, the axially extending tab being located between a first pair of anti-rotation members to prevent rotation of the position sensing plate about the axis.
8. The lock detection mechanism of claim 7, wherein the axially extending tab is connected to the

- position sensing plate at a first end, wherein the axially extending tab is displaceable by the position sensing plate along the axis, wherein the axially extending tab is connected to the sensor target at a second end, and wherein a position of the sensor target is detectable by the sensor.
9. The lock detection mechanism of claim 8, wherein the sensor is a magnetic-type position sensor that is spaced from the position sensing plate.
10. The lock detection mechanism of claim 8, wherein the position sensing plate comprises a notch, and wherein at least a portion of the tab fits within the notch.
11. The lock detection mechanism of claim 8, wherein the first pair of anti-rotation members includes first and second members that are parallel with each other.
12. The lock detection mechanism of claim 7, wherein the position sensing plate comprises one or more recessed portions, each of the one or more recessed portions receiving a portion of one of the one or more push rods.
13. The lock detection mechanism of claim 12, wherein each of the one or more push rods includes a groove receiving the respective recessed portion of the position sensing plate and at least one snap-ring on at least one side of the position sensing plate.
14. The lock detection mechanism of claim 7, wherein the ramped collar is rotatable by an electronic actuator mechanism.
15. A differential assembly comprising: a differential including a gear set disposed within a housing and operably coupling a power input location to a first half-axle output and a second half-axle output; an electrically activated locking assembly operable between a locked position, in which the first and second half-axle outputs are prevented from rotating relative to each other, and an unlocked position, in which the first and second half-axle outputs are enabled to rotate relative to each other; and the lock detection mechanism of claim 7 for sensing and indication of a locked and unlocked state of the locking element.
16. The differential assembly of claim 7, wherein the first pair of anti-rotation members includes first cylindrical lug and second cylindrical lug.
17. A lock detection arrangement for a differential assembly, the lock detection arrangement comprising: a sensor assembly including a position sensing plate and a position sensor, the position sensing plate being configured for connection to a locking element of the differential assembly and axially displaceable with reference to the position sensor between a locked state of the locking element and an unlocked state of the locking element; and a pair of parallel anti-rotation lugs between which a first tab structure of the position sensing plate extends, the pair of parallel anti-rotation lugs preventing rotation of the position sensing plate.
18. The lock detection arrangement of claim 17, wherein each of the pair of parallel anti-rotation lugs has a cylindrical shape, and wherein side surfaces of the first tab structure are parallel to the pair of parallel anti-rotation lugs when the position sensing plate is centered between the pair of parallel anti-rotation lugs.
19. The lock detection arrangement of claim 17, further comprising: a second pair of anti-rotation lugs opposite the first pair of anti-rotation lugs; and a second tab structure opposite the first tab structure and extending between the second pair of anti-rotation lugs.
20. The differential assembly of claim 17, wherein side surfaces of the first tab structure are parallel to the pair of anti-rotation lugs when the position sensing plate is centered between the pair of anti-rotation lugs.
21. The lock detection arrangement of claim 17, the first tab structure supports a sensor target of the sensor assembly.
-