

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405015
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kim; Minsoo et al.

Dehumidification apparatus and dehumidification method using the same

Abstract

Provided is a dehumidification apparatus including: a storage compartment that provides an accommodation space; a circulation blower that forms an air current flowing along a circulation path connected to the accommodation space; a heat pump that exchanges heat with the air current flowing along the circulation path; and an air current diverter, wherein the heat pump includes: a first heat exchanger that absorbs heat from the air current; and a second heat exchanger that releases heat, wherein the circulation path includes a first circulation path in which the air current passes through the second heat exchanger to the accommodation space and a second circulation path in which the air current passed through the first heat exchanger is allowed to bypass the second heat exchanger and flow to the accommodation space, and wherein the air current diverter diverts the circulation path from the first circulation path to the second circulation path.

Inventors: Kim; Minsoo (Suwon-si, KR), Na; Joongwon (Suwon-si, KR), Seo; Kookjeong (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 84543001

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/661149

Filed: April 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220412579 A1	Dec. 29, 2022

Foreign Application Priority Data

KR	10-2021-0085021	Jun. 29, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/005296 20220412 PENDING child-doc US 17661149

Publication Classification

Int. Cl.: F24F3/153 (20060101); F24F11/72 (20180101)

U.S. Cl.:

CPC F24F3/153 (20130101); F24F11/72 (20180101);

Field of Classification Search

CPC: F24F (3/153); F24F (11/72); F25B (30/02); A47L (23/205); A47L (23/18)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9976242	12/2017	Ryoo et al.	N/A	N/A
2005/0086824	12/2004	Ono et al.	N/A	N/A
2007/0157660	12/2006	Lee et al.	N/A	N/A
2016/0160419	12/2015	Ryoo	68/12.14	D06F 25/00
2020/0040504	12/2019	Rochford et al.	N/A	N/A
2021/0093743	12/2020	Kim et al.	N/A	N/A
2021/0401266	12/2020	Yoo	N/A	A61L 2/26
2024/0260810	12/2023	Kim	N/A	A61L 2/07

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4306217	12/1993	DE	D06F 58/02
2765235	12/2013	EP	N/A
2005024113	12/2004	JP	N/A
2011-092329	12/2010	JP	N/A
2014-090944	12/2013	JP	N/A
2014-150859	12/2013	JP	N/A
100565677	12/2005	KR	N/A
100624023	12/2005	KR	N/A
20070074301	12/2006	KR	N/A
10-2010-0067751	12/2009	KR	N/A
10-2015-0117431	12/2014	KR	N/A
10-1613963	12/2015	KR	N/A
10-2021-0016968	12/2020	KR	N/A
10-2021-0016974	12/2020	KR	N/A
10-2021-0017015	12/2020	KR	N/A

10-2230674	12/2020	KR	N/A
102246320	12/2020	KR	N/A
20210038161	12/2020	KR	N/A
102496520	12/2022	KR	N/A

OTHER PUBLICATIONS

DE-4306217-A1 translation. cited by examiner

International Search Report dated Aug. 3, 2022 in connection with International Patent Application No. PCT/KR2022/005296, 4 pages. cited by applicant

Written Opinion of the International Searching Authority dated Aug. 3, 2022 in connection with International Patent Application No. PCT/KR2022/005296, 5 pages. cited by applicant

Office Action issued Mar. 14, 2025, in connection with Korean Patent Application No. 10-2021-0085021, 16 pages. cited by applicant

Primary Examiner: Martin; Elizabeth J

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2022/005296, filed Apr. 12, 2022, which is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2021-0085021, filed Jun. 29, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference in their entirety.

BACKGROUND

1. Field

(1) The disclosure relates to a dehumidification apparatus and a dehumidification method using the same.

2. Description of the Related Art

(2) A dehumidification apparatus is an apparatus for caring for and storing clothes and shoes worn by people, and in particular, maintaining shoes and the like in a pleasant state by controlling the humidity. Such a dehumidification apparatus may include a filter and a steamer for performing deodorization and sterilization on shoes, etc. disposed in the dehumidification apparatus. In the process of caring for shoes, etc., air discharged from inside the dehumidification apparatus to the outside may cause users to feel unpleasant due to the odor of the air. In addition, steam injected onto shoes, etc. in the dehumidification apparatus may sterilize shoes, and the like but may damage the shoes due to the high temperature of the steam.

SUMMARY

(3) Therefore, it is an object of the disclosure to provide a dehumidification apparatus capable of controlling the dehumidifying temperature, and dehumidification method using the same.

(4) The technical objectives of the disclosure are not limited to the above, and other objectives may become apparent to those of ordinary skill in the art based on the following descriptions.

(5) According to an aspect of the disclosure, there is provided a dehumidification apparatus including: a storage compartment configured to provide an accommodation space; a circulation blower configured to form an internal air current flowing along a circulation path connected to the accommodation space; a heat pump configured to exchange heat with the internal air current moving along the circulation path; and an air current diverter, wherein the heat pump includes: a first heat exchanger configured to absorb heat from the internal air current; and a second heat exchanger configured to release heat to a surrounding, wherein the circulation path includes a first

circulation path in which the internal air current passed through the first heat exchanger is allowed to pass through the second heat exchanger and flow to the accommodation space and a second circulation path in which the internal air current passed through the first heat exchanger is allowed to bypass the second heat exchanger and flow to the accommodation space, and wherein the air current diverter is configured to divert the circulation path from the first circulation path to the second circulation path.

(6) According to an aspect of the disclosure, there is provided a dehumidification apparatus including: a storage compartment configured to provide an accommodation space; a circulation blower configured to form an internal air current flowing along a circulation path connected to the accommodation space; a heat pump configured to exchange heat with the internal air current moving along the circulation path, and includes an evaporator, a compressor, a condenser, an expansion valve, and a refrigerant pipe; an outdoor cooling blower configured to form an external air current in an outdoor air cooling path connected to an outdoor space; and a controller configured to control the outdoor air cooling blower, the internal air current introduced from the accommodation space sequentially passes through the evaporator and the condenser along the circulation path and returns to the accommodation space, and the controller is configured to select and perform at least one of: a first dehumidifying mode in which the external air current is transferred to the condenser to perform outdoor air cooling on the condenser; and a second dehumidifying mode in which the outdoor air cooling on the condenser using the external air current is stopped.

(7) Other aspects of embodiments will become apparent from the following detailed description and the annexed drawings.

(8) Before undertaking the DETAILED DESCRIPTION below, it may be advantageous to set forth definitions of certain words and phrases used throughout this patent document: the terms “include” and “comprise,” as well as derivatives thereof, mean inclusion without limitation; the term “or,” is inclusive, meaning and/or; the phrases “associated with” and “associated therewith,” as well as derivatives thereof, may mean to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with, have, have a property of, or the like; and the term “controller” means any device, system or part thereof that controls at least one operation, such a device may be implemented in hardware, firmware or software, or some combination of at least two of the same. It should be noted that the functionality associated with any particular controller may be centralized or distributed, whether locally or remotely.

(9) Moreover, various functions described below can be implemented or supported by one or more computer programs, each of which is formed from computer readable program code and embodied in a computer readable medium. The terms “application” and “program” refer to one or more computer programs, software components, sets of instructions, procedures, functions, objects, classes, instances, related data, or a portion thereof adapted for implementation in a suitable computer readable program code. The phrase “computer readable program code” includes any type of computer code, including source code, object code, and executable code. The phrase “computer readable medium” includes any type of medium capable of being accessed by a computer, such as read only memory (ROM), random access memory (RAM), a hard disk drive, a compact disc (CD), a digital video disc (DVD), or any other type of memory. A “non-transitory” computer readable medium excludes wired, wireless, optical, or other communication links that transport transitory electrical or other signals. A non-transitory computer readable medium includes media where data can be permanently stored and media where data can be stored and later overwritten, such as a rewritable optical disc or an erasable memory device.

(10) Definitions for certain words and phrases are provided throughout this patent document, those of ordinary skill in the art should understand that in many, if not most instances, such definitions apply to prior, as well as future uses of such defined words and phrases.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These and/or other aspects of the disclosure will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings of which:
- (2) FIG. 1 is a schematic diagram illustrating a dehumidification apparatus according to embodiments of the disclosure;
- (3) FIG. 2 is a perspective view illustrating a dehumidification apparatus according to embodiments of the disclosure;
- (4) FIG. 3 is a partially exploded perspective view illustrating a dehumidification apparatus according to embodiments of the disclosure;
- (5) FIG. 4 is an enlarged perspective view illustrating an upper side of a dehumidification apparatus according to embodiments of the disclosure;
- (6) FIG. 5 is an enlarged perspective view illustrating a part of a dehumidification apparatus according to embodiments of the disclosure;
- (7) FIG. 6 is an enlarged perspective views illustrating a part of a dehumidification apparatus according to embodiments of the disclosure;
- (8) FIG. 7 is a perspective view illustrating a part of a machine compartment of a dehumidification apparatus according to embodiments of the disclosure;
- (9) FIG. 8A is a cross-sectional view showing a portion cut away from FIG. 7;
- (10) FIG. 8B is a cross-sectional views showing a portion cut away from FIG. 7;
- (11) FIG. 9A is a plan view of some areas of FIG. 7;
- (12) FIG. 9B is a plan view of some areas of FIG. 7;
- (13) FIG. 10 is a flowchart showing a dehumidification method using a dehumidification apparatus according to embodiments of the disclosure;
- (14) FIG. 11 is a schematic diagram illustrating a dehumidification apparatus according to embodiments of the disclosure;
- (15) FIG. 12 is a perspective view illustrating a part of a machine compartment of a dehumidification apparatus according to embodiments of the disclosure;
- (16) FIG. 13 is an enlarged partial exploded perspective view illustrating some areas of FIG. 12;
- (17) FIG. 14 is an enlarged exploded perspective view illustrating some components of FIG. 13;
- (18) FIG. 15A is a plan view of some areas of FIG. 12;
- (19) FIG. 15B is a plan view of some areas of FIG. 12; and
- (20) FIG. 16 is a flowchart of a dehumidification method using a dehumidification apparatus according to embodiments of the disclosure.

DETAILED DESCRIPTION

- (21) FIGS. 1 through 16, discussed below, and the various embodiments used to describe the principles of the present disclosure in this patent document are by way of illustration only and should not be construed in any way to limit the scope of the disclosure. Those skilled in the art will understand that the principles of the present disclosure may be implemented in any suitably arranged system or device
- (22) The embodiments set forth herein and illustrated in the configuration according to the disclosure are only the most preferred embodiments and are not representative of the full the technical spirit according to the disclosure, so it should be understood that they may be replaced with various equivalents and modifications at the time according to the disclosure.
- (23) Throughout the drawings, like reference numerals refer to like parts or components.
- (24) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to limit the disclosure. It is to be understood that the singular forms “a,” “an,” and

“the” include plural references unless the context clearly dictates otherwise. It will be further understood that the terms “include”, “comprise” and/or “have” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(25) The terms including ordinal numbers like “first” and “second” may be used to explain various components, but the components are not limited by the terms. The terms are only for the purpose of distinguishing a component from another. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings according to the disclosure. Descriptions shall be understood as to include any and all combinations of one or more of the associated listed items when the items are described by using the conjunctive term “~ and/or ~,” or the like.

(26) Hereinafter, embodiments according to the disclosure will be described in detail with reference to the accompanying drawings.

(27) FIG. 1 is a schematic diagram illustrating a dehumidification apparatus according to embodiments of the disclosure.

(28) Referring to FIG. 1, a dehumidification apparatus **100** may be provided. The dehumidification apparatus **100** may be an apparatus for caring for and/or storing shoes and clothes. More specifically, the dehumidification apparatus **100** may be an apparatus for caring for shoes or the like or storing the shoes in a certain state, by performing deodorization, sterilization, and dehumidification operations on the shoes or the like. Hereinafter, for the sake of simplicity in description, a target for caring is described as a shoe, but the disclosure is not limited thereto, and other household items, such as clothing, may also be a target for caring.

(29) The dehumidification apparatus **100** may include a storage compartment SC, a machine compartment MC, a controller C, and an inputter IP.

(30) The storage compartment SC may be a place in which shoes are stored. The storage compartment SC may include a first housing H1, a door D, and a sterilization light source L.

(31) The first housing H1 may form the external appearance of the storage compartment SC. The first housing H1 may provide an accommodation space SH. That is, the accommodation space SH may be defined by the first housing H1. Shoes may be stored in the accommodation space SH. That is, in a state in which shoes are stored in the accommodation space SH, care and storage of the shoes may be conducted.

(32) The door D may be coupled to a side of the first housing H1. The door D may allow the accommodation space SH to be separated from or connected to the outdoor space. That is, when the door D is opened, the accommodation space SH may be exposed to the outside, and when the door D is closed, the accommodation space SH may be separated from the outside. When the door D is closed, the air in the accommodation space SH may be isolated from the air of the outdoor space. The user may open or close the door D to accommodate the shoes in the accommodation space SH or take out the shoes from the accommodation space SH.

(33) The sterilization light source L may be coupled to an inner surface of the first housing H1. The sterilization light source L may perform a sterilization operation on the shoes accommodated in the accommodation space SH. To this end, the sterilization light source L may transmit ultraviolet rays. That is, the sterilization light source L may include an ultraviolet ray (UV) lamp. More specifically, the sterilization light source L may include a xenon (Xe) lamp. However, the disclosure is not limited thereto, and the sterilization light source L may include other light sources capable of sterilizing shoes in the accommodation space SH.

(34) The machine compartment MC may include a mechanical device for caring for shoes in the storage compartment SC. For example, the machine compartment MC may include a second housing H2, a steamer **70**, a heat pump **30**, an air current circulator **10**, and an outdoor air cooler **50**.

(35) The second housing H2 may form the external appearance of the machine compartment MC. The steamer **70**, the heat pump **30**, the air current circulator **10**, the outdoor air cooler **50**, and the like may be located inside the second housing H2. However, the disclosure is not limited thereto, and a portion of each of the steamer **70**, the heat pump **30**, the air current circulator **10**, and the outdoor air cooler **50** may be located outside the second housing H2.

(36) The steamer **70** may generate steam and spray the generated steam into the accommodation space SH. The steamer **70** may include a steam tank **71**, a steam pipe **77**, a steam generator **73**, a steam compressor **75**, and a steam injector **7N**.

(37) The steam tank **71** may store water for steam generation. Water in the steam tank **71** may need to be periodically filled. To this end, the steam tank **71** may be disposed in a place that may be easily accessed by a user. Details thereof will be described below.

(38) The steam pipe **77** may connect the steam tank **71**, the steam generator **73**, the steam compressor **75**, and the steam injector **7N**. Water in the steam tank **71** may move along the steam pipe **77** to the steam generator **73**.

(39) The steam generator **73** may generate steam using water. For example, the steam generator **73** may heat water that has moved along the steam pipe **77** using a heating wire to generate steam. The generated steam may continue to move along the steam pipe **77**.

(40) The steam compressor **75** may provide the steam pipe **77** with a driving force. That is, the steam compressor **75** may allow the steam in the steam pipe **77** to be moved and injected through the steam injector **7N**.

(41) The steam injector **7N** may inject the steam generated by the steam generator **73** into the accommodation space SH. To this end, the steam injector **7N** may include one or more nozzles. The injector **7N** may be provided in plural. The plurality of steam injectors **7N** may be arranged adjacent to each other as shown in FIG. 1, but the arrangement is not limited thereto. That is, the plurality of steam injectors **7N** may be spaced apart from each other to inject steam to various positions in the accommodation space SH. In the following description, unless otherwise specified, the steam injector **7N** will be described in a single unit for the sake of convenience in description.

(42) In the above, the steamer **70** has been described as generating and supplying steam by an instantaneous heating method, but the disclosure is not limited thereto. That is, unlike that shown in FIG. 1, the steamer **70** may generate steam in a water tank type heating method and supply the steam to the accommodation space SH.

(43) When steam is injected into the accommodation space SH by the steamer **70**, shoes disposed in the accommodation space SH may be steam sterilized and/or deodorized. More specifically, shoes in the accommodation space SH may be sterilized and/or deodorized by high-temperature steam. That is, the dehumidification apparatus **100** may provide a steam injecting mode for shoes.

(44) The heat pump **30** may perform a cycle while exchanging heat with the outside. For example, the heat pump **30** may include a vapor compression refrigeration cycle in which a refrigerant circulates and heat-exchanges with surroundings. In this case, the heat pump **30** may include a refrigerant pipe **39**, a first heat exchanger **31**, a compressor **33**, a second heat exchanger **35**, and an expansion valve **37**.

(45) The refrigerant pipe **39** may refer to a pipe through which a refrigerant flows. The refrigerant in the refrigerant pipe **39** may be a working fluid of a refrigeration cycle. The type of the refrigerant may be selected in consideration of the range of temperature that may be required for dehumidification and deodorization. The refrigerant pipe **39** may connect the first heat exchanger **31**, the compressor **33**, the second heat exchanger **35**, and the expansion valve **37**. The refrigerant may move along the refrigerant pipe **39** and sequentially pass through the first heat exchanger **31**, the compressor **33**, the second heat exchanger **35**, and the expansion valve **37**. Details thereof will be described below with reference to FIG. 7.

(46) The first heat exchanger **31** may absorb heat from the surroundings. More specifically, the first heat exchanger **31** may absorb heat from the surroundings, and a refrigerant passing through the

first heat exchanger **31** may absorb heat from the first heat exchanger **31**. The refrigerant in a liquid state and passing through the first heat exchanger **31** may absorb heat from the first heat exchanger **31** to become a gaseous refrigerant. That is, the first heat exchanger **31** may be an evaporator.

(47) The compressor **33** may compress the refrigerant that has passed through the first heat exchanger **31** into a high temperature and high pressure refrigerant. More specifically, a low-temperature and low-pressure gas refrigerant that passed through the first heat exchanger **31** may be converted into a high-temperature and high-pressure gas by the compressor **33**. To this end, the compressor **33** may be supplied with power from the outside. By the power transmitted from the outside, the refrigerant passing through the compressor **33** may be compressed. The compressor **33** may include a constant speed compressor or an inverter compressor. The type of the compressor **33** may be selected in consideration of the type of the refrigerant and required temperature and pressure conditions.

(48) The second heat exchanger **35** may release heat to the surroundings. More specifically, the refrigerant passing through the second heat exchanger **35** may transfer heat to the second heat exchanger **35**, and the second heat exchanger **35** may release heat to the surroundings. The gaseous refrigerant passing through the second heat exchanger **35** may transfer heat to the second heat exchanger **35** to become a liquid refrigerant. That is, the second heat exchanger **35** may be a condenser. A high-temperature and high-pressure gas refrigerant passing through the second heat exchanger **35** may release heat to become a low-temperature and high-pressure liquid refrigerant. Details thereof will be described below.

(49) The expansion valve **37** may expand the refrigerant that has passed through the second heat exchanger **35** into a low temperature and a low pressure refrigerant. More specifically, a low-temperature and high-pressure liquid refrigerant that has passed through the second heat exchanger **35** may be converted into a low-temperature and low-pressure fluid by the expansion valve **37**. The refrigerant passed through the expansion valve **37** may be a two-phase refrigerant in which liquid and gas are mixed. However, the disclosure is not limited thereto, and the refrigerant passed through the expansion valve **37** may be a one-phase refrigerant in a completely liquid state. The refrigerant passed through the expansion valve **37** may return to the first heat exchanger **31** along the refrigerant pipe **39**.

(50) Although the heat pump **30** has been described as performing a vapor compression type refrigeration cycle using a refrigerant, the disclosure is not limited thereto. For example, unlike the description shown in FIG. 1, the heat pump **30** may be a thermoelectric element using the Peltier effect. In this case, the first heat exchanger **31** may not be an evaporator. In addition, the second heat exchanger **35** may not be a condenser. The compressor **33**, the expansion valve **37**, the refrigerant pipe **39**, or the like may be omitted. Alternatively, the heat pump **30** may be configured to perform a refrigeration cycle different from that described above.

(51) The air current circulator **10** may circulate air in the accommodation space SH. More specifically, the air current circulator **10** may circulate the air in the accommodation space SH to the outside of the accommodation space SH, and dehumidify the circulated air. To this end, the air current circulator **10** may provide a circulation path **10h**. The circulation path **10h** may be a path connected to the accommodation space SH and located outside the accommodation space SH. Air in the accommodation space SH may be introduced into the circulation path **10h** through an inlet **10X**. Hereinafter, air flowing into the circulation path **10h** and moving may be referred to as an internal air current AC. The term “air current” used herein may refer to air flowing in a certain direction. In addition, the internal air current on the circulation path **10h** may flow out into the accommodation space SH through an outlet **10Y**. The air current circulator **10** may exchange heat with the heat pump **30** between the inlet **10X** and the outlet **10Y**. That is, the internal air current on the circulation path **10h** may exchange heat with the heat pump **30**. When the heat pump **30** forms a vapor compression cycle using a refrigerant, the internal air current on the circulation path **10h** may exchange heat with a refrigerant that is a working fluid of the heat pump **30**. To this end, parts of

the circulation path **10h** may overlap parts of the heat pump **30**.

(52) For example, a part of the circulation path **10h** may overlap the first heat exchanger **31**. When the circulation path **10h** is referred to as overlapping the first heat exchanger **31**, the circulation path **10h** may overlap the surrounding space of components constituting the first heat exchanger **31**. Accordingly, the internal air current on the circulation path **10h** may be introduced into the first heat exchanger **31**. When the internal air current is referred to as being introduced into the first heat exchanger **31**, the internal air current moving along the circulation path **10h** approaches the surroundings of the first heat exchanger **31** such that heat transfer between the internal air current and the first heat exchanger **31** is performable. The internal air current on the circulation path **10h** may release heat to the first heat exchanger **31**. That is, the first heat exchanger **31** may absorb heat from the internal air current on the circulation path **10h**. When the internal air current on the circulation path **10h** approaches the first heat exchanger **31**, releases heat to the first heat exchanger **31**, and then moves away from the first heat exchanger **31**, the internal air current is referred to as passing through the first heat exchanger **31**.

(53) In addition, a part of the circulation path **10h** may overlap the second heat exchanger **35**. When the circulation path **10h** is referred to as overlapping the second heat exchanger **35**, the circulation path **10h** may overlap the surrounding space of components constituting the second heat exchanger **35**. Accordingly, the internal air current on the circulation path **10h** that passed through the first heat exchanger **31** may be introduced into the second heat exchanger **35**. When the internal air current is referred to as being introduced into the second heat exchanger **35**, the internal air current moving along the circulation path **10h** approaches the surroundings of the second heat exchanger **35** such that heat transfer between the internal air current and the second heat exchanger **35** is performable. The internal air current on the circulation path **10h** may absorb heat from the second heat exchanger **35**. That is, the second heat exchanger **35** may release heat to the internal air current on the circulation path **10h**. When the internal air current on the circulation path **10h** approaches the second heat exchanger **35**, absorbs heat from the second heat exchanger **35**, and then moves away from the second heat exchanger **35**, the internal air current may be referred to as passing through the second heat exchanger **35**.

(54) Alternatively, a part of the circulation path **10h** may bypass the second heat exchanger **35**. That is, a part of the circulation path **10h** passed through the first heat exchanger **31** may be formed to bypass the second heat exchanger **35** and connect to the accommodation space SH. Accordingly, in this case, the internal air current on the circulation path **10h** may exchange heat only with the first heat exchanger **31** without exchanging heat with the second heat exchanger **35**. That is, the air current circulator **10** may allow the internal air current to pass through the second heat exchanger **35** or bypass the second heat exchanger **35** before returning to the accommodation space SH, thereby adjusting the temperature of the internal air current returning to the accommodation space SH. Hereinafter, an example of the circulation path **10h** for the above-function will be described in detail.

(55) The circulation path **10h** may include a first heat exchange path **11h**, a first connection path **16h**, a second heat exchange path **12h**, a bypass path **13h**, a second connection path **14h**, and an outlet path **15h**.

(56) The first heat exchange path **11h** may connect the accommodation space SH to the first heat exchanger **31**. Air in the accommodation space SH may pass through the inlet **10X** and may move along the first heat exchange path **11h** to the first heat exchanger **31**. The internal air current on the circulation path **10h**, while passing through the first heat exchanger **31**, may release heat to the first heat exchanger **31**. Accordingly, the internal air current, while passing through the first heat exchanger **31**, may decrease in temperature. More specifically, the temperature of the internal air current passing through the first heat exchanger **31** may be lowered below the dew point. For example, the internal air current passed through the first heat exchanger **31** may have a decrease in temperature up to about 0 degrees Celsius to about 15 degrees Celsius. Accordingly, water vapor in

the internal air current passing through the first heat exchanger **31** may be condensed. Accordingly, the absolute humidity of the internal air current passed through the first heat exchanger **31** may be lowered. That is, the internal air current passed through the first heat exchanger **31** may be dehumidified. In addition, by dehumidifying the internal air current on the circulation path **10h**, a deodorizing effect may also occur. The water vapor condensed in the first heat exchanger **31** may be discharged to a discharge tank. Details thereof will be described below.

(57) The first connection path **16h** may connect the first heat exchanger **31** to the second heat exchange path **12h** and the bypass path **13h**. That is, the internal air current passed through the first heat exchanger **31** may move along the first connection path **16h** to the second heat exchange path **12h** or the bypass path **13h**.

(58) The second heat exchange path **12h** may connect the first connection path **16h** to the second heat exchanger **35**. The second heat exchange path **12h** may be referred to as a first circulation path. The internal air current passed through the first heat exchanger **31** may move along the second heat exchange path **12h** to the second heat exchanger **35**. The internal air current passing through the second heat exchanger **35** on the circulation path **10h** may absorb heat from the second heat exchanger **35**. Accordingly, the internal air current on the circulation path **10h**, while passing through the second heat exchanger **35**, may increase in temperature. For example, the internal air current passed through the second heat exchanger **35** may have an increase in temperature up to about 25 degrees Celsius to about 40 degrees Celsius.

(59) The bypass path **13h** may connect the first connection path **16h** to the outlet path **15h**. That is, the bypass path **13h** may bypass the second heat exchanger **35** such that the internal air current passed through the first heat exchanger **31** returns to the accommodation space SH without exchanging heat with the second heat exchanger **35**. Accordingly, the internal air current passed through the first heat exchanger **31** may bypass the second heat exchanger **35** along the bypass path **13h**. Hereinafter, the bypass path **13h** may be referred to as a second circulation path.

(60) The second connection path **14h** may connect the second heat exchanger **35** to the outlet path **15h**. That is, the internal air current passed through the second heat exchanger **35** may move along the second connection path **14h** to the outlet path **15h**.

(61) The outlet path **15h** may connect the bypass path **13h** and the second connection path **14h** to the accommodation space SH. The internal air current that has moved along the bypass path **13h** and the second connection path **14h** may return to the accommodation space SH along the outlet path **15h**.

(62) The circulation path **10h** described above may be provided by a duct or the like. That is, each of the first heat exchange path **11h**, the first connection path **16h**, the second heat exchange path **12h**, the bypass path **13h**, the second connection path **14h**, and the outlet path **15h** may be defined by a duct. Details thereof will be described below with reference to FIGS. 7 to 9B.

(63) The air current circulator **10** may include an air current diverter **10d**, a first filter **F1**, a second filter **F2**, a temperature sensor **19**, and a circulation blower **18**.

(64) The air current diverter **10d** may adjust the direction of the internal air current on the circulation path **10h**. That is, the air current diverter **10d** may adjust the movement direction of the internal air current to transport the internal air current to a specific path. For example, the air current diverter **10d** may allow the internal air current passed through the first heat exchanger **31** to move to the second heat exchanger **35** or bypass the second heat exchanger **35**. More specifically, the air current diverter **10d** may allow the internal air current on the first connection path **16h** to be transported to the second heat exchange path **12h** or to the bypass path **13h**. By operations of the air current diverter **10d**, the internal air current on the circulation path **10h** may enter or bypass the second heat exchanger **35** before returning to the accommodation space SH. The air current diverter **10d** may include a component for transporting the internal air current passed through the first heat exchanger **31** to one of the second heat exchange path **12h** and the bypass path **13h**. For example, the air current diverter **10d** may include a damper. More specifically, the air current

diverter **10d** may include a first damper **12d**, a second damper **13d**, and a fourth damper **14d**.

(65) The first damper **12d** may adjust the internal air current between the first heat exchanger **31** and the second heat exchange path **12h**. For example, the first damper **12d** may be located in the second heat exchange path **12h** to allow or block the internal air current on the first connection path **16h** transported toward the second heat exchange path **12h**. That is, when the first damper **12d** is opened, the internal air current on the first connection path **16h** may flow into the second heat exchange path **12h**. Conversely, when the first damper **12d** is closed, the internal air current on the first connection path **16h** may not flow into the second heat exchange path **12h**. In addition, the first damper **12d** may prevent the external air current in the outdoor air cooler **50** from flowing into the accommodation space SH through the second heat exchanger **35**.

(66) The second damper **13d** may adjust the internal air current between the first heat exchanger **31** and the bypass path **13h**. For example, the second damper **13d** may be located in the bypass path **13h** to allow or block the internal air current on the first connection path **16h** transported toward the bypass path **13h**. That is, when the second damper **13d** is opened, the internal air current on the first connection path **16h** may flow into the bypass path **13h**. Conversely, when the second damper **13d** is closed, the internal air current on the first connection path **16h** may not flow into the bypass path **13h**.

(67) The fourth damper **14d** may be located in the second connection path **14h**. The fourth damper **14d** may prevent the internal air current, which has bypassed the second heat exchanger **35** along the bypass path **13h**, from flowing backward to the second heat exchanger **35** along the second connection path **14h**. In addition, the fourth damper **14d** may prevent the external air current in the outdoor air cooler **50** from flowing into the accommodation space SH through the second heat exchanger **35**. That is, each of the first damper **12d** and the second damper **13d** may block the inflow of the external air current into the accommodation space SH. Details thereof will be described below.

(68) Although the air current diverter **10d** is illustrated as including three dampers, the disclosure is not limited thereto. For example, only one damper may exist between the second heat exchange path **12h** and the bypass path **13h** unlike shown in FIG. 1. That is, the internal air current passed through the first heat exchanger **31** may be allowed to flow through one of the second heat exchange path **12h** and the bypass path **13h** using a single damper according to a selection. In addition, although the air current diverter **10d** has been described as having a damper shape, the disclosure is not limited thereto. That is, unlike that shown in FIG. 1, the air current diverter **10d** may include another type of configuration capable of changing the direction of the internal air current on the circulation path **10h**.

(69) The first filter **F1** may filter the internal air current on the circulation path **10h**. For example, the first filter **F1** may include a dust filter to filter out particulate matter, such as dust, in the internal air current passing through the first filter **F1**. The first filter **F1** may be located on the circulation path **10h**. Alternatively, the first filter **F1** may be located between the circulation path **10h** and the accommodation space SH. The first filter **F1** may need to be replaced periodically. To this end, the first filter **F1** may be disposed in a place that may be easily accessed by a user. Details thereof will be described below.

(70) The second filter **F2** may filter the internal air current on the circulation path **10h**. For example, the second filter **F2** may include a photo-catalyst filter to filter out odor-causing substances in the internal air current passing through the second filter **F2**. Therefore, the dehumidification apparatus **100** for deodorization and dehumidification according to the disclosure may not only provide the deodorization effect by steam and/or dehumidification, but also the deodorization effect by the second filter **F2**. The second filter **F2** may be located on the circulation path **10h**. Alternatively, the second filter **F2** may be located between the circulation path **10h** and the accommodation space SH. The lifetime of the second filter **F2** may be relatively long. For example, the second filter **F2** may be used semi-permanently. However, the disclosure is not

limited thereto, and the second filter F2 may also need to be periodically replaced, similar to the first filter F1.

(71) The temperature sensor **19** may measure the temperature of the internal air current. The temperature sensor **19** may be disposed on the circulation path **10h**. For example, the temperature sensor **19** may be disposed on the outlet path **15h**. The temperature sensor **19** may measure the temperature of the internal air current returning to the accommodation space SH through the outlet path **15h**.

(72) The circulation blower **18** may provide the circulation path **10h** with a driving force of an internal air current. That is, the circulation blower **18** may generate an internal air current in the circulation path **10h**. More specifically, the circulation blower **18** may cause the air in the accommodation space SH to move to the circulation path **10h** and form an internal air current. The circulation blower **18** may be located on the outlet path **15h**, but is not limited thereto. The circulation blower **18** may include a blowing fan. In this case, the circulation blower **18** may generate an internal air current in the circulation path **10h** by rotation of the fan.

(73) The outdoor air cooler **50** may be connected to the second heat exchanger **35**. More specifically, the outdoor air cooler **50** may be connected to the second heat exchanger **35** to cool the second heat exchanger **35** using an external air current. The outdoor air cooler **50** may include an outdoor air cooling path **50h**, an outdoor air damper **50d**, and an outdoor air cooling blower **58**.

(74) The outdoor air cooling path **50h** may connect the second heat exchanger **35** to the outdoor space. More specifically, the outdoor air cooling path **50h** may refer to a path connecting the second heat exchanger **35** to a space outside the dehumidification apparatus **100**. A part of the outdoor air cooling path **50h** may overlap the second heat exchanger **35**. Accordingly, outdoor air may enter the space around the second heat exchanger **35** through the outdoor air cooling path **50h**. When the above-described outdoor air cooler **50** is referred to as being connected to the second heat exchanger **35**, the outdoor air cooling path **50h** provided by the outdoor air cooler **50** may partially overlap the second heat exchanger **35**. Details thereof will be described below. The outdoor air cooling path **50h** may include an outdoor air inlet path **51h** and an outdoor air outlet path **53h**. Outdoor air may be transferred to the second heat exchanger **35** along the outdoor air inlet path **51h**. Hereinafter, the air flowing into and through the outdoor air cooling path **50h** may be referred to as an external air current (EAC). The external air current cooled by the second heat exchanger **35** may return to the outdoor space along the outdoor air outlet path **53h**.

(75) The outdoor air damper **50d** may adjust the external air current between the second heat exchanger **35** and the outdoor air cooling path **50h**. The outdoor air damper **50d** may be referred to as a third damper. The outdoor air damper **50d** may include a first outdoor air damper **51d** and a second outdoor air damper **53d**. The first outdoor air damper **51d** may be located on the outdoor air inlet path **51h**. The second outdoor air damper **53d** may be located on the outdoor air outlet path **53h**. When the first outdoor air damper **51d** and the second outdoor air damper **53d** are opened, the second heat exchanger **35** may be connected to the outdoor space. When the first outdoor air damper **51d** and the second outdoor air damper **53d** are closed, the second heat exchanger **35** may be blocked from the outdoor space.

(76) The outdoor air cooling blower **58** may provide the outdoor air cooling path **50h** with a driving force of an external air current. That is, the outdoor air cooling blower **58** may generate an external air current in the outdoor air cooling path **50h**. The outdoor air cooling blower **58** may be located on the outdoor air inlet path **51h**, but is not limited thereto. The outdoor air cooling blower **58** may include a blowing fan. In this case, the outdoor air cooling blower **58** may generate an external air current in the outdoor air cooling path **50h** by rotation of the fan.

(77) The controller C may include a memory and a processor. The memory may be an integrated circuit (IC) chip that stores programs, instructions, and data for the operation of the dehumidification apparatus **100**. The processor may generate a control signal for controlling the operation of the dehumidification apparatus **100** based on the program, instruction, and data stored

in the memory. The memory and the processor may be mounted on a printed circuit board (PCB). The PCB may be located in a machine compartment (MC), but the disclosure is not limited thereto. The controller C may control the dehumidification apparatus **100**. More specifically, the controller C may control the air current diverter **10d**, the compressor **33**, the circulation blower **18**, the outdoor air cooling blower **58**, the outdoor air damper **50d**, a steam compressor **75**, a steam generator **73**, and the like.

(78) For example, when the controller C closes the first damper **12d** and the fourth damper **14d** and opens the second damper **13d**, the internal air current passed through the first heat exchanger **31** may bypass the second heat exchanger **35** and return to the accommodation space SH. The internal air current bypassed the second heat exchanger **35** may return to the accommodation space SH along the outlet path **15h**. The air returned to the accommodation space SH may have a lower temperature state as a result of bypassing the second heat exchanger **35**. In this case, the air supplied to the accommodation space SH through the circulation path **10h** may be low-temperature and low-humidity air. An operation mode of the controller C controlling the dehumidification apparatus **100** under such conditions may be referred to as a first dehumidifying mode.

(79) In the first dehumidifying mode, the controller C may open the first outdoor air damper **51d** and the second outdoor air damper **53d**. When the first outdoor air damper **51d** and the second outdoor air damper **53d** are opened, the external air current may move to the second heat exchanger **35**. Alternatively, when the controller C opens the first outdoor air damper **51d** and the second outdoor air damper **53d**, and further operates the outdoor air cooling blower **58**, a larger amount of external air current flows to the second heat exchanger **35**. The second heat exchanger **35** may release heat to the external air current. Accordingly, a refrigerant passing through the second heat exchanger **35** may be cooled by the external air current. Because the internal air current on the circulation path **10h** in the first dehumidifying mode bypasses the second heat exchanger **35**, a refrigerant in the second heat exchanger **35** may not release heat to the internal air current on the circulation path **10h**. In this case, in order to cool the refrigerant in the second heat exchanger **35**, the controller C may open the first outdoor air damper **51d** and the second outdoor air damper **53d**. When the first outdoor air damper **51d** and the second outdoor air damper **53d** are opened, an external air current may be introduced into the second heat exchanger **35**. That is, the second heat exchanger **35** may be cooled by the external air current. Accordingly, even when the internal air current on the circulation path **10h** bypasses the second heat exchanger **35**, the refrigerant passing through the second heat exchanger **35** may release heat, so that the refrigeration cycle may continue. Because, in the first dehumidifying mode, the first damper **12d** and the fourth damper **14d** are in a closed state, the external air current introduced into the second heat exchanger **35** through the outdoor air cooling path **50h** may be prevented from flowing into the accommodation space SH, or conversely, the air in the accommodation space SH may be prevented from escaping to the outside. Accordingly, odors generated from shoes disposed in the accommodation space SH may be prevented from leaking to the outside of the dehumidification apparatus **100**.

(80) In addition, when the controller C opens the first damper **12d** and the fourth damper **14d** and closes the second damper **13d**, the internal air current passed through the first heat exchanger **31** may be introduced into the second heat exchanger **35**. The internal air current on the circulation path **10h** may absorb heat from the second heat exchanger **35**, and thus have a relatively high temperature. The internal air current passed through the second heat exchanger **35** may return to the accommodation space SH along the outlet path **15h**. In this case, the air supplied to the accommodation space SH through the circulation path **10h** may be relatively high in temperature and low in humidity. An operation mode of the controller C controlling the dehumidification apparatus **100** under such conditions may be referred to as a second dehumidifying mode.

(81) In addition, the controller C may control components required to be controlled in the dehumidification apparatus **100** to turn on/off devices or adjust outputs. In addition, the controller C may receive information about the temperature of the internal air current from the temperature

sensor **19**. More specifically, the controller C may receive information about the temperature of the internal air current returning to the accommodation space SH from the temperature sensor **19**. The controller C may determine whether to perform the first dehumidifying mode or the second dehumidifying mode based on the information about the temperature of the internal air current returning to the accommodation space SH. Details thereof will be described below. With such operations of the controller C, the steam injection mode, the first dehumidifying mode, and/or the second dehumidifying mode may be performed.

(82) The inputter IP may include an input device for a user to control the dehumidification apparatus **100**. For example, the inputter IP may include a touchable display. The user may manipulate the dehumidification apparatus **100** by inputting a command to the controller C through the inputter IP.

(83) When the steam injection mode is performed, the humidity of the accommodation space SH may rise very high. In addition, when the steam injection mode is performed, the temperature of the accommodation space SH may also rise very high due to the high-temperature steam. Shoes stored in the accommodation space SH may be vulnerable to high temperatures. Therefore, after sterilizing by injecting steam to shoes in the accommodation space SH, there may be a need to lower the temperature of the accommodation space SH. To this end, the first dehumidifying mode may lower the humidity and temperature of the air in the accommodation space SH. Because in the first dehumidifying mode, the internal air current on the circulation path **10h** bypasses the second heat exchanger **35**, the internal air current may be supplied to the accommodation space SH in a fairly low temperature state. Accordingly, the accommodation space SH, the temperature of which has risen due to the high-temperature steam, may be rapidly cooled. Accordingly, the shoes in the accommodation space SH may be prevented from being damaged due to the high temperature. In addition, because the temperature is rapidly lowered using the first dehumidifying mode, the stroke time of the dehumidification apparatus **100** may be shortened. Accordingly, the user may rapidly care for shoes.

(84) When the first dehumidifying mode is performed and thus the temperature of the accommodation space SH is sufficiently lowered, the controller C may perform the second dehumidifying mode. In the second dehumidifying mode, the accommodation space SH may be supplied with air having a temperature higher than with the first dehumidifying mode. More specifically, due to the air supplied in the second dehumidifying mode, the temperature of the accommodation space SH may be maintained at a level suitable for storage of shoes.

(85) The dehumidification apparatus **100** according to embodiments of the disclosure may control the temperature of the air supplied to the accommodation space SH by bypassing the second heat exchanger **35**. That is, the temperature of the dehumidified air may be adjusted without a need to control on/off of the compressor **33**. It may take a long time to turn on/off of the compressor **33**. For example, even when the compressor **33** is turned off, heat release of the second heat exchanger **35** may not immediately stop. In addition, even when the compressor **33** is turned on, a great amount of heat may not be immediately released from the second heat exchanger **35**. Therefore, it may take a lot of time to control the dehumidification temperature through on/off operations of the compressor **33**. Furthermore, repeated on/off operations of the compressor **33** may apply a load to the compressor **33**, which may shorten the lifespan of the compressor **33**. Moreover, when the compressor **33** is turned off, the heat absorbed by the first heat exchanger **31** is also reduced or eliminated, so that the dehumidifying effect on the internal air current in the first heat exchanger **31** may be reduced or eliminated. On the other hand, the dehumidification apparatus **100** according to the disclosure may control the dehumidification temperature by selectively bypassing the second heat exchanger as required, while the compressor **33** is continuously operated. Therefore, immediate temperature control of the internal air current may be performable, which benefits the care of shoes, and shorten the stroke time. In addition, the lifespan of the compressor may be extended. Furthermore, because the dehumidifying effect of the first heat exchanger **31** is

maintained, the dehumidifying performance of the accommodation space SH may be improved.

(86) Even in a case of using an inverter compressor, the speed of dehumidification temperature control may be limited. In addition, adjusting the output of the inverter compressor may lead to a change in the amount of heat absorbed by the first heat exchanger **31**, so that the dehumidifying effect of the first heat exchanger **31** also changes. On the other hand, the dehumidification apparatus **100** according to the disclosure may use a method of bypassing the second heat exchanger **35** rather than a method of controlling the compressor **33**, and thus improve the speed of dehumidification temperature control, which is insufficient for the inverter compressor, and further maintain the dehumidification performance of the first heat exchanger **31** in a constant level.

(87) In the above, the configuration of the dehumidification apparatus **100** according to the disclosure has been briefly described with reference to FIG. **1**. Hereinafter, embodiments in which the dehumidification apparatus **100** according to the disclosure is applied to a specific product will be described with reference to FIGS. **2** to **10**.

(88) FIG. **2** is a perspective view illustrating a dehumidification apparatus according to embodiments of the disclosure, and FIG. **3** is a partially exploded perspective view illustrating a dehumidification apparatus according to embodiments of the disclosure.

(89) In the following description, components that are substantially the same as or similar to those described with reference to FIG. **1** may be omitted, or described in brief, for the sake of convenience in description.

(90) Referring to FIGS. **2** and **3**, a shoe care apparatus F may be provided. The shoe care apparatus F shown in FIG. **2** may represent an embodiment of the dehumidification apparatus **100** (refer to FIG. **1**) described with reference to FIG. **1**. The shoe care apparatus F may be an apparatus that cares for and/or stores shoes. The shoe care apparatus F may perform steam sterilization, dehumidification, and deodorization on shoes. The shoe care apparatus F may include a storage compartment SC, a discharge tank **20**, a machine compartment MC, a, and an inputter IP. The storage compartment SC, the machine compartment MC, the controller, and the inputter IP of the shoe care apparatus F may correspond to the storage compartment, the machine compartment, the controller, and the inputter of the dehumidification apparatus described with reference to FIG. **1**, respectively.

(91) The storage compartment SC may include a first housing H**1**, a door D, a shoe support **90**, a fixer **80**, a partition plate **40**, a lower support plate **60**, and a discharge tank **20**.

(92) The first housing H**1** may be a component corresponding to the first housing described with reference to FIG. **1**. The first housing H**1** may provide an accommodation space SH. Shoes may be disposed in the accommodation space SH. The shoe support **90**, the fixer **80**, the partition plate **40**, and the lower support plate **60** may be located in the accommodation space SH.

(93) The door D may be a component corresponding to the door described with reference to FIG. **1**. The door D may be coupled to a side of the first housing H**1**. The door D may allow the accommodation space SH to be divided from or connected to the outdoor space. The user may open and close the door D to accommodate shoes in the accommodation space SH or take out shoes from the accommodation space SH.

(94) The shoe support **90** may be located in the accommodation space SH. The shoe may be held on the shoe support **90**. A pair of shoes may be held inside a single shoe support **90**. The shoe support **90** may be fastened to the fixer **80** and fixed to one side of the first housing H**1**. The shoe support **90** may be detachably coupled to the first housing H**1**. For example, the shoe support **90** may be inserted into the fixer **80** in a sliding manner. More specifically, the shoe support **90** may be slid in a horizontal direction from the door D toward the inside of the first housing H**1** and coupled to the fixer **80**. The shoe support **90** may be provided in plural. For example, two shoe supports **90** may be provided. However, for the sake of simplification of description below, the shoe support **90** will be described in a single unit. Further details of the shoe support **90** will be described below with reference to FIGS. **5** and **6**.

(95) The fixer **80** may fix the shoe support **90** at a predetermined position. The fixer **80** may be located on an inner surface of the first housing **H1**. The fixer **80** may be provided in plural. For example, the fixer **80** may be provided in two fixers **80**. The two fixers **80** may be spaced apart in an upper and lower direction. However, for the sake of simplification of description below, the fixer **80** will be described in a single unit. Details of the fixer **80** will be described below with reference to FIGS. **4** and **5**.

(96) The partition plate **40** may be located in the accommodation space **SH**. More specifically, the partition plate **40** may be disposed perpendicular to the inner surface of the first housing **H1**. The partition plate **40** may have a flat shape that is deployed in a horizontal direction. The partition plate **40** may allow a plurality of pairs of shoes to be stored separately in a single shoe care apparatus **F**. The partition plates **40** may be provided in plural. For example, the partition plate **40** may be provided as two partition plates **40**. However, for the sake of simplification in description below, the partition plate **40** will be described in a single unit.

(97) The lower support plate **60** may be located in a lower portion of the accommodation space **SH**. The lower support plate **60** may cover the first filter **F1** and the second filter **F2**. The lower support plate **60** may include a lower discharge hole **61**. The lower discharge hole **61** may pass through the lower support plate **60** in the upper and lower direction. Through the lower discharge hole **61**, air in the accommodation space **SH** may move to a first filter **F1** and a second filter **F2**. That is, the accommodation space **SH** may be connected to an inlet **10X** through the lower discharge hole **61**, the first filter **F1**, and the second filter **F2**. The inlet **10X** of FIG. **3** may be a component corresponding to the inlet described with reference to FIG. **1**. That is, the inlet **10X** may be an inlet connected to the circulation path (**10h** in FIG. **1**). In addition, the first filter **F1** and the second filter **F2** may be components corresponding to the first filter and the second filter described with reference to FIG. **1**, respectively. Because the inlet **10X** is located in the lower portion of the accommodation space **SH**, air of high humidity in the accommodation space **SH** may easily flow into the inlet **10X**.

(98) The discharge tank **20** may be located below the storage compartment **SC**. For example, the discharge tank **20** may be inserted into a discharge tank groove **20X**. For easy access by a user, the discharge tank **20** may be exposed on the front of the shoe care apparatus **F**. The discharge tank **20** may provide a discharge inlet **20h**. Through the discharge inlet **20h**, water may be introduced into the discharge tank **20**. More specifically, water condensed in the first heat exchanger (**31** in FIG. **1**) described with reference to FIG. **1** may be stored in the discharge tank **20** through the discharge inlet **20h**. To this end, the positions of the discharge tank **20** and the first heat exchanger **31** may be selected such that the discharge inlet **20h** is located below the first heat exchanger **31**. The user may dispose of the water in the discharge tank **20** by separating the discharge tank **20** from the discharge tank groove **20X** whenever a predetermined time passes.

(99) The machine compartment **MC** may be located below the storage compartment **SC**. The machine compartment **MC** may include a second housing **H2**. The second housing **H2** may be a component corresponding to the second housing described with reference to FIG. **1**, but unlike FIG. **1**, the second housing **H2** may be inserted into a lower space of the first housing **H1**. The internal configuration of the second housing **H2** will be described below with reference to FIGS. **7** to **9B**.

(100) A steam tank **71**, unlike that shown in FIG. **1**, may be exposed to the outside of the machine compartment **MC**. More specifically, the steam tank **71** may be exposed on the front of the shoe care apparatus **F** so that the user may easily access the steam tank **71**. The steam tank **71** may provide a tank inlet **71h**. Water may be filled in the steam tank **71** through the tank inlet **71h**. When water is contained in the steam tank **71**, steam may be generated by the steam generator **73** and injected into the accommodation space **SH** as described with reference to FIG. **1**. The user may replenish water in the steam tank **71** by separating the steam tank **71** from a tank groove **71X** whenever a steam sterilization mode is performed more than a predetermined number of times.

(101) The inputter IP may be coupled to the door D. More specifically, the inputter IP may be located on an upper side of the door D. The inputter IP may be a touchable display. The user may control the shoe care apparatus F using the inputter IP located on the upper side of the door D.

(102) FIG. 4 is an enlarged perspective view illustrating an upper side of a dehumidification apparatus according to embodiments of the disclosure.

(103) Referring to FIG. 4, a sterilizing light source L, an outlet 10Y, and a steam injector 7N may be located on the ceiling of the first housing H1. The sterilization light source L, the outlet 10Y, and the steam injector 7N of FIG. 4 may be components corresponding to the sterilization light source, the outlet, and the steam injector described with reference to FIG. 1, respectively. The shoes in the accommodation space SH may be sterilized by ultraviolet rays or the like transmitted from the sterilization light source L.

(104) The outlet 10Y may be connected to an air current circulator of the machine compartment (MC in FIG. 3). The air dehumidified through the air current circulator may return to the accommodation space SH through the outlet 10Y. Because the outlet 10Y is installed on the ceiling of the first housing H1, the low-humidity air from the machine compartment may be spread in the accommodation space SH in a downward direction.

(105) Steam supplied from the steamer of the machine compartment (MC in FIG. 3) may be injected into the accommodation space SH through the steam injector 7N. Because the steam injector 7N is installed on the ceiling of the first housing H1, steam from the machine compartment may be injected onto the shoes in the accommodation space SH in the downward direction.

(106) The fixer 80 may include a sliding bar 81, an air current connection hole 81h, and a steam connection hole 83h. The sliding bar 81 may extend in a horizontal direction. More specifically, the sliding bar 81 may extend a predetermined length in a horizontal direction from the door (D in FIG. 3) toward the inside of the first housing (H1 in FIG. 3). The air current connection hole 81h may be connected to the air current circulator of the machine compartment (MC in FIG. 3). The air current connection hole 81h may be a component corresponding to the outlet 10Y described with reference to FIG. 1. The steam connection hole 83h may be connected to the steam generator of the machine compartment MC. Details thereof will be described below with reference to FIGS. 5 and 6.

(107) FIGS. 5 and 6 are enlarged perspective views illustrating a part of a dehumidification apparatus according to embodiments of the disclosure.

(108) Referring to FIGS. 5 and 6, the shoe support 90 may include a support body 95, an air current extension hole 91h, a steam extension hole 93h, a hanger 97, and a handle 99.

(109) The support body 95 may have a shape extending in one direction. The support body 95 may provide a sliding groove 95h. The sliding groove 95h may extend along the support body 95. The support body 95 may be coupled to the fixer 80 described with reference to FIG. 4. More specifically, the support body 95 may be slidably inserted into the fixer 80 in such a way that the sliding groove 95h engages with the sliding bar 81 described with reference to FIG. 4. That is, the support body 95 may slide in a horizontal direction from the door D toward the inside of the first housing H1 and may be slidably coupled to the fixer 80.

(110) The air current extension hole 91h may extend from the support body 95 to the inside of the hanger 97. For example, the air current extension hole 91h may extend from a rear surface of the support body 95 adjacent to the sliding groove 95h toward the hanger 97 in another horizontal direction crossing the one direction. In a state in which the shoe support 90 is coupled to the fixer 80, the air current extension hole 91h may communicate with the air current connection hole 81h described with reference to FIG. 4.

(111) The steam extension hole 93h may extend from the support body 95 to the inside of the hanger 97. For example, the steam extension hole 93h may extend from the rear surface of the support body 95 adjacent to the sliding groove 95h toward the hanger 97 in another horizontal direction crossing the one direction. The steam extension hole 93h may be spaced apart from the air current extension hole 91h. In a state in which the shoe support 90 is coupled to the fixer 80, the

steam extension hole **93h** may communicate with the steam connection hole **83h** described with reference to FIG. 4.

(112) The hanger **97** may be coupled to the front of the support body **95**. That is, the hanger **97** may be coupled to the front surface of the support body **95** opposite to the rear surface from which the air current extension hole **91h** is formed to start. The shoe may be held on the hanger **97**. For example, the shoe may be held on the hanger **97** so that the hanger **97** is inserted into the shoe. Two hangers **97** may be coupled to a single support body **95**. The two hangers **97** may be spaced apart from each other. For the sake of simplification of description, in the following description, the hanger **97** will be described in a single unit. The hanger **97** may include an outlet **971h** and a steam injector **973**.

(113) The outlet **971h** may be provided on a lower surface of the hanger **97**. The outlet **971h** may be connected to the air current extension hole **91h**. Therefore, in the state in which the shoe support **90** is coupled to the fixer **80**, the internal air current on the circulation path **10h** of the air current circulator of the machine compartment (MC, in FIG. 3) passes through the air current connection hole (**81h** in FIG. 4) and the air current extension hole **91**, and through the outlet **971h**, returns to the accommodation space SH. In a state in which a shoe is held on the shoe support **90**, the inside of the shoe may be dehumidified by the low-humidity air discharged from the air current circulator. The outlet **971h** may be provided in plural on a single hanger **97**.

(114) The steam injector **973** may be a component corresponding to the steam injector **7N** described with reference to FIG. 1. That is, as described with reference to FIG. 4, the shoe care apparatus F does not only include the steam injector **7N** on the ceiling of the first housing **H1**, but also includes the steam injector **973** on the hanger **97**. The steam injector **973** may be provided on the lower surface of the hanger **97**. The steam injector **973** may be connected to the steam extension hole **93h**. Therefore, in a state in which the shoe support **90** is coupled to the fixer **80**, a steam generated from the steamer of the machine compartment (MC in FIG. 1) may pass through the steam connection hole (**83h** in FIG. 4) and the steam extension hole **93h**, and through the steam injector **973**, jet to the accommodation space SH. In a state in which the shoe is held on the shoe support **90**, the inside of the shoe may be sterilized by the steam from the steamer. The steam injector **973** may be provided in plural on a single hanger **97**.

(115) The handle **99** may be coupled on the support body **95**. The user may move the shoe support **90** by holding the handle **99**. For example, in a state in which the shoe is held on the shoe support **90**, the user may insert or remove the shoe support **90** into or from the fixer **80** by holding the handle **99**.

(116) With the shoe care apparatus according to the embodiments of the disclosure, the shoe may be securely hung inside the first housing **H1**. In addition, steam sterilization may be performed on the inside and outside of the shoe hung on the shoe support **90**. In addition, dehumidification may be performed on the inside and outside of the shoe. Therefore, not only the outside of the shoe but also the inside of the shoe clean may be cared for cleanness.

(117) FIG. 7 is a perspective view illustrating a part of a machine compartment of a dehumidification apparatus according to embodiments of the disclosure.

(118) In the following description, a direction **D1** in FIG. 7 may be referred to as a first direction, a direction **D2** crossing the first direction **D1** may be referred to as a second direction, and a direction **D3** crossing each of the first direction **D1** and the second direction **D2** may be referred to as a third direction.

(119) Referring to FIG. 7, the machine compartment MC may include an air current circulator **10**, a heat pump **30**, a steamer, and an outdoor air cooler **50**. The air current circulator **10**, the heat pump **30**, the steamer, and the outdoor air cooler **50** are components corresponding to the air current circulator, the heat pump, the steamer, and the outdoor air cooler described with reference to FIG. 1, respectively.

(120) The air current circulator **10** may include a first heat exchange duct **11**, a first connection duct

16, a second heat exchange duct **12**, a bypass duct **13**, a second connection duct **14**, and an outlet duct **15**.

(121) The first heat exchange duct **11** may provide a first heat exchange path (**11h** in FIG. 1). That is, the first heat exchange path **11h** may be defined by the first heat exchange duct **11**. By the first heat exchange duct **11**, the inlet **10X** may be connected to the first heat exchanger **31**.

(122) The first connection duct **16** may provide a first connection path (**16h** in FIG. 1). That is, the first connection path **16h** may be defined by the first connection duct **16**. By the first connection duct **16**, the first heat exchanger **31** may be connected to the bypass duct **13** and the second heat exchange duct **12**.

(123) The second heat exchange duct **12** may provide a second heat exchange path (**12h** in FIG. 1). That is, the second heat exchange path **12h** may be defined by the second heat exchange duct **12**. By the second heat exchange duct **12**, the first connection duct **16** may be connected to the second heat exchanger **35**. A first damper **12d** may be located in the second heat exchange duct **12**.

(124) The bypass duct **13** may provide a bypass path (**13h** in FIG. 1). That is, the bypass path **13h** may be defined by the bypass duct **13**. By the bypass duct **13**, the first connection duct **16** may be connected to the outlet duct **15**. A second damper **13d** may be located in the bypass duct **13**.

(125) The second connection duct **14** may provide a second connection path (**14h** in FIG. 1). That is, the second connection path **14h** may be defined by the second connection duct **14**. By the second connection duct **14**, the second heat exchanger **35** may be connected to the outlet duct **15**. A fourth damper **14d** may be located in the second connection duct **14**.

(126) The outlet duct **15** may provide an outlet path (**15h** in FIG. 1). That is, the outlet path **15h** may be defined by the outlet duct **15**. By the outlet duct **15**, the bypass duct **13** and the second connection duct **14** may be connected to the outlet (**10Y** in FIG. 1).

(127) The heat pump **30** may include a first heat exchanger **31**, a compressor **33**, a second heat exchanger **35**, an expansion valve **37**, and a refrigerant pipe **39**. The components of the heat pump **30** may correspond to the respective components of the heat pump described with reference to FIG. 1.

(128) The first heat exchanger **31** may be surrounded by a first heat exchange cover **31C**. The first heat exchanger **31** may take a form of a tube in which a passage through which a refrigerant flows is provided. More specifically, the first heat exchanger **31** may have a serpentine tubular shape for efficient heat transfer within the first heat exchange cover **31C**. A refrigerant that has moved along the refrigerant pipe **39** may be introduced into the first heat exchanger **31**. In certain embodiments, the first heat exchanger **31** may further include a heat absorbing plate for efficiently transferring ambient heat to the refrigerant. The first heat exchange cover **31C** may surround at least a portion of the first heat exchanger **31**. An inner space defined by the first heat exchange cover **31C** may be provided at an inner side of the first heat exchange cover **31C**. An internal air current moved along the first heat exchange duct **11** may be introduced into the inner space of the first heat exchange cover **31C**. The internal air current may pass through the inner space of the first heat exchange cover **31C** and move to the first connection duct **16**. When the internal air current passes through the inner space of the first heat exchange cover **31C** while exchanging heat with the first heat exchanger **31**, the internal air current may be referred to as passing through the first heat exchanger **31**. The inner space of the first heat exchange cover **31C** may connect a first heat exchange path (**11h** in FIG. 1) provided by the first heat exchange duct **11** to the first connection path (**16h** in FIG. 1) provided by the first connection duct **16**. The inner space between the first heat exchange path **11h** and the first connection path **16h** may be considered as a part of the circulation path **10h**.

Accordingly, it can be seen that the circulation path **10h** passes through the first heat exchanger **31** in the first direction **D1**. When a refrigerant enters the first heat exchanger **31** through the refrigerant pipe **39**, the refrigerant may absorb heat from the first heat exchanger **31**. Accordingly, the temperature of the first heat exchanger **31** may be lowered. Accordingly, the first heat exchanger **31** may absorb heat from the surroundings. That is, the first heat exchanger **31** may

absorb heat from the internal air current on the circulation path **10h**. More specifically, the first heat exchanger **31** may absorb heat from the internal air current on the circulation path **10h** that passes through the surroundings of the first heat exchanger **31** in the internal space provided by the first heat exchange cover **31C**. The refrigerant passing through the first heat exchanger **31** and absorbing heat may move to the compressor **33** along the refrigerant pipe **39**. The internal air current passing through the first heat exchanger **31** and releasing heat may be introduced into the first connection duct **16**.

(129) The second heat exchanger **35** may be surrounded by a second heat exchange cover **35C**. The second heat exchanger **35** may take a tube in which a passage through which a refrigerant flows is provided. More specifically, the second heat exchanger **35** may have a serpentine tubular shape for efficient heat transfer within the second heat exchange cover **35C**. The refrigerant that has moved along the refrigerant pipe **39** may be introduced into the second heat exchanger **35**. In certain embodiments, the second heat exchanger **35** may further include a heat dissipating plate for efficiently transferring heat of the refrigerant to the surroundings. The second heat exchange cover **35C** may surround at least a portion of the second heat exchanger **35**. An inner space (**35Ch** in FIG. **8A**) defined by the second heat exchange cover **35C** may be provided at an inner side of the second heat exchange cover **35C**. An internal air current that has moved along the second heat exchange duct **12** may be introduced into the inner space **35Ch** of the second heat exchange cover **35C**. The internal air current may pass through the inner space **35Ch** of the second heat exchange cover **35C** and move to the second connection duct **14**. When the internal air current passes through the inner space **35Ch** of the second heat exchange cover **35C** while exchanging heat with the second heat exchanger **35**, the internal air current may be referred to as passing through the second heat exchanger **35**. The inner space **35Ch** of the second heat exchange cover **35C** may connect a second heat exchange path (**12h** in FIG. **1**) provided by the second heat exchange duct **12** to a second connection path (**14h** in FIG. **1**) provided by the second connection duct **14**. The inner space **35Ch** between the second heat exchange path **12h** and the second connection path **14h** may be considered a part of the circulation path **10h**. Accordingly, the circulation path **10h** passes through the second heat exchanger **35** in the first direction **D1**. When a refrigerant enters the second heat exchanger **35** through the refrigerant pipe **39**, the refrigerant may release heat to the second heat exchanger **35**. Accordingly, the temperature of the second heat exchanger **35** may rise. Accordingly, the second heat exchanger **35** may release heat to the surroundings. That is, the second heat exchanger **35** may release heat to the internal air current on the circulation path **10h**. More specifically, the second heat exchanger **35** may release heat to the internal air current on the circulation path **10h** that passes through the surrounding of the second heat exchanger **35** in the inner space **35Ch** provided by the second heat exchange cover **35C**. The refrigerant having released heat while passing through the second heat exchanger **35** may move to the expansion valve **37** along the refrigerant pipe **39**. The internal air current having heat while passing through the second heat exchanger **35** may be introduced into the second connection duct **14**.

(130) The outdoor air cooler **50** may include an outdoor air inlet duct **51** and an outdoor air outlet duct **53**.

(131) The outdoor air inlet duct **51** may provide an outdoor air inlet path **51h**. That is, the outdoor air inlet path **51h** may be defined by the outdoor air inlet duct **51**. A first outdoor air damper **51d** and an outdoor air cooling blower **58** may be located in the outdoor air inlet duct **51**. An end of the outdoor air inlet duct **51** may be connected to a space outside the machine compartment **MC**, further, the outdoor space of the shoe care apparatus (**F** in FIG. **3**). In addition, the other end of the outdoor air inlet duct **51** may be connected to the second heat exchanger **35**.

(132) The outdoor air outlet duct **53** may provide an outdoor air outlet path (**53h** in FIG. **1**). That is, the outdoor air outlet path **53h** may be defined by the outdoor air outlet duct **53**. An end of the outdoor air outlet duct **53** may be connected to the second heat exchanger **35**. The outdoor air outlet duct **53** may be connected to the outdoor air inlet duct **51** through the second heat exchanger **35**. In

addition, the other end of the outdoor air outlet duct **53** may be connected to a space outside the machine compartment MC, further, the outdoor space of the shoe care apparatus (F in FIG. 3).

(133) FIGS. **8A** and **8B** are cross-sectional views showing a portion cut away from FIG. 7, and FIGS. **9A** and **9B** are plan views of some areas of FIG. 7.

(134) Referring to FIGS. **8A** and **9A**, the first dehumidifying mode executed by the controller (C in FIG. 1) will be described.

(135) First, referring to FIG. **8A**, the first damper **12d** and the fourth damper **14d** may be closed under the control of the controller C. In addition, the second damper **13d** may be opened under the control of the controller C. Accordingly, the internal air current AC of the first connection path **16h** may bypass the second heat exchanger **35** along the bypass path **13h**. The internal air current AC may not exchange heat with the second heat exchanger **35**. Accordingly, the temperature of the internal air current AC may remain relatively low in temperature. The low-temperature internal air current AC may return to the accommodation space (SH in FIG. 2) through the outlet path **15h**. As such, the first dehumidifying mode in which the accommodation space SH is supplied with low-temperature and low-humidity air may be performed.

(136) Next, referring to FIG. **9A**, in the first dehumidifying mode, the first outdoor air damper **51d** and the second outdoor air damper **53d** may be opened under the control of the controller C. In addition, the outdoor air cooling blower **58** may be driven. The refrigerant in the second heat exchanger **35** may be cooled only by the external air current EAC rather than by the internal air current AC on the circulation path **10h**. In this case, the first damper (**12d** in FIG. **8B**) and the fourth damper (**14d** in FIG. **8B**) are closed, and thus the external air current EAC may not flow into the accommodation space SH. In addition, the internal air current AC circulating along the circulation path **10h** may not flow out to the outside. Accordingly, odors in the internal air current may be prevented from leaking to the outside.

(137) Referring to FIGS. **8B** and **9B**, the second dehumidifying mode executed by the controller (C in FIG. 1) will be described.

(138) First, referring to FIG. **8B**, the first damper **12d** and the fourth damper **14d** may be opened under the control of the controller C. In addition, the second damper **13d** may be closed under the control of the controller C. Accordingly, the internal air current AC on the first connection path **16h** may flow into the inner space **35Ch** defined by the second heat exchange cover **35C** along the second heat exchange path **12h**. The internal air current AC may receive heat from the second heat exchanger **35** in the second heat exchange cover **35C**. Accordingly, the temperature of the internal air current AC may rise. The internal air current AC in a high temperature state may pass through the second connection path **14h** and the outlet path **15h** and return to the accommodation space (SH in FIG. 2). As such, the second dehumidifying mode in which the accommodation space SH is supplied with high-temperature and low-humidity air may be performed.

(139) Next, referring to FIG. **9B**, in the second dehumidifying mode, the first outdoor air damper **51d** and the second outdoor air damper **53d** may be closed under the control of the controller C. In addition, the outdoor air cooling blower **58** may not be driven. The refrigerant in the second heat exchanger **35** may be cooled only by the internal air current on the circulation path **10h**, rather than by the outdoor air. Accordingly, outdoor air may not flow into the second heat exchanger **35**. In addition, the internal air current AC circulating along the circulation path **10h** may not flow out to the outside. Accordingly, odors in the internal air current may be prevented from leaking to the outside.

(140) FIG. **10** is a flowchart showing a dehumidification method using a dehumidification apparatus according to embodiments of the disclosure.

(141) Referring to FIG. **10**, a dehumidification method S may be provided. The dehumidification method S may be a method of performing care and storage on shoes using a dehumidification apparatus. The dehumidification method S may include performing a steam injection mode **S1**, performing a first dehumidifying mode **S2**, measuring the temperature of the air current **S3**,

performing mode determination **S4**, and performing a second dehumidifying mode **S5**. Hereinafter, each operation of the dehumidification method **S** shown in FIG. **10** will be described with reference to FIGS. **1** to **9B**.

(142) Referring to FIGS. **1** and **10**, the performing of the steam injection mode (**S1**) may include injecting steam into the accommodation space **SH** using the steamer **70**. More specifically, in response to shoes in the accommodation space **SH** requiring steam sterilization, the controller **C** may inject steam into the accommodation space **SH** using the steamer **70**, to perform steam sterilization on the shoes. Under the control of the controller **C**, water in the steam tank **71** moves along the steam pipe **77** and becomes steam in the steam generator **73**, and the steam is injected to the accommodation space **SH** through the steam injector **7N**. As described with reference to FIGS. **4** to **6**, when the steam injectors **7N** are disposed in various places, steam sterilization may be performed on the inside and outside of the shoe through steam injection. By the steam injected into the accommodation space **SH**, the temperature of the accommodation space **SH** may be significantly high.

(143) Referring to FIGS. **7**, **8A**, **9A** and **10**, the performing of the first dehumidifying mode (**S2**) may including allowing air inside the accommodation space (**SH** in FIG. **1**) to move along the circulation path **10h** of the air current circulator **10** and exchange heat with the first heat exchanger **31**. The air in the accommodation space **SH** may move along the first heat exchange path **11h** and release heat in the first heat exchanger **31**. That is, the first heat exchanger **31** may absorb heat of the internal air current. Accordingly, the temperature of the internal air current passed through the first heat exchanger **31** may be lowered.

(144) The performing of the first dehumidifying mode (**S2**) may include allowing the internal air current that has passed through the first heat exchanger **31** to return to the accommodation space **SH** by bypassing the second heat exchanger **35**. To this end, the controller **C** may close the first damper **12d** and the fourth damper **14d** and open the second damper **13d**. The internal air current that has passed through the first heat exchanger **31** and has become in a low temperature state may bypass the second heat exchanger **35** along the bypass path **13h**. That is, the internal air current may not exchange heat with the second heat exchanger **35**. Accordingly, the low-temperature internal air current may return to the accommodation space **SH** while remaining relatively low in temperature. Accordingly, the air in the accommodation space **SH**, which has been heated by the steam, may be cooled rapidly. That is, the temperature of the accommodation space **SH** may be rapidly lowered. Accordingly, the shoes in the accommodation space **SH** injected with the steam may be prevented from being damaged by the high temperature. In addition, because the temperature of the accommodation space **SH** is rapidly lowered, the stroke time of the dehumidification apparatus may be shortened.

(145) The performing of the first dehumidifying mode (**S2**) may include cooling, by the controller **C**, the second heat exchanger **35** with an external air current using the outdoor air cooler **50**. More specifically, the controller **C** may open the first outdoor air damper **51d** and the second outdoor air damper **53d**, and operate the outdoor air cooling blower **58**. Accordingly, the air outside the shoe care apparatus **F** may enter the second heat exchanger **35** along the outdoor air inlet path **51h**. The second heat exchanger **35** may release heat to the external air current. Accordingly, the refrigerant in the second heat exchanger **35** may be condensed by releasing heat. The external air current that has received heat from the second heat exchanger **35** may exit to the outside along the outdoor air outlet path **53h**.

(146) Referring again to FIGS. **1** and **10**, the measuring of the temperature of the air current (**S3**) may include measuring the temperature of the internal air current returning to the accommodation space **SH** using the temperature sensor **19**. Alternatively, when the temperature sensor **19** is located in the accommodation space **SH** and/or outside the accommodation space **SH**, the temperature sensor **19** may measure the internal and/or external temperature of the accommodation space **SH**. Information about the temperature measured by the temperature sensor **19** may be transmitted to

the controller C.

(147) The performing of the mode determination (S4) may include determining, by the controller C, whether to perform the first dehumidifying mode or perform the second dehumidifying mode based on the information received from the temperature sensor 19. For example, the controller C may compare a target temperature with the temperature currently supplied to the accommodation space SH to determine a mode to be performed. More specifically, in response to the target temperature being lower than the measured current temperature, the controller C may continue to perform the first dehumidifying mode such that the temperature of the internal air current supplied to the accommodation space SH is lowered to the target temperature. Conversely, in response to the target temperature being higher than the measured current temperature, the controller C may stop the first dehumidifying mode to increase the temperature of the internal air current supplied to the accommodation space SH, and may perform the second dehumidifying mode. The target temperature may be a temperature input by a user. Alternatively, the target temperature may be a temperature previously stored in the controller C that is optimized for caring and/or storing shoes.

(148) FIGS. 7, 8B, 9B and 10, the performing of the second dehumidifying mode (S5) may including allowing air inside the accommodation space (SH in FIG. 1) to move along the circulation path 10h of the air current circulator 10 and exchange heat with the first heat exchanger 31. The air in the accommodation space SH may move along the first heat exchange path 11h and release heat in the first heat exchanger 31. That is, the first heat exchanger 31 may absorb heat of the internal air current. Accordingly, the temperature of the internal air current having passed through the first heat exchanger 31 may be lowered.

(149) The performing of the second dehumidifying mode (S5) may include allowing the internal air current having passed through the first heat exchanger 31 to exchange heat with the second heat exchanger 35 and then return to the accommodation space SH. To this end, the controller C may open the first damper 12d and the fourth damper 14d and close the second damper 13d. The internal air current having passed through the first heat exchanger 31 and converted into a low temperature state may be directed to the second heat exchanger 35 along the second heat exchange path 12h. The internal air current on the circulation path 10h may absorb heat from the second heat exchanger 35. Accordingly, the internal air current in a low temperature state may be converted into relatively high temperature state. The internal air current converted into a high temperature state due to heat exchange with the second heat exchanger 35 may return to the accommodation space SH along the outlet path 15h. Accordingly, the temperature of the air in the accommodation space SH, which has been lowered as a result of the first dehumidifying mode, may be slightly increased or may be maintained at a certain level. That is, the temperature of the accommodation space SH may be managed at an appropriate level. Accordingly, the shoes in the accommodation space SH may be stored at an appropriate temperature.

(150) The performing of the second dehumidifying mode (S5) may include stopping, by the controller C, the outdoor air cooling of the second heat exchanger 35 using the outdoor air cooler 50C. More specifically, the controller C may close the first outdoor air damper 51d and the second outdoor air damper 53d, and stop the operation of the outdoor air cooling blower 58. Accordingly, air outside the shoe care apparatus F may not flow into the second heat exchanger 35. In addition, the internal air current on the circulation path 10h may not flow to the outside.

(151) Although the shoe care apparatus (F in FIG. 2) has been described as an example of the apparatus (100 in FIG. 1) for dehumidification, the disclosure is not limited thereto. That is, the dehumidification apparatus 100 may perform care and storage on tops and bottoms as well as shoes.

(152) FIG. 11 is a schematic diagram illustrating a dehumidification apparatus according to embodiments of the disclosure.

(153) In the following description, components that are substantially the same as or similar to those described with reference to FIGS. 1 to 10 may be omitted, or described in brief, for the sake of

convenience in description.

(154) Referring to FIG. 11, a dehumidification apparatus **100A** may be provided. The dehumidification apparatus **100A** may be partially similar to the dehumidification apparatus **100** described with reference to FIG. 1. The dehumidification apparatus **100A** may include a storage compartment SC, a machine compartment MCA, a controller C, and an inputter IP. The storage compartment SC, the controller C, and the inputter IP may be substantially the same as or similar to the storage compartment, the controller, and the inputter described with reference to FIG. 1, respectively.

(155) The machine compartment MCA may include a second housing H2, a steamer **70**, a heat pump **30A**, an air current circulator **10A**, and an outdoor air cooler **50A**.

(156) The second housing H2 may be substantially the same as or similar to the second housing described with reference to FIG. 1. The steamer **70** may be substantially the same as or similar to the steamer described with reference to FIG. 1.

(157) The heat pump **30A** may include a refrigerant pipe **39**, a first heat exchanger **31**, a compressor **33**, a second heat exchanger **35A**, and an expansion valve **37**. The refrigerant pipe **39**, the first heat exchanger **31**, the compressor **33**, and the expansion valve **37** may be substantially the same as or similar to the refrigerant pipe, the first heat exchanger, the compressor, and the expansion valve described with reference to FIG. 1, respectively. The second heat exchanger **35A** may be slightly different from the second heat exchanger **35** described with reference to FIG. 1. Details of the second heat exchanger **35A** will be described below with reference to FIGS. 13 and 14.

(158) The air current circulator **10A** may provide a circulation path **10Ah**. However, the air current circulator **10A** may be slightly different from the air current circulator **10** described with reference to FIG. 1. For example, the air current circulator **10A** may not provide the bypass path shown in FIG. 1. That is, the circulation path **10Ah** may provide only a first heat exchange path **11h**, a second heat exchange path **12h**, and an outlet path **15h**.

(159) The outdoor air cooler **50A** may be connected to the second heat exchanger **35A**. More specifically, the outdoor air cooler **50A** may be connected to the second heat exchanger **35A** to cool the second heat exchanger **35A** using an external air current. The outdoor air cooler **50A** may include an outdoor air cooling path **50Ah**, an outdoor air damper **50d**, and an outdoor air cooling blower **58**. The outdoor air cooling path **50Ah**, the outdoor air damper **50d**, and the outdoor air cooling blower **58** may be substantially the same as or similar to those described with reference to FIG. 1. However, a portion at which the outdoor air cooler **50A** is connected to the second heat exchanger **35A** may be different from that described with reference to FIG. 1.

(160) The following description will be made in relation to a part of the dehumidification apparatus **100A** that is different from that of FIG. 1.

(161) The internal air current moving along the circulation path **10Ah** may pass through the second heat exchanger **35A**. That is, the internal air current may not bypass the second heat exchanger **35A**. At the second heat exchanger **35A**, the circulation path **10Ah** may cross the outdoor air cooling path **50Ah**. The internal air current on the circulation path **10Ah** may exchange heat with the second heat exchanger **35A**. In addition, the external air current on the outdoor air cooling path **50Ah** may exchange heat with the second heat exchanger **35A**. At the second heat exchanger **35A**, the outdoor air cooling path **50Ah** may not be connected to the circulation path **10Ah**. More specifically, at the second heat exchanger **35A**, the outdoor air cooling path **50Ah** may be separated from and unconnected with the circulation path **10Ah**. Therefore, the internal air current moving along the circulation path **10Ah** may be prevented from flowing out of the dehumidification apparatus **100A** through the outdoor air cooling path **50Ah** at the second heat exchanger **35A**. In addition, the external air current on the outdoor air cooling path **50Ah** may be prevented from flowing into the accommodation space SH through the circulation path **10Ah** at the second heat exchanger **35A**. An example of a configuration for not connecting the outdoor air cooling path

50Ah to the circulation path **10Ah** at the second heat exchanger **35A** will be described below with reference to FIGS. **13** and **14**.

(162) The dehumidification apparatus **100A** according to the embodiment of FIG. **11** may also perform a steam injection mode, a first dehumidifying mode, and a second dehumidifying mode. The steam injection mode may be substantially the same as or similar to that described with reference to FIG. **1**.

(163) In the first dehumidifying mode, the internal air current AC on the circulation path **10Ah** may continuously pass through the second heat exchanger **35A**. In addition, the controller C may open the first outdoor air damper **51d** and the second outdoor air damper **53d**. As needed, the controller C may operate the outdoor air cooling blower **58**. Accordingly, the outdoor air cooler **50A** may exchange heat with the second heat exchanger **35A**. More specifically, the second heat exchanger **35A** may release heat to the external air current on the outdoor air cooling path **50Ah**. Accordingly, the refrigerant passing through the second heat exchanger **35A** may be condensed. Because the outdoor air cooler **50A** absorbs heat from the second heat exchanger **35A**, the internal air current on the circulation path **10Ah** may absorb a relatively small amount of heat or may not absorb heat. Therefore, the internal air current on the circulation path **10Ah**, which has passed through the first heat exchanger **31** and converted into a low temperature state, may remain relatively low in temperature. Accordingly, the accommodation space SH may be supplied with relatively low temperature air.

(164) In the second dehumidifying mode, the internal air current AC on the circulation path **10Ah** may continuously pass through the second heat exchanger **35A**. On the other hand, heat exchange between the outdoor air cooler **50A** and the second heat exchanger **35A** may be stopped. More specifically, the controller C may close the first outdoor air damper **51d** and the second outdoor air damper **53d**. Alternatively, the controller C may stop the operation of the outdoor air cooling blower **58** while the first outdoor air damper **51d** and the second outdoor air damper **53d** are open. Accordingly, the second heat exchanger **35A** may not exchange heat with the external air current. The second heat exchanger **35A** may exchange heat only with the internal air current on the circulation path **10Ah**. The internal air current on the circulation path **10Ah** passing through the second heat exchanger **35A** receives heat, so that the temperature of the internal air current may rise. Accordingly, the accommodation space SH may be supplied with relatively high temperature air.

(165) The dehumidification apparatus **100A** according to the embodiments of the disclosure described with reference to FIG. **11** may have substantially the same or similar effects as the dehumidification apparatus **100** described with reference to FIG. **1**.

(166) In the above, the configuration of the dehumidification apparatus **100A** according to the disclosure has been briefly described with reference to FIG. **11**. Hereinafter, an embodiment in which the dehumidification apparatus **100A** according to the disclosure is applied to a specific product will be described with reference to FIGS. **12** to **15B**.

(167) FIG. **12** is a perspective view illustrating a part of a machine compartment of a dehumidification apparatus according to embodiments of the disclosure.

(168) The dehumidification apparatus shown in FIG. **11** may be applied to a shoe care apparatus. An embodiment in which the dehumidification apparatus of FIG. **11** is applied to a shoe care apparatus may include all the components described with reference to FIGS. **2** to **6**. Accordingly, for the sake of convenience in description, components corresponding to those described with reference to FIGS. **2** to **6** may be omitted in the following description and only differences from the embodiment of FIG. **7** will be described.

(169) Referring to FIG. **12**, the machine compartment MCA of the shoe care apparatus may include a steamer, an air current circulator **10A**, a heat pump **30A**, and an outdoor air cooler **50A**.

(170) At the second heat exchanger **35A**, the air current circulator **10A** may overlap the outdoor air cooler **50A**. Unlike the air current circulator **10** described with reference to FIG. **7**, the air current

circulator **10A** may not include the bypass duct (**13** in FIG. 7) and the air current diverter (**10d** in FIG. 1).

(171) The second heat exchanger **35A** of the heat pump **30A** may be different from the second heat exchanger **35** described with reference to FIG. 7. Details thereof will be described below with reference to FIGS. **13** and **14**.

(172) At the second heat exchanger **35A**, the outdoor air cooler **50A** may overlap the air current circulator **10A** and the second heat exchanger **35A**. The outdoor air inlet path **51h** may be defined by the outdoor air inlet duct **51**. The outdoor air outlet path (**53h** in FIG. **11**) may be defined by the outdoor air outlet duct **53**. However, the disclosure is not limited thereto, and the outdoor air inlet path **51h** and the outdoor air outlet path **53h** may refer to a movement path of the external air current formed in a portion of the space inside the machine compartment **MCA** without having a separate duct.

(173) Hereinafter, the second heat exchanger **35A** of the shoe care apparatus will be described in detail with reference to FIGS. **13** to **14**.

(174) FIG. **13** is an enlarged partial exploded perspective view illustrating some areas of FIG. **12**, and FIG. **14** is an enlarged exploded perspective view illustrating some components of FIG. **13**.

(175) Referring to FIGS. **13** and **14**, the second heat exchanger **35A** may be surrounded by a second heat exchange duct **12**, an outlet duct **15**, an outdoor air inlet duct **51**, an outdoor air outlet duct **53**, an upper plate **35U**, and a lower plate **35L**.

(176) The upper plate **35U** may cover the second heat exchanger **35A** from above. More specifically, the upper plate **35U** may cover an upper side of the second heat exchanger **35A** that is surrounded by the second heat exchange duct **12**, the outlet duct **15**, the outdoor air inlet duct **51**, and the outdoor air outlet duct **53**, to isolate the second heat exchanger **35A** from the outside.

(177) The lower plate **35L** may support the second heat exchanger **35A** from below. More specifically, the lower plate **35L** may cover a lower side of the second heat exchanger **35A** that is surrounded by the second heat exchange duct **12**, the outlet duct **15**, the outdoor air inlet duct **51**, and the outdoor air outlet duct **53**, to isolate the second heat exchanger **35A** from the outside.

(178) The second heat exchanger **35A** may include a heat exchange refrigerant pipe **354**, a side plate **352**, a circulation path connector **353**, an outdoor air cooling path connector **355**, a first separation plate **357**, and a second separation plate **359**.

(179) The heat exchange refrigerant pipe **354** may be connected to the refrigerant pipe (**39** in FIG. **12**). A refrigerant passing through the compressor (**33** in FIG. **12**) may move along the refrigerant pipe **39** and enter the heat exchange refrigerant pipe **354**. The refrigerant in the heat exchange refrigerant pipe **354** may release heat to the surroundings. That is, when the refrigerant releases heat toward the heat exchange refrigerant pipe **354**, the heat exchange refrigerant pipe **354** may release heat to the surroundings. More specifically, the heat released from the refrigerant may be transferred to the surroundings through the heat exchange refrigerant pipe **354**, the circulation path connector **353**, the outdoor air cooling path connector **355**, the first separation plate **357**, and the second separation plate **359**. The refrigerant may be condensed while releasing heat in the heat exchange refrigerant pipe **354**.

(180) The side plate **352** may cover side surfaces of the heat exchange refrigerant pipe **354**, the circulation path connector **353**, the outdoor air cooling path connector **355**, the first separation plate **357**, and the second separation plate **359**. The side plate **352** may secure and support such components. The side plate **352** may provide a side through-hole **352h**. The side through-hole **352h** may allow the heat exchange refrigerant pipe **354** to be connected to the refrigerant pipe (**39** in FIG. **12**). In addition, the side through-hole **352h** may allow the outdoor air inlet path **51h** and the outdoor air outlet path (**53h** in FIG. **11**) to be connected to the inner space of the second heat exchanger **35A**. The side plate **352** may be provided in plural. For example, the side plate **352** may be provided as two side plates **352**. The two side plates **352** may be disposed to face each other.

(181) The circulation path connector **353** may provide a first path groove **353g**. The first path

groove 353g may extend in the first direction D1. The first path groove 353g may connect the second heat exchange path 12h to the outlet path (15h in FIG. 11). The first path groove 353g between the second heat exchange path 12h and the outlet path 15h may be considered a part of the circulation path (10Ah in FIG. 11). Accordingly, the circulation path 10Ah passes through the second heat exchanger 35A in the first direction D1. The first path groove 353g may be provided in plural. The plurality of first path grooves 353g may be spaced apart from each other in the second direction D2. In addition, the first path groove 353g may be provided on both the upper side and the lower side of the circulation path connector 353. The first path groove 353g formed on the upper side of the circulation path connector 353 and the first path groove 353g formed on the lower side of the circulation path connector 353 may be disposed to alternate with each other. In this case, the circulation path connector 353 may have a serpentine plate shape as shown in FIG. 14.

(182) The outdoor air cooling path connector 355 may provide a second path groove 355g and a refrigerant pipe groove 355c. The second path groove 355g may extend in the second direction D2. The second path groove 355g may connect the outdoor air inlet path 51h to the outdoor air outlet path (53h in FIG. 11). The second path groove 355g between the outdoor air inlet path 51h and the outdoor air outlet path 53h may be considered a part of the outdoor air cooling path 50Ah. Accordingly, the outdoor air cooling path 50Ah passes through the second heat exchanger 35A in the second direction D2. The second path groove 355g may be provided in plural. The plurality of second path grooves 355g may be spaced apart from each other in the first direction D1. In addition, the second path groove 355g may be provided on both the upper side and the lower side of the outdoor air cooling path connector 355. The second path groove 355g formed on the upper side of the outdoor air cooling path connector 355 and the second path groove 355g formed on the lower side of the outdoor air cooling path connector 355 may be disposed to alternate with each other. In this case, the outdoor air cooling path connector 355 may have a serpentine plate shape as shown in FIG. 14. The refrigerant pipe groove 355c may extend in the second direction D2. Each of the width and/or height of the refrigerant pipe groove 355c may be larger than that of the width and/or height of the second path groove 355g. The heat exchange refrigerant pipe 354 may be disposed in the refrigerant pipe groove 355c. Although the refrigerant pipe groove 355c is illustrated as being provided on the lower side of the outdoor air cooling path connector 355, the disclosure is not limited thereto. That is, the refrigerant pipe groove 355c may be provided even on the upper side of the outdoor air cooling path connector 355. The refrigerant pipe groove 355c may be provided in plural. The plurality of refrigerant pipe grooves 355c may be spaced apart from each other in the first direction D1.

(183) The first separation plate 357 may cover the upper side of the circulation path connector 353. The second separation plate 359 may cover the lower side of the circulation path connector 353. More specifically, the second separation plate 359 may be disposed between the circulation path connector 353 and the outdoor air cooling path connector 355.

(184) As illustrated in FIG. 14, the heat exchange refrigerant pipe 354, the second separation plate 359, the outdoor air cooling path connector 355, the circulation path connector 353, and the first separation plate 357 may be sequentially stacked in a layered structure. The layered structure may be repeated several times. In a state in which a plurality of components are stacked, the side plates 352 may be inserted on the both sides to fix and support the layered structure.

(185) As described with reference to FIGS. 13 and 14, the outdoor air cooling path connector 355 and the circulation path connector 353 may be stacked in the upper and lower direction. The first separation plate 357 and the second separation plate 359 may be inserted between the outdoor air cooling path connector 355 and the circulation path connector 353 in the layered structure, so that the connection between the first path groove 353g and the second path groove 355g may be blocked. In addition, the connection between the first path groove 353g and the second path groove 355g may be blocked also by the side plate 352. An external air current entering the second heat exchanger 35A along the outdoor air cooling path (50Ah in FIG. 11) may move along the second

path groove 355g. The internal air current entering the second heat exchanger 35A along the circulation path (10Ah in FIG. 11) may move along the first path groove 353g. Therefore, the external air current entering the second heat exchanger 35A along the outdoor air cooling path 50Ah and the internal air current entering the second heat exchanger 35A along the circulation path 10Ah may not be mixed with each other. That is, the first separation plate 357 and the second separation plate 359 are inserted between the outdoor air cooling path connector 355 and the circulation path connector 353, so that the external air current on the outdoor air cooling path 50Ah and the internal air current on the circulation path 10Ah may simultaneously flow without mixing with each other. In addition, because the heat exchange refrigerant pipe 354 is inserted between the outdoor air cooling path connector 355 and the circulation path connector 353, the external air current moving along the outdoor air cooling path 50Ah and/or the internal air current moving along the circulation path 10Ah may exchange heat with the heat exchange refrigerant pipe 354. Furthermore, the heat exchange refrigerant pipe 354 is disposed to extend in the second direction D2, so that the internal air current is prevented from flowing into the second path groove 355g, and thus odor is prevented from leaking to the outside.

(186) FIG. 15A is a plan view of some areas of FIG. 12 and FIG. 15B is a plan view of some areas of FIG. 12.

(187) Referring to FIG. 15A, in the first dehumidifying mode, the controller (C in FIG. 11) may open the first outdoor air damper 51d and the second outdoor air damper 53d. Alternatively, in the second dehumidifying mode, the controller C, in a state in which the first outdoor air damper 51d and the second outdoor air damper 53d are already open, may start the operation of the outdoor air cooling blower 58. Alternatively, without the first outdoor air damper 51d and the second outdoor air damper 53d, the controller C may only start driving the outdoor air cooling blower 58.

Accordingly, an external air current EAC may be generated in the outdoor air cooling path 50Ah. Accordingly, outdoor air cooling of the heat exchange refrigerant pipe 354 in the second heat exchanger 35A may be performed. The cooling of the heat exchange refrigerant pipe 354 in the second heat exchanger 35A may be performed by the external air current EAC on the outdoor air cooling path 50Ah. Heat transfer from the heat exchange refrigerant pipe 354 to the internal air current AC moving along the circulation path 10Ah may be weak or absent. Accordingly, the temperature of the internal air current AC on the circulation path 10Ah passed through the second heat exchanger 35A may not rise or may rise slightly. Accordingly, low-temperature and low-humidity air may be provided to the accommodation space (SH in FIG. 11).

(188) Referring to FIG. 15B, in the second dehumidifying mode, the controller (C in FIG. 11) may close the first outdoor air damper 51d and the second outdoor air damper 53d. Alternatively, in the second dehumidifying mode, the controller C may stop the operation of the outdoor air cooling blower 58 in a state in which the first outdoor air damper 51d and the second outdoor air damper 53d are open. Alternatively, without the first outdoor air damper 51d and the second outdoor air damper 53d, the controller C may only stop the driving of the outdoor air cooling blower 58. Accordingly, an external air current may not be formed in the outdoor air cooling path 50Ah. Accordingly, the outdoor air cooling of the heat exchange refrigerant pipe 354 of the second heat exchanger 35A may be stopped or only weak. The cooling of the heat exchange refrigerant pipe 354 in the second heat exchanger 35A may be performed by the internal air current AC moving along the circulation path 10Ah. Accordingly, the temperature of the internal air current AC on the circulation path 10Ah passed through the second heat exchanger 35A may increase. Accordingly, high-temperature and low-humidity air may be provided to the accommodation space (SH, see FIG. 11).

(189) FIG. 16 is a flowchart of a dehumidification method using a dehumidification apparatus according to embodiments of the disclosure.

(190) Referring to FIG. 16, a dehumidification method (S') may be provided. The dehumidification method (S') may be a method of caring for and storing shoes using a dehumidification apparatus.

The dehumidification method (S') may include performing a steam injection mode (S1'), performing a first dehumidifying mode (S2'), measuring the temperature of an air current (S3'), performing mode determination (S4'), and performing a second dehumidifying mode (S5'). Hereinafter, each operation of the dehumidification method S' shown in FIG. 16 will be described with reference to FIGS. 11 to 15B.

(191) The performing of the steam injection mode (S1') may be substantially the same as or similar to the performing of the steam injection mode (S1) described with reference to FIG. 10.

(192) Referring to FIGS. 12, 15A and 16, the performing of the first dehumidifying mode (S2') may allow air in the accommodation space (SH, see FIG. 11) to move along the circulation path 10Ah of the air current circulator 10A and sequentially pass the first heat exchanger 31 and the second heat exchanger 35A. The internal air current on the circulation path 10Ah may pass through the second heat exchanger 35A and return to the accommodation space SH.

(193) The performing of the first dehumidifying mode (S2') may further include cooling, by the controller (C in FIG. 11), the second heat exchanger 35A with an external air current using the outdoor air cooler 50A. That is, the outdoor air cooler 50A may be used to transport an external air current to the second heat exchanger 35A such that the second heat exchanger 35A is subject to outdoor air cooling. More specifically, the controller C may open the first outdoor air damper 51d and the second outdoor air damper 53d and/or operate the outdoor air cooling blower 58.

Accordingly, outdoor air may enter the second heat exchanger 35A along the outdoor air inlet path 51h. The second heat exchanger 35A may release heat to the external air current. Accordingly, the second heat exchanger 35A may be cooled. The external air current, the temperature of which has risen by receiving heat from the second heat exchanger 35A, may escape to the outside along the outdoor air outlet path 53h.

(194) In the performing of the first dehumidifying mode (S2'), the second heat exchanger 35A may be cooled by an external air current on the outdoor air cooling path 50Ah. Accordingly, the cooling effect by the internal air current on the circulation path 10Ah may be relatively weak. That is, the temperature of the internal air current on the circulation path 10Ah passed through the second heat exchanger 35A may be relatively low. The air supplied to the accommodation space SH may be relatively low in temperature and low in humidity.

(195) Referring to FIG. 16, the measuring of the temperature of the air current (S3') may be substantially the same as or similar to the measuring of the temperature of the air current (S3) described with reference to FIG. 10. The mode identification (S4') may be substantially the same as or similar to the mode determination (S4) described with reference to FIG. 10.

(196) Referring to FIGS. 12, 15B and 16, the performing of the second dehumidifying mode (S5') may include allow the air in the accommodation space (SH, see FIG. 11) to move along the circulation path 10Ah of the air current circulator 10A and sequentially pass through the first heat exchanger 31 and the second heat exchanger 35A. The internal air current on the circulation path 10Ah may pass through the second heat exchanger 35A and return to the accommodation space SH.

(197) The performing of the second dehumidifying mode (S5') may further include stopping, by the controller (C in FIG. 11), the outdoor air cooling of the second heat exchanger 35A using the outdoor air cooler 50A. More specifically, the controller C may close the first outdoor air damper 51d and the second outdoor air damper 53d and/or stop the operation of the outdoor air cooling blower 58. Accordingly, an external air current in which outdoor air is directed toward the second heat exchanger 35A may not be generated. Accordingly, the outdoor air cooling for the second heat exchanger 35A using the external air current may be stopped.

(198) In the performing of the second dehumidifying mode (S5'), the second heat exchanger 35A may be cooled by the internal air current on the circulation path 10Ah. The cooling effect by the external air current on the outdoor air cooling path 50Ah may be relatively weak or absent. Accordingly, the temperature of the internal air current on the circulation path 10Ah passed through the second heat exchanger 35A may be relatively high. The air provided to the accommodation

space SH may be relatively high in temperature and low in humidity.

(199) As is apparent from the above, the dehumidification apparatus according to the disclosure and the dehumidification method using the same can rapidly adjust the temperature of a dehumidified air current.

(200) The dehumidification apparatus according to the disclosure and the dehumidification method using the same can adjust the dehumidifying temperature without controlling the output of the compressor.

(201) The dehumidification apparatus according to the disclosure and the dehumidification method using the same can adjust the dehumidifying temperature while maintaining the dehumidifying performance above a certain level.

(202) The dehumidification apparatus according to the disclosure and the dehumidification method using the same can prevent shoes from being damaged and shorten the stroke time by rapidly lowering the temperature in a storage compartment supplied with a high-temperature steam and removing moisture.

(203) The effects of the disclosure are not limited to those described above, and other effects not described above will be clearly understood by those skilled in the art from the above detailed description.

(204) Although few embodiments according to the disclosure have been shown and described, the above embodiment is illustrative purpose only, and it would be appreciated by those skilled in the art that changes and modifications may be made in these embodiments without departing from the principles and scope according to the disclosure, the scope of which is defined in the claims and their equivalents.

(205) Although the present disclosure has been described with various embodiments, various changes and modifications may be suggested to one skilled in the art. It is intended that the present disclosure encompass such changes and modifications as fall within the scope of the appended claims.

Claims

1. A dehumidification apparatus comprising: a storage compartment configured to provide an accommodation space; a circulation blower configured to form an internal air current flowing along a circulation path connected to the accommodation space; a heat pump configured to exchange heat with the internal air current flowing along the circulation path; an outdoor air cooler including an outdoor air cooling path and an outdoor damper disposed in the outdoor air cooling path, the outdoor air cooling path separate from the circulation path; and an air current diverter, wherein the heat pump includes: a first heat exchanger configured to absorb heat from the internal air current; and a second heat exchanger configured to release heat to a surrounding, wherein the circulation path includes: a first circulation path in which the internal air current passed through the first heat exchanger passes through the second heat exchanger and flow to the accommodation space; and a second circulation path in which the internal air current passed through the first heat exchanger bypasses the second heat exchanger and flow to the accommodation space, and wherein the air current diverter is configured to divert the circulation path from the first circulation path to the second circulation path, and wherein the outdoor air damper selectively opens when the air current diverter diverts the circulation path from the first circulation path to the second circulation path.

2. The dehumidification apparatus of claim 1, further comprising a steamer configured to inject a steam into the accommodation space.

3. The dehumidification apparatus of claim 1, further comprising a controller configured to control the air current diverter, wherein the controller is further configured to: perform a first dehumidifying mode by controlling the air current diverter such that the internal air current is directed to the accommodation space along the second circulation path; and perform a second

dehumidifying mode by controlling the air current diverter such that the internal air current is directed to the accommodation space along the first circulation path.

4. The dehumidification apparatus of claim 3, wherein the air current diverter includes: a first damper configured to selectively block a path connecting the first heat exchanger to the second heat exchanger; and a second damper configured to selectively block a path allowing the internal air current passed through the first heat exchanger to bypass the second heat exchanger, and wherein the controller is further configured to: perform the first dehumidifying mode by controlling the air current diverter such that the first damper is closed and the second damper is opened; and perform the second dehumidifying mode by controlling the air current diverter such that the first damper is opened and the second damper is closed.

5. The dehumidification apparatus of claim 3, further comprising: an outdoor air inlet path provided to allow the external air introduced from an outdoor space via the outdoor air damper to pass through the second heat exchanger and flow to an outside; and wherein the controller is further configured to control the outdoor air damper such that the outdoor air inlet path is opened during the first dehumidifying mode.

6. The dehumidification apparatus of claim 3, further comprising a temperature sensor configured to output a signal for detecting a temperature of the internal air current, wherein the controller is further configured to control the air current diverter based on the signal received from the temperature sensor.

7. The dehumidification apparatus of claim 6, wherein: the temperature sensor is disposed between the second heat exchanger and the accommodation space on the circulation path, the controller is configured to: detect a current temperature based on the signal received from the temperature sensor, compare the current temperature with a target temperature, and upon determining that the current temperature is higher than the target temperature, perform the first dehumidifying mode, and upon determining that the current temperature is lower than the target temperature, perform the second dehumidifying mode.

8. The dehumidification apparatus of claim 1, wherein: the first heat exchanger is an evaporator, and the second heat exchanger is a condenser.

9. The dehumidification apparatus of claim 1, further comprising: a first housing forming the accommodation space; a fixer located on an inner surface of the first housing; and a shoe support detachably mounted on the fixer.

10. The dehumidification apparatus of claim 9, wherein: the shoe support further includes a hanger on which a shoe is held, the fixer is provided with an air current connection hole connected to the circulation path, and the hanger includes an outlet port through which air supplied through the air current connection hole is discharged.

11. A dehumidification apparatus comprising: a storage compartment forming an accommodation space; a circulation blower configured to form an internal air current flowing along a circulation path connected to the accommodation space; a heat pump configured to exchange heat with the internal air current moving along the circulation path, and includes an evaporator, a compressor, a condenser, an expansion valve, and a refrigerant pipe; an outdoor cooling blower configured to form an external air current in an outdoor air cooling path separate from the circulation path and connected to an outdoor space; an air current diverter; an outdoor air damper disposed in the outdoor air cooling path; and a controller configured to control the outdoor air cooling blower, wherein the internal air current introduced from the accommodation space sequentially passes through the evaporator and the condenser along the circulation path and returns to the accommodation space, and wherein the controller is configured to select and perform at least one of: a first dehumidifying mode in which the external air current is transferred to the condenser to perform outdoor air cooling on the condenser; and a second dehumidifying mode in which the outdoor air cooling on the condenser using the external air current is stopped, wherein the outdoor air damper selectively when the air current diverter diverts the circulation path from a first

circulation path to a second circulation path.

12. The dehumidification apparatus of claim 11, further comprising a steamer configured to inject a steam to the accommodation space, wherein the controller is further configured to perform a steam injecting mode by controlling the steamer such that the steam is injected to the accommodation space.

13. The dehumidification apparatus of claim 11, wherein the controller is further configured to: perform the first dehumidifying mode after a steam injecting mode is performed, and perform the second dehumidifying mode after the first dehumidifying mode is performed.

14. The dehumidification apparatus of claim 11, wherein the outdoor air cooling path is separate from and not connected to the circulation path.

15. The dehumidification apparatus of claim 14, wherein: the circulation path passes through the condenser in a first direction, and the outdoor air cooling path passes through the condenser in a second direction crossing the first direction.

16. The dehumidification apparatus of claim 11, wherein the controller is further configured to open the outdoor air damper in the first dehumidifying mode.

17. The dehumidification apparatus of claim 11, further comprising: a first housing forming the accommodation space; a fixer located on an inner surface of the first housing; and a shoe support detachably mounted on the fixer.

18. The dehumidification apparatus of claim 17, wherein: the shoe support further includes a hanger on which a shoe is held, the fixer is provided with an air current connection hole connected to the circulation path, and the hanger includes an outlet port through which air supplied through the air current connection hole is discharged.
