

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407589
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hatta; Saki et al.

Packet capture device and packet capture method

Abstract

A packet capture device a packet analysis unit that analyzes an input packet; a flow identification unit that identifies a flow as a capture target; an output adjustment unit that adjusts a packet amount of the flow as the capture target to be output to a storage unit; a buffer unit that temporarily accumulates a packet of the flow as the capture target; and the storage unit that stores the packet of the flow as the capture target, in which the output adjustment unit is configured to decide whether to output the packet of the flow as the capture target to the storage unit for each predetermined measurement interval on the basis of a measurement result of the packet amount of the capture target in a predetermined measurement interval, and discard the packet not to be output to the storage unit.

Inventors:	Hatta; Saki (Tokyo, JP), Uzawa; Hiroyuki (Tokyo, JP), Yoshida; Shuhei (Tokyo, JP), Nitta; Koyo (Tokyo, JP)
Applicant:	Nippon Telegraph and Telephone Corporation (Tokyo, JP)
Family ID:	84425105
Assignee:	NIPPON TELEGRAPH AND TELEPHONE CORPORATION (Tokyo, JP)
Appl. No.:	18/568470
Filed (or PCT Filed):	June 11, 2021
PCT No.:	PCT/JP2021/022234
PCT Pub. No.:	WO2022/259502
PCT Pub. Date:	December 15, 2022

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Publication Classification

Int. Cl.: H04L43/062 (20220101); H04L43/026 (20220101); H04L43/067 (20220101);
H04L43/16 (20220101); H04L43/12 (20220101)

U.S. Cl.:

CPC H04L43/062 (20130101); H04L43/067 (20130101); H04L43/16 (20130101);

Field of Classification Search

CPC: H04L (43/062); H04L (43/067); H04L (43/16); H04L (43/026); H04L (43/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8937962	12/2014	Tomonaga	370/428	H04L 65/80
2005/0213504	12/2004	Enomoto	370/235	H04L 47/32
2013/0254324	12/2012	Kramnik	709/213	H04L 43/04
2013/0258858	12/2012	Cherian et al.	N/A	N/A
2014/0355613	12/2013	Pope et al.	N/A	N/A
2017/0339062	12/2016	Mayer-Wolf	N/A	H04L 49/9005
2022/0045918	12/2021	Ogita	N/A	H04L 43/022

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4955722	12/2011	JP	N/A

OTHER PUBLICATIONS

R. Takao, "IOS-XE: How to capture packets using EPC (Embedded Packet Capture)," Cisco Community, Jul. 22, 2020, 39 pages total with English Translation. cited by applicant

Primary Examiner: Hossain; Kamal M

Attorney, Agent or Firm: Slater Matsil, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a national phase entry of PCT Application No. PCT/JP2021/022234, filed on Jun. 11, 2021, which application is hereby incorporated herein by reference.

TECHNICAL FIELD

(2) The present invention relates to a packet capture technology of capturing a packet in a network.

BACKGROUND

(3) With the progress of virtualization technology in network functions virtualization (NFV)/software defined networking (SDN), various services using virtual machines (VMs) and the like are provided, and the network becomes large and complicated. A packet capture device capable of selectively capturing a packet of a specific flow (aggregate of packets in which a rule obtained by combining transmission source/destination MAC addresses, IP addresses, and the like is the same) is one of devices essential for failure analysis of the network described above.

(4) FIG. 11 illustrates a configuration diagram of a conventional packet capture device (Patent Literature 1). The conventional packet capture device includes a packet analysis unit 11 that analyzes a header of an input packet, and a flow identification unit 12 that specifies a flow registered in a rule table. A filtering unit 13 discards a flow packet that does not correspond in the flow identification unit 12, outputs the corresponding flow to a capture file generation unit, buffers a plurality of packets to be collected, then converts the packet into a capture file, and stores the capture file in a storage unit 16.

CITATION LIST

Patent Literature

(5) Patent Literature 1: JP 4955722 B2

SUMMARY

Technical Problem

(6) In the configuration of the conventional device, when a packet input rate exceeds a capture rate (processing speed of conversion into a capture file and writing to a storage medium), the process of writing the capture file into the storage unit 16 cannot be performed in time, and the buffer overflows. There is a problem that continuous discarding of input packets occurs for a long time due to buffer overflow, and there is a possibility that all capture data in a time zone required for analysis is lost.

(7) As a method for avoiding continuous discarding, it is conceivable to prepare a sufficient amount of buffers, but the amount of buffers capable of filling the difference between the input rate and the internal processing speed at the high speed NW becomes enormous, and there is a problem that the circuit scale becomes large.

(8) Embodiments of the present invention have been made to solve the above problems, and an object of embodiments of the present invention is to provide a packet capture device capable of preventing loss of capture data due to continuous discarding of input packets while avoiding an increase in circuit scale.

Solution to Problem

(9) In order to solve the above problem, provided is a packet capture device that captures a packet flowing through a capture target network, the packet capture device including: a packet analysis unit that analyzes an input packet; a flow identification unit that identifies a flow as a capture target; an output adjustment unit that adjusts a packet amount of the flow as the capture target to be output to a storage unit; a buffer unit that temporarily accumulates a packet of the flow as the capture target; and the storage unit that stores the packet of the flow as the capture target, in which the output adjustment unit is configured to decide whether to output the packet of the flow as the capture target to the storage unit for each predetermined measurement interval on the basis of a measurement result of the packet amount of the capture target in a predetermined measurement interval, and discard the packet not to be output to the storage unit.

(10) In order to solve the above problem, a packet capture method of embodiments of the present invention is a packet capture method in a packet capture device that captures a packet flowing through a capture target network, the packet capture method including steps of: analyzing an input packet; identifying a flow as a capture target; adjusting a packet amount of the flow as the capture target to be stored; temporarily accumulating a packet of the flow as the capture target; and storing the packet of the flow as the capture target, in which, in the adjusting the packet amount, whether to store the packet of the flow as the capture target for each predetermined measurement interval is

decided on the basis of a measurement result of the packet amount of the capture target in a predetermined measurement interval, and the packet not to be stored is discarded.

Advantageous Effects of Embodiments of Invention

(11) According to embodiments of the present invention, it is possible to provide a packet capture device capable of preventing loss of capture data due to continuous discarding of input packets while avoiding an increase in circuit scale.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram illustrating a configuration example of a packet capture device according to a first embodiment of the present invention.
- (2) FIG. 2 is a diagram for explaining an operation of an output adjustment unit according to the first embodiment of the present invention.
- (3) FIG. 3 is a diagram illustrating a configuration example of the output adjustment unit according to the first embodiment of the present invention.
- (4) FIG. 4 is a flowchart illustrating an operation procedure of a packet capture method according to the first embodiment of the present invention.
- (5) FIG. 5 is a diagram illustrating a configuration example of the output adjustment unit according to a second embodiment of the present invention.
- (6) FIG. 6 is a flowchart illustrating an operation procedure in a packet capture device according to the second embodiment of the present invention.
- (7) FIG. 7 is a diagram illustrating a configuration example of a packet capture device according to a third embodiment of the present invention.
- (8) FIG. 8 is a flowchart illustrating an example of an operation procedure in a threshold determination unit according to the third embodiment of the present invention.
- (9) FIG. 9 is a flowchart illustrating another example of an operation procedure in the threshold determination unit according to the third embodiment of the present invention.
- (10) FIG. 10 is a configuration example of a computer for achieving the packet capture device according to the present embodiment.
- (11) FIG. 11 is a diagram illustrating a configuration of a conventional packet capture device.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

(12) Hereinafter, embodiments of the present invention will be described in detail with reference to the drawings. The present invention is not limited to the following embodiments.

First Embodiment

(13) A first embodiment of the present invention will be described. FIG. 1 is a diagram illustrating a configuration example of a packet capture device according to the first embodiment of the present invention. FIG. 2 is a diagram for explaining an operation of an output adjustment unit according to the first embodiment of the present invention.

(14) Configuration of Packet Capture Device

(15) A packet capture device **10** is a device that captures a packet flowing through a capture target network **200**. The packet capture device **10** includes: a packet analysis unit **11** that analyzes an input packet; a flow identification unit **12** that identifies a flow as a capture target; a filtering unit **13** that filters the packet of the flow as the capture target on the basis of an identification result of the flow identification unit **12**; an output adjustment unit **14** that adjusts a packet amount of the flow as the capture target to be output to a storage unit **16**; a capture file generation unit **15** that has a buffer for temporarily accumulating a packet in order to generate a capture file of the flow as the capture target and generates the file; and the storage unit **16** that stores the packet of the flow as the capture target. The output adjustment unit **14** is arranged in a preceding stage of the capture file

generation unit **15**, and is configured to decide whether to output the packet of the flow as the capture target to the storage unit **16** and discard the packet not to be output to the storage unit **16**. The output adjustment unit **14** can prevent the occurrence of the long-time continuous discarding of the input packet by discarding the packets thinned out for each measurement interval.

(16) Operation of Output Adjustment Unit

(17) FIG. **2** is a diagram for explaining an operation of an output adjustment unit according to the first embodiment of the present invention. The output adjustment unit is configured to decide whether to output the packet of the flow as the capture target to the storage unit **16** every predetermined measurement interval on the basis of the measurement result of the packet amount of the capture target in the predetermined measurement interval, and discard the packet not to be output to the storage unit **16**.

(18) In FIG. **2**, the packet amount of the packet to be captured is measured at predetermined measurement intervals, and when the measured packet amount is equal to or larger than a predetermined decision threshold, the packet as the capture target input thereafter is discarded. When the measurement interval ends, the measured packet amount is reset, and the measurement of the packet amount is resumed. Thereafter, by repeating this operation, packet discard processing is performed at predetermined measurement intervals.

(19) By such an operation, input packet discarding can be performed by thinning out at regular measurement intervals. Therefore, it is possible to avoid packet discarding that continues for a long time while avoiding an increase in the circuit scale without preparing an enormous buffer amount. In FIG. **2**, as the measurement interval is made smaller, the discard frequency becomes higher, and the amount of packets discarded in one measurement interval becomes smaller. The measurement interval can be appropriately determined by the user according to system requirements such as the amount of packets to be captured and the buffer amount.

(20) Configuration of Output Adjustment Unit

(21) FIG. **3** is a diagram illustrating a configuration example of the output adjustment unit according to the first embodiment of the present invention. In the configuration example of FIG. **3**, the output adjustment unit **14** includes a cumulative counter unit **21** that accumulates and adds the byte (bit) length of the input packet by the measurement interval, and a discard decision unit **22** that compares the cumulative addition value in the cumulative counter unit **21** with a decision threshold and determines whether to discard the input packet. The discard decision unit **22** allows a packet output to the storage unit **16** to pass as a pass packet at each measurement interval, and discards a packet not output to the storage unit **16**.

(22) The counter of the cumulative counter unit **21** starts cumulative addition after the start of the measurement interval, is reset after the measurement interval elapses, and this is repeated. As a result, a packet output to the storage unit **16** is determined for each measurement interval and a packet not output to the storage unit **16** can be discarded. The measurement interval can be changed by user setting, and the measurement interval can be appropriately set according to system requirements.

(23) When the capture rate as the bottleneck is known in advance, the maximum count value according to the capture rate as the bottleneck can be set as the decision threshold in the discard decision unit **22** by setting the value of capture rate $\times$ measurement interval. The discard decision unit **22** is configured to compare the calculated rate of the input packet with the decision threshold and discard the input packet when the cumulative counter value $>$ the decision threshold is satisfied.

(24) When the cumulative counter value $>$ the decision threshold is not satisfied, the input packet is output to the capture file generation unit **15** as a pass packet. The capture file generation unit **15** includes a two-sided buffer of a passage packet writing surface and a writing surface to the storage unit **16**, and can simultaneously write the passage packet into the buffer and output the passage packet from the buffer to the storage unit **16** by the two-sided buffer.

(25) Operation of Packet Capture Method

(26) A packet capture method of embodiments of the present invention includes steps of: analyzing an input packet; identifying a flow as a capture target; temporarily accumulating a packet of the flow as the capture target; storing the packet of the flow as the capture target in a storage unit **16**; and determining the packet to be output to the storage unit **16** at predetermined measurement intervals on the basis of a measurement result of a packet amount of the capture target at a predetermined measurement interval and discarding the packet not to be output to the storage unit **16**.

(27) FIG. **4** is a flowchart illustrating an operation procedure of a packet capture method according to the first embodiment of the present invention. In the packet capture device **10**, when a packet is received from the capture target network **200** (step **S1-1**), the received packet is buffered (step **S1-2**), and header information is extracted by performing header analysis of the packet (step **S1-3**).

(28) Next, the header extracted by the header analysis is compared with a rule in a rule table **100** to identify whether the flow is a flow as a capture target (step **S1-4**). When the flow does not match the rule (step **S1-5**: NO), the buffered packet is discarded (step **S1-6**).

(29) When the flow matches the rule (step **S1-5**: YES), the packet length in the measurement interval is cumulatively added (step **S1-7**), and the cumulative addition value of the packet length is compared with the decision threshold (step **S1-8**). When the cumulative addition value is larger than the decision threshold (step **S1-8**: YES), the packet is discarded (step **S1-6**).

(30) When the cumulative addition value is equal to or smaller than the decision threshold (step **S1-8**: NO), a capture file is generated (step **S1-9**), and the generated capture file is stored in the storage unit (step **S1-10**).

(31) As described above, in the first embodiment, the output adjustment unit **14** that determines whether to output the packet of the flow as the capture target to the storage unit **16** for each predetermined measurement interval on the basis of the measurement result of the packet amount of the capture target in the predetermined measurement interval and discards the packet not to be output to the storage unit **16** is provided. Therefore, it is possible to finely discard the input packet in units of measurement intervals, and it is possible to avoid the continuously discarding of the input packet for a long time due to buffer overflow.

(32) In the present embodiment, the case where it is determined whether to output the packet of the flow as the capture target to the storage unit **16** by comparing the cumulative addition value of the packet length with the decision threshold has been described. However, the amount of the packet of the capture target as a reference for determination can be acquired by another method. For example, the output adjustment unit **14** may acquire the accumulation amount of packets accumulated in the buffer of the capture file generation unit **15** at a predetermined measurement interval, and determine whether to output the packet to the storage unit **16** on the basis of the accumulation amount.

(33) In this case, the discard decision unit **22** is configured to output the input packet of the capture target to the buffer unit when the accumulation amount in the buffer of the capture file generation unit **15** is equal to or smaller than a predetermined decision threshold, and discard the input packet of the capture target when the accumulation amount in the buffer unit is larger than the predetermined decision threshold.

(34) The rate of the packet of the capture target is calculated using the cumulative addition value of the packet length which is the amount of the packet of the capture target, and the calculated rate and the capture rate of the capture file conversion are compared to determine whether to discard the packet. In this case, a writing rate of a packet from the buffer unit to the storage unit **16** can be used as the decision threshold in the discard decision unit **22**.

(35) As described above, by determining whether to discard the packet by using the information on the accumulation amount in the buffer and the packet writing rate from the buffer to the storage unit **16**, it is possible to avoid continuous discarding of the input packet for a long time due to buffer overflow.

Second Embodiment

(36) In the first embodiment, a configuration has been described in which the output adjustment unit **14** cumulatively adds the byte (bit) length of the input packet at the measurement interval and discards the input packet until the start of the next measurement interval after the cumulative addition value exceeds the decision threshold, so that the discard amount of the discard packet can be thinned out. In the second embodiment, a configuration example in which discarded packet information is clarified by counting discarded packet types will be described.

(37) FIG. 5 is a diagram illustrating a configuration example of the output adjustment unit according to a second embodiment of the present invention. The difference from the output adjustment unit **14** of the first embodiment is that a discard counter unit **33** that counts the number of discarded packets of the discarded packet for each type is provided. The discard counter unit **33** identifies the packet discarded by the discard decision unit **22** for each flow and counts the number of packets discarded for each flow of the packet. The flow is identified using a result of type determination by the flow identification unit **12**. A counter for counting the number of discarded packets may be prepared for each flow type, or when a counter scale for each flow is increased, a counter for collectively counting a plurality of flows may be prepared.

(38) FIG. 6 is a flowchart illustrating an operation procedure in a packet capture device according to the second embodiment of the present invention. Processing similar to the flowchart of FIG. 4 is performed except that processing of storing the number of discarded packets for each flow (step S2-8) is added.

(39) As described above, according to the second embodiment, by outputting the number of discarded packets for each flow of packets to the storage unit **16**, it is possible to grasp the type of the discarded flow and the number of discarded packets through the storage unit **16**. With such a configuration, even if the content of the packet cannot be grasped as the capture file, the type and number of flows of the discarded packet can be grasped, so that it is possible to provide data useful for analysis after packet capture.

Third Embodiment

(40) In the first and second embodiments, a configuration has been described in which the output adjustment unit **14** cumulatively adds the byte (bit) length of the input packet at the measurement interval and discards the input packet until the start of the next measurement interval after the cumulative addition value exceeds the decision threshold, so that the discard amount of the discard packet can be thinned out. In the case of the first and second embodiments, since it is not determined whether to discard on the basis of the buffer accumulation amount of the capture file generation unit **15**, when the capture rate decreases due to processing other than the capture rate as a bottleneck, and when the decision threshold for determining whether to discard is constant, buffer overflow may occur. In the third embodiment, a configuration example in which the decision threshold is dynamically changed on the basis of the buffer accumulation amount of the capture file generation unit **15** will be described.

(41) FIG. 7 is a diagram illustrating a configuration example of a packet capture device according to a third embodiment of the present invention. The present embodiment is different from the first and second embodiments in that a threshold determination unit **17** that dynamically determines a threshold on the basis of the buffer accumulation amount of the capture file generation unit **15** is added.

(42) In the threshold determination unit **17**, since the number of packet processing that can be processed without causing buffer overflow can be grasped from the buffer accumulation amount, for example, when the buffer accumulation amount is large, it is an imminent situation immediately before the buffer overflow. Therefore, by setting a decision threshold of a small value, packets are promptly discarded and thinned out. On the other hand, when the buffer accumulation amount is relatively small, since there is a margin in the buffer amount, control is performed such that the decision threshold is determined to be a relatively large value according to the buffer accumulation

amount.

(43) Control of Decision Threshold According to Buffer Accumulation Amount

(44) The threshold determination unit **17** dynamically determines a threshold on the basis of the buffer accumulation amount of the capture file generation unit **15**. In the present embodiment, a plurality of accumulation amount thresholds for determining the magnitude of the accumulation amount of the packet and a plurality of predetermined decision thresholds are provided, and the decision threshold is determined on the basis of a comparison result between the accumulation amount of the packet and the plurality of accumulation amount thresholds. The decision threshold is changed for each measurement interval.

(45) For example, the accumulation amount of the packet in the buffer is divided into four stages, the accumulation amount threshold ($AC_high, AC_mid, AC_low, AC_high > AC_mid > AC_low$) is determined as the accumulation amount threshold of three buffers serving as the divisions of the respective stages, and the decision threshold ($TH_low, TH_mid, TH_high\ 1, TH_high\ 2, TH_low < TH_mid < TH_high\ 1 < TH_high\ 2$) corresponding to these accumulation amount thresholds is determined. In the following description, a case where the accumulation amount of packets in the buffer is divided into four stages will be described, but the number of the accumulation amount threshold and the number of the decision threshold are not limited thereto, and the number of the accumulation amount threshold and the number of the decision threshold can be appropriately determined by the user according to system requirements such as the amount of packets to be captured and the buffer amount.

(46) Assuming that the accumulation amount threshold indicating a state in which the buffer accumulation amount is large is AC_high (first accumulation amount threshold), the accumulation amount threshold indicating a state in which the buffer accumulation amount is medium is AC_mid (second accumulation amount threshold), and the accumulation amount threshold indicating a state in which the buffer accumulation amount is small is AC_low (third accumulation amount threshold), when the buffer accumulation amount $> AC_high$, the decision threshold is set to TH_low (first decision threshold) that is the lowest since the state is immediately before the buffer overflow, and the packet is quickly discarded.

(47) As similar to this, when $AC_high > \text{buffer accumulation amount} > AC_mid$, the decision threshold is determined as TH_mid (second decision threshold), when $AC_mid > \text{buffer accumulation amount} > AC_low$, the decision threshold is determined as TH_high (third decision threshold), and when $AC_low > \text{buffer accumulation amount} > 0$, the decision threshold is determined as TH_high2 (fourth decision threshold).

(48) FIG. **8** is a flowchart illustrating an example of an operation procedure in a threshold determination unit according to the third embodiment of the present invention. FIG. **8** is an operation procedure when the threshold is changed in accordance with the measurement interval. When the measurement interval starts (step **S3-1**), the accumulation amount of the buffer is checked (step **S3-2**). When the accumulation amount of the buffer is larger than AC_high (step **S3-3**: YES), the decision threshold is determined to be TH_low (step **S3-4**).

(49) When the accumulation amount of the buffer is equal to or smaller than AC_high (step **S3-3**: NO), the accumulation amount of the buffer is compared with AC_mid (step **S3-5**), and when the accumulation amount of the buffer is larger than AC_mid (step **S3-5**: YES), the decision threshold is determined to TH_mid larger than TH_low (step **S3-6**).

(50) When the accumulation amount of the buffer is equal to or smaller than AC_mid (step **S3-5**: NO), the accumulation amount of the buffer is compared with AC_low (step **S3-7**), and when the accumulation amount of the buffer is larger than AC_low (step **S3-7**: YES), the decision threshold is determined to TH_high1 larger than TH_mid (step **S3-8**).

(51) When the accumulation amount of the buffer is equal to or smaller than AC_low (step **S3-7**: NO), the decision threshold is determined to be TH_high2 larger than TH_high1 (step **S3-9**).

(52) FIG. **9** is a flowchart illustrating another example of an operation procedure in the threshold

determination unit according to the third embodiment of the present invention. In FIG. 8, the decision threshold is changed in accordance with the measurement interval, but in FIG. 9, the decision threshold is changed at a timing independent of the measurement interval.

(53) In FIG. 9, the check of the buffer accumulation amount and the change of the decision threshold based on the buffer accumulation amount are repeated at predetermined time intervals. In FIG. 9, the timer at a predetermined time interval is reset (step S4-1), and the buffer accumulation amount is checked and the decision threshold is changed on the basis of the buffer accumulation amount (steps S4-2 to S4-9). The processing of steps S4-2 to S4-9 is similar to the processing in steps S3-2 to S3-9 in FIG. 8.

(54) When a timeout has occurred after the decision threshold has been changed (step S4-10: YES), the timer is reset (step S4-1), and the buffer accumulation amount is checked again and the decision threshold is changed on the basis of the buffer accumulation amount (steps S4-2 to S4-9). When the timeout has not occurred (step S4-10: NO), the process returns to the check of the buffer accumulation amount (step S4-2), and the decision threshold is changed on the basis of the buffer accumulation amount.

(55) The time interval in FIG. 9 can be appropriately determined by the user according to system requirements such as the amount of packets to be captured and the buffer amount. For example, the predetermined time interval may be set to a time interval to secure the processing time for processing steps S4-2 to S4-9 in FIG. 9.

(56) As described above, according to the third embodiment, by dynamically changing the decision threshold for determining a packet to be discarded in the output adjustment unit according to the accumulation buffer amount, it is possible to avoid buffer overflow even when the capture rate decreases due to processing other than the capture rate serving as a bottleneck.

(57) Configuration Example of Packet Capture Device

(58) The packet capture device 10 in the present embodiment can be implemented in various forms. For example, the packet capture device 10 may be achieved by hardware of a board on a server, or the function of the packet capture device 10 may be achieved by software operating on a computer.

(59) A configuration example of a computer operating as the packet capture device 10 is illustrated in FIG. 8. Each unit of the packet capture device 10 included in the packet capture system of the present embodiment can be implemented by a computer including a central processing unit (CPU), a storage device, and an external interface (hereinafter, external I/F) and a program for controlling those hardware resources.

(60) The computer 300 includes a CPU 400, a storage device 600, and an external I/F 700, which are connected to each other via an I/O interface 500. A packet capture program and the like for achieving the operation of the packet capture system of the present embodiment and data such as a capture file are stored in the storage device 600, and another external computer 800 that transmits and receives a signal, a computer constituting a network, and the like are connected to the external I/F 700. The CPU 400 can execute the packet capture processing described in the present embodiment in accordance with a processing program or the like stored in the storage device 600. The processing program can be recorded in a computer-readable recording medium or can be provided via a network.

(61) Extension of Embodiments

(62) Although the present invention has been described so far with reference to an embodiment, the present invention is not limited to the above embodiment. Various changes that can be understood by those skilled in the art can be made in the configuration of the present invention within the scope of the present invention.

REFERENCE SIGNS LIST

(63) 10 Packet capture device 11 Packet analysis unit 12 Flow identification unit 13 Filtering unit 14 Output adjustment unit 15 Capture file generation unit 16 Storage unit 100 Rule table 200 Capture target network.

Claims

1. A packet capture device, comprising: one or more processors; and a non-transitory computer-readable storage device storing a program to be executed by the processor, the program including instructions for: analyzing input packets; identifying a flow as a capture target from the input packets; adjusting a packet amount of the flow to be stored as an adjusted flow, wherein adjusting the packet amount of the flow comprises: deciding whether to store packets of the flow for each predetermined measurement interval based on a measurement result of a packet amount of the capture target in the predetermined measurement interval; and discarding one or more first packets of the flow not to be stored as the adjusted flow; temporarily accumulating, in a buffer, one or more second packets of the flow to be stored as the adjusted flow; and storing, in a storage device, the adjusted flow as the capture target, wherein the instructions for adjusting the packet amount of the flow to be stored as the adjusted flow further comprise instructions for: determining a predetermined decision threshold according to an accumulation amount of one or more packets in the buffer; and determining the predetermined decision threshold from a plurality of the predetermined decision thresholds based on a comparison result between the accumulation amount and an accumulation amount threshold, wherein when the accumulation amount is larger than the accumulation amount threshold, setting a first decision threshold as the predetermined decision threshold, and when the accumulation amount is equal to or smaller than the accumulation amount threshold, setting a second decision threshold larger than the first decision threshold as the predetermined decision threshold.
2. The packet capture device according to claim 1, wherein the instructions include further instructions to output information on a packet amount of the one or more first packets discarded from the flow.
3. The packet capture device according to claim 1, wherein the instructions for adjusting the packet amount of the flow to be stored as the adjusted flow comprises further instructions for: deciding whether to store each packet of the flow for each predetermined measurement interval based on the measurement result of the packet amount of the capture target in the predetermined measurement interval and a writing rate of a respective packet from the buffer to the storage device.
4. The packet capture device according to claim 1, wherein the instructions for adjusting the packet amount of the flow to be stored as the adjusted flow comprises further instructions for: cumulatively adding a packet length of the capture target that has been input at the predetermined measurement interval to determine a cumulative addition value; and deciding to store a first packet of the flow when the cumulative addition value is equal to or smaller than the predetermined decision threshold; and discarding a second packet of the capture target when the cumulative addition value is larger than the predetermined decision threshold.
5. The packet capture device according to claim 4, wherein the instructions include further instructions for: determining the predetermined decision threshold from the plurality of the predetermined decision thresholds based on a comparison result between the accumulation amount of the one or more packets in the buffer and a plurality of the accumulation amount thresholds, wherein the plurality of the accumulation amount thresholds includes at least three different accumulation amount thresholds.
6. The packet capture device according to claim 5, wherein the instructions to determine the predetermined decision threshold include further instructions for: when the accumulation amount of the one or more packets is larger than a first accumulation amount threshold of the plurality of the accumulation amount thresholds, setting a first decision threshold as the predetermined decision threshold; when the accumulation amount of the one or more packets is equal to or smaller than the first accumulation amount threshold and larger than a second accumulation amount threshold smaller than the first accumulation amount threshold, setting a second decision threshold larger

than the first decision threshold as the predetermined decision threshold; when the accumulation amount of the one or more packets is equal to or smaller than the second accumulation amount threshold and larger than a third accumulation amount threshold smaller than the second accumulation amount threshold, setting a third decision threshold larger than the second decision threshold as the predetermined decision threshold; and when the accumulation amount of the one or more packets is equal to or smaller than the third accumulation amount threshold, setting a fourth decision threshold larger than the third decision threshold as the predetermined decision threshold.

7. The packet capture device according to claim 1, wherein the instructions for adjusting the packet amount of the flow to be stored as the adjusted flow comprises further instructions for: acquiring information on an accumulation amount of packets accumulated in the buffer at the predetermined measurement interval, and sending a first input packet of the capture target to the buffer when the accumulation amount of packets is equal to or smaller than the predetermined decision threshold, and discarding a second input packet of the capture target when the accumulation amount of the packets is larger than the predetermined decision threshold.

8. A packet capture method, comprising: analyzing input packets; identifying a flow as a capture target from the input packets; adjusting a packet amount of the flow to be stored as an adjusted flow, wherein adjusting the packet amount of the flow comprises: deciding whether to store packets of the flow for each predetermined measurement interval based on a measurement result of a packet amount of the capture target in the predetermined measurement interval; and discarding one or more first packets of the flow not to be stored as the adjusted flow; temporarily accumulating, in a buffer, one or more second packets of the flow to be stored as the adjusted flow; and storing, in a storage device, the adjusted flow as the capture target, wherein adjusting the packet amount of the flow to be stored as the adjusted flow further comprises: determining a predetermined decision threshold according to an accumulation amount of one or more packets in the buffer; and determining a predetermined decision threshold from a plurality of the predetermined decision thresholds based on a comparison result between the accumulation amount and an accumulation amount threshold, wherein when the accumulation amount is larger than the accumulation amount threshold, setting a first decision threshold as the predetermined decision threshold, and when the accumulation amount is equal to or smaller than the accumulation amount threshold, setting a second decision threshold larger than the first decision threshold as the predetermined decision threshold.

9. The packet capture method according to claim 8, further comprising outputting information on a packet amount of the one or more first packets discarded from the flow.

10. The packet capture method according to claim 8, wherein adjusting the packet amount of the flow to be stored as the adjusted flow further comprises: deciding whether to store each packet of the flow for each predetermined measurement interval based on the measurement result of the packet amount of the capture target in the predetermined measurement interval and a writing rate of a respective packet from the buffer to the storage device.

11. The packet capture method according to claim 8, wherein adjusting the packet amount of the flow to be stored as the adjusted flow further comprises: cumulatively adding a packet length of the capture target that has been input at the predetermined measurement interval to determine a cumulative addition value; and deciding to store a first packet of the flow when the cumulative addition value is equal to or smaller than the predetermined decision threshold; and discarding a second packet of the capture target when the cumulative addition value is larger than the predetermined decision threshold.

12. The packet capture method according to claim 11, further comprising: determining the predetermined decision threshold from a plurality of the predetermined decision thresholds based on a comparison result between the accumulation amount of the one or more packets in the buffer and a plurality of the accumulation amount thresholds, wherein the plurality of the accumulation amount thresholds includes at least three different accumulation amount thresholds.

13. The packet capture method according to claim 12, wherein determining the predetermined decision threshold comprises: when the accumulation amount of the one or more packets is larger than a first accumulation amount threshold of the plurality of the accumulation amount thresholds, setting a first decision threshold as the predetermined decision threshold; when the accumulation amount of the one or more packets is equal to or smaller than the first accumulation amount threshold and larger than a second accumulation amount threshold smaller than the first accumulation amount threshold, setting a second decision threshold larger than the first decision threshold as the predetermined decision threshold; when the accumulation amount of the one or more packets is equal to or smaller than the second accumulation amount threshold and larger than a third accumulation amount threshold smaller than the second accumulation amount threshold, setting a third decision threshold larger than the second decision threshold as the predetermined decision threshold; and when the accumulation amount of the one or more packets is equal to or smaller than the third accumulation amount threshold, setting a fourth decision threshold larger than the third decision threshold as the predetermined decision threshold.

14. The packet capture method according to claim 8, wherein adjusting the packet amount of the flow to be stored as the adjusted flow further comprises: acquiring information on an accumulation amount of packets accumulated in the buffer at the predetermined measurement interval, and sending a first input packet of the capture target to the buffer when the accumulation amount of the packets is equal to or smaller than the predetermined decision threshold, and discarding a second input packet of the capture target when the accumulation amount of the packets is larger than the predetermined decision threshold.
