

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386935
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kubota; Daisuke et al.

Electronic device and program

Abstract

A novel electronic device is provided. An electronic device capable of executing various types of processing by simple operation is provided. An electronic device with a high security level is provided. The electronic device includes a control portion, a detection portion, and a memory portion. The detection portion has a function of detecting touch operation and a function of obtaining fingerprint data on a touching finger. The memory portion has a function of retaining fingerprint data on a plurality of finger registered in advance. The control portion has functions of comparing the fingerprint data on the touching finger obtained by the detection portion with the fingerprint data on the plurality of fingers when the detection portion detects touch operation, and executing processing corresponding to the fingerprint data on the touching finger or a combination of the touch operation and the fingerprint data on the touching finger when the fingerprint data on the touching finger matches any one piece of the fingerprint data on the plurality of fingers.

Inventors:	Kubota; Daisuke (Atsugi, JP), Kusunoki; Koji (Isehara, JP)
Applicant:	Semiconductor Energy Laboratory Co., Ltd. (Atsugi, JP)
Family ID:	75164881
Assignee:	Semiconductor Energy Laboratory Co., Ltd. (Atsugi, JP)
Appl. No.:	18/398403
Filed:	December 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240127625 A1	Apr. 18, 2024

Foreign Application Priority Data

JP	2019-176624	Sep. 27, 2019
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 17642979 US 11900721 WO PCT/IB2020/058502 20200914 child-doc US 18398403

Publication Classification

Int. Cl.: **G06V40/13** (20220101); **G06F21/32** (20130101); **G06V40/12** (20220101); G06F3/041 (20060101); H10K59/80 (20230101)

U.S. Cl.:

CPC **G06F21/32** (20130101); **G06V40/1318** (20220101); **G06V40/1365** (20220101); G06F3/0412 (20130101); H10K59/8792 (20230201)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8736587	12/2013	Yamazaki	N/A	N/A
9155498	12/2014	Akiyama	N/A	N/A
9167994	12/2014	Akiyama	N/A	N/A
11832464	12/2022	Kubota et al.	N/A	N/A
2010/0007632	12/2009	Yamazaki	N/A	N/A
2013/0075761	12/2012	Akiyama	N/A	N/A
2014/0056493	12/2013	Gozzini	N/A	N/A
2014/0299879	12/2013	Yamazaki	N/A	N/A
2016/0063230	12/2015	Alten	N/A	N/A
2019/0065717	12/2018	Won et al.	N/A	N/A
2019/0095079	12/2018	Deotale et al.	N/A	N/A
2020/0160025	12/2019	Dangy-caye	N/A	N/A
2021/0066442	12/2020	Watanabe	N/A	G09G 3/3275
2021/0066669	12/2020	Kubota et al.	N/A	N/A
2021/0096678	12/2020	Kubota et al.	N/A	N/A
2022/0069025	12/2021	Yamazaki	N/A	H10K 50/85
2022/0173174	12/2021	Hatsumi	N/A	G09G 3/30
2022/0246694	12/2021	Watanabe	N/A	H05B 33/02
2022/0253517	12/2021	Yamazaki	N/A	G06V 40/1365
2022/0278172	12/2021	Kubota et al.	N/A	N/A
2022/0285461	12/2021	Hatsumi	N/A	G06V 40/1318
2022/0292871	12/2021	Kawashima et al.	N/A	N/A
2022/0294981	12/2021	Kubota et al.	N/A	N/A

2022/0317796	12/2021	Kubota et al.	N/A	N/A
2022/0320064	12/2021	Takahashi et al.	N/A	N/A
2022/0327187	12/2021	Yoshimoto et al.	N/A	N/A
2022/0327857	12/2021	Kusunoki et al.	N/A	N/A
2022/0344443	12/2021	Yamazaki et al.	N/A	N/A
2022/0394202	12/2021	Takahashi et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
07-308308	12/1994	JP	N/A
2007-081203	12/2006	JP	N/A
2007-133528	12/2006	JP	N/A
2007-304646	12/2006	JP	N/A
2010-040042	12/2009	JP	N/A
2013-073965	12/2012	JP	N/A
2013-232232	12/2012	JP	N/A
2015-026387	12/2014	JP	N/A
2016-035768	12/2015	JP	N/A
2018-077633	12/2017	JP	N/A
2018-136665	12/2017	JP	N/A
2020-0015710	12/2019	KR	N/A
WO-2019/007514	12/2018	WO	N/A

OTHER PUBLICATIONS

International Search Report (Application No. PCT/IB2020/058502) Dated Dec. 22, 2020. cited by applicant

Written Opinion (Application No. PCT/IB2020/058502) Dated Dec. 22, 2020. cited by applicant

Primary Examiner: Haley; Joseph R

Attorney, Agent or Firm: Robinson Intellectual Property Law Office, P.C.

Background/Summary

TECHNICAL FIELD

(1) One embodiment of the present invention relates to an electronic device. One embodiment of the present invention relates to a display device. One embodiment of the present invention relates to a program.

(2) Note that one embodiment of the present invention is not limited to the above technical field. Examples of the technical field of one embodiment of the present invention include a semiconductor device, a display device, a light-emitting device, a power storage device, a memory device, an electronic device, a lighting device, an input device (e.g., a touch sensor), an input/output device (e.g., a touch panel), a driving method thereof, and a manufacturing method thereof.

BACKGROUND ART

(3) Information terminal devices, for example, mobile phones such as smartphones, tablet information terminals, and laptop PCs (personal computers) have been widely used. Most of such information terminal devices enable intuitive screen operation by a touch of a user's finger on the

screen. For example, multi-touch, such as touch, swipe, or pinch in or pinch out with two fingers, or touch time differences is utilized, whereby functions such as an enlargement and a reduction, and classification of operations can be achieved.

(4) Such information terminal devices often include personal information or the like, and thus various authentication technologies for preventing abuse have been developed.

(5) For example, Patent Document 1 discloses an electronic device including a fingerprint sensor in a push button switch portion.

REFERENCE

Patent Document

(6) [Patent Document 1] United States Published Patent Application No. 2014/0056493

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(7) However, multi-touch operation also includes some functions, which are difficult to execute, e.g., a function executed by operation with four or more fingers.

(8) An object of one embodiment of the present invention is to provide a novel electronic device. An object of one embodiment of the present invention is to provide an electronic device capable of executing various types of processing by simple operation. Another object of one embodiment of the present invention is to provide an electronic device with a high security level.

(9) Note that the description of these objects does not preclude the existence of other objects. One embodiment of the present invention does not need to achieve all the objects. Other objects can be derived from the description of the specification, the drawings, and the claims.

Means for Solving the Problems

(10) One embodiment of the present invention is an electronic device including a control portion, a detection portion, and a memory portion. The detection portion has a function of detecting touch operation and a function of obtaining fingerprint data on a touching finger. The memory portion has a function of retaining fingerprint data on a plurality of fingers registered in advance. The control portion has functions of comparing the fingerprint data on the touching finger with each piece of the fingerprint data on the plurality of fingers, and executing processing corresponding to fingerprint data that matches the fingerprint data on the touching finger among the fingerprint data on the plurality of fingers in the case where the fingerprint data on the touching finger matches any piece of the fingerprint data on the plurality of fingers.

(11) Another embodiment of the present invention is an electronic device including a control portion, a detection portion, and a memory portion. The detection portion has a function of detecting touch operation and a function of obtaining fingerprint data on a touching finger. The memory portion has a function of retaining fingerprint data on a plurality of fingers registered in advance. The control portion has functions of comparing the fingerprint data on the touching finger with each piece of the fingerprint data on the plurality of fingers, and executing processing corresponding to a combination of the touch operation and fingerprint data that matches the fingerprint data on the touching finger among the fingerprint data on the plurality of fingers in the case where the fingerprint data on the touching finger matches any piece of the fingerprint data on the plurality of fingers.

(12) Another embodiment of the present invention is an electronic device including a control portion, a display portion, and a memory portion. The display portion has a function of displaying an image, a function of detecting touch operation, and a function of obtaining fingerprint data on a touching finger. The memory portion has a function of retaining fingerprint data on a plurality of fingers registered in advance. The control portion has functions of comparing the fingerprint data on the touching finger with each piece of the fingerprint data on the plurality of fingers, and executing processing corresponding to fingerprint data that matches the fingerprint data on the touching finger among the fingerprint data on the plurality of fingers in the case where the fingerprint data on the touching finger matches any piece of the fingerprint data on the plurality of

fingers.

(13) Another embodiment of the present invention is an electronic device including a control portion, a display portion, and a memory portion. The display portion has a function of displaying an image, a function of detecting touch operation, and a function of obtaining fingerprint data on a touching finger. The memory portion has a function of retaining fingerprint data on a plurality of fingers registered in advance. The control portion has functions of comparing the fingerprint data on the touching finger with each piece of the fingerprint data on the plurality of fingers, and executing processing corresponding to a combination of the touch operation and fingerprint data that matches the fingerprint data on the touching finger among the fingerprint data on the plurality of fingers in the case where the fingerprint data on the touching finger matches any piece of the fingerprint data on the plurality of fingers.

(14) In the above, the electronic device preferably has a function of bringing a system into a locked state in the case where the fingerprint data on the touching finger does not match any pieces of the fingerprint data on the plurality of fingers.

(15) In the above, the display portion preferably includes a plurality of pixels and has a function of authenticating fingerprint data in a whole display region. In that case, it is preferable that the pixel include a light-emitting element and a light-receiving element, and the light-emitting element and the light-receiving element be provided on the same plane.

(16) In the above, the light-emitting element preferably has a stacked-layer structure in which a first electrode, a light-emitting layer, and a common electrode are stacked. The light-receiving element preferably has a stacked-layer structure in which a second electrode, an active layer, and the common electrode are stacked. In that case, the light-emitting layer and the active layer preferably contain different organic compounds from each other. Furthermore, it is preferable that the first electrode and the second electrode be provided on the same plane to be apart from each other and the common electrode be provided to cover the light-emitting layer and the active layer.

(17) Alternatively, in the above, the light-emitting element preferably has a stacked-layer structure in which a first electrode, a common layer, a light-emitting layer, and a common electrode are stacked. The light-receiving element preferably has a stacked-layer structure in which a second electrode, the common layer, an active layer, and the common electrode are stacked. In that case, the light-emitting layer and the active layer preferably contain different organic compounds from each other. Furthermore, it is preferable that the first electrode and the second electrode be provided on the same plane to be apart from each other, the common electrode be provided to cover the light-emitting layer and the active layer, and the common layer be provided to cover the first electrode and the second electrode.

(18) In the above, it is preferable that the light-emitting element have a function of emitting visible light, and the light-receiving element have a function of receiving the visible light emitted by the light-emitting element.

(19) Alternatively, in the above, it is preferable that the light-emitting element have a function of emitting infrared light, and the light-receiving element have a function of receiving the infrared light emitted by the light-emitting element.

(20) Another embodiment of the present invention is a program that is executed by an electronic device including a control portion and a detection portion. Here, the detection portion has a function of detecting touch operation and a function of obtaining fingerprint data on a touching finger. The program of one embodiment of the present invention includes following steps: a step of obtaining the fingerprint data on the touching finger when the detection portion detects touch operation, a step in which the control portion compares the fingerprint data on the touching finger with fingerprint data on a plurality of fingers that is registered in advance, and a step in which the control portion executes processing corresponding to the fingerprint data on the touching finger in the case where the fingerprint data on the touching finger and any one piece of the fingerprint data on the plurality of fingers match.

(21) Another embodiment of the present invention is a program that is executed by an electronic device including a control portion and a detection portion. Here, the detection portion has a function of detecting touch operation and a function of obtaining fingerprint data on a touching finger. The program of one embodiment of the present invention includes following steps: a step of obtaining the fingerprint data on the touching finger when the detection portion detects touch operation, a step in which the control portion compares the fingerprint data on the touching finger with fingerprint data on a plurality of fingers that is registered in advance, and a step in which the control portion executes processing corresponding to a combination of touch operation and fingerprint data that matches the fingerprint data on the touching finger among the fingerprint data on the plurality of fingers in the case where the fingerprint data on the touching finger and any one piece of the fingerprint data on the plurality of fingers match.

(22) In the above, the program of one embodiment of the present invention preferably includes a step in which the control portion brings a system into a locked state in the case where the fingerprint data on the touching finger does not match any pieces of the fingerprint data on the plurality of fingers.

Effect of the Invention

(23) According to one embodiment of the present invention, an electronic device in which processing, which is set, differs depending on the kind of finger and thereby various types of processing can be executed by simple operation can be provided. Alternatively, an electronic device with a high security level can be provided. Alternatively, a novel electronic device can be provided.

(24) Note that the description of these effects does not preclude the existence of other effects. One embodiment of the present invention does not need to have all these effects. Other effects can be derived from the description of the specification, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a diagram illustrating a structure example of an electronic device.

(2) FIG. 2 is a diagram showing an operation method example of an electronic device.

(3) FIG. 3A and FIG. 3B are diagrams illustrating structure examples of electronic devices.

(4) FIG. 4A and FIG. 4B are diagrams illustrating a structure example of an electronic device and operation method examples thereof.

(5) FIG. 5A to FIG. 5C are diagrams illustrating structure examples of an electronic device and operation method examples thereof.

(6) FIG. 6A to FIG. 6D and FIG. 6F are cross-sectional views illustrating examples of a display device.

(7) FIG. 6E and FIG. 6G are diagrams illustrating examples of an image captured by the display device.

(8) FIG. 6H and FIG. 6J to FIG. 6L are top views illustrating examples of a pixel.

(9) FIG. 7A to FIG. 7G are top views illustrating examples of a pixel.

(10) FIG. 8A and FIG. 8B are cross-sectional views illustrating examples of a display device.

(11) FIG. 9A and FIG. 9B are cross-sectional views illustrating examples of a display device.

(12) FIG. 10A to FIG. 10C are cross-sectional views illustrating examples of a display device.

(13) FIG. 11A is a cross-sectional view illustrating an example of a display device.

(14) FIG. 11B and FIG. 11C are diagrams illustrating examples of a top surface layout of a resin layer.

(15) FIG. 12 is a perspective view illustrating an example of a display device.

(16) FIG. 13 is a cross-sectional view illustrating an example of a display device.

(17) FIG. 14 is a cross-sectional view illustrating an example of a display device.

(18) FIG. 15A is a cross-sectional view illustrating an example of a display device. FIG. 15B is a cross-sectional view illustrating an example of a transistor.

(19) FIG. 16A and FIG. 16B are circuit diagrams illustrating examples of a pixel circuit.

(20) FIG. 17A and FIG. 17B are diagrams illustrating an example of an electronic device.

(21) FIG. 18A to FIG. 18D are diagrams illustrating examples of electronic devices.

(22) FIG. 19A to FIG. 19F are drawings illustrating examples of electronic devices.

MODE FOR CARRYING OUT THE INVENTION

(23) Embodiments are described in detail with reference to the drawings. Note that the present invention is not limited to the following description, and it will be readily appreciated by those skilled in the art that modes and details of the present invention can be modified in various ways without departing from the spirit and scope of the present invention. Thus, the present invention should not be construed as being limited to the description in the following embodiments.

(24) Note that in structures of the invention described below, the same portions or portions having similar functions are denoted by the same reference numerals in different drawings, and a description thereof is not repeated. Furthermore, the same hatch pattern is used for the portions having similar functions, and the portions are not especially denoted by reference numerals in some cases.

(25) In addition, the position, size, range, or the like of each structure illustrated in drawings does not represent the actual position, size, range, or the like in some cases for easy understanding. Therefore, the disclosed invention is not necessarily limited to the position, size, range, or the like disclosed in the drawings.

(26) Note that the term “film” and the term “layer” can be interchanged with each other depending on the case or circumstances. For example, the term “conductive layer” can be changed into the term “conductive film”. As another example, the term “insulating film” can be changed into the term “insulating layer”.

Embodiment 1

(27) In this embodiment, an electronic device of one embodiment of the present invention and an operation method of the electronic device are described.

(28) Note that in the drawings attached to this specification, the block diagram in which components are classified according to their functions and shown as independent blocks is illustrated; however, it is difficult to separate actual components completely according to their functions, and one component may be related to a plurality of functions or a plurality of components may achieve one function.

(29) More specific examples of the electronic device of one embodiment of the present invention are described below with reference to drawings.

(30) When the electronic device of one embodiment of the present invention is provided with a function of recognizing differences in fingers, such as a forefinger and a middle finger, touching the electronic device from obtained fingerprint data, simple and various types of operation is possible. For example, a display screen can be enlarged by tapping with a forefinger, and the display screen can be reduced by tapping with a middle finger.

(31) In addition, in the electronic device of one embodiment of the present invention, simple and various types of operation is possible by recognizing differences in fingers, such as a forefinger and a middle finger, touching the electronic device from obtained fingerprint data and combining the fingerprint data and touch operation. For example, a predetermined application can be started by double-tapping with a forefinger, and the started application can be terminated by double-tapping with a middle finger.

(32) Furthermore, in the electronic device of one embodiment of the present invention, detecting touch operation and obtaining fingerprint data can be performed in a display portion. Thus, an additional fingerprint sensor or the like need not be provided, and thus the number of members for forming the electronic device can be minimized.

Structure Example of Electronic Device

(33) FIG. 1 illustrates a block diagram of a device **10** that is an example of the electronic device of one embodiment of the present invention. The device **10** includes a control portion **11**, a display portion **12**, and a memory portion **13**. The display portion **12** includes a detection portion **21**. The device **10** can be used as an electronic device such as an information terminal device, for example.

(34) The display portion **12** has a function of displaying an image, a function of detecting touch operation, and a function of obtaining fingerprint data on a finger touching a screen or the like. Here, an example where the display portion **12** includes the detection portion **21** is illustrated. The detection portion **21** is a portion having, out of the above functions of the display portion **12**, the function of detecting touch operation and the function of obtaining fingerprint data. The display portion **12** can also be referred to as a touch panel with a fingerprint data obtaining function. For example, a display device described in detail in Embodiment 2 can be used for the display portion **12**.

(35) The detection portion **21** has a function of outputting the data on the position touched by a finger on a screen to the control portion **11**. Furthermore, the detection portion **21** has a function of capturing a fingerprint image of a finger touching the screen and outputting the image data as fingerprint data to the control portion **11**.

(36) It is preferable that the display portion **12** be capable of obtaining fingerprint data on a finger touching any position on the screen. That is, a range where the touch sensor functions and a range where fingerprint data can be obtained preferably match or substantially match on the screen.

(37) The memory portion **13** has a function of retaining user's fingerprint data registered in advance and processing data that corresponds to the fingerprint data or a combination of the fingerprint data and touch operation. The memory portion **13** can output the data to the control portion **11** in accordance with a request from the control portion **11**. Note that the processing data may be individually set by an application or the like in the electronic device.

(38) In order to achieve various types of operation, the memory portion **13** preferably retains fingerprint data on all the fingers of a user used in operating the screen. For example, other than fingerprint data on user's right forefinger and left forefinger, fingerprint data on the user's right middle finger and left middle finger is preferably retained. In addition to them, one or more kinds of fingerprint data on a ring finger, a little finger, and a thumb are preferably retained, and fingerprint data on all the five fingers of the user may be retained.

(39) The control portion **11** has a function of requesting the detection portion **21** to obtain fingerprint data when touch operation is detected by the detection portion **21**. Then, the control portion **11** has a function of comparing the fingerprint data input from the detection portion **21** with the fingerprint data on a plurality of fingers registered in advance. When the control portion **11** determines that the fingerprint data input from the detection portion **21** matches any one piece of the fingerprint data on the plurality of fingers, the control portion **11** executes processing corresponding to the fingerprint data or processing corresponding to a combination of the fingerprint data and touch operation, which are set in advance. Furthermore, when the control portion **11** determines that the input fingerprint data does not match any pieces of the registered fingerprint data, the control portion **11** preferably has a function of shifting a system into a predetermined state. Here, the predetermined state refers to a state in which a device is locked or a state in which a warning message indicating that the fingerprint data does not match is displayed on the screen, for example. Note that the function may be the function of shifting the system into a state different from the examples described in this specification. Alternatively, the control portion **11** does not necessarily have the function.

(40) Examples of a fingerprint authentication method executed by the control portion **11** include a method using the degree of similarity between two images compared, e.g., a template matching method or a pattern matching method. Alternatively, fingerprint authentication processing may be executed by inference using machine learning. At this time, the fingerprint authentication

processing is preferably executed by inference using a neural network, in particular.

(41) The control portion **11** can function as, for example, a central processing unit (CPU). The control portion **11** interprets and executes instructions from various programs with the use of a processor to process various kinds of data and control programs. Programs that might be executed by the processor may be stored in a memory region of the processor or may be stored in the memory portion **13**.

Operation Example of Electronic Device

(42) An operation example of the device **10** is described below. FIG. **2** is a flow chart of the operation of the device **10**. The flow chart shown in FIG. **2** includes Step **S1** to Step **S6**.

(43) In Step **S1**, the detection portion **21** detects touch operation. When a touch is detected, the processing proceeds to Step **S2**. When touch operation is not performed, the system is on standby until touch operation is performed (the processing proceeds to Step **S1** again).

(44) In the case where touch operation is not performed for a certain period in Step **S1**, the control portion **11** may bring the system into a locked state.

(45) In Step **S2**, the detection portion **21** obtains fingerprint data. The detection portion **21** outputs the obtained fingerprint data to the control portion **11**.

(46) In Step **S3**, the control portion **11** executes fingerprint authentication processing. Specifically, a plurality of pieces of fingerprint data retained in advance in the memory portion **13** and the fingerprint data obtained by the detection portion **21** are compared. Then, the control portion **11** determines whether the latter matches any of the former. Among the plurality of pieces of fingerprint data retained in the memory portion **13**, in the case where fingerprint data on a finger A matches the fingerprint data obtained by the detection portion **21**, the processing proceeds to Step **S4**. In addition, among the plurality of pieces of fingerprint data retained in the memory portion **13**, in the case where fingerprint data on a finger B matches the fingerprint data obtained by the detection portion **21**, the processing proceeds to Step **S5**. By contrast, in the case where the fingerprint data obtained by the detection portion **21** does not match any of the plurality of pieces of fingerprint data retained in the memory portion **13**, the processing proceeds to Step **S6**.

(47) In Step **S4**, on the basis of the touch operation detected by the detection portion **21**, the control portion **11** executes processing A corresponding to the fingerprint data on the finger A.

Alternatively, on the basis of the touch operation detected by the detection portion **21**, the control portion **11** executes the processing A corresponding to a combination of the fingerprint data on the finger A and the touch operation. Examples of the touch operation include tap, long tap, swipe, flick, slide, and drag.

(48) In Step **S5**, on the basis of the touch operation detected by the detection portion **21**, the control portion **11** executes processing B corresponding to the fingerprint data on the finger B.

Alternatively, on the basis of the touch operation detected by the detection portion **21**, the control portion **11** executes the processing B corresponding to a combination of the fingerprint data on the finger B and the touch operation. Examples of the touch operation include tap, long tap, swipe, flick, slide, and drag.

(49) Note that each of the finger A and the finger B here is a predetermined finger having fingerprint data retained in advance in the memory portion **13** and refers to, for example, any of a forefinger, a middle finger, a ring finger, a little finger, and a thumb. Note that in this specification, for the sake of convenience, only processings of the case where the fingerprint data on the finger A and the finger B is detected are described; however, the processing may be changed as appropriate in accordance with the number of pieces of fingerprint data retained in the memory portion **13**. For example, when the memory portion **13** retains fingerprint data on a predetermined finger C registered in advance and the detection portion **21** detects the fingerprint data on the finger C, the control portion **11** preferably has processing of executing processing C corresponding to the fingerprint data on the finger C or a combination of the fingerprint data on the finger C and touch operation.

(50) With the above function, in the case where the same operation is performed with different fingers, different processings corresponding to fingerprint data on each finger can be executed. Thus, processing that has needed operation with two fingers, for example, operation such as pinch in or pinch out can be executed with one finger, whereby simple and various types of operation is possible.

(51) Alternatively, for example, various types of processing can be executed by only tap operation. For example, by tapping with a middle finger, scrolling of a screen that has needed slide operation can be performed. That is, without performing operation of sliding a finger, various types of operation is possible. Thus, a device that is easy to operate even for elderly people or people with disabled hands can be achieved.

(52) Note that processing corresponding to a combination of fingerprint data on a finger and touch operation may work with application functionality. For example, in a certain application, the application can be terminated by tapping the screen with a ring finger, and in another application, processing of deleting a file can be executed by tapping an image or an icon, which is associated with the file, with a ring finger.

(53) In Step **S6**, the control portion **11** executes predetermined processing X. As the processing X, for example, processing of locking a system or processing of displaying a warning message indicating that the fingerprint data does not match on the screen is preferably executed. This renders the electronic device unavailable to the user operating the electronic device. Alternatively, available functions are limited.

(54) Note that as the processing X in Step **S6**, processing different from the examples described in this specification may be executed. Alternatively, the processing is not necessarily executed.

(55) By repeating the processing shown in FIG. **2**, various types of processing can be executed in the device **10**.

(56) The above is the description of the flow chart shown in FIG. **2**.

(57) Note that although an example in which processing corresponding to fingerprint data on one finger is executed is shown in FIG. **2**, one embodiment of the present invention is not limited thereto. In one embodiment of the present invention, processing corresponding to a combination of pieces of fingerprint data on two or more fingers (or fingerprint data and touch operation) may be executed. For example, examples of the touch operation that can be executed with each finger include tap, long tap, swipe, flick, slide, and drag, and examples of the touch operation that can be executed with two fingers include pinch in, pinch out, and rotation. Specifically, the case of tapping with a forefinger and a middle finger and the case of tapping with a forefinger and a ring finger may cause execution of different types of processing.

(58) Note that a processing method, an operation method, a performance method, a display method, or the like that is executed by the electronic device of one embodiment of the present invention might be described as a program, for example. For example, a program in which the processing method, operation method, performance method, display method, or the like that is described above as an example and executed by the device **10** and the like is written can be stored in a non-transitory storage medium and can be read and executed by an arithmetic device or the like included in the control portion **11** of the device **10**. Accordingly, a program that makes hardware execute the operation method or the like described above as an example and a non-transitory storage medium storing the program are embodiments of the present invention.

Modification Example

(59) Although the display portion **12** includes the detection portion **21** in the above example, they may be provided separately. A device **10A** illustrated in FIG. **3A** is an example in which the detection portion **21** is not included in the display portion **12**.

(60) Examples of the detection portion **21** of the device **10A** include a touch pad that does not have an image display function.

(61) Alternatively, the device **10A** may include the following two portions: the display portion **12**

not having a function of obtaining fingerprint data and the detection portion **21** having a function of displaying an image. That is, a touch panel with a fingerprint data obtaining function may be used as the detection portion **21** that is an input means, and the display portion **12** may be separately included as an image display means.

(62) Alternatively, a detection portion for detecting a touch and a detection portion for obtaining fingerprint data may be separately provided. A device **10B** illustrated in FIG. **3B** is an example in which a detection portion **21A** for obtaining fingerprint data is included in the display portion **12**, and a detection portion **21B** for detecting a touch is independently provided. For example, a display device described in detail in Embodiment 2 may be used in the display portion **12**, and a capacitive touch sensor may be used in the detection portion **21B**.

(63) Note that in the device **10B**, the detection portion **21B** for detecting a touch may be included in the display portion **12**, and the detection portion **21A** for obtaining fingerprint data may be independently provided.

Specific Example

(64) A specific example of an electronic device of one embodiment of the present invention is described below.

(65) FIG. **4A** schematically illustrates an electronic device **30** and a first finger **25** operating the electronic device **30**. The electronic device **30** includes a display portion **31**. The electronic device **30** is a portable information terminal device functioning as a smartphone, for example.

(66) As the electronic device **30**, the device **10**, the device **10A**, or the device **10B** can be used.

(67) In FIG. **4A**, the fingertip of the first finger **25** touches the display portion **31**. At this time, the display portion **31** can obtain fingerprint data **26** of the first finger **25**.

(68) Furthermore, FIG. **4A** illustrates the fingerprint data **26** obtained by the display portion **31** and fingerprint data **27** of a plurality of fingers of a user registered in advance in the electronic device **30**. When the control portion **11** determines that the fingerprint data **26** obtained by the display portion **31** matches fingerprint data **27A** that is one of the fingerprint data on the plurality of fingers, processing corresponding to the fingerprint data **27A** (or a combination of the fingerprint data **27A** and touch operation) is executed. For example, as illustrated in FIG. **4A**, the user can perform operation such as an enlargement of an image **35** by tapping with the first finger **25**.

(69) FIG. **4B** schematically illustrates the electronic device **30** and a second finger **28** operating the electronic device **30**.

(70) In FIG. **4B**, the fingertip of the second finger **28** touches the display portion **31**. At this time, the display portion **31** can obtain fingerprint data **29** of the second finger **28**.

(71) Furthermore, like FIG. **4A**, FIG. **4B** illustrates the fingerprint data **29** obtained by the display portion **31** and the fingerprint data **27** of a plurality of fingers of a user registered in advance in the electronic device **30**. When the control portion **11** determines that the fingerprint data **29** obtained by the display portion **31** matches fingerprint data **27B** that is one of the fingerprint data on the plurality of fingers, processing in accordance with the fingerprint data **27B** (or a combination of the fingerprint data **27B** and touch operation) is executed. For example, as illustrated in FIG. **4B**, the user can perform operation such as a reduction of the image **35** by tapping with the second finger **28**.

(72) FIG. **5A** illustrates an electronic device **40** that is a specific example of one embodiment of the present invention. The electronic device **40** functions as a laptop personal computer.

(73) The electronic device **40** includes a display portion **41**, an input portion **42**, a plurality of input keys **43**, a housing **44**, a housing **45**, a hinge portion **46**, and the like. The housing **44** is provided with the display portion **41**. The housing **45** is provided with the input portion **42** and the input keys **43**. The housing **44** and the housing **45** are joined together by the hinge portion **46**.

(74) The input portion **42** functions as a touch pad. The input portion **42** has a function of obtaining the data on the position touched by the fingertip of a finger **24** and touch operation, and a function of obtaining fingerprint data on the fingertip.

- (75) In the case where a touch panel is used for the display portion **41**, the display portion **41** preferably has a function of obtaining fingerprint data.
- (76) FIG. **5B** illustrates an electronic device **40A** using a flexible display for a display portion **41A**. The display portion **41A** is provided across the housing **44** and the housing **45**. Thus, seamless display across two housings is possible.
- (77) The display portion **41A** has a function of displaying an image, a function of obtaining the data on the position touched by the fingertip of the finger **24** and touch operation, and a function of obtaining fingerprint data on the fingertip.
- (78) FIG. **5C** illustrates an electronic device **40B** provided with display portions on each of the two housings. The housing **44** is provided with a display portion **41B**. The housing **45** is provided with a display portion **41C**.
- (79) At least one of the display portion **41B** and the display portion **41C**, preferably both of them, has/have a function of displaying an image, a function of obtaining the data on the position touched by the fingertip of the finger **24**, and a function of obtaining the fingerprint data on the fingertip.
- (80) The above is the description of the specific example.
- (81) This embodiment can be combined with the other embodiments as appropriate. In this specification, in the case where a plurality of structure examples are shown in one embodiment, the structure examples can be combined as appropriate.

Embodiment 2

- (82) In this embodiment, display devices of one embodiment of the present invention are described with reference to FIG. **6** to FIG. **15**.
- (83) The display device of this embodiment can be favorably used in the display portion of the device described in Embodiment 1.
- (84) The display portion of the display device of one embodiment of the present invention has a function of displaying an image with the use of a light-emitting element (also referred to as a light-emitting device). Furthermore, the display portion also has one or both of an image capturing function and a sensing function.
- (85) The display device of one embodiment of the present invention includes a light-receiving element (also referred to as a light-receiving device) and a light-emitting element. Alternatively, the display device of one embodiment of the present invention includes a light-emitting and light-receiving element (also referred to as a light-emitting and light-receiving device) and a light-emitting element.
- (86) First, the display device including a light-receiving element and a light-emitting element is described.
- (87) The display device of one embodiment of the present invention includes a light-receiving element and a light-emitting element in a display portion. In the display device of one embodiment of the present invention, the light-emitting elements are arranged in a matrix in the display portion, and an image can be displayed on the display portion. Furthermore, the light-receiving elements are arranged in a matrix in the display portion, and the display portion has one or both of an image capturing function and a sensing function. The display portion can be used as an image sensor or a touch sensor. That is, by detecting light with the display portion, an image can be captured and the approach or contact of an object (e.g., a finger or a stylus) can be detected. Furthermore, in the display device of one embodiment of the present invention, the light-emitting elements can be used as a light source of the sensor. Accordingly, a light-receiving portion and a light source do not need to be provided separately from the display device; hence, the number of components of an electronic device can be reduced.
- (88) In the display device of one embodiment of the present invention, when an object reflects (or scatters) light emitted by the light-emitting element included in the display portion, the light-receiving element can detect the reflected light (or the scattered light); thus, image capturing and touch operation (touch or approach) detection are possible even in a dark place.

(89) The display device of one embodiment of the present invention has a function of displaying an image with the use of a light-emitting element. That is, the light-emitting element functions as a display element (also referred to as a display device).

(90) As the light-emitting element, an EL element (also referred to as an EL device) such as an OLED (Organic Light Emitting Diode) or a QLED (Quantum-dot Light Emitting Diode) is preferably used. As a light-emitting substance contained in the EL element, a substance emitting fluorescence (a fluorescent material), a substance emitting phosphorescence (a phosphorescent material), an inorganic compound (such as a quantum dot material), a substance exhibiting thermally activated delayed fluorescence (a thermally activated delayed fluorescence (TADF) material), or the like can be given. Alternatively, an LED (a light-emitting diode) such as a micro-LED can be used as the light-emitting element.

(91) The display device of one embodiment of the present invention has a function of detecting light with the use of a light-receiving element.

(92) When the light-receiving element is used as an image sensor, the display device can capture an image using the light-receiving element. For example, the display device of this embodiment can be used as a scanner.

(93) For example, data on biological information of a fingerprint, a palm print, or the like can be obtained with the use of the image sensor. That is, a biological authentication sensor can be incorporated in the display device. When the display device incorporates a biological authentication sensor, the number of components of an electronic device can be reduced as compared to the case where a biological authentication sensor is provided separately from the display device; thus, the size and weight of the electronic device can be reduced.

(94) When the light-receiving element is used as the touch sensor, the display device can detect the approach or contact of an object with the use of the light-receiving element.

(95) As the light-receiving element, a pn photodiode or a pin photodiode can be used, for example. The light-receiving element functions as a photoelectric conversion element (also referred to as a photoelectric conversion device) that detects light entering the light-receiving element and generates charge. The amount of charge generated from the light-receiving element depends on the amount of light entering the light-receiving element.

(96) It is particularly preferable to use an organic photodiode including a layer containing an organic compound as the light-receiving element. An organic photodiode, which is easily made thin, lightweight, and large in area and has a high degree of freedom for shape and design, can be used in a variety of display devices.

(97) In one embodiment of the present invention, organic EL elements (also referred to as organic EL devices) are used as the light-emitting elements, and organic photodiodes are used as the light-receiving elements. The organic EL elements and the organic photodiodes can be formed over one substrate. Thus, the organic photodiodes can be incorporated in the display device including the organic EL elements.

(98) If all the layers of the organic EL elements and the organic photodiodes are formed separately, the number of deposition steps becomes extremely large. Since a large number of layers of the organic photodiodes can have structures in common with the organic EL elements, concurrently depositing the layers that can have a common structure can inhibit an increase in the number of deposition steps.

(99) For example, one of a pair of electrodes (a common electrode) can be a layer shared by the light-receiving element and the light-emitting element. For example, at least one of a hole-injection layer, a hole-transport layer, an electron-transport layer, and an electron-injection layer is preferably a layer shared by the light-receiving element and the light-emitting element. As another example, the light-receiving element and the light-emitting element can have the same structure except that the light-receiving element includes an active layer and the light-emitting element includes a light-emitting layer. In other words, the light-receiving element can be manufactured by

only replacing the light-emitting layer of the light-emitting element with an active layer. When the light-receiving element and the light-emitting element include common layers in such a manner, the number of deposition steps and the number of masks can be reduced, thereby reducing the number of manufacturing steps and the manufacturing cost of the display device. Furthermore, the display device including the light-receiving element can be manufactured using an existing manufacturing apparatus and an existing manufacturing method for the display device.

(100) Note that a layer shared by the light-receiving element and the light-emitting element might have functions different in the light-receiving element and the light-emitting element. In this specification, the name of a component is based on its function in the light-emitting element. For example, a hole-injection layer functions as a hole-injection layer in the light-emitting element and functions as a hole-transport layer in the light-receiving element. Similarly, an electron-injection layer functions as an electron-injection layer in the light-emitting element and functions as an electron-transport layer in the light-receiving element. Note that a layer shared by the light-receiving element and the light-emitting element may have the same functions in the light-emitting element and the light-receiving element. The hole-transport layer functions as a hole-transport layer in both of the light-emitting element and the light-receiving element, and the electron-transport layer functions as an electron-transport layer in both of the light-emitting element and the light-receiving element.

(101) Next, a display device including a light-emitting and light-receiving element and a light-emitting element is described.

(102) In the display device of one embodiment of the present invention, a subpixel exhibiting any color includes a light-emitting and light-receiving element instead of a light-emitting element, and subpixels exhibiting the other colors each include a light-emitting element. The light-emitting and light-receiving element has both a function of emitting light (a light-emitting function) and a function of receiving light (a light-receiving function). For example, in the case where a pixel includes three subpixels of a red subpixel, a green subpixel, and a blue subpixel, at least one of the subpixels includes a light-emitting and light-receiving element, and the other subpixels each include a light-emitting element. Thus, the display portion of the display device of one embodiment of the present invention has a function of displaying an image using both a light-emitting and light-receiving element and a light-emitting element.

(103) The light-emitting and light-receiving element functions as both a light-emitting element and a light-receiving element, whereby the pixel can have a light-receiving function without an increase in the number of subpixels included in the pixel. Thus, the display portion of the display device can be provided with one or both of an image capturing function and a sensing function while keeping the aperture ratio of the pixel (aperture ratio of each subpixel) and the resolution of the display device. Accordingly, in the display device of one embodiment of the present invention, the aperture ratio of the pixel can be more increased and the resolution can be increased more easily than in a display device provided with a subpixel including a light-receiving element separately from a subpixel including a light-emitting element.

(104) In the display portion in the display device of one embodiment of the present invention, the light-emitting and light-receiving elements and the light-emitting elements are arranged in a matrix, and an image can be displayed on the display portion. The display portion can be used as an image sensor or a touch sensor. Furthermore, in the display device of one embodiment of the present invention, the light-emitting elements can be used as a light source of the sensor. Accordingly, a light-receiving portion and a light source do not need to be provided separately from the display device; hence, the number of components of an electronic device can be reduced.

(105) In the display device of one embodiment of the present invention, when an object reflects (or scatters) light emitted by the light-emitting element included in the display portion, the light-emitting and light-receiving element can detect the reflected light (or the scattered light); thus, image capturing and touch operation (touch or approach) detection are possible even in a dark

place.

(106) The light-emitting and light-receiving element can be manufactured by combining an organic EL element and an organic photodiode. For example, by adding an active layer of an organic photodiode to a layered structure of an organic EL element, the light-emitting and light-receiving element can be manufactured. Furthermore, in the light-emitting and light-receiving element formed of a combination of an organic EL element and an organic photodiode, concurrently depositing layers that can be shared with the organic EL element can inhibit an increase in the number of deposition steps.

(107) For example, one of a pair of electrodes (a common electrode) can be a layer shared by the light-emitting and light-receiving element and the light-emitting element. For example, at least one of a hole-injection layer, a hole-transport layer, an electron-transport layer, and an electron-injection layer is preferably a layer shared by the light-emitting and light-receiving element and the light-emitting element. As another example, the light-emitting and light-receiving element and the light-emitting element can have the same structure except for the presence or absence of an active layer of the light-receiving element. In other words, the light-emitting and light-receiving element can be manufactured by only adding the active layer of the light-receiving element to the light-emitting element. When the light-emitting and light-receiving element and the light-emitting element include common layers in such a manner, the number of deposition steps and the number of masks can be reduced, thereby reducing the number of manufacturing steps and the manufacturing cost of the display device. Furthermore, the display device including the light-emitting and light-receiving element can be manufactured using an existing manufacturing apparatus and an existing manufacturing method for the display device.

(108) Note that a layer included in the light-emitting and light-receiving element might have a different function between the case where the light-emitting and light-receiving element functions as the light-receiving element and the case where the light-emitting and light-receiving element functions as the light-emitting element. In this specification, the name of a component is based on its function in the case where the light-emitting and light-receiving element functions as a light-emitting element. For example, a hole-injection layer functions as a hole-injection layer in the case where the light-emitting and light-receiving element functions as the light-emitting element, and functions as a hole-transport layer in the case where the light-emitting and light-receiving element functions as the light-receiving element. Similarly, an electron-injection layer functions as an electron-injection layer in the case where the light-emitting and light-receiving element functions as the light-emitting element, and functions as an electron-transport layer in the case where the light-emitting and light-receiving element function as the light-receiving element. A layer included in the light-emitting and light-receiving element may have the same function in both the case where the light-emitting and light-receiving element functions as the light-receiving element and the case where the light-emitting and light-receiving element functions as the light-emitting element. The hole-transport layer functions as a hole-transport layer in the case where the light-emitting and light-receiving element functions as either a light-emitting element or a light-receiving element, and the electron-transport layer functions as an electron-transport layer in the case where the light-emitting and light-receiving element functions as either a light-emitting element or a light-receiving element.

(109) The display device of this embodiment has a function of displaying an image with the use of a light-emitting element and a light-emitting and light-receiving element. That is, the light-emitting element and the light-emitting and light-receiving element function as a display element.

(110) The display device of this embodiment has a function of detecting light with the use of a light-emitting and light-receiving element. The light-emitting and light-receiving element can detect light having a shorter wavelength than light emitted by the light-emitting and light-receiving element itself.

(111) When the light-emitting and light-receiving element is used as an image sensor, the display

device of this embodiment can capture an image using the light-emitting and light-receiving element. For example, the display device of this embodiment can be used as a scanner.

(112) When the light-emitting and light-receiving element is used as the touch sensor, the display device of this embodiment can detect the approach or contact of an object with the use of the light-emitting and light-receiving element.

(113) The light-emitting and light-receiving element functions as a photoelectric conversion element that detects light entering the light-emitting and light-receiving element and generates charge. The amount of charge generated from the light-emitting and light-receiving element depends on the amount of light entering the light-emitting and light-receiving element.

(114) The light-emitting and light-receiving element can be manufactured by adding an active layer of the light-receiving element to the above-described structure of the light-emitting element.

(115) A pn or pin photodiode structure can be applied to the light-emitting and light-receiving element, for example.

(116) It is particularly preferable to use, for the light-emitting and light-receiving element, an active layer of an organic photodiode including a layer containing an organic compound. An organic photodiode, which is easily made thin, lightweight, and large in area and has a high degree of freedom for shape and design, can be used in a variety of display devices.

(117) The display device of one embodiment of the present invention is specifically described below with reference to drawings.

(118) [Display Device]

(119) FIG. 6A to FIG. 6D and FIG. 6F illustrate cross-sectional views of display devices of embodiments of the present invention.

(120) A display device **200A** illustrated in FIG. 6A includes a layer **203** including a light-receiving element, a functional layer **205**, and a layer **207** including a light-emitting element between a substrate **201** and a substrate **209**.

(121) In the display device **200A**, red (R) light, green (G) light, and blue (B) light are emitted from the layer **207** including a light-emitting element.

(122) The light-receiving element included in the layer **203** including a light-receiving element can detect light that enters from the outside of the display device **200A**.

(123) A display device **200B** illustrated in FIG. 6B includes a layer **204** including a light-emitting and light-receiving element, the functional layer **205**, and the layer **207** including a light-emitting element between the substrate **201** and the substrate **209**.

(124) In the display device **200B**, green (G) light and blue (B) light are emitted from the layer **207** including a light-emitting element, and red (R) light is emitted from the layer **204** including a light-emitting and light-receiving element. In the display device of one embodiment of the present invention, the color of light emitted by the layer **204** including a light-emitting and light-receiving element is not limited to red. Furthermore, the color of light emitted by the layer **207** including a light-emitting element is not limited to the combination of green and blue.

(125) The light-emitting and light-receiving element included in the layer **204** including a light-emitting and light-receiving element can detect light that enters from the outside of the display device **200B**. The light-emitting and light-receiving element can detect one or both of green (G) light and blue (B) light, for example.

(126) The functional layer **205** includes a circuit for driving the light-receiving element or the light-emitting and light-receiving element and a circuit for driving the light-emitting element. A switch, a transistor, a capacitor, a resistor, a wiring, a terminal, and the like can be provided in the functional layer **205**. Note that in the case where the light-emitting element and the light-receiving element are driven by a passive-matrix method, a structure not provided with a switch or a transistor may be employed.

(127) The display device of one embodiment of the present invention may have a function of detecting an object such as a finger that is touching the display device (a function of a touch panel).

For example, after light emitted by the light-emitting element in the layer **207** including a light-emitting element is reflected by a finger **202** that is touching the display device **200A** as illustrated in FIG. **6C**, the light-receiving element in the layer **203** including a light-receiving element detects the reflected light. Thus, the touch of the finger **202** on the display device **200A** can be detected. Furthermore, in the display device **200B**, after light emitted by the light-emitting element in the layer **207** including a light-emitting element is reflected by a finger that is touching the display device **200B**, the light-emitting and light-receiving element in the layer **204** including a light-emitting and light-receiving element can detect the reflected light. Although a case where light emitted by the light-emitting element is reflected by an object is described below as an example, light might be scattered by an object.

(128) The display device of one embodiment of the present invention may have a function of detecting an object that is close to (but is not touching) the display device as illustrated in FIG. **6D** or capturing an image of such an object.

(129) The display device of one embodiment of the present invention may have a function of detecting a fingerprint of the finger **202**. FIG. **6E** illustrates a diagram of an image captured by the display device of one embodiment of the present invention. In an image-capturing range **263** in FIG. **6E**, the outline of the finger **202** is indicated by a dashed line and the outline of a contact portion **261** is indicated by a dashed-dotted line. In the contact portion **261**, a high-contrast image of a fingerprint **262** can be captured owing to a difference in the amount of light entering the light-receiving element (or the light-emitting and light-receiving element).

(130) The display device of one embodiment of the present invention can also function as a pen tablet. FIG. **6F** illustrates a state in which a tip of a stylus **208** slides in a direction indicated by a dashed arrow while the tip of the stylus **208** touches the substrate **209**.

(131) As illustrated in FIG. **6F**, when the scattered light scattered by the contact surface between the tip of the stylus **208** and the substrate **209** enters the light-receiving element (or the light-emitting and light-receiving element) that is positioned in a portion overlapping with the contact surface, the position of the tip of the stylus **208** can be detected with high accuracy.

(132) FIG. **6G** illustrates an example of a path **266** of the stylus **208** that is detected by the display device of one embodiment of the present invention. The display device of one embodiment of the present invention can detect the position of an object to be detected, such as the stylus **208**, with high position accuracy, so that high-definition drawing can be performed using a drawing application or the like. Unlike the case of using a capacitive touch sensor, an electromagnetic induction touch pen, or the like, the display device can detect even the position of a highly insulating object to be detected, the material of a tip portion of the stylus **208** is not limited, and a variety of writing materials (e.g., a brush, a glass pen, a quill pen, and the like) can be used.

(133) [Pixel]

(134) The display device of one embodiment of the present invention includes a plurality of pixels arranged in a matrix. One pixel includes a plurality of subpixels. One subpixel includes one light-emitting element, one light-emitting and light-receiving element, or one light-receiving element.

(135) The plurality of pixels each include one or more of a subpixel including a light-emitting element, a subpixel including a light-receiving element, and a subpixel including a light-emitting and light-receiving element.

(136) For example, the pixel includes a plurality of (e.g., three or four) subpixels each including a light-emitting element and one subpixel including a light-receiving element.

(137) Note that the light-receiving element may be provided in all the pixels or may be provided in some of the pixels. In addition, one pixel may include a plurality of light-receiving elements. One light-receiving element may be provided across a plurality of pixels. The resolution of the light-receiving element may be different from the resolution of the light-emitting element.

(138) In the case where the pixel includes three subpixels each including a light-emitting element, as the three subpixels, subpixels of three colors of RGB, subpixels of three colors of yellow (Y),

cyan (C), and magenta (M), and the like can be given. In the case where the pixel includes four subpixels each including a light-emitting element, as the four subpixels, subpixels of four colors of R, G, B, and white (W), subpixels of four colors of R, G, B, and Y, and the like can be given. (139) FIG. 6H, FIG. 6J, FIG. 6K, and FIG. 6L illustrate examples of a pixel which includes a plurality of subpixels each including a light-emitting element and includes one subpixel including a light-receiving element. Note that the arrangement of subpixels is not limited to the illustrated order in this embodiment. For example, the positions of a subpixel (B) and a subpixel (G) may be reversed.

(140) The pixels illustrated in FIG. 6H, FIG. 6J, and FIG. 6K each include a subpixel (PD) having a light-receiving function, a subpixel (R) that exhibits red light, a subpixel (G) that exhibits green light, and a subpixel (B) that exhibits blue light.

(141) Matrix arrangement is applied to the pixel illustrated in FIG. 6H, and stripe arrangement is applied to the pixel illustrated in FIG. 6J. FIG. 6K illustrates an example in which the subpixel (R) that exhibits red light, the subpixel (G) that exhibits green light, and the subpixel (B) that exhibits blue light are arranged laterally in one row and the subpixel (PD) having a light-receiving function is arranged thereunder. In other words, in FIG. 6K, the subpixel (R), the subpixel (G), and the subpixel (B) are arranged in the same row, which is different from the row in which the subpixel (PD) is provided.

(142) The pixel illustrated in FIG. 6L includes a subpixel (X) that exhibits light of a color other than RGB, in addition to the components of the pixel illustrated in FIG. 6K. The light of a color other than RGB can be white (W) light, yellow (Y) light, cyan (C) light, magenta (M) light, infrared light (IR), or the like. In the case where the subpixel (X) exhibits infrared light, the subpixel (PD) having a light-receiving function preferably has a function of detecting infrared light. The subpixel (PD) having a light-receiving function may have a function of detecting both visible light and infrared light. The wavelength of light detected by the light-receiving element can be determined depending on the application of a sensor.

(143) Alternatively, for example, the pixel includes a plurality of subpixels each including a light-emitting element and one subpixel including a light-emitting and light-receiving element.

(144) The display device including the light-emitting and light-receiving element has no need to change the pixel arrangement when incorporating a light-receiving function into pixels; thus, a display portion can be provided with one or both of an image capturing function and a sensing function without reductions in aperture ratio and resolution.

(145) Note that the light-emitting and light-receiving element may be provided in all the pixels or may be provided in some of the pixels. In addition, one pixel may include a plurality of light-emitting and light-receiving elements.

(146) FIG. 7A to FIG. 7D illustrate examples of a pixel which includes a plurality of subpixels each including a light-emitting element and includes one subpixel including a light-emitting and light-receiving element.

(147) A pixel illustrated in FIG. 7A employs stripe arrangement and includes a subpixel (R-PD) that exhibits red light and has a light-receiving function, a subpixel (G) that exhibits green light, and a subpixel (B) that exhibits blue light. In a display device including a pixel composed of three subpixels of RGB, a light-emitting element used in the R subpixel can be replaced with a light-emitting and light-receiving element, so that the display device can have a light-receiving function in the pixel.

(148) A pixel illustrated in FIG. 7B includes a subpixel (R-PD) that exhibits red light and has a light-receiving function, a subpixel (G) that exhibits green light, and a subpixel (B) that exhibits blue light. The subpixel (R-PD) is provided in a column different from a column where the subpixel (G) and the subpixel (B) are positioned. The subpixel (G) and the subpixel (B) are alternately arranged in the same column; one is provided in an odd-numbered row and the other is provided in an even-numbered row. The color of the subpixel positioned in a column different from

the column where the subpixels of the other colors are positioned is not limited to red (R) and may be green (G) or blue (B).

(149) A pixel illustrated in FIG. 7C employs matrix arrangement and includes a subpixel (R-PD) that exhibits red light and has a light-receiving function, a subpixel (G) that exhibits green light, a subpixel (B) that exhibits blue light, and a subpixel (X) that exhibits light of a color other than RGB. Also in a display device including a pixel composed of four subpixels of RGBX, a light-emitting element used in the R subpixel can be replaced with a light-emitting and light-receiving element, so that the display device can have a light-receiving function in the pixel.

(150) FIG. 7D illustrates two pixels, each of which is composed of three subpixels surrounded by dotted lines. The pixels illustrated in FIG. 7D each include a subpixel (R-PD) that exhibits red light and has a light-receiving function, a subpixel (G) that exhibits green light, and a subpixel (B) that exhibits blue light. In the pixel on the left in FIG. 7D, the subpixel (G) is positioned in the same row as the subpixel (R-PD), and the subpixel (B) is positioned in the same column as the subpixel (R-PD). In the pixel on the right in FIG. 7D, the subpixel (G) is positioned in the same row as the subpixel (R-PD), and the subpixel (B) is positioned in the same column as the subpixel (G). In every odd-numbered row and every even-numbered row of the pixel layout illustrated in FIG. 7D, the subpixel (R-PD), the subpixel (G), and the subpixel (B) are repeatedly arranged. In addition, subpixels of different colors are arranged in the odd-numbered row and the even-numbered row in every column.

(151) FIG. 7E illustrates four pixels which employ pentile arrangement; adjacent two pixels each have a different combination of two subpixels that exhibit light of different colors. Note that the shape of the subpixels illustrated in FIG. 7E indicates a top-surface shape of the light-emitting elements and the light-emitting and light-receiving elements included in the subpixels. FIG. 7F is a modification example of the pixel arrangement of FIG. 7E.

(152) The upper-left pixel and the lower-right pixel in FIG. 7E each include a subpixel (R-PD) that exhibits red light and has a light-receiving function and a subpixel (G) that exhibits green light. The lower-left pixel and the upper-right pixel in FIG. 7E each include a subpixel (G) that exhibits green light and a subpixel (B) that exhibits blue light.

(153) The upper-left pixel and the lower-right pixel in FIG. 7F each include a subpixel (R-PD) that exhibits red light and has a light-receiving function and a subpixel (G) that exhibits green light. The lower-left pixel and the upper-right pixel in FIG. 7F each include a subpixel (R-PD) that exhibits red light and has a light-receiving function and a subpixel (B) that exhibits blue light.

(154) In FIG. 7E, the subpixel (G) that exhibits green light is provided in each pixel. Meanwhile, in FIG. 7F, the subpixel (R-PD) that exhibits red light and has a light-receiving function is provided in each pixel. The structure illustrated in FIG. 7F achieves higher-resolution image capturing than the structure illustrated in FIG. 7E because of having a subpixel having a light-receiving function in each pixel. Thus, the accuracy of biometric authentication can be increased, for example.

(155) The top-surface shape of the light-emitting elements and the light-emitting and light-receiving elements is not particularly limited and can be a circular shape, an elliptical shape, a polygonal shape, a polygonal shape with rounded corners, or the like. The top-surface shape of the light-emitting elements included in the subpixels (G) is a circular in the example in FIG. 7E and square in the example in FIG. 7F. The top surface shape of the light-emitting elements and the light-emitting and light-receiving elements may vary depending on the color thereof, or the light-emitting elements and the light-emitting and light-receiving elements of some colors or every color may have the same top-surface shape.

(156) The aperture ratio of subpixels may vary depending on the color of the subpixels, or may be the same among the subpixels of some colors or every color. For example, the aperture ratio of a subpixel of a color provided in each pixel (the subpixel (G) in FIG. 7E, and the subpixel (R-PD) in FIG. 7F) may be made lower than those of subpixels of the other colors.

(157) FIG. 7G is a modification example of the pixel arrangement of FIG. 7F. Specifically, the

structure of FIG. 7G is obtained by rotating the structure of FIG. 7F by 45°. Although one pixel is regarded as being formed of two subpixels in FIG. 7F, one pixel can be regarded as being formed of four subpixels as illustrated in FIG. 7G.

(158) In the description with reference to FIG. 7G, one pixel is regarded as being formed of four subpixels surrounded by dotted lines. A pixel includes two subpixels (R-PD), one subpixel (G), and one subpixel (B). The pixel including a plurality of subpixels having a light-receiving function allows high-resolution image capturing. Accordingly, the accuracy of biometric authentication can be increased. For example, the resolution of image capturing can be the square root of 2 times the resolution of display.

(159) A display device which employs the structure illustrated in FIG. 7F or FIG. 7G includes p (p is an integer greater than or equal to 2) first light-emitting elements, q (q is an integer greater than or equal to 2) second light-emitting elements, and r (r is an integer greater than p and q) light-emitting and light-receiving elements. As for p and r, $r=2p$ is satisfied. As for p, q, and r, $r=p+q$ is satisfied. Either the first light-emitting elements or the second light-emitting elements emits green light, and the other light-emitting elements emit blue light. The light-emitting and light-receiving elements emit red light and have a light-receiving function.

(160) In the case where touch detection is performed with the light-emitting and light-receiving elements, for example, it is preferable that light emitted by a light source be hard for a user to recognize. Since blue light has low visibility than green light, light-emitting elements that emit blue light are preferably used as a light source. Accordingly, the light-emitting and light-receiving elements preferably have a function of receiving blue light.

(161) As described above, the display device of this embodiment can employ any of various types of pixel arrangements.

(162) [Device Structure]

(163) Next, detailed structures of the light-emitting element, the light-receiving element, and the light-emitting and light-receiving element which can be used in the display device of one embodiment of the present invention are described.

(164) The display device of one embodiment of the present invention can have any of the following structures: a top-emission structure in which light is emitted in a direction opposite to the substrate where the light-emitting element is formed, a bottom-emission structure in which light is emitted toward the substrate where the light-emitting element is formed, and a dual-emission structure in which light is emitted toward both surfaces.

(165) In this embodiment, a top-emission display device is described as an example.

(166) In this specification and the like, unless otherwise specified, in describing a structure including a plurality of components (e.g., light-emitting elements or light-emitting layers), alphabets are not added when a common part for the components is described. For example, when a common part of a light-emitting layer **283R**, a light-emitting layer **283G**, and the like is described, the light-emitting layers are simply referred to as the light-emitting layer **283**, in some cases.

(167) A display device **280A** illustrated in FIG. 8A includes a light-receiving element **270PD**, a light-emitting element **270R** that emits red (R) light, a light-emitting element **270G** that emits green (G) light, and a light-emitting element **270B** that emits blue (B) light.

(168) Each of the light-emitting elements includes a pixel electrode **271**, a hole-injection layer **281**, a hole-transport layer **282**, a light-emitting layer, an electron-transport layer **284**, an electron-injection layer **285**, and a common electrode **275** which are stacked in this order. The light-emitting element **270R** includes the light-emitting layer **283R**, the light-emitting element **270G** includes the light-emitting layer **283G**, and the light-emitting element **270B** includes a light-emitting layer **283B**. The light-emitting layer **283R** includes a light-emitting substance that emits red light, the light-emitting layer **283G** includes a light-emitting substance that emits green light, and the light-emitting layer **283B** includes a light-emitting substance that emits blue light.

(169) The light-emitting elements are electroluminescent elements that emit light to the common

electrode 275 side by voltage application between the pixel electrodes 271 and the common electrode 275.

(170) The light-receiving element 270PD includes the pixel electrode 271, the hole-injection layer 281, the hole-transport layer 282, an active layer 273, the electron-transport layer 284, the electron-injection layer 285, and the common electrode 275 which are stacked in this order.

(171) The light-receiving element 270PD is a photoelectric conversion element that receives light entering from the outside of the display device 280A and converts it into an electric signal.

(172) In the description made in this embodiment, the pixel electrode 271 functions as an anode and the common electrode 275 functions as a cathode in both of the light-emitting element and the light-receiving element. In other words, when the light-receiving element is driven by application of reverse bias between the pixel electrode 271 and the common electrode 275, light entering the light-receiving element can be detected and charge can be generated and extracted as current.

(173) In the display device of this embodiment, an organic compound is used for the active layer 273 of the light-receiving element 270PD. In the light-receiving element 270PD, the layers other than the active layer 273 can have structures in common with the layers in the light-emitting elements. Therefore, the light-receiving element 270PD can be formed concurrently with the formation of the light-emitting elements only by adding a step of depositing the active layer 273 in the manufacturing process of the light-emitting elements. The light-emitting elements and the light-receiving element 270PD can be formed over one substrate. Accordingly, the light-receiving element 270PD can be incorporated into the display device without a significant increase in the number of manufacturing steps.

(174) The display device 280A is an example in which the light-receiving element 270PD and the light-emitting elements have a common structure except that the active layer 273 of the light-receiving element 270PD and the light-emitting layers 283 of the light-emitting elements are separately formed. Note that the structures of the light-receiving element 270PD and the light-emitting elements are not limited thereto. The light-receiving element 270PD and the light-emitting elements may include separately formed layers other than the active layer 273 and the light-emitting layers 283. The light-receiving element 270PD and the light-emitting elements preferably include at least one layer used in common (common layer). Thus, the light-receiving element 270PD can be incorporated into the display device without a significant increase in the number of manufacturing steps.

(175) A conductive film that transmits visible light is used as the electrode through which light is extracted, which is either the pixel electrode 271 or the common electrode 275. A conductive film that reflects visible light is preferably used as the electrode through which light is not extracted.

(176) The light-emitting elements included in the display device of this embodiment preferably employs a micro optical resonator (microcavity) structure. Thus, one of the pair of electrodes of the light-emitting elements is preferably an electrode having properties of transmitting and reflecting visible light (a semi-transmissive and semi-reflective electrode), and the other is preferably an electrode having a property of reflecting visible light (a reflective electrode). When the light-emitting elements have a microcavity structure, light obtained from the light-emitting layers can be resonated between both of the electrodes, whereby light emitted from the light-emitting elements can be intensified.

(177) Note that the semi-transmissive and semi-reflective electrode can have a stacked-layer structure of a reflective electrode and an electrode having a property of transmitting visible light (also referred to as a transparent electrode).

(178) The light transmittance of the transparent electrode is greater than or equal to 40%. For example, an electrode having a visible light (light at wavelengths greater than or equal to 400 nm and less than 750 nm) transmittance higher than or equal to 40% is preferably used in the light-emitting elements. The semi-transmissive and semi-reflective electrode has a visible light reflectance of higher than or equal to 10% and lower than or equal to 95%, preferably higher than

or equal to 30% and lower than or equal to 80%. The reflective electrode has a visible light reflectance of higher than or equal to 40% and lower than or equal to 100%, preferably higher than or equal to 70% and lower than or equal to 100%. These electrodes preferably have a resistivity less than or equal to $1 \times 10^{-2} \Omega\text{cm}$. Note that in the case where any of the light-emitting elements emits near-infrared light (light with a wavelength greater than or equal to 750 nm and less than or equal to 1300 nm), the near-infrared light transmittance and reflectance of these electrodes preferably satisfy the above-described numerical ranges of the visible light transmittance and reflectance.

(179) The light-emitting element includes at least the light-emitting layer **283**. The light-emitting element may further include, as a layer other than the light-emitting layer **283**, a layer containing a substance with a high hole-injection property, a substance with a high hole-transport property, a hole-blocking material, a substance with a high electron-transport property, a substance with a high electron-injection property, a substance with a bipolar property (a substance with a high electron- and hole-transport property), or the like.

(180) For example, the light-emitting elements and the light-receiving element can share at least one of the hole-injection layer, the hole-transport layer, the electron-transport layer, and the electron-injection layer. Furthermore, at least one of the hole-injection layer, the hole-transport layer, the electron-transport layer, and the electron-injection layer can be separately formed for the light-emitting elements and the light-receiving element.

(181) The hole-injection layer is a layer injecting holes from an anode to the hole-transport layer, and a layer containing a material with a high hole-injection property. As the material with a high hole-injection property, an aromatic amine compound and a composite material containing a hole-transport material and an acceptor material (electron-accepting material) can be used.

(182) In the light-emitting element, the hole-transport layer is a layer transporting holes, which are injected from the anode by the hole-injection layer, to the light-emitting layer. In the light-receiving element, the hole-transport layer is a layer transporting holes, which are generated in the active layer on the basis of incident light, to the anode. The hole-transport layer is a layer including a hole-transport material. As the hole-transport material, a substance having a hole mobility of greater than or equal to $10^{-6} \text{ cm}^2/\text{Vs}$ is preferable. Note that other substances can also be used as long as they have a property of transporting more holes than electrons. As the hole-transport material, materials having a high hole-transport property, such as a π -electron-rich heteroaromatic compound (e.g., a carbazole derivative, a thiophene derivative, and a furan derivative) and an aromatic amine (a compound having an aromatic amine skeleton), are preferable.

(183) In the light-emitting element, the electron-transport layer is a layer transporting electrons, which are injected from the cathode by the electron-injection layer, to the light-emitting layer. In the light-receiving element, the electron-transport layer is a layer transporting electrons, which are generated in the active layer on the basis of incident light, to the cathode. The electron-transport layer is a layer including an electron-transport material. As the electron-transport material, a substance having an electron mobility of greater than or equal to $1 \times 10^{-6} \text{ cm}^2/\text{Vs}$ is preferable. Note that other substances can also be used as long as they have a property of transporting more electrons than holes. As the electron-transport material, it is possible to use a material having a high electron-transport property, such as a metal complex having a quinoline skeleton, a metal complex having a benzoquinoline skeleton, a metal complex having an oxazole skeleton, a metal complex having a thiazole skeleton, an oxadiazole derivative, a triazole derivative, an imidazole derivative, an oxazole derivative, a thiazole derivative, a phenanthroline derivative, a quinoline derivative having a quinoline ligand, a benzoquinoline derivative, a quinoxaline derivative, a dibenzoquinoxaline derivative, a pyridine derivative, a bipyridine derivative, a pyrimidine derivative, or a π -electron deficient heteroaromatic compound such as a nitrogen-containing heteroaromatic compound.

(184) The electron-injection layer is a layer injecting electrons from a cathode to the electron-transport layer, and a layer containing a material with a high electron-injection property. As the material with a high electron-injection property, an alkali metal, an alkaline earth metal, or a compound thereof can be used. As the material with a high electron-injection property, a composite material containing an electron-transport material and a donor material (electron-donating material) can also be used.

(185) The light-emitting layer **283** is a layer containing a light-emitting substance. The light-emitting layer **283** can contain one or more kinds of light-emitting substances. As the light-emitting substance, a substance that exhibits an emission color of blue, purple, bluish purple, green, yellowish green, yellow, orange, red, or the like is appropriately used. As the light-emitting substance, a substance that emits near-infrared light can also be used.

(186) Examples of the light-emitting substance include a fluorescent material, a phosphorescent material, a TADF material, and a quantum dot material.

(187) Examples of the fluorescent material are a pyrene derivative, an anthracene derivative, a triphenylene derivative, a fluorene derivative, a carbazole derivative, a dibenzothiophene derivative, a dibenzofuran derivative, a dibenzoquinoxaline derivative, a quinoxaline derivative, a pyridine derivative, a pyrimidine derivative, a phenanthrene derivative, and a naphthalene derivative.

(188) Examples of the phosphorescent material include an organometallic complex (particularly an iridium complex) having a 4H-triazole skeleton, a 1H-triazole skeleton, an imidazole skeleton, a pyrimidine skeleton, a pyrazine skeleton, or a pyridine skeleton; an organometallic complex (particularly an iridium complex) having a phenylpyridine derivative including an electron-withdrawing group as a ligand; a platinum complex; and a rare earth metal complex.

(189) The light-emitting layer **283** may contain one or more kinds of organic compounds (e.g., a host material and an assist material) in addition to the light-emitting substance (a guest material). As the one or more kinds of organic compounds, one or both of the hole-transport material and the electron-transport material can be used. As the one or more kinds of organic compounds, a bipolar material or a TADF material may be used.

(190) The light-emitting layer **283** preferably includes a phosphorescent material and a combination of a hole-transport material and an electron-transport material that easily forms an exciplex. With such a structure, light emission can be efficiently obtained by ExTET (Exciplex-Triplet Energy Transfer), which is energy transfer from an exciplex to a light-emitting substance (a phosphorescent material). When a combination of materials is selected so as to form an exciplex that exhibits light emission whose wavelength overlaps with the wavelength of a lowest-energy-side absorption band of the light-emitting substance, energy can be transferred smoothly and light emission can be obtained efficiently. With this structure, high efficiency, low-voltage driving, and a long lifetime of the light-emitting element can be achieved at the same time.

(191) In the combination of materials for forming an exciplex, the HOMO level (the highest occupied molecular orbital level) of the hole-transport material is preferably higher than or equal to the HOMO level of the electron-transport material. The LUMO level (the lowest unoccupied molecular orbital level) of the hole-transport material is preferably higher than or equal to the LUMO level of the electron-transport material. Note that the LUMO levels and the HOMO levels of the materials can be derived from the electrochemical characteristics (the reduction potentials and the oxidation potentials) of the materials that are measured by cyclic voltammetry (CV).

(192) Note that the formation of an exciplex can be confirmed by a phenomenon in which the emission spectrum of a mixed film in which the hole-transport material and the electron-transport material are mixed is shifted to the longer wavelength side than the emission spectrum of each of the materials (or has another peak on the longer wavelength side), observed by comparison of the emission spectra of the hole-transport material, the electron-transport material, and the mixed film of these materials, for example. Alternatively, the formation of an exciplex can be confirmed by a

difference in transient response, such as a phenomenon in which the transient photoluminescence (PL) lifetime of the mixed film has longer lifetime components or has a larger proportion of delayed components than that of each of the materials, observed by comparison of the transient PL of the hole-transport material, the transient PL of the electron-transport material, and the transient PL of the mixed film of these materials. The transient PL can be rephrased as transient electroluminescence (EL). That is, the formation of an exciplex can also be confirmed by a difference in transient response observed by comparison of the transient EL of the hole-transport material, the transient EL of the electron-transport material, and the transient EL of the mixed film of these materials.

(193) The active layer **273** includes a semiconductor. Examples of the semiconductor include an inorganic semiconductor such as silicon and an organic semiconductor including an organic compound. This embodiment shows an example in which an organic semiconductor is used as the semiconductor included in the active layer **273**. The use of an organic semiconductor is preferable because the light-emitting layer **283** and the active layer **273** can be formed by the same method (e.g., a vacuum evaporation method) and thus the same manufacturing apparatus can be used.

(194) Examples of an n-type semiconductor material included in the active layer **273** are electron-accepting organic semiconductor materials such as fullerene (e.g., C.sub.60 and C.sub.70) and a fullerene derivative. Fullerene has a soccer ball-like shape, which is energetically stable. Both the HOMO level and the LUMO level of fullerene are deep (low). Having a deep LUMO level, fullerene has an extremely high electron-accepting property (acceptor property). When π -electron conjugation (resonance) spreads in a plane as in benzene, the electron-donating property (donor property) usually increases. Although π -electrons widely spread in fullerene having a spherical shape, its electron-accepting property is high. The high electron-accepting property efficiently causes rapid charge separation and is useful for a light-receiving element. Both C.sub.60 and C.sub.70 have a wide absorption band in the visible light region, and C.sub.70 is especially preferable because of having a larger π -electron conjugation system and a wider absorption band in the long wavelength region than C.sub.60.

(195) Examples of the n-type semiconductor material include a metal complex having a quinoline skeleton, a metal complex having a benzoquinoline skeleton, a metal complex having an oxazole skeleton, a metal complex having a thiazole skeleton, an oxadiazole derivative, a triazole derivative, an imidazole derivative, an oxazole derivative, a thiazole derivative, a phenanthroline derivative, a quinoline derivative, a benzoquinoline derivative, a quinoxaline derivative, a dibenzoquinoxaline derivative, a pyridine derivative, a bipyridine derivative, a pyrimidine derivative, a naphthalene derivative, an anthracene derivative, a coumarin derivative, a rhodamine derivative, a triazine derivative, and a quinone derivative.

(196) Examples of a p-type semiconductor material contained in the active layer **273** include electron-donating organic semiconductor materials such as copper(II) phthalocyanine (CuPc), tetraphenyldibenzoperiflanthene (DBP), or zinc phthalocyanine (ZnPc), tin phthalocyanine (SnPc), and quinacridone.

(197) Examples of a p-type semiconductor material include a carbazole derivative, a thiophene derivative, a furan derivative, and a compound having an aromatic amine skeleton. Other examples of the p-type semiconductor material include a naphthalene derivative, an anthracene derivative, a pyrene derivative, a triphenylene derivative, a fluorene derivative, a pyrrole derivative, a benzofuran derivative, a benzothiophene derivative, an indole derivative, a dibenzofuran derivative, a dibenzothiophene derivative, an indolocarbazole derivative, a porphyrin derivative, a phthalocyanine derivative, a naphthalocyanine derivative, a quinacridone derivative, a polyphenylene vinylene derivative, a polyparaphenylene derivative, a polyfluorene derivative, a polyvinylcarbazole derivative, and a polythiophene derivative.

(198) The HOMO level of the electron-donating organic semiconductor material is preferably shallower (higher) than the HOMO level of the electron-accepting organic semiconductor material.

The LUMO level of the electron-donating organic semiconductor material is preferably shallower (higher) than the LUMO level of the electron-accepting organic semiconductor material.

(199) Fullerene having a spherical shape is preferably used as the electron-accepting organic semiconductor material, and an organic semiconductor material having a substantially planar shape is preferably used as the electron-donating organic semiconductor material. Molecules of similar shapes tend to aggregate, and aggregated molecules of similar kinds, which have molecular orbital energy levels close to each other, can increase the carrier-transport property.

(200) For example, the active layer **273** is preferably formed by co-evaporation of an n-type semiconductor and a p-type semiconductor.

(201) Either a low molecular compound or a high molecular compound can be used for the light-emitting element and the light-receiving element, and an inorganic compound may also be contained. Each of the layers included in the light-emitting element and the light-receiving element can be formed by an evaporation method (including a vacuum evaporation method), a transfer method, a printing method, an inkjet method, a coating method, or the like.

(202) A display device **280B** illustrated in FIG. **8B** is different from the display device **280A** in that the light-receiving element **270PD** and the light-emitting element **270R** have the same structure.

(203) The light-receiving element **270PD** and the light-emitting element **270R** share the active layer **273** and the light-emitting layer **283R**.

(204) Here, it is preferable that the light-receiving element **270PD** have a structure in common with the light-emitting element that emits light with a wavelength longer than that of the light desired to be detected. For example, the light-receiving element **270PD** having a structure in which blue light is detected can have a structure which is similar to that of one or both of the light-emitting element **270R** and the light-emitting element **270G**. For example, the light-receiving element **270PD** having a structure in which green light is detected can have a structure similar to that of the light-emitting element **270R**.

(205) When the light-receiving element **270PD** and the light-emitting element **270R** have a common structure, the number of deposition steps and the number of masks can be smaller than those for the structure in which the light-receiving element **270PD** and the light-emitting element **270R** include separately formed layers. As a result, the number of manufacturing steps and the manufacturing cost of the display device can be reduced.

(206) When the light-receiving element **270PD** and the light-emitting element **270R** have a common structure, a margin for misalignment can be narrower than that for the structure in which the light-receiving element **270PD** and the light-emitting element **270R** include separately formed layers. Accordingly, the aperture ratio of a pixel can be increased, so that the light extraction efficiency of the display device can be increased. This can extend the life of the light-emitting element. Furthermore, the display device can exhibit a high luminance. Moreover, the definition of the display device can also be increased.

(207) The light-emitting layer **283R** includes a light-emitting material that emits red light. The active layer **273** contains an organic compound that absorbs light with a wavelength shorter than that of red light (e.g., one or both of green light and blue light). The active layer **273** preferably contains an organic compound that does not easily absorb red light and that absorbs light with a wavelength shorter than that of red light. In this way, red light can be efficiently extracted from the light-emitting element **270R**, and the light-receiving element **270PD** can detect light with a wavelength shorter than that of red light at high accuracy.

(208) Although the light-emitting element **270R** and the light-receiving element **270PD** have the same structure in an example of the display device **280B**, the light-emitting element **270R** and the light-receiving element **270PD** may include optical adjustment layers with different thicknesses.

(209) A display device **280C** illustrated in FIG. **9A** and FIG. **9B** includes a light-emitting and light-receiving element **270R-PD** that emits red (R) light and has a light-receiving function, the light-emitting element **270G** that emits green (G) light, and the light-emitting element **270B** that emits

blue (B) light.

(210) Each of the light-emitting elements includes the pixel electrode **271**, the hole-injection layer **281**, the hole-transport layer **282**, a light-emitting layer, the electron-transport layer **284**, the electron-injection layer **285**, and the common electrode **275** which are stacked in this order. The light-emitting element **270G** includes the light-emitting layer **283G**, and the light-emitting element **270B** includes the light-emitting layer **283B**. The light-emitting layer **283G** includes a light-emitting substance that emits green light, and the light-emitting layer **283B** includes a light-emitting substance that emits blue light.

(211) The light-emitting and light-receiving element **270R-PD** includes the pixel electrode **271**, the hole-injection layer **281**, the hole-transport layer **282**, the active layer **273**, the light-emitting layer **283R**, the electron-transport layer **284**, the electron-injection layer **285**, and the common electrode **275** which are stacked in this order.

(212) Note that the light-emitting and light-receiving element **270R-PD** included in the display device **280C** has the same structure as the light-emitting element **270R** and the light-receiving element **270PD** included in the display device **280B**. Furthermore, the light-emitting elements **270G** and **270B** included in the display device **280C** also have the same structures as the light-emitting elements **270G** and **270B**, which are included in the display device **280B**.

(213) FIG. **9A** illustrates a case where the light-emitting and light-receiving element **270R-PD** functions as a light-emitting element. In the example of FIG. **9A**, the light-emitting element **270B** emits blue light, the light-emitting element **270G** emits green light, and the light-emitting and light-receiving element **270R-PD** emits red light.

(214) FIG. **9B** illustrates a case where the light-emitting and light-receiving element **270R-PD** functions as a light-receiving element. In the example of FIG. **9B**, the light-emitting and light-receiving element **270R-PD** detects blue light emitted by the light-emitting element **270B** and green light emitted by the light-emitting element **270G**.

(215) The light-emitting element **270B**, the light-emitting element **270G**, and the light-emitting and light-receiving element **270R-PD** each include the pixel electrode **271** and the common electrode **275**. In this embodiment, the case where the pixel electrode **271** functions as an anode and the common electrode **275** functions as a cathode is described as an example.

(216) In the description made in this embodiment, also in the light-emitting and light-receiving element **270R-PD**, the pixel electrode **271** functions as an anode and the common electrode **275** functions as a cathode as in the light-emitting element. In other words, when the light-emitting and light-receiving element **270R-PD** is driven by application of reverse bias between the pixel electrode **271** and the common electrode **275**, light entering the light-emitting and light-receiving element **270R-PD** can be detected and charge can be generated and extracted as current.

(217) Note that it can be said that the light-emitting and light-receiving element **270R-PD** illustrated in FIG. **9A** and FIG. **9B** has a structure in which the active layer **273** is added to the light-emitting element. That is, the light-emitting and light-receiving element **270R-PD** can be formed concurrently with the formation of the light-emitting element only by adding a step of depositing the active layer **273** in the manufacturing process of the light-emitting element. The light-emitting element and the light-emitting and light-receiving element can be formed over one substrate. Thus, one or both of an image capturing function and a sensing function can be provided to the display portion without a significant increase in the number of manufacturing steps.

(218) The stacking order of the light-emitting layer **283R** and the active layer **273** is not limited. FIG. **9A** and FIG. **9B** each illustrate an example in which the active layer **273** is provided over the hole-transport layer **282**, and the light-emitting layer **283R** is provided over the active layer **273**. The light-emitting layer **283R** may be provided over the hole-transport layer **282**, and the active layer **273** may be provided over the light-emitting layer **283R**.

(219) As illustrated in FIG. **9A** and FIG. **9B**, the active layer **273** and the light-emitting layer **283R** may be in contact with each other. Furthermore, a buffer layer may be interposed between the

active layer **273** and the light-emitting layer **283R**. As the buffer layer, at least one layer of a hole-injection layer, a hole-transport layer, an electron-transport layer, an electron-injection layer, a hole-blocking layer, an electron-blocking layer, and the like can be used.

(220) The buffer layer provided between the active layer **273** and the light-emitting layer **283R** can inhibit transfer of excitation energy from the light-emitting layer **283R** to the active layer **273**. Furthermore, the buffer layer can also be used to adjust the optical path length (cavity length) of the microcavity structure. Thus, high emission efficiency can be obtained from a light-emitting and light-receiving element including the buffer layer between the active layer **273** and the light-emitting layer **283R**.

(221) The light-emitting and light-receiving element may exclude at least one layer of the hole-injection layer **281**, the hole-transport layer **282**, the electron-transport layer **284**, and the electron-injection layer **285**. Furthermore, the light-emitting and light-receiving element may include another functional layer such as a hole-blocking layer or an electron-blocking layer.

(222) The light-emitting and light-receiving element may include a layer that serves as both a light-emitting layer and an active layer without including the active layer **273** and the light-emitting layer **283R**. As the layer serving as both a light-emitting layer and an active layer, a layer containing three materials which are an n-type semiconductor that can be used for the active layer **273**, a p-type semiconductor that can be used for the active layer **273**, and a light-emitting substance that can be used for the light-emitting layer **283R** can be used, for example.

(223) Note that an absorption band on the lowest energy side of an absorption spectrum of a mixed material of the n-type semiconductor and the p-type semiconductor and a maximum peak of an emission spectrum (PL spectrum) of the light-emitting substance preferably do not overlap with each other and are further preferably positioned fully apart from each other.

(224) In the light-emitting and light-receiving element, a conductive film that transmits visible light is used as the electrode through which light is extracted. A conductive film that reflects visible light is preferably used as the electrode through which light is not extracted.

(225) The functions and materials of the layers constituting the light-emitting and light-receiving element are similar to those of the layers constituting the light-emitting elements and the light-receiving element and not described in detail.

(226) A detailed structure of the display device of one embodiment of the present invention is described below with reference to FIG. **10** and FIG. **11**.

(227) [Display Device **100A**]

(228) FIG. **10A** is a cross-sectional view of a display device **100A**.

(229) The display device **100A** includes a light-receiving element **110** and a light-emitting element **190**.

(230) The light-emitting element **190** includes a pixel electrode **191**, a buffer layer **192**, a light-emitting layer **193**, a buffer layer **194**, and a common electrode **115** which are stacked in this order. The buffer layer **192** can include one or both of a hole-injection layer and a hole-transport layer. The light-emitting layer **193** contains an organic compound. The buffer layer **194** can include one or both of an electron-injection layer and an electron-transport layer. The light-emitting element **190** has a function of emitting visible light. Note that the display device **100A** may also include a light-emitting element having a function of emitting infrared light.

(231) The light-receiving element **110** includes the pixel electrode **191**, a buffer layer **182**, an active layer **183**, a buffer layer **184**, and the common electrode **115** which are stacked in this order. The buffer layer **182** can include a hole-transport layer. The active layer **183** contains an organic compound. The buffer layer **184** can include an electron-transport layer. The light-receiving element **110** has a function of detecting visible light. Note that the light-receiving element **110** may also have a function of detecting infrared light.

(232) This embodiment is described assuming that the pixel electrode **191** functions as an anode and the common electrode **115** functions as a cathode in both of the light-emitting element **190** and

the light-receiving element **110**. In other words, the light-receiving element **110** is driven by application of reverse bias between the pixel electrode **191** and the common electrode **115**, so that light entering the light-receiving element **110** can be detected and charge can be generated and extracted as current in the display device **100A**.

(233) The pixel electrode **191**, the buffer layer **182**, the buffer layer **192**, the active layer **183**, the light-emitting layer **193**, the buffer layer **184**, the buffer layer **194**, and the common electrode **115** may each have a single-layer structure or a stacked-layer structure.

(234) The pixel electrodes **191** are positioned over an insulating layer **214**. The pixel electrodes **191** can be formed using the same material in the same step. End portions of the pixel electrodes **191** are covered with a partition **216**. The two pixel electrodes **191** adjacent to each other are electrically insulated (electrically isolated) from each other by the partition **216**.

(235) An organic insulating film is suitable for the partition **216**. Examples of materials that can be used for the organic insulating film include an acrylic resin, a polyimide resin, an epoxy resin, a polyamide resin, a polyimide-amide resin, a siloxane resin, a benzocyclobutene-based resin, a phenol resin, and precursors of these resins. The partition **216** is a layer that transmits visible light. A partition that blocks visible light may be provided instead of the partition **216**.

(236) The common electrode **115** is a layer shared by the light-receiving element **110** and the light-emitting element **190**.

(237) The material, thickness, and the like of the pair of electrodes can be the same between the light-receiving element **110** and the light-emitting element **190**. Accordingly, the manufacturing cost of the display device can be reduced and the manufacturing process of the display device can be simplified.

(238) The display device **100A** includes the light-receiving element **110**, the light-emitting element **190**, a transistor **131**, a transistor **132**, and the like between a pair of substrates (a substrate **151** and a substrate **152**).

(239) In the light-receiving element **110**, the buffer layer **182**, the active layer **183**, and the buffer layer **184**, which are positioned between the pixel electrode **191** and the common electrode **115**, can each be referred to as an organic layer (a layer containing an organic compound). The pixel electrode **191** preferably has a function of reflecting visible light. The common electrode **115** has a function of transmitting visible light. Note that in the case where the light-receiving element **110** is configured to detect infrared light, the common electrode **115** has a function of transmitting infrared light. Furthermore, the pixel electrode **191** preferably has a function of reflecting infrared light.

(240) The light-receiving element **110** has a function of detecting light. Specifically, the light-receiving element **110** is a photoelectric conversion element that receives light **122** entering from the outside of the display device **100A** and converts it into an electric signal. The light **122** can also be expressed as light that is emitted from the light-emitting element **190** and then reflected by an object. The light **122** may enter the light-receiving element **110** through a lens or the like provided in the display device **100A**.

(241) In the light-emitting element **190**, the buffer layer **192**, the light-emitting layer **193**, and the buffer layer **194**, which are positioned between the pixel electrode **191** and the common electrode **115**, can be collectively referred to as an EL layer. The EL layer includes at least the light-emitting layer **193**. As described above, the pixel electrode **191** preferably has a function of reflecting visible light. The common electrode **115** has a function of transmitting visible light. Note that in the case where the display device **100A** includes a light-emitting element that emits infrared light, the common electrode **115** has a function of transmitting infrared light. Furthermore, the pixel electrode **191** preferably has a function of reflecting infrared light.

(242) The light-emitting element included in the display device of this embodiment preferably employs a micro optical resonator (microcavity) structure.

(243) The buffer layer **192** or the buffer layer **194** may have a function as an optical adjustment

layer. By changing the thickness of the buffer layer **192** or the buffer layer **194**, light of a particular color can be intensified and taken out from each light-emitting element.

(244) The light-emitting element **190** has a function of emitting visible light. Specifically, the light-emitting element **190** is an electroluminescent element that exhibits light to the substrate **152** side by applying voltage between the pixel electrode **191** and the common electrode **115** (see light emission **121**).

(245) The pixel electrode **191** included in the light-receiving element **110** is electrically connected to a source or a drain of the transistor **131** through an opening provided in the insulating layer **214**.

(246) The pixel electrode **191** included in the light-emitting element **190** is electrically connected to a source or a drain of the transistor **132** through an opening provided in the insulating layer **214**.

(247) The transistor **131** and the transistor **132** are on and in contact with the same layer (the substrate **151** in FIG. **10A**).

(248) At least part of a circuit electrically connected to the light-receiving element **110** and a circuit electrically connected to the light-emitting element **190** are preferably formed using the same material in the same step. In that case, the thickness of the display device can be reduced compared with the case where the two circuits are separately formed, resulting in simplification of the manufacturing steps.

(249) The light-receiving element **110** and the light-emitting element **190** are preferably covered with a protective layer **116**. In FIG. **10A**, the protective layer **116** is provided on and in contact with the common electrode **115**. Providing the protective layer **116** can inhibit entry of impurities such as water into the light-receiving element **110** and the light-emitting element **190**, so that the reliability of the light-receiving element **110** and the light-emitting element **190** can be increased. The protective layer **116** and the substrate **152** are bonded to each other with an adhesive layer **142**.

(250) A light shielding layer **158** is provided on a surface of the substrate **152** on the substrate **151** side. The light shielding layer **158** has openings in a position overlapping with the light-emitting element **190** and in a position overlapping with the light-receiving element **110**.

(251) Here, the light-receiving element **110** detects light that is emitted from the light-emitting element **190** and then reflected by an object. However, in some cases, light emitted from the light-emitting element **190** is reflected inside the display device **100A** and enters the light-receiving element **110** without through an object. The light shielding layer **158** can reduce the influence of such stray light. For example, in the case where the light shielding layer **158** is not provided, light **123** emitted from the light-emitting element **190** is reflected by the substrate **152** and reflected light **124** enters the light-receiving element **110** in some cases. Providing the light shielding layer **158** can inhibit entry of the reflected light **124** into the light-receiving element **110**. Consequently, noise can be reduced, and the sensitivity of a sensor using the light-receiving element **110** can be increased.

(252) For the light shielding layer **158**, a material that blocks light emitted from the light-emitting element can be used. The light shielding layer **158** preferably absorbs visible light. As the light shielding layer **158**, a black matrix can be formed using a metal material or a resin material containing pigment (e.g., carbon black) or dye, for example. The light shielding layer **158** may have a stacked-layer structure of a red color filter, a green color filter, and a blue color filter.

(253) [Display Device **100B**]

(254) FIG. **10B** and FIG. **10C** illustrate cross-sectional views of a display device **100B**. Note that in the description of the display device below, components similar to those of the above-mentioned display device are not described in some cases.

(255) The display device **100B** includes a light-emitting element **190B**, a light-emitting element **190G**, and a light-emitting and light-receiving element **190R-PD**.

(256) The light-emitting element **190B** includes the pixel electrode **191**, a buffer layer **192B**, a light-emitting layer **193B**, a buffer layer **194B**, and the common electrode **115** which are stacked in this order. The light-emitting element **190B** has a function of emitting blue light **121B**.

(257) The light-emitting element **190G** includes the pixel electrode **191**, a buffer layer **192G**, a light-emitting layer **193G**, a buffer layer **194G**, and the common electrode **115** which are stacked in this order. The light-emitting element **190G** has a function of emitting green light **121G**.

(258) The light-emitting and light-receiving element **190R-PD** includes the pixel electrode **191**, a buffer layer **192R**, the active layer **183**, a light-emitting layer **193R**, a buffer layer **194R**, and the common electrode **115** which are stacked in this order. The light-emitting and light-receiving element **190R-PD** has a function of emitting red light **121R** and a function of detecting the light **122**.

(259) FIG. **10B** illustrates a case where the light-emitting and light-receiving element **190R-PD** functions as a light-emitting element. FIG. **10B** illustrates an example in which the light-emitting element **190B** emits blue light, the light-emitting element **190G** emits green light, and the light-emitting and light-receiving element **190R-PD** emits red light.

(260) FIG. **10C** illustrates a case where the light-emitting and light-receiving element **190R-PD** functions as a light receiving element. FIG. **10C** illustrates an example in which the light-emitting and light-receiving element **190R-PD** detects blue light emitted by the light-emitting element **190B** and green light emitted by the light-emitting element **190G**.

(261) The display device **100B** includes the light-emitting and light-receiving element **190R-PD**, the light-emitting element **190G**, the light-emitting element **190B**, the transistor **132**, and the like between a pair of substrates (the substrate **151** and a substrate **152**).

(262) The pixel electrode **191** is positioned over the insulating layer **214**. The two pixel electrodes **191** adjacent to each other are electrically insulated from each other by the partition **216**. The pixel electrode **191** is electrically connected to the source or the drain of the transistor **132** through the opening provided in the insulating layer **214**.

(263) The light-emitting and light-receiving element and the light-emitting elements are preferably covered with the protective layer **116**. The protective layer **116** and the substrate **152** are bonded to each other with the adhesive layer **142**. The light shielding layer **158** is provided on the surface of the substrate **152** on the substrate **151** side.

(264) [Display Device **100C**]

(265) FIG. **11A** illustrates a cross-sectional view of a display device **100C**.

(266) The display device **100C** includes the light-receiving element **110** and the light-emitting element **190**.

(267) The light-emitting element **190** includes the pixel electrode **191**, a common layer **112**, the light-emitting layer **193**, a common layer **114**, and the common electrode **115** in this order. The common layer **112** can include one or both of a hole-injection layer and a hole-transport layer. The light-emitting layer **193** contains an organic compound. The common layer **114** can include one or both of an electron-injection layer and an electron-transport layer. The light-emitting element **190** has a function of emitting visible light. Note that the display device **100C** may also include a light-emitting element having a function of emitting infrared light.

(268) The light-receiving element **110** includes the pixel electrode **191**, the common layer **112**, the active layer **183**, the common layer **114**, and the common electrode **115** which are stacked in this order. The active layer **183** contains an organic compound. The light-receiving element **110** has a function of detecting visible light. Note that the light-receiving element **110** may also have a function of detecting infrared light.

(269) The pixel electrode **191**, the common layer **112**, the active layer **183**, the light-emitting layer **193**, the common layer **114**, and the common electrode **115** may each have a single-layer structure or a stacked-layer structure.

(270) The pixel electrode **191** is positioned over the insulating layer **214**. The two pixel electrodes **191** adjacent to each other are electrically insulated from each other by the partition **216**. The pixel electrode **191** is electrically connected to the source or the drain of the transistor **132** through the opening provided in the insulating layer **214**.

(271) The common layer **112**, the common layer **114**, and the common electrode **115** are layers shared by the light-receiving element **110** and the light-emitting element **190**. At least some of the layers constituting the light-receiving element **110** and the light-emitting element **190** preferably have common structures, in which case the number of manufacturing steps of the display device can be reduced.

(272) The display device **100C** includes the light-receiving element **110**, the light-emitting element **190**, the transistor **131**, the transistor **132**, and the like between the pair of substrates (the substrate **151** and the substrate **152**).

(273) The light-receiving element **110** and the light-emitting element **190** are preferably covered with the protective layer **116**. The protective layer **116** and the substrate **152** are bonded to each other with the adhesive layer **142**.

(274) A resin layer **159** is provided on the surface of the substrate **152** on the substrate **151** side. The resin layer **159** is provided in a position overlapping with the light-emitting element **190** and is not provided in a position overlapping with the light-receiving element **110**.

(275) The resin layer **159** can be provided in the position overlapping with the light-emitting element **190** and have an opening **159p** in the position overlapping with the light-receiving element **110**, as illustrated in FIG. **11B**, for example. Alternatively, as illustrated in FIG. **11C**, the resin layer **159** can be provided to have an island shape in a position overlapping with the light-emitting element **190** but not in a position overlapping with the light-receiving element **110**.

(276) The light shielding layer **158** is provided on the surface of the substrate **152** on the substrate **151** side and on a surface of the resin layer **159** on the substrate **151** side. The light shielding layer **158** has openings in a position overlapping with the light-emitting element **190** and in a position overlapping with the light-receiving element **110**.

(277) Here, the light-receiving element **110** detects light that is emitted from the light-emitting element **190** and then reflected by an object. However, in some cases, light emitted from the light-emitting element **190** is reflected inside the display device **100C** and enters the light-receiving element **110** without through an object. The light shielding layer **158** can absorb such stray light and thereby reduce entry of stray light into the light-receiving element **110**. For example, the light shielding layer **158** can absorb stray light **123a** that has passed through the resin layer **159** and has been reflected by the surface of the substrate **152** on the substrate **151** side. Moreover, the light shielding layer **158** can absorb stray light **123b** before the stray light **123b** reaches the resin layer **159**. This can inhibit stray light from entering the light-receiving element **110**. Consequently, noise can be reduced, and the sensitivity of a sensor using the light-receiving element **110** can be increased. It is particularly preferable that the light shielding layer **158** be positioned close to the light-emitting element **190**, in which case stray light can be further reduced. This is preferable also in terms of improving display quality, because the light shielding layer **158** positioned close to the light-emitting element **190** can inhibit viewing angle dependence of display.

(278) Providing the light shielding layer **158** can control the range where the light-receiving element **110** detects light. When the light shielding layer **158** is positioned apart from the light-receiving element **110**, the image-capturing range is narrowed, and the image-capturing resolution can be increased.

(279) In the case where the resin layer **159** has an opening, the light shielding layer **158** preferably covers at least part of the opening and at least part of a side surface of the resin layer **159** exposed in the opening.

(280) In the case where the resin layer **159** is provided in an island shape, the light shielding layer **158** preferably covers at least part of a side surface of the resin layer **159**.

(281) Since the light shielding layer **158** is provided along the shape of the resin layer **159** in such a manner, the distance from the light shielding layer **158** to the light-emitting element **190** (specifically, the light-emitting region of the light-emitting element **190**) is shorter than the distance from the light shielding layer **158** to the light-receiving element **110** (specifically, the light-

receiving region of the light-receiving element **110**). Accordingly, noise of the sensor can be reduced, the imaging resolution can be increased, and viewing angle dependence of display can be inhibited. Thus, both the display quality and imaging quality of the display device can be increased.

(282) The resin layer **159** is a layer that transmits light emitted from the light-emitting element **190**. Examples of materials for the resin layer **159** include an acrylic resin, a polyimide resin, an epoxy resin, a polyamide resin, a polyimide-amide resin, a siloxane resin, a benzocyclobutene-based resin, a phenol resin, and precursors of these resins. Note that a component provided between the substrate **152** and the light shielding layer **158** is not limited to the resin layer and may be an inorganic insulating film or the like. As the component becomes thicker, a larger difference occurs between the distance from the light shielding layer to the light-receiving element and the distance from the light shielding layer to the light-emitting element. An organic insulating film such as a resin or the like is suitable for the component because it is easily formed to have a large thickness.

(283) In order to compare the distance from the light shielding layer **158** to the light-receiving element **110** and the distance from the light shielding layer **158** to the light-emitting element **190**, it is possible to use, for example, the shortest distance **L1** from an end portion of the light shielding layer **158** on the light-receiving element **110** side to the common electrode **115** and the shortest distance **L2** from an end portion of the light shielding layer **158** on the light-emitting element **190** side to the common electrode **115**. With the shortest distance **L2** smaller than the shortest distance **L1**, stray light from the light-emitting element **190** can be inhibited, and the sensitivity of the sensor using the light-receiving element **110** can be increased. Furthermore, viewing angle dependence of display can be inhibited. With the shortest distance **L1** larger than the shortest distance **L2**, the image-capturing range of the light-receiving element **110** can be narrowed, and the image-capturing resolution can be increased.

(284) In addition, when the adhesive layer **142** is provided such that a portion overlapping with the light-receiving element **110** is made thicker than a portion overlapping with the light-emitting element **190**, a difference also can be made between the distance from the light shielding layer **158** to the light-receiving element **110** and the distance from the light shielding layer **158** to the light-emitting element **190**.

(285) A more detailed structure of the display device of one embodiment of the present invention is described below with reference to FIG. **12** to FIG. **15**.

(286) [Display Device **100D**]

(287) FIG. **12** illustrates a perspective view of a display device **100D**, and FIG. **13** illustrates a cross-sectional view of the display device **100D**.

(288) The display device **100D** has a structure in which the substrate **152** and the substrate **151** are bonded to each other. In FIG. **12**, the substrate **152** is denoted by a dashed line.

(289) The display device **100D** includes a display portion **162**, a circuit **164**, a wiring **165**, and the like. FIG. **12** illustrates an example in which an IC **173** and an FPC **172** are integrated on the display device **100D**. Thus, the structure illustrated in FIG. **12** can be regarded as a display module including the display device **100D**, the IC (integrated circuit), and the FPC (Flexible Printed Circuit).

(290) As the circuit **164**, for example, a scan line driver circuit can be used.

(291) The wiring **165** has a function of supplying a signal and power to the display portion **162** and the circuit **164**. The signal and power are input to the wiring **165** from the outside through the FPC **172** or from the IC **173**.

(292) FIG. **12** illustrates an example in which the IC **173** is provided over the substrate **151** by a COG (Chip On Glass) method, a COF (Chip On Film) method, or the like. An IC including a scan line driver circuit, a signal line driver circuit, or the like can be used as the IC **173**, for example. Note that the display device **100D** and the display module may have a structure that is not provided with an IC. The IC may be provided over the FPC by a COF method or the like.

(293) FIG. **13** illustrates an example of cross sections of part of a region including the FPC **172**,

part of a region including the circuit **164**, part of a region including the display portion **162**, and part of a region including an end portion of the display device **100D** illustrated in FIG. **12**.

(294) The display device **100D** illustrated in FIG. **13** includes a transistor **241**, a transistor **245**, a transistor **246**, a transistor **247**, the light-emitting element **190B**, the light-emitting element **190G**, the light-emitting and light-receiving element **190R-PD**, and the like between the substrate **151** and the substrate **152**.

(295) The substrate **152** and the protective layer **116** are bonded to each other with the adhesive layer **142**. A solid sealing structure, a hollow sealing structure, or the like can be employed to seal the light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD**. In FIG. **13**, a space surrounded by the substrate **152**, the adhesive layer **142**, and the insulating layer **214** is sealed with the adhesive layer **142**, and the solid sealing structure is employed.

(296) The light-emitting element **190B** has a stacked-layer structure in which the pixel electrode **191**, the common layer **112**, the light-emitting layer **193B**, the common layer **114**, and the common electrode **115** are stacked in this order from the insulating layer **214** side. The pixel electrode **191** is connected to a conductive layer **222b** included in the transistor **247** through an opening provided in the insulating layer **214**. The transistor **247** has a function of controlling the driving of the light-emitting element **190B**. The end portion of the pixel electrode **191** is covered with the partition **216**. The pixel electrode **191** contains a material that reflects visible light, and the common electrode **115** contains a material that transmits visible light.

(297) The light-emitting element **190G** has a stacked-layer structure in which the pixel electrode **191**, the common layer **112**, the light-emitting layer **193G**, the common layer **114**, and the common electrode **115** are stacked in this order from the insulating layer **214** side. The pixel electrode **191** is connected to the conductive layer **222b** included in the transistor **246** through an opening provided in the insulating layer **214**. The transistor **246** has a function of controlling the driving of the light-emitting element **190G**.

(298) The light-emitting and light-receiving element **190R-PD** has a stacked-layer structure in which the pixel electrode **191**, the common layer **112**, the active layer **183**, the light-emitting layer **193R**, the common layer **114**, and the common electrode **115** are stacked in this order from the insulating layer **214** side. The pixel electrode **191** is electrically connected to the conductive layer **222b** included in the transistor **245** through an opening provided in the insulating layer **214**. The transistor **245** has a function of controlling the driving of the light-emitting and light-receiving element **190R-PD**.

(299) Light emitted by the light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD** is emitted toward the substrate **152** side. Light enters the light-emitting and light-receiving element **190R-PD** through the substrate **152** and the adhesive layer **142**. For the substrate **152** and the adhesive layer **142**, a material having a high visible-light-transmitting property is preferably used.

(300) The pixel electrodes **191** included in the light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD** can be formed using the same material in the same step. The common layer **112**, the common layer **114**, and the common electrode **115** are used in common in the light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD**. The light-emitting and light-receiving element **190R-PD** has the structure of the red-light-emitting element to which the active layer **183** is added. The light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD** can have a common structure except for the active layer **183** and the light-emitting layer **193** of each color. Thus, the display portion **162** of the display device **100D** can have a light-receiving function without a significant increase in the number of manufacturing steps.

(301) The light shielding layer **158** is provided on the surface of the substrate **152** on the substrate

151 side. The light shielding layer **158** includes openings in positions overlapping with the light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD**. Providing the light shielding layer **158** can control the range where the light-emitting and light-receiving element **190R-PD** detects light. As described above, it is preferable to control light entering the light-emitting and light-receiving element by adjusting the position of the opening of the light shielding layer provided in a position overlapping with the light-emitting and light-receiving element **190R-PD**. Furthermore, with the light shielding layer **158**, light can be inhibited from directly entering the light-emitting and light-receiving element **190R-PD** from the light-emitting element **190** without through an object. Hence, a sensor with less noise and high sensitivity can be obtained.

(302) The transistor **241**, the transistor **245**, the transistor **246**, and the transistor **247** are formed over the substrate **151**. These transistors can be formed using the same materials in the same steps.

(303) An insulating layer **211**, an insulating layer **213**, an insulating layer **215**, and the insulating layer **214** are provided in this order over the substrate **151**. Parts of the insulating layer **211** function as gate insulating layers of the transistors. Parts of the insulating layer **213** function as gate insulating layers of the transistors. The insulating layer **215** is provided to cover the transistors. The insulating layer **214** is provided to cover the transistors and has a function of a planarization layer. Note that there is no limitation on the number of gate insulating layers and the number of insulating layers covering the transistors, and each insulating layer may have either a single layer or two or more layers.

(304) A material into which impurities such as water and hydrogen do not easily diffuse is preferably used for at least one of the insulating layers that cover the transistors. This allows the insulating layer to serve as a barrier layer. Such a structure can effectively inhibit diffusion of impurities into the transistors from the outside and increase the reliability of the display device.

(305) An inorganic insulating film is preferably used as each of the insulating layer **211**, the insulating layer **213**, and the insulating layer **215**. As the inorganic insulating film, a silicon nitride film, a silicon oxynitride film, a silicon oxide film, a silicon nitride oxide film, an aluminum oxide film, or an aluminum nitride film can be used, for example. A hafnium oxide film, a hafnium oxynitride film, a hafnium nitride oxide film, an yttrium oxide film, a zirconium oxide film, a gallium oxide film, a tantalum oxide film, a magnesium oxide film, a lanthanum oxide film, a cerium oxide film, a neodymium oxide film, or the like may be used. A stack including two or more of the above insulating films may also be used. Note that a base film may be provided between the substrate **151** and the transistors. Any of the above-described inorganic insulating films can be used as the base film.

(306) Here, an organic insulating film often has a lower barrier property than an inorganic insulating film. Therefore, the organic insulating film preferably has an opening in the vicinity of an end portion of the display device **100D**. This can inhibit entry of impurities from the end portion of the display device **100D** through the organic insulating film. Alternatively, the organic insulating film may be formed so that an end portion of the organic insulating film is positioned on the inner side compared to the end portion of the display device **100D**, to prevent the organic insulating film from being exposed at the end portion of the display device **100D**.

(307) An organic insulating film is suitable for the insulating layer **214** functioning as a planarization layer. Examples of materials that can be used for the organic insulating film include an acrylic resin, a polyimide resin, an epoxy resin, a polyamide resin, a polyimide-amide resin, a siloxane resin, a benzocyclobutene-based resin, a phenol resin, and precursors of these resins.

(308) By provision of the protective layer **116** that covers the light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD**, impurities such as water can be inhibited from entering the light-emitting element **190B**, the light-emitting element **190G**, and the light-emitting and light-receiving element **190R-PD**, leading to an increase in the reliability of the light-emitting element **190B**, the light-emitting element **190G**, and

the light-emitting and light-receiving element **190R-PD**.

(309) In a region **228** illustrated in FIG. **13**, an opening is formed in the insulating layer **214**. This can inhibit entry of impurities into the display portion **162** from the outside through the insulating layer **214** even when an organic insulating film is used as the insulating layer **214**. Thus, the reliability of the display device **100D** can be increased.

(310) In the region **228** in the vicinity of an end portion of the display device **100D**, the insulating layer **215** and the protective layer **116** are preferably in contact with each other through the opening in the insulating layer **214**. In particular, the inorganic insulating film included in the insulating layer **215** and the inorganic insulating film included in the protective layer **116** are preferably in contact with each other. Thus, entry of impurities from the outside into the display portion **162** through the organic insulating film can be inhibited. Thus, the reliability of the display device **100D** can be increased.

(311) The protective layer **116** may have a single-layer structure or a stacked-layer structure. For example, the protective layer **116** may have a stacked-layer structure of an organic insulating film and an inorganic insulating film. In that case, an end portion of the inorganic insulating film preferably extends beyond an end portion of the organic insulating film.

(312) Each of the transistor **241**, the transistor **245**, the transistor **246**, and the transistor **247** includes a conductive layer **221** functioning as a gate, the insulating layer **211** functioning as the gate insulating layer, a conductive layer **222a** and the conductive layer **222b** functioning as a source and a drain, a semiconductor layer **231**, the insulating layer **213** functioning as the gate insulating layer, and a conductive layer **223** functioning as a gate. Here, a plurality of layers obtained by processing the same conductive film are illustrated with the same hatching pattern. The insulating layer **211** is positioned between the conductive layer **221** and the semiconductor layer **231**. The insulating layer **213** is positioned between the conductive layer **223** and the semiconductor layer **231**.

(313) There is no particular limitation on the structure of the transistors included in the display device of this embodiment. For example, a planar transistor, a staggered transistor, or an inverted staggered transistor can be used. A top-gate or a bottom-gate transistor structure may be employed. Alternatively, gates may be provided above and below a semiconductor layer in which a channel is formed.

(314) The structure in which the semiconductor layer where a channel is formed is provided between two gates is used for the transistor **241**, the transistor **245**, the transistor **246**, and the transistor **247**. The two gates may be connected to each other and supplied with the same signal to drive the transistor. Alternatively, a potential for controlling the threshold voltage may be supplied to one of the two gates and a potential for driving may be supplied to the other to control the threshold voltage of the transistor.

(315) There is no particular limitation on the crystallinity of a semiconductor material used in the transistor, and any of an amorphous semiconductor or a semiconductor having crystallinity (a microcrystalline semiconductor, a polycrystalline semiconductor, a single crystal semiconductor, or a semiconductor partly including crystal regions) may be used. A semiconductor having crystallinity is preferably used, in which case deterioration of the transistor characteristics can be inhibited.

(316) A semiconductor layer of a transistor preferably includes a metal oxide (also referred to as an oxide semiconductor). Alternatively, the semiconductor layer of the transistor may include silicon. Examples of silicon include amorphous silicon and crystalline silicon (e.g., low-temperature polysilicon or single crystal silicon).

(317) The semiconductor layer preferably includes indium, M (M is one or more kinds selected from gallium, aluminum, silicon, boron, yttrium, tin, copper, vanadium, beryllium, titanium, iron, nickel, germanium, zirconium, molybdenum, lanthanum, cerium, neodymium, hafnium, tantalum, tungsten, and magnesium), and zinc, for example. Specifically, M is preferably one or more kinds

selected from aluminum, gallium, yttrium, and tin.

(318) It is particularly preferable to use an oxide containing indium (In), gallium (Ga), and zinc (Zn) (also referred to as IGZO) for the semiconductor layer.

(319) When the semiconductor layer is an In-M-Zn oxide, the atomic ratio of In is preferably greater than or equal to the atomic ratio of M in the In-M-Zn oxide. Examples of the atomic ratio of the metal elements in such an In-M-Zn oxide include In:M:Zn=1:1:1 or a composition in the neighborhood thereof, In:M:Zn=1:1:1.2 or a composition in the neighborhood thereof, In:M:Zn=2:1:3 or a composition in the neighborhood thereof, In:M:Zn=3:1:2 or a composition in the neighborhood thereof, In:M:Zn=4:2:3 or a composition in the neighborhood thereof, In:M:Zn=4:2:4.1 or a composition in the neighborhood thereof, In:M:Zn=5:1:3 or a composition in the neighborhood thereof, In:M:Zn=5:1:6 or a composition in the neighborhood thereof, In:M:Zn=5:1:7 or a composition in the neighborhood thereof, In:M:Zn=5:1:8 or a composition in the neighborhood thereof, In:M:Zn=6:1:6 or a composition in the neighborhood thereof, and In:M:Zn=5:2:5 or a composition in the neighborhood thereof. Note that a composition in the neighborhood includes the range of $\pm 30\%$ of an intended atomic ratio.

(320) For example, when the atomic ratio is described as In:Ga:Zn=4:2:3 or a composition in the neighborhood thereof, the case is included where the atomic ratio of Ga is greater than or equal to 1 and less than or equal to 3 and the atomic ratio of Zn is greater than or equal to 2 and less than or equal to 4 with the atomic ratio of In being 4. When the atomic ratio is described as In:Ga:Zn=5:1:6 or a composition in the neighborhood thereof, the case is included where the atomic ratio of Ga is greater than 0.1 and less than or equal to 2 and the atomic ratio of Zn is greater than or equal to 5 and less than or equal to 7 with the atomic ratio of In being 5. When the atomic ratio is described as In:Ga:Zn=1:1:1 or a composition in the neighborhood thereof, the case is included where the atomic ratio of Ga is greater than 0.1 and less than or equal to 2 and the atomic ratio of Zn is greater than 0.1 and less than or equal to 2 with the atomic ratio of In being 1.

(321) The transistor included in the circuit **164** and the transistor included in the display portion **162** may have the same structure or different structures. A plurality of transistors included in the circuit **164** may have the same structure or two or more kinds of structures. Similarly, a plurality of transistors included in the display portion **162** may have the same structure or two or more kinds of structures.

(322) A connection portion **244** is provided in a region of the substrate **151** that does not overlap with the substrate **152**. In the connection portion **244**, the wiring **165** is electrically connected to the FPC **172** via a conductive layer **166** and a connection layer **242**. On the top surface of the connection portion **244**, the conductive layer **166** obtained by processing the same conductive film as the pixel electrode **191** is exposed. Thus, the connection portion **244** and the FPC **172** can be electrically connected to each other through the connection layer **242**.

(323) A variety of optical members can be arranged on an outer surface of the substrate **152**. Examples of the optical members include a polarizing plate, a retardation plate, a light diffusion layer (a diffusion film or the like), an anti-reflective layer, and a light-condensing film. Furthermore, an antistatic film inhibiting the attachment of dust, a water repellent film suppressing the attachment of stain, a hard coat film inhibiting generation of a scratch caused by the use, a shock absorbing layer, or the like may be provided on the outer surface of the substrate **152**.

(324) For each of the substrate **151** and the substrate **152**, glass, quartz, ceramic, sapphire, resin, or the like can be used. When a flexible material is used for the substrate **151** and the substrate **152**, the flexibility of the display device can be increased.

(325) For the adhesive layer, a variety of curable adhesives, e.g., a photocurable adhesive such as an ultraviolet curable adhesive, a reactive curable adhesive, a thermosetting adhesive, and an anaerobic adhesive can be used. Examples of these adhesives include an epoxy resin, an acrylic resin, a silicone resin, a phenol resin, a polyimide resin, an imide resin, a PVC (polyvinyl chloride) resin, a PVB (polyvinyl butyral) resin, and an EVA (ethylene vinyl acetate) resin. In particular, a

material with low moisture permeability, such as an epoxy resin, is preferred. Alternatively, a two-component resin may be used. An adhesive sheet or the like may be used.

(326) As the connection layer, an anisotropic conductive film (ACF), an anisotropic conductive paste (ACP), or the like can be used.

(327) For the structures, materials, and the like of the light-emitting elements **190G** and **190B** and the light-emitting and light-receiving element **190R-PD**, the above description can be referred to.

(328) As materials that can be used for a gate, a source, and a drain of a transistor and conductive layers such as a variety of wirings and electrodes included in a display device, metals such as aluminum, titanium, chromium, nickel, copper, yttrium, zirconium, molybdenum, silver, tantalum, and tungsten, an alloy containing any of these metals as its main component, and the like can be given. A film containing any of these materials can be used in a single layer or as a stacked-layer structure.

(329) As a light-transmitting conductive material, a conductive oxide such as indium oxide, indium tin oxide, indium zinc oxide, zinc oxide, or zinc oxide containing gallium, or graphene can be used. Alternatively, a metal material such as gold, silver, platinum, magnesium, nickel, tungsten, chromium, molybdenum, iron, cobalt, copper, palladium, or titanium, or an alloy material containing the metal material can be used. Further alternatively, a nitride of the metal material (e.g., titanium nitride) or the like may be used. Note that in the case of using the metal material or the alloy material (or the nitride thereof), the thickness is preferably set small enough to be able to transmit light. A stacked-layer film of any of the above materials can be used as a conductive layer. For example, a stacked-layer film of indium tin oxide and an alloy of silver and magnesium, or the like is preferably used for increased conductivity. These materials can also be used for conductive layers such as a variety of wirings and electrodes that constitute a display device, and conductive layers (conductive layers functioning as a pixel electrode or a common electrode) included in a light-emitting element and a light-receiving element (or a light-emitting and light-receiving element).

(330) As an insulating material that can be used for each insulating layer, for example, a resin such as an acrylic resin or an epoxy resin, and an inorganic insulating material such as silicon oxide, silicon oxynitride, silicon nitride oxide, silicon nitride, or aluminum oxide can be given.

(331) [Display Device **100E**]

(332) FIG. **14** and FIG. **15A** illustrate cross-sectional views of a display device **100E**. A perspective view of the display device **100E** is similar to that of the display device **100D** (FIG. **9**). FIG. **14** illustrates an example of cross sections of part of a region including the FPC **172**, part of the circuit **164**, and part of the display portion **162** in the display device **100E**. FIG. **15A** illustrates an example of a cross section of part of the display portion **162** in the display device **100E**. FIG. **14** specifically illustrates an example of a cross section of a region including the light-receiving element **110** and the light-emitting element **190R** that emits red light in the display portion **162**. FIG. **15A** specifically illustrates an example of a cross section of a region including the light-emitting element **190G** that emits green light and the light-emitting element **190B** that emits blue light in the display portion **162**.

(333) The display device **100E** illustrated in FIG. **14** and FIG. **15A** includes a transistor **243**, a transistor **248**, a transistor **249**, a transistor **240**, the light-emitting element **190R**, the light-emitting element **190G**, the light-emitting element **190B**, the light-receiving element **110**, and the like between a substrate **153** and a substrate **154**.

(334) The resin layer **159** and the common electrode **115** are bonded to each other with the adhesive layer **142**, and the display device **100E** employs a solid sealing structure.

(335) The substrate **153** and the insulating layer **212** are bonded to each other with an adhesive layer **155**. The substrate **154** and an insulating layer **157** are bonded to each other with an adhesive layer **156**.

(336) To fabricate the display device **100E**, first, a first formation substrate provided with the

insulating layer **212**, the transistors, the light-receiving element **110**, the light-emitting elements, and the like and a second formation substrate provided with the insulating layer **157**, the resin layer **159**, the light shielding layer **158**, and the like are bonded to each other with the adhesive layer **142**. Then, the substrate **153** is bonded to a surface exposed by separation of the first formation substrate, and the substrate **154** is bonded to a surface exposed by separation of the second formation substrate, whereby the components formed over the first formation substrate and the second formation substrate are transferred to the substrate **153** and the substrate **154**. The substrate **153** and the substrate **154** preferably have flexibility. Accordingly, the flexibility of the display device **100E** can be increased.

(337) The inorganic insulating film that can be used as the insulating layer **211**, the insulating layer **213**, and the insulating layer **215** can be used as the insulating layer **212** and the insulating layer **157**.

(338) The light-emitting element **190R** has a stacked-layer structure in which the pixel electrode **191**, the common layer **112**, the light-emitting layer **193R**, the common layer **114**, and the common electrode **115** are stacked in this order from an insulating layer **214b** side. The pixel electrode **191** is connected to a conductive layer **169** through an opening provided in the insulating layer **214b**. The conductive layer **169** is connected to the conductive layer **222b** included in the transistor **248** through an opening provided in an insulating layer **214a**. The conductive layer **222b** is connected to a low-resistance region **231n** through an opening provided in the insulating layer **215**. That is, the pixel electrode **191** is electrically connected to the transistor **248**. The transistor **248** has a function of controlling the driving of the light-emitting element **190R**.

(339) Similarly, the light-emitting element **190G** has a stacked-layer structure in which the pixel electrode **191**, the common layer **112**, the light-emitting layer **193G**, the common layer **114**, and the common electrode **115** are stacked in this order from the insulating layer **214b** side. The pixel electrode **191** is electrically connected to the low-resistance region **231n** of the transistor **249** through the conductive layer **169** and the conductive layer **222b** of the transistor **249**. That is, the pixel electrode **191** is electrically connected to the transistor **249**. The transistor **249** has a function of controlling the driving of the light-emitting element **190G**.

(340) In addition, the light-emitting element **190B** has a stacked-layer structure in which the pixel electrode **191**, the common layer **112**, the light-emitting layer **193B**, the common layer **114**, and the common electrode **115** are stacked in this order from the insulating layer **214b** side. The pixel electrode **191** is electrically connected to the low-resistance region **231n** of the transistor **240** through the conductive layer **169** and the conductive layer **222b** of the transistor **240**. That is, the pixel electrode **191** is electrically connected to the transistor **240**. The transistor **240** has a function of controlling the driving of the light-emitting element **190B**.

(341) The light-receiving element **110** has a stacked-layer structure in which the pixel electrode **191**, the common layer **112**, the active layer **183**, the common layer **114**, and the common electrode **115** are stacked in this order from the insulating layer **214b** side.

(342) The end portion of the pixel electrode **191** is covered with the partition **216**. The pixel electrode **191** contains a material that reflects visible light, and the common electrode **115** contains a material that transmits visible light.

(343) Light emitted by the light-emitting elements **190R**, **190G**, and **190B** is emitted toward the substrate **154** side. Light enters the light-receiving element **110** through the substrate **154** and the adhesive layer **142**. For the substrate **154**, a material having a high visible-light-transmitting property is preferably used.

(344) The pixel electrodes **191** can be formed using the same material in the same step. The common layer **112**, the common layer **114**, and the common electrode **115** are used in common in the light-receiving element **110** and the light-emitting elements **190R**, **190G**, and **190B**. The light-receiving element **110** and the light-emitting element of each color can have a common structure except for the active layer **183** and the light-emitting layer. Thus, the light-receiving element **110**

can be incorporated into the display device **100E** without a significant increase in the number of manufacturing steps.

(345) The resin layer **159** and the light shielding layer **158** are provided on a surface of the insulating layer **157** on the substrate **153** side. The resin layer **159** is provided in positions overlapping with the light-emitting elements **190R**, **190G**, and **190B** and is not provided in a position overlapping with the light-receiving element **110**. The light shielding layer **158** is provided to cover the surface of the insulating layer **157** on the substrate **153** side, a side surface of the resin layer **159**, and a surface of the resin layer **159** on the substrate **153** side. The light shielding layer **158** has openings in a position overlapping with the light-receiving element **110** and in positions overlapping with the light-emitting elements **190R**, **190G**, and **190B**. Providing the light shielding layer **158** can control the range where the light-receiving element **110** detects light. Furthermore, with the light shielding layer **158**, light can be inhibited from directly entering the light-receiving element **110** from the light-emitting elements **190R**, **190G**, and **190B** without through an object. Hence, a sensor with less noise and high sensitivity can be obtained. Providing the resin layer **159** allows the distance from the light shielding layer **158** to the light-emitting element of each color to be shorter than the distance from the light shielding layer **158** to the light-receiving element **110**. Accordingly, viewing angle dependence of display can be inhibited while noise of the sensor is reduced. Thus, both the display quality and imaging quality can be increased.

(346) As illustrated in FIG. **14**, the partition **216** has an opening between the light-receiving element **110** and the light-emitting element **190R**. A light shielding layer **219a** is provided to fill the opening. The light shielding layer **219a** is positioned between the light-receiving element **110** and the light-emitting element **190R**. The light shielding layer **219a** absorbs light emitted from the light-emitting element **190R**. This can inhibit stray light from entering the light-receiving element **110**.

(347) A spacer **219b** is provided over the partition **216** and positioned between the light-emitting element **190G** and the light-emitting element **190B**. A top surface of the spacer **219b** is preferably closer to the light shielding layer **158** than a top surface of the light shielding layer **219a** is. For example, the sum of the height (thickness) of the partition **216** and the height (thickness) of the spacer **219b** is preferably larger than the height (thickness) of the light shielding layer **219a**. Thus, filling with the adhesive layer **142** can be facilitated. As illustrated in FIG. **15A**, the light shielding layer **158** may be in contact with the common electrode **115** (or the protective layer) in a portion where the spacer **219b** and the light shielding layer **158** overlap with each other.

(348) The connection portion **244** is provided in a region of the substrate **153** that does not overlap with the substrate **154**. In the connection portion **244**, the wiring **165** is electrically connected to the FPC **172** through a conductive layer **167**, the conductive layer **166**, and the connection layer **242**. The conductive layer **167** can be obtained by processing the same conductive film as the conductive layer **169**. On the top surface of the connection portion **244**, the conductive layer **166** obtained by processing the same conductive film as the pixel electrode **191** is exposed. Thus, the connection portion **244** and the FPC **172** can be electrically connected to each other through the connection layer **242**.

(349) Each of the transistor **243**, the transistor **248**, the transistor **249**, and the transistor **240** includes the conductive layer **221** functioning as a gate, the insulating layer **211** functioning as a gate insulating layer, a semiconductor layer including a channel formation region **231i** and a pair of low-resistance regions **231n**, the conductive layer **222a** connected to one of the pair of low-resistance regions **231n**, the conductive layer **222b** connected to the other of the pair of low-resistance regions **231n**, an insulating layer **225** functioning as a gate insulating layer, the conductive layer **223** functioning as a gate, and the insulating layer **215** covering the conductive layer **223**. The insulating layer **211** is positioned between the conductive layer **221** and the channel formation region **231i**. The insulating layer **225** is positioned between the conductive layer **223** and the channel formation region **231i**.

(350) The conductive layer **222a** and the conductive layer **222b** are connected to the corresponding low-resistance regions **231n** through openings provided in the insulating layer **215**. One of the conductive layer **222a** and the conductive layer **222b** functions as a source, and the other functions as a drain.

(351) In FIG. **14** and FIG. **15A**, the insulating layer **225** overlaps with the channel formation region **231i** of the semiconductor layer **231** and does not overlap with the low-resistance regions **231n**. The structure illustrated in FIG. **14** and FIG. **15A** can be formed by processing the insulating layer **225** using the conductive layer **223** as a mask, for example. In FIG. **14** and FIG. **15A**, the insulating layer **215** is provided to cover the insulating layer **225** and the conductive layer **223**, and the conductive layer **222a** and the conductive layer **222b** are connected to the low-resistance regions **231n** through the openings in the insulating layer **215**. Furthermore, an insulating layer that covers the transistor may be provided over the conductive layer **222a** and the conductive layer **222b**.

(352) Meanwhile, a transistor **252** illustrated in FIG. **15B** is an example in which the insulating layer **225** covers a top surface and a side surface of the semiconductor layer. The conductive layer **222a** and the conductive layer **222b** are connected to the corresponding low-resistance regions **231n** through openings provided in the insulating layer **225** and the insulating layer **215**.

(353) As described above, in the display device of one embodiment of the present invention, the distances between the two light-emitting elements and the light-receiving element (or the light-emitting and light-receiving element) differ from each other, and the distances from the two light-emitting elements to the opening of the light shielding layer overlapping with the light-receiving element (or the light-emitting and light-receiving element) differ from each other. With this structure, the light-receiving element or the light-emitting and light-receiving element can receive light coming from one of the two light-emitting elements more than light coming from the other. Accordingly, much light coming from the light-emitting element used as a light source can be made to enter the light-receiving element or the light-emitting and light-receiving element in the display device of one embodiment of the present invention, for example.

Example of Pixel Circuit

(354) The display device of one embodiment of the present invention includes, in the display portion, first pixel circuits each including a light-receiving element and second pixel circuits each including a light-emitting element. The first pixel circuits and the second pixel circuits are each arranged in a matrix.

(355) FIG. **16A** illustrates an example of the first pixel circuit including a light-receiving element, and FIG. **16B** illustrates an example of the second pixel circuit including a light-emitting element.

(356) A pixel circuit **PIX1** illustrated in FIG. **16A** includes a light-receiving element **PD**, a transistor **M1**, a transistor **M2**, a transistor **M3**, a transistor **M4**, and a capacitor **C1**. Here, an example in which a photodiode is used as the light-receiving element **PD** is illustrated.

(357) A cathode of the light-receiving element **PD** is electrically connected to a wiring **V1**, and an anode thereof is electrically connected to one of a source and a drain of the transistor **M1**. A gate of the transistor **M1** is electrically connected to a wiring **TX**, and the other of the source and the drain is electrically connected to one electrode of the capacitor **C1**, one of a source and a drain of the transistor **M2**, and a gate of the transistor **M3**. A gate of the transistor **M2** is electrically connected to a wiring **RES**, and the other of the source and the drain thereof is electrically connected to a wiring **V2**. One of a source and a drain of the transistor **M3** is electrically connected to a wiring **V3**, and the other of the source and the drain thereof is electrically connected to one of a source and a drain of the transistor **M4**. A gate of the transistor **M4** is electrically connected to a wiring **SE**, and the other of the source and the drain thereof is electrically connected to a wiring **OUT1**.

(358) A constant potential is supplied to the wiring **V1**, the wiring **V2**, and the wiring **V3**. When the light-receiving element **PD** is driven with a reverse bias, a potential lower than the potential of the wiring **V1** is supplied to the wiring **V2**. The transistor **M2** is controlled by a signal supplied to the wiring **RES** and has a function of resetting the potential of a node connected to the gate of the

transistor M3 to a potential supplied to the wiring V2. The transistor M1 is controlled by a signal supplied to the wiring TX and has a function of controlling the timing at which the potential of the node changes, in accordance with a current flowing through the light-receiving element PD. The transistor M3 functions as an amplifier transistor for performing output in response to the potential of the node. The transistor M4 is controlled by a signal supplied to the wiring SE and functions as a selection transistor for reading an output corresponding to the potential of the node by an external circuit connected to the wiring OUT1.

(359) A pixel circuit PIX2 illustrated in FIG. 16B includes a light-emitting element EL, a transistor M5, a transistor M6, a transistor M7, and a capacitor C2. Here, an example in which a light-emitting diode is used as the light-emitting element EL is illustrated. In particular, an organic EL element is preferably used as the light-emitting element EL.

(360) A gate of the transistor M5 is electrically connected to a wiring VG, one of a source and a drain of the transistor M5 is electrically connected to a wiring VS, and the other of the source and the drain of the transistor M5 is electrically connected to one electrode of the capacitor C2 and a gate of the transistor M6. One of a source and a drain of the transistor M6 is electrically connected to a wiring V4, and the other thereof is electrically connected to an anode of the light-emitting element EL and one of a source and a drain of the transistor M7. A gate of the transistor M7 is electrically connected to a wiring M5, and the other of the source and the drain thereof is electrically connected to a wiring OUT2. A cathode of the light-emitting element EL is electrically connected to a wiring V5.

(361) A constant potential is supplied to the wiring V4 and the wiring V5. In the light-emitting element EL, the anode side can have a high potential and the cathode side can have a lower potential than the anode side. The transistor M5 is controlled by a signal supplied to the wiring VG and functions as a selection transistor for controlling a selection state of the pixel circuit PIX2. The transistor M6 functions as a driving transistor that controls a current flowing through the light-emitting element EL, in accordance with a potential supplied to the gate. When the transistor M5 is in an on state, a potential supplied to the wiring VS is supplied to the gate of the transistor M6, and the emission luminance of the light-emitting element EL can be controlled in accordance with the potential. The transistor M7 is controlled by a signal supplied to the wiring MS and has a function of outputting a potential between the transistor M6 and the light-emitting element EL to the outside through the wiring OUT2.

(362) The wiring V1, to which the cathode of the light-receiving element PD is electrically connected, and the wiring V5, to which the cathode of the light-emitting element EL is electrically connected, can be provided in the same layer and have the same level of potential.

(363) In the display device of one embodiment of the present invention, it is preferable to use transistors including a metal oxide (also referred to as an oxide semiconductor) in their semiconductor layers where channels are formed (such transistors are also referred to as OS transistors below) as all the transistors included in the first pixel circuit PIX1 and the second pixel circuit PIX2. An OS transistor has an extremely low off-state current and enables charge stored in a capacitor that is series-connected to the transistor to be retained for along time. Furthermore, power consumption of the display device can be reduced with an OS transistor.

(364) Alternatively, in the display device of one embodiment of the present invention, it is preferable to use transistors including silicon in their semiconductor layers where channels are formed (such transistors are also referred to as Si transistors below) as all the transistors included in the pixel circuit PIX1 and the pixel circuit PIX2. As silicon, single crystal silicon, polycrystalline silicon, amorphous silicon, and the like can be given. It is particularly preferable to use transistors including low-temperature polysilicon (LTPS) (hereinafter also referred to as LTPS transistors) in their semiconductor layers. An LTPS transistor has high field-effect mobility and can operate at high speed.

(365) With the use of Si transistors such as LTPS transistors, a variety of circuits formed using a

CMOS circuit and a display portion can be easily formed on the same substrate. Thus, external circuits mounted on the display device can be simplified, and costs of parts and mounting costs can be reduced.

(366) In the display device of one embodiment of the present invention, two kinds of transistors are preferably used in the pixel circuit PIX1. Specifically, the pixel circuit PIX1 preferably includes an OS transistor and an LTPS transistor. Changing the material of the semiconductor layer depending on the desired function of the transistor can increase the quality of the pixel circuit PIX1 and the accuracy of sensing and image capturing. In that case, in the pixel circuit PIX2, one or both of an OS transistor and an LTPS transistor may be used.

(367) Furthermore, even when two kinds of transistors (e.g., OS transistors and LTPS transistors) are used in the pixels, using the LTPS transistors facilitates formation of a variety of circuits formed using a CMOS circuit and a display portion on the same substrate. Thus, external circuits mounted on the display device can be simplified, and costs of parts and mounting costs can be reduced.

(368) A transistor using a metal oxide having a wider band gap and a lower carrier density than silicon can achieve an extremely low off-state current. Thus, such a low off-state current enables retention of charges accumulated in a capacitor that is connected in series with the transistor for a long time. Therefore, it is particularly preferable to use OS transistors as the transistor M1, the transistor M2, and the transistor M5 each of which is connected in series with the capacitor C1 or the capacitor C2.

(369) A Si transistor is preferably used as the transistor M3. This enables high-speed reading operation of imaging data.

(370) Note that the display device which includes, in the display portion, the first pixel circuits each including a light-receiving element and the second pixel circuits each including a light-emitting element can be driven in any of an image display mode, an image capture mode, and a mode of simultaneously performing image display and image capturing. In the image display mode, a full-color image can be displayed using the light-emitting element, for example. In the image capture mode, an image for image capturing (e.g., a green monochromatic image or a blue monochromatic image) can be displayed using the light-emitting element and image capturing can be performed using the light-receiving element, for example. Fingerprint authentication can be performed in the image capture mode, for example. In the mode of simultaneously performing image display and image capturing, an image for image capturing can be displayed using the light-emitting element and image capturing can be performed using the light-receiving element in some pixels, and a full-color image can be displayed using the light-emitting element in the other pixels, for example.

(371) Although the transistors are illustrated as n-channel transistors in FIG. 16A and FIG. 16B, p-channel transistors can alternatively be used. The transistors are not limited to single-gate transistors and may further include a back gate.

(372) One or more layers including one or both of the transistor and the capacitor are preferably provided to overlap with the light-receiving element PD or the light-emitting element EL. Thus, the effective area of each pixel circuit can be reduced, and a high-definition display portion can be achieved.

(373) This embodiment can be combined with the other embodiments as appropriate.

Embodiment 3

(374) In this embodiment, a metal oxide (also referred to as an oxide semiconductor) that can be used in the OS transistor described in the above embodiment is described.

(375) The metal oxide preferably contains at least indium or zinc. In particular, indium and zinc are preferably contained. In addition, aluminum, gallium, yttrium, tin, or the like is preferably contained. Furthermore, one or more kinds selected from boron, silicon, titanium, iron, nickel, germanium, zirconium, molybdenum, lanthanum, cerium, neodymium, hafnium, tantalum,

tungsten, magnesium, cobalt, and the like may be contained.

(376) The metal oxide can be formed by a sputtering method, a chemical vapor deposition (CVD) method such as a metal organic chemical vapor deposition (MOCVD) method, an atomic layer deposition (ALD) method, or the like.

(377) <Classification of Crystal Structure>

(378) Amorphous (including a completely amorphous structure), CAAC (c-axis-aligned crystalline), nc (nanocrystalline), CAC (cloud-aligned composite), single-crystal, and polycrystalline (poly crystal) structures can be given as examples of a crystal structure of an oxide semiconductor.

(379) Note that a crystal structure of a film or a substrate can be evaluated with an X-ray diffraction (XRD) spectrum. For example, evaluation is possible using an XRD spectrum which is obtained by GIXD (Grazing-Incidence XRD) measurement. Note that a GIXD method is also referred to as a thin film method or a Seemann-Bohlin method.

(380) For example, the XRD spectrum of the quartz glass substrate shows a peak with a substantially bilaterally symmetrical shape. On the other hand, the peak of the XRD spectrum of the IGZO film having a crystal structure has a bilaterally asymmetrical shape. The asymmetrical peak of the XRD spectrum clearly shows the existence of crystal in the film or the substrate. In other words, the crystal structure of the film or the substrate cannot be regarded as “amorphous” unless it has a bilaterally symmetrical peak in the XRD spectrum.

(381) A crystal structure of a film or a substrate can also be evaluated with a diffraction pattern obtained by a nanobeam electron diffraction (NBED) method (such a pattern is also referred to as a nanobeam electron diffraction pattern). For example, a halo pattern is observed in the diffraction pattern of the quartz glass substrate, which indicates that the quartz glass substrate is in an amorphous state. Furthermore, not a halo pattern but a spot-like pattern is observed in the diffraction pattern of the IGZO film deposited at room temperature. Thus, it is suggested that the IGZO film deposited at room temperature is in an intermediate state, which is neither a crystal state nor an amorphous state, and it cannot be concluded that the IGZO film is in an amorphous state.

(382) <<Structure of Oxide Semiconductor>>

(383) Oxide semiconductors might be classified in a manner different from the above-described one when classified in terms of the structure. Oxide semiconductors are classified into a single crystal oxide semiconductor and a non-single-crystal oxide semiconductor, for example. Examples of the non-single-crystal oxide semiconductor include the above-described CAAC-OS and nc-OS. Other examples of the non-single-crystal oxide semiconductor include a polycrystalline oxide semiconductor, an amorphous-like oxide semiconductor (a-like OS), and an amorphous oxide semiconductor.

(384) Here, the above-described CAAC-OS, nc-OS, and a-like OS are described in detail.

(385) [CAAC-OS]

(386) The CAAC-OS is an oxide semiconductor that has a plurality of crystal regions each of which has c-axis alignment in a particular direction. Note that the particular direction refers to the film thickness direction of a CAAC-OS film, the normal direction of the surface where the CAAC-OS film is formed, or the normal direction of the surface of the CAAC-OS film. The crystal region refers to a region having a periodic atomic arrangement. When an atomic arrangement is regarded as a lattice arrangement, the crystal region also refers to a region with a uniform lattice arrangement. The CAAC-OS has a region where a plurality of crystal regions are connected in the a-b plane direction, and the region has distortion in some cases. Note that distortion refers to a portion where the direction of a lattice arrangement changes between a region with a uniform lattice arrangement and another region with a uniform lattice arrangement in a region where a plurality of crystal regions are connected. That is, the CAAC-OS is an oxide semiconductor having c-axis alignment and having no clear alignment in the a-b plane direction.

(387) Note that each of the plurality of crystal regions is formed of one or more fine crystals

(crystals each of which has a maximum diameter of less than 10 nm). In the case where the crystal region is formed of one fine crystal, the maximum diameter of the crystal region is less than 10 nm. In the case where the crystal region is formed of a large number of fine crystals, the size of the crystal region may be approximately several tens of nanometers.

(388) In the case of an In-M-Zn oxide (the element M is one or more kinds selected from aluminum, gallium, yttrium, tin, titanium, and the like), the CAAC-OS tends to have a layered crystal structure (also referred to as a stacked-layer structure) in which a layer containing indium (In) and oxygen (hereinafter, an In layer) and a layer containing the element M, zinc (Zn), and oxygen (hereinafter, an (M,Zn) layer) are stacked. Indium and the element M can be replaced with each other. Therefore, indium may be contained in the (M,Zn) layer. In addition, the element M may be contained in the In layer. Note that Zn may be contained in the In layer. Such a layered structure is observed as a lattice image in a high-resolution transmission electron microscope (TEM) image, for example.

(389) When the CAAC-OS film is subjected to structural analysis by Out-of-plane XRD measurement with an XRD apparatus using $\theta/2\theta$ scanning, for example, a peak indicating c-axis alignment is detected at 2θ of 31° or around 31° . Note that the position of the peak indicating c-axis alignment (the value of 2θ) may change depending on the kind, composition, or the like of the metal element contained in the CAAC-OS.

(390) For example, a plurality of bright spots are observed in the electron diffraction pattern of the CAAC-OS film. Note that one spot and another spot are observed point-symmetrically with a spot of the incident electron beam passing through a sample (also referred to as a direct spot) as the symmetric center.

(391) When the crystal region is observed from the particular direction, a lattice arrangement in the crystal region is basically a hexagonal lattice arrangement; however, a unit lattice is not always a regular hexagon and is a non-regular hexagon in some cases. A pentagonal lattice arrangement, a heptagonal lattice arrangement, and the like are included in the distortion in some cases. Note that a clear grain boundary cannot be observed even in the vicinity of the distortion in the CAAC-OS. That is, formation of a crystal grain boundary is inhibited by the distortion of lattice arrangement. This is probably because the CAAC-OS can tolerate distortion owing to a low density of arrangement of oxygen atoms in the a-b plane direction, an interatomic bond distance changed by substitution of a metal atom, and the like.

(392) Note that a crystal structure in which a clear grain boundary is observed is what is called polycrystal. It is highly probable that the grain boundary becomes a recombination center and captures carriers and thus decreases the on-state current and field-effect mobility of a transistor, for example. Thus, the CAAC-OS in which no clear grain boundary is observed is one of crystalline oxides having a crystal structure suitable for a semiconductor layer of a transistor. Note that Zn is preferably contained to form the CAAC-OS. For example, an In—Zn oxide and an In—Ga—Zn oxide are suitable because they can inhibit generation of a grain boundary as compared with an In oxide.

(393) The CAAC-OS is an oxide semiconductor with high crystallinity in which no clear grain boundary is observed. Thus, in the CAAC-OS, a reduction in electron mobility due to the grain boundary is unlikely to occur. Moreover, since the crystallinity of an oxide semiconductor might be decreased by entry of impurities, formation of defects, or the like, the CAAC-OS can be regarded as an oxide semiconductor that has small amounts of impurities and defects (e.g., oxygen vacancies). Thus, an oxide semiconductor including the CAAC-OS is physically stable. Therefore, the oxide semiconductor including the CAAC-OS is resistant to heat and has high reliability. In addition, the CAAC-OS is stable with respect to high temperature in the manufacturing process (what is called thermal budget). Accordingly, the use of the CAAC-OS for the OS transistor can extend the degree of freedom of the manufacturing process.

(394) [nc-OS]

(395) In the nc-OS, a microscopic region (e.g., a region with a size greater than or equal to 1 nm and less than or equal to 10 nm, in particular, a region with a size greater than or equal to 1 nm and less than or equal to 3 nm) has a periodic atomic arrangement. In other words, the nc-OS includes a fine crystal. Note that the size of the fine crystal is, for example, greater than or equal to 1 nm and less than or equal to 10 nm, particularly greater than or equal to 1 nm and less than or equal to 3 nm; thus, the fine crystal is also referred to as a nanocrystal. Furthermore, there is no regularity of crystal orientation between different nanocrystals in the nc-OS. Thus, the orientation in the whole film is not observed. Accordingly, the nc-OS cannot be distinguished from an a-like OS or an amorphous oxide semiconductor by some analysis methods. For example, when an nc-OS film is subjected to structural analysis by Out-of-plane XRD measurement with an XRD apparatus using $\theta/2\theta$ scanning, a peak indicating crystallinity is not detected. Furthermore, a diffraction pattern like a halo pattern is observed when the nc-OS film is subjected to electron diffraction (also referred to as selected-area electron diffraction) using an electron beam with a probe diameter larger than the diameter of a nanocrystal (e.g., larger than or equal to 50 nm). Meanwhile, in some cases, a plurality of spots in a ring-like region with a direct spot as the center are observed in the obtained electron diffraction pattern when the nc-OS film is subjected to electron diffraction (also referred to as nanobeam electron diffraction) using an electron beam with a probe diameter nearly equal to or smaller than the diameter of a nanocrystal (e.g., 1 nm or larger and 30 nm or smaller).

(396) [a-like OS]

(397) The a-like OS is an oxide semiconductor having a structure between those of the nc-OS and the amorphous oxide semiconductor. The a-like OS contains void or a low-density region. That is, the a-like OS has low crystallinity as compared with the nc-OS and the CAAC-OS. Moreover, the a-like OS has higher hydrogen concentration in the film than the nc-OS and the CAAC-OS.

(398) <<Structure of Oxide Semiconductor>>

(399) Next, the above-described CAC-OS is described in detail. Note that the CAC-OS relates to the material composition.

(400) [CAC-OS]

(401) The CAC-OS refers to one composition of a material in which elements constituting a metal oxide are unevenly distributed with a size greater than or equal to 0.5 nm and less than or equal to 10 nm, preferably greater than or equal to 1 nm and less than or equal to 3 nm, or a similar size, for example. Note that a state in which one or more metal elements are unevenly distributed and regions including the metal element(s) are mixed with a size greater than or equal to 0.5 nm and less than or equal to 10 nm, preferably greater than or equal to 1 nm and less than or equal to 3 nm, or a similar size in a metal oxide is hereinafter referred to as a mosaic pattern or a patch-like pattern.

(402) In addition, the CAC-OS has a composition in which materials are separated into a first region and a second region to form a mosaic pattern, and the first regions are distributed in the film (this composition is hereinafter also referred to as a cloud-like composition). That is, the CAC-OS is a composite metal oxide having a composition in which the first regions and the second regions are mixed.

(403) Note that the atomic ratios of In, Ga, and Zn to the metal elements contained in the CAC-OS in an In—Ga—Zn oxide are denoted by [In], [Ga], and [Zn], respectively. For example, the first region in the CAC-OS in the In—Ga—Zn oxide has [In] higher than that in the composition of the CAC-OS film. Moreover, the second region has [Ga] higher than that in the composition of the CAC-OS film. For example, the first region has higher [In] and lower [Ga] than the second region. Moreover, the second region has higher [Ga] and lower [In] than the first region.

(404) Specifically, the first region contains indium oxide, indium zinc oxide, or the like as its main component. The second region contains gallium oxide, gallium zinc oxide, or the like as its main component. That is, the first region can be referred to as a region containing In as its main component. The second region can be referred to as a region containing Ga as its main component.

(405) Note that a clear boundary between the first region and the second region cannot be observed in some cases.

(406) In a material composition of a CAC-OS in an In—Ga—Zn oxide that contains In, Ga, Zn, and O, regions containing Ga as a main component are observed in part of the CAC-OS and regions containing In as a main component are observed in part thereof. These regions are randomly dispersed to form a mosaic pattern. Thus, it is suggested that the CAC-OS has a structure in which metal elements are unevenly distributed.

(407) The CAC-OS can be formed by a sputtering method under a condition where a substrate is not heated, for example. Moreover, in the case of forming the CAC-OS by a sputtering method, any one or more selected from an inert gas (typically, argon), an oxygen gas, and a nitrogen gas are used as a deposition gas. The flow rate of the oxygen gas to the total flow rate of the deposition gas in deposition is preferably as low as possible, for example, the flow rate of the oxygen gas to the total flow rate of the deposition gas in deposition is higher than or equal to 0% and lower than 30%, preferably higher than or equal to 0% and lower than or equal to 10%.

(408) For example, energy dispersive X-ray spectroscopy (EDX) is used to obtain EDX mapping, and according to the EDX mapping, the CAC-OS in the In—Ga—Zn oxide has a structure in which the region containing In as its main component (the first region) and the region containing Ga as its main component (the second region) are unevenly distributed and mixed.

(409) Here, the first region has a higher conductivity than the second region. In other words, when carriers flow through the first region, the conductivity of a metal oxide is exhibited. Accordingly, when the first regions are distributed in a metal oxide as a cloud, high field-effect mobility (μ) can be achieved.

(410) The second region has a higher insulating property than the first region. In other words, when the second regions are distributed in a metal oxide, leakage current can be inhibited.

(411) Thus, in the case where a CAC-OS is used for a transistor, by the complementary function of the conducting function due to the first region and the insulating function due to the second region, the CAC-OS can have a switching function (On/Off function). A CAC-OS has a conducting function in part of the material and has an insulating function in another part of the material; as a whole, the CAC-OS has a function of a semiconductor. Separation of the conducting function and the insulating function can maximize each function. Accordingly, when the CAC-OS is used for a transistor, high on-state current ($I_{\text{sub.on}}$), high field-effect mobility (μ), and excellent switching operation can be achieved.

(412) A transistor using a CAC-OS has high reliability. Thus, the CAC-OS is most suitable for a variety of semiconductor devices such as display devices.

(413) An oxide semiconductor has various structures with different properties. Two or more kinds among the amorphous oxide semiconductor, the polycrystalline oxide semiconductor, the a-like OS, the CAC-OS, the nc-OS, and the CAAC-OS may be included in an oxide semiconductor of one embodiment of the present invention.

(414) <Transistor Including Oxide Semiconductor>

(415) Next, the case where the above oxide semiconductor is used for a transistor is described.

(416) When the above oxide semiconductor is used for a transistor, a transistor with high field-effect mobility can be achieved. In addition, a transistor having high reliability can be achieved.

(417) An oxide semiconductor having a low carrier concentration is preferably used in a transistor. For example, the carrier concentration of an oxide semiconductor is lower than or equal to $1 \times 10^{17} \text{ cm}^{-3}$, preferably lower than or equal to $1 \times 10^{15} \text{ cm}^{-3}$, further preferably lower than or equal to $1 \times 10^{13} \text{ cm}^{-3}$, still further preferably lower than or equal to $1 \times 10^{11} \text{ cm}^{-3}$, yet further preferably lower than $1 \times 10^{10} \text{ cm}^{-3}$, and higher than or equal to $1 \times 10^{-9} \text{ cm}^{-3}$. In order to reduce the carrier concentration of an oxide semiconductor film, the impurity concentration in the oxide semiconductor film is reduced so that the density of defect states can be reduced. In this specification and the like, a state with a low

impurity concentration and a low density of defect states is referred to as a highly purified intrinsic or substantially highly purified intrinsic state. Note that an oxide semiconductor having a low carrier concentration may be referred to as a highly purified intrinsic or substantially highly purified intrinsic oxide semiconductor.

(418) A highly purified intrinsic or substantially highly purified intrinsic oxide semiconductor film has a low density of defect states and thus has a low density of trap states in some cases.

(419) Charge trapped by the trap states in the oxide semiconductor takes a long time to disappear and might behave like fixed charge. Thus, a transistor whose channel formation region is formed in an oxide semiconductor with a high density of trap states has unstable electrical characteristics in some cases.

(420) Accordingly, in order to obtain stable electrical characteristics of a transistor, reducing the impurity concentration in an oxide semiconductor is effective. In order to reduce the impurity concentration in the oxide semiconductor, it is preferable that the impurity concentration in an adjacent film be also reduced. Examples of impurities include hydrogen, nitrogen, an alkali metal, an alkaline earth metal, iron, nickel, and silicon.

(421) <Impurity>

(422) Here, the influence of each impurity in the oxide semiconductor is described.

(423) When silicon or carbon, which is one of Group 14 elements, is contained in the oxide semiconductor, defect states are formed in the oxide semiconductor. Thus, the concentration of silicon or carbon in the oxide semiconductor and the concentration of silicon or carbon in the vicinity of an interface with the oxide semiconductor (the concentration obtained by secondary ion mass spectrometry (SIMS)) are each set lower than or equal to 2×10^{18} atoms/cm³, preferably lower than or equal to 2×10^{17} atoms/cm³.

(424) When the oxide semiconductor contains an alkali metal or an alkaline earth metal, defect states are formed and carriers are generated in some cases. Thus, a transistor using an oxide semiconductor that contains an alkali metal or an alkaline earth metal is likely to have normally-on characteristics. Thus, the concentration of an alkali metal or an alkaline earth metal in the oxide semiconductor, which is obtained by SIMS, is lower than or equal to 1×10^{18} atoms/cm³, preferably lower than or equal to 2×10^{16} atoms/cm³.

(425) Furthermore, when the oxide semiconductor contains nitrogen, the oxide semiconductor easily becomes n-type by generation of electrons serving as carriers and an increase in carrier concentration. As a result, a transistor using an oxide semiconductor containing nitrogen as a semiconductor is likely to have normally-on characteristics. When nitrogen is contained in the oxide semiconductor, a trap state is sometimes formed. This might make the electrical characteristics of the transistor unstable. Therefore, the concentration of nitrogen in the oxide semiconductor, which is obtained by SIMS, is set lower than 5×10^{19} atoms/cm³, preferably lower than or equal to 5×10^{18} atoms/cm³, further preferably lower than or equal to 1×10^{18} atoms/cm³, still further preferably lower than or equal to 5×10^{17} atoms/cm³.

(426) Hydrogen contained in the oxide semiconductor reacts with oxygen bonded to a metal atom to be water, and thus forms an oxygen vacancy in some cases. Entry of hydrogen into the oxygen vacancy generates an electron serving as a carrier in some cases. Furthermore, bonding of part of hydrogen to oxygen bonded to a metal atom causes generation of an electron serving as a carrier in some cases. Thus, a transistor using an oxide semiconductor containing hydrogen is likely to have normally-on characteristics. Accordingly, hydrogen in the oxide semiconductor is preferably reduced as much as possible. Specifically, the hydrogen concentration in the oxide semiconductor, which is obtained by SIMS, is set lower than 1×10^{20} atoms/cm³, preferably lower than 1×10^{19} atoms/cm³, further preferably lower than 5×10^{18} atoms/cm³, still further preferably lower than 1×10^{18} atoms/cm³.

(427) When an oxide semiconductor with sufficiently reduced impurities is used for the channel

formation region of the transistor, stable electrical characteristics can be given.

(428) This embodiment can be combined with the other embodiments as appropriate.

Embodiment 4

(429) In this embodiment, electronic devices of embodiments of the present invention are described with reference to FIG. 17 to FIG. 19.

(430) An electronic device of one embodiment of the present invention can perform image capturing or detect touch operation (touch or approach) in a display portion. Thus, the electronic device can have improved functionality and convenience, for example.

(431) Examples of the electronic devices of one embodiment of the present invention include a digital camera, a digital video camera, a digital photo frame, a mobile phone, a portable game console, a portable information terminal, and an audio reproducing device, in addition to electronic devices with a relatively large screen, such as a television device, a desktop or laptop personal computer, a monitor of a computer or the like, digital signage, and a large game machine such as a pachinko machine.

(432) The electronic device of one embodiment of the present invention may include a sensor (a sensor having a function of measuring force, displacement, position, speed, acceleration, angular velocity, rotational frequency, distance, light, liquid, magnetism, temperature, a chemical substance, sound, time, hardness, electric field, current, voltage, electric power, radiation, flow rate, humidity, gradient, oscillation, a smell, or infrared rays).

(433) The electronic device of one embodiment of the present invention can have a variety of functions. For example, the electronic device can have a function of displaying a variety of data (a still image, a moving image, a text image, and the like) on the display portion, a touch panel function, a function of displaying a calendar, date, time, and the like, a function of executing a variety of software (programs), a wireless communication function, and a function of reading out a program or data stored in a recording medium.

(434) An electronic device **6500** illustrated in FIG. 17A is a portable information terminal that can be used as a smartphone.

(435) The electronic device **6500** includes a housing **6501**, a display portion **6502**, a power button **6503**, buttons **6504**, a speaker **6505**, a microphone **6506**, a camera **6507**, a light source **6508**, and the like. The display portion **6502** has a touch panel function.

(436) The display device described in Embodiment 2 can be used in the display portion **6502**.

(437) FIG. 17B is a schematic cross-sectional view including an end portion of the housing **6501** on the microphone **6506** side.

(438) A protection member **6510** having a light-transmitting property is provided on a display surface side of the housing **6501**, and a display panel **6511**, an optical member **6512**, a touch sensor panel **6513**, a printed circuit board **6517**, a battery **6518**, and the like are provided in a space surrounded by the housing **6501** and the protection member **6510**.

(439) The display panel **6511**, the optical member **6512**, and the touch sensor panel **6513** are fixed to the protection member **6510** with an adhesive layer (not illustrated).

(440) Part of the display panel **6511** is folded back in a region outside the display portion **6502**, and an FPC **6515** is connected to the part that is folded back. An IC **6516** is mounted on the FPC **6515**. The FPC **6515** is connected to a terminal provided on the printed circuit board **6517**.

(441) A flexible display of one embodiment of the present invention can be used as the display panel **6511**. Thus, an extremely lightweight electronic device can be provided. Since the display panel **6511** is extremely thin, the battery **6518** with high capacity can be mounted with the thickness of the electronic device controlled. An electronic device with a narrow frame can be obtained when part of the display panel **6511** is folded back so that the portion connected to the FPC **6515** is positioned on the rear side of a pixel portion.

(442) Using the display device described in Embodiment 2 as the display panel **6511** allows image capturing on the display portion **6502**. For example, an image of a fingerprint is captured by the

display panel **6511**; thus, fingerprint authentication can be performed.

(443) By further including the touch sensor panel **6513**, the display portion **6502** can have a touch panel function. A variety of types such as a capacitive type, a resistive type, a surface acoustic wave type, an infrared type, an optical type, and a pressure-sensitive type can be used for the touch sensor panel **6513**. Alternatively, the display panel **6511** may function as a touch sensor; in such a case, the touch sensor panel **6513** is not necessarily provided.

(444) FIG. **18A** illustrates an example of a television device. In a television device **7100**, a display portion **7000** is incorporated in a housing **7101**. Here, a structure in which the housing **7101** is supported by a stand **7103** is illustrated.

(445) The display device described in Embodiment 2 can be used in the display portion **7000**.

(446) Operation of the television device **7100** illustrated in FIG. **18A** can be performed with an operation switch provided in the housing **7101** or a separate remote controller **7111**. Alternatively, the display portion **7000** may include a touch sensor, and the television device **7100** may be operated by touch on the display portion **7000** with a finger or the like. The remote controller **7111** may be provided with a display portion for displaying data output from the remote controller **7111**. With operation keys or a touch panel provided in the remote controller **7111**, channels and volume can be operated and videos displayed on the display portion **7000** can be operated.

(447) Note that the television device **7100** has a structure in which a receiver, a modem, and the like are provided. A general television broadcast can be received with the receiver. When the television device is connected to a communication network with or without wires via the modem, one-way (from a transmitter to a receiver) or two-way (between a transmitter and a receiver or between receivers, for example) data communication can be performed.

(448) FIG. **18B** illustrates an example of a laptop personal computer. A laptop personal computer **7200** includes a housing **7211**, a keyboard **7212**, a pointing device **7213**, an external connection port **7214**, and the like. In the housing **7211**, the display portion **7000** is incorporated.

(449) The display device described in Embodiment 2 can be used in the display portion **7000**.

(450) FIG. **18C** and FIG. **18D** illustrate examples of digital signage.

(451) Digital signage **7300** illustrated in FIG. **18C** includes a housing **7301**, the display portion **7000**, a speaker **7303**, and the like. Furthermore, the digital signage can include an LED lamp, operation keys (including a power switch or an operation switch), a connection terminal, a variety of sensors, a microphone, and the like.

(452) FIG. **18D** is digital signage **7400** attached to a cylindrical pillar **7401**. The digital signage **7400** includes the display portion **7000** provided along a curved surface of the pillar **7401**.

(453) The display device described in Embodiment 2 can be used for the display portion **7000** in FIG. **18C** and FIG. **18D**.

(454) A larger area of the display portion **7000** can increase the amount of data that can be provided at a time. The larger display portion **7000** attracts more attention, so that the effectiveness of the advertisement can be increased, for example.

(455) The use of a touch panel in the display portion **7000** is preferable because in addition to display of a still image or a moving image on the display portion **7000**, intuitive operation by a user is possible. Moreover, for an application for providing information such as route information or traffic information, usability can be enhanced by intuitive operation.

(456) As illustrated in FIG. **18C** and FIG. **18D**, it is preferable that the digital signage **7300** or the digital signage **7400** can work with an information terminal **7311** or an information terminal **7411** such as a smartphone a user has through wireless communication. For example, information of an advertisement displayed on the display portion **7000** can be displayed on a screen of the information terminal **7311** or the information terminal **7411**. By operation of the information terminal **7311** or the information terminal **7411**, display on the display portion **7000** can be switched.

(457) It is possible to make the digital signage **7300** or the digital signage **7400** execute a game

with the use of the screen of the information terminal **7311** or the information terminal **7411** as an operation means (controller). Thus, an unspecified number of users can join in and enjoy the game concurrently.

(458) Electronic devices illustrated in FIG. **19A** to FIG. **19F** include a housing **9000**, a display portion **9001**, a speaker **9003**, an operation key **9005** (including a power switch or an operation switch), a connection terminal **9006**, a sensor **9007** (a sensor having a function of measuring force, displacement, position, speed, acceleration, angular velocity, rotational frequency, distance, light, liquid, magnetism, temperature, a chemical substance, sound, time, hardness, electric field, current, voltage, electric power, radiation, flow rate, humidity, gradient, oscillation, a smell, or infrared rays), a microphone **9008**, and the like.

(459) The electronic devices illustrated in FIG. **19A** to FIG. **19F** have a variety of functions. For example, the electronic devices can have a function of displaying a variety of data (a still image, a moving image, a text image, and the like) on the display portion, a touch panel function, a function of displaying a calendar, date, time, and the like, a function of controlling processing with the use of a variety of software (programs), a wireless communication function, and a function of reading out and processing a program or data stored in a recording medium. Note that the functions of the electronic devices are not limited thereto, and the electronic devices can have a variety of functions. The electronic devices may include a plurality of display portions. The electronic devices may each include a camera or the like and have a function of taking a still image or a moving image and storing the taken image in a recording medium (an external recording medium or a recording medium incorporated in the camera), a function of displaying the taken image on the display portion, or the like.

(460) The details of the electronic devices illustrated in FIG. **19A** to FIG. **19F** are described below.

(461) FIG. **19A** is a perspective view illustrating a portable information terminal **9101**. For example, the portable information terminal **9101** can be used as a smartphone. Note that the portable information terminal **9101** may be provided with the speaker **9003**, the connection terminal **9006**, the sensor **9007**, or the like. The portable information terminal **9101** can display characters and image information on its plurality of surfaces. FIG. **19A** illustrates an example where three icons **9050** are displayed. Information **9051** indicated by dashed rectangles can be displayed on another surface of the display portion **9001**. Examples of the information **9051** include notification of reception of an e-mail, SNS, or an incoming call, the title and sender of an e-mail, SNS, or the like, the date, the time, remaining battery, and the reception strength of an antenna. Alternatively, the icon **9050** or the like may be displayed in the position where the information **9051** is displayed.

(462) FIG. **19B** is a perspective view illustrating a portable information terminal **9102**. The portable information terminal **9102** has a function of displaying information on three or more surfaces of the display portion **9001**. Here, an example in which information **9052**, information **9053**, and information **9054** are displayed on different surfaces is illustrated. For example, a user can check the information **9053** displayed in a position that can be observed from above the portable information terminal **9102**, with the portable information terminal **9102** put in a breast pocket of his/her clothes. The user can see the display without taking out the portable information terminal **9102** from the pocket and decide whether to answer the call, for example.

(463) FIG. **19C** is a perspective view illustrating a watch-type portable information terminal **9200**. For example, the portable information terminal **9200** can be used as a smartwatch. The display surface of the display portion **9001** is curved and provided, and display can be performed along the curved display surface. Mutual communication between the portable information terminal **9200** and, for example, a headset capable of wireless communication enables hands-free calling. With the connection terminal **9006**, the portable information terminal **9200** can perform mutual data transmission with another information terminal and charging. Note that the charging operation may be performed by wireless power feeding.

(464) FIG. 19D to FIG. 19F are perspective views illustrating a foldable portable information terminal **9201**. FIG. 19D is a perspective view of an opened state of the portable information terminal **9201**, FIG. 19F is a perspective view of a folded state thereof, and FIG. 19E is a perspective view of a state in the middle of change from one of FIG. 19D and FIG. 19F to the other. The portable information terminal **9201** is highly portable in the folded state and is highly browsable in the opened state because of a seamless large display region. The display portion **9001** of the portable information terminal **9201** is supported by three housings **9000** joined by hinges **9055**. For example, the display portion **9001** can be folded with a radius of curvature greater than or equal to 0.1 mm and less than or equal to 150 mm.

(465) This embodiment can be combined with the other embodiments as appropriate.

REFERENCE NUMERALS

(466) **C1**: capacitor, **C2**: capacitor, **L1**: shortest distance, **L2**: shortest distance, **M1**: transistor, **M2**: transistor, **M3**: transistor, **M4**: transistor, **M5**: transistor, **M6**: transistor, **M7**: transistor, **OUT1**: wiring, **OUT2**: wiring, **PIX1**: pixel circuit, **PIX2**: pixel circuit, **V1**: wiring, **V2**: wiring, **V3**: wiring, **V4**: wiring, **V5**: wiring, **10**: device, **10A**: device, **10B**: device, **11**: control portion, **12**: display portion, **13**: memory portion, **21**: detection portion, **21A**: detection portion, **21B**: detection portion, **24**: finger, **25**: first finger, **26**: fingerprint data, **27**: fingerprint data, **27A**: fingerprint data, **27B**: fingerprint data, **28**: second finger, **29**: fingerprint data, **30**: electronic device, **31**: display portion, **35**: image, **40**: electronic device, **40A**: electronic device, **40B**: electronic device, **41**: display portion, **41A**: display portion, **41B**: display portion, **41C**: display portion, **42**: input portion, **43**: input key, **44**: housing, **45**: housing, **46**: hinge portion, **100A**: display device, **100B**: display device, **100C**: display device, **100D**: display device, **100E**: display device, **110**: light-receiving element, **112**: common layer, **114**: common layer, **115**: common electrode, **116**: protective layer, **121**: light emission, **121B**: light, **121G**: light, **121R**: light, **122**: light, **123**: light, **123a**: stray light, **123b**: stray light, **124**: reflected light, **131**: transistor, **132**: transistor, **142**: adhesive layer, **151**: substrate, **152**: substrate, **153**: substrate, **154**: substrate, **155**: adhesive layer, **156**: adhesive layer, **157**: insulating layer, **158**: light shielding layer, **159**: resin layer, **159p**: opening, **162**: display portion, **164**: circuit, **165**: wiring, **166**: conductive layer, **167**: conductive layer, **169**: conductive layer, **172**: FPC, **173**: IC, **182**: buffer layer, **183**: active layer, **184**: buffer layer, **190**: light-emitting element, **190B**: light-emitting element, **190G**: light-emitting element, **190R-PD**: light-emitting and light-receiving element, **190R**: light-emitting element, **191**: pixel electrode, **192**: buffer layer, **192B**: buffer layer, **192G**: buffer layer, **192R**: buffer layer, **193**: light-emitting layer, **193B**: light-emitting layer, **193G**: light-emitting layer, **193R**: light-emitting layer, **194**: buffer layer, **194B**: buffer layer, **194G**: buffer layer, **194R**: buffer layer, **200A**: display device, **200B**: display device, **201**: substrate, **202**: finger, **203**: layer including a light-emitting element, **204**: layer including a light-emitting and light-receiving element, **205**: functional layer, **207**: layer including a light-emitting element, **208**: stylus, **209**: substrate, **211**: insulating layer, **212**: insulating layer, **213**: insulating layer, **214**: insulating layer, **214a**: insulating layer, **214b**: insulating layer, **215**: insulating layer, **216**: partition, **219a**: light shielding layer, **219b**: spacer, **221**: conductive layer, **222a**: conductive layer, **222b**: conductive layer, **223**: conductive layer, **225**: insulating layer, **228**: region, **231**: semiconductor layer, **231i**: channel formation region, **231n**: low-resistance region, **240**: transistor, **241**: transistor, **242**: connection layer, **243**: transistor, **244**: connection portion, **245**: transistor, **246**: transistor, **247**: transistor, **248**: transistor, **249**: transistor, **252**: transistor, **261**: contact portion, **262**: fingerprint, **263**: image-capturing range, **266**: path, **270B**: light-emitting element, **270G**: light-emitting element, **270PD**: light-receiving element, **270R-PD**: light-emitting and light-receiving element, **270R**: light-emitting element, **271**: pixel electrode, **273**: active layer, **275**: common electrode, **280A**: display device, **280B**: display device, **280C**: display device, **281**: hole-injection layer, **282**: hole-transport layer, **283**: light-emitting layer, **283B**: light-emitting layer, **283G**: light-emitting layer, **283R**: light-emitting layer, **284**: electron-transport layer, **285**: electron-injection layer, **6500**: electronic device, **6501**: housing, **6502**: display portion, **6503**: power button, **6504**: button, **6505**: speaker, **6506**:

microphone, **6507**: camera, **6508**: light source, **6510**: protection member, **6511**: display panel, **6512**: optical member, **6513**: touch sensor panel, **6515**: FPC, **6516**: IC, **6517**: printed circuit, **6518**: battery, **7000**: display portion, **7100**: television device, **7101**: housing, **7103**: stand, **7111**: remote controller, **7200**: laptop personal computer, **7211**: housing, **7212**: keyboard, **7213**: pointing device, **7214**: external connection port, **7300**: digital signage, **7301**: housing, **7303**: speaker, **7311**: information terminal, **7400**: digital signage, **7401**: pillar, **7411**: information terminal, **9000**: housing, **9001**: display portion, **9003**: speaker, **9005**: operation key, **9006**: connection terminal, **9007**: sensor, **9008**: microphone, **9050**: icon, **9051**: information, **9052**: information, **9053**: information, **9054**: information, **9055**: hinge, **9101**: portable information terminal, **9102**: portable information terminal, **9200**: portable information terminal, **9201**: portable information terminal

Claims

1. An electronic device comprising: a control portion, a display portion, and a memory portion, wherein the display portion comprises a pixel, wherein the pixel comprises a light-emitting element, a light-receiving element, and a partition, wherein the light-emitting element comprises a first electrode, a common layer over the first electrode, a light-emitting layer over the common layer, and a common electrode over the light-emitting layer, wherein the light-receiving element comprises a second electrode, the common layer over the second electrode, an active layer over the common layer, and the common electrode over the active layer, wherein an end portion of the first electrode and an end portion of the second electrode are covered with the partition, wherein the common layer and the common electrode are provided over the partition, wherein the light-emitting layer and the active layer contain different organic compounds from each other, wherein the display portion is configured to display an image, configured to detect a touch operation, and configured to obtain fingerprint data on a touching finger, wherein the memory portion is configured to retain fingerprint data on a plurality of fingers registered in advance, and wherein the control portion is configured to compare the fingerprint data on the touching finger with each piece of the fingerprint data on the plurality of fingers, and configured to execute processing corresponding to fingerprint data that matches the fingerprint data on the touching finger among the fingerprint data on the plurality of fingers in the case where the fingerprint data on the touching finger matches any piece of the fingerprint data on the plurality of fingers.
2. An electronic device comprising: a control portion, a display portion, and a memory portion, wherein the display portion comprises a pixel, wherein the pixel comprises a light-emitting element, a light-receiving element, and a light shielding layer, wherein the light-emitting element comprises a first electrode, a common layer over the first electrode, a light-emitting layer over the common layer, and a common electrode over the light-emitting layer, wherein the light-receiving element comprises a second electrode, the common layer over the second electrode, an active layer over the common layer, and the common electrode over the active layer, wherein the light-emitting layer and the active layer contain different organic compounds from each other, wherein the light shielding layer is provided over the light-emitting element and the light-receiving element, wherein a shortest distance between a first end portion of the light shielding layer and the common electrode of the light-emitting element is shorter than a shortest distance between a second end portion of the light shielding layer and the common electrode of the light-receiving element, wherein the display portion is configured to display an image, configured to detect a touch operation, and configured to obtain fingerprint data on a touching finger, wherein the memory portion is configured to retain fingerprint data on a plurality of fingers registered in advance, and wherein the control portion is configured to compare the fingerprint data on the touching finger with each piece of the fingerprint data on the plurality of fingers, and configured to execute processing corresponding to fingerprint data that matches the fingerprint data on the touching finger among the fingerprint data on the plurality of fingers in the case where the fingerprint data on the touching finger matches any piece

of the fingerprint data on the plurality of fingers.

3. The electronic device according to claim 2, wherein the pixel further comprises a partition, wherein an end portion of the first electrode and an end portion of the second electrode are covered with the partition, and wherein the common layer and the common electrode are provided over the partition.

4. The electronic device according to claim 1, wherein the control portion is configured to bring a system into a locked state in the case where the fingerprint data on the touching finger does not match any pieces of the fingerprint data on the plurality of fingers.

5. The electronic device according to claim 1, wherein the display portion is configured to authenticate the fingerprint data in a whole display region.

6. The electronic device according to claim 1, wherein the light-emitting element is configured to emit visible light, and wherein the light-receiving element is configured to receive the visible light emitted by the light-emitting element.

7. The electronic device according to claim 1, wherein the light-emitting element is configured to emit infrared light, and wherein the light-receiving element is configured to receive the infrared light emitted by the light-emitting element.

8. The electronic device according to claim 2, wherein the control portion is configured to bring a system into a locked state in the case where the fingerprint data on the touching finger does not match any pieces of the fingerprint data on the plurality of fingers.

9. The electronic device according to claim 2, wherein the display portion is configured to authenticate the fingerprint data in a whole display region.

10. The electronic device according to claim 2, wherein the light-emitting element is configured to emit visible light, and wherein the light-receiving element is configured to receive the visible light emitted by the light-emitting element.

11. The electronic device according to claim 2, wherein the light-emitting element is configured to emit infrared light, and wherein the light-receiving element is configured to receive the infrared light emitted by the light-emitting element.
