

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284346

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Wu; Francis et al.

ON-SCREEN VIRTUAL KEYBOARDS WITH SIDE-BY-SIDE KEYBOARD PORTIONS

Abstract

Systems and methods described herein include displaying a keyboard on a display. The virtual keyboard is split into a first keyboard portion including an inner zone including one or more letters and an outer zone including a first group of letters that are positioned to surround the inner zone of the first keyboard portion; and into a second keyboard portion including an inner zone including one or more letters and an outer zone including a second group of letters that are positioned to surround the inner zone of the second keyboard portion. The methods and systems described herein include respectively generate first and second signals pertaining to selection of a letter on the first and second keyboard portion in response to a user interacting with one or more control inputs in a first of second group of control inputs on a handheld controller.

Inventors: Wu; Francis (Waterloo, CA), Chowdhury; Sakib (Toronto, CA), Cobb; Jack (Mono, CA), Kazman; Michael (Kitchener, CA), Singh; Sidhartha (Brampton, CA), Tian; Qinghe (Waterloo, CA), Snyder; Mathew (Kitchener, CA)

Applicant: Sony Interactive Entertainment LLC (San Mateo, CA)

Family ID: 1000007784955

Appl. No.: 18/597555

Filed: March 06, 2024

Publication Classification

Int. Cl.: G06F3/023 (20060101); A63F13/23 (20140101)

U.S. Cl.:

CPC G06F3/0236 (20130101); A63F13/23 (20140902)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is related to U.S. Non-Provisional application Ser. No. _____, filed on the same date as this application, entitled “ON-SCREEN, SPLIT VIRTUAL KEYBOARDS,” and identified by Attorney Docket No. 158447 [SIEA23116US00], the entire disclosure of which is hereby fully incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] This invention relates generally to virtual keyboards and, more specifically, to on-screen split virtual keyboards that enable the user to enter characters using two separate cursors.

BACKGROUND

[0003] Typical virtual keyboards generated on screens coupled to computing devices, gaming consoles, and the like generally have a layout resembling the layout of their counterpart physical keyboards. Such virtual keyboards include one on-screen cursor, which may be moved by a user via a controller from one letter to the next letter to input each word letter by letter, which is not very efficient, and can be time consuming when entering long words or phrases.

SUMMARY

[0004] In some embodiments, a method includes displaying a keyboard on a display. The keyboard is split into a first keyboard portion including an inner zone including one or more first letters of an alphabet and an outer zone including a first group of letters of the alphabet that are positioned to surround the inner zone of the first keyboard portion, and a second keyboard portion including an inner zone including one or more second letters of the alphabet and an outer zone including a second group of letters of the alphabet that are positioned to surround the inner zone of the second keyboard portion. The method also includes generating first signals pertaining to selection of a letter on the first keyboard portion in response to a user interacting with one or more control inputs in a first group of control inputs on a controller and generating second signals pertaining to selection of a letter on the second keyboard portion in response to the user interacting with one or more control inputs in a second group of control inputs on the controller.

[0005] In some implementations, the first signals cause a first cursor to move within the first keyboard portion and cause the letter in the first keyboard portion to be selected, and the second signals cause a second cursor to move within the second keyboard portion and cause the letter in the second keyboard portion to be selected.

[0006] In some aspects, the first group of letters of the alphabet of the outer zone of the first keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the first keyboard portion, and the second group of letters of the alphabet of the outer zone of the second keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the second keyboard portion.

[0007] In some embodiments, the first group of control inputs is located on a left side of the handheld controller and the second group of control inputs is located on a right side of the handheld controller. In certain aspects, the user interacting with one or more control inputs in the first group of control inputs on the handheld controller comprises the user interacting with a first analog control input, and the user interacting with one or more control inputs in the second group of control inputs on the handheld controller comprises the user interacting with a second analog control input.

[0008] In some implementations, the one or more control inputs in the first group of control inputs and the one or more control inputs in the second group of control inputs are respectively configured to allow a first cursor on the first keyboard portion and a second cursor on the second keyboard portion to be moved substantially simultaneously.

[0009] In some embodiments, the inner zone of each of the first and second keyboards includes one letter and the outer zone of each of the first and second keyboard includes twelve letters. In other embodiments, the inner zone of each of the first and second keyboards includes at least two letters and the outer zone of each of the first and second keyboard includes at most eleven letters.

[0010] In some embodiments, a non-transitory computer readable storage medium storing one or more computer programs configured to cause a processor-based system to execute steps comprising displaying a keyboard on a display. The keyboard is split into: a first keyboard portion including an inner zone including one or more first letters of an alphabet and an outer zone including a first group of letters of the alphabet that are positioned to surround the inner zone of the first keyboard portion; and a second keyboard portion including an inner zone including one or more second letters of the alphabet and an outer zone including a second group of letters of the alphabet that are positioned to surround the inner zone of the second keyboard portion; generating first signals pertaining to selection of a letter on the first keyboard portion in response to a user interacting with one or more control inputs in a first group of control inputs on a handheld controller; and generating second signals pertaining to selection of a letter on the second keyboard portion in response to the user interacting with one or more control inputs in a second group of control inputs on the handheld controller.

[0011] In some embodiments, a system includes a display; a handheld controller; and a processor-based system in communication with the display and the handheld controller and configured to execute steps including displaying a keyboard on a display. The keyboard is split into: a first keyboard portion including an inner zone including one or more first letters of an alphabet and an outer zone including a first group of letters of the alphabet that are positioned to surround the inner zone of the first keyboard portion; and a second keyboard portion including an inner zone including one or more second letters of the alphabet and an outer zone including a second group of letters of the alphabet that are positioned to surround the inner zone of the second keyboard portion; generating first signals pertaining to selection of a letter on the first keyboard portion in response to a user interacting with one or more control inputs in a first group of control inputs on a handheld controller; and generating second signals pertaining to selection of a letter on the second keyboard portion in response to the user interacting with one or more control inputs in a second group of control inputs on the handheld controller.

[0012] A better understanding of the features and advantages of various embodiments of the present invention will be obtained by reference to the following detailed description and accompanying drawings which set forth illustrative embodiments of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] Disclosed herein are embodiments of systems and methods pertaining to on-screen side-by-side virtual keyboards that enable the user to enter characters using two separate cursors. This description includes drawings, wherein:

[0014] FIG. 1 depicts a display screen view diagram illustrating a prior art virtual keyboard visible thereon;

[0015] FIG. 2 depicts a display screen view diagram illustrating a hand-held controller and a virtual keyboard in accordance with some embodiments;

[0016] FIG. 3 depicts a screen view diagram illustrating the virtual keyboard and the hand-held controller of FIG. 2, but with the analog joysticks of the hand-held controller being moved to move the corresponding cursors on the virtual keyboard;

[0017] FIG. 4 depicts a display screen view diagram illustrating the virtual keyboard in accordance with some embodiments, where a predictive engine predicts and suggests a word that the user is

attempting to type in based on one or more initial letters of the word;

[0018] FIG. 5 depicts a display screen view diagram illustrating a hand-held controller and a virtual keyboard in accordance with some embodiments;

[0019] FIG. 6 is a schematic diagram of a system in accordance with some embodiments;

[0020] FIG. 7 is a block diagram of a computing device in accordance with some embodiments; and

[0021] FIG. 8 is a flow diagram representative of a method in accordance with some embodiments.

[0022] Elements in the figures are illustrated for simplicity and clarity and have not been drawn to scale. For example, the dimensions and/or relative positioning of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of various embodiments of the present invention. Also, common but well-understood elements that are useful or necessary in a commercially feasible embodiment are often not depicted in order to facilitate a less obstructed view of these various embodiments of the present invention. Certain actions and/or steps may be described or depicted in a particular order of occurrence while those skilled in the art will understand that such specificity with respect to sequence is not actually required. The terms and expressions used herein have the ordinary technical meaning as is accorded to such terms and expressions by persons skilled in the technical field as set forth above except where different specific meanings have otherwise been set forth herein.

DETAILED DESCRIPTION

[0023] The following description is not to be taken in a limiting sense, but is made merely for the purpose of describing the general principles of exemplary embodiments. Reference throughout this specification to “one embodiment,” “an embodiment,” or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, appearances of the phrases “in one embodiment,” “in an embodiment,” and similar language throughout this specification may, but do not necessarily, all refer to the same embodiment.

[0024] Generally speaking, pursuant to various embodiments, systems and methods described herein include displaying a keyboard on a display. The virtual keyboard is split into a first keyboard portion including an inner zone including one or more letters and an outer zone including a first group of letters that are positioned to surround the inner zone of the first keyboard portion; and into a second keyboard portion including an inner zone including one or more letters and an outer zone including a second group of letters that are positioned to surround the inner zone of the second keyboard portion. The methods and systems described herein include respectively generate first and second signals pertaining to selection of a letter on the first and second keyboard portion in response to a user interacting with one or more control inputs in a first of second group of control inputs on a handheld controller.

[0025] FIG. 1 shows a conventional virtual keyboard **10**, which may be displayed on a screen **11** of a display (e.g., a television, monitor, handheld device, etc.), and which enables a user to type one or more words into a text input field **12** by using a cursor **18** to select one character **20** (e.g., a letter, a number, or a symbol) at a time. The keyboard **10** may include special characters **22** (e.g., up arrow, space bar, back space, etc.), which may be selected with the use of the cursor **18**, or by pressing a specific input **24** (e.g., a button labeled with letters and/or symbols A, B, X, Y, with a “cross,” “circle,” “triangle,” “square,” L1, L2, R1, and/or R2, etc.) on a hand-held controller **130** (see, e.g., FIG. 2) being operated by a user, and the specific input **24** of the controller **130** that may be interacted with by the user to select one of these special characters **22** may be displayed within the virtual keyboard **10** on the screen **11**. Since this keyboard **10** is limited to selection of one character **20** at a time by sequentially moving one cursor **18** to each of the letters of an intended word or phrase, typing in a long word or phrase may become time consuming or tedious for a user.

[0026] FIG. 2 shows a virtual keyboard **100** according to some embodiments described herein, which is displayed on a screen **111** of a display (e.g., a television, monitor, handheld device, etc.),

and which facilitates the ease, speed, and accuracy of typing by a user of a hand-held controller **130**. The keyboard **100** includes a first keyboard portion **102** and a second keyboard portion **104**. Each of the first and second keyboard portions **102**, **104** of the exemplary virtual keyboard **100** illustrated in FIG. 2 may include characters **120** such as letters (e.g., a, b, c, etc.), numbers (1, 2, 3, etc.), and special symbols (e.g., question mark, exclamation, coma, period, etc.).

[0027] Notably, the virtual keyboard **100** does not have to be limited to only two keyboard portions **102**, **104**. For example, in some embodiments, the virtual keyboard **100** may include four (or more) different keyboard portions each including different characters (e.g., letters, numbers, symbols, etc.), and the user is permitted to switch between the first keyboard portion **102** and a third keyboard portion by pressing a pre-determined button input (e.g., L2, etc.) on the hand-held controller **130**, and to switch between the second keyboard portion **104** and a fourth keyboard portion by pressing a pre-determined button input (e.g., R2, etc.) on the hand-held controller **130**.

[0028] Like the conventional virtual keyboard **10** shown in FIG. 1, the virtual keyboard **100** according to the embodiment illustrated in FIG. 2 includes an input field **112**, which enables the user to type in letters, numbers, and special symbols/characters by sequentially selecting the appropriate characters **120** on the virtual keyboard **100** using a hand-held controller **130**. Also like the conventional virtual keyboard **10** shown in FIG. 1, the exemplary virtual keyboard **100** of FIG. 2 includes special characters **122** (e.g., up arrow, space bar, back space, etc.), which may be selected with the use of the cursor **118**, or by pressing a specific input **124** (e.g., button) on a hand-held controller **130** being operated by a user, causing the specific input **124** that the user interacts with to select one of these special characters **122** to be displayed on the screen **111**.

[0029] Unlike the conventional virtual keyboard **10** of FIG. 1, in the exemplary keyboard **100** shown in FIG. 2, the first keyboard portion **102** and the second keyboard portion **104** of the virtual keyboard **100** are visibly separated by a space or a gap **106**, making it clearly visible to a user that the first keyboard portion **102** is separate and distinct from the second keyboard portion **104**. It will be appreciated, however, that, in some embodiments, the first keyboard portion **102** and the second keyboard portion **104** may be separately operable and distinct, but positioned so close together relative to each other such that there would not be a visible gap therebetween.

[0030] The exemplary virtual keyboard **100** of FIG. 2 is shown as having a first virtual keyboard portion **102** including an inner zone **103** including at least one character field **120** each containing one letter and an outer zone **105** including a plurality of character fields **120** each containing one letter. In addition, the exemplary virtual keyboard **100** of FIG. 2 has a second virtual keyboard portion **104** including an inner zone **107** including at least one character field **120** each containing one letter and an outer zone **109** including a plurality of character fields **120** each containing one letter. In the embodiment illustrated in FIG. 2, each of the inner zones **103**, **107** and outer zones **105**, **109** has a generally circular overall shape, and each of the outer zones **105**, **109** surrounds/encircles its respective inner zone **103**, **107**. It will be appreciated that the inner zones **103**, **107** and outer zones **105**, **109** do not have to be generally circular, and may be of another suitable overall shape.

[0031] With reference to FIG. 2, the first keyboard portion **102** and the second keyboard portion **104** of the virtual keyboard **100** each contain one half of the letters of the English alphabet, with the first keyboard portion **102** containing a total of thirteen letters (one letter “f” in the inner zone **103**, and twelve letters “a,” “s,” “d,” “z,” “x,” “c,” “g,” “t,” “r,” “e,” “w,” and “q” in the outer zone **105**), and the second keyboard portion **104** similarly containing a total of thirteen letters (one letter “j” in the inner zone **107**, and twelve letters “h,” “v,” “b,” “n,” “m,” “k,” “l,” “p,” “o,” “i,” “u,” and “y” in the outer zone **109**). It will be appreciated that the total number of letters located in each of the zones **103**, **105**, **107**, **109** of the virtual keyboard **100**, as well as the locations of each of the letters within its respective zone **103**, **105**, **107**, **109** are shown by way of example only.

[0032] For example, in some embodiments, each of the inner and outer zones **103**, **105**, **107**, **109** may have different letters or a different total number of letters in them, or include the same letters,

but in different locations within their respective zones **103**, **105**, **107**, **109**. For example, in some implementations, each of the inner zones **103**, **107** may include four letters while each of the outer zones **105**, **109** may include nine letters. In addition, as will be discussed above with reference to FIG. 5, in one embodiment, the virtual keyboard **400** includes a first keyboard portion **402** with an inner zone **403** including six letters of the English alphabet and an outer zone **405** including seven letters of the English alphabet, as well as a second keyboard portion **404** with an inner zone **407** that includes six letters of the English alphabet and an outer zone **409** that includes seven letters of the English alphabet.

[0033] Another difference between the exemplary keyboard **100** of FIG. 2 and the conventional keyboard **10** of FIG. 1 is that the keyboard **100** includes not one cursor **18**, but two separate cursors **118** and **119** that facilitate a user's selection of characters **120** on the first and second keyboard portions **102**, **104** of the virtual keyboard **100**. In other words, the first keyboard portion **102** includes its own dedicated cursor **118**, which permits the user to select the characters **120** (e.g., letters) of the first keyboard portion **102** but not the characters **120** (e.g., letters) of the second keyboard portion **104**. Similarly, the second keyboard portion **104** includes its own dedicated cursor **119**, which permits the user to select the characters **120** of the second keyboard portion **104**, but not the characters **120** of the first keyboard portion **102**.

[0034] In the illustrated embodiment, a handheld controller **130** (which will be discussed in more detail below) is used to move the first cursor **118** on the first keyboard portion **102** to select a character **120** desired by the user, and to move the second cursor **119** on the second keyboard portion **104** to select a character **120** desired by the user. In one implementation, the hand-held controller **130** includes a first group of controls **132**, which enables the user to move the first cursor **118** on the first keyboard portion **102** and to select a character **120** desired by the user. This hand-held controller **130** further includes a second group of controls **134**, which enables the user to move the second cursor **119** on the second keyboard portion **104** and to select a character **120** desired by the user.

[0035] In the embodiment illustrated in FIG. 2, the first group of controls **132** is represented by a first (e.g., left) analog stick of the controller **130** (and may also include a left-hand side directional pad), and the second group of controls **134** is represented by a second (e.g., right) analog stick of the controller **130** (and may also include a right-hand side directional pad). Notably, each of the first and second group of controls **132**, **134** is not limited to an analog stick, and may include only an analog stick, only a directional pad, only a combination of buttons, or a combination thereof.

[0036] In the embodiment illustrated in FIG. 2, the first keyboard portion **102** of the virtual keyboard **100** is located on the left-hand side of the screen **111** and the second keyboard portion **104** is located on the right-hand side of the screen **111**. To facilitate the logic and ease of use of the virtual keyboard **100** by the user, the first group of controls **132**, which enables the user to move the first cursor **118** on the left-hand side first keyboard portion **102** and to select a character **120** desired by the user, is located on a left-hand side of the hand-held controller **130**. By the same token, the second group of controls **134**, which enables the user to move the second cursor **119** on the right-hand side second keyboard portion **104** and to select a character **120** desired by the user, is located on a right-hand side of the hand-held controller **130**.

[0037] On the exemplary virtual keyboard **100** shown in FIG. 2, letter “f” (located within the inner zone **103**) is shown as being selected on the first keyboard portion **102** by the first cursor **118**, and the letter “j” (located within the inner zone **107**) is shown as being selected on the second keyboard portion **104** by the second cursor **119**. In the example shown in FIG. 2, each of the left and right analog sticks **132**, **134** of the hand-held controller **130** is shown as being in a substantially vertical position. In the illustrated embodiment, to move the first cursor **118** of the first keyboard portion **102** from the selected letter “f” to another letter of the first keyboard portion **102**, the user would move the left analog stick **132** of the hand-held controller **130** in the direction of the desired letter. By the same token, to move the second cursor **119** of the second keyboard portion **104** from the

selected letter “j” to another letter of the second keyboard portion **104**, the user would move the right analog stick **134** of the hand-held controller **130** in the direction of the desired letter.

[0038] For example, FIG. 3 shows that the directional movement of the left analog stick **132** (by the user), from the substantially vertical orientation of the left analog stick **132** shown in FIG. 2, in a generally left direction (as indicated by the directional arrow in FIG. 3) and toward the letter “a,” caused the first cursor **118** to move from the letter “f” to the letter “a,” which is located to the left of the letter “f” on the first keyboard portion **102**. Similarly, FIG. 3 shows that directional movement of the right analog stick **134** (by the user), from the substantially vertical orientation of the right analog stick **134** shown in FIG. 2, in a generally left direction (indicated by the directional arrow in FIG. 3) and toward the letter “h,” caused the second cursor **119** to move from the letter “j” to the letter “h,” which is located to the left of the letter “j” on the second keyboard portion **104**.

[0039] If, for example, the user were to move the left analog stick **132** in a vertically upward direction from the substantially vertical orientation shown in FIG. 2, the first cursor **118** would move from the letter “f” to the letter “e,” which is located directly above the letter “f” on the first keyboard portion **102**. By the same token, if the user were to move the right analog stick **134** in a vertically downward direction from the substantially vertical orientation shown in FIG. 2, the second cursor **119** would move from the letter “j” to the letter “n,” which is located directly below the letter “j” on the second keyboard portion **104**.

[0040] In the embodiment illustrated in FIG. 2, each of the first and second cursors **118**, **119** is displayed within the virtual keyboard **100** as a thicker/bold-font bounding box (as compared to the thinner bounding boxes surrounding the letters not being selected by a cursor **118**, **119**) that surrounds (encircles) a respective one of the characters **120** (in this case, characters “f” and “j”) of the first and second keyboard portions **102**, **104**. While the bounding box representing each respective cursor **118**, **119** is shown as being circular in FIG. 2, it will be appreciated that the bounding box may be of any other suitable shape. Further, in some aspects, instead of being represented by a bounding box that surrounds a respective one of the characters (e.g., letters) **120**, the first and second cursors **118**, **119** may be represented within the virtual keyboard **100** as an enlarged version of the respective character on which the respective cursor **118**, **119** is located.

[0041] In other words, in some implementations, if the letter “e” were to be selected by the first cursor **118** on the first keyboard portion **102**, there would be no visible circular bounding box surrounding the letter “e,” but instead the letter “e” would appear in a size that is larger than its original size when not selected by the first cursor **118**. In some other embodiments, instead of being represented by a bounding box that surrounds a respective one of the characters (e.g., letters) **120**, the first and second cursors **118**, **119** may be represented by a color (e.g., a coloring of the letter on which the respective cursor **118**, **119** is located, or a coloring around the letter on which the respective cursor **118**, **119** is located).

[0042] With reference to FIG. 4, in some embodiments, the virtual keyboard **100** includes word suggestion fields **140**, **142**, **144** that visually indicate a suggested word to the user, which is generated by a prediction engine **180** based on an analysis of the first one or more initial letters of a word that the user starts to type into the input field **112**, a represents a prediction by the prediction engine **180** of the word that the user is attempting to type into the input field **112**. While three word suggestion fields **140**, **142**, **144** are shown in the exemplary keyboard **100** of FIG. 4, it will be appreciated that the virtual keyboard **100** may include less than three word suggestion fields or more than three word suggestion fields akin to the word suggestion fields **140**, **142**, **144**.

[0043] In the example illustrated in FIG. 4, the prediction engine **180** has predicted, based on an analysis of the user typing in “hello hap” into the input field **112**, that the user is most likely attempting to type in one of three possible words that start with “hap,” namely, “happy” (shown in word suggestion field **140**), “happen” (shown in word suggestion field **142**), or “hapless” (shown in word suggestion field **144**). In some aspects, even if only the initial letter (e.g., “h”) of the second word (following “happy”) were to appear (instead of “hap”) within the input field **112** of the

keyboard **100** after being selected by the user, the predictive engine **180** could have predicted (based on historical and other data available to the predictive engine **180**) that the user is attempting to type in “happy,” “happen,” or “hapless,” thereby causing the words “happy,” “happen,” or “hapless” to appear in word suggestion fields **140**, **142**, or **144**, respectfully. After that, the user would be permitted to complete the full word that the user is attempting to type within the input field **112** by selecting (e.g., via the first or second analog stick **132**, **134** or via another control input (e.g., R2) of the hand-held controller **130**) the full word appearing in one of the word suggestion fields **140**, **142**, **144** that matches the full word that the user is actually attempting to type into the input field **112**.

[0044] In some embodiments, the predictive engine **180** is programmed with a trained predictive model that is trained to generate, based at least on the complete list of complete words previously typed in by the user into the input field **112**, a prediction of which letter the user is most likely to select next on the virtual keyboard **100** and/or a prediction of the full word that the user is most likely attempting to enter into the input field **112**. In certain aspects, the predictive model of the predictive engine **180** may be continuously updated (e.g., to expand the library of words that may be suggested) over time as the user uses the controller **130** to type in words and/or phrases into the input field **112** of the virtual keyboard **100**. In the example shown in FIG. 4, the predictive engine **180** has predicted, based at least on the historical data associated with the user, that the user is attempting to enter the word “happy,” “happen,” or “hapless” into the input field **112**.

[0045] In the embodiment illustrated in FIGS. 3-4, each of the outer zones **105**, **109** includes 12 letters positioned in pattern of a complete circle (i.e., 360 degrees), such that the “hit-box” of each of the 12 letters positioned in each of the outer zones **105**, **109** is set at 30 degrees. In some embodiments, the “hit-box” of each of the letters in the outer zones **105**, **109** may be static regardless of the predictions by the predictive engine **180**. In other words, regardless of the next letter predicted by the predictive engine **180** to be typed in by the user, the “hit-box” of each of the letters of each of the outer zones **105**, **109** remains at 30 degrees. As such, it is equally easy for the user to “hit” (i.e., select) the letter that the predictive engine **180** has predicted will be the next-selected letter, or a letter to the right or left of the letter that the predictive engine **180** has predicted will be the next-selected letter.

[0046] In certain implementations, the “hit-box” of each of the letters in the outer zones **105**, **109** dynamically changes based on the predictions by the predictive engine **180**. In other words, in some embodiments, after the predictive engine **180** predicts the next letter that is most likely to be typed in by the user, the “hit-box” of the letter predicted to be next is increased (e.g., by 5, 10, 15, 20, etc. degrees from 30 degrees to 35, 40, 45, 50, etc. degrees) so that it is easier for the user to “hit” (i.e., select) the letter that the predictive engine **180** has predicted will be the next-selected letter than a letter to the right or left of the letter that the predictive engine **180** has predicted will be the next-selected letter. In one implementation, after the predictive engine **180** predicts the next letter that is most likely to be typed in by the user, the “hit-box” of the letter predicted to be next may be displayed in a changed (i.e., different color) so that it is easier for the user to recognize and “hit” (i.e., select) the letter that the predictive engine **180** has predicted will be the next-selected letter as opposed to a letter to the right or left (which will remain in its original color) of the letter that the predictive engine **180** has predicted will be the next-selected letter.

[0047] In some embodiments, the virtual keyboard **100** is configured such that: (1) the default position of the first cursor **118** is on the centrally-located letter “f” of the inner zone **103** of the first keyboard portion **104**, and such that the first cursor **118** resets to be located on the centrally-located letter “f” after any letter of the first keyboard portion **102** is selected by the user; and (2) the default position of the second cursor **119** is on the centrally-located letter “j” of the inner zone **107** of the second keyboard portion **104**, and such that the second cursor **119** resets to be located on the centrally-located letter “j” after any letter of the second keyboard portion **104** is selected by the user.

[0048] For example, in some embodiments, if the user were to use the first cursor **118** to input the letter “w” into the input field **112**, the location of the first cursor **118** would reset such that the first cursor is positioned on the letter “f,” and the user would have to move the first cursor **118** from its location on the letter “f” to the location of the next letter the user intends to type into the text input field **112**. On the other hand, in certain embodiments, the virtual keyboard **100** is configured such that each of the first and second cursors **118**, **119** does not reset to the centrally-located letter of the respective first and second inner zones **103**, **107**, but instead remains on the letter that is last selected. For example, if the user were to use the first cursor **118** to input the letter “w” into the input field **112**, the first cursor would remain on the letter “w” and the user would have to move the first cursor **118** from its location on the letter “w” to the location of the next letter the user intends to type into the text input field **112**.

[0049] Without wishing to be limited to theory, the two-cursor split virtual keyboards **100** described herein enable users to type in words and phrases faster than (e.g., at least 1.5 times faster) and at least as accurately as the existing conventional virtual keyboards, thereby providing a significant time savings for the users and helping the users input their data into their on-screen virtual keyboards via an easy to use and intuitive virtual keyboard design that avoids the slow and tedious data entry offered by conventional on-screen keyboards.

[0050] FIG. 5 shows a virtual keyboard **400** according to another embodiment of the invention. This exemplary virtual keyboard **400** is displayed on a screen **111** of a display (e.g., a television, monitor, handheld device, etc.), and, like the virtual keyboard **100**, is designed to facilitate the ease, speed, and accuracy of typing by a user of a hand-held controller **130**.

[0051] Like the virtual keyboard **100**, the virtual keyboard **400** includes a first keyboard portion **402** and a second keyboard portion **404**, as well as a first cursor **418** that may be used to select characters **420** on the first keyboard portion **402** and a second cursor **419** that may be used to select characters **420** on the second keyboard portion **404**. Like the keyboard **100**, the keyboard **400** according to the embodiment illustrated in FIG. 5 includes an input field **412**, which enables the user to type in letters, numbers, and special symbols/characters by sequentially selecting the appropriate characters **420** on the virtual keyboard **400** using a hand-held controller **130**. Also like the keyboard **100** shown in FIG. 2, the exemplary virtual keyboard **400** of FIG. 5 includes special characters **422** (e.g., up arrow, space bar, back space, etc.), which may be selected via a first or second cursor **418**, **419** and by pressing a specific input **424** (e.g., an analog stick, a button, etc.) on a hand-held controller **130** being operated by a user, causing the specific input **424** that the user interacts with to select one of these special characters **422** to be displayed on the screen **111**.

[0052] In the embodiment illustrated in FIG. 5, like the inner zones **103**, **107** and outer zones **105**, **109** of the keyboard **100**, each of the inner zones **403**, **407** and outer zones **405**, **409** of the keyboard **400** has a generally circular overall shape, and each of the outer zones **405**, **409** surrounds/encircles its respective inner zone **403**, **407**. It will be appreciated that the inner zones **403**, **407** and outer zones **405**, **409** do not have to be generally circular, and may be of another suitable overall shape.

[0053] Also like the virtual keyboard **100** of FIG. 2, in the exemplary keyboard **400** shown in FIG. 4, the first keyboard portion **402** and the second keyboard portion **404** of the virtual keyboard **100** are visibly separated by a space or a gap **406**, making it clearly visible to a user that the first keyboard portion **402** is separate and distinct from the second keyboard portion **404**. In addition, like keyboard **100** of FIG. 2, the first and second keyboard portions **402**, **404** of the keyboard **400** each respectively include an inner zone **403**, **407** and an outer zone **405**, **409**.

[0054] However, unlike the keyboard **100**, the inner zones **103** and **107** of which contain one letter as discussed above, the inner zones **403**, **407** of the keyboard **400** each contain six letters (i.e., “a,” “e,” “i,” “y,” “u,” and “o” in inner zone **403**, and letters “t,” “r,” “s,” “d,” “n,” and “h” in inner zone **407**). Furthermore, unlike the keyboard **100**, the outer zones **105** and **109** of which contain twelve letters as discussed above, the inner zones **403**, **407** of the keyboard **400** each contain seven letters

(i.e., letters “b,” “k,” “j,” “q,” “v,” “x,” and “z” in outer zone **407**, and letters “f,” “g,” “c,” “l,” “m,” and “p,” and “w” in outer zone **409**).

[0055] It will be appreciated that the total number of letters located in each of the zones **403**, **405**, **407**, **409** of the virtual keyboard **400**, as well as the locations of each letter within its respective zone **403**, **405**, **407**, **409** are shown by way of example only, and can be varied. In some embodiments, the letters placed into the inner zones **403**, **407** of the keyboard **400** and into the outer zones **405**, **409** of the keyboard **400** are chosen based on their statistical frequency of use in commonly used words. To put it another way, the letters “a,” “e,” “i,” “y,” “u,” and “o” located in inner zone **403** may be placed into the inner zone **403** due to a determination that these letters are associated with a higher expected frequency of use than the letters “b,” “k,” “j,” “q,” “v,” “x,” and “z” located in outer zone **407**. By the same token, the letters “t,” “r,” “s,” “d,” “n,” and “h” located in inner zone **407** may be placed into the inner zone **405** due to a determination that these letters are associated with a higher expected frequency of use than the letters “f,” “g,” “c,” “l,” “m,” and “p,” and “w” located in outer zone **409**.

[0056] FIG. **6** shows an exemplary embodiment of a system **200** that enables a user to take advantage of various embodiments of the virtual keyboard **100** described above. The exemplary system **200** shown in FIG. **6** includes a screen **111** (which may be the display of stand-alone device such as a television, monitor, etc., or which may be the display of a portable hand-held device, such as a portable gaming console, smart phone, tablet, laptop, etc.). The screen **111** may display a graphical user interface **160**, which may be a video stream associated with a video game, an on-screen menu, or other visual content which may utilize an on-screen virtual keyboard **100**. The system **200** of FIG. **6** includes a computing device **150** (which may be one or more computing devices as pointed out below) operatively coupled/connected to a display screen **111** and configured to communicate over a network (or connection) **140** with the display screen **111**, one or more hand-held controllers **130** (which may be wired or wireless), and a predictive engine **180** (which may be incorporated into the computing device **150** or stored on a computer/server remote to the computing device **150**).

[0057] The exemplary network **140** depicted in FIG. **6** may be a wide-area network (WAN), a local area network (LAN), a personal area network (PAN), a wireless local area network (WLAN), Wi-Fi, Zigbee, Bluetooth (e.g., Bluetooth Low Energy (BLE) network), or any other internet or intranet network, or combinations of such networks. Generally, communication between various electronic devices of system **200** may take place over hard-wired, wireless, cellular, Wi-Fi or Bluetooth networked components or the like. In some embodiments, one or more electronic devices of system **200** may include cloud-based features or services, such as cloud-based memory storage, cloud-based predictive engine, etc.

[0058] The computing device **150** may be a stationary or portable electronic device, for example, a stationary gaming console, a portable gaming console, a desktop computer, a laptop computer, a tablet, a mobile phone, a single server or a series of communicatively connected servers, or any other electronic device including a control circuit that includes a programmable processor and may be coupled/connected to a display screen **111**. In some embodiments, the computing device **150** is configured for running video games thereon (e.g., from a disc inserted into the computing device **150**, from an onboard memory of the computing device **150**, from a remote server/host, etc.) In some aspects, the computing device **150** is configured for data entry and processing and for communication with other devices of the system **200** via the network **140**.

[0059] With reference to FIG. **7**, an exemplary computing device **150** configured for use with exemplary systems and devices described herein includes a control circuit **310** including a programmable processor (e.g., a microprocessor or a microcontroller) electrically coupled via a connection **315** to a memory **320** and via a connection **325** to a power supply **330**. The control circuit **310** can comprise a fixed-purpose hard-wired platform or can comprise a partially or wholly programmable platform, such as a microcontroller, an application specification integrated circuit, a

field programmable gate array, and so on. These architectural options are well known and understood in the art and require no further description here.

[0060] The control circuit **310** can be configured (for example, by using corresponding programming stored in the memory **320** as will be well understood by those skilled in the art) to carry out one or more of the steps, actions, and/or functions described herein. In some embodiments, the memory **320** may be integral to the processor-based control circuit **310** or can be physically discrete (in whole or in part) from the control circuit **310** and is configured non-transitorily store the computer instructions that, when executed by the control circuit **310**, cause the control circuit **310** to behave as described herein. (As used herein, this reference to “non-transitorily” will be understood to refer to a non-ephemeral state for the stored contents (and hence excludes when the stored contents merely constitute signals or waves) rather than volatility of the storage media itself and hence includes both non-volatile memory (such as read-only memory (ROM)) as well as volatile memory (such as an erasable programmable read-only memory (EPROM))). Accordingly, the memory and/or the control unit may be referred to as a non-transitory medium or non-transitory computer readable medium.

[0061] The control circuit **310** of the computing device **150** is also electrically coupled via a connection **335** to an input/output **340** that can receive signals from, for example, from one or more hand-held controllers **130**, predictive engine **180**, etc. The input/output **340** of the computing device **150** can also send signals to other devices, for example, a signal to the electronic display **111**, predictive engine **180**, etc.

[0062] The processor-based control circuit **310** of the computing device **150** shown in FIG. 7 is electrically coupled via a connection **345** to a user interface **350**, which may include inputs **370** (e.g., buttons, ports, touch screens, etc.) that permit an operator of the computing device **150** to manually control the computing device **150** by inputting commands via touch button operation and/or voice commands and/or via a physically connected device (e.g., hand-held controller **130**, etc.). Possible commands may, for example, cause the computing device **150** to turn on and off, reset, eject a video game disc, etc. In some embodiments, the user interface **350** of the computing device **150** may also include a speaker **360** that provides audible feedback (e.g., notifications, alerts, etc.) to the operator of the computing device **150**. It will be appreciated that the performance of such functions by the processor-based control circuit **310** of the computing device **150** is not dependent on a human operator, and that the control circuit **310** of the computing device **150** may be programmed to perform such functions without a human operator.

[0063] In the embodiment illustrated in FIG. 6, the system **200** includes a predictive engine **180** that is configured to obtain (e.g., from the computing device **150** and over the network **140**) and process (e.g., via an artificial intelligence/machine learning model) the data representative of the text input (e.g., words and phrases) entered by the user via the hand-held controller **130** into the input field **112** of the virtual keyboard **100**. This processing of the user's input of letters or numerical characters permits the predictive engine **180** to generate one or more predictions of the words that the user is attempting to type into the virtual keyboard **100**.

[0064] In the embodiment illustrated in FIG. 6, the predictive engine **180** and the computing device **150** are shown as being implemented as two separate physical devices (which may be located at the same physical location or in different physical locations). It will be appreciated, however, that the computing device **150** and the predictive engine **180** may be implemented as a single physical device. In some aspects, the predictive engine **180** may be stored, for example, on non-volatile storage media (e.g., a hard drive, flash drive, or removable optical disk) internal or external to the computing device **150**, or internal or external to computing devices separate and distinct from the computing device **150**. In some embodiments, the predictive engine **180** may be cloud-based.

[0065] In certain implementations, the predictive engine **180** processes the data representing the text being input by the user into the input field **112** of the virtual keyboard **100** by executing one or more trained machine learning modules and/or trained neural network modules/models. In certain

aspects, the neural network executed by the predictive engine **180** (by itself or via the control circuit **310** of the computing device **150**) may be a deep convolutional neural network. The neural network module/model may be trained using various data sets, including, but not limited to: letter-by-letter sequential entries made by the user when typing any word or character into the virtual keyboard **100**, a library of complete words previously entered by the user into the virtual keyboard **100**, a dictionary-like library of possible words that may be suggested to the user, etc.

[0066] In some embodiments, the predictive engine **180** may be trained to analyze the user's text input into the input field **112** of the virtual keyboard **100** using one or more machine learning algorithms, including but not limited to Linear Regression, Logistic Regression, Decision Tree, SVM, Naïve Bayes, kNN, K-Means, Random Forest, Dimensionality Reduction Algorithms, Large Language Model Algorithms, Transformer Algorithms, and Gradient Boosting Algorithms. In some embodiments, the trained machine learning/neural network module/model of the predictive engine **180** includes a computer program code stored in a memory and/or executed by a control circuit (e.g., the control circuit **310**) to process an in-progress text input by the user to generate a list of predicted words that the user is attempting to type into the virtual keyboard.

[0067] As noted above, in some implementations, the predictive engine **180** is programmed with a trained machine learning model that is trained to generate, based on an available list of the full words previously typed in by the user into the input field **112**, a prediction of which letter the user is most likely to select next on the virtual keyboard **100** and/or a prediction of the full word that the user is most likely attempting to enter into the input field **112**. In certain aspects, the predictive model of the predictive engine **180** may be continuously updated in real time as a result of the user typing in new (i.e., previously unentered) words into the virtual keyboard **100**.

[0068] The exemplary system **200** shown in FIG. **6** further includes a hand-held controller **130**. Generally, gaming-specific computing devices/entertainment systems such as stationary or portable gaming consoles (e.g., Sony PlayStation, PlayStation Portable, Microsoft X Box, Nintendo Switch, etc.) include a hand-held game controller, which permits a user to enter in-game or menu commands or other instructions into the computing/gaming system to control a video game, a gaming-associated stream, or a gaming-associated menu.

[0069] The exemplary hand-held controller **130** illustrated in FIGS. **2-3** includes various control inputs. For example, the hand-held controller includes a first analog joystick **132** and a second analog joystick **134**, which may be referred to herein as a “first group of control inputs” and a “second group of control inputs,” respectively. In some embodiments, a manipulated variable of a first or second analog stick **132**, **134** (e.g., the directional movement caused by a user using the user's finger(s)) is converted from an analog value into a digital value, which is transmitted by the hand-held controller **130** to the computing device **150**, in turn causing a responsive in-game action, which is visible to the user on the screen **111**.

[0070] In some embodiments, the hand-held controller **130** is provided with various button inputs **124** that may be pushed by a user. In the exemplary embodiment shown in FIG. **2**, the controller **130** includes a third button (e.g., **L2**, etc.) that permits the user to switch the letters of the first and second virtual keyboard portions between lower case letters and capital letters; a fourth button (e.g., triangle, etc.) that permits the user to create a space between the letters, a fifth button (e.g., **R3**, etc.) that permits the user to select a special character that is not a letter; a sixth button (e.g., square, etc.) that permits the user to undo the selection of one or more of the letters; a seventh button (e.g., **L1**, etc.) that permits the user to enter a letter selected by the first cursor **118** to be entered into the text input field **112**; an eighth button (e.g., **R1**, etc.) that permits the user to enter a letter selected by the second cursor **119** to be entered into the text input field **112**; and a ninth button (e.g., touch pad, etc.) that may be touched or pressed by the user to, for example, move the first and second cursors **118**, **119** or select letters via the first and second cursors **118**, **119**. It will be appreciated that the number of button inputs **124** of the hand-held controller **130** and the functions assigned to each of the button inputs **124** of the hand-held controller **130** are shown/described by

way of example only.

[0071] In some embodiments, after a user uses the first analog stick **132** to move the first cursor **118** to the user-desired letter of the first keyboard portion **102**, the user then presses one of the button inputs **124** (e.g., L1) of the hand-held controller (which may be located on a left-hand side of the hand-held controller **130** just like the first analog stick **132**) to enter a selection of the user-desired letter and cause the user-selected letter to appear in the input field **112** of the virtual keyboard **100**. Similarly, after a user uses the second analog stick **134** to move the second cursor **119** to the user-desired letter of the second keyboard portion **104**, the user presses one of the button inputs **124** (e.g., R1) of the hand-held controller **130** (which may be located on a right-hand side of the hand-held controller **130** just like the second analog stick **134**) to enter a selection of the user-desired letter and cause this letter to appear in the input field **112** of the virtual keyboard **100**.

[0072] Notably, the exemplary virtual keyboard **100** illustrated in FIG. 2 includes a character field **122**, which visually indicates both the function (e.g., space bar) of the character field **122** (in this case, by a bracket representing a space bar) and the button (in this case, the triangle button input **124**) of the controller **130** that executes this particular function. In some embodiments, the first and second analog sticks **132**, **134** may themselves be pressable, and the controller **130** may be configured such that, after the user navigates the first and second cursors **118**, **119** via their respective first and second analog sticks **132**, **134** to the user-desired letter, instead of pressing a separate button input **124** (e.g., L1 or R1) of the controller **130**, the user may press the first analog stick **132** to select the letter underlying the first cursor **118** and the second analog stick **134** to select the letter underlying the second cursor **119**.

[0073] In certain embodiments, the first and second analog sticks **132**, **134** are configured to have user-adjustable dead zones, i.e., zones, where directional movement of an analog stick does not cause a responsive action on the display screen **111**. In other words, the dead zone of each of the first and second analog sticks **132**, **134** may be defined as an area (or an imaginary perimeter) around an analog stick **132**, **134**, where movement of the analog stick **132**, **134** does not input a command into the controller **130** until the analog stick **132**, **134** is moved by the user out of the dead zone.

[0074] The dead zone of a directional analog stick of a hand-held controller **130** may be expressed in degrees. For example, if the dead zone of the first analog stick **132** is 20 degrees, movement of the first analog stick **132** up to 20 degrees relative to the vertical would not cause the first cursor **118** to move on the first keyboard portion **102**. On the other hand, the movement of the first analog stick **132** by 21 or more degrees relative to the vertical would cause the first cursor **118** to move on the first keyboard portion **102** in a direction corresponding to the movement of the direction of movement of the first analog stick **132**.

[0075] In certain embodiments, the hand-held controller **130** is configured such that, when the user holds the first analog stick **132** outside of its respective dead zone, a first delay timer is triggered to delay the movement of the first cursor **118** between adjacent ones of the letters of the first keyboard portion **102** of the virtual keyboard **100** for a predetermined period of time. Similarly, in some implementations, the hand-held controller **130** is configured such that, when the user holds the second analog stick **132** outside of its respective dead zone, a second delay timer is triggered to delay the movement of the second cursor **119** between adjacent ones of the letters of the second keyboard portion **104** of the virtual keyboard **100** for a predetermined period of time.

[0076] The delay timers associated with the first and second analog sticks **132**, **134** may be set independently from one another and may be identical or different from one another. In one embodiment, the hand-held controller **130** may be configured such that the length of the first and second delay timers decreases in proportion to an increasing number of adjacent letters to be moved across by the first and second cursors **118**, **119** in response to a directional tilt of the first and second analog sticks **132**, **134** relative to the vertical. The aim of this feature is to prevent the cursors **118**, **119** from moving too fast across adjacent letters of their respective first and second

keyboard portions **102**, **104**, thereby reducing the chances that the directional movement of the first and second analog sticks **132**, **134** is too fast to permit the user to stop the first and second cursor **118**, **119** on a desired letter instead of going past it. This feature is described in more detail in application Ser. No. _____, filed on the same date as the present application, entitled "ON-SCREEN, SPLIT VIRTUAL KEYBOARDS," and identified by Attorney Docket No. 158447 [SIEA23116US00], the entire disclosure of which is hereby fully incorporated by reference herein in its entirety.

[0077] FIG. **8** shows an exemplary embodiment of a method **500** of providing a virtual keyboard **100**. The method **500** includes displaying a virtual keyboard **100** on a display **111** such that the virtual keyboard **100** is split into a first keyboard portion **102** and a second keyboard portion **104**, with the first keyboard portion **102** including an inner zone **103** and an outer zone **105**, and the second keyboard portion **104** including an inner zone **103** and an outer zone **105** (step **510**). As discussed above, in some embodiments, the display **111** may be a stand-alone display such as a television, a monitor, etc. In other embodiments, the display **111** may be incorporated into a computing device **150**, which may include but is not limited to a hand-held gaming console, a tablet, a laptop, a mobile phone, etc.

[0078] The exemplary illustrated method **500** further includes generating first signals pertaining to selection of a character **120** on the first keyboard portion **102** in response to a user interacting with one or more control inputs in a first group of control inputs (e.g., a first analog stick **132**) on a handheld controller **130** (step **520**). In addition, the method **500** includes generating second signals pertaining to selection of a character **120** on the second keyboard portion **104** in response to the user interacting with one or more control inputs in a second group of control inputs (e.g., a second analog stick **134**) on the handheld controller **130**. (step **530**)

[0079] In some embodiments, one or more of the embodiments, methods, approaches, schemes, and/or techniques described above may be implemented in one or more computer programs or software applications executable by a processor-based apparatus or system. By way of example, such processor-based system may comprise a smartphone, tablet computer, virtual reality (VR), augmented reality (AR), or mixed reality (MR) system, entertainment system, game console, mobile device, computer, workstation, gaming computer, desktop computer, notebook computer, server, graphics workstation, client, portable device, pad-like device, communications device or equipment, etc. Such computer program(s) or software may be used for executing various steps and/or features of the above-described methods, schemes, and/or techniques. That is, the computer program(s) or software may be adapted or configured to cause or configure a processor-based apparatus or system to execute and achieve the functions described herein. For example, such computer program(s) or software may be used for implementing any embodiment of the above-described methods, steps, techniques, schemes, or features. As another example, such computer program(s) or software may be used for implementing any type of tool or similar utility that uses any one or more of the above-described embodiments, methods, approaches, schemes, and/or techniques. In some embodiments, one or more such computer programs or software may comprise a VR, AR, or MR application, communications application, object positional tracking application, a tool, utility, application, computer simulation, computer game, video game, role-playing game (RPG), other computer simulation, or system software such as an operating system, BIOS, macro, or other utility. In some embodiments, program code macros, modules, loops, subroutines, calls, etc., within or without the computer program(s) may be used for executing various steps and/or features of the above-described methods, schemes and/or techniques. In some embodiments, such computer program(s) or software may be stored or embodied in a non-transitory computer readable storage or recording medium or media, such as a tangible computer readable storage or recording medium or media. In some embodiments, such computer program(s) or software may be stored or embodied in transitory computer readable storage or recording medium or media, such as in one or more transitory forms of signal transmission (for example, a propagating electrical or

electromagnetic signal).

[0080] Therefore, in some embodiments the present invention provides a computer program product comprising a medium for embodying a computer program for input to a computer and a computer program embodied in the medium for causing the computer to perform or execute steps comprising any one or more of the steps involved in any one or more of the embodiments, methods, approaches, schemes, and/or techniques described herein. For example, in some embodiments the present invention provides one or more non-transitory computer readable storage mediums storing one or more computer programs adapted or configured to cause a processor-based apparatus or system to execute steps comprising any one or more of the embodiments, methods, approaches, schemes, and/or techniques described herein.

[0081] While the invention herein disclosed has been described by means of specific embodiments and applications thereof, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope of the invention set forth in the claims.

Claims

1. A method comprising: displaying a keyboard on a display, wherein the keyboard is split into: a first keyboard portion including an inner zone including one or more first letters of an alphabet and an outer zone including a first group of letters of the alphabet that are positioned to surround the one or more first letters included in the inner zone of the first keyboard portion with even spacing, the first group of letters being different than the one or more first letters; and a second keyboard portion including an inner zone including one or more second letters of the alphabet and an outer zone including a second group of letters of the alphabet that are positioned to surround the one or more second letters included in inner zone of the second keyboard portion with even spacing, the second group of letters being different than the one or more second letters; generating first signals pertaining to selection of a letter on the first keyboard portion in response to a user interacting with one or more control inputs in a first group of control inputs on a handheld controller; and generating second signals pertaining to selection of a letter on the second keyboard portion in response to the user interacting with one or more control inputs in a second group of control inputs on the handheld controller.
2. The method of claim 1, wherein: the first signals cause a first cursor to move within the first keyboard portion and cause the letter in the first keyboard portion to be selected; and the second signals cause a second cursor to move within the second keyboard portion and cause the letter in the second keyboard portion to be selected.
3. The method of claim 1, wherein the first group of letters of the alphabet of the outer zone of the first keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the first keyboard portion, and wherein the second group of letters of the alphabet of the outer zone of the second keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the second keyboard portion.
4. The method of claim 1, wherein: the first group of control inputs is located on a left side of the handheld controller; and the second group of control inputs is located on a right side of the handheld controller.
5. The method of claim 1, wherein: the user interacting with one or more control inputs in the first group of control inputs on the handheld controller comprises the user interacting with a first analog control input; and the user interacting with one or more control inputs in the second group of control inputs on the handheld controller comprises the user interacting with a second analog control input.
6. The method of claim 1, wherein the one or more control inputs in the first group of control inputs and the one or more control inputs in the second group of control inputs are respectively configured to allow a first cursor on the first keyboard portion and a second cursor on the second

keyboard portion to be moved substantially simultaneously.

7. The method of claim 1, wherein: the inner zone of each of the first and second keyboards includes one letter and the outer zone of each of the first and second keyboards includes twelve letters; or the inner zone of each of the first and second keyboards includes at least two letters and the outer zone of each of the first and second keyboards includes at most eleven letters.

8. A non-transitory computer readable storage medium storing one or more computer programs configured to cause a processor-based system to execute steps comprising: displaying a keyboard on a display, wherein the keyboard is split into: a first keyboard portion including an inner zone including one or more first letters of an alphabet and an outer zone including a first group of letters of the alphabet that are positioned to surround the one or more first letters included in inner zone of the first keyboard portion with even spacing, the first group of letters being different than the one or more first letters; and a second keyboard portion including an inner zone including one or more second letters of the alphabet and an outer zone including a second group of letters of the alphabet that are positioned to surround the one or more second letters included in the inner zone of the second keyboard portion with even spacing, the second group of letters being different than the one or more second letters; generating first signals pertaining to selection of a letter on the first keyboard portion in response to a user interacting with one or more control inputs in a first group of control inputs on a handheld controller; and generating second signals pertaining to selection of a letter on the second keyboard portion in response to the user interacting with one or more control inputs in a second group of control inputs on the handheld controller.

9. The non-transitory computer readable storage medium of claim 8, wherein: the first signals cause a first cursor to move within the first keyboard portion and cause the letter in the first keyboard portion to be selected; and the second signals cause a second cursor to move within the second keyboard portion and cause the letter in the second keyboard portion to be selected.

10. The non-transitory computer readable storage medium of claim 8, wherein the first group of letters of the alphabet of the outer zone of the first keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the first keyboard portion, and wherein the second group of letters of the alphabet of the outer zone of the second keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the second keyboard portion.

11. The non-transitory computer readable storage medium of claim 8, wherein: the first group of control inputs is located on a left side of the handheld controller; and the second group of control inputs is located on a right side of the handheld controller.

12. The non-transitory computer readable storage medium of claim 8, wherein: the user interacting with one or more control inputs in the first group of control inputs on the handheld controller comprises the user interacting with a first analog control input; and the user interacting with one or more control inputs in the second group of control inputs on the handheld controller comprises the user interacting with a second analog control input.

13. The non-transitory computer readable storage medium of claim 8, wherein the one or more control inputs in the first group of control inputs and the one or more control inputs in the second group of control inputs are respectively configured to allow a first cursor on the first keyboard portion and a second cursor on the second keyboard portion to be moved substantially simultaneously.

14. The non-transitory computer readable storage medium of claim 8, wherein: the inner zone of each of the first and second keyboards includes one letter and the outer zone of each of the first and second keyboards includes twelve letters; or the inner zone of each of the first and second keyboards includes at least two letters and the outer zone of each of the first and second keyboards includes at most eleven letters.

15. A system, comprising: a display; a handheld controller; and a processor-based system in communication with the display and the handheld controller and configured to execute steps

comprising: displaying a keyboard on a display, wherein the keyboard is split into: a first keyboard portion including an inner zone including one or more first letters of an alphabet and an outer zone including a first group of letters of the alphabet that are positioned to surround the one or more first letters included in the inner zone of the first keyboard portion with even spacing, the first group of letters being different than the one or more first letters; and a second keyboard portion including an inner zone including one or more second letters of the alphabet and an outer zone including a second group of letters of the alphabet that are positioned to surround the one or more second letters included in the inner zone of the second keyboard portion with even spacing, the first group of letters being different than the one or more first letters; generating first signals pertaining to selection of a letter on the first keyboard portion in response to a user interacting with one or more control inputs in a first group of control inputs on a handheld controller; and generating second signals pertaining to selection of a letter on the second keyboard portion in response to the user interacting with one or more control inputs in a second group of control inputs on the handheld controller.

16. The system of claim 15, wherein: the first signals cause a first cursor to move within the first keyboard portion and cause the letter in the first keyboard portion to be selected; and the second signals cause a second cursor to move within the second keyboard portion and cause the letter in the second keyboard portion to be selected.

17. The system of claim 15, wherein the first group of letters of the alphabet of the outer zone of the first keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the first keyboard portion, and wherein the second group of letters of the alphabet of the outer zone of the second keyboard portion is positioned to encircle the one or more first letters of the alphabet of the inner zone of the second keyboard portion.

18. The system of claim 15, wherein: the first group of control inputs is located on a left side of the handheld controller; and the second group of control inputs is located on a right side of the handheld controller.

19. The system of claim 15, wherein: the user interacting with one or more control inputs in the first group of control inputs on the handheld controller comprises the user interacting with a first analog control input; and the user interacting with one or more control inputs in the second group of control inputs on the handheld controller comprises the user interacting with a second analog control input.

20. The system of claim 15, wherein the one or more control inputs in the first group of control inputs and the one or more control inputs in the second group of control inputs are respectively configured to allow a first cursor on the first keyboard portion and a second cursor on the second keyboard portion to be moved substantially simultaneously.

21. The system of claim 15, wherein: the inner zone of each of the first and second keyboards includes one letter and the outer zone of each of the first and second keyboards includes twelve letters; or the inner zone of each of the first and second keyboards includes at least two letters and the outer zone of each of the first and second keyboards includes at most eleven letters.

22. The method of claim 1, wherein the user interacting with the one or more control inputs in the first group of control inputs on the handheld controller comprises the user selecting one or more of the first letters of the alphabet in the inner zone of the first keyboard portion using a particular control input that is different than a directional input of an analog joystick.
