

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285935

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Janssen; Johannes Henricus Johanna et al.

ELECTRONIC DEVICE WITH WARPAGE MITIGATION AND METHOD THEREFOR

Abstract

An electronic device with warpage mitigation is provided. The electronic device includes an electronic component mounted on a first major side of a device substrate and interconnected with a plurality of conductive traces of the device substrate. A heat sink having a raised feature is affixed with a second major side of the device substrate such that the raised feature is located below the electronic component.

Inventors: Janssen; Johannes Henricus Johanna (Venray, NL), Offermann; Bernd (Hamburg, DE)

Applicant: NXP B.V. (Eindhoven, NL)

Family ID: 94284110

Appl. No.: 18/598009

Filed: March 07, 2024

Publication Classification

Int. Cl.: H01L23/40 (20060101); H01L21/48 (20060101); H01L23/00 (20060101); H01L23/13 (20060101)

U.S. Cl.:

CPC H01L23/4006 (20130101); H01L21/4871 (20130101); H01L23/13 (20130101); H01L2023/4062 (20130101); H01L24/48 (20130101); H01L2224/48227 (20130101); H01L2924/3511 (20130101)

Background/Summary

BACKGROUND

Field

[0001] This disclosure relates generally to semiconductor device packaging, and more specifically, to electronic devices with warpage mitigation and method of forming the same.

Related Art

[0002] Today, there is an increasing trend to include sophisticated electronic devices in products and systems that are subject to extreme environmental conditions. These sophisticated electronic devices may include features for specific applications which may impact the configuration of the electronic device packages, for example. For some features and applications, the configuration of the electronic device packages may be susceptible to lower reliability, lower performance, and higher product or system costs. Accordingly, significant challenges exist in accommodating these features and applications while minimizing the impact on electronic devices' reliability, performance, and costs.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] The present invention is illustrated by way of example and is not limited by the accompanying figures, in which like references indicate similar elements. Elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale.

[0004] FIG. 1 illustrates, in a simplified top-side-up cross-sectional view, an example electronic device with warpage mitigation at a stage of manufacture in accordance with an embodiment.

[0005] FIG. 2A, FIG. 2B, FIG. 3 and FIG. 4 illustrate, in simplified cross-sectional views, example embodiments of an electronic component of the electronic device in accordance with an embodiment.

[0006] FIG. 5 illustrates, in a simplified cross-sectional view, an alternative example electronic device with warpage mitigation at a stage of manufacture in accordance with an embodiment.

[0007] FIG. 6 illustrates, in a simplified flow diagram view, an example method of assembling the example electronic device in accordance with an embodiment.

DETAILED DESCRIPTION

[0008] Generally, there is provided, an electronic device having warpage mitigation. The electronic device may be configured for operation and/or storage at cryogenic temperatures (e.g., -153°C . and lower). The electronic device includes an electronic component mounted on a first side of a device substrate and interconnected with conductive features of the device substrate. The device substrate with mounted electronic component is attached to a heat sink. The heat sink includes a raised feature configured to mitigate warpage of the device substrate when subjected to cryogenic temperatures. The raised feature is in thermal contact with a second side of the device substrate directly opposite of the mounted electronic component. By forming the heat sink with raised feature in this manner, the heat sink substantially compensates for potential warpage caused by inherent mismatches in coefficient of thermal expansion (CTE) between the device substrate and the electronic device. Accordingly, the device substrate remains in thermal contact with the heat sink during exposure to cryogenic temperatures where extreme mismatches in CTE may occur. Maintaining thermal contact and conduction between the device substrate and the heat sink provide improved thermal dissipation, device performance and reliability across various temperature ranges including cryogenic temperatures.

[0009] FIG. 1 illustrates, in a simplified top-side-up plan view, an example electronic device **100** with warpage mitigation at a stage of manufacture in accordance with an embodiment. At this stage, the electronic device **100** includes an electronic component **102** mounted on a device substrate **104**, and the device substrate affixed to a heat sink **120**. The electronic component **102** is

mounted on a first major side of the device substrate **104** and interconnected with a plurality of conductive traces (not shown) of the device substrate. The term “conductive,” as used herein, generally refers to electrical conductivity unless otherwise described. The electronic component **102** may include circuitry in the form of an integrated circuit suitable for operation at cryogenic temperatures. The heat sink **120** is affixed on a second major side of the device substrate **104** such that a raised feature **108** is located directly below the electronic component **102**. The device substrate **104** may be affixed to the heat sink **120** by way of fasteners **110**, for example. The size and shape of the electronic component **102** and corresponding raised feature **108** of the heat sink **120** in this embodiment are chosen for illustration purposes. Example implementations of the electronic component **102** are depicted in FIG. 2A, FIG. 2B, FIG. 3 and FIG. 4.

[0010] In this embodiment, the heat sink **120** includes a bulk portion **106** and the raised feature **108**. The raised feature **108** extends vertically above the bulk portion **106**. The raised feature may be formed as a plateau-like structure having a flat top surface **122** that is higher than surrounding top surface areas **124** of bulk portion **106** of the heat sink **120**. For example, the plane at the top surface **122** of the raised feature **108** is located above the plane at the top surface **124** of the bulk portion **106** of the heat sink by a predetermined height **112**. In this embodiment, the predetermined height dimension **112** may be in a range of approximately 500 microns to 2 millimeters. The heat sink **120** may be formed from a suitable material (e.g., copper, aluminum, diamond) or alloys thereof having good heat dissipation properties. In this embodiment, the raised feature **108** and the bulk portion **106** of the heat sink **120** are formed from a same contiguous material such as copper. In some embodiments, the raised feature **108** of the heat sink **120** may be formed separately and subsequently attached to the bulk portion **106** by way of a thermally conductive adhesive or solder.

[0011] In this embodiment, the area of the top surface **122** of the raised feature **108** is approximately in a range of 50% to 75% of the area of the bottom surface of the electronic device **102**. By way of example for illustrative purposes, the raised feature **108** may be formed as a substantially square shape having a width dimension **116** and a top surface area. In this example, the top surface area of the raised feature **108** is substantially equal to the dimension **116** multiplied by dimension **116** or (dimension **116**) ². Likewise, the electronic device **102** may be formed as a substantially square shape having a device width dimension **118** and a bottom surface area. The bottom surface area of the electronic device is substantially equal to the dimension **118** multiplied by dimension **118** or (dimension **118**) ². Accordingly in this example, the width dimension **118** of the electronic device **102** may be approximately in a range of 1.15 to 1.4 times greater than the width dimension **116** of the raised feature **108**. Because the area of the top surface **122** of the raised feature **108** is substantially smaller than the area of the bottom surface of the electronic device **102**, an outer perimeter portion of the electronic device overhangs the raised feature **108** by a predetermined overhang dimension **114**. It may be desirable for the electronic device **102** to be aligned over the raised feature **108** such that the overhang dimension **114** is symmetrical or similar around the perimeter for optimal heat dissipation.

[0012] The device substrate **104** may be characterized as a laminate printed circuit board (PCB) in this embodiment. The device substrate **104** may be formed from as a plurality of electrically conductive and/or thermally conductive features (not shown) separated by a non-conductive material. In this embodiment, the device substrate **104** is formed from materials suitable for being subjected to cryogenic temperatures. The device substrate **104** with mounted electronic component **102** is pretensioned **126** (e.g., stretched) when affixed to the heat sink **120** in a manner without compromising the mechanical integrity of the device substrate. Because the device substrate **104** is pretensioned when affixed to the heat sink **120**, a compression results between the device substrate **104** and raised feature **108** of the heat sink. In this embodiment, the device substrate **104** is configured to remain in thermal contact with the raised feature **108** of the heat sink **120** during exposure to cryogenic temperatures. In this embodiment, an air gap may exist between portions of the of the device substrate **104** and top surface portions of the bulk region **106** surrounding the

raised feature **108** of the heat sink **120**. In this embodiment a portion of the device substrate **104** is disposed directly between the electronic component **102** and the heat sink **120**.

[0013] FIG. 2A and FIG. 2B illustrate, in simplified cross-sectional views, example embodiments of an electronic component **200** of the electronic device **100** depicted in FIG. 1 in accordance with an embodiment. In the embodiments of FIG. 2A and FIG. 2B, the electronic component **200** includes a semiconductor die **202** mounted on the device substrate **104** and interconnected with conductive traces **208** of the device substrate **104**. A backside of the semiconductor die **202** is affixed to the device substrate **104** by way of a die attach adhesive or film (not shown). Bond pads **204** of the semiconductor die **202** are interconnected with the traces **208** by way of bond wires **206**. In the embodiment depicted in FIG. 2B, the semiconductor die **202** and interconnecting bond wires **206** are over-molded with the encapsulant (e.g., epoxy molding compound) **210** by way of a molding process, for example.

[0014] The semiconductor die **202** has an active side (e.g., major side having circuitry, bond pads) and the backside (e.g., major side opposite of the active side). As depicted in the cross-sectional views of FIG. 2A and FIG. 2B, the semiconductor die **202** is in an active-side-up orientation, for example. In this embodiment, the semiconductor die **202** is configured for operation at cryogenic temperatures and may be formed from any suitable semiconductor material, such as silicon, germanium, gallium arsenide, gallium nitride, and the like. The semiconductor die **202** may further include digital circuits, analog circuits, RF circuits, power circuits, memory, processor, sensor, the like, and combinations thereof at the active side.

[0015] FIG. 3 illustrates, in a simplified cross-sectional view, another example embodiment of an electronic component **300** of the electronic device **100** depicted in FIG. 1 in accordance with an embodiment. In this embodiment, the electronic component **300** includes a semiconductor die **302** mounted on a spacer **308** which is affixed to the device substrate **104**. The spacer **308** may be affixed to the device substrate **104** by way of a die attach adhesive or film (not shown). The spacer **308** may be formed from a suitable semiconductor material, such as silicon, sapphire, germanium, gallium arsenide, gallium nitride, and the like. It may be desirable for the thermal and mechanical properties of the spacer **308** to be similar to those of the semiconductor die **302**. In some embodiments, the spacer **308** may be electrically conductive. The semiconductor die **302** is affixed to the device substrate **104** by way of a die attach adhesive or film (not shown). Bond pads **304** of the semiconductor die **302** are interconnected with traces **310** of the device substrate **104** by way of bond wires **306**.

[0016] The semiconductor die **302** has an active side (e.g., major side having circuitry, bond pads) and a backside (e.g., major side opposite of the active side). As depicted in the cross-sectional view of FIG. 3, the backside of the semiconductor die **302** is mounted on the spacer **308** in an active-side-up orientation, for example. In this embodiment, the semiconductor die **302** is configured for operation at cryogenic temperatures and may be formed from any suitable semiconductor material, such as silicon, germanium, gallium arsenide, gallium nitride, and the like. The semiconductor die **302** may further include digital circuits, analog circuits, RF circuits, power circuits, memory, processor, sensor, the like, and combinations thereof at the active side.

[0017] FIG. 4 illustrates, in a simplified cross-sectional view, another example embodiment of an electronic component **400** of the electronic device **100** depicted in FIG. 1 in accordance with an embodiment. In this embodiment, the electronic component **400** includes a semiconductor die **402** mounted on an interposer **406**. The interposer **406** is affixed to a spacer **412** which is affixed on the device substrate **104**. The interposer **406** may be formed from a silicon die, PCB or PCB-like substrate, for example. The interposer **406** is configured to provide conductive connections between the semiconductor die **402** and other active and/or passive devices (not shown) of the electronic component **400**. For example, bond pads **404** of the semiconductor die **402** are interconnected with interposer traces **408** by way of bond wires **414** and interposer traces **410** are interconnected with conductive traces **418** of the device substrate **104** by way of bond wires **416**. In

addition, the interposer **406** is configured to provide common surface for mounting the semiconductor die **402** and other active and/or passive devices of the electronic component **400**. The interposer traces **408** and **410** may be interconnected with one another and may be interconnected with the other devices of the electronic component **400**. In this embodiment, the semiconductor die **402** is interconnected with the device substrate **104** by way of the interposer **406** and bond wires **414** and **416**.

[0018] The semiconductor die **402** has an active side (e.g., major side having circuitry, bond pads) and a backside (e.g., major side opposite of the active side). As depicted in the cross-sectional view of FIG. 4, the backside of the semiconductor die **402** is mounted on the interposer **406** in an active-side-up orientation, for example. In this embodiment, the semiconductor die **402** is configured for operation at cryogenic temperatures and may be formed from any suitable semiconductor material, such as silicon, germanium, gallium arsenide, gallium nitride, and the like. The semiconductor die **402** may further include digital circuits, analog circuits, RF circuits, power circuits, memory, processor, sensor, the like, and combinations thereof at the active side.

[0019] FIG. 5 illustrates, in a simplified top-side-up plan view, an alternative example electronic device **500** with warpage mitigation at a stage of manufacture in accordance with an embodiment. At this stage, the electronic device **500** includes an electronic component **502** mounted on a device substrate **504**, and the device substrate affixed to a heat sink **518**. The electronic component **502** is mounted on a first major side of the device substrate **504** and interconnected with a plurality of conductive traces (not shown) of the device substrate. Example implementations of the electronic component **102** depicted in FIG. 2A, FIG. 2B, FIG. 3 and FIG. 4 may be applicable to the electronic component **502**, for example.

[0020] The heat sink **520** is affixed on a second major side of the device substrate **504**. In this embodiment, the heat sink **518** includes a bulk portion **506** and an alternative raised feature **508**. The raised feature **508** extends vertically above the bulk portion **506**. The raised feature **508** may be formed as a pyramid-like or conical like shape having a flat top surface **514** that is higher than a plane of the surrounding top surface areas **516** of bulk portion **506**. For example, the plane at the top surface **514** of the raised feature **508** is located above the plane at the outer perimeter top surface areas **516** of the bulk portion **506** of the heat sink **518** by a predetermined height **512**. In this embodiment, the predetermined height dimension **512** may be in a range of approximately 500 microns to 2 millimeters. It may be desirable for the electronic device **502** to be aligned directly over the top surface **514** of the raised feature **508** for optimal heat dissipation. The heat sink **518** may be formed from suitable materials or alloys thereof having good heat dissipation properties at cryogenic temperatures. The device substrate **504** may be affixed to the heat sink **518** by way of fasteners **510**, for example.

[0021] The device substrate **504** may be characterized as a laminate PCB in this embodiment. The device substrate **504** may be formed from as a plurality of electrically conductive and/or thermally conductive features (not shown) separated by a non-conductive material. In this embodiment, the device substrate **504** is formed from materials suitable for 5 cryogenic temperatures. The device substrate **504** with mounted electronic component **502** is pretensioned **520** (e.g., stretched) when affixed to the heat sink **518**. Because the device substrate **504** is pretensioned when affixed to the heat sink **518**, a compression results between the device substrate **504** and raised feature **508** of the heat sink. In this embodiment, the device substrate **504** is configured to remain in thermal contact with the raised feature **508** of the heat sink **518** during exposure to cryogenic temperatures. In this embodiment a portion of the device substrate **504** is disposed directly between the electronic component **502** and the heat sink **518**.

[0022] FIG. 6 illustrates, in a simplified flow diagram view, an example method **600** of assembling an example electronic device in accordance with an embodiment. The method **600** is consistent with the example electronic device **100** depicted in FIG. 1 and the alternative example electronic device **500** depicted in FIG. 5.

[0023] At step **602**, mount electronic component on device substrate. In this embodiment, the electronic component is mounted on a first major side of the device substrate and interconnected with a plurality of conductive traces of the device substrate. Example embodiments of the electronic component are depicted in FIG. 2A, FIG. 2B, FIG. 3 and FIG. 4. The device substrate may be formed as a laminate PCB having a plurality of electrically conductive and/or thermally conductive features separated by a non-conductive material, for example. In this embodiment, the electronic component and the device substrate are configured for operation at cryogenic temperatures.

[0024] At step **604**, pretension device substrate on heat sink. In this embodiment, the device substrate with mounted electronic component is pretensioned on the heat sink such that pressure is exerted between the raised feature and the device substrate. The pressure exerted between the raised feature and the device substrate forms a compression between the raised feature and the device substrate, for example. In this embodiment, the device substrate subtly deforms across the heat sink without adversely affecting the integrity of the device substrate or mounted electronic component when pretensioned.

[0025] At step **606**, affix device substrate to heat sink. In this embodiment, the pretensioned device substrate with mounted electronic component is attached to the heat sink in a manner that results in a compression between the raised feature of the heat sink and the device substrate. The device substrate may be attached to the heat sink by way of fasteners, for example. By having the compression between the raised feature of the heat sink and the device substrate in this embodiment, the device substrate is configured to remain in thermal contact with the raised feature of the heat sink during exposure to cryogenic temperatures. Accordingly, potential device substrate warpage due to inherent mismatches in the CTE of the electronic device are substantially minimized.

[0026] Generally, there is provided, an electronic device including a device substrate having a plurality of conductive traces; an electronic component mounted on a first major side of the device substrate and interconnected with the plurality of conductive traces; and a heat sink having a raised feature, the heat sink affixed on a second major side of the device substrate such that the raised feature is located directly below the electronic component. The device substrate may be pretensioned before the heat sink is affixed on the second major side of the device substrate. The heat sink may be affixed on the second major side of the device substrate by way of one or more fasteners. The electronic component may overlap the raised feature by a predetermined distance. A top surface of the raised feature may be on a plane above a plane of a bulk portion of the heat sink. The raised feature and the bulk portion of the heat sink may be formed from a same contiguous material. The raised feature may be attached to the bulk portion of the heat sink. The electronic component may include a semiconductor die interconnected with the plurality of conductive traces. The electronic device may be configured for operation at cryogenic temperatures.

[0027] In another embodiment, there is provided, a method including mounting an electronic component on a first major side of a device substrate, the electronic component interconnected with a plurality of conductive traces of the device substrate; and affixing the device substrate on a heat sink, the heat sink having a raised feature in thermal contact with a second major side of the device substrate directly opposite of the electronic component mounted on the first major side of the device substrate. The device substrate may be pretensioned when affixing the device substrate on the heat sink such that pressure is exerted between the raised feature and the device substrate. The device substrate may be configured to remain in thermal contact with the raised feature of the heat sink during exposure to a cryogenic temperature. A width dimension of the electronic component may be greater than a width dimension of the raised feature by a predetermined distance. A top surface of the raised feature in thermal contact with the second major side of the device substrate may extend vertically from a plane of a bulk portion of the heat sink by a predetermined height. The electronic component mounted on the first major side of the device substrate may include a

semiconductor die interconnected with the plurality of conductive traces of the device substrate.

[0028] In yet another embodiment, there is provided, an electronic device including a device substrate having a first major side and a second major side opposite of the first major side, a plurality of conductive traces formed at the first major side of the device substrate; an electronic component mounted on the first major side of the device substrate and interconnected with the plurality of conductive traces; and a heat sink having a raised feature, the heat sink affixed on the second major side of the device substrate such that the raised feature is in thermal contact with the second major side of the device substrate directly opposite of the electronic component mounted on the first major side of the device substrate. A width dimension of the electronic component may be greater than a width dimension of the raised feature by a predetermined distance. A top surface of the raised feature in thermal contact with the second major side of the device substrate may extend vertically from a plane of a bulk portion of the heat sink by a predetermined height. The electronic component mounted on the first major side of the device substrate may include a semiconductor die interconnected with the plurality of conductive traces of the device substrate. The device substrate may be configured to remain in thermal contact with the raised feature of the heat sink during exposure to a cryogenic temperature.

[0029] By now, it should be appreciated that there has been provided an electronic device having warpage mitigation. The electronic device may be configured for operation and/or storage at cryogenic temperatures (e.g., -153°C . and lower). The electronic device includes an electronic component mounted on a first side of a device substrate and interconnected with conductive features of the device substrate. The device substrate with mounted electronic component is attached to a heat sink. The heat sink includes a raised feature configured to mitigate warpage of the device substrate when subjected to cryogenic temperatures. The raised feature is in thermal contact with a second side of the device substrate directly opposite of the mounted electronic component. By forming the heat sink with raised feature in this manner, the heat sink substantially compensates for potential warpage caused by inherent mismatches in CTE between the device substrate and the electronic device. Accordingly, the device substrate remains in thermal contact with the heat sink during exposure to cryogenic temperatures where extreme mismatches in CTE may occur. Maintaining thermal contact and conduction between the device substrate and the heat sink provide improved thermal dissipation, device performance and reliability across various temperature ranges including cryogenic temperatures.

[0030] The terms “front,” “back,” “top,” “bottom,” “over,” “under” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the invention described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein.

[0031] Although the invention is described herein with reference to specific embodiments, various modifications and changes can be made without departing from the scope of the present invention as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of the present invention. Any benefits, advantages, or solutions to problems that are described herein with regard to specific embodiments are not intended to be construed as a critical, required, or essential feature or element of any or all the claims.

[0032] Furthermore, the terms “a” or “an,” as used herein, are defined as one or more than one. Also, the use of introductory phrases such as “at least one” and “one or more” in the claims should not be construed to imply that the introduction of another claim element by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim element to inventions containing only one such element, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an.” The same holds true for

the use of definite articles.

[0033] Unless stated otherwise, terms such as “first” and “second” are used to arbitrarily distinguish between the elements such terms describe. Thus, these terms are not necessarily intended to indicate temporal or other prioritization of such elements.

Claims

1. An electronic device comprising: a device substrate having a plurality of conductive traces; an electronic component mounted on a first major side of the device substrate and interconnected with the plurality of conductive traces; and a heat sink having a raised feature, the heat sink affixed on a second major side of the device substrate such that the raised feature is located directly below the electronic component.
2. The electronic device of claim 1, wherein the device substrate is pretensioned before the heat sink is affixed on the second major side of the device substrate.
3. The electronic device of claim 1, wherein the heat sink is affixed on the second major side of the device substrate by way of one or more fasteners.
4. The electronic device of claim 1, wherein the electronic component overlaps the raised feature by a predetermined distance.
5. The electronic device of claim 1, wherein a top surface of the raised feature is on a plane above a plane of a bulk portion of the heat sink.
6. The electronic device of claim 5, wherein the raised feature and the bulk portion of the heat sink are formed from a same contiguous material.
7. The electronic device of claim 5, wherein the raised feature is attached to the bulk portion of the heat sink.
8. The electronic device of claim 1, wherein the electronic component includes a semiconductor die interconnected with the plurality of conductive traces.
9. The electronic device of claim 1, wherein the electronic device is configured for operation at cryogenic temperatures.
10. A method comprising: mounting an electronic component on a first major side of a device substrate, the electronic component interconnected with a plurality of conductive traces of the device substrate; and affixing the device substrate on a heat sink, the heat sink having a raised feature in thermal contact with a second major side of the device substrate directly opposite of the electronic component mounted on the first major side of the device substrate.
11. The method of claim 10, wherein the device substrate is pretensioned when affixing the device substrate on the heat sink such that pressure is exerted between the raised feature and the device substrate.
12. The method of claim 10, wherein the device substrate is configured to remain in thermal contact with the raised feature of the heat sink during exposure to a cryogenic temperature.
13. The method of claim 10, wherein a width dimension of the electronic component is greater than a width dimension of the raised feature by a predetermined distance.
14. The method of claim 10, wherein a top surface of the raised feature in thermal contact with the second major side of the device substrate extends vertically from a plane of a bulk portion of the heat sink by a predetermined height.
15. The method of claim 10, wherein the electronic component mounted on the first major side of the device substrate includes a semiconductor die interconnected with the plurality of conductive traces of the device substrate.
16. An electronic device comprising: a device substrate having a first major side and a second major side opposite of the first major side, a plurality of conductive traces formed at the first major side of the device substrate; an electronic component mounted on the first major side of the device substrate and interconnected with the plurality of conductive traces; and a heat sink having a raised

feature, the heat sink affixed on the second major side of the device substrate such that the raised feature is in thermal contact with the second major side of the device substrate directly opposite of the electronic component mounted on the first major side of the device substrate.

17. The electronic device of claim 16, wherein a width dimension of the electronic component is greater than a width dimension of the raised feature by a predetermined distance.

18. The electronic device of claim 16, wherein a top surface of the raised feature in thermal contact with the second major side of the device substrate extends vertically from a plane of a bulk portion of the heat sink by a predetermined height.

19. The electronic device of claim 16, wherein the electronic component mounted on the first major side of the device substrate includes a semiconductor die interconnected with the plurality of conductive traces of the device substrate.

20. The electronic device of claim 16, wherein the device substrate is configured to remain in thermal contact with the raised feature of the heat sink during exposure to a cryogenic temperature.
