

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286881

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Madtha; Jivan Joseph et al.

Orchestrating Distribution Of Digital Certificates To An Execution Environment Of A Computing Network

Abstract

A system executes a first testing process utilizing a sandbox sub-environment executing in an execution environment of a computing network to perform a first set of testing operations associated with a new certificate bundle that includes a new CA certificate. Responsive to successful testing via the sandbox sub-environment, the new certificate bundle is installed on a host executing in the execution environment. The system utilizes a testing service executing on the host to perform a second set of testing operations associated with the new certificate bundle. Responsive to successful testing via the testing service executing on the host, the new CA certificate is activated in the execution environment by issuing entity certificates to a set of nodes associated with the host for execution against the new CA certificate.

Inventors: Madtha; Jivan Joseph (Saratoga, CA), Elakhwas; Ayman (Austin, TX), Chau; Bill (Sammamish, WA)

Applicant: Oracle International Corporation (Redwood Shores, CA)

Family ID: 96950004

Assignee: Oracle International Corporation (Redwood Shores, CA)

Appl. No.: 18/599675

Filed: March 08, 2024

Publication Classification

Int. Cl.: H04L9/40 (20220101); H04L9/32 (20060101)

U.S. Cl.:

CPC H04L63/0823 (20130101); H04L9/3263 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates to distribution of digital certificates to network entities of a computing network. More particularly, the present disclosure relates to testing the digital certificates in connection with distribution of digital certificates to the network entities.

BACKGROUND

[0002] A computing network, such as a virtual cloud network, includes network entities that communicate with one another. Communications between network entities may be performed in accordance with a security protocol, whereby network entities authenticate one another by presenting a digital certificate. A digital certificate may be issued to a network entity by a certificate authority (CA). The digital certificate includes a digital signature generated using a private key of the CA that issued the digital certificate. The digital signature can be validated using a CA certificate of the CA that includes a public key corresponding to the private key. When a network entity presents a valid digital certificate to another network entity, the other network entity can trust that it is communicating with the network entity, as opposed to some unknown entity, based on a trust relationship with a CA that issued the digital certificate.

[0003] A certificate bundle includes a set of CA certificates for validating digital certificates issued to network entities. The certificate bundle is distributed to network entities throughout the computing network. New digital certificates are periodically issued to network entities. In some instances, the new digital certificates are issued based on a new CA certificate that supersedes a previous CA certificate. Network entities with the existing certificate bundle, which does not include the new CA certificate, are not able to validate the new digital certificates.

[0004] The content of this background section should not be construed as prior art merely by virtue of its presence in this section.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The embodiments are illustrated by way of example and not by way of limitation in the figures of the accompanying drawings. References to “an” or “one” embodiment in this disclosure are not necessarily to the same embodiment, and refer to at least one embodiment. In the drawings:

[0006] FIGS. 1-4 are block diagrams illustrating patterns for implementing a cloud infrastructure as a service system in accordance with one or more embodiments;

[0007] FIG. 5 is a hardware system in accordance with one or more embodiments;

[0008] FIG. 6A illustrates features of an example system in accordance with one or more embodiments;

[0009] FIG. 6B illustrates features of an example sandbox sub-environment in accordance with one or more embodiments;

[0010] FIG. 6C illustrates features of an example execution environment in accordance with one or more embodiments;

[0011] FIGS. 7A-7C are flowcharts that illustrate example operations pertaining to an example certificate distribution process in accordance with one or more embodiments;

[0012] FIGS. 8A-8C are flowcharts that illustrate example operations pertaining to testing processes that may be executed in connection with a certificate distribution process in accordance with one or more embodiments;

[0013] FIG. 9A is a flowchart that illustrates an example testing process for utilizing a sandbox sub-environment of an execution environment to perform testing operations pertaining to a

certificate bundle in accordance with one or more embodiments;

[0014] FIG. 9B is a flowchart that illustrates an example testing process for utilizing a testing service executing on a network entity in an execution environment to perform testing operations pertaining to a certificate bundle in accordance with one or more embodiments; and

[0015] FIG. 9C is a flowchart that illustrates an example testing process for utilizing a production service executing on a network entity in an execution environment to perform testing operations pertaining to a certificate bundle in accordance with one or more embodiments.

DETAILED DESCRIPTION

[0016] In the following description, for the purposes of explanation, numerous specific details are set forth to provide a thorough understanding. One or more embodiments may be practiced without these specific details. Features described in one embodiment may be combined with features described in a different embodiment. In some examples, well-known structures and devices are described with reference to a block diagram form to avoid unnecessarily obscuring the present disclosure.

[0017] 1. GENERAL OVERVIEW [0018] 2. AUTHENTICATING NETWORK ENTITIES [0019] 3. CLOUD COMPUTING TECHNOLOGY [0020] 4. COMPUTER SYSTEM [0021] 5. ARCHITECTURAL OVERVIEW [0022] 6. EXAMPLE CERTIFICATE DISTRIBUTION PROCESSES [0023] 7. EXAMPLE TESTING PROCESSES [0024] 8. MISCELLANEOUS; EXTENSIONS

1. General Overview

[0025] A system executes a certificate distribution process that incrementally increases exposure to an execution environment of a computing network in response to successful testing processes executed at incremental steps of the certificate distribution process. An example certificate distribution process includes distributing to a computing network a certificate bundle that includes one or more CA certificates for use in authenticating entity certificates issued to network entities of the computing network. Additionally, or alternatively, an example certificate distribution process includes distributing entity certificates to the computing network. The incremental exposure to the execution environment of the computing network may include using a sandbox sub-environment of the execution environment to perform a set of testing operations prior to advancing to a next stage in the certificate distribution process. Additionally, or alternatively, the incremental exposure to the execution environment may include utilizing a testing service installed on a network entity executing in the execution environment to perform a set of testing operations prior to advancing to a next stage in the certificate distribution process. Additionally, or alternatively, the incremental exposure to the execution environment may include utilizing a production service installed on a network entity executing in the execution environment to perform a set of testing operations prior to advancing to a next stage in the certificate distribution process.

[0026] In one example, the system generates a first certificate bundle in an execution environment of the computing network. The first certificate bundle includes a first CA certificate and a second CA certificate. A second certificate bundle that includes a second instance of the second CA certificate is already installed in the execution environment when the system generates the first certificate bundle in the execution environment. In one example, the first certificate bundle is generated in a first portion of the execution environment, and the second certificate bundle is installed in a second portion of the execution environment. The first certificate bundle may be a new certificate bundle that the system generates to replace the second certificate bundle. The first CA certificate may be a new CA certificate that is generated to replace the second CA certificate. The first certificate bundle includes the second CA certificate so that the second CA certificate can continue to be utilized to authenticate entity certificates that were issued from the second CA certificate. In one example, the second CA certificate may be utilized prior to replacing the entity certificates issued from the second CA certificate with new entity certificates issued from the first CA certificate. Additionally, or alternatively, the second CA certificate may be utilized, in at least portion of an execution environment, to authenticate entity certificates issued from the first CA

certificate while the first CA certificate is subject to one or more testing processes as described herein.

[0027] In one example, the system executes a first testing process for utilizing a sandbox sub-environment executing in a first portion of the execution environment to perform a first set of one or more testing operations associated with the first certificate bundle. While executing the first testing process, the first certificate bundle is yet to be installed in the first portion of the execution environment, and the second certificate bundle that includes the second instance of the second CA certificate is installed in the first portion of the execution environment. In response to determining that the first set of one or more testing operations is successful, the system installs the first certificate bundle, including the first CA certificate and the second CA certificate, on a first network entity executing in the first portion of the execution environment. By installing the first certificate bundle in the first portion of the execution environment, the first certificate bundle supersedes the second certificate bundle in the first portion of the execution environment.

[0028] In one example, the system executes a second testing process for utilizing a first testing service executing on the first network entity to perform a second set of one or more testing operations associated with the first certificate bundle. While executing the second testing process, the first CA certificate is yet to be activated in the first portion of the execution environment, and the second CA certificate is active in the first portion of the execution environment. In response to determining that the second set of one or more testing operations is successful, the system activates the first CA certificate in the first portion of the execution environment at least by transmitting a first entity certificate to a second network entity executing in the first portion of the execution environment for authentication against the first CA certificate. The first entity certificate supersedes a second entity certificate previously utilized by the second network entity for authentication against the second CA certificate.

[0029] In one example, the system executes a third testing process for utilizing a production service executing on a third network entity executing in the first portion of the execution environment to perform a third set of one or more testing operations associated with the first certificate bundle. In response to determining that the third set of one or more testing operations is successful, the system removes the second CA certificate from the first portion of the execution environment. The system may remove the second CA certificate from the first portion of the execution environment by generating a third certificate bundle in the execution environment that includes the first CA certificate and that does not include the second CA certificate.

[0030] In one example, upon successfully performing the certificate distribution process in the first portion of the execution environment, the system may perform the certificate distribution process in a second portion of the execution environment. The first portion of the execution environment may correspond to a first availability domain of the computing network and/or to a first set of one or more regions of the computing network. Additionally, or alternatively, the second portion of the execution environment may correspond to a second availability domain of the computing network and/or to a second set of one or more regions of the computing network.

[0031] In one example, the system performs one or more of the testing processes with respect to a plurality of segments of the execution environment prior to advancing to a next stage in the certificate distribution process. A segment of the execution environment may include a plurality of network entities. The plurality of network entities may include a host and a set of one or more nodes. Additionally, or alternatively, the segment of the execution environment may include a particular service, resource, or infrastructure that the system selects for testing. The system may test a plurality of services, resources, or infrastructures prior to advancing to a next stage in the certificate distribution process. Additionally, or alternatively, the system may test a plurality of instances of the particular service, resource, or infrastructure prior to advancing to a next stage in the certificate distribution process.

[0032] In one example, the system utilizes a sandbox sub-environment of the execution

environment to perform a set of testing operations associated with a new certificate bundle prior to distributing the new certificate bundle for installation in the execution environment. The system utilizes the sandbox sub-environment to test the certificate bundle in the execution environment without impacting network entities that are executing in the execution environment.

[0033] The set of testing operations performed utilizing a sandbox sub-environment include installing a first certificate bundle on a first sandbox instance executing in the sandbox sub-environment. The first certificate bundle may include a first CA certificate and a second CA certificate. The set of testing operations performed utilizing the sandbox sub-environment further include a set of one or more testing processes associated with the first certificate bundle. While executing the set of one or more testing processes in the sandbox sub-environment, the second CA certificate is active in the execution environment for authenticating entity certificates issued to network entities based on the second CA certificate. The system executes the set of one or more testing processes at least by utilizing the sandbox instance to perform a first set of one or more testing operations. The first set of one or more testing operations may include receiving, at the sandbox instance, a first entity certificate issued based on the first CA certificate and utilizing the sandbox instance to authenticate the first entity certificate against the first CA certificate. In one example, the system determines, based at least on successfully authenticating the first entity certificate against the first CA certificate, that the first set of one or more testing operations is successful. The system may execute additional sets of testing operations with respect to additional sandbox instances executing in the sandbox sub-environment. In one example, the system utilizes a second sandbox instance to perform a second set of one or more testing operations that include utilizing the second sandbox instance to authenticate a second entity certificate issued based on the first CA certificate. In response to determining that the set of one or more testing processes in the sandbox sub-environment are successful, the system distributes the first certificate bundle to the execution environment.

[0034] In one example, the system utilizes a testing service installed on a network entity that is executing in an execution environment to perform a set of testing operations associated with a new certificate bundle prior to activating a new CA certificate in the new certificate bundle. The system utilizes the testing service to test the new CA certificate on a network entity that is executing in the execution environment when the new CA certificate has not yet been activated in the execution environment.

[0035] The set of testing operations performed utilizing a testing service include installing a first certificate bundle on a first network entity that includes a testing service. The first certificate bundle may include a first CA certificate and a second CA certificate. The set of testing operations performed utilizing the testing service further include a set of one or more testing processes associated with the first certificate bundle. While executing the set of one or more testing processes, the second CA certificate is active in the execution environment for authenticating entity certificates issued to network entities based on the second CA certificate. The system executes the set of one or more testing processes at least by utilizing a first testing service executing on the first network entity to perform a first set of one or more testing operations. The first set of one or more testing operations may include receiving, at the first network entity, a first entity certificate issued based on the first CA certificate and utilizing the first testing service to authenticate the first entity certificate against the first CA certificate. In one example, the system determines, based at least on successfully authenticating the first entity certificate against the first CA certificate, that the first set of one or more testing operations is successful. The system may execute additional sets of testing operations with respect to additional network entities executing in the execution environment. In one example, the system utilizes a second testing service executing on a second network entity to perform a second set of one or more testing operations that include utilizing the second testing service to authenticate a second entity certificate issued to the second network entity based on the first CA certificate. In response to determining that the set of one or more testing processes are

successful, the system activates the first CA certificate in the execution environment at least by transmitting entity certificates to network entities for authentication against the first CA certificate. The entity certificates transmitted to network entities for authentication against the first CA certificate supersede the entity certificates issued to network entities based on the second CA certificate.

[0036] In one example, the system utilizes a production service installed on a network entity that is executing in an execution environment to perform a set of testing operations associated with a new certificate bundle. The testing operations that utilize the production service may be performed for a first portion of the execution environment where the new CA certificate is active, while the new CA certificate is yet to be activated in a second portion of the execution environment. The system utilizes the production service in the first portion of the execution environment to test the new CA certificate in an active state prior to activating the new CA certificate in the second portion of the execution environment.

[0037] The set of testing operations performed utilizing a production service include installing a first certificate bundle on a first network entity that includes a production service. The first certificate bundle may include a first CA certificate and a second CA certificate. The set of testing operations performed utilizing the production service further include a set of one or more testing processes associated with the first certificate bundle. While executing the set of one or more testing processes, the second CA certificate is active in the execution environment for authenticating entity certificates issued to network entities based on the second CA certificate. The system executes the set of one or more testing processes at least by utilizing a first production service executing on the first network entity to perform a first set of one or more testing operations. The first set of one or more testing operations may include receiving, at the first network entity, a first entity certificate issued based on the first CA certificate and utilizing the first production service to authenticate the first entity certificate against the first CA certificate. In one example, the system determines, based at least on successfully authenticating the first entity certificate against the first CA certificate, that the first set of one or more testing operations is successful. The system may execute additional sets of testing operations with respect to additional network entities executing in the execution environment. The network entities that the system utilizes to perform the testing operations utilizing a production service may be the same or different from the network entities that the system utilizes to perform the testing operations utilizing a testing service. In one example, the system utilizes a second production service executing on a second network entity to perform a second set of one or more testing operations that include utilizing the second production service to authenticate a second entity certificate issued to the second network entity based on the first CA certificate. In response to determining that the set of one or more testing processes are successful, the system removes the second CA certificate from the execution environment.

[0038] One or more embodiments described in this Specification and/or recited in the claims may not be included in this General Overview section.

2. Authenticating Network Entities

[0039] Network entities may utilize the CA certificates to authenticate other network entities associated with the virtual cloud network. The CA certificates that are utilized to authenticate network entities may be stored in a certificate bundle. In one example, communications between network entities may be conducted according to a security protocol. The security protocol may include authenticating a network entity based on an entity certificate issued to the network entity by a CA, for example, prior to establishing communications with the network entity.

[0040] One or more embodiments may include techniques described in U.S. patent application Ser. No. 18/354,498, filed Jul. 18, 2023 (the '498 Application). The entirety of the '498 Application is incorporated herein by reference. In one example, one or more embodiments may include one or more systems, components, and/or operations pertaining to validating network entity certificate chains as described in the '498 Application.

[0041] In one example, the entity certificate and a CA certificate corresponding to the CA that issued the entity certificate may represent at least a portion of a certificate chain. The certificate chain may include the CA certificate and one or more subordinate certificates, including the entity certificate issued by the CA based on the CA certificate. To authenticate the network entity, one or more signature-key pairs in the certificate chain are validated.

[0042] In one example, a top-level CA may issue the entity certificate. In this case, the certificate chain may include one signature-key pair—that is, the digital signature of the top-level CA in the entity certificate, and the public key of the top-level CA. Such a top-level CA is sometimes referred to as a root CA. In another example, the certificate chain may include signature-key pairs corresponding to multiple CA certificates. For example, a root CA may issue an intermediate CA certificate to an intermediate CA, and the intermediate CA may issue the entity certificate to the network entity. In this case, the certificate chain includes two signature-key pairs—that is, (i) the digital signature of the intermediate CA in the entity certificate and the public key of the intermediate CA, and (ii) the digital signature of the root CA in the intermediate CA certificate and the public key of the root CA.

[0043] As used herein, the term “certificate authority certificate” or “CA certificate” refers to a digital certificate issued by a certificate authority to establish its own identity and authenticity. A certificate authority certificate may be a root CA certificate or an intermediate CA certificate.

[0044] A certificate authority certificate may be used to sign and issue other digital certificates including those used for secure communication between network entities.

[0045] As used herein, the term “certificate authority” or “CA” refers to an entity responsible for issuing and managing digital certificates. The certificate authority verifies the identity of network entities and digitally signs their certificates to attest to their authenticity.

[0046] As used herein, the term “root certificate authority certificate” or “root CA certificate” refers to a top-level CA certificate in a certificate chain or hierarchy. A root CA certificate may be self-issued and/or self-signed by a root certificate authority. As used herein, the term “root CA” refers to a top-level CA in a CA hierarchy. A root CA may issue root CA certificates, intermediate CA certificates, or entity certificates.

[0047] As used herein, the term “intermediate certificate authority certificate” or “intermediate CA certificate” refers to an intermediate-level CA certificate in a certificate chain or hierarchy. An intermediate CA certificate may be issued by a root certificate authority. An intermediate CA certificate is located between a root CA certificate and an entity certificate in a certificate chain or hierarchy. As used herein, the term “intermediate CA” refers to an intermediate-level CA in a CA hierarchy. An intermediate CA may issue entity certificates, for example, pursuant to authority granted to an intermediate certificate authority according to a root certificate authority.

[0048] As used herein, the term “entity certificate” refers to a digital certificate issued to an entity such as a network entity associated with a virtual cloud network. An entity certificate may be used to verify the identity of the entity and enable secure communication between entities such as between network entities in a virtual cloud network. An entity certificate may be issued by a certificate authority, such as root CA or an intermediate certificate authority.

[0049] As used herein, the term “network entity” refers to a device, component, or element within a computer network and/or cloud infrastructure. A network entity may be implemented in hardware and/or software.

[0050] As used herein, the term “subordinate certificate” refers to a digital certificate that was issued based on another digital certificate. An entity certificate is a subordinate certificate to one or more CA certificates that share a certificate chain with the entity certificate including the CA certificate of the CA that issued the entity certificate. An intermediate CA certificate is a subordinate certificate to a root CA certificate of the root CA that issued the intermediate CA certificate.

[0051] In one example, an entity certificate may be an instance principal certificate. As used herein,

the term “instance principal certificate” refers to a digital certificate used to authenticate and secure communication for an instance or VM associated with a virtual cloud network. In one example, instances and VMs may be created, scaled, and terminated dynamically. Instance principal certificates may be associated with an instance or VM during its lifecycle and may be automatically generated and managed by the virtual cloud network infrastructure. An instance principal certificate may provide limited access to communicate with certain network entities. For example, an instance principal may be issued to a network entity, and the limited access of the instance principal may be based on permissions assigned to the network entity.

[0052] As used herein, the term “digital certificate” refers to a digitally signed electronic document that binds a public key to the identity of an entity. A digital certificate may conform to International Telecommunication Union standard X.509. A digital certificate may include an issuer's name, a certificate holder's name, a public key, issuer (CA) information, and expiration date. Digital certificates may be used in various security protocols, such as SSL/TLS, to establish the identity and authenticity of the communicating parties and facilitate secure communication.

3. Cloud Computing Technology

[0053] Infrastructure as a Service (IaaS) is an application of cloud computing technology. IaaS can be configured to provide virtualized computing resources over a public network (e.g., the Internet). In an IaaS model, a cloud computing provider can host the infrastructure components (e.g., servers, storage devices, network nodes (e.g., hardware), deployment software, platform virtualization (e.g., a hypervisor layer), or the like). In some cases, an IaaS provider may also supply a variety of services to accompany those infrastructure components; example services include billing software, monitoring software, logging software, load balancing software, clustering software, etc. Thus, as these services may be policy-driven, IaaS users may be able to implement policies to drive load balancing to maintain application availability and performance.

[0054] In some instances, IaaS customers may access resources and services through a wide area network (WAN), such as the Internet, and can use the cloud provider's services to install the remaining elements of an application stack. For example, the user can log in to the IaaS platform to create virtual machines (VMs), install operating systems (OSs) on the VMs, deploy middleware such as databases, create storage buckets for workloads and backups, and install enterprise software into that VM. Customers can then use the provider's services to perform various functions, including balancing network traffic, troubleshooting application issues, monitoring performance, and managing disaster recovery, etc.

[0055] In some cases, a cloud computing model will involve the participation of a cloud provider. The cloud provider may, but need not, be a third-party service that specializes in providing (e.g., offering, renting, selling) IaaS. An entity may also opt to deploy a private cloud, becoming its own provider of infrastructure services.

[0056] In some examples, IaaS deployment is the process of implementing a new application, or a new version of an application, onto a prepared application server or other similar device. IaaS deployment may also include the process of preparing the server (e.g., installing libraries, daemons, etc.). The deployment process is often managed by the cloud provider below the hypervisor layer (e.g., the servers, storage, network hardware, and virtualization). Thus, the customer may be responsible for handling (OS), middleware, and/or application deployment such as on self-service virtual machines. The self-service virtual machines can be spun up on demand.

[0057] In some examples, IaaS provisioning may refer to acquiring computers or virtual hosts for use, even installing needed libraries or services on them. In most cases, deployment does not include provisioning, and the provisioning may need to be performed first.

[0058] In some cases, there are challenges for IaaS provisioning. There is an initial challenge of provisioning the initial set of infrastructure. There is an additional challenge of evolving the existing infrastructure (e.g., adding new services, changing services, removing services, etc.) after the initial provisioning is completed. In some cases, these challenges may be addressed by enabling

the configuration of the infrastructure to be defined declaratively. In other words, the infrastructure (e.g., what components are needed and how components interact) can be defined by one or more configuration files. Thus, the overall topology of the infrastructure (e.g., what resources depend on one another and how resources work together) can be described declaratively. In some instances, once the topology is defined, a workflow can be generated that creates and/or manages the different components described in the configuration files.

[0059] In some examples, an infrastructure may have many interconnected elements. For example, there may be one or more virtual private clouds (VPCs) (e.g., a potentially on-demand pool of configurable and/or shared computing resources), also known as a core network. In some examples, there may also be one or more inbound/outbound traffic group rules provisioned to define how the inbound and/or outbound traffic of the network will be set up for one or more virtual machines (VMs). Other infrastructure elements may also be provisioned, such as a load balancer, a database, or the like. As more and more infrastructure elements are desired and/or added, the infrastructure may incrementally evolve.

[0060] In some instances, continuous deployment techniques may be employed to enable deployment of infrastructure code across various virtual computing environments. Additionally, the described techniques can enable infrastructure management within these environments. In some examples, service teams can write code that is desired to be deployed to one or more, but often many, different production environments (e.g., across various different geographic locations, sometimes spanning the entire world). In some embodiments, infrastructure and resources may be provisioned (manually and/or using a provisioning tool) prior to deployment of code to be executed on the infrastructure. However, in some examples, the infrastructure that will deploy the code may first be set up. In some instances, the provisioning can be done manually, a provisioning tool may be utilized to provision the resources, and/or deployment tools may be utilized to deploy the code once the infrastructure is provisioned.

[0061] FIG. 1 is a block diagram illustrating an example pattern of an IaaS architecture **100** according to at least one embodiment. Service operators **102** can be communicatively coupled to a secure host tenancy **104** that can include a virtual cloud network (VCN) **106** and a secure host subnet **108**. In some examples, the service operators **102** may be using one or more client computing devices, such as portable handheld devices (e.g., an iPhone®, cellular telephone, an iPad®, computing tablet, a personal digital assistant (PDA)) or wearable devices (e.g., a Google Glass® head mounted display), running software such as Microsoft Windows Mobile®, and/or a variety of mobile operating systems such as iOS, Windows Phone, Android, BlackBerry 8, Palm OS, and the like, and being Internet, e-mail, short message service (SMS), Blackberry®, or other communication protocol enabled. Alternatively, the client computing devices can be general purpose personal computers, including personal computers and/or laptop computers running various versions of Microsoft Windows®, Apple Macintosh®, and/or Linux operating systems.

[0062] The client computing devices can be workstation computers running any of a variety of commercially-available UNIX® or UNIX-like operating systems, including without limitation the variety of GNU/Linux operating systems such as Google Chrome OS. Additionally, or alternatively, client computing devices may be any other electronic device, such as a thin-client computer, an Internet-enabled gaming system (e.g., a Microsoft Xbox gaming console with or without a Kinect® gesture input device), and/or a personal messaging device, capable of communicating over a network that can access the VCN **106** and/or the Internet.

[0063] The VCN **106** can include a local peering gateway (LPG) **110** that can be communicatively coupled to a secure shell (SSH) VCN **112** via an LPG **110** contained in the SSH VCN **112**. The SSH VCN **112** can include an SSH subnet **114**, and the SSH VCN **112** can be communicatively coupled to a control plane VCN **116** via the LPG **110** contained in the control plane VCN **116**. Also, the SSH VCN **112** can be communicatively coupled to a data plane VCN **118** via an LPG **110**. The control plane VCN **116** and the data plane VCN **118** can be contained in a service tenancy

119 that can be owned and/or operated by the IaaS provider.

[0064] The control plane VCN **116** can include a control plane demilitarized zone (DMZ) tier **120** that acts as a perimeter network (e.g., portions of a corporate network between the corporate intranet and external networks). The DMZ-based servers may have restricted responsibilities and help keep breaches contained. Additionally, the DMZ tier **120** can include one or more load balancer (LB) subnet(s) **122**, a control plane app tier **124** that can include app subnet(s) **126**, a control plane data tier **128** that can include database (DB) subnet(s) **130** (e.g., frontend DB subnet(s) and/or backend DB subnet(s)). The LB subnet(s) **122** contained in the control plane DMZ tier **120** can be communicatively coupled to the app subnet(s) **126** contained in the control plane app tier **124** and an Internet gateway **134** that can be contained in the control plane VCN **116**. The app subnet(s) **126** can be communicatively coupled to the DB subnet(s) **130** contained in the control plane data tier **128** and a service gateway **136** and a network address translation (NAT) gateway **138**. The control plane VCN **116** can include the service gateway **136** and the NAT gateway **138**.

[0065] The control plane VCN **116** can include a data plane mirror app tier **140** that can include app subnet(s) **126**. The app subnet(s) **126** contained in the data plane mirror app tier **140** can include a virtual network interface controller (VNIC) **142** that can execute a compute instance **144**. The compute instance **144** can communicatively couple the app subnet(s) **126** of the data plane mirror app tier **140** to app subnet(s) **126** that can be contained in a data plane app tier **146**.

[0066] The data plane VCN **118** can include the data plane app tier **146**, a data plane DMZ tier **148**, and a data plane data tier **150**. The data plane DMZ tier **148** can include LB subnet(s) **122** that can be communicatively coupled to the app subnet(s) **126** of the data plane app tier **146** and the Internet gateway **134** of the data plane VCN **118**. The app subnet(s) **126** can be communicatively coupled to the service gateway **136** of the data plane VCN **118** and the NAT gateway **138** of the data plane VCN **118**. The data plane data tier **150** can also include the DB subnet(s) **130** that can be communicatively coupled to the app subnet(s) **126** of the data plane app tier **146**.

[0067] The Internet gateway **134** of the control plane VCN **116** and of the data plane VCN **118** can be communicatively coupled to a metadata management service **152** that can be communicatively coupled to public Internet **154**. Public Internet **154** can be communicatively coupled to the NAT gateway **138** of the control plane VCN **116** and of the data plane VCN **118**. The service gateway **136** of the control plane VCN **116** and of the data plane VCN **118** can be communicatively couple to cloud services **156**.

[0068] In some examples, the service gateway **136** of the control plane VCN **116** or of the data plane VCN **118** can make application programming interface (API) calls to cloud services **156** without going through public Internet **154**. The API calls to cloud services **156** from the service gateway **136** can be one-way; the service gateway **136** can make API calls to cloud services **156**, and cloud services **156** can send requested data to the service gateway **136**. However, cloud services **156** may not initiate API calls to the service gateway **136**.

[0069] In some examples, the secure host tenancy **104** can be directly connected to the service tenancy **119**. The service tenancy **119** may otherwise be isolated. The secure host subnet **108** can communicate with the SSH subnet **114** through an LPG **110** that may enable two-way communication over an otherwise isolated system. Connecting the secure host subnet **108** to the SSH subnet **114** may give the secure host subnet **108** access to other entities within the service tenancy **119**.

[0070] The control plane VCN **116** may allow users of the service tenancy **119** to set up or otherwise provision desired resources. Desired resources provisioned in the control plane VCN **116** may be deployed or otherwise used in the data plane VCN **118**. In some examples, the control plane VCN **116** can be isolated from the data plane VCN **118**, and the data plane mirror app tier **140** of the control plane VCN **116** can communicate with the data plane app tier **146** of the data plane VCN **118** via VNICs **142** that can be contained in the data plane mirror app tier **140** and the

data plane app tier **146**

[0071] In some examples, users of the system, or customers, can make requests, for example create, read, update, or delete (CRUD) operations, through public Internet **154** that can communicate the requests to the metadata management service **152**. The metadata management service **152** can communicate the request to the control plane VCN **116** through the Internet gateway **134**. The request can be received by the LB subnet(s) **122** contained in the control plane DMZ tier **120**. The LB subnet(s) **122** may determine that the request is valid, and in response, the LB subnet(s) **122** can transmit the request to app subnet(s) **126** contained in the control plane app tier **124**. If the request is validated and requires a call to public Internet **154**, the call to public Internet **154** may be transmitted to the NAT gateway **138** that can make the call to public Internet **154**. Metadata that may be desired to be stored by the request can be stored in the DB subnet(s) **130**.

[0072] In some examples, the data plane mirror app tier **140** can facilitate direct communication between the control plane VCN **116** and the data plane VCN **118**. For example, changes, updates, or other suitable modifications to configuration may be desired to be applied to the resources contained in the data plane VCN **118**. Via a VNIC **142**, the control plane VCN **116** can directly communicate with, and can thereby execute the changes, updates, or other suitable modifications to configuration to, resources contained in the data plane VCN **118**.

[0073] In some embodiments, the control plane VCN **116** and the data plane VCN **118** can be contained in the service tenancy **119**. In this case, the user, or the customer, of the system may not own or operate either the control plane VCN **116** or the data plane VCN **118**. Instead, the IaaS provider may own or operate the control plane VCN **116** and the data plane VCN **118**. The control plane VCN **116** and the data plane VCN **118** may be contained in the service tenancy **119**. This embodiment can enable isolation of networks that may prevent users or customers from interacting with other users', or other customers', resources. Also, this embodiment may allow users or customers of the system to store databases privately without needing to rely on public Internet **154** for storage.

[0074] In other embodiments, the LB subnet(s) **122** contained in the control plane VCN **116** can be configured to receive a signal from the service gateway **136**. In this embodiment, the control plane VCN **116** and the data plane VCN **118** may be configured to be called by a customer of the IaaS provider without calling public Internet **154**. Customers of the IaaS provider may desire this embodiment since database(s) that the customers use may be controlled by the IaaS provider and may be stored on the service tenancy **119**. The service tenancy **119** may be isolated from public Internet **154**.

[0075] FIG. **2** is a block diagram illustrating another example pattern of an IaaS architecture **200** according to at least one embodiment. Service operators **202** (e.g., service operators **102** of FIG. **1**) can be communicatively coupled to a secure host tenancy **204** (e.g., the secure host tenancy **104** of FIG. **1**) that can include a virtual cloud network (VCN) **206** (e.g., the VCN **106** of FIG. **1**) and a secure host subnet **208** (e.g., the secure host subnet **108** of FIG. **1**). The VCN **206** can include a local peering gateway (LPG) **210** (e.g., the LPG **110** of FIG. **1**) that can be communicatively coupled to a secure shell (SSH) VCN **212** (e.g., the SSH VCN **112** of FIG. **1**) via an LPG **110** contained in the SSH VCN **212**. The SSH VCN **212** can include an SSH subnet **214** (e.g., the SSH subnet **114** of FIG. **1**), and the SSH VCN **212** can be communicatively coupled to a control plane VCN **216** (e.g., the control plane VCN **116** of FIG. **1**) via an LPG **210** contained in the control plane VCN **216**. The control plane VCN **216** can be contained in a service tenancy **219** (e.g., the service tenancy **119** of FIG. **1**), and the data plane VCN **218** (e.g., the data plane VCN **118** of FIG. **1**) can be contained in a customer tenancy **221** that may be owned or operated by users, or customers, of the system.

[0076] The control plane VCN **216** can include a control plane DMZ tier **220** (e.g., the control plane DMZ tier **120** of FIG. **1**) that can include LB subnet(s) **222** (e.g., LB subnet(s) **122** of FIG. **1**), a control plane app tier **224** (e.g., the control plane app tier **124** of FIG. **1**) that can include app

subnet(s) **226** (e.g., app subnet(s) **126** of FIG. **1**), and a control plane data tier **228** (e.g., the control plane data tier **128** of FIG. **1**) that can include database (DB) subnet(s) **230** (e.g., similar to DB subnet(s) **130** of FIG. **1**). The LB subnet(s) **222** contained in the control plane DMZ tier **220** can be communicatively coupled to the app subnet(s) **226** contained in the control plane app tier **224** and an Internet gateway **234** (e.g., the Internet gateway **134** of FIG. **1**) that can be contained in the control plane VCN **216**. The app subnet(s) **226** can be communicatively coupled to the DB subnet(s) **230** contained in the control plane data tier **228** and a service gateway **236** (e.g., the service gateway **136** of FIG. **1**) and a network address translation (NAT) gateway **238** (e.g., the NAT gateway **138** of FIG. **1**). The control plane VCN **216** can include the service gateway **236** and the NAT gateway **238**.

[0077] The control plane VCN **216** can include a data plane mirror app tier **240** (e.g., the data plane mirror app tier **140** of FIG. **1**) that can include app subnet(s) **226**. The app subnet(s) **226** contained in the data plane mirror app tier **240** can include a virtual network interface controller (VNIC) **242** (e.g., the VNIC of **142**) that can execute a compute instance **244** (e.g., similar to the compute instance **144** of FIG. **1**). The compute instance **244** can facilitate communication between the app subnet(s) **226** of the data plane mirror app tier **240** and the app subnet(s) **226** that can be contained in a data plane app tier **246** (e.g., the data plane app tier **146** of FIG. **1**) via the VNIC **242** contained in the data plane mirror app tier **240** and the VNIC **242** contained in the data plane app tier **246**.

[0078] The Internet gateway **234** contained in the control plane VCN **216** can be communicatively coupled to a metadata management service **252** (e.g., the metadata management service **152** of FIG. **1**) that can be communicatively coupled to public Internet **254** (e.g., public Internet **154** of FIG. **1**). Public Internet **254** can be communicatively coupled to the NAT gateway **238** contained in the control plane VCN **216**. The service gateway **236** contained in the control plane VCN **216** can be communicatively couple to cloud services **256** (e.g., cloud services **156** of FIG. **1**).

[0079] In some examples, the data plane VCN **218** can be contained in the customer tenancy **221**. In this case, the IaaS provider may provide the control plane VCN **216** per customer, and the IaaS provider may, for the customer, set up a unique, compute instance **244** that is contained in the service tenancy **219**. Compute instance **244** may allow communication between the control plane VCN **216** contained in the service tenancy **219** and the data plane VCN **218** that is contained in the customer tenancy **221**. The compute instance **244** may allow resources provisioned in the control plane VCN **216** that is contained in the service tenancy **219** to be deployed or otherwise used in the data plane VCN **218** that is contained in the customer tenancy **221**.

[0080] In other examples, the customer of the IaaS provider may have databases that live in the customer tenancy **221**. In this example, the control plane VCN **216** can include the data plane mirror app tier **240** that can include app subnet(s) **226**. The data plane mirror app tier **240** can reside in the data plane VCN **218**, but the data plane mirror app tier **240** may not live in the data plane VCN **218**. That is, the data plane mirror app tier **240** may have access to the customer tenancy **221**, but the data plane mirror app tier **240** may not exist in the data plane VCN **218** or be owned or operated by the customer of the IaaS provider. The data plane mirror app tier **240** may be configured to make calls to the data plane VCN **218** but may not be configured to make calls to any entity contained in the control plane VCN **216**. The customer may desire to deploy or otherwise use resources in the data plane VCN **218** that are provisioned in the control plane VCN **216**, and the data plane mirror app tier **240** can facilitate the desired deployment or other usage of resources of the customer.

[0081] In some embodiments, the customer of the IaaS provider can apply filters to the data plane VCN **218**. In this embodiment, the customer can determine what the data plane VCN **218** can access, and the customer may restrict access to public Internet **254** from the data plane VCN **218**. The IaaS provider may not be able to apply filters or otherwise control access of the data plane VCN **218** to any outside networks or databases. Applying filters and controls by the customer onto the data plane VCN **218**, contained in the customer tenancy **221**, can help isolate the data plane

VCN **218** from other customers and from public Internet **254**.

[0082] In some embodiments, cloud services **256** can be called by the service gateway **236** to access services that may not exist on public Internet **254**, on the control plane VCN **216**, or on the data plane VCN **218**. The connection between cloud services **256** and the control plane VCN **216** or the data plane VCN **218** may not be live or continuous. Cloud services **256** may exist on a different network owned or operated by the IaaS provider. Cloud services **256** may be configured to receive calls from the service gateway **236** and may be configured to not receive calls from public Internet **254**. Some cloud services **256** may be isolated from other cloud services **256**, and the control plane VCN **216** may be isolated from cloud services **256** that may not be in the same region as the control plane VCN **216**. For example, the control plane VCN **216** may be located in “Region 1,” and cloud service “Deployment 1” may be located in Region 1 and in “Region 2.” If a call to Deployment 1 is made by the service gateway **236** contained in the control plane VCN **216** located in Region 1, the call may be transmitted to Deployment 1 in Region 1. In this example, the control plane VCN **216**, or Deployment 1 in Region 1, may not be communicatively coupled to, or otherwise in communication with, Deployment 1 in Region 2.

[0083] FIG. **3** is a block diagram illustrating another example pattern of an IaaS architecture **300** according to at least one embodiment. Service operators **302** (e.g., service operators **102** of FIG. **1**) can be communicatively coupled to a secure host tenancy **304** (e.g., the secure host tenancy **104** of FIG. **1**) that can include a virtual cloud network (VCN) **306** (e.g., the VCN **106** of FIG. **1**) and a secure host subnet **308** (e.g., the secure host subnet **108** of FIG. **1**). The VCN **306** can include an LPG **310** (e.g., the LPG **110** of FIG. **1**) that can be communicatively coupled to an SSH VCN **312** (e.g., the SSH VCN **112** of FIG. **1**) via an LPG **310** contained in the SSH VCN **312**. The SSH VCN **312** can include an SSH subnet **314** (e.g., the SSH subnet **114** of FIG. **1**), and the SSH VCN **312** can be communicatively coupled to a control plane VCN **316** (e.g., the control plane VCN **116** of FIG. **1**) via an LPG **310** contained in the control plane VCN **316** and to a data plane VCN **318** (e.g., the data plane VCN **118** of FIG. **1**) via an LPG **310** contained in the data plane VCN **318**. The control plane VCN **316** and the data plane VCN **318** can be contained in a service tenancy **319** (e.g., the service tenancy **119** of FIG. **1**).

[0084] The control plane VCN **316** can include a control plane DMZ tier **320** (e.g., the control plane DMZ tier **120** of FIG. **1**) that can include load balancer (LB) subnet(s) **322** (e.g., LB subnet(s) **122** of FIG. **1**), a control plane app tier **324** (e.g., the control plane app tier **124** of FIG. **1**) that can include app subnet(s) **326** (e.g., similar to app subnet(s) **126** of FIG. **1**), and a control plane data tier **328** (e.g., the control plane data tier **128** of FIG. **1**) that can include DB subnet(s) **330**. The LB subnet(s) **322** contained in the control plane DMZ tier **320** can be communicatively coupled to the app subnet(s) **326** contained in the control plane app tier **324** and to an Internet gateway **334** (e.g., the Internet gateway **134** of FIG. **1**) that can be contained in the control plane VCN **316**, and the app subnet(s) **326** can be communicatively coupled to the DB subnet(s) **330** contained in the control plane data tier **328** and to a service gateway **336** (e.g., the service gateway of FIG. **1**) and a network address translation (NAT) gateway **338** (e.g., the NAT gateway **138** of FIG. **1**). The control plane VCN **316** can include the service gateway **336** and the NAT gateway **338**.

[0085] The data plane VCN **318** can include a data plane app tier **346** (e.g., the data plane app tier **146** of FIG. **1**), a data plane DMZ tier **348** (e.g., the data plane DMZ tier **148** of FIG. **1**), and a data plane data tier **350** (e.g., the data plane data tier **150** of FIG. **1**). The data plane DMZ tier **348** can include LB subnet(s) **322** that can be communicatively coupled to trusted app subnet(s) **360**, untrusted app subnet(s) **362** of the data plane app tier **346**, and the Internet gateway **334** contained in the data plane VCN **318**. The trusted app subnet(s) **360** can be communicatively coupled to the service gateway **336** contained in the data plane VCN **318**, the NAT gateway **338** contained in the data plane VCN **318**, and DB subnet(s) **330** contained in the data plane data tier **350**. The untrusted app subnet(s) **362** can be communicatively coupled to the service gateway **336** contained in the data plane VCN **318** and DB subnet(s) **330** contained in the data plane data tier **350**. The data plane

data tier **350** can include DB subnet(s) **330** that can be communicatively coupled to the service gateway **336** contained in the data plane VCN **318**.

[0086] The untrusted app subnet(s) **362** can include one or more primary VNICs **364(1)-(N)** that can be communicatively coupled to tenant virtual machines (VMs) **366(1)-(N)**. Tenant(s) VM **366(1)-(N)** can be communicatively coupled to a respective app subnet **367(1)-(N)** that can be contained in respective container egress VCNs **368(1)-(N)** that can be contained in respective customer tenancies **380(1)-(N)**. Respective secondary VNICs **372(1)-(N)** can facilitate communication between the untrusted app subnet(s) **362** contained in the data plane VCN **318** and the app subnet contained in the container egress VCNs **368(1)-(N)**. Container egress VCNs **368(1)-(N)** can include a NAT gateway **338** that can be communicatively coupled to public Internet **354** (e.g., public Internet **154** of FIG. **1**).

[0087] The Internet gateway **334** contained in the control plane VCN **316** and contained in the data plane VCN **318** can be communicatively coupled to a metadata management service **352** (e.g., the metadata management service **152** of FIG. **1**) that can be communicatively coupled to public Internet **354**. Public Internet **354** can be communicatively coupled to the NAT gateway **338** contained in the control plane VCN **316** and contained in the data plane VCN **318**. The service gateway **336** contained in the control plane VCN **316** and contained in the data plane VCN **318** can be communicatively couple to cloud services **356**.

[0088] In some embodiments, the data plane VCN **318** can be integrated with customer tenancies **380**. This integration can be useful or desirable for customers of the IaaS provider in some cases such as a case that may desire support when executing code. The customer may provide code to run that may be destructive, may communicate with other customer resources, or may otherwise cause undesirable effects. In response to this, the IaaS provider may determine whether or not to run code given to the IaaS provider by the customer.

[0089] In some examples, the customer of the IaaS provider may grant temporary network access to the IaaS provider and request a function to be attached to the data plane app tier **346**. Code to run the function may be executed in the VMs **366(1)-(N)**, and the code may not be configured to run anywhere else on the data plane VCN **318**. VM **366(1)-(N)** may be connected to one customer tenancy **380**. Respective containers **381(1)-(N)** contained in the VMs **366(1)-(N)** may be configured to run the code. In this case, there can be a dual isolation (e.g., the containers **381(1)-(N)** running code), where the containers **381(1)-(N)** may be contained in at least the VM **366(1)-(N)** that are contained in the untrusted app subnet(s) **362**) that may help prevent incorrect or otherwise undesirable code from damaging the network of the IaaS provider or from damaging a network of a different customer. The containers **381(1)-(N)** may be communicatively coupled to the customer tenancy **380** and may be configured to transmit or receive data from the customer tenancy **380**. The containers **381(1)-(N)** may not be configured to transmit or receive data from any other entity in the data plane VCN **318**. Upon completion of running the code, the IaaS provider may kill or otherwise dispose of the containers **381(1)-(N)**.

[0090] In some embodiments, the trusted app subnet(s) **360** may run code that may be owned or operated by the IaaS provider. In this embodiment, the trusted app subnet(s) **360** may be communicatively coupled to the DB subnet(s) **330** and be configured to execute CRUD operations in the DB subnet(s) **330**. The untrusted app subnet(s) **362** may be communicatively coupled to the DB subnet(s) **330**, but in this embodiment, the untrusted app subnet(s) may be configured to execute read operations in the DB subnet(s) **330**. The containers **381(1)-(N)** that can be contained in the VM **366(1)-(N)** of the customer and that may run code from the customer may not be communicatively coupled with the DB subnet(s) **330**.

[0091] In other embodiments, the control plane VCN **316** and the data plane VCN **318** may not be directly communicatively coupled. In this embodiment, there may be no direct communication between the control plane VCN **316** and the data plane VCN **318**. However, communication can occur indirectly through at least one method. An LPG **310** may be established by the IaaS provider

that can facilitate communication between the control plane VCN **316** and the data plane VCN **318**. In another example, the control plane VCN **316** or the data plane VCN **318** can make a call to cloud services **356** via the service gateway **336**. For example, a call to cloud services **356** from the control plane VCN **316** can include a request for a service that can communicate with the data plane VCN **318**.

[0092] FIG. **4** is a block diagram illustrating another example pattern of an IaaS architecture **400** according to at least one embodiment. Service operators **402** (e.g., service operators **102** of FIG. **1**) can be communicatively coupled to a secure host tenancy **404** (e.g., the secure host tenancy **104** of FIG. **1**) that can include a virtual cloud network (VCN) **406** (e.g., the VCN **106** of FIG. **1**) and a secure host subnet **408** (e.g., the secure host subnet **108** of FIG. **1**). The VCN **406** can include an LPG **410** (e.g., the LPG **110** of FIG. **1**) that can be communicatively coupled to an SSH VCN **412** (e.g., the SSH VCN **112** of FIG. **1**) via an LPG **410** contained in the SSH VCN **412**. The SSH VCN **412** can include an SSH subnet **414** (e.g., the SSH subnet **114** of FIG. **1**), and the SSH VCN **412** can be communicatively coupled to a control plane VCN **416** (e.g., the control plane VCN **116** of FIG. **1**) via an LPG **410** contained in the control plane VCN **416** and to a data plane VCN **418** (e.g., the data plane VCN **118** of FIG. **1**) via an LPG **410** contained in the data plane VCN **418**. The control plane VCN **416** and the data plane VCN **418** can be contained in a service tenancy **419** (e.g., the service tenancy **119** of FIG. **1**).

[0093] The control plane VCN **416** can include a control plane DMZ tier **420** (e.g., the control plane DMZ tier **120** of FIG. **1**) that can include LB subnet(s) **422** (e.g., LB subnet(s) **122** of FIG. **1**), a control plane app tier **424** (e.g., the control plane app tier **124** of FIG. **1**) that can include app subnet(s) **426** (e.g., app subnet(s) **126** of FIG. **1**), and a control plane data tier **428** (e.g., the control plane data tier **128** of FIG. **1**) that can include DB subnet(s) **430** (e.g., DB subnet(s) **330** of FIG. **3**). The LB subnet(s) **422** contained in the control plane DMZ tier **420** can be communicatively coupled to the app subnet(s) **426** contained in the control plane app tier **424** and to an Internet gateway **434** (e.g., the Internet gateway **134** of FIG. **1**) that can be contained in the control plane VCN **416**, and the app subnet(s) **426** can be communicatively coupled to the DB subnet(s) **430** contained in the control plane data tier **428** and to a service gateway **436** (e.g., the service gateway of FIG. **1**) and a network address translation (NAT) gateway **438** (e.g., the NAT gateway **138** of FIG. **1**). The control plane VCN **416** can include the service gateway **436** and the NAT gateway **438**.

[0094] The data plane VCN **418** can include a data plane app tier **446** (e.g., the data plane app tier **146** of FIG. **1**), a data plane DMZ tier **448** (e.g., the data plane DMZ tier **148** of FIG. **1**), and a data plane data tier **450** (e.g., the data plane data tier **150** of FIG. **1**). The data plane DMZ tier **448** can include LB subnet(s) **422** that can be communicatively coupled to trusted app subnet(s) **460** (e.g., trusted app subnet(s) **360** of FIG. **3**) and untrusted app subnet(s) **462** (e.g., untrusted app subnet(s) **362** of FIG. **3**) of the data plane app tier **446** and the Internet gateway **434** contained in the data plane VCN **418**. The trusted app subnet(s) **460** can be communicatively coupled to the service gateway **436** contained in the data plane VCN **418**, the NAT gateway **438** contained in the data plane VCN **418**, and DB subnet(s) **430** contained in the data plane data tier **450**. The untrusted app subnet(s) **462** can be communicatively coupled to the service gateway **436** contained in the data plane VCN **418** and DB subnet(s) **430** contained in the data plane data tier **450**. The data plane data tier **450** can include DB subnet(s) **430** that can be communicatively coupled to the service gateway **436** contained in the data plane VCN **418**.

[0095] The untrusted app subnet(s) **462** can include primary VNICS **464(1)-(N)** that can be communicatively coupled to tenant virtual machines (VMs) **466(1)-(N)** residing within the untrusted app subnet(s) **462**. Tenant VM **466(1)-(N)** can run code in a respective container **467(1)-(N)** and be communicatively coupled to an app subnet **426** that can be contained in a data plane app tier **446** that can be contained in a container egress VCN **468**. Respective secondary VNICS **472(1)-(N)** can facilitate communication between the untrusted app subnet(s) **462** contained in the data

plane VCN **418** and the app subnet contained in the container egress VCN **468**. The container egress VCN can include a NAT gateway **438** that can be communicatively coupled to public Internet **454** (e.g., public Internet **154** of FIG. **1**).

[0096] The Internet gateway **434** contained in the control plane VCN **416** and contained in the data plane VCN **418** can be communicatively coupled to a metadata management service **452** (e.g., the metadata management service **152** of FIG. **1**) that can be communicatively coupled to public Internet **454**. Public Internet **454** can be communicatively coupled to the NAT gateway **438** contained in the control plane VCN **416** and contained in the data plane VCN **418**. The service gateway **436** contained in the control plane VCN **416** and contained in the data plane VCN **418** can be communicatively couple to cloud services **456**.

[0097] In some examples, the pattern illustrated by the architecture of block diagram **400** of FIG. **4** may be considered an exception to the pattern illustrated by the architecture of block diagram **300** of FIG. **3** and may be desirable for a customer of the IaaS provider if the IaaS provider cannot directly communicate with the customer (e.g., a disconnected region). The respective containers **467(1)-(N)** that are contained in the VMs **466(1)-(N)** for customers can be accessed in real-time by the customer. The containers **467(1)-(N)** may be configured to make calls to respective secondary VNICS **472(1)-(N)** contained in app subnet(s) **426** of the data plane app tier **446** that can be contained in the container egress VCN **468**. The secondary VNICS **472(1)-(N)** can transmit the calls to the NAT gateway **438** that may transmit the calls to public Internet **454**. In this example, the containers **467(1)-(N)** that can be accessed in real time by the customer can be isolated from the control plane VCN **416** and can be isolated from other entities contained in the data plane VCN **418**. The containers **467(1)-(N)** may also be isolated from resources from other customers.

[0098] In other examples, the customer can use the containers **467(1)-(N)** to call cloud services **456**. In this example, the customer may run code in the containers **467(1)-(N)** that request a service from cloud services **456**. The containers **467(1)-(N)** can transmit this request to the secondary VNICS **472(1)-(N)** that can transmit the request to the NAT gateway that can transmit the request to public Internet **454**. Public Internet **454** can transmit the request to LB subnet(s) **422** contained in the control plane VCN **416** via the Internet gateway **434**. In response to determining the request is valid, the LB subnet(s) can transmit the request to app subnet(s) **426** that can transmit the request to cloud services **456** via the service gateway **436**.

[0099] It should be appreciated that IaaS architectures **100**, **200**, **300**, and **400** may include components that are different and/or additional to the components shown in the figures. Further, the embodiments shown in the figures represent non-exhaustive examples of a cloud infrastructure system that may incorporate an embodiment of the disclosure. In some other embodiments, the IaaS systems may have more or fewer components than shown in the figures, may combine two or more components, or may have a different configuration or arrangement of components.

[0100] In certain embodiments, the IaaS systems described herein may include a suite of applications, middleware, and database service offerings that are delivered to a customer in a self-service, subscription-based, elastically scalable, reliable, highly available, and secure manner. An example of such an IaaS system is the Oracle Cloud Infrastructure (OCI) provided by the present assignee.

[0101] In one or more embodiments, a computer network provides connectivity among a set of nodes. The nodes may be local to and/or remote from one other. The nodes are connected by a set of links. Examples of links include a coaxial cable, an unshielded twisted cable, a copper cable, an optical fiber, and a virtual link.

[0102] A subset of nodes implements the computer network. Examples of such nodes include a switch, a router, a firewall, and a network address translator (NAT). Another subset of nodes uses the computer network. Such nodes (also referred to as “hosts”) may execute a client process and/or a server process. A client process makes a request for a computing service (such as execution of a particular application and/or storage of a particular amount of data). A server process responds by

executing the requested service and/or returning corresponding data.

[0103] A computer network may be a physical network, including physical nodes connected by physical links. A physical node is any digital device. A physical node may be a function-specific hardware device, such as a hardware switch, a hardware router, a hardware firewall, and a hardware NAT. Additionally, or alternatively, a physical node may be a generic machine that is configured to execute various virtual machines and/or applications performing respective functions. A physical link is a physical medium connecting two or more physical nodes. Examples of links include a coaxial cable, an unshielded twisted cable, a copper cable, and an optical fiber.

[0104] A computer network may be an overlay network. An overlay network is a logical network implemented on top of another network such as a physical network. A node in an overlay network corresponds to a respective node in the underlying network. Hence, a node in an overlay network is associated with both an overlay address (to address to the overlay node) and an underlay address (to address the underlay node that implements the overlay node). An overlay node may be a digital device and/or a software process, such as a virtual machine, an application instance, or a thread. A link that connects overlay nodes is implemented as a tunnel through the underlying network. The overlay nodes at either end of the tunnel treat the underlying multi-hop path between them as a single logical link. Tunneling is performed through encapsulation and decapsulation.

[0105] In an embodiment, a client may be local to and/or remote from a computer network. The client may access the computer network over other computer networks, such as a private network or the Internet. The client may communicate requests to the computer network using a communications protocol such as Hypertext Transfer Protocol (HTTP). The requests are communicated through an interface, such as a client interface (such as a web browser), a program interface, or an application programming interface (API).

[0106] In an embodiment, a computer network provides connectivity between clients and network resources. Network resources include hardware and/or software configured to execute server processes. Examples of network resources include a processor, a data storage, a virtual machine, a container, and/or a software application. Network resources are shared amongst multiple clients. Clients request computing services from a computer network independently of one another. Network resources are dynamically assigned to the requests and/or clients on an on-demand basis. Network resources assigned to a request and/or client may be scaled up or down based on one or more of the following: (a) the computing services requested by a particular client, (b) the aggregated computing services requested by a particular tenant, or (c) the aggregated computing services requested of the computer network. Such a computer network may be referred to as a “cloud network.”

[0107] In an embodiment, a service provider provides a cloud network to one or more end users. Various service models may be implemented by the cloud network, including, but not limited to, Software-as-a-Service (SaaS), Platform-as-a-Service (PaaS), and Infrastructure-as-a-Service (IaaS). In SaaS, a service provider provides end users the capability to use the service provider's applications that are executing on the network resources. In PaaS, the service provider provides end users the capability to deploy custom applications onto the network resources. The custom applications may be created using programming languages, libraries, services, and tools supported by the service provider. In IaaS, the service provider provides end users the capability to provision processing, storage, networks, and other fundamental computing resources provided by the network resources. Any arbitrary applications, including an operating system, may be deployed on the network resources.

[0108] In an embodiment, various deployment models may be implemented by a computer network, including, but not limited to, a private cloud, a public cloud, and a hybrid cloud. In a private cloud, network resources are provisioned for exclusive use by a particular group of one or more entities; the term “entity” as used herein refers to a corporation, organization, person, or other entity. The network resources may be local to and/or remote from the premises of the particular

group of entities. In a public cloud, cloud resources are provisioned for multiple entities that are independent from one another (also referred to as “tenants” or “customers”). The computer network and the network resources thereof are accessed by clients corresponding to different tenants. Such a computer network may be referred to as a “multi-tenant computer network.” Several tenants may use a same particular network resource at different times and/or at the same time. The network resources may be local to and/or remote from the premises of the tenants. In a hybrid cloud, a computer network comprises a private cloud and a public cloud. An interface between the private cloud and the public cloud allows for data and application portability. Data stored at the private cloud and data stored at the public cloud may be exchanged through the interface. Applications implemented at the private cloud and applications implemented at the public cloud may have dependencies on one other. A call from an application at the private cloud to an application at the public cloud (and vice versa) may be executed through the interface.

[0109] In an embodiment, tenants of a multi-tenant computer network are independent of one another. For example, a business or operation of one tenant may be separate from a business or operation of another tenant. Different tenants may demand different network requirements for the computer network. Examples of network requirements include processing speed, amount of data storage, security requirements, performance requirements, throughput requirements, latency requirements, resiliency requirements, Quality of Service (QOS) requirements, tenant isolation, and/or consistency. The same computer network may need to implement different network requirements demanded by different tenants.

[0110] In one or more embodiments, in a multi-tenant computer network, tenant isolation is implemented to ensure that the applications and/or data of different tenants are not shared with other tenants. Various tenant isolation approaches may be used.

[0111] In an embodiment, a tenant is associated with a tenant ID. The network resource of the multi-tenant computer network is tagged with a tenant ID. A tenant is permitted access to a particular network resource when the tenant and the particular network resources are associated with a same tenant ID.

[0112] In an embodiment, a tenant is associated with a tenant ID. An application, implemented by the computer network, is tagged with a tenant ID. Additionally, or alternatively, data structures and/or datasets, stored by the computer network, are tagged with a tenant ID. A tenant is permitted access to a particular application, data structure, and/or dataset when the tenant and the particular application, data structure, and/or dataset are associated with a same tenant ID.

[0113] As an example, a database implemented by a multi-tenant computer network may be tagged with a tenant ID. A tenant associated with the corresponding tenant ID may access data of a particular database. As another example, an entry in a database implemented by a multi-tenant computer network may be tagged with a tenant ID. A tenant associated with the corresponding tenant ID may access data of a particular entry. However, multiple tenants may share the database.

[0114] In an embodiment, a subscription list identifies a set of tenants, and, for a particular tenant, a set of applications that the particular tenant is authorized to access. For a particular application, a list of tenant IDs of tenants authorized to access the particular application is stored. A tenant is permitted access to a particular application when the tenant ID of the tenant is included in the subscription list corresponding to the particular application.

[0115] In an embodiment, network resources (such as digital devices, virtual machines, application instances, and threads) corresponding to different tenants are isolated to tenant-specific overlay networks maintained by the multi-tenant computer network. As an example, packets from any source device in a tenant overlay network may be transmitted to other devices within the same tenant overlay network. Encapsulation tunnels are used to prohibit any transmissions from a source device on a tenant overlay network to devices in other tenant overlay networks. Specifically, the packets received from the source device are encapsulated within an outer packet. The outer packet is transmitted from a first encapsulation tunnel endpoint (in communication with the source device

in the tenant overlay network) to a second encapsulation tunnel endpoint (in communication with the destination device in the tenant overlay network). The second encapsulation tunnel endpoint decapsulates the outer packet to obtain the original packet transmitted by the source device. The original packet is transmitted from the second encapsulation tunnel endpoint to the destination device in the same particular overlay network.

4. Computer System

[0116] FIG. 5 illustrates an example computer system 500. An embodiment of the disclosure may be implemented upon the computer system 500. As shown in FIG. 5, computer system 500 includes a processing unit 504 that communicates with peripheral subsystems via a bus subsystem 502. These peripheral subsystems may include a processing acceleration unit 506, an I/O subsystem 508, a storage subsystem 518, and a communications subsystem 524. Storage subsystem 518 includes tangible computer-readable storage media 522 and a system memory 510.

[0117] Bus subsystem 502 provides a mechanism for letting the various components and subsystems of computer system 500 to communicate with one another as intended. Although bus subsystem 502 is shown schematically as a single bus, alternative embodiments of the bus subsystem may utilize multiple buses. Bus subsystem 502 may be any of several types of bus structures, including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. For example, such architectures may include an Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus. Additionally, such architectures may be implemented as a Mezzanine bus manufactured to the IEEE P1386.1 standard.

[0118] Processing unit 504 controls the operation of computer system 500. Processing unit 504 can be implemented as one or more integrated circuits (e.g., a conventional microprocessor or microcontroller). One or more processors may be included in processing unit 504. These processors may include single core or multicore processors. In certain embodiments, processing unit 504 may be implemented as one or more independent processing units 532 and/or 534 with single or multicore processors included in the processing unit. In other embodiments, processing unit 504 may also be implemented as a quad-core processing unit formed by integrating two dual-core processors into a single chip.

[0119] In various embodiments, processing unit 504 can execute a variety of programs in response to program code and can maintain multiple concurrently executing programs or processes. At any given time, the program code to be executed can be wholly or partially resident in processing unit 504 and/or in storage subsystem 518. Through suitable programming, processing unit 504 can provide various functionalities described above. Computer system 500 may additionally include a processing acceleration unit 506 that can include a digital signal processor (DSP), a special-purpose processor, and/or the like.

[0120] I/O subsystem 508 may include user interface input devices and user interface output devices. User interface input devices may include a keyboard, pointing devices such as a mouse or trackball, a touchpad or touch screen incorporated into a display, a scroll wheel, a click wheel, a dial, a button, a switch, a keypad, audio input devices with voice command recognition systems, microphones, and other types of input devices. User interface input devices may include, for example, motion sensing and/or gesture recognition devices such as the Microsoft Kinect® motion sensor that enables users to control and interact with an input device, such as the Microsoft Xbox® 360 game controller, through a natural user interface using gestures and spoken commands. User interface input devices may also include eye gesture recognition devices such as the Google Glass® blink detector that detects eye activity (e.g., ‘blinking’ while taking pictures and/or making a menu selection) from users and transforms the eye gestures as input into an input device (e.g., Google Glass®). Additionally, user interface input devices may include voice recognition sensing devices that enable users to interact with voice recognition systems (e.g., Siri® navigator), through

voice commands.

[0121] User interface input devices may also include, without limitation, three dimensional (3D) mice, joysticks or pointing sticks, gamepads and graphic tablets, and audio/visual devices such as speakers, digital cameras, digital camcorders, portable media players, webcams, image scanners, fingerprint scanners, barcode reader 3D scanners, 3D printers, laser rangefinders, and eye gaze tracking devices. Additionally, user interface input devices may include medical imaging input devices such as computed tomography, magnetic resonance imaging, position emission tomography, or medical ultrasonography devices. User interface input devices may also include audio input devices such as MIDI keyboards, digital musical instruments and the like.

[0122] User interface output devices may include a display subsystem, indicator lights, or non-visual displays such as audio output devices, etc. The display subsystem may be a cathode ray tube (CRT), a flat-panel device, such as that using a liquid crystal display (LCD) or plasma display, a projection device, a touch screen, and the like. In general, use of the term “output device” is intended to include any type of device and mechanism for outputting information from computer system **500** to a user or other computer. For example, user interface output devices may include, without limitation, a variety of display devices that visually convey text, graphics and audio/video information, such as monitors, printers, speakers, headphones, automotive navigation systems, plotters, voice output devices, and modems.

[0123] Computer system **500** may comprise a storage subsystem **518** that provides a tangible non-transitory computer-readable storage medium for storing software and data constructs that provide the functionality of the embodiments described in this disclosure. The software can include programs, code modules, instructions, scripts, etc., that when executed by one or more cores or processors of processing unit **504** provide the functionality described above. Storage subsystem **518** may also provide a repository for storing data used in accordance with the present disclosure.

[0124] As depicted in the example in FIG. 5, storage subsystem **518** can include various components, including a system memory **510**, computer-readable storage media **522**, and a computer readable storage media reader **520**. System memory **510** may store program instructions, such as application programs **512**, that are loadable and executable by processing unit **504**. System memory **510** may also store data, such as program data **514**, that is used during the execution of the instructions and/or data that is generated during the execution of the program instructions. Various programs may be loaded into system memory **510** including, but not limited to, client applications, Web browsers, mid-tier applications, relational database management systems (RDBMS), virtual machines, containers, etc.

[0125] System memory **510** may also store an operating system **516**. Examples of operating system **516** may include various versions of Microsoft Windows®, Apple Macintosh®, and/or Linux operating systems, a variety of commercially-available UNIX® or UNIX-like operating systems (including without limitation the variety of GNU/Linux operating systems, the Google Chrome® OS, and the like) and/or mobile operating systems such as iOS, Windows® Phone, Android® OS, BlackBerry® OS, and Palm® OS operating systems. In certain implementations where computer system **500** executes one or more virtual machines, the virtual machines along with their guest operating systems (GOSs) may be loaded into system memory **510** and executed by one or more processors or cores of processing unit **504**.

[0126] System memory **510** can come in different configurations depending upon the type of computer system **500**. For example, system memory **510** may be volatile memory (such as random access memory (RAM)) and/or non-volatile memory (such as read-only memory (ROM), flash memory, etc.). Different types of RAM configurations may be provided, including a static random access memory (SRAM), a dynamic random access memory (DRAM), and others. In some implementations, system memory **510** may include a basic input/output system (BIOS) containing basic routines that help to transfer information between elements within computer system **500** such as during start-up.

[0127] Computer-readable storage media **522** may represent remote, local, fixed, and/or removable storage devices plus storage media for temporarily and/or more permanently containing, storing, computer-readable information for use by computer system **500**, including instructions executable by processing unit **504** of computer system **500**.

[0128] Computer-readable storage media **522** can include any appropriate media known or used in the art, including storage media and communication media, such as but not limited to volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage and/or transmission of information. This can include tangible computer-readable storage media such as RAM, ROM, electronically erasable programmable ROM (EEPROM), flash memory or other memory technology, CD-ROM, digital versatile disk (DVD), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or other tangible computer readable media.

[0129] By way of example, computer-readable storage media **522** may include a hard disk drive that reads from or writes to non-removable, nonvolatile magnetic media, a magnetic disk drive that reads from or writes to a removable, nonvolatile magnetic disk, and an optical disk drive that reads from or writes to a removable, nonvolatile optical disk such as a CD ROM, DVD, and Blu-Ray® disk, or other optical media. Computer-readable storage media **522** may include, but is not limited to, Zip® drives, flash memory cards, universal serial bus (USB) flash drives, secure digital (SD) cards, DVD disks, digital video tape, and the like. Computer-readable storage media **522** may also include solid-state drives (SSD) based on non-volatile memory, such as flash-memory based SSDs, enterprise flash drives, solid state ROM, and the like, SSDs based on volatile memory such as solid state RAM, dynamic RAM, static RAM, DRAM-based SSDs, magnetoresistive RAM (MRAM) SSDs, and hybrid SSDs that use a combination of DRAM and flash memory based SSDs. The disk drives and their associated computer-readable media may provide non-volatile storage of computer-readable instructions, data structures, program modules, and other data for computer system **500**.

[0130] Machine-readable instructions executable by one or more processors or cores of processing unit **504** may be stored on a non-transitory computer-readable storage medium. A non-transitory computer-readable storage medium can include physically tangible memory or storage devices that include volatile memory storage devices and/or non-volatile storage devices. Examples of non-transitory computer-readable storage medium include magnetic storage media (e.g., disk or tapes), optical storage media (e.g., DVDs, CDs), various types of RAM, ROM, or flash memory, hard drives, floppy drives, detachable memory drives (e.g., USB drives), or other type of storage device.

[0131] Communications subsystem **524** provides an interface to other computer systems and networks. Communications subsystem **524** serves as an interface for receiving data from and transmitting data to other systems from computer system **500**. For example, communications subsystem **524** may enable computer system **500** to connect to one or more devices via the Internet. In some embodiments, communications subsystem **524** can include radio frequency (RF) transceiver components to access wireless voice and/or data networks (e.g., using cellular telephone technology, advanced data network technology, such as 3G, 4G or EDGE (enhanced data rates for global evolution), WiFi (IEEE 802.11 family standards, or other mobile communication technologies, or any combination thereof), global positioning system (GPS) receiver components, and/or other components. In some embodiments, communications subsystem **524** can provide wired network connectivity (e.g., Ethernet) in addition to or instead of a wireless interface.

[0132] In some embodiments, communications subsystem **524** may also receive input communication in the form of structured and/or unstructured data feeds **526**, event streams **528**, event updates **530**, and the like on behalf of one or more users who may use computer system **500**.

[0133] By way of example, communications subsystem **524** may be configured to receive data feeds **526** in real-time from users of social networks and/or other communication services, such as Twitter® feeds, Facebook® updates, web feeds such as Rich Site Summary (RSS) feeds, and/or real-time updates from one or more third party information sources.

[0134] Additionally, communications subsystem **524** may be configured to receive data in the form of continuous data streams. The continuous data streams may include event streams **528** of real-time events and/or event updates **530** that may be continuous or unbounded in nature with no explicit end. Examples of applications that generate continuous data may include sensor data applications, financial tickers, network performance measuring tools (e.g., network monitoring and traffic management applications), clickstream analysis tools, automobile traffic monitoring, and the like.

[0135] Communications subsystem **524** may also be configured to output the structured and/or unstructured data feeds **526**, event streams **528**, event updates **530**, and the like to one or more databases that may be in communication with one or more streaming data source computers coupled to computer system **500**.

[0136] Computer system **500** can be one of various types, including a handheld portable device (e.g., an iPhone® cellular phone, an iPad® computing tablet, a PDA), a wearable device (e.g., a Google Glass® head mounted display), a PC, a workstation, a mainframe, a kiosk, a server rack, or any other data processing system.

[0137] Due to the ever-changing nature of computers and networks, the description of computer system **500** depicted in FIG. **5** is intended as a non-limiting example. Many other configurations having more or fewer components than the system depicted in FIG. **5** are possible. For example, customized hardware might also be used and/or particular elements might be implemented in hardware, firmware, software (including applets), or a combination. Further, connection to other computing devices, such as network input/output devices, may be employed. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art will appreciate other ways and/or methods to implement the various embodiments.

5. Architectural Overview

[0138] FIGS. **6A-6C** illustrate features of an example system **600** in accordance with one or more embodiments. The system **600** described with reference to FIGS. **6A-6C** may perform operations pertaining to distribution processes for distributing digital certificates to an execution environment of a computing network. A distribution process may include issuing CA certificates, generating certificate bundles that included the CA certificates, and distributing the certificate bundles to the execution environment. The certificate bundles may be utilized in an authentication protocol for authenticating network entities in the execution environment based on entity certificates issued based on a CA certificate in a certificate bundle. Additionally, or alternatively, a distribution process may include issuing entity certificates to network entities and distributing the entity certificates to the network entities for authentication in the authentication protocol. Additionally, or alternatively, the system **600** described with reference to FIGS. **6A-6C** may perform operations pertaining to testing processes for testing digital certificates in an execution environment of a computing network and/or in a sandbox sub-environment executing in the execution environment of the computing network. A testing process may be executed in connection with the distribution of digital certificates to the execution environment. In one example, one or more testing processes may be executed prior to and/or between incremental steps in a distribution process.

A. Example Computing Network

[0139] As shown in FIG. **6A**, the system **600** includes a computing network such as a virtual cloud network **602**. The virtual cloud network **602** includes a plurality of network entities **604** (such as network entity **604a**, network entity **604b**, network entity **604n**, network entity **604v**, network entity **604w**, and network entity **604z**). In one example, network entity **604a** is a host, and network entity **604b** and network entity **604n** are nodes serviced by network entity **604a**. Additionally, or alternatively, network entity **604v** is a host, and network entity **604w** and network entity **604z** are nodes serviced by network entity **604v**.

[0140] As shown in FIG. **6A**, the virtual cloud network **602** may include one or more availability domains **606**, such as availability domain **606a** and availability domain **606n**. Additionally, or

alternatively, the virtual cloud network **602** may include one or more regions **608**, such as region **608a** and region **608n**. An availability domain **606** includes at least one region **608**. A particular region **608** is located in a particular availability domain **606**. For example, region **608a** and region **608n** are located in availability domain **606a**. A region **608** includes a plurality of network entities **604**. A particular network entity **604** is located in a particular region **608**. For example, network entity **604a**, network entity **604b**, network entity **604n**, network entity **604v**, network entity **604w**, and network entity **604z** are located in region **608a**.

[0141] The virtual cloud network **602** further includes a public key infrastructure (PKI) service **610** for generating digital certificates and a certificate distribution service **612** for distributing the digital certificates to the network entities **604**. Additionally, the system **600** includes an orchestration service **614** for orchestrating certificate distribution processes and testing processes. Further, the system includes an event monitoring service **616**. The event monitoring service monitors events associated with the virtual cloud network **602** such as events associated with the network entities **604**. The orchestration service **614** interacts with the event monitoring service **616** and/or directly with the network entities **604** to obtain information that the orchestration service **614** utilizes to orchestrate certificate distribution processes and testing processes.

[0142] The virtual cloud network **602** further includes at least one execution environment **618** and at least one sandbox sub-environment **620**. The execution environment **618** includes network entities **604** and other portions of the virtual cloud network **602** that deploy and/or run network services, resources, and/or infrastructure. The sandbox sub-environment **620** represents a portion of the execution environment **618** that is logically or physically isolated from the network entities **604** executing in the execution environment **618**. As shown in FIG. 6A, the execution environment **618** includes hosts, such as network entity **604a**, and nodes, such as network entity **604b** and network entity **604n**. In one example, the execution environment additionally includes the PKI service **610**, the certificate distribution service **612**, the orchestration service **614**, and/or the event monitoring service **616**.

[0143] The orchestration service **614** may orchestrate testing processes that are executed within a sandbox sub-environment **620**. Additionally, or alternatively, the orchestration service **614** may orchestrate testing processes that are executed within an execution environment **618**. The testing processes executed within the sandbox sub-environment **620** are performed without impacting network entities **604** executing in the execution environment **618**. The sandbox sub-environment **620** is capable of communicating with the PKI service **610**, the certificate distribution service **612**, the orchestration service **614**, and the event monitoring service **616**, for example, for purposes of executing testing processes orchestrated by the orchestration service **614**.

[0144] In one example, one or more of the network entities **604** execute a testing service **622** for performing testing processes. For example, as shown in FIG. 6A, a testing service **622** is executing on network entity **604a**. The orchestration service **614** may utilize the testing service **622** to perform testing processes corresponding to a first CA certificate, such as a new CA certificate, that is yet to be activated in the portion of the execution environment **618**, where the network entity **604** that is executing testing service **622** is located. The testing processes that utilize the testing service **622** may be performed, while a second CA certificate, such as a current CA certificate, is active in the portion of the execution environment **618**, where the network entity **604** that is executing testing service **622** is located.

[0145] In one example, one or more of the network entities **604** execute one or more production services **624**. A production service may include database services, application hosting services, networking services, security services, identity and access management services, key management services, backup services, container orchestration services, virtual machine services, or content delivery services. For example, as shown in FIG. 6A, a production service **624** is executing on network entity **604v**. The orchestration service **614** may utilize the production service **624** to perform testing processes corresponding to a first CA certificate, such as a new CA certificate, that

is activated in a first portion of the execution environment **618**, where the network entity **604** executing production service **624** is located. The testing processes that utilize the production service **624** may be performed while a second CA certificate, such as a current CA certificate, is active in a second portion of the execution environment that is logically or physically isolated from the first portion of the execution environment **618**, where the network entity **604** executing the production service **624** is located.

[0146] Referring further to FIG. **6A**, the PKI service **610** includes a certificate authority **626**, a certificate repository **628**, and a certificate lifecycle module **630**. The certificate authority **626** issues CA certificates. Additionally, the certificate authority **626** issues subordinate certificates based on CA certificates. In one example, the certificate authority **626** issues a root CA certificate. Additionally, or alternatively, the certificate authority **626** may issue a set of entity certificates from the root CA certificate. Additionally, or alternatively, the certificate authority **626** may issue one or more intermediate CA certificates from the root CA certificate. Additionally, or alternatively, the certificate authority **626** may issue one or more entity certificates from an intermediate CA certificate.

[0147] One or more CA certificates issued by the certificate authority **626** are stored in the certificate repository **628**. In one example, the certificate authority **626** may generate a certificate bundle **632** that includes one or more CA certificates. The certificate authority **626** may store one or more certificate bundles **632** in the certificate repository **628**. Additionally, or alternatively, the certificate repository **628** may store subordinate certificates for distribution to the execution environment. In one example, the certificate repository **628** may store a set of entity certificates issued based on a CA certificate in a certificate bundle **632** stored in the certificate repository **628**.

[0148] In one example, as shown in FIG. **6A**, the certificate repository **628** includes a current certificate bundle **632a** and a new certificate bundle **632n**. The current certificate bundle **632a** may include a current CA certificate. The new certificate bundle **632n** may include a new CA certificate. In one example, the new certificate bundle **632n** may additionally include the current CA certificate. The new certificate bundle **632n**, including the new CA certificate, may supersede the current certificate bundle **632a** upon being distributed to the execution environment **618**. When the new certificate bundle **632n** supersedes the current certificate bundle **632a**, the new certificate bundle becomes the current certificate bundle **632a**. In one example, a new certificate bundle **632n** that includes a new CA certificate and a current CA certificate may supersede a current certificate bundle that includes the current CA certificate. Subsequently, the current CA certificate included in the new certificate bundle **632n** may be removed from the execution environment by distributing a new certificate bundle **632n** that includes the new CA certificate and that is exclusive of (does not include) the current CA certificate.

[0149] The certificate lifecycle module **630** performs operations associated with expiration and replacement of digital certificates. The certificate lifecycle module **630** may determine that a current CA certificate is approaching expiration. In response to determining that the CA certificate is approaching expiration, the certificate lifecycle module **630** may prompt the certificate authority **626** to generate a new CA certificate that will supersede the current CA certificate. Additionally, or alternatively, the certificate lifecycle module **630** may prompt the certificate authority **626** to generate new entity certificates. The certificate authority **626** may generate new entity certificates, for example, when prompted by the certificate lifecycle module **630**, to replace expiring entity certificates and/or in connection with issuance of new CA certificates.

[0150] In one example, the certificate lifecycle module **630** may maintain a data structure that identifies a certificate bundle **632** that is available for distribution to the execution environment. Additionally, or alternatively, the data structure may identify the CA certificate to be utilized by the certificate authority **626** when generating subordinate certificates. Additionally, or alternatively, the data structure may identify a set of subordinate certificates that are available for distribution to the execution environment. In one example, the data structure maintained by the certificate lifecycle

module **630** may include one or more epoch dates that represent an expiry date for one or more digital certificates. When the epoch date meets a threshold date, the certificate lifecycle module **630** may trigger issuance of new digital certificates to replace the digital certificates associated with the epoch date. An epoch date may correspond to at least a portion of the execution environment. In one example, a first epoch date may correspond to a CA certificate, and a second epoch date may correspond to a set of subordinate certificates issued from the CA certificate. Additionally, or alternatively, a first epoch date may correspond to a first portion of the execution environment, and a second epoch date may correspond to a second portion of the execution environment.

[0151] The certificate lifecycle module **630** may update an epoch date corresponding to one or more digital certificates to trigger issuance of new digital certificates to replace the digital certificates corresponding to the updated epoch date. Additionally, or alternatively, the certificate lifecycle module **630** may update an epoch date corresponding to at least a portion of the execution environment to trigger issuance of new digital certificates with respect to the portion of the execution environment corresponding to the updated epoch date. In one example, the certificate lifecycle module **630** may update an epoch date corresponding to a particular set of network entities, such as a host (e.g., network entity **604a**) and a set of nodes corresponding to the host (e.g., network entity **604b** and network entity **604n**). Additionally, or alternatively, the certificate lifecycle module **630** may update an epoch date corresponding to a particular region **608** and/or a particular availability domain **606**.

[0152] In one example, the certificate lifecycle module **630** may update an epoch date in response to a prompt from the orchestration service **614**. Additionally, or alternatively, the certificate lifecycle module **630** may update an epoch date in response to an input from a user input device. Additionally, or alternatively, the certificate lifecycle module **630** may update an epoch date in response to a security concern. The issuance of new digital certificates corresponding to the updated epoch date may mitigate the security concern.

[0153] The certificate distribution service **612** may distribute certificate bundles **632** and/or subordinate certificates to the execution environment. The certificate distribution service **612** may identify the certificate bundles **632** and/or subordinate certificates for distribution to the execution environment based on the data structure maintained by the certificate lifecycle module **630**. In one example, one or more network entities may periodically prompt the certificate distribution service **612** for a new certificate bundle **632**. When a new certificate bundle **632** is available for distribution, the certificate distribution service **612** may distribute the certificate bundle **632** to the one or more network entities in response to the periodic prompts. Additionally, or alternatively, one or more network entities may periodically prompt the certificate distribution service **612** for new subordinate certificates. When new subordinate certificates are available for distribution, the certificate distribution service **612** may distribute the new subordinate certificates to the one or more network entities in response to the periodic prompts. Additionally, or alternatively, the certificate distribution service **612** may periodically check the data structure for new certificate bundles and/or new subordinate certificates that are available for distribution and may distribute the new certificate bundles and/or new subordinate certificates to the corresponding network entities. Additionally, or alternatively, the certificate distribution service **612** may distribute certificate bundles and/or subordinate certificates in response to a prompt from the orchestration service **614**.

[0154] Separate instances of a particular certificate bundle may be distributed to different network entities. The separate instances of the particular certificate bundle may include the same set of one or more CA certificates. In one example, a first instance of a first certificate may include a first set of one or more CA certificates, and a second instance of the first certificate bundle may also include the first set of one or more CA certificates. The first instance of the first certificate bundle may be distributed to a first network entity, and the second instance of the first certificate bundle may be distributed to a second network entity. Separate instances of the same CA certificate(s) may be included in both the first instance and the second instance of the first certificate bundle.

Additionally, or alternatively, multiple instances of a CA certificate may be included in different certificate bundles. In one example, a first instance of a first CA certificate may be included in a first certificate bundle, and a second instance of the first CA certificate may be included in a second certificate bundle. The first instance and the second instance of the first CA certificate may be separate instances of the same CA certificate.

[0155] Referring further to FIG. 6A, the orchestration service **614** includes an orchestration agent **634**, a test validation module **636**, and a policy module **638**. The orchestration agent **634** may orchestrate one or more certificate distribution processes. Additionally, or alternatively, the orchestration agent **634** may orchestrate one or more testing processes. In one example, the orchestration agent **634** may orchestrate one or more testing processes at one or more incremental steps of a certificate distribution process. In one example, the orchestration agent **634** may orchestrate a certificate distribution process that incrementally increases exposure to the execution environment **618** in response to successful testing processes.

[0156] The orchestration agent **634** may interact with the PKI service **610** and/or the certificate distribution service in connection with orchestration of certificate distribution processes and/or testing processes. In one example, the orchestration agent **634** prompts the PKI service **610** to issue new digital certificates. Additionally, or alternatively, the orchestration agent **634** prompts the certificate distribution service **612** to distribute the new digital certificates to the corresponding network entities **604**. In one example, the orchestration agent **634** prompts the certificate lifecycle module **630** to update an epoch date to trigger issuance and/or distribution of new digital certificates.

[0157] The test validation module **636** may perform validations to validate testing processes orchestrated by the orchestration agent **634**. The validations performed by the validation module **636** may correspond to one or more testing operations of a testing process. Additionally, or alternatively, the validations may correspond to the testing process as a whole. In one example, the test validation module **636** may determine whether a testing processes and/or a testing operation is successful. The orchestration agent **634** may advance to a next stage of a testing process and/or a certificate distribution process in response to an indication from the test validation module **636**. The indication from the test validation module **636** may represent one or more successful testing results.

[0158] The policy module **638** may include one or more policies for certificate distribution processes and/or testing processes orchestrated by the orchestration agent **634**. The one or more policies may indicate timing and/or conditions for initiating certificate distribution processes and/or testing processes. Additionally, or alternatively, the one or more policies may indicate a sequence of steps for a particular certificate distribution process and/or testing process. The orchestration agent may initiate a certificate distribution process and/or a testing process based on one or more policies in the policy module **638**. Additionally, or alternatively, the orchestration agent may select a certificate distribution process and/or a testing process based on one or more policies in the policy module **638**.

B. Example Execution Environments

[0159] Referring to FIG. 6B, example execution environments **618** are further described. As shown in FIG. 6B, an execution environment **618** may include a plurality of network entities **604**, such as host network entity **604e**, node network entity **604f**, and node network entity **604m**. Additionally, or alternatively, the execution environment **618** may include network entity **604a** and network entity **604v** shown in FIG. 6A. As illustrated with respect to host network entity **604e**, a network entity **604** may include a PKI agent **650** (e.g., PKI agent **650a**), a certificate downloader **652** (e.g., certificate downloader **652a**), and a storage medium **654** (e.g., storage medium **654a**). The PKI agent **650** periodically prompts the PKI service **610** for new certificate bundles and/or new subordinate certificates. The certificate downloader **652** downloads new certificate bundles and/or new subordinate certificates from the certificate distribution service **612**. The certificate

downloader **652** installs certificate bundles to the storage medium **654**. Additionally, the certificate downloader **652** stores the subordinate certificates in storage medium **654**.

[0160] In one example, the certificate downloader **652** distributes certificate bundles and/or subordinate certificates to other network entities **604**, such as node network entity **604f** and/or node network entity **604m**. The certificate downloader **652** of host network entity **604e** may download a first entity certificate issued to host network entity **604e**, a second entity certificate issued to node network entity **604f**, and a third entity certificate issued to node network entity **604m**. The certificate downloader **652** may store the first entity certificate in the storage medium **654** associated with the host network entity **604e** for use by the host network entity **604e** when authenticating against a CA certificate in accordance with a security protocol. The certificate downloader **652** may transmit the second entity certificate to node network entity **604f**. Node network entity **604f** may store the second entity certificate in a storage medium associated with node network entity **604f** and may utilize the second entity certificate when authenticating against a CA certificate in accordance with a security protocol. The certificate downloader **652** may transmit the third entity certificate to node network entity **604m**. Node network entity **604m** may store the third entity certificate in a storage medium associated with node network entity **604m** and may utilize the third entity certificate when authenticating against a CA certificate in accordance with a security protocol.

i. Example Testing Services

[0161] In one example, as illustrated in FIG. **6B** with respect to host network entity **604e**, a network entity **604** may include a testing service **622**. Additionally, or alternatively, as illustrated in FIG. **6B** with respect to host network entity **604e**, a network entity **604** may include a production service **624**. The testing service **622** may execute testing operations corresponding to a new CA certificate that is yet to be activated in the portion of the execution environment **618** where the network entity **604** is located. The testing service **622** may execute the testing operations without impacting operations of the production service **624**. The testing service **622** may include a dedicated instance of a PKI agent **650** (e.g., PKI agent **650b**), a certificate downloader **652** (e.g., certificate downloader **652b**), and/or a storage medium **654** (e.g., storage medium **654b**). The testing service **622** may utilize PKI agent **650b**, certificate downloader **652b**, and/or storage medium **654b** to download certificate bundles and/or subordinate certificates to the testing service **622** without impacting operations of the production service **624**. In one example, the testing service **622** may download a new certificate bundle **632n** (FIG. **6A**) to storage medium **654b** while a current certificate bundle **632a** (FIG. **6A**) is stored in storage medium **654a**. The production service **624** may utilize the current certificate bundle **632a** while the testing service **622** executes testing operations corresponding to the new certificate bundle **632n**.

ii. Example Testing Service Validations

[0162] As shown in FIG. **6B**, the testing service **622** may include one or more testing modules **656**, such as testing module **656a** and testing module **656n**. A testing module **656** may perform one or more testing operations associated with a certificate bundle. The one or more testing operations may include one or more testing service validations. The one or more testing service validations may include validating that the testing service **622** has downloaded and installed the correct certificate bundle for testing. Additionally, or alternatively, the one or more testing service validations may include validating that the certificate bundle includes the correct set of CA certificates. A testing module **656** may validate that the testing service **622** has downloaded and installed the correct certificate bundle and/or that the certificate bundle includes the correct set of CA certificates by examining one or more file attributes of the certificate bundle and/or the CA certificates. In one example, the testing module **656** may compare a first set of file attributes corresponding to the certificate bundle and/or the CA certificates in the storage medium **654b** against a second set of file attributes corresponding to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. **6A**) of the PKI service **610**. The testing module

656 may determine that the storage medium **654b** includes the correct certificate bundle and/or the correct CA certificates when the first set of file attributes matches the second set of file attributes. [0163] Additionally, or alternatively, the testing module **656** may compute a first hash value corresponding to the certificate bundle and/or the CA certificates in the storage medium **654b** and compare the first hash value against a second hash value corresponding to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. 6A) of the PKI service **610**. The second hash value may be computed by the testing module **656** or by the PKI service **610**. The testing module **656** may determine that the storage medium **654b** includes the correct certificate bundle and/or the correct CA certificates when the first hash value matches the second hash value. [0164] Additionally, or alternatively, the testing module **656** may compare a first timestamp corresponding to the certificate bundle and/or the CA certificates in the storage medium **654b** against a second timestamp corresponding to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. 6A) of the PKI service **610**. The first timestamp may represent a time when the certificate bundle was downloaded by the testing service **622** or by the network entity **604** that executes the testing service **622**. The second timestamp may represent a time when the certificate bundle was generated by the PKI service **610**. The testing module **656** may determine that the storage medium **654b** includes the correct certificate bundle and/or the correct CA certificates when the first timestamp is subsequent to the second timestamp.

iii. Example Testing Service Authentications

[0165] In one example, the one or more testing operations may include one or more testing service authentications. The one or more testing service authentications may include authenticating one or more entity certificates against a CA certificate downloaded to the testing service **622**. The one or more entity certificates may be authenticated against a CA certificate by a testing module **656**. The one or more entity certificates may be downloaded to the testing service **622** by certificate downloader **652b**. Additionally, or alternatively, the testing service **622** may obtain one or more entity certificates from other network entities **604** for authentication against the CA certificate downloaded to the testing service **622**. The testing module **656** may determine that the certificate bundle and/or the CA certificates are configured correctly when the one or more entity certificates successfully authenticate to a CA certificate in the certificate bundle. In one example, the testing module **656** may authenticate one or more new entity certificates against a new CA certificate in a new certificate bundle to confirm that the one or more new entity certificates successfully authenticate to the new CA certificate. Additionally, or alternatively, the testing module **656** may authenticate one or more current entity certificates against a current CA certificate in a new certificate bundle to confirm that the one or more new current certificates successfully authenticate to the current CA certificate when the current CA certificate is included in the new certificate bundle. Additionally, or alternatively, a testing module **656** may validate the one or more entity certifies based on file attributes, hash values, and/or timestamps as described above with respect to certificate bundles and/or CA certificates.

iv. Example Production Service Validations

[0166] In one example, the one or more testing operations may include one or more production service validations. The one or more production service validations may include validating that a production service **624** has downloaded and installed the correct certificate bundle for testing. Additionally, or alternatively, the one or more production service validations may include validating that the certificate bundle includes the correct set of CA certificates. A production service **624** may validate that the production service **624** has downloaded and installed the correct certificate bundle and/or that the certificate bundle includes the correct set of CA certificates by examining one or more file attributes of the certificate bundle and/or the CA certificates. In one example, the production service **624** may compare a first set of file attributes corresponding to the certificate bundle and/or the CA certificates in the storage medium **654b** against a second set of file attributes corresponding to the certificate bundle and/or the CA certificates in the certificate

repository **628** (FIG. 6A) of the PKI service **610**. The production service **624** may determine that the storage medium **654b** includes the correct certificate bundle and/or the correct CA certificates when the first set of file attributes matches the second set of file attributes.

[0167] Additionally, or alternatively, the production service **624** may compute a first hash value corresponding to the certificate bundle and/or the CA certificates in the storage medium **654b** and compare the first hash value against a second hash value corresponding to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. 6A) of the PKI service **610**. The second hash value may be computed by the production service **624** or by the PKI service **610**. The production service **624** may determine that the storage medium **654b** includes the correct certificate bundle and/or the correct CA certificates when the first hash value matches the second hash value.

[0168] Additionally, or alternatively, the production service **624** may compare a first timestamp corresponding to the certificate bundle and/or the CA certificates in the storage medium **654b** against a second timestamp corresponding to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. 6A) of the PKI service **610**. The first timestamp may represent a time when the certificate bundle was downloaded by the production service **624** or by the network entity **604** that executes the production service **624**. The second timestamp may represent a time when the certificate bundle was generated by the PKI service **610**. The production service **624** may determine that the storage medium **654b** includes the correct certificate bundle and/or the correct CA certificates when the first timestamp is subsequent to the second timestamp.

v. Example Production Service Authentications

[0169] In one example, the one or more testing operations may include one or more production service authentications. The one or more production service authentications may include authenticating one or more entity certificates against a CA certificate downloaded to the production service **624**. The one or more one or more production service authentications may be performed in connection with production operations executed by the production service **624**. Additionally, or alternatively, the one or more one or more production service authentications may be performed as testing operations that are distinct from production operations executed by the production service **624**. The one or more entity certificates may be authenticated against a CA certificate by the production service **624**. Production service authentications may be performed as testing operations that are distinct from production operations executed by the production service **624**, and the one or more entity certificates may be downloaded to the production service **624** by certificate downloader **652b**. Additionally, or alternatively, the production service **624** may obtain one or more entity certificates from other network entities **604** for authentication against the CA certificate in production service authentications that are performed as production operations and/or testing operations. The production service **624** may determine that the certificate bundle and/or the CA certificates are configured correctly when the one or more entity certificates successfully authenticate to a CA certificate in the certificate bundle. In one example, the production service **624** may authenticate one or more new entity certificates against a new CA certificate in a new certificate bundle to confirm that the one or more new entity certificates successfully authenticate to the new CA certificate. Additionally, or alternatively, the production service **624** may authenticate one or more current entity certificates against a current CA certificate in a new certificate bundle to confirm that the one or more new current certificates successfully authenticate to the current CA certificate when the current CA certificate is included in the new certificate bundle. Additionally, or alternatively, the production service **624** may validate the one or more entity certifies based on file attributes, hash values, and/or timestamps as described above with respect to certificate bundles and/or CA certificates.

vi. Example Event Service Validations for Execution Environment Operations

[0170] Referring further to FIG. 6B, as illustrated with respect to host network entity **604e**, a network entity **604** may include an event collector **658** (e.g., event collector **658a**). An event collector **658** may collect information pertaining to events occurring with respect to the network

entity **604** and transmit the information to the event monitoring service **616**. The event monitoring service **616** may transmit the information to the orchestration service **614**.

[0171] In one example, the event monitoring service transmits test results to the orchestration service **614**. In one example, the event monitoring service **616** may generate event logs, and the orchestration service **614** may detect events in the event logs generated by the event monitoring service **616**. The events in the event logs may include, or may be indicative of, the test results. In one example, the event monitoring service **616** may transmit the event logs to the orchestration service **614**.

[0172] The orchestration service **614** may perform one or more testing operations based on information from the event monitoring service **616**. The one or more event service validations may include one or more testing operations performed by the orchestration service **614** based on information from the event monitoring service **616**.

[0173] In one example, the event service validations may be associated with testing operations performed by a testing service **622**. In one example, the information from the event monitoring service **616** may indicate a testing service **622** has downloaded and installed a certificate bundle for testing, and/or a testing module **656** has successfully validated that the correct certificate bundle has been installed, and/or the certificate bundle includes the set CA certificates. Additionally, or alternatively, the orchestration service **614** may utilize the information from the event monitoring service **616** to validate the correct certificate bundle has been installed, and/or the certificate bundle includes the set CA certificates. Additionally, or alternatively, the information from the event monitoring service **616** may indicate a testing service **622** has downloaded one or more entity certificates, and/or a testing module **656** has successfully authenticated the one or more entity certificates against a corresponding CA certificate. The information from the event monitoring service **616** may include file attributes, hash values, and/or timestamps associated with certificate bundles and/or entity certificates. The orchestration service **614** may validate certificate bundles, CA certificates, and/or entity certificates based on file attributes, hash values, and/or timestamps included in the information from the event monitoring service **616**.

[0174] In one example, the event service validations may be associated with testing operations performed by a production service **624**. In one example, the information from the event monitoring service **616** may indicate that the production service **624** has downloaded and installed a certificate bundle, and/or the production service **624** has successfully validated that the correct certificate bundle has been installed, and/or the certificate bundle includes the set CA certificates.

Additionally, or alternatively, the orchestration service **614** may utilize the information from the event monitoring service **616** to validate the correct certificate bundle has been installed for use by the production service **624**, and/or the certificate bundle includes the set CA certificates.

Additionally, or alternatively, the information from the event monitoring service **616** may indicate the production service **624** has downloaded one or more entity certificates, and/or a testing module **656** has successfully authenticated the one or more entity certificates against a corresponding CA certificate. The information from the event monitoring service **616** may include file attributes, hash values, and/or timestamps associated with certificate bundles and/or entity certificates. The orchestration service **614** may validate certificate bundles, CA certificates, and/or entity certificates based on file attributes, hash values, and/or timestamps included in the information from the event monitoring service **616**.

C. Example Sandbox Sub-Environments

[0175] Referring to FIG. 6C, example sandbox sub-environments **620** are further described. As shown in FIG. 6C, a sandbox sub-environment **620** may include a plurality of sandbox instances **670**, such as sandbox instance **670a** and sandbox instance **670n**. In one example, a sandbox sub-environment **620** may include different sandbox instances **670** that have a configuration that corresponds to a network entity in the execution environment **618**. Additionally, or alternatively, a sandbox instance **670** may have a configuration for performing a sandbox iteration of a certificate

distribution process and/or for testing the sandbox iteration of certificate distribution process without having a configuration that corresponds to a network entity **604** in the execution environment **618**.

[0176] A sandbox instance **670** includes one or more sandbox services **672**. For example, as shown in FIG. 6C, sandbox instance **670_n** includes sandbox service **672_a** and sandbox service **672_n**. The one or more sandbox services **672** may execute operations associated with performing a sandbox iteration of a certificate distribution process. Additionally, or alternatively, the one or more sandbox services **672** may execute testing operations corresponding to the sandbox iteration of the certificate distribution process. The one or more sandbox services **672** may execute the operations associated with the sandbox iteration of the certificate distribution process without impacting operations of the execution environment **618**. In one example, a sandbox service **672** may have a configuration that corresponds to a production service **624** (FIG. 6A) of a network entity **604** in the execution environment **618**. Additionally, or alternatively, a sandbox service **672** may have a configuration for performing the sandbox iteration of the certificate distribution process and/or for testing the sandbox iteration of certificate distribution process without having a configuration that corresponds to a production service **624** of a network entity **604** in the execution environment **618**.

[0177] The sandbox sub-environment **620** may include a dedicated instance of a PKI agent **650** (e.g., PKI agent **650_n**), a certificate downloader **652** (e.g., certificate downloader **652_n**), and/or a storage medium **654** (e.g., storage medium **654_n**). In one example, PKI agent **650_n**, certificate downloader **652_n**, and/or storage medium **654_n** may be particular to sandbox instance **670_n**. Alternatively, PKI agent **650_n**, certificate downloader **652_n**, and/or storage medium **654_n** may be utilized throughout the sandbox sub-environment **620** such as by a plurality of sandbox instance **670**. The sandbox instance **670_n** may utilize PKI agent **650_b**, certificate downloader **652_b**, and/or storage medium **654_b** to download certificate bundles and/or subordinate certificates to the testing service **622** without impacting operations of the execution environment **618**. The sandbox iteration of the certificate distribution process may include distributing a new certificate bundle **632_n** (FIG. 6A) that includes a new CA certificate to the sandbox sub-environment **620**, while a current certificate bundle **632_a** (FIG. 6A) that includes a current CA certificate is utilized in the execution environment **618**. Sandbox instance **670_n** may download a new certificate bundle **632_n** (FIG. 6A) to storage medium **654_n** and execute one or more testing operations corresponding to the new certificate bundle **632_n**.

i. Example Sandbox Service Validations

[0178] A sandbox services **672** may perform one or more testing operations associated with a certificate bundle. The one or more testing operations may include one or more sandbox service validations. The one or more sandbox service validations may include validating that the sandbox instance **670** has downloaded and installed the correct certificate bundle for testing. Additionally, or alternatively, the one or more sandbox service validations may include validating that the certificate bundle includes the correct set of CA certificates. A sandbox service **672** may validate that the correct certificate bundle has been downloaded and installed, and/or the certificate bundle includes the correct set of CA certificates by examining one or more file attributes of the certificate bundle and/or the CA certificates. In one example, the sandbox service **672** may compare a first set of file attributes, corresponding to the certificate bundle and/or the CA certificates in the storage medium **654_n** of the sandbox instance **670_n**, against a second set of file attributes, corresponding to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. 6A) of the PKI service **610**. The sandbox service **672** may determine that the storage medium **654_n** includes the correct certificate bundle and/or the correct CA certificates when the first set of file attributes matches the second set of file attributes.

[0179] Additionally, or alternatively, a sandbox service **672** may compute a first hash value corresponding to the certificate bundle and/or the CA certificates in the storage medium **654_n** of the sandbox instance **670_n** and compare the first hash value against a second hash value corresponding

to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. 6A) of the PKI service **610**. The second hash value may be computed by the sandbox service **672** or by the PKI service **610**. The sandbox service **672** may determine that the storage medium **654n** includes the correct certificate bundle and/or the correct CA certificates when the first hash value matches the second hash value.

[0180] Additionally, or alternatively, a sandbox service **672** may compare a first timestamp corresponding to the certificate bundle and/or the CA certificates in the storage medium **654n** of the sandbox instance **670n** against a second timestamp corresponding to the certificate bundle and/or the CA certificates in the certificate repository **628** (FIG. 6A) of the PKI service **610**. The first timestamp may represent a time when the certificate bundle was downloaded by the sandbox service **672** or the sandbox instance **670n** executing the sandbox service **672**. The second timestamp may represent a time when the certificate bundle was generated by the PKI service **610**. The sandbox service **672** may determine that the storage medium **654n** includes the correct certificate bundle and/or the correct CA certificates when the first timestamp is subsequent to the second timestamp.

ii. Example Sandbox Service Authentications

[0181] In one example, the one or more testing operations may include one or more sandbox service authentications. The one or more sandbox service authentications may include authenticating one or more entity certificates against a CA certificate downloaded to the sandbox instance **670n**. The one or more entity certificates may be authenticated against a CA certificate by a sandbox service **672**. The one or more entity certificates may be downloaded to the sandbox instance **670n** by certificate downloader **652n**. The certificate downloader **652n** may store the one or more entity certificates in storage medium **654n**. The sandbox service **627** may obtain the one or more entity certificates from the storage medium **654n** for authentication against the CA certificate. Additionally, or alternatively, the sandbox service **672** may obtain one or more entity certificates from other sandbox services **672** and/or from other sandbox instances **670** for authentication against the CA certificate downloaded to sandbox instance **670n**. The sandbox service **672** may determine the certificate bundle and/or the CA certificates are configured correctly when the one or more entity certificates successfully authenticate to a CA certificate in the certificate bundle. In one example, the sandbox service **672** may authenticate one or more new entity certificates against a new CA certificate in a new certificate bundle to confirm the one or more new entity certificates successfully authenticate to the new CA certificate. Additionally, or alternatively, the sandbox service **672** may authenticate one or more current entity certificates against a current CA certificate in a new certificate bundle to confirm the one or more new current certificates successfully authenticate to the current CA certificate when the current CA certificate is included in the new certificate bundle. Additionally, or alternatively, the sandbox service **672** may validate the one or more entity certifies based on file attributes, hash values, and/or timestamps as described above with respect to certificate bundles and/or CA certificates.

iii. Example Event Service Validations for Sandbox Sub-Environment Operations

[0182] Referring further to FIG. 6C, as illustrated with respect to sandbox instance **670n**, a sandbox instance **670** may include an event collector **658** (e.g., event collector **658n**). An event collector **658** may collect information pertaining to events occurring with respect to the sandbox instance **670** and transmit the information to the event monitoring service **616**. The event monitoring service **616** may transmit the information to the orchestration service **614**. The orchestration service **614** may perform one or more testing operations based on information from the event monitoring service **616**. The one or more event service validations may include one or more testing operations performed by the orchestration service **614** based on information from the event monitoring service **616**.

[0183] In one example, the event service validations may be associated with testing operations performed by a sandbox service **672**. In one example, the information from the event monitoring

service **616** may indicate the sandbox instance **670** has downloaded and installed a certificate bundle for testing, and/or a sandbox service **672** has successfully validated that the correct certificate bundle has been installed, and/or the certificate bundle includes the set CA certificates. Additionally, or alternatively, the orchestration service **614** may utilize the information from the event monitoring service **616** to validate the correct certificate bundle has been installed, and/or the certificate bundle includes the set CA certificates. Additionally, or alternatively, the information from the event monitoring service **616** may indicate a sandbox instance **670** has downloaded one or more entity certificates, and/or a sandbox service **672** has successfully authenticated the one or more entity certificates against a corresponding CA certificate. The information from the event monitoring service **616** may include file attributes, hash values, and/or timestamps associated with certificate bundles and/or entity certificates. The orchestration service **614** may validate certificate bundles, CA certificates, and/or entity certificates based on file attributes, hash values, and/or timestamps included in the information from the event monitoring service **616**.

D. Example Network Entities

[0184] Referring again to FIG. **6A**, the system **600** may include a plurality of network entities **604**. The network entities **604** may be located throughout the virtual cloud network **602**. A network entity **604** may reside on a substrate network, an overlay network, or a network interface. A network entity **604** may be implemented in hardware and/or software. A network entity may include a host, a node, an agent, a service, a component, an endpoint, or other element. The plurality of network entities **604** may include one or more substrate entities, one or more interface entities, and/or one or more overlay entities.

[0185] As used herein, the term “substrate entity” refers to a network entity **604** implemented in a substrate network. As used herein, the term “substrate network” refers to a physical network infrastructure. The substrate network provides a foundation of a virtual cloud network. The substrate network may include physical network devices, such as routers, switches, network links, and other networking components. The substrate network may provide the basic connectivity and transport capabilities necessary for data transmission within and between data centers.

[0186] The one or more substrate entities may include substrate hosts, routers, firewalls appliances, load balancers, storage devices, and/or substrate services. A substrate host may include an endpoint within the substrate network, such as a bare metal host, a virtual machine, a container, or a physical server. A substrate service may include a service executing or executable on a substrate entity, such as a firmware service, a network connectivity service, an addressing service, a name resolution service, a security service, a network monitoring service, a load balancing service, and/or a storage service. A firmware service may be associated with functionality or management of network infrastructure components or services, such as network devices, boot-up or initialization process, hardware controls, feature enablement, updates, hardware abstraction, network configuration, and/or network management. In one example, a substrate entity may include a combination of hardware and software. In one example, the one or more substrate entities may include one or more substrate hosts and/or one or more substrate services. In one example, a substrate host may include a bare metal host. In one example, a substrate service may include a firmware service. The substrate entities may communicate with one another, and/or with other network entities **604** using logical network addresses assigned within the overlay network.

[0187] As used herein, the term “network interface” refers to a communication interface between a substrate network and an overlay network, such as a network interface card, a smartNIC, or the like. A network interface may include one or more interface entities, such as a node on the network interface or an interface service executing or executable on the network interface. A node on the network interface may include a programmable hardware component, a memory component, or a gateway component. In one example, a network interface may include a network interface card such as a smartNIC. Additionally, or alternatively, a network interface may include a node or an endpoint on a network interface card or smartNIC.

[0188] A gateway component may provide connectivity between the substrate network and the network interface and/or between the network interface and the overlay network. For example, a gateway component may enable communication between overlay entities and substrate entities. Additionally, or alternatively, a gateway component may provide connectivity between the overlay network and external networks, such as the internet or other networks outside the overlay network. For example, an overlay gateway may enable communication between overlay entities and external endpoints.

[0189] As used herein, the term “overlay network” refers to a virtual network built on a substrate network using software-defined networking (SDN), virtualization, tunneling, and/or encapsulation technologies. An overlay network may operate independently of the underlying substrate network. An overlay network may provide logical separation and isolation of traffic, enable virtual network provisioning, and/or allow for implementation of various network services and policies. Virtual machines, hosts, containers, or virtual network functions running on a substrate network may be connected via an overlay network.

[0190] As used herein, the term “overlay entity” refers to a network entity implemented on an overlay network. The overlay network may include a plurality of overlay entities. The plurality of overlay entities may include overlay hosts, overlay services, subnets, overlay controllers, and/or overlay clients. In one example, the overlay network may include a plurality of overlay entities. In one example, an overlay entity may include an overlay host. Additionally, or alternatively, an overlay entity may include an overlay service. The plurality of overlay entities may communicate with one another using logical network addresses assigned within the overlay network.

[0191] An overlay host may include an endpoint within the overlay network, such as a virtual machine, a container, or a physical server. An overlay service may include a service executing or executable on an overlay entity. An overlay service may include a client-specific service such as a service installed by a client. Additionally, or alternatively, an overlay service may include a virtual network creation service, a virtual network management service, a virtual machine orchestration service, a container orchestration service, a network virtualization service, an overlay security service, a load balancing service, a multi-tenancy service, and/or a tenant isolation service.

[0192] A subnet may include a virtual network segment that has a distinct addressing scheme and/or a distinct set of network policies or services. A subnet may include a set of overlay hosts. Multiple subnets may be utilized to partition respective sets of overlay hosts. An overlay controller may oversee management, control, provisioning, configuration, and/or monitoring of an overlay network, network entities on the overlay network, and/or network policies within the overlay. An overlay controller interacts with the underlying substrate network, for example, to coordinate the operation of overlay hosts and/or communications across virtual switches and tunnels. An overlay client may include an endpoint or device that initiates communication within the overlay network. An overlay client may be a specific instance or role within an overlay host. An overlay host may include a set of overlay clients. An overlay client may include a consumer or user of services provided by overlay hosts or the IaaS. An overlay client may request and consume resources or services from overlay hosts that act as consumers or clients of those resources or services.

[0193] The plurality of network entities **604** may include a plurality of data repositories. The data repositories may include any type of storage unit and/or device (e.g., a file system, database, collection of tables, or any other storage mechanism) for storing data. Further, a data repository may include multiple different storage units and/or devices. The multiple different storage units and/or devices may or may not be of the same type or located at the same physical site. The data repositories may share one or more storage units with one another. Additionally, or alternatively, the data repositories may include one or more storage units that differ from one another. Further, one or more of the data repositories may be implemented or executed on the same computing system as virtual cloud network **602**. Additionally, or alternatively, one or more of the data repositories may be implemented or executed on a computing system separate from virtual cloud

network **602**.

[0194] In one or more embodiments, the system **600** may include more or fewer components than the components illustrated in FIGS. **6A-6C**. The components illustrated in FIGS. **6A-6C** may be local to or remote from one another. The components illustrated in FIGS. **6A-6C** may include software and/or hardware components. Components may be distributed over multiple applications and/or machines. Multiple components may be combined into one application and/or machine. Operations described with respect to one component may instead be performed by another component. Additional embodiments and/or examples relating to the system **600** are described above in Section 2, titled “Cloud Computing Technology”.

[0195] In an embodiment, the system **600** may include various components implemented on one or more digital devices. The term “digital device” refers to any hardware device that includes a processor. A digital device may refer to a physical device executing an application or a virtual machine. Examples of digital devices include a computer, a tablet, a laptop, a desktop, a netbook, a server, a web server, a network policy server, a proxy server, a generic machine, a function-specific hardware device, a hardware router, a hardware switch, a hardware firewall, a hardware firewall, a hardware network address translator (NAT), a hardware load balancer, a mainframe, a television, a content receiver, a set-top box, a printer, a mobile handset, a smartphone, a personal digital assistant (PDA), a wireless receiver and/or transmitter, a base station, a communication management device, a router, a switch, a controller, an access point, and/or a client device.

6. Example Certificate Distribution Processes

[0196] Referring now to FIGS. **7A-7C**, operations pertaining to an example certificate distribution process are further described. The operations **700** described with reference to FIGS. **7A-7C** may be associated with distributing a new set of one or more CA certificates to a plurality of network entities for use in a certificate authentication process. The CA certificates may include root CA certificates and/or intermediate CA certificates. The CA certificates may be housed in a certificate bundle. One or more operations **700** illustrated in FIGS. **7A-7C** may be modified, rearranged, or omitted. Accordingly, the particular sequence of operations **700** illustrated in FIGS. **7A-7C** should not be construed as limiting the scope of one or more embodiments. As shown in FIG. **7A**, operations **700** pertaining to the certificate distribution process may include a series or sequence of phases. In one example, as shown, the operations **700** include a series or sequence of phases such as four (4) phases. In another example, the series or sequence of phases may include more or less than four (4) phases, for example, including at least a portion of the phases shown in FIG. **7A**.

[0197] In one example, the certificate distribution process may be orchestrated by an orchestration service. In one example, the certificate distribution process may be executed in response to a trigger condition. The trigger condition may be determined based on at least one of the following: an expiry date of a certificate bundle and/or a CA certificate, a security alert, or an operator input. The trigger condition may be detected by the orchestration service.

[0198] In one example, prior to executing the certificate distribution process, the orchestration service may determine whether another certificate distribution process is taking place. Additionally, or alternatively, the orchestration service may determine whether any certificate distribution processes are inactive prior to commencing a certificate distribution process. In one example, the orchestration service may determine whether a certificate distribution process is taking place with respect to a first portion of the virtual cloud network prior to commencing a certificate distribution process with respect to the first portion of the virtual cloud network. In response to determining that any certificate distribution processes are inactive, the orchestration service may execute the certificate distribution process.

[0199] Referring to FIG. **7A**, the operations **700** include, at block **702**, generating and distributing a new certificate bundle including a new set of one or more CA certificates to a set of network entities associated with a virtual cloud network. The new set of one or more CA certificates may include at least one new CA certificate. Additionally, or alternatively, a set of new CA certificates

may be added to existing certificate bundles.

[0200] At block **704**, the operations **700** include determining whether the new certificate bundle has been successfully distributed. When the new certificate bundle has been successfully distributed, the operations **700** may proceed to a next phase in the distribution process. The operation at block **702** and/or **704** may represent Phase 1 of a certificate distribution process.

[0201] In one example, the operations **700** include, at block **706**, activating the new CA certificates in the new certificate bundle. In one example, activating the new CA certificate may include the PKI service issuing one or more entity certificates. The operation at block **706** may represent Phase 2 of a certificate distribution process. The new CA certificate may be activated in at least a portion of the execution environment. In one example, the new CA certificate may be sequentially activated in a plurality of portions of the execution environment.

[0202] The orchestration service may activate the new CA certificate by designating the new CA certificate as a target CA certificate for issuing new entity certificates in the portion of the execution environment where the new CA certificate is being activated. The orchestration service may instruct the certificate lifecycle module to designate the new CA certificate as the target CA certificate for issuing new entity certificates, and the certificate lifecycle module may update a data structure to indicate that the new CA certificate is designated as the target CA certificate. In one example, the certificate lifecycle module may update an epoch date corresponding to the target network entity. The new CA certificate may be designated as the target CA certificate with respect to the portion of the execution environment where the new CA certificate is being activated. In one example, the new CA certificate is designated as the target CA certificate with respect to a host network entity and a set of node network entities serviced by the host network entity. The designation of the new CA certificate as the target CA certificate may activate the CA certificate in at least a portion of the execution environment.

[0203] In one example, the operations **700** include, at block **708**, distributing new entity certificates to the set of network entities. At block **710**, the operations **700** include determining whether the new entity certificates have been successfully distributed. Additionally, or alternatively, the operations may include determining whether the new intermediate CA certificates have been successfully distributed. When the new entity certificates (and/or the new intermediate CA certificates) have been successfully distributed, the operations **700** may proceed to a next phase in the distribution process. The operation at block **708** and **710** may represent Phase 3 of a certificate distribution process.

[0204] The new entity certificates may be distributed to network entities in at least a portion of the execution environment corresponding to the activation of the new CA certificate at block **706**. In one example, the CA certificate may be sequentially activated in a plurality of portions of the execution environment corresponding to activation of the new CA certificate at block **706**.

[0205] In one example, the operations **700** include, at block **712**, removing earlier CA certificates that were distributed prior to the new CA certificates. For example, the earlier CA certificates may include CA certificates that are being superseded by the new CA certificates. Removing an earlier CA certificate with respect to a particular network entity may include deleting the earlier CA certificate from a storage medium associated with the particular network entity. For example, the operations **700** include transmitting, to the particular network entity, an instruction to delete the earlier CA certificate from the storage medium. In response to receiving the instruction, the particular network entity may delete the earlier CA certificate from the storage medium.

[0206] Additionally, or alternatively, removing an earlier CA certificate with respect to a network entity may include replacing a first new certificate bundle with a second new certificate bundle. The first new certificate bundle includes the new CA certificates and the earlier CA certificates, and the second new certificate bundle includes the new CA certificates and does not include the earlier CA certificates, effectively removing the earlier CA certificates from the first new certificate bundle. The second new certificate bundle may be distributed to the particular network entity and

installed in the storage medium associated with the particular network entity, and the first new certificate bundle may be deleted from the storage medium. The operation at block **712** may represent Phase 4 of a certificate distribution process.

[0207] Referring to FIG. **7B**, example operations **700** associated with distributing a new certificate bundle, at block **702** of FIG. **7A**, are further described. As shown in FIG. **7B**, the operations **700** include, at block **720**, generating a new certificate bundle including a new CA certificate and a current CA certificate, and installing the new certificate bundle in a sandbox instance executing in a sandbox sub-environment. The new certificate bundle may be generated by a PKI service. A certificate downloader may receive the new certificate bundle and install the new certificate bundle in a storage medium associated with the sandbox instance.

[0208] At block **722**, the operations **700** include performing a testing process for testing the new certificate bundle in a sandbox sub-environment. The testing process may include at least a portion of the testing process described with reference to FIGS. **8A-8C**. Additionally, or alternatively, the testing process may include one or more of the testing operations described with reference to FIG. **9A**. In one example, the testing process at block **722** includes one or more sandbox service validations and/or one or more event service validations.

[0209] At block **724**, the operations **700** include determining whether the testing process performed at block **722** is successful. When the orchestration service determines that the testing process performed at block **722** is successful, the operations may proceed to block **726**. When the orchestration service determines that the testing process performed at block **722** is unsuccessful, the orchestration service may generate an alert, and/or the orchestration service may suspend or abort the certificate distribution process. Additionally, or alternatively, the orchestration service may initiate a troubleshooting process to determine one or more reasons for the unsuccessful testing process.

[0210] At block **726**, the operations **700** include generating a set of new entity certificates based on the new CA certificate for testing in the sandbox sub-environment. The certificate authority of the PKI infrastructure may generate the new entity certificates. In one example, the new entity certificates include sample entity certificates. The sample entity certificates may be representative of a set of one or more types of network entities executing in the execution environment and/or that may be instantiated in the execution environment. The sample entity certificates may represent the types of entity certificates that may be issued based on the new CA certificate when the new CA certificate is activated in the execution environment. Additionally, or alternatively, the new entity certificates may include entity certificates corresponding to one or more network entities in particular. For example, the certificate authority may generate entity certificates for one or more particular network entities for use in the testing process performed in the sandbox sub-environment.

[0211] At block **728**, the operations **700** include transmitting the set of new entity certificates to a sandbox instance executing in the sandbox sub-environment. The certificate distribution service may transmit the set of new entity certificates to the sandbox instance. At block **730**, the operations **700** include storing the set of new entity certificates in a storage medium in the sandbox sub-environment associated with the sandbox instance. The certificate downloader may receive and/or download the set of new entity certificates and store the set of new entity certificates in the storage medium associated with the sandbox instance.

[0212] At block **732**, the operations **700** include performing a testing process for testing the set of new entity certificates in the sandbox sub-environment. The testing process may include at least a portion of the testing process described with reference to FIGS. **8A-8C**. Additionally, or alternatively, the testing process may include one or more of the testing operations described with reference to FIG. **9A**. In one example, the testing process at block **732** includes one or more sandbox service validations and/or one or more event service validations. Additionally, or alternatively, the testing process at block **732** may include one or more sandbox service authentications.

[0213] At block **734**, the operations **700** include determining whether the testing process performed at block **732** is successful. When the orchestration service determines that the testing process performed at block **732** is successful, the operations may proceed to block **736**. When the orchestration service determines that the testing process performed at block **732** is unsuccessful, the orchestration service may generate an alert, and/or the orchestration service may suspend or abort the certificate distribution process. Additionally, or alternatively, the orchestration service may initiate a troubleshooting process to determine one or more reasons for the unsuccessful testing process.

[0214] At block **736**, the operations **700** include publishing the new certificate bundle. The new certificate bundle may be published at least by making the new certificate bundle available for download by network entities in the execution environment. The new certificate bundle may be stored in a certificate repository for download by network entities in the execution environment. Additionally, a certificate lifecycle module may update a data structure to indicate that the certificate bundle is available for distribution to the execution environment.

[0215] In one example, the orchestration service may initiate installation of the new certificate bundle in the execution environment, for example, by making the new certificate bundle available for download by network entities in the execution environment. The installation of the new certificate bundle may be initiated in response to determining that the one or more testing operations are successful, at block **734**. Additionally, or alternatively, when the orchestration service determines that the one or more testing operations are unsuccessful, the orchestration service may refrain from initiating installation of the new certificate bundle in the execution environment.

[0216] At block **738**, the operations **700** include network entities in the execution environment downloading the new certificate bundle. A network entity that downloads the new certificate bundle may install the new certificate bundle in a storage medium associated with the network entity.

[0217] Referring to FIG. 7C, example operations **700** associated with activating CA certificates in a new certificate bundle, at block **706** of FIG. 7A, are further described. As shown in FIG. 7C, the operations **700** include, at block **740**, designating the new CA certificate as a target CA certificate for issuing new entity certificates associated with a target network entity executing in the execution environment. The orchestration service may provide an instruction to the certificate lifecycle module to designating the new CA certificate as the target CA certificate for issuing new entity certificates, and the certificate lifecycle module may update a data structure to indicate that the new CA certificate is designated as the target CA certificate. In one example, the certificate lifecycle module may update an epoch date corresponding to the target network entity. The new CA certificate may be designated as the target CA certificate with respect to a portion of the execution environment. In one example, the new CA certificate is designated as the target CA certificate with respect to a host network entity and a set of node network entities serviced by the host network entity. The designation of the new CA certificate as the target CA certificate may activate the CA certificate in at least a portion of the execution environment.

[0218] At block **742**, the operations **700** include receiving a request from the target network entity for a set of new entity certificates for testing in the execution environment. A PKI agent of the target network entity may transmit the request for the set of new entity certificates to a PKI service. At block **744**, the operations **700** include generating the set of new entity certificates requested by the target network entity. The PKI service may generate the set of new entity certificates. In one example, the PKI service may generate the set of new entity certificates in response to the request from the PKI agent. Additionally, or alternatively, the new entity certificates may be generated by the PKI service prior to receiving the request from the PKI agent. At block **746**, the operations **700** include transmitting the set of new entity certificates to the target network entity. The certificate distribution service may transmit the new entity certificates to the target network entity. A certificate downloader associated with the target network entity may receive and/or download the

set of new entity certificates and store the set of new entity certificates in a storage medium associated with the target network entity.

[0219] At block **748**, the operations **700** include performing a testing process for utilizing the target network entity for testing the new certificate bundle in the execution environment.

[0220] The testing process may include at least a portion of the testing process described with reference to FIGS. **8A-8C**. Additionally, or alternatively, the testing process may include one or more of the testing operations described with reference to FIGS. **9B** and/or **9C**. In one example, the testing process at block **748** includes one or more testing service validations and/or one or more testing service authentications. Additionally, or alternatively, the testing process at block **748** may include one or more production service validations and/or one or more production service authentications. Additionally, or alternatively, the testing process at block **732** may include one or more event service validations.

[0221] At block **750**, the operations **700** include determining whether the testing process preformed at block **748** is successful. When the orchestration service determines that the testing process preformed at block **748** is successful, in one example, the operations may proceed to block **752** (Option A). Additionally, or alternatively, when the orchestration service determines that the testing process preformed at block **748** is successful, the operations may proceed to block **754** (Option B). When the orchestration service determines that the testing process preformed at block **748** is unsuccessful, the orchestration service may generate an alert, and/or the orchestration service may suspend or abort the certificate distribution process. In one example, the operations may proceed to block **752** when the orchestration service determines that the testing process performed at block **748** is unsuccessful. Additionally, or alternatively, the orchestration service may initiate a troubleshooting process to determine one or more reasons for the unsuccessful testing process.

[0222] At block **752**, the operations **700** include designating the current CA certificate as the target CA certificate for issuing new entity certificates associated with the target network entity for use in the execution environment. The operations at block **752** may reverse the operations at block **740** that designated the new CA certificate as a target CA certificate. When the testing process performed at block **748** is unsuccessful, the current CA certificate is designated as the target CA certificate at block **752**, so new entity certificates will be generated based on the current CA certificate and transmitted to the target network entity. The target network entity may utilize the new entity certificates to continue executing operations in the execution environment, for example, following the suspending or aborting of the certificate distribution process and/or during the troubleshooting process. When, at block **750**, the testing process performed at block **748** is determined successful, in one example (Option A), the current CA certificate is designated as the target CA certificate at block **752**, so new entity certificates will be generated based on the current CA certificate and transmitted to the target network entity. The target network entity may utilize the new entity certificates to continue executing operations in the execution environment, for example, while the testing process is performed with respect to other network entities. The certificate lifecycle module may update the data structure to indicate that the current CA certificate is designated as the target CA certificate. The update to the data structure at block **752** may reverse the update to the data structure at block **740**.

[0223] At block **754**, the operations **700** include determining whether or not to perform the testing process with respect to another target network entity. When the orchestration service determines that the testing process will be performed with respect to another target network entity, the operations may return to block **740**. When the orchestration service determines that the testing processes are complete, the operations **700** may proceed to block **756**.

[0224] In one example, when the orchestration service determines at block **750** that the testing process performed at block **748** with respect to a first portion of the execution environment is successful, and the operations proceed to block **754** (Option B), the operations **700** may include utilizing the new CA certificate as the target CA certificate for issuing new entity certificates to

network entities in the first portion of the execution environment. The new CA certificate may be activated in the first portion of the execution environment by designating the new CA certificate as the target CA certificate for issuing new entity certificates to network entities in the first portion of the execution environment. The PKI service may generate new entity certificates for the network entities in the first portion of the execution environment that were not issued a new entity certificate for authentication against the new CA certificate at block **740**. The network entities in the first portion of the execution environment may utilize the new entity certificates to authenticate against the new CA certificate in accordance with a security protocol associated with production operations in the execution environment.

[0225] Additionally, or alternatively, when the orchestration service determines at block **750** that the testing process performed at block **748** with respect to a first portion of the execution environment is successful, and the operations proceed to block **754** (Option B), the operations **700** may include initiating activation of the new CA certificate in a second portion of the execution environment. The orchestration service may initiate activation of the new CA certificate in a second portion of the execution environment by designating the new CA certificate as the target CA certificate for issuing new entity certificates to network entities in the execution environment. The PKI service may generate new entity certificates for the network entities in the second portion of the execution environment, and the network entities in the second portion of the execution environment may utilize the new entity certificates to authenticate against the new CA certificate in accordance with a security protocol associated with production operations in the execution environment.

[0226] At block **756**, the operations **700** include determining whether the testing processes performed at block **748** with respect to one or more of the iterations of target network entities were successful. When the orchestration service determines that the testing processes performed at block **748** were successful, the operations may proceed to block **758**. When the orchestration service determines, at block **750**, that one or more of the testing process performed at block **748** were unsuccessful, the orchestration service may generate an alert, and/or the orchestration service may suspend or abort the certificate distribution process. Additionally, or alternatively, the orchestration service may initiate a troubleshooting process to determine one or more reasons for the unsuccessful testing process.

[0227] At block **758**, the operations **700** include designating the current CA certificate as the target CA certificate for issuing new entity certificates throughout the execution environment. In one example, the orchestration service may initiate activation of the current CA certificate by designating the current CA certificate as the target CA certificate for issuing new entity certificates throughout the execution environment. The orchestration service may initiate activation of the current CA certificate in response to determining that the set of one or more testing operations are successful at block **750** and/or at block **756**. Additionally, or alternatively, in response to determining that the set of one or more testing operations are unsuccessful at block **750** and/or at block **756**, the orchestration service may refrain from initiating activation of the new CA certificate. Additionally, or alternatively, in response to determining that the set of one or more testing operations are unsuccessful at block **750** and/or at block **756**, the orchestration service may revert back to the current CA certificate, for example, by designating the current CA certificate as the target CA certificate for issuing new entity certificates associated with the target network entity for use in the execution environment.

[0228] The certificate lifecycle module may update the data structure to indicate that the new CA certificate is designated as the target CA certificate for issuing new entity certificates throughout the execution environment. The update to the data structure at block **752** may reverse an update to the data structure at block **752**. Additionally, or alternatively, the update to the data structure at block **752** may designate additional network entities (e.g., network entities that were not included in a testing process at block **748**) for receiving new entity certificates issued from the new CA

certificate. By designating the new CA certificate as the target CA certificate for issuing new entity certificates throughout the execution environment, the PKI service may generate new entity certificates from the new CA certificate in response to requests from PKI agents throughout the execution environment. A new entity certificate generated based on the new CA certificate may be distributed to one or more network entities that do not already have a new entity certificate. In one example, a new entity certificate generated based on the new CA certificate may be distributed to one or more network entities that were not included in a testing process at block **748**. Additionally, or alternatively, a new entity certificate generated based on the new CA certificate may be distributed to one or more network entities that received an entity certificate issued based on the current CA certificate subsequent to a testing process at block **752**.

6. Example Testing Processes

[0229] Referring to FIGS. **8A-8C**, example operations **800** pertaining to testing processes that may be executed in connection with a certificate distribution process are further described. One or more operations **800** described with reference to FIGS. **8A-8C** may be modified, combined, rearranged, or omitted. Accordingly, the particular sequence of operations **800** described with reference to FIGS. **8A-8C** should not be construed as limiting the scope of one or more embodiments. In one example, the operations described with reference to FIGS. **8A-8C** may include one or more operations **700** described with reference to FIGS. **7A-7C**. In one example, the operations **800** may be performed by the one or more components of the system described with reference to FIGS. **6A-6C**.

[0230] Referring to FIG. **8A**, the operations **800** include, at block **802**, generating a new certificate bundle in an execution environment of a virtual cloud network. The new certificate bundle may include a set of one or more CA certificates. The set of one or more CA certificates may include a new CA certificate and a current CA certificate. Generating the new certificate bundle may be initiated by an orchestration service. The new certificate bundle may be generated by a PKI service in response to a command from the orchestration service. Generating the new certificate bundle may include transmitting a command from the orchestration service to the PKI service to cause the PKI service to generate the new certificate bundle.

[0231] At block **804**, the operations **800** include executing a testing process for utilizing a sandbox sub-environment of the execution environment to perform a set of one or more testing operations pertaining to the new certificate bundle. The testing process may include one or more of the testing operations described with reference to FIG. **9A**. In one example, the testing process at block **804** includes one or more sandbox service validations and/or one or more event service validations. Additionally, or alternatively, the testing process at block **804** may include one or more sandbox service authentications. The testing process may be initiated by the orchestration service. A sandbox instance executing in the sandbox sub-environment may execute at least a portion of the testing process. The testing process may include transmitting a command from the orchestration service to the sandbox instance to cause the sandbox instance to execute the testing process. Additionally, or alternatively, the testing process may include the orchestration service receiving test results from the sandbox instance and/or from the event monitoring service. Additionally, or alternatively, the orchestration service may detect events in an event log generated by the event monitoring service, and the events may be indicative of the test results.

[0232] At block **806**, the operations **800** include determining whether the testing process executed in the sandbox sub-environment at block **804** is successful. When the orchestration service determines that the testing process executed in the sandbox sub-environment is successful, the operations **800** may proceed to block **808**. When the orchestration service determines that the sandbox sub-environment testing process is unsuccessful, the system may abort the operations **800**, or the system may suspend the operations **800**, for example, until the system determines that the sandbox sub-environment testing process is successful. In one example, one or more alerts may be generated in response to determining that the sandbox sub-environment testing process is

unsuccessful. One or more troubleshooting operations may be initiated in response to the one or more alerts.

[0233] At block **808**, the operations **800** include determining whether the testing process is to be performed in an additional sandbox sub-environment. When the orchestration service determines that the testing process is to be performed in an additional sandbox sub-environment, the operations **800** may return to block **804**, where the testing process may be executed in the additional sandbox sub-environment. When the orchestration service determines that the testing process is not to be performed in an additional sandbox sub-environment, the operations **800** may proceed to block **814** of FIG. **8B**. In one example, the operations **800** may proceed to block **814** of FIG. **8B** upon having executed the testing process with respect to a set of one or more sandbox sub-environments. Additionally, or alternatively, the operations **800** may proceed to block **814** of FIG. **8B** concurrently with executing the testing process in the additional sandbox sub-environment.

[0234] In one example, the operations **800** include, at block **810**, maintaining, in the execution environment, a current certificate bundle that includes the current CA certificate. The current certificate bundle including the current CA certificate may be maintained in the execution environment concurrently with execution of the testing process in the sandbox sub-environment. In one example, the operations **800** include, at block **812**, authenticating, based at least in part on the current CA certificate of the current certificate bundle, an entity certificate of a network entity executing in the execution environment. The entity certificate may be authenticated against the current CA certificate in connection with one or more production operations executed by a production service in the execution environment. The entity certificate may be authenticated at block **812** concurrently with execution of the testing process in the sandbox sub-environment. In one example, the operations **800** may proceed from block **812** to block **836** of FIG. **8C**.

[0235] Referring to FIG. **8B**, the operations **800** include, at block **814**, selecting a network entity executing in the execution environment for installing the new certificate bundle. The new certificate bundle may be installed for purposes of performing a testing process that utilizes a testing service executing on the network entity. In one example, the network entity is a host network entity. The orchestration service may select the network entity for installing the new certificate bundle based on one or more policies maintained by a policy module.

[0236] At block **816**, the operations **800** include initiating installation of the new certificate bundle on the network entity. The installation of the new certificate bundle on the network entity may be initiated in response to determining that the one or more testing operations are successful at block **806**. Additionally, or alternatively, when the orchestration service determines that the one or more testing operations are unsuccessful, the orchestration service may refrain from initiating installation of the new certificate bundle on the network entity. The orchestration service may initiate installation of the new certificate bundle on the network entity by transmitting a command to a PKI service to distribute the new certificate bundle to the network entity. In response to the command from the orchestration service, the PKI service causes a certificate distribution service to distribute the new certificate bundle to the network entity. The network entity receives the certificate bundle and installs the certificate bundle in a storage medium associated with the network entity.

[0237] At block **818**, the operations **800** include executing a testing process for utilizing a testing service executing on the network entity to perform a set of one or more testing operations pertaining to the new certificate bundle. The testing process may include one or more of the testing operations described with reference to FIG. **9B**. In one example, the testing process at block **818** includes one or more testing service validations and/or one or more event service validations. Additionally, or alternatively, the testing process at block **818** may include one or more testing service authentications. The testing process may be initiated by the orchestration service. A testing service executing on the network entity may execute at least a portion of the testing process. The testing process may include transmitting a command from the orchestration service to the testing service to cause the testing service to execute the testing process. Additionally, or alternatively, the

testing process may include the orchestration service receiving test results from the testing service and/or from the event monitoring service. Additionally, or alternatively, the orchestration service may detect events in an event log generated by the event monitoring service, and the events may be indicative of the test results.

[0238] At block **820**, the operations **800** include determining whether the testing process executed utilizing the testing service is successful. When the orchestration service determines that the testing process executed utilizing the testing service is successful, the operations **800** may proceed to block **822**. When the orchestration service determines that the testing process executed utilizing the testing service is unsuccessful, the system may abort the operations **800**, or the system may suspend the operations **800**, for example, until the system determines that the testing process is successful. In one example, one or more alerts may be generated in response to determining that the testing process is unsuccessful. One or more troubleshooting operations may be initiated in response to the one or more alerts.

[0239] At block **822**, the operations **800** include determining whether the testing process is to be performed for an additional network entity that is executing a testing service in the execution environment. When the orchestration service determines that the testing process is to be performed for an additional network entity executing a testing service in the environment, the operations **800** may return to block **814**, where an additional a network entity may be selected. When the orchestration service determines that the testing process is not to be performed for an additional network entity, the operations **800** may proceed to block **824**. In one example, the operations **800** may proceed to block **824** upon having executed the testing process with respect to a set of one or more network entities that are executing a testing service in the execution environment.

Additionally, or alternatively, the operations **800** may proceed to block **824** concurrently with executing the testing process for the additional network entities.

[0240] At block **824**, the operations **800** include initiating activation of the new CA certificate in the execution environment. The new CA certificate may be activated in a portion of the execution environment associated with the network entity utilized to perform the testing process at block **818**. The orchestration service initiates activation of the new CA certificate by causing transmission of entity certificates to network entities located in the portion of the execution environment corresponding to the testing process. The network entities may utilize the new entity certificates for authentication against the new CA certificate. In one example, the orchestration service transmits a command to a PKI service to issue new entity certificates to the network entities based on the new CA certificate. In response to the command from the orchestration service, the PKI service issues the new entity certificates and causes a certificate distribution service to distribute the new entity certificate to the network entities. In one example, the network entity utilized to perform the testing process is a host network entity, and the new CA certificate is activated with respect to the host network entity and a set of node network entities serviced by the host network entity. From block **824**, the operations **800** may proceed to block **826** of FIG. 8C.

[0241] In one example, the orchestration service may determine, at block **820**, that the testing process at block **818** is successful with respect to a first portion of the execution environment, and that the testing process is to be performed for another portion of the execution environment at block **822**. Additionally, the operations **800** may include initiating activation of the new CA certificate with respect to the first portion of the execution environment at block **824** and executing the testing process at block **818** with respect to the second portion of the execution environment. The orchestration service may initiate activation of the new CA certificate with respect to the first portion of the execution environment. Additionally, the orchestration service may execute the testing process with respect to the second portion of the execution environment responsive to determining the testing process is successful with respect to the first portion of the execution environment and/or that the testing process is to be performed for the second portion of the execution environment.

[0242] The network entities in the first portion of the execution environment may utilize new entity certificates issued from the new CA to authenticate against the new CA certificate, while the testing process at block **818** is being performed with respect to the second portion of the execution environment. Additionally, or alternatively, when the orchestration service determines that the testing process at block **818** is not to be performed for an additional portion of the execution environment, the operations **800** may include initiating activation of the new CA certificate at block **824** with respect to the remainder of the execution environment.

[0243] In one example, the operations **800** include, at block **810** (FIG. **8A**), maintaining the current certificate bundle that includes the current CA certificate in the execution environment concurrently with the testing process performed utilizing the network entity executing the testing service. In one example, the operations **800** include, at block **812** (FIG. **8A**), authenticating, based at least in part on the current CA certificate of the current certificate bundle, an entity certificate of a network entity executing in the execution environment concurrently with the testing process performed utilizing the network entity executing the testing service.

[0244] Referring to FIG. **8C**, the operations **800** include, at block **826**, initiating installation of the new certificate bundle throughout the execution environment. The orchestration service may initiate installation of the new certificate bundle by transmitting a command to the PKI service to distribute the first certificate bundle to network entities throughout the execution environment. In response to the command from the orchestration service, the PKI service causes the certificate distribution service to distribute the new certificate bundle throughout the execution environment.

[0245] At block **828**, the operations **800** include executing a testing process for utilizing a production service executing on a network entity in the execution environment to perform a set of one or more testing operations pertaining to the new certificate bundle. The testing process may include one or more of the testing operations described with reference to FIG. **9C**. In one example, the testing process at block **828** includes one or more production service validations and/or one or more event service validations. Additionally, or alternatively, the testing process at block **828** may include one or more production service authentications. The testing process may be initiated by the orchestration service. A production service executing on the network entity may execute at least a portion of the testing process. The testing process may include transmitting a command from the orchestration service to the testing service to cause the testing service to execute the testing process. Additionally, or alternatively, the testing process may include the orchestration service receiving test results from the testing service and/or from the event monitoring service.

Additionally, or alternatively, the orchestration service may detect events in an event log generated by the event monitoring service, and the events may be indicative of the test results.

[0246] At block **830**, the operations **800** include determining whether the testing process executed utilizing the production service is successful. When the orchestration service determines that the testing process executed utilizing the production service is successful, the operations **800** may proceed to block **832**. When the orchestration service determines that the first testing process executed utilizing the production service is unsuccessful, the system may abort the operations **800**, or the system may suspend the operations **800**, for example, until the system determines that the testing process is successful. In one example, one or more alerts may be generated in response to determining that the testing process is unsuccessful. One or more troubleshooting operations may be initiated in response to the one or more alerts.

[0247] At block **832**, the operations **800** include determining whether the testing process is to be performed for an additional network entity utilizing a production service executing on the network entity. When the orchestration service determines that the testing process is to be performed for an additional network, the operations **800** may return to block **832**, where an additional a network entity may be selected. When the orchestration service determines that the testing process is not to be performed for an additional network entity, the operations **800** may proceed to block **836**. In one example, the operations **800** may proceed to block **836** upon having executed the testing process

with respect to a set of one or more network entities that are executing a production service in the execution environment. Additionally, or alternatively, the operations **800** may proceed to block **824** concurrently with executing the testing process for the additional network entities.

[0248] At block **834**, the operations **800** include initiating removal of the current CA certificate from the execution environment. As mentioned above, the current CA certificate is included in the new certificate bundle generated at block **802** (FIG. **8A**) and installed in the execution environment at block **826**. The orchestration service may initiate removal of the current CA certificate from the execution environment. The current CA certificate may be removed from a portion of the execution environment associated with the network entity utilized to perform the testing process at block **828**. The current CA certificate may be removed from the execution environment by distributing an additional new certificate bundle that supersedes the new certificate bundle installed in the execution environment at block **826**. The additional new certificate bundle includes the new CA certificate and is exclusive of (does not include) the current CA certificate. The orchestration service may cause the additional new certificate bundle to be distributed to the execution environment by transmitting a command to the PKI service to distribute the additional new certificate bundle to the execution environment. In response to the command from the orchestration service, the PKI service causes the certificate distribution service to distribute the additional new certificate bundle to the execution environment. At block **836**, the operations **800** include authenticating entity certificates of network entities executing in the execution environment based at least in part on the new CA certificate.

[0249] In one example, the orchestration service may determine at block **830** that the testing process at block **828** is successful with respect to a first portion of the execution environment, and that the testing process is to be performed for another portion of the execution environment at block **822**. Additionally, the operations **800** may include initiating removal of the current CA certificate with respect to the first portion of the execution environment at block **834** and executing the testing process at block **828** with respect to the second portion of the execution environment. The orchestration service may initiate removal of the current CA certificate with respect to the first portion of the execution environment. Additionally, the orchestration service may execute the testing process with respect to the second portion of the execution environment responsive to determining that the testing process is successful with respect to the first portion of the execution environment and/or that the testing process is to be performed for the second portion of the execution environment.

[0250] The network entities in the first portion of the execution environment may utilize new entity certificates issued from the new CA to authenticate against the new CA certificate, while the testing process at block **828** is being performed with respect to the second portion of the execution environment. Additionally, or alternatively, when the orchestration service determines that the testing process at block **828** is not to be performed for an additional portion of the execution environment, the operations **800** may include initiating removal of the current CA certificate at block **834** with respect to the remainder of the execution environment.

[0251] In one example, the operations **800** include, at block **810** (FIG. **8A**), maintaining the current certificate bundle that includes the current CA certificate in the execution environment concurrently with the testing process performed utilizing the network entity executing the production service. In one example, the operations **800** include, at block **812** (FIG. **8A**), authenticating, based at least in part on the current CA certificate of the current certificate bundle, an entity certificate of a network entity executing in the execution environment concurrently with the testing process performed utilizing the network entity executing the production service.

A. Example Testing Utilizing a Sandbox Sub-Environment

[0252] Referring to FIG. **9A**, example operations **900** associated with performing a testing process for testing a new certificate bundle in a sandbox sub-environment are further described.

[0253] One or more operations **900** described with reference to FIG. **9A** may be modified,

combined, rearranged, or omitted. Accordingly, the particular sequence of operations **900** described with reference to FIG. **9A** should not be construed as limiting the scope of one or more embodiments. In one example, the operations **900** described with reference to FIG. **9A** may include one or more operations **800** described with reference to FIGS. **8A-8C**. Additionally, or alternatively, the operations **900** described with reference to FIG. **9A** may include one or more operations **700** described with reference to FIGS. **7A-7C**. In one example, the operations **900** may be performed by the one or more components of the system described with reference to FIGS. **6A-6C**.

[0254] As shown in FIG. **9A**, the operations **900** include, at block **902**, downloading the new certificate bundle to the sandbox sub-environment of the execution environment. A sandbox instance executing in the sandbox sub-environment may download the new certificate bundle. At block **904**, the operations **900** include installing the new certificate bundle in the sandbox sub-environment. The sandbox instance may install the new certificate bundle in a storage medium associated with the sandbox instance.

[0255] At block **906**, the operations **900** include utilizing the sandbox sub-environment to perform the one or more testing operations associated with the new certificate bundle. The sandbox instance may execute at least a portion of the one or more testing operations. At block **908**, the operations **900** include providing one or more test results indicating that the one or more testing operations are successful. The sandbox instance may provide the one or more test results to the orchestration service. Additionally, or alternatively, the event monitoring service may provide the one or more test results to the orchestration service.

[0256] The one or more testing operations at block **906** may include one or more sandbox service authentications. A sandbox service authentication may include one or more of the operations described with reference to block **910**, block **912**, and/or block **914**. Additionally, or alternatively, the one or more testing operations at block **906** may include one or more sandbox service validations. A sandbox service validation may include one or more of the operations described with reference to block **916** and/or block **918**. Additionally, or alternatively, the one or more testing operations at block **906** may include one or more event service validations associated with the one or more testing operations. An event service validation may include one or more of the operations described with reference to block **920** and/or block **922**.

[0257] At block **910**, the operations **900** include downloading, to the sandbox sub-environment, an entity certificate corresponding to a network entity executing in the execution environment. A certificate downloader executing on a sandbox instance in the sandbox sub-environment may download the new certificate bundle to a storage medium associated with the first network entity.

[0258] At block **912**, the operations **900** include authenticating the entity certificate against the new CA certificate of the new certificate bundle. The sandbox instance may authenticate the entity certificate by validating a certificate chain that includes the entity certificate and the new CA certificate. At block **914**, the operations **900** include determining whether the entity certificate successfully authenticates to the new CA certificate. When the system determines that the entity certificate successfully authenticates to the new CA certificate, the operations may proceed to block **908**, where the sandbox instance provides a test result to the orchestration service, indicating a successful testing operation.

[0259] At block **916**, the operations **900** include performing a set of one or more sandbox service validations. The one or more sandbox service validations may include validating that the sandbox instance has downloaded and installed the correct certificate bundle for testing. Additionally, or alternatively, the one or more sandbox service validations may include validating that the certificate bundle includes the correct set of CA certificates. The sandbox instance may perform the sandbox service validations by examining one or more file attributes of the certificate bundle and/or the CA certificates. Additionally, or alternatively, the sandbox instance may perform the sandbox service validations by comparing a first hash value corresponding to the certificate bundle and/or the CA

certificates downloaded by the sandbox instance against a second hash value corresponding to the certificate bundle and/or the CA certificates in the certificate repository of the PKI service. Additionally, or alternatively, the sandbox instance may perform the sandbox service validations by comparing a first timestamp corresponding to the certificate bundle and/or the CA certificates downloaded by the sandbox instance against a second timestamp corresponding to the certificate bundle and/or the CA certificates in the certificate repository.

[0260] At block **918**, the operations **900** include determining whether the set of one or more sandbox service validations are successful. When the system determines that the set of one or more sandbox service validations are successful, the operations may proceed to block **908**, where the sandbox instance provides a test result to the orchestration service, indicating a successful testing operation.

[0261] At block **920**, the operations **900** include performing a set of one or more event service validations. The one or more event service validations may include transmitting information from the event monitoring service to the orchestration service associated with operations performed by the sandbox service. The information from the event monitoring service may include file attributes, hash values, and/or timestamps associated with certificate bundles and/or entity certificates.

[0262] At block **922**, the operations **900** include determining whether the set of one or more event service validations are successful. When the system determines that the set of one or more event service validations are successful, the operations may proceed to block **908**, where the event monitoring service provides a test result to the orchestration service, indicating a successful testing operation.

B. Example Testing Utilizing a Testing Service in an Execution Environment

[0263] Referring to FIG. **9B**, example operations **900** associated with performing a testing process for testing a certificate bundle utilizing a testing service installed on a network entity execution in an execution environment are further described. One or more operations **900** described with reference to FIG. **9B** may be modified, combined, rearranged, or omitted. Accordingly, the particular sequence of operations **900** described with reference to FIG. **9B** should not be construed as limiting the scope of one or more embodiments. In one example, the operations **900** described with reference to FIG. **9B** may include one or more operations **800** described with reference to FIGS. **8A-8C**. Additionally, or alternatively, the operations **900** described with reference to FIG. **9B** may include one or more operations **700** described with reference to FIGS. **7A-7C**. In one example, the operations **900** may be performed by the one or more components of the system described with reference to FIGS. **6A-6C**.

[0264] As shown in FIG. **9B**, the operations **900** include, at block **930**, downloading the new certificate bundle to a first network entity executing in the execution environment. The first network entity may be a host network entity. A certificate downloader executing on the first network entity may download the new certificate bundle to a storage medium associated with the first network entity. At block **932**, the operations **900** include installing the new certificate bundle on the first network entity. The certificate downloader may install the new certificate bundle in the storage medium associated with the first network entity.

[0265] At block **934**, the operations **900** include utilizing a testing service executing on the first network entity to perform the one or more testing operations associated with the new certificate bundle. The testing service executing on the first network entity may execute at least a portion of the one or more testing operations. At block **936**, the operations **900** include providing one or more test results indicating that the one or more testing operations are successful. The testing service executing on the first network entity may provide the one or more test results to the orchestration service. Additionally, or alternatively, the event monitoring service may provide the one or more test results to the orchestration service.

[0266] The one or more testing operations at block **934** may include one or more testing service authentications. A testing service authentication may include one or more of the operations

described with reference to block **938**, block **940**, and/or block **942**. Additionally, or alternatively, the one or more testing operations at block **934** may include one or more testing service validations. A testing service validation may include one or more of the operations described with reference to block **944** and/or block **946**. Additionally, or alternatively, the one or more testing operations at block **934** may include one or more event service validations associated with the one or more testing operations at block **934**. An event service validation may include one or more of the operations described with reference to block **948** and/or block **950**.

[0267] At block **938**, the operations **900** include downloading, to the testing service executing on the first network entity, an entity certificate corresponding to a second network entity executing in the execution environment. The second network entity may be a node network entity serviced by the first network entity. A certificate downloader executing on the first network entity may download the new certificate bundle to a storage medium associated with the first network entity.

[0268] At block **940**, the operations **900** include authenticating the entity certificate against the new CA certificate of the new certificate bundle. The testing service may authenticate the entity certificate by validating a certificate chain that includes the entity certificate and the new CA certificate. In one example, the entity certificate downloaded at block **938** and authenticated at block **940** may be a sample entity certificate received from a certificate distribution service.

Additionally, or alternatively, the entity certificate downloaded at block **938** and authenticated at block **940** may be a received from another network entity executing in the execution environment. In one example, a new entity certificate generated by the PKI service may be transmitted to a first network entity, such as a host network entity, and the host network entity may transmit the new entity certificate to a second network entity such as a node network entity. The host network entity may receive and/or download the entity certificate from the node network entity at block **938** for authentication at block **940**. Additionally, or alternatively, the new entity certificate downloaded at block **938** and authenticated at block **840** may be utilized in for authentication in accordance with a security protocol in the execution environment. In one example, the new entity certificate generated by the PKI service may be transmitted to a first network entity, such as a host network entity, and the host network entity may utilize the new entity certificate for authentication in accordance with a security protocol in the execution environment. In one example, the first network entity that downloads the new entity certificate at block **938** may transmit the new entity certificate to a third network entity executing in the execution, and the third network entity may authenticate the new entity certificate against the new CA certificate.

[0269] At block **942**, the operations **900** include determining whether the entity certificate successfully authenticates to the new CA certificate. When the testing service determines that the entity certificate successfully authenticates to the new CA certificate, the operations may proceed to block **936**, where the testing service executing on the first network entity provides a test result to the orchestration service indicating a successful testing operation.

[0270] At block **944**, the operations **900** include performing a set of one or more testing service validations. The one or more testing service validations may include validating that the network entity that is executing the testing service has downloaded and installed the correct certificate bundle for testing. Additionally, or alternatively, the one or more testing service validations may include validating that the certificate bundle includes the correct set of CA certificates. The testing service may perform the testing service validations by examining one or more file attributes of the certificate bundle and/or the CA certificates. Additionally, or alternatively, the testing service may perform the testing service validations by comparing a first hash value corresponding to the certificate bundle and/or the CA certificates downloaded by the network entity that is executing the testing service against a second hash value corresponding to the certificate bundle and/or the CA certificates in the certificate repository of the PKI service. Additionally, or alternatively, the testing service may perform the testing service validations by comparing a first timestamp corresponding to the certificate bundle and/or the CA certificates downloaded by the network entity that is

executing the testing service against a second timestamp corresponding to the certificate bundle and/or the CA certificates in the certificate repository.

[0271] At block **946**, the operations **900** include determining whether the set of one or more testing service validations are successful. When the testing service determines that the set of one or more testing service validations are successful, the operations may proceed to block **936**, where the testing service provides a test result to the orchestration service indicating a successful testing operation.

[0272] At block **948**, the operations **900** include performing a set of one or more event service validations. The one or more event service validations may include transmitting information from the event monitoring service to the orchestration service associated with operations performed by the testing service. The information from the event monitoring service may include file attributes, hash values, and/or timestamps associated with certificate bundles and/or entity certificates.

[0273] At block **950**, the operations **900** include determining whether the set of one or more event service validations are successful. When the event monitoring service determines that the set of one or more event service validations are successful, the operations may proceed to block **936**, where the event monitoring service provides a test result to the orchestration service indicating a successful testing operation.

C. Example Testing Utilizing a Production Service in the Execution Environment

[0274] Referring to FIG. **9C**, example operations **900** associated with performing a testing process for testing a certificate bundle utilizing a production service installed on a network entity executing in an execution environment are further described. One or more operations **900** described with reference FIG. **9C** may be modified, combined, rearranged, or omitted. Accordingly, the particular sequence of operations **900** described with reference to FIG. **9C** should not be construed as limiting the scope of one or more embodiments. In one example, the operations **900** described with reference to FIG. **9C** may include one or more operations **800** described with reference to FIGS. **8A-8C**. Additionally, or alternatively, the operations **900** described with reference to FIG. **9C** may include one or more operations **700** described with reference to FIGS. **7A-7C**. In one example, the operations **900** may be performed by the one or more components of the system described with reference to FIGS. **6A-6C**.

[0275] As shown in FIG. **9C**, the operations **900** include, at block **960**, downloading the new certificate bundle to the first network entity executing in the execution environment. The first network entity may be a host network entity. The first network entity described with reference to FIG. **9C** may be the first network entity described with reference to FIG. **9B**, or the first network entity described with reference to FIG. **9C** may be a different network entity from the first network entity described with reference to FIG. **9B**.

[0276] A certificate downloader executing on the first network entity may download the new certificate bundle to a storage medium associated with the first network entity. At block **962**, the operations **900** include installing the new certificate bundle on the first network entity. The certificate downloader may install the new certificate bundle in the storage medium associated with the first network entity.

[0277] At block **964**, the operations **900** include utilizing a production service executing on the first network entity to perform the one or more testing operations associated with the new certificate bundle. The production service executing on the first network entity may execute at least a portion of the one or more testing operations. At block **966**, the operations **900** include providing one or more test results indicating that the one or more testing operations are successful. The production service executing on the first network entity may provide the one or more test results to the orchestration service. Additionally, or alternatively, the event monitoring service may provide the one or more test results to the orchestration service.

[0278] The one or more testing operations at block **964** may include one or more production service authentications. A production service authentication may include one or more of the

operations described with reference to block **968**, block **970**, and/or block **972**. Additionally, or alternatively, the one or more testing operations at block **964** may include one or more production service validations. A production service validation may include one or more of the operations described with reference to block **974** and/or block **976**. Additionally, or alternatively, the one or more testing operations at block **964** may include one or more event service validations associated with the one or more testing operations at block **964**. An event service validation may include one or more of the operations described with reference to block **978** and/or block **980**.

[0279] At block **968**, the operations **900** include receiving, at the production service executing on the first network entity, an entity certificate corresponding to a second network entity executing in the execution environment. The second network entity may be a node network entity serviced by the first network entity. The second network entity described with reference to FIG. **9C** may be the second network entity described with reference to FIG. **9B**, or the second network entity described with reference to FIG. **9C** may be a different network entity from the second network entity described with reference to FIG. **9B**. The production service may receive the entity certificate from the second network entity for authentication in accordance with a security protocol associated with executing a production operation. The production operation may include a communication exchange between the first network entity and the second network entity that occurs after having authenticated in accordance with the security protocol.

[0280] At block **970**, the operations **900** include authenticating the entity certificate received from the second network entity against the new CA certificate of the new certificate bundle. The production service may authenticate the entity certificate by validating a certificate chain that includes the entity certificate and the new CA certificate. At block **972**, the operations **900** include determining whether the entity certificate successfully authenticates to the new CA certificate. When the production service determines that the entity certificate successfully authenticates to the new CA certificate, the operations may proceed to block **966**, where the production service executing on the first network entity provides a test result to the orchestration service indicating a successful testing operation.

[0281] At block **974**, the operations **900** include performing a set of one or more production service validations. The one or more production service validations may include validating the network entity that is executing the production service has downloaded and installed the correct certificate bundle for testing. Additionally, or alternatively, the one or more production service validations may include validating the certificate bundle includes the correct set of CA certificates. The production service may perform the production service validations by examining one or more file attributes of the certificate bundle and/or the CA certificates. Additionally, or alternatively, the production service may perform the production service validations by comparing a first hash value corresponding to the certificate bundle and/or the CA certificates downloaded by the network entity that is executing the production service against a second hash value corresponding to the certificate bundle and/or the CA certificates in the certificate repository of the PKI service. Additionally, or alternatively, the production service may perform the production service validations by comparing a first timestamp corresponding to the certificate bundle and/or the CA certificates downloaded by the network entity that is executing the production service against a second timestamp corresponding to the certificate bundle and/or the CA certificates in the certificate repository.

[0282] At block **976**, the operations **900** include determining whether the set of one or more production service validations are successful. When the production service determines that the set of one or more production service validations are successful, the operations may proceed to block **966**, where the production service provides a test result to the orchestration service, indicating a successful testing operation.

[0283] At block **978**, the operations **900** include performing a set of one or more event service validations. The one or more event service validations may include transmitting information from the event monitoring service to the orchestration service associated with operations performed by

the production service. The information from the event monitoring service may include file attributes, hash values, and/or timestamps associated with certificate bundles and/or entity certificates.

[0284] At block **980**, the operations **900** include determining whether the set of one or more event service validations are successful. When the event monitoring service determines that the set of one or more event service validations are successful, the operations may proceed to block **936**, where the event monitoring service provides a test result to the orchestration service, indicating a successful testing operation.

8. Miscellaneous; Extensions

[0285] Embodiments are directed to a system with one or more devices that include a hardware processor and that are configured to perform any of the operations described herein and/or recited in any of the claims below. Embodiments are directed to a system that includes means to perform any of the operations described herein and/or recited in any of the claims below. In an embodiment, a non-transitory, computer-readable storage medium comprises instructions that, when executed by one or more hardware processors, causes performance of any of the operations described herein and/or recited in any of the claims.

[0286] Any combination of the features and functionalities described herein may be used in accordance with one or more embodiments. In the foregoing specification, embodiments have been described with reference to numerous specific details that may vary from implementation to implementation. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense. The sole and exclusive indicator of the scope of patent protection, and what is intended by the applicants to be the scope of patent protection, is the literal and equivalent scope of the set of claims that issue from this application in the specific form that such claims issue, including any subsequent correction.

[0287] References, including publications, patent applications, and patents, cited herein are hereby incorporated by reference to the same extent as if the references were individually and specifically indicated to be incorporated by reference and were set forth in entirety herein.

Claims

1. One or more non-transitory computer-readable media storing instructions that, when executed by one or more hardware processors, cause performance of operations comprising: generating, in an execution environment of a virtual cloud network, a first certificate bundle comprising a first certificate authority (CA) certificate and a second CA certificate; executing a first testing process for utilizing a first sandbox sub-environment executing in a first portion of the execution environment to perform a first set of one or more testing operations associated with the first certificate bundle, wherein while executing the first testing process, the first certificate bundle is yet to be installed in the first portion of the execution environment and a second certificate bundle comprising the second CA certificate is installed in the first portion of the execution environment; responsive to determining that the first set of one or more testing operations is successful: initiating installation of the first certificate bundle, including the first CA certificate and the second CA certificate, on a first network entity executing in the first portion of the execution environment, wherein the first certificate bundle supersedes the second certificate bundle; executing a second testing process for utilizing a first testing service executing on the first network entity to perform a second set of one or more testing operations associated with the first certificate bundle, wherein while executing the second testing process, the first CA certificate is yet to be activated in the first portion of the execution environment and the second CA certificate is active in the first portion of the execution environment; responsive to determining that the second set of one or more testing operations is successful: initiating activation of the first CA certificate in the first portion of the execution environment at least by causing transmission of a first entity certificate to a second

network entity executing in the first portion of the execution environment for authentication against the first CA certificate, wherein the first entity certificate supersedes a second entity certificate previously utilized by the second network entity for authentication against the second CA certificate.

2. The one or more non-transitory computer-readable media of claim 1, wherein the operations further comprise: determining a set of one or more test results corresponding to the first set of one or more testing operations, wherein the set of one or more test results comprises at least one of: a first test result comprising a first indication that the first certificate bundle stored in a certificate repository matches the first certificate bundle installed in the first sandbox sub-environment, a second test result comprising a second indication that a third entity certificate issued based at least in part on the first CA certificate is successfully downloaded to the first sandbox sub-environment, or a third test result comprising a third indication that a certificate chain comprising the third entity certificate and the first CA certificate is successfully authenticated in the first sandbox sub-environment; and determining, based at least in part on the set of one or more test results, that the first set of one or more testing operations is successful.

3. The one or more non-transitory computer-readable media of claim 2, wherein determining the set of one or more test results corresponding to the first set of one or more testing operations comprises at least one of: receiving the set of one or more test results from a sandbox service executing in the first sandbox sub-environment; or detecting a set of one or more events in an event log generated by an event monitoring service, wherein the set of one or more events is indicative of the set of one or more test results.

4. The one or more non-transitory computer-readable media of claim 1, wherein the operations further comprise: determining a set of one or more test results corresponding to the second set of one or more testing operations, wherein the set of one or more test results comprises at least one of: a first test result comprising a first indication that the first certificate bundle stored in a certificate repository matches the first certificate bundle installed on a storage medium associated with the first testing service executing on the first network entity, a second test result comprising a second indication that a third entity certificate issued based at least in part on the first CA certificate is successfully downloaded to the first network entity, or a third test result comprising a third indication that a certificate chain comprising the third entity certificate and the first CA certificate is successfully authenticated by the first testing service; and determining, based at least in part on the set of one or more test results, that the second set of one or more testing operations is successful.

5. The one or more non-transitory computer-readable media of claim 4, wherein determining the set of one or more test results corresponding to the second set of one or more testing operations comprises: receiving the set of one or more test results from the first testing service; or detecting a set of one or more events in an event log generated by an event monitoring service, wherein the set of one or more events is indicative of the set of one or more test results.

6. The one or more non-transitory computer-readable media of claim 1, wherein the operations further comprise: executing a third testing process for utilizing a production service executing on a third network entity executing in the first portion of the execution environment to perform a third set of one or more testing operations associated with the first certificate bundle; responsive to determining that the third set of one or more testing operations is successful: initiating removal of the second CA certificate from the first portion of the execution environment.

7. The one or more non-transitory computer-readable media of claim 6, wherein the operations further comprise: determining a set of one or more test results corresponding to the second set of one or more testing operations, wherein the set of one or more test results comprises at least one of: a first test result comprising a first indication that the first certificate bundle stored in a certificate repository matches the first certificate bundle installed on a storage medium associated with the production service executing on the third network entity, a second test result comprising a second

indication that a third entity certificate issued based at least in part on the first CA certificate is successfully downloaded to the third network entity, or a third test result comprising a third indication that a certificate chain comprising the third entity certificate and the first CA certificate is successfully authenticated by the production service; and determining, based at least in part on the set of one or more test results, that the third set of one or more testing operations is successful.

8. The one or more non-transitory computer-readable media of claim 7, wherein determining the set of one or more test results corresponding to the third set of one or more testing operations comprises: receiving the set of one or more test results from the first testing service; or detecting a set of one or more events in an event log generated by an event monitoring service, wherein the set of one or more events is indicative of the set of one or more test results.

9. The one or more non-transitory computer-readable media of claim 1, wherein the first CA certificate is a first intermediate CA certificate issued from a first root CA certificate, and wherein the second CA certificate is a second intermediate CA certificate issued from the first root CA certificate, wherein the first intermediate CA certificate supersedes the second intermediate CA certificate.

10. The one or more non-transitory computer-readable media of claim 1, wherein the operations further comprise: determining a trigger condition for executing a certificate distribution process for distributing, to a set of network entities executing in the first portion of the execution environment, a set of new digital certificates issued based at least in part on the first CA certificate for use in an authentication protocol for authenticating the set of network entities, wherein the set of network entities comprises the first network entity and the second network entity; executing the certificate distribution process in response to determining the trigger condition, wherein the certificate distribution process comprises: executing the first testing process for utilizing the first sandbox sub-environment to perform the first set of one or more testing operations; initiating installation of the first certificate bundle throughout the first portion of the execution environment; executing the second testing process for utilizing the first testing service to perform the second set of one or more testing operations; removing the second CA certificate from the first portion of the execution environment.

11. The one or more non-transitory computer-readable media of claim 10, wherein the trigger condition is determined based on at least one of: an expiry date of the first CA certificate, a security alert, or an operator input.

12. The one or more non-transitory computer-readable media of claim 10, wherein the operations further comprise: prior to executing the certificate distribution process: determining that any processes for distributing certificates to a first portion of the virtual cloud network are inactive; and responsive to determining that any processes for distributing certificates to the first portion of the virtual cloud network are inactive: executing the certificate distribution process for a second portion of the virtual cloud network.

13. The one or more non-transitory computer-readable media of claim 1, wherein the operations further comprise: executing a third testing process for utilizing a second sandbox sub-environment executing in a second portion of the execution environment to perform a third set of one or more testing operations associated with the first certificate bundle, responsive to determining that the third set of one or more testing operations is unsuccessful: refraining from initiating installation of the first certificate bundle on a third network entity executing in the second portion of the execution environment.

14. The one or more non-transitory computer-readable media of claim 1, wherein the operations further comprise: initiating installation of the first certificate bundle on a third network entity executing in a second portion of the execution environment; executing a third testing process for utilizing a second testing service executing on the third network entity to perform a third set of one or more testing operations associated with the first certificate bundle, responsive to determining that the third set of one or more testing operations is unsuccessful: refraining from initiating

activation of the first CA certificate in the second portion of the execution environment; and reverting back to the second certificate bundle with respect to the third network entity.

15. The one or more non-transitory computer-readable media of claim 14, wherein the operations further comprise: further responsive to determining that the third set of one or more testing operations is unsuccessful: reverting back to the second CA certificate in the first portion of the execution environment at least by causing transmission of a third entity certificate to the second network entity for authentication against the second CA certificate, wherein the third entity certificate supersedes the first entity certificate previously transmitted to the second network entity in connection with activation of the first CA certificate.

16. The one or more non-transitory computer-readable media of claim 1, wherein the operations further comprise: initiating installation of the first certificate bundle on a third network entity executing in the first portion of the execution environment; executing a third testing process for utilizing a second testing service executing on the third network entity to perform a third set of one or more testing operations associated with the first certificate bundle; determining that the third set of one or more testing operations is successful; wherein initiating activation of the first CA certificate in the first portion of the execution environment is further responsive to determining that the third set of one or more testing operations is successful.

17. The one or more non-transitory computer-readable media of claim 1, wherein initiating installation of the first certificate bundle on the first network entity comprises: transmitting a command to a public key infrastructure service to distribute the first certificate bundle to the first network entity; wherein responsive to the command, the public key infrastructure service causes a certificate distribution service to distribute the first certificate bundle to the first network entity, and wherein the first network entity receives the first certificate bundle and installs the first certificate bundle in a storage medium associated with the first network entity.

18. The one or more non-transitory computer-readable media of claim 1, wherein initiating activation of the first CA certificate in the first portion of the execution environment comprises: transmitting a command to a public key infrastructure service to issue the first entity certificate to the second network entity based at least in part on the first CA certificate and to transmit the first entity certificate to the second network entity; wherein responsive to the command, the public key infrastructure service issues the first entity certificate and causes a certificate distribution service to transmit the first entity certificate to the second network entity, and wherein the second network entity receives the first entity certificate and utilizes the first entity certificate for authentication against the first CA certificate.

19. A method, comprising: generating, in an execution environment of a virtual cloud network, a first certificate bundle comprising a first certificate authority (CA) certificate and a second CA certificate; executing a first testing process for utilizing a first sandbox sub-environment executing in a first portion of the execution environment to perform a first set of one or more testing operations associated with the first certificate bundle, wherein while executing the first testing process, the first certificate bundle is yet to be installed in the first portion of the execution environment and a second certificate bundle comprising the second CA certificate is installed in the first portion of the execution environment; responsive to determining that the first set of one or more testing operations is successful: initiating installation of the first certificate bundle, including the first CA certificate and the second CA certificate, on a first network entity executing in the first portion of the execution environment, wherein the first certificate bundle supersedes the second certificate bundle; executing a second testing process for utilizing a first testing service executing on the first network entity to perform a second set of one or more testing operations associated with the first certificate bundle, wherein while executing the second testing process, the first CA certificate is yet to be activated in the first portion of the execution environment and the second CA certificate is active in the first portion of the execution environment; responsive to determining that the second set of one or more testing operations is successful: initiating activation of the first CA

certificate in the first portion of the execution environment at least by causing transmission of a first entity certificate to a second network entity executing in the first portion of the execution environment for authentication against the first CA certificate, wherein the first entity certificate supersedes a second entity certificate previously utilized by the second network entity for authentication against the second CA certificate; wherein the method is performed by at least one device including a hardware processor.

20. A system, comprising: at least one hardware processor; wherein the system is configured to execute operations, using the at least one hardware processor, the operations comprising: generating, in an execution environment of a virtual cloud network, a first certificate bundle comprising a first certificate authority (CA) certificate and a second CA certificate; executing a first testing process for utilizing a first sandbox sub-environment executing in a first portion of the execution environment to perform a first set of one or more testing operations associated with the first certificate bundle, wherein while executing the first testing process, the first certificate bundle is yet to be installed in the first portion of the execution environment and a second certificate bundle comprising the second CA certificate is installed in the first portion of the execution environment; responsive to determining that the first set of one or more testing operations is successful: initiating installation of the first certificate bundle, including the first CA certificate and the second CA certificate, on a first network entity executing in the first portion of the execution environment, wherein the first certificate bundle supersedes the second certificate bundle; executing a second testing process for utilizing a first testing service executing on the first network entity to perform a second set of one or more testing operations associated with the first certificate bundle, wherein while executing the second testing process, the first CA certificate is yet to be activated in the first portion of the execution environment and the second CA certificate is active in the first portion of the execution environment; responsive to determining that the second set of one or more testing operations is successful: initiating activation of the first CA certificate in the first portion of the execution environment at least by causing transmission of a first entity certificate to a second network entity executing in the first portion of the execution environment for authentication against the first CA certificate, wherein the first entity certificate supersedes a second entity certificate previously utilized by the second network entity for authentication against the second CA certificate.
