

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386355
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Suzuki; Akihiro

Route generation method, device, and program for a work vehicle operating in a narrow area

Abstract

A route generation method executes generating a plurality of work routes where a work vehicle travels straight in a first direction that is a travel direction of the work vehicle, in a work area where a crop is arranged, generating a movement route that is a route continuous with the work route and that includes a straight route where the work vehicle travels straight, in a headland area adjacent to the work area in the first direction, in non-work areas surrounding the work area, where the crop is not arranged, and generating a movement route that is a single route continuous with the movement route and that guides the work vehicle to each of the plurality of work routes.

Inventors:	Suzuki; Akihiro (Osaka, JP)
Applicant:	Yanmar Holdings Co., Ltd. (Osaka, JP)
Family ID:	81749162
Assignee:	Yanmar Holdings Co., Ltd. (Osaka, JP)
Appl. No.:	17/824950
Filed:	May 26, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220382291 A1	Dec. 01, 2022

Foreign Application Priority Data

JP	2021-091521	May. 31, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: G05D1/00 (20240101); A01M7/00 (20060101)

U.S. Cl.:

CPC G05D1/0219 (20130101); A01M7/0089 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2017/0227969	12/2016	Murray	N/A	A01D 42/00
2018/0321683	12/2017	Foster	N/A	G05D 1/0221
2022/0167543	12/2021	Bast	N/A	G05D 1/0223

Primary Examiner: Lee; James J

Assistant Examiner: Reinert; Jonathan E

Background/Summary

CROSS-REFERENCE

(1) This application claims foreign priority of JP2021-091521 filed May 31, 2021, the disclosure of which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(2) This invention relates to a route generation method, a route generation device, and a route generation program for generating a target route for a traveling vehicle that autonomously travels in a travel area.

BACKGROUND ART

(3) Work vehicles that travel autonomously while spraying a chemical solution on crops planted in fields, farms, and other work areas are known (see, for example, Patent Document 1). For example, the aforementioned work vehicle travels autonomously along a target route that is pre-generated on the basis of information such as the shape of the field, the position of the crop, and the content of the work.

PRIOR ART DOCUMENT

Patent Document

(4) Patent Document 1: Japanese Patent Application Publication No. 2021-000021

SUMMARY OF INVENTION

Technical Problem

(5) Here, in a case of a field with a narrow headland area, the aforementioned work vehicle may not be able to turn properly when moving in a crop row. For example, in a field where a headland area is narrow and a sufficient turning area cannot be secured, when the aforementioned work vehicle makes a turn (for example, 180-degree turn) in the headland area to finish the work of the first crop row and enter the next second crop row, the aforementioned work vehicle may deviate out of the field. With a conventional technique, it is difficult to generate an appropriate target route for such a

field.

(6) An object of the present invention relates to a route generation method, a route generation device, and a route generation program capable of appropriately generating a target route in a field where a sufficient turning area cannot be secured.

Solution to Problem

(7) A route generation method according to the present invention is a method that executes generating a plurality of work routes where a work vehicle travels straight in a first direction that is a travel direction of the work vehicle, in a work area where a work object is arranged, generating a first movement route that is a route continuous with the work route and that includes a straight route where the work vehicle travels straight, in a first non-work area adjacent to the work area in the first direction, in non-work areas surrounding the work area, where the work object is not arranged, and generating a second movement route that is a single route continuous with the first movement route and that guides the work vehicle to each of the plurality of work routes.

(8) A route generation device according to the present invention includes a route generation processor. The route generation processor generates a plurality of work routes where the work vehicle travels straight in the first direction that is a travel direction of the work vehicle, in the work area where a work object is arranged. Further, the route generation processor generates a first movement route that is a route continuous with the work route and that includes a straight route where the work vehicle travels straight, in a first non-work area adjacent to the work area in the first direction, in non-work areas surrounding the work area, where the work object is not arranged. Further, the route generation processor generates a second movement route that is a single route continuous with the first movement route and that guides the work vehicle to each of the plurality of work routes.

(9) A route generation program according to the present invention is a program for causing one or more processors to execute generating a plurality of work routes where a work vehicle travels straight in a first direction that is a travel direction of the work vehicle, in a work area where a work object is arranged, generating a first movement route that is a route continuous with the work route and that includes a straight route where the work vehicle travels straight, in a first non-work area adjacent to the work area in the first direction, in non-work areas surrounding the work area, where the work object is not arranged, and generating a second movement route that is a single route continuous with the first movement route and that guides the work vehicle to each of the plurality of work routes.

Advantageous Effects of Invention

(10) According to the present invention, it is possible to provide a route generation method, a route generation device, and a route generation program capable of appropriately generating a target route in a field where a sufficient turning area cannot be secured.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram illustrating an overall configuration of an autonomous travel system according to an embodiment of the present invention.

(2) FIG. 2 is a block diagram illustrating a configuration of the autonomous travel system according to the embodiment of the present invention.

(3) FIG. 3 is an external view of a work vehicle according to the embodiment of the present invention, viewed from the left front side.

(4) FIG. 4A is an external view of the left side of the work vehicle according to the embodiment of the present invention, viewed from the left side.

(5) FIG. 4B is an external view of the right side of the work vehicle according to the embodiment

of the present invention, viewed from the right side.

(6) FIG. 4C is an external view of the back side of the work vehicle according to the embodiment of the present invention, viewed from the back side.

(7) FIG. 5 is a diagram illustrating an example of a crop row according to the embodiment of the present invention.

(8) FIG. 6 is a diagram illustrating an example of a target route in a first route generation mode according to the embodiment of the present invention.

(9) FIG. 7A is a diagram for explaining a method for generating the target route according to the embodiment of the present invention.

(10) FIG. 7B is a diagram for explaining a method for generating the target route according to the embodiment of the present invention.

(11) FIG. 8 is a diagram illustrating an example of a field according to the embodiment of the present invention.

(12) FIG. 9 is a diagram for explaining a condition for switching the route generation mode according to the embodiment of the present invention.

(13) FIG. 10 is a diagram illustrating an example of a target route in a second route generation mode according to the embodiment of the present invention.

(14) FIG. 11 is a flowchart illustrating an example of a procedure of autonomous travel processing executed by the autonomous travel system according to the embodiment of the present invention.

(15) FIG. 12 is a diagram illustrating another example of the target route in the second route generation mode according to the embodiment of the present invention.

(16) FIG. 13 is a diagram illustrating another example of the target route in the second route generation mode according to the embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

(17) The embodiments described below are examples of embodiments of the present invention and do not limit the technical scope of the present invention.

(18) [Autonomous Travel System 1]

(19) As illustrated in FIGS. 1 and 2, an autonomous travel system 1 according to an embodiment of the present invention includes a work vehicle 10, an operation terminal 20, a base station 40, and a satellite 50. The work vehicle 10 and the operation terminal 20 can communicate via a communication network N1. For example, the work vehicle 10 and the operation terminal 20 can communicate via a cellular telephone line network, a packet line network, or a wireless LAN.

(20) In the present embodiment, a case where the work vehicle 10 is a vehicle that performs a spraying work to spray a chemical solution, water, or the like on a crop V (see FIG. 5) planted in a field F is taken as an example. The field F is, for example, an orchard such as a vineyard or an apple orchard. The crop V is, for example, the fruit tree of a grape. The spraying work described above is, for example, the spraying of a chemical solution, water, or the like on the crop V. In other embodiments, the work vehicle 10 may be a vehicle for weeding, leaf cutting, or harvesting.

(21) The crop V is arranged in multiple rows at predetermined intervals in the field F. Specifically, as illustrated in FIG. 5, a plurality of crops V are planted in a straight line in a predetermined direction (direction D1), constituting a crop row Vr that includes a plurality of crops V in a straight line. FIG. 5 illustrates an example of three crop rows Vr. Each crop row Vr is arranged with a predetermined interval W1 in a row direction (direction D2). The area (space) of an interval W2 between adjacent crop rows Vr is the work passage where the work vehicle 10 performs the spraying work on the crop V while traveling in the direction D1.

(22) Further, the work vehicle 10 can also travel automatically (autonomously) along a predetermined target route R. For example, as illustrated in FIG. 6, the work vehicle 10 autonomously travels along the target route R including a work route R1 (work routes R1a to R1f) and a movement route R2, from a work start position S to a work end position G. The work route R1 is a straight line route on which the work vehicle 10 performs a spraying work on the crop V,

and the movement route R2 is a straight line route on which the work vehicle 10 moves between the crop rows Vr without performing the spraying work. The movement route R2 includes, for example, a turning route and a straight route. In the example illustrated in FIG. 6, crops V consisting of crop rows Vr1 to Vr11 are arranged in the field F. In FIG. 6, a position where the crop V is planted (crop position) is represented by “Vp”. Further, the work vehicle 10 traveling in the field F in FIG. 6 has a gantry-shaped vehicle body 100 (see FIG. 4C), and sprays a chemical solution on the crop V of the crop row Vr and a crop row Vr adjacent to the crop row Vr while traveling over one crop row Vr. For example, as illustrated in FIG. 6, when the work vehicle 10 travels over the crop row Vr5, the left side body (left side section 100L) of the work vehicle 10 travels in the work passage between crop rows Vr4 and Vr5, and the right side body (right side section 100R) of the work vehicle 10 travels in the work passage between the crop rows Vr5 and Vr6, and sprays a chemical solution on the crop V in the crop rows Vr4, Vr5, and Vr6.

(23) Further, the work vehicle 10 travels autonomously in a predetermined row order. For example, the work vehicle 10 travels over the crop row Vr1, then over the crop row Vr3, then over the crop row Vr5. In this way, the work vehicle 10 performs autonomous traveling in accordance with a preset crop row Vr order. The work vehicle 10 may travel one row at a time in the order in which the crop rows Vr are arranged, or may travel every other row of a plurality of rows.

(24) The satellite 50 is a positioning satellite that constitutes a satellite positioning system such as GNSS (Global Navigation Satellite System), and transmits a GNSS signal (satellite signal). The base station 40 is a reference point (reference station) that constitutes the satellite positioning system. The base station 40 transmits correction information to the work vehicle 10 to calculate the current position of the work vehicle 10.

(25) The positioning device 16 mounted on the work vehicle 10 executes positioning processing that calculates the current position (latitude, longitude, and altitude) and the current orientation of the work vehicle 10 with the use of the GNSS signal transmitted from the satellite 50. Specifically, the positioning device 16 measures the position of the work vehicle 10 with the use of an RTK (Real Time Kinematic) method or the like for measuring the position of the work vehicle 10 on the basis of the positioning information (GNSS signal, etc.) received by two receivers (antenna 164 and base station 40) and the correction information generated by the base station 40. The aforementioned positioning method is a well-known technique, and thus the detailed description is omitted.

(26) The following is a detailed description of each component of the autonomous travel system 1.

(27) [Work Vehicle 10]

(28) FIG. 3 is an external view of the work vehicle 10, viewed from the left front side. FIG. 4A is an external view of the left side of the work vehicle 10 viewed from the left side, FIG. 4B is an external view of the right side of the work vehicle 10 viewed from the right side, and FIG. 4C is an external view of the back side of the work vehicle 10 viewed from the back side.

(29) As illustrated in FIGS. 1 to 4, the work vehicle 10 includes a vehicle control device 11, a storage 12, a traveling device 13, a spraying device 14, a communicator 15, a positioning device 16, and an obstacle detection device 17. The vehicle control device 11 is electrically connected to the storage 12, traveling device 13, spraying device 14, positioning device 16, obstacle detection device 17, and the like. The vehicle control device 11 and the positioning device 16 may be capable of wireless communication.

(30) The communicator 15 is a communication interface for connecting the work vehicle 10 to the communication network N1 by wire or wirelessly and for executing data communication according to a predetermined communication protocol with external devices such as the operation terminal 20 via the communication network N1.

(31) The storage 12 is a non-volatile storage unit such as an HDD (Hard Disk Drive) or an SSD (Solid State Drive) that stores various types of information. The storage 12 stores control programs such as an autonomous traveling program to cause the vehicle control device 11 perform

autonomous travel processing (see FIG. 11) described below. For example, the autonomous traveling program is non-transiently recorded on a computer-readable recording medium, such as a CD and a DVD, and is read by a predetermined reading device (not illustrated) and stored in the storage 12. The aforementioned autonomous traveling program may be downloaded from a server (not illustrated) to the work vehicle 10 via the communication network N1 and stored in the storage 12. Further, the storage 12 stores route data including information on the target route R generated at the operation terminal 20. For example, the aforementioned route data is transferred from the operation terminal 20 to the work vehicle 10 and stored in the storage 12.

(32) Here, the work vehicle 10 includes a gantry-shaped vehicle body 100 that travels over crops V (fruit trees) planted in multiple rows in the field F. As illustrated in FIG. 4C, the vehicle body 100 is formed in a gantry shape by a left side section 100L, a right side section 100R, and a connection section 100C connecting the left side section 100L and right side section 100R. A space 100S that allows the passage of the crop V is secured inside the left side section 100L, the right side section 100R, and the connection section 100C.

(33) Crawlers 101 are provided at the lower end of each of the left side section 100L and right side section 100R of the vehicle body 100. An engine (not illustrated) and a battery (not illustrated) are provided on the left side section 100L. A storage tank 14A (see FIG. 4B) and the like of the spraying device 14 are provided on the right side section 100R. In this way, by distributing and arranging the components on the left side section 100L and the right side section 100R of the vehicle body 100, the balance between the right and left is equilibrated and the center of gravity is lowered in the work vehicle 10. As a result, the work vehicle 10 can travel stably on slopes and other surfaces in the field F.

(34) The traveling device 13 is the driver that drives the work vehicle 10. The traveling device 13 includes an engine, the crawlers 101, and the like.

(35) The right and left crawlers 101 are driven by power from the engine with independent speed changes possible through a hydrostatic stepless transmission device. Accordingly, the vehicle body 100 is brought into a state of traveling straight in the forward-traveling direction by driving the right and left crawlers 101 at an even speed in the forward-traveling direction and is brought into a state of traveling straight in the backward-traveling direction by driving the right and left crawlers 101 at an even speed in the backward-traveling direction. Further, the vehicle body 100 is brought into a state of turning while traveling forward by driving the right and left crawlers 101 at an uneven speed in the forward-traveling direction and is brought into a state of turning while traveling backward by driving the right and left crawlers 101 at an uneven speed in the backward-traveling direction. Further, the vehicle body 100 is brought into a pivot turn (pivotal brake turn) state by driving one of the right and left crawlers 101 while the driving of the other crawler 101 is stopped, and is brought into a spin turn state (ultra-pivotal turn) by driving the right and left crawlers 101 at an even speed in the forward-traveling direction and the backward-traveling direction. Further, the vehicle body 100 is brought to a traveling stopped state by stopping the driving of the right and left crawlers 101. The right and left crawlers 101 may be configured so as to be electrically driven by an electric motor.

(36) As illustrated in FIG. 4C, the spraying device 14 includes a storage tank 14A that stores a chemical solution or the like, a spraying pump (not illustrated) that pumps the chemical solution or the like, an electric spraying motor (not illustrated) that drives the spraying pump, two spray pipes 14B provided in parallel on the right and left on the back of the vehicle body 100 in a vertical position, a total of 12 spray nozzles 14C, three provided for each spray pipe 14B, an electronically controlled valve unit (not illustrated) that changes the amount and pattern of spraying the chemical solution or the like, and a plurality of spraying pipes (not illustrated) connecting these.

(37) Each spray nozzle 14C is attached to the corresponding spray pipe 14B in a vertically repositionable manner. This allows each spray nozzle 14C to change the interval between adjacent spray nozzles 14C and the height position with respect to the spray pipe 14B in accordance with the

object to be sprayed (crop V). Further, each spray nozzle **14C** is attached in such a manner that the height position and right/left position with respect to the vehicle body **100** can be changed in accordance with the object to be sprayed.

(38) In the spraying device **14**, the number of the spray nozzles **14C** provided in each spray pipe **14B** can be changed in various ways depending on the type of crop V, the length of each spray pipe **14B**, and other factors.

(39) As illustrated in FIG. **4C**, of the plurality of spray nozzles **14C**, three spray nozzles **14C** provided on the leftmost spray pipe **14B** spray the chemical solution to the left toward the crop Va located on the left outer side of the vehicle body **100**. Of the plurality of spray nozzles **14C**, three spray nozzles **14C** provided on the left inner spray pipe **14B** adjacent to the leftmost spray pipe **14B** spray the chemical solution to the right toward a crop Vb located in the space **100S** at the center of the right and left sides of the vehicle body **100**. Of the plurality of spray nozzles **14C**, three spray nozzles **14C** provided on the rightmost spray pipe **14B** spray the chemical solution to the right toward a crop Vc located on the right outer side of the vehicle body **100**. Of the plurality of spray nozzles **14C**, three spray nozzles **14C** provided on the right inner spray pipe **14B** adjacent to the rightmost spray pipe **14B** spray the chemical solution to the left toward the crop Vb located in the space **100S**.

(40) With the above configuration, in the spraying device **14**, the two spray pipes **14B** and six spray nozzles **14C** on the left side section **100L** of the vehicle body **100** function as a left side sprayer **14L**. Further, the two spray pipes **14B** and six spray nozzles **14C** on the right side section **100R** of the vehicle body **100** function as a right side sprayer **14R**. In addition, the right and left sprayers **14L** and **14R** are disposed on the back of the vehicle body **100** with a right-left interval that allows the passage of the crop Vb (space **100S**) between the right and left sprayers **14L** and **14R** in the state of being able to spray in the right-left directions.

(41) In the spraying device **14**, the spray patterns by the sprayers **14L** and **14R** include a 4-way spray pattern where each of the sprayers **14L** and **14R** sprays the chemical solution in both the right and left directions, and a direction-limited spray pattern where the direction of the spray by the sprayers **14L** and **14R** is limited. The aforementioned direction-limited spray pattern includes a left side 3-way spray pattern where the sprayer **14L** sprays the chemical solution in both right and left directions and the sprayer **14R** sprays the chemical solution only in the left direction, a right side 3-way spray pattern where the sprayer **14L** sprays the chemical solution only in the right direction and the sprayer **14R** sprays the chemical solution in both right and left directions, a 2-way spray pattern where the sprayer **14L** sprays the chemical solution only in the right direction and the sprayer **14R** sprays the chemical solution only in the left direction, a left side 1-way spray pattern where the sprayer **14L** sprays only in the left direction and the sprayer **14R** does not spray the chemical solution, and a right side 1-way spray pattern where the sprayer **14R** sprays only in the right direction and the sprayer **14L** does not spray the chemical solution.

(42) Mounted on the vehicle body **100** are an autonomous traveling controller that causes the vehicle body **100** to autonomously travel along the target route R in the field F on the basis of positioning information or the like acquired from the positioning device **16**, an engine controller that controls the engine, and an HST (Hydro-Static Transmission) controller that controls a hydrostatic stepless transmission device, and a work device controller that controls a work device such as the spraying device **14**. Each controller is constructed by an electronic control unit equipped with a microcontroller or the like, various information, a control program, or the like stored in a non-volatile memory of the microcontroller (for example, EEPROM such as a flash memory). Various information stored in non-volatile memory may include a pre-generated target route R, and the like. In the present embodiment, the respective controllers are collectively referred to as the “vehicle control device **11**” (see FIG. **2**).

(43) The positioning device **16** is a communication device equipped with a positioning controller **161**, a storage **162**, a communicator **163**, an antenna **164**, and the like. The antenna **164** is provided

in front of and behind the ceiling of the vehicle body **100** (connection section **100C**) (see FIG. 3). Further, the ceiling of the vehicle body **100** is also equipped with an indicator light **102** or the like that displays the traveling state of the work vehicle **10** (see FIG. 3). The aforementioned battery is connected to the positioning device **16**, and the positioning device **16** can operate while the aforementioned engine is stopped.

(44) The communicator **163** is a communication interface for connecting the positioning device **16** to the communication network **N1** by wire or wirelessly and for executing data communication according to a predetermined communication protocol with external devices such as the base station **40** via the communication network **N1**.

(45) The antenna **164** receives radio waves (GNSS signals) transmitted from satellites. Since the antenna **164** is provided in front of and behind the work vehicle **10**, the current position and orientation of the work vehicle **10** can be accurately measured.

(46) The positioning controller **161** is a computer system including one or more processors and a storage memory such as a non-volatile memory and a RAM. The storage **162** is a non-volatile memory or the like that stores control programs for causing the positioning controller **161** perform positioning processing, as well as data such as positioning information and movement information. The positioning controller **161** measures the current position and current orientation of the work vehicle **10** by a predetermined positioning method (RTK method, etc.) on the basis of GNSS signals that the antenna **164** receives from the satellite **50**.

(47) The obstacle detection device **17** includes a LiDAR sensor **171L** on the front left side of the vehicle body **100** and a LiDAR sensor **171R** on the front right side of the vehicle body **100** (see FIG. 3). Each LiDAR sensor measures the distance from the LiDAR sensor to each distance measurement point (object to be measured) in the measurement range by, for example, the TOF (Time Of Flight) method, in which the distance to the distance measurement point is measured on the basis of the round-trip time for a laser light emitted by the LiDAR sensor to return after reaching the distance measurement point.

(48) For the LiDAR sensor **171L**, a predetermined range on the front left side of the vehicle body **100** is set as the measurement range, and for the LiDAR sensor **171R**, a predetermined range on the front right side of the vehicle body **100** is set as the measurement range. Each LiDAR sensor transmits measurement information to the vehicle control device **11**, such as the distance to each distance measurement point and the scanning angle (coordinates) to each distance measurement point.

(49) Further, the obstacle detection device **17** includes right and left ultrasonic sensors **172F** (see FIG. 3) provided on the front side of the vehicle body **100** and right and left ultrasonic sensors **172R** (see FIGS. 4A to 4C) provided on the rear side of the vehicle body **100**. Each ultrasonic sensor measures the distance from the ultrasonic sensor to the distance measurement point by the TOF method, in which the distance to the distance measurement point is measured on the basis of the round-trip time for an ultrasonic wave transmitted by the ultrasonic sensor to return after reaching the distance measurement point.

(50) For the ultrasonic sensor **172F** on the front left side, a predetermined range on the front left side of the vehicle body **100** is set as the measurement range. For the ultrasonic sensor **172F** on the front right side, a predetermined range on the front right side of the vehicle body **100** is set as the measurement range. For the ultrasonic sensor **172R** on the rear left side, a predetermined range on the rear left side of the vehicle body **100** is set as the measurement range. For the ultrasonic sensor **172R** on the rear right side, a predetermined range on the rear right side of the vehicle body **100** is set as the measurement range. Each ultrasonic sensor transmits the measurement information including the distance to the object to be measured and the direction of the object to be measured to the vehicle control device **11**.

(51) Further, the obstacle detection device **17** includes right and left contact sensors **173F** (see FIG. 3) provided on the front side of the vehicle body **100** and right and left contact sensors **173R** (see

FIGS. 4A and 4B) provided on the rear side of the vehicle body **100**. The contact sensor **173F** on the front side of the vehicle body **100** detects an obstacle when the obstacle contacts the contact sensor **173F**. In front of the contact sensor **173R** on the rear side of the vehicle body **100** (rear side of the work vehicle **10**), the spraying device **14** is provided. When an obstacle comes into contact with the spraying device **14**, the contact sensor **173R** detects the obstacle by the spraying device **14** moving to the rear (front side of the work vehicle **10**). Each contact sensor transmits a detection signal to the vehicle control device **11** when detecting an obstacle.

(52) The vehicle control device **11** executes avoidance processing to avoid obstacles when there is a possibility that the work vehicle **10** may collide with an obstacle, on the basis of measurement information on the obstacle acquired from the obstacle detection device **17**.

(53) The vehicle control device **11** includes control devices such as a CPU, a ROM, and a RAM. The aforementioned CPU is a processor that performs various arithmetic operations. The aforementioned ROM is a non-volatile storage in which control programs such as a BIOS and an OS for causing the CPU to execute various types of arithmetic processing are stored in advance. The aforementioned RAM is a volatile or non-volatile storage that stores various information, and is used as a temporary storage memory (work area) for various types of processing executed by the CPU. In addition, the vehicle control device **11** controls the work vehicle **10** by executing various control programs stored in advance in the aforementioned ROM or the storage **12** by the CPU.

(54) The vehicle control device **11** controls the travel of the work vehicle **10**. Specifically, the vehicle control device **11** causes the work vehicle **10** to autonomously travel along the target route R on the basis of position information indicating the position of the work vehicle **10** measured by the positioning device **16**. For example, when the aforementioned state becomes RTK positioning available and the operator presses the start button on the operation terminal **20**, the operation terminal **20** outputs a work start instruction to the work vehicle **10**. When acquiring the work start instruction from the operation terminal **20**, the vehicle control device **11** starts the autonomous traveling of the work vehicle **10** on the basis of the position information indicating the position of the work vehicle **10** measured by the positioning device **16**. As a result, the work vehicle **10** starts autonomous traveling along the target route R and starts a spraying work by the spraying device **14** in the work passage.

(55) Further, the vehicle control device **11** stops the autonomous traveling of the work vehicle **10** when acquiring a travel stop instruction from the operation terminal **20**. For example, when the operator presses the stop button on the operation screen of the operation terminal **20**, the operation terminal **20** outputs the aforementioned travel stop instruction to the work vehicle **10**. The vehicle control device **11** stops the autonomous traveling of the work vehicle **10** when acquiring the aforementioned travel stop instruction from the operation terminal **20**. This causes the work vehicle **10** to stop its autonomous traveling and the spraying work by the spraying device **14**.

(56) The above configuration allows the work vehicle **10** to travel autonomously with high precision along the target route R, and also allows the spraying of a chemical solution or the like by the spraying device **14** to be performed properly.

(57) The configuration of the work vehicle **10** described above is a configuration example of the work vehicle of the present invention, and the present invention is not limited to the configuration described above. The work vehicle **10** described above is a vehicle that can perform a spraying work in which a sprayed object is sprayed on a first crop row Vr and a second crop row Vr in each of the right-left directions of the first crop row Vr while traveling over the first crop row Vr. As another embodiment, the work vehicle **10** may have a normal shape in which the entire vehicle body **100** travels between the crop rows Vr (work passages) instead of the gantry shape of the vehicle body **100**. In this case, the work vehicle **10** autonomously travels in each work passage without straddling the crop row Vr. Further, the spraying device **14** includes one sprayer, and switches among a spray pattern that sprays a chemical solution in right and left directions, a spray pattern that sprays the chemical solution only to the left, and a spray pattern that sprays the

chemical solution only to the right, to perform the spraying work.

(58) [Operation Terminal **20**]

(59) As illustrated in FIG. **2**, the operation terminal **20** is an information processing apparatus that includes a controller **21**, a storage **22**, an operation acceptor/displayer **23**, a communicator **24**, and the like. The operation terminal **20** may include a portable terminal such as a tablet device, and a smartphone. The operation terminal **20** is an example of the route generation device of the present invention.

(60) The communicator **24** is a communication interface for connecting the operation terminal **20** to the communication network **N1** by wire or wirelessly and for executing data communication according to a predetermined communication protocol with one or more external devices such as the work vehicle **10** via the communication network **N1**.

(61) The operation acceptor/displayer **23** is a user interface that includes a display such as an LCD or an organic EL display that displays various types of information and an operation acceptor such as a touch panel, mouse, and keyboard that accepts operations. The operator can operate the aforementioned operation acceptor to register various types of information (work vehicle information, field information, work information, etc., as described below) on the operation screen displayed on the aforementioned display. Further, the operator can also operate the aforementioned operation acceptor to give work start and travel stop instructions to the work vehicle **10**.

Furthermore, the operator, at a distance from the work vehicle **10**, can grasp the traveling state, working condition, and surrounding situation of the work vehicle **10** that autonomously travels in the field **F** along the target route **R**, on the basis of the traveling locus displayed on the operation terminal **20** and the surrounding image of the vehicle body **100**.

(62) The storage **22** is a non-volatile storage such as an HDD or an SSD that stores various types of information. The storage **22** stores control programs such as an autonomous traveling program (route generation program) to cause the controller **21** perform autonomous travel processing (see FIG. **11**) including route generation processing described below. For example, the aforementioned autonomous traveling program is non-transiently recorded on a computer-readable recording medium such as a CD and a DVD, and is read by a predetermined reading device (not illustrated) and stored in the storage **22**. The aforementioned autonomous traveling program may be downloaded from a server (not illustrated) to the operation terminal **20** via the communication network **N1** and stored in the storage **22**.

(63) The controller **21** includes control devices such as a CPU, a ROM, and a RAM. The aforementioned CPU is a processor that performs various arithmetic operations. The aforementioned ROM is a non-volatile storage in which control programs such as a BIOS and an OS for causing the CPU to execute various types of arithmetic processing are stored in advance. The aforementioned RAM is a volatile or non-volatile storage that stores various information, and is used as a temporary storage memory (work area) for various types of processing executed by the CPU. In addition, the controller **21** controls the operation terminal **20** by executing various control programs stored in advance in the ROM or the storage **22** by the CPU.

(64) In the case of a field **F** with a narrow headland area, the work vehicle **10** may not be able to turn properly when moving in the crop row **Vr**. For example, as illustrated in FIG. **8**, in a field **F** where a headland area **Fa** is narrow and a sufficient turning area cannot be secured, when the work vehicle **10** makes a turn (for example, 180-degree turn) in the headland area **Fa** to finish the work of the first crop row and enter the next second crop row, the work vehicle **10** may deviate out of the field. With a conventional technique, it is difficult to generate an appropriate target route **R** for such a field **F**. In contrast, the operation terminal **20** according to the present embodiment can generate a target route **R** appropriately in the field **F** where a sufficient turning area cannot be secured.

(65) In FIG. **8**, a sign **F1** represents a work area where the crop **V** is arranged, and signs **Fa** and **Fc** represent a headland area where the work vehicle **10** turns (turning area), and a sign **Fb** represents a movement area for the work vehicle **10** to move. Further, the headland areas **Fa** and **Fc** and the

movement area Fb are the areas surrounding the work area F1 and the crop V is included in the non-work area where the crop V is not arranged.

(66) Specifically, as illustrated in FIG. 2, the controller **21** includes various processors such as a setting processor **211**, a route generation processor **212**, and an output processor **213**. The controller **21** functions as the aforementioned various processors by executing various processing according to the aforementioned control program by the aforementioned CPU. Further, some or all of the aforementioned processors may be configured by an electronic circuit. The aforementioned control program may be a program to cause a plurality of processors to function as the aforementioned processors.

(67) The setting processor **211** sets and registers information on the work vehicle **10** (hereinafter referred to as work vehicle information), information on the field F (hereinafter referred to as field information), and information on a work (here, the spraying work) (hereinafter referred to as work information).

(68) In the setting processing of the aforementioned work vehicle information, the setting processor **211** sets the information such as the model of the work vehicle **10**, the position where the antenna **164** is attached in the work vehicle **10**, the type of the work machine (here, the spraying device **14**), the size and shape of the work machine, the position of the work machine with respect to the work vehicle **10**, the vehicle speed and engine speed during work of the work vehicle **10**, and the vehicle speed and engine speed during turning of the work vehicle **10**, by the operator performing an operation to register the information on the operation terminal **20**. In the present embodiment, information on the spraying device **14** is set as information on a work machine.

(69) In the setting processing of the aforementioned field information, the setting processor **211** sets the information such as the position and shape of the field F, the work start position S to start a work and the work end position G to finish the work (see FIG. 6), and the work direction, by the operator performing an operation to register the information on the operation terminal **20**. The work direction means the direction where the work vehicle **10** travels while performing a spraying work with the spraying device **14** in the work area F1 which is the area of the field F excluding the non-work area such as the headland area Fa.

(70) Information on the position and shape of the field F can be acquired automatically, for example, by the operator manually driving the work vehicle **10** along the perimeter of the field F by one round and recording the transition of the position information of the antenna **164** at that time. Further, the position and shape of the field F can also be acquired on the basis of a polygon obtained by specifying multiple points on a map by the operator operating the operation terminal **20** while the map is displayed on the operation terminal **20**. The area identified by the acquired position and shape of the field F is the area where the work vehicle **10** can travel (travel area).

(71) In the setting processing of the aforementioned work information, the setting processor **211** is configured to be able to set the number of skips which is the number of work routes to be skipped when the work vehicle **10** turns in the headland, the width of the headland, and the like, as the work information.

(72) The route generation processor **212** generates a target route R, which is a route where the work vehicle **10** travels autonomously, on the basis of each of the aforementioned setting information. The target route R is, for example, a route from the work start position S to the work end position G. The route generation processor **212** generates the target route R in the first route generation mode in the case of the field F where a sufficient turning area can be secured, and generates the target route R in the second route generation mode in the case of the field F where a sufficient turning area cannot be secured. In other words, the route generation processor **212** sets the route generation mode to generate the target route R to the first route generation mode or the second route generation mode on the basis of the shape of the field F, to perform the route generation processing that generates the target route R. The route generation processor **212** is an example of the route generation processor of the present invention.

(73) Here, an example of the generation method of the target route R (see FIG. 6) in the first route generation mode will be described. The target route R illustrated in FIG. 6 includes a straight work route R1 for spraying a chemical solution on the crop V in the area (work area F1) where the crop V is planted, and a movement route R2 for moving between the crop rows Vr without spraying in the area where crop V is not planted (headland area Fa).

(74) FIGS. 7A and 7B illustrate an overview of a method for generating the target route R in the first route generation mode. FIG. 7A schematically illustrates a crop row Vr. First, the operator manually drives the work vehicle 10 along the perimeter of the crop row Vr (see FIG. 7A). The work vehicle 10 detects an end point E1 on one side (bottom side in FIG. 7A) and an end point E2 on the other side (top side in FIG. 7A) of each crop row Vr while traveling and acquires position information (coordinates) of the respective end point E1 and E2. The end points E1 and E2 may be the location of a crop V that has already been planted or the location of a target that indicates the location of a crop V that will be planted in the future. When acquiring the position information (coordinates) of the respective end point E1 and E2 from the work vehicle 10, the route generation processor 212 sets a line L1 (see FIG. 7B) connecting the corresponding end points E1 and E2 to the work route R1 of the crop row Vr, and generates a target route R including a plurality of work routes R1 and a movement route R2 (turning route). Further, the route generation processor 212 generates a target route R where the work vehicle 10 reciprocates on the plurality of work routes R1 in the work area F1 and turns 180 degrees in the headland area Fa. The route generation processor 212 may store the generated target route R in the storage 22.

(75) Next, an example of the generation method of the target route R in the second route generation mode will be described using the field F illustrated in FIG. 8 as an example. Here, the route generation processor 212 generates the target route R in the second route generation mode when the information on the field F and the work vehicle 10 fulfills a predetermined condition. Specifically, the route generation processor 212 generates the target route R in the second route generation mode when the following conditional expression is fulfilled.

$$D < 1.5L + W/2 + r$$

(76) FIG. 9 schematically illustrates a relation between the work vehicle 10 and the headland area Fa. FIG. 9 illustrates how the work vehicle 10 finishes the work of a work route Rx (first crop row Vr), turns a turning route Ra in the headland area Fa, and moves to a next work route Ry (second crop row Vr). In the above conditional expression, “D” indicates the width of the headland area Fa, “L” indicates the overall length of the work vehicle 10, “W” indicates the width of the work vehicle 10, and “r” indicates the turning radius of the work vehicle 10. The turning start position of the work vehicle 10 is set at a position half the length (0.5L) of the total length of the work vehicle 10 from the end point E2 (end point) of the crop row Vr.

(77) If the above conditional expression is fulfilled, the work vehicle 10 cannot make a 180-degree turn in the headland area Fa, and may deviate out of the field. Accordingly, the route generation processor 212 generates the target route R in the second route generation mode when the above conditional expression is fulfilled. In other words, the route generation processor 212 generates the target route R (see FIG. 6) in the first route generation mode when the above conditional expression is not fulfilled, and generates the target route R (see FIG. 10) in the second route generation mode when the above conditional expression is fulfilled.

(78) FIG. 10 illustrates an example of the target route R in the second route generation mode. The route generation processor 212 accepts operations to specify the work start position S and the work end position G from the operator on the operation screen, and sets the work start position S and the work end position G on the basis of the operations.

(79) Further, the route generation processor 212 generates a plurality of work routes R1 (work routes R1a to Rif in FIG. 10) where the work vehicle 10 travels straight in a first direction Da that is a travel direction of the work vehicle 10, in the work area F1. As in the method for generating the work route R1 of the target route R by the first route generation mode (see FIGS. 7A and 7B), the

route generation processor **212** generates a plurality of work routes **R1** in one direction (first direction **Da**) by a line connecting the end points **E1** and **E2** of each crop row **Vr**.

(80) Further, the route generation processor **212** generates a movement route **R3** (corresponding to the first movement route of the present invention) that is continuous with the work route **R1**, in the headland area **Fa** (corresponding to the first non-work area of the present invention) adjacent to the work area **F1** in the first direction **Da**, in non-work areas surrounding the work area **F1**, where the crop **V** is not arranged. The movement route **R3** includes a turning route **R3a** that connects to the work route **R1** and a straight route **R3b** that connects to the turning route **R3a**. Further, the straight route **R3b** extends in a direction inclined at a predetermined angle θ with respect to the first direction **Da**.

(81) Further, the route generation processor **212** generates a movement route **R4** (corresponding to the second movement route of the present invention) that is a single route continuous with the movement route **R3** and that guides the work vehicle **10** to each of the plurality of work routes **R1** (work routes **R1a** to **R1f**). The movement route **R4** includes a turning route **R4a** that connects to the straight route **R3b** and a straight route **R4b** that connects to the turning route **R4a**. Further, the movement route **R4** is included in the movement area **Fb** (corresponding to the second non-work area of the present invention) adjacent to the work area **F1** in a direction orthogonal to the first direction **Da**, in the non-work areas. Further, the straight route **R4b** extends in a second direction **Db** that is a direction opposite to the first direction **Da**.

(82) Further, the route generation processor **212** generates a movement route **R5** that is continuous with the movement route **R4** and that connects to each of the plurality of work routes **R1** (work routes **R1a** to **R1f**). The movement route **R5** includes a turning route **R5a** that connects to the straight route **R4b**, a straight route **R5b** that connects to the turning route **R5a**, and a turning route **R5c** that connects to the straight route **R5b** and the work route **R1**. Further, the movement route **R5** is included in a headland area **Fc** adjacent to the work area **F1** in the second direction **Db**, in the non-work areas. Further, the straight route **R5b** extends in a direction orthogonal to the first direction **Da** and the second direction **Db**. The headland area **Fc** illustrated in FIG. **10** may have a width that does not fulfill the above conditional expression.

(83) Further, the route generation processor **212** sets a turning radius **TR0** of the turning route **R3a**, a turning radius **TR1** of the turning route **R4a**, a turning radius **TR2** of the turning route **R5a**, and a turning radius **TR3** of the turning route **R5c**. For example, the route generation processor **212** accepts an operation to select a turning radius from the operator on the operation screen

(corresponding to the user operation of the present invention). In addition, the route generation processor **212** sets the turning radius of each turning route on the basis of the operator's selection operation. Here, the angle θ between the work route **R1** and the straight route **R3b** is greater than 90 degrees. In this case, the route generation processor **212** sets the turning radius **TR0** of the turning route **R3a** to a value smaller than the turning radius **TR1** of the turning route **R4a**, the turning radius **TR2** of the turning route **R5a**, and the turning radius **TR3** of the turning route **R5c**. In other words, the route generation processor **212** turns the work vehicle **10** by setting the turning radius to a smaller value in the headland area **Fa** where a sufficient turning area cannot be secured.

(84) The method for setting the turning radius is not limited to the above configuration. As another embodiment, the route generation processor **212** may set each turning radius on the basis of the information such as the shape of the field **F**, the width of the turning area (headland area **Fa**), and the size and shape of the work vehicle **10**. In other words, the route generation processor **212** may automatically set each turning radius without the aforementioned user operation.

(85) In this way, in the second route generation mode, the route generation processor **212** generates the target route **R** including the work route **R1**, movement route **R3**, **R4**, and **R5** (see FIG. **10**) where the work vehicle **10** travels autonomously from the work start position **S** to the work end position **G**. The work vehicle **10** autonomously travels along the generated target route **R**. In other words, when traveling in the work area **F1**, the work vehicle **10** travels on the work routes **R1a** to

Rif in the first direction Da in sequence and repeatedly travel the same movement route R4 (straight route R4b) when traveling in the movement area Fb, thereby traveling around the field F. In this way, the work vehicle 10 travels around by traveling in sequence on the work routes R1a to Rif as approach routes and traveling on the movement route R4 as a fixed return route.

(86) Further, the route generation processor 212 sets the travel speed of the work vehicle 10 traveling along the target route R. Specifically, the route generation processor 212 sets the travel speed of the work vehicle 10 traveling along the movement routes R3, R4, and R5 to a speed according to the length of the movement route. For example, the route generation processor 212 sets the travel speed to be faster as the length of the straight route included in the movement route is longer. For example, if the travel speed for the work route R1 is V1, the travel speed for the straight route R3b is V3, the travel speed for the straight route R4b is V4, and the travel speed for the straight route R5b is V5, then the travel speeds V3, V4, and V5 are set to be higher than V1. Further, if the length of the straight route R4b is longer than the straight route R3b or the straight route R5b, the travel speed V4 is set to be higher than the travel speed V3 or V5. This makes it possible to shorten the travel time compared to the case where the travel speeds for the movement routes R3, R4, and R5 are set uniformly (same speed), thereby improving work efficiency.

(87) As described above, the route generation processor 212 generates the target route R in the first route generation mode when the field F does not fulfill the aforementioned conditional expression, and generates the target route R in the second route generation mode when at least part of the headland area of the field F fulfills the aforementioned conditional expression.

(88) The output processor 213 outputs route data including information on the target route R generated by the route generation processor 212 to the work vehicle 10. The output processor 213 may output the route data to a server (not illustrated). The aforementioned server stores and manages a plurality of the route data to be acquired from each of the plurality of operation terminals 20, in association with the operation terminals 20 and the work vehicle 10.

(89) In addition to the processing described above, the controller 21 executes the processing of displaying various types of information on the operation acceptor/displayer 23. For example, the controller 21 displays, on the operation acceptor/displayer 23, a registration screen for registering work vehicle information, field information, work information, and the like, an operation screen for generating the target route R, an operation screen for causing the work vehicle 10 start autonomous traveling, a display screen for displaying the traveling state of the work vehicle 10, or the like.

(90) Further, the controller 21 accepts various operations from the operator. Specifically, the controller 21 accepts, from the operator, a work start instruction to start work on the work vehicle 10, a travel stop instruction to stop the travel of the work vehicle 10 during autonomous travel, or the like. Upon receipt of each of the aforementioned instructions, the controller 21 outputs each of the aforementioned instructions to the work vehicle 10.

(91) Upon receipt of the work start instruction from the operation terminal 20, the vehicle control device 11 of the work vehicle 10 starts the autonomous traveling and the spraying work of the work vehicle 10. Further, upon receipt of the travel stop instruction from the operation terminal 20, the vehicle control device 11 stops the autonomous traveling and the spraying work of the work vehicle 10.

(92) The operation terminal 20 may be able to access the website of the agricultural support service provided by the server (agricultural support site) via the communication network N1. In this case, the operation terminal 20 can function as a terminal for operating the server by executing a browser program by the controller 21.

(93) [Autonomous Travel Processing]

(94) With reference to FIG. 11, an example of the autonomous travel processing executed by the controller 21 of the operation terminal 20 and the vehicle control device 11 of the work vehicle 10 is described below.

(95) The present invention can be viewed as an invention of an autonomous traveling method that

executes one or more steps included in the aforementioned autonomous travel processing. Further, one or more steps included in the aforementioned autonomous travel processing described here may be appropriately omitted. Each step in the aforementioned autonomous travel processing may be executed in a different order as long as the same effect is obtained. Furthermore, although a case where the controller **21** and the vehicle control device **11** execute each step in the aforementioned autonomous travel processing is described here as an example, an autonomous traveling method in which one or more processors execute each step in the autonomous travel processing in a distributed manner is also considered as another embodiment. The aforementioned autonomous travel processing includes route generation processing executed by the controller **21** of the operation terminal **20**. Further, the aforementioned autonomous traveling method includes the route generation method of the present invention.

(96) In step **S1**, the controller **21** of the operation terminal **20** registers various setting information. Specifically, the controller **21** sets and registers information on the work vehicle **10** (work vehicle information), information on the field **F** (field information), and information on a work (work information), on the basis of the operator's setting operations.

(97) Next, in step **S2**, the controller **21** determines whether the width of the headland area of the field **F** is greater than a predetermined width. For example, in the field **F** illustrated in FIG. **8**, the controller **21** determines whether a width **D** (see FIG. **9**) of the headland area **Fa** is greater than or equal to than a predetermined width ($1.5L+W/2+r$) on the basis of the aforementioned field information. If the width **D** of the headland area **Fa** is greater than or equal to the predetermined width (**S2**: Yes), the processing proceeds to step **S3**. On the other hand, if the width **D** of the headland area **Fa** is less than the predetermined width (**S2**: No), the processing proceeds to step **S21**. The field **F** illustrated in FIG. **6** represents a field where the width **D** of the headland area **Fa** is equal to or greater than a predetermined width, and the field **F** illustrated in FIG. **8** represents a field where the width **D** of the headland area **Fa** is less than the predetermined width.

(98) In step **S3**, the controller **21** generates the target route **R** in the first route generation mode. For example, when an operation to specify the work start position **S** and the work end position **G** in the field **F** illustrated in FIG. **6** is received from the operator, the controller **21** generates the target route **R** including the plurality of work routes **R1** for reciprocating the work vehicle **10** in the work area **F1** and the movement route **R2** for turning the work vehicle **10** 180 degrees in the headland areas **Fa** and **Fc**. After step **S3**, the processing proceeds to step **S4**.

(99) In contrast, in step **S21**, the controller **21** generates the target route **R** in the second route generation mode. For example, when an operation to specify the work start position **S** and the work end position **G** in the field **F** illustrated in FIG. **8** is received from the operator, the controller **21** generates the target route **R** including the plurality of work routes **R1** where the work vehicle **10** travels in one direction (first direction **Da**) in the work area **F1**, the movement route **R3** that includes the straight route **R3b** where the work vehicle **10** travels straight in the headland area **Fa**, the movement route **R4** that is a single route continuous with the movement route **R3** and that includes the straight route **R4b** where the work vehicle **10** travels straight in one direction (second direction **Db**), and the movement route **R5** that is a route continuous with the movement route **R4** and that causes the work vehicle **10** to enter each work route **R1** (work routes **111a** to **R1f**).

(100) The movement route **R4** is set in the movement area **Fb** of the non-work area, and the straight route **R4b** included in the movement route **R4** extends in the second direction **Db** that is a direction opposite to the first direction **Da**. After step **S21**, the processing proceeds to step **S4**.

(101) In step **S4**, the controller **21** transfers the route data of the target route **R** to the work vehicle **10**. When acquiring the aforementioned route data, the vehicle control device **11** of the work vehicle **10** stores same in the storage **12**.

(102) Next, in step **S5**, the vehicle control device **11** determines whether a work start instruction has been acquired from the operation terminal **20**. For example, when the operator presses the start button on the operation terminal **20**, the operation terminal **20** outputs a work start instruction to the

work vehicle **10**. When the vehicle control device **11** acquires the work start instruction from the operation terminal **20** (S5: Yes), the processing proceeds to step S6. The vehicle control device **11** waits until acquiring the work start instruction from the operation terminal **20** (S5: No).

(103) In step S6, the vehicle control device **11** starts autonomous traveling along the target route R according to the aforementioned route data. For example, in the field F illustrated in FIG. 6, the work vehicle **10** autonomously travels along the target route R generated in the first route generation mode. Further, for example, in the field F illustrated in FIG. 10, the work vehicle **10** autonomously travels along the target route R generated in the second route generation mode.

(104) Next, in step S7, the vehicle control device **11** determines whether the work vehicle **10** has finished the work. The vehicle control device **11** determines that the work has been finished when the position of the work vehicle **10** coincides with the work end position G. When the work vehicle **10** has finished the work (S7: Yes), the above autonomous travel processing ends. The vehicle control device **11** repeats the processing of step S7 until the work vehicle **10** finishes the work and continues autonomous traveling.

(105) As described above, the autonomous travel system **1** according to the present embodiment generates the plurality of work routes R1 where the work vehicle **10** travels straight in the first direction Da that is a travel direction of the work vehicle **10**, in the work area F1 where the work object (crop V) is arranged, generates the movement route R3 that is a route continuous with the work route R1 and that includes the straight route R3b where the work vehicle **10** travels straight, in the first non-work area (headland area Fa) adjacent to the work area F1 in the first direction Da, in non-work areas surrounding the work area F1, where the aforementioned work object is not arranged, and generates the movement route R4 that is a single route continuous with the movement route R3 and that guides the work vehicle **10** to each of the plurality of work routes R1.

(106) Further, an autonomous travel method (route generation method) according to the present embodiment is a method in which one or more processors execute generating the plurality of work routes R1 where the work vehicle **10** travels straight in the first direction Da that is a travel direction of the work vehicle **10**, in the work area F1 where the work object (crop V) is arranged, generating the movement route R3 that is a route continuous with the work route R1 and that includes the straight route R3b where the work vehicle **10** travels straight, in the first non-work area (headland area Fa) adjacent to the work area F1 in the first direction Da, in non-work areas surrounding the work area F1, where the aforementioned work object is not arranged, and generating the movement route R4 that is a single route continuous with the movement route R3 and that guides the work vehicle **10** to each of the plurality of work routes R1.

(107) According to the above configuration, for example, as illustrated in FIG. 10, in a case where the headland area Fa has a shape that makes it difficult to turn the work vehicle **10** 180 degrees, after the work vehicle **10** has traveled on the work route R1, it is possible to generate the target route R for traveling straight on the straight route R3b without turning 180 degrees in the headland area Fa. Thus, it is possible to generate the target route R appropriately in the field F where a sufficient turning area cannot be secured. In addition, the work vehicle **10** can perform a work while traveling efficiently and autonomously, even in the field F where a sufficient turning area cannot be secured.

(108) The present invention is not limited to the above-described embodiment. Other embodiments of the present invention will be described below.

(109) For example, the field F illustrated in FIG. 12 is a field where both the headland area Fa adjacent to the first direction Da and the headland area Fc adjacent to the second direction Db with respect to the work area F1 fulfill the above conditional expression. In this case, as another embodiment of the present invention, the route generation processor **212** generates a movement route R5 which connects to the work route R1, in the headland area Fc adjacent to the work area F1 in the second direction Db, in non-work areas surrounding the work area F1, where the crop V is not arranged. The movement route R5 includes a turning route R5a that connects to the straight

route **R4b** of the movement route **R4** and a straight route **R5b** that connects to the turning route **R5c**. Further, the straight route **R5b** extends in a direction inclined at a predetermined angle θ with respect to the first direction **Da**.

(110) Further, the route generation processor **212** sets the turning radius **TR3** of the turning route **R5c** to a value smaller than the turning radius **TR1** of the turning route **R4a** and the turning radius **TR2** of the turning route **R5a**. In this way, the route generation processor **212** generates the target route **R** in the second route generation mode when at least a part of the headland area of the field **F** fulfills the aforementioned conditional expression.

(111) As another embodiment of the present invention, the movement route **R4** (return route) that connects to the movement route **R3** included in the headland area **Fa** where it is difficult for the work vehicle **10** to make a 180-degree turn may be included in the work area **F1**. In other words, the straight route **R4b** included in the movement route **R4** may be one of the work routes **R1**. For example, as illustrated in FIG. 13, the straight route **R4b** is the work route **R1g** located at the end of the work area **F1** in the plurality of work routes **R1**. As a result, when traveling in the work area **F1**, the work vehicle **10** travels on the work routes **R1a** to **R1f** in the first direction **Da** in sequence and repeatedly travel the same movement route **R4** (work route **R1g**), thereby traveling around the field **F**. In this way, the work vehicle **10** travels around by traveling in sequence on the work routes **R1a** to **R1f** as approach routes and traveling on the work route **R1g** as a fixed return route.

(112) In the target route **R** illustrated in FIG. 13, the work vehicle **10** performs the spraying work when traveling on the work route **R1g** for the first time and does not perform the spraying work when traveling on the work route **R1g** for the second and subsequent times. Further, the work vehicle **10** may set the travel speed for the second and subsequent travels on the work route **R1g** to a higher speed than that for the first travel.

(113) In each of the above embodiments, the operation terminal **20** alone corresponds to the route generation device according to the present invention, but the route generation device according to the present invention may include one or more components of the operation terminal **20** and the server (not illustrated). For example, the aforementioned server alone may constitute the route generation device according to the present invention.

REFERENCE SIGNS LIST

(114) **1**: autonomous travel system **10**: work vehicle **11**: vehicle control device **14**: spraying device **16**: positioning device **17**: obstacle detection device **20**: operation terminal (route generation device) **211**: setting processor **212**: route generation processor **213**: output processor **40**: base station **50**: satellite **F**: field **F1**: work area **R**: target route **R1**: work route **R2**: movement route **R3**: movement route (first movement route) **R3b**: straight route **R4**: movement route (second movement route) **R4b**: straight route **Fa**: headland area (first non-work area) **Fb**: movement area (second non-work area) **V**: crop (work object) **Vr**: crop row **Da**: first direction **Db**: second direction

Claims

1. An autonomous travel system for a route generation comprising: a work vehicle having an autonomous traveling controller, mounted on the work vehicle, executing and traveling on a plurality of work routes where the work vehicle travels straight in a first direction that is a travel direction of the work vehicle, in a work area where a work object is arranged; wherein the work vehicle having the controller, executes and travels on a first movement route that is a route continuous with at least one of the plurality of work routes and that includes a straight route, in a first non-work area adjacent to the work area in the first direction, in non-work areas surrounding the work area, where the work object is not arranged; and the work vehicle having the controller, executes and travels on a second movement route that is a single route continuous with the first movement route and that guides the work vehicle to each of the plurality of work routes.
2. The autonomous travel system for a route generation according to claim 1, wherein the second

movement route includes a straight route where the work vehicle travels straight in a second direction that is a direction opposite to the first direction.

3. The autonomous travel system for a route generation according to claim 1, wherein the second movement route is included in a second non-work area adjacent to the work area in a direction orthogonal to the first direction, in the non-work areas.

4. The autonomous travel system for a route generation according to claim 1, wherein the second movement route is a work route located at an end of the work area in the plurality of work routes.

5. The autonomous travel system for a route generation according to claim 1, wherein the straight route included in the first movement route extends in a direction inclined with respect to the first direction.

6. The autonomous travel system for a route generation according to claim 1, wherein a turning radius of a turning route included in the first movement route is set to a smaller value than a turning radius of a turning route included in the second movement route.

7. The autonomous travel system for a route generation according to claim 6, wherein a user operation to select a turning radius of a turning route is accepted, and the turning radius of the turning route included in the first movement route and the turning radius of the turning route included in the second movement route are set on a basis of the user operation.

8. The autonomous travel system for a route generation according to claim 1, wherein a travel speed of the work vehicle traveling on the second movement route is set to a speed according to a length of the second movement route.

9. The autonomous travel system for a route generation according to claim 1, wherein the work vehicle is a vehicle that can perform a spraying work in which a sprayed object is sprayed on a first work object and a second work object in each of the right-left directions of the first work object while traveling over the first work object.

10. An autonomous travel system for a route generation comprising: a work vehicle; and an operation terminal having a route generation processor that generates in an autonomous traveling controller, mounted on the work vehicle, wherein the work vehicle travels on a plurality of work straight in a first direction that is a travel direction of the work vehicle, in a work area where a work object is arranged; the work vehicle travels on a first movement route that is a route continuous with at least one of the plurality of work routes and that includes a straight route, in a first non-work area adjacent to the work area in the first direction, in non-work areas surrounding the work area, where the work object is not arranged; and the work vehicle travels on a second movement route that is a single route continuous with the first movement route and that guides the work vehicle to each of the plurality of work routes.

11. An autonomous travel system comprising: a work vehicle; and an operation terminal containing a route generation program for causing one or more processors in an autonomous traveling controller, mounted on the work vehicle, to execute wherein: the work vehicle with the controller, executes and travels on a plurality of work routes straight in a first direction that is a travel direction of the work vehicle, in a work area where a work object is arranged; the work vehicle with the controller, executes and travels on a first movement route that is a route continuous with at least one of the plurality of work routes and that includes a straight route where the work vehicle travels straight, in a first non-work area adjacent to the work area in the first direction, in non-work areas surrounding the work area, where the work object is not arranged; and the work vehicle with the controller, executes and travels on a second movement route that is a single route continuous with the first movement route and that guides the work vehicle to each of the plurality of work routes.
