

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396581
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Mitchell; Tonia

Taco holder

Abstract

A taco holder includes a rigid body and a pusher. The body is shaped like a truncated taco shell, including two sides and a bottom corresponding to those of the taco shell. An inside of the body cradles the taco in a lengthwise direction. The body sides include respective sliding slots penetrating the body and arranged in the lengthwise direction. The pusher is shaped like an angled cross-section of the body and contacts respective edges of the sides of the cradled taco. The pusher includes respective tabs extending through the sliding slots for securing the pusher to the inside of the body while allowing movement of the pusher and contacted taco along the inside of the body in the lengthwise direction. The pusher pushes the taco toward the truncated end in response to applied pressure to the tabs from outside the body in the lengthwise direction.

Inventors:	Mitchell; Tonia (Yonkers, NY)
Applicant:	JOBMOMMA LLC (Yonkers, NY)
Family ID:	1000008778045
Assignee:	JOBMOMMA LLC (Yonkers, NY)
Appl. No.:	17/840171
Filed:	June 14, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220400881 A1	Dec. 22, 2022

Related U.S. Application Data

us-provisional-application US 63212282 20210618

Publication Classification

Int. Cl.: A47G21/00 (20060101); A47F1/12 (20060101); A47F7/00 (20060101); A47B75/00 (20060101); A47G19/30 (20060101)

U.S. Cl.:

CPC A47G21/001 (20130101); A47F1/125 (20130101); A47F7/00 (20130101); A47B75/00 (20130101); A47F7/0071 (20130101); A47G2019/306 (20130101)

Field of Classification Search

CPC: A47G (21/001); A47G (2019/306); A47G (1/125); A47G (2400/10); A47G (19/30); A47G (19/32); A47G (2200/106); A47G (2023/0666); A47G (23/0625); A47G (19/06); A47F (1/126); A47F (1/125); A47F (7/0071); A47F (7/00); A47B (75/00); B65D (85/36); B65D (65/16); B65D (77/2024); B65D (2577/205)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3446416	12/1968	Epstein	229/87.08	A47G 21/001
4270660	12/1980	Putt	211/85.4	A47G 19/30
D263786	12/1981	Kohan	D19/90	N/A
4362247	12/1981	Rueda	211/85.4	A47G 19/30
D278199	12/1984	Richards	D7/411	N/A
D279160	12/1984	Hunt	D7/411	N/A
D282338	12/1985	Putt	D7/504	N/A
4573570	12/1985	Cortopassi	426/396	A47G 19/30
4653645	12/1986	Thomas	426/119	A47G 19/30
D304664	12/1988	Wyant	D7/504	N/A
4938515	12/1989	Fazio	2/21	A41D 13/082
D318984	12/1990	Wickham	D7/601	N/A
D319372	12/1990	Cobb	D7/504	N/A
D334111	12/1992	Yockey	D7/507	N/A
D350671	12/1993	Asner	D7/504	N/A
6273278	12/2000	Enyedy	211/85.4	A47F 7/0071
D467121	12/2001	Zietz	D7/504	N/A
D523289	12/2005	David	D7/601	N/A
D524112	12/2005	Cogley	D7/601	N/A
D524114	12/2005	Dodge	D7/601	N/A
D538596	12/2006	Camp	D7/504	N/A
D563166	12/2007	Woolfolk	D7/553.6	N/A
D668507	12/2011	Williamson	D7/504	N/A
D728894	12/2014	Rogers	D1/122	N/A
D735966	12/2014	Boldt	D1/122	N/A
D770243	12/2015	Esquivel	D7/672	N/A
D857522	12/2018	Blake	D9/710	N/A
D892553	12/2019	Summers	D7/586	N/A

D966815	12/2021	Spruell	D7/504	N/A
D1021536	12/2023	Turner	D7/553.1	N/A
D1025705	12/2023	Gilmore	D7/504	N/A
D1030412	12/2023	Gilmore	D7/504	N/A
D1043245	12/2023	He	D7/504	N/A
D1045505	12/2023	Godsill	D7/368	N/A
2008/0193613	12/2007	Kovich	426/138	A21D 13/42
2016/0316947	12/2015	Shendelman	N/A	A47G 21/001
2018/0213958	12/2017	Shendelman	N/A	A47G 23/0625

Primary Examiner: Barnett; Devin K

Attorney, Agent or Firm: Leason Ellis LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims the benefit of U.S. Provisional Application No. 63/212,282, filed Jun. 18, 2021, which is incorporated by reference herein in its entirety.

FIELD OF THE DISCLOSURE

(1) The present disclosure relates in general to a utensil and in particular to a taco holder that holds a hard-sided taco and facilitates eating the taco without breaking the shell or making a mess.

BACKGROUND OF THE DISCLOSURE

(2) Hard-sided tacos are popular food items. However, they can be messy to consume as the taco shell is subject to breaking earlier than desired and the filling is subject to coming out of the taco shell before consumption.

(3) It is in regard to these and other problems in the art that the present disclosure is directed to provide a technical solution for an effective taco holder that reduces shell breakage and mess of a taco during consumption.

SUMMARY OF THE DISCLOSURE

(4) According to a first aspect of the disclosure, a taco holder for holding a hard-sided taco while eating is provided. The taco holder comprises a rigid body and a pusher. The rigid body has a truncated shape of similar proportions to a taco shell of the hard-sided taco, including two sides and a bottom connecting the two sides and corresponding to sides and bottom of the taco shell, an inside of the body being larger than and configured to cradle the hard-sided taco in a lengthwise direction along a length of the taco, the sides of the body including respective sliding slots penetrating the body and arranged in the lengthwise direction. The pusher has a shape of an angled cross-section of the body and configured to contact respective edges of the sides of the taco shell of the cradled taco, the pusher comprising respective tabs extending through the sliding slots for securing the pusher to the inside of the body while allowing movement of the pusher and contacted taco along the inside of the body in the lengthwise direction. The pusher is configured to push the contacted taco from one end of the body to a truncated end of the body in response to pressure applied to at least one of the tabs from an outside of the body in the lengthwise direction,

(5) In an embodiment consistent with the above, the truncated end of the body comprises a rest to elevate the truncated end of the body with respect to the one end of the body when resting on a flat level surface, the rest being further configured to contact the surface in conjunction with the one end of the body and allow the body and cradled taco to stand up on the surface.

(6) In an embodiment consistent with the above, the rest is further configured to make at least two

points of contact with the surface when the body is standing up.

(7) In an embodiment consistent with the above, the bottom of the body is flat.

(8) In an embodiment consistent with the above, the taco shell has a shape of a symmetrically folded circle, the fold being centered at the bottom of the taco shell and extending in the lengthwise direction when the hard-sided taco is cradled in the taco holder.

(9) In an embodiment consistent with the above, the sliding slots oppose each other in a widthwise direction perpendicular to the lengthwise direction, the pusher has a height in a height direction perpendicular to the lengthwise and widthwise directions, and the cross-section of the body in the lengthwise direction between the sliding slots is uniform below the height of the pusher.

(10) In an embodiment consistent with the above, the pusher is inwardly curved to conform to the edges of the sides of the taco shell of the cradled taco.

(11) In an embodiment consistent with the above, each side of the body extends away from the bottom of the body at an oblique angle to define the angled cross-section of the body and wherein the shape of the pusher conforms to the so-defined oblique angles to define the angled cross-section of the body.

(12) In an embodiment consistent with the above, edges of the pusher adjacent to each side of the rigid body move in response to the applied pressure with a uniform, close spacing to each side, whereby the edges of the sides of the taco shell of the contacted taco are engaged by the pusher throughout its movement in the lengthwise direction.

(13) According to another aspect of the disclosure, a taco holder for holding a hard-sided taco while eating is provided. The taco holder comprises a rigid body and a pusher. The rigid body has a truncated shape of similar proportions to a taco shell of the hard-sided taco, including two sides and a bottom connecting the two sides and corresponding to sides and bottom of the taco shell, an inside of the body being larger than and configured to cradle the hard-sided taco in a lengthwise direction along a length of the taco, the sides and bottom of the body including respective sliding slots arranged in the lengthwise direction. The pusher has a shape of an angled cross-section of the body and configured to contact respective edges of the sides of the taco shell of the cradled taco, the pusher comprising respective tabs extending through the sliding slots for securing the pusher to the inside of the body while allowing movement of the pusher and contacted taco along the inside of the body in the lengthwise direction. The pusher is configured to push the contacted taco from one end of the body to a truncated end of the body in response to pressure applied to at least one of the tabs from an outside of the body in the lengthwise direction,

(14) In an embodiment consistent with the second taco holder described above, the truncated end of the body comprises a rest to elevate the truncated end of the body with respect to the one end of the body when resting on a flat level surface, the rest being further configured to contact the surface in conjunction with the one end of the body and allow the body and cradled taco to stand up on the surface while not allowing the respective tab extending through the respective sliding slot of the bottom of the body to contact the surface.

(15) In an embodiment consistent with the second taco holder described above, the rest is further configured to make at least two points of contact with the surface when the body is standing up on the surface.

(16) In an embodiment consistent with the second taco holder described above, the bottom of the body is flat.

(17) In an embodiment consistent with the second taco holder described above, the taco shell has a shape of a symmetrically folded circle, the fold being centered at the bottom of the taco shell and extending in the lengthwise direction when the hard-sided taco is cradled in the taco holder.

(18) In an embodiment consistent with the second taco holder described above, the respective sliding slots of the sides of the body oppose each other in a widthwise direction perpendicular to the lengthwise direction, the pusher has a height in a height direction perpendicular to the lengthwise and widthwise directions, and the cross-section of the body in the lengthwise direction

between the respective sliding slots of the sides of the body is uniform below the height of the pusher.

(19) In an embodiment consistent with the second taco holder described above, the pusher is inwardly curved to conform to the edges of the sides of the taco shell of the cradled taco.

(20) In an embodiment consistent with the second taco holder described above, each side of the body extends away from the bottom of the body at an oblique angle to define the angled cross-section of the body and wherein the shape of the pusher conforms to the so-defined oblique angles to define the angled cross-section of the body.

(21) In an embodiment consistent with the second taco holder described above, edges of the pusher adjacent to each side of the rigid body move in response to the applied pressure with a uniform, close spacing to each side, whereby the edges of the sides of the taco shell of the contacted taco are engaged by the pusher throughout its movement in the lengthwise direction.

(22) Any combinations of the various embodiments and implementations disclosed herein can be used. These and other aspects and features can be appreciated from the following description of certain embodiments together with the accompanying drawings and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 shows an oblique view of an example taco holder, according to an embodiment.

(2) FIG. 2 shows a top view of the taco holder of FIG. 1.

(3) FIG. 3 shows another oblique view of the taco holder of FIGS. 1-2.

(4) FIG. 4 shows yet another oblique view of the taco holder of FIGS. 1-3.

(5) FIG. 5 shows a rear view of the taco holder of FIGS. 1-4.

(6) FIG. 6 shows a side view of the taco holder of FIGS. 1-5.

(7) FIG. 7 shows a side view of an example taco holder, according to another embodiment.

(8) FIG. 8 shows an oblique view of the taco holder of FIG. 7.

(9) FIG. 9 shows an elevated front view of the taco holder of FIGS. 7-8.

(10) FIG. 10 shows an oblique view of the taco holder of FIGS. 7-9 cradling a hard-shell taco.

(11) It is noted that the drawings are illustrative and not necessarily to scale, and that the same or similar features have the same or similar reference numerals throughout.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS OF THE DISCLOSURE

(12) In example embodiments, a taco holder is provided. The taco holder holds (for example, cradles) a hard-sided taco while containing the filling and protecting the taco shell from early breakage. In addition, the taco holder advances the taco from one end (a back end or rear end) of the taco holder to the other end (a front end or truncated end) to permit eating of the taco with little mess or breakage. In some embodiments, the taco holder has an elevated rest at the front end to facilitate standing the taco holder (and cradled taco) upright on a flat level surface with the front end being higher than the back end. The taco holder includes a movable pusher at the back end that contacts the back end of the taco and moves the taco forward during consumption. In some embodiments, the pusher is tongue-shaped. The pusher helps protect the taco shell from breaking and helps contain the filling (or contents) of the taco within the taco holder. This results in cleaner eating with less breakage of the taco shell.

(13) As mentioned above, while tacos are popular foods, factors such as the type and amount of filling (e.g., meat, lettuce, cheese, tomatoes, to name a few) along with the fragile nature of hard-sided taco shells contribute to challenges in consuming tacos without unintended mess or shell breakage.

(14) Accordingly, in example embodiments of the present disclosure, taco holders that reduce or possibly eliminate such undesired or unintended consequences are provided. Some such taco

holders hold a filled taco while preventing messing the hands or the table when eating the taco. In some embodiments, the taco holder includes a taco-shell-shaped body to contain and hold a filled taco (such as a filled taco of similar size to the body). In some embodiments, the body has truncated (such as flat or straight) edges at one end (that is, a truncated end) in order to allow convenient access to the taco while eating. On the two sides of the body are respective sliding slots (such as extending through or penetrating the body). In some embodiments, the bottom of the body also has a sliding slot.

(15) Each sliding slot provided extends in the lengthwise direction of the body. The taco holder further has a pushing tongue-like piece (a pusher) with corresponding tabs extending into (and possibly through) the sliding slots. The tabs hold the pusher in the same orientation in the body, allowing the pusher to fill the cross-section of the body (or at least the lower cross-section of the body) while the sliding slots enable the pusher to move from one end of the body to the other (truncated) end while pushing a taco cradled in the body out of the holder for consumption by the user. By moving the tabs from outside the body (such as tabs that extend from inside the body to outside the body), the pusher (and corresponding cradled taco) move along the sliding slots from one end of the body to the other end (e.g., the truncated end), allowing the taco to be eaten one bite at a time without mess and without breaking the shell. Further details are now described with reference to FIGS. 1-10.

(16) FIG. 1 shows an oblique view of an example taco holder **100**, according to an embodiment. FIG. 2 shows a top view of the taco holder **100** of FIG. 1. FIG. 3 shows another oblique view of the taco holder **100** of FIGS. 1-2. FIG. 4 shows yet another oblique view of the taco holder **100** of FIGS. 1-3. FIG. 5 shows a rear view of the taco holder **100** of FIGS. 1-4. FIG. 6 shows a side view of the taco holder **100** of FIGS. 1-5.

(17) Referring to FIGS. 1-6, the taco holder **100** is for holding a hard-sided taco while eating. However, the taco holder **100** is not limited to consuming hard-sided tacos. For example, the taco holder **100** can also be used to eat other partially-wrapped food items, such as soft-sided tacos or lettuce wraps. The taco holder **100** includes a rigid body **110** and a tongue-like pusher **160**. The body **110** and pusher **160** can be made of any durable material suitable for contacting tacos and other foods, such as plastic, metal, or wood. The body **110** and the pusher **160** together cradle the hard-sided taco being consumed. This helps confine the filling of the taco to the taco holder **100** while also retarding unintended breakage of the shell. The pusher **160** provides the required force to move the taco from one end of the taco holder **100** to the truncated end at the desired rate of consumption.

(18) The body **110** has a truncated shape of similar proportions to a taco shell of the hard-sided taco being consumed (such as slightly larger, ignoring the truncated end). The body **110** includes two sides **120** and a bottom **130** connecting the two sides **120** and corresponding to sides and bottom of the taco shell. Here, the inside of the body **110** is larger than the taco, and cradles the taco in a lengthwise direction along a length of the taco. The sides **120** of the body **110** include respective sliding slots **140** penetrating the body **110**. The sides **120** are arranged in the lengthwise direction. In some embodiments, the sides of the body extend away from the bottom at an oblique angle in order to accommodate a filled taco. The oblique angle defines an angled cross-section of the body (see FIG. 4).

(19) The pusher **160** has a shape of an angled cross-section of the body **110**. In some embodiments, the edges of the pusher conform to oblique angles to define the angled cross-section of the body. The pusher **160** contacts respective edges of the sides of the cradled taco. The pusher **160** includes respective tabs **170** extending through the sliding slots **140** for securing the pusher **160** to the inside of the body **110** while allowing movement of the pusher **160** and contacted taco along the inside of the body **110** in the lengthwise direction. The pusher **160** pushes the taco from one end of the body **110** to the truncated end of the body **110** in response to pressure that has been applied to at least one of the tabs **170** from an outside of the body **110** in the lengthwise direction. The tabs **170**

transfer the lengthwise force to the pusher **160**, which in turn moves the taco lengthwise to the truncated end. In some embodiments, the pusher **160** is angled (from vertical) to better apply force to the edges of the taco, which helps better cradle the taco (resulting in less mess) and prevent unintended breakage of the entire taco shell during eating. In some embodiments, edges of the pusher **160** that are adjacent to each side of the body **110** advance between the sides of the body toward the truncated end with a uniform, close spacing to each side **120**, whereby edges of the taco shell are engaged by the pusher throughout its movement in the lengthwise direction.

(20) In some embodiments, the truncated end of the body **110** includes a rest to elevate the truncated end of the body **110** with respect to the one end of the body **110** when resting on a flat level surface (such as a table or tray). The rest contacts the surface in conjunction with the one end of the body **110** (such as by three points of contact) and allows the body **110** (and cradled taco) to stand up on the surface when the taco holder **100** is not being handled by a user. The taco holder **100** can still hold a taco while in this standing position, which allows the user to take a break from eating the taco without having to hold onto the taco. In some such embodiments, the rest makes at least two points of contact with the surface when the body **110** is standing up (while the other end of the taco holder **100** provides at least one point of contact with the table or other surface).

(21) In some embodiments, the bottom **130** of the body **110** is flat. This allows the taco holder **100** to more easily stand up, even without a rest. It also allows better cradling of flat-bottomed taco shells. In some embodiments, the taco shell (and by extension, the body **110** of the taco holder **100**) has a shape of a symmetrically folded circle. The fold is centered at the bottom of the taco shell and extends in the lengthwise direction when the taco is cradled in the taco holder **100**.

(22) In some embodiments, the sliding slots **140** oppose each other in a widthwise direction perpendicular to the lengthwise direction. In addition, the pusher **160** has a height in a height direction perpendicular to the lengthwise and widthwise directions. Further, the cross-section of the body **110** in the lengthwise direction (between the sliding slots **140**) is uniform below the height of the pusher **160**. In some embodiments, the pusher **160** is inwardly curved to conform to the edges of the sides of the taco shell. This allows for still better contact with the taco and even further reduced likelihood of unintended shell breakage.

(23) FIG. 7 shows a side view of an example taco holder **200**, according to another embodiment. FIG. 8 shows an oblique view of the taco holder **200** of FIG. 7. FIG. 9 shows an elevated front view of the taco holder **200** of FIGS. 7-8. FIG. 10 shows an oblique view of the taco holder **200** of FIGS. 7-9 cradling a hard-shell taco **290**.

(24) Referring to FIGS. 7-10, the taco holder **200** is for holding a hard-sided taco **290** while eating. The taco holder **200** includes a rigid body **210** and a pusher **260**. The body **210** has a truncated shape of similar proportions to a taco shell of the hard-sided taco **290**, including two sides **220** and a bottom **230** connecting the two sides **220** and corresponding to sides and bottom of the taco shell. The inside of the body **210** is larger than the taco **290** and cradles the taco **290** in a lengthwise direction along a length of the taco **290**. The sides **220** and bottom **230** of the body **210** including respective sliding slots **240** arranged in the lengthwise direction.

(25) The pusher **260** has a shape of an angled cross-section of the body **210**, optionally the same as described in connection with the first embodiment. The pusher **260** contacts respective edges of the sides of the cradled taco **290**. The pusher **260** includes respective tabs **270** extending through the sliding slots **240** for securing the pusher **260** to the inside of the body **210** while allowing movement of the pusher **260** and contacted taco **290** along the inside of the body **210** in the lengthwise direction. The pusher **260** pushes the taco **290** from one end of the body **210** to a truncated end of the body **210** by applying pressure to at least one of the tabs **270** from an outside of the body **210** in the lengthwise direction,

(26) In some embodiments, the truncated end of the body **210** includes a rest **250** to elevate the truncated end of the body **210** with respect to the one end of the body **210** when resting on a flat level surface. The rest **250** contacts the surface in conjunction with the one end of the body and

allows the body **210** (and cradled taco **290**, see FIG. **10**) to stand up on the surface while not allowing the respective tab **240** (bottom tab) extending through the respective sliding slot **240** of the bottom **230** of the body **210** to contact the surface.

(27) In some embodiments, the rest **250** makes at least two points of contact with the surface when the body **210** is standing up on the surface. In some embodiments, the bottom **230** of the body **210** is flat. In some embodiments, the taco shell has a shape of a symmetrically folded circle. The fold is centered at the bottom of the taco shell and extends in the lengthwise direction when the taco **290** is cradled in the taco holder **200**.

(28) In some embodiments, the respective sliding slots **240** of the sides **220** of the body **210** oppose each other in a widthwise direction perpendicular to the lengthwise direction. The pusher **260** has a height in a height direction perpendicular to the lengthwise and widthwise directions. The cross-section of the body **210** in the lengthwise direction between the respective sliding slots **240** of the sides **220** of the body **210** is uniform at least below the height of the pusher **260**. In some embodiments, the pusher **260** is inwardly curved to conform to the edges of the sides of the taco shell.

(29) In summary, in example embodiments, a taco holder is constructed to contain and hold a filled taco for convenience and cleanness in eating. The taco holder includes a taco shell shaped body to contain and hold a filled taco. The shell has a flat (or truncated) edge at one end in order to allow a taco eater to eat the taco conveniently. On the two sides of the shell body are constructed two sliding slots. In each of the slots is disposed with a sliding bar that is connected with a tongue-like piece. When the shell body holds a filled taco inside, by moving the sliding bar, the tongue-like piece pushes the filled taco out of the taco holder for the taco eater to eat one bite at a time.

(30) The subject matter described above is provided by way of illustration only and should not be construed as limiting. Various modifications and changes can be made to the subject matter described herein without following the example embodiments and applications illustrated and described, and without departing from the true spirit and scope of the invention encompassed by the present disclosure, which is defined by the set of recitations in the following claims and by structures and functions or steps which are equivalent to these recitations.

Claims

1. A taco holder for holding a hard-sided taco while eating, the taco holder comprising: a rigid body having a truncated shape of similar proportions to a taco shell of the hard-sided taco, including two sides and a bottom connecting the two sides and corresponding to sides and bottom of the taco shell, an inside of the body being larger than and configured to cradle the hard-sided taco in a lengthwise direction along a length of the taco, the sides of the body including respective sliding slots penetrating the body and arranged in the lengthwise direction; and a pusher having a shape of an angled cross-section of the body and configured to contact respective edges of the sides of the taco shell of the cradled taco, the pusher comprising respective tabs extending through the sliding slots for securing the pusher to the inside of the body while allowing movement of the pusher and contacted taco along the inside of the body in the lengthwise direction, wherein the pusher is configured to push the contacted taco from one end of the body to a truncated end of the body in response to pressure applied to at least one of the tabs from an outside of the body in the lengthwise direction.

2. The taco holder of claim 1, wherein the truncated end of the body comprises a rest to elevate the truncated end of the body with respect to the one end of the body when resting on a flat level surface, the rest being further configured to contact the surface in conjunction with the one end of the body and allow the body and cradled taco to stand up on the surface.

3. The taco holder of claim 2, wherein the rest is further configured to make at least two points of contact with the surface when the body is standing up.

4. The taco holder of claim 1, wherein the bottom of the body is flat.
5. The taco holder of claim 1, wherein the taco shell has a shape of a symmetrically folded circle, the fold being centered at the bottom of the taco shell and extending in the lengthwise direction when the hard-sided taco is cradled in the taco holder.
6. The taco holder of claim 1, wherein the sliding slots oppose each other in a widthwise direction perpendicular to the lengthwise direction, the pusher has a height in a height direction perpendicular to the lengthwise and widthwise directions, and the cross-section of the body in the lengthwise direction between the sliding slots is uniform below the height of the pusher.
7. The taco holder of claim 1, wherein the pusher is inwardly curved to conform to the edges of the sides of the taco shell of the cradled taco.
8. The taco holder of claim 1, wherein each side of the body extends away from the bottom of the body at an oblique angle to define the angled cross-section of the body and wherein the shape of the pusher conforms to the so-defined oblique angles to define the angled cross-section of the body.
9. The taco holder of claim 1, wherein edges of the pusher adjacent to each side of the rigid body move in response to the applied pressure with a uniform, close spacing to each side, whereby the edges of the sides of the taco shell of the contacted taco are engaged by the pusher throughout its movement in the lengthwise direction.
10. A taco holder for holding a hard-sided taco while eating, the taco holder comprising: a rigid body having a truncated shape of similar proportions to a taco shell of the hard-sided taco, including two sides and a bottom connecting the two sides and corresponding to sides and bottom of the taco shell, an inside of the body being larger than and configured to cradle the hard-sided taco in a lengthwise direction along a length of the taco, the sides and bottom of the body including respective sliding slots arranged in the lengthwise direction; and a pusher having a shape of an angled cross-section of the body and configured to contact respective edges of the sides of the taco shell of the cradled taco, the pusher comprising respective tabs extending through the sliding slots for securing the pusher to the inside of the body while allowing movement of the pusher and contacted taco along the inside of the body in the lengthwise direction, wherein the pusher is configured to push the contacted taco from one end of the body to a truncated end of the body in response to pressure applied to at least one of the tabs from an outside of the body in the lengthwise direction.
11. The taco holder of claim 10, wherein the truncated end of the body comprises a rest to elevate the truncated end of the body with respect to the one end of the body when resting on a flat level surface, the rest being further configured to contact the surface in conjunction with the one end of the body and allow the body and cradled taco to stand up on the surface while not allowing the respective tab extending through the respective sliding slot of the bottom of the body to contact the surface.
12. The taco holder of claim 11, wherein the rest is further configured to make at least two points of contact with the surface when the body is standing up on the surface.
13. The taco holder of claim 10, wherein the bottom of the body is flat.
14. The taco holder of claim 10, wherein the taco shell has a shape of a symmetrically folded circle, the fold being centered at the bottom of the taco shell and extending in the lengthwise direction when the hard-sided taco is cradled in the taco holder.
15. The taco holder of claim 10, wherein the respective sliding slots of the sides of the body oppose each other in a widthwise direction perpendicular to the lengthwise direction, the pusher has a height in a height direction perpendicular to the lengthwise and widthwise directions, and the cross-section of the body in the lengthwise direction between the respective sliding slots of the sides of the body is uniform below the height of the pusher.
16. The taco holder of claim 10, wherein the pusher is inwardly curved to conform to the edges of the sides of the taco shell of the cradled taco.
17. The taco holder of claim 10, wherein each side of the body extends away from the bottom of

the body at an oblique angle to define the angled cross-section of the body and wherein the shape of the pusher conforms to the so-defined oblique angles to define the angled cross-section of the body.

18. The taco holder of claim 10, wherein edges of the pusher adjacent to each side of the rigid body move in response to the applied pressure with a uniform, close spacing to each side, whereby the edges of the sides of the taco shell of the contacted taco are engaged by the pusher throughout its movement in the lengthwise direction.
