

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396730
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Greenwood; Megan et al.

Braided implant with detachment mechanism

Abstract

An occlusive device can include a segment including an open end and a proximal end. The occlusive device can include a push wire that is positioned proximal of the proximal end. The occlusive device can include a detachment feature that is attached to the push wire via a detachment groove. The occlusive device can include a sleeve surrounding the push wire. In a non-deployed configuration, the sleeve can surround the detachment feature and prevent release of the proximal end of the segment from the push wire. In a deployed configuration, the proximal end can be flush with a proximal end of the spherical cavity.

Inventors: Greenwood; Megan (Raynham, MA), Sloss; Scott (Raynham, MA), Sharma; Tushar (Raynham, MA), Cohn; William (Raynham, MA), Garbin; Nicolo (Raynham, MA)

Applicant: DePuy Synthes Products, Inc. (Raynham, MA)

Family ID: 1000008778160

Assignee: DEPUY SYNTHES PRODUCTS, INC. (Raynham, MA)

Appl. No.: 17/954458

Filed: September 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240099720 A1	Mar. 28, 2024

Publication Classification

Int. Cl.: A61B17/12 (20060101); A61B17/00 (20060101)

U.S. Cl.:

CPC **A61B17/12113** (20130101); **A61B17/12031** (20130101); **A61B17/12168** (20130101);
A61B2017/00915 (20130101); A61B2017/12054 (20130101)

Field of Classification Search

CPC: A61B (17/12113); A61B (17/12031); A61B (17/12168); A61B (17/17172); A61B
(2017/00915); A61B (2017/12054); A61B (2017/00526)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3429408	12/1968	Maker et al.	N/A	N/A
5108407	12/1991	Geremia et al.	N/A	N/A
5122136	12/1991	Guglielmi et al.	N/A	N/A
5217484	12/1992	Marks	N/A	N/A
5250071	12/1992	Palermo	606/198	G02B 26/0825
5263964	12/1992	Purdy	N/A	N/A
5334210	12/1993	Gianturco	606/151	A61B 17/12022
5350397	12/1993	Palermo et al.	N/A	N/A
5382259	12/1994	Phelps et al.	N/A	N/A
5417708	12/1994	Hall	128/899	A61B 17/1215
5484409	12/1995	Atkinson et al.	N/A	N/A
5569221	12/1995	Houser et al.	N/A	N/A
5582619	12/1995	Ken	N/A	N/A
5624449	12/1996	Pham	606/1	A61B 17/12022
5853418	12/1997	Ken	606/198	A61B 17/12113
5899935	12/1998	Ding	N/A	N/A
5925059	12/1998	Palermo et al.	N/A	N/A
6113622	12/1999	Tieshima	N/A	N/A
6203547	12/2000	Nguyen et al.	N/A	N/A
6334864	12/2001	Amplatz	606/200	A61B 17/12172
6368338	12/2001	Konya	606/200	A61B 17/12109
6391037	12/2001	Greenhalgh	N/A	N/A
6454780	12/2001	Wallace	N/A	N/A
6506204	12/2002	Mazzocchi	N/A	N/A
6561988	12/2002	Turturro et al.	N/A	N/A
6636758	12/2002	Sanchez	600/585	A61B 90/39
7367987	12/2007	Balgobin et al.	N/A	N/A
7371251	12/2007	Mitelberg et al.	N/A	N/A
7371252	12/2007	Balgobin et al.	N/A	N/A
7377932	12/2007	Mitelberg et al.	N/A	N/A

7708754	12/2009	Balgobin et al.	N/A	N/A
7708755	12/2009	Davis, III et al.	N/A	N/A
7722636	12/2009	Farnan	606/200	A61B 17/12022
7799052	12/2009	Balgobin et al.	N/A	N/A
7811305	12/2009	Balgobin et al.	N/A	N/A
7819891	12/2009	Balgobin et al.	N/A	N/A
7819892	12/2009	Balgobin et al.	N/A	N/A
7901444	12/2010	Slazas	N/A	N/A
7942894	12/2010	West	N/A	N/A
7985238	12/2010	Balgobin	606/191	A61M 29/00
8062325	12/2010	Mitelberg et al.	N/A	N/A
8333796	12/2011	Tompkins	623/1.11	A61B 17/12113
8449591	12/2012	Litzenberg et al.	N/A	N/A
8795316	12/2013	Balgobin	606/200	A61B 17/1214
8974488	12/2014	Tan et al.	N/A	N/A
9155540	12/2014	Lorenzo	N/A	A61B 17/1214
9232992	12/2015	Heidner	N/A	N/A
9314326	12/2015	Wallace et al.	N/A	N/A
9486223	12/2015	Que	N/A	A61B 17/12145
9532792	12/2016	Galdonik et al.	N/A	N/A
9532873	12/2016	Kelley	N/A	N/A
9533344	12/2016	Monetti et al.	N/A	N/A
9539011	12/2016	Chen et al.	N/A	N/A
9539022	12/2016	Bowman	N/A	N/A
9539122	12/2016	Burke et al.	N/A	N/A
9539382	12/2016	Nelson	N/A	N/A
9549830	12/2016	Bruszewski et al.	N/A	N/A
9554805	12/2016	Tompkins et al.	N/A	N/A
9561125	12/2016	Bowman et al.	N/A	N/A
9572982	12/2016	Burnes et al.	N/A	N/A
9579484	12/2016	Barnell	N/A	N/A
9585642	12/2016	Dinsmoor et al.	N/A	N/A
9615832	12/2016	Bose et al.	N/A	N/A
9615951	12/2016	Bennett et al.	N/A	N/A
9622753	12/2016	Cox	N/A	N/A
9636115	12/2016	Henry et al.	N/A	N/A
9636439	12/2016	Chu et al.	N/A	N/A
9642675	12/2016	Werneth et al.	N/A	N/A
9655633	12/2016	Leynov et al.	N/A	N/A
9655645	12/2016	Staunton	N/A	N/A
9655989	12/2016	Cruise et al.	N/A	N/A
9662120	12/2016	Lagodzki et al.	N/A	N/A
9662129	12/2016	Galdonik et al.	N/A	N/A
9662238	12/2016	Dwork et al.	N/A	N/A
9662425	12/2016	Lilja et al.	N/A	N/A

9668898	12/2016	Wong	N/A	N/A
9675477	12/2016	Thompson	N/A	N/A
9675782	12/2016	Connolly	N/A	N/A
9676022	12/2016	Ensign et al.	N/A	N/A
9692557	12/2016	Murphy	N/A	N/A
9693852	12/2016	Lam	N/A	A61F 2/0105
9700262	12/2016	Janik et al.	N/A	N/A
9700399	12/2016	Acosta-Acevedo	N/A	N/A
9717421	12/2016	Griswold et al.	N/A	N/A
9717500	12/2016	Tieu et al.	N/A	N/A
9717502	12/2016	Teoh et al.	N/A	N/A
9724103	12/2016	Cruise et al.	N/A	N/A
9724526	12/2016	Strother et al.	N/A	N/A
9750565	12/2016	Bloom et al.	N/A	N/A
9757260	12/2016	Greenan	N/A	N/A
9764111	12/2016	Gulachenski	N/A	N/A
9770251	12/2016	Bowman et al.	N/A	N/A
9770577	12/2016	Li	N/A	N/A
9775621	12/2016	Tompkins et al.	N/A	N/A
9775706	12/2016	Peterson	N/A	A61F 2/966
9775732	12/2016	Khenansho	N/A	N/A
9788800	12/2016	Mayoras, Jr.	N/A	N/A
9795391	12/2016	Saatchi et al.	N/A	N/A
9801980	12/2016	Karino et al.	N/A	N/A
9808599	12/2016	Bowman et al.	N/A	N/A
9833252	12/2016	Sepetka et al.	N/A	N/A
9833604	12/2016	Lam et al.	N/A	N/A
9833625	12/2016	Waldhauser et al.	N/A	N/A
9907555	12/2017	Buiser	N/A	A61B 17/12022
9918718	12/2017	Lorenzo	N/A	N/A
10034670	12/2017	Elgård et al.	N/A	N/A
10282851	12/2018	Gorochow	N/A	N/A
10285710	12/2018	Lorenzo et al.	N/A	N/A
10517604	12/2018	Bowman et al.	N/A	N/A
10653425	12/2019	Gorochow et al.	N/A	N/A
10806402	12/2019	Cadieu et al.	N/A	N/A
10806461	12/2019	Lorenzo	N/A	N/A
10806462	12/2019	Lorenzo	N/A	N/A
10888331	12/2020	Pederson et al.	N/A	N/A
11051928	12/2020	Casey et al.	N/A	N/A
2001/0049519	12/2000	Holman et al.	N/A	N/A
2001/0056281	12/2000	Wallace	606/108	A61B 17/1214
2002/0072705	12/2001	Vrba et al.	N/A	N/A
2002/0165569	12/2001	Ramzipoor et al.	N/A	N/A
2003/0216757	12/2002	Gerberding	606/151	A61B 17/12172
2004/0002731	12/2003	Aganon et al.	N/A	N/A
2004/0034363	12/2003	Wilson et al.	N/A	N/A

2004/0059367	12/2003	Davis et al.	N/A	N/A
2004/0087964	12/2003	Diaz et al.	N/A	N/A
2005/0149108	12/2004	Cox	606/200	A61B 17/12022
2006/0025802	12/2005	Sowers	N/A	N/A
2006/0064151	12/2005	Guterman	N/A	N/A
2006/0111771	12/2005	Ton	623/1.15	A61F 2/962
2006/0116711	12/2005	Elliott et al.	N/A	N/A
2006/0135021	12/2005	Calhoun et al.	N/A	N/A
2006/0155303	12/2005	Konya	606/108	A61B 17/12122
2006/0276824	12/2005	Mitelberg et al.	N/A	N/A
2006/0276825	12/2005	Mitelberg et al.	N/A	N/A
2006/0276826	12/2005	Mitelberg et al.	N/A	N/A
2006/0276827	12/2005	Mitelberg et al.	N/A	N/A
2006/0276830	12/2005	Balgobin et al.	N/A	N/A
2006/0276833	12/2005	Balgobin et al.	N/A	N/A
2007/0010850	12/2006	Balgobin et al.	N/A	N/A
2007/0083132	12/2006	Sharrow	N/A	N/A
2007/0083226	12/2006	Buiser	606/200	A61B 17/12113
2007/0179520	12/2006	West	606/200	A61B 17/1214
2007/0203519	12/2006	Lorenzo	606/200	A61B 17/1214
2007/0233168	12/2006	Davis et al.	N/A	N/A
2007/0270903	12/2006	Davis, III et al.	N/A	N/A
2007/0270930	12/2006	Schenck	N/A	N/A
2007/0299422	12/2006	Inganas	606/191	A61B 17/1214
2008/0027561	12/2007	Mitelberg et al.	N/A	N/A
2008/0035160	12/2007	Woodson et al.	N/A	N/A
2008/0045997	12/2007	Balgobin et al.	N/A	N/A
2008/0082113	12/2007	Bishop et al.	N/A	N/A
2008/0097462	12/2007	Mitelberg et al.	N/A	N/A
2008/0119887	12/2007	Que et al.	N/A	N/A
2008/0221654	12/2007	Buiser	606/191	A61B 17/12145
2008/0281350	12/2007	Sepetka	N/A	N/A
2008/0300616	12/2007	Que et al.	N/A	N/A
2008/0306503	12/2007	Que et al.	N/A	N/A
2009/0036877	12/2008	Nardone	606/1	A61B 17/12022
2009/0062726	12/2008	Ford et al.	N/A	N/A
2009/0099592	12/2008	Buiser et al.	N/A	N/A
2009/0177261	12/2008	Teoh	623/1.11	A61B 17/12022
2009/0312748	12/2008	Johnson et al.	N/A	N/A
2010/0094395	12/2009	Kellett	623/1.11	A61B 17/1215

2010/0114017	12/2009	Lenker et al.	N/A	N/A
2010/0160944	12/2009	Teoh et al.	N/A	N/A
2010/0324649	12/2009	Mattsson	N/A	N/A
2011/0092997	12/2010	Kang	N/A	N/A
2011/0295303	12/2010	Freudenthal	N/A	N/A
2012/0035707	12/2011	Mitelberg et al.	N/A	N/A
2012/0041472	12/2011	Tan et al.	N/A	N/A
2012/0283768	12/2011	Cox et al.	N/A	N/A
2013/0066413	12/2012	Jin et al.	N/A	N/A
2013/0138136	12/2012	Beckham	29/520	A61B 17/12136
2013/0338701	12/2012	Wilson et al.	N/A	N/A
2014/0058435	12/2013	Jones	606/200	A61B 17/1214
2014/0135812	12/2013	Divino et al.	N/A	N/A
2014/0200607	12/2013	Sepetka et al.	N/A	N/A
2014/0207175	12/2013	Aggerholm	N/A	N/A
2014/0277085	12/2013	Mirigian et al.	N/A	N/A
2014/0277092	12/2013	Teoh et al.	N/A	N/A
2014/0277093	12/2013	Guo et al.	N/A	N/A
2015/0112378	12/2014	Torp	606/1	A61B 17/1214
2015/0182227	12/2014	Le et al.	N/A	N/A
2015/0230802	12/2014	Lagodzki et al.	N/A	N/A
2015/0335333	12/2014	Jones et al.	N/A	N/A
2016/0022275	12/2015	Garza	N/A	N/A
2016/0157869	12/2015	Elgård et al.	N/A	N/A
2016/0228125	12/2015	Pederson, Jr. et al.	N/A	N/A
2016/0310304	12/2015	Mialhe	N/A	N/A
2016/0346508	12/2015	Williams et al.	N/A	N/A
2017/0007264	12/2016	Cruise et al.	N/A	N/A
2017/0007265	12/2016	Guo et al.	N/A	N/A
2017/0020670	12/2016	Murray et al.	N/A	N/A
2017/0020700	12/2016	Bienvenu et al.	N/A	N/A
2017/0027640	12/2016	Kunis et al.	N/A	N/A
2017/0027692	12/2016	Bonhoeffer et al.	N/A	N/A
2017/0027725	12/2016	Argentine	N/A	N/A
2017/0035436	12/2016	Morita	N/A	N/A
2017/0035567	12/2016	Duffy	N/A	N/A
2017/0042548	12/2016	Lam	N/A	N/A
2017/0049596	12/2016	Schabert	N/A	N/A
2017/0071737	12/2016	Kelley	N/A	N/A
2017/0072452	12/2016	Monetti et al.	N/A	N/A
2017/0079671	12/2016	Morero et al.	N/A	N/A
2017/0079680	12/2016	Bowman	N/A	N/A
2017/0079766	12/2016	Wang et al.	N/A	N/A
2017/0079767	12/2016	Leon-Yip	N/A	N/A
2017/0079812	12/2016	Lam et al.	N/A	N/A
2017/0079817	12/2016	Sepetka et al.	N/A	N/A
2017/0079819	12/2016	Pung	N/A	A61F 2/82

2017/0079820	12/2016	Lam	N/A	A61F 2/966
2017/0086851	12/2016	Wallace et al.	N/A	N/A
2017/0086996	12/2016	Peterson et al.	N/A	N/A
2017/0095259	12/2016	Tompkins et al.	N/A	N/A
2017/0100126	12/2016	Bowman et al.	N/A	N/A
2017/0100141	12/2016	Morero et al.	N/A	N/A
2017/0100143	12/2016	Granfield	N/A	N/A
2017/0100183	12/2016	Iaizzo et al.	N/A	N/A
2017/0105739	12/2016	Dias et al.	N/A	N/A
2017/0113023	12/2016	Steingisser et al.	N/A	N/A
2017/0135801	12/2016	Delaney, Jr.	N/A	A61B 17/12122
2017/0147765	12/2016	Mehta	N/A	N/A
2017/0151032	12/2016	Loisel	N/A	N/A
2017/0165062	12/2016	Rothstein	N/A	N/A
2017/0165065	12/2016	Rothstein et al.	N/A	N/A
2017/0165454	12/2016	Tuohy et al.	N/A	N/A
2017/0172581	12/2016	Bose et al.	N/A	N/A
2017/0172766	12/2016	Vong	N/A	A61F 2/885
2017/0172772	12/2016	Khenansho	N/A	N/A
2017/0189033	12/2016	Sepetka et al.	N/A	N/A
2017/0189035	12/2016	Porter	N/A	N/A
2017/0215902	12/2016	Leynov et al.	N/A	N/A
2017/0216484	12/2016	Cruise et al.	N/A	N/A
2017/0224350	12/2016	Shimizu et al.	N/A	N/A
2017/0224355	12/2016	Bowman et al.	N/A	N/A
2017/0224467	12/2016	Piccagli et al.	N/A	N/A
2017/0224511	12/2016	Dwork et al.	N/A	N/A
2017/0224953	12/2016	Tran et al.	N/A	N/A
2017/0231749	12/2016	Perkins et al.	N/A	N/A
2017/0245864	12/2016	Franano et al.	N/A	N/A
2017/0245885	12/2016	Lenker	N/A	N/A
2017/0252064	12/2016	Staunton	N/A	N/A
2017/0258476	12/2016	Hayakawa et al.	N/A	N/A
2017/0265983	12/2016	Lam et al.	N/A	N/A
2017/0281192	12/2016	Tieu et al.	N/A	N/A
2017/0281331	12/2016	Perkins et al.	N/A	N/A
2017/0281344	12/2016	Costello	N/A	N/A
2017/0281909	12/2016	Northrop et al.	N/A	N/A
2017/0281912	12/2016	Melder et al.	N/A	N/A
2017/0290593	12/2016	Cruise et al.	N/A	N/A
2017/0290654	12/2016	Sethna	N/A	N/A
2017/0296324	12/2016	Argentine	N/A	N/A
2017/0296325	12/2016	Marrocco et al.	N/A	N/A
2017/0303939	12/2016	Greenhalgh et al.	N/A	N/A
2017/0303942	12/2016	Greenhalgh et al.	N/A	N/A
2017/0303947	12/2016	Greenhalgh et al.	N/A	N/A
2017/0303948	12/2016	Wallace et al.	N/A	N/A
2017/0304041	12/2016	Argentine	N/A	N/A
2017/0304097	12/2016	Corwin	N/A	A61F 2/07

2017/0304595	12/2016	Nagasrinivasa et al.	N/A	N/A
2017/0312109	12/2016	Le	N/A	N/A
2017/0312484	12/2016	Shipley et al.	N/A	N/A
2017/0316561	12/2016	Helm et al.	N/A	N/A
2017/0319826	12/2016	Bowman et al.	N/A	N/A
2017/0333228	12/2016	Orth et al.	N/A	N/A
2017/0333236	12/2016	Greenan	N/A	N/A
2017/0333678	12/2016	Bowman et al.	N/A	N/A
2017/0340383	12/2016	Bloom et al.	N/A	N/A
2017/0348014	12/2016	Wallace et al.	N/A	N/A
2017/0348514	12/2016	Guyon et al.	N/A	N/A
2018/0028779	12/2017	von Oepen et al.	N/A	N/A
2018/0228493	12/2017	Aguilar	N/A	A61B 17/12113
2018/0250150	12/2017	Majercak et al.	N/A	N/A
2018/0280667	12/2017	Keren	N/A	N/A
2018/0289375	12/2017	Hebert et al.	N/A	N/A
2018/0325706	12/2017	Hebert et al.	N/A	N/A
2019/0192162	12/2018	Lorenzo et al.	N/A	N/A
2019/0255290	12/2018	Snyder et al.	N/A	N/A
2019/0328398	12/2018	Lorenzo	N/A	N/A
2020/0093499	12/2019	Lorenzo	N/A	A61B 17/12172
2020/0229957	12/2019	Bardsley et al.	N/A	N/A
2021/0001082	12/2020	Lorenzo et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1728478	12/2005	EP	N/A
1985244	12/2007	EP	N/A
3092956	12/2015	EP	N/A
3501427	12/2018	EP	N/A
3760139	12/2020	EP	N/A
2006-334408	12/2005	JP	N/A
2012-000464	12/2011	JP	N/A
2012-523943	12/2011	JP	N/A
2013-78584	12/2012	JP	N/A
2013-212372	12/2012	JP	N/A
WO 2012/158152	12/2011	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report for European Application No. 20196478.0, mailed Jan. 25, 2021, 11 Pages. cited by applicant

Extended European Search Report for European Application No. 22184571.2, mailed Dec. 8, 2022, 8 pages. cited by applicant

Extended European Search Report for European Application No. 22184574.6, mailed Dec. 6, 2022, 10 pages. cited by applicant

Background/Summary

FIELD OF INVENTION

(1) The present invention generally relates to medical instruments, and more particularly, to embolic implants detachment mechanisms for aneurysm therapy.

BACKGROUND

(2) Cranial aneurysms can be complicated and difficult to treat due to their proximity to critical brain tissues. Recently, tubular braided implants have been introduced that have the potential to treat an aneurysm or other arterio-venous malformation easily, accurately, and safely in a parent vessel without blocking flow into perforator vessels communicating with the parent vessel. Implant devices for treating aneurysms must be delivered through long, small, tortuous blood vessels and positioning must be controlled precisely to ensure aneurysm filling without causing additional occlusions or clotting in nearby vessels. Accordingly, it is necessary to have a delivery and detachment mechanism providing the connection point between a tubular braided implant and a delivery catheter that has the ability to deliver, position, manipulate, and then release the implant.

SUMMARY

(3) It is an object of the present invention to provide systems, devices, and methods to meet the above-stated needs. Generally, it is an object of the present invention to provide an endovascular implantation system for occluding a spherical cavity. The endovascular implantation system can include an occlusive segment that includes an open end and a proximal end and is configured to occlude a spherical cavity. The endovascular implantation system can include a push wire that is positioned proximal of the proximal end of the occlusive segment. The push wire can include one or more indentations on an outer surface of the push wire approximate a distal end of the push wire. The proximal end of the occlusive segment can include a detachment feature that is shaped to at least partially recess into the one or more indentations of the push wire. The occlusive device can include a sleeve surrounding at least a portion of the push wire. In a non-deployed configuration, the sleeve can at least partially surround the detachment feature and prevent release of the proximal end of the occlusive segment from the push wire. In a deployed configuration, the sleeve can be retracted proximally from the detachment feature to thereby detach the occlusive segment from the push wire.

(4) In some examples, the detachment feature can further include a plurality of wire loops that extend from the proximal end of the segment that are configured to fit into the one or more indentations that are positioned on a distal tip of the push wire.

(5) In some examples, the one or more indentations can include a plurality of laser-etched pockets. Each of the laser-etched pockets can be shaped to fit a corresponding wire loop of the plurality of wire loops.

(6) In some examples, the detachment feature can further include a plurality of balls that extend from the proximal end of the segment. The plurality of balls can be configured to fit into the one or more indentations positioned on distal tip of the push wire.

(7) In some examples, the one or more indentations can include an annular groove circumscribing an outer surface of the push wire.

(8) In some examples, in the deployed configuration, the occlusive segment can expand to occlude the spherical cavity.

(9) In some examples, in the deployed configuration the occlusive segment can extend in a distal

direction from the proximal end and can include two inversions that separate three sections of the segment which at least partially overlap each other such that the proximal end is affixed to an innermost section of the three sections and a middle section of the three sections can extend between the two inversions and is positioned within an outermost section and around the innermost section.

(10) In some examples, the endovascular implantation system can include a microcatheter that is configured to deliver the occlusive segment, the push wire, and the sleeve to the spherical cavity with the occlusive device in the non-deployed configuration. The microcatheter can include a lumen, and the segment can have a diameter in the non-deployed configuration sized to fit within the lumen of the microcatheter.

(11) In some examples, the endovascular implantation system can include a band that is approximate the proximal end of the segment. The band can include radiopaque material.

(12) In some examples, in the deployed configuration, the open end of the occlusive segment can be positioned approximate a distal wall of the spherical cavity and the band can be suspended within the spherical cavity.

(13) In some examples, the spherical cavity can be an aneurysm sac.

(14) In some examples, the occlusive segment can include a tubular braid.

(15) In another aspect, a method for constructing an endovascular treatment system is disclosed. The method can include providing an occlusive segment that includes an open end and a proximal end. The method can include shaping the occlusive segment to a predetermined shape to which the segment is capable of self-expanding. Shaping the predetermined shape can include inverting the segment to form a proximal inversion that is folded towards the distal direction to thereby define an outermost section of the segment. Shaping the predetermined shape can include inverting the segment to form a distal inversion folded toward the proximal direction to thereby define a middle section between the proximal and distal inversion of the segment that is at least partially surrounded by the outermost section and defines an innermost section between the distal inversion and the proximal end that is at least partially surrounded by the middle section. The method can include providing a detachment feature that is affixed to the proximal end of the segment. The method can include providing a push wire having one or more indentations in a distal end of the push wire. The method can include recessing at least a portion of the detachment feature into the one or more indentations of the push wire. The method can include positioning a sleeve to at least partially surround the push wire and the detachment feature.

(16) In some examples, the sleeve is effective to retain the proximal end of the segment attached to the push wire.

(17) In some examples, the detachment feature can further include a plurality of wire loops that extend from the proximal end that can be configured to fit into the one or more indentations positioned on the distal end of the push wire.

(18) In some examples, the one or more indentations can include a plurality of laser-etched pockets. Each of the laser-etched pockets can be shaped to fit a corresponding wire loop of the plurality of wire loops.

(19) In some examples, the detachment feature can further include a plurality of balls that extend from the proximal end of the segment. The plurality of balls can be configured to fit into the one or more indentations that are positioned on the distal end of the push wire.

(20) In some examples, in the deployed configuration, the proximal end of the segment can be flush with a proximal end of the spherical cavity. In some examples, the spherical cavity can be an aneurysm sac.

(21) In another aspect, a method of occluding a spherical cavity is disclosed. The method can include providing an expandable segment that includes an open end and a proximal end in a non-deployed configuration. The method can include affixing the proximal end to a push wire via a detachment feature. The method can include positioning a sleeve over at least a portion of the push

wire and at least a portion of the detachment feature to prevent detachment of the proximal end of the expandable segment from the distal end of the push wire. The method can include delivering the expandable segment, push wire, and sleeve to a treatment site via a microcatheter. The method can include sliding the sleeve proximally, thereby releasing the proximal end from the distal end of the push wire and causing the expandable segment to expand to a deployed configuration to occlude the spherical cavity.

(22) In some examples, the detachment feature can further include a plurality of wire loops that extend from the proximal end that can be configured to fit into the one or more indentations positioned on the distal end of the push wire.

(23) In some examples, the one or more indentations can include a plurality of laser-etched pockets. Each of the laser-etched pockets can be shaped to fit a corresponding wire loop of the plurality of wire loops.

(24) In some examples, the detachment feature can further include a plurality of balls that extend from the proximal end of the segment. The plurality of balls can be configured to fit into the one or more indentations that are positioned on the distal end of the push wire.

(25) In some examples, the one or more indentations can include an annular groove circumscribing an outer surface of the push wire.

(26) In some examples, the proximal end is flush with a proximal end of the spherical cavity. In some examples, the spherical cavity can be an aneurysm.

(27) In some examples, in the deployed configuration, the expandable segment can include two inversions that separate three sections which at least partially overlap each other such that the proximal end is affixed to an innermost section of the three sections, and a middle section of the three sections extends between the two inversion and is positioned within an outermost section and around the innermost section.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and further aspects of this invention are further discussed with reference to the following description in conjunction with the accompanying drawings, in which like numerals indicate like structural elements and features in various figures. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating principles of the invention. The figures depict one or more implementations of the inventive devices, by way of example only, not by way of limitation.

(2) FIGS. 1A through 1G are illustrations of an example endovascular treatment system including an implant having a tubular braid that expands to a predetermined shape as the tubular braid exits a microcatheter according to aspects of the present invention;

(3) FIG. 2A is an illustration of an example endovascular treatment system including an implant with a detachment feature that includes balls in a non-deployed configuration, according to aspects of the present invention;

(4) FIG. 2B is cross-sectional illustration of the system as indicated in FIG. 2A according to aspects of the present invention;

(5) FIG. 2C is an illustration of the system of FIG. 2A with the detachment feature in a deployed configuration, according to aspects of the present invention;

(6) FIG. 3A is an illustration of another example endovascular treatment system including an implant with a detachment feature including loops and a push wire including laser-etched pockets in a non-deployed configuration, according to aspects of the present invention;

(7) FIG. 3B is a cross-sectional illustration of the system of FIG. 3A according to aspects of the present invention;

- (8) FIG. 3C is an illustration of the system of FIG. 3A with the detachment feature in a deployed configuration, according to aspects of the present invention;
- (9) FIGS. 4A and 4B are illustrations of measurements of an example spherical cavity and implant according to aspects of the present invention;
- (10) FIG. 5 is a flowchart of a method for constructing an endovascular treatment system, according to aspects of the present invention; and
- (11) FIG. 6 is a flowchart of a method for occluding a spherical cavity, according to aspects of the present invention.

DETAILED DESCRIPTION

- (12) As used herein, the terms “about” or “approximately” for any numerical values or ranges indicate a suitable dimensional tolerance that allows the part or collection of components to function for its intended purpose as described herein. More specifically, “about” or “approximately” may refer to the range of values $\pm 20\%$ of the recited value, e.g. “about 90%” may refer to the range of values from 71% to 99%.
- (13) When used herein, the terms “tubular” and “tube” are to be construed broadly and are not limited to a structure that is a right cylinder or strictly circumferential in cross-section or of a uniform cross-section throughout its length. For example, the tubular structure or system is generally illustrated as a substantially right cylindrical structure. However, the tubular system may have a tapered or curved outer surface without departing from the scope of the present invention.
- (14) Examples presented herein generally include a braided implant that can secure within an aneurysm sac and occlude a majority of the aneurysm's neck. The implant can include a tubular braid that can be set into a predetermined shape, compressed for delivery through a microcatheter, and implanted in at least one implanted position that is based on the predetermined shape and the geometry of the aneurysm in which the braid is implanted. When compressed, the implant can be sufficiently short to mitigate friction forces produced when the implant is delivered unsheathed through the microcatheter allowing for a more simplistic delivery system compared to some other known braided embolic implant delivery systems. The implant can be as described in U.S. Pat. No. 10,653,425, the entirety of which is incorporated herein by reference as if included in full.
- (15) FIGS. 1A through 1G are illustrations of an example implant **100** having a segment **110** expanding to a deployed configuration as the segment **110** exits a microcatheter **600**. The implant **100** can have a deployed shape similar to as illustrated below in reference to FIGS. 1G, 2C and 4B. As illustrated in FIG. 1A, the segment **110** can be shaped to a non-deployed shape that is extended to a single layer of tubular braid having a compressed circumference/diameter sized to be delivered through the microcatheter **600** and a length L. The illustrated implant **100** can have a length L of between about 22 mm and about 25 mm. As will be appreciated and understood by a person skilled in the art, the length L of a specific segment **110** can be tailored based on the size and shape of the aneurysm being treated.
- (16) During delivery through the microcatheter **600**, the detachment feature **164** can be attached to a delivery system at a proximal end **112** of the implant **100**, and the open end **114** can define the distal end of the implant **100**. The delivery system is drawn simplistically in FIGS. 1A through 1C for the sake of simplicity of illustration, and example delivery system configurations are shown in greater detail in FIGS. 2A through 2C and 3A through 3C. Collapsing the segment **110** to a single layer tube can result in a segment **110** that has a sufficiently small diameter and a sufficiently short length L to mitigate effects of friction force on the segment **110** when it is delivered through lumen **608** of the microcatheter **600**, allowing the segment **110** to be delivered unsheathed in some applications. In some applications, segment **110** is delivered through lumen **608** of microcatheter **600** with a sheath **170** covering some or all of segment **110**. Sheath **170** can be configured to be placed over at least detachment feature **164** to keep detachment feature **164** from releasing the connection between a distal end of push wire **160** and the implant **110**.
- (17) As illustrated in FIG. 1B, the open end **114** can be positioned to exit the microcatheter **600**

before any other portion of the segment **110** exits the microcatheter. The open end **114** can expand as it exits the microcatheter **600**. If the open end **114** is unconstrained by an aneurysm as illustrated, the open end can expand to its circumference in the predetermined shape.

(18) As illustrated in FIG. **1C**, the distal portion of the segment **110** can continue to expand radially as it exits the microcatheter **600**.

(19) As illustrated in FIG. **1D**, the segment **110** can form an inversion **122** defining an outer section **142** as the segment **110** is further pushed out of the microcatheter **600**.

(20) As illustrated in FIGS. **1E**, **1F**, and **1G**, the “S” shape of a middle section **144** can begin to form as the segment **110** is further pushed from the microcatheter **600**.

(21) FIG. **2A** is an illustration of an example endovascular treatment system **100** including an implant with a detachment feature, in a non-deployed configuration, that includes balls, according to an exemplary embodiment. FIG. **2B** is cross-sectional illustration of the system **100** as indicated in FIG. **2A**. As shown, implant **100** can be delivered through a lumen **608** of microcatheter **600** to a treatment site. The implant can include a segment **110** which can be formed as a heat-set tubular braided implant that, when released from the microcatheter at a treatment site, the segment **110** can expand into a deployed configuration as shown in FIG. **2C**. The segment can include an open end **114** (not shown) and a proximal end **112** that can be attached to a push wire **160** via a detachment feature **164A**. Detachment feature **164A** can include one or more balls that are shaped to fit into one or more indentations **162A** located on distal end of push wire **160**. The one or more indentations **162** can include an annular groove circumscribing the outer surface of the push wire **160** that is sized to receive the balls. Additionally, or alternatively, the one or more indentations **162** can include a plurality of circular or semi-spherical pockets sized to receive the balls. A sheath **170** can be positioned over the implant **100** such that sheath **170** covers at least a portion of the detachment feature **164A**, thereby retaining the detachment feature **164A** at least partially recessed within the one or more indentations **162A** until the sheath **170** is removed. As illustrated, approximate the proximal end of the segment **110** can be a band **130**. However, band **130** is an optional feature and implant **100** can be configured to not include band **130**. Band **130** can be made of a radiopaque material in order to facilitate tracking the position of implant **100** as implant **100** is delivered through vasculature to a treatment site.

(22) FIG. **2C** is an illustration of the system of FIG. **2A** in a deployed configuration. After implant **100** is delivered to a treatment site (e.g., spherical cavity **10**, as described below in FIG. **4A**), the implant **100** can be manipulated to expand from the non-deployed configuration to the deployed configuration by pushing the implant **100** out from microcatheter **600**. FIG. **2C** shows the implant **100** detached from push wire **160**. The sheath **170** has been removed by being slid proximally into microcatheter **600**, thus allowing detachment feature **164A** to detach from the one or more indentations **162A**. In some examples, there can be one detachment feature **164A** and one corresponding indentation or groove **162A**, two detachment features **164A** and two corresponding indentations or grooves **162A**, or more than two detachment features **164A** and corresponding indentations or grooves **162A**. As shown, implant **100** can expand to the deployed configuration having two inversions **122**, **124**, dividing the segment **110** into three segments **142**, **144**, **146**. In the deployed configuration, the segment **110** can have an outer section **142** extending from the open end **114** of the segment **110** to one of the inversions **122**, an inner section **146** extending from the proximal end **112** of the segment **110** to the other of the inversions **124**, and a middle section **144** extending between the two inversions **122**, **124**.

(23) FIG. **3A** is an illustration of another example endovascular treatment system including an implant with a detachment feature including loops and a push wire including laser-etched pockets in a non-deployed configuration. Proximal end **112** of implant **100** segment **110** is shown with sheath **170** extended over the proximal end **112** in FIG. **3A**. Sheath **170** can be translated proximally, thereby exposing the proximal end **112** of segment **110** and allowing detachment feature **164B** to be released from corresponding grooves **162B**. The detachment feature **164B** can

be one or more loops formed on the proximal end **112** of the implant segment **110**. Push wire **160** can include one or more indentations **162B** on the distal end of push wire **160**. In some examples, the one or more indentations **162B** can include laser-etched pockets that are shaped to fit the one or more loops of detachment feature **164B**.

(24) FIG. 3B is a cross-sectional view of the system **100** showing the loop and pocket detachment mechanism as indicated in FIG. 3A. As can be seen in FIG. 3B, the pockets **162B** can extend radially into the push wire **160** and correspond to the shape of the one or more loops of detachment feature **164B**.

(25) FIG. 3C is an illustration of the system **100** after the detachment feature **164b** expands so that loops release from the indentations **162B** of the push wire **160**. The sheath **170** is retracted to allow the detachment feature **164b** to expand.

(26) FIGS. 4A and 4B are illustrations of measurements of an example spherical cavity and implant according to aspects of the present invention. FIG. 4A is an illustration of height HAL sac diameter DA, and neck diameter DN, which are measurements of a spherical cavity **10**. In some examples, spherical cavity can be an aneurysm of a patient. The location of the plane **18** defining a boundary between the spherical cavity **10** and blood vessels is also illustrated. As shown, the spherical cavity **10** can include a neck **16**, a wall **14**, and a distal wall **15**. The spherical cavity **10** can also include a spherical cavity interior **12**. The endovascular implant **100** can be configured to occlude the spherical cavity **10** when the implant is in a deployed configuration.

(27) FIG. 4B is an illustration of height HA2 of an example implant **100** in a deployed configuration. In the deployed configuration, the braid **110** of the example implant **100** can be substantially radially symmetrical about vertical axis y, and therefore can have substantially circular concentric cross-sections each describable by its diameter. FIG. 4B highlights the height HA2 of the implant **100** in a deployed configuration measured between the inversions **122**, **124**, an outer diameter D1 of the outer section **142**, which corresponds to the diameter of the open end **114**, and the outer diameter D2 of the middle section **144**. It should be understood that the height HA2 of example implant **100** can be varied to match the height HA1 of spherical cavity **10** such that a proximal end of segment **110** is flush with a proximal end of the spherical cavity **10** in the deployed state. For example, the proximal end of segment **110** can be flush with the plane **18** when in the deployed configuration, as shown in FIG. 4A. Although FIG. 4B illustrates only one example deployed configuration, it should be understood that the height and diameter of example implants described herein **100** and portions thereof can be varied to fit spherical cavities **10** of varying dimensions.

(28) FIG. 5 is a flowchart of a method **500** for constructing an endovascular treatment system. In block **502**, the method can include providing a segment **110** including an open end **114** and a proximal end **112**. The segment can include a braided tubular implant. The open end can be on a distal end of the segment.

(29) In block **504**, the method can include shaping the segment to a predetermined shape to which the segment is capable of self-expanding. Shaping the segment to a predetermined shape can include inverting the segment to form a proximal inversion **122** folded towards the distal direction thereby defining an outermost section **142** of the segment. Shaping the segment to a predetermined shape can include inverting the segment to form a distal inversion **124** folded toward the proximal direction to define a middle section **144** between the proximal and distal inversion of the segment. The middle section of the segment can be at least partially surrounded by the outermost section and define an innermost section **146** between the distal inversion and the proximal end **112** that is at least partially surrounded by the middle section **144**.

(30) In block **506**, the method can include providing a detachment feature **164** that is affixed to the proximal end of the segment. In some examples, the detachment feature **164** can include one or more balls **164A** that are configured to fit into one or more indentations **162A** formed within a distal end of push wire **160**. In some examples, the detachment feature **164** can include one or more

wire loops **164B** formed from a proximal end of the segment **110** of the implant **100**, and the one or more wire loops **164B** are configured to fit into the one or more indentations **162B** formed within a distal end of push wire **160**.

(31) In block **508**, the method can include providing a push wire **160** that includes one or more indentations **162** in a distal end of the push wire **160**.

(32) In block **510**, the method can include recessing at least a portion of the detachment feature **164** into the one or more indentations on the push wire.

(33) In block **512**, the method can include positioning a sleeve **170** at least partially surrounding the push wire **160** and the proximal end **112** of the segment **110**.

(34) FIG. **6** is a flowchart of a method **601** for occluding a spherical cavity. In block **602**, the method can include providing an expandable segment **110** that includes an open end **114** and a proximal end **112** in a non-deployed configuration.

(35) In block **604**, the method can include affixing the proximal end **112** to a push wire **160** via a detachment feature **164**.

(36) In block **606**, the method can include positioning a sleeve over the push wire **160** and the detachment feature **164** to prevent detachment of the proximal end **112** from the distal end of the push wire **160**.

(37) In block **609**, the method can include delivering the expandable segment **110**, push wire **160**, and sleeve **170** to a treatment site via a microcatheter **600**.

(38) In block **610**, the sleeve **170** can be slid proximally, thereby releasing the proximal end **112** of the segment **110** from the distal end of the push wire **160**. In response, the segment **110** can expand to occlude the spherical cavity **10**.

(39) The tubular braid **110** of the example implant **100** can include memory shape material that can be heat set to a predetermined shape, can be deformed for delivery through a catheter, and can self-expand to an implanted shape that is based on the predetermined shape and confined by the anatomy of the aneurysm in which it is implanted.

(40) The example implant **100** described herein can rely on a radial outward force to anchor the implant within the sac of an aneurysm. To this end, the braid **110** can be shaped to a predetermined shape having a diameter that is greater than its height so that the braid is radially constricted when implanted in an aneurysm. The ratio of diameter to height of the braid **110** in a respective predetermined shape can be within the range of 2:1 to 1:3 to treat aneurysms of many known sizes and shapes.

(41) The descriptions contained herein are examples of embodiments of the invention and are not intended in any way to limit the scope of the invention. As described herein, the invention contemplates many variations and modifications of the implant, including alternative materials, alternative geometries, alternative detachment features, alternative delivery systems, alternative means for forming a braid into a predetermined shape, alternative treatment methods, etc. These modifications would be apparent to those having ordinary skill in the art to which this invention relates and are intended to be within the scope of the claims which follow.

Claims

1. An endovascular implantation system, comprising: an occlusive segment configured to occlude a spherical cavity and comprising an open end and a proximal end; a push wire positioned proximal of the proximal end of the occlusive segment and comprising one or more indentations on an outer surface of the push wire approximate a distal end of the push wire; a detachment feature affixed to the proximal end of the occlusive segment and shaped to at least partially recess into the one or more indentations of the push wire; and a sleeve surrounding at least a portion of the push wire, wherein in a non-deployed configuration, the sleeve surrounds at least a portion of the detachment feature and thereby prevents release of the proximal end of the occlusive segment from the push

wire, and wherein in a deployed configuration, the sleeve is retracted proximally from the detachment feature to thereby detach the occlusive segment from the push wire.

2. The endovascular implantation system of claim 1, wherein the detachment feature further comprises a plurality of wire loops extending from the proximal end of the occlusive segment that are at least partially recessed into the one or more indentations of the push wire in the non-deployed configuration.

3. The endovascular implantation system of claim 2, wherein the one or more indentations comprise a plurality of laser-etched pockets, each of the laser-etched pockets shaped to receive a corresponding wire loop of the plurality of wire loops.

4. The endovascular implantation system of claim 1, wherein the detachment feature further comprises a plurality of balls extending from the proximal end that are configured to fit into the one or more indentations of the push wire in the non-deployed configuration.

5. The endovascular implantation system of claim 1, wherein in the deployed configuration, the occlusive segment expands to occlude the spherical cavity.

6. The endovascular implantation system of claim 1, wherein in the deployed configuration the occlusive segment extends in a distal direction from the proximal end and comprises two inversions separating three sections which at least partially overlap each other such that the proximal end is affixed to an innermost section of the three sections, and a middle section of the three sections extends between the two inversions and is positioned within an outermost section and around the innermost section.

7. The endovascular implantation system of claim 1, further comprising: a microcatheter configured to deliver the occlusive segment, the push wire, and the sleeve to the spherical cavity in the non-deployed configuration, the microcatheter comprising a lumen, wherein the segment comprises a diameter in the non-deployed configuration sized to fit within the lumen of the microcatheter.

8. The endovascular implantation system of claim 1, further comprising a band approximate the proximal end of the occlusive segment, wherein the band comprises radiopaque material.

9. The endovascular implantation system of claim 8, wherein, in the deployed configuration, the open end is positioned approximate a distal wall of the spherical cavity, and the band is suspended within the spherical cavity.

10. A method for constructing an endovascular implantation system, the method comprising: providing an occlusive segment comprising an open end and a proximal end; shaping, as follows, the occlusive segment to a predetermined shape to which the segment is capable of self-expanding: inverting the segment to form a proximal inversion folded toward a distal direction thereby defining an outermost section of the segment, and inverting the segment to form a distal inversion folded toward the proximal direction thereby defining a middle section between the proximal and distal inversion of the segment that is at least partially surrounded by the outermost section and defining an innermost section between the distal inversion and the proximal end that is at least partially surrounded by the middle section; providing a detachment feature affixed to the proximal end of the segment; providing a push wire comprising one or more indentations approximate a distal end of the push wire; recessing at least a portion of the detachment feature into the one or more indentations of the push wire; and positioning a sleeve to at least partially surround the distal end of the push wire and the detachment feature.

11. The method of claim 10, wherein the sleeve is effective to retain the proximal end of the occlusive segment attached to the push wire.

12. The method of claim 10, wherein the detachment feature further comprises a plurality of wire loops extending from the proximal end that are configured to fit into the one or more indentations positioned on the distal end of the push wire.

13. The method of claim 12, wherein the one or more indentations comprise a plurality of laser-etched pockets, each of the laser-etched pockets shaped to fit a corresponding wire loop of the

plurality of wire loops.

14. The method of claim 10, wherein the detachment feature further comprises a plurality of balls extending from the proximal end that are configured to fit into the one or more indentations positioned on the distal end of the push wire.

15. A method of occluding a spherical cavity, the method comprising: providing an expandable segment comprising an open end and a proximal end in a non-deployed configuration; affixing the proximal end to a push wire via a detachment feature; positioning a sleeve over the push wire and the detachment feature to prevent detachment of the proximal end from a distal end of the push wire; delivering the expandable segment, push wire, and sleeve to a treatment site via a microcatheter; and sliding the sleeve proximally, thereby releasing the proximal end from the distal end of the push wire and causing the expandable segment to expand to a deployed configuration to occlude the spherical cavity.

16. The method of claim 15, wherein the detachment feature further comprises a plurality of wire loops extending from the proximal end that are configured to fit into one or more indentations positioned on a distal end of the push wire.

17. The method of claim 16, wherein the one or more indentations comprise a plurality of laser-etched pockets, each of the laser-etched pockets shaped to fit a corresponding wire loop of the plurality of wire loops.

18. The method of claim 15, wherein the detachment feature further comprises a plurality of balls extending from the proximal end that are configured to fit into the one or more indentations positioned on the distal end of the push wire.

19. The method of claim 15, wherein in the deployed configuration, the proximal end of the expandable segment is flush with a proximal end of the spherical cavity.

20. The method of claim 19, wherein in the deployed configuration the expandable segment comprises two inversions separating three sections which at least partially overlap each other such that the proximal end of the expandable segment is affixed to an innermost section of the three sections and a middle section of the three sections extends between the two inversions and is positioned within an outermost section and around the innermost section.
