

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398571
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Mason; Greg Stephen et al.

Armoured joint—anti-skew stake bracket

Abstract

An armoured joint for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint, wherein the apparatus includes a first anchorage part for anchoring to the first component and a second anchorage part for anchoring to the second component, a first plate coupled to the first anchorage part, a second plate coupled to the second anchorage part, the first plate defining a first edge, the second plate defining a second edge, wherein the first edge and the second edge are shaped to facilitate bringing together of the first edge and the second edge, and wherein the second anchorage part is adapted to be movable relative to the first anchorage part from a close configuration in which the second edge is brought together with the first edge to a spaced configuration in which the second edge is spaced relative to the first edge, wherein the first anchorage part or the second anchorage part has a support section, the armoured joint including a bracket for supporting the armoured joint relative to a ground surface, the bracket comprising an angled upper leg and an angled lower leg, wherein the bracket is fixed to the support section by the angled upper leg and the angled lower leg, the angled upper leg being fixed to the support section to extend downwardly from the support section at a first angle and the angled lower leg being fixed to the support section to extend upwardly from the support section at a second angle of the same magnitude as the first angle.

Inventors:	Mason; Greg Stephen (Brisbane, AU), Rogers; Ryan (Brisbane, AU)
Applicant:	Illinois Tool Works Inc. (Glenview, IL)
Family ID:	1000008778079
Assignee:	Illinois Tool Works Inc. (Glenview, IL)
Appl. No.:	17/862878
Filed:	July 12, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230009418 A1	Jan. 12, 2023

Foreign Application Priority Data

AU

2021204996

Jul. 12, 2021

Publication Classification

Int. Cl.: **E04F15/14** (20060101); **E01C11/10** (20060101); **E04B5/36** (20060101); E04B5/32 (20060101)

U.S. Cl.:

CPC **E04F15/142** (20130101); **E01C11/106** (20130101); **E04B5/36** (20130101); E01C2201/16 (20130101); E04B2005/322 (20130101); E04B2005/324 (20130101)

Field of Classification Search

CPC: E04F (15/02194); E04F (15/142); E04F (15/14); E04G (21/185); E04G (13/00); E04B (5/36); E04B (5/32); E04B (5/23); E04B (1/6804); E04B (1/483); E04B (1/043); E04B (1/48); E04B (2005/322); E04B (2005/324)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2094853	12/1936	Shaw	N/A	N/A
2181005	12/1938	Westcott	N/A	N/A
2316233	12/1942	Fischer	N/A	N/A
2349983	12/1943	Alexander	N/A	N/A
2654297	12/1952	Nettleton	N/A	N/A
3559541	12/1970	Watstein	N/A	N/A
3690226	12/1971	Hein	404/68	E01D 19/06
3862810	12/1974	Welch	404/66	E01C 11/126
4080086	12/1977	Watson	404/69	E01D 19/06
4733513	12/1987	Schrader et al.	N/A	N/A
4942912	12/1989	Gakhar et al.	N/A	N/A
5005331	12/1990	Shaw et al.	N/A	N/A
5205942	12/1992	Fitzgerald	N/A	N/A
5216862	12/1992	Shaw et al.	N/A	N/A
5261635	12/1992	Flathau	N/A	N/A
5458433	12/1994	Stastny	N/A	N/A
5487249	12/1995	Shaw et al.	N/A	N/A
5730544	12/1997	Dils et al.	N/A	N/A
5830378	12/1997	Butler	N/A	N/A
6019546	12/1999	Ruiz	N/A	N/A
6021994	12/1999	Shartzner	N/A	N/A
6145262	12/1999	Schrader et al.	N/A	N/A
6354760	12/2001	Boxall et al.	N/A	N/A
6550213	12/2002	Butler	N/A	N/A

6629681	12/2002	Miller	N/A	N/A
6775952	12/2003	Boxall et al.	N/A	N/A
6874288	12/2004	Washa	N/A	N/A
6926463	12/2004	Shaw et al.	N/A	N/A
7228666	12/2006	Michiels	N/A	N/A
7338230	12/2007	Shaw et al.	N/A	N/A
7481031	12/2008	Boxall et al.	N/A	N/A
7547158	12/2008	Mucci	N/A	N/A
7604432	12/2008	Shaw et al.	N/A	N/A
7637689	12/2008	Boxall et al.	N/A	N/A
7716890	12/2009	Boxall et al.	N/A	N/A
7736088	12/2009	Boxall et al.	N/A	N/A
8142104	12/2011	Connolly	N/A	N/A
8302359	12/2011	Boxall et al.	N/A	N/A
8303210	12/2011	Parkes et al.	N/A	N/A
8356955	12/2012	Nadler	N/A	N/A
8381470	12/2012	Boxall et al.	N/A	N/A
8516761	12/2012	Laiho et al.	N/A	N/A
8539726	12/2012	Laiho et al.	N/A	N/A
8573884	12/2012	Nadler	N/A	N/A
8627626	12/2013	Boxall et al.	N/A	N/A
9260867	12/2015	Arnold	N/A	N/A
9574309	12/2016	Mcdonald	N/A	N/A
9637874	12/2016	Ganey	N/A	N/A
9765485	12/2016	Keen	N/A	N/A
10094075	12/2017	Keen	N/A	N/A
10323359	12/2018	Meuwissen et al.	N/A	N/A
10711410	12/2019	Meuwissen	N/A	E01C 11/14
10851501	12/2019	De Rivas	N/A	E01C 11/08
2003/0146365	12/2002	Miller et al.	N/A	N/A
2006/0275078	12/2005	Shaw et al.	N/A	N/A
2007/0269266	12/2006	Kelly et al.	N/A	N/A
2008/0263981	12/2007	OBrien	N/A	N/A
2010/0054858	12/2009	Mayo et al.	N/A	N/A
2010/0086351	12/2009	Mercer	N/A	N/A
2015/0016870	12/2014	Arnold	403/266	E01C 11/08
2017/0009446	12/2016	Eve	N/A	E01C 11/126
2018/0135297	12/2017	Parkes	N/A	E04B 1/483
2019/0301153	12/2018	Hansort	N/A	E04C 5/163
2020/0263422	12/2019	Murdoch	N/A	E01C 11/14
2020/0325638	12/2019	Murdoch et al.	N/A	N/A
2020/0332476	12/2019	Murdoch et al.	N/A	N/A
2021/0189739	12/2020	Mason	N/A	E01C 11/14
2022/0010546	12/2021	Mason	N/A	N/A
2022/0145615	12/2021	Mason	N/A	E04C 5/168
2023/0323609	12/2022	Wiatrowski	52/396.04	E01C 11/14

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2712305	12/2008	CA	N/A
102007020816	12/2007	DE	N/A
1598478	12/2004	EP	N/A
3029949	12/2015	FR	N/A
3043105	12/2016	FR	N/A
2285641	12/1994	GB	N/A
2421049	12/2005	GB	N/A
2467877	12/2009	GB	N/A
2500626	12/2012	GB	N/A
2511729	12/2013	GB	N/A
2530344	12/2015	GB	N/A
100786357	12/2006	KR	N/A
9828500	12/1997	WO	N/A
WO 2004/065694	12/2003	WO	N/A
WO 2005/103412	12/2004	WO	N/A
WO 2005/111332	12/2004	WO	N/A
WO 2006/123176	12/2005	WO	N/A
WO 2009/153604	12/2008	WO	N/A
WO 2010/004294	12/2009	WO	N/A
WO 2013/076500	12/2012	WO	N/A
WO 2013/128151	12/2012	WO	N/A
WO 2014/060752	12/2013	WO	N/A
WO 2014/096980	12/2013	WO	N/A
WO 2014/111712	12/2013	WO	N/A
WO 2019/074632	12/2018	WO	N/A

OTHER PUBLICATIONS

Diamond Dowel® System Tapered Plate Dowels for Formed Construction Joints brochure , PNA Construction Technologies, available Nov. 19, 2018 (2 pages). cited by applicant
Diamond™ Dowel Load Transfer System Industrial Slab on Ground brochure, Danley™ Systems, available Nov. 19, 2018 (8 pages). cited by applicant
Load Transfer Systems Dowel Cradles Industrial Slab on Ground brochure, ITW Construction Systems and Danley Systems, available prior to Nov. 19, 2018 (12 pages). cited by applicant

Primary Examiner: Agudelo; Paola

Attorney, Agent or Firm: Neal, Gerber & Eisenberg LLP

Background/Summary

PRIORITY CLAIM

(1) The present application claims priority to and the benefit of Australian Patent Application No. 2021204996, filed Jul. 12, 2021, the entire contents of which are incorporated herein by reference.

CROSS-REFERENCE TO RELATED APPLICATIONS

(2) This application is related to the following commonly owned co-pending patent applications: U.S. application Ser. No. 17/892,895, entitled “ARMoured JOINT-DISRUPTIVE FOLDED

ANCHOR RAIL”; U.S. application Ser. No. 17/862,011, entitled “JOINT EDGE PROTECTION APPARATUS-FULLY BRIDGED WAVE PLATES”; U.S. application Ser. No. 17/862,029, entitled “EDGE PROTECTION SYSTEM-FLOATING COVER PLATE ON INTERSECTION”; U.S. application Ser. No. 17/862,637, entitled “EDGE PROTECTION SYSTEM-INTERSECTION CONTINUOUS PERIMETER JOINT LINE”; and U.S. application Ser. No. 17/862,639, entitled “EDGE PROTECTION SYSTEM-JOINT ORIENTATION MARKER.”

FIELD

(3) The present disclosure relates broadly to an edge protection system, or an armoured joint, for protecting the edges of components formed of settable material such as concrete. The components formed of settable material may be in the form of concrete flooring components, for example, flooring components of industrial concrete flooring. The present disclosure relates to a fully bridged wave plate and, more particularly, but not exclusively, to a fully bridged and supported top wave plate.

BACKGROUND

(4) It is known that the edges of components formed of settable material—such as concrete—may be subject to damage. In particular, where the components formed of settable material are in the form of concrete flooring components forming a floor surface (such as in a warehouse or storage facility), the edges of the concrete flooring components may be subject to damage as forklifts and the like travel from one concrete component onto a neighbouring concrete component. This damage may be exacerbated where one flooring component rises relative to the neighbouring flooring component forming a raised bump which is subject to wear.

(5) It has been proposed to provide an edge protection system to protect the edges of concrete flooring components. However, the applicant has determined that existing edge protection systems are relatively expensive, may be over-engineered, may be subject to incorrect installation and/or may not adequately prevent movement of one concrete panel relative to a neighbouring concrete panel. Examples of the present disclosure aim to improve the life-cycle of a material handling equipment (MHE) crossing by providing an impact free joint, providing an alternative to straight gap systems with wheel impact.

(6) The applicant has determined that it would be advantageous for there to be provided an improved edge protection system which alleviates or at least ameliorates one or more of the disadvantages of existing edge protection systems. In particular, the applicant has identified that it would be advantageous for there to be provided a joint edge management system which provides load transfer, protecting concrete edges from spalling caused by materials handling equipment (MHE) with small hard wheels, travelling at speed, carrying high loads.

SUMMARY

(7) There is disclosed a joint edge protection apparatus for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint, wherein the apparatus includes a first anchorage part for anchoring within the first component and a second anchorage part for anchoring within the second component, a first plate coupled to the first anchorage part, a second plate coupled to the second anchorage part, the first plate defining a first abutment surface, the second plate defining a second abutment surface, wherein the first abutment surface and the second abutment surface are shaped to facilitate abutment of at least a portion of the second abutment surface against the first abutment surface, and wherein the second anchorage part is adapted to be movable relative to the first anchorage part from an abutting configuration in which at least a portion of the second abutment surface is in abutment with the first abutment surface to a spaced configuration in which the second abutment surface is spaced relative to the first abutment surface, wherein the first anchorage part defines a support surface to support the second plate as the second anchorage part is moved between the abutting configuration and the spaced configuration, and wherein, in the abutting configuration an interface between the first abutment surface and the second abutment surface is offset relative to an interface between the

first anchorage part and the second anchorage part such that the interface of the first abutment surface and the second abutment surface is positioned above the support surface.

(8) Preferably, the first abutment surface and the second abutment surface are correspondingly shaped to facilitate abutment of the second abutment surface against the first abutment surface, such that in the abutting configuration the second abutment surface is in abutment with the first abutment surface.

(9) Preferably, the first abutment surface and the second abutment surface are correspondingly shaped with a wave shape to facilitate abutment of the second abutment surface against the first abutment surface. In one form, the wave shape of the first abutment surface is matched to the wave shape of the second abutment surface to facilitate continuous abutment in the abutting configuration. In an alternative form, the wave shape of the first abutment surface is mismatched to the wave shape of the second abutment surface to facilitate periodic abutment in the abutting configuration.

(10) In a preferred form, the apparatus is arranged such that a gap between the first abutment surface and the second abutment surface, throughout a range of movement, is located above said support surface such that the gap is fully spanned by the support surface. More preferably, the gap is fully bridged by the support surface such that contaminants including vermin and debris are prevented from entering the joint between the first component and the second component. Even more preferably, the fully bridged gap provides a well for application of joint material. In one example, the joint material is in the form of a joint epoxy and/or sealant.

(11) Preferably, the range of movement corresponds to a gap between the first abutment surface and the second abutment surface being between 0 mm and 20 mm.

(12) In a preferred form, said offset, in use, results in the interface between the first abutment surface and the second abutment surface being offset from a centre of the joint between the first component and the second component.

(13) Preferably, the first anchorage part includes a first lacer bar supported by a series of spaced ribs.

(14) It is preferred that the second anchorage part includes a second lacer bar supported by a series of spaced ribs.

(15) Preferably, the or each lacer bar is in the form of a rail.

(16) There is also disclosed a joint edge protection apparatus for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint, wherein the apparatus includes a first anchorage part for anchoring within the first component and a second anchorage part for anchoring within the second component, the first anchorage part being provided with a first plate, the second anchorage part being provided with a second plate, the first plate defining a first interface surface, the second plate defining a second interface surface, wherein the first interface surface and the second interface surface are shaped to facilitate abutment of at least a portion of the second interface surface against the first interface surface, and wherein the second anchorage part is adapted to be movable relative to the first anchorage part from an abutting configuration in which at least a portion of the second interface surface is in abutment with the first interface surface to a spaced configuration in which the second interface surface is spaced relative to the first interface surface, wherein the first interface surface and the second interface surface are each shaped with a wave shape, wherein the wave shape of the first interface surface is mismatched to the wave shape of the second interface surface to facilitate periodic abutment of the second interface surface against the first interface surface in the abutting configuration.

(17) There is also disclosed an armoured joint for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint, wherein the apparatus includes a first anchorage part for anchoring within the first component and a second anchorage part for anchoring within the second component, a first plate coupled to the

first anchorage part, a second plate coupled to the second anchorage part, the first plate defining a first abutment surface, the second plate defining a second abutment surface, wherein the first abutment surface and the second abutment surface are correspondingly shaped to facilitate abutment of the second abutment surface against the first abutment surface, and wherein the second anchorage part is adapted to be movable relative to the first anchorage part from an abutting configuration in which the second abutment surface is in abutment with the first abutment surface to a spaced configuration in which the second abutment surface is spaced relative to the first abutment surface, wherein the first anchorage part includes an elongated angled anchorage lacer bar, the elongated angled anchorage lacer bar being supported by a series of spaced ribs and the rail being tilted out of the plane of the ribs.

(18) Preferably, the elongated angled anchorage lacer bar is substantially perpendicular to the first plate.

(19) Preferably, the first anchorage part and the second anchorage part each have a respective elongated angled anchorage lacer bar, each of the respective elongated angled anchorage lacer bars being supported by a respective series of spaced ribs and each lacer bar being tilted out of the plane of the respective ribs.

(20) It is preferred that the armoured joint includes at least one dowel for maintaining level of the second anchorage part relative to the first anchorage part.

(21) In one form, the anchorage lacer bar varies in width between ribs.

(22) Preferably, each of the spaced ribs has a tapered foot which tapers outwardly into the lacer bar. More preferably, each tapered foot progressively tapers outwardly into the lacer bar.

(23) Preferably, each rib is bent at the tapered foot such that the lacer bar is tilted out of a plane of the ribs.

(24) In a preferred form, each of the ribs is angled at an acute angle relative to the first plate, and the lacer bar is tilted to be substantially perpendicular to the first plate.

(25) Preferably, between each pair of successive ribs, an upper edge of the lacer bar is tapered progressively outwardly then progressively inwardly.

(26) It is preferred that, between each pair of successive ribs, an upper edge of the lacer bar has a generally wave-like form. More preferably, between each pair of successive ribs, the upper edge of the lacer bar has a single wave form.

(27) In one form, the lacer bar is in the form of a part of sheet metal.

(28) In accordance with the present disclosure, there is provided an armoured joint for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint, wherein the apparatus includes a first anchorage part for anchoring to the first component and a second anchorage part for anchoring to the second component, a first plate coupled to the first anchorage part, a second plate coupled to the second anchorage part, the first plate defining a first edge, the second plate defining a second edge, wherein the first edge and the second edge are correspondingly shaped to facilitate bringing together of the first edge and the second edge, and wherein the second anchorage part is adapted to be movable relative to the first anchorage part from a close configuration in which the second edge is brought together with the first edge to a spaced configuration in which the second edge is spaced relative to the first edge, wherein the first anchorage part or the second anchorage part has a support section, the armoured joint including a bracket for supporting the armoured joint relative to a ground surface, the bracket comprising an angled upper leg and an angled lower leg, wherein the bracket is fixed to the support section by the angled upper leg and the angled lower leg, the angled upper leg being fixed to the support section to extend downwardly from the support section at a first angle and the angled lower leg being fixed to the support section to extend upwardly from the support section at a second angle of the same magnitude as the first angle.

(29) Preferably, a distal end of the upper leg is fixed relative to a distal end of the lower leg.

(30) It is preferred that the upper leg is in the form of a straight part and the lower leg is in the form

of a straight part.

(31) Preferably, the upper leg is provided with an aperture for receiving a support stake, for supporting the armoured joint relative to a ground surface, and the lower leg is provided with an aperture for receiving the support stake. More preferably, the aperture of the upper leg and the aperture of the lower leg are arranged to receive the support stake with the support stake in a substantially perpendicular orientation relative to a plane of the first plate.

(32) Even more preferably, the apertures and the support stake are arranged to provide a sliding condition in which the stake is able to be slid relative to the bracket and a locked condition in which the stake is locked against sliding relative to the bracket, wherein the stake is rotated about its longitudinal axis relative to the bracket between the sliding condition and the locked condition.

(33) Preferably, the upper leg meets the lower leg at a bent portion of the bracket.

(34) In a preferred form, the upper leg meets the lower leg at an intermediate vertical section between the upper leg and the lower leg.

(35) Preferably, the bracket is symmetrical in a horizontal central plane.

(36) There is also disclosed an assembly including an armoured joint as described above, in combination with a stake, wherein the stake extends through the upper leg and the lower leg.

(37) Preferably, the stake is non-circular and an aperture in each of the upper leg and lower leg is non-circular, such that the stake is able to be rotated relative to the bracket between a sliding condition, in which the stake is able to be slid relative to the bracket, and a locked condition, in which the stake is locked against sliding relative to the bracket.

(38) In a preferred form, the first anchorage part includes an elongated angled anchorage lacer bar, the elongated angled anchorage lacer bar being supported by a series of spaced ribs and the lacer bar being tilted out of the plane of the ribs.

(39) Preferably, the first anchorage part defines a support surface to support the second plate as the second anchorage part is moved between the close configuration and the spaced configuration, and wherein, in the close configuration an interface between the first edge and the second edge is offset relative to a joint between the first component and the second component such that the interface of the first edge and the second edge is positioned above the support surface.

(40) Preferably, each of the apertures is in the shape of a slot, and the stake has a cross-sectional shape having opposed parallel flat sides connected at either end by a round portion.

(41) There is also disclosed an edge protection system including a first expandable armoured joint to protect a first joint extending in a first direction, a second expandable armoured joint to protect a second joint extending in a second direction and an intersection module including a cover plate located at an intersection of the first expandable armoured joint and the second expandable armoured joint.

(42) Preferably, the first expandable armoured joint includes a first pair of plates arranged to be moved apart to open a crevice between the plates in response to expansion of the first joint, and the second expandable armoured joint includes a second pair of plates arranged to be moved apart to open a crevice between the plates in response to expansion of the second joint. More preferably, each of the first pair of plates has a wavy edge, the wavy edges being brought together in a contracted condition of the first expandable armoured joint, and wherein each of the second pair of plates has a wavy edge, the wavy edges being brought together in a contracted condition of the second expandable armoured joint.

(43) Preferably, the cover plate is removable from a remainder of said intersection module. More specifically, the plate is removable to facilitate installation. Although not the main function, the removability of the plate may be used for repair and/or top plate replacement.

(44) Preferably, the edge protection system includes an anchored support for supporting the intersection module relative to a ground surface, an upper support of the intersection module being adapted to receive the cover plate fastened thereto. More preferably, the anchored support anchors the intersection module in a fixed location relative to the ground surface during expansion of the

first expandable armoured joint and the second expandable armoured joint.

(45) In a preferred form, the first joint is a joint between concrete slab sections and the second joint is a joint between concrete slab sections. More preferably, the cover plate is a load supporting member being braced by each slab section when the slab sections move through slab shrinkage. Even more preferably, the cover plate is a load supporting member being braced by each slab section when the slab sections move through slab shrinkage with each slab moving up to 20 mm.

(46) In a preferred form, the intersection module includes a central support column, the central support column having an upper support plate and a lower anchor plate, the cover plate being fastened to the upper support plate so as to be connected to the central support column and the lower anchor plate to remain vertically coupled to the concrete slab sections.

(47) More preferably, the edge protection system includes a stake which is inserted through the central support column for supporting the intersection module relative to the ground surface.

(48) Preferably, the upper support plate is in the form of an upper cleat plate which is spaced vertically from the lower anchor plate.

(49) In a preferred form, the stake is in the form of a star picket. More preferably, the stake is arranged to prevent the central support column from rotating relative to the ground surface and from translational movement relative to the ground surface. Even more preferably, the cleat plate and the lower anchor plate restrict movement of the star picket angularly at spaced locations of the central support column.

(50) Preferably, the first direction is not parallel to the second direction. More preferably, the first direction is perpendicular to the second direction.

(51) There is also disclosed an edge protection system including a first expandable armoured joint to protect a first joint extending in a first direction, a second expandable armoured joint to protect a second joint extending in a second direction and an intersection module at an intersection of the first expandable armoured joint and the second expandable armoured joint, wherein the first expandable armoured joint has a first joint line, the second expandable armoured joint has a second joint line, and wherein the intersection module provides a perimeter joint line such that there is a continuous joint line including the first joint line, the perimeter joint line and the second joint line.

(52) Preferably, the intersection module includes a cover plate, and the continuous joint line extends at least partially around a perimeter of the cover plate between the first joint line and the second joint line.

(53) Preferably, the first joint line has a generally wavy form and the second joint line has a generally wavy form. More preferably, the cover plate is arranged such that, regardless of where lengths of the wavy first and second joints are cut, the wavy first joint line and the wavy second joint line will connect to the active joint line of the intersection module. In one form, the cover plate is arranged to ensure such that joint lines are matched to standard joint runs.

(54) Preferably, joint openings at the perimeter of the cover plate are halved in thickness when used in a four-way intersection configuration. More preferably, a joint gap is split up on either side of the cover plate.

(55) There is also disclosed an edge protection system including a first expandable armoured joint to protect a first joint extending in a first direction, a second expandable armoured joint to protect a second joint extending in a second direction and an intersection module at an intersection of the first expandable armoured joint and the second expandable armoured joint, wherein the intersection module has an indicator to enable a user to ensure correct orientation of the intersection module.

(56) Preferably, the intersection module includes a cover plate which is generally symmetrical in shape. More preferably, the cover plate is generally octagonal in shape.

(57) In one form, the indicator is in the form of a discreet marking.

(58) In one particular form, the indicator is in the form of a small hole in the cover plate.

(59) Preferably, the indicator is provided to enable a user to orientate joints during installation on-site in a common direction to ensure joint lines match.

- (60) In a preferred form, the indicator is positioned in one of four orientations on a first intersection module on-site depending upon a first pour location. More preferably, subsequent intersection modules are placed each with the respective indicator oriented in the same direction as for the first intersection module.
- (61) Preferably, the intersection module is arranged to allow for two-way, three-way and four-way intersections to be formed without adjusting orientation of the intersection module.
- (62) Preferably, the indicator is repeated on a plurality of assembly pieces of the intersection module to assist with orientation of star picket guides to a common orientation. More preferably, the indicator is repeated on an upper support plate and a lower support plate of a support column of the intersection module.
- (63) In one form, the first expandable armoured joint has a first joint line, the second expandable armoured joint has a second joint line, and the intersection module provides a perimeter joint line such that there is a continuous joint line including the first joint line, the perimeter joint line and the second joint line.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present disclosure is further described by way of non-limiting example only with reference to the accompanying drawings, in which:
- (2) FIG. 1 shows a perspective view of a joint edge protection apparatus having fully bridged and supported top wave plates;
- (3) FIG. 2 shows a cross sectional view of the joint edge protection apparatus cast into concrete slabs;
- (4) FIG. 3 shows a top perspective view of the joint edge protection apparatus having a wave-like gap between the plates filled;
- (5) FIG. 4 shows a side perspective view of a joint edge protection apparatus having a disruptive folded continuous sheet metal anchor rail;
- (6) FIG. 5 shows a cross sectional view of the joint edge protection apparatus showing transfer of forces;
- (7) FIG. 6 shows a detailed side view of the disruptive folded anchor rail depicting passage of forces;
- (8) FIG. 7 shows a further detailed side view of the disruptive folded anchor rail;
- (9) FIG. 8 shows a cross sectional view of an anti-skew stake bracket;
- (10) FIG. 9 shows a further cross sectional view of the stake bracket shown supporting a joint edge protection apparatus;
- (11) FIG. 10 shows free and locked orientations of a stake relative to an aperture of the stake bracket;
- (12) FIG. 11 shows a top perspective view of an edge protection system having a floating cover plate at an intersection;
- (13) FIG. 12 shows detail of an intersection module including the cover plate;
- (14) FIG. 13 shows a sectional view of the intersection top plate anchorage through the central column;
- (15) FIG. 14 shows a top perspective view of the intersection module shown anchored by a stake;
- (16) FIG. 15 shows a side view of the intersection module shown anchored by the stake;
- (17) FIG. 16 shows a top view of an intersection module providing a continuous perimeter joint line;
- (18) FIG. 17 shows a top view of the intersection module shown at a four-way intersection of joint gap openings;

- (19) FIG. **18** shows a top view of the intersection module shown at a three-way intersection of joint gap openings;
- (20) FIG. **19** shows a top view of the intersection module shown at a two way intersection of joint gap openings;
- (21) FIG. **20** shows a top view of the intersection module having a joint orientation marker on the top plate;
- (22) FIG. **21** shows a top perspective view of an edge protection system having a plurality of intersection modules, each of the intersection modules having a marker oriented in a common direction;
- (23) FIG. **22** shows a top perspective view of the edge protection system in a four-way intersection, showing orientation of the marker;
- (24) FIG. **23** shows a top perspective view of the edge protection system in a three-way intersection, showing orientation of the marker;
- (25) FIG. **24** shows a top perspective view of the edge protection system in a two way intersection, showing orientation of the marker;
- (26) FIG. **25** shows the marker being replicated on multiple components of the intersection module to ensure correct relative orientation/alignment of the components;
- (27) FIG. **26** shows fully bridged wave plates—end view (offset joint lines);
- (28) FIG. **27** shows fully bridged wave plates—end view (offset joint lines with hidden);
- (29) FIG. **28** shows fully bridged wave plates—perspective (offset joint lines);
- (30) FIG. **29** shows fully bridged wave plates—perspective (offset joint lines, with filler);
- (31) FIG. **30** shows fully bridged wave plates—perspective (open);
- (32) FIG. **31** shows fully bridged wave plates—perspective (open, with filler);
- (33) FIG. **32** shows fully bridged wave plates—perspective (closed);
- (34) FIG. **33** shows fully bridged wave plates—plan view (closed);
- (35) FIG. **34** shows fully bridged wave plates—plan view (open);
- (36) FIG. **35** shows disruptive folded anchor rail—end view (simples, one side);
- (37) FIG. **36** shows disruptive folded anchor rail—end view;
- (38) FIG. **37** shows disruptive folded anchor rail—front view;
- (39) FIG. **38** shows disruptive folded anchor rail—perspective (full joint, simple);
- (40) FIG. **39** shows disruptive folded anchor rail—perspective (one side);
- (41) FIG. **40** shows disruptive folded anchor rail—perspective (one side, rail only);
- (42) FIG. **41** shows disruptive folded anchor rail—top view (one side);
- (43) FIG. **42** shows anti skew stake bracket—end view (simple);
- (44) FIG. **43** shows anti skew stake bracket—end view;
- (45) FIG. **44** shows anti skew stake bracket—perspective (locked stake);
- (46) FIG. **45** shows anti skew stake bracket—perspective (loose stake);
- (47) FIG. **46** shows anti skew stake bracket—perspective (simple);
- (48) FIG. **47** shows anti skew stake bracket—perspective;
- (49) FIG. **48** shows anti skew stake bracket—plan view (locked stake);
- (50) FIG. **49** shows anti skew stake bracket—plan view (loose stake);
- (51) FIG. **50** shows floating cover plate on intersection—perspective (centre column);
- (52) FIG. **51** shows floating cover plate on intersection—perspective (step 1);
- (53) FIG. **52** shows floating cover plate on intersection—perspective (step 2);
- (54) FIG. **53** shows floating cover plate on intersection—perspective (step 3);
- (55) FIG. **54** shows floating cover plate on intersection—perspective (step 4);
- (56) FIG. **55** shows floating cover plate on intersection—perspective (step 5);
- (57) FIG. **56** shows floating cover plate on intersection—plan view (centre column);
- (58) FIG. **57** shows floating cover plate on intersection—plan view (perimeter gap, closed);
- (59) FIG. **58** shows floating cover plate on intersection—plan view (perimeter gap, open);

(60) FIG. **59** shows floating cover plate on intersection—side view (centre column with hidden);
(61) FIG. **60** shows floating cover plate on intersection—side view (centre column);
(62) FIG. **61** shows intersection continuous perimeter joint line—plan view (2-way, open);
(63) FIG. **62** shows intersection continuous perimeter joint line—plan view (3-way, open);
(64) FIG. **63** shows intersection continuous perimeter joint line—plan view (4-way, open);
(65) FIG. **64** shows intersection continuous perimeter joint line—plan view (closed);
(66) FIG. **65** shows joint orientation marker—perspective (intersection layout);
(67) FIG. **66** shows joint orientation marker—perspective (matching holes);
(68) FIG. **67** shows joint orientation marker—perspective;
(69) FIG. **68** shows joint orientation marker—plan view (intersection layout);
(70) FIG. **69** shows joint orientation marker—plan view;
(71) FIGS. **70a** to **70c** show an example of a joint edge protection apparatus having deliberately mismatched waves to facilitate lateral movement; and
(72) FIGS. **71a** to **71d** show another example of a joint edge protection apparatus having deliberately mismatched waves as well as predefined gaps to facilitate lateral movement.

DETAILED DESCRIPTION

1. Fully Bridged and Supported Top Wave Plates

(73) With reference to FIGS. **1** to **7** and FIGS. **26** to **34**, there is shown a joint edge protection apparatus having fully bridged and supported top wave plates in accordance with an example of the present disclosure.

(74) More specifically, there is provided a joint edge protection apparatus **10** for protecting an edge of a first component **12** formed of settable material and an edge of a second component **14** formed of settable material at a joint **16**. The apparatus **10** includes a first anchorage part **18** for anchoring within the first component **12** and a second anchorage part **20** for anchoring within the second component **14**. The apparatus **10** also includes a first plate **22** coupled to the first anchorage part **18**, a second plate **24** coupled to the second anchorage part **20**, the first plate **22** defining a first abutment surface **26** and the second plate **24** defining a second abutment surface **28**.

(75) The first abutment surface **26** and the second abutment surface **28** are correspondingly shaped to facilitate abutment of the second abutment surface **28** against the first abutment surface **26**. The second anchorage part **20** is adapted to be movable relative to the first anchorage part **18** from an abutting configuration (the FIG. **32**) in which the second abutment surface **28** is in abutment with the first abutment surface **26** to a spaced configuration (the FIG. **30**) in which the second abutment surface **28** is spaced relative to the first abutment surface **26**. The first anchorage part **18** defines a support surface **30** to support the second plate **24** as the second anchorage part **20** is moved between the abutting configuration and the spaced configuration. In the abutting configuration, an interface between the first abutment surface **26** and the second abutment surface **28** is offset relative to an interface between the first anchorage part **18** and the second anchorage part **20** such that the interface of the first abutment surface **26** and the second abutment surface **28** is positioned above the support surface **30**. In other words, the line of abutment between the first abutment surface **26** and the second abutment surface **28** is offset relative to the joint **16** such that the second plate **24** is supported by the first anchorage part **18** having the support surface **30**.

(76) The first abutment surface **26** and the second abutment surface **28** are correspondingly shaped with a wave shape (the FIG. **1**) to facilitate abutment of the second abutment surface **28** against the first abutment surface **26**.

(77) In the preferred example shown in the drawings, the apparatus **10** is arranged such that a gap **32** between the first abutment surface **26** and the second abutment surface **28**, throughout a range of movement, is located above the support surface **30** such that the gap **32** is fully spanned by the support surface **30**. In this way, the gap **32** is fully bridged by the support surface **30** such that debris is prevented from entering the joint **16** between the first component **12** and the second component **14**. The fully bridged gap **32** may provide a well **34** for application of joint material **36**.

The joint material **36** may be in the form of a joint epoxy and/or sealant.

(78) The range of movement corresponds to a gap **32** between the first abutment surface **26** and the second abutment surface **28** being between 0 mm and 20 mm.

(79) In use, the offset results in the interface between the first abutment surface **26** and the second abutment surface **28** being offset from a centre of the joint **16** between the first component **12** and the second component **14**.

(80) The first anchorage part **18** may include a first lacer bar **38** supported by a series of spaced ribs **40**. Similarly, the second anchorage part **20** may include a second lacer bar **42** supported by a series of spaced ribs **40**. Each of the lacer bars **38**, **42** may be in the form of a rail.

(81) Accordingly, as will be appreciated from the above, this aspect relates to: The separation plate and joint line under the top wave plates **22**, **24** is offset from the centre of the joint **16** to allow 20 mm of supported opening of the waved top plates **22**, **24** while fully supporting both sides of the joint **16** with concrete and steel. The resultant waved gap **32** between wave plates **22**, **24** at 20 mm is fully enclosed and does not allow debris to enter the remaining section (slab height—6 mm) of the joint **16**. Enclosing the joint gap **32** with the support surface **30** helps to reduce corrosion and binding (debris) of the load transfer mechanisms (dowels). The fully enclosed bridged gap **32** can act as a 6 mm deep well **34** for application of joint epoxies and sealants (if required). Epoxy is fully supported by steel and concrete. The bridged gap **32** acts as barrier against foreign objects entering the potential 20 mm joint **16**.

2. Disruptive Folded Continuous Sheet Metal Anchor Rail

(82) With reference to FIGS. 5 to 7 and FIGS. 35 to 41, there is also disclosed an armoured joint having a disruptive folded continuous sheet metal anchor rail.

(83) More specifically, as shown in FIGS. 5 to 7, the joint edge protection apparatus **10** forms an armoured joint having a disruptive folded continuous sheet metal anchor rail. In particular, the armoured joint protects an edge of the first component **12** formed of settable material and an edge of the second component **14** formed of settable material at the joint **16**. The apparatus **10** includes the first anchorage part **18** for anchoring within the first component **12** and the second anchorage part **20** for anchoring within the second component **14**. The first plate **22** is coupled to the first anchorage part **18** and the second plate **24** is coupled to the second anchorage part **20**. The first plate **22** defines the first abutment surface **26**, and the second plate **24** defines the second abutment surface **28**. The first abutment surface **26** and the second abutment surface **28** are correspondingly shaped to facilitate abutment of the second abutment surface **28** against the first abutment surface **26**. The second anchorage part **20** is adapted to be movable relative to the first anchorage part **18** from an abutting configuration (see FIG. 32) in which the second abutment surface **28** is in abutment with the first abutment surface **26** to a spaced configuration (see FIG. 30) in which the second abutment surface **28** is spaced relative to the first abutment surface **26**. The first anchorage part **18** includes the first lacer bar **38** which is in the form of an elongated angled anchorage lacer bar **38**. The first lacer bar **38** is supported by a series of the spaced ribs **40** and the first lacer bar **38** is in the form of a rail which is tilted out of a plane of the ribs **40** (see FIG. 5).

(84) The elongated angled anchorage lacer bar **38** is substantially perpendicular to the first plate **22**. In particular, as seen in FIG. 5, the first lacer bar **38** may be substantially vertical whereas the first plate **22** may be substantially horizontal for supporting forklifts and the like moving across a working floor surface.

(85) As can be seen in FIG. 5, the first anchorage part **18** and the second anchorage part **20** each have a respective elongated angled anchorage lacer bar **38**, **42**. Each of the respective elongated angled anchorage lacer bars are supported by a respective series of spaced ribs **40** and each lacer bar is tilted/bent out of a plane of the respective ribs **40**. In this way, the joint edge protection apparatus **10** is provided with a disruptive folded continuous sheet metal anchor rail which provides more consistent anchorage along the armoured joint.

(86) The armoured joint in the form of the joint edge protection apparatus **10** may include at least

one dowel **44** for maintaining level of the second anchorage part **20** relative to the first anchorage part **42**. In particular, as shown in FIG. 3 and FIG. 4, the joint edge protection apparatus **10** may include a plate dowel which is movable within one or more housing/sheath/sleeve fitted to the second anchorage part **20** and/or the first anchorage part **18**. The dowel **44** may be in the form of a plate dowel being generally rectangular or square in shape and, in situ, having edges extending at an angle to a central axis of the joint **16**. In particular, the plate dowel may have edges extending at an angle of approximately 45° to a central axis of the joint.

(87) As can be seen in FIG. 4, the anchorage lacer bar **42** varies in width between the ribs **40**. Specifically, it can be seen that, between adjacent ribs **40**, the lacer bar **42** increases in width to a thickest portion which is midway between the adjacent ribs **40**. This is achieved by having a straight lower edge to the lacer bar **42** and a tapered upper edge to the lacer bar **42**, which upper edge tapers outwardly to an apex **46** which is midway between the adjacent ribs **40**.

(88) Accordingly, in this way, between each pair of successive ribs **40**, the upper edge of the lacer bar **42** is tapered progressively outwardly to the apex **46** and then progressively inwardly to the next rib **40**. As such, between each pair of successive ribs **40**, the upper edge of the lacer bar **42** has a generally wave-like form. Even more specifically, in the example shown, between each pair of successive ribs **40** the upper edge of the lacer bar **42** has a single wave form. The lacer bar **42** may be in the form of a part of sheet metal.

(89) As can be seen in FIG. 6 and FIG. 7, each of the spaced ribs **40** has a tapered foot **48** which tapers outwardly into the lacer bar **42**. Each tapered foot **48** progressively tapers outwardly into the lacer bar **42**. As will be appreciated in symmetry, the first lacer bar **38** may take a similar form to the second lacer bar **42**, as shown in FIG. 6 and FIG. 7.

(90) Each rib **40** may be bent at the tapered foot **48** such that the lacer bar **42** is tilted out of a plane of the ribs **40** (see FIG. 5). In the particular example shown in the drawings, each of the ribs **40** is angled at an acute angle relative to the first plate **22** (that is, an outside angle between the ribs **40** and the horizontal is an acute angle), and the second lacer bar **42** is tilted to be substantially perpendicular to the first plate **22**. Similarly, the first lacer bar **38** is also tilted to be substantially perpendicular to the first plate **22**.

(91) Accordingly, as will be appreciated from the above, this aspect relates to: A continuous sheet metal studding rail—or lacer bar—to anchor the joint evenly into the concrete components. More consistent anchorage along the armoured plate joint may be achieved with this arrangement. Large cut-outs to allow adequate concrete and aggregate flow around anchor points and under joint plates. Folded through anchor point to provide better pull-out resistance. That is, the arrangement requires the fold to un-bend before the anchor can pull out. This removes a sheet metal blade nature of anchorage. Fold on end of anchor points is connected between points by a sheet metal lacer bar—this ties anchorage at each stud into the neighbouring points, increasing pull out resistance. The lacer bar fold adds stiffness and rigidity to the entire rail length. Cut-outs are broken up along the rail length with the cut-outs continuing around the fold. This potentially removes a crack-inducing nature of a straight edge in the slab. Additional wave formation along the straight edge between anchor points increases the surface area of the bottom of the cut-out giving better anchorage.

3. Anti-Skew Stake Bracket

(92) Turning to FIGS. 8, 9 and 42 to 49, there is also shown a joint edge protection apparatus **10** being supported by an anti-skew stake bracket **50**. Advantageously, the bracket **50** has mirrored angled legs which provide stronger support for heavier joints, achieved by the arc of movement of the legs.

(93) More specifically, as will be appreciated from the above, the joint edge protection apparatus **10** provides an armoured joint for protecting an edge of the first component **12** formed of settable material and an edge of the second component **14** formed of settable material at the joint **16**. The apparatus **10** includes the first anchorage part **18** for anchoring to the first component **12** and the second anchorage part **20** for anchoring to the second component **14**. The apparatus **10** also

includes the first plate **22** coupled to the first anchorage part **18** and the second plate **24** coupled to the second anchorage part **20**. The first plate **22** defines the first abutment surface **26** in the form of a first edge and the second plate **24** defines the second abutment surface **28** in the form of a second edge. The first edge **26** and the second edge **28** are correspondingly shaped to facilitate bringing together of the first edge **26** and the second edge **28**. In particular, the second anchorage part **20** is adapted to be movable relative to the first anchorage part **18** from a close configuration (see FIG. **32**) in which the second edge **28** is brought together with the first edge **26** to a spaced configuration (see FIG. **30**) in which the second edge **28** is spaced relative to the first edge **26**.

(94) The first anchorage part **18** or the second anchorage part **20** has a support section **52**, the armoured joint including the bracket **50** for supporting the armoured joint relative to a ground surface. The bracket **50** comprises an angled upper leg **54** and an angled lower leg **56**, the bracket **50** being fixed to the support section **52** by the angled upper leg **54** and the angled lower leg **56**. With reference to FIG. **9**, the angled upper leg **54** is fixed to the support section **52** to extend downwardly from the support section **52** at a first angle **58**, and the angled lower leg **56** is fixed to the support section **52** to extend upwardly from the support section **52** at a second angle **60** of the same magnitude as the first angle **58**.

(95) A distal end **62** of the upper leg **54** is fixed relative to a distal end **64** of the lower leg **56**. The distal end **62** of the upper leg **54** may be connected to the distal end **64** of the lower leg **56** by way of an intermediate portion as shown in FIG. **8**, or, alternatively, may be directly connected as shown in FIG. **9**. The upper leg **54** may be in the form of a straight part and the lower leg **56** may be in the form of a straight part.

(96) As shown in FIGS. **9** and **10**, the upper leg **54** may be provided with an aperture **66** for receiving a support stake **68**, for supporting the armoured joint relative to a ground surface, and the lower leg **56** may be provided with an aperture **70** for receiving the support stake **68**. The aperture **66** of the upper leg **54** and the aperture **70** of the lower leg **56** are arranged to receive the support stake **68** with the support stake **68** in a substantially perpendicular orientation relative to a plane of the first plate **22**. In other words, the support stake **68** may be substantially vertical whereas the first plate **22** is substantially horizontal.

(97) Turning to FIG. **10**, the apertures **66**, **70** and the support stake **68** are arranged to provide a sliding condition (see left-hand side of FIG. **10**) in which the stake **68** is able to be slid relative to the bracket **50** and a locked condition (the right-hand side of FIG. **10**) in which the stake **68** is locked against sliding relative to the bracket **50**. This may be achieved, as shown, by configuring the apertures **66**, **70** each as an elongated slot, with the stake **68** having a cross-section with parallel straight sides. In this way, the stake **68** is rotated about its longitudinal axis relative to the bracket **50** between the sliding condition and the locked condition.

(98) The upper leg **54** may meet the lower leg **56** at a bent portion of the bracket **50**, as shown in FIG. **9**. Alternatively, the upper leg **54** may meet the lower leg **56** at an intermediate vertical section between the upper leg **54** and the lower leg **56**. The bracket **50** may be symmetrical in a horizontal central plane.

(99) There may also be provided the armoured joint together with the stake in an assembly. In other words, there may be provided an assembly including an armoured joint as described above, in combination with a stake, wherein the stake extends through the upper leg and the lower leg.

(100) As shown clearly in FIG. **10**, the stake **68** is non-circular and the aperture **66**, **70** in each of the upper leg **54** and lower leg **56** is non-circular. In this way, the stake **68** is able to be rotated relative to the bracket **50** between a sliding condition, in which the stake **68** is able to be slid relative to the bracket **50**, and a locked condition, in which the stake **68** is locked against sliding relative to the bracket **50**.

(101) The first anchorage part **18** may include the elongated angled anchorage lacer bar **38**, the elongated angled anchorage lacer bar **38** being supported by a series of spaced ribs **40** and the lacer bar **38** being tilted out of the plane of the ribs **40**.

(102) The first anchorage part **18** may define the support surface **30** to support the second plate **24** as the second anchorage part **20** is moved between the close configuration and the spaced configuration. In the close configuration, an interface between the first edge **26** and the second edge **28** is offset relative to the joint **16** between the first component **12** and the second component **14** such that the interface of the first edge **26** and the second edge **28** is positioned above (and supported by) the support surface **30**.

(103) Each of the apertures **66**, **70** may be in the shape of a slot (see FIG. **10**), and the stake **68** may have a cross-sectional shape having opposed parallel flat sides connected at either end by a round portion.

(104) Accordingly, as will be appreciated from the above, this aspect relates to: Mirrored angled legs **54**, **56** of the stake bracket **50** provide stronger support for heavier joints. They resist skewing under weight by requiring the angled leg to overcome the mirrored angle of the opposing leg of the bracket **50** before skewing. Angled nature of bracket **50** moves fixing points on separation plate both higher (on top) and lower (on bottom) to help brace the joint where it is required. Stake brackets **50** have slots **66**, **70** which work with twist-and-lock stakes **68** for joint height adjustment, levelling and lock-off.

4. Floating Cover Plate System on Intersection

(105) With reference to FIGS. **11** to **15** and FIGS. **50** to **60**, there is disclosed an edge protection system **72** having a floating cover plate system on an intersection. Advantageously, the floating cover plate system provides a centralised cover plate which allows concrete slab sections at the intersection to open away from the cover plate, leaving the cover plate fixed in place.

(106) More specifically, there is shown an edge protection system **72** including a first expandable armoured joint **74** to protect a first joint **76** extending in a first direction, a second expandable armoured joint **78** to protect a second joint **80** extending in a second direction and an intersection module **82** including a cover plate **84** located at an intersection **86** of the first expandable armoured joint **74** and the second expandable armoured joint **76**. The first expandable armoured joint **74** and the second expandable armoured joint **78** may each be in the form of a joint edge protection apparatus **10** as described above.

(107) The first expandable armoured joint **74** includes a first pair of plates **88** arranged to be moved apart to open a crevice **90** between the plates in response to expansion of the first joint **76**, and the second expandable armoured joint **78** includes a second pair of plates **92** arranged to be moved apart to open a crevice **94** between the plates **92** in response to expansion of the second joint **80**. Each of the first pair of plates **88** has a wavy edge **96**, the wavy edges **96** being brought together in a contracted condition of the first expandable armoured joint **74**. Each of the second pair of plates **92** also has a wavy edge **96**, the wavy edges **96** being brought together in a contracted condition of the second expandable armoured joint **78**.

(108) The cover plate **84** is removable from a remainder of the intersection module **82**.

(109) The edge protection system **72** includes an anchored support **98** for supporting the intersection module **82** relative to a ground surface. An upper support **100** of the intersection module **82** is adapted to receive the cover plate **84** fastened thereto. The anchored support **98** anchors the intersection module **82** in a fixed location relative to the ground surface during expansion of the first expandable armoured joint **74** and the second expandable armoured joint **78**.

(110) In the example shown, the first joint **76** is a joint between concrete slab sections **102** and the second joint **80** is also a joint between concrete slab sections **102**. The cover plate **84** is a load supporting member being braced by each slab section **102** when the slab sections **102** move through slab shrinkage. In particular, it is typical for the slab sections **102** to shrink during drying of the concrete. More specifically, the cover plate **84** is a load supporting member being braced by each slab section **102** when the slab sections **102** move through slab shrinkage with each slab moving up to 20 mm. This support may be achieved by way of the intersection module **82** having a separate anchorage part **104** for each of the separate slab sections **102**, such that each anchorage

part **104** is cast into a respective one of the slab sections **102**. In turn, the anchorage parts **104** are vertically supported by a central lower shoulder **106** and a central upper shoulder **108** of the intersection module **82**.

(111) The intersection module **82** includes a central support column **110**, the central support column **110** having an upper support plate (in the form of central upper shoulder **108**) and a lower anchor plate (in the form of central lower shoulder **106**), the cover plate **84** being fastened to the upper support plate **108** so as to be connected to the central support column **110** and the lower anchor plate **106** to remain vertically coupled to the concrete slab sections **102**.

(112) The edge protection system **72** includes a stake **112** which is inserted through the central support column **110** for supporting the intersection module **82** relative to the ground surface. The upper support plate (central upper shoulder **108**) may be in the form of an upper cleat plate which is spaced vertically from the lower anchor plate (central lower shoulder **106**).

(113) The stake **112** may be in the form of a star picket. The stake **112** may be arranged to prevent the central support column **110** from rotating relative to the ground surface and from translational movement relative to the ground surface, as depicted by arrows in FIGS. **14** and **15**. The cleat plate **108** and the lower anchor plate **106** restrict movement of the star picket angularly at spaced locations of the central support column **110**.

(114) In the example shown in the drawings, the first direction is not parallel to the second direction such that the first joint **76** is not parallel to the second joint **80**. More specifically, in the example shown in the drawings, the first direction is perpendicular to the second direction such that the first joint **76** is perpendicular to the second joint **80**.

(115) Accordingly, as will be appreciated from the above, this aspect relates to: A centralised cover plate **84** which allows the slab sections **102** at the intersection **86** to open away from the cover plate **84**, leaving the cover plate **84** fixed in place. The cover plate **84** is load supporting, being braced by each slab section **102** when the slab sections **102** move through slab shrinkage up to 20 mm.

Anchor plate is fixed down without studs, using its connection to the central support column **110** and bottom anchor plate **106** to remain fixed to the concrete slab. The top cover plate **84** can be removed, and the star picket **112** can be hammered down the central column **110** through the guide holes in the top cleat plate **108** and the bottom anchor plate **106** acting like an axis to fix and support the top plate assembly. The star picket **112** can be hammered flush with the top cleat plate **108** before replacing the top cover plate above to cover. The star picket **112** prevents the central assembly from rotating and fixes it laterally in both 'X' and 'Y' directions. The guides at the cleat plate (top) **108** and anchor plate (bottom) **106** restrict movement against the star picket **112** angularly at opposite ends of the assembly.

5. Intersection Continuous Perimeter Joint Line

(116) With reference to FIGS. **16** to **19** and FIGS. **61** to **64**, there is shown an edge protection system **72** having an intersection continuous perimeter joint line **114**. Advantageously, this feature results in the joint line circling a perimeter of the centralised cover plate **84** to the next joint run rather than continuing directly across the intersection module **82** meaning that, no matter where infill lengths of the wavy plates **88**, **92** are cut, they will connect to the active joint line at the intersection module **82**.

(117) More specifically, as shown in the drawings, there is depicted an edge protection system **72** including a first expandable armoured joint **74** to protect a first joint **76** extending in a first direction and a second expandable armoured joint **78** to protect a second joint **80** extending in a second direction. The edge protection system **72** also includes an intersection module **82** at an intersection **86** of the first expandable armoured joint **74** and the second expandable armoured joint **78**. The first expandable armoured joint **74** has a first joint line **116** and the second expandable armoured joint **78** has a second joint line **118**. The intersection module **82** provides a perimeter joint line **120** such that there is a continuous joint line including the first joint line **116**, the perimeter joint line **120** and the second joint line **118**.

(118) The intersection module **82** includes the cover plate **84**, and the continuous joint line extends at least partially around a perimeter of the cover plate **84** between the first joint line **116** and the second joint line **118**.

(119) The first joint line **116** has a generally wavy form and the second joint line **118** also has a generally wavy form. The cover plate **84** is arranged such that, regardless of where lengths of the wavy first and second plate pairs **88**, **92** are cut, the wavy first joint line **116** and the wavy second joint line **118** will connect to the active joint line of the intersection module **82**. In one form, the cover plate **84** is arranged to ensure that joint lines are matched to standard joint runs.

(120) As will be appreciated by those skilled in the art, joint openings at the perimeter of the cover plate **84** are halved in thickness when used in a four-way intersection configuration, as shown in FIG. **17**. In particular, a joint gap may be split up on either side of the cover plate **84**. The edge protection system **72** may also be used at a three-way intersection configuration as shown in FIG. **18** or a two-way intersection configuration as shown in FIG. **19**.

(121) Accordingly, as will be appreciated from the above, this aspect relates to: The joint line does not continue directly across the intersection module, it instead circles the perimeter of a centralised cover plate **84** to the next joint run. A perimeter joint line means that no matter where infill lengths of the wavy plates **88**, **92** are cut, they will connect to the active joint line of the intersection module **82**. Joint lines **116**, **118** are never mismatched to standard joint runs. Joint gap openings at the perimeter of the central plate **84** are halved when used in 4-way intersection configuration (most common). The joint gap is split up on either side of the central plate **84**.

6. Joint Orientation Marker on Intersection

(122) With reference to FIGS. **20** to **25** and FIGS. **65** to **69**, there is also disclosed an edge protection system **72** having a joint orientation marker **122** to ensure correct orientation of the intersection module **82**, rotationally about a central axis of the intersection module **82**.

(123) In particular, the edge protection system **72** includes a first expandable armoured joint **74** to protect a first joint **76** extending in a first direction and a second expandable armoured joint **78** to protect a second joint **80** extending in a second direction. The edge protection system **72** also includes an intersection module **82** at an intersection **86** of the first expandable armoured joint **74** and the second expandable armoured joint **78**. The intersection module **82** has an indicator **122** to enable a user to ensure correct orientation of the intersection module **82**.

(124) The intersection module **82** includes a cover plate **84** which is generally symmetrical in shape. In particular, as shown in the drawings, the cover plate **84** is generally octagonal in shape.

(125) The indicator **122** may be in the form of a discreet marking. In one particular form, the indicator **122** may be in the form of a small hole in the cover plate **84**. The indicator **122** is provided to enable a user to orientate joints during installation on-site in a common direction to ensure joint lines match.

(126) This is important as although the cover plate **84** itself appears to be symmetrical from above, the components of the intersection module **82** below the cover plate **84** are not symmetrical. Specifically, it is important that the anchorage parts **104** of the intersection module **82** align with the joints of the concrete slab sections **102**, as well as with the anchorage parts **104** of the other intersection modules **82** within the edge protection system **72**.

(127) In a method of installation, the indicator **122** is positioned in one of four rotational orientations on a first intersection module **82** on-site depending upon a first pour location. Subsequent intersection modules **82** within the same edge protection system **72** (see FIG. **21**) are placed each with the respective indicator **122** oriented in the same direction as for the first intersection module **82**.

(128) The intersection module **82** may be arranged to allow for two-way, three-way and four-way intersections to be formed without adjusting orientation of the intersection module **82**. FIG. **22** shows a four-way intersection, FIG. **23** shows a three-way intersection and FIG. **24** shows a two-way intersection.

(129) With reference to FIG. 25, the indicator **122** may be repeated on a plurality of assembly pieces of the intersection module **82** to assist with orientation of star picket guides to a common orientation. In particular, as shown in FIG. 25, the indicator **122** may be repeated on an upper support plate **108** and a lower support plate **106** of a support column **110** of the intersection module **82**.

(130) The first expandable armoured joint **74** may have a first joint line **116**, and the second expandable armoured joint **78** may have a second joint line **118**. The intersection module **82** may provide a perimeter joint line **120** such that there is a continuous joint line including the first joint line **116**, the perimeter joint line **120** and the second joint line **118**.

(131) Accordingly, as will be appreciated from the above, this aspect relates to: A joint orientation marker **122** in the form of a small hole in the top cover plate **84** which acts as a positioning marker to orientate all joints during installation onsite in the same direction, ensuring joint lines match up. The small hole is to be positioned in one of four orientations on a first intersection onsite depending upon first pour location. All subsequent intersections for the project are to be place with the respective hole rotationally oriented in the same direction. Module nature on intersection allows for 2-way, 3-way and 4-way intersection to be formed without adjusting intersection orientation. Hole is repeated on all central top plate assembly pieces to help orientate star picket guides to the same orientation.

(132) Advantageously, the applicant has identified that examples of the present disclosure may serve to prolong the serviceability of the floor (working surface). Forklift wheels are fully supported by the “wave” plate design to a joint width opening of 20 mm. Modular design intersection provides a fast, effective and intuitive set up of two, three and four way intersections, significantly mitigating the risk of restraint that leads to uncontrolled concrete cracking and spalling.

(133) FIG. 70 shows an example of a joint edge protection apparatus **10** having a wave profile for providing a capability for extra lateral movement. More specifically, the wave form of one plate **22** is deliberately mismatched relative to the wave form of the other plate **24** so as to facilitate lateral movement.

(134) In particular, FIG. 70 shows a joint edge protection apparatus **10** for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint. The apparatus **10** includes a first anchorage part for anchoring within the first component and a second anchorage part for anchoring within the second component, the first anchorage part being provided with a first plate **22**. The second anchorage part is provided with a second plate **24**. The first plate **22** defines a first interface surface **26** and the second plate **24** defines a second interface surface **28**. The first interface surface **26** and the second interface surface **28** are shaped to facilitate abutment of at least a portion of the second interface surface **28** against the first interface surface **26**. The second anchorage part is adapted to be movable relative to the first anchorage part from an abutting configuration in which at least a portion of the second interface surface **28** is in abutment with the first interface surface **26**, to a spaced configuration in which the second interface surface **28** is spaced relative to the first interface surface **26**. The first interface surface **26** and the second interface surface **28** are each shaped with a wave shape, wherein the wave shape of the first interface surface **26** is mismatched to the wave shape of the second interface surface **28** to facilitate periodic abutment of the second interface surface **28** against the first interface surface **26** in the abutting configuration. In other words, the wave shapes are mismatched so as to ensure gaps between the points/regions of periodic abutment.

(135) As can be seen in FIGS. 70a, 70b and 70c, each of these representations shows the joint edge protection apparatus **10** in the abutting configuration. FIG. 70a shows a default position in which the first plate **22** and the second plate **24** are laterally aligned such that points or regions of contact/abutment are at each peak and trough of the wave forms. The mismatching of the waveforms ensures in this default position that, between each peak and trough there is a gap

between the first interface surface **26** and the second interface surface **28**. FIG. **70b** shows a configuration in which the first plate **22** is moved 2 mm downwardly relative to the second plate **24** in an arrangement in which slopes of the waveforms come together in a nested arrangement to form an S-shaped portion of abutment which extends from a peak of the wave form of the first interface surface **26** to a trough of the wave form of the first interface surface **26**. Similarly, FIG. **70c** shows a configuration in which the first plate **22** is moved 2 mm upwardly relative to the second plate **24** in an arrangement in which the slopes of the waveforms come together in a nested arrangement to form an S-shaped portion of abutment which extends from a peak of the waveform of the first interface surface **26** to a trough of the waveform of the first interface surface **26**.

(136) As will be appreciated, in each of the configurations shown in FIGS. **70a**, **70b** and **70c**, there is periodic abutment in the abutting configuration in contrast to the arrangement shown in FIG. **22** in which the waveforms are matched such that the abutment there is continuous.

(137) Returning to FIGS. **70a** to **70c**, advantageously, the joint top plates **22**, **24** have a mismatched full length waved tooth profile to provide low impact joint transition while giving extra lateral movement accommodation during slab curing. An additional gap has been allowed either side of the teeth to allow lateral movement at 0 mm joint gap if required of up to 2 mm (in either direction). This additional gap is shown in FIG. **70a** and is due to the mismatching of the wave forms. The teeth have tapered (45° sides to provide 1:1 lateral movement versus joint opening, the additional 2 mm gap providing extra allowance for high shrinkage parts of the slab (corners) and rectangular slabs.

(138) As shown in FIGS. **71a** to **71d**, the first plate **22** and second plate **24** may also be provided with predefined gaps **124** of 4 mm between the plates **22**, **24** at joining lengths to allow joint lateral movement within binding during slab shrinkage. The arrangement shown provides adjustment capability when connecting joints while maintaining a minimum 2 mm predefined gap.

(139) Accordingly, FIGS. **71a** to **71d** show another example of a joint edge protection apparatus **10** having deliberately mismatched waves as well as predefined gaps **124** to facilitate lateral movement. FIG. **71a** shows the first plate **22** and the second plate **24** in a default position with a predefined gap **124** of 4 mm in place. FIG. **71b** shows the first plate **22** moved upwardly relative to the second plate **24**, with the predefined gaps **124** of 4 mm still in place. FIG. **71c** shows the predefined gap **124** reduced to accommodate upward movement of one second plate **24** relative to the first plate **22** as well as relative to an adjacent second plate **24**. FIG. **71d** shows a predefined gap **124** increased to accommodate downward movement of one second plate **24** relative to the first plate **22** as well as relative to an adjacent second plate **24**.

(140) The described construction has been advanced merely by way of example and many modifications and variations may be made without departing from the spirit and scope of the present disclosure, which includes every novel feature and combination of features herein disclosed. In particular, the applicant has determined that other modifications may include one or more of the following: cutting of bottom sheet metal anchor above dowel plates and sleeves to allow better concrete compaction around dowels; added twist and lock stake receptacles on an opposite side of the joint to stake brackets to allow joint levelling during setup without welding; removed section of separation plate at top section at an offset end. This can be arranged to allow direct connection between top section pieces to prevent stepping of joint lengths; changing all clamping bolt nuts to wing nuts to aid in removal after pouring (if required); increased adjustment capability to offset clamping bolt by way of increased bolthole size; plug weld location under top plate change slots for fillet welds; and assembly bolthole (4 places) increase from 10.5 mm diameter to 11 mm diameter.

(141) Throughout this specification and the claims which follow, unless the context requires otherwise, the word “comprise”, and variations such as “comprises” and “comprising”, will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

(142) The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge.

LIST OF REFERENCE NUMERALS

(143) **10** joint edge protection apparatus **12** first component **14** second component **16** joint **18** first anchorage part **20** second anchorage part **22** first plate **24** second plate **26** first abutment surface **28** second abutment surface **30** support surface **32** gap **34** well **36** joint material **38** first lacer bar **40** spaced ribs **42** second lacer bar **44** dowel **46** apex **48** tapered foot **50** bracket **52** support section **54** upper leg **56** lower leg **58** first angle **60** second angle **62** distal end of the upper leg **64** distal end of the lower leg **66** aperture in upper leg **68** stake **70** aperture in lower leg **72** edge protection system **74** first expandable armoured joint **76** first joint **78** second expandable armoured joint **80** second joint **82** intersection module **84** cover plate **86** intersection **88** first pair of plates **90** first crevice **92** second pair of plates **94** second crevice **96** wavy edge **98** anchored support **100** upper support **102** concrete slab sections **104** anchorage part **106** central lower shoulder **108** central upper shoulder **110** central support column **112** stake **114** intersection continuous perimeter joint line **116** first joint line **118** second joint line **120** perimeter joint line **122** joint orientation marker **124** predefined gap

Claims

1. An armoured joint for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint, the armoured joint comprising: a first anchorage part configured to be anchored to the first component; a second anchorage part configured to be anchored to the second component; a first plate coupled to the first anchorage part, the first plate defining a first edge; a second plate coupled to the second anchorage part, the second plate defining a second edge; and a bracket configured to support the armoured joint relative to a ground surface, the bracket including an angled upper leg and an angled lower leg, wherein the first edge and the second edge are shaped to facilitate bringing together of the first edge and the second edge, wherein the second anchorage part is movable relative to the first anchorage part from a close configuration in which the second edge is brought together with the first edge to a spaced configuration in which the second edge is spaced relative to the first edge, wherein the first anchorage part or the second anchorage part has a support section, wherein the bracket is fixed to the support section by the angled upper leg and the angled lower leg, the angled upper leg being fixed to the support section to extend downwardly from the support section at a first angle and the angled lower leg being fixed to the support section to extend upwardly from the support section at a second angle of the same magnitude as the first angle.
2. The armoured joint of claim 1, wherein a distal end of the upper leg is fixed relative to a distal end of the lower leg.
3. The armoured joint of claim 1, wherein the upper leg is in the form of a first straight part and the lower leg is in the form of a second straight part.
4. The armoured joint of claim 1, wherein the upper leg defines an aperture configured to receive a support stake to support the armoured joint relative to a ground surface, and the lower leg defines an aperture configured to receive the support stake.
5. The armoured joint of claim 4, wherein the aperture of the upper leg and the aperture of the lower leg are arranged to receive the support stake with the support stake in a substantially perpendicular orientation relative to a plane of the first plate.
6. The armoured joint as of claim 5, wherein the apertures and the support stake are arranged to provide a sliding condition in which the support stake is able to be slide relative to the bracket and a locked condition in which the support stake is locked against sliding relative to the bracket, wherein the support stake is rotatable about its longitudinal axis relative to the bracket between the

sliding condition and the locked condition.

7. The armoured joint of claim 1, wherein the upper leg meets the lower leg at a bent portion of the bracket.
 8. The armoured joint of claim 1, wherein the upper leg meets the lower leg at an intermediate vertical section between the upper leg and the lower leg.
 9. The armoured joint of claim 1, wherein the bracket is symmetrical in a horizontal central plane.
 10. The armoured joint of claim 1, wherein the first anchorage part includes an elongated angled anchorage lacer bar, the elongated angled anchorage lacer bar being supported by a series of spaced ribs and the elongated angled anchorage lacer bar being tilted out of a plane of the ribs.
 11. The armoured joint of claim 1, wherein the first anchorage part defines a support surface configured to support the second plate as the second anchorage part is moved between the close configuration and the spaced configuration, and wherein, in the close configuration an interface between the first edge and the second edge is offset relative to a joint between the first component and the second component such that the interface of the first edge and the second edge is positioned above the support surface.
 12. An assembly comprising: an armoured joint for protecting an edge of a first component formed of settable material and an edge of a second component formed of settable material at a joint, the armoured joint comprising: a first anchorage part configured to be anchored to the first component; a second anchorage part configured to be anchored to the second component; a first plate coupled to the first anchorage part, the first plate defining a first edge; a second plate coupled to the second anchorage part, the second plate defining a second edge; and a bracket configured to support the armoured joint relative to a ground surface, the bracket including an angled upper leg and an angled lower leg, wherein the first edge and the second edge are shaped to facilitate bringing together of the first edge and the second edge, wherein the second anchorage part is movable relative to the first anchorage part from a close configuration in which the second edge is brought together with the first edge to a spaced configuration in which the second edge is spaced relative to the first edge, wherein the first anchorage part or the second anchorage part has a support section, wherein the bracket is fixed to the support section by the angled upper leg and the angled lower leg, the angled upper leg being fixed to the support section to extend downwardly from the support section at a first angle and the angled lower leg being fixed to the support section to extend upwardly from the support section at a second angle of the same magnitude as the first angle; and a stake, wherein the stake is extendable through the upper leg and the lower leg.
 13. The assembly of claim 12, wherein the stake is non-circular and an aperture in each of the upper leg and lower leg is non-circular, such that the stake is able to be rotated relative to the bracket between a sliding condition, in which the stake is able to be slide relative to the bracket, and a locked condition, in which the stake is locked against sliding relative to the bracket.
 14. The assembly of claim 12, wherein each of the apertures is in the shape of a slot, and the stake has a cross-sectional shape having opposed parallel flat sides connected at either end by a round portion.
-