

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398917
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Aly; Amr Maher Abdellati et al.

Heat exchanger for HVAC system

Abstract

A heat exchanger for a heating, ventilation, and/or air conditioning (HVAC) system includes a plurality of tubes configured to direct a working fluid therethrough and defining a first section and a second section of the heat exchanger. The first section and the second section extend crosswise relative to one another. The heat exchanger also includes an end sheet coupled to an end of the first section. The end sheet includes a flange extending toward the second section.

Inventors: Aly; Amr Maher Abdellati (Wichita, KS), Cheng; Xianjin (Andover, KS), Morrow; Cole Brennan (Derby, KS), Romero; Elmer Wayne (Oxford, KS), Szczepanski; Stephen (Wichita, KS)

Applicant: Johnson Controls Tyco IP Holdings LLP (Milwaukee, WI)

Family ID: 1000008778042

Assignee: Johnson Controls Light Commercial IP GmbH (Neuhausen am Rheinfall, CH)

Appl. No.: 17/837298

Filed: June 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230400222 A1	Dec. 14, 2023

Publication Classification

Int. Cl.: F24F13/30 (20060101); F24F1/0067 (20190101); F24F13/20 (20060101); F24F13/22 (20060101); F28D1/047 (20060101); F28D21/00 (20060101)

U.S. Cl.:

CPC **F24F13/30** (20130101); **F24F1/0067** (20190201); **F24F13/20** (20130101); **F24F13/222** (20130101); **F28D1/0477** (20130101); F28D2021/0071 (20130101)

Field of Classification Search

CPC: F24F (13/30); F24F (13/20); F24F (13/222); F28D (1/0477); F28D (2021/0071)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4546820	12/1984	Whipple	165/77	F28D 1/0435
2022/0011010	12/2021	Silva	N/A	F24F 13/029
2023/0093227	12/2022	Chapin	62/291	F25B 39/02
2023/0152012	12/2022	Dong	62/159	F28F 9/26

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1597527	12/2010	EP	N/A

Primary Examiner: Fletcher; Jerry-Daryl

Assistant Examiner: Myers; Keith Stanley

Attorney, Agent or Firm: Fletcher Yoder, P.C.

Background/Summary

BACKGROUND

(1) This section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present disclosure and are described below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present disclosure. Accordingly, it should be noted that these statements are to be read in this light, and not as admissions of prior art.

(2) Heating, ventilation, and/or air conditioning (HVAC) systems are utilized in residential, commercial, and industrial environments to control environmental properties, such as temperature and humidity, for occupants of the respective environments. An HVAC system may control the environmental properties by conditioning a supply air flow delivered to the environment. For example, the HVAC system may include a heat exchanger configured to place the supply air flow in a heat exchange relationship with a working fluid (e.g., a refrigerant) of a vapor compression system to condition the supply air flow. It may be desirable to limit a physical footprint occupied by the heat exchanger. For example, reducing the physical footprint associated with the heat exchanger may increase efficient usage of space and/or facilitate ease of transportation of the heat exchanger.

SUMMARY

(3) A summary of certain embodiments disclosed herein is set forth below. It should be noted that these aspects are presented merely to provide the reader with a brief summary of these certain embodiments and that these aspects are not intended to limit the scope of this disclosure. Indeed,

this disclosure may encompass a variety of aspects that may not be set forth below.

(4) In one embodiment, a heat exchanger for a heating, ventilation, and/or air conditioning (HVAC) system includes a plurality of tubes configured to direct a working fluid therethrough and defining a first section and a second section of the heat exchanger. The first section and the second section extend crosswise relative to one another. The heat exchanger also includes an end sheet coupled to an end of the first section. The end sheet has a flange extending toward the second section.

(5) In one embodiment, a heat exchanger for a heating, ventilation, and/or air conditioning (HVAC) system includes a plurality of tubes configured to direct a working fluid therethrough. The plurality of tubes defines a first panel section, a second panel section, and an intermediate section extending between the first panel section and the second panel section, and the first panel section and the second panel section are configured to rotate relative to one another about the intermediate section. The heat exchanger also includes an end sheet coupled to the first panel section. The end sheet has a flange extending between the first panel section and the second panel section

(6) In one embodiment, a heat exchanger for a heating, ventilation, and/or air conditioning (HVAC) system includes a plurality of tubes configured to direct a working fluid therethrough, a first section having a first portion of the plurality of tubes, and a second section having a second portion of the plurality of tubes. The first section includes a first end sheet extending along a first direction of working fluid flow through the first portion of the plurality of tubes, the first end sheet includes a first flange, the second section includes a second end sheet extending along a second direction of working fluid flow through the second portion of the plurality of tubes, the second end sheet includes a second flange, and the first flange and the second flange extend toward one another

Description

DESCRIPTION OF DRAWINGS

(1) Various aspects of this disclosure may be better understood upon reading the following detailed description and upon reference to the drawings in which:

(2) FIG. 1 is a perspective view of an embodiment of a heating, ventilation, and/or air conditioning (HVAC) system for environmental management that may employ one or more HVAC units, in accordance with an aspect of the present disclosure;

(3) FIG. 2 is a perspective view of an embodiment of a packaged HVAC unit that may be used in the HVAC system of FIG. 1, in accordance with an aspect of the present disclosure;

(4) FIG. 3 is a cutaway perspective view of an embodiment of a residential, split HVAC system, in accordance with an aspect of the present disclosure;

(5) FIG. 4 is a schematic of an embodiment of a vapor compression system that can be used in any of the systems of FIGS. 1-3, in accordance with an aspect of the present disclosure;

(6) FIG. 5 is a perspective view of an embodiment of a heat exchanger for an HVAC system, in accordance with an aspect of the present disclosure;

(7) FIG. 6 is a front view of an embodiment of a heat exchanger for an HVAC system, in accordance with an aspect of the present disclosure;

(8) FIG. 7 is a rear view of an embodiment of a heat exchanger for an HVAC system, in accordance with an aspect of the present disclosure;

(9) FIG. 8 is a front view of an embodiment of a heat exchanger for an HVAC system, illustrating the heat exchanger in a compact configuration, in accordance with an aspect of the present disclosure;

(10) FIG. 9 is a detailed perspective view of an embodiment of a heat exchanger for an HVAC system, in accordance with an aspect of the present disclosure; and

(11) FIG. 10 is a perspective view of an embodiment of a heat exchanger for an HVAC system, in accordance with an aspect of the present disclosure.

DETAILED DESCRIPTION

(12) One or more specific embodiments will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be noted that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be noted that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

(13) When introducing elements of various embodiments of the present disclosure, the articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be noted that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features.

(14) The present disclosure is directed to a heating, ventilation, and/or air conditioning (HVAC) system. The HVAC system may be configured to condition (e.g., heat, cool) an air flow and deliver the conditioned air flow to a space, such as a room, to condition the space. For example, the HVAC system may include a heat exchanger configured to place the air flow in a heat exchange relationship with a working fluid, such as a refrigerant, to change a temperature of the air flow. The air flow may then be delivered to the space as a supply air flow to adjust the temperature of the space, such as toward a target or set point temperature of the space.

(15) Existing or conventional heat exchangers may occupy an undesirable (e.g., large) physical footprint. As an example, a heat exchanger may have a shape, a geometry, or other features that increase a space or volume occupied by the heat exchanger. Thus, the heat exchanger may reduce efficient usage of space, such as a space within an enclosure of an HVAC system, a transportation space, and/or a storage space. As a result, certain operations or services, such as installation, transportation, and/or storage of the heat exchanger, may be difficult to perform.

(16) Thus, it is presently recognized that limiting the physical footprint of the heat exchanger may improve performance of various operations related to the heat exchanger. Accordingly, embodiments of the present disclosure are directed to a heat exchanger that includes features for limiting the space occupied by the heat exchanger. For example, the heat exchanger includes tubes through which a working fluid may flow. The tubes may define a first section of the heat exchanger and a second section of the heat exchanger. A first end sheet may be coupled to the first section, and a second end sheet may be coupled to the second section. For instance, the first end sheet may extend along a direction of flow of working fluid through the tubes in the first section, and the second end sheet may extend along a direction of flow of working fluid through the tubes in the second section. The first end sheet and the second end sheet may be configured to couple to a plate. As an example, the plate may block undesirable air flow out of an area between the first section and the second section of the heat exchanger, thereby increasing an efficiency of the heat exchanger to transfer heat between the air flow and working fluid via air flow across the tubes. The first end sheet may include a first flange, the second end sheet may include a second flange, and the plate may be configured to couple to the first end sheet via the first flange and to the second end sheet via the second flange. The first flange and the second flange may extend toward one another, such as toward a space or area formed between the first section and the second section. Thus, the first flange and the second flange may not increase a dimension or size of an outer boundary associated with the heat exchanger (e.g., surrounding a perimeter of the sections of the heat exchanger). In this manner, the flanges enable the heat exchanger to couple to the plate while limiting the physical

footprint occupied by the heat exchanger. Thus, the space in which the heat exchanger is disposed may be efficiently utilized.

(17) In certain embodiments, the first section and the second section may be configured to move (e.g., rotate) relative to one another. For example, the first section and the second section may be configured to move toward one another to transition the heat exchanger to a compact configuration, and the first section and the second section may be configured to move away from one another to transition the heat exchanger to an expanded configuration. Additionally, a first notch may be formed in the first end sheet and a second notch may be formed in the second end sheet. The first notch may be configured to receive the second flange of the second end sheet, and the second notch may be configured to receive the first flange of the first end sheet in the compact configuration. As an example, the first notch may enable the second flange of the second end sheet to overlap with the first section, and the second notch may enable the first flange of the first end sheet to overlap with the second section. Thus, the notches may block the first flange from contacting the second end sheet and/or the second flange from contacting the first end sheet in a manner that would limit or block movement of the first section and the second section toward one another to transition the heat exchanger to the compact configuration. Accordingly, the notches may enable a desirable range of movement of the first section and the second section of the heat exchanger (e.g., to enable transition to the compact configuration).

(18) As used herein, the terms “approximately,” “generally,” “substantially,” and so forth, are intended to convey that the property value being described may be within a relatively small range of the property value, as those of ordinary skill would understand. For example, when a property value is described as being “approximately” equal to (or, for example, “substantially similar” to) a given value, this is intended to convey that the property value may be within $\pm 5\%$, within $\pm 4\%$, within $\pm 3\%$, within $\pm 2\%$, within $\pm 1\%$, or even closer, of the given value. Similarly, when a given feature is described as being “substantially parallel” to another feature, “generally perpendicular” to another feature, and so forth, this is intended to convey that the given feature is within $\pm 5\%$, within $\pm 4\%$, within $\pm 3\%$, within $\pm 2\%$, within $\pm 1\%$, or even closer, to having the described nature, such as being parallel to another feature, being perpendicular to another feature, and so forth. Mathematical terms, such as “parallel” and “perpendicular,” should not be rigidly interpreted in a strict mathematical sense, but should instead be interpreted as one of ordinary skill in the art would interpret such terms. For example, one of ordinary skill in the art would understand that two lines that are substantially parallel to each other are parallel to a substantial degree, but may have minor deviation from exactly parallel.

(19) Turning now to the drawings, FIG. 1 illustrates an embodiment of a heating, ventilation, and/or air conditioning (HVAC) system for environmental management that may employ one or more HVAC units. As used herein, an HVAC system includes any number of components configured to enable regulation of parameters related to climate characteristics, such as temperature, humidity, air flow, pressure, air quality, and so forth. For example, an “HVAC system” as used herein is defined as conventionally understood and as further described herein. Components or parts of an “HVAC system” may include, but are not limited to, all, some of, or individual parts such as a heat exchanger, a heater, an air flow control device, such as a fan, a sensor configured to detect a climate characteristic or operating parameter, a filter, a control device configured to regulate operation of an HVAC system component, a component configured to enable regulation of climate characteristics, or a combination thereof. An “HVAC system” is a system configured to provide such functions as heating, cooling, ventilation, dehumidification, pressurization, refrigeration, filtration, or any combination thereof. The embodiments described herein may be utilized in a variety of applications to control climate characteristics, such as residential, commercial, industrial, transportation, or other applications where climate control is desired.

(20) In the illustrated embodiment, a building **10** is air conditioned by a system that includes an HVAC unit **12**. The building **10** may be a commercial structure or a residential structure. As shown,

the HVAC unit **12** is disposed on the roof of the building **10**; however, the HVAC unit **12** may be located in other equipment rooms or areas adjacent the building **10**. The HVAC unit **12** may be a single package unit containing other equipment, such as a blower, integrated air handler, and/or auxiliary heating unit. In other embodiments, the HVAC unit **12** may be part of a split HVAC system, such as the system shown in FIG. **3**, which includes an outdoor HVAC unit **58** and an indoor HVAC unit **56**.

(21) The HVAC unit **12** is an air cooled device that implements a refrigeration cycle to provide conditioned air to the building **10**. Specifically, the HVAC unit **12** may include one or more heat exchangers across which an air flow is passed to condition the air flow before the air flow is supplied to the building. In the illustrated embodiment, the HVAC unit **12** is a rooftop unit (RTU) that conditions a supply air stream, such as environmental air and/or a return air flow from the building **10**. After the HVAC unit **12** conditions the air, the air is supplied to the building **10** via ductwork **14** extending throughout the building **10** from the HVAC unit **12**. For example, the ductwork **14** may extend to various individual floors or other sections of the building **10**. In certain embodiments, the HVAC unit **12** may be a heat pump that provides both heating and cooling to the building with one refrigeration circuit configured to operate in different modes. In other embodiments, the HVAC unit **12** may include one or more refrigeration circuits for cooling an air stream and a furnace for heating the air stream.

(22) A control device **16**, one type of which may be a thermostat, may be used to designate the temperature of the conditioned air. The control device **16** also may be used to control the flow of air through the ductwork **14**. For example, the control device **16** may be used to regulate operation of one or more components of the HVAC unit **12** or other components, such as dampers and fans, within the building **10** that may control flow of air through and/or from the ductwork **14**. In some embodiments, other devices may be included in the system, such as pressure and/or temperature transducers or switches that sense the temperatures and pressures of the supply air, return air, and so forth. Moreover, the control device **16** may include computer systems that are integrated with or separate from other building control or monitoring systems, and even systems that are remote from the building **10**.

(23) FIG. **2** is a perspective view of an embodiment of the HVAC unit **12**. In the illustrated embodiment, the HVAC unit **12** is a single package unit that may include one or more independent refrigeration circuits and components that are tested, charged, wired, piped, and ready for installation. The HVAC unit **12** may provide a variety of heating and/or cooling functions, such as cooling only, heating only, cooling with electric heat, cooling with dehumidification, cooling with gas heat, or cooling with a heat pump. As described above, the HVAC unit **12** may directly cool and/or heat an air stream provided to the building **10** to condition a space in the building **10**.

(24) As shown in the illustrated embodiment of FIG. **2**, a cabinet **24** encloses the HVAC unit **12** and provides structural support and protection to the internal components from environmental and other contaminants. In some embodiments, the cabinet **24** may be constructed of galvanized steel and insulated with aluminum foil faced insulation. Rails **26** may be joined to the bottom perimeter of the cabinet **24** and provide a foundation for the HVAC unit **12**. In certain embodiments, the rails **26** may provide access for a forklift and/or overhead rigging to facilitate installation and/or removal of the HVAC unit **12**. In some embodiments, the rails **26** may fit onto “curbs” on the roof to enable the HVAC unit **12** to provide air to the ductwork **14** from the bottom of the HVAC unit **12** while blocking elements such as rain from leaking into the building **10**.

(25) The HVAC unit **12** includes heat exchangers **28** and **30** in fluid communication with one or more refrigeration circuits. Tubes within the heat exchangers **28** and **30** may circulate refrigerant, such as R-**410A**, through the heat exchangers **28** and **30**. The tubes may be of various types, such as multichannel tubes, conventional copper or aluminum tubing, and so forth. Together, the heat exchangers **28** and **30** may implement a thermal cycle in which the refrigerant undergoes phase changes and/or temperature changes as it flows through the heat exchangers **28** and **30** to produce

heated and/or cooled air. For example, the heat exchanger **28** may function as a condenser where heat is released from the refrigerant to ambient air, and the heat exchanger **30** may function as an evaporator where the refrigerant absorbs heat to cool an air stream. In other embodiments, the HVAC unit **12** may operate in a heat pump mode where the roles of the heat exchangers **28** and **30** may be reversed. That is, the heat exchanger **28** may function as an evaporator and the heat exchanger **30** may function as a condenser. In further embodiments, the HVAC unit **12** may include a furnace for heating the air stream that is supplied to the building **10**. While the illustrated embodiment of FIG. 2 shows the HVAC unit **12** having two of the heat exchangers **28** and **30**, in other embodiments, the HVAC unit **12** may include one heat exchanger or more than two heat exchangers.

(26) The heat exchanger **30** is located within a compartment **31** that separates the heat exchanger **30** from the heat exchanger **28**. Fans **32** draw air from the environment through the heat exchanger **28**. Air may be heated and/or cooled as the air flows through the heat exchanger **28** before being released back to the environment surrounding the HVAC unit **12**. A blower assembly **34**, powered by a motor **36**, draws air through the heat exchanger **30** to heat or cool the air. The heated or cooled air may be directed to the building **10** by the ductwork **14**, which may be connected to the HVAC unit **12**. Before flowing through the heat exchanger **30**, the conditioned air flows through one or more filters **38** that may remove particulates and contaminants from the air. In certain embodiments, the filters **38** may be disposed on the air intake side of the heat exchanger **30** to prevent contaminants from contacting the heat exchanger **30**.

(27) The HVAC unit **12** also may include other equipment for implementing the thermal cycle. Compressors **42** increase the pressure and temperature of the refrigerant before the refrigerant enters the heat exchanger **28**. The compressors **42** may be any suitable type of compressors, such as scroll compressors, rotary compressors, screw compressors, or reciprocating compressors. In some embodiments, the compressors **42** may include a pair of hermetic direct drive compressors arranged in a dual stage configuration **44**. However, in other embodiments, any number of the compressors **42** may be provided to achieve various stages of heating and/or cooling. Additional equipment and devices may be included in the HVAC unit **12**, such as a solid-core filter drier, a drain pan, a disconnect switch, an economizer, pressure switches, phase monitors, and humidity sensors, among other things.

(28) The HVAC unit **12** may receive power through a terminal block **46**. For example, a high voltage power source may be connected to the terminal block **46** to power the equipment. The operation of the HVAC unit **12** may be governed or regulated by a control board **48**. The control board **48** may include control circuitry connected to a thermostat, sensors, and alarms. One or more of these components may be referred to herein separately or collectively as the control device **16**. The control circuitry may be configured to control operation of the equipment, provide alarms, and monitor safety switches. Wiring **49** may connect the control board **48** and the terminal block **46** to the equipment of the HVAC unit **12**.

(29) FIG. 3 illustrates a residential heating and cooling system **50**, also in accordance with present techniques. The residential heating and cooling system **50** may provide heated and cooled air to a residential structure, as well as provide outside air for ventilation and provide improved indoor air quality (IAQ) through devices such as ultraviolet lights and air filters. In the illustrated embodiment, the residential heating and cooling system **50** is a split HVAC system. In general, a residence **52** conditioned by a split HVAC system may include refrigerant conduits **54** that operatively couple the indoor unit **56** to the outdoor unit **58**. The indoor unit **56** may be positioned in a utility room, an attic, a basement, and so forth. The outdoor unit **58** is typically situated adjacent to a side of residence **52** and is covered by a shroud to protect the system components and to prevent leaves and other debris or contaminants from entering the unit. The refrigerant conduits **54** transfer refrigerant between the indoor unit **56** and the outdoor unit **58**, typically transferring primarily liquid refrigerant in one direction and primarily vaporized refrigerant in an opposite

direction.

(30) When the system shown in FIG. 3 is operating as an air conditioner, a heat exchanger **60** in the outdoor unit **58** serves as a condenser for re-condensing vaporized refrigerant flowing from the indoor unit **56** to the outdoor unit **58** via one of the refrigerant conduits **54**. In these applications, a heat exchanger **62** of the indoor unit functions as an evaporator. Specifically, the heat exchanger **62** receives liquid refrigerant, which may be expanded by an expansion device, and evaporates the refrigerant before returning it to the outdoor unit **58**.

(31) The outdoor unit **58** draws environmental air through the heat exchanger **60** using a fan **64** and expels the air above the outdoor unit **58**. When operating as an air conditioner, the air is heated by the heat exchanger **60** within the outdoor unit **58** and exits the unit at a temperature higher than it entered. The indoor unit **56** includes a blower or fan **66** that directs air through or across the indoor heat exchanger **62**, where the air is cooled when the system is operating in air conditioning mode. Thereafter, the air is passed through ductwork **68** that directs the air to the residence **52**. The overall system operates to maintain a desired temperature as set by a system controller. When the temperature sensed inside the residence **52** is higher than the set point on the thermostat, or the set point plus a small amount, the residential heating and cooling system **50** may become operative to refrigerate additional air for circulation through the residence **52**. When the temperature reaches the set point, or the set point minus a small amount, the residential heating and cooling system **50** may stop the refrigeration cycle temporarily.

(32) The residential heating and cooling system **50** may also operate as a heat pump. When operating as a heat pump, the roles of heat exchangers **60** and **62** are reversed. That is, the heat exchanger **60** of the outdoor unit **58** will serve as an evaporator to evaporate refrigerant and thereby cool air entering the outdoor unit **58** as the air passes over the outdoor heat exchanger **60**. The indoor heat exchanger **62** will receive a stream of air blown over it and will heat the air by condensing the refrigerant.

(33) In some embodiments, the indoor unit **56** may include a furnace system **70**. For example, the indoor unit **56** may include the furnace system **70** when the residential heating and cooling system **50** is not configured to operate as a heat pump. The furnace system **70** may include a burner assembly and heat exchanger, among other components, inside the indoor unit **56**. Fuel is provided to the burner assembly of the furnace **70** where it is mixed with air and combusted to form combustion products. The combustion products may pass through tubes or piping in a heat exchanger, separate from heat exchanger **62**, such that air directed by the blower **66** passes over the tubes or pipes and extracts heat from the combustion products. The heated air may then be routed from the furnace system **70** to the ductwork **68** for heating the residence **52**.

(34) FIG. 4 is an embodiment of a vapor compression system **72** that can be used in any of the systems described above. The vapor compression system **72** may circulate a refrigerant through a circuit starting with a compressor **74**. The circuit may also include a condenser **76**, an expansion valve(s) or device(s) **78**, and an evaporator **80**. The vapor compression system **72** may further include a control panel **82** that has an analog to digital (A/D) converter **84**, a microprocessor **86**, a non-volatile memory **88**, and/or an interface board **90**. The control panel **82** and its components may function to regulate operation of the vapor compression system **72** based on feedback from an operator, from sensors of the vapor compression system **72** that detect operating conditions, and so forth.

(35) In some embodiments, the vapor compression system **72** may use one or more of a variable speed drive (VSDs) **92**, a motor **94**, the compressor **74**, the condenser **76**, the expansion valve or device **78**, and/or the evaporator **80**. The motor **94** may drive the compressor **74** and may be powered by the variable speed drive (VSD) **92**. The VSD **92** receives alternating current (AC) power having a particular fixed line voltage and fixed line frequency from an AC power source, and provides power having a variable voltage and frequency to the motor **94**. In other embodiments, the motor **94** may be powered directly from an AC or direct current (DC) power

source. The motor **94** may include any type of electric motor that can be powered by a VSD or directly from an AC or DC power source, such as a switched reluctance motor, an induction motor, an electronically commutated permanent magnet motor, or another suitable motor.

(36) The compressor **74** compresses a refrigerant vapor and delivers the vapor to the condenser **76** through a discharge passage. In some embodiments, the compressor **74** may be a centrifugal compressor. The refrigerant vapor delivered by the compressor **74** to the condenser **76** may transfer heat to a fluid passing across the condenser **76**, such as ambient or environmental air **96**. The refrigerant vapor may condense to a refrigerant liquid in the condenser **76** as a result of thermal heat transfer with the environmental air **96**. The liquid refrigerant from the condenser **76** may flow through the expansion device **78** to the evaporator **80**.

(37) The liquid refrigerant delivered to the evaporator **80** may absorb heat from another air stream, such as a supply air stream **98** provided to the building **10** or the residence **52**. For example, the supply air stream **98** may include ambient or environmental air, return air from a building, or a combination of the two. The liquid refrigerant in the evaporator **80** may undergo a phase change from the liquid refrigerant to a refrigerant vapor. In this manner, the evaporator **80** may reduce the temperature of the supply air stream **98** via thermal heat transfer with the refrigerant. Thereafter, the vapor refrigerant exits the evaporator **80** and returns to the compressor **74** by a suction line to complete the cycle.

(38) In some embodiments, the vapor compression system **72** may further include a reheat coil in addition to the evaporator **80**. For example, the reheat coil may be positioned downstream of the evaporator relative to the supply air stream **98** and may reheat the supply air stream **98** when the supply air stream **98** is overcooled to remove humidity from the supply air stream **98** before the supply air stream **98** is directed to the building **10** or the residence **52**.

(39) Any of the features described herein may be incorporated with the HVAC unit **12**, the residential heating and cooling system **50**, or other HVAC systems. Additionally, while the features disclosed herein are described in the context of embodiments that directly heat and cool a supply air stream provided to a building or other load, embodiments of the present disclosure may be applicable to other HVAC systems as well. For example, the features described herein may be applied to mechanical cooling systems, free cooling systems, chiller systems, or other heat pump or refrigeration applications.

(40) The present disclosure is directed to a heat exchanger that has tubes defining a first section and a second section. A first end sheet may be coupled to the first section, and a second end sheet may be coupled to the second section. The first end sheet may include a first flange, the second end sheet may include a second flange, and a plate may be configured to couple to the first end sheet and the second end sheet via the first flange and the second flange, respectively. For example, the plate may engage with the flanges, and fasteners may be inserted through the plate and the flanges to bias the plate against the end sheets, thereby securing the plate to the first section and the second section of the heat exchanger. The first flange may extend toward the second end sheet, and the second flange may extend toward the first end sheet. Thus, the flanges may extend inwardly from the first and second sections and do not increase an outer boundary defined by an outer perimeter of the heat exchanger (e.g., of the first and second sections). As such, the flanges may enable a reduced physical footprint occupied by the heat exchanger.

(41) With this in mind, FIG. 5 is a perspective view of an embodiment of a heat exchanger **150** (e.g., a heat exchanger assembly) for an HVAC system **152**, which may include the HVAC unit **12**, the residential heating and cooling system **50**, or any other suitable HVAC system. An air flow **153** may be directed across the heat exchanger **150**, and a working fluid (e.g., a refrigerant) may be directed through the heat exchanger **150** during operation of the HVAC system **152**. For example, the heat exchanger **150** may include an inlet **154** through which the working fluid may be directed into the heat exchanger **150**, and the heat exchanger **150** may include an outlet **156** through which the working fluid may be discharged from the heat exchanger **150**. The heat exchanger **150** may

further include tubes, coils, or channels **158** that direct working fluid from the inlet **154** to the outlet **156**. Thus, the working fluid may flow through the heat exchanger **150** by flowing into the inlet **154**, through the tubes **158**, and out of the outlet **156**. In some embodiments, the tubes **158** may include microchannel tubes, but the tubes **158** may include any suitable tubes in additional or alternative embodiments to direct working fluid therethrough.

(42) The air flow **153** (e.g., a supply air flow, a return air flow, an ambient air flow) may be directed across the tubes **158** during operation of the heat exchanger **150**. The tubes **158** may enable heat transfer between the air flow **153** directed across the tubes **158** and the working fluid flowing through the tubes **158**, thereby changing the temperature of the air flow **153**. As an example, heat may transfer from the air flow **153** to the tubes **158** and to the working fluid, thereby cooling the air flow **153** and heating the working fluid. As another example, heat may transfer from the working fluid to the tubes **158** and to the air flow **153**, thereby heating the air flow **153** and cooling the working fluid. Additionally, each tube **158** may be offset from one another along a first axis **159** to form spaces between adjacent tubes **158** to enable the air flow **153** to be directed through the heat exchanger **150** and across the tubes **158** via the spaces. For example, the air flow **153** may be directed from the heat exchanger **150** to a space serviced by the HVAC system **152** to condition the space. Furthermore, the working fluid may be directed from the heat exchanger **150** to another component of the HVAC system **152**, such as to a compressor (e.g., the compressor **42**, the compressor **74**), to circulate through a vapor compression system of the HVAC system **152**.

(43) The illustrated heat exchanger **150** includes a first section **160** (e.g., a first panel section, a first slab) and a second section **162** (e.g., a second panel section, a second slab) defined by the tubes **158** (e.g., microchannel tubes). The first section **160** and the second section **162** may be positioned crosswise to one another. For example, each of the sections **160**, **162** may have a planar or flat (e.g., a rectangular) geometry. The first section **160** may have a first edge **164** (e.g., of one of the tubes **158**), the second section **162** may have a second edge **166** (e.g., of the same tube **158** having the first edge **164**, of a different tube **158**), and the sections **160**, **162** may be oriented to form an angle **168** (e.g., an acute angle) between the first edge **164** and the second edge **166**. As such, the first section **160** and the second section **162** may be crosswise to one another to form a V-shape or A-shape configuration defining a space or channel **170** between the first section **160** and the second section **162**. Each section **160**, **162** may include a portion of the tubes **158** (e.g., a portion of each of the tubes **158**). For example, the first section **160** may include a first tube portion **158A** (e.g., a first portion or length of each tube), and the second section **162** may include a second tube portion **158B** (e.g., a second portion or length of each tube). Working fluid may flow through each of the first tube portion **158A** and the second tube portion **158B**.

(44) The heat exchanger **150** may include a first manifold **172** (e.g., an inlet manifold) that may fluidly couple the inlet **154** to the tubes **158**, and the heat exchanger **150** may include a second manifold **174** that may fluidly couple the outlet **156** to the tubes **158**. For example, the first manifold **172** may receive the working fluid from the inlet **154** and direct the fluid to each of the tubes **158** (e.g., the first tube portion **158A**) at the first section **160**, and the second manifold **174** may receive the working fluid from each of the tubes **158** (e.g., the second tube portion **158B**) at the second section **162** and discharge the working fluid via the outlet **156**. In certain embodiments, the heat exchanger **150** may include more than two manifolds. For example, the heat exchanger **150** may include multiple inlets **154** and/or multiple outlets **156**, and the tubes **158** may be coupled to each inlet **154** and outlet **156** via a different manifold.

(45) Each tube **158** may extend from the first manifold **172** to the second manifold **174**. That is, each tube **158** may extend along a first dimension **176** (e.g., a first length, a first width) of the first section **160** and also along a second dimension **178** (e.g., a second length, a second width) of the second section **162**. Thus, each individual tube **158** may be a part of the first tube portion **158A** and the second tube portion **158B**, and each tube **158** may direct working fluid flow from first section **160** to the second section **162**. In certain embodiments, the working fluid may flow multiple times

across the first section **160** and/or the second section **162** (e.g., along the dimensions **176**, **178**) before being discharged from the heat exchanger **150**. For example, the working fluid may flow through one of the tubes **158** from the first section **160** to the second section **162**, then along another one of the tubes **158** from the second section **162** to the first section **160**, and subsequently along yet another one of the tubes **158** from the first section **160** to the second section **162** toward the outlet **156**. In this manner, the working fluid may flow through multiple passes of the heat exchanger **150**, and sets of the tubes **158** may be positioned in series with one another with respect to the flow of working fluid through the tubes **158**. Additionally or alternatively, working fluid may flow in parallel through sets of the tubes **158**. By way of example, working fluid may flow through the inlet **154** and split or divide into multiple working fluid flows within the first manifold **172** to flow through multiple sets of tubes **158** (e.g., from the first section **160** to the second section **162**) in parallel with one another. The working fluid flows may combine (e.g., within the second manifold **174**) before flowing through the outlet **156**. Although the inlet **154** and the outlet **156** are positioned at different sections **160**, **162** in the illustrated embodiment, additionally or alternatively, the inlet **154** and the outlet **156** may be positioned at the same section (e.g., at the first section **160**, at the second section **162**) of the heat exchanger **150**. In this manner, the working fluid may enter and exit the heat exchanger **150** at the same section.

(46) In additional or alternative embodiments, the first tube portions **158A** may be fluidly separate from the second tube portions **158B**. That is, each tube **158** may extend along one of the dimensions **176**, **178** and not along the other of the dimensions **176**, **178**. Thus, working fluid may flow through one of the sections **160**, **162** and not the other of the sections **160**, **162**. For example, each of the sections **160**, **162** may receive a separate working fluid flow, such as from separate vapor compression systems, and each section **160**, **162** may separately discharge the working fluid flow. To this end, each of the sections **160**, **162** may include a dedicated or separate inlet **154** and outlet **156** for the respective tube portions **158A**, **158B**.

(47) The heat exchanger **150** may include an intermediate section or a transition region **180** extending between the first section **160** and the second section **162**. For example, the first section **160** and the second section **162** may interface with one another at the intermediate section **180**. In some embodiments, such as embodiments in which each tube **158** extends from the first manifold **172** to the second manifold **174**, each tube **158** may include a bend **182** to form the first tube portion **158A** and the second tube portion **158B**. The bend **182** may be disposed in the intermediate section **180**. Thus, the first section **160** and the second section **162** may transition between one another at the intermediate section **180**. In additional or alternative embodiments, such as embodiments in which each tube portion **158A**, **158B** is fluidly separate from one another, the first tube portion **158A** and the second tube portion **158B** may be coupled to one another at the intermediate section **180**. For example, the tubes **158** of the first section **160** and the tubes **158** of the second section **162** may be separate components that are coupled to one another at the intermediate section **180** to form the first tube portion **158A** and the second tube portion **158B**. In any case, the first tube portion **158A** may extend from the first manifold **172** to the intermediate section **180**, and the second tube portion **158B** may extend from the second manifold **174** to the intermediate section **180**.

(48) In some embodiments, the air flow **153** may be directed in a direction along (e.g., generally parallel to) a second axis **184** (e.g., a vertical axis), such as in a direction **186** crosswise (e.g., generally perpendicular) to a third axis **188** (e.g., a lateral axis), through the heat exchanger **150**. Thus, the air flow **153** may be directed into the space **170** and through the second section **162** or through the first section **160**. Additionally or alternatively, the air flow **153** may be directed in an opposite direction with respect to the direction **186** through the heat exchanger **150**. Thus, the air flow **153** may be directed through the first section **160** or through the second section **162** and into the space **170**. In further embodiments, the air flow **153** may be directed in a different direction, such as along the first axis **159**, along the third axis **188**, or in any direction therebetween.

(49) The heat exchanger **150** may also include end sheets (e.g., end panels, cap sheets) to facilitate incorporation of additional components. For example, the first section **160** may include a first end sheet **190**, and the second section **162** may include a second end sheet **192**. As further described herein, the end sheets **190**, **192** may be configured to couple to another component, such as a plate, thereby attaching the component to the sections **160**, **162** of the heat exchanger **150**. For instance, the first end sheet **190** may include first flanges **194**, and the second end sheet **192** may include second flanges **196**. Each of the first flanges **194** may include a first opening or hole **198**, and each of the second flanges **196** may include a second opening or hole **200**. A component (e.g., an end plate, a side plate, a delta plate) may be configured to engage with the first flanges **194** and the second flanges **196**, and fasteners may be inserted through the component and the first flanges **194** via the first openings **198** and/or through the component and the second flanges **196** via the second openings **200** to secure the component onto the end sheets **190**, **192**. In additional or alternative embodiments, the first end sheet **190** and/or the second end sheet **192** may be coupled to another component using other features, such as a weld, an adhesive, a punch, and the like, which may be arranged on the flanges **194**, **196**.

(50) The end sheets **190**, **192** may be positioned at a first side **206** (e.g., a front side) of the heat exchanger **150** to enable the component to couple to the first side **206** of the heat exchanger **150**. The first side **206** may extend crosswise with respect to a second side **208** (e.g., a bottom side, an underside, a first end) and a third side **210** (e.g., a top side, a second end) of the heat exchanger **150**. The first surface **202** of the first end sheet **190** may be generally planar with a second surface **204** of the second end sheet **192** along the first side **206** to enable the component to engage each of the first end sheet **190** (e.g., the first flanges **194**) and the second end sheet **192** (e.g., the second flanges **196**) at the first side **206** and extend crosswise to the second side **208** and the third side **210**. In the illustrated embodiment, the manifolds **172**, **174** are disposed at and extend along (e.g., along the first axis **159**) the second side **208**, and the intermediate section **180** is disposed at and extends along (e.g., along the first axis **159**) the third side **210**. However, in additional or alternative embodiments, the manifolds **172**, **174** may be disposed at the third side **210**, and the intermediate section **180** may be disposed at the second side **208**.

(51) FIG. **6** is a front view of an embodiment of the heat exchanger **150**. In the illustrated embodiment, the sections **160**, **162** are oriented crosswise with respect to one another, the second axis **184**, and the third axis **188**. Additionally, the first flanges **194** of the first end sheet **190** and the second flanges **196** of the second end sheet **192** may extend generally toward one another. That is, the first flanges **194** may extend toward the second section **162** (e.g., at least partially along the third axis **188**), and the second flanges **196** may extend toward the first section **160** (e.g., at least partially along the third axis **188**). In this manner, the flanges **194**, **196** may extend inwardly or in a direction (e.g., along the third axis **188**) toward the space **170** between the first section **160** and the second section **162**. Such orientation of the flanges **194**, **196** may limit (e.g., do not increase) a physical footprint or volume occupied by the heat exchanger **150**. For example, the heat exchanger **150** may be confined within an outer boundary **240** defined by a perimeter of the heat exchanger **150** viewed along the first axis **159**. The outer boundary **240** extends along a first exterior side **242** (e.g., opposite a first interior side **244** facing the space **170**) of the first section **160**, along a second exterior side **246** of the second section **162** (e.g., opposite a second interior side **248** facing the space **170**), across the intermediate section **180**, and across the manifolds **172**, **174**. The flanges **194**, **196** extend inwardly (e.g., from the interior sides **244**, **248**) and toward an interior defined by the outer boundary **240**. As such, the flanges **194**, **196** do not increase a size or dimension of the outer boundary **240** and the physical footprint or volume occupied by the heat exchanger **150**.

(52) In certain embodiments, the first section **160** and the second section **162** may be configured to move relative to one another. By way of example, the first section **160** and the second section **162** may rotate or pivot relative to one another about the intermediate section **180**. For instance, the bend **182** may define a rotational axis **250** that extends in a direction along the first axis **159**. The

first tube portion **158A** and the second tube portion **158B** may rotate relative to one another about the rotational axis **250** to rotate the first section **160** and the second section **162** relative to one another.

(53) As an example, FIG. **6** illustrates the heat exchanger **150** in an expanded configuration **252** in which the first section **160** and the second section **162** may extend crosswise relative to one another (e.g., at the angle **168**) to form the space **170**. The heat exchanger **150** may be installed in the HVAC system **152** in the expanded configuration **252** to facilitate greater heat transfer between the heat exchanger **150** and the air flow **153** during operation of the HVAC system **150**. For example, the crosswise orientation of the first section **160** and the second section **162** in the expanded configuration **252** may enable increased heat transfer between the first tube portion **158A** and the air flow **153** and between the second tube portion **158B** and the air flow **153**, such as via heat transfer between the tubes **158** and the air flow **153** within the space **170**. The first section **160** and the second section **162** may also rotate in inward directions **254** toward one another to reduce a magnitude of the angle **168**, the size of the space **170**, and the size or dimensions of the outer boundary **240**. Reducing the size of the outer boundary **240** may reduce the physical footprint or volume occupied by the heat exchanger **150** and enable more efficient usage of the space in which the heat exchanger **150** is disposed. Indeed, as further described herein, the sections **160**, **162** may be rotated in inward directions **254** to transition the heat exchanger **150** from the expanded configuration **252** to a compact configuration in which the sections **160**, **162** may extend along and/or engage one another. For instance, the heat exchanger **150** may be more easily stored and/or transported in the compact configuration, such as for delivery, maintenance, service, or other operations in which the heat exchanger **150** may not be installed in the HVAC system **152**.

(54) The sections **160**, **162** may also be rotated in outward directions **256** away from one another to transition the heat exchanger **150** from the compact configuration to the illustrated expanded configuration **252**. Rotation of the sections **160**, **162** in the outward directions **256** may increase a magnitude of the angle **168**, the space **170**, and the size or dimensions of the outer boundary **240**. For example, the sections **160**, **162** may be rotated in the outward directions **256** prior to installation of the heat exchanger **150** within the HVAC system **152**. In some embodiments, the heat exchanger **150** may also be adjusted to an intermediate configuration (e.g., a partially expanded configuration, a partially compact configuration) between the expanded configuration **252** and the compact configuration. As an example, the heat exchanger **150** may be adjusted to the intermediate configuration to facilitate installation of the heat exchanger **150** in the HVAC system **152**, such as to accommodate various tolerances, dimensions, and/or structural boundaries that may be imposed by a structure or component of the HVAC system **152** within which the heat exchanger **150** is positioned. Thus, adjustability of the sections **160**, **162** may increase flexibility associated with usage of the heat exchanger **150**.

(55) In certain embodiments, the sections **160**, **162** may be movable relative to one another via a manual force imparted (e.g., by an operator, by a technician) onto the first section **160** and/or the second section **162**. Indeed, the heat exchanger **150** may be adjustable between various configurations without usage of an additional tool or device dedicated to moving the sections **160**, **162** relative to one another. For example, the manual force may be imparted to move the sections **160**, **162** (e.g., via elastic deformation) in the inward directions **254** to transition the heat exchanger **150** to the compact configuration. Furthermore, a lack of manual force being imparted on the sections **160**, **162** may cause the sections **160**, **162** to move in the outward directions **254** (e.g., due to elastic deformation, a spring force of the tubes **158**) to transition the heat exchanger **150** to the expanded configuration **252**.

(56) As an example, the heat exchanger **150** may be arranged to enable the manual force to rotate the sections **160**, **162** via the bend **182**. For instance, each tube **158** may have a certain dimension (e.g., a thickness), each tube **158** may be bent, flexed, and/or twisted to form the bend **182** having a particular geometry, and/or each tube **158** may be formed from a material (e.g., a metal) to enable

the sections **160**, **162** to rotate via a manual force and transition the heat exchanger **150** between various configurations without deforming (e.g., plastically deforming, permanently deforming) the tubes **158**. Furthermore, the heat exchanger **150** (e.g., the tubes **158**) may be arranged to block excessive rotation of the sections **160**, **162** in the outward directions **256**. For example, the sections **160**, **162** may be blocked from rotating and forming the angle **168** with a magnitude that is greater than a threshold angle during an absence of the manual force imparted onto the first section **160** and/or the second section **162**. Indeed, when no manual force is imparted onto the sections **160**, **162**, the heat exchanger **150** may transition to the expanded configuration **252** (e.g., a resting configuration) in which the first section **160** and the second section **162** are oriented in at the angle **168** having a desired magnitude in which the heat exchanger **150** may be installed in the HVAC system **152** and operating to transfer heat between the air flow **153** and a working fluid.

(57) First notches **258** (e.g., cutouts) may be formed in the first end sheet **190**, and second notches **260** (e.g., cutouts) may be formed in the second end sheet **192**. Each first notch **258** may be configured to receive a corresponding second flange **196** of the second end sheet **192** in the compact configuration of the heat exchanger **150**, and each second notch **260** may be configured to receive a corresponding first flange **194** of the first end sheet **190** in the compact configuration. The first notches **258** and the second notches **260** may enable increased rotation of the sections **160**, **162** in the inward directions **254** to cause the first flanges **194** to overlap with the second section **162** and the second flanges **196** to overlap with the first section **160**. In other words, the first notches **258** may block the second flanges **196** from contacting the first end sheet **190**, and the second notches **260** may block the first flanges **194** from contacting the second end sheet **192** during transition of the heat exchanger **150** to the compact configuration. For this reason, the notches **258**, **260** may enable rotation of the sections **160**, **162** in the inward directions **254** until the first edge **164** of the first section **160** and the second edge **166** of the second section **162** engage with one another, rather than, for example, until the first flanges **194** engage with the second end sheet **192** and/or the second notches **260** engage with the first end sheet **190**.

(58) FIG. 7 is a rear view of an embodiment of the heat exchanger **150** in the expanded configuration **252**. The heat exchanger **150** may have end sheets positioned at a fourth side **280** (e.g., a rear side), opposite the first side **206**, of the heat exchanger **150**. For example, the first section **160** may include a third end sheet **282** coupled at the fourth side **280**, and the second section **162** may include a fourth end sheet **284** coupled at the fourth side **280**. The third end sheet **282** and the fourth end sheet **284** may also enable coupling of another component (e.g., a plate) to the first section **160** and the second section **162** at the fourth side **280**. For example, the third end sheet **282** may include third flanges **286** that have third openings or holes **288**, and the fourth end sheet **284** may include fourth flanges **290** that have fourth openings or holes **292**. The third end sheet **282** (e.g., the third flanges **286**) and the fourth end sheet **284** (e.g., the fourth flanges **290**) may be configured to engage with the component. Fasteners may be inserted through the component and the third flanges **286** via the third openings **288** and/or through the component and the fourth flanges **290** via the fourth openings **292** to secure the component onto the third end sheet **282** and the fourth end sheet **284**.

(59) Notches may also be formed into the third end sheet **282** and the fourth end sheet **284** to enable receipt of a corresponding one of the third flanges **288** or the fourth flanges **290** in the compact configuration of the heat exchanger **150**. For example, third notches **294** may be formed in the third end sheet **282**, and each third notch **294** may be configured to receive one of the fourth flanges **290** of the fourth end sheet **284** in the compact configuration. Furthermore, fourth notches **296** may be formed in the fourth end sheet **284**, and each fourth notch **296** may be configured to receive one of the third flanges **288** of the third end sheet **282** in the compact configuration. In this manner, abutment between the third flanges **288** and the fourth end sheet **284** may be avoided, and abutment between the fourth flanges **290** and the third end sheet **282** may be avoided, thereby enabling increased rotation of the sections **160**, **162** in the inward directions **254**. For example, the

third flanges **288** may overlap with the second section **162** along the third axis **188** and the fourth flanges **290** may overlap with the first section **160** along the third axis **188** in the compact configuration.

(60) FIG. **8** is a front view of an embodiment of the heat exchanger **150** in a compact configuration **320**. In the compact configuration **320**, the first section **160** and the second section **162** may be engaged with one another and/or extend along one another (e.g., along the second axis **184**). Thus, the outer boundary **240** defined by the perimeter of the heat exchanger **150** in the compact configuration **320** may be less than (e.g., substantially less than, smaller than) the outer boundary **240** associated with the heat exchanger **150** in the expanded configuration **252**. As such, the heat exchanger **150** may occupy a reduced physical footprint (e.g., a reduced volume of space) in the compact configuration **320**. The compact configuration **320** of the heat exchanger **150** may enable more efficient usage of space. For instance, the heat exchanger **150** may be more easily moved and/or stored, such as to accommodate positioning of other objects within a confined space (e.g., during storage or transportation of the heat exchanger **150**).

(61) In the compact configuration, the first flanges **194** of the first end sheet **190** may be positioned within corresponding second notches **260** formed in the second end sheet **192** and may overlap with the second section **160** along the third axis **188**. Additionally, the second flanges **196** of the second end sheet **192** may be positioned within corresponding first notches **258** of the first end sheet **190** and may overlap with the first section **160** along the third axis **188**. Such positioning of the flanges **194**, **196** in the notches **258**, **260** may enable increased movement of the sections **160**, **162** to engage with or extend along one another in the compact configuration **320**. Thus, the inward extension of the flanges **194**, **196** may limit (e.g., may not increase) the size of the outer boundary **240** associated with the compact configuration **320** of the heat exchanger **150**. Moreover, the inward extension of the flanges **194**, **196** may shield the flanges **194**, **196** from certain external elements. For instance, contact between the flanges **194**, **196** and objects that are positioned at the first exterior side **242** of the first section **160** and/or at the second exterior side **246** of the second section **162** may be avoided. As an example, the orientation of the flanges **194**, **196** may enable the first exterior side **242** and/or the second exterior side **246** to have a flatter geometry, and the heat exchanger **150** may be positioned against (e.g., flush with) another object, such as another heat exchanger **150**, a wall, a panel, and so forth, at the first exterior side **242** and/or at the second exterior side **246**. Thus, the spatial positioning of the heat exchanger **150** with respect to an adjacent object may be more efficient. As another example, the orientation of the flanges **194**, **196** may enable the heat exchanger **150** to be moved (e.g., in the compact configuration **320**) without causing contact between the flanges **194**, **196** and another object, such as a user, an enclosure, another component of the HVAC system **152**, and so forth. As such, a structural integrity, a geometry, and/or a useful lifespan of the flanges **194**, **196** may be increased.

(62) In the illustrated embodiment, a first flange **194** may be positioned adjacent to a corresponding one of the second flanges **196** in the compact configuration **320**. However, in additional or alternative embodiments, the first flanges **194** and the second flanges **196** may be arranged such that the first flanges **194** are positioned further apart from the second flanges **196** in the compact configuration **320**. In other words, there may be a greater offset distance between a first flange **194** and an adjacent second flange **196** along the second axis **184**.

(63) FIG. **9** is a detailed perspective view of an embodiment of the heat exchanger **150**. In the illustrated embodiment, the first end sheet **190** is coupled to and extends along a first end **340** of the first section **160**. For example, the first end sheet **190** may extend along the first tube portions **158A** of the first section **160**. Additionally, the second end sheet **192** is coupled to and extends along a second end **342** of the second section **162**, such as along the second tube portions **158B** of the second section **162**. As described above, the working fluid may flow through the first tube portions **158A** and through the second tube portions **158B**, such as between the tube portions **158** via the intermediate section **180** (e.g., via the bend **182**). Thus, the first end sheet **190** may extend

along a direction of the flow of working fluid through the first tube portions **158A** at the first section **160**, and the second end sheet **192** may extend along a direction of the flow of working fluid through the second tube portions **158B** at the second section **162**.

(64) Additionally, the heat exchanger **150** may include fins **344** that are coupled to the tubes or tube portions **158** (e.g., microchannel tubes). First fins **344A** may be coupled to the first tube portions **158A**, and second fins **344B** may be coupled to the second tube portions **158B**. For instance, the first fins **344A** may span between adjacent first tube portions **158A** to couple the adjacent first tube portions **158A** to one another, and the second fins **344B** may span between adjacent second tube portions **158B** to couple the adjacent second tube portions **158B** to one another. The fins **344** may increase an efficiency of the operation of the heat exchanger **150** to transfer heat between the working fluid flowing through the tubes **158** and the air flow **153** directed across the tubes **158**. For example, the fins **344** may increase heat transfer by absorbing additional heat from the working fluid or from the air flow **153**. Thus, heat transfer between the working fluid and the air flow **153** may be enabled via the tubes **158** and via the fins **344**. In the illustrated embodiment, the fins **344** have a wave or zigzag shaped profile, but the fins **344** may have any suitable profile in additional or alternative embodiments.

(65) In some embodiments, the first end sheet **190** may be coupled to or secured to one of the first fins **344A**, such as a fin **346** that is positioned outermost (e.g., along the first axis **159**) at the first end **340** of the first section **160**. Additionally, the second end sheet **192** may be coupled to or secured to one of the second fins **344B**, such as a fin **348** that is positioned outermost (e.g., along the first axis **159**) at the second end **342** of the second section **162**. By way of example, the first end sheet **190** and the second end sheet **192** may be coupled to the respective fins **344** via a weld, an adhesive, a fastener, a brazing technique, and so forth. Furthermore, the first notches **258** formed in the first end sheet **190** may expose the fin **346** at the first end **340**, and the second notches **260** formed in the second end sheet **192** may expose the fin **348** at the second end **342**. In certain embodiments, in the compact configuration **320**, the first flanges **194** of the first end sheet **190** may extend into the corresponding second notches **260** of the second end sheet **192** and engage with (e.g., abut against) the fin **348**, and the second flanges **196** of the second end sheet **192** may extend into the corresponding first notches **258** of the first end sheet **190** and engage with (e.g., abut against) the fin **346**. In additional or alternative embodiments, the first flanges **194** may overlap with the fin **348** without contacting the fin **348**, and the second flanges **196** may overlap with the fin **346** without contacting the fin **346** in the compact configuration **320**. In further embodiments, the first end sheet **190** may be coupled to one of the first tube portions **158A** (e.g., a first tube portion **158A** positioned outermost along the first axis **159** at the first end **340**), and/or the second end sheet **192** may be coupled to one of the second tube portions **158B** (e.g., a second tube portion **158B** positioned outermost along the first axis **159** at the second end **342**). In such embodiments, the first flanges **194** may overlap with and/or engage with one of the second tube portions **158B** (e.g., by extending into the corresponding second notches **260**), and/or the second flanges **196** may overlap with and/or engage with one of the first tube portions **158A** (e.g., by extending into the corresponding first notches **258**).

(66) The third end sheet **282** may similarly be coupled to the first section **160**, and the fourth end sheet **284** may similarly be coupled to the second section **162** in the manner illustrated in FIG. 9 with respect to the first end sheet **190** and the second end sheet **192**. That is, the third end sheet **282** may be coupled to one of the first fins **344A**, and the fourth end sheet **284** may be coupled to one of the second fins **344B**. In this manner, the third end sheet **282** may extend along the flow of working fluid through the first tube portions **158A** at the first section **160**, and the fourth end sheet **284** may extend along the flow of working fluid through the second tube portions **158B** at the second section **162**. Additionally, in the compact configuration **320**, the third flanges **286** of the third end sheet **282** may be configured to abut one of the second fins **344B** to which the fourth end sheet **284** is coupled, and the fourth flanges **290** of the fourth end sheet **284** may be configured to

about one of the first fins **344A** to which the third end sheet **282** is coupled.

(67) FIG. **10** is a perspective view of an embodiment of the heat exchanger **150**. A plate **370** (e.g., a delta plate, sheet metal), shown in phantom lines in FIG. **10**, may be coupled to the heat exchanger **150** via the first end sheet **190** and the second end sheet **192**. For example, the plate **370** may be positioned between the inlet **154**/outlet **156** and the end sheets **190**, **192** along the first axis **159**. The plate **370** may be placed in engagement with the first surface **202** of the first end sheet **190** and the second surface **204** of the second end sheet **192** and therefore extend from the first section **160** to the second section **162** to occlude (e.g., partially enclose) the space **170** formed between the first section **160** and the second section **162** of the heat exchanger **150**. Thus, the plate **370** may block the air flow **153** out of the space **170** along the first axis **159** and force the air flow **153** across the tubes **158**. As such, the plate **370** may increase contact between the tubes **158** and the air flow **153**, thereby increasing efficiency of the heat exchanger **150**.

(68) The plate **370** may include openings or holes **372** that may align with the first openings **198** of the first flanges **194** of the first end sheet **190** and the second openings **200** of the second flanges **196** of the second end sheet **192**. The heat exchanger **150** may include fasteners **374** that are configured to extend through the openings **372** of the plate **370** that are aligned with the first openings **198** of the first end sheet **190** and/or through the openings **372** of the plate **370** that are aligned with the second openings **200** of the second end sheet **192**. The fasteners **374** may secure the plate **370** onto the flanges **194**, **196**. For example, the fasteners **374** may include self-tapping screws that may bias the plate **370** against the end sheets **190**, **192** via the flanges **194**, **196** without having to access the space **170** between the first section **160** and the second section **162** (e.g., to position a nut through which the fasteners **374** may be inserted). Additionally or alternatively, any other suitable feature or components, such as another type of fastener **374**, a weld, an adhesive, a punch, and so forth, may be used to couple the plate **370** to the end sheets **190**, **192**.

(69) The plate **370** may be configured to mount to a drain pan **376**. By way of example, the drain pan **376** may include walls **378** that define an internal volume **380** of the drain pan **376**, and the plate **370** may extend into the internal volume **380** and engage with a base **379** of the walls **378**. Mounting the plate **370** and the drain pan **376** onto one another may cause the heat exchanger **150** (e.g., the first section **160**, the second section **162**) to be at least partially disposed in the drain pan **376**, such as in an installed configuration of the heat exchanger **150**. For instance, the manifolds **172**, **174** and/or the tubing **158** may be positioned within the internal volume **380** of the drain pan **376** and may also engage with the base **379** of the drain pan **376**. The drain pan **376** may improve operation of the HVAC system **152**, such as of the heat exchanger **150**. As an example, operation of the heat exchanger **150** may generate condensate on the heat exchanger **150**, such as on the tubes **158**, the inlet **154**, the outlet **156**, the manifolds **172**, **174**, and so forth. The drain pan **376** may receive the condensate generated on the heat exchanger **150**, such as via a gravitational force, and the drain pan **376** may direct the condensate away from the heat exchanger **150**. Thus, the drain pan **376** may block the condensate from affecting a performance of the heat exchanger **150** to increase a heat transfer efficiency of the heat exchanger **150**. Although the illustrated drain pan **376** has a rectangular shape, the drain pan **376** may have any suitable shape configured to receive condensate generated on the heat exchanger **150**.

(70) In some embodiments, the plate **370** may have a shape or profile that extends along (e.g., corresponds with, matches) the outer boundary **240** associated with the heat exchanger **150** in the expanded configuration **252**. As an example, the plate **370** may not extend past (e.g., may be aligned with, may be flush with) the exterior sides **242**, **246** of the heat exchanger **150**. Therefore, a reduced amount of material may be used to manufacture the plate **370** as compared to a plate **370** that extends beyond the exterior sides **242**, **246** (e.g., to enable interfacing with end sheets having flanges that extend outwardly away from the space **170**). For this reason, a cost, a duration of time, and/or a difficulty associated with manufacture of the plate **370** may be reduced. Furthermore, the plate **370** may extend along (e.g., correspond with, match) a profile of the manifolds **172**, **174** to

accommodate the positioning of the inlet **154** and the outlet **156**. That is, the plate **370** may have respective recesses **382** (e.g., formed at corners of the plate **370**) that may be configured to receive the inlet **154** and the outlet **156** while the plate **370** is coupled to the heat exchanger **150** in an assembled configuration of the heat exchanger **150**. Further still, the plate **370** may extend along the end sheets **190**, **192** from the manifolds **172**, **174** toward the intermediate section **180** to occlude the space **170**. However, the plate **370** may not extend past where the bend **182** initiates to avoid contact with the bend **182**. Thus, the plate **370** may be positioned in greater engagement with (e.g., more flush with) the end sheets **190**, **192** for better securement to the end sheets **190**, **192**, and the plate **370** may avoid affecting rotation between the sections **160**, **162**. As such, the plate **370** may accommodate the features of the heat exchanger **150** without extending beyond the outer boundary **240** defined by the sections **160**, **162**. Thus, the plate **370** may enable the heat exchanger **150** to occupy a limited physical footprint.

(71) In certain embodiments, another plate similar to the plate **370** may be configured to couple to the third end sheet **282** and the fourth end sheet **284** using similar techniques. That is, the plate may have a profile that is contained within the outer boundary **240** and accommodates various features (e.g., the manifolds **172**, **174**, the bend **182**) of the heat exchanger **182**. The plate may be configured to engage with the third flanges **286** of the third end sheet **282** and the fourth flanges **290** of the fourth end sheet **284**, and the plate may have openings that align with the third openings **288** of the third end sheet **282** and/or the fourth openings **292** of the fourth end sheet **284**. Fasteners may be inserted through the openings of the plate that are aligned with the third openings **288** and/or the fourth openings **292** to bias the plate against the end sheets **282**, **284**. The plate may further occlude the space **170** to increase efficiency of the heat exchanger **150**, and the plate may also be configured to mount to the drain pan **376** to facilitate positioning of the first section **160** and the second section **162** within the drain pan **376**.

(72) Although each end sheet **190**, **192**, **282**, **284** illustrated in FIGS. **5-10** includes three flanges and three notches, each end sheet **190**, **192**, **282**, **284** may have any suitable number of flanges and notches in additional or alternative embodiments. For example, one of the end sheets **190**, **192**, **282**, **284** may have one flange, two flanges, or more than three flanges to facilitate coupling with a plate (e.g., the plate **370**). In such embodiments, another one of the end sheets **190**, **192**, **282**, **284** may have a corresponding number of notches (e.g., the first notches **258**, the second notches **260**, the third notches **294**, the fourth notches **296**) configured to receive the flanges in the compact configuration **320** of the heat exchanger **150**.

(73) The present disclosure may provide one or more technical effects useful in the operation of an HVAC system. For example, the HVAC system may include a heat exchanger with tubes through which a working fluid may flow. The HVAC system may also direct an air flow across the tubes of the heat exchanger, and the heat exchanger may place the air flow in a heat exchange relationship with the working fluid to condition the air flow. In some embodiments, the tubes may define a first section and a second section of the heat exchanger, and the first section and the second section may be oriented to form a space extending therebetween. The heat exchanger may include a first end sheet coupled at the first section and extending along a flow of working fluid through the tubes at the first section, as well as a second end sheet coupled at the second section and extending along a flow of working fluid through the tubes at the second section. The first end sheet may include first flanges that extend toward the second end sheet, and the second end sheet may include second flanges that extend toward the first end sheet. In this manner, the orientation of the flanges may limit an outer boundary defined by the heat exchanger and may therefore limit a physical footprint occupied by the heat exchanger. The flanges may facilitate coupling of a plate onto the end sheets. By way of example, the plate may be placed in engagement with the flanges, and fasteners may be inserted through the plate and the flanges to bias the plate against the end sheets and secure the plate onto the sections of the heat exchanger. The plate may occlude the space formed between the first section and the second section and block undesirable flow of air out from the space. As such,

usage of the plate may force air to flow across the heat exchanger tubes. In this manner, the flanges may improve a performance (e.g., an efficiency) associated with the heat exchanger.

(74) In certain embodiments, the sections of the heat exchanger may be movable relative to one another. For instance, the sections may be rotated toward one another to move the flanges toward an opposing end sheet and further reduce a physical footprint occupied by the heat exchanger. For this reason, the first end sheet may include notches configured to receive the second flanges of the second end sheet, and the second end sheet may include notches configured to receive the first flanges of the first end sheet. The notches may enable the first flanges to overlap with the second end sheet and the second flanges to overlap with the first end sheet, thereby blocking contact between the first flanges and the second end sheet and/or between the second flanges and the first end sheet that may otherwise block movement of the sections toward one another. As such, the notches may enable a desirable range of motion between the sections of the heat exchanger, such as to enable the first section and the second section to engage with and/or extend along one another and reduce the physical footprint associated with the heat exchanger below a threshold size. The technical effects and technical problems in the specification are examples and are not limiting. It should be noted that the embodiments described in the specification may have other technical effects and can solve other technical problems.

(75) While only certain features and embodiments of the disclosure have been illustrated and described, many modifications and changes may occur to those skilled in the art, such as variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, including temperatures and pressures, mounting arrangements, use of materials, colors, orientations, and so forth without materially departing from the novel teachings and advantages of the subject matter recited in the claims. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the disclosure. Furthermore, in an effort to provide a concise description of the exemplary embodiments, all features of an actual implementation may not have been described, such as those unrelated to the presently contemplated best mode of carrying out the disclosure, or those unrelated to enabling the claimed disclosure. It should be noted that in the development of any such actual implementation, as in any engineering or design project, numerous implementation specific decisions may be made. Such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure, without undue experimentation.

(76) The techniques presented and claimed herein are referenced and applied to material objects and concrete examples of a practical nature that demonstrably improve the present technical field and, as such, are not abstract, intangible or purely theoretical. Further, if any claims appended to the end of this specification contain one or more elements designated as “means for [perform]ing [a function] . . . ” or “step for [perform]ing [a function] . . . ”, it is intended that such elements are to be interpreted under 35 U.S.C. 112(f). However, for any claims containing elements designated in any other manner, it is intended that such elements are not to be interpreted under 35 U.S.C. 112(f).

Claims

1. A heat exchanger for a heating, ventilation, and/or air conditioning (HVAC) system, comprising: a plurality of tubes configured to direct a working fluid therethrough, wherein the plurality of tubes defines a first section and a second section of the heat exchanger, and the first section and the second section extend crosswise relative to one another; and an end sheet coupled to an end of the first section, wherein the end sheet comprises a plurality of flanges extending toward the second section, wherein the heat exchanger is configured to transition between an expanded configuration and a compact configuration, the first section and the second section extend crosswise relative to

one another in the expanded configuration, the first section and the second section extend along one another in the compact configuration, and the plurality of flanges overlaps with the second section in the compact configuration of the heat exchanger.

2. The heat exchanger of claim 1, wherein the end sheet extends along the end of the first section and along a direction of working fluid flow through the plurality of tubes of the first section.

3. The heat exchanger of claim 1, wherein the end sheet is a first end sheet, the end is a first end, the plurality of flanges is a first plurality of flanges, the heat exchanger comprises a second end sheet coupled to a second end of the second section, and the second end sheet comprises a second plurality of flanges extending toward the first section.

4. The heat exchanger of claim 3, comprising a plate configured to be secured to the first plurality of flanges and the second plurality of flanges and extend from the first section to the second section.

5. The heat exchanger of claim 4, comprising a first fastener configured to extend through the plate and a first flange of the first plurality of flanges and a second fastener configured to extend through the plate and a second flange of the second plurality of flanges.

6. The heat exchanger of claim 1, wherein the end sheet is a first end sheet, the end is a first end, the plurality of flanges comprises a first flange, the heat exchanger comprises a second end sheet coupled to a second end of the second section, the second end sheet comprises a notch formed therein, and the notch is configured to receive the first flange in the compact configuration of the heat exchanger.

7. The heat exchanger of claim 1, wherein the first section comprises a first manifold configured to receive the working fluid and direct the working fluid into the plurality of tubes, and the second section comprises a second manifold configured to receive the working fluid from the plurality of tubes and discharge the working fluid from the heat exchanger.

8. The heat exchanger of claim 7, wherein each tube of the plurality of tubes extends from the first manifold to the second manifold, and each tube of the plurality of tubes comprises a bend formed between the first section and the second section.

9. The heat exchanger of claim 1, comprising a plurality of fins extending between the plurality of tubes, wherein the end sheet is coupled to a fin of the plurality of fins.

10. A heat exchanger for a heating, ventilation, and/or air conditioning (HVAC) system, comprising: a plurality of tubes configured to direct a working fluid therethrough, wherein the plurality of tubes defines a first panel section, a second panel section, and an intermediate section extending between the first panel section and the second panel section, wherein the first panel section and the second panel section are configured to rotate relative to one another about the intermediate section, the first panel section and the second panel section are configured to rotate toward one another to transition the heat exchanger to a compact configuration, and the first panel section and the second panel section are configured to rotate away from one another to transition the heat exchanger to an expanded configuration; a first end sheet coupled to the first panel section, wherein the first end sheet comprises a flange extending between the first panel section and the second panel section; and a second end sheet coupled to the second panel section, wherein the second end sheet comprises a notch formed therein, and the notch is configured to receive the flange of the first end sheet in the compact configuration of the heat exchanger.

11. The heat exchanger of claim 10, comprising a plurality of fins extending between the plurality of tubes, wherein the second end sheet is coupled to a fin of the plurality of fins, and the flange is configured to extend into the notch and engage with the fin in the compact configuration of the heat exchanger.

12. The heat exchanger of claim 10, wherein the plurality of tubes comprises microchannel tubes.

13. A heat exchanger for a heating, ventilation, and/or air conditioning (HVAC) system, comprising: a plurality of tubes configured to direct a working fluid therethrough; a first section comprising a first portion of the plurality of tubes, wherein the first section comprises a first end

sheet extending along a first direction of working fluid flow through the first portion of the plurality of tubes, and the first end sheet comprises a first flange; and a second section comprising a second portion of the plurality of tubes, wherein the second section comprises a second end sheet extending along a second direction of working fluid flow through the second portion of the plurality of tubes, the second end sheet comprises a second flange, the first flange and the second flange extend toward one another, and the first flange is separate from the second flange, wherein the first section and the second section are configured to rotate toward one another to transition the heat exchanger to a compact configuration, the first section and the second section are configured to rotate away from one another to transition the heat exchanger to an expanded configuration, and the first flange overlaps with the second section in the compact configuration of the heat exchanger.

14. The heat exchanger of claim 13, comprising a plate configured to couple to the first end sheet via the first flange and to the second end sheet via the second flange, wherein the plate is configured to at least partially enclose a space formed between the first section and the second section.

15. The heat exchanger of claim 14, wherein the plate is configured to extend into a drain pan, and the first section and the second section are configured to be at least partially disposed in the drain pan in an installed configuration of the heat exchanger.

16. The heat exchanger of claim 13, wherein each tube of the plurality of tubes extends from the first section to the second section, each tube forms a bend between the first section and the second section, and the first section and the second section are configured to rotate relative to one another via the bend.

17. The heat exchanger of claim 1, wherein the heat exchanger is configured to transition from the expanded configuration to the compact configuration via application of a manual force to the first section, the second section, or both.

18. The heat exchanger of claim 1, wherein the plurality of tubes comprises microchannel tubes.

19. The heat exchanger of claim 10, wherein each tube of the plurality of tubes comprises a bend at least partially defining the intermediate section.

20. The heat exchanger of claim 13, wherein the plurality of tubes comprises microchannel tubes.
