

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399862
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Shin; Yoonho et al.

Method for recovering database file in electronic device

Abstract

According to an embodiment, an electronic device includes a memory including a database file and at least one processor connected to the memory. The at least one processor may identify damage to the database file while a first application running on the electronic device accesses the database file. The at least one processor may control a second application running on the electronic device to wait without accessing the database file until recovery of the damaged database file is completed. The at least one processor may record recovery state information indicating that the database file is recovered if the recovery of the damaged database file is completed. The at least one processor may control the second application to access the recovered database file based on the recovery state information.

Inventors: Shin; Yoonho (Suwon-si, KR), Lee; Kisung (Suwon-si, KR), Jun; Hyeun (Suwon-si, KR), Woo; Hobin (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008778088

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Gyeonggi-Do, KR)

Appl. No.: 18/107424

Filed: February 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230259487 A1	Aug. 17, 2023

Foreign Application Priority Data

KR	10-2022-0016389	Feb. 08, 2022
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2023/001745 20230207 PENDING child-doc US 18107424

Publication Classification

Int. Cl.: G06F16/11 (20190101); G06F11/14 (20060101); G06F16/176 (20190101)

U.S. Cl.:

CPC G06F16/122 (20190101); G06F11/1469 (20130101); G06F16/1774 (20190101); G06F2201/80 (20130101); G06F2201/84 (20130101)

Field of Classification Search

CPC: G06F (16/122); G06F (16/1774); G06F (11/1469); G06F (2201/80); G06F (2201/84); G06F (17/30)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11757914	12/2022	Jakobsson	726/25	H04L 51/42
2005/0216462	12/2004	Xiao	N/A	N/A
2005/0246612	12/2004	Leis et al.	N/A	N/A
2007/0088970	12/2006	Buxton et al.	N/A	N/A
2011/0246503	12/2010	Bender	707/769	G06F 9/546
2013/0227224	12/2012	Koinuma et al.	N/A	N/A
2016/0364158	12/2015	Narayanan	N/A	G06F 11/2094
2017/0192863	12/2016	Eluri et al.	N/A	N/A
2018/0276268	12/2017	Doval	N/A	G06F 11/0751
2018/0373877	12/2017	Bruso	N/A	G06F 21/552
2020/0034251	12/2019	Antonopoulos et al.	N/A	N/A
2020/0201718	12/2019	Richter et al.	N/A	N/A
2020/0265010	12/2019	Lee	N/A	G06F 16/252
2021/0165716	12/2020	Li	N/A	G06F 11/1474
2023/0342345	12/2022	Xiao	N/A	G06F 16/215

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101976254	12/2010	CN	N/A
112506710	12/2020	CN	N/A
H07121419	12/1994	JP	N/A
H11134236	12/1998	JP	N/A
2009163529	12/2008	JP	N/A
20060004915	12/2005	KR	N/A

20070031209	12/2006	KR	N/A
20090114177	12/2008	KR	N/A
100983300	12/2009	KR	N/A
20130099801	12/2012	KR	N/A
20210089266	12/2020	KR	N/A
20230070986	12/2022	KR	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for International Application No. PCT/KR2023/001745; International Filing Date Feb. 7, 2023; Date of Mailing May 15, 2023; 9 Pages. cited by applicant
 Extended European Search Report corresponding to Application No. 23753116.5-1203; Dated Dec. 4, 2024. cited by applicant

Primary Examiner: Harmon; Courtney

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application, claiming priority under § 365(c), of International Application No. PCT/KR2023/001745, filed on Feb. 7, 2023, which is based on and claims the benefit of Korean patent application number 10-2022-0016389, filed on Feb. 8, 2022, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

TECHNICAL FIELD

(1) An embodiment of the disclosure relates to a technique for recovering a database when damage occurs in the database operating in an electronic device.

BACKGROUND

(2) With the development of digital technology, various types of electronic devices, such as mobile communication terminals, smartphones, tablet personal computers (PCs), and wearable devices, are widely used.

(3) The electronic device may store various data to provide various user experiences. For the operation of various data, the electronic device may include a storage device layer including a main memory (e.g., random access memory (RAM)) and storage, which is a mass storage device, like a computer system does, and various data may constitute a database system implemented in various structures.

(4) The electronic device may manage the data of one or more applications, services, and/or operating systems based on the database. For example, the electronic device may process the data of a database based on the running application, service, and/or operating system.

(5) When the electronic device recognizes database damage, the electronic device may perform a recovery operation on the database. If the process (e.g., the application) accesses the database being restored while recovering the damaged database in the electronic device, an error may occur in the database recovery operation in progress.

(6) Further, if the process accesses the database being restored while recovering the damaged database in the electronic device, the process may not normally recognize the database and a database error may occur.

BRIEF DESCRIPTION

- (7) Embodiments of the disclosure are not limited to the foregoing objectives, and other objectives would readily be appreciated by a skilled artisan from the following detailed description taken in conjunction with the accompanying drawings.
- (8) According to an embodiment, an electronic device includes a memory including a database file and at least one processor connected to the memory. The at least one processor may identify damage to the database file while a first application run on the electronic device accesses the database file, control a second application run on the electronic device to wait without accessing the database file until recovery of the damaged database file is completed, record recovery state information indicating that the database file is recovered if the recovery of the damaged database file is completed, and control the second application to access the recovered database file based on the recovery state information.
- (9) According to an embodiment, a method for operating an electronic device may include identifying damage to a database file while a first application run on the electronic device accesses the database file, controlling a second application run on the electronic device to wait without accessing the database file until recovery of the damaged database file is completed, recording recovery state information indicating that the database file is recovered based on identifying that the recovery of the damaged database file is completed, and controlling the second application to access the recovered database file based on the recovery state information.
- (10) According to an embodiment, a computer program product comprises a storage medium storing instructions configured to be executed by at least one processor of an electronic device to perform a plurality of operations. The plurality of operations comprising identifying that the database file is damaged while a first application running on the electronic device accesses the database file; controlling a second application running on the electronic device to wait without accessing the database file until recovery of the damaged database file is completed; recording recovery state information indicating that the database file is recovered if the recovery of the damaged database file is completed; and controlling the second application to access the recovered database file based on the recovery state information.
- (11) According to an embodiment, the electronic device may identify a database recovery operation or a database recovery state to reduce errors in the database recovery operation.
- (12) According to an embodiment of the disclosure, the electronic device may identify a database recovery operation to prevent conflicts and data errors between processes accessing the database being restored.
- (13) According to an embodiment, the electronic device may identify a database recovery state and prevent data loss when a process accesses the restored database.
-

Description

DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to an embodiment;
- (2) FIG. 2 is a block diagram illustrating an example of a program according to an embodiment;
- (3) FIG. 3 is a view illustrating an example of an operation related to a database stored in an electronic device according to an embodiment;
- (4) FIG. 4 is a view illustrating another example of an operation related to a database stored in an electronic device according to an embodiment;
- (5) FIG. 5 is a view illustrating a case where a database file stored in an electronic device is damaged according to an embodiment;
- (6) FIG. 6 is a view illustrating a recovery operation of a database module implemented in an electronic device according to an embodiment;

- (7) FIG. 7 is a view illustrating a recovery operation of a database stored in an electronic device according to an embodiment;
- (8) FIG. 8 is a view illustrating a recovery operation identification logic of an electronic device according to an embodiment;
- (9) FIG. 9 is a view illustrating a recovery state identification logic of an electronic device according to an embodiment;
- (10) FIG. 10 is a view illustrating an example of metadata for a database file stored in an electronic device according to an embodiment;
- (11) FIG. 11 is a view illustrating a recovery information table for a database file stored in an electronic device according to an embodiment;
- (12) FIG. 12 is a view illustrating another example of metadata for a database file stored in an electronic device according to an embodiment;
- (13) FIG. 13 is a view illustrating a database recovery operation identification logic of an electronic device according to an embodiment;
- (14) FIGS. 14A and 14B are views illustrating an example of a database recovery state identification logic of an electronic device according to an embodiment;
- (15) FIGS. 15A and 15B are views illustrating another example of a database recovery state identification logic of an electronic device according to an embodiment; and
- (16) FIGS. 16A and 16B are views illustrating another example of a database recovery state identification logic of an electronic device according to an embodiment.

DETAILED DESCRIPTION

- (17) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to an embodiment.
- (18) Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with at least one of an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one (e.g., the connecting terminal **178**) of the components may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. According to an embodiment, some (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) of the components may be integrated into a single component (e.g., the display module **160**).
- (19) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes

the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be configured to use lower power than the main processor **121** or to be specified for a designated function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(20) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. The artificial intelligence model may be generated via machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(21) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(22) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(23) The input module **150** may receive a command or data to be used by other component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, keys (e.g., buttons), or a digital pen (e.g., a stylus pen).

(24) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(25) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display **160** may include a touch sensor configured to detect a touch, or a pressure sensor configured to measure the intensity of a force generated by the touch.

(26) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(27) The sensor module **176** may detect an operational state (e.g., power or temperature) of the

electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an accelerometer, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(28) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(29) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(30) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or motion) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(31) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(32) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(33) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(34) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device **104** via a first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or a second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., local area network (LAN) or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify or authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g.,

international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**. (35) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1ms or less) for implementing URLLC.

(36) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device). According to an embodiment, the antenna module **197** may include one antenna including a radiator formed of a conductor or conductive pattern formed on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., an antenna array). In this case, at least one antenna appropriate for a communication scheme used in a communication network, such as the first network **198** or the second network **199**, may be selected from the plurality of antennas by, e.g., the communication module **190**. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, other parts (e.g., radio frequency integrated circuit (RFIC)) than the radiator may be further formed as part of the antenna module **197**.

(37) According to an embodiment, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(38) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(39) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. The external electronic devices **102** or **104** each may be a device of the same or a different type from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The

electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an Internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(40) The electronic device according to an embodiment of the disclosure may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(41) It should be appreciated that an embodiment of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(42) As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(43) An embodiment as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(44) According to an embodiment, a method according to an embodiment of the disclosure may be

included and provided in a computer program product. The computer program products may be traded as commodities between sellers and buyers. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., Play Store™), or between two user devices (e.g., smartphones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(45) According to an embodiment, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities. Some of the plurality of entities may be separately disposed in different components. According to an embodiment, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to an embodiment, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to an embodiment, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(46) FIG. 2 is a block diagram **200** illustrating the program **140** according to an embodiment. According to an embodiment, the program **140** may include an operating system (OS) **142** to control one or more resources of the electronic device **101**, middleware **144**, or an application **146** executable in the OS **142**. The OS **142** may include, for example, Android™, iOS™, Windows™, Symbian™, Tizen™, or Bada™. At least part of the program **140**, for example, may be pre-loaded on the electronic device **101** during manufacture, or may be downloaded from or updated by an external electronic device (e.g., the electronic device **102** or **104**, or the server **108**) during use by a user.

(47) The OS **142** may control management (e.g., allocating or deallocation) of one or more system resources (e.g., process, memory, or power source) of the electronic device **101**. The OS **142**, additionally or alternatively, may include one or more driver programs to drive other hardware devices of the electronic device **101**, for example, the input module **150**, the sound output module **155**, the display module **160**, the audio module **170**, the sensor module **176**, the interface **177**, the haptic module **179**, the camera module **180**, the power management module **188**, the battery **189**, the communication module **190**, the subscriber identification module **196**, or the antenna module **197**.

(48) The middleware **144** may provide various functions to the application **146** such that a function or information provided from one or more resources of the electronic device **101** may be used by the application **146**. The middleware **144** may include, for example, an application manager **201**, a window manager **203**, a multimedia manager **205**, a resource manager **207**, a power manager **209**, a database manager **211**, a package manager **213**, a connectivity manager **215**, a notification manager **217**, a location manager **219**, a graphic manager **221**, a security manager **223**, a telephony manager **225**, or a voice recognition manager **227**.

(49) The application manager **201**, for example, may manage the life cycle of the application **146**. The window manager **203**, for example, may manage one or more graphical user interface (GUI) resources that are used on a screen. The multimedia manager **205**, for example, may identify one or more formats to be used to play media files, and may encode or decode a corresponding one of the media files using a codec appropriate for a corresponding format selected from the one or more formats. The resource manager **207**, for example, may manage the source code of the application **146** or a memory space of the memory **130**. The power manager **209**, for example, may manage the

capacity, temperature, or power of the battery **189**, and determine or provide related information to be used for the operation of the electronic device **101** based at least in part on corresponding information of the capacity, temperature, or power of the battery **189**. According to an embodiment, the power manager **209** may interwork with a basic input/output system (BIOS) (not shown) of the electronic device **101**.

(50) The database manager **211**, for example, may generate, search, or change a database to be used by the application **146**. The package manager **213**, for example, may manage installation or update of an application that is distributed in the form of a package file. The connectivity manager **215**, for example, may manage a wireless connection or a direct connection between the electronic device **101** and the external electronic device. The notification manager **217**, for example, may provide a function to notify a user of an occurrence of a specified event (e.g., an incoming call, message, or alert). The location manager **219**, for example, may manage locational information on the electronic device **101**. The graphic manager **221**, for example, may manage one or more graphic effects to be offered to a user or a user interface related to the one or more graphic effects.

(51) The security manager **223**, for example, may provide system security or user authentication. The telephony manager **225**, for example, may manage a voice call function or a video call function provided by the electronic device **101**. The voice recognition manager **227**, for example, may transmit a user's voice data to the server **108**, and receive, from the server **108**, a command corresponding to a function to be executed on the electronic device **101** based at least in part on the voice data, or text data converted based at least in part on the voice data. According to an embodiment, the middleware **244** may dynamically delete some existing components or add new components. According to an embodiment, at least part of the middleware **144** may be included as part of the OS **142** or may be implemented as another software separate from the OS **142**.

(52) The application **146** may include, for example, a home **251**, dialer **253**, short message service (SMS)/multimedia messaging service (MMS) **255**, instant message (IM) **257**, browser **259**, camera **261**, alarm **263**, contact **265**, voice recognition **267**, email **269**, calendar **271**, media player **273**, album **275**, watch **277**, health **279** (e.g., for measuring the degree of workout or biometric information, such as blood sugar), or environmental information **281** (e.g., for measuring air pressure, humidity, or temperature information) application. According to an embodiment, the application **146** may further include an information exchanging application (not shown) that is capable of supporting information exchange between the electronic device **101** and the external electronic device. The information exchange application, for example, may include a notification relay application adapted to transfer designated information (e.g., a call, message, or alert) to the external electronic device or a device management application adapted to manage the external electronic device. The notification relay application may transfer notification information corresponding to an occurrence of a specified event (e.g., receipt of an email) at another application (e.g., the email application **269**) of the electronic device **101** to the external electronic device. Additionally or alternatively, the notification relay application may receive notification information from the external electronic device and provide the notification information to a user of the electronic device **101**.

(53) The device management application may control the power (e.g., turn-on or turn-off) or the function (e.g., brightness, resolution, or focus) of the external electronic device or some component thereof (e.g., a display module or a camera module of the external electronic device). The device management application, additionally or alternatively, may support installation, delete, or update of an application running on the external electronic device.

(54) FIG. 3 is a view illustrating an example of an operation related to a database stored in an electronic device according to an embodiment.

(55) The electronic device **101** may correspond to at least one of a smartphone, a smart pad, a tablet PC, a personal digital assistance (PDA), a laptop PC, or a desktop PC. The electronic device **101** may include a processor **120**, a memory **130**, and a display module **160**. The electronic device **101**

may be at least partially identical to the electronic device **101** shown in FIG. **1**.

(56) According to an embodiment, the processor **120** may execute one or more instructions stored in the memory **130**. The processor **120** may include at least one of circuits for processing data, e.g., an integrated circuit (IC), an arithmetic logic unit (ALU), a field programmable gate array (FPGA), and a large scale integration (LSI). The memory **130** may store data related to the electronic device **101**. The memory **130** may include a volatile memory **132** or a non-volatile memory **134**. The non-volatile memory **134** may be in the form of an internal memory **136** included in the electronic device **101** and/or an external memory **138** detachable to the electronic device **101**.

(57) According to an embodiment, the memory **130** may store instructions related to the application **146** and instructions related to an operating system (e.g., the operating system **142** of FIG. **1**). The operating system may be system software executed by the processor **120**. The processor **120** may manage the hardware components (e.g., the memory **130** of FIG. **1** to the antenna module **197** of FIG. **1**) included in the electronic device **101** by executing the operating system. The operating system may provide an application programming interface (API) to the application **146** that is the remaining software except for the system software.

(58) According to an embodiment, one or more applications **146** that are a set of a plurality of instructions may be installed in the memory **130**. That the application **146** is installed in the memory **130** may mean that the application **146** is stored in a format that may be executed by the processor **120** connected to the memory **130**.

(59) According to an embodiment, the display module **160** may visually output information to the user through at least one of organic light emitting diodes (OLEDs), liquid crystal displays (LCDs), and light emitting diodes (LEDs). According to an embodiment, to more intuitively control the user interface (UI) output through the display module **160**, the electronic device **101** may include a touch sensor panel (touchscreen panel, TSP) (not shown) disposed on the display module **160**.

(60) According to an embodiment, the program **140** may include a database manager **211** and/or a database (DB) library **310** to provide functions for performing data processing between the application **146** and the database **330**. The DB library **310** may be included in middleware (e.g., the middleware **144** of FIGS. **1** and **2**). The middleware may provide various functions to the application **146** such that a function or information provided from one or more resources of the electronic device **101**, such as the database **330**, may be used by the application **146**. The electronic device **101** may create, search, or change the database **330** by the application **146** based on the database manager **211** and/or the DB library **310**.

(61) According to an embodiment, the DB library **310** may include a data log and recovery manager **315** that manages the modified data of the database **330** based on the application **146** and detects and recovers errors related to data modifications. According to an embodiment, when the function for processing or modifying the data of the database **330** included in the DB library **310** is executed based on the application **146** running on the electronic device **101**, the electronic device **101** may access the data (or database file) included in the database **330** through the file system **320**. When the data (or database file) is transferred from the file system **320** to the application **146**, the electronic device **101** may ensure consistency and/or integrity of data based on the data log and recovery manager **315**.

(62) According to an embodiment, the electronic device **101** may manage the data stored in the storage based on the volatile memory **132** based on the file system **320**. According to an embodiment, the electronic device **101** may manage the location where the data (e.g., file) of the database **330** is stored using the file system **320**. According to an embodiment, the file system **320** may be included in the operating system.

(63) According to an embodiment, the electronic device **101** may set at least part of the volatile memory **132** and/or non-volatile memory **134** of the memory **130**, as storage. The storage may correspond to a storage area where data related to the electronic device **101** is stored. Hereinafter, the memory may refer to a portion of the volatile memory **132** and/or the non-volatile memory **134**

that is distinct from the storage area. For example, the memory may correspond to a task area for processing data related to the electronic device **101**.

(64) According to an embodiment, the electronic device **101** may manage data related to the application **146** based on the database **330**. The database **330** is a set of structured data and may refer to a set of data stored in storage based on a designated list or data structure.

(65) According to an embodiment, applications and services installed in the electronic device **101** may operate based on the database **330**. According to an embodiment, access to the database **330** by a plurality of different applications and services may occur frequently while the electronic device **101** is operating. According to an embodiment, the number of databases **330** stored in the storage of the electronic device **101** is not limited to the embodiment illustrated in FIG. 3, and may be plural.

(66) According to an embodiment, in order for the electronic device **101** to execute the application **146** without an error, the electronic device **101** may guarantee data integrity that maintains data stored in the database **330** in a normal state while ensuring the atomicity of the transaction related to the database **330**. Atomicity may mean that the results of computation of data of the database **330** based on all operations included in one transaction are all stored or none are stored in the database **330**.

(67) According to an embodiment, transaction may mean a unit of an operation performed to change the state of the database **330**. According to an embodiment, a transaction is a logical unit of work (LUW) of operations related to the data of the database **330** and may be a unit of interaction between the application **146** and the database **330**. The operation related to the data of the database **330** may mean, e.g., an operation for accessing the database **330** based on a structured query language (SQL), such as OPEN, SELECT, INSERT, DELETE, UPDATE, or CLOSE.

(68) According to an embodiment, one transaction may mean a set of one or more operations and/or query words related to the data of the database **330**. According to an embodiment, operations included in a transaction and related to the data of the database **330** may include a data read operation, data addition operation, data deletion operation, and data modification operation. Commit of a transaction may mean that all operations related to data included in the transaction have been successfully performed.

(69) According to an embodiment, the electronic device **101** may guarantee the integrity and atomicity of data of the database **330** based on the database manager **211** and/or the data log and recovery manager **315**. For example, the electronic device **101** may ensure the integrity and atomicity of the data of the database **330** by managing the modified data of the database **330** based on a journal scheme. The journal scheme may include a write-ahead logging (WAL) scheme and/or a roll-back scheme.

(70) According to an embodiment, the electronic device **101** may include an SQLite-based database **330**. The electronic device **101** may ensure the atomicity of the transaction by accessing the SQLite-based database **330** according to the WAL scheme.

(71) FIG. 4 is a view illustrating another example of an operation related to a database stored in an electronic device according to an embodiment.

(72) Referring to FIG. 4, an electronic device **400** (e.g., the electronic device **101** of FIG. 1 or the electronic device **101** of FIG. 3) may include an application **410**, a database (DB) module **415**, and a database **460**. According to an embodiment, the DB module **415** may include a database manager **420** (e.g., the database manager **211** of FIG. 2 or the database manager **211** of FIG. 3) implemented on a first layer, an error handler **430** implemented on the first layer, a recovery manager **440** implemented on the first layer, and a DB library **450** implemented on a second layer. According to an embodiment, the first layer may be implemented as a java layer used on Android OS, and the second layer may be implemented as a native layer used on Android OS, for instance.

(73) According to an embodiment, the DB module **415** may be implemented in the processor (e.g., the processor **120** of FIG. 1 or the processor **120** of FIG. 3) in the electronic device. According to

an embodiment, the DB module **415** may provide a function for performing processing of data between the application **410** and the database **460**. According to an embodiment, the DB module **415** may perform generation, search or modification of the database **460** by the application **410**. According to an embodiment, the DB module **415** may detect and/or restore data file errors in the database **460** when accessing the application **410**.

(74) According to an embodiment, the application **410** may be implemented as the application **146** of FIGS. **1** to **3**. According to an embodiment, the error handler **430** may be included in the database manager **211**. According to an embodiment, the recovery manager **440** may be implemented as the recovery manager **315** of FIG. **3**, and the DB library **450** may be implemented as the DB library **310** of FIG. **3**, and the database **460** may be implemented as the database **330** of FIG. **3**.

(75) According to an embodiment, when the database engine used on the Android OS is SQLite, the database manager **420** may be implemented using an SQLiteDatabase, and the DB library **450** may be implemented as libsqlite.so. According to an embodiment, the database manager **420** may process a code set existing on the DB framework according to an open and/or query command for the database **460** performed by the application **410**. According to an embodiment, the DB library **450** may be implemented on the native layer, where the programming language used in the Android OS is executed.

(76) According to an embodiment, the application **410** may transmit a database open request to the DB module **415**, and the DB module **415** may transmit an open, read, and/or write command to the database **460** through the file system (e.g., the file system **320** of FIG. **3**). According to an embodiment, the DB module **415** may transmit, to the application **410**, result information according to the open, read, and/or write command transmitted to the database **460**.

(77) According to an embodiment, the database file in the database **460** may be damaged due to an unexpected system or hardware error during operation of the electronic device **400**. According to an embodiment, when the header or schema of the database **460** is damaged, critical metadata may not be accessed, so that access to the database **460** may be impossible. According to an embodiment, even when some data in the database **460** is damaged, the remaining data may not be accessed, so that the database **460** may be initialized. For example, if the database **460** is initialized, critical user data, such as existing user data, contacts, or messages, may be lost. According to an embodiment, the electronic device **400** may extract valid user data from the damaged database file through various database recovery schemes and constitute a new database file, thereby recovering the damaged database file.

(78) FIG. **5** is a view illustrating a case where a database file stored in an electronic device is damaged according to an embodiment.

(79) Referring to FIG. **5**, a first application **510** run on the electronic device (e.g., the electronic device **101** of FIG. **1**, the electronic device **101** of FIG. **3**, or the electronic device **400** of FIG. **4**) may access the database file **530** and then recognize damage to the database file **530** and perform recovery of the database file **530**. For example, a first page (page 1) in the database file **530** may be partially damaged, and a whole *i*th page (page *i*) may be damaged.

(80) According to an embodiment, a second application **520** run on the electronic device may access the damaged database file **530** to access the damaged database file **530**. According to an embodiment, when the second application **520** accesses the database file **530** while the first application **510** recovers the database file **530**, the recovery process in progress may not normally be performed. According to an embodiment, the second application **520** accessing the database file **530** while the first application **510** recovers the database file **530** may fail to normally recognize the database file **530**, causing an additional error.

(81) According to an embodiment, when the process conflicts between the applications **510** and **520**, the recovery process for the database file may not normally be performed but may fail, causing loss of the critical user data.

(82) According to an embodiment, the database file normally recovered by the recovery logic of the first application **510** may not perfectly match the database file before damaged, so that an unexpected operation may be caused in the second application **520** when the second application **520** accesses the recovered database file.

(83) FIG. **6** is a view illustrating a recovery operation of a database module implemented in an electronic device according to an embodiment.

(84) Referring to FIG. **6**, in operation **601**, an application (e.g., the application **410** of FIG. **4**) run on the electronic device (e.g., the electronic device **101** of FIG. **1**, the electronic device **101** of FIG. **3**, or the electronic device **400** of FIG. **4**) may send a request for database (DB) open to the database module (e.g., the DB module **415** of FIG. **4**). In operation **603**, the database module may check the consistency of the database (or database file). In operation **605**, the database module may detect (or identify) whether the database (or database file) is damaged.

(85) When the database (or database file) is detected as not damaged (no in **605**) in operation **605**, in operation **607**, the application may determine that the DB open for which the database module has been requested succeeds. According to an embodiment, when the database (or database file) is not damaged, the database module may transmit a message indicating that DB open succeeds to the application.

(86) When the database (or database file) is detected as damaged in operation **605** (yes in **605**), in operation **609**, the database module may attempt to recover the database (or database file). In operation **611**, the database module may determine whether the recovery of the database (or database file) succeeds.

(87) When it is determined in operation **611** that the recovery of the database (or database file) succeeds (yes in **611**), in operation **607**, the application may determine that the DB open for which the database module has been requested succeeds. According to an embodiment, when the recovery of the database (or database file) succeeds, the database module may transmit a message indicating that DB open succeeds to the application.

(88) When the recovery of the database (or database file) does not succeed as a result of the determination in operation **611** (no in **611**), in operation **613**, the database (or database file) may be initialized. In operation **615**, the database module may transfer a message indicating a DB open failure (or error) to the application. In operation **617**, the application may receive the message indicating the DB open failure (or error) and know that DB open fails.

(89) According to an embodiment, the application may transfer damage to the database (or database file) to the error handler (the error handler **430** of FIG. **4**) included in the database module, and the error handler (the error handler **430** of FIG. **4**) may request the recovery manager (the recovery manager **440** of FIG. **4**) to recover the database (or database file). According to an embodiment, the recovery manager (the recovery manager **440** of FIG. **4**) may transfer a recovery request to the native layer to perform recovery.

(90) FIG. **7** is a view illustrating a recovery operation of a database stored in an electronic device according to an embodiment.

(91) Referring to FIG. **7**, an electronic device **700** (e.g., the electronic device **101** of FIG. **1**, the electronic device **101** of FIG. **3**, or the electronic device **400** of FIG. **4**) may include an application **710**, a database (DB) module **715**, and a database **760**. According to an embodiment, the DB module **715** may include a database manager **720** (e.g., the database manager **211** of FIG. **2** or the database manager **211** of FIG. **3**) implemented on a first layer, an error handler **730** implemented on the first layer, a recovery manager **740** implemented on the first layer, and a DB library **750** implemented on a second layer. According to an embodiment, the first layer may be implemented as a Java layer used on Android OS, and the second layer may be implemented as a native layer used on Android OS.

(92) According to an embodiment, the DB module **715** may be implemented in the processor (e.g., the processor **120** of FIG. **1** or the processor **120** of FIG. **3**) in the electronic device. According to

an embodiment, the DB module **715** may provide a function for performing processing of data between the application **10** and the database **60**. According to an embodiment, the DB module **715** may perform generation, search or modification of the database **760** by the application **710**. According to an embodiment, the DB module **715** may detect and/or restore database file errors in the database **760** when accessing the application **710**.

(93) According to an embodiment, the application **710** may be implemented as the application **146** of FIGS. **1** to **3**. According to an embodiment, the error handler **730** may be included in the database manager **720**. According to an embodiment, the recovery manager **740** may be implemented as the recovery manager **315** of FIG. **3**, and the DB library **750** may be implemented as the DB library **310** of FIG. **3**, and the database **760** may be implemented as the database **330** of FIG. **3**.

(94) According to an embodiment, the DB library **750** may include a recovery operation identification logic **751** and a recovery state identification logic **753**. According to an embodiment, the recovery operation identification logic **751** may be for identifying a recovery operation for a database (or database file). According to an embodiment, the recovery state identification logic **753** may be for identifying whether a database (or database file) is in a recovered state.

(95) According to an embodiment, when the database engine used on the Android OS is SQLite, the database manager **720** may be implemented using an SQLiteDatabase, and the DB library **750** may be implemented as libsqlite.so. According to an embodiment, the database manager **720** may process a code set existing on the DB framework according to an open and/or query command for the database **760** performed by the application **710**. According to an embodiment, the DB library **750** may be implemented on the native layer where the programming language used in the Android OS is executed.

(96) According to an embodiment, the application **710** may transmit a database open request to the DB module **715**, and the DB module **715** may transmit an open, read, and/or write command to the database **760** through the file system (e.g., the file system **320** of FIG. **3**). According to an embodiment, the DB module **715** may transmit, to the application **710**, result information according to the open, read, and/or write command transmitted to the database **760**.

(97) According to an embodiment, the recovery operation identification logic **751** may identify that the application run on the electronic device **700** performs a recovery process on the database (or database file). According to an embodiment, the recovery operation identification logic **751** may allow the second application to wait without accessing the database (or database file) by identifying the recovery process on the database (or database file) performed when the first application requests DB open.

(98) According to an embodiment, when the application run on the electronic device **700** completes the recovery process for the database (or database file), the recovery state identification logic **753** may identify that the database (or database file) is a recovered database (or database file). According to an embodiment, as the first application identifies that the database (or database file) is recovered by the recovery process performed when requesting DB open, the recovery state identification logic **753** may allow the second application to consider access to the database (or database file) when the database (or database file) is accessed.

(99) FIG. **8** is a view illustrating a recovery operation identification logic of an electronic device according to an embodiment.

(100) Referring to FIG. **8**, a first application **810** run on an electronic device (e.g., the electronic device **101** of FIG. **1**, the electronic device **101** of FIG. **3**, the electronic device **400** of FIG. **4**, or the electronic device **700** of FIG. **7**) may access a database file **830** and, then, the database module (e.g., the DB module **715** of FIG. **7**) may recognize (or identify) damage to the database file **830**, and a recovery process for the database file **830** may be performed by the database module. For example, the database module may identify that part of the first page (page 1) in the database file **830** is damaged, and an entire ith page (page i) is damaged and recover them.

(101) According to an embodiment, the database module may set a file lock indicating that the database file **830** is being recovered before starting the recovery process for the database file **830**. According to an embodiment, the file lock may be an exclusive lock that may be uniquely set in the database file **830**. According to an embodiment, the file lock may be generated and/or managed by the file system (the file system **320** of FIG. **3**) in the electronic device.

(102) According to an embodiment, the file lock may be implemented as a variable that may be set to true or false (e.g., a Boolean value). For example, if the variable of the file lock is set to true, it may be recognized that the file lock is set in the database file **830** and, if the variable of the file lock is set to false, it may be recognized that the file lock is not set in the database file **830**.

(103) According to an embodiment, the second application **820** run on the electronic device may identify the file lock set in the database file **830** when accessing the database file **830** being recovered and may wait without accessing the database file **830**. For example, when accessing the database file **830**, the second application **820** may identify that the variable of the file lock set in the database file **830** is true and wait without accessing the database file **830** until the variable of the file lock is changed to false. According to an embodiment, when recovery of the database file **830** is completed without separate modification, the second application **820** may seamlessly access the database file **830**.

(104) FIG. **9** is a view illustrating a recovery state identification logic of an electronic device according to an embodiment.

(105) Referring to FIG. **9**, after an application run on an electronic device (e.g., the electronic device **101** of FIG. **1**, the electronic device **101** of FIG. **3**, the electronic device **400** of FIG. **4**, or the electronic device **700** of FIG. **7**) accesses the database file **920**, the database module may recognize damage to the database file **920** and perform a recovery process for the database file **920**. For example, the database module may identify that part of the first page (page 1) in the database file **920** is damaged, and an entire ith page (page i) is damaged and recover them.

(106) According to an embodiment, the database module may identify that the database file **920** is normally restored using the recovery state identification logic **910**. According to an embodiment, after normally recovering the damaged database file **920**, the database module may store information indicating that the database file **920** is normally recovered in the storage **940** through the attribute of the metadata **930** for the database file **920**.

(107) According to an embodiment, the electronic device may record whether the database file **920** is normally recovered through an extended attribute (e.g., xattr) of an index node (e.g., Mode) which is the metadata for system files, such as Linux system files. According to an embodiment, the extended attribute of an index node may mean a metadata area that may be additionally defined by the user. According to an embodiment, the key value of the extended attribute of an index node may be set to "recovered," indicating that the database file **920** is normally recovered.

(108) According to an embodiment, another application run on the electronic device may identify a specific attribute of the metadata **930** for the database file **920**, identify whether the database file **920** is normally recovered, recognize that the database file **920** is a recovered database file based on the result of the identification, and access the database file **920**.

(109) FIG. **10** is a view illustrating an example of metadata for a database file stored in an electronic device according to an embodiment.

(110) Referring to FIG. **10**, the database module (e.g., the DB module **715** of FIG. **7**) may identify that the database file **1000** (or database) is damaged and perform a recovery process on the damaged database file **1000**. According to an embodiment, after recovering the damaged database file **1000**, the database module may generate a recovered database file **1010** and metadata **1012** for the recovered database file **1010**. According to an embodiment, the metadata **1012** may include attribute information indicating that the database file **1010** is a database file recovered and generated.

(111) FIG. **11** is a view illustrating a recovery information table for a database file stored in an

electronic device according to an embodiment.

(112) Referring to FIG. 11, after recovery of the database (or database file) is completed, the database module (e.g., the DB module 715 of FIG. 7) may add a table to the database (or database file) to record that the database (or database file) is recovered.

(113) For example, a damaged database 1100 may include table one 1101 and table two 1103, and a recovered database 1110 may include table one 1111, table two 1113, and a recovery information table (recovered) 1115. For example, the recovery information table (recovered) 1115 may indicate that the database is recovered.

(114) FIG. 12 is a view illustrating another example of metadata for a database file stored in an electronic device according to an embodiment.

(115) Referring to FIG. 12, a database file (or database) 1200 may be stored in a unit of a page. According to an embodiment, the first page of the database file 1200 may be a metadata page 1210, and the metadata page 1210 may store information, such as a database header 1211 and schema.

(116) According to an embodiment, the metadata page 1210 may include recovery information (recovered) 1213 indicating that the database file is recovered, using a space not used in the metadata page 1210 in the database file 1200.

(117) FIG. 13 is a view illustrating a database recovery operation identification logic of an electronic device according to an embodiment.

(118) Referring to FIG. 13, in operation 1301, an application (e.g., the application 710 of FIG. 7) run on the electronic device (e.g., the electronic device 101 of FIG. 1, the electronic device 101 of FIG. 3, or the electronic device 700 of FIG. 7) may send a request for database (DB) open to the database module (e.g., the DB module 715 of FIG. 7). In operation 1303, the database module may check the consistency of the database (or database file). In operation 1305, the database module may detect whether the database (or database file) is damaged.

(119) When the database (or database file) is detected as damaged as a result of the determination in operation 1305 (yes in 1305), in operation 1307, the database module may determine whether the database recovery lock is set. When it is determined in operation 1307 that the database recovery lock is not set (no in 1307), in operation 1309, the database module may set the database recovery lock. In operation 1311, the database module may recover the database (or database file) and, in operation 1313, the database module may release the database recovery lock.

(120) In operation 1315, the database module may determine whether the recovery of the database (or database file) succeeds. When it is determined in operation 1315 that the recovery of the database (or database file) succeeds (yes in 1315), in operation 1317, the database module may record the database recovery state and, in operation 1319, the application may determine that the DB open for which the database module has been requested succeeds. According to an embodiment, when the recovery of the database (or database file) succeeds, the database module may transmit a message indicating that DB open succeeds to the application.

(121) When the recovery of the database (or database file) does not succeed as a result of the determination in operation 1315 (no in 1315), in operation 1321, the database (or database file) may be initialized. In operation 1323, the database module may transfer a message indicating that a DB open failure (or error) to the application. In operation 1325, the application may receive the message indicating the DB open failure (or error) and know that DB open fails.

(122) When it is determined in operation 1305 that damage to the database (or database file) is not detected (no in 1305) (e.g., when the database is not damaged), in operation 1319, the application may determine that the DB open for which the database module has been requested succeeds.

(123) When it is determined in operation 1307 that the database recovery lock is set (yes in 1307), in operation 1327, the application may wait a predetermined time. In operation 1329, the database module may determine whether the recovery of the database (or database file) succeeds. When it is determined in operation 1329 that the recovery of the database (or database file) succeeds (yes in 1329), in operation 1319, the application may determine that the DB open for which the database

module has been requested succeeds. According to an embodiment, when the recovery of the database (or database file) succeeds, the database module may transmit a message indicating that DB open succeeds to the application.

(124) When the recovery of the database (or database file) does not succeed as a result of the determination in operation **1329** (no in **1329**), in operation **1323**, the database module may transfer a message indicating DB open failure (or error) to the application. Thereafter, in operation **1325**, the application may receive the message indicating the DB open failure (or error) and know that DB open fails.

(125) According to an embodiment, if damage to the database (or database file) occurs when the application accesses the database (or database file), a logic for identifying whether the database (or database file) recovery operation is executed may be performed.

(126) According to an embodiment, the database recovery operation identification logic may be performed using a database recovery lock. According to an embodiment, the database recovery lock may be a file lock and may be a lock (exclusive lock) that may be uniquely set for the database file. According to an embodiment, before starting the database recovery, the database recovery lock may be set. According to an embodiment, when another application detects damage to the database (or database file), it is possible to determine whether the database recovery operation is being performed by identifying whether the database recovery lock is set.

(127) According to an embodiment, when recovery of the database (or database file) is successfully completed, information about the database (or database file) recovery state may be recorded on the metadata (e.g., the extended attribute area of the Linux system) for the database file. According to an embodiment, if recording of the database (or database file) recovery state is completed, the database recovery lock may be released.

(128) FIGS. **14A** and **14B** are views illustrating an example of a database recovery state identification logic of an electronic device according to an embodiment.

(129) Referring to FIG. **14A**, in operation **1401**, an electronic device (e.g., the electronic device **101** of FIG. **1**, the electronic device **101** of FIG. **3**, or the electronic device **700** of FIG. **7**) may start a database (DB) recovery state recording logic (e.g., the recovery state identification logic **753** of FIG. **7**) and, in operation **1403**, the electronic device may identify whether the DB is a DB for which the DB recovery function has been set.

(130) When it is determined in operation **1403** that the DB is a DB for which the DB recovery function has been set, in operation **1405**, the electronic device may record the content of the DB recovery in the metadata area (e.g., the xattr area of the linux system) of the DB file.

(131) Referring to FIG. **14B**, in operation **1412**, the application (e.g., the application **710** of FIG. **7**) run on the electronic device may request the database module (e.g., the DB module **715** of FIG. **7**) to identify the DB recovery state. In operation **1414**, the database module may identify information about the metadata area (e.g., the xattr area of the linux system) of the DB file and, in operation **1416**, the database module may determine whether the DB is a DB for which recovery task has been performed. According to an embodiment, the database module may fetch the entire xattr information of the database file to identify the database recovery state and then identify whether database recovery record is stored in the xattr information.

(132) When it is determined in operation **1416** that the DB is a DB for which the recovery task has been performed, in operation **1418**, the database module may transfer a message indicating that the DB is in a recovered state to the application. When it is determined in operation **1416** that the DB is not a DB for which recovery task has been performed, in operation **1420**, the database module may transfer a message indicating that the DB is in a non-recovered state to the application.

(133) FIGS. **15A** and **15B** are views illustrating another example of a database recovery state identification logic of an electronic device according to an embodiment.

(134) Referring to FIG. **15A**, in operation **1501**, an electronic device (e.g., the electronic device **101** of FIG. **1**, the electronic device **101** of FIG. **3**, or the electronic device **700** of FIG. **7**) may start

a database (DB) recovery state recording logic (e.g., the recovery state identification logic **753** of FIG. 7) and, in operation **1503**, the electronic device may identify whether the DB is a DB for which the DB recovery function has been set.

(135) When it is determined in operation **1503** that the DB is a DB for which the DB recovery function has been set, in operation **1505**, the electronic device may record the content of the DB recovery in the metadata page of the DB file.

(136) Referring to FIG. **15B**, in operation **1512**, the application (e.g., the application **710** of FIG. 7) run on the electronic device may request the database module (e.g., the DB module **715** of FIG. 7) to identify the DB recovery state. In operation **1514**, the database module may identify information about the metadata page of the DB file and, in operation **1516**, the database module may determine whether the DB is a DB for which a recovery task has been performed.

(137) When it is determined in operation **1516** that the DB is a DB for which the recovery task has been performed, in operation **1518**, the database module may transfer a message indicating that the DB is in a recovered state to the application. When it is determined in operation **1516** that the DB is not a DB for which recovery task has been performed, in operation **1520**, the database module may transfer a message indicating that the DB is in a non-recovered state to the application.

(138) FIGS. **16A** and **16B** are views illustrating another example of a database recovery state identification logic of an electronic device according to an embodiment.

(139) Referring to FIG. **16A**, in operation **1601**, an electronic device (e.g., the electronic device **101** of FIG. 1, the electronic device **101** of FIG. 3, or the electronic device **700** of FIG. 7) may start a database (DB) recovery state recording logic (e.g., the recovery state identification logic **753** of FIG. 7) and, in operation **1603**, the electronic device may identify whether the DB is a DB for which the DB recovery function has been set.

(140) When it is determined in operation **1603** that the DB is a DB for which the DB recovery function has been set, in operation **1605**, the electronic device may add a new table to the DB and record the content of the DB recovery.

(141) Referring to FIG. **16B**, in operation **1612**, the application (e.g., the application **710** of FIG. 7) run on the electronic device may request the database module (e.g., the DB module **715** of FIG. 7) to identify the DB recovery state. In operation **1614**, the database module may identify table information of the DB and, in operation **1616**, the database module may determine whether the DB is a DB for which recovery task has been performed.

(142) When it is determined in operation **1616** that the DB is a DB for which the recovery task has been performed, in operation **1618**, the database module may transfer a message indicating that the DB is in a recovered state to the application. When it is determined in operation **1616** that the DB is not a DB for which a recovery task has been performed, in operation **1620**, the database module may transfer a message indicating that the DB is in a non-recovered state to the application.

(143) According to an embodiment, an electronic device (e.g., the electronic device **101** of FIG. 1, the electronic device **101** of FIG. 3, or the electronic device **700** of FIG. 7) may include a memory (e.g., the memory **130** of FIG. 1 or the memory **130** of FIG. 3) including a database file and at least one processor (e.g., the processor **120** of FIG. 1, the processor **120** of FIG. 3, or the DB module **715** of FIG. 7) connected to the memory.

(144) According to an embodiment, the at least one processor may identify damage to the database file while a first application run on the electronic device accesses the database file. According to an embodiment, the at least one processor may control a second application run on the electronic device to wait without accessing the database file until recovery of the damaged database file is completed. According to an embodiment, the at least one processor may record recovery state information indicating that the database file is recovered if the recovery of the damaged database file is completed. According to an embodiment, the at least one processor may control the second application to access the recovered database file based on the recovery state information.

(145) According to an embodiment, the at least one processor may set a file lock on the damaged

database file to indicate that the database file is being recovered. According to an embodiment, the at least one processor may recover the damaged database file. According to an embodiment, the file lock may be an exclusive lock uniquely set for the database file. According to an embodiment, the at least one processor may release the file lock for the database file if the recovery of the damaged database file succeeds.

(146) According to an embodiment, if the recovery state information is set to a first value, it may indicate that the database file is recovered, and if the recovery state information is set to a second value, it may indicate that the database file is not recovered. According to an embodiment, the recovery state information may be implemented as a user defined attribute included in metadata for the database file. According to an embodiment, the user defined attribute may be set as an Mode xattr used in a linux system. According to an embodiment, the recovery state information may be implemented as a table included in the recovered database file. According to an embodiment, the database file may be constituted of a plurality of pages, and the recovery state information may be included in a first page in the database file.

(147) According to an embodiment, the at least one processor may include a database library (e.g., the DB library 750 of FIG. 7). The database library may be set to include a first logic (e.g., the recovery operation identification logic 751 of FIG. 7) for identifying a recovery operation for the database file and a second logic (e.g., the recovery state identification logic 733 of FIG. 7) for identifying a recovery state for the database file.

Claims

1. An electronic device comprising: at least one processor including processing circuitry; and memory including one or more storage mediums storing instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: receive a request from a first application running on the electronic device to open a database file, wherein the database file is stored in the memory, identify that the database file is damaged as a damaged database file responsive to the first application running on the electronic device requesting to open the database file, set a file lock on the damaged database file to indicate that the database file is being recovered, identify a second application running on the electronic device that wants to access the damaged database file while recovering the database file, based on the file lock, identify that the database file is being recovered and control the second application to wait without accessing the damaged database file until recovery of the damaged database file is completed, record recovery state information indicating that the damaged database file is recovered as a recovered database file based on identifying that the recovery of the damaged database file is completed, release the file lock for the database file based on the recovery of the damaged database file succeeding and after completion of recording the recovery state information, and control the second application to access the recovered database file based on the recovery state information, wherein the recovered database file is accessible by the first application.
2. The electronic device of claim 1, wherein the instructions, when executed by the processing circuitry individually or collectively, cause the electronic device to recover the damaged database file using the first application accessing on the database file.
3. The electronic device of claim 1, wherein the file lock is an exclusive lock uniquely set for the database file.
4. The electronic device of claim 1, wherein based on the recovery state information being set to a first value, the first value indicates that the damaged database file is recovered, and based on the recovery state information being set to a second value, the second value indicates that the damaged database file is not recovered.
5. The electronic device of claim 1, wherein the recovery state information is implemented as a user defined attribute included in metadata for the database file.

6. The electronic device of claim 5, wherein the user defined attribute is set as an extended attribute of an index node of a file system.
7. The electronic device of claim 1, wherein the recovery state information is implemented as a table included in the recovered database file.
8. The electronic device of claim 1, wherein the database file is constituted of a plurality of pages, and wherein the recovery state information is included in a first page in the database file.
9. The electronic device of claim 1, wherein the at least one processor includes a database library, and wherein the database library is set to include a first logic for identifying a recovery operation for the damaged database file and a second logic for identifying a recovery state for the damaged database file.
10. A method for operating an electronic device, the method comprising: receiving a request from a first application running on the electronic device to open a database file, wherein the database file is stored in memory of the electronic device; identifying, by at least one processor of the electronic device executing a plurality of instructions stored in a memory of the electronic device, that the database file is damaged as a damaged database file responsive to a first application running on the electronic device requesting to open the database file; setting a file lock on the damaged database file to indicate that the database file is being recovered; identifying a second application running on the electronic device that wants to access the damaged database file while recovering the database file; based on the lock, identifying that the database file is being recovered and controlling, by the at least one processor of the electronic device, the second application to wait without accessing the damaged database file until recovery of the damaged database file is completed; recording, by the at least one processor of the electronic device, recovery state information indicating that the damaged database file is recovered as a recovered database file based on identifying that the recovery of the damaged database file is completed; releasing the file lock for the database file based on the recovery of the damaged database file succeeding and after completion of recording the recovery state information; and controlling, by the at least one processor of the electronic device, the second application to access the recovered database file based on the recovery state information, wherein the recovered database file is accessible by the first application.
11. The method of claim 10, further comprising: recovering, by the at least one processor, the damaged database file using the first application accessing on the database file.
12. The method of claim 10, wherein the file lock is an exclusive lock uniquely set for the database file.
13. The method of claim 10, wherein based on the recovery state information being set to a first value, the first value indicates that the damaged database file is recovered, and based on the recovery state information being set to a second value, the second value indicates that the damaged database file is not recovered.
14. The method of claim 10, wherein the recovery state information is implemented as a user defined attribute included in metadata for the database file.
15. The method of claim 14, wherein the user defined attribute is set as an extended attribute of an index node of a file system.
16. The method of claim 10, wherein the recovery state information is implemented as a table included in the recovered database file.
17. The method of claim 10, wherein the database file is constituted of a plurality of pages, and wherein the recovery state information is included in a first page in the database file.
18. A computer program product comprising a non-transitory storage medium storing instructions that, when executed by at least one processor of an electronic device individually or collectively, cause the electronic device to perform a plurality of operations, the plurality of operations comprising: receiving a request from a first application running on the electronic device to open a database file, wherein the database file is stored in memory of the electronic device; identifying that the database file stored in a memory of the electronic device is damaged as a damaged

database file responsive to a first application running on the electronic device requesting to open the database file; setting a file lock on the damaged database file to indicate that the database file is being recovered; identifying a second application running on the electronic device that wants to access the damaged database file while recovering the database file; based on the lock, identifying that the database file is being recovered and controlling the second application to wait without accessing the damaged database file until recovery of the damaged database file is completed; recording recovery state information in the electronic device indicating that the damaged database file is recovered as a recovered database file based on identifying that the recovery of the damaged database file is completed; releasing the file lock for the database file based on the recovery of the damaged database file succeeding and after completion of recording the recovery state information; and controlling the second application to access the recovered database file based on the recovery state information, wherein the recovered database file is accessible by the first application.
