

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12400273
B2
August 26, 2025
Larson; Jim et al.

Methods and systems for submitting and/or processing insurance claims for damaged motor vehicle glass

Abstract

A method and system for submitting an insurance claim for damaged motor vehicle glass are provided that can include: receiving a plurality of images associated with motor vehicle glass at processing circuitry; performing image processing operations on each of the plurality of images to determine one or more of glass damage, glass type, and/or claim fraud; and submitting an insurance claim for motor vehicle glass repair or replace based on the glass type or damage, or flagging the claim as fraud. There is also provided a non-transitory computer readable storing instruction that when executed by a processor, causes a computer system to perform the following method. The method can include: prompting a user for initial claim submission information; prompting the user for a plurality of images of portions of motor vehicle glass, performing image processing operations on each of the plurality of images to train or improve the computer system, determine one or more of glass damage, glass type, and/or claim fraud; and one of submit or reject an insurance claim for glass repair.

Inventors: Larson; Jim (Chandler, AZ), Zabasajja; Edward (Chandler, AZ), Mullen; Craig J. (Phoenix, AZ), Nelson; Douglas J. (Chandler, AZ), Simmons; Deron (Chandler, AZ)

Applicant: Neural Claim System, Inc. (Chandler, AZ)

Family ID: 1000008778168

Assignee: Neural Claim System, Inc. (Chandler, AZ)

Appl. No.: 18/122085

Filed: March 15, 2023

Prior Publication Data

Document Identifier
US 20230214936 A1

Publication Date
Jul. 06, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 17198114 20210310 PENDING child-doc US 18122085
continuation-in-part parent-doc US 17016097 20200909 ABANDONED child-doc US 17198114
us-provisional-application US 62897746 20190909

Publication Classification

Int. Cl.: **G06Q40/08** (20120101); **G06V10/764** (20220101); **G06V10/94** (20220101); **G06V20/50** (20220101)

U.S. Cl.:

CPC **G06Q40/08** (20130101); **G06V10/764** (20220101); **G06V10/945** (20220101);
G06V20/50 (20220101);

Field of Classification Search

CPC: G06Q (40/08); G06Q (10/10); G06Q (10/20); G06Q (30/0185); G06V (10/764); G06V (10/945); G06V (20/50); G06V (10/245); G06V (10/25); G06V (20/62); G06N (20/00); G06N (5/025)

USPC: 705/3-44

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8364505	12/2012	Kane et al.	N/A	N/A
8527357	12/2012	Ganesan	705/26.1	G06Q 30/06
8712893	12/2013	Brandmaier et al.	N/A	N/A
9600733	12/2016	Wilbert et al.	N/A	N/A
9824453	12/2016	Collins et al.	N/A	N/A
9886771	12/2017	Chen et al.	N/A	N/A
9990662	12/2017	Couch et al.	N/A	N/A
10319094	12/2018	Chen et al.	N/A	N/A
10360601	12/2018	Adegan	N/A	N/A
10373260	12/2018	Haller, Jr. et al.	N/A	N/A
10706321	12/2019	Chen	N/A	G06T 3/4007
10733160	12/2019	Leise et al.	N/A	N/A
10803527	12/2019	Zankat	N/A	G06V 30/40
10909673	12/2020	Forutanpour et al.	N/A	N/A
11288789	12/2021	Chen	N/A	G06T 7/001
11361387	12/2021	Call	N/A	G06Q 50/16
2002/0188479	12/2001	Renwick et al.	N/A	N/A
2008/0172258	12/2007	Weger et al.	N/A	N/A
2012/0297337	12/2011	St. Denis et al.	N/A	N/A
2015/0317612	12/2014	Couch	N/A	N/A

2015/0332411	12/2014	Bush et al.	N/A	N/A
2017/0147991	12/2016	Franke et al.	N/A	N/A
2017/0221110	12/2016	Sullivan et al.	N/A	N/A
2017/0293894	12/2016	Taliwal et al.	N/A	N/A
2017/0315007	12/2016	Fitzgerald	N/A	G06F 3/0418
2017/0352104	12/2016	Hanson et al.	N/A	N/A
2017/0372465	12/2016	Forutanpour et al.	N/A	N/A
2018/0040039	12/2017	Wells et al.	N/A	N/A
2018/0182039	12/2017	Wang et al.	N/A	N/A
2018/0240194	12/2017	Dong et al.	N/A	N/A
2018/0260793	12/2017	Li et al.	N/A	N/A
2018/0293806	12/2017	Zhang et al.	N/A	N/A
2019/0114717	12/2018	Labrie	N/A	G06Q 40/08
2020/0090321	12/2019	Xu	N/A	N/A
2021/0081698	12/2020	Lindeman et al.	N/A	N/A
2021/0142464	12/2020	Tian et al.	N/A	N/A
2022/0122243	12/2021	Fitzgerald	N/A	G06V 10/25

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105405054	12/2015	CN	N/A
106203644	12/2015	CN	N/A
WO 2018/039560	12/2017	WO	N/A
WO 2018/055340	12/2017	WO	N/A

OTHER PUBLICATIONS

Shih-Lin, et al., “Technique on Vehicle Damage Assessment After Collisions Using Optical Radar Technology and Iterative Closest Point Algorithm”, IEEE Access 12 : 174507-174518. The Institute of Electrical and Electronics Engineers, Inc. (IEEE).. (Year: 2024). cited by examiner
EP EP 20862118 Extend. Search Rpt, Aug. 29, 2023, Neural Claim System Inc. cited by applicant
WO PCT/US2022/019649 IPRP, Sep. 21, 2023, Neural Claim System Inc. cited by applicant
WO PCT/US2024/020097 Search Rept., Jun. 26, 2024, Neural Claim System, Inc. cited by applicant
WO PCT/US2024/020097 Writ. Opin., Jun. 26, 2024, Neural Claim System, Inc. cited by applicant
WO PCT/US20/049978 Search Report, Nov. 27, 2020, Neural Claim System, Inc. cited by applicant
WO PCT/US20/049978 Written Opin, Nov. 27, 2000, Neural Claim System, Inc. cited by applicant
WO PCT/US2020/049978 IPRP, Mar. 9, 2022, Neural Claim System, Inc. cited by applicant
WO PCT/US2022/019649 Search Rept., May 23, 2022, Neural Claim System, Inc. cited by applicant
WO PCT/US2022/019649 Writ. Opin., May 23, 2022, Neural Claim System, Inc. cited by applicant
D'Angelo, “Classify vehicle damage images”, IBM Developer, Feb. 2018, 5 pages, United States. cited by applicant
Haller, “AI in Claims—It's Happening Now”, <https://www.cccis.com/category/insurance>) Feb. 2018, 4 pages, United States. cited by applicant
<https://www.glassbytes.com/2018/02/autoglass-launches-artificial-intelligence-technology>, Feb. 2018, 1 page, United States. cited by applicant
Huetter, “Mitchell gives details on photography, data set, decision-making under new AI crash

image analysis”, Repairer Driven News, Oct. 2016, 7 pages, United States. cited by applicant
Turo, “Automotive Insurance with TensorFlow: Estimating Damage/Repair Costs”,
www.altoros.com/blog/author/sophie-turo, Feb. 2018, 6 pages, United States. cited by applicant
EP EP 2276946 Ext. Search Rpt., Jan. 2, 2025, Neural Claim System, Inc. cited by applicant
O’Toole “5 ways to know your auto glass claim isn’t fraudulent”, Property & Casualty 360 ALM
Media Properties, LLC, Proquest Document ID 1829028324, Oct. 14, 2016, 3 pages, United States.
cited by applicant
Rosenfield, “A Clear View on the Future of Auto Glass”, ALM Media Properties, LLC, Proquest
Document ID 1786091824, May 2016, 3 pages, United States. cited by applicant

Primary Examiner: Poinvil; Frantzy

Attorney, Agent or Firm: Wells St. John P.S.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation-in-part of U.S. patent application Ser. No. 17/198,114 filed Mar. 10, 2021, entitled “Methods and Systems for Submitting and/or Processing Insurance Claims for Damaged Motor Vehicle Glass”, which is a continuation-in-part of U.S. patent application Ser. No. 17/016,097 filed Sep. 9, 2020, entitled “Methods and Systems for Submitting and/or Processing Insurance Claims for Damaged Motor Vehicle Glass”, which claims priority to and the benefit of U.S. Provisional Patent Application Ser. No. 62/897,746 filed Sep. 9, 2019, entitled “Methods and Systems for Submitting and/or Processing Insurance Claims for Damaged Motor Vehicle Glass”, the entirety of each of which is incorporated by reference herein.

TECHNICAL FIELD

(1) The present disclosure relates to systems and methods for submitting and processing insurance claims, and more particularly to systems and methods for submitting and processing insurance claims for damaged motor vehicle glass.

BACKGROUND

(2) Most road vehicles in the North America contain glass windows and windshields, yet the ability to associate manufacturer vehicle data with vehicle auto glass is difficult. There does not exist a commonly available programmatic way to tie manufacturer vehicle specifics to reconcilable auto glass.

(3) This challenge exists because the electronically distributed data between the record of origin for auto glass in North America (National Auto Glass Specifications “NAGS”— Mitchell) and one of the largest Manufacturer Build Data providers of vehicle data in North America is incompatible.

(4) When motor vehicle glass such as windshields are damaged, they are typically covered by insurance, and because they are covered by insurance, this necessitates the submission of a claim for insurance coverage. Currently, this can be done by having an insurance adjuster come out and look at your motor vehicle, or taking your motor vehicle in to an adjuster. This can require considerable time and effort, and slow the process of eventually getting your glass fixed through repair or replacement. The present disclosure provides automated methods and systems for submitting and/or processing an insurance claim for damaged motor vehicle glass. The methods can provide for greater efficiency and processing.

SUMMARY

(5) The present disclosure provides a repeatable and reproducible process to combine vehicle manufacturer data with auto glass data via an application programming interface (API). The API

manipulates the outputs of the electronic datasets from Manufacture Build Data Provider(s) and the National Auto Glass Specifications (NAGS) into an agglutinated response.

(6) Methods for submitting and/or processing insurance claims for damaged motor vehicle glass are provided that can include: receiving a plurality of images associated with motor vehicle glass at processing circuitry; performing image processing operations on each of the plurality of images to determine one or more of glass damage, glass type, and/or claim fraud; and submitting an insurance claim for glass repair or replacement based on the glass type or damage, or flagging the claim as fraud.

(7) The present disclosure also provides a non-transitory computer readable storing instruction that when executed by a processor, causes a computer system to perform the following method. The method can include: prompting a user for initial claim submission information; prompting the user for a plurality of images of portions of motor vehicle glass; performing image processing operations on each of the plurality of images to train the computer system, determine one or more of glass damage, glass type, and/or claim fraud; and one of submit or reject an insurance claim for motor vehicle glass repair or replacement.

(8) The present disclosure also provides a non-transitory computer-readable storage medium storing instruction that, when executed by a processor, causes a computer system to perform the following method: prompt a user for vehicle glass vendor information; process the information to determine if the user is in possession of the vehicle and/or whether the glass of the vehicle needs to be repaired or replaced; if the user is in possession of the vehicle and a replacement is determined, the user is: prompted for the VIN number of the vehicle; and the VIN number is processed through third party data to determine the required part numbers; if the user is not in possession of the vehicle, the user is: prompted for the VIN number of the vehicle; prompted for photos of the vehicle, vehicle glass, and damaged portions; the captured photos are proceed to determine repair or replace; if replace, the VIN number is processed through third party data to determine the required part numbers; and if repair, the method ends.

Description

DRAWINGS

(1) Embodiments of the disclosure are described below with reference to the following accompanying drawings.

(2) FIG. 1 is a representation of motor vehicle glass having a long crack and a chip therein.

(3) FIG. 2 is an example method according to an embodiment of the disclosure.

(4) FIG. 3 is a representation of a process flow according to an embodiment of the disclosure.

(5) FIG. 4A is a represented portion of an overall method as part of a system for automatically generating and/or processing insurance claims.

(6) FIG. 4B is a represented portion of an overall method as part of a system for automatically generating and/or processing insurance claims.

(7) FIG. 4C is a represented portion of an overall method as part of a system for automatically generating and/or processing insurance claims.

(8) FIG. 4D is a represented portion of an overall method as part of a system for automatically generating and/or processing insurance claims.

(9) FIG. 4E is an example interface prompt for a use according to an embodiment of the disclosure.

(10) FIG. 4F is a represented portion of an overall method as part of a system for automatically generating and/or processing insurance claims

(11) FIG. 5A is a more detailed portion of the system and/or methods shown in FIG. 4.

(12) FIG. 5B is a depiction of motor vehicle glass image registration according to an embodiment of the disclosure.

- (13) FIG. 5C is a depiction of motor vehicle identification points according to an embodiment of the disclosure.
- (14) FIG. 5D is a depiction of a particular motor vehicle highlighting a specific motor vehicle tag.
- (15) FIG. 5E is a depiction of motor vehicle Drivers Primary Viewing Area (DPVA) according to an embodiment of the disclosure.
- (16) FIG. 5F is a depiction of an overview to be altered by touching the screen to indicate the location of the damage.
- (17) FIG. 6 is a depiction of a car windshield having at least two portions.
- (18) FIG. 7A is a depiction of a car windshield having at least 9 portions, with each of the portions having a unique identifier.
- (19) FIG. 7B is a depiction of the altered overview (FIG. 5F) with identifiers upon a windshield according to an embodiment of the disclosure.
- (20) FIG. 8 is portion 4 of FIG. 7A.
- (21) FIG. 9 is portion 3 of FIG. 7A.
- (22) FIG. 10A is portion 3, 6 or 9 of FIG. 7A.
- (23) FIG. 10B is a depiction of an example glass identifier according to an embodiment of the disclosure.
- (24) FIGS. 11A-11G are depictions of different forms of damaged motor vehicle glass breaks.
- (25) FIGS. 12A-12B are more detailed portions of the overall system and method shown in FIGS. 4A-4E.
- (26) FIG. 13 is a more detailed representation of the overall system shown in FIGS. 4A-4E.
- (27) FIG. 14 is an even more in-depth depiction of the overall system and methods shown in FIGS. 4A-4E.
- (28) FIG. 15 is a depiction of a group of portions of motor vehicle glass according to an embodiment of the disclosure.
- (29) FIG. 16 is a depiction of image augmentation according to an embodiment of the disclosure.
- (30) FIG. 17 is another depiction of image augmentation according to an embodiment of the disclosure.
- (31) FIGS. 18A-18D are depictions of image augmentation according to an embodiment of the disclosure.
- (32) FIG. 19 is a depiction of an additional method or system that can be used in combination with the method or systems of the present disclosure according to an embodiment of the disclosure.
- (33) FIG. 20 is a depiction of an additional method or system that can be used in combination with the method or systems of the present disclosure according to an embodiment of the disclosure.
- (34) FIG. 21 is a depiction of an additional method or system that can be used in combination with the method or systems of the present disclosure according to an embodiment of the disclosure.
- (35) FIG. 22 is a depiction of an additional method or system that can be used in combination with the method or systems of the present disclosure according to an embodiment of the disclosure.
- (36) FIG. 23 is a depiction of an additional method or system that can be used in combination with the method or systems of the present disclosure according to an embodiment of the disclosure.

DESCRIPTION

- (37) This disclosure is submitted in furtherance of the constitutional purposes of the U.S. Patent Laws “to promote the progress of science and useful arts” (Article 1, Section 8).
- (38) The present disclosure will be described with reference to FIGS. 1-23. Referring first to FIG. 1, example motor vehicle glass 10 is shown that includes a chip 12 as well as a crack 14. Glass 10 can include multiple chips and/or multiple cracks. Glass 10 can be a windshield of a motor vehicle for example and it may or may not be constructed of Silicon. Glass 10 can also be a primarily polymeric construction such as a laminate. As can be seen, the crack extends a distance across the glass, and there is a single chip. The chip can be any one of a number of types of chips and occupy any place on the motor vehicle glass. Accordingly, the glass 10 of FIG. 1 is damaged; hence it is

designated as prior art.

(39) Referring next to FIG. 2, an overall system is shown that includes a user **16** operating an image capturing device or camera **18**. This image capturing device or camera **18** can be any form of electronic image capturing device. It is not necessary that the image capturing device be a person digital assistant or cell phone, or even a tablet or other form of computer. It need not have a plethora of processing circuitry ability; the only requirement is that it is able to capture images. Accordingly, the device **18** can have at least some processing circuitry, at least a sufficient configuration to capture, store, and/or transfer one or more images. The image(s) captured utilizing camera **18** can be then transferred or uploaded to processing circuitry **20**, which includes a database **22** operably coupled to software **24** and hardware **26**. In accordance with example configurations, images can be captured and processed on the same or multiple devices connected via wire or wirelessly. The images may also be processed using cloud-based storage and/or processing software.

(40) In accordance with example implementations, the images can be captured by following prompts or directions from an application on the computing device such as a tablet or smart phone having processing circuitry and a camera. These prompts or directions can specify the image to be captured and the order in which the images are captured, for example. As described in more detail in the following description, not only can the system prompt the capture of automobile glass, specific portions of automobile glass, but also specific portions of the automobile, such as, for example, specific section of the automobile glass, automobile identifiers, glass identifiers, license plates.

(41) The processing circuitry can include personal computing system that includes a computer processing unit that can include one or more microprocessors, one or more support circuits, circuits that include power supplies, clocks, input/output interfaces, circuitry, and the like. Generally, all computer processing units described herein can be of the same general type. Application Platform Interface (API) that allows communication between different software applications in the system. The memory can include random access memory, read only memory, removable disc memory, flash memory, and various combinations of these types of memory. The memory can be referred to as a main memory and be part of a cache memory or buffer memory. The memory can store various software packages and components such as an operating system.

(42) The computing system may also include a web server that can be of any type of computing device adapted to distribute data and process data requests. The web server can be configured to execute system application software such as the reminder schedule software, databases, electronic mail, and the like. The memory of the web server can include system application interfaces for interacting with users and one or more third party applications. Computer systems of the present disclosure can be standalone or work in combination with other servers and other computer systems that can be utilized, for example, with larger corporate systems such as financial institutions, insurance providers, and/or software support providers. The system is not limited to a specific operating system but may be adapted to run on multiple operating systems such as, for example, Linux and/or Microsoft Windows. The computing system can be coupled to a server and this server can be located on the same site as the computer system or at a remote location, for example.

(43) In accordance with example implementations, these processes may be utilized in connection with the processing circuitry described. The processes may use software and/or hardware of the following combinations or types. For example, with respect to server-side languages, the circuitry may use Java, Python, PHP, .NET, Ruby, JavaScript, or Dart, for example. Some other types of servers that the systems may use include Apache/PHP, .NET, Ruby, NodeJS, Java, and/or Python. Databases that may be utilized are Oracle, MySQL, SQL, NoSQL, or SQLite (for Mobile). Client-side languages that may be used, this would be the user side languages, for example, are ASM, C, C++, C #, Java, Objective-C, Swift, ActionScript/Adobe AIR, or JavaScript/HTML5.

Communications between the server and client may be utilized using TCP/UDP Socket based

connections, for example, as Third-Party data network services that may be used include GSM, LTE, HSPA, UMTS, CDMA, WiMAX, WIFI, Cable, and DSL. The hardware platforms that may be utilized within processing circuitry include embedded systems such as (Raspberry PI/Arduino), (Android, iOS, Windows Mobile)—phones and/or tablets, or any embedded system using these operating systems, i.e., cars, watches, glasses, headphones, augmented reality wear etc., or desktops/laptops/hybrids (Mac, Windows, Linux). The architectures that may be utilized for software and hardware interfaces include x86 (including x86-64), or ARM.

(44) The systems and/or processing circuitry **20** of the present disclosure can include a server or cluster of servers, one or more devices **18**, additional computing devices, several network connections linking devices **18** to server(s) including the network connections, one or more databases **22**, and a network connection between the server and the additional computing devices, such as those devices that may be linked to an adjuster.

(45) Device **18** and/or processing circuitry **20** and/or plurality of devices **18** and the additional computing device can be any type of communication devices that support network communication, including a telephone, a mobile phone, a smart phone, a personal computer, a laptop computer, a smart watch, a personal digital assistant (PDA), a wearable or embedded digital device(s), a network-connected vehicle, etc. In some embodiments, the devices **18** and the computing device can support multiple types of networks. For example, the devices **18** and the computing device may have wired or wireless network connectivity using IP (Internet Protocol) or may have mobile network connectivity allowing over cellular and data networks.

(46) The various networks may take the form of multiple network topologies. For example, networks can include wireless and/or wired networks. Networks can link the server and the devices **18**. Networks can include infrastructure that support the links necessary for data communication between at least one device **18** and a server. Networks may include a cell tower, base station, and switching network as well as cloud-based networks.

(47) As described in greater detail herein, devices **18** can be used to capture one or more images of damaged glass. The images are transmitted over a network connection to a server. The server can process the images to assess damage, obtain information to assist with determination and/or condition of repair costs, process a claim, detect fraud, and/or train the system to better review future images. The features can be transmitted over network connection to another computer device for approval or adjustment.

(48) In accordance with example implementations, device **18** can have the following functional components; one or more processors, memory, network interfaces, storage devices, power source, one or more output devices, one or more input devices, and software modules—operating the system and a motor vehicle glass claims application—stored in memory. The software modules can be provided as being contained in memory, but in certain embodiments, the software modules can be contained in storage devices or a combination of memory and storage devices. Each of the components including the processor, memory, network interfaces, storage devices, power source, output devices, input devices, operating system, the network monitor, and the data collector can be interconnected physically, communicatively, and/or operatively for inter-component communications.

(49) The processor can be configured to implement functionality and/or process instructions for execution within device **18**. For example, the processor can execute instructions stored in the memory or instructions stored on a storage device. Memory can be a non-transient, computer-readable storage medium, and configured to store information within device **18** during operation. In some embodiments, memory can include a temporary memory, an area for information not to be maintained when the device **18** is turned off. Examples of such temporary memory include volatile memories such as Random Access Memory (RAM), dynamic random access memories (DRAM), and Static Random Access Memory (SRAM). Memory can also maintain program instructions for execution by the processor.

(50) Device **18** can also include one or more non-transient computer-readable storage media. The storage device can be generally configured to store larger amounts of information than memory. The storage device can further be configured for long-term storage of information. In some embodiments, the storage device can include non-volatile storage elements. Non-limiting examples of non-volatile storage elements include magnetic hard discs, optical discs, floppy discs, flash memories, or forms of electrically programmable memories (EPROM) or electrically erasable and programmable (EEPROM) memories.

(51) Device **18** can use network interfaces to communicate with external devices or server(s) via one or more networks, and other types of networks through which a communication with the device **18** may be established. Network interfaces may be a network interface card, such as an Ethernet card, an optical transceiver, a radio frequency transceiver, or any other type of device that can send and receive information. Other non-limiting examples of network interfaces include Bluetooth, Cellular Connection Technology (e.g., 3G LTE) and Wi-Fi radios in client computing devices, and Universal Serial Bus (USB). In specific implementations, device **18** may not have access to an entirety of the system. For example, the system will have a database that includes a myriad of captured as well as generated images and certain implementations will not allow access to these images by the prompted operator.

(52) Device **18** can include one or more power sources to provide power to the device. Non-limiting examples of power sources can include single-use power sources, rechargeable power sources, and/or power sources developed from nickel-cadmium, lithium-ion, or other suitable material.

(53) One or more output devices can also be included in device **18**. Output devices can be configured to provide output to a user using tactile, audio, and/or video stimuli. Output devices can include a display screen (part of the presence-sensitive screen), a sound card, a video graphics adapter card, or any other type of device for converting a signal into an appropriate form understandable to humans or machines. Additional examples of output devices can include a speaker such as headphones, a Cathode Ray Tube (CRT) monitor, a Liquid Crystal Display (LCD), or any other type of device that can generate intelligible output to a user.

(54) Device **18** can include one or more input devices. Input devices can be configured to receive input from a user or a surrounding environment of the user through tactile, audio, and/or video feedback. Non-limiting examples of input devices can include a photo and video camera, presence-sensitive screen, a mouse, a keyboard, a voice responsive system, microphone or any other type of input device. In some examples, a presence-sensitive screen includes a touch-sensitive screen.

(55) Device **18** can include an operating system. The operating system can control operations of the components of the device **18**. For example, the operating system can facilitate the interaction of the processors, memory, network interface, storage device(s), input device, output device, and power source.

(56) Device **18** can be configured to use a claims application to capture one or more images of damaged glass. In some embodiments, the claims application may guide a user of device **18** as to which views should be captured. In some embodiments, the claims application can interface with and receive inputs from a GPS transceiver and/or accelerometer.

(57) The servers can be at least one computing machine that can assess and accurately identify vehicle glass repair, replacement or a no damage disposition, glass part number (i.e., glass part number, pricing, and/or availability), advance-driver assistance-system (ADAS) calibration requirements and supported moldings required based on images provided from device **18**. The server can have access to one or more databases and other facilities that provide the features described herein.

(58) Servers, according to certain aspects of the disclosure can include one or more processors, memory, network interface(s), storage device(s), and software modules—image processing engines, damage estimation engines, and database query and edit engines can be stored in the

memory. The software modules are provided as being stored in memory, but in certain embodiments, the software modules are stored in storage devices or a combination of memory and storage devices. In certain embodiments, each of the components including the processor(s), memory, network interface(s), storage device(s), media manager, connection service router, data organizer, and database editor are interconnected physically, communicatively, and/or operatively for inter-component communications.

(59) Processor(s), analogous to processor(s) in device **18**, can be configured to implement functionality and/or process instructions for execution within the server. For example, processor(s) can execute instructions stored in memory or instructions stored on storage devices. Memory, which may be a non-transient, computer-readable storage medium, is configured to store information within the server during operation. In some embodiments, memory includes a temporary memory, i.e., an area for information not to be maintained when the server is turned off. Examples of such temporary memory include volatile memories such as Random Access Memory (RAM), dynamic random access memories (DRAM), and Static Random Access Memories (SRAM). Memory also maintains program instructions for execution by processor(s).

(60) The server uses network interface(s) to communicate with external devices via one or more networks. Such networks may also include one or more wireless networks, wired networks, fiber optics networks, and other types of networks through which communication between the server and an external device may be established. Network interface(s) may be a network interface card, such as an Ethernet card, an optical transceiver, a radio frequency transceiver, or any other type of device that can send and receive information.

(61) Storage devices of the processing circuitry of the present disclosure can be provided as part of a server to include one or more non-transient computer-readable storage media. Storage devices are generally configured to store larger amounts of information than memory. Storage devices can be configured for long-term storage of information. In some examples, storage devices can include non-volatile storage elements. Examples of non-volatile storage elements can include, but are not limited to, magnetic hard discs, optical discs, floppy discs, flash memories, resistive memories, or forms of electrically programmable memory (EPROM) or electrically erasable and programmable (EEPROM) memory.

(62) Servers can include instructions that implement an image processing engine configured to receive images of damaged glass from one or more devices **18** and perform image processing on the images. The server can further include instructions that implement a damage estimation engine that receives the images processed by the image processing engine and, in conjunction with a database query an edit engine that has access to a database storing parts and labor costs, calculates an estimate for repair or replacement of the damaged motor vehicle glass.

(63) Accordingly, user **16** can prepare or capture a plurality of images of motor vehicle glass **10**, and these images can be uploaded to processing circuitry **20**, and this processing circuitry can operate in accordance with the methods and systems disclosed herein, including interacting with a third-party processing circuitry **28** to process a claim **30**.

(64) Referring next to FIG. **3**, processing circuitry **20** and methods used therein can include generally three method components that operate in most circumstances together to process claim **30**. This module **32** can include module **34** that can acquire information for first notice of loss; module **36**, which is machine learning and training, and module **38**, which is fraud detection.

(65) Module **34** is entitled “FNOL” (First Notice of Loss) can be filed using but not limited to a carrier web site, carrier app, or NCS interactive voice response system, for example. Additionally, the FNOL can be acquired using TPA as method and the NCS APP may interface with an insurance carrier's system. Accordingly, during First Notice of Loss, there is a series of proprietary questions; a “survey” can be initiated, including but not limited to: “Are you aware a claim has been filed on your policy?” “Did you notice the damage, or did a glass shop employee point it out?” “Has the work been done?” “If yes, why did the shop proceed without authorization?” Then, a description of

the damages is requested; appearance, size, and quantity. Each filing of the FNOI method can utilize security features as part of the claim reporting process, including personal identification number, authorization, claim number, policy number and insured, multi-factor authorization to access policy information to avoid claim recycling (refiling claims within 180 days or per carrier specific guidelines) and verification of claim. Once the claim has been verified, the methods of the present disclosure can prompt the insured for required photos, including but not limited to those photos requested as will be described below. The Machine Learning and Training module **36** can utilize the information gained regarding specifics of a specific claimant, specifics of a specific car, specifics relating to glass type; also the Machine Learning and Training module **36** can utilize images acquired to determine the presence of a repairable chip; the presence of a repairable crack; or the presence of a chip and/or crack that cannot be repaired and requires glass replacement. Module **36** can be considered an artificial intelligence module. For example, the module can be software that includes and/or applies a set or sets of business rules that are used to develop and train fraud models and/or glass damage models under supervised learning. For example, models can be customized to detect fraud via prediction models that are monitored based on pre-defined business rules including but not limited to vehicle type, damage reported, vehicle location, owner of the vehicle and coverage type etc., as will be detailed herein. Also, the module can be configured to apply these same learning techniques to image capture and/or augmentation that is used to initiate vehicle glass damage identification and/or repair determination. For example, the preparation of additional images from single images of damage and the comparison of those images to image rules. The image rules including but not limited to previously categorized images of window damage.

(66) Machine Learning module or AI **36** can be configured to utilize or incorporate the AI Provider's TensorFlow (See, for example [tensorflow.org](https://www.tensorflow.org)) image recognition technology for image recognition and/or analysis. It is contemplated that other AI technology may be used as well. This image recognition can capture the glass morphology and structural damage, for example. In accordance with example implementations, computer vision can be used to prepare extracts of glass damage information that describes the morphology and structure of glass damage via tagging tasks that provide for labeling of specific features (size and shape) of a given image. Classification of a given image can be based on specific detection tasks that are tied to pixel-level precision for image detection. Detection is followed with segmentation into pre-defined glass damage buckets based on ROLAGS standards.

(67) Accordingly, module **32** also includes Fraud Detection module **38**. Fraud Detection module **38** can include classification logic, which identifies correlations of various physical, vision, computing and data parameters to determine indicators of fraud. This module can proceed to either alert, reject, or pass or accept the claim per predefined requirements that improve over time with data collection and utilizing machine learning in accordance with module **36**. Fraud Detection module **38** can run concurrently with the systems and methods herein, by cross-referencing photo indications with information gathered by third-party vendors **28** to identify characteristics including but not limited to Image Related Parameters, for example: color of vehicle different between photos; interior is a different color between photos; lighting is different from photo to photo; photos show vehicle inside a structure, then outside; shade band in some photos and not in others; frit band different from photo to photo; stickers showing in some photos and not in others; surroundings different photo to photo; photos identified to be from library or photo from the internet; as well as Vehicle Information, such as: glass LOGO doesn't match the type of vehicle; date and time stamp off; date and time stamp before Date of Loss (D.O.L.); geo tag is on some photos and not on others, geo tag is off; geo tag greater than a predefined number of miles from insured's address; photos from different phone number than that of the policyholder, for example.

(68) Referring next to FIGS. **4A-4E**, an example overall method is shown as part of a system for submitting an insurance claim for the damaged motor vehicle glass in FIGS. **4A-4E**. Clearly this

overall method is too large to be printed on a single sheet as a diagram; therefore, it is provided in components. First, we will address the steps in FIG. 4A. In step 40, a software application or “app” is initiated by the user. This could be a non-transitory computer readable storage medium storing instruction that executes a prompt for the user to initial claim submission information. In accordance with example implementations, this processing can include a mobile device registering sequence. This can be a requirement to register a “mobile number” such as phone number, with the system to obtain a unique ID registration code for the user. In accordance with other implementations, a deeplink paste through a text or email can be used to register. In this system, the next step 42, the claim submission information can be web initiated or initiated through a website or via cloud based system. In step 44, the carrier or third-party agent can be initiated, and then in step 45, an automated phone system can be initiated. At step 34, the First Notice of Loss module is initiated or entered. From there, in step 46 there is an inspection protocol, and following from that inspection protocol can be a proof of loss concept 48, and then a photo request that also provides from inspection protocol 50. Additionally, these steps as well as other steps in the system can be completed with UI/UX tools that guide a user the methods and/or systems. For example, image guidance, instruction guidance, voice guidance, video guidance, video tools, FAQ pages, and/or a Chat Bot.

(69) Referring next to FIG. 4B, upon completing step 48 for the proof of loss, a vehicle identification and policy coverage deductible can be entered by the user at 52 and third-party data is acquired at 54. Third-party data acquisition can include a VIN decode, NAGS part information including labor kits and molding, or ADAS manufacturer calibration guidelines in 56, 58, and 60. From there, a decision regarding the presence or absence of an ADAS component can be made at 61 and from there a type of glass decision can be made at 63 and rendered by the system. Entering the third party data 54 is not always performed. For example, where glass does not need to be replaced, but can be repaired, third party data processing 54 can be by passed and the system can proceed to the methods of FIG. 4D. Accordingly, not all VIN's received by the system necessarily enter third party data processing 54. This determination can be made during the processing of step 74. For example, during AI determination, repair or replace can be determined. If repair, then step 53 allows third party data step 54 to be bypassed. If replace, then step 53 can require third party data step 54 processing.

(70) Referring next to FIG. 4C, from step 80 (FIG. 4D), either or both of fraud detection or photo failure can be made to proceed to failure photo step 68 and/or fraud detection 70. Accordingly, there is a failure photo decision at 68 that can include a part of a fraud detection component 70, which is at least one part of the link between the FNOL fraud detection component and the machine learning component. From there, during this acquisition, a determination can be made whether the photos are sufficient or not at a decision 64 (requiring technical assistance), and if necessary, technical support can be provided at 66. Automated prompts can be given by the system for the acquisition of photos at step 62 and a return to photo request at step 50 of FIG. 4A.

(71) Referring next to FIG. 4D, an example machine learning system is described with reference to the damaged motor vehicle glass claim submission systems and methods of the present disclosure. Accordingly, after step 50, the photos can be provided to a machine learning at step 72. The photos include, but are not limited to, as will be described later, the glass ID, ADAS camera, the VIN number, the glass overview with indicators 500 or 700, see for example, FIG. 5E and/or FIG. 7B, close up measured photo of each damaged area, mileage, and vehicle capture information such as images of the four corners of the vehicle and/or rear of vehicle including license plate.

(72) Prior to proceeding to step 74, upload failures where photos were captured by the user, but failed to be received by the system for processing prior to step 74, can be validated and retried through a job batch scheduling method at step 73 that operates when system capacity is favorable. In accordance with example implementations, photos can be requested in step 50 and provided, however, the photos acquired in step 72 failed to upload for processing in 74. For example, cameras

placed within about 10 inches from the glass when capturing images have proven effective to provide the images, but these images may fail to be uploaded. Accordingly, the uploading of these photos can be attempted again at step **73**.

(73) Proceeding next to step **74**, motor vehicle glass can be analyzed for count of damage areas, classify each damaged area, measure size of each damaged area, and an AI determination of repair, replacement or wear & tear. For example, a measured photo can include, but is not limited to, the inclusion of certain known reference materials, such as currency, ruler, any other objective reference matter. During this step, the images, particularly the images of the damaged glass can be augmented. For example, an overview image can be taken such as FIG. 5F. The glass itself can be augmented with physical markers such as the adhesive tags **500** shown in FIG. 5E. The system can be configured to recognize these tags by color or oddity (for example, they don't belong) and zoom in to these portions creating images for processing. Alternatively, the glass can be digitally augmented in accordance with FIG. 7B, wherein the user displays the image on an interface then touches or marks the image at the location of the damage **700**. The marked or augmented image can then be processed focusing on the marked or augmented portions.

(74) Additionally, upon completion of the AI determination of the steps of **74**, a threshold for using third party data can be established. Accordingly, where the AI determination is to “replace”, the system can proceed between **52** to **54** of FIG. 4B. Where the AI determination does not include a “replace” conclusion, the system may not access or use third party data at step **53**.

(75) Following step **74** can be step **75**, which includes VIN number and glass ID, whether or not the glass ID matches the VIN number, and whether or not the VIN number indicates the presence or absence of an ADAS and/or whether or not the VIN number matches the VIN number submitted by the user. Referring next to step **77**, the Unrelated Prior Damage (UPD) or commercial use can be determined, and vehicle capture information such as the four corners of the motor vehicle or rear and/or vehicle including license plate can be captured information in step **78**. This information can be provided to the fraud detection determination in step **80** referenced in FIG. 12A-12B.

(76) Additionally, step **79** customer effort survey can provide feedback on tools used for UI “User Interface”/UX “User Experience” for example Image Guidance, Instructional Guidance, Voice Guidance, Video Tools, FAQ Information and Chat Bot. Questions for example; Was it Easy to Retrieve APP, Ease of Login & Registration Process, Was APP easy to Navigate, and Option to send additional Survey Request. Subject matter of **74**, **75**, **77** and/or **79** can be used in decision step **80**, and example prompt screen for which is shown in FIG. 4E.

(77) Referring next to FIG. 4F, a determination of fraud detection is made in step **82** after AI determination of pass in step **81**, and this decision can determine repairable in **83** or replace in **84**, or no damage in **85**. This can be done on an autoglass-by-autoglass basis, or on a photo-by-photo basis. If there is a replacement window, NAGS identified part and calibration requirements can be sent to the vendor in **86**. Build sheet data can be used in combination with a translation table to secure the NAGS part number, for example. If there is no damage, then the claim is sent back to the carrier in **87**. If there is a replace or repairable determination, a work order is generated and released in **88**.

(78) Referring next to FIG. 5A, an example method of the first notice of loss is described in more detail or with reference to another example implementation, wherein an interface **100** can include as described herein a camera or a personal digital assistant or cell phone or laptop computer, for example. Survey questions are initiated to the user in step **102**, and security information is initiated to the user in step **104**. The system prompts the user to capture images as described in step **72** of FIG. 4D. Referring to FIG. 5B, an example depiction of VIN # image registration is shown. In accordance with example implementations a user can launch an NCS VIN scanner Application. The NCS VIN scanner Application utilizes a barcode reader, QR code reader and includes a built-in OCR text reader with autofocus. The Mobile APP can prompt the user to align the vehicle VIN within a rendered bracket frame as shown. VIN registration can be completed after alignment and

autofocus criteria are met. In accordance with additional implementations, and with reference to FIG. 5C, the user can acquire a VIN # image. An example VIN # image is shown in FIG. 5D. The system can use this image to identify the year, make, model of vehicle, build features and part selection.

(79) Referring to FIG. 5E an example motor vehicle Drivers Primary Viewing Area (DPVA) is shown. In accordance with example implementations, a user can launch an NCS windshield photo Application which launches a windshield image capture Mobile APP. The NCS windshield Mobile APP can prompt the user to align the motor vehicle glass image within a rendered frame as shown. Motor vehicle Drivers Primary Viewing Area (DPVA) is complete after alignment and autofocus criteria are met. In accordance with another implementation, and with reference to FIG. 5F, an NCS APP photo of an overview to be altered by touching the screen to indicate the location of the damage.

(80) Accordingly, and with reference to FIG. 6, the windshield **10** can be divided into portions, for example, A and B at the very least, but these portions are commensurate with the prompting of portions by the systems and methods of the present disclosure.

(81) Referring to FIG. 7A, an even more detailed depiction of portions **10A** and **10B** is shown wherein there are 9 portions, each of the 9 portions having a specific designation. Accordingly, within these “damage zones” the system can request that you enter each of these pictured portions in the designated order in order to place them with the proper identifier. Referring to FIG. 7B, identifiers are placed manually or are created electronically via the Mobile APP touch screen process to identify damages. The identifiers are placed manually or are created electronically via the Mobile APP touch screen to identify areas of damage.

(82) Accordingly, and with reference to FIG. 8, portion **4** in FIG. 7A may include a depiction of an ADAS **112**. A portion **3** in FIG. 7A can include VIN **114** as shown in FIG. 9. A portion **3**, **6** or **9** in FIG. 7A, can include glass ID **116** as shown in FIGS. **10A** and **10B**.

(83) In accordance with example implementations, and with reference to FIGS. **11A-11E**, example windshield chips are shown, with FIG. **11A** representing a half moon chip of the size shown; FIG. **11B** representing a star chip of the size shown; FIG. **11C** representing a bullseye chip of the size shown; FIG. **11D** showing a combo chip of the size shown, and FIG. **11E** showing a batwing chip of the size shown; FIG. **11F** showing a crack of the size shown; and FIG. **11G** showing a surface pit extending into outside lite, but not through the plastic interlayer and/or into the inside lite of the window. Accordingly, and with reference to FIGS. **12A** and **12B**, a more detailed example of fraud detection is shown, wherein the instances are weighed to determine whether or not fraud exists, and each of these instances or inconsistencies can be given a certain weight, and then totaled, and this totaled weight can be given an amount that is either above or below the fraud threshold.

Accordingly, in step **200**, details are received, and in step **202**, the individual details are processed. In step **204**, the vehicle color is compared between the photos and in **206**, the vehicle interior color is compared between the photos. The lighting of the photos is compared for consistency in **208**; the setting of or pose of the motor vehicle, particularly the windshield, is compared in **210**; the presence of shade bands in the photographs is compared in **212**; the frit band associated with the photographs is compared in **214**; and the stickers across the different portions of the photographs are compared in **216**. The surroundings to the vehicle are compared in **218**; historical photos of the vehicle, if available, are compared in **220**; and the windshield logo, if any, is compared with that which should exist in **224**; and the date and time stamp of the photos is compared in **226**, for example.

(84) With reference to FIGS. **12B**, continuing on, the GEO tag of the photos is compared in **228**, and whether or not the GEO tag was on or off is determined in **230**. The GEO tag distance of a predetermined number of miles from the insured's address in comparison to that of the photos is made in **232**, and a determination of whether the photos were from different device ids (e.g., those generated from different phone numbers, texts, emails, etc.) is made in **234**. Raw fraud counts are

made in **236**, and if it achieves a threshold number in **238**, then fraud is determined in **240**, or no fraud is determined in **242**.

(85) Referring next to FIG. **13**, an example implementation of a machine learning relating to the images is shown, wherein images are received in step **300**, and the damage classified in step **302** by the type of break at **304**, the size of the break in **306**, the number of breaks per image in **308**, and the location of the breaks on the windshield itself in **310**. This machine learning is done first with data augmentation at **312** (example implementations are described with reference to FIGS. **5E** and **7B**), and then the system fits received data to model in **314** and compared to the truth table as described, for example, in FIGS. **12A** and **12B**, at step **316**, for a final disposition regarding fraud and/or replacement or repair of the windshield at **318**.

(86) Referring next to FIG. **14**, data augmentation example step **312** is shown with an HPT driver or programming **320** preparing rotated image at **322**, flipped images at **324**, and brightness or contrast changed images at **326**, and color jittering at **328**.

(87) In accordance with example implementations and with reference to FIG. **15**, as part of data augmentation, the images that are next to each other, for example, 9, 6, and 3 can have the perimeters associated with those images, for example, perimeter **400** and **402**, compared to ensure that they are overlapping with existing images as part of fraud detection.

(88) Referring next to FIG. **16**, an example image, in this case **6** can be rotated or flipped as part of data augmentation to create additional images **404**, **406**, **408**, and **410**. These images can be stored for later use as representative of a certain chip **12**.

(89) With reference to FIG. **17**, portion **6** with chip **12** can have color jittering performed at **412** and/or brightness contrast changed to produce additional images at **414**.

(90) FIGS. **18A-18D** show images that have been augmented such as flipped, rotated, brightness/contrast changed, or color jittered, for example. Finally, this information, along with additional information shown below in the Table 1 can be included as part of the systems and methods of the present disclosure. For example, additional details relating to the size of the chip, the location of the chip can be entered into the system and be part of the machine learning. This can provide for additional efficiency in the system and method.

(91) TABLE-US-00001 TABLE 1 Location YES NO DPVA: (12" See DPVA See Other in width Classification than DPVA within the Step Below Classification wiper sweep) Step Below ADAS (Rear Replace See Other View Mirror than DPVA Area Classification Step Below DPVA (12 inches wide in wiper sweep) Crush Type Size Zone YES NO Bullseye chip 1" or less in 3/16ths Repair Replace diameter inch or less Halfmoon chip 1" or less in 3/16ths Repair Replace diameter inch or less Star chip 1" or less in 3/16ths Repair Replace diameter inch or less Combo chip 1" or less in 3/16ths Repair Replace diameter inch or less Batwing chip less than 6" 3/16ths Repair Replace in diameter inch or less Multiple chips Greater than 3/16ths Repair Replace 4" between inch chips or less Other than DPVA: (Anywhere other than DPVA) Type Size YES NO Bullseye chip 1" or less in 3/8ths Repair Replace diameter inch or less Halfmoon chip 1" or less in 3/8ths Repair Replace diameter inch or less Star chip 3" in 3/8ths Repair Replace diameter inch or less or less Combo chip 2" in 3/8ths Repair Replace diameter inch or less or less Batwing chip less than 6" 3/8ths Repair Replace in diameter inch or less Option Count YES NO Option 1 1 Repair Replace Option 2 Less than 2 Repair Replace Option 3 Less than 3 Repair Replace Option 4 Less than 4 Repair Replace Option 5 Less than 5 Repair Replace Option 6 Less than 6 Repair Replace Option 7 Less than 7 Repair Replace Option 8 Less than 8 Repair Replace Option + Less than + Repair Replace

(92) Referring next to FIG. **19**, a third party vendors method and/or system **500** is provided that can be used alone or in combination with the methods and systems described herein is provided. At step **501** a determination of glass vendor need is made. Where the vehicle is at the glass vendor and repair rather than replacement is needed, the method or system is completed. Where the vehicle is not at the glass vendor and/or the vehicle is with the glass vendor and replacement is needed, a glass work order is logged at, for example, using the application at step **502**. This application can

use one or more of the processing steps of FIG. 4A, such as **40**, **42**, **44**, and/or **45**.

(93) Upon logging a work order at **502**, a determination is made regarding the glass vendor having the vehicle or not. If the glass vendor has the vehicle the system can proceed to step **504**, if not the system can proceed to **505**.

(94) The method or system can allow glass vendors to utilize the AI application developed and maintained by the methods described herein via at least two separate functions **504** or **505**.

(95) Where the vehicle is at the glass vendor or glass salesperson and replacement is determined, at **511** access to the systems and/or methods of the present disclosure can be granted via an application to process the VIN (Vehicle Identification Number). After step **511**, a decision of repair or replace can be determined, and the VIN may be processed at **512**, match confirmed at **513**, and part numbers provided at **514**. Accordingly, the system or method herein at FIG. 4B at steps **54-63** can process information (VIN, for example), access glass/vehicle feature codes via third party applications, and provide accurate parts via NAGS which will give the glass vendor results including glass parts, type of glass, pricing, kits and molding requirements at **514**, for example.

(96) Alternatively, where the vehicle is not at the glass vendor or salesperson, at **505**, the glass vendor can obtain permission via communication with a system monitor, such as the system or method owner or licensee. This permission can be requested at **505**, via a text, call, e-mail, instant message, etc., then granted or denied. When granted, access authorization can be granted via a link or password as for example at **506**. The granted user, such as Vehicle owner can log into the above system or method at step **507** and scan vehicle information such as a bar or QR code or enters VIN into the system at **508**. At step **509**, the user can be prompted to or provide a series of photos which are captured at **509**, information is uploaded to the A.I. at **510** and then the method proceeds to the repair/replace decision. Steps **508** and **509** can utilize the processing of step **50** as well as steps **72**, **74**, and/or **75**.

(97) With reference to FIGS. **20-23**, the methods and systems of the present disclosure can utilize alone or in combination with the other methods and conditions of the present disclosure, the following methods and conditions as described in FIGS. **20-23**. In these figures, reference is made to the following definitions.

(98) Manufacturer Build Data Provider(s) are purchased property that contain a suite of software tools on vehicle manufacturer data. It contains build sheets on OEM vehicle parts, components, rates, and exact vehicle specifications as provided by vehicle manufacturers and can be translated to identify NAGS data.

(99) National Auto Glass Specifications. The National Auto Glass Specifications (NAGS), owned by Mitchell, define the type of itemized auto glass products that correspond to given vehicles.

(100) Application Programming Interface. An Application Programming Interface (API) is a software translator. It allows two difference software technologies to have a common language between one another.

(101) At present, Manufacture Build Data and NAGS uses two separate and distinct API languages. The present disclosure has discovered that when a license for Manufacture Build Data is established, developers are granted access to Manufacture Build Data API. Manufacture Build Data Providers use a RESTful API for each of its services which is compatible to standard create, read, update, and delete (CRUD) methods used in most web-based technology solutions. Manufacture Build Data Provider's underlining technology is known as JavaScript Object Notation (JSON). A NAGS licensed developer is granted access to its API which is returned in an extensible markup language known as XML. JSON uses key-value pairs to associate its various fields whereas XML uses tags (similar to HTML) to associate its fields.

(102) Manufacture Build Data Provider's vehicle manufacturer data request requires a single parameter. This parameter is the vehicle identification number (VIN). When a request to Manufacture Build Data Provider is made using a verified (VIN), manufacture data on a vehicle is returned. Included in the response from Manufacture Build Data Provider are all the known vehicle

features. Some of these features are specific to the Windshield. Examples of windshield features are “Rain Sensors” to detect precipitation and “Lane Departure Warning Signals” to detect lane departure. Each feature response comes with a feature key.

(103) After the Manufacture Build Data Provider request is complete, a second request is made to NAGS. NAGS returns all windshields for a given vehicle year, make, model, and body style. The year, make, model, and body style is first obtained from the earlier Manufacture Build Data Provider vehicle manufacturer data response.

(104) In accordance with example implementations, the methods and systems of the present disclosure collects, stores, and maintains a software table of vehicle features that pertain to windshields. This table contains a list of feature keys and their association to common words seen in NAGS windshields. NAGS does not contain feature keys. It only contains feature descriptions. The present systems and methods translates the XML response from NAGS into a JSON equivalent response. It then searches for feature key matches between Manufacture Build Data Provider and NAGS through its “Translation Table”. The feature key of the Manufacture Build Data Provider is found in the Translation Table which contains the feature descriptions of NAGS windshields. When a match is made, the corresponding windshields for a given vehicle year, make, model, and body style are returned. This is provided in more detail in FIG. 23 and Table 1 below.

(105) In accordance with one implementation as shown in FIG. 20, system **700** includes from the Manufacture Build Data Provider in **701**, Manufacture Build Data Provider Feature Keys are established. The step continues to **702**, wherein in the Translation Table, the Manufacture Build Data Provider Feature Keys and NAGS Feature Descriptions are provided. On to step **703**, at NAGS, NAGS Feature Descriptions are provided. This is the association between the Manufacture Build Data Provider and the NAGS Feature Descriptions.

(106) In accordance with at least one example implementation, referring to FIG. 21, system **800** is provided that gives an example of a rental car use case. In step **801**, a rental car staff member, for example, can scan glass to locate any chips or cracks. The system proceeds to step **802**, which is to determine whether or not there is a chip or crack present. If a chip or crack is located, the agent uses processing circuitry to acquire photos of all damages in **803**. The images can then be scanned in step **804** via the AI platform, and disposition of the damage is determined as repair or replace. If replacement is determined, then in step **805** the build sheet data is obtained, and in **806** the data is translated by the translation table, and part data is obtained through a third party. In **808**, a replacement dispatch is sent to the glass replacement vendor. If repair only work is done, the system proceeds to **807** to return documentation to the rental staff member's hand held device via API or electronic communication, and the system returns to **808** as described, and then finally, the claim is invoiced in step **809**.

(107) Referring next to FIG. 22, system **900** is provided as an example for total loss or vehicle glass conditioning. In step **901**, a vehicle is determined a total loss or needs to be conditioned. In step **902**, the vehicle is inspected by a third party salvage vendor, insurance carrier representative, or repair facility, and then the user will identify if there are any chips or cracks in the glass at **907**. If there is damage, photos will be taken of the area damaged at **910**. If no damage, at **903** a series of photos are taken to indicate if there is a pit in the windshield, and if so, the severity. Refer to FIG. 11G regarding pits. The method and system will determine the number of pits in a defined area in each photo, and determine level of wear and tear at steps **904** and **905**. The damage will be uploaded using handheld device into the system or method at **906**. The methods or system will determine the number of chips present at **911**, or if the glass is cracked. The system will report the number of repairable chips back to the client and then report back to the client indicating for glass replacement at **915**, and if glass replacement is required, build sheet data will be provided at **914** and obtained through a third party at **906**. That data received is translated into the translation table described, and part data and pricing is obtained thorough a third party not shown in the system. The replacement cost is sent to the insurance client at **906** and the claim is billed at **906**.

(108) Referring to FIG. 23 and with reference to FIGS. 19-22 and the below Table, a VIN # can be entered into NGS at **1010**. At **1012**, the API with VIN # can be provided to a decode service. Decode services are vendors that are provided a vehicle VIN # and returns at least one or more of the year, make, model, edition, body style, etc. of the vehicle. A determination of VIN # validity can be made at **1014**, and if NULL, the method returns to **1010** to request or await a new VIN #. If valid, at **1018**, a Vendor Decode service is used. Then, at **1020** Build Data and Feature Sets are acquired using information received from the decode service. Using Table 2 below, at **1022**, NGS is translated to normalize Yr, Make, Model, and Body Style to NAGS as shown with one example below.

(109) TABLE-US-00002

TABLE 2 TP Build Data Provider Equipment	Equipment NAGS Features
ID ID 2 Category Feature Name Value ID ID 2 NAGSID ID ID 2 Feature Name	Calibration
211 444 Heated Wiper Rest 4 444 9 17 9 Heated Wiper Park	

(110) At **1024**, NAGS part information is acquired via API. At **1026** NGS translation table 3 below is used to match Feature sets to Identify part(s). Calibration requirements can be obtained as well. Then at **1028** NGS displays Correct Part(s) information including Unique NAGS Features not Associated with Build Data.

(111) TABLE-US-00003

TABLE 3 Mar- manu- keting Trim styleid country year facturer division
series model trim trim_2 variation
300466 US 2009 Honda Acura TSX TSX Base 4dr Sdn Man
300467 US 2009 Honda Acura TSX TSX Base 4dr Sdn Auto
300468 US 2009 Honda Acura TSX TSX Base Tech 4dr Sdn Pkg Man Tech Pkg
300469 US 2009 Honda Acura TSX TSX Base Tech 4dr Sdn Pkg Auto Tech Pkg
302602 US 2009 Honda Acura RL RL 3.7 4dr Sdn (Natl)
302603 US 2009 Honda Acura RL RL 3.7 4dr Sdn (HI)
302604 US 2009 Honda Acura RL RL 3.7 Tech 4dr Sdn Pkg Tech Pkg (Natl)
302605 US 2009 Honda Acura RL RL 3.7 Tech/ 4dr Sdn CMBS Tech/ w/ CMBS PAX w/PAX (Natl)
305590 US 2009 Honda Acura RDX RDX Base AWD 4dr
305591 US 2009 Honda Acura RDX RDX Base Tech AWD 4dr Pkg Tech Pkg
306981 US 2009 Honda Acura MDX MDX Base AWD 4dr NAGS Body Vehicle mfg friendly_ NAGS NAGS Body styleid
variation style type carcode model Make Model Style
300466 4dr Sdn Sedan Car CU2569JW Manual Acura TSX 4 Door Man Sedan
300467 4dr Sdn Sedan Car CU2669JW Automatic Acura TSX 4 Door Auto Sedan
300468 4dr Sdn Sedan Car CU2569KW Manual with Acura TSX 4 Door Man Technology Sedan Package
300469 4dr Sdn Sedan Car CU2669KW Automatic Acura TSX 4 Door Auto with Sedan Technology Package
302602 4dr Sdn Sedan Car KB2659KW Automatic Acura RL 4 Door (Natl) Sedan
302603 4dr Sdn Sedan Car KB2639KW Automatic Acura RL 4 Door (HI) (Hawaii) Sedan
302604 4dr Sdn Sedan Car KB2669KW Automatic Acura RL 4 Door (Natl) with Sedan Technology Package
302605 4dr Sdn Sedan Car KB2669KXW Automatic Acura RL 4 Door (Natl) with Sedan Technology and CMBS/ PAX Packages
305590 AWD Sport Sport TB1829JNW AWD Acura RDX 4 Door 4dr Utility Utility Utility
305591 AWD Sport Sport TB1859KNW AWD with Acura RDX 4 Door 4dr Utility Utility Technology Utility Package
306981 4WD Sport Sport YD2829JNW AWD Acura MDX 4 Door 4dr Utility Utility Utility

(112) In compliance with the statute, embodiments of the invention have been described in language more or less specific as to structural and methodical features. It is to be understood, however, that the entire invention is not limited to the specific features and/or embodiments shown and/or described, since the disclosed embodiments comprise forms of putting the invention into effect.

Claims

1. A non-transitory computer-readable storage medium storing instruction that, when executed by a processor, causes a computer system to perform the following method: prompt a user for initial claim submission information; prompt a user for a plurality of images of portions of motor vehicle glass; perform image processing operations on each of the plurality of images to determine one or

more of glass damage, glass type, and/or claim fraud, wherein the image processing operations include: prompting the use for the VIN number of the vehicle; prompting for photos of the vehicle, vehicle glass, and damaged portions; accessing data of the photos of the vehicle, vehicle glass, and damaged portions from the user; using the processor, processing the data of the photos of the vehicle, vehicle glass, and damaged portions to determine repair or replace, wherein the processing includes: classifying the damaged portions; augmenting the data of the photos; fitting the data of the photos to a model; and comparing the data of the photos to a truth table; if replace, the VIN number is processed through third party data to determine the required part numbers; and if repair, a work order is generated; and submit insurance claim for motor vehicle glass repair or replace.

2. The computer readable storage medium of claim 1 wherein the method further comprises comparing information from the plurality of images to initial claim submission information.

3. The computer readable storage medium of claim 1 wherein the method further comprises comparing information from the plurality of images to third party information.

4. The computer readable storage medium of claim 1 wherein the method further comprises comparing information from the plurality of images to trained system information.

5. The computer readable storage medium of claim 1 wherein the machine learning and/or training comprises augmenting the images received.
