

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401314
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Jiang; Li

Solar tracker

Abstract

A solar tracker includes a main beam and at least one slewing reducer, one of the slewing reducer is connected to a motor, the motor is controlled by a motor controller, and the motor controller is connected to the motor by a cable; the slewing reducer that is connected to the motor is a driving slewing reducer, and the other slewing reducers are driven slewing reducers, the torque of the driving slewing reducer is transmitted to the driven slewing reducers through a transmission shaft, and the driving slewing reducer and the driven slewing reducers rotate synchronously to drive the main beam to rotate; the main beam is provided through the interior of the slewing reducer.

Inventors: Jiang; Li (Zhejiang, CN)

Applicant: Hangzhou Sino-Deutsche Power Transmission Equipment Co., Ltd. (Zhejiang, CN)

Family ID: 1000008778188

Assignee: Hangzhou Sino-Deutsche Power Transmission Equipment Co., Ltd (Hangzhou, CN)

Appl. No.: 18/207164

Filed: June 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230336113 A1	Oct. 19, 2023

Foreign Application Priority Data

CN	202011423316.3	Dec. 08, 2020
CN	202110124983.X	Jan. 29, 2021
CN	202110306266.9	Mar. 23, 2021
CN	202110566999.6	May. 24, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/125982 20211025 PENDING child-doc US 18207164

Publication Classification

Int. Cl.: H02S20/32 (20140101); F16H1/16 (20060101); F16H57/021 (20120101)

U.S. Cl.:

CPC H02S20/32 (20141201); F16H1/16 (20130101); F16H2057/0213 (20130101)

Field of Classification Search

CPC: H02S (20/32); F16H (1/16); F16H (2057/0213)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2019/0296688	12/2018	Kresse	N/A	F24S 25/12

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104033507	12/2013	CN	N/A
104980098	12/2014	CN	N/A
209435158	12/2018	CN	N/A
111245342	12/2019	CN	N/A
111262512	12/2019	CN	N/A
211209639	12/2019	CN	F24S 30/48
211296653	12/2019	CN	N/A
111731038	12/2019	CN	N/A
111765236	12/2019	CN	N/A
111853161	12/2019	CN	N/A
112671316	12/2020	CN	N/A
112815045	12/2020	CN	N/A
112987801	12/2020	CN	N/A
217590716	12/2021	CN	H02S 20/32

OTHER PUBLICATIONS

International Search Report of PCT Patent Application No. PCT/CN2021/125982 issued on Jan. 30, 2022. cited by applicant

Primary Examiner: Elahmadi; Zakaria

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a Continuation Application of PCT Application No. PCT/CN2021/125982 filed on Oct. 25, 2021, which claims the benefit of Chinese Patent Application Nos. 202011423316.3 filed on Dec. 8, 2020, 202110124983.X filed on Jan. 29, 2021, 202110306266.9 filed on Mar. 23, 2021 and 202110566999.6 filed on May 24, 2021. All the above are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present invention generally relates to the technical field of solar power generation, and particularly to a solar tracker.

BACKGROUND

(2) The solar photovoltaic power generation has a rapidly rising proportion in the power generation market, and its market prospect is extremely considerable. In the large-scale commercial power stations, the tracking power generation system can increase the power generation capacity of a power station by more than 20% compared with stationary power generation systems. Therefore, more and more commercial power stations will adopt tracking power generation in the future, and more requirements will be proposed for a single main beam multi-point driving solar tracking power generation system (tracking support). At present, the mainstream flat single-axis or oblique single-axis tracking power generation system in the current market has increased the installed power due to the increased power of assembly, and their structural shortcomings have become increasingly obvious, which cannot adapt to the higher and more use requirements of the tracker in the future. Since the conventional flat single axis has only one rigid support driving point, the longer the length of the single support, the easier it is to produce low-frequency resonance; in addition, the torque tube at both ends of the driving point is prone to torsion deformation at the end of the main beam, which has suppressed the increase in the installed capacity and reduced the cost per watt of conventional flat single-axis tracking power generation system.

SUMMARY

(3) In order to overcome the shortcomings of the prior art, the present invention provides a solar tracker.

(4) In order to solve the problems that the flat single-axis in the solar tracking system is prone to low-frequency resonance and the main beam of the torque tube at both ends of the main beam is prone to torsion and deformation, a single main beam multi-point driving solar tracking power generation system is provided.

(5) A single main beam multi-point driving solar tracking system, comprising a main beam and at least one slewing reducer, one of the slewing reducer is connected to a motor, the motor is controlled by a motor controller, and the motor controller is connected to the motor by a cable; the slewing reducer that is connected to the motor is a driving slewing reducer, and the other slewing reducers are driven slewing reducers, the torque of the driving slewing reducer is transmitted to the driven slewing reducers through a transmission shaft, and the driving slewing reducer and the driven slewing reducers rotate synchronously to drive the main beam to rotate.

(6) In the tracking power generation system, the solar panel is fixed on the main beam, and the main beam rotates to drive the angle adjustment of the solar panel to realize the tracking of the solar energy by the solar panel. Generally, the span of two columns is basically 7 to 8 meters or more. Therefore, when the torque transmission shaft has a large span between the driving slewing reducer and the driven slewing reducer, it is prone to sag under its dead weight, leading to lag in torque transmission and creeping phenomenon.

(7) In the solar tracking system, the stability of the transmission shaft is the basis for the stability of the entire tracking system. The object of the first aspect of the present invention is to provide a solar tracking system with stable torque transmission.

(8) Optionally, the slewing reducer and the transmission shaft are rotatably provided with the main

beam synchronously in the same direction.

(9) Optionally, the slewing reducer is a worm gear slewing reducer, the worm gear of the slewing reducer is fixedly arranged on the column, and the shell of the slewing reducer is fixedly connected to the main beam, the worm gear rotatably engages with the shell; when the motor is started, the worm rotates around the worm gear while revolving to drive the slewing reducer and the main beam to rotate.

(10) Optionally, the transmission shaft is provided with a plurality of connecting members spaced apart in the length direction, and the connecting member is connected to the main beam.

(11) Optionally, one end of the connecting member is sleeved on the transmission shaft, and the other end is sleeved on the main beam, the transmission shaft is provided with a bearing at the connection point, and the main beam is provided with a frame and a fastener at the connection point.

(12) Optionally, a connecting plate is provided on the column, and a connecting portion connected to the connecting plate is provided on the worm gear.

(13) Optionally, the shell of the slewing reducer is provided with a first connecting column and a second connecting column, and the main beam on the left side of the slewing reducer is connected to the first connecting column, the main beam on the right side of the slewing reducer is connected to the second connecting column; the second connecting column and the shell are an integral structure, and the first connecting column is detachably connected to the second connecting column.

(14) Optionally, a rolling bearing assembly and a sliding bearing assembly are provided between the worm gear and the first connecting column, and the rolling bearing assembly comprises an inner ring, an outer ring, and a plurality of balls arranged between the inner ring and the outer ring, the inner ring is formed on the first connecting column, and the outer ring is formed on the worm gear.

(15) Optionally, the sliding bearing assembly comprises a first sliding portion and a second sliding portion, and the first sliding portion is formed on the second connecting column, the second sliding portion is formed on the worm gear.

(16) Optionally, the worm gear is provided with an incomplete convex ring in the circumferential direction, and the shell is provided with a lobe engaging with the incomplete convex ring.

(17) Optionally, one end of the worm is externally sleeved with a first bevel gear and a transmission gear, and the motor output end is provided with a first gear meshing with the transmission gear, the transmission shaft is externally sleeved with a second bevel gear, and the first bevel gear meshes with the second bevel gear.

(18) Solar power stations are usually installed in areas where the environment is relatively harsh (such as plains and deserts). The winds and sands, corrosive gases, rainwater, etc. can shorten the service life of the transmission shaft and affect its use effect. The object of the second aspect of the present invention is to provide a multi-point drive tracking transmission system that improves the service life of the transmission shaft.

(19) Optionally, the transmission shaft is positioned inside the main beam.

(20) Optionally, the slewing reducer is provided with a plurality of bevel gear sets, and the transmission shaft drivingly engages with an input end or an output end of the slewing reducer through the plurality of bevel gear sets.

(21) Optionally, a bevel gear set and a universal corner joint are provided inside the slewing reducer, and the transmission shaft drivingly engages with an input end or an output end of the slewing reducer through the bevel gear set or the universal joint.

(22) Optionally, a first bevel gear set, a second bevel gear set and a third bevel gear set are provided inside the slewing reducer, the transmission shaft is externally sleeved with a fourth bevel gear, and one end of the first bevel gear set meshes with the input end or output end of the slewing reducer, one end of the third bevel gear set meshes with the fourth bevel gear, and the two ends of

the second bevel gear set mesh with the other ends of the first bevel gear set and the third bevel gear set, respectively.

(23) Optionally, a first bevel gear set and a second bevel gear set are provided inside the slewing reducer, the transmission shaft is externally sleeved with a fourth bevel gear, the first bevel gear set meshes with the fourth bevel gear, and one end of the second bevel gear set meshes with the input end or output end of the slewing reducer, and the other end of the second bevel gear set meshes with the first bevel gear set, and the universal joint is provided on the second bevel gear set.

(24) Optionally, the slewing reducer is a worm gear slewing reducer. The worm gear of the slewing reducer is integrally formed with a first connecting column and a second connecting column. The main beam on the left side of the slewing reducer is connected to the first connecting column, and the main beam on the right side of the slewing reducer is connected to the second connecting column.

(25) Optionally, both the first connecting column and the second connecting column are arranged in a rectangular shape.

(26) Optionally, the shell of the slewing reducer is provided with a first limiting portion, and the worm gear is circumferentially provided with a second limiting portion that engages with the first limiting portion.

(27) In the solar tracking system, the motor is connected to the motor controller through a cable, and the stability of the cable is the basis for the stability and reliability of the entire tracking system. The object of the third aspect of present invention is to provide a solar tracking system with a stable connection between the motor and the motor controller.

(28) Optionally, the lower part of the shell of the slewing reducer is provided with a mounting position for the motor, and the motor and the motor controller are in a relatively static state.

(29) Optionally, the motor controller is provided on the main beam.

(30) Optionally, the motor controller is provided on the column.

(31) Optionally, the slewing reducer is a worm gear slewing reducer, and the motor is arranged in parallel with the worm.

(32) Optionally, the output end of the motor is provided with a first gear, the worm is provided with a transmission gear, and the shell is provided with a transfer gear, and the transfer gear meshes with the first gear and the transmission gear respectively.

(33) Optionally, a support lug is provided outside the motor shell, and a support portion connected to the support lug is provided on the shell.

(34) In the tracking power generation system, the motor is the key to driving the slewing reducer, and the slewing reducer drives the main beam to rotate. The motor has an important relationship with the mounting method of the slewing reducer. The object of the fourth aspect of the present invention is to provide a photovoltaic tracking system with multiple installation orientations of motors.

(35) Optionally, the lower part of the shell of the slewing reducer is provided with a mounting position for the motor.

(36) Optionally, the motor is disposed at the lower part of the shell of the slewing reducer, the motor and the shell of the slewing reducer are on the same vertical plane, and the motor is arranged in parallel with the worm of the slewing reducer.

(37) Optionally, the motor is disposed at the lower part of the shell of the slewing reducer, the motor and the shell of the slewing reducer are on the same vertical plane, and the motor is arranged perpendicularly to the worm of the slewing reducer.

(38) Optionally, the motor is disposed on the left side of the lower part of the shell of the slewing reducer, and the motor is arranged perpendicularly to the worm of the slewing reducer.

(39) Optionally, the motor is disposed on the right side of the lower part of the shell of the slewing reducer, and the motor is arranged perpendicularly to the worm of the slewing reducer.

(40) Optionally, the motor output end is connected to a worm through a gear drive.

(41) In the solar tracking system, the slewing reducer is the core device that drives the rotation of the main beam. The object of the fifth aspect of the present invention is to provide a slewing reducer with high radial load and good stability.

(42) Optionally, the shell of the slewing reducer is provided with a first limiting portion, and the worm gear is circumferentially provided on a second limiting portion that engages with the first limiting portion.

(43) Optionally, the first limiting portion is a lobe fixedly connected in the shell, and the second limiting portion is a convex ring fixedly to the worm gear in the circumferential direction.

(44) Optionally, the lower part of the shell of the slewing reducer is provided with an installation position for the power supply.

(45) Optionally, the slewing reducer is a worm gear slewing reducer, the worm gear of the slewing reducer is fixedly arranged on the column, and the shell of the slewing reducer is fixedly connected to the main beam, the worm gear rotatably engages with the shell; when the motor is started, the worm rotates around the worm gear while revolving to drive the slewing reducer and the main beam to rotate.

(46) Optionally, the shell is provided with a first connecting column and a second connecting column, the main beam on the left side of the slewing reducer is connected to the first connecting column, and the main beam on the right side of the slewing reducer is connected to the second connecting column; the second connecting column and the shell are an integral structure, and the first connecting column is detachably connected to the second connecting column.

(47) Optionally, a rolling bearing assembly and a sliding bearing assembly are provided between the worm gear and the first connecting column, and the rolling bearing assembly comprises an inner ring, an outer ring, and a plurality of balls arranged between the inner ring and the outer ring, the inner ring is formed on the first connecting column, and the outer ring is formed on the worm gear.

(48) Optionally, the sliding bearing assembly comprises a first sliding portion and a second sliding portion, and the first sliding portion is formed on the second connecting column, the second sliding portion is formed on the worm gear.

(49) Optionally, a bevel gear set and a universal joint are provided inside the slewing reducer, and the transmission shaft drivingly engages an input end or an output end of the slewing reducer through the bevel gear set or the universal joint.

(50) Optionally, a first bevel gear set, a second bevel gear set and a third bevel gear set are provided inside the slewing reducer, the transmission shaft is externally sleeved with a fourth bevel gear, and one end of the first bevel gear set meshes with the input end or output end of the slewing reducer, one end of the third bevel gear set meshes with the fourth bevel gear, and the two ends of the second bevel gear set mesh with the other ends of the first bevel gear set and the third bevel gear set, respectively.

(51) Optionally, a first bevel gear set and a second bevel gear set are provided inside the slewing reducer, the transmission shaft is externally sleeved with a fourth bevel gear, the first bevel gear set meshes with the fourth bevel gear, and one end of the second bevel gear set meshes with the input end or output end of the slewing reducer, and the other end of the second bevel gear set meshes with the first bevel gear set, and the universal joint is provided on the second bevel gear set.

(52) Optionally, the slewing reducer is a worm gear slewing reducer. The worm gear of the slewing reducer is integrally formed with a first connecting column and a second connecting column. The main beam on the left side of the slewing reducer is connected to the first connecting column, and the main beam on the right side of the slewing reducer is connected to the second connecting column.

(53) In the tracking power generation system, the stability of the transmission shaft is the basis for the stability of the entire tracking system. During the long-term movement of the transmission shaft, the multi-point driving tracking support has a large span between the two column supports,

which will cause the transmission shaft to sag and cause deformation. The object of the sixth aspect of the present invention is to provide a solar tracking system with stable torque transmission.

(54) Optionally, the connecting member is connected to the main beam through a sliding rail, and the connecting member can slide on the sliding rail.

(55) Optionally, the connecting member slides outside the sliding rail.

(56) Optionally, a slip ring is provided on the connecting member, and the slip ring is sleeved outside the sliding rail.

(57) Optionally, the connecting member slides inside the sliding rail.

(58) Optionally, an annular chute is provided outside the connecting member, an annular groove that engages with the annular chute is provided inside the sliding rail, and the annular chute can slide in the annular groove.

(59) Optionally, the sliding rail is arranged in a circular arc shape, the sliding rail is provided with a frame consistent with the shape of the main beam, and the main beam is provided through the interior of the frame.

(60) Optionally, both ends of the worm gear are connected to the main beam by a connecting assembly, and the connecting assembly comprises a disc, a square shaft, and a connecting column arranged between the disc and the square shaft.

(61) Optionally, the square shaft is arranged eccentrically relative to the disc, the disc is provided with a first positioning hole, and the worm gear is provided with a second positioning hole, and the first positioning hole is in anti-rotation engagement with the second positioning hole through a locking member.

(62) In the solar tracking system, the main beam may not be mounted or the length is insufficient due to the column size error for foundation construction. The object of the seventh aspect of the present invention is to provide a multi-point drive tracking transmission system with a controllable length of the main beam.

(63) Optionally, the main beam is provided through the interior of the slewing reducer.

(64) Optionally, the main beam is sleeved with a rotating shaft, and the rotating shaft engages with the worm gear through a rolling bearing.

(65) Optionally, the main beam is connected to the rotating shaft and a shell through a retaining member.

(66) Optionally, the retaining member is provided with a convex ring extending outwardly in the axial direction, a first inclined plane structure is arranged on the outer wall of the convex ring from top to bottom, a second inclined plane structure is arranged on the inner wall of the rotating shaft and the shell of the slewing reducer from bottom to top, and the first inclined plane can move left and right along the second inclined plane.

(67) Optionally, the retaining member is provided with a truncated cone extending outwardly in the radial direction, the truncated cone is provided with a first locking hole, both the rotating shaft and the shell of the slewing reducer are provided with a second locking hole, and the first locking hole is in anti-rotation engagement with the second locking hole through a locking member.

(68) Optionally, a first inclined plane structure is arranged on the outer wall of the retaining member from top to bottom, and the inner wall of the rotating shaft is provided with a plurality of stiffeners extending inwardly in the circumferential direction, a second inclined plane structure is arranged on the inner walls of the stiffeners from bottom to top, and the first inclined plane can move left and right along the second inclined plane.

(69) Optionally, the retaining member is provided with a boss extending outwardly in the radial direction, the boss is provided with a first locking hole, both the rotating shaft and the shell of the slewing reducer are provided with a second locking hole, and the first locking hole is in anti-rotation engagement with the second locking hole through a locking member.

(70) Optionally, the shape of the inner wall of the retaining member is the same as the shape of the outer wall of the main beam.

(71) The seven aspects of technical solutions of the present invention can be used as independent solutions or can be combined with each other. The structure in the solution of any aspect of the present invention can be used as an independent technical solution or can be combined with other technical solutions.

(72) In summary, the present invention has the following technical solutions.

(73) 1. The transmission shaft and the main beam of the present invention move simultaneously in the same direction, and the transmission shaft can be supported by the main beam, so that the transmission shaft is not easy to be twisted or broken, and has a long service life; in addition, with this structure, the diameter of the transmission shaft needs not to be too large, so the equipment investment cost is low; and because the transmission shaft, the motor, and the main beam all rotate synchronously, the photovoltaic panel will not collide with the transmission shaft during the flipping process of the main beam, so the main beam has a larger adjustable angle, a higher flexibility, and the equipment has a prolonged service life.

(74) 2. With the integrated arrangement of the second connecting column and the shell, the processing is more convenient, sufficient strength and rigidity can be guaranteed, and safety can be ensured; in addition, the first connecting column and the second connecting column are arranged separately, so that it is more convenient to assemble the first connecting column and the second connecting column, and replace them separately when damaged, with low cost for maintenance. The split structure can make the connecting column structure to be stronger during processing, to prolong the service life; and with the detachable connection method, the assembly and maintenance are very convenient.

(75) 3. The transmission shaft is provided inside the main beam, which prevents the transmission shaft from being affected by the harsh environment, avoids problems of the transmission shaft such as corrosion and aging, etc., and extends the service life of the transmission shaft; in addition, the jamming of the transmission shaft caused by wind and sand is reduced, lowering the fault rate; and, because the transmission shaft is provided inside, the appearance and layout of the entire equipment is more concise and beautiful.

(76) 4. The arrangement of universal joints ensures that the transmission chain realizes the corner function and makes the power transmission more stable.

(77) 5. The motor and the motor controller are arranged in a relatively static state, so that the cable between the motor and the motor controller will not be pulled during the flipping process of the main beam, and there will be no cable rupture or loose interface. The equipment fault rate is low and the safety is high; moreover, the cables will not be threaded, knotted and wound, ensuring the beautiful appearance of the entire equipment.

(78) 6. The structures of the first limiting portion and second limiting portion are provided, which ensures that the slewing reducer has a higher stability during rotation; moreover, it ensures higher safety protection ability in case of failure of external travel switch.

(79) 7. The multi-point driving tracking of the large span between two columns of the connecting member solves the problems of the deformation of the transmission shaft caused by sagging, the rotation vibration caused by the bending of transmission shaft, and the discontinuous rotation of the transmission shaft caused by the sagging and deformation;

(80) 8. With the arrangement of the sliding rail and connecting member, the main beam drives the slip ring of the transmission shaft to rotate; the rotations of the main beam and the transmission shaft do not interfere with each other, and both of them can rotate freely within a limited range;

(81) 9. With the eccentric setting, one end that connects to the worm gear is designed to be small and the other end is designed to be large, to match the main beam with a large size;

(82) 10. The main beam passes through the middle of the reducer, so the length of the main beam can be longer, which can effectively reduce the joints between the main beams, increase the rigidity and strength of the entire support and reduce the risk;

(83) 11. The inner ring of the retaining member is provided with the same shape as the main beam,

to ensure the rigidity of the connection between the torque tube and the reducer;
(84) 12. The first inclined plane and the second inclined plane are provided. When the locking member moves, the retaining member will shrink and change, and produce a radial pressure on the main beam, to achieve the purpose of locking the torque tube of the main beam.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic view of the present invention.
- (2) FIG. 2 is an exploded view of the present invention.
- (3) FIG. 3 is a schematic view of a slewing reducer of the present invention.
- (4) FIG. 4 is an exploded view of a slewing reducer of the present invention.
- (5) FIG. 5 is a partial cross-sectional view I of a slewing reducer of the present invention.
- (6) FIG. 6 is an enlarged view of a structure at A in FIG. 5.
- (7) FIG. 7 is a partial schematic view I of the present invention.
- (8) FIG. 8 is a partial cross-sectional three-dimensional view II of the present invention.
- (9) FIG. 9 is an enlarged view of a structure at B in FIG. 8.
- (10) FIG. 10 is a partial cross-sectional three-dimensional view III of the present invention.
- (11) FIG. 11 is an enlarged view of a structure at C in FIG. 10.
- (12) FIG. 12 is the second partial schematic view of the present invention.
- (13) FIG. 13 is a partial schematic view II of the present invention.
- (14) FIG. 14 is a schematic view of a worm gear of the present invention.
- (15) FIG. 15 is a three-dimensional sectional view of another embodiment of the slewing reducer in FIG. 1.
- (16) FIG. 16 is a perspective view of a transmission shaft in FIG. 15.
- (17) FIG. 17 is a perspective view of a second connecting column in FIG. 15.
- (18) FIG. 18 is a perspective view of a plug in FIG. 15.
- (19) FIG. 19 is a schematic view illustrating the inside arrangement of a transmission shaft of the present invention.
- (20) FIG. 20 is an exploded view illustrating the inside arrangement of a transmission shaft of the present invention.
- (21) FIG. 21 is a schematic view of a slewing reducer illustrating the inside arrangement of a transmission shaft of the present invention.
- (22) FIG. 22 is an exploded view of a slewing reducer illustrating the inside arrangement of a transmission shaft of the present invention.
- (23) FIG. 23 is a partial sectional view I of a slewing reducer illustrating the inside arrangement of a transmission shaft of the present invention.
- (24) FIG. 24 is an enlarged schematic diagram of a structure at D in FIG. 23.
- (25) FIG. 25 is a partial sectional view II of a slewing reducer illustrating the inside arrangement of a transmission shaft of the present invention.
- (26) FIG. 26 is an enlarged view of a structure at E in FIG. 25.
- (27) FIG. 27 is a schematic view of a worm gear illustrating the inside arrangement of a transmission shaft of the present invention.
- (28) FIG. 28 is a partial sectional view III of a slewing reducer illustrating the inside arrangement of a transmission shaft of the present invention.
- (29) FIG. 29 is an enlarged view of a structure at F in FIG. 28.
- (30) FIG. 30 is a schematic view of a slewing reducer illustrating the inside arrangement of a transmission shaft according to the second embodiment of the present invention.
- (31) FIG. 31 is a partial sectional view of a slewing reducer illustrating the inside arrangement of a

transmission shaft according to the second embodiment of the present invention.

(32) FIG. 32 is a schematic view illustrating a second mounting method of a motor arranged on the left side of a shell of a slewing reducer of the present invention.

(33) FIG. 33 is a schematic view I illustrating a third mounting method in which a motor and a worm are on the same plane and arranged vertically in the present invention.

(34) FIG. 34 is a schematic view II illustrating a third mounting method in which a motor and a worm are on the same plane and arranged vertically in the present invention.

(35) FIG. 35 is a schematic view illustrating a fourth mounting method of a motor arranged on the right side of a shell of a slewing reducer of the present invention.

(36) FIG. 36 is a schematic view illustrating the first embodiment in which a connecting member and a transmission shaft of the present invention are connected.

(37) FIG. 37 is an exploded view illustrating the first embodiment in which a connecting member and a transmission shaft of the present invention are connected.

(38) FIG. 38 is a partial schematic view illustrating the first embodiment in which a connecting member and a transmission shaft of the present invention are connected.

(39) FIG. 39 is a schematic view of a square shaft of the present invention.

(40) FIG. 40 is a schematic view of a worm gear of the present invention.

(41) FIG. 41 is the second embodiment in which a connecting member and a transmission shaft of the present invention are connected.

(42) FIG. 42 is a partial schematic view of the second embodiment in which a connecting member and a transmission shaft of the present invention are connected.

(43) FIG. 43 is a schematic view of the first embodiment of a retaining member of the present invention.

(44) FIG. 44 is an exploded view of the first embodiment of a retaining member of the present invention.

(45) FIG. 45 is a partial sectional view of the first embodiment of a retaining member of the present invention.

(46) FIG. 46 is a schematic view of a first retaining member of the present invention.

(47) FIG. 47 is a schematic view of a rotating shaft of the present invention.

(48) FIG. 48 is a schematic view of a rotating shaft of the present invention.

(49) FIG. 49 is a partial sectional view of the second embodiment of a retaining member of the present invention.

(50) FIG. 50 is a schematic view of a second retaining member of the present invention.

(51) FIG. 51 is a schematic view of the third embodiment of a retaining member of the present invention.

(52) FIG. 52 is partial perspective view of FIG. 51.

(53) FIG. 53 is partial three-dimensional sectional view of FIG. 51.

(54) FIG. 54 is a perspective view of a shell in FIG. 51.

(55) FIG. 55 is a perspective view of a retaining member in FIG. 51.

(56) FIG. 56 is a three-dimensional sectional view of another part in FIG. 51.

(57) FIG. 57 is a three-dimensional sectional view of FIG. 51.

(58) FIG. 58 is an enlarged view at C in FIG. 57.

(59) FIG. 59 is a perspective view of a mounting base in FIG. 51.

DETAILED DESCRIPTION

(60) As shown in FIGS. 1 to 59, a single main beam multi-point driving solar tracking system comprises a main beam 12 and at least one slewing reducer 1, and the number of the slewing reducers 1 can be adjusted according to the specific situation, which can be one or more than one, a plurality of slewing reducers 1 have exactly the same internal structure; one of the slewing reducer is connected to a motor 3, the motor 3 is controlled by a motor controller, and the motor 3 controller is connected to the motor by a cable; wherein the slewing reducer 1 that is connected to

the motor **3** is a driving slewing reducer, and the other slewing reducers **1** are driven slewing reducers, the torque of the driving slewing reducer is transmitted to the driven slewing reducers through a transmission shaft **10**, and the driving slewing reducer and the driven slewing reducers rotate synchronously to drive the main beam **12** to rotate.

(61) As shown in FIG. 1, in some embodiments, the slewing reducer **1** and the transmission shaft **10** are rotatably provided with the main beam **12** synchronously in the same direction. The transmission shaft also follows the main beam to rotate synchronously in the same direction during the rotation of the main beam and the slewing reducer, which ensures that the main beam will not touch the transmission shaft during the rotation, and no jamming phenomenon that causes inability to rotate will occur; in addition, when the main beam and the transmission shaft rotate together, they will drive the connected lines to rotate together, therefore, the line needs not to be very long, and the line can be simplified. During the rotation, the line will not be knotted and wound. Ultimately, the transmission shaft and the main beam rotate synchronically in the same direction, which ensures that the bearing capacity of the transmission shaft is increased and the service life of the transmission shaft is extended.

(62) As shown in FIGS. 2 to 5 and FIG. 14, in some embodiments, the slewing reducer **1** is a worm gear slewing reducer, the worm gear **14** of the slewing reducer is fixedly arranged on the column **19**, and the shell of the slewing reducer **1** is fixedly connected to the main beam **12**, the worm gear **14** rotatably engages with the shell of the slewing reducer **1**; when the motor **3** is started, the worm **15** rotates around the worm gear **14** while revolving to drive the slewing reducer and the main beam **12** to rotate. The column **19** and the main beam **12** mentioned above are the prior art. The bottom of the column **19** is in contact with the ground, and the main beam **12** can drive the photovoltaic panel to rotate together; it is not described here again. A sealing ring **16** is provided at the joint between the worm gear **14** and the slewing reducer **1**. The sealing ring **16** can be made of materials with good weather resistance, such as rubber, steel plate, etc. The materials with good weather resistance can block the direct sunlight to the sealing ring **16**, delay the aging of the seals and increase the service life. The sealing ring **16** is U-shaped, and the sealing ring **16** is provided with a circle of convex rib **17**. The sealing ring **16** can prevent external dust from entering and has a certain dustproof effect. In addition, when the sealing ring **16** is inserted between the shell of the slewing reducer **1** and the worm gear **14**, the sealing ring **16** and the worm gear **14** are fixed through the convex rib **17**, which ensures the stability of the worm gear **14** when rotating.

Optionally, a cover plate **18** is provided on the shell of the slewing reducer **1**. The cover plate **18** can be fixed to the shell of the slewing reducer **1** in a shape of bolts and nuts. The cover plate **18** keeps the shell of the slewing reducer **1** in a closed state. The arrangement of the cover plate **18** can prevent external dust from entering the shell of slewing reducer **1** and affect the stability of its internal mechanical structure; the worm gear **14** of slewing reducer is fixedly arranged on the column **19**, and the shell of the slewing reducer **1** is fixedly connected to the main beam **12**, the worm gear **14** rotatably engages with the shell of the slewing reducer **1**; when the motor **3** is started, the worm **15** rotates around the worm gear **14** while revolving to drive the slewing reducer and the main beam **12** to rotate. The column **19** and the main beam **12** mentioned above are the prior art. The bottom of the column **19** is in contact with the ground, and the main beam **12** can drive the photovoltaic panel to rotate together; it is not described here again.

(63) As shown in FIG. 7, in some embodiments, the transmission shaft **10** is composed of a circular pillar **100** and two diamond-shaped pillars **101**. The diamond-shaped pillars **101** are hexagon, and the two ends of the circular pillar **100** are inserted inside the two diamond-shaped pillars **101**. The transmission shaft **10** is externally sleeved with a second bearing **11** that engages with the slewing reducer **1**.

(64) As shown in FIGS. 2 and 13, in some embodiments, the transmission shaft **10** is provided with a plurality of connecting members **20** spaced apart in the length direction, and the connecting member **20** is connected to the main beam **12**. Specifically, a buckle **21** is provided on one end of

the connecting member **20** that is connected to the main beam **12**, and the buckle **21** is buckled on the main beam **12**.

(65) As shown in FIGS. **2** and **13**, in some embodiments, one end of the connecting member **20** is sleeved on the transmission shaft **10**, and the other end is sleeved on the main beam **12**, the transmission shaft **10** is provided with a first bearing **22** at the connection point, and the main beam **12** is provided with a frame **23** at the connection point, and the buckle **21** is buckled outside of frame **23**. Specifically, the frame **23** is sleeved outside the main beam **12**, and a pair of corner portions extending outwardly is provided on the frame **23**. The pair of corner portions can be fixed in the form of bolts and nuts, so that the frame **23** and the main beam **12** are connected more firmly; furthermore, with the arrangement of the buckle **21**, the connecting member **20** and frame **23** achieve detachable. When the parts of the connecting member **20** are damaged, the connecting member **20** can be replaced directly, which is more convenient and quick. Finally, the arrangement of the connecting member **20** can reinforce the fixing effect between main beam **12** and transmission shaft **10**, ensuring higher synchronous transmission efficiency in the same direction.

(66) As shown in FIG. **12**, in some embodiments, a connecting plate **24** is provided on the column **19**, and a connecting portion **25** connected to the connecting plate **24** is provided on the worm gear **14**. The connecting plate **24** and the connecting portion **25** can be fixed in the form of bolts and nuts, and can be replaced separately when damaged, with a low maintenance cost.

(67) As shown in FIGS. **5** and **10**, in some embodiments, the shell of the slewing reducer **1** is provided with a first connecting column **130** and a second connecting column **131**, and the main beam **12** on the left side of the slewing reducer is connected to the first connecting column **130**, the main beam **12** on the right side of the slewing reducer is connected to the second connecting column **131**; the second connecting column **131** and the shell of the slewing reducer **1** are an integral structure, and the first connecting column **130** is detachably connected to the second connecting column **131**. With the integrated arrangement of the second connecting column **131** and the shell of the slewing reducer **1**, the processing is more convenient, sufficient strength and rigidity can be guaranteed, and safety can be ensured; in addition, the first connecting column **130** and the second connecting column **131** are arranged separately, so that it is more convenient to assemble the first connecting column **130** and the second connecting column **131**, and replace them separately when damaged, with low cost for maintenance. The split structure can make the connecting column structure to be stronger during processing, to prolong the service life; and with the detachable connection method, the assembly and maintenance are very convenient.

(68) As shown in FIGS. **5** and **6**, in some embodiments, a rolling bearing assembly **26** and a sliding bearing assembly **27** are provided between the worm gear **14** and the first connecting column **130**, and the rolling bearing assembly **26** comprises an inner ring **260**, an outer ring **261**, and a plurality of balls **262** arranged between the inner ring **260** and the outer ring **261**, the inner ring **260** is formed on the first connecting column **130**, and the outer ring **261** is formed on the worm gear **14**. Specifically, the outer ring **261** is circumferentially provided with a sealing strip **263**, and the sealing strip **263** can block dust from entering the inside of the ball **262**, ensuring the stability of the ball **262** during rolling and making power transmission smoother.

(69) As shown in FIG. **5**, FIG. **17**, FIG. **18**, in some embodiments, an annular chute **2611** is formed between the inner ring **260** and the outer ring **261** for a plurality of balls **262** to slide. A plug hole **1311** is provided on the second connecting column **131** in the radial direction. The plug hole **1311** is corresponding to the circular chute **2611** and is in communication with the inner holes of the circular chute **511** and the second connecting column **131**; a plug **1312** is inserted into the plug hole **1311**, to block the plug hole **1311** and fix the plug **1312** and the second connecting column with a taper pin **1313**; when the second connecting column **131** is connected to the turbine **14**, the ball **262** is inserted into the annular chute **2611** through the plug hole **1311**, and plugged by the plug **1312**. The structure is simple and is convenient to mount.

(70) As shown in FIG. **7**, in some embodiments, the first connecting column **130** and the second

connecting column **131** are provided with the same shape, and both of which are composed of four straight sides and four arcs. Specifically, the four arcs in a rectangular shape are provided on the four corners of the four straight sides, so that the four corners bulge outwardly.

(71) As shown in FIGS. **5** and **6**, in some embodiments, the sliding bearing assembly **27** comprises a first sliding portion **270** and a second sliding portion **271**, and the first sliding portion **270** is formed on the second connecting column **131**, the second sliding portion **271** is formed on the worm gear **14**.

(72) As shown in FIGS. **8** and **9**, in some embodiments, one end of the worm **15** is externally sleeved with a first bevel gear **30** and a transmission gear **301**, and the motor **3** output end is provided with a first gear **31**, the shell is provided with a transfer gear **32**, and the first gear **31** meshes with its transmission gear **301** through the transfer gear **32**. Specifically, the first gear **31** and the transfer gear **32** have the same shape and size, the area of the first gear **31** is smaller than the first bevel gear **30**, the circular pillar **100** outside the transmission shaft **10** is externally sleeved with the second bevel gear **33**, and the second bevel gear **33** meshes with a first bevel gear **30**. When the motor **3** is started, the motor **3** drives the first gear **31** to rotate, and the first gear **31** meshes with the transfer gear **32**, the transfer gear **32** rotates, and the transfer gear **32** rotates to mesh with the transmission gear **301**, the transmission gear **301** rotates to drive worm **15** to rotate, and the worm **15** rotates to drive first bevel gear **30** to rotate. The first bevel gear **30** rotates to mesh with the second bevel gear **33**, and the second bevel gear **33** drives the transmission shaft **10** to rotate.

(73) Of course, as shown in FIGS. **15** and **16**, in other embodiments, one end of the worm **15** is externally sleeved with a transmission gear **30a**, and the circular pillar **100b** is provided with a sub-worm **1001** that meshes with the transmission gear **30a** and a connecting end **1002** that can be partially inserted into a diamond-shaped pillar **101**. The connecting end is a diamond that engages with the diamond-shaped pillar **101**, and the sub-worm **1001**, the connecting end **1002** and the circular pillar **100b** are arranged as an integral structure; the transmission shaft **10b** is driven by a motor, to drive the circular pillar **100b** to rotate. The worm **15** is driven to rotate through the engagement of the sub-worm **1001** and the transmission gear **30a**, and the worm **15** revolves around the turbine **14** while rotating.

(74) As shown in FIG. **19**, in some embodiments, the transmission shaft **10** is positioned inside the main beam **12**. The transmission shaft **10** is positioned inside the main beam **12**, which reduces the long-term exposure of the transmission shaft **10** to the outside to cause the transmission shaft **10** to be corrosive, so that the service life of the transmission shaft **10** is improved. In addition, because the transmission shaft is provided inside, the appearance and layout of the entire equipment is more concise and beautiful.

(75) As shown in FIG. **21** and FIGS. **5** to **26**, in some embodiments, the slewing reducer **1** is provided with a plurality of bevel gear sets, and the transmission shaft **10** drivingly engages with an input end or an output end of the slewing reducer **1** through the plurality of bevel gear sets.

(76) As shown in FIGS. **25** and **26**, in some embodiments, a first bevel gear set **43**, a second bevel gear set **44** and a third bevel gear set **45** are provided inside the slewing reducer **1**, the circular pillar **100a** inside the transmission shaft **10** is externally sleeved with a fourth bevel gear **46**, and one end of the first bevel gear set **43** meshes with the input end or output end of the slewing reducer **1**, one end of the third bevel gear set **45** meshes with the fourth bevel gear **46**, and the two ends of the second bevel gear set **44** mesh with the other ends of the first bevel gear set **43** and the third bevel gear set **45**, respectively. Specifically, the first bevel gear set **43** is composed of a first bevel gear **430** and a first transmission rod **431**. The first bevel gear **430** is provided in pair. The first transmission rod **431** is configured to connect a pair of first bevel gears **430**; the second bevel gear set **44** is composed of a pair of second bevel gears **440** and a second transmission rod **441**. The second bevel gear **440** is provided in pair. The second transmission rod **441** is configured to connect a pair of second bevel gears **440**; the third bevel gear set **45** is composed of a pair of third

bevel gears **450** and a third transmission rod **451**. The third bevel gear **450** is provided in pair. The third transmission rod **451** is configured to connect a pair of third bevel gears **450**. Optionally, the input end or output end of the slewing reducer **1** is sleeved on a pair of fifth bevel gears **48** outside of one end of the worm **15**, a sixth bevel gear **49** that meshes with one of the fifth bevel gears **48** and a seventh bevel gear **490** that meshes with the sixth bevel gear **49**. The seventh bevel gear **490** is connected to the input end of the motor **3**, and the fifth bevel gear **48** meshes with one of the first bevel gears **430**; specifically, the first transmission rod **431**, the second transmission rod **441** and the third transmission rod **451** are all provided with a third bearing **4510** that is connected to the shell of the slewing reducer. Optionally, the third bearing **4510** of the third transmission rod **451** is externally sleeved with a connecting base **600** that is connected to the transmission shaft **10**. The two ends of the connecting base **600** have supports extending outwardly. The supports are provided with through-holes. The transmission shaft **10** is provided through the through-holes. The arrangement of the connecting base **600** can provide a stable supporting on the transmission shaft **10**, ensuring that the transmission shaft **10** can rotate stably.

(77) Optionally, as shown in FIGS. **30** and **31**, in other embodiments, a first bevel gear set **43** and a second bevel gear set **44** are provided inside the slewing reducer **1**, the transmission shaft **10** is externally sleeved with a fourth bevel gear **46**, the first bevel gear set **43** meshes with the fourth bevel gear **46**, and one end of the second bevel gear set **44** meshes with the input end or output end of the slewing reducer **1**, and the other end of the second bevel gear set meshes with the first bevel gear set **43**; Specifically, the first bevel gear set **43** is composed of a pair of first bevel gears **430** and a first transmission rod **431**. The first bevel gear **430** is provided in pair. The first transmission rod **431** is configured to connect a pair of first bevel gears **430**; the second bevel gear set **44** is composed of a pair of second bevel gears **440** and a second transmission rod **441**. The second bevel gear **440** is provided in pair. The second transmission rod **441** is configured to connect a pair of second bevel gears **440**. The universal joint **42** is provided on the second bevel gear set **44**.

Optionally, the input end or output end of the slewing reducer **1** is composed of a pair of fifth bevel gears **48** sleeved outside of one end of the worm **15** and a sixth bevel gear **49** that meshes with one of the fifth bevel gears **48**. The sixth bevel gear **49** is connected to the input end of the motor **3**, and the other fifth bevel gear **48** meshes with one of the second bevel gears **440**. Specifically, both the first transmission rod **431** and the second transmission rod **441** are provided with a third bearing that is connected to the inside of the shell. Optionally, the third bearing of the second transmission rod **441** is externally sleeved with a connecting base **600** connected to the transmission shaft **10**.

The connecting base **600** are provided with supports extending outwardly. The supports are provided with through-holes. The transmission shaft **10** is provided through the through-holes. The arrangement of the connecting base **600** can provide a stable supporting on the transmission shaft **10**, ensuring that the transmission shaft **10** can rotate stably.

(78) As shown in FIGS. **21**, **25** and **28** to **29**, in some embodiments, the slewing reducer **1** is a worm gear **14** slewing reducer **1**. The worm gear **14** of the slewing reducer **1** is integrally formed with a first connecting column **130** and a second connecting column **131**. The main beam **12** on the left side of the slewing reducer **1** is connected to the first connecting column **130**, and the main beam **12** on the right side of the slewing reducer **1** is connected to the second connecting column **131**. With the integrated arrangement of the second connecting column and the shell, the processing is more convenient, sufficient strength and rigidity can be guaranteed, and safety can be ensured. Specifically, a sealing ring **16** is provided at the joint between the worm gear **14** and the shell, and the joint between the worm gear **14** and the transmission shaft **10**. The sealing ring **16** can be made of materials with good weather resistance, such as rubber, steel plate, etc. The materials with good weather resistance can block the direct sunlight to the sealing ring **16**, delay the aging of the seals and increase the service life. The sealing ring **16** is U-shaped, and the sealing ring **16** is provided with a circle of convex rib **17**. The sealing ring **16** can prevent external dust from entering and has a certain dustproof effect. In addition, when the sealing ring **16** is inserted between the shell and the

worm gear **14**, the sealing ring **16** and the worm gear **14** are fixed through the convex rib **17**, which ensures the stability of the worm gear **14** when rotating. Optionally, both sides of the shell are provided with self-lubricating bearings to engage with the worm gear **14**. The self-lubricating bearings can be connected with the shell by one end cover, and the end cover and the two sides of the shell are connected in the form of bolts and nuts. The outer diameter of the worm gear **14** is in fit with the self-lubricating bearing and can rotate in the self-lubricating bearing. It can bear a great radial load. At the same time, the bearing flange can bear a certain axial load. When one bearing is the fulcrum and a moment is generated with the other bearing, the two bearings can withstand a certain overturning load when they are in fit.

(79) As shown in FIG. 7, in some embodiments, the lower part of the shell of the slewing reducer **1** is provided with a mounting position **34** for the motor **3** to be placed. The motor **3** is controlled by the motor controller, and the motor controller is connected to the motor **3** by a cable. The motor **3** and the motor controller are in a relatively static state. The relatively static state is that an object keeps the position unchanged relative to another reference object. It is a relatively movable and relatively static, and the motion and static are relative.

(80) As shown in FIGS. 1 and 2, in some embodiments, the motor controller is provided on the main beam **12**.

(81) Preferably, as shown in FIGS. 19 and 20, in some embodiments, the motor controller is provided on the column **19**.

(82) Preferably, as shown in FIGS. 23 to 34, in some embodiments, the motor **3b** is disposed at the lower part of the shell of the slewing reducer **1**, the motor **3b** and the shell of the slewing reducer **1** are on the same vertical plane, and the motor **3b** is arranged in parallel with the worm of the slewing reducer **1**, the motor output end is connected to the worm by gear drive. The gear transmission is a prior art. The intermesh between the gears transmits the power to the worm. The parallel arrangement in the same horizontal plane can reduce the space occupancy rate and make the entire slewing reducer more beautiful.

(83) Preferably, as shown in FIG. 32, in some embodiments, the motor **3c** is disposed on the left side of the lower part of the shell of the slewing reducer **1**, and the left side is arranged relative to the slewing reducer, and the motor **3c** is arranged perpendicularly to the worm of the slewing reducer **1**. The motor output end is connected to the worm through a gear transmission. The gear transmission is a prior art, which is the meshing between gears and gears to transmit power to the worm. The perpendicular arrangement on the left side guarantees the transmission of multiple layers between gear and gear, making the transmission power to be more stable.

(84) Preferably, as shown in FIG. 35, in some embodiments, the motor **3d** is disposed on the right side of the lower part of the shell of the slewing reducer **1**, and the right side is arranged relative to the slewing reducer, and the motor **3d** is arranged perpendicularly to the worm of the slewing reducer **1**. The motor output end is connected to the worm through a gear transmission. The gear transmission is a prior art, which is the meshing between gears and gears to transmit power to the worm. The perpendicular arrangement on the left side guarantees the transmission of multiple layers between gear and gear, making the transmission power to be more stable.

(85) As shown in FIGS. 19 to 21, in some embodiments, the motor controller and the shell of the slewing reducer **1** are disposed on the main beam. The motor controller is mounted on the main beam, so that the main beam drives the motor controller and the shell to rotate. The shell rotation also drives the motor **3** to rotate, which ensures that when the rotation is synchronized in the same direction, it will also drive the connected lines to rotate together, so the line needs not to be very long and needs to be simplified. During the rotation, the line will not be knotted and wound. The simple arrangement between lines makes the entire appearance of the equipment to be more beautiful.

(86) As shown in FIGS. 2 and 8, optionally, both the motor **3** controller and the shell of the slewing reducer **1** are disposed on the column **19**. By mounting on column **19** through the shell and the

motor 3 controller, the line of the motor 3 and the motor 3 controller needs not to be very long, so the line needs not to be very long and needs to be simplified. During the rotation, the line will not be knotted and wound. The simple arrangement between lines makes the entire appearance of the equipment to be more beautiful.

(87) As shown in FIG. 21, in some embodiments, the motor 3 and the worm 15 are arranged in parallel.

(88) As shown in FIG. 4, in some embodiments, a support lug 35 is provided on the shell of the motor 3, and a support portion 36 connected to the support lug 35 is provided on the shell of the slewing reducer. The support lug 35 and the support portion 36 can be fixed in the form of bolts and nuts, so that the motor 3 is firmly arranged on the shell of the slewing reducer 1.

(89) As shown in FIG. 8, in some embodiments, the shell of the slewing reducer 1 is provided with a first limiting portion 141, and the worm gear 14 is circumferentially provided with a second limiting portion 140 that engages with the first limiting portion 141.

(90) As shown in FIGS. 23 and 24, in some embodiments, the shell of the slewing reducer 1 is provided with a first limiting portion 141, and the worm gear 14 is circumferentially provided with a second limiting portion 140 that engages with the first limiting portion 141. The arrangement of the first limiting portion 141 and the second limiting portion 140 ensures that the slewing reducer 1 has a higher stability during rotation. Furthermore, such arrangement ensures a higher safety protection capability in the event of failure of the external limit switch.

(91) As shown in FIGS. 23 and 24, in some embodiments, the first limiting portion 141 is provided for at least two lobes. The lobes are fixedly connected to the top inside the shell of the slewing reducer 1. The second limiting portion 140 is provided for a convex ring, and the convex ring is fixedly connected to the circumferential direction of the worm gear 14.

(92) As shown in FIGS. 23 and 24, in some embodiments, the convex ring is provided in half of the circumferential direction of the worm gear 14, namely, one-half circle. When the worm gear 14 rotates, the convex ring also rotates. At this time, one of the lobes abuts against the incomplete convex ring, to limit the rotation of the worm gear 14. Specifically, a plurality of cover plates 76 are provided on the shell of the slewing reducer 1. The cover plates 76 can be connected to the shell of the slewing reducer 1 in the form of bolts and nuts. Through the arrangement of the cover plate 76, a relative airtightness of the shell of the slewing reducer 1 makes it difficult for external dust to enter the shell of slewing reducer 1, ensuring the stability of the internal mechanical operation of the shell of slewing reducer 1. Optionally, a leg 77 that is connected to the column 19 is provided outside of the shell of the slewing reducer 1, and the leg 77 can also be configured to fix the shell 70 in the form of a bolt and a nut.

(93) As shown in FIGS. 36 and 37, in some embodiments, the connecting member 20 rotatably engages with the transmission shaft 10 through a self-lubricating bearing. The self-lubricating bearing is a prior art and will not be described here again. The connecting member 20 is connected to the main beam 12 through the sliding rail, and the connecting member 20 can slide on the sliding rail. With the arrangement of the sliding rail and connecting member, the main beam drives the slip ring of the transmission shaft to rotate; the rotations of the main beam and the transmission shaft do not interfere with each other, and both of them can rotate freely within a limited range.

(94) As shown in FIG. 42, in some embodiments, the connecting member 20 slides outside the sliding rail 131.

(95) As shown in FIG. 42, in some embodiments, a slip ring 15b is provided on the connecting member 20, and the slip ring 15b is sleeved on the outside of the sliding rail 131, and the slip ring 15b moves along the trajectory of the sliding rail 131.

(96) As shown in FIG. 38, preferably, in some embodiments, the connecting member 20 slides inside the sliding rail 131.

(97) As shown in FIG. 38, preferably, in some embodiments, an annular chute 141 is provided outside the connecting member 20, an annular groove 17b that engages with the annular chute is

provided inside the sliding rail **131**, and the annular chute **141** can slide in the annular groove **17b**.
(98) As shown in FIG. **38**, in some embodiments, the sliding rail **131** is arranged in a circular arc shape, the sliding rail **131** is provided with a frame **132** consistent with the shape of the main beam **12**, and the main beam **12** is provided through the interior of the frame **132**. Specifically, a pair of support portions extending outwardly is provided on the frame **132**, and the pair of support portions can be fixed by bolts and nuts.

(99) As shown in FIG. **39**, in some embodiments, both ends of the worm gear **14** are connected to the main beam **12** by a connecting assembly, and the connecting assembly comprises a disc **110**, a square shaft **111**, and a connecting column **1120** arranged between the disc **110** and the square shaft **111**. Specifically, the disc, square shaft, and connecting column are processed into a whole, and the four corners of the square shaft are arc-shaped. The shape of the outer ring of the square shaft is the same as the shape of the inner wall of the main beam.

(100) As shown in FIG. **39**, in some embodiments, the square shaft **111** is arranged eccentrically relative the disc **110**. Through the eccentric setting, the design size of one end connected with the worm gear is small, which can avoid the interference of the mounted connecting bolt, and the other end has a larger design size, which can match the main beam of larger size, and the eccentric design can reduce the moment arm of the support, that is, reducing the driving torque of the whole support, and effectively reducing the driving energy of the whole support. The disc **110** is provided with a first positioning hole **112**, and the worm gear **14** is provided with a second positioning hole **113**, and the first positioning hole **112** is in anti-rotation engagement with the second positioning hole **113** through a locking member **114**. Specifically, the locking member **114** can be provided as bolts and nuts.

(101) As shown in FIG. **45**, in some embodiments, the main beam **12** is externally sleeved with a rotating shaft **2**, and the rotating shaft **2** engages with the worm gear **14** through a rolling bearing **20a**. Specifically, the rolling bearing **20a** is a four-point contact ball bearing. The four-point contact ball bearing is a prior art and a separate type of bearing, that is to say, a set of bearings are angular contact ball bearing that can bear bidirectional axial load. It is not described in more details here.

(102) As shown in FIG. **45**, in some embodiments, the main beam **12** is connected to the rotating shaft **2** and the shell of the slewing reducer **1** through a retaining member **21a**.

(103) As shown in FIG. **46**, in some embodiments, the retaining member **21a** is provided with a convex ring **210** extending outwardly in the axial direction. Specifically, the inner wall of the convex ring **210** matches the outer wall of the main beam **12**. The outer wall of the **210** is arranged in an arc shape. In this embodiment, the number of the retaining members **21a** is four, and the retaining members are evenly distributed in the circumferential direction of the main beam **12**; the outer wall of the convex ring **210** is provided with the first inclined plane **211** from top to the bottom. The rotating shaft **2** and the inner wall of the shell of the slewing reducer **1** are provided with the second inclined plane **212** from bottom to top, and the first inclined plane **211** can move left and right along the second inclined plane **212**.

(104) As shown in FIG. **46**, the retaining member **21a** is provided with a truncated cone **22a** extending outwardly in the radial direction, the truncated cone **22a** is provided with a first locking hole **23b**, both the rotating shaft **2** and the shell of the slewing reducer **1** are provided with a second locking hole **24a**, and the first locking hole **23b** is in anti-rotation engagement with the second locking hole **24a** through a locking member **25a**, and the locking member **25a** can be provided with bolts and nuts. When the retaining member **21a** is axially locked by the locking member **25a** and moves, the radial spacing between the four retaining members **21a** will shrink and change. The locking force of the screw is changed by the first inclined plane **26a** and the second inclined plane **27a** to the radial pressure of the retaining member **21** on the main beam **12**, to achieve the purpose of locking the torque tube of the main beam **12**.

(105) As shown in FIGS. **48** and **49**, preferably, in some embodiments, a first inclined plane **211a** structure is arranged on the outer wall of the retaining member **21a** from top to bottom, and the

retaining member **21a** is arranged in 4 pairs, and are arranged evenly on the left and right sides of the main beam **12** in the circumferential direction. Specifically, the inner wall of the retaining member **21a** is a plane, and the surface in contact with the main beam **12** is a plane; the inner wall of the rotating shaft **2** is provided with a plurality of stiffeners **220** extending inwardly in the circumferential direction. The number of stiffeners is 8 to 12, and a second inclined plane **212a** structure is arranged on the inner walls of the stiffeners **220** from bottom to top, and the first inclined plane **211a** can move left and right along the second inclined plane **212a**.

(106) As shown in FIG. 50, preferably, in some embodiments, the retaining member **21a** is provided with a boss **221** extending outwardly in the radial direction, the boss **221** is provided with a first locking hole **23a**, both the rotating shaft **2** and the shell of the slewing reducer **1** are provided with a second locking hole **24a**, and the first locking hole **23a** is in anti-rotation engagement with the second locking hole **24a** through a locking member **21a**. After the main beam passes through the inner hole, the retaining member **21a** is pulled to produce axial movement by twisting the locking member **25a**. The retaining member **2** and the second inclined plane of the stiffener can change their own radial position through sliding meshing. When the retaining member **2** is moved to the proper position, the distance between the two sets of symmetrical retaining members **2** becomes smaller, and the plane of each retaining member **2** fits with the outer plane of the main beam of the torque tube, so as to achieve the purpose of locking the torque tube of the main beam.

(107) As shown in FIG. 50, in some embodiments, the shape of the inner wall of the retaining member **21a** is the same as the shape of the outer wall of the main beam **12**.

(108) Of course, as shown in FIGS. 51 to 54, in other embodiments, the shell is provided with a mounting hole **121** for the main beam **12** to pass through, the mounting hole **121** is provided as a polygonal hole. The shape and size of the mounting hole **121** are corresponding to the main beam **12**, and the mounting hole **121** has a taper in the length direction; a plurality of retaining members **21b** are provided between the main beam **12** and the wall of the mounting hole **121** to restrict the relative positions of the main beam **12** and the side wall of the mounting hole **121**. The retaining member **21b** is in anti-rotation engagement with the main beam **12** and the inner wall of the mounting hole **121**.

(109) Specifically, as shown in FIGS. 52 to 55, the retaining member **21b** is provided with at least two flanged portions **213** and a connecting portion **214** that is connected to the flanged portions **213**, and an angle is formed between the two flanged portions **213**. The angle is corresponding to the angle between the adjacent sides of the main beam **12**, and the size of the inner edge of the flanged portion **213** is corresponding to the size near the edge of the main beam **12**, and can be completely fit to the main beam **12**; the outer edge of the flanged portion **213** is provided with a taper, and the taper and size of the flanged portion **213** are the same as those close to the edge of the mounting hole **121**; the connecting portion **214** is connected to the shell by screws; when the main beam **12** is connected to the mounting hole **121**, a plurality of retaining members **21b** are respectively fit to the edges of the main beam **12** respectively, such that the outer taper of the retaining member **21b** is fit to the inner taper of the mounting hole **121**, and the connection point of the adjacent flanged portion **213** is corresponding to the edge of the mounting hole **121**, and then the screw is screwed to push the retaining member **21b** to move axially, and then the retaining member **21b** will be stuck into the mounting hole **121** until the surface of the main beam **12** is completely fit to the retaining member **21b**, thereby locking the axial and radial directions of the main beam **12**. In this mounting method, the main beam **12** passes through the middle of the slewing reducer **1**, so a set of flat single-axis main beam **12** can reduce joints to make a single main beam **12** to be longest, thereby reducing the wastage of materials and avoiding the wastage of improper length of the main beam **12** caused by construction error of the column **19** on the site, and reducing the difficulty of on-site construction and improving the installation progress.

(110) Since the flanged portion **213** is completely fit to both sides of the edge of the main beam **12** and squeezes the main beam **12**, the strength near the edge of the main beam **12** in the present

invention is greater than the strength of the side of the main beam **12**, avoiding the deformation of the main beam **12** caused by small joint surface and improving the anti-deformation ability of the main beam **12**.

(111) Further, as shown in FIGS. **53** and **54**, the inner wall of the mounting hole **121** is provided with a plurality of reinforcing plates **1211** in the length direction. When the connecting portion **214** is connected to the shell, the outer edge of the flanged portion **213** is pressed against and is fit to the reinforcing plate **1211**; the inner wall of the mounting hole **121** is further provided with a first weight-reducing groove **1212** and a second weight-reducing groove **1213** to reduce the weight of the shell. The first weight-reducing groove **1212** is formed between two reinforcing plates **1211** on the inner wall of the same mounting hole **121**, the second weight-reducing groove **1213** is provided between the reinforcing plate **1211** and the inner wall of the mounting hole **121**.

(112) Referring to FIG. **53** and FIG. **54**, in some embodiments, the shell is provided as a chimney structure, and the shell is provided with an inner layer **105** and a periphery **106**. The worm gear is partially inserted between the inner layer **105** and the periphery **106**; the inner layer **105** and the periphery **106** are provided on the shell, and the inner layer **105** is directly and rotatably connected to the worm gear **14**, thereby connecting the shell and the worm gear **14**, reducing intermediate transmission links, making the slewing reducer **30** to be compact, improving the assembly efficiency and reducing the production cost.

(113) As shown in FIGS. **56** to **58**, in some embodiments, the shell is provided with a mounting boss **103**, and the mounting boss **103** is screwed with a locking cover **104**, which is convenient for observing the operation of the bearing, and one end of the locking cover **104** abuts against the bearing at the end portion of the worm **15**; the locking cover **104** is provided with a plurality of positioning holes **1041** in the radial direction. After the locking cover **104** is mounted in place, a set screw **1042** is mounted inside the positioning hole **1041** and connected to the shell, avoiding the movement of the locking cover **104** during the operation of the driving mechanism. A through-hole **1043** is provided in the middle of the locking cover **104**, and a sealing cover **1044** is provided disassembly in the through-hole **1043**. The sealing cover **1044** is easy to disassemble to facilitate the lubrication of the bearing at the end portion of the worm **15** and facilitate the observation of operating conditions; The locking cover **1044** is provided with a sealing groove **1044a**, and the sealing groove **1044a** is provided with a sealing ring **1045** to seal the gap between the locking cover **104** and the mounting boss **103**. When the locking cover **104** is mounted in place, the end face of the locking cover **104** is flush with the end face of the mounting boss **103**. In addition, the end of the locking cover **104** facing away from the worm **15** is arranged with a plurality of locking grooves **1046** around the through-hole **1043**, which need to be adapted with key to match with the locking grooves **1046** to rotate the locking cover **104**, and prevent unrelated persons from opening or closing at will, increasing the degree of safety.

(114) As shown in FIG. **51** and FIG. **59**, in some embodiments, the shell is fixed on column **19** through a mounting base **29**, and a support **191** is symmetrically provided on both sides of the column **19**. The support **191** is provided in an L shape. One side is detachably connected to the column **19**, and the other side is flush with the top surface of column **19** to form a mounting plane. The two supports **191** and column **19** jointly support the mounting base **29** to improve the stability of the mounting base **29**; the connecting surface of the mounting base **29** and the support **191** is provided with a first strip hole **291**. The fastening bolt passes through the first strip hole **291** and is connected to the support **191**. The position of the mounting base on the support **191** can be adjusted appropriately through the first strip hole **291**; the mounting base **29** is provided with an extension portion **292** in the length direction of the column **19**, and the extension portion **292** is fit to the column **19** and is connected by fastening bolts to improve the stability of the mounting base **29**. In addition, the extension portion **292** is provided with a second strip hole **293**, and the fastening bolt partially penetrates the second strip hole **293**, so as to prevent the fastening bolt from affecting the displacement of the mounting base **29**.

(115) Any embodiment of the present invention can be used as an independent technical solution, or can be combined with other embodiments.

(116) The above description shows and describes the basic principles and main features, and advantages of the present invention. For those skilled in the art, it is obvious that the present invention is not limited to the details of the above exemplary embodiments, and can be realized in other specific forms without departing from the spirit or basics of the present invention. Therefore, from any point of view, the embodiments should be regarded as exemplary and non-restrictive. The scope of the present invention is defined by the appended claims rather than the above description. Therefore, it is intended that all changes falling within the meaning and scope of equivalent elements of the claims are included in the present invention. Any reference signs in the claims should not be regarded as limiting the claims involved.

(117) In addition, it should be understood that although this description is described in accordance with the embodiments, not each embodiment only includes an independent technical solution. The narration in the description is only for clarity, and those skilled in the art should regard the description as a whole. The technical solutions in the various examples can also be appropriately combined to form other embodiments that can be understood by those skilled in the art.

Claims

1. A solar tracker, comprising a main beam and at least one slewing reducer, one of the at least one slewing reducer is connected to a motor, the motor is controlled by a motor controller, and the motor controller is connected to the motor by a cable; wherein the one of the at least one slewing reducer that is connected to the motor is a driving slewing reducer, and other slewing reducers are driven slewing reducers, a torque of the driving slewing reducer is transmitted to the driven slewing reducers through a transmission shaft, and the driving slewing reducer and the driven slewing reducers rotate synchronously to drive the main beam to rotate; the main beam is provided through an interior of the at least one slewing reducer; wherein the main beam is sleeved with a rotating shaft, and the rotating shaft engages with a worm gear through a rolling bearing; wherein the main beam is connected to the rotating shaft and a shell through a retaining member; wherein the retaining member is provided with a convex ring extending outwardly in an axial direction, a first inclined plane is arranged on an outer wall of the convex ring from top to bottom, a second inclined plane is arranged on an inner wall of the rotating shaft and the shell of the at least one slewing reducer from bottom to top, and the first inclined plane can move left and right along the second inclined plane.

2. The solar tracker according to claim 1, wherein the retaining member is provided with a truncated cone extending outwardly in a radial direction, the truncated cone is provided with a first locking hole, both the rotating shaft and the shell of the at least one slewing reducer are provided with a second locking hole, and the first locking hole is in anti-rotation engagement with the second locking hole through a locking member.

3. A solar tracker, comprising a main beam and at least one slewing reducer, one of the at least one slewing reducer is connected to a motor, the motor is controlled by a motor controller, and the motor controller is connected to the motor by a cable; wherein the one of the at least one slewing reducer that is connected to the motor is a driving slewing reducer, and other slewing reducers are driven slewing reducers, a torque of the driving slewing reducer is transmitted to the driven slewing reducers through a transmission shaft, and the driving slewing reducer and the driven slewing reducers rotate synchronously to drive the main beam to rotate; the main beam is provided through an interior of the at least one slewing reducer; wherein the main beam is sleeved with a rotating shaft, and the rotating shaft engages with a worm gear through a rolling bearing; wherein the main beam is connected to the rotating shaft and a shell through a retaining member; wherein a first inclined plane is arranged on an outer wall of the retaining member from top to bottom, and an

inner wall of the rotating shaft is provided with a plurality of stiffeners extending inwardly in a circumferential direction, a second inclined plane is arranged on the inner walls of the plurality of stiffeners from bottom to top, and the first inclined plane can move left and right along the second inclined plane.

4. The solar tracker according to claim 3, wherein the retaining member is provided with a boss extending outwardly in a radial direction, the boss is provided with a first locking hole, both the rotating shaft and the shell of the at least one slewing reducer are provided with a second locking hole, and the first locking hole is in anti-rotation engagement with the second locking hole through a locking member.

5. The solar tracker according to claim 1, wherein a shape of the inner wall of the retaining member is same as the shape of the outer wall of the main beam.

6. A single main beam multi-point driving solar tracking system, comprising a main beam and at least one slewing reducer, one of the at least one slewing reducers is connected to a motor, and the motor is controlled by a motor controller, and the motor controller is connected to the motor by a cable; wherein the one of the at least one slewing reducer that is connected to the motor is a driving slewing reducer, and other slewing reducers are driven slewing reducers, a torque of the driving slewing reducer is transmitted to the driven slewing reducers through a transmission shaft, and the driving slewing reducer and the driven slewing reducers rotate synchronously to drive the main beam to rotate; the at least one slewing reducer and the transmission shaft are rotatably provided with the main beam synchronously in same direction; wherein a shell of the at least one slewing reducer is provided with a first connecting column and a second connecting column, and the main beam on a left side of the at least one slewing reducer is connected to the first connecting column, the main beam on a right side of the at least one slewing reducer is connected to the second connecting column; the second connecting column and the shell are an integral structure, and the first connecting column is detachably connected to the second connecting column.

7. The single main beam multi-point driving solar tracking system according to claim 6, wherein the at least one slewing reducer is a worm gear slewing reducer, a worm gear of the at least one slewing reducer is fixedly arranged on the column, and the shell of the at least one slewing reducer is fixedly connected to the main beam, the worm gear rotatably engages with the shell; when the motor is started, a worm rotates around the worm gear while revolving to drive the at least one slewing reducer and the main beam to rotate.

8. The single main beam multi-point driving solar tracking system according to claim 6, wherein the transmission shaft is provided with a plurality of connecting members spaced apart in a length direction, and each connecting member is connected to the main beam.

9. The single main beam multi-point driving solar tracking system according to claim 8, wherein one end of each connecting member is sleeved on the transmission shaft, and the other end is sleeved on the main beam, the transmission shaft is provided with a bearing at a connection point, and the main beam is provided with a frame and a fastener at the connection point.

10. The single main beam multi-point driving solar tracking system according to claim 7, wherein a connecting plate is provided on the column, and a connecting portion connected to the connecting plate is provided on the worm gear.

11. The single main beam multi-point driving solar tracking system according to claim 7, wherein a rolling bearing assembly and a sliding bearing assembly are provided between the worm gear and the first connecting column, and the rolling bearing assembly comprises an inner ring, an outer ring, and a plurality of balls arranged between the inner ring and the outer ring, the inner ring is formed on the first connecting column, and the outer ring is formed on the worm gear.

12. The single main beam multi-point driving solar tracking system according to claim 11, wherein the sliding bearing assembly comprises a first sliding portion and a second sliding portion, and the first sliding portion is formed on the second connecting column, the second sliding portion is formed on the worm gear.

13. The single main beam multi-point driving solar tracking system according to claim 7, wherein one end of the worm is externally sleeved with a first bevel gear and a transmission gear, and a motor output end is provided with a first gear meshing with the transmission gear, the transmission shaft is externally sleeved with a second bevel gear, and the first bevel gear meshes with the second bevel gear.
