

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276281

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Hermalyn; Brendan et al.

Systems for Capturing Emissions

Abstract

A system for directly capturing and measuring greenhouse gasses from a mixture of gasses over a wide range of concentrations from ambient air to combustion exhaust products including: an emissions capture reaction vessel; a reaction media container configured to house a volume of reaction media, the reaction media configured to extract a constituent gas from gas flowing through the emissions capture reaction vessel and capture constituent gas; an intake and exhaust manifold configured to receive and release, respectively a portion of a gas stream via a first access tap on the exhaust stack; a computer system comprised of sensors and actuators connected to a network to directly measure efficiency and uptake of a system, and a fan arranged within the housing and configured to influence the amount and speed of the gas stream.

Inventors: Hermalyn; Brendan (Brooklyn, NY), Kolaczynski; John (Brooklyn, NY), Patterson; Samuel (Brooklyn, NY), Juvvadi; Mihir (Brooklyn, NY), Evenat; Thomas (Brooklyn, NY), Schultz; Peter (Providence, RI)

Applicant: Thalo Labs, Inc. (Brooklyn, NY)

Family ID: 87070011

Appl. No.: 19/212490

Filed: May 19, 2025

Related U.S. Application Data

parent US continuation 18466402 20230913 parent-grant-document US 12330116 child US 19212490

parent US continuation 18096529 20230112 parent-grant-document US 12121853 child US 18466402

us-provisional-application US 63298940 20220112

Publication Classification

Int. Cl.: **B01D53/62** (20060101); **B01D53/00** (20060101); **B01D53/34** (20060101)

U.S. Cl.:

CPC **B01D53/62** (20130101); **B01D53/005** (20130101); **B01D53/346** (20130101);
B01D2251/604 (20130101); **B01D2257/504** (20130101); **B01D2258/0283** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This Application is a continuation of and claims the benefit of U.S. application Ser. No. 18/466,402, filed on Sep. 13, 2023, which is a continuation of and claims the benefit of U.S. application Ser. No. 18/096,529, filed on Jan. 12, 2023 (now U.S. Pat. No. 12,121,853), which claims the benefit of U.S. Provisional Application No. 63/298,940, filed on Jan. 12, 2022, each of which is incorporated in its entirety by this reference.

TECHNICAL FIELD

[0002] This invention relates generally to the field of emissions capture and more specifically to a new and useful system for capturing emissions in the field of emissions capture.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0003] FIG. 1 is a flowchart representation of a system;
[0004] FIGS. 2A, 2B, 2C, and 2D are schematic representations of variations of the system;
[0005] FIG. 3 is a flowchart representation of one variation of the system;
[0006] FIG. 4 is a flowchart representation of one variation of the system;
[0007] FIG. 5 is a flowchart representation of one variation of the system; and
[0008] FIG. 6 is an electrical block diagram of one variation of the system.

DESCRIPTION OF THE EMBODIMENTS

[0009] The following description of embodiments of the invention is not intended to limit the invention to these embodiments but rather to enable a person skilled in the art to make and use this invention. Variations, configurations, implementations, example implementations, and examples described herein are optional and are not exclusive to the variations, configurations, implementations, example implementations, and examples they describe. The invention described herein can include any and all permutations of these variations, configurations, implementations, example implementations, and examples.

1. System

[0010] As shown in FIGS. 1-6, a system **100** for directly capturing emissions from an exhaust stack **102** in a building includes: an emissions capture reaction vessel **110**; a housing **111**; a reaction media container **114**; a housing inlet **113**; a housing outlet **112**; and a fan **115**.

[0011] The emissions capture reaction vessel **110** can be arranged proximal the exhaust stack **102** and includes: a housing **111**; a reaction media container **114** arranged within the housing **111** and configured to house a volume of reaction media, the reaction media configured to extract a constituent gas from flowing through the emissions capture reaction vessel **110** and capture constituent gas; a housing inlet **113** arranged on the housing **111** and configured to receive a portion of an exhaust gas stream, exhausting through the exhaust stack **102** and inbound to the emissions

capture reaction vessel **110**, via a first access tap at a first height on the exhaust stack **102** and configured to feed the portion of the exhaust gas stream toward the reaction media container **114**; a housing outlet **112** arranged on the housing **111** and configured to return the portion of the exhaust gas stream, exiting the reaction media container **114**, back to the exhaust stack **102** via a second access tap at a second height, greater than the first height, on the exhaust stack; and a fan **115** arranged within the housing **111** and configured to influence the portion of the exhaust gas stream from the housing inlet **113**, over the reaction media container **114**, and through the housing outlet **112**.

[0012] As shown in FIG. 3, one variation of the system **100** includes a first emissions capture reaction vessel **110** and includes: a first housing **111**; a first reaction media container **114** arranged within the first housing **111** and configured to house a volume of reaction media, the reaction media configured to extract a constituent gas from gas flowing through the first emissions capture reaction vessel **110** and capture constituent gas; a first housing inlet **113** arranged on the first housing **111** and configured to receive a portion of an exhaust gas stream, exhausting through the exhaust stack **102** and inbound to the first emissions capture reaction vessel **110**, via a first access tap at a first height on the exhaust stack **102** and configured to feed the portion of the exhaust gas stream toward the reaction media container **114**; a first housing outlet **112** arranged on the first housing **111** and coupled to a second housing inlet **113** of a second emissions capture reaction vessel **110**. The system **100** further includes a second emissions capture reaction vessel **110** and includes: a second housing **111**; a second reaction media container **114** arranged within the second housing **111** and configured to house the volume of the reaction media, the reaction media configured to extract the constituent gas from gas flowing through the second emissions capture reaction vessel **110** and capture constituent gas; a second housing inlet **113** arranged on the second housing **111** and configured to return the portion of the exhaust gas stream, exiting the second reaction media container **114**, back to the exhaust stack **102** via a second access tap at a second height, greater than the first height, on the exhaust stack **102**.

[0013] As shown in FIG. 4, one variation of the system **100** includes: a housing inlet manifold **126** coupled to a first access tap at a first height on an air supply; a housing outlet manifold **128** coupled to a second access tap at a second height, greater than the first height, on the air supply **102**; and a first emissions capture reaction vessel **110**. The first emissions capture reaction vessel **110** includes: a first housing **111**; a first reaction media container **114** arranged within the first housing **111** and configured to house a volume of reaction media, the reaction media configured to extract a constituent gas from gas flowing through the first emissions capture reaction vessel **110** and capture constituent gas; a first housing inlet **113** arranged on the first housing **111**, coupled to the housing inlet manifold **126**, and configured to receive a first portion of a gas stream from the air supply via the housing inlet manifold **126**; and a first housing outlet arranged on the first housing **111**, coupled to the housing outlet manifold **128**, and configured to return the first portion of the gas stream back to the air supply **102** via the housing outlet manifold **128**. The system **100** also includes a second emissions capture reaction vessel **110** and includes: a second housing **111**; a second reaction media container **114** arranged within the second housing **111** and configured to house the volume of the reaction media, the reaction media configured to extract the constituent gas from gas flowing through the second emissions capture reaction vessel **110** and capture constituent gas; a second housing inlet **113** arranged on the second housing **111**, coupled to the housing inlet manifold **126**, and configured to receive a second portion of the gas stream from the air supply **102** via the housing inlet manifold **126**; and a second housing outlet **112** arranged on the second housing **111**, coupled to the housing outlet manifold **128**, and configured to return the second portion of the gas stream back to the air supply via the housing outlet manifold **128**.

2. Applications

[0014] Generally, the system **100** includes an emissions capture reaction vessel **110** that includes: a housing **111**; a reaction media container **114**; a housing inlet **113**; a housing outlet **112**; and a fan

115. The system **100** can also include: a set of sensors **130** (e.g., gas sensors, temperature sensors, gas flow sensors); a controller **150**; and/or a remote computer system that cooperate to: capture a portion of an exhaust gas stream exhausting through an exhaust stack **102** coupled to a utility system—such as a boiler, a furnace, a water heater, a space heater, an air heater, a drying machine, a fireplace, a generator, a cogeneration device—located within and/or on a building (e.g., educational building, industrial building) from a first access tap on the exhaust stack **102**; absorb constituent gas (e.g., carbon dioxide) from this portion of the exhaust gas stream and capture constituent gas (e.g., carbon dioxide) via reaction media (e.g., a metal oxide or hydroxide solid) housed within the reaction media container **114** of the emissions capture reaction vessel **110**; and return the portion of the exhaust gas stream (e.g., processed gas) back into a second access tap on the exhaust stack **102**.

[0015] More specifically, the emissions capture reaction vessel **110** can include: a housing **111**; a housing inlet **113** configured to receive the portion of the exhaust gas stream from the first access tap at a first height on the exhaust stack **102**; a reaction media container **114** arranged within the housing and configured to house reaction media. The reaction media can: extract a constituent gas (e.g., carbon dioxide) from the exhaust gas stream; and capture the constituent gas (e.g., carbon dioxide) for sequestering during a future time period. The emissions capture reaction vessel **110** also includes a housing outlet **112** configured to return the portion of the exhaust gas stream back into a second access tap at a second height, greater than the first height, on the exhaust stack **102**.

[0016] In one implementation, the system **100** can be configured to include a set of emissions capture reaction vessels **110** (e.g., 3 emissions capture reaction vessels, 10 emissions capture reaction vessels, 20 emissions capture reaction vessels) to capture carbon corresponding to carbon emissions (e.g., 2,000 parts-per-million of carbon dioxide, 10,000 parts-per-million of carbon dioxide, 80,000 parts-per-million of carbon dioxide) from an exhaust stack **102** connected to a utility system located within and/or on an educational building.

[0017] In one variation, the system **100** can be configured to include a set of emissions capture reaction vessels **110** configured to capture carbon from a low carbon dioxide concentration emitting exhaust stack **102** connected to a furnace located within and/or on a building. In another variation, the system **100** can be configured to include a set of emissions capture reaction vessels **110** configured to capture carbon from a high carbon dioxide concentration emitting exhaust stack **102** connected to a boiler located within and/or on an industrial building.

[0018] Furthermore, the controller **150** can cooperate with a remote computer system to: read timeseries concentrations of the portion of the exhaust gas stream from a gas sensor **130**, gas flow rates from a gas flow rate sensor **130**, and temperatures from a temperature sensor **130** during a processing cycle; monitor gas flow rate, mass flux, and temperature via the set of sensors (e.g., gas sensors, gas flow rate sensors, temperature sensors); execute actions (e.g., generate notifications) indicating removal and replacement of reaction media housed within the reaction media container **114** of the emissions capture reaction vessel **110**; selectively trigger actuators—such as a fan **115**, a heating element **116** and/or a valve **140**—within the system **100** and thereby achieve minimal to no generation of constituent gases (e.g., carbon monoxide, nitrogen oxide, sulfur oxide) and combustion of gas within the system **100** and/or within the building during a processing cycle.

[0019] In one variation, the system **100** can include an emissions capture reaction vessel **110** that includes: a housing **111**; a reaction media container **114**; a housing inlet **113**; a housing outlet **112**; a fan **115**; a set of sensors **130** (e.g., gas sensors, temperature sensors, gas flow sensors); a controller **150**; and/or a remote computer system that cooperate to capture a portion of greenhouse gasses from an air supply within a building (e.g., ambient indoor air or located near or in the flow of a circulating HVAC system or air handler) and/or outside of a building (e.g., an industrial building, a sports arena, a data center, a manufacturing facility, a stadium). Furthermore, the system **100** can process both: combustion exhaust gas (e.g., when a boiler or other building system is in operation); and non-combusted gas (e.g., when the boiler or other building system is inactive).

3. System

[0020] As described above, the system **100** includes an emissions capture reaction vessel **110** that can be arranged proximal an exhaust stack **102** in a building and includes: a housing **111**; a reaction media container **114** arranged in the housing **111** and configured to house a volume of a reaction media; a housing inlet **113** arranged on the housing **111** and configured to receive a portion of the exhaust gas stream via a first access tap at a first height on the exhaust stack **102**; a housing outlet **112** arranged on the housing **111** and configured to return the portion of the exhaust gas stream (e.g., processed gas), exiting the reaction media container **114**, back to the exhaust stack **102** via a second access tap on the exhaust stack **102**; from the housing **111** to the exhaust stack **102**; and a fan **115** arranged within the housing **111** and configured to extract (e.g., pull) gas from the exhaust stack **102** into the housing inlet **113** and configured to influence the portion of the exhaust gas stream from the housing inlet, over the reaction media container **114**, and through the housing outlet **112**. The system **100** can also include a heating element **116**, a filter **117**, a door **118**, an interlock **119**, a set of couplers **120**, and/or a valve **140**.

3.1 Housing Inlet+Housing Outlet+Reaction Media Container

[0021] The emissions capture reaction vessel **110** includes: a housing **111**; a reaction media container **114** arranged within the housing **111** and configured to house a volume of reaction media (e.g., sorbent); a housing inlet **113** arranged on the housing **111**; and a housing outlet **112** arranged on the housing **111**.

[0022] In one implementation, the housing inlet **113** is arranged on the housing **111** and configured to receive a portion of an exhaust gas stream, exhausting through the exhaust stack **102** and inbound to the emissions capture reaction vessel **110**, via a first access tap at a first height on the exhaust stack **102** and configured to feed the portion of the exhaust gas stream toward the reaction media container **114**. The reaction media container **114** is arranged within the housing **111** and is configured to house a volume (e.g., 80 kg, 100 kg) of reaction media. The reaction media can extract (e.g., absorb, adsorb) a constituent gas (e.g., carbon dioxide) from the portion of the exhaust gas stream flowing through the emissions capture reaction vessel **110** and capture the constituent gas (e.g., carbon dioxide) for sequestration. The housing outlet **112** is arranged on the housing **111** and configured to return the portion of the exhaust gas stream, exiting the reaction media container **114**, back to the exhaust stack **102** via a second access tap at a second height, greater than the first height, on the exhaust stack **102**.

[0023] In one variation, the reaction media container **114** can include a baghouse—such as a shaker baghouse, a reverse air baghouse, a pulse jet baghouse—that includes a set of bags configured to house the volume of reaction media (e.g., calcium oxide, hydroxides, amines, metal organic framework). The reaction media can capture the constituent gas and convert the constituent gas into a carbon product (e.g., carbonate, compressed liquefied carbon dioxide, elemental carbon, ethanol, calcium carbonate) during a processing cycle. Once the total constituent gas absorbed by the reaction media approaches a constituent gas capacity (e.g., maximum capacity of the reaction media), a bag in the set of bags within the baghouse can be removed from the reaction media container **114** and replaced with a bag configured to house the volume of new reaction media. Alternatively, the reaction media container **114** can include any other container (e.g., tube, tray, bucket, bottle) configured to house any other volume of reaction media within the housing **111** of the emissions capture reaction vessel **110** and can be replaced once the total constituent gas absorbed by the reaction media approaches the constituent gas capacity.

[0024] Furthermore, the system **100** can include an external reaction media container **114** configured to house a second volume of reaction media, the reaction media can extract (e.g., absorb, adsorb) a constituent gas (e.g., carbon dioxide) from the portion of the exhaust gas stream flowing through the emissions capture reaction vessel **110** into the external media container **114** and return the portion of the exhaust gas stream based into the housing inlet **113** of the emissions capture reaction vessel **110**.

3.2 Fan

[0025] The emissions capture reaction vessel **110** can also include a fan **115**. The fan **115** is arranged within the housing **111** and configured to influence the portion of the exhaust gas stream from the housing inlet **113**, over the reaction media container **114**, and through the housing outlet **112**.

[0026] In one variation, the fan **115** can be configured to influence the portion of the exhaust gas stream flowing through the housing **111** of the emissions capture reaction vessel **110** at a first speed in order to reduce carbon monoxide generation and/or combustion of gas moving through the system **100**.

[0027] In another variation, the fan can be configured to influence the mass flux of the exhaust gas stream from the housing inlet **113**, over the reaction media container **114**, and through the housing outlet **112**.

3.3 Heating Element+Filter

[0028] The emissions capture reaction vessel **110** can also include a heating element **116** and/or a filter **117**. The heating element **116** can be arranged within the housing **111** at the housing outlet **112** of the emissions capture reaction vessel **110** and can be configured to increase the temperature of gas moving through the emissions capture reaction vessel **110**. The filter **117** can be arranged within the housing **111** at the housing inlet **113** of the emissions capture reaction vessel **110** and can be configured to remove constituent gases (e.g., nitrogen oxide, sulfur oxide, carbon monoxide) from gas entering the housing inlet **113** of the emissions capture reaction vessel **110** prior to commencement of a processing cycle.

3.4 Valve

[0029] As shown in FIG. 5, the system **100** can further include a valve **140** interposed between the housing inlet **113** and the first access tap on the exhaust stack **102** and configured to close at the housing inlet **113** to prevent the exhaust gas stream from entering the housing inlet **113**.

[0030] In one variation, the valve **140** is configured to operate in an open position to convey the portion of the exhaust gas stream through the emissions capture reaction vessel **110** and in a closed position to prevent the portion of the exhaust gas stream from entering the housing **111** via the housing inlet **113**. In this variation, a user (e.g., technician, custodial staff, administrator, manager) affiliated with the building can operate (e.g., turn, rotate) the valve **140** to an open position such that the exhaust gas stream can flow from the first access tap on the exhaust stack **102** into the housing inlet **113** of the emissions capture reaction vessel **110**. The user can also operate the valve **140** in a closed position to reduce movement of the exhaust gas stream from entering into the emissions capture reaction vessel **110**.

[0031] Thus, the user can quickly service the emissions capture reaction vessel **110**—such as removing the reaction media container **114** and the volume of reaction media within the reaction media container **114**, filling the reaction media container **114** with new reaction media, and returning the reaction media container **114** to the housing **111**—once the valve **140** is in a closed position.

3.5 Door+Interlock

[0032] The emissions capture reaction vessel **110** further includes a door **118** configured to open to enable transfer of a replacement volume of reaction media into the emissions capture reaction vessel **110** and an interlock **119** coupled to the door.

[0033] In one variation, the emissions capture reaction vessel **110** can include a bag removably coupled to the reaction media container **114** and configured to house the volume of the reaction media. The reaction media can extract the constituent gas from gas flowing through the first emissions capture reaction vessel **110** and capture constituent gas. In this variation, the door **118** is configured to open to enable transfer of a replacement bag configured to house the volume of the reaction media.

[0034] In yet another variation, the door **118** is configured to enable transfer of a replacement volume of reaction media into the reaction media container **114** within the housing **111** of the

emissions capture reaction vessel **110**. In this variation, the valve **140** is arranged between the housing inlet **113** and the first access tap on the exhaust stack **102** and configured to close at the housing inlet **113** to prevent the portion of the exhaust gas stream from flowing through the emissions capture reaction vessel **110** and the interlock **119** is coupled to the door **118** and configured to open the door in response to a threshold duration of time of closure of the valve **140**, and thereby prevents gas from exiting the emissions capture reaction vessel **110** through the door **118** when the emissions capture reaction vessel **110** is serviced.

3.6 Couplers

[0035] The system **100** can further include a set of couplers **120** interposed between the emissions capture reaction vessel **110** and the exhaust stack **102**.

[0036] In one implementation, a first coupler **120**, in the set of couplers **120**, is configured to fluidly couple to the first access tap at the first height on the exhaust stack **102** and a second coupler **120**, in the set of couplers **120**, is configured to fluidly couple to the second access tap at the second height, greater than the first height, on the exhaust stack **102**. In this implementation, the housing inlet **113** is coupled to the first coupler **120** and configured to receive the portion of the exhaust gas stream from the exhaust stack **102** via the first coupler **120** and the housing outlet **112** is coupled to the second coupler **120** and configured to return the portion of the exhaust gas stream back to the exhaust stack **102** via the second coupler **120**.

4. Sensors

[0037] Generally, the system **100** includes a set of sensors **130** coupled to the emissions capture reaction vessel **110** and each sensor, in the set of sensors **130**, is configured to collect non-optical data—such as concentration of gas, gas flow rate, and/or temperature of gas—as gas (e.g., carbon dioxide greenhouse gases) moves through the emissions capture reaction vessel **110** during a processing cycle.

[0038] In one implementation, the system **100** includes a first sensor **130** arranged proximal the housing inlet **113** and a second sensor **130** arranged proximal the housing outlet **112**. The first sensor **130** is configured to collect non-optical data—such as concentration of gas, gas flow rate, and/or temperature—of the portion of the exhaust gas stream entering the housing via the housing inlet **113** during a processing cycle and the second sensor **130** is configured to collect non-optical data—such as concentration of gas, gas flow rate, and/or temperature—of the portion of the exhaust gas stream exiting the housing via the housing outlet **112**.

4.1 Gas Sensors

[0039] In one variation, the system **100** includes a set of gas sensors **130** configured to output signals corresponding to a concentration (e.g., in parts per million): of constituent gas from the portion of the exhaust gas stream (e.g., constituent gas greenhouse gases) exiting the first access tap on the exhaust stack **102** within and/or on a building; and of constituent gas from the portion of the exhaust gas stream (e.g., processed gas) exiting the housing outlet **112** of the emissions capture reaction vessel **110** back into the second access tap of the exhaust stack **102**.

[0040] In one variation, the system **100** includes a first gas sensor **130** arranged proximal the housing inlet **113** and configured to output a first signal corresponding to a first concentration of the constituent gas (e.g., carbon dioxide) from the exhaust gas stream entering the first housing via the housing inlet. The system **100** also includes a second gas sensor **130** arranged proximal the housing outlet **112** and configured to output a second signal corresponding to a second concentration of constituent gas (e.g., carbon dioxide) from the exhaust gas stream, less than the first concentration of gas, exiting the housing outlet **112** of the emissions capture reaction vessel **110** back into the second access tap of the exhaust stack **102**.

[0041] In another variation, the system **100** includes a spectrometer configured to detect a concentration of constituent gas (e.g., carbon dioxide) from the portion of the exhaust gas stream exiting the exhaust stack **102** and a second concentration of constituent gas (e.g., carbon dioxide) from the portion of the exhaust gas stream, less than the first concentration of gas, exiting the

housing outlet **112** of the emissions capture reaction vessel **110**.

[0042] Additionally and/or alternatively, the system **100** can include a first gas flow sensor **130**—such as a wire anemometer or other gas flux sensor **130**—arranged proximal the housing inlet **113** and configured to output a first signal corresponding to a first flow rate of constituent gas (e.g., carbon dioxide) from the exhaust gas stream entering the housing via the housing inlet. The system **100** also includes a second gas flow sensor **130**—such as a wire anemometer or other gas flux sensor **130**—arranged proximal the housing outlet **112** and configured to output a second signal corresponding to a second flow rate of constituent gas (e.g., carbon dioxide) from the exhaust gas stream exiting the housing via the housing outlet **112**.

[0043] Once the system **100** is deployed proximal the exhaust stack **102** in and/or on a building, the controller **150** can: sample these gas flow sensors **130**, such as at a rate of 1 Hz or once per minute; store these data in local memory; and/or stream these data to the remote computer system for further processing.

4.2 Temperature Sensors

[0044] Furthermore, the system **100** can include a set of temperature sensors **130** configured to output signals corresponding to a temperature of the portion of the exhaust gas stream entering the housing via the housing inlet **113** and/or a temperature of the portion of the exhaust gas stream exiting the housing **111** via the housing outlet **112**.

[0045] In one implementation, a first temperature sensor **130** is arranged proximal the housing inlet **113** and configured to output a first signal corresponding to a first temperature of the portion of the exhaust gas stream entering the first housing via the housing inlet. The system **100** also includes a second temperature sensor **130** arranged proximal the housing outlet **112** and configured to output a second signal corresponding to a second temperature of the portion of the exhaust gas stream (e.g., processed gas) exiting the housing via the housing outlet **112**.

[0046] Once the system **100** is deployed proximal an exhaust stack **102** in and/or on the building, the controller **150** can: sample these temperature sensors, such as at a rate of once per minute or once per hour; store these data in local memory; and/or stream these data to the remote computer system for further processing.

5. Controller and Communications

[0047] As described above, the controller **150** can: sample the foregoing sensors continuously or intermittently, such as once per minute; compress and store these raw data locally; and intermittently broadcast these raw data to the remote computer system, such as once per day.

[0048] Alternatively, the controller **150** can execute methods and techniques described below to locally process these raw data and then transmit derived data and insights to the remote computer system, such as once per day.

[0049] For example, the controller **150** can interpret a temperature difference between the portion of the exhaust gas stream entering the housing inlet **113** and exiting the housing outlet **112** based on signals from a set of temperature sensors. The controller **150** can then activate the heating element **116**, activate the fan **115** to influence the portion of the exhaust gas stream moving through the housing at a second speed, and/or close the valve to prevent the exhaust gas stream from entering the housing inlet, in response to the temperature of constituent gas exiting the housing via the housing outlet **112** falling below the temperature of constituent gas entering the housing via the housing inlet **113** by more than a threshold temperature difference.

[0050] In another example, the controller **150** can selectively close the valve **140** to reduce the concentration of constituent gas from the exhaust gas stream moving through the emissions capture reaction vessel **110**, in response to the first concentration of gas exceeding a threshold concentration of gas.

[0051] In yet another example, the controller **150** can selectively close the valve **140** to prevent the portion of the exhaust gas stream entering the housing **111** via the housing inlet **113**, in response to the door **118** opening.

5.1 Remote Computer System

[0052] The remote computer system—such as a remote server—can receive raw data from the set of sensors (e.g., gas sensors, gas flow sensors, temperature sensors) installed in the building and can manipulate these raw data: to estimate a gas flow rate of constituent gas; to interpret a temperature difference of the exhaust gas stream entering and exiting the housing **111** throughout the processing cycle; and to estimate a gas absorption rate and total constituent gas absorbed by the reaction media during a period of time in order to achieve accurate and repeatable conveyance of gas through the emissions capture reaction vessel **110**. The remote computer system can also selectively trigger actuators within the system **100** (e.g., a fan **115**, a heating element **116**, a valve **140**); and to execute actions (e.g., generate prompts, generate notifications) prompting a user (e.g., manager, custodial staff, maintenance worker) affiliated with the building to service the emissions capture reaction vessel **110**, as further described below.

6. Processing Cycle: Carbon Capture

[0053] Generally, the remote computer system can generate a processing cycle and transmit this processing cycle to the controller **150**. The controller **150** can then execute the processing cycle, implemented by the system **100**, to capture gas (e.g., carbon dioxide, greenhouse gases) from an exhaust stack **102** located within a building.

[0054] In one implementation, during a first segment of the processing cycle, the controller can trigger the fan **115** to extract a portion of an exhaust gas stream from a first access tap on the exhaust stack **102** into the housing inlet **113** of the emissions capture reaction vessel **110**. Then, during a second segment of the processing cycle, the reaction media within the reaction media container **114** of the emissions capture reaction vessel **110** can: extract constituent gas (e.g., carbon dioxide) from the portion of the exhaust gas stream; and capture the constituent gas. The reaction media can later be removed and thereby sequestering the captured constituent gas for future periods of time (e.g., 10 years, 100 years, 1,000 years, 10,000 years). Lastly, during a third segment of the processing cycle, the system **100** can return the portion of the exhaust gas stream (e.g., processed gas) from the housing outlet **112** of the emissions capture reaction vessel **110** into a second access tap on the exhaust stack **102** located within the building. Upon termination of the processing cycle, the controller **150** can read raw data from the set of sensors **130** (e.g., gas sensors, gas flow sensors, temperature sensors) and manipulate these data to calculate an amount of constituent gas absorbed by the reaction media, a gas flow rate, a gas concentration difference, a temperature difference of gas between the exhaust gas stream entering the housing **111** via the housing inlet **113** and exiting the housing **111** via the housing outlet **112** of the emissions capture reaction vessel **110**.

[0055] Alternatively, the controller **150** can transmit these raw data to the remote computer system and the remote computer system can manipulate these data to calculate an amount of constituent gas absorbed by the reaction media, a gas flow rate, a gas concentration difference, a temperature difference of gas between the exhaust gas stream entering the housing **111** via the housing inlet **113** and exiting the housing **111** via the housing outlet **112** of the emissions capture reaction vessel **110**.

7. Metrics: Gas Flow Rate+Temperature Difference+Gas Mass Flux

[0056] Furthermore, the remote computer system can maintain a temperature difference between the housing inlet **113** and the housing outlet **112** of the emissions capture reaction vessel **110** and gas flow and mass flux of gas moving through the emissions capture reaction vessel **110**.

[0057] In one implementation, the controller **150** can read raw data from the set of sensors **130** (e.g., gas sensors, gas flow sensors, temperature sensors) and manipulate these raw data to track a temperature difference of the exhaust gas stream between the housing inlet **113** and the housing outlet **112** of the emissions capture reaction vessel **110** and the gas flow in the emissions capture reaction vessel **110**.

[0058] Alternatively, the controller **150** can transmit these raw data to the remote computer system throughout the processing cycle in (near) real time and then the remote computer system can manipulate these raw data to track a temperature difference of the exhaust gas stream between the

housing inlet **113** and the housing outlet **112** of the emissions capture reaction vessel **110** and the gas flow in the emissions capture reaction vessel **110**.

7.1 Threshold Temperature Difference

[0059] In one variation, during the processing cycle, the controller **150** and/or the remote computer system can access a first temperature of gas from a first temperature sensor **130** arranged proximal the housing inlet **113** and configured to detect a temperature of the exhaust gas stream entering the housing inlet **113** of the emissions capture reaction vessel **110** from the first access tap on the exhaust stack **102**. The controller **150** and/or the remote computer system can then access a second temperature of gas from a second temperature sensor **130** arranged proximal the housing outlet **112** and configured to detect a temperature of the exhaust gas stream exiting the housing outlet **112** of the emissions capture reaction vessel **110**. Accordingly, the controller **150** and/or remote computer system can interpret a temperature difference between the exhaust gas stream entering the housing inlet **113** and exiting the housing outlet **112** of the emissions capture reaction vessel **110** based on the first temperature and the second temperature. In response to the second temperature falling below the first temperature by more than a threshold temperature difference, the controller **150** and/or remote computer system can selectively close the valve **140** to prevent the exhaust gas stream from entering the housing inlet **113**.

[0060] In another variation, the controller **150** and/or the remote computer system can implement methods and techniques described above to interpret a temperature difference between the portion of the exhaust gas stream entering the housing inlet **113** and the portion of the exhaust gas stream exiting the housing outlet **112** based on the first temperature of gas and the second temperature of gas. Then, in response to the second temperature falling below the first temperature by more than a threshold temperature difference, the controller **150** and/or the remote computer system can activate the heating element **116**—arranged proximal the housing outlet **112** of the emissions capture reaction vessel **110**—to increase the temperature of gas flowing through the emissions capture reaction vessel **110**.

[0061] In yet another variation, the controller **150** and/or remote computer system can implement methods and techniques described above to interpret a temperature difference between the exhaust gas stream entering the housing inlet **113** and exiting the housing outlet **112** of the emissions capture reaction vessel **110** based on the first temperature and the second temperature. In response to the second temperature falling below the first temperature by more than a threshold temperature difference (e.g., between 210 degrees Fahrenheit to 250 degrees Fahrenheit), the controller **150** and/or remote computer system can selectively activate the fan **115** to influence the portion of the exhaust gas stream moving through the housing at a second speed greater than the first speed.

[0062] Therefore, the controller **150** and/or the remote computer system can manipulate a temperature difference of the exhaust gas stream to within a minimum threshold temperature difference in order to achieve minimal to no generation of constituent gases (e.g., carbon monoxide) within the building or combustion of gas during a processing cycle.

7.2 Gas Concentration

[0063] In one variation, during the processing cycle, the controller and/or remote computer system can access a first concentration of constituent gas from a first gas sensor **130** arranged proximal the housing inlet **113** and configured to detect gas entering the housing via the housing inlet **113** from the first access tap on the exhaust stack **102**. The controller **150** and/or remote computer system can then access a second concentration of constituent gas from a second gas sensor **130** arranged proximal the housing outlet **112** and configured to detect gas exiting the housing **111** via the housing outlet **112**. Then, in response to the first concentration of constituent gas falling below a threshold concentration of constituent gas (e.g., 10 parts-per-million, 50 parts-per-million), the controller **150** and/or remote computer system can trigger the valve **140** to a closed position to prevent the exhaust gas stream from flowing through the emissions capture reaction vessel **110** from the first access tap on the exhaust stack **102**.

[0064] Therefore, the controller **150** and/or remote computer system can monitor gas flow of the exhaust gas stream entering into the housing **111** via the housing inlet **113** from the first access tap on the exhaust stack **102** and can trigger the valve **140** to prevent the exhaust gas stream from entering the housing **111** and thereby enabling a user to open the door **118** and service the emissions capture reaction vessel **110**.

7.3 Reaction Media Capacity

[0065] In one implementation, the controller **150** and/or remote computer system can manipulate data from the set of sensors to track the portion of constituent gas (e.g., carbon dioxide) that is absorbed by the reaction media within the reaction media container **114** of the emissions capture reaction vessel **110**. More specifically, during a particular time period, the controller **150** and/or remote computer system can leverage data from the set of sensors to calculate the constituent gas absorbed by the reaction media within the reaction media container **114** of the emissions capture reaction vessel **110** for each processing cycle.

[0066] For example, at an initial time prior to the processing cycle, the remote computer system can access a maximum constituent gas capacity. Then, during the processing cycle, the controller **150** can trigger the fan **115** within the housing of the emissions capture reaction vessel **110** to extract a portion of exhaust gas stream from the first access tap on the exhaust stack **102** via the housing inlet **113** and the reaction media within the reaction media container **114** of the emissions capture reaction vessel **110** can extract a constituent gas (e.g., carbon dioxide) from the portion of the exhaust gas stream and capture the constituent gas. The captured constituent gas can be stored within a container (e.g., tube, bucket, bottle) coupled to the reaction media container **114** as described above.

[0067] The controller **150** can then trigger the fan **115** to return the portion of exhaust gas stream (e.g., processed gas) from the housing outlet **112** back to the second access port on the exhaust stack **102** located within the building. During the processing cycle, the controller **150** can access raw data from the set of sensors and transmit these data to the remote computer system to calculate constituent gas absorbed by the reaction media during the processing cycle that is stored in the container (e.g., tube, bucket, bottle). Then, in response to the constituent gas absorbed by the reaction media falling below the maximum constituent gas capacity, the controller **150** can execute a second processing cycle.

[0068] During the second processing cycle, the controller **150** can trigger the fan **115** within the housing of the emissions capture reaction vessel **110** to extract a next portion of the exhaust gas stream from the first access port on the exhaust stack **102** via the housing inlet **113** and the reaction media within the reaction media container **114** can extract a constituent gas (e.g., carbon dioxide) from this portion of the exhaust gas stream and capture the constituent gas. The constituent gas can be stored within the container (e.g., tube, bucket, bottle) coupled to the reaction media container **114**. The controller **150** can then trigger the fan **115** to return this portion of exhaust gas stream (e.g., processed gas) from the housing outlet **112** back to the second access port on the exhaust stack **102** located within the building.

[0069] Accordingly, the controller **150** and/or remote computer system can calculate constituent gas absorbed by the reaction media during the second processing cycle that is stored in the container (e.g., tube, bucket, bottle) and calculate a total constituent gas absorbed by the reaction media during the first processing cycle and the second processing cycle. Then, in response to the total constituent gas absorbed by the reaction media approaching the maximum constituent gas capacity of the reaction media, the controller **150** and/or remote computer system can generate a notification indicating removal and replacement of the container and the volume of reaction media within the reaction media container **114** of the emissions capture reaction vessel **110**; and serve the notification to a user (e.g., manager, administrator, custodial staff, technician) affiliated with the building.

7.3.1 Reaction Media Removal and Reloading

[0070] Once the total constituent gas absorbed by the reaction media approaches the maximum gas capacity of the reaction media, a user (e.g., custodial staff, technician) affiliated with the building can open the door **118** of the emissions capture reaction vessel **110** and remove the reaction media container **114** and/or the container with the volume of reaction media and thus the total captured constituent gas, from the emissions capture reaction vessel **110**. The user can then reload the reaction media container **114** with a new container with the volume of reaction media into the housing of the emissions capture reaction vessel **110**.

[0071] In one variation, the user can receive the notification prompting the user to remove the container with the volume of reaction media and reload new reaction media within the emissions capture reaction vessel **110** via a user portal. The user can then remove the container with the reaction media housed within the reaction media container **114** and thus the total captured constituent gas and the container can be transported to a facility for sequestering. The user can then replace the container with a new container configured to house a volume of new reaction media.

[0072] For example, a computing device-accessible by custodial staff affiliated with the building—can receive the notification prompting custodial staff to replace the container with reaction media via the user portal. The custodial staff can then: turn the valve **140** to a closed position; open the housing **111** of the emissions capture reaction vessel **110**; and remove the volume of reaction media and thus the total captured constituent gas in the container from the reaction media container **114** within the housing **111** into a bin that can be transported to a warehouse for sequestering. The user can then: replace the container with a new container with new reaction media; close the housing **111** of the emissions capture reaction vessel **110**; and turn the valve **140** to an open position to enable gas to move from the access tap on the exhaust stack **102** into the housing inlet **113** of the emissions capture reaction vessel **110**. The controller **150** can then execute a next processing cycle with the new reaction media and repeat these methods and techniques for each other processing cycle and for each other new reaction media.

[0073] Additionally or alternatively, the user can implement the methods and techniques described above to remove and replace the container with a new container with new reaction media into the reaction media container **114** arranged within the housing of the emissions capture reaction vessel **110** during a maintenance (e.g., cleaning, servicing) time period predefined by the user (e.g., manager, administrator, technician, custodial staff) affiliated with the building.

7. Variations: Set of Emissions Capture Reaction Vessels

[0074] The system **100** can be configured to include a set of emissions capture reaction vessels **110** (e.g., 3 emissions capture reaction vessels, 10 emissions capture reaction vessels, 20 emissions capture reaction vessels) to capture carbon corresponding to the carbon greenhouse gases (e.g., 2,000 parts-per-million of carbon dioxide, 10,000 parts-per-million of carbon dioxide, 80,000 parts-per-million of carbon dioxide) from an exhaust stack **102** coupled to a utility system—such as a boiler, a furnace, a water heater, a space heater, a drying machine, a fireplace, and/or a generator etc.—located within and/or on a building.

[0075] As shown in FIG. 3, in one implementation, the system **100** can be configured to include a set of emissions capture reaction vessels **110** connected in series for a low emitting exhaust stack **102** (e.g., a furnace emitting 10,000 parts-per-million of carbon dioxide) such that the container with reaction media within the reaction media container **114** of each emissions capture reaction vessel **110** can be replaced in sequential order according to a schedule.

[0076] As shown in FIG. 4, in another implementation, the system **100** can be configured to include a set of emissions capture reaction vessels **110** connected in parallel for a high emitting exhaust stack **102** (e.g., a boiler emitting 80,000 parts-per-million of carbon dioxide) such that the container with reaction media within the reaction media container **114** of each emissions capture reaction vessel **110** can be replaced during a particular time period.

7.1 Variation: Emissions Capture Reaction Vessels Connected in Parallel

[0077] In one variation, the system **100** can be configured to include a set of (e.g., two, three)

emissions capture reaction vessels **110** connected in parallel such that the system **100** can capture carbon, from an exhaust stack **102** emitting a low carbon dioxide concentration exhaust stack (e.g., a furnace emitting 10,000 parts-per-million of carbon dioxide) within a small-scale building (e.g., educational building, office building), in the set of emissions capture reaction vessels **110**.

[0078] In one implementation, the system **100** can include: two emissions capture reaction vessels **110**; a housing inlet manifold **126**; a housing outlet manifold **128**; a set of sensors **130**; and a primary controller **160**. In this example, the housing inlet manifold **126** is fluidly coupled to a first access tap at a first height on an exhaust stack **102** coupled to a furnace within an educational building and the housing outlet manifold **128** is fluidly coupled to a second access tap at a second height, greater than the first height, on the exhaust stack **102** coupled to the furnace.

[0079] The first emissions capture reaction vessel **110**, in the set of emissions capture reaction vessels **110**, includes: a first housing **111**; a first housing inlet **113** arranged on the first housing **111**, coupled to the housing inlet manifold **126**, and configured to receive a first portion of exhaust gas stream (e.g., high concentration carbon dioxide), exhausting through the exhaust stack **102** and inbound to the first emissions capture reaction vessel **110**, via the first access tap on the exhaust stack **102**; and a first housing outlet **112**, arranged on the first housing **111**, coupled to the housing outlet manifold **128**, and configured to return the first portion of exhaust gas stream (e.g., low concentration carbon dioxide) to the second access tap on the exhaust stack **102**. The second emissions capture reaction vessel **110** includes: a second housing **111**; a second housing inlet **113** arranged on the second housing **111**, coupled to the housing inlet manifold **126**, and configured to receive a second portion of exhaust gas stream (e.g., high concentration carbon dioxide), exhausting through the exhaust stack **102** and inbound to the second emissions capture reaction vessel **110**, via the first access tap on the exhaust stack **102**; and a second housing outlet **112** arranged on the second housing **111**, coupled to the housing outlet manifold **128**, and configured to return the second portion of the exhaust gas stream (e.g., low concentration carbon dioxide) to the second access tap on the exhaust stack **102**.

[0080] For example, during a first time period, the primary controller **160** can trigger a first fan **115** arranged within the first emissions capture reaction vessel **110** to extract a first portion of exhaust gas stream from the first access tap on the exhaust stack **102** into the first housing inlet **113** of the first emissions capture reaction vessel **110** via the housing inlet manifold **126**. The first emissions capture reaction vessel **110** can absorb a constituent gas (e.g., high concentration carbon dioxide) from the first portion of exhaust gas stream and capture the constituent gas (e.g., high concentration carbon dioxide) via the reaction media housed within the first reaction media container **114** and return the portion of exhaust gas stream (e.g., low concentration carbon dioxide) from the first housing outlet **112** to the second access tap on the exhaust stack **102** via the housing outlet manifold **128**.

[0081] During the first time period, the primary controller **160** can trigger a second fan **115** arranged within the second emissions capture reaction vessel **110** to extract a second portion of exhaust gas stream from the first access tap on the exhaust stack **102** into the first housing inlet **113** of the first emissions capture reaction vessel **110** via the housing inlet manifold **126**. The second emissions capture reaction vessel **110** can similarly absorb the constituent gas (e.g., high concentration carbon dioxide) from the second portion of exhaust gas stream and capture the constituent gas (e.g., high concentration carbon dioxide) via the reaction media housed within the second reaction media container **114** and return the portion of exhaust gas stream (e.g., low concentration carbon dioxide) from the second housing outlet **112** to the second access tap on the exhaust stack **102** via the housing outlet manifold **128**.

[0082] During a second time period succeeding the first time period, the primary controller **160** can: receive a first signal from a first gas flow sensor **130** corresponding to a first gas flow rate of constituent gas from the exhaust gas stream entering the first housing **111** via the first housing inlet

113; and receive a second signal from a second gas flow sensor **130** corresponding to a second gas flow rate of constituent gas from the exhaust gas stream exiting the second housing **111** via the second housing outlet **112**. The primary controller **160** can then estimate a gas flow rate of constituent gas based on the first signal and the second signal, and, in response to the total constituent gas absorbed by the reaction media in each emissions capture reaction vessel **110** approaching a constituent gas capacity of the volume of reaction media, the primary controller **160** can generate a notification indicating removal and replacement of the reaction media within the reaction media container **114** of each emissions capture reaction vessel **110**; and transmit the notification to a user (e.g., manager, administrator, custodial staff, technician) affiliated with the educational building via a user portal.

[0083] Therefore, the system **100** can be configured to include a set of emissions capture reaction vessels **110** to capture carbon from a low carbon dioxide concentration emitting exhaust stack **102** coupled to a furnace within and/or on an educational building and the reaction media within each emissions capture reaction vessel **110** can be replaced during a particular time period.

7.2 Variation: Emissions Capture Reaction Vessels Connected in Series

[0084] In one variation, the system **100** can be configured to include a set of emissions capture reaction vessels **110** connected in series such that the system **100** can capture carbon, from a high carbon dioxide concentration emitting exhaust stack **102** (e.g., a boiler emitting 80,000 parts-per-million of carbon dioxide) within a large-scale building (e.g., industrial building), in the set of emissions capture reaction vessels **110**.

[0085] In one implementation, the system **100** can include: two emissions capture reaction vessels **110**; a set of sensors **130**; and a primary controller **160**. The first emissions capture reaction vessel **110** includes: a first housing inlet **113** configured to receive a portion of exhaust gas stream (e.g., high concentration carbon dioxide) from the first access tap on the exhaust stack **102**; and a first housing outlet **112** configured to feed processed gas (e.g., low concentration carbon dioxide) into a second housing inlet **113** of the second emissions capture reaction vessel **110**. The second emissions capture reaction vessel **110** includes the second housing inlet **113** configured to receive the processed gas from the first housing outlet **112** of the first emissions capture reaction vessel **110** and a second housing outlet **112** configured to return the processed gas (e.g., low concentration carbon dioxide) to the second access tap on the exhaust stack **102**.

[0086] For example, during a processing cycle, the primary controller **160** can trigger a first fan **115** to extract a first portion of exhaust gas stream from the exhaust stack **102** into the first housing inlet **113** of the first emissions capture reaction vessel **110**. During a first time period, the first emissions capture reaction vessel **110** can then capture constituent gas from the portion of the exhaust gas stream via reaction media within the first reaction media container **114** and feed processed gas (e.g., low concentration carbon dioxide) from the first housing outlet **112** to the second housing inlet **113** of the second emissions capture reaction vessel **110**. During a second time period succeeding the first time period, the second emissions capture reaction vessel **110** can capture constituent gas via reaction media within the second reaction media container **114** and return processed gas (e.g., low concentration carbon dioxide) from the second housing outlet **112** to the second access tap on the exhaust stack **102**.

[0087] During a second time period succeeding the first time period, the primary controller **160** can: receive a first signal from a first gas flow sensor **130** corresponding to a first gas flow rate of constituent gas from the exhaust gas stream entering the first housing **111** via the first housing inlet **113**; and receive a second signal from a second gas flow sensor **130** corresponding to a second gas flow rate of constituent gas from the exhaust gas stream exiting the second housing **111** via the second housing outlet **112**. The primary controller **160** can then: estimate a gas flow rate of constituent gas based on the first signal and the second signal; and, in response to the total constituent gas absorbed by the reaction media in each emissions capture reaction vessel **110** approaching a constituent gas capacity of the volume of reaction media, generate a notification

indicating removal and replacement of the reaction media within the reaction media container **114** of each emissions capture reaction vessel **110**; and transmit the notification to a user (e.g., manager, administrator, custodial staff, technician) affiliated with the educational building via a user portal. [0088] Therefore, the system **100** can be configured to include a set of emissions capture reaction vessels **110** to capture carbon from a high carbon dioxide concentration emitting exhaust stack **102** connected to a boiler within and/or on an industrial building and the first emissions capture reaction vessel **110** can be replaced during a first time period and the second emissions capture reaction vessel **110** can be replaced during a second time period succeeding the first time period.

[0089] The systems and methods described herein can be embodied and/or implemented at least in part as a machine configured to receive a computer-readable medium storing computer-readable instructions. The instructions can be executed by computer-executable components integrated with the application, applet, host, server, network, website, communication service, communication interface, hardware/firmware/software elements of a user computer or mobile device, wristband, smartphone, or any suitable combination thereof. Other systems and methods of the embodiment can be embodied and/or implemented at least in part as a machine configured to receive a computer-readable medium storing computer-readable instructions. The instructions can be executed by computer-executable components integrated by computer-executable components integrated with apparatuses and networks of the type described above. The computer-readable medium can be stored on any suitable computer readable media such as RAMs, ROMs, flash memory, EEPROMs, optical devices (CD or DVD), hard drives, floppy drives, or any suitable device. The computer-executable component can be a processor but any suitable dedicated hardware device can (alternatively or additionally) execute the instructions.

[0090] As a person skilled in the art will recognize from the previous detailed description and from the figures and claims, modifications and changes can be made to the embodiments of the invention without departing from the scope of this invention as defined in the following claims.

Claims

1. A system for processing an air supply comprising: a housing; a housing inlet arranged on the housing and configured to receive a portion of the air supply of an external area of the housing; a filter arranged within the housing at the housing inlet and configured to remove particular matter or a particular gas from the portion of the air supply entering the housing inlet; a reaction media arranged within the housing, the reaction media configured to receive the filtered portion of the air supply and capture a portion of a constituent gas from the filtered portion of the air supply; a housing outlet arranged on the housing and configured to return the portion of the air supply exiting the reaction media back to the external area of the housing; and a fan arranged within the housing and configured to influence the portion of the air supply from the housing inlet, through the reaction media, and through the housing outlet.
2. The system of claim 1, wherein the filter is arranged in series with the reaction media.
3. The system of claim 1, further comprising: a set of sensors; and a controller that receives outputs of the set of sensors and controls the system to process both combustion exhaust gas and non-combusted gas.
4. The system of claim 3, wherein the set of sensors include a gas sensor, a temperature sensor, and a gas flow sensor.
5. The system of claim 1, further comprising: a first gas sensor arranged proximal the housing inlet to output a first signal corresponding to a first concentration of the constituent gas from the portion of the air supply entering the housing inlet; and a second gas sensor arranged proximal the housing outlet to output a second signal corresponding to a second concentration of the constituent gas from the portion of the air supply exiting the reaction media.
6. The system of claim 5, further comprising: a controller configured to estimate a constituent gas

absorption rate by the reaction media based on a difference between the first concentration of the constituent gas and the second concentration of the constituent gas.

7. The system of claim 1, further comprising: a gas sensor to output a signal corresponding to a concentration of the constituent gas from the portion of the air supply entering the housing inlet; and a controller to receive the signal from the gas sensor, and based on the concentration of the constituent gas being above a threshold amount, to cause the fan to influence the portion of the air supply moving through the housing at an increased speed.

8. The system of claim 1: wherein the housing inlet is configured to receive the portion of the air supply which is characterized by a first carbon dioxide concentration; wherein the reaction media absorbs carbon dioxide from the filtered portion of the air supply to capture the portion of the constituent gas; and wherein the housing outlet is configured to return the portion of the air supply back to the external area of the housing, the portion of the air supply returned characterized by a second carbon dioxide concentration less than the first carbon dioxide concentration.

9. The system of claim 1, further comprising: a first access tap to couple the housing inlet to an exhaust stack to receive the portion of the air supply; and a second access tap to couple the housing outlet to the exhaust stack to return the portion of the air supply exiting the reaction media.

10. The system of claim 1, wherein the housing inlet receives the portion of the air supply from a heating ventilation and air conditioning (HVAC) system.

11. The system of claim 1, wherein the housing inlet receives the portion of the air supply from ambient indoor air.

12. The system of claim 1, further comprising: a reaction media container housing the reaction media.

13. The system of claim 1, further comprising: a set of sensors; and a controller configured to execute a processing cycle to filter the portion of the air supply and to capture the portion of the constituent gas from the filtered portion of the air supply; wherein during a first segment of the processing cycle, the controller triggers the fan to draw the portion of the air supply into the housing inlet; wherein during a second segment of the processing cycle, the reaction media captures the portion of the constituent gas from the filtered portion of the air supply; wherein during a third segment of the processing cycle, the portion of the air supply exiting the reaction media is returned back to the external area of the housing; and upon termination of the processing cycle, the controller receives outputs from the set of sensors to calculate one or more of an amount of the constituent gas captured by the reaction media, a gas flow rate, and a gas concentration difference.

14. The system of claim 13, further comprising: during the second processing cycle, the controller triggers the fan to draw a next portion of the air supply into the housing inlet.

15. A method for processing an air supply comprising: receiving, at a housing inlet arranged on a housing, a portion of the air supply of an external area of the housing; filtering particular matter or a particular gas from the portion of the air supply entering the housing inlet by a filter arranged within the housing at the housing inlet; capturing a portion of a constituent gas from the filtered portion of the air supply by a reaction media arranged within the housing; and returning the portion of the air supply exiting the reaction media back to the external area of the housing via a housing outlet arranged on the housing.

16. The method of claim 15, further comprising: influencing the portion of the air supply from the housing inlet, through the reaction media, and through the housing outlet by a fan arranged within the housing.

17. The method of claim 15, further comprising arranging the filter in series with the reaction media.

18. The method of claim 15, further comprising: determining a first concentration of the constituent gas from the portion of the air supply entering the housing inlet; and determining a second concentration of the constituent gas from the portion of the air supply exiting the reaction media.

19. The method of claim 18, further comprising: estimating a constituent gas absorption rate by the reaction media based on a difference between the first concentration of the constituent gas and the second concentration of the constituent gas.

20. The method of claim 15, further comprising: determining a concentration of the constituent gas from the portion of the air supply entering the housing inlet; and based on the concentration of the constituent gas being above a threshold amount, causing a fan to influence the portion of the air supply moving through the housing at an increased speed.
