

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276660

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

YAMAMOTO; Akiyoshi et al.

CRASH BOX

Abstract

A crash box comprising a hollow tubular body including a pair of half bodies, a pair of front mounting plates to be mounted to cover front end portions of the pair of half bodies, and a pair of rear mounting plates to be mounted to cover rear end portions of the pair of half bodies. The pair of front mounting plates and the pair of rear mounting plates are mounted on the pair of half bodies in a first direction by spot welding or riveting, pairs of flange portions formed by bending the pair of half bodies outward from both side edges on the opening sides of the pair of half bodies are superposed on each other, and mounted on each other in a second direction by spot welding, or riveting or bolting, and the first direction and the second direction are the same direction.

Inventors: YAMAMOTO; Akiyoshi (Aichi, JP), RYUTAKI; Kozo (Aichi, JP)

Applicant: TOYODA IRON WORKS CO., LTD. (Aichi, JP)

Family ID: 86612393

Appl. No.: 18/689464

Filed (or PCT Filed): December 02, 2022

PCT No.: PCT/JP2022/044552

Foreign Application Priority Data

JP 2021-197059

Dec. 03, 2021

Publication Classification

Int. Cl.: B60R19/34 (20060101); B21J15/02 (20060101); B23K11/11 (20060101)

U.S. Cl.:

CPC B60R19/34 (20130101); B21J15/02 (20130101); B23K11/115 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to a crash box.

BACKGROUND ART

[0002] A bumper reinforcement of a vehicle is mounted on a side member extending in a front-and-rear direction in the lower part of the vehicle body. The portion where the bumper reinforcement is mounted is often provided with a crash box designed to absorb impact energy at the time of a collision. For example, a crash box described in JP-A-2014-238103 includes a hollow tubular body placed along the vehicle front-and-rear direction, and a mounting plate fixed by, for example, arc welding to both axial end portions of the tubular body. The tubular body includes a pair of half bodies, and the half bodies are fixed by, for example, spot welding or arc welding with flange portions thereof superposed.

SUMMARY OF INVENTION

[0003] When the tubular body and the mounting plates of the crash box described in the above publication are formed of alloyed hot-dip galvanized steel sheets, zinc fumes are generated from the surfaces when the tubular body and the mounting plates are fixed to each other by arc welding. Moreover, in butt arc welding for the tubular body and the mounting plates, a blowhole may be generated in a weld bead portion. As a result, a zinc fume removal process and a reworking of the bead portion are required, and the manufacturing cost increases. Moreover, when the tubular body is mounted by butt arc welding on the mounting plates, burn-through easily occurs in a thin portion, and it is difficult to achieve thinning.

[0004] One aspect of the disclosed technology is a crash box provided between a bumper reinforcement extending in a vehicle width direction and a side member extending in a vehicle front-and-rear direction to absorb impact energy at the time of a collision, the crash box including: a hollow tubular body placed along the vehicle front-and-rear direction, the tubular body including a pair of half bodies of approximately hat shape in cross section, the pair of half bodies each having a bottom surface portion, vertical wall portions extending from the bottom surface portion, and flange portions extending from the vertical wall portions; a pair of front mounting plates placed respectively at front end portions of the pair of half bodies and mounted on one of the bumper reinforcement and the side member; and a pair of rear mounting plates placed respectively at rear end portions of the pair of half bodies and mounted on the other of the bumper reinforcement and the side member, in which the pair of front mounting plates and the pair of rear mounting plates are mounted on the pair of half bodies in a first direction by spot welding or riveting, the flange portions are superposed on each other and mounted in a second direction by spot welding or riveting, or bolting, and the first direction and the second direction are the same direction.

[0005] In some embodiments, each of the front mounting plates of the pair and the rear mounting plates of the pair includes a plurality of bent pieces formed by bending parts thereof inward, the pair of front mounting plates and the pair of rear mounting plates are joined by spot welding the pluralities of bent pieces to outer surfaces of the bottom surface portions of the corresponding half bodies, and are mounted in such a manner as to cover the front and rear end portions of the pair of half bodies, and the pair of half bodies is joined together by spot welding with pairs of the flange portions superposed on each other.

[0006] Another aspect of the disclosed technology is a method for manufacturing the crash box, including the steps of: joining the pluralities of bent pieces of one of the front mounting plates and one of the rear mounting plates by spot welding to the outer surface of the bottom surface portion at both side edge portions of the corresponding one of the half bodies; joining the pluralities of bent pieces of the other front mounting plate and the other rear mounting plate by spot welding to the

outer surface of the bottom surface portion at both side edge portions of the corresponding other half body; superposing the pairs of the flange portions on each other in such a manner that an inner surface of the bottom surface portion of the one of the half bodies faces an inner surface of the bottom surface portion of the other half body; and joining the pairs of the superposed flange portions by spot welding.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0007] FIG. 1 is a plan view illustrating a crash box disposed between a side member and a bumper reinforcement according to one embodiment.

[0008] FIG. 2 is a perspective view of the crash box illustrated in FIG. 1.

[0009] FIG. 3 is an exploded perspective view of the crash box illustrated in FIG. 1.

[0010] FIG. 4 is a cross-sectional view of the crash box illustrated in FIG. 1, taken along line IV-IV.

[0011] FIG. 5 is a cross-sectional view of the crash box illustrated in FIG. 1, taken along line V-V.

[0012] FIG. 6 is a cross-sectional view of the crash box illustrated in FIG. 1, taken along line VI-VI.

[0013] FIG. 7 is a perspective view illustrating a crash box according to another embodiment,

[0014] FIG. 8 is an exploded perspective view of the crash box illustrated in FIG. 7.

[0015] FIG. 9 is a cross-sectional view of the crash box illustrated in FIG. 7, taken along line IX-IX.

[0016] FIG. 10 is a plan view illustrating a crash box according to still another embodiment.

[0017] FIG. 11 is a perspective view of the crash box illustrated in FIG. 10.

[0018] FIG. 12 is an exploded perspective view of the crash box illustrated in FIG. 10.

[0019] FIG. 13 is a cross-sectional view of the crash box illustrated in FIG. 10, taken along line XIII-XIII.

[0020] FIG. 14 is a cross-sectional view of the crash box illustrated in FIG. 10, taken along line XIV-XIV.

[0021] FIG. 15 is a cross-sectional view of the crash box illustrated in FIG. 10, taken along line XV-XV.

[0022] FIG. 16 is a cross-sectional view of a crash box according to yet another embodiment.

[0023] FIG. 17 is a plan view illustrating a crash box according to still yet another embodiment,

[0024] FIG. 18 is a perspective view of the crash box illustrated in FIG. 17 as viewed from the front side.

[0025] FIG. 19 is a perspective view of the crash box illustrated in FIG. 17 as viewed from the rear side.

[0026] FIG. 20 is an exploded perspective view of the crash box illustrated in FIG. 17.

[0027] FIG. 21 is a cross-sectional view of the crash box illustrated in FIG. 17, taken along line XXI-XXI.

[0028] FIG. 22 is a cross-sectional view of the crash box illustrated in FIG. 17, taken along line XXII-XXII.

[0029] FIG. 23 is a cross-sectional view of the crash box illustrated in FIG. 17, taken along line XXIII-XXIII.

[0030] FIG. 24 is a perspective view of a crash box according to still another embodiment as viewed from the front side.

[0031] FIG. 25 is an exploded perspective view of the crash box illustrated in FIG. 24.

[0032] FIG. 26 is a cross-sectional view of a crash box according to yet another embodiment.

DESCRIPTION OF EMBODIMENTS

Crash Box

[0033] Various embodiments of the present invention are described in detail hereinafter with reference to the drawings. FIGS. **1** to **6** illustrate a crash box **1** according to one embodiment. Note that an arrow FR provided as appropriate in each drawing indicates forward relative to a vehicle, and an arrow UP indicates upward. Furthermore, an arrow IN indicates inward in a vehicle width direction. In the following description, descriptions regarding the directions may be based on these directions.

[0034] As illustrated in FIG. **1**, the crash box **1** is provided between an end portion of a bumper reinforcement **2** extending in the vehicle width direction and a side member **3L** extending in a vehicle front-and-rear direction. The bumper reinforcement **2** is mounted on the side member **3L** and, at the time of a collision, the crash box **1** is compressed and deformed in the vehicle front-and-rear direction to absorb the impact energy. Although FIG. **1** illustrates the left end portion of the bumper reinforcement **2** and the left crash box **1**, the right end portion can also be configured symmetrically with respect to the left end portion. Note that although the bumper reinforcement **2** and the crash box **1** are described as members provided at the front end of the vehicle, various features described below are also applicable to a case in which these members are provided at the rear end of the vehicle as another embodiment.

Main Body Portion of Crash Box

[0035] As illustrated in FIGS. **1** and **2**, the crash box **1** has a main body portion **11** formed as a hollow tubular body with its axis oriented in the vehicle front-and-rear direction. The main body portion **11** can be formed by, for example, combining upper and lower half bodies **11A** and **11B** having an approximately hat shape in cross section. Moreover, the crash box **1** includes a pair of front mounting plates **12A** and **12B** that are joined by spot welding, while in contact with the front (bumper-side) end portions of the half bodies **11A** and **11B**, in such a manner as to cover the front end portions. Moreover, the crash box **1** includes a pair of rear mounting plates **13A** and **13B** that are joined by spot welding, while in contact with the rear (vehicle body-side) end portions of the half bodies **11A** and **11B**, in such a manner as to cover the rear end portions.

[0036] The crash box **1** is disposed between the bumper reinforcement **2** and the side member **3L** in a position in which the axis of the main body portion **11** forming the tubular body is substantially parallel to the vehicle front-and-rear direction, and is fixed integrally with the bumper reinforcement **2** and the side member **3L** by unillustrated joining means such as bolts via the pair of front mounting plates **12A** and **12B** and the pair of rear mounting plates **13A** and **13B**. Here, in FIGS. **1** and **2**, black dots indicate joint locations by spot welding. Note that joining may be performed by not limited to spot welding but also another welding method such as laser welding.

[0037] The half bodies **11A** and **11B** can be formed into approximately hat shapes in cross section that are generally symmetric with respect to each other in an up-and-down direction, by press forming of steel sheets. For example, alloyed hot-dip galvanized steel sheets or hot-dip galvanized steel sheets can be used. The thickness can be approximately 1.0 mm to 1.6 mm, and the tensile strength can be approximately 590 MPa. As illustrated in FIG. **3**, the half bodies **11A** and **11B** each have a bottom surface portion **21C**, a pair of opposing vertical wall portions **21A** and **21B** extending from the edges of the bottom surface portion **21C**, and a pair of flange portions **21D** and **21E** extending outward, substantially parallel to the bottom surface portion **21C**, from the edges of the pair of vertical wall portions **21A** and **21B**, that is, the edges on the opening side of the hat shape.

[0038] Moreover, as illustrated in FIGS. **1** to **3**, the rear edge portions of the half bodies **11A** and **11B** are recessed forward on the outer side in the vehicle width direction. Moreover, the width in the front-and-rear direction is narrower on the outer side in the vehicle width direction than on the inner side in the vehicle width direction, and the half bodies **11A** and **11B** each have a trapezoidal shape in plan view. Each of the half bodies **11A** and **11B** is formed, at the central portion in the vehicle width direction of the bottom surface portion **21C**, with a recessed portion **21F** that has a

width of approximately half the total width in the vehicle width direction and is recessed into the opening of the hat shape (with a depth of, for example, approximately 10 mm to 20 mm) from a position slightly rearward of the front end portion relative to the vehicle to the rear end.

Front Mounting Plates

[0039] The front mounting plates **12A** and **12B** are formed in approximately horizontal rectangular flat sheets in front view that are symmetric with respect to each other in the up-and-down direction, by press forming of the steel sheets. For example, alloyed hot-dip galvanized steel sheets or hot-dip galvanized steel sheets can be used. The thickness can be approximately 2.0 mm to 2.6 mm, and the tensile strength can be approximately 440 MPa. As illustrated in FIGS. **2** to **4** and **6**, the side edges on the outer side in the vehicle width direction of the front mounting plates **12A** and **12B** extend to the vicinities of the distal ends of the flange portions **21E** on the outer side in the vehicle width direction of the half bodies **11A** and **11B**. The side edges on the inner side in the vehicle width direction of the front mounting plates **12A** and **12B** extend (for example, approximately 30 mm to 40 mm) beyond the distal ends of the flange portions **21D** on the inner side in the vehicle width direction of the half bodies **11A** and **11B**.

[0040] The front mounting plates **12A** and **12B** extend (for example, approximately 10 mm to 20 mm) beyond the bottom surface portions **21C** of their corresponding half bodies **11A** and **11B** in the up-and-down direction. Each of the front mounting plates **12A** and **12B** is provided with bent pieces **23A** and **23B** having an approximately L shape in side view at positions of the bottom surface portion **21C** of its corresponding half body **11A** or **11B**, and the bent pieces **23A** and **23B** are spot-welded to the outer surface of the bottom surface portion **21C**. The heights of protrusion of the bent pieces **23A** and **23B** from the front mounting plates **12A** and **12B** can be set to be substantially the same.

[0041] The bent pieces **23A** and **23B** of the each of the front mounting plates **12A** and **12B** are formed in an approximately L shape in side view by punching U-shaped grooves in the each of the front mounting plates **12A** and **12B** and bending portions surrounded by the grooves inward (toward the rear of the vehicle) at an approximately right angle at the positions of the bottom surface portion **21C** of its corresponding half body **11A** or **11B**.

[0042] The front mounting plates **12A** and **12B** are provided, at their side edge portions on opposite sides, each with a narrow reinforcement rib **25** bent inward (toward the rear of the vehicle) at an approximately right angle. The front mounting plates **12A** and **12B** are each provided, at their adjacent side edge portions, with a wide reinforcement rib **26** bent inward (toward the rear of the vehicle) at an approximately right angle, all the way from the side edge on the outer side in the vehicle width direction (the left side in FIG. **4**) of the bent piece **23A** to the side edge on the inner side in the vehicle width direction (the right side in FIG. **4**) of the bent piece **23B**. The width in the vehicle front-and-rear direction of the reinforcement ribs **26** can be set to a substantially constant width that is substantially the same dimension as the height of protrusion of the bent pieces **23A** and **23B** from the front mounting plates **12A** and **12B**.

[0043] As illustrated in FIG. **4**, the height of the each of the front mounting plates **12A** and **12B** from the inner surfaces in the vehicle up-and-down direction of the bent pieces **23A** and **23B** to the outer surface in the vehicle up-and-down direction of the reinforcement rib **26** is formed to be substantially the same as, or slightly less than, the height of the each of the half bodies **11A** and **11B** from the outer surface in the vehicle up-and-down direction of the bottom surface portion **21C** to the outer surfaces in the vehicle up-and-down direction of the flange portions **21D** and **21E**.

[0044] The each of the front mounting plates **12A** and **12B** is formed with through-holes **27** at a position outward in the vehicle width direction relative to the center in the vehicle width direction and at a position of an inner edge portion in the vehicle width direction. An unillustrated nut is mounted on the rear end portion of each of the through-holes **27** by joining such as arc welding, spot welding, or laser welding, and is integrally assembled by bolting to the bumper reinforcement

Rear Mounting Plates

[0045] As illustrated in FIGS. 2, 3, and 5, the rear mounting plates **13A** and **13B** are formed in approximately horizontal rectangular shapes in front view that are symmetric with respect to each other in the up-and-down direction, by press forming of steel sheets. For example, alloyed hot-dip galvanized steel sheets or hot-dip galvanized steel sheets can be used. The thickness can be approximately 2.0 mm to 2.6 mm, and the tensile strength can be approximately 440 MPa. The rear mounting plates **13A** and **13B** can have substantially the same thickness as the front mounting plates **12A** and **12B**. Specifically, as illustrated in FIGS. 1 to 3, the rear mounting plates **13A** and **13B** are bent along the rear ends of their corresponding half bodies **11A** and **11B**, and formed in a stepped shape.

[0046] The rear mounting plates **13A** and **13B** extend to substantially the central portions of the flange portions **21D** and **21E** of the half bodies **11A** and **11B** in the vehicle width direction. The rear mounting plates **13A** and **13B** extend beyond the main body portion **11** in the up-and-down direction. For example, the width in the up-and-down direction of the rear mounting plates **13A** and **13B** can be approximately twice the height from the flange portions **21D** and **21E** to the bottom surface portions **21C** of the corresponding half bodies **11A** and **11B**. The upper edge on the outer side in the vehicle width direction of the upper rear mounting plate **13A** is inclined outward and obliquely downward.

[0047] Each of the rear mounting plates **13A** and **13B** is provided with two approximately L-shaped bent pieces **31A** and **31B** at positions of the bottom surface portion **21C** of its corresponding half body **11A** or **11B**, and the bent pieces **31A** and **31B** are spot-welded to the outer surface of the bottom surface portion **21C**. The each of the rear mounting plates **13A** and **13B** is provided with an approximately L-shaped bent piece **31C** at a position of the recessed portion **21F** of its corresponding half body **11A** or **11B**, and the bent piece **31C** is spot-welded to the outer surface of the recessed portion **21F**. The heights of protrusion of the bent pieces **31A** to **31C** from the rear mounting plates **13A** and **13B** can be set to be substantially the same.

[0048] The two outer bent pieces **31A** and **31B** of the each of the rear mounting plates **13A** and **13B** are formed in an approximately L shape in side view by punching U-shaped grooves in the each of the rear mounting plates **13A** and **13B** and bending portions surrounded by the grooves inward (toward the front of the vehicle) at a substantially right angle at the positions of the bottom surface portion **21C** of the each of the half bodies **11A** and **11B**.

[0049] The central bent piece **31C** of the each of the rear mounting plates **13A** and **13B** is similarly formed in an approximately L shape in side view by punching a U-shaped groove in the each of the rear mounting plates **13A** and **13B** and bending portions surrounded by the grooves inward (toward the front of the vehicle) at an approximately right angle at the position of the recessed portion **21F** of the corresponding half body **11A** or **11B**.

[0050] The rear mounting plates **13A** and **13B** are each provided, at their adjacent side edge portions, with a wide reinforcement rib **33** bent inward (toward the front of the vehicle) at an approximately right angle, all the way from the side edge on the outer side in the vehicle width direction (the right side in FIG. 5) of the bent piece **31A** to the side edge on the inner side in the vehicle width direction (the left side in FIG. 5) of the bent piece **31B**. The width in the vehicle front-and-rear direction of the reinforcement ribs **33** can be set to a substantially constant width that is substantially the same dimension as the height of protrusion of the bent pieces **31A** to **31C** from the rear mounting plates **13A** and **13B**.

[0051] As illustrated in FIG. 5, the height of the each of the rear mounting plates **13A** and **13B** from the bent pieces **31A** and **31B** to the reinforcement rib **33** is formed to be substantially the same as, or slightly less than, the height of the each of the half bodies **11A** and **11B** from the outer surface of the bottom surface portion **21C** in the vehicle up-and-down direction to the outer surfaces of the flange portions **21D** and **21E** in the vehicle up-and-down direction.

[0052] The each of the rear mounting plates **13A** and **13B** is formed with two through-holes **35**

aligned along the vehicle width direction between the bent piece **31B** and a side edge portion outward of the bent piece **31B**. An unillustrated bolt is inserted through each of the through-holes **35** from the front side of the vehicle, and is integrally assembled by bolting to the side member **3L**.

Assembly of Crash Box

[0053] An assembly procedure of the crash box **1** is described with reference to FIGS. **3** to **6**.

Firstly, the front mounting plate **12A** to be placed on the upper side is brought into contact with the front end portion of the corresponding half body **11A**, and the bent pieces **23A** and **23B** are brought into contact with the outer surface of the bottom surface portion **21C** of the half body **11A**.

Consequently, the side edge of the front mounting plate **12A** is located at a position corresponding to the side edge on the outer side in the vehicle width direction of the flange portion **21E** on the outer side in the vehicle width direction of the half body **11A**.

[0054] Subsequently, the rear mounting plate **13A** to be placed on the upper side is brought into contact with the rear end portion of the corresponding half body **11A**, and the two outer bent pieces **31A** and **31B** are brought into contact with the outer surface of the bottom surface portion **21C** of the half body **11A**. The central bent piece **31C** is brought into contact with the outer surface of the recessed portion **21F** formed in the bottom surface portion **21C**. Consequently, both side edges of the rear mounting plate **13A** are located at positions corresponding to substantially the central portions in the vehicle width direction of the flange portions **21D** and **21E** of the half body **11A**.

[0055] The bent pieces **23A** and **23B** of the front mounting plate **12A** are then joined by spot welding to the outer surface of the bottom surface portion **21C** of the corresponding half body **11A**. The bent pieces **31A** to **31C** of the rear mounting plate **13A** are joined by spot welding to the outer surfaces of the bottom surface portion **21C** and the recessed portion **21F** of the half body **11A**. Consequently, an upper side semifinished product **37** (refer to FIG. **6**) is assembled in which the front mounting plate **12A** and the rear mounting plate **13A** are welded in such a manner as to cover the front and rear end portions of the half body **11A**. Here, in FIGS. **4** to **6**, x marks indicate joint locations by spot welding.

[0056] Next, the half body **11B** to be placed on the lower side is placed in such a manner that the opening side of the hat shape faces downward. Then, the corresponding front mounting plate **12B** is brought into contact with the front end portion of the half body **11B**, and the bent pieces **23A** and **23B** are brought into contact with the outer surface of the bottom surface portion **210** of the half body **11B**. Consequently, the side edge on the outer side in the vehicle width direction of the front mounting plate **12B** is located at a position corresponding to the side edge on the outer side in the vehicle width direction of the flange portion **21E** on the outer side in the vehicle width direction of the half body **11B**.

[0057] Subsequently, the rear mounting plate **13B** to be placed on the lower side is brought into contact with the rear end portion of the half body **11B**, and the bent pieces **31A** and **31B** are brought into contact with the outer surface of the bottom surface portion **21C** of the half body **11B**. The bent piece **31C** of the rear mounting plate **13B** is brought into contact with the outer surface of the recessed portion **21F** formed in the bottom surface portion **21C**. Consequently, both side edges in the vehicle width direction of the rear mounting plate **13B** are located at positions corresponding to substantially the central portions in the vehicle width direction of the flange portions **21D** and **21E** of the half body **11B**.

[0058] Next, the bent pieces **23A** and **23B** of the front mounting plate **12B** are joined by spot welding to the outer surface of the bottom surface portion **21C** of the half body **11B**. The bent pieces **31A** to **31C** of the rear mounting plate **13B** are joined by spot welding to the outer surfaces of the bottom surface portion **21C** and the recessed portion **21F** of the half body **11B**.

Consequently, a lower side semifinished product **38** (refer to FIG. **6**) is assembled in which the front mounting plate **12B** and the rear mounting plate **13B** are welded in such a manner as to cover the front and rear end portions of the half body **11B**. Here, in FIGS. **4** to **6**, x marks indicate joint locations by spot welding.

[0059] After that, as illustrated in FIG. 3, the flange portions **21D** of the half bodies **11A** and **11B** are superposed on each other, and the flange portions **21E** of the half bodies **11A** and **11B** are superposed on each other, in such a manner that the inner surface of the bottom surface portion **21C** of the half body **11A** forming the upper side semifinished product **37** faces the inner surface of the bottom surface portion **21C** of the half body **11B** forming the lower side semifinished product **38**. As illustrated in FIGS. 1 to 5, each of the pair of superposed flange portions **21D** and the pair of superposed flange portions **21E** is then joined together by spot welding, in a plurality of places, for example, two places, in the vehicle front-and-rear direction. Consequently, as illustrated in FIG. 2, the crash box **1** is assembled. Here, in FIGS. 1 and 2, black dots indicate joint locations by spot welding. In FIGS. 4 and 5, x marks indicate joint locations by spot welding.

[0060] In the crash box **1** described above, the mounting direction in which the front mounting plates **12A** and **12B** and the rear mounting plates **13A** and **13B** are mounted by spot welding on the half bodies **11A** and **11B** is the same direction as the mounting direction in which the flange portions **21D** and **21E** of the half bodies **11A** and **11B** are superposed on each other and mounted by spot welding. As a result, the assembly time of the crash box **1** can be reduced, and the manufacturing cost can be reduced.

[0061] Moreover, arc welding is not required for the manufacture of the crash box **1** described above, and it is possible to avoid burn-through caused by arc welding in a thin portion. As a result, the front mounting plates **12A** and **12B**, the rear mounting plates **13A** and **13B**, and the half bodies **11A** and **11B**, which form the crash box **1**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, also when the front mounting plates **12A** and **12B**, the rear mounting plates **13A** and **13B**, and the half bodies **11A** and **11B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zinc fumes from being generated from the surface of the crash box **1**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost.

Joining of Flanges with Rivet Pins

[0062] As illustrated in FIGS. 7 to 9, as another embodiment, in a crash box **51**, it is also possible to join each of the pair of superposed flange portions **21D** and the pair of superposed flange portions **21E** of the half bodies **11A** and **11B** by a plurality of flange joining-purpose rivet pins **53**, instead of spot welding, in a plurality of places, for example, two places, in the vehicle front-and-rear direction.

[0063] Specifically, as illustrated in FIG. 8, the pair of flange portions **21D** and **21E** of each of a pair of the half bodies **11A** and **11B** is each formed with joining-purpose through-holes **55** through each of which a stepped portion **53B** of the rivet pin **53** is inserted, in a plurality of places, for example, two places, in the vehicle front-and-rear direction. Moreover, each of the rivet pins **53** includes a thin (for example, approximately 1 mm to 3 mm thick) disk portion **53A** and a pair of the stepped portions **53B** formed coaxially with a reduced outer diameter at both axial end portions of the disk portion **53A**.

[0064] The outer diameter of the disk portions **53A** is set to be greater than the inner diameter of the joining-purpose through-holes **55** (to be greater by, for example, approximately 2 mm to 7 mm than the inner diameter of the joining-purpose through-holes **55**). Moreover, the pairs of the stepped portions **53B** are formed with an outer diameter that allows the pairs of the stepped portions **53B** to be inserted through the joining-purpose through-holes **55**. Moreover, the length of the pairs of the stepped portions **53B** is set to be greater (by, for example, approximately 2 mm to 5 mm) than the plate thickness of the pairs of flange portions **21D** and **21E**. In other words, the stepped portions **53B** are set in such a manner as to protrude (for example, approximately 2 mm to 5 mm) from the joining-purpose through-holes **55** when the stepped portions **53B** are inserted through the joining-purpose through-holes **55** and the disk portions **53A** come into contact with the surfaces on the opening sides of the pairs of flange portions **21D** and **21E**.

Assembly of Crash Box

[0065] Next, an assembly procedure of the crash box **51** is described with reference to FIGS. **8** and **9**. As illustrated in FIGS. **8** and **9**, as in the assembly procedure of the crash box **1**, firstly, the front mounting plate **12A** to be placed on the upper side is brought into contact with the front end portion of the half body **11A**, and the bent pieces **23A** and **23B** are brought into contact with the outer surfaces of both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11A**. Moreover, the side edge on the outer side in the vehicle width direction of the front mounting plate **12A** is caused to face the side edge on the outer side in the vehicle width direction of the flange portion **21E** on the outer side in the vehicle width direction of the half body **11A**.

[0066] Subsequently, the rear mounting plate **13A** to be placed on the upper side is brought into contact with the rear end portion of the half body **11A**, and the bent pieces **31A** and **31B** are brought into contact with the outer surfaces of the both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11A**. Moreover, the bent piece **31C** of the rear mounting plate **13A** is brought into contact with the outer surface of the recessed portion **21F** formed in the bottom surface portion **21C**. Moreover, the both side edges in the vehicle width direction of the rear mounting plate **13A** are caused to face substantially the central portions in the vehicle width direction of the flange portions **21D** and **21E** of the half body **11A**.

[0067] The bent pieces **23A** and **23B** of the front mounting plate **12A** are then joined by spot welding to the outer surface of the bottom surface portion **21C** of the half body **11A**. Moreover, the bent pieces **31A** to **31C** of the rear mounting plate **13A** are joined by spot welding to the outer surfaces of the bottom surface portion **21C** and the recessed portion **21F** of the half body **11A**. Consequently, the semifinished product **37** (refer to FIG. **6**) is assembled in which the front mounting plate **12A** and the rear mounting plate **13A** are welded in such a manner as to cover the front and rear end portions of the half body **11A**. Here, in FIG. **9**, x marks indicate joint locations by spot welding.

[0068] Next, the half body **11B** to be placed on the lower side is placed in such a manner that the opening side faces downward. Then, the front mounting plate **12B** to be placed on the lower side is brought into contact with the front end portion of the half body **11B**, and the bent pieces **23A** and **23B** are brought into contact with the outer surfaces of both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11B**. Moreover, the side edge on the outer side in the vehicle width direction of the front mounting plate **12B** is caused to face the side edge on the outer side in the vehicle width direction of the flange portion **21E** on the outer side in the vehicle width direction of the half body **11B**.

[0069] Subsequently, the rear mounting plate **13B** to be placed on the lower side is brought into contact with the rear end portion of the half body **11B**, and the bent pieces **31A** and **31B** are brought into contact with the outer surfaces of the both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11B**. Moreover, the bent piece **31C** of the rear mounting plate **13B** is brought into contact with the outer surface of the recessed portion **21F** formed in the bottom surface portion **21C**. Moreover, the both side edges in the vehicle width direction of the rear mounting plate **13B** are caused to face substantially the central portions in the vehicle width direction of the flange portions **21D** and **21E** of the half body **11B**.

[0070] The bent pieces **23A** and **23B** of the front mounting plate **12B** are then joined by spot welding to the outer surface of the bottom surface portion **21C** of the half body **11B**. Moreover, the bent pieces **31A** to **31C** of the rear mounting plate **13B** are joined by spot welding to the outer surfaces of the bottom surface portion **21C** and the recessed portion **21F** of the half body **11B**. Consequently, the semifinished product **38** (refer to FIG. **6**) is assembled in which the front mounting plate **12B** and the rear mounting plate **13B** are welded in such a manner as to cover the front and rear end portions of the half body **11B**.

[0071] After that, as illustrated in FIG. **8**, the opening side of the half body **11B** forming the semifinished product **38** is placed in such a manner as to face upward, and one of the stepped

portions **53B** of the rivet pins **53** are inserted respectively through the joining-purpose through-holes **55** formed in the pair of flange portions **21D** and **21E** of the half body **11B**. With the opening side of the half body **11A** forming the semifinished product **37** facing downward, each of the pair of flange portions **21D** and the pair of flange portions **21E** of the half bodies **11A** and **11B** is then superposed on each other in such a manner that the others of the stepped portions **53B** of the rivet pins **53** are inserted respectively through the joining-purpose through-holes **55** formed in the pair of flange portions **21D** and **21E** of the half body **11A**.

[0072] Subsequently, as illustrated in FIGS. **7** and **9**, the pair of the stepped portions **53B** of each of the rivet pins **53** is riveted in the up-and-down direction by an unillustrated riveting apparatus, and the each of the pair of superposed flange portions **21D** and the pair of superposed flange portions **21E** is joined together in a plurality of places, for example, two places, in the vehicle front-and-rear direction. Consequently as illustrated in FIG. **7**, the crash box **51** is assembled. Here, in FIG. **7**, black dots indicate joint locations by spot welding. Moreover, in FIG. **9**, x marks indicate joint locations by spot welding.

[0073] The crash box **51** described above can be assembled in such a manner that the mounting direction in which the pair of front mounting plates **12A** and **12B** and the pair of rear mounting plates **13A** and **13B** are mounted by spot welding on the pair of the half bodies **11A** and **11B** is the same direction as the mounting direction in which the each of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of the half bodies **11A** and **11B** is superposed on each other and mounted by riveting the rivet pins **53**. As a result, the assembly time of the crash box **51** can be reduced, and the manufacturing cost can be reduced.

[0074] Moreover, arc welding is not required for the manufacture of the crash box **51**, and it is possible to ensure prevention of bum-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates **12A** and **12B**, the pair of rear mounting plates **13A** and **13B**, and the pair of the half bodies **11A** and **11B**, which form the crash box **51**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, when the pair of front mounting plates **12A** and **12B**, the pair of rear mounting plates **13A** and **13B**, and the pair of the half bodies **11A** and **11B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zinc fumes from being generated from the surface of the crash box **51**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost.

Joining of Flanges with Rivet Pins and Coupling of Bottom Surface Portions

[0075] As illustrated in FIGS. **10** and **11**, as another embodiment, it is also possible to connect the pair of front mounting plates **12A** and **12B**, the pair of rear mounting plates **13A** and **13B**, and the pair of the half bodies **11A** and **11B** with a plurality of bottom surface portion coupling-purpose rivet pins **65** and **66** and a plurality of flange joining-purpose rivet pins **63**, instead of spot welding.

[0076] Specifically, the pair of front mounting plates **12A** and **12B** is integrally connected by the bottom surface portion coupling-purpose rivet pins **65**, while in contact with the front end portions of the half bodies **11A** and **11B**, in such a manner as to cover the front end portions of the pair of the half bodies **11A** and **11B**. Moreover, the pair of rear mounting plates **13A** and **13B** is integrally connected by the bottom surface portion coupling-purpose rivet pins **65** and **66**, while in contact with the rear end portions of the half bodies **11A** and **11B**, in such a manner as to cover the rear end portions of the pair of the half bodies **11A** and **11B**. Moreover, the each of the pair of superposed flange portions **21D** and the pair of superposed flange portions **21E** of the half bodies **11A** and **11B** is joined together with the flange joining-purpose rivet pins **63** in a plurality of places, for example, two places, in the vehicle front-and-rear direction.

[0077] As illustrated in FIG. **12**, the pair of flange portions **21D** and **21E** of each of the pair of the half bodies **11A** and **11B** is each formed with joining-purpose through-holes **73** through each of which a stepped portion **63B** of the rivet pin **63** is inserted, in a plurality of places, for example, two places, in the vehicle front-and-rear direction. Moreover, each of the rivet pins **63** includes a

thin (for example, approximately 1 mm to 3 mm thick) disk portion **63A** and a pair of the stepped portions **63B** formed coaxially with a reduced outer diameter at both axial end portions of the disk portion **63A**.

[0078] The outer diameter of the disk portions **63A** is set to be greater than the inner diameter of the joining-purpose through-holes **73** (to be greater by, for example, approximately 2 mm to 7 mm than the inner diameter of the joining-purpose through-holes **73**). Moreover, the pairs of the stepped portions **63B** are formed with an outer diameter that allows the pairs of the stepped portions **63B** to be inserted through the joining-purpose through-holes **73**. Moreover, the length of the pairs of the stepped portions **63B** is set to be greater (by, for example, approximately 2 mm to 5 mm) than the plate thickness of the pairs of flange portions **21D** and **21E**. In other words, the stepped portions **63B** are set in such a manner as to protrude (for example, approximately 2 mm to 5 mm) from the joining-purpose through-holes **73** when the stepped portions **63B** are inserted through the joining-purpose through-holes **73** and the disk portions **63A** come into contact with the surfaces on the opening sides of the pairs of flange portions **21D** and **21E**.

[0079] As illustrated in FIGS. **12** and **13**, the front side edge portions of the bottom surface portions **21C** of the pair of the half bodies **11A** and **11B** are each formed with a pair of first riveting-purpose through-holes **68** through each of which a stepped portion **65B** formed at both ends of the rivet pin **65** can be inserted, at positions where the bent pieces **23A** and **23B** of each of the pair of front mounting plates **12A** and **12B** come into contact with the outer surface. Moreover, the bent pieces **23A** and **23B** of the each of the pair of front mounting plates **12A** and **12B** are formed with a pair of second riveting-purpose through-holes **69** through each of which the stepped portion **65B** formed at the both ends of the rivet pin **65** can be inserted, at positions facing the first riveting-purpose through-holes **68** formed in the front side edge portion of the bottom surface portion **21C** of each of the pair of the half bodies **11A** and **11B**.

[0080] The reinforcement rib **26** of the each of the pair of front mounting plates **12A** and **12B** is formed with a pair of support-purpose through-holes **71** through each of which a shaft portion **65A** of the rivet pin **65** can be inserted, at positions facing, in the up-and-down direction, the second riveting-purpose through-holes **69** formed in the bent pieces **23A** and **23B**.

[0081] As illustrated in FIG. **12**, each of the rivet pins **65** includes the shaft portion **65A** formed in a shaft shape that is long in the up-and-down direction, and a pair of the stepped portions **65B** formed coaxially with a reduced outer diameter at both axial end portions of the shaft portion **65A**. The outer diameter of the shaft portions **65A** is set to be greater than the inner diameter of the first riveting-purpose through-holes **68** formed in the bottom surface portions **21C** of the pair of the half bodies **11A** and **11B** (to be greater by, for example, approximately 2 mm to 7 mm than the inner diameter of the first riveting-purpose through-holes **68**). As illustrated in FIG. **13**, the length of the shaft portions **65A** is formed to be substantially equal to a distance between the bottom surface portions **21C** that face each other when the pairs of flange portions **21D** and **21E** superposed on each other of the pair of the half bodies **11A** and **11B** are joined by the plurality of rivet pins **63**.

[0082] The length of the pairs of the stepped portions **65B** is set to be greater (by, for example, approximately 2 mm to 5 mm) than the total thickness of the plate thickness of the bottom surface portions **21C** of the pair of the half bodies **11A** and **11B** and the plate thickness of the bent pieces **23A** and **23B** of the pair of front mounting plates **12A** and **12B**. In other words, the stepped portions **65B** are set in such a manner as to protrude (for example, approximately 2 mm to 5 mm) from the second riveting-purpose through-holes **69** when the stepped portions **65B** are inserted through the first riveting-purpose through-holes **68** and the second riveting-purpose through-holes **69** and the shaft portions **65A** come into contact with the inner surfaces of the bottom surface portions **21C**.

[0083] As illustrated in FIGS. **12** and **14**, the pair of the half bodies **11A** and **11B** are each formed, at the rear side edge portions of the bottom surface portions **21C**, with the pair of first riveting-purpose through-holes **68** through each of which the stepped portion **65B** formed at the both ends

of the rivet pin **65** can be inserted, at positions where the bent pieces **31A** and **31B** of each of the pair of rear mounting plates **13A** and **13B** come into contact with the outer surface. Moreover, the pair of the half bodies **11A** and **11B** are each formed, at the rear side edge portions of the recessed portions **21F**, with the first riveting-purpose through-hole **68** through which a stepped portion **66B** formed at both ends of the rivet pin **66** can be inserted, at a position where the bent piece **31C** of each of the pair of rear mounting plates **13A** and **13B** comes into contact with the outer surface. [0084] The bent pieces **31A** and **31B** of the each of the pair of rear mounting plates **13A** and **13B** are formed with the pair of second riveting-purpose through-holes **69** through each of which the stepped portion **65B** formed at the both ends of the rivet pin **65** can be inserted, at positions facing the first riveting-purpose through-holes **68** formed in the rear side edge portion of the bottom surface portion **21C** of the each of the pair of the half bodies **11A** and **11B**. Moreover, the bent piece **31C** of the each of the pair of rear mounting plates **13A** and **13B** is formed with the second riveting-purpose through-hole **69** through which the stepped portion **66B** formed at the both ends of the rivet pin **66** can be inserted, at a position facing the first riveting-purpose through-hole **68** formed in the rear side edge portion of the recessed portion **21F** of the each of the pair of the half bodies **11A** and **11B**.

[0085] The reinforcement rib **33** of the each of the pair of rear mounting plates **13A** and **13B** is formed with three support-purpose through-holes **71** through which the shaft portions **65A** and **66A** of the rivet pins **65** and **66** can be inserted, at positions facing, in the up-and-down direction, the second riveting-purpose through-holes **69** formed in the bent pieces **31A** to **31C**.

[0086] As illustrated in FIG. **12**, each of the rivet pins **66** includes the shaft portion **66A** formed in a shaft shape that is long in the up-and-down direction, and a pair of the stepped portions **66B** formed coaxially with a reduced outer diameter at both axial end portions of the shaft portion **66A**. The outer diameter of the shaft portions **66A** is set to be greater than the inner diameter of the first riveting-purpose through-holes **68** formed in the bottom surface portions **21C** of the pair of the half bodies **11A** and **11B** (to be greater by, for example, approximately 3 mm to 7 mm than the inner diameter of the first riveting-purpose through-holes **68**). For example, the outer diameter of the shaft portions **66A** is set to be substantially the same dimension as the outer diameter of the shaft portions **65A** of the rivet pins **65**.

[0087] As illustrated in FIG. **14**, the length of the shaft portions **66A** is formed to be substantially equal to a distance between the recessed portions **21F** that face each other when the pairs of flange portions **21D** and **21E** superposed on each other of the pair of the half bodies **11A** and **11B** are joined by the plurality of rivet pins **63**. Moreover, the length of the pairs of the stepped portions **66B** is set to be greater (by, for example, approximately 2 mm to 5 mm) than the total thickness of the plate thickness of the bottom surface portions **21C** of the pair of the half bodies **11A** and **11B** and the plate thickness of the bent pieces **31C** of the pair of rear mounting plates **13A** and **13B**.

[0088] For example, the length of the pairs of the stepped portions **66B** is set to be substantially equal to the length of the pairs of the stepped portions **65B** of the rivet pins **65**. In other words, the stepped portions **66B** are set in such a manner as to protrude (for example, approximately 2 mm to 5 mm) from the second riveting-purpose through-holes **69** when the stepped portions **66B** are inserted through the first riveting-purpose through-holes **68** and the second riveting-purpose through-holes **69** and the shaft portions **66A** come into contact with the inner surfaces of the recessed portions **21F**.

Assembly of Crash Box

[0089] Next, an assembly procedure of a crash box **61** is described with reference to FIGS. **12** to **15**. As illustrated in FIGS. **12** to **15**, firstly, the half body **11B** to be placed on the lower side is placed in such a manner that the opening side faces upward. Then, the front mounting plate **12B** to be placed on the lower side is brought into contact with the front end portion of the half body **11B**, and the bent pieces **23A** and **23B** are brought into contact with the outer surfaces of both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11B**. In

this state, the front mounting plate **12B** is then positioned, in the vehicle width direction, relative to the half body **11B** in such a manner that the first riveting-purpose through-holes **68** formed in the front side edge portion of the bottom surface portion **21C** of the half body **11B** communicate with the second riveting-purpose through-holes **69** formed respectively in the bent pieces **23A** and **23B**. [0090] Subsequently, the rear mounting plate **13B** to be placed on the lower side is brought into contact with the rear end portion of the half body **11B**, and the bent pieces **31A** and **31B** are brought into contact with the outer surfaces of the both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11B**. Moreover, the bent piece **31C** of the rear mounting plate **13B** is brought into contact with the outer surface of the recessed portion **21F** formed in the bottom surface portion **21C**. In this state, the rear mounting plate **13B** is then positioned, in the vehicle width direction, relative to the half body **11B** in such a manner that the first riveting-purpose through-holes **68** formed in the rear side edge portions of the bottom surface portion **21C** and the recessed portion **21F** of the half body **11B** communicate with the second riveting-purpose through-holes **69** formed respectively in the bent pieces **31A** to **31C**.

[0091] After that, one end sides of the shaft portions **65A** of the rivet pins **65** are inserted respectively through the pair of support-purpose through-holes **71** formed in the reinforcement rib **26** of the front mounting plate **12B**. The stepped portions **65B** formed at the lower end portions of the shaft portions **65A** are then inserted through the first riveting-purpose through-holes **68** formed in the bottom surface portion **21C** and the second riveting-purpose through-holes **69** formed respectively in the bent pieces **23A** and **23B**, and the lower ends of the shaft portions **65A** are brought into contact with the inner surface of the bottom surface portion **21C**.

[0092] Moreover, one end sides of the shaft portions **65A** of the rivet pins **65** are inserted respectively through the two support-purpose through-holes **71** formed in both end portions in the vehicle width direction of the reinforcement rib **33** of the rear mounting plate **13B**. The stepped portions **65B** formed at the lower end portions of the shaft portions **65A** are then inserted through the first riveting-purpose through-holes **68** formed in the bottom surface portion **21C** and the second riveting-purpose through-holes **69** formed respectively in the bent pieces **31A** and **31B**, and the lower ends of the shaft portions **65A** are brought into contact with the inner surface of the bottom surface portion **21C**.

[0093] Moreover, one end side of the shaft portion **66A** of the rivet pin **66** is inserted through the support-purpose through-hole **71** formed in substantially the central portion in the vehicle width direction of the reinforcement rib **33** of the rear mounting plate **13B**. The stepped portion **66B** formed at the lower end portion of the shaft portion **66A** is then inserted through the first riveting-purpose through-hole **68** formed in the recessed portion **21F** of the half body **11B** and the second riveting-purpose through-hole **69** formed in the bent piece **31C**, and the lower end of the shaft portion **66A** is brought into contact with the inner surface of the recessed portion **21F**.

[0094] Moreover, ones of the stepped portions **63B** of the rivet pins **63** are inserted respectively through the joining-purpose through-holes **73** formed in the pair of flange portions **21D** and **21E** of the half body **11B**, and the disk portions **63A** are brought into contact with the flange portions **21D** and **21E**.

[0095] Subsequently, the half body **11A** to be placed on the upper side is placed in such a manner that the opening side faces downward. Then, the front mounting plate **12A** to be placed on the upper side is brought into contact with the front end portion of the half body **11A**, and the bent pieces **23A** and **23B** are brought into contact with the outer surfaces of the both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11A**. In this state, the front mounting plate **12A** is then positioned, in the vehicle width direction, relative to the half body **11A** in such a manner that the first riveting-purpose through-holes **68** formed in the front side edge portion of the bottom surface portion **21C** of the half body **11A** communicate with the second riveting-purpose through-holes **69** formed respectively in the bent pieces **23A** and **23B**.

[0096] Then, the rear mounting plate **13A** to be placed on the upper side is brought into contact

with the rear end portion of the half body **11A**, and the bent pieces **31A** and **31B** are brought into contact with the outer surfaces of the both outer edge portions in the vehicle width direction of the bottom surface portion **21C** of the half body **11A**. Moreover, the bent piece **31C** of the rear mounting plate **13A** is brought into contact with the outer surface of the recessed portion **21F** formed in the bottom surface portion **21C**. In this state, the rear mounting plate **13A** is then positioned, in the vehicle width direction, relative to the half body **11A** in such a manner that the first riveting-purpose through-holes **68** formed in the rear side edge portions of the bottom surface portion **21C** and the recessed portion **21F** of the half body **11A** communicate with the second riveting-purpose through-holes **69** formed respectively in the bent pieces **31A** to **31C**

[0097] Subsequently, the half body **11A** with the opening side facing downward is placed directly above the half body **11B** in a state where the bent pieces **23A** and **23B** of the front mounting plate **12A** and the bent pieces **31A** to **31C** of the rear mounting plate **13A** are positioned on the outer surfaces of the bottom surface portion **21C** and the recessed portion **21F** relative to the half body **11A**. Then, the half body **11A** with the opening side facing downward, the front mounting plate **12A**, and the rear mounting plate **13A** are integrally lowered downward.

[0098] The upper end sides (the other end sides) of the shaft portions **65A** of the rivet pins **65** are then inserted respectively through the pair of support-purpose through-holes **71** formed in the reinforcement rib **26** of the front mounting plate **12A**, the stepped portions **65B** formed at the upper end portions (the other end portions) of the shaft portions **65A** are inserted through the first riveting-purpose through-holes **68** formed in the bottom surface portion **21C** and the second riveting-purpose through-holes **69** formed respectively in the bent pieces **23A** and **23B**, and the upper ends (the other ends) of the shaft portions **65A** are brought into contact with the inner surface of the bottom surface portion **21C**.

[0099] Moreover, at the same time, the upper end sides (the other end sides) of the shaft portions **65A** of the rivet pins **65** are inserted respectively through the two support-purpose through-holes **71** formed in the both end portions in the vehicle width direction of the reinforcement rib **33** of the rear mounting plate **13B**. The stepped portions **65B** formed at the upper end portions of the shaft portions **65A** are then inserted through the first riveting-purpose through-holes **68** formed in the bottom surface portion **21C** and the second riveting-purpose through-holes **69** formed respectively in the bent pieces **31A** and **31B**, and the upper ends of the shaft portions **65A** are brought into contact with the inner surface of the bottom surface portion **21C**.

[0100] Moreover, the upper end side (the other end side) of the shaft portion **66A** of the rivet pin **66** is inserted through the support-purpose through-hole **71** formed in substantially the central portion in the vehicle width direction of the reinforcement rib **33** of the rear mounting plate **13B**. The stepped portion **66B** formed at the upper end portion of the shaft portion **66A** is then inserted through the first riveting-purpose through-hole **68** formed in the recessed portion **21F** of the half body **11A** and the second riveting-purpose through-hole **69** formed in the bent piece **31C**, and the upper end of the shaft portion **66A** is brought into contact with the inner surface of the recessed portion **21F**.

[0101] Moreover, at the same time, the upper stepped portions **63B** of the rivet pins **63** placed in the pair of flange portions **21D** and **21E** of the half body **11B** are inserted through the joining-purpose through-holes **73** formed in the pair of flange portions **21D** and **21E** of the half body **11A**. The upper end portions of the disk portions **63A** of the rivet pins **63** are then brought into contact with the pair of flange portions **21D** and **21E** of the half body **11A**, and each of the pair of flange portions **21D** and the pair of flange portions **21E** of the half bodies **11A** and **11B** is superposed on each other.

[0102] After that, as illustrated in FIGS. **13** to **15**, the pair of the stepped portions **63B** formed at the both end portions of each of the rivet pins **63**, the pair of the stepped portions **65B** formed at the both end portions of each of the rivet pins **65**, and the pair of the stepped portions **66B** formed at the both end portions of each of the rivet pins **66** are riveted in the up-and-down direction by an

unillustrated riveting apparatus for the purpose of joining. Consequently, as illustrated in FIG. 11, the crash box **61** is assembled.

[0103] The crash box **61** described above can be assembled in such a manner that the mounting direction in which the pair of front mounting plates **12A** and **12B** and the pair of rear mounting plates **13A** and **13B** are mounted on the pair of the half bodies **11A** and **11B** and riveted with the rivet pins **65** and **66** is the same direction as the mounting direction in which the each of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of the half bodies **11A** and **11B** is superposed on each other and mounted and riveted with the rivet pins **63**. As a result, the assembly time of the crash box **61** can be reduced, and the manufacturing cost can be reduced.

[0104] Moreover, arc welding is not required for the manufacture of the crash box **61**, and it is possible to ensure prevention of bum-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates **12A** and **12B**, the pair of rear mounting plates **13A** and **13B**, and the pair of the half bodies **11A** and **11B**, which form the crash box **61**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, when the pair of front mounting plates **12A** and **12B**, the pair of rear mounting plates **13A** and **13B**, and the pair of the half bodies **11A** and **11B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zine fumes from being generated from the surface of the crash box **61**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost.

Joining of Flanges with Bolts

[0105] As illustrated in FIG. 16, as another embodiment, the pairs of flange portions **21D** and **21E** superposed on each other of the half bodies **11A** and **11B** may be joined together by bolting with hexagon socket head cap screws **83** inserted respectively through the joining-purpose through-holes **55**, and nuts **85**, instead of the flange joining-purpose rivet pins **53**.

[0106] Specifically, the opening side of the half body **11B** forming the semifinished product **38** (refer to FIG. 6) is placed in such a manner as to face upward. Each of the pair of flange portions **21D** and the pair of flange portions **21E** of the half bodies **11A** and **11B** is then superposed on each other in such a manner that the inner surface of the bottom surface portion **21C** of the half body **11A** forming the semifinished product **37** (refer to FIG. 6) faces the inner surface of the bottom surface portion **21C** of the half body **11B** forming the semifinished product **38**.

[0107] The hexagon socket head cap screws **83** are inserted from above respectively through the communicating joining-purpose through-holes **55** of the pairs of flange portions **21D** and **21E** superposed on each other of the half bodies **11A** and **11B**, and tightened with the nuts **85** to join the pairs of superposed flange portions **21D** and **21E**. Consequently, a crash box **81** is assembled.

[0108] The crash box **81** described above can be assembled in such a manner that the mounting direction in which the pair of front mounting plates **12A** and **12B** and the pair of rear mounting plates **13A** and **13B** are mounted by spot welding on the pair of the half bodies **11A** and **11B** is the same direction as the mounting direction in which the each of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of the half bodies **11A** and **11B** is superposed on each other and mounted by bolting with the hexagon socket head cap screws **83** and the nuts **85**. As a result, the assembly time of the crash box **81** can be reduced, and the manufacturing cost can be reduced.

[0109] Moreover, arc welding is not required for the manufacture of the crash box **81**, and it is possible to ensure prevention of burn-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates **12A** and **12B**, the pair of rear mounting plates **13A** and **13B**, and the pair of the half bodies **11A** and **11B**, which form the crash box **81**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, when the pair of front mounting plates **12A** and **12B**, the pair of rear mounting plates **13A** and **13B**, and the pair of the half bodies **11A** and **11B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zine fumes from being generated from the surface

of the crash box **81**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost.

Crash Box with Lashing Nut

[0110] FIGS. **17** to **23** illustrate a crash box **91** according to another embodiment. As illustrated in FIGS. **17** to **19**, the crash box **91** includes a main body portion **92** formed as a hollow tubular body placed with its axis oriented in the vehicle front-and-rear direction, and the main body portion **92** includes a pair of half bodies **92A** and **92B** having an approximately hat shape in cross section. The pair of half bodies **92A** and **92B** is integrally connected together by a pair of the bottom surface portion coupling-purpose rivet pins **65** (refer to FIG. **12**). Each of the pair of superposed flange portions **21D** and the pair of superposed flange portions **21E** of the half bodies **92A** and **92B** is joined together by the flange joining-purpose rivet pins **63** (refer to FIG. **12**) in a plurality of places, for example, two places, in the vehicle front-and-rear direction.

[0111] The crash box **91** includes a pair of front mounting plates **93A** and **93B** that are mounted by spot welding, while in contact with the front end portions of the pair of half bodies **92A** and **92B**, in such a manner as to cover the front end portions. Moreover, the crash box **91** includes a pair of rear mounting plates **95A** and **95B** that are mounted by spot welding in such a manner as to protrude from the rear side edge portions of the pair of half bodies **92A** and **92B** in directions away from each other.

[0112] The crash box **91** is disposed between the bumper reinforcement **2** and the side member **3L** in a position in which the axis of the main body portion **92** forming the tubular body is substantially parallel to the vehicle front-and-rear direction, and is fixed integrally with the bumper reinforcement **2** and the side member **3L** by, for example, unillustrated bolts via the pair of front mounting plates **93A** and **93B** and the pair of rear mounting plates **95A** and **95B**. Here, in FIGS. **17** to **19**, black dots indicate joint locations by spot welding. Note that joining may be performed by not limited to spot welding but also welding such as laser welding.

[0113] The pair of half bodies **92A** and **92B** has substantially the same configuration as the half bodies **11A** and **11B** in FIGS. **1** to **6**. The half bodies **92A** and **92B** are formed in approximately hat shapes in cross section that are symmetric with respect to each other in the up-and-down direction, by press forming of steel sheets. For example, alloyed hot-dip galvanized steel sheets or hot-dip galvanized steel sheets can be used. The thickness can be approximately 1.0 mm to 1.6 mm, and the tensile strength can be approximately 590 MPa.

[0114] Specifically, as illustrated in FIG. **20**, the pair of half bodies **92A** and **92B** each has the bottom surface portion **21C** (refer to FIG. **17**) having an approximately trapezoidal shape in plan view, the pair of opposing vertical wall portions **21A** and **21B** extending from the edges of the bottom surface portion **21C**, and the pair of flange portions **21D** and **21E** extending substantially parallel to the bottom surface portion **21C**, from the edges of the pair of vertical wall portions **21A** and **21B**, that is, the edges on the opening side of the hat shape.

[0115] However, the central portion in the vehicle width direction of the bottom surface portion **210** of each of the pair of half bodies **92A** and **92B** is formed with a recessed portion **21G** that has a width of approximately half the total width in the vehicle width direction and is recessed toward the opening side (with a depth of, for example, approximately 10 mm to 20 mm) along the entire width in the vehicle front-and-rear direction. As illustrated in FIGS. **17** to **19**, the rear edge portion of the each of the pair of half bodies **92A** and **92B** from substantially the central portion to the outer portion in the vehicle width direction is recessed toward the front of the vehicle. Therefore, the width in the vehicle front-and-rear direction from substantially the central portion to the outer portion in the vehicle width direction is slightly narrower than the width in the vehicle front-and-rear direction from substantially the central portion to the inner portion in the vehicle width direction.

[0116] As illustrated in FIG. **20**, each of the pairs of flange portions **21D** and **21E** of the pair of half bodies **92A** and **92B** is each formed with the joining-purpose through-holes **73** through each of

which the stepped portion **63B** of the rivet pin **63** is inserted, in a plurality of places, for example, two places, in the vehicle front-and-rear direction. Each of the rivet pins **63** includes the thin (for example, approximately 1 mm to 3 mm thick) disk portion **63A** and the pair of the stepped portions **63B** formed coaxially with a reduced outer diameter at the both axial end portions of the disk portion **63A**.

[0117] The outer diameter of the disk portions **63A** is set to be greater than the inner diameter of the joining-purpose through-holes **73** (to be greater by, for example, approximately 2 mm to 7 mm than the inner diameter of the joining-purpose through-holes **73**). The pairs of the stepped portions **63B** are formed with an outer diameter that allows the pairs of the stepped portions **63B** to be inserted through the joining-purpose through-holes **73**. The length of the pairs of the stepped portions **63B** is set to be greater (by, for example, approximately 2 mm to 5 mm) than the plate thickness of the pairs of flange portions **21D** and **21E**. In other words, the stepped portions **63B** are set in such a manner as to protrude (for example, approximately 2 mm to 5 mm) from the joining-purpose through-holes **73** when the stepped portions **63B** are inserted through the joining-purpose through-holes **73** and the disk portions **63A** come into contact with the surfaces on the opening sides of the pairs of flange portions **21D** and **21E**.

[0118] The pair of front mounting plates **93A** and **93B** is formed in approximately horizontal rectangular flat sheets in front view that are symmetric with respect to each other in the up-and-down direction, by press forming of steel sheets. For example, alloyed hot-dip galvanized steel sheets or hot-dip galvanized steel sheets can be used. The thickness can be approximately 2.0 mm to 2.6 mm, and the tensile strength can be approximately 440 MPa. As illustrated in FIGS. **18** to **21** and **23**, the side edges on the outer side in the vehicle width direction of the pair of front mounting plates **93A** and **93B** face the vertical wall portions **21B** on the outer side in the vehicle width direction of the pair of half bodies **92A** and **92B**. The side edges on the inner side in the vehicle width direction of the front mounting plates **93A** and **93B** extend inward in the vehicle width direction and longer (by, for example, approximately 40 mm to 50 mm) than each of the vertical wall portions **21A** on the inner side in the vehicle width direction of the half bodies **92A** and **92B**.

[0119] The upper edges of the pair of front mounting plates **93A** and **93B** are located at substantially the same height as the height from the pairs of flange portions **21D** and **21E** to the bottom surface portions **21C** of the pair of opposing half bodies **92A** and **92B**. The portions, which face the recessed portions **21G** of the pair of half bodies **92A** and **92B**, of the side edge portions on the opposite sides of the pair of front mounting plates **93A** and **93B** are recessed in directions closer to each other along the front edge portions of the recessed portions **21G**.

[0120] The edge portions on the outer side in the vehicle width direction of the pair of front mounting plates **93A** and **93B** are each provided with a bent piece **97A** that has an L shape in side view and is bent inward (toward the rear of the vehicle) at an approximately right angle. The bent pieces **97A** come into contact with the inner side surfaces of the vertical wall portions **21B** of the pair of half bodies **92A** and **92B**. The side edge portions on the opposite sides of the pair of front mounting plates **93A** and **93B** are each provided, at a position facing substantially the central portion in the vehicle width direction of the recessed portion **21G** of each of the pair of half bodies **92A** and **92B**, with a welding-purpose mounting piece **97B** (a spot welding-purpose mounting piece) that has an approximately L shape in side view and is bent rearward at an approximately right angle. The welding-purpose mounting pieces **97B** are joined by spot welding to the outer surfaces of the recessed portions **21G**.

[0121] The side edge portions on the opposite sides of the pair of front mounting plates **93A** and **93B** are each provided with a pair of riveting-purpose mounting pieces **97C** and **97D** that have an approximately L shape in side view and are bent rearward at an approximately right angle, in two places of positions facing the bottom surface portions **21C** on both sides in the vehicle width direction of the pair of half bodies **92A** and **92B**. The pairs of riveting-purpose mounting pieces **97C** and **97D** are joined to the outer surfaces of the bottom surface portions **21C** with the rivet pins

65.

[0122] As illustrated in FIGS. **20** and **21**, the front side edge portions of the bottom surface portions **21C** of the pair of half bodies **92A** and **92B** are each formed with a pair of third riveting-purpose through-holes **98** through each of which the stepped portion **65B** formed at both ends of the rivet pin **65** can be inserted, at positions where the riveting-purpose mounting pieces **97C** and **97D** of each of the pair of front mounting plates **93A** and **93B** come into contact with the outer surface. The riveting-purpose mounting pieces **97C** and **97D** of the each of the pair of front mounting plates **93A** and **93B** are formed with a pair of fourth riveting-purpose through-holes **99** through each of which the stepped portion **65B** formed at the both ends of the rivet pin **65** can be inserted, at positions facing the third riveting-purpose through-holes **98** formed in the front side edge portion of the bottom surface portion **21C** of the each of the pair of half bodies **92A** and **92B**.

[0123] As illustrated in FIG. **20**, each of the rivet pins **65** includes the shaft portion **65A** formed in a shaft shape that is long in the up-and-down direction, and the pair of the stepped portions **65B** formed coaxially with the reduced outer diameter at both axial end portions of the shaft portion **65A**. The outer diameter of the shaft portions **65A** is set to be greater than the inner diameter of the third riveting-purpose through-holes **98** formed in the bottom surface portions **21C** of the pair of half bodies **92A** and **92B** (to be greater by, for example, approximately 2 mm to 7 mm than the inner diameter of the third riveting-purpose through-holes **98**). As illustrated in FIG. **21**, the length of the shaft portions **65A** is formed to be substantially equal to a distance between the bottom surface portions **21C** that face each other when the pairs of flange portions **21D** and **21E** superposed on each other of the pair of half bodies **92A** and **92B** are joined with the plurality of rivet pins **63**.

[0124] The length of the pairs of the stepped portions **65B** is set to be greater (by, for example, approximately 2 mm to 5 mm) than the total thickness of the plate thickness of the bottom surface portions **21C** of the pair of half bodies **92A** and **92B** and the plate thickness of the riveting-purpose mounting pieces **97C** and **97D** of the pair of front mounting plates **93A** and **93B**. In other words, the stepped portions **65B** are set in such a manner as to protrude (for example, approximately 2 mm to 5 mm) from the fourth riveting-purpose through-holes **99** when the stepped portions **65B** are inserted through the third riveting-purpose through-holes **98** and the fourth riveting-purpose through-holes **99** and the shaft portions **65A** come into contact with the inner surfaces of the bottom surface portions **21C**.

[0125] As illustrated in FIGS. **18** to **20**, the pair of front mounting plates **93A** and **93B** is each formed with through-holes **100** through each of which an unillustrated bolt can be inserted, at a position outward of the center in the vehicle width direction and at a position of the edge portion inward of the center in the vehicle width direction. Nuts **101** into each of which the unillustrated bolt inserted through the through-hole **100** is screwed are mounted by joining such as arc welding, spot welding, or laser welding on the rear end portions of the through-holes **100** formed in the edge portions on the inner side in the vehicle width direction of the pair of front mounting plates **93A** and **93B**.

Lashing Nut

[0126] As illustrated in FIGS. **17** and **18**, the adjacent side edge portions of the pair of front mounting plates **93A** and **93B** are formed with nut insertion-purpose notch portions **102A** and **102B** cut in an approximately semicircular shape in directions away from each other. The nut insertion-purpose notch portions **102A** and **102B** are provided at positions facing the bottom surface portions **21C** of the pair of half bodies **92A** and **92B**, and an approximately cylindrical lashing nut **103** is inserted from inside the main body portion **92** toward the front. The lashing nut **103** protrudes (for example, approximately 5 mm to 20 mm) from the bumper reinforcement **2** toward the front of the vehicle, and a screw portion of a hook for hanging a rope for towing/lashing to move the vehicle is screwed into the lashing nut **103** and mounted therein.

[0127] As illustrated in FIGS. **20**, **21**, and **23**, the lashing nut **103** is mounted on a lashing nut

mounting plate **105** that has an approximately horizontal rectangular shape in front view and is placed behind the pair of front mounting plates **93A** and **93B**. The lashing nut mounting plate **105** has a shape substantially the same as the cross-sectional shape of the front end portion of the main body portion **92** that is the hollow tubular body, and includes a flat plate portion **105A** whose side edge portions on opposite sides are in contact with, or in close proximity to, the inner surfaces of the bottom surface portions **21C** and the recessed portions **21G**.

[0128] The side edge portions on the opposite sides of the flat plate portion **105A** are formed with four second support-purpose mounting pieces **105B** that are bent rearward. from both end portions in the vehicle width direction at an approximately right angle in such a manner as to face the bottom surface portions **21C** of the pair of half bodies **92A** and **92B** and that are in contact with the inner surfaces of the bottom surface portions **21C**. The second support-purpose mounting pieces **105B** face the riveting-purpose mounting pieces **97C** and **97D** of the pair of front mounting plates **93A** and **93B**, the riveting-purpose mounting pieces **97C** and **97D** being placed on the outer surfaces of the bottom surface portions **21C** of the pair of half bodies **92A** and **92B**. Therefore, two pairs (a plurality of pairs) of the second support-purpose mounting pieces **105B** are provided in such a manner as to face each other in the up-and-down direction.

[0129] The second support-purpose mounting pieces **105B** are formed respectively with second support-purpose through-holes **105C** through each of which the shaft portion **65A** of the rivet pin **65** can be inserted and that are formed coaxially in the up-and-down direction, at positions facing each of the third riveting-purpose through-holes **98** formed in the bottom surface portions **21C** of the pair of half bodies **92A** and **92B**. The flat plate portion **105A** is formed with a through-hole **105D** through which the lashing nut **103** is inserted from the rear to bring a flange portion **103A** into contact with the rear end portion of the flat plate portion **105A**. The through-hole **105D** is formed at a position facing each of the nut insertion-purpose notch portions **102A** and **102B** of the pair of front mounting plates **93A** and **93B**.

[0130] The lashing nut **103** is inserted in advance through the through-hole **105D** from the rear, and the flange portion **103A** is joined to the flat plate portion **105A** by, for example, arc welding, spot welding, or laser welding. The flat plate portion **105A** is formed with through-holes **105E** through each of which the unillustrated bolt can be inserted, respectively at positions facing the through-holes **100** on the outer side in the vehicle width direction of the pair of front mounting plates **93A** and **93B**.

[0131] The nuts **101** into each of which the unillustrated bolt inserted through the through-hole **105E** is screwed are mounted respectively on the rear end portions of the through-holes **105E** by joining such as arc welding, spot welding, or laser welding. Therefore, the crash box **91** is integrally assembled to the bumper reinforcement **2** by bolting with the nuts **101** welded to the edge portions on the inner side in the vehicle width direction of the pair of front mounting plates **93A** and **93B** and the nuts **101** welded to the through-holes **105E** in the lashing nut mounting plate **105**.

[0132] The pair of rear mounting plates **95A** and **95B** is formed by press forming of steel sheets. For example, alloyed hot-dip galvanized steel sheets or hot-dip galvanized steel sheets can be used. The thickness can be approximately 2.0 mm to 2.6 mm, and the tensile strength can be approximately 440 MPa. The thickness of the pair of rear mounting plates **95A** and **95B** can be set to be substantially the same as the thickness of the pair of front mounting plates **93A** and **93B**. As illustrated in FIGS. **17** to **20**, **22**, and **23**, the pair of rear mounting plates **95A** and **95B** has approximately horizontal rectangular shapes in front view that are symmetric with respect to each other in the up-and-down direction, and the adjacent side edge portions are in contact with the outer surfaces of the bottom surface portions **21C** and the recessed portions **21G** along substantially the entire lengths.

[0133] The height of the pair of rear mounting plates **95A** and **95B** from the bottom surface portions **21C** decreases progressively from the central portions in the vehicle width direction

toward the outer side in the vehicle width direction. The pair of rear mounting plates **95A** and **95B** is formed in an approximately crank shape in plan view by bending substantially the central portions to the outer portions in the vehicle width direction toward the front of the vehicle in such a manner that substantially the central portions to the outer portions in the vehicle width direction can come into contact with the outer surfaces of the rear edge portions of the corresponding half bodies **92A** and **92B** of the pair.

[0134] The length in the vehicle width direction of the pair of rear mounting plates **95A** and **95B** is formed to be equal to the distance from positions facing the proximal end portions of the flange portions **21D** on the inner side in the vehicle width direction of the pair of half bodies **92A** and **92B** to the side edge portions on the outer side in the vehicle width direction of the bottom surface portions **21C**. The width in the up-and-down direction of the pair of rear mounting plates **95A** and **95B** is approximately two-thirds the height in the up-and-down direction from the pairs of flange portions **21D** and **21E** to the bottom surface portions **21C** of the pair of half bodies **92A** and **92B**. The adjacent side edge portions of the pair of rear mounting plates **95A** and **95B** protrude in a horizontal trapezoidal shape in directions closer to each other in such a manner as to come into contact with the outer surfaces of the recessed portions **21G**.

[0135] As illustrated in FIG. **20**, the pair of rear mounting plates **95A** and **95B** is each formed with a mounting rib portion **107** bent forward at an approximately right angle from a side edge portion on the inner side in the vehicle width direction to the side edge portion adjacent to the side edge portion of the other rear mounting plate. As illustrated in FIGS. **17** and **20**, the mounting rib portions **107** are formed with a width dimension that allows the mounting rib portions **107** to be spot welded to the bottom surface portions **21C** and the recessed portions **21G**, which come into contact with the mounting rib portions **107**, at positions facing the bottom surface portions **21C** and the edge portions on the inner side in the vehicle width direction of the recessed portions **210** of the pair of half bodies **92A** and **92B**.

[0136] As illustrated in FIGS. **20** and **22**, the pair of rear mounting plates **95A** and **95B** are each formed, in portions facing the bottom surface portions **21C** on the inner side in the vehicle width direction of the pair of half bodies **92A** and **92B**, with two through-holes **108** along the vehicle width direction, allowing a spacing substantially equal to the width of the opposing bottom surface portions **21C**, at a position of substantially the central portion in the vehicle up-and-down direction. An unillustrated bolt is inserted through each of the through-holes **108** from the front, and is integrally assembled by bolting to the side member **3L**.

Tension Plate

[0137] As illustrated in FIGS. **19**, **20**, **22**, and **23**, an elongated tension plate **111** is fixed on the rear side of the pair of half bodies **92A** and **92B**, with both end portions of the tension plate **111** sandwiched between the flange portions **21D** and **21E**, and placed along the vehicle width direction. The tension plate **111** is formed in a long slender, approximately rectangular shape in plan view, by press forming of a steel sheet. For example, a rolled steel sheet for general structure can be used. The thickness can be approximately 2.0 mm to 2.6 mm, and the tensile strength can be approximately 330 MPa to 540 MPa. The thickness of the tension plate **111** is set to be substantially the same as the thickness of the disk portions **63A** of the rivet pins **63**.

[0138] As illustrated in FIGS. **19** and **22**, the length of the tension plate **111** is set to be slightly less than the distance between the side edge portions on both outer sides in the vehicle width direction of the flange portions **21D** and **21E** of the pair of half bodies **92A** and **92B**. Both end portions in the length direction of the tension plate **111** are formed with a pair of mounting-purpose through-holes **111A**, respectively at positions facing the joining-purpose through-holes **73** provided on the rear side of the pairs of flange portions **21D** and **21E** of the pair of half bodies **92A** and **92B**. The pair of mounting-purpose through-holes **111A** is formed with a diameter that allows the disk portions **63A** of the rivet pins **63** to be inserted through the pair of mounting-purpose through-holes **111A**.

[0139] As illustrated in FIGS. **19**, **20**, and **23**, the tension plate **111** is provided, at its front side edge

portion, with a narrow reinforcement rib **111B** bent upward at an approximately right angle along the entire length of a portion between the pairs of vertical wall portions **21A** and **21B** when the tension plate **111** is placed between the pairs of flange portions **21D** and **21E**. Note that the reinforcement rib **111B** may be bent downward at an approximately right angle.

Assembly of Crash Box

[0140] Next, an assembly procedure of the crash box **91** is described with reference to FIGS. **20** to **23**. As illustrated in FIGS. **20** to **23**, firstly, the front mounting plate **93A** to be placed on the upper side is brought into contact with the front end portion of the half body **92A** that is placed in such a manner that the opening side faces downward. Then, the bent piece **97A** of the front mounting plate **93A** is brought into contact with the inner surface of the vertical wall portion **21B** on the outer side in the vehicle width direction, and the welding-purpose mounting piece **97B** is brought into contact with the outer surface of the front end portion of the recessed portion **21G** of the half body **92A**.

[0141] Moreover, the pair of riveting-purpose mounting pieces **97C** and **97D** of the front mounting plate **93A** is brought into contact with the outer surfaces of the front end portions of the bottom surface portions **21C** of the half body **92A**, respectively, and placed and positioned in such a manner that the fourth riveting-purpose through-holes **99** in the riveting-purpose mounting pieces **97C** and **97D** communicate with the third riveting-purpose through-holes **98** in the bottom surface portions **21C**, respectively. The mounting rib portion **107** of the rear mounting plate **95A** to be placed on the upper side is subsequently brought into contact with the outer surfaces of the bottom surface portions **21C** and the recessed portion **21G**, and placed and positioned along the rear side edge portion of the half body **92A**.

[0142] In this state, the welding-purpose mounting piece **97B** of the front mounting plate **93A** is then joined by spot welding to the outer surface of the recessed portion **21G** of the half body **92A**. Moreover, the mounting rib portion **107** of the rear mounting plate **95A** is joined by spot welding to the outer surfaces of the bottom surface portions **21C** and the recessed portion **21G** of the half body **92A**. Consequently, a semifinished product **113** (refer to FIG. **23**) is assembled in which the front mounting plate **93A** is mounted in such a manner as to cover the front end portion of the half body **92A** and in which the rear mounting plate **95A** is mounted in such a manner as to protrude from the outer surface of the rear side edge portion of the half body **92A** in a direction away from each other. Here, in FIGS. **21** to **23**, x marks indicate joint locations by spot welding.

[0143] Next, the half body **92B** to be placed on the lower side is placed in such a manner that the opening side faces downward. The front mounting plate **93B** to be placed on the lower side is then brought into contact with the front end portion of the half body **92B**. Then, the bent piece **97A** of the front mounting plate **93B** is brought into contact with the inner surface of the vertical wall portion **21B** on the outer side in the vehicle width direction, and the welding-purpose mounting piece **97B** is brought into contact with the outer surface of the front end portion of the recessed portion **21G** of the half body **92B**.

[0144] Moreover, the pair of riveting-purpose mounting pieces **97C** and **97D** of the front mounting plate **93B** is brought into contact with the outer surfaces of the front end portions of the bottom surface portions **21C** of the half body **92B**, respectively, and placed and positioned in such a manner that the fourth riveting-purpose through-holes **99** in the riveting-purpose mounting pieces **97C** and **97D** communicate with the third riveting-purpose through-holes **98** in the bottom surface portions **21C**, respectively. Subsequently, the mounting rib portion **107** of the rear mounting plate **95B** to be placed on the lower side is brought into contact with the outer surfaces of the bottom surface portions **21C** and the recessed portion **21G**, and placed and positioned along the rear side edge portion of the half body **92B**.

[0145] In this state, the welding-purpose mounting piece **97B** of the front mounting plate **93B** is then joined by spot welding to the outer surface of the recessed portion **21G** of the half body **92B**. Moreover, the mounting rib portion **107** of the rear mounting plate **95B** is joined by spot welding to the outer surfaces of the bottom surface portions **21C** and the recessed portion **21G** of the half body

92B. Consequently, a semifinished product **115** (refer to FIG. **23**) is assembled in which the front mounting plate **93B** is mounted in such a manner as to cover the front end portion of the half body **92B** and in which the rear mounting plate **95B** is mounted in such a manner as to protrude from the outer surface of the rear side edge portion of the half body **92B** in a direction away from each other. Here, in FIGS. **21** to **23**, x marks indicate joint locations by spot welding.

[0146] After that, the semifinished product **115** to be placed on the lower side is placed in such a manner that the opening side of the half body **92B** faces upward. The stepped portions **65B** formed at one end portions (the lower end portions) of a pair of the rivet pins **65** are inserted respectively through the third riveting-purpose through-holes **98** formed in the front edge portions of the bottom surface portions **21C** of the half body **92B** and the fourth riveting-purpose through-holes **99** formed in the riveting-purpose mounting pieces **97D** of the front mounting plate **93B** to bring the lower ends of the shaft portions **65A** into contact with the inner surfaces of the bottom surface portions **21C**.

[0147] Subsequently, the shaft portions **65A** of the rivet pins **65** are inserted through the second support-purpose through-holes **105C** formed in the second support-purpose mounting pieces **105B**, which face each other in the up-and-down direction, in the lashing nut mounting plate **105** where the lashing nut **103** has been welded to the end portion at the rear of the through-hole **105D** relative to the vehicle. Then, the lower side edge portion of the lashing nut mounting plate **105** is brought into contact with the inner surface of the front side edge portion of the half body **92B**, and the lashing nut **103** is caused to protrude forward from the nut insertion-purpose notch portion **102B** of the front mounting plate **93B**. Moreover, the stepped portions **65B** protrude upward from the upper second support-purpose through-holes **105C** in the lashing nut mounting plate **105**.

[0148] Moreover, ones of the stepped portions **63B** of the rivet pins **63** are inserted respectively through the joining-purpose through-holes **73** formed in the pair of flange portions **21D** and **21E** of the half body **92B**, and the disk portions **63A** are brought into contact with the flange portions **21D** and **21E**. The pair of mounting-purpose through-holes **111A** formed in the both end portions in the longitudinal direction of the tension plate **111** is then placed, and inserted through the disk portions **63A** of the rivet pins **63** placed on the rear sides of the pair of flange portions **21D** and **21E**.

[0149] Subsequently, the semifinished product **113** to be placed on the upper side is placed directly above the half body **92B** opening upward with the opening side of the half body **92A** facing downward. Then, the semifinished product **113** with the opening side of the half body **92A** facing downward is then lowered downward, and the stepped portions **65B** protruding from the upper second support-purpose through-holes **105C** in the lashing nut mounting plate **105** are inserted through the third riveting-purpose through-holes **98** formed in the front edge portions of the bottom surface portions **21C** of the half body **92A**.

[0150] Subsequently, the semifinished product **113** is lowered further downward, and the stepped portions **65B** inserted respectively through the third riveting-purpose through-holes **98** are inserted respectively through the fourth riveting-purpose through-holes **99** formed in the riveting-purpose mounting pieces **97C** and **97D** of the front mounting plate **93A**, and the upper ends of the shaft portions **65A** are brought into contact with the inner surfaces of the bottom surface portions **21C** of the half body **92A**.

[0151] Moreover, at the same time, the upper stepped portions **63B** of the rivet pins **63** placed in the pair of flange portions **21D** and **21E** of the half body **92B** are inserted through the joining-purpose through-holes **73** formed in the pair of flange portions **21D** and **21E** of the half body **92A**. The upper end portions of the disk portions **63A** of the rivet pins **63** are then brought into contact with the pair of flange portions **21D** and **21B** of the half body **92A**, and each of the pair of flange portions **21D** and the pair of flange portions **21E** of the half bodies **92A** and **92B** is superposed on each other.

[0152] After that, as illustrated in FIGS. **21** to **23**, the pair of the stepped portions **63B** formed at the both end portions of each of the rivet pins **63**, and the pair of the stepped portions **65B** formed

at the both end portions of each of the rivet pins **65** are riveted in the up-and-down direction by an unillustrated riveting apparatus for the purpose of joining. Consequently, as illustrated in FIGS. **18** and **19**, the crash box **91** is assembled.

[0153] The crash box **91** described above can be assembled in such a manner that the mounting direction in which the welding-purpose mounting pieces **97B** of the pair of front mounting plates **93A** and **93B** and the mounting rib portions **107** of the pair of rear mounting plates **95A** and **95B** are mounted by spot welding on the pair of half bodies **92A** and **92B** is the same direction as the mounting direction in which the each of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of half bodies **92A** and **92B** is superposed on each other, and mounted and riveted with the pair of the rivet pins **65** and the plurality of rivet pins **63**. As a result, the assembly time of the crash box **91** can be reduced, and the manufacturing cost can be reduced.

[0154] Moreover, arc welding is not required for the manufacture of the crash box **91**, and it is possible to ensure prevention of burn-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **91**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, when the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zinc fumes from being generated from the surface of the crash box **91**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost.

[0155] Moreover, the mechanical strength at the front end portion of the crash box **91** can be reinforced by the lashing nut mounting plate **105** that is placed at the front end portion of the hollow tubular body formed by the pair of half bodies **92A** and **92B** and supported by the pair of the rivet pins **65**. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **91**, can be thinned, and the manufacturing cost can be reduced.

[0156] Moreover, the pair of half bodies **92A** and **92B** is superposed on each other with the tension plate **111** sandwiched between the pairs of flange portions **21D** and **21E**, and joined together by riveting the rivet pins **63** inserted respectively through the both end portions of the tension plate **111**. Consequently, the tension plate **111** placed in the vehicle width direction can reinforce the mechanical strength in the vehicle width direction at the rear end portion of the crash box **91**. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **91**, can be thinned, and the manufacturing cost can be reduced.

Omission of Lashing Nut

[0157] As illustrated in FIGS. **24** and **25**, as another embodiment, it is also possible to omit the lashing nut **103**, the lashing nut mounting plate **105**, and the bottom surface portion coupling-purpose rivet pins **65** from a crash box **121**.

[0158] Accordingly, the pair of half bodies **92A** and **92B** is not each formed with the pair of third riveting-purpose through-holes **98** through each of which the stepped portion **65B** formed at both ends of the rivet pin **65** can be inserted, in the front side edge portions of their respective bottom surface portions **21C**. The riveting-purpose mounting pieces **97C** and **97D** of the pair of front mounting plates **93A** and **93B** are not each formed with the pair of fourth riveting-purpose through-holes **99** through each of which the stepped portion **65B** formed at the both ends of the rivet pin **65** can be inserted. Note that the nut insertion-purpose notch portions **102A** and **102B** of the pair of front mounting plates **93A** and **93B** may not be formed.

[0159] As illustrated in FIG. **24**, the welding-purpose mounting pieces **97B** and the riveting-purpose mounting pieces **97C** and **97D** of the pair of front mounting plates **93A** and **93B** are joined by spot welding to and mounted on the outer surfaces of the recessed portions **21G** and the bottom surface portions **210** of the corresponding half bodies **92A** and **92B** of the pair. Consequently, the

pair of front mounting plates **93A** and **93B** is mounted in such a manner as to cover the front end portions of the pair of half bodies **92A** and **92B**. In FIG. **24**, black dots indicate joint locations by spot welding. Note that joining may be performed by not limited to spot welding but also welding such as laser welding.

[0160] The nuts **101** into each of which the unillustrated bolt inserted through the through-hole **100** is screwed are mounted by joining such as arc welding, spot welding, or laser welding on the rear end portions of the through-holes **100** formed at the positions outward in the vehicle width direction with respect to the centers in the vehicle width direction of the pair of front mounting plates **93A** and **93B**. Therefore, the crash box **121** is integrally assembled to the bumper reinforcement **2** by bolting with the nuts **101** welded at the positions outward in the vehicle width direction with respect to the centers of the pair of front mounting plates **93A** and **93B** in the vehicle width direction and at the rear end portions of the through-holes **100** of the edge portions on the inner side in the vehicle width direction of the pair of front mounting plates **93A** and **93B**.

Assembly of Crash Box

[0161] Next, an assembly procedure of the crash box **121** is described with reference to FIG. **25**. As illustrated in FIG. **25**, firstly, the front mounting plate **93A** to be placed on the upper side is brought into contact with the front end portion of the half body **92A** that is placed in such a manner that the opening side faces downward. Then, the bent piece **97A** of the front mounting plate **93A** is brought into contact with the inner surface of the vertical wall portion **21B** on the outer side in the vehicle width direction, and the welding-purpose mounting piece **97B** is brought into contact with the outer surface of the front end portion of the recessed portion **21G** of the half body **92A**.

[0162] Moreover, the pair of riveting-purpose mounting pieces **97C** and **97D** of the front mounting plate **93A** is placed and positioned in contact with the outer surfaces of the front end portions of the bottom surface portions **21C** of the half body **92A**. The mounting rib portion **107** of the rear mounting plate **95A** to be placed on the upper side is subsequently brought into contact with the outer surfaces of the bottom surface portions **21C** and the recessed portion **21G**, and placed and positioned along the rear side edge portion of the half body **92A**.

[0163] Then, in this state, the welding-purpose mounting piece **97B** of the front mounting plate **93A** is joined by spot welding to the outer surface of the recessed portion **21G** of the half body **92A**, and the riveting-purpose mounting pieces **97C** and **97D** of the front mounting plate **93A** are joined by spot welding to the outer surfaces of the bottom surface portions **21C** of the half body **92A**. Moreover, the mounting rib portion **107** of the rear mounting plate **95A** is joined by spot welding to the outer surfaces of the bottom surface portions **21C** and the recessed portion **21G** of the half body **92A**. Consequently, a semifinished product **113** (refer to FIG. **23**) is assembled in which the front mounting plate **93A** is mounted in such a manner as to cover the front end portion of the half body **92A** and in which the rear mounting plate **95A** is mounted in such a manner as to protrude from the outer surface of the rear side edge portion of the half body **92A** in a direction away from each other.

[0164] Next, the half body **92B** to be placed on the lower side is placed in such a manner that the opening side faces downward. The front mounting plate **93B** to be placed on the lower side is then brought into contact with the front end portion of the half body **92B**. Then, the bent piece **97A** of the front mounting plate **93B** is brought into contact with the inner surface of the vertical wall portion **21B** on the outer side in the vehicle width direction, and the welding-purpose mounting piece **97B** is brought into contact with the outer surface of the front end portion of the recessed portion **21G** of the half body **92B**.

[0165] Moreover, the pair of riveting-purpose mounting pieces **97C** and **97D** of the front mounting plate **93B** is placed and positioned in contact with the outer surfaces of the front end portions of the bottom surface portions **21C** of the half body **92B**. Subsequently, the mounting rib portion **107** of the rear mounting plate **95B** to be placed on the lower side is brought into contact with the outer surfaces of the bottom surface portions **21C** and the recessed portion **21G**, and placed and

positioned along the rear side edge portion of the half body **92B**.

[0166] Then, in this state, the welding-purpose mounting piece **97B** of the front mounting plate **93B** is joined by spot welding to the outer surface of the recessed portion **21G** of the half body **92B**, and the riveting-purpose mounting pieces **97C** and **97D** of the front mounting plate **93B** are joined by spot welding to the outer surfaces of the bottom surface portions **21C** of the half body **92B**. Moreover, the mounting rib portion **107** of the rear mounting plate **95B** is joined by spot welding to the outer surfaces of the bottom surface portions **21C** and the recessed portion **210** of the half body **92B**. Consequently, a semifinished product **115** (refer to FIG. **23**) is assembled in which the front mounting plate **93B** is mounted in such a manner as to cover the front end portion of the half body **92B** and in which the rear mounting plate **95B** is mounted in such a manner as to protrude from the outer surface of the rear side edge portion of the half body **92B** in a direction away from each other.

[0167] After that, the semifinished product **115** to be placed on the lower side is placed in such a manner that the opening side of the half body **92B** faces upward. Ones of the stepped portions **63B** of the rivet pins **63** are then inserted respectively through the joining-purpose through-hole **73** formed in the pair of flange portions **21D** and **21E** of the half body **92B**, and the disk portions **63A** are brought into contact with the flange portions **21D** and **21E**. The pair of mounting-purpose through-holes **111A**, formed in the both end portions in the longitudinal direction of the tension plate **111** is then placed, and inserted through the disk portions **63A** of the rivet pins **63** placed on the rear sides of the pair of flange portions **21D** and **21E**.

[0168] The semifinished product **113** to be placed on the upper side is then placed directly above the half body **92B** opening upward with the opening side of the half body **92A** facing downward. Subsequently, the semifinished product **113** with the opening side of the half body **92A** facing downward is lowered downward, and the upper stepped portions **63B** of the rivet pins **63** placed in the pair of flange portions **21D** and **21E** of the half body **92B** are inserted respectively through the joining-purpose through-holes **73** formed in the pair of flange portions **21D** and **21E** of the half body **92A**.

[0169] The upper end portions of the disk portions **63A** of the rivet pins **63** are then brought into contact with the pair of flange portions **21D** and **21E** of the half body **92A**, and each of the pair of flange portions **21D** and the pair of flange portions **21E** of the half bodies **92A** and **92B** is superposed on each other. After that, the pair of the stepped portions **63B** formed at the both end portions of the each of the rivet pins **63** is riveted in the up-and-down direction by an unillustrated riveting apparatus for the purpose of joining. Consequently, as illustrated in FIG. **24**, the crash box **121** is assembled.

[0170] The crash box **121** described above can be assembled in such a manner that the mounting direction in which the welding-purpose mounting pieces **97B** and the riveting-purpose mounting pieces **97C** and **97D** of the pair of front mounting plates **93A** and **93B** and the mounting rib portions **107** of the pair of rear mounting plates **95A** and **95B** are mounted by spot welding on the pair of half bodies **92A** and **92B** is the same direction as the mounting direction in which the each of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of half bodies **92A** and **92B** is superposed, mounted on each other and riveted with the plurality of rivet pins **63**. As a result, the assembly time of the crash box **121** can be reduced, and the manufacturing cost can be reduced.

[0171] Moreover, arc welding is not required for the manufacture of the crash box **121**, and it is possible to ensure prevention of burn-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **121**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, when the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized

steel sheets, it is possible to prevent zinc fumes from being generated from the surface of the crash box **121**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost. [0172] Moreover, the pair of half bodies **92A** and **92B** is superposed on each other with the tension plate **111** sandwiched between the pairs of flange portions **21D** and **21E**, and is connected by riveting the rivet pins **63** inserted respectively through the both end portions of the tension plate **111**. Consequently, the tension plate **111** placed in the vehicle width direction can reinforce the mechanical strength in the vehicle width direction at the rear end portion of the crash box **121**. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **121**, can be thinned, and the manufacturing cost can be reduced.

Joining of Flanges with Bolts

[0173] As illustrated in FIG. **26**, as another embodiment, it is also possible to join the pairs of flange portions **21D** and **21E** superposed on each other of the half bodies **92A** and **92B** by bolting with hexagon socket head cap screws **133** inserted respectively through the joining-purpose through-holes **73** and nuts **135**, instead of the rear flange joining-purpose rivet pins **63**.

[0174] Specifically, the opening side of the half body **92B** forming the semifinished product **115** (refer to FIG. **23**) is placed in such a manner as to face upward. Ones of the stepped portions **63B** of the rivet pins **63** are then inserted respectively through the front joining-purpose through-holes **73** among the joining-purpose through-holes **73** (refer to FIG. **25**) formed in the pair of flange portions **21D** and **21E** of the half body **92B**. The pair of mounting-purpose through-holes **111A** formed in the both end portions in the longitudinal direction of the tension plate **111** is then placed in such a manner as to be substantially coaxial with the joining-purpose through-holes **73** on the rear sides of the pair of flange portions **21D** and **21E**.

[0175] The semifinished product **113** to be placed on the upper side is then placed directly above the half body **92B** opening upward with the opening side of the half body **92A** facing downward. Subsequently, the semifinished product **113** with the opening side of the half body **92A** facing downward is lowered downward, and the upper stepped portions **63B** of the rivet pins **63** placed in the pair of flange portions **21D** and **21E** of the half body **92B** are inserted through the front joining-purpose through-holes **73** among the joining-purpose through-holes **73** formed in the pair of flange portions **21D** and **21E** of the half body **92A**.

[0176] The upper end portions of the disk portions **63A** of the rivet pins **63** are then brought into contact with the pair of flange portions **21D** and **21E** of the half body **92A**. Moreover, at the same time, the both end portions of the tension plate **111** are brought into contact with the pair of flange portions **21D** and **21E** of the half body **92A**, and each of the pair of flange portions **21D** and the pair of flange portions **21E** of the half bodies **92A** and **92B** is superposed on each other.

[0177] The hexagon socket head cap screws **133** are then inserted from below through the rear joining-purpose through-holes **73** of the pairs of flange portions **21D** and **21E** superposed on each other of the half bodies **92A** and **92B** and the mounting-purpose through-holes **111A** formed in the both end portions of the tension plate **111**, and joined by bolting with the nuts **135**. Consequently, a crash box **131** is assembled.

[0178] Note that instead of the rivet pins **63** placed on the front sides of the flange portions **21D** and **21E** of the crash box **131**, bolting with a pair of the hexagon socket head cap screws **133** and a pair of the nuts **135** may be used for joining. Moreover, in this case, it is preferable that bolting be performed with washers having substantially the same thickness as the tension plate **111** put in between with the front joining-purpose through-holes **73** of the flange portions **21D** and **21E**.

[0179] The crash box **131** described above can be assembled in such a manner that the mounting direction in which the welding-purpose mounting pieces **97B** and the riveting-purpose mounting pieces **97C** and **97D** of the pair of front mounting plates **93A** and **93B** and the mounting rib portions **107** of the pair of rear mounting plates **95A** and **95B** are mounted by spot welding on the pair of half bodies **92A** and **92B** is the same direction as the mounting direction in which the each

of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of half bodies **92A** and **92B** is superposed and mounted on each other by riveting with a pair of the rivet pins **63** and by bolting with the pair of the hexagon socket head cap screws **133** and the pair of the nuts **135**. As a result, the assembly time of the crash box **131** can be reduced, and the manufacturing cost can be reduced.

[0180] Moreover, arc welding is not required for the manufacture of the crash box **131**, and it is possible to ensure prevention of burn-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **131**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, when the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zinc fumes from being generated from the surface of the crash box **131**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost.

[0181] Moreover, the pair of half bodies **92A** and **92B** is superposed on each other with the tension plate **111** sandwiched between the pairs of flange portions **21D** and **21E**, and is joined together by bolting with the pair of the hexagon socket head cap screws **133** inserted through the both end portions of the tension plate **111** and the pair of the nuts **135**. Consequently, the tension plate **111** placed in the vehicle width direction can reinforce the mechanical strength in the vehicle width direction at the rear end portion of the crash box **131**. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **131**, can be thinned, and the manufacturing cost can be reduced.

Other Embodiments

[0182] As still another embodiment, the crash boxes **1**, **51**, **61**, **81**, **91**, **121**, and **131** may be provided between the bumper reinforcement **2** and the side member **3L** extending in the vehicle front-and-rear direction in an orientation rotated (for example, 90 degrees or 180 degrees) around the axes of the main body portions **11** and **92**.

[0183] As yet another embodiment, in the crash box **121** of FIGS. **24** to **25**, the joining-purpose through-holes **73** may not be formed in the pairs of flange portions **21D** and **21E** of the pair of half bodies **92A** and **92B**. Moreover, the tension plate **111** may not be formed with the mounting-purpose through-holes **111A**, at the both end portions in the longitudinal direction. Moreover, spacers that have, for example, a circular or rectangular shape and are formed of flat sheets made of metal such as iron having substantially the same thickness as the tension plate **111** may be sandwiched at positions corresponding to the front joining-purpose through-holes **73** of the flange portions **21D** and **21E**.

[0184] Each of the pair of flange portions **21D** and the pair of flange portions **21E** of the half bodies **92A** and **92B** may be then superposed on each other, and joined by spot welding at the positions where the rivet pins **63** were supposed to be placed, with the tension plate **111** and the spacers sandwiched therebetween. Consequently, the superposed flange portions **21D** and **21E** on both sides in the vehicle width direction of the crash box **121** can be joined by spot welding with the tension plate **111** sandwiched therebetween, and assembled together.

[0185] Therefore, the assembly can be performed in such a manner that the mounting direction in which the welding-purpose mounting pieces **97B** and the riveting-purpose mounting pieces **97C** and **97D** of the pair of front mounting plates **93A** and **93B** and the mounting rib portions **107** of the pair of rear mounting plates **95A** and **95B** are mounted by spot welding on the pair of half bodies **92A** and **92B** is the same direction as the mounting direction in which the each of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of half bodies **92A** and **92B** is superposed on each other and mounted by spot welding. As a result, the assembly time of the crash box **121** can be reduced, and the manufacturing cost can be reduced.

[0186] Moreover, arc welding is not required for the manufacture of the crash box **121**, and it is

possible to ensure prevention of burn-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **131**, can be thinned (to a plate thickness of, for example, approximately 0.8 mm to 1 mm). Moreover, when the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B** are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zinc fumes from being generated from the surface of the crash box **121**, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost. [0187] Moreover, each of the pair of flange portions **21D** and the pair of flange portions **21E** of the pair of half bodies **92A** and **92B** is superposed on each other with the tension plate **111** and the spacers sandwiched therebetween, and joined together by spot welding. Consequently, the tension plate **111** placed in the vehicle width direction can reinforce the mechanical strength in the vehicle width direction at the rear end portion of the crash box **121**. As a result, the pair of front mounting plates **93A** and **93B**, the pair of rear mounting plates **95A** and **95B**, and the pair of half bodies **92A** and **92B**, which form the crash box **121**, can be thinned, and the manufacturing cost can be reduced.

Advantages of Embodiments

[0188] The embodiments described above have at least the following effects: For example, the pair of front mounting plates and the pair of rear mounting plates are mounted by spot welding or riveting on the front and rear end portions in the vehicle front-and-rear direction of the pair of half bodies. Moreover, each of the pairs of flange portions is superposed on each other in such a manner as to form a tubular body to mount the pair of half bodies on each other by spot welding, riveting, or bolting. The assembly is then performed in such a manner that the mounting direction in which the pair of front mounting plates and the pair of rear mounting plates are mounted on the pair of half bodies is the same direction as the mounting direction in which the each of the pairs of flange portions of the pair of half bodies is superposed and mounted on each other.

[0189] Consequently, arc welding is not required for the manufacture of the crash box, and it is possible to ensure prevention of burn-through caused by arc welding in a thin portion. As a result, the pair of front mounting plates, the pair of rear mounting plates, and the pair of half bodies, which form the crash box, can be thinned. Moreover, when the pair of front mounting plates, the pair of rear mounting plates, and the pair of half bodies are formed of hot-dip galvanized steel sheets or alloyed hot-dip galvanized steel sheets, it is possible to prevent zinc fumes from being generated from the surface of the crash box, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost. Moreover, the pair of front mounting plates, the pair of rear mounting plates, and the pair of half bodies can be assembled in the same direction by spot welding, riveting, or bolting, and integrated into a single unit; therefore, the crash box assembly process can be made more efficient.

[0190] In some embodiments, the pair of front mounting plates and the pair of rear mounting plates are joined by spot welding the pluralities of bent pieces to the outer surfaces of the bottom surface portions of the half bodies. Moreover, the pair of half bodies is joined together by spot welding with each of the pairs of flange portions of the pair of half bodies superposed on each other. Consequently, the assembly can be performed in such a manner that the mounting direction in which the pair of front mounting plates and the pair of rear mounting plates are mounted by spot welding on the pair of half bodies is the same direction as the mounting direction in which each of the pairs of flange portions of the pair of half bodies is superposed on each other and mounted by spot welding. As a result, the assembly time of the crash box can be reduced, and the manufacturing cost can be reduced.

[0191] In some embodiments, the pair of front mounting plates and the pair of rear mounting plates are joined by spot welding the pluralities of bent pieces to the outer surfaces of the bottom surface portions of the corresponding half bodies. Moreover, the pair of half bodies is joined together by

riveting or bolting of the flange joining-purpose rivet pins or bolts inserted through the plurality of joining-purpose through-holes with each of the pairs of flange portions of the pair of half bodies superposed on each other.

[0192] Consequently, the assembly can be performed in such a manner that the mounting direction in which the pair of front mounting plates and the pair of rear mounting plates are mounted by spot welding on the pair of half bodies is the same direction as the mounting direction in which the each of the pairs of flange portions of the pair of half bodies is superposed and mounted on each other. As a result, the assembly time of the crash box can be reduced, and the manufacturing cost can be reduced.

[0193] In some embodiments, the pair of half bodies, the pair of front mounting plates, and the pair of rear mounting plates are integrally joined by riveting the plurality of bottom surface coupling-purpose rivet pins and the plurality of flange joining-purpose rivet pins. Consequently, the assembly can be performed in such a manner that the mounting direction in which the pair of front mounting plates and the pair of rear mounting plates are mounted on the pair of half bodies is the same direction as the mounting direction in which each of the pairs of flange portions of the pair of half bodies is superposed and mounted on each other. As a result, the assembly time of the crash box can be reduced, and the manufacturing cost can be reduced.

[0194] In some embodiments, the pluralities of spot welding-purpose mounting pieces of the pair of front mounting plates are joined by spot welding to the outer surfaces of the bottom surface portions of the corresponding half bodies. The mounting rib portions, which are bent forward along the entire width, of the pair of rear mounting plates are joined by spot welding to the outer surfaces of the bottom surface portions of the corresponding half bodies. Moreover, the pair of half bodies is joined together by riveting or bolting of the flange joining-purpose rivet pins or bolts inserted through the plurality of joining-purpose through-holes with each of the pairs of flange portions of the pair of half bodies superposed on each other.

[0195] Consequently, the assembly can be performed in such a manner that the mounting direction in which the pair of front mounting plates and the pair of rear mounting plates are mounted by spot welding on the pair of half bodies is the same direction as the mounting direction in which the each of the pairs of flange portions of the pair of half bodies is superposed and mounted on each other. As a result, the assembly time of the crash box can be reduced, and the manufacturing cost can be reduced.

[0196] In some embodiments, the spot welding-purpose mounting pieces of the pair of front mounting plates are joined by spot welding to the outer surfaces of the bottom surface portions of the corresponding half bodies. The mounting rib portions, which are bent forward along the entire width, of the pair of rear mounting plates are joined by spot welding to the outer surfaces of the bottom surface portions of the corresponding half bodies. Moreover, the pair of half bodies is integrally connected by riveting the plurality of bottom surface portion coupling-purpose rivet pins and the plurality of flange joining-purpose rivet pins.

[0197] Consequently, the assembly can be performed in such a manner that the mounting direction in which the pair of front mounting plates and the pair of rear mounting plates are mounted on the pair of half bodies is the same direction as the mounting direction in which each of the pairs of flange portions of the pair of half bodies is mounted on each other. As a result, the assembly time of the crash box can be reduced, and the manufacturing cost can be reduced.

[0198] In some embodiments, the mechanical strength at the front end portion of the crash box can be reinforced by the lashing nut mounting plate that is placed at the front end portion of the hollow tubular body formed with the pair of half bodies and supported by the plurality of bottom surface portion coupling-purpose rivet pins. As a result, the pair of front mounting plates, the pair of rear mounting plates, and the pair of half bodies, which form the crash box, can be thinned, and the manufacturing cost can be reduced.

[0199] In some embodiments, the pair of half bodies is superposed on each other with the tension

plate sandwiched between the pairs of flange portions, and is joined together by riveting the flange joining-purpose rivet pins inserted respectively through the both end portions of the tension plate. Consequently, the tension plate placed in the vehicle width direction can reinforce the mechanical strength in the vehicle width direction at the rear end portion of the crash box. As a result, the pair of front mounting plates, the pair of rear mounting plates, and the pair of half bodies, which form the crash box, can be thinned, and the manufacturing cost can be reduced.

[0200] In some embodiments, the pair of front mounting plates, the pair of rear mounting plates, and the pair of half bodies are formed of alloyed hot-dip galvanized steel sheets. Consequently, it is possible to prevent zinc fumes from being generated from the surface of the crash box, eliminate the need for the zinc fume removal process, and reduce the manufacturing cost, and also it is possible to improve press formability, paintability, and rust-prevention performance.

[0201] Up to this point various embodiments have been described above. However, the present invention is not limited to these embodiments. Naturally, various improvements, modifications, additions, and deletions can be made within the scope that does not depart from the purport of the present invention.

Claims

1. A crash box provided between a bumper reinforcement extending in a vehicle width direction and a side member extending in a vehicle front-and-rear direction to absorb impact energy at the time of a collision, the crash box comprising: a hollow tubular body placed along the vehicle front-and-rear direction, the tubular body including a pair of half bodies of approximately hat shape in cross section, the pair of half bodies each having a bottom surface portion, vertical wall portions extending from the bottom surface portion, and flange portions extending from the vertical wall portions; a pair of front mounting plates placed respectively at front end portions of the pair of half bodies and mounted on one of the bumper reinforcement and the side member; and a pair of rear mounting plates placed respectively at rear end portions of the pair of half bodies and mounted on the other of the bumper reinforcement and the side member, wherein the pair of front mounting plates and the pair of rear mounting plates are mounted on the pair of half bodies in a first direction by spot welding or riveting, the flange portions are superposed on each other and mounted in a second direction by spot welding or riveting, or bolting, and the first direction and the second direction are the same direction.

2. The crash box according to claim 1, wherein each of the front mounting plates of the pair and the rear mounting plates of the pair includes a plurality of bent pieces formed by bending parts thereof inward, the pair of front mounting plates and the pair of rear mounting plates are joined by spot welding the pluralities of bent pieces to outer surfaces of the bottom surface portions of the corresponding half bodies, and are mounted in such a manner as to cover the front and rear end portions of the pair of half bodies, and the pair of half bodies is joined together by spot welding with pairs of the flange portions superposed on each other.

3. The crash box according to claim 1, wherein each of the front mounting plates of the pair and the rear mounting plates of the pair includes a plurality of bent pieces formed by bending parts thereof inward, each of the pair of half bodies includes a plurality of joining-purpose through-holes through each of which a flange joining-purpose rivet pin or a bolt is inserted, in a pair of the flange portions, the pair of front mounting plates and the pair of rear mounting plates are joined by spot welding the pluralities of bent pieces to outer surfaces of the bottom surface portions of the corresponding half bodies, and are mounted in such a manner as to cover the front and rear end portions of the pair of half bodies, and the pair of half bodies is joined together by riveting or bolting of the flange joining-purpose rivet pins or the bolts inserted through the plurality of joining-purpose through-holes, with the pairs of the flange portions superposed on each other.

4. The crash box according to claim 1, further comprising: a plurality of bottom surface portion

coupling-purpose rivet pins each having stepped portions with a reduced outer diameter at both end portion, the plurality of bottom surface portion coupling-purpose rivet pins being configured to couple front and rear side edge portions of the bottom surface portions of the pair of half bodies; and a plurality of flange joining-purpose rivet pins configured to join pairs of the flange portions of the pair of half bodies, wherein each of the pair of half bodies includes: a plurality of first riveting-purpose through-holes that are formed in the front and rear side edge portions of the bottom surface portions and through which end portions of the bottom surface portion coupling-purpose rivet pins are inserted; and a plurality of joining-purpose through-holes that are formed in the pair of the flange portions and through which the flange joining-purpose rivet pins are inserted, each of the front mounting plates of the pair and the rear mounting plates of the pair includes: a plurality of bent pieces each formed with a second riveting-purpose through-hole through which the end portion of the bottom surface portion coupling-purpose rivet pin is inserted, the bent pieces being formed by being bent inward respectively at positions facing the plurality of first riveting-purpose through-holes of the half body to be mounted; and a support-purpose bent portion formed with a plurality of support-purpose through-holes through each of which the bottom surface portion coupling-purpose rivet pin is inserted, at positions facing the second riveting-purpose through-holes, the support-purpose bent portion being bent inward from a side edge portion on an opening side of the corresponding half body, corresponding to the plurality of bent pieces, each of the pair of front mounting plates and the pair of rear mounting plates is placed in such a manner that the support-purpose bent portions face each other, and is placed in such a manner that the pluralities of bent pieces are brought into contact with an outer surface of the bottom surface portion of the corresponding half body in such a manner as to cover the front and rear end portions of each of the pair of half bodies, the plurality of bottom surface portion coupling-purpose rivet pins is inserted respectively through the pluralities of support-purpose through-holes formed in the support-purpose bent portions, and the both end portions inserted through the first riveting-purpose through-holes are inserted through the second riveting-purpose through-holes of the corresponding bent pieces, the plurality of flange joining-purpose rivet pins is inserted respectively through the pluralities of joining-purpose through-holes formed in the opposing pairs of the flange portions, and the pair of half bodies, the pair of front mounting plates, and the pair of rear mounting plates are integrally connected by riveting the plurality of bottom surface portion coupling-purpose rivet pins and the plurality of flange joining-purpose rivet pins.

5. The crash box according to claim 1, comprising a plurality of flange joining-purpose rivet pins, or bolts and nuts, configured to join pairs of the superposed flange portions of the pair of half bodies, wherein the pair of front mounting plates includes a plurality of spot welding-purpose mounting pieces that are bent rearward from side edge portions on opposite sides of the pair of front mounting plates and are in contact with outer surfaces of the bottom surface portions of the half bodies, the pair of rear mounting plates includes mounting rib portions that are bent forward from adjacent side edge portions of the pair of rear mounting plates and are in contact with the outer surfaces of the bottom surface portions of the half bodies, each of the pair of half bodies includes, in the pair of the flange portions, a plurality of joining-purpose through-holes through which the flange joining-purpose rivet pins or the bolts are inserted, the pair of front mounting plates is joined by spot welding the plurality of spot welding-purpose mounting pieces to the outer surfaces of the bottom surface portions of the corresponding half bodies, and is mounted in such a manner as to cover the front end portions of the pair of half bodies, the pair of rear mounting plates is joined by spot welding the mounting rib portions to the outer surfaces of rear side edge portions of the bottom surface portions of the corresponding half bodies, and is mounted in such a manner as to protrude from the bottom surface portions of the pair of half bodies in directions away from each other, and the pair of half bodies is joined together by riveting or bolting of the flange joining-purpose rivet pins or bolts inserted through the plurality of joining-purpose through-holes, with the pairs of the flange portions superposed on each other.

6. The crash box according to claim 1, comprising: a plurality of bottom surface portion coupling-purpose rivet pins each having stepped portions with a reduced outer diameter at both end portion, the plurality of bottom surface portion coupling-purpose rivet pins being configured to couple front side edge portions of the bottom surface portions of the pair of half bodies in a state where the front side edge portions face each other; and a plurality of flange joining-purpose rivet pins configured to join pairs of the flange portions of the pair of half bodies, wherein each of the pair of half bodies includes: a plurality of third riveting-purpose through-holes that are formed in the front side edge portion of the bottom surface portion and through which end portions of the bottom surface portion coupling-purpose rivet pins are inserted; and a plurality of joining-purpose through-holes that are formed in the pair of the flange portions and through which the flange joining-purpose rivet pins are inserted, the pair of front mounting plates includes: spot welding-purpose mounting pieces that are bent rearward from side edge portions on opposite sides of the pair of front mounting plates and are in contact with outer surfaces of the bottom surface portions of the corresponding half bodies; and a plurality of riveting-purpose mounting pieces that are bent rearward from the side edge portions on the opposite sides, corresponding to the plurality of third riveting-purpose through-holes, are in contact with the outer surfaces of the bottom surface portions of the corresponding half bodies, and are formed with fourth riveting-purpose through-holes through which the end portions of the bottom surface portion coupling-purpose rivet pins are inserted, the pair of rear mounting plates includes mounting rib portions that are bent forward from adjacent side edge portions of the pair of rear mounting plates and are in contact with the outer surfaces of rear side edge portions of the bottom surface portions of the half bodies, the pair of front mounting plates is joined by spot welding the spot welding-purpose mounting pieces to the outer surfaces of the bottom surface portions of the corresponding half bodies, and is mounted in such a manner as to cover the front end portions of the pair of half bodies, the pair of rear mounting plates is joined by spot welding the mounting rib portions to the outer surfaces of the rear side edge portions of the bottom surface portions of the corresponding half bodies, and is mounted in such a manner as to protrude from the bottom surface portions of the pair of half bodies in directions away from each other, both end portions, which have been inserted through the third riveting-purpose through-holes of the pair of half bodies, of each of the plurality of bottom surface portion coupling-purpose rivet pins are inserted through the fourth riveting-purpose through-holes of the corresponding riveting-purpose mounting pieces, the plurality of flange joining-purpose rivet pins is inserted respectively through the pluralities of joining-purpose through-holes formed in the opposing pairs of the flange portions, and the pair of half bodies, the pair of front mounting plates, and the pair of rear mounting plates are integrally connected by riveting the plurality of bottom surface portion coupling-purpose rivet pins and the plurality of flange joining-purpose rivet pins.

7. The crash box according to claim 6, comprising a flat nut mounting plate that is placed at a front or rear end portion of the hollow tubular body formed by the pair of half bodies and on which a nut for towing or lashing a vehicle is mounted in such a manner as to protrude outward of the crash box, wherein the nut mounting plate includes a plurality of second support-purpose mounting pieces that are bent inward from both side edge portions on opposite sides of the nut mounting plate, corresponding to the third riveting-purpose through-holes, are in contact with inner surfaces of the bottom surface portions of the corresponding half bodies, and are each formed with a second support-purpose through-hole through which a shaft portion of the bottom surface portion coupling-purpose rivet pin is inserted, at positions facing the third riveting-purpose through-holes, the pair of front mounting plates, or the pair of rear mounting plates, includes a nut insertion-purpose notch portion cut in adjacent side edge portions of the pair of front mounting plates or the pair of rear mounting plates in directions away from each other, through which the nut is inserted, the plurality of bottom surface portion coupling-purpose rivet pins is inserted respectively through the second support-purpose through-holes formed in a plurality of pairs of the second support-purpose mounting pieces that are formed in the nut mounting plate and face each other in a vehicle

up-and-down direction, and the both end portions inserted through the third riveting-purpose through-holes are inserted through the fourth riveting-purpose through-holes in the corresponding riveting-purpose mounting pieces, and the pair of half bodies, the pair of front mounting plates, and the pair of rear mounting plates are integrally connected by riveting the plurality of bottom surface portion coupling-purpose rivet pins and the plurality of flange joining-purpose rivet pins, and the nut mounting plate is placed inside front end portions of the pair of half bodies so that the nut protrudes outward of the crash box from the nut insertion-purpose notch portion.

8. The crash box according to claim 5, comprising an elongated tension plate that is placed along the vehicle width direction and is sandwiched between the pairs of the flange portions of the pair of half bodies in such a manner that both end portions of the tension plate face the joining-purpose through-holes provided on rear sides of the pairs of the flange portions, wherein the flange joining-purpose rivet pins each include: a disk portion larger than the joining-purpose through-hole; and a stepped portion at each of both axial end portions of the disk portion to be inserted through the joining-purpose through-hole, the tension plate includes a pair of mounting-purpose through-holes that are formed in the both end portions and through which the disk portions of the flange joining-purpose rivet pins are inserted, the tension plate is placed in such a manner that the disk portions of a pair of the flange joining-purpose rivet pins whose stepped portions have been inserted through the joining-purpose through-holes provided on the rear sides of the pair of the flange portions of one of the half bodies are inserted through the pair of mounting-purpose through-holes, and the pair of half bodies is superposed on each other with the tension plate sandwiched between the pairs of the flange portions, and joined together by riveting the stepped portions inserted through the plurality of joining-purpose through-holes.

9. The crash box according to claim 1, wherein the pair of front mounting plates, the pair of rear mounting plates, and the pair of half bodies are formed of alloyed hot-dip galvanized steel sheets.

10. A method for manufacturing the crash box according to claim 2, comprising the steps of: joining the pluralities of bent pieces of one of the front mounting plates and one of the rear mounting plates by spot welding to the outer surface of the bottom surface portion at both side edge portions of the corresponding one of the half bodies; joining the pluralities of bent pieces of the other front mounting plate and the other rear mounting plate by spot welding to the outer surface of the bottom surface portion at both side edge portions of the corresponding other half body; superposing the pairs of the flange portions on each other in such a manner that an inner surface of the bottom surface portion of the one of the half bodies faces an inner surface of the bottom surface portion of the other half body; and joining the pairs of the superposed flange portions by spot welding.

11. A method for manufacturing the crash box according to claim 3, comprising the steps of: joining the pluralities of bent pieces of one of the front mounting plates and one of the rear mounting plates by spot welding to the outer surface of the bottom surface portion at both side edge portions of the corresponding one of the half bodies; joining the pluralities of bent pieces of the other front mounting plate and the other rear mounting plate by spot welding to the outer surface of the bottom surface portion at both side edge portions of the corresponding other half body; superposing the pairs of the flange portions on each other in such a manner that an inner surface of the bottom surface portion of the one of the half bodies faces an inner surface of the bottom surface portion of the other half body, and inserting the flange joining-purpose rivet pins or the bolts through the pluralities of the joining-purpose through-holes of the pairs of the superposed flange portions; and riveting or tightening the inserted flange joining-purpose rivet pins or the bolts.

12. A method for manufacturing the crash box according to claim 4, comprising the steps of: placing the pluralities of bent pieces of one of the front mounting plates and one of the rear mounting plates in such a manner as to be in contact with the outer surface of the bottom surface portion at both side edge portions of the corresponding one of the half bodies, and to cause the plurality of first riveting-purpose through-holes to communicate with pluralities of the second

riveting-purpose through-holes; inserting one end sides of the bottom surface portion coupling-purpose rivet pins respectively through the pluralities of support-purpose through-holes formed in the support-purpose bent portions of the one of the front mounting plates and the one of the rear mounting plates, which have been placed, and inserting the one end portions of the bottom surface portion coupling-purpose rivet pins through the first riveting-purpose through-holes and the second riveting-purpose through-holes; inserting one end portions of the flange joining-purpose rivet pins through the plurality of joining-purpose through-holes formed in the pair of the flange portions of one of the half bodies; placing the pluralities of bent pieces of the other front mounting plate and the other rear mounting plate in such a manner as to be in contact with the outer surface of the bottom surface portion at both side edge portions of the corresponding other half body, and to cause the plurality of first riveting-purpose through-holes to communicate with pluralities of the second riveting-purpose through-holes; inserting the other end sides of the bottom surface portion coupling-purpose rivet pins respectively through the pluralities of support-purpose through-holes formed in the support-purpose bent portions of the other front mounting plate and the other rear mounting plate, which have been placed, and inserting the other end portions of the bottom surface portion coupling-purpose rivet pins through the first riveting-purpose through-holes and the second riveting-purpose through-holes of the other half body; inserting the other end portions of the inserted flange joining-purpose rivet pins through the plurality of joining-purpose through-holes formed in the pair of the flange portions of the other half body; and riveting the both end portions of the plurality of bottom surface portion coupling-purpose rivet pins inserted through the pluralities of the second riveting-purpose through-holes of the pair of front mounting plates and the pair of rear mounting plates, and the both end portions of the plurality of flange joining-purpose rivet pins inserted through the pluralities of joining-purpose through-holes of the pair of half bodies.

13. A method for manufacturing the crash box according to claim 5, comprising the steps of: joining a plurality of the spot welding-purpose mounting pieces of one of the front mounting plates by spot welding to the outer surface of the bottom surface portion at a front side edge portion of corresponding one of the half bodies, and joining the mounting rib portion of one of the rear mounting plates by spot welding to the outer surface of the bottom surface portion at a rear side edge portion of the one of the half bodies; joining a plurality of the spot welding-purpose mounting pieces of the other front mounting plate by spot welding to the outer surface of the bottom surface portion at a front side edge portion of the corresponding other half body, and joining the mounting rib portion of the other rear mounting plate by spot welding to the outer surface of the bottom surface portion at a rear side edge portion of the other half body; superposing the pairs of the flange portions on each other in such a manner that an inner surface of the bottom surface portion of the one of the half bodies faces an inner surface of the bottom surface portion of the other half body, and inserting the flange joining-purpose rivet pins or the bolts through the pluralities of joining-purpose through-holes of the pairs of the superposed flange portions; and riveting or tightening the inserted flange joining-purpose rivet pins or the bolts.

14. A method for manufacturing the crash box according to claim 6, comprising the steps of: placing the spot welding-purpose mounting piece and a plurality of the riveting-purpose mounting pieces of one of the front mounting plates in such a manner as to be in contact with the outer surface of the bottom surface portion at the front side edge portion of corresponding one of the half bodies, and to cause the plurality of third riveting-purpose through-holes to communicate with a plurality of the fourth riveting-purpose through-holes; joining the spot welding-purpose mounting piece of the placed one of the front mounting plates by spot welding to the outer surface of the bottom surface portion of the corresponding one of the half bodies, and joining the mounting rib portion of one of the rear mounting plates by spot welding to the outer surface of the bottom surface portion at the rear side edge portion of the one of the half bodies; placing the spot welding-purpose mounting piece and a plurality of the riveting-purpose mounting pieces of the other front

mounting plate in such a manner as to be in contact with the outer surface of the bottom surface portion at the front side edge portion of the corresponding other half body and to cause the plurality of third riveting-purpose through-holes to communicate with a plurality of the fourth riveting-purpose through-holes; joining the spot welding-purpose mounting piece of the placed other front mounting plate by spot welding to the outer surface of the bottom surface portion of the corresponding other half body, and joining the mounting rib portion of the other rear mounting plate by spot welding to the outer surface of the bottom surface portion at the rear side edge portion of the other half body; inserting one end portions of the plurality of bottom surface portion coupling-purpose rivet pins, from an inner surface of the bottom surface portion, through the plurality of third riveting-purpose through-holes of the one of the half bodies and the plurality of the fourth riveting-purpose through-holes of the one of the front mounting plates, and inserting one end portions of the flange joining-purpose rivet pins through the plurality of joining-purpose through-holes formed in the pair of the flange portions of the one of the half bodies; inserting the other end portions of the plurality of placed bottom surface portion coupling-purpose rivet pins, from an inner surface of the bottom surface portion of the other half body, through the plurality of third riveting-purpose through-holes of the other half body and the plurality of the fourth riveting-purpose through-holes of the other front mounting plate, and inserting the other end portions of the plurality of placed flange joining-purpose rivet pins through the plurality of joining-purpose through-holes formed in the pair of the flange portions of the other half body; and riveting the both end portions of the bottom surface portion coupling-purpose rivet pins inserted respectively through the pluralities of the fourth riveting-purpose through-holes of the pair of front mounting plates and the both end portions of the plurality of flange joining-purpose rivet pins inserted respectively through the pluralities of joining-purpose through-holes of the pair of half bodies.
