

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279376

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

KE; Chung-Yu et al.

ELECTRONIC PACKAGE AND MANUFACTURING METHOD THEREOF

Abstract

An electronic package is provided, in which a plurality of antenna structures and a heat sink are integrated on a package module including an electronic element, so as to guide the heat energy generated by the electronic element out of the package module via the heat sink. Therefore, when the electronic package is configured with the plurality of antenna structures, the heat dissipation of the electronic element can be improved.

Inventors: KE; Chung-Yu (Taichung City, TW), CHEN; Liang-Pin (Taichung City, TW)

Applicant: SILICONWARE PRECISION INDUSTRIES CO., LTD. (Taichung City, TW)

Family ID: 86689241

Assignee: SILICONWARE PRECISION INDUSTRIES CO., LTD. (Taichung City, TW)

Appl. No.: 19/209456

Filed: May 15, 2025

Foreign Application Priority Data

TW

111119694

May. 26, 2022

Related U.S. Application Data

parent US continuation 17858905 20220706 parent-grant-document US 12334456 child US 19209456

Publication Classification

Int. Cl.: H01L23/66 (20060101); **H01L21/48** (20060101); **H01L23/00** (20060101); **H01L23/367** (20060101); **H01L23/373** (20060101); **H01L25/065** (20230101); **H01Q1/22** (20060101)

U.S. Cl.:

CPC H01L23/66 (20130101); **H01L21/4882** (20130101); **H01L23/367** (20130101); **H01L23/3736** (20130101); **H01Q1/2283** (20130101); H01L24/16 (20130101); H01L24/32 (20130101); H01L24/73 (20130101); H01L25/0655 (20130101); H01L2223/6616 (20130101); H01L2223/6688 (20130101); H01L2224/16237 (20130101); H01L2224/32225 (20130101); H01L2224/73204 (20130101); H01L2924/2027 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation of U.S. patent application Ser. No. 17/858,905 filed Jul. 6, 2022, which claims benefit of priority to Taiwanese Patent Application No. 111119694 filed May 26, 2022, the entire contents of which are incorporated herein by reference.

BACKGROUND

1. Technical Field

[0002] The present disclosure relates to an electronic package, and more particularly, to an electronic package having an antenna structure and a manufacturing method thereof.

2. Description of Related Art

[0003] At present, wireless communication technology has been widely used in various consumer electronic products (such as mobile phones, tablet computers, etc.) to facilitate receiving or sending various wireless signals. In addition, in order to meet the portability of consumer electronic products and the convenience of surfing the Internet, the manufacture and design of wireless communication modules are developed towards the needs of light, thin, short and small, wherein patch antennas are widely used in wireless communication modules of electronic products due to their characteristics of small size, light weight and easy manufacture.

[0004] At present, the related application technology of 5G will be fully commercialized in the future, and its application frequency range is about 1 GHz to 1000 GHz high-frequency frequency band, and its commercial application mode is 5G with 4G LTE, and a cellular base station is set up outdoors so as to cooperate with the small base station located indoors. Therefore, 5G mobile communication will use a large number of antennas in the base station to meet the requirements of the 5G system for large-capacity, fast transmission and low latency.

[0005] FIG. 1A is a schematic perspective view of a conventional semiconductor package **1** having an antenna structure. As shown in FIG. 1, the semiconductor package **1** comprises: a semiconductor chip **11** having a plurality of electrode pads **110**, a plurality of conductive pillars **13**, a cladding layer **15** covering the semiconductor chip **11** and the plurality of conductive pillars **13**, a carrier structure **10** and a circuit structure **16** arranged on opposite sides of the cladding layer **15** to be electrically connected to each other via the plurality of conductive pillars **13**, a plurality of conductive elements **17** disposed on the carrier structure **10** to connect to a circuit board **8**, an insulating spacer **14** disposed on the circuit structure **16** by a bonding layer **12**, a plurality of first antenna bodies **18b** disposed on the circuit structure **16** by the bonding layer **12**, and a plurality of second antenna bodies **19b** disposed on the insulating spacer **14**.

[0006] The electrode pads **110** of the semiconductor chip **11** are provided with conductive bumps **112** to electrically connect the circuits of the carrier structure **10**, and during the manufacturing

process, the conductive bumps **112** can be covered with a protective film **114** according to requirements.

[0007] The carrier structure **10** is provided with a first antenna layer **18a**, and the circuit structure **16** is provided with a second antenna layer **19a**, so that the first antenna bodies **18b** correspond to the position of the first antenna layer **18a** to form a low-frequency antenna structure **18**, and the second antenna bodies **19b** correspond to the position of the second antenna layer **19a** to form a high-frequency antenna structure **19** surrounded by the low-frequency antenna structure **18**, as shown in FIG. **1B**, and the semiconductor chip **11** controls the operations of the low-frequency antenna structure **18** and the high-frequency antenna structure **19**.

[0008] However, in the conventional semiconductor package **1**, the semiconductor chip **11** is embedded in the cladding layer **15**, resulting in poor heat dissipation, which affects the semiconductor chip **11** to provide electrical functions required for operating a 5G system. It cannot even meet the requirements of the antenna operation of the 5G system.

[0009] Furthermore, in the conventional semiconductor package **1**, the conductive pillars **13** are disposed at the periphery of the semiconductor chip **11**, so that the high-frequency antenna structure **19** cannot be superimposed above the conductive pillars **13**. Therefore, when the signal of the high-frequency antenna structure **19** needs to be transmitted to the circuit board **8** via the conductive pillars **13**, the signal needs to be fanned out to the periphery of a vertical projection area **Z** of the high-frequency antenna structure **19** via the circuit structure **16**. At this point, the path (the signal path **L1** shown in FIG. **1A**) of the high-frequency antenna structure **19** for transmitting the antenna signal is too long, resulting in the transmission speed of the antenna signal being too slow.

[0010] Therefore, how to overcome the above-mentioned drawbacks of the prior art has become an urgent issue to be solved at present.

SUMMARY

[0011] In view of the various deficiencies of the prior art, the present disclosure provides an electronic package, which comprises: a package module internally configured with at least one electronic element and a plurality of feeding lines electrically connected to the at least one electronic element, wherein the plurality of feeding lines are defined with a first antenna layer and a second antenna layer; a heat sink disposed on a portion of a surface of the package module and extending into the package module to thermally connect the at least one electronic element; first antenna bodies disposed on portions of the surface of the package module corresponding to a position of the first antenna layer, wherein the first antenna bodies and the first antenna layer are kept at a distance, such that the first antenna bodies and the first antenna layer form a first antenna structure; an insulating spacer disposed on a portion of the surface of the package module; and second antenna bodies disposed on the insulating spacer corresponding to a position of the second antenna layer, wherein the second antenna bodies and the second antenna layer are located on opposite sides of the insulating spacer, such that the second antenna bodies and the second antenna layer form a second antenna structure.

[0012] The present disclosure provides a method of manufacturing an electronic package, the method comprises: providing a package module internally configured with at least one electronic element and a plurality of feeding lines electrically connected to the at least one electronic element, wherein the plurality of feeding lines are defined with a first antenna layer and a second antenna layer; disposing an insulating spacer on a portion of a surface of the package module; forming a heat sink on a portion of the surface of the package module, wherein the heat sink extends into the package module to thermally connect the at least one electronic element; and forming first antenna bodies on portions of the surface of the package module corresponding to a position of the first antenna layer and forming second antenna bodies on the insulating spacer corresponding to a position of the second antenna layer, wherein the first antenna bodies and the first antenna layer are kept at a distance, such that the first antenna bodies and the first antenna layer form a first antenna structure, and wherein the second antenna bodies and the second antenna layer are located on

opposite sides of the insulating spacer, such that the second antenna bodies and the second antenna layer form a second antenna structure.

[0013] In the aforementioned manufacturing method, the manufacturing process of the heat sink comprises: forming a recess portion in the package module to expose the at least one electronic element; and forming a metal material in the recess portion and protruding from the surface of the package module, so that the metal material becomes the heat sink.

[0014] In the aforementioned electronic package and the manufacturing method thereof, the heat sink is annular.

[0015] In the aforementioned electronic package and the manufacturing method thereof, the heat sink surrounds the insulating spacer.

[0016] In the aforementioned electronic package and the manufacturing method thereof, the insulating spacer is a dielectric layer.

[0017] In the aforementioned electronic package and the manufacturing method thereof, the first antenna bodies and the first antenna layer transmit signals in a coupled manner.

[0018] In the aforementioned electronic package and the manufacturing method thereof, the second antenna bodies and the second antenna layer transmit signals in a coupled manner.

[0019] In the aforementioned electronic package and the manufacturing method thereof, the package module includes a cladding layer covering the at least one electronic element, wherein the first antenna bodies and the first antenna layer are located on opposite sides of the cladding layer. Further, the package module further includes a plurality of conductive pillars embedded in the cladding layer and a first circuit structure and a second circuit structure disposed on the opposite sides of the cladding layer to be electrically connected to each other via the plurality of conductive pillars, wherein the first circuit structure is provided with the first antenna layer, and the second circuit structure is provided with the second antenna layer, such that the insulating spacer and the first antenna bodies are disposed on one surface of the second circuit structure. For example, a plurality of the electronic elements are embedded in the cladding layer, such that the plurality of conductive pillars are located between at least two of the electronic elements; or, the second antenna structure is superimposed on the plurality of conductive pillars.

[0020] In the aforementioned electronic package and the manufacturing method thereof, the heat sink is in contact with the at least one electronic element.

[0021] As can be seen from the above, in the electronic package and the manufacturing method thereof of the present disclosure, the thermal energy generated by the electronic element is guided out of the package module via the heat sink, so that the electronic element can dissipate heat according to requirements. Therefore, compared with the prior art, when the electronic package is configured with a plurality of antenna structures, the heat dissipation of the electronic element can be improved, so that the electronic package can provide electrical functions required to operate the 5G system, so as to meet the requirements of the antenna operation of the 5G system.

[0022] Furthermore, by superimposing the second antenna structure on the plurality of conductive pillars, it is beneficial to reduce the path for the second antenna structure to transmit the antenna signal to the external circuit board, so that the transmission speed of the antenna signal can be increased.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] FIG. 1A is a schematic cross-sectional view of a conventional semiconductor package.

[0024] FIG. 1B is a schematic top plan view of FIG. 1A.

[0025] FIG. 2A to FIG. 2H are schematic cross-sectional views illustrating a method of manufacturing an electronic package according to the present disclosure.

[0026] FIG. 3 is a schematic top plan view of FIG. 2H.

DETAILED DESCRIPTIONS

[0027] The following describes the implementation of the present disclosure with examples. Those skilled in the art can easily understand other advantages and effects of the present disclosure from the contents disclosed in this specification.

[0028] It should be understood that, the structures, ratios, sizes, and the like in the accompanying figures are used for illustrative purposes to facilitate the perusal and comprehension of the contents disclosed in the present specification by one skilled in the art, rather than to limit the conditions for practicing the present disclosure. Any modification of the structures, alteration of the ratio relationships, or adjustment of the sizes without affecting the possible effects and achievable proposes should still be deemed as falling within the scope defined by the technical contents disclosed in the present specification. Meanwhile, terms such as “upper,” “first,” “second,” “one” and the like used herein are merely used for clear explanation rather than limiting the practicable scope of the present disclosure, and thus, alterations or adjustments of the relative relationships thereof without essentially altering the technical contents should still be considered in the practicable scope of the present disclosure.

[0029] FIG. 2A to FIG. 2H are schematic cross-sectional views illustrating a method of manufacturing an electronic package 2 according to the present disclosure.

[0030] As shown in FIG. 2A, a first circuit structure 20 disposed on a carrier board 9 is provided, and a plurality of conductive pillars 23 are formed on the first circuit structure 20.

[0031] In an embodiment, the first circuit structure 20 is, for example, a substrate structure, and the substrate structure is with a core layer or without a core layer (coreless), wherein the first circuit structure 20 may include at least one first insulating layer 200 and at least one first circuit layer 201 disposed on the first insulating layer 200. For example, the specification of the first circuit layer 201 is a redistribution layer (RDL), the material for forming the first circuit layer 201 is copper, and the material for forming the first insulating layer 200 is a dielectric material such as polybenzoxazole (PBO), polyimide (PI), prepreg (PP) and the like.

[0032] Furthermore, the first circuit structure 20 is further configured with a first antenna layer 28a electrically connected to the first circuit layer 201. For example, the first antenna layer 28a is fabricated together with the first circuit layer 201 by an RDL process.

[0033] In addition, the carrier board 9 is, for example, a board body made of semiconductor material (such as silicon or glass), on which a release layer 90 and an adhesive layer 91 are sequentially formed by coating for the first circuit structure 20 to be disposed on the adhesive layer 91.

[0034] In addition, the conductive pillars 23 are, for example, pillar bodies, linear bodies or spherical bodies, which are erected on the first circuit layer 201 and electrically connected to the first circuit layer 201, wherein the material for forming the conductive pillars 23 is a metal material such as copper or gold or a solder material, but is not limited to the above.

[0035] As shown in FIG. 2B, at least one electronic element 21 is disposed on the first circuit structure 20.

[0036] The electronic element 21 is an active element, a passive element, or a combination of the active element and the passive element, and the active element is such as a semiconductor chip, and the passive element is such as a resistor, a capacitor, or an inductor.

[0037] In an embodiment, the electronic element 21 is a semiconductor chip, which has an active surface 21a and an inactive surface 21b opposite to the active surface 21a, and the active surface 21a has a plurality of electrode pads (not shown), so that the electronic element 21 is bonded onto the first circuit structure 20 by a flip-chip method and its electrode pads are electrically connected to the first circuit layer 201 via a plurality of conductive bumps 212. Further, the conductive bumps 212 can be covered with a bonding layer 214 such as an underfill according to requirements.

[0038] Furthermore, if a plurality of the electronic elements 21 are provided, the plurality of

conductive pillars **23** can be located between at least two of the electronic elements **21**, so that an open area **S** without conductive material is formed on the periphery of a group where the plurality of electronic elements **21** are distributed.

[0039] As shown in FIG. 2C, a cladding layer **25** is formed on the first circuit structure **20**, so that the cladding layer **25** covers the electronic element **21**, the bonding layer **214** and the plurality of conductive pillars **23**, wherein the cladding layer **25** has a first surface **25a** and a second surface **25b** opposite to the first surface **25a**, and the cladding layer **25** is bonded to the first circuit structure **20** via the first surface **25a** thereof. Then, via a leveling process, the second surface **25b** of the cladding layer **25** is flush with end surfaces **23b** of the conductive pillars **23** (or the inactive surface **21b** of the electronic element **21**), so that the end surfaces **23b** of the conductive pillars **23** (or the inactive surface **21b** of the electronic element **21**) is exposed from the second surface **25b** of the cladding layer **25**.

[0040] In an embodiment, the cladding layer **25** is an insulating material, such as polyimide (PI), dry film, epoxy resin, or molding compound, which can be formed on the first circuit structure **20** by lamination or molding.

[0041] Furthermore, the leveling process is to remove a portion of the material of each of the conductive pillars **23** and a portion of the material of the cladding layer **25** (even removing a portion of the material of the inactive surface **21b** of the electronic element **21**) by grinding, so that the second surface **25b** of the cladding layer **25** and the end surfaces **23b** of the conductive pillars **23** (or the inactive surface **21b** of the electronic element **21**) are coplanar.

[0042] As shown in FIG. 2D, a second circuit structure **26** is formed on the second surface **25b** of the cladding layer **25**, and the second circuit structure **26** is electrically connected to the conductive pillars **23**, so that the second circuit structure **26** is stacked on the first circuit structure **20** to form a package module **2a**.

[0043] In an embodiment, the second circuit structure **26** includes a second insulating layer **260** and a second circuit layer **261** such as RDL disposed on the second insulating layer **260**, so that the second circuit layer **261** is electrically connected to the plurality of conductive pillars **23**.

Alternatively, the second circuit structure **26** may also include a plurality of second insulating layers **260** and a plurality of second circuit layers **261**.

[0044] Further, the material for forming the second circuit layer **261** is copper, and the material for forming the second insulating layer **260** is a dielectric material such as polybenzoxazole (PBO), polyimide (PI), prepreg (PP) and the like.

[0045] In addition, the second circuit structure **26** is further configured with a second antenna layer **29a** electrically connected to the second circuit layer **261**. For example, the second antenna layer **29a** is fabricated together with the second circuit layer **261** by an RDL process.

[0046] It should be understood that there are various types of package modules **2a**, which are not limited to the above, and are hereby described.

[0047] As shown in FIG. 2E, an insulating spacer **24** is formed on the second circuit structure **26**, and a recess portion **A** exposing the electronic element **21** is formed in the second circuit structure **26**.

[0048] In an embodiment, the insulating spacer **24** is a dielectric layer, which is a dielectric material such as polyimide (PI), dry film, or molding compound and the like, but is not limited to the above. For example, a dielectric layer is first coated on the entire surface of the second circuit structure **26**, and then a portion of the material of the dielectric layer is removed by etching to form the insulating spacer **24**.

[0049] Furthermore, the recess portion **A** penetrates through the second circuit structure **26** to expose the inactive surface **21b** of the electronic element **21**; it should be understood that if the cladding layer **25** covers the inactive surface **21b** of the electronic element **21**, the recess portion **A** needs to extend into the second surface **25b** of the cladding layer **25**, so that the inactive surface **21b** of the electronic element **21** is exposed from the recess portion **A**.

[0050] As shown in FIG. 2F, a heat sink **22** is formed in the recess portion A, so that the heat sink **22** is thermally connected to the electronic element **21**, and the heat sink **22** protrudes from the second circuit structure **26** (or the surface of the package module **2a**).

[0051] In an embodiment, the heat sink **22** is made of a metal material such as copper, and the recess portion A is an annular groove, so that the heat sink **22** is annular so as to surround the insulating spacer **24**, as shown in FIG. 3.

[0052] As shown in FIG. 2G, first antenna bodies **28b** corresponding to the first antenna layer **28a** are formed on portions of the surface of the second insulating layer **260** of the second circuit structure **26**, so that a first antenna structure **28** is formed by keeping a distance between the first antenna bodies **28b** and the first antenna layer **28a**, and second antenna bodies **29b** corresponding to the second antenna layer **29a** are formed on the insulating spacer **24**, so that a second antenna structure **29** is formed such that the second antenna bodies **29b** and the second antenna layer **29a** are located on opposite sides of the insulating spacer **24**, and the first antenna bodies **28b** surround the second antenna bodies **29b**, as shown in FIG. 3.

[0053] In an embodiment, taking the 6 gigahertz (GHz) frequency band as a boundary, the first antenna structure **28** is a low-frequency band antenna, that is, below 6 GHz (commonly known as Sub-6 GHz), and the second antenna structure **29** is a high-frequency band antenna, that is, higher than 6 GHz. For example, the electronic element **21** transmits and receives low-frequency 5G millimeter-wave signals with frequencies of Sub-6 GHz (about 410-7125 megahertz [MHz]) via the first antenna structure **28**, and the electronic element **21** transmits and receives high-frequency 5G millimeter-wave (mmWave) signals with frequencies of 24-53 gigahertz (GHz) via the second antenna structure **29**.

[0054] Furthermore, the first antenna bodies **28b** and the first antenna layer **28a** transmit signals in a coupled manner, and the first antenna layer **28a** is used as a feeding line of the first antenna structure **28**. In addition, the second antenna bodies **29b** and the second antenna layer **29a** also transmit signals in a coupled manner, and the second antenna layer **29a** is used as a feeding line of the second antenna structure **29**. For example, the antenna layer and the antenna bodies can generate radiated energy from alternating voltage, alternating current, or radiation changes, and the radiated energy is an electromagnetic field, so that the antenna layer and the antenna bodies can be electromagnetically coupled to each other, so that the antenna signal can be transmitted between the antenna layer and the antenna bodies. In addition, there is no other metal layer between the first antenna layer **28a** and the first antenna bodies **28b**, such as the intervals corresponding to the upper and lower parts of the open area S.

[0055] In addition, dielectric regions of the high-frequency band antenna (such as the insulating spacer **24** and the second insulating layer **260**) should have a dielectric coefficient less than 3, for example, SiLK, MSQ, PI (including Nano air, fluorine group), or other suitable materials; on the other hand, dielectric regions of the low-frequency band antenna (such as the second insulating layer **260**, the cladding layer **25** and the first insulating layer **200**) should have a dielectric coefficient less than 3.7, for example, epoxy resin, PI, or other suitable materials.

[0056] In addition, the first antenna bodies **28b** and the second antenna bodies **29b** can be fabricated by means of sputtering, vapor deposition, electroplating, electroless plating, plating, or foiling, etc., so that the first antenna bodies **28b** are located outside the ring of the heat sink **22**, and the second antenna bodies **29b** are located inside the ring of the heat sink **22**.

[0057] As shown in FIG. 2H, the carrier board **9** and the release layer **90** and the adhesive layer **91** thereon are removed to expose the first circuit structure **20** for forming a plurality of conductive elements **27** such as solder balls on the first circuit layer **201** of the first circuit structure **20** to obtain the electronic package **2** of the present disclosure, so that the electronic package **2** can be mounted on the circuit board **8** via the conductive elements **27** in the subsequent process.

[0058] In an embodiment, an Under Bump Metallurgy (UBM) layer may be formed on the first circuit layer **201** according to requirements to facilitate the bonding of the conductive elements **27**.

[0059] Therefore, in the manufacturing method of the present disclosure, the heat sink **22** extends and protrudes from the package module **2a**, so as to guide the thermal energy generated by the electronic element **21** out of the package module **2a**, so that the electronic element **21** can dissipate heat according to requirements. Therefore, compared with the prior art, when the electronic package **2** is configured with the first antenna structure **28** and the second antenna structure **29**, the heat dissipation required by the electronic element **21** can still be met, so that the electronic package **2** is made to provide electrical functions required for operating the 5G system, so as to meet the requirements of the antenna operation of the 5G system.

[0060] Furthermore, by disposing the conductive pillars **23** between two electronic elements **21**, the second antenna structure **29** is superimposed on the conductive pillars **23** and the electronic elements **21**, so as to facilitate reducing the path of the second antenna structure **29** transmitting the antenna signal to the circuit board **8** (the conductive elements **27**), such that the transmission speed of the antenna signal can be increased. For example, the signal of the second antenna structure **29** can be transmitted to the circuit board **8** via the conductive pillars **23** below the second antenna structure **29**, and a path of the second antenna structure **29** passing through the second circuit structure **26** (a signal path L2 shown in FIG. 2H) is located within a vertical projection area P of the second antenna structure **29** without fanning out to the periphery of the vertical projection area P of the second antenna structure **29**, thereby greatly reducing the path for transmitting the antenna signal of the second antenna structure **29**.

[0061] Furthermore, the configuration of the insulating spacer **24** facilitates the integration of the first antenna structure **28** and the second antenna structure **29** on the package module **2a** without interfering with each other, so that the electronic package **2** can send/receive different antenna signals according to requirements. Therefore, the electronic package **2** can be configured with antenna structures including multiple frequencies, so that a single electronic package **2** can meet the needs of radio-frequency products with multiple frequencies.

[0062] The present disclosure further provides an electronic package **2**, which comprises: a package module **2a**, at least one heat sink **22**, an insulating spacer **24**, first antenna bodies **28b** and second antenna bodies **29b**.

[0063] The package module **2a** is internally configured with at least one electronic element **21** and a plurality of feeding lines electrically connected to the electronic element **21**, wherein the plurality of feeding lines are defined with a first antenna layer **28a** and a second antenna layer **29a**.

[0064] The heat sink **22** is disposed on a portion of the surface of the package module **2a** and extends into the package module **2a** to thermally connect the electronic element **21**.

[0065] The first antenna bodies **28b** are disposed on portions of the surface of the package module **2a** corresponding to the position of the first antenna layer **28a**, and a distance is maintained between the first antenna bodies **28b** and the first antenna layer **28a**, so that the first antenna bodies **28b** and the first antenna layer **28a** form a first antenna structure **28**.

[0066] The insulating spacer **24** is disposed on a portion of the surface of the package module **2a**.

[0067] The second antenna bodies **29b** are disposed on the insulating spacer **24** corresponding to the position of the second antenna layer **29a**, and the second antenna bodies **29b** and the second antenna layer **29a** are located on opposite sides of the insulating spacer **24**, so that the second antenna structure **29** is formed by the second antenna bodies **29b** and the second antenna layer **29a**.

[0068] In one embodiment, the heat sink **22** is annular.

[0069] In one embodiment, the heat sink **22** surrounds the insulating spacer **24**.

[0070] In one embodiment, the first antenna bodies **28b** and the first antenna layer **28a** transmit signals in a coupled manner.

[0071] In one embodiment, the insulating spacer **24** is a dielectric layer.

[0072] In one embodiment, the second antenna bodies **29b** and the second antenna layer **29a** transmit signals in a coupled manner.

[0073] In one embodiment, the package module **2a** includes a cladding layer **25** covering the

electronic element **21**, so that the first antenna bodies **28b** and the first antenna layer **28a** are located on opposite sides of the cladding layer **25**. Further, the package module **2a** further includes a plurality of conductive pillars **23**, which are embedded in the cladding layer **25**, and a first circuit structure **20** and a second circuit structure **26**, which are disposed on opposite sides of the cladding layer **25** to be electrically connected to each other via the plurality of conductive pillars **23**, so that the first circuit structure **20** is provided with the first antenna layer **28a**, and the second circuit structure **26** is provided with the second antenna layer **29a**, such that the insulating spacer **24** and the first antenna bodies **28b** are disposed on one surface of the second circuit structure **20**. For example, a plurality of the electronic elements **21** are embedded in the cladding layer **25**, so that the plurality of conductive pillars **23** are located between at least two of the electronic elements **21**; or, the second antenna structure **29** is superimposed on the conductive pillars **23**.

[0074] In one embodiment, the heat sink **22** is in contact with the electronic element **21**.

[0075] To sum up, the electronic package and the manufacturing method thereof of the present disclosure facilitate the heat dissipation of the electronic element by the design of the heat sink. Therefore, when the electronic product using this electronic package operates the antenna function of various frequencies, it can maintain the normal radio-frequency function and will not cause poor conditions due to overheating.

[0076] Furthermore, by superimposing the second antenna structure on the plurality of conductive pillars, it is beneficial to reduce the path for the second antenna structure to transmit the antenna signal to the external circuit board, so that the transmission speed of the antenna signal can be increased.

[0077] The foregoing embodiments are provided for the purpose of illustrating the principles and effects of the present disclosure, rather than limiting the present disclosure. Anyone skilled in the art can modify and alter the above embodiments without departing from the spirit and scope of the present disclosure. Therefore, the scope of protection with regard to the present disclosure should be as defined in the accompanying claims listed below.

Claims

1. An electronic package, comprising: a package module internally configured with at least one electronic element and a plurality of feeding lines electrically connected to the at least one electronic element, wherein the plurality of feeding lines are defined with a first antenna layer and a second antenna layer; a heat sink disposed on an inactive surface of the at least one electronic element and thermally connected to the at least one electronic element; and an insulating spacer disposed on a portion of a surface of the package module.
2. The electronic package of claim 1, wherein the heat sink is annular.
3. The electronic package of claim 1, wherein the heat sink surrounds the insulating spacer.
4. The electronic package of claim 1, wherein the insulating spacer is a dielectric layer.
5. The electronic package of claim 1, further comprising: first antenna bodies disposed on portions of the surface of the package module corresponding to a position of the first antenna layer, wherein the first antenna bodies and the first antenna layer are kept at a distance, such that the first antenna bodies and the first antenna layer form a first antenna structure; and second antenna bodies disposed on the insulating spacer corresponding to a position of the second antenna layer, wherein the second antenna bodies and the second antenna layer are located on opposite sides of the insulating spacer, such that the second antenna bodies and the second antenna layer form a second antenna structure.
6. The electronic package of claim 5, wherein the first antenna bodies and the first antenna layer and the second antenna bodies and the second antenna layer transmit signals in a coupled manner.
7. The electronic package of claim 5, wherein the package module includes a cladding layer covering the at least one electronic element, and wherein the first antenna bodies and the first

antenna layer are located on opposite sides of the cladding layer.

8. The electronic package of claim 7, wherein the package module further includes a plurality of conductive pillars embedded in the cladding layer and a first circuit structure and a second circuit structure disposed on the opposite sides of the cladding layer to be electrically connected to each other via the plurality of conductive pillars, and wherein the first circuit structure is provided with the first antenna layer, and the second circuit structure is provided with the second antenna layer, such that the insulating spacer and the first antenna bodies are disposed on one surface of the second circuit structure.

9. The electronic package of claim 8, wherein the second antenna structure is superimposed on the plurality of conductive pillars.

10. The electronic package of claim 8, wherein a plurality of the electronic elements are embedded in the cladding layer, such that the plurality of conductive pillars are located between at least two of the electronic elements.

11. The electronic package of claim 1, wherein the heat sink is in contact with the at least one electronic element.

12. A method of manufacturing an electronic package, comprising: providing a package module internally configured with at least one electronic element and a plurality of feeding lines electrically connected to the at least one electronic element, wherein the plurality of feeding lines are defined with a first antenna layer and a second antenna layer; disposing an insulating spacer on a portion of a surface of the package module; and forming a heat sink on an inactive surface of the at least one electronic element, wherein the heat sink is thermally connected to the at least one electronic element.

13. The method of claim 12, wherein the heat sink is annular.

14. The method of claim 12, wherein the heat sink surrounds the insulating spacer.

15. The method of claim 12, wherein the insulating spacer is a dielectric layer.

16. The method of claim 12, further comprising: forming first antenna bodies on portions of the surface of the package module corresponding to a position of the first antenna layer and forming second antenna bodies on the insulating spacer corresponding to a position of the second antenna layer, wherein the first antenna bodies and the first antenna layer are kept at a distance, such that the first antenna bodies and the first antenna layer form a first antenna structure, and wherein the second antenna bodies and the second antenna layer are located on opposite sides of the insulating spacer, such that the second antenna bodies and the second antenna layer form a second antenna structure.

17. The method of claim 16, wherein the first antenna bodies and the first antenna layer and the second antenna bodies and the second antenna layer transmit signals in a coupled manner.

18. The method of claim 16, wherein the package module includes a cladding layer covering the at least one electronic element, and wherein the first antenna bodies and the first antenna layer are located on opposite sides of the cladding layer.

19. The method of claim 18, wherein the package module further includes a plurality of conductive pillars embedded in the cladding layer and a first circuit structure and a second circuit structure disposed on the opposite sides of the cladding layer to be electrically connected to each other via the plurality of conductive pillars, and wherein the first circuit structure is provided with the first antenna layer, and the second circuit structure is provided with the second antenna layer, such that the insulating spacer and the first antenna bodies are disposed on one surface of the second circuit structure.

20. The method of claim 19, wherein a plurality of the electronic elements are embedded in the cladding layer, such that the plurality of conductive pillars are located between at least two of the electronic elements.

21. The method of claim 19, wherein the second antenna structure is superimposed on the plurality of conductive pillars.

22. The method of claim 12, wherein the heat sink is in contact with the at least one electronic element.

23. The method of claim 12, wherein a manufacturing process of the heat sink comprises: forming a recess portion in the package module to expose the at least one electronic element; and forming a metal material in the recess portion and protruding from the surface of the package module, so that the metal material becomes the heat sink.
