

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280189

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

O'LEARY; Fiona Paula et al.

USER INTERFACES FOR WIDE ANGLE VIDEO CONFERENCE

Abstract

The present disclosure generally relates to embodiments for video communication interfaces for automatically adjusting a displayed representation of a field-of-view of a camera in response to detecting a change in a scene.

Inventors: O'LEARY; Fiona Paula (Palo Alto, CA), ALDAN; Ali-Amir (Sunnyvale, CA), ARDAUD; Guillaume (San Francisco, CA), CHANG; Jae Woo (Los Altos Hills, CA), MANZARI; Johnnie B. (San Francisco, CA), MISSIG; Julian (Redwood City, CA), YELLAMRAJU; Siva Kiran (Palo Alto, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 87558290

Appl. No.: 19/189639

Filed: April 25, 2025

Related U.S. Application Data

parent US continuation 18138348 20230424 parent-grant-document US 12301979 child US 19189639

parent US continuation 17482977 20210923 parent-grant-document US 11671697 child US 18138348

us-provisional-application US 63176811 20210419

us-provisional-application US 63143881 20210131

Publication Classification

Int. Cl.: H04N23/62 (20230101); G06F3/04842 (20220101); G06F3/04845 (20220101); G06F3/04883 (20220101); G06T7/20 (20170101); G10L21/0208 (20130101);

U.S. Cl.:

CPC **H04N23/62** (20230101); **G06F3/04845** (20130101); **G06F3/04883** (20130101);
G06T7/20 (20130101); **G10L21/0208** (20130101); **H04L65/403** (20130101);
H04N5/2621 (20130101); **H04N5/2628** (20130101); **H04N5/272** (20130101);
H04N23/611 (20230101); **H04N23/667** (20230101); **H04N23/69** (20230101);
G06F3/04842 (20130101); G06T2207/10016 (20130101); G06T2207/30196 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/138,348, entitled “USER INTERFACES FOR WIDE ANGLE VIDEO CONFERENCE,” filed Apr. 24, 2023, which is a continuation of U.S. patent application Ser. No. 17/482,977 (now U.S. Pat. No. 11,671,697), entitled “USER INTERFACES FOR WIDE ANGLE VIDEO CONFERENCE,” filed Sep. 23, 2021, which claims priority to U.S. Provisional Patent Application No. 63/176,811, entitled “USER INTERFACES FOR WIDE ANGLE VIDEO CONFERENCE,” filed Apr. 19, 2021, and U.S. Provisional Patent Application No. 63/143,881, entitled “USER INTERFACES FOR WIDE ANGLE VIDEO CONFERENCE,” filed Jan. 31, 2021, the contents of each of which are hereby incorporated by reference in their entireties for all purposes.

FIELD

[0002] The present disclosure relates generally to computer user interfaces, and more specifically to techniques for managing a live video communication session.

BACKGROUND

[0003] Computer systems can include hardware and/or software for displaying an interface for a live video communication session.

BRIEF SUMMARY

[0004] Some techniques for managing a live video communication session using electronic devices, however, are generally cumbersome and inefficient. For example, some existing techniques use a complex and time-consuming user interface, which may include multiple key presses or keystrokes. Existing techniques require more time than necessary, wasting user time and device energy. This latter consideration is particularly important in battery-operated devices.

[0005] Accordingly, the present technique provides electronic devices with faster, more efficient methods and interfaces for managing a live video communication session. Such methods and interfaces optionally complement or replace other methods for managing a live video communication session. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. For battery-operated computing devices, such methods and interfaces conserve power and increase the time between battery charges.

[0006] Example methods are described herein. An example method includes, at a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices: displaying, via the display generation component, a communication request interface that includes: a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras during a live video communication session; while displaying the communication request interface, receiving, via the

one or more input devices, a set of one or more inputs that includes a selection of the first selectable graphical user interface object; in response to receiving the set of one or more inputs that includes a selection of the first selectable graphical user interface object, displaying, via the display generation component, a live video communication interface for the live video communication session; while displaying the live video communication interface, detecting a change in a scene in the field-of-view of the one or more cameras; and in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting a representation of the field-of-view of the one or more cameras during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting a representation of the field-of-view of the one or more cameras during the live video communication session.

[0007] Example non-transitory computer-readable storage media are described herein. An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices. The one or more programs include instructions for: displaying, via the display generation component, a communication request interface that includes: a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras during a live video communication session; while displaying the communication request interface, receiving, via the one or more input devices, a set of one or more inputs that includes a selection of the first selectable graphical user interface object; in response to receiving the set of one or more inputs that includes a selection of the first selectable graphical user interface object, displaying, via the display generation component, a live video communication interface for the live video communication session; while displaying the live video communication interface, detecting a change in a scene in the field-of-view of the one or more cameras; and in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting a representation of the field-of-view of the one or more cameras during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting a representation of the field-of-view of the one or more cameras during the live video communication session.

[0008] Example transitory computer-readable storage media are described herein. An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices. The one or more programs include instructions for: displaying, via the display generation component, a communication request interface that includes: a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras during a live video communication session; while displaying the communication request interface, receiving, via the one or more input devices, a set of one or more inputs that includes a selection of the first selectable graphical user interface object; in response to receiving the set of one or more inputs that includes a selection of the first selectable graphical user interface object, displaying, via the display generation component, a live video communication interface for the live video communication session; while displaying the live video communication interface, detecting a

change in a scene in the field-of-view of the one or more cameras; and in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting a representation of the field-of-view of the one or more cameras during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting a representation of the field-of-view of the one or more cameras during the live video communication session.

[0009] Example computer systems are described herein. An example computer system includes: a display generation component; one or more cameras; one or more input devices; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors. The one or more programs include instructions for: displaying, via the display generation component, a communication request interface that includes: a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras during a live video communication session; while displaying the communication request interface, receiving, via the one or more input devices, a set of one or more inputs that includes a selection of the first selectable graphical user interface object; in response to receiving the set of one or more inputs that includes a selection of the first selectable graphical user interface object, displaying, via the display generation component, a live video communication interface for the live video communication session; while displaying the live video communication interface, detecting a change in a scene in the field-of-view of the one or more cameras; and in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting a representation of the field-of-view of the one or more cameras during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting a representation of the field-of-view of the one or more cameras during the live video communication session.

[0010] An example computer system includes: a display generation component; one or more cameras; one or more input devices; means for displaying, via the display generation component, a communication request interface that includes: a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras during a live video communication session; means for, while displaying the communication request interface, receiving, via the one or more input devices, a set of one or more inputs that includes a selection of the first selectable graphical user interface object; means for, in response to receiving the set of one or more inputs that includes a selection of the first selectable graphical user interface object, displaying, via the display generation component, a live video communication interface for the live video communication session; means for, while displaying the live video communication interface, detecting a change in a scene in the field-of-view of the one or more cameras; and means for in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting a representation of the field-of-view of the one or more cameras during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting a representation of the field-of-view of the one or more cameras during the live video communication session.

[0011] An example method includes, at a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices: displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including concurrently displaying: a representation of one or more participants in the live video communication session other than participants visible via the one or more cameras; and a representation of a field-of-view of the one or more cameras that is visually associated with a visual indication of an option to change the representation of the field-of-view of the one or cameras during the live video communication session; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to initiate a process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session; and in response to detecting the set of one or more inputs, initiating the process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session.

[0012] An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices. The one or more programs include instructions for: displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including concurrently displaying: a representation of one or more participants in the live video communication session other than participants visible via the one or more cameras; and a representation of a field-of-view of the one or more cameras that is visually associated with a visual indication of an option to change the representation of the field-of-view of the one or cameras during the live video communication session; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to initiate a process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session; and in response to detecting the set of one or more inputs, initiating the process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session.

[0013] An example transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices. The one or more programs include instructions for: displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including concurrently displaying: a representation of one or more participants in the live video communication session other than participants visible via the one or more cameras; and a representation of a field-of-view of the one or more cameras that is visually associated with a visual indication of an option to change the representation of the field-of-view of the one or cameras during the live video communication session; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to initiate a process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session; and in response to detecting the set of one or more inputs, initiating the process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session.

[0014] An example computer system includes: a display generation component; one or more cameras; one or more input devices; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors. The one or more programs include instructions for: displaying, via the display generation component, a live video

communication interface for a live video communication session, the live video communication interface including concurrently displaying: a representation of one or more participants in the live video communication session other than participants visible via the one or more cameras; and a representation of a field-of-view of the one or more cameras that is visually associated with a visual indication of an option to change the representation of the field-of-view of the one or cameras during the live video communication session; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to initiate a process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session; and in response to detecting the set of one or more inputs, initiating the process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session.

[0015] An example computer system includes: a display generation component; one or more cameras; one or more input devices; means for displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including concurrently displaying: a representation of one or more participants in the live video communication session other than participants visible via the one or more cameras; and a representation of a field-of-view of the one or more cameras that is visually associated with a visual indication of an option to change the representation of the field-of-view of the one or cameras during the live video communication session; and means for, while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to initiate a process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session; and means for, in response to detecting the set of one or more inputs, initiating the process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session.

[0016] An example method includes, at a computer system that is in communication with a display generation component and one or more cameras: displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including one or more representations of a field-of-view of the one or more cameras; while the live video communication session is active, capturing, via the one or more cameras, image data for the live video communication session; in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that an amount of separation between a first participant and a second participant meets separation criteria, concurrently displaying, via the display generation component: a representation of a first portion of the field-of-view of the one or more cameras at a first region of the live video communication interface; and a representation of a second portion of the field-of-view of the one or more cameras at a second region of the live video communication interface that is distinct from the first region, wherein the representation of the first portion of the field-of-view of the one or more cameras and the representation of the second portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a third portion of the field-of-view of the one or more cameras that is in between the first portion of the field-of-view of the one or more cameras and the second portion of the field-of-view of the one or more cameras; and in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that the amount of separation between the first participant and the second participant does not meet the separation criteria, displaying, via the display generation component, a representation of a fourth portion of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant.

[0017] An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras. The one or more programs include instructions for: displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including one or more representations of a field-of-view of the one or more cameras; while the live video communication session is active, capturing, via the one or more cameras, image data for the live video communication session; in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that an amount of separation between a first participant and a second participant meets separation criteria, concurrently displaying, via the display generation component: a representation of a first portion of the field-of-view of the one or more cameras at a first region of the live video communication interface; and a representation of a second portion of the field-of-view of the one or more cameras at a second region of the live video communication interface that is distinct from the first region, wherein the representation of the first portion of the field-of-view of the one or more cameras and the representation of the second portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a third portion of the field-of-view of the one or more cameras that is in between the first portion of the field-of-view of the one or more cameras and the second portion of the field-of-view of the one or more cameras; and in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that the amount of separation between the first participant and the second participant does not meet the separation criteria, displaying, via the display generation component, a representation of a fourth portion of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant.

[0018] An example transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more cameras. The one or more programs include instructions for: displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including one or more representations of a field-of-view of the one or more cameras; while the live video communication session is active, capturing, via the one or more cameras, image data for the live video communication session; in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that an amount of separation between a first participant and a second participant meets separation criteria, concurrently displaying, via the display generation component: a representation of a first portion of the field-of-view of the one or more cameras at a first region of the live video communication interface; and a representation of a second portion of the field-of-view of the one or more cameras at a second region of the live video communication interface that is distinct from the first region, wherein the representation of the first portion of the field-of-view of the one or more cameras and the representation of the second portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a third portion of the field-of-view of the one or more cameras that is in between the first portion of the field-of-view of the one or more cameras and the second portion of the field-of-view of the one or more cameras; and in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that the amount of separation between the first participant and the second participant does not meet the separation criteria, displaying, via the display generation component, a representation of a fourth portion of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a portion of

the field-of-view of the one or more cameras that is in between the first participant and the second participant.

[0019] An example computer system includes: a display generation component; one or more cameras; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors. The one or more programs include instructions for: displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including one or more representations of a field-of-view of the one or more cameras; while the live video communication session is active, capturing, via the one or more cameras, image data for the live video communication session; in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that an amount of separation between a first participant and a second participant meets separation criteria, concurrently displaying, via the display generation component: a representation of a first portion of the field-of-view of the one or more cameras at a first region of the live video communication interface; and a representation of a second portion of the field-of-view of the one or more cameras at a second region of the live video communication interface that is distinct from the first region, wherein the representation of the first portion of the field-of-view of the one or more cameras and the representation of the second portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a third portion of the field-of-view of the one or more cameras that is in between the first portion of the field-of-view of the one or more cameras and the second portion of the field-of-view of the one or more cameras; and in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that the amount of separation between the first participant and the second participant does not meet the separation criteria, displaying, via the display generation component, a representation of a fourth portion of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant.

[0020] An example computer system includes: a display generation component; one or more cameras; means for displaying, via the display generation component, a live video communication interface for a live video communication session, the live video communication interface including one or more representations of a field-of-view of the one or more cameras; means for, while the live video communication session is active, capturing, via the one or more cameras, image data for the live video communication session; means for, in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that an amount of separation between a first participant and a second participant meets separation criteria, concurrently displaying, via the display generation component: a representation of a first portion of the field-of-view of the one or more cameras at a first region of the live video communication interface; and a representation of a second portion of the field-of-view of the one or more cameras at a second region of the live video communication interface that is distinct from the first region, wherein the representation of the first portion of the field-of-view of the one or more cameras and the representation of the second portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a third portion of the field-of-view of the one or more cameras that is in between the first portion of the field-of-view of the one or more cameras and the second portion of the field-of-view of the one or more cameras; and means for, in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras, that the amount of separation between the first participant and the second participant does not meet the separation criteria, displaying, via the display generation component, a representation of a fourth portion of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a

portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant.

[0021] In accordance with some embodiments, a method performed at a computer system that is in communication with one or more output generation components and one or more input devices is described. The method comprises: detecting, via the one or more input devices, a request to display a system interface; in response to detecting the request to display the system interface, displaying, via the one or more output generation components, the system interface that includes a plurality of concurrently displayed controls for controlling different system functions of the computer system, including: in accordance with a determination that a media communication session has been active within a predetermined amount of time, the plurality of concurrently displayed controls includes a set of one or more media communication controls, wherein the media communication controls provide access to media communication settings that determine how media is handled by the computer system during media communication sessions; and in accordance with a determination that a media communication session has not been active within the predetermined amount of time, the plurality of concurrently displayed controls are displayed without the set of one or more media communication controls; while displaying the system interface having the set of one or more media communication controls, detecting, via the one or more input devices, a set of one or more inputs including an input directed to the set of one or more media communication controls; and in response to detecting the set of one or more inputs including the input directed to the set of one or more media communication controls when a respective media communication session has been active within the predetermined amount of time, adjusting the media communication settings for the respective media communication session.

[0022] In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with one or more output generation components and one or more input devices, the one or more programs including instructions for: detecting, via the one or more input devices, a request to display a system interface; in response to detecting the request to display the system interface, displaying, via the one or more output generation components, the system interface that includes a plurality of concurrently displayed controls for controlling different system functions of the computer system, including: in accordance with a determination that a media communication session has been active within a predetermined amount of time, the plurality of concurrently displayed controls includes a set of one or more media communication controls, wherein the media communication controls provide access to media communication settings that determine how media is handled by the computer system during media communication sessions; and in accordance with a determination that a media communication session has not been active within the predetermined amount of time, the plurality of concurrently displayed controls are displayed without the set of one or more media communication controls; while displaying the system interface having the set of one or more media communication controls, detecting, via the one or more input devices, a set of one or more inputs including an input directed to the set of one or more media communication controls; and in response to detecting the set of one or more inputs including the input directed to the set of one or more media communication controls when a respective media communication session has been active within the predetermined amount of time, adjusting the media communication settings for the respective media communication session.

[0023] In accordance with some embodiments, a transitory computer-readable storage medium is described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with one or more output generation components and one or more input devices, the one or more programs including instructions for: detecting, via the one or more input devices, a request to display a system interface; in response to detecting the request to display the system

interface, displaying, via the one or more output generation components, the system interface that includes a plurality of concurrently displayed controls for controlling different system functions of the computer system, including: in accordance with a determination that a media communication session has been active within a predetermined amount of time, the plurality of concurrently displayed controls includes a set of one or more media communication controls, wherein the media communication controls provide access to media communication settings that determine how media is handled by the computer system during media communication sessions; and in accordance with a determination that a media communication session has not been active within the predetermined amount of time, the plurality of concurrently displayed controls are displayed without the set of one or more media communication controls; while displaying the system interface having the set of one or more media communication controls, detecting, via the one or more input devices, a set of one or more inputs including an input directed to the set of one or more media communication controls; and in response to detecting the set of one or more inputs including the input directed to the set of one or more media communication controls when a respective media communication session has been active within the predetermined amount of time, adjusting the media communication settings for the respective media communication session.

[0024] In accordance with some embodiments, a computer system is described. The computer system comprises: one or more output generation components; one or more input devices; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: detecting, via the one or more input devices, a request to display a system interface; in response to detecting the request to display the system interface, displaying, via the one or more output generation components, the system interface that includes a plurality of concurrently displayed controls for controlling different system functions of the computer system, including: in accordance with a determination that a media communication session has been active within a predetermined amount of time, the plurality of concurrently displayed controls includes a set of one or more media communication controls, wherein the media communication controls provide access to media communication settings that determine how media is handled by the computer system during media communication sessions; and in accordance with a determination that a media communication session has not been active within the predetermined amount of time, the plurality of concurrently displayed controls are displayed without the set of one or more media communication controls; while displaying the system interface having the set of one or more media communication controls, detecting, via the one or more input devices, a set of one or more inputs including an input directed to the set of one or more media communication controls; and in response to detecting the set of one or more inputs including the input directed to the set of one or more media communication controls when a respective media communication session has been active within the predetermined amount of time, adjusting the media communication settings for the respective media communication session.

[0025] In accordance with some embodiments, a computer system is described. The computer system comprises: one or more output generation components; one or more input components; means for detecting, via the one or more input devices, a request to display a system interface; means, responsive to detecting the request to display the system interface, for displaying, via the one or more output generation components, the system interface that includes a plurality of concurrently displayed controls for controlling different system functions of the computer system, including: in accordance with a determination that a media communication session has been active within a predetermined amount of time, the plurality of concurrently displayed controls includes a set of one or more media communication controls, wherein the media communication controls provide access to media communication settings that determine how media is handled by the computer system during media communication sessions; and in accordance with a determination that a media communication session has not been active within the predetermined amount of time, the plurality of concurrently displayed controls are displayed without the set of one or more media

communication controls; means, while displaying the system interface having the set of one or more media communication controls, for detecting, via the one or more input devices, a set of one or more inputs including an input directed to the set of one or more media communication controls; and means, responsive to detecting the set of one or more inputs including the input directed to the set of one or more media communication controls when a respective media communication session has been active within the predetermined amount of time, for adjusting the media communication settings for the respective media communication session.

[0026] In accordance with some embodiments, a method performed at a computer system that is in communication with one or more output generation components, one or more cameras, and one or more input devices is described. The method comprises: displaying, via the one or more output generation components, a live video communication interface for a live video communication session, wherein displaying the live video communication interface includes concurrently displaying: a representation of a field-of-view of the one or more cameras of the computer system, wherein the representation of the field-of-view of the one or more cameras is visually associated with an indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras during the live video communication session; and a representation of one or more participants in the live video communication session that is different from the representation of the field-of-view of the one or more cameras of the computer system; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to change an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras; and in response to detecting the set of one or more inputs, changing the appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras.

[0027] In accordance with some embodiments, a non-transitory computer-readable storage medium is described. The non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with one or more output generation components, one or more cameras, and one or more input devices, the one or more programs including instructions for: displaying, via the one or more output generation components, a live video communication interface for a live video communication session, wherein displaying the live video communication interface includes concurrently displaying: a representation of a field-of-view of the one or more cameras of the computer system, wherein the representation of the field-of-view of the one or more cameras is visually associated with an indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras during the live video communication session; and a representation of one or more participants in the live video communication session that is different from the representation of the field-of-view of the one or more cameras of the computer system; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to change an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras; and in response to detecting the set of one or more inputs, changing the appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras.

[0028] In accordance with some embodiments, a transitory computer-readable storage medium is

described. The transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with one or more output generation components, one or more cameras, and one or more input devices, the one or more programs including instructions for: displaying, via the one or more output generation components, a live video communication interface for a live video communication session, wherein displaying the live video communication interface includes concurrently displaying: a representation of a field-of-view of the one or more cameras of the computer system, wherein the representation of the field-of-view of the one or more cameras is visually associated with an indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras during the live video communication session; and a representation of one or more participants in the live video communication session that is different from the representation of the field-of-view of the one or more cameras of the computer system; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to change an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras; and in response to detecting the set of one or more inputs, changing the appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras.

[0029] In accordance with some embodiments, a computer system is described. The computer system comprises: one or more output generation components; one or more cameras; one or more input devices; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying, via the one or more output generation components, a live video communication interface for a live video communication session, wherein displaying the live video communication interface includes concurrently displaying: a representation of a field-of-view of the one or more cameras of the computer system, wherein the representation of the field-of-view of the one or more cameras is visually associated with an indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras during the live video communication session; and a representation of one or more participants in the live video communication session that is different from the representation of the field-of-view of the one or more cameras of the computer system; and while displaying the live video communication interface for the live video communication session, detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to change an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras; and in response to detecting the set of one or more inputs, changing the appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras.

[0030] In accordance with some embodiments, a computer system is described. The computer system comprises: one or more output generation components; one or more cameras; one or more input devices; and means for displaying, via the one or more output generation components, a live video communication interface for a live video communication session, wherein displaying the live video communication interface includes concurrently displaying: a representation of a field-of-view of the one or more cameras of the computer system, wherein the representation of the field-of-view of the one or more cameras is visually associated with an indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the

one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras during the live video communication session; and a representation of one or more participants in the live video communication session that is different from the representation of the field-of-view of the one or more cameras of the computer system; and means, while displaying the live video communication interface for the live video communication session, for detecting, via the one or more input devices, a set of one or more inputs that corresponds to a request to change an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras; and means, responsive to detecting the set of one or more inputs, for changing the appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras.

[0031] Executable instructions for performing these functions are, optionally, included in a non-transitory computer-readable storage medium or other computer program product configured for execution by one or more processors. Executable instructions for performing these functions are, optionally, included in a transitory computer-readable storage medium or other computer program product configured for execution by one or more processors.

[0032] Thus, devices are provided with faster, more efficient methods and interfaces for managing a live video communication session, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace other methods for managing a live video communication session.

Description

DESCRIPTION OF THE FIGURES

[0033] For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

[0034] FIG. 1A is a block diagram illustrating a portable multifunction device with a touch-sensitive display in accordance with some embodiments.

[0035] FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments.

[0036] FIG. 2 illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

[0037] FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments.

[0038] FIG. 4A illustrates an exemplary user interface for a menu of applications on a portable multifunction device in accordance with some embodiments.

[0039] FIG. 4B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

[0040] FIG. 5A illustrates a personal electronic device in accordance with some embodiments.

[0041] FIG. 5B is a block diagram illustrating a personal electronic device in accordance with some embodiments.

[0042] FIG. 5C illustrates an exemplary diagram of a communication session between electronic devices, in accordance with some embodiments.

[0043] FIGS. 6A-6Q illustrate exemplary user interfaces for managing a live video communication session, in accordance with some embodiments.

[0044] FIGS. 7A-7B depict a flow diagram illustrating a method for managing a live video communication session, in accordance with some embodiments.

[0045] FIGS. **8A-8R** illustrate exemplary user interfaces for managing a live video communication session, in accordance with some embodiments.

[0046] FIG. **9** is a flow diagram illustrating a method for managing a live video communication session, in accordance with some embodiments.

[0047] FIGS. **10A-10J** illustrate exemplary user interfaces for managing a live video communication session, in accordance with some embodiments.

[0048] FIG. **11** is a flow diagram illustrating a method for managing a live video communication session, in accordance with some embodiments.

[0049] FIGS. **12A-12U** illustrate exemplary user interfaces for managing a live video communication session, in accordance with some embodiments.

[0050] FIG. **13** is a flow diagram illustrating a method for managing a live video communication session, in accordance with some embodiments.

[0051] FIG. **14** is a flow diagram illustrating a method for managing a live video communication session, in accordance with some embodiments.

DESCRIPTION OF EMBODIMENTS

[0052] The following description sets forth exemplary methods, parameters, and the like. It should be recognized, however, that such description is not intended as a limitation on the scope of the present disclosure but is instead provided as a description of exemplary embodiments.

[0053] There is a need for electronic devices that provide efficient methods and interfaces for managing a live video communication session. Such techniques can reduce the cognitive burden on a user who participates in a video communication session, thereby enhancing productivity. Further, such techniques can reduce processor and battery power otherwise wasted on redundant user inputs.

[0054] Below, FIGS. **1A-1B**, **2**, **3**, **4A-4B**, and **5A-5C** provide a description of exemplary devices for performing the techniques for managing a live video communication session. FIGS. **6A-6Q** illustrate exemplary user interfaces for managing a live video communication session. FIGS. **7A-7B** depict a flow diagram illustrating methods of managing a live video communication session in accordance with some embodiments. The user interfaces in FIGS. **6A-6Q** are used to illustrate the processes described below, including the processes in FIGS. **7A-7B**. FIGS. **8A-8R** illustrate exemplary user interfaces for managing a live video communication session. FIG. **9** is a flow diagram illustrating methods of managing a live video communication session in accordance with some embodiments. The user interfaces in FIGS. **8A-8R** are used to illustrate the processes described below, including the processes in FIG. **9**. FIGS. **10A-10J** illustrate exemplary user interfaces for managing a live video communication session. FIG. **11** is a flow diagram illustrating methods of managing a live video communication session in accordance with some embodiments. The user interfaces in FIGS. **10A-10J** are used to illustrate the processes described below, including the processes in FIG. **11**. FIGS. **12A-12U** illustrate exemplary user interfaces for managing a live video communication session. FIGS. **13** and **14** are flow diagrams illustrating methods of managing a live video communication session in accordance with some embodiments. The user interfaces in FIGS. **12A-12U** are used to illustrate the processes described below, including the processes in FIGS. **13** and **14**.

[0055] In addition, in methods described herein where one or more steps are contingent upon one or more conditions having been met, it should be understood that the described method can be repeated in multiple repetitions so that over the course of the repetitions all of the conditions upon which steps in the method are contingent have been met in different repetitions of the method. For example, if a method requires performing a first step if a condition is satisfied, and a second step if the condition is not satisfied, then a person of ordinary skill would appreciate that the claimed steps are repeated until the condition has been both satisfied and not satisfied, in no particular order. Thus, a method described with one or more steps that are contingent upon one or more conditions having been met could be rewritten as a method that is repeated until each of the conditions

described in the method has been met. This, however, is not required of system or computer readable medium claims where the system or computer readable medium contains instructions for performing the contingent operations based on the satisfaction of the corresponding one or more conditions and thus is capable of determining whether the contingency has or has not been satisfied without explicitly repeating steps of a method until all of the conditions upon which steps in the method are contingent have been met. A person having ordinary skill in the art would also understand that, similar to a method with contingent steps, a system or computer readable storage medium can repeat the steps of a method as many times as are needed to ensure that all of the contingent steps have been performed.

[0056] Although the following description uses terms “first,” “second,” etc. to describe various elements, these elements should not be limited by the terms. In some embodiments, these terms are used to distinguish one element from another. For example, a first touch could be termed a second touch, and, similarly, a second touch could be termed a first touch, without departing from the scope of the various described embodiments. In some embodiments, the first touch and the second touch are two separate references to the same touch. In some embodiments, the first touch and the second touch are both touches, but they are not the same touch.

[0057] The terminology used in the description of the various described embodiments herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description of the various described embodiments and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0058] The term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

[0059] Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Exemplary embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. Other portable electronic devices, such as laptops or tablet computers with touch-sensitive surfaces (e.g., touch screen displays and/or touchpads), are, optionally, used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a touch-sensitive surface (e.g., a touch screen display and/or a touchpad). In some embodiments, the electronic device is a computer system that is in communication (e.g., via wireless communication, via wired communication) with a display generation component. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. As used herein, “displaying” content includes causing to display the content (e.g., video data rendered or decoded by display controller 156) by transmitting, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content.

[0060] In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse, and/or a joystick.

[0061] The device typically supports a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

[0062] The various applications that are executed on the device optionally use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device are, optionally, adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device optionally supports the variety of applications with user interfaces that are intuitive and transparent to the user.

[0063] Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. 1A is a block diagram illustrating portable multifunction device **100** with touch-sensitive display system **112** in accordance with some embodiments. Touch-sensitive display **112** is sometimes called a “touch screen” for convenience and is sometimes known as or called a “touch-sensitive display system.” Device **100** includes memory **102** (which optionally includes one or more computer-readable storage media), memory controller **122**, one or more processing units (CPUs) **120**, peripherals interface **118**, RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, input/output (I/O) subsystem **106**, other input control devices **116**, and external port **124**. Device **100** optionally includes one or more optical sensors **164**. Device **100** optionally includes one or more contact intensity sensors **165** for detecting intensity of contacts on device **100** (e.g., a touch-sensitive surface such as touch-sensitive display system **112** of device **100**). Device **100** optionally includes one or more tactile output generators **167** for generating tactile outputs on device **100** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **112** of device **100** or touchpad **355** of device **300**). These components optionally communicate over one or more communication buses or signal lines **103**.

[0064] As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity

threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure, and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

[0065] As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user's sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user's hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a “down click” or “up click” of a physical actuator button. In some cases, a user will feel a tactile sensation such as an “down click” or “up click” even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user's movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as “roughness” of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an “up click,” a “down click,” “roughness”), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

[0066] It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **1A** are implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application-specific integrated circuits.

[0067] Memory **102** optionally includes high-speed random access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Memory controller **122** optionally controls access to memory **102** by other components of device **100**.

[0068] Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU **120** and memory **102**. The one or more processors **120** run or execute various software programs (such as computer programs (e.g., including instructions)) and/or sets of instructions stored in memory **102** to perform various functions for device **100** and to process data. In some embodiments, peripherals interface **118**, CPU **120**, and memory controller **122** are, optionally, implemented on a single chip, such as chip **104**. In some other embodiments, they are, optionally, implemented on separate chips.

[0069] RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic

signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The RF circuitry **108** optionally includes well-known circuitry for detecting near field communication (NFC) fields, such as by a short-range communication radio. The wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Bluetooth Low Energy (BTLE), Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, and/or IEEE 802.11ac), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

[0070] Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data is, optionally, retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. 2). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

[0071] I/O subsystem **106** couples input/output peripherals on device **100**, such as touch screen **112** and other input control devices **116**, to peripherals interface **118**. I/O subsystem **106** optionally includes display controller **156**, optical sensor controller **158**, depth camera controller **169**, intensity sensor controller **159**, haptic feedback controller **161**, and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input control devices **116**. The other input control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some embodiments, input controller(s) **160** are, optionally, coupled to any (or none) of the following: a keyboard, an infrared port, a USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. 2) optionally include an up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. 2). In some embodiments, the electronic device is a computer system that is in communication (e.g., via wireless communication, via wired communication) with one or more input devices. In some embodiments, the one or more input devices include a touch-sensitive

surface (e.g., a trackpad, as part of a touch-sensitive display). In some embodiments, the one or more input devices include one or more camera sensors (e.g., one or more optical sensors **164** and/or one or more depth camera sensors **175**), such as for tracking a user's gestures (e.g., hand gestures) as input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system.

[0072] A quick press of the push button optionally disengages a lock of touch screen **112** or optionally begins a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, U.S. Pat. No. 7,657,849, which is hereby incorporated by reference in its entirety. A longer press of the push button (e.g., **206**) optionally turns power to device **100** on or off. The functionality of one or more of the buttons are, optionally, user-customizable. Touch screen **112** is used to implement virtual or soft buttons and one or more soft keyboards.

[0073] Touch-sensitive display **112** provides an input interface and an output interface between the device and a user. Display controller **156** receives and/or sends electrical signals from/to touch screen **112**. Touch screen **112** displays visual output to the user. The visual output optionally includes graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output optionally corresponds to user-interface objects.

[0074] Touch screen **112** has a touch-sensitive surface, sensor, or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch screen **112** and convert the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages, or images) that are displayed on touch screen **112**. In an exemplary embodiment, a point of contact between touch screen **112** and the user corresponds to a finger of the user.

[0075] Touch screen **112** optionally uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies are used in other embodiments. Touch screen **112** and display controller **156** optionally detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **112**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone® and iPod Touch® from Apple Inc. of Cupertino, California.

[0076] A touch-sensitive display in some embodiments of touch screen **112** is, optionally, analogous to the multi-touch sensitive touchpads described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), **6,570,557** (Westerman et al.), and/or **6,677,932** (Westerman), and/or U.S. Patent Publication 2002/0015024A **1**, each of which is hereby incorporated by reference in its entirety. However, touch screen **112** displays visual output from device **100**, whereas touch-sensitive touchpads do not provide visual output.

[0077] A touch-sensitive display in some embodiments of touch screen **112** is described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 2, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive Input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input

Device Placement On A Touch Screen User Interface,” filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, “Operation Of A Computer With A Touch Screen Interface,” filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, “Activating Virtual Keys Of A Touch-Screen Virtual Keyboard,” filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, “Multi-Functional Hand-Held Device,” filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

[0078] Touch screen **112** optionally has a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user optionally makes contact with touch screen **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

[0079] In some embodiments, in addition to the touch screen, device **100** optionally includes a touchpad for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is, optionally, a touch-sensitive surface that is separate from touch screen **112** or an extension of the touch-sensitive surface formed by the touch screen.

[0080] Device **100** also includes power system **162** for powering the various components. Power system **162** optionally includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

[0081] Device **100** optionally also includes one or more optical sensors **164**. FIG. 1A shows an optical sensor coupled to optical sensor controller **158** in I/O subsystem **106**. Optical sensor **164** optionally includes charge-coupled device (CCD) or complementary metal-oxide semiconductor (CM OS) phototransistors. Optical sensor **164** receives light from the environment, projected through one or more lenses, and converts the light to data representing an image. In conjunction with imaging module **143** (also called a camera module), optical sensor **164** optionally captures still images or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch screen display **112** on the front of the device so that the touch screen display is enabled for use as a viewfinder for still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the user's image is, optionally, obtained for video conferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of optical sensor **164** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **164** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

[0082] Device **100** optionally also includes one or more depth camera sensors **175**. FIG. 1A shows a depth camera sensor coupled to depth camera controller **169** in I/O subsystem **106**. Depth camera sensor **175** receives data from the environment to create a three dimensional model of an object (e.g., a face) within a scene from a viewpoint (e.g., a depth camera sensor). In some embodiments, in conjunction with imaging module **143** (also called a camera module), depth camera sensor **175** is optionally used to determine a depth map of different portions of an image captured by the imaging module **143**. In some embodiments, a depth camera sensor is located on the front of device **100** so that the user's image with depth information is, optionally, obtained for video conferencing while the user views the other video conference participants on the touch screen display and to capture selfies with depth map data. In some embodiments, the depth camera sensor **175** is located on the

back of device, or on the back and the front of the device **100**. In some embodiments, the position of depth camera sensor **175** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a depth camera sensor **175** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

[0083] In some embodiments, a depth map (e.g., depth map image) contains information (e.g., values) that relates to the distance of objects in a scene from a viewpoint (e.g., a camera, an optical sensor, a depth camera sensor). In one embodiment of a depth map, each depth pixel defines the position in the viewpoint's Z-axis where its corresponding two-dimensional pixel is located. In some embodiments, a depth map is composed of pixels wherein each pixel is defined by a value (e.g., 0-255). For example, the "0" value represents pixels that are located at the most distant place in a "three dimensional" scene and the "255" value represents pixels that are located closest to a viewpoint (e.g., a camera, an optical sensor, a depth camera sensor) in the "three dimensional" scene. In other embodiments, a depth map represents the distance between an object in a scene and the plane of the viewpoint. In some embodiments, the depth map includes information about the relative depth of various features of an object of interest in view of the depth camera (e.g., the relative depth of eyes, nose, mouth, ears of a user's face). In some embodiments, the depth map includes information that enables the device to determine contours of the object of interest in a z direction.

[0084] Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. 1A shows a contact intensity sensor coupled to intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor **165** optionally includes one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor **165** receives contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

[0085] Device **100** optionally also includes one or more proximity sensors **166**. FIG. 1A shows proximity sensor **166** coupled to peripherals interface **118**. Alternately, proximity sensor **166** is, optionally, coupled to input controller **160** in I/O subsystem **106**. Proximity sensor **166** optionally performs as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device"; Ser. No. 11/240,788, "Proximity Detector In Handheld Device"; Ser. No. 11/620,702, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 11/586,862, "Automated Response To And Sensing Of User Activity In Portable Devices"; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables touch screen **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

[0086] Device **100** optionally also includes one or more tactile output generators **167**. FIG. 1A shows a tactile output generator coupled to haptic feedback controller **161** in I/O subsystem **106**. Tactile output generator **167** optionally includes one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Contact intensity sensor **165** receives tactile feedback generation instructions from haptic feedback module **133** and generates tactile outputs on device **100** that are capable of being sensed by a user of device **100**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-

sensitive display system **112**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **100**) or laterally (e.g., back and forth in the same plane as a surface of device **100**). In some embodiments, at least one tactile output generator sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

[0087] Device **100** optionally also includes one or more accelerometers **168**. FIG. **1A** shows accelerometer **168** coupled to peripherals interface **118**. Alternately, accelerometer **168** is, optionally, coupled to an input controller **160** in I/O subsystem **106**. Accelerometer **168** optionally performs as described in U.S. Patent Publication No. 20050190059, “Acceleration-based Theft Detection System for Portable Electronic Devices,” and U.S. Patent Publication No. 20060017692, “Methods And Apparatuses For Operating A Portable Device Based On An Accelerometer,” both of which are incorporated by reference herein in their entirety. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **100** optionally includes, in addition to accelerometer(s) **168**, a magnetometer and a GPS (or GLONASS or other global navigation system) receiver for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**.

[0088] In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or sets of instructions) **136**. Furthermore, in some embodiments, memory **102** (FIG. **1A**) or **370** (FIG. **3**) stores device/global internal state **157**, as shown in FIGS. **1A** and **3**.

Device/global internal state **157** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **112**; sensor state, including information obtained from the device's various sensors and input control devices **116**; and location information concerning the device's location and/or attitude.

[0089] Operating system **126** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, IOS, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

[0090] Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE®, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with, the 30-pin connector used on iPod® (trademark of Apple Inc.) devices.

[0091] Contact/motion module **130** optionally detects contact with touch screen **112** (in conjunction with display controller **156**) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface. Determining movement of the point of contact,

which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., “multitouch”/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

[0092] In some embodiments, contact/motion module **130** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has “clicked” on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **100**). For example, a mouse “click” threshold of a trackpad or touch screen display can be set to any of a large range of predefined threshold values without changing the trackpad or touch screen display hardware. Additionally, in some implementations, a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click “intensity” parameter).

[0093] Contact/motion module **130** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (liftoff) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (liftoff) event.

[0094] Graphics module **132** includes various known software components for rendering and displaying graphics on touch screen **112** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast, or other visual property) of graphics that are displayed. As used herein, the term “graphics” includes any object that can be displayed to a user, including, without limitation, text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations, and the like.

[0095] In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

[0096] Haptic feedback module **133** includes various software components for generating instructions used by tactile output generator(s) **167** to produce tactile outputs at one or more locations on device **100** in response to user interactions with device **100**.

[0097] Text input module **134**, which is, optionally, a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts module **137**, e-mail client module **140**, IM module **141**, browser module **147**, and any other application that needs text input).

[0098] GPS module **135** determines the location of the device and provides this information for use in various applications (e.g., to telephone module **138** for use in location-based dialing; to camera module **143** as picture/video metadata; and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

[0099] Applications **136** optionally include the following modules (or sets of instructions), or a subset or superset thereof: [0100] Contacts module **137** (sometimes called an address book or contact list); [0101] Telephone module **138**; [0102] Video conference module **139**; [0103] E-mail

client module **140**; [0104] Instant messaging (IM) module **141**; [0105] Workout support module **142**; [0106] Camera module **143** for still and/or video images; [0107] Image management module **144**; [0108] Video player module; [0109] Music player module; [0110] Browser module **147**; [0111] Calendar module **148**; [0112] Widget modules **149**, which optionally include one or more of: weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, dictionary widget **149-5**, and other widgets obtained by the user, as well as user-created widgets **149-6**; [0113] Widget creator module **150** for making user-created widgets **149-6**; [0114] Search module **151**; [0115] Video and music player module **152**, which merges video player module and music player module; [0116] Notes module **153**; [0117] Map module **154**; and/or [0118] Online video module **155**.

[0119] Examples of other applications **136** that are, optionally, stored in memory **102** include other word processing applications, other image editing applications, drawing applications, presentation applications, JA VA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

[0120] In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, contacts module **137** are, optionally, used to manage an address book or contact list (e.g., stored in application internal state **192** of contacts module **137** in memory **102** or memory **370**), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone module **138**, video conference module **139**, e-mail client module **140**, or IM module **141**; and so forth.

[0121] In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, telephone module **138** are optionally, used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in contacts module **137**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation, and disconnect or hang up when the conversation is completed. As noted above, the wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies.

[0122] In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, optical sensor **164**, optical sensor controller **158**, contact/motion module **130**, graphics module **132**, text input module **134**, contacts module **137**, and telephone module **138**, video conference module **139** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

[0123] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, e-mail client module **140** includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module **144**, e-mail client module **140** makes it very easy to create and send e-mails with still or video images taken with camera module **143**.

[0124] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, the instant messaging module **141** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages, and to view received instant messages. In some embodiments, transmitted and/or received instant messages optionally

include graphics, photos, audio files, video files and/or other attachments as are supported in an MMS and/or an Enhanced Messaging Service (EMS). As used herein, “instant messaging” refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

[0125] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, GPS module **135**, map module **154**, and music player module, workout support module **142** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (sports devices); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store, and transmit workout data.

[0126] In conjunction with touch screen **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact/motion module **130**, graphics module **132**, and image management module **144**, camera module **143** includes executable instructions to capture still images or video (including a video stream) and store them into memory **102**, modify characteristics of a still image or video, or delete a still image or video from memory **102**.

[0127] In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and camera module **143**, image management module **144** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

[0128] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, browser module **147** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

[0129] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, e-mail client module **140**, and browser module **147**, calendar module **148** includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to-do lists, etc.) in accordance with user instructions.

[0130] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and browser module **147**, widget modules **149** are mini-applications that are, optionally, downloaded and used by a user (e.g., weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, and dictionary widget **149-5**) or created by the user (e.g., user-created widget **149-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript® file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript® file (e.g., Yahoo!® Widgets).

[0131] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and browser module **147**, the widget creator module **150** are, optionally, used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

[0132] In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, search module **151** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **102** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

[0133] In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, and browser module **147**, video and music player module **152** includes executable instructions that allow the user to

download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present, or otherwise play back videos (e.g., on touch screen **112** or on an external, connected display via external port **124**). In some embodiments, device **100** optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

[0134] In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, notes module **153** includes executable instructions to create and manage notes, to-do lists, and the like in accordance with user instructions.

[0135] In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, GPS module **135**, and browser module **147**, map module **154** are, optionally, used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions, data on stores and other points of interest at or near a particular location, and other location-based data) in accordance with user instructions.

[0136] In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, text input module **134**, e-mail client module **140**, and browser module **147**, online video module **155** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **124**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **141**, rather than e-mail client module **140**, is used to send a link to a particular online video. Additional description of the online video application can be found in U.S. Provisional Patent Application No. 60/936,562, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Jun. 20, 2007, and U.S. patent application Ser. No. 11/968,067, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Dec. 31, 2007, the contents of which are hereby incorporated by reference in their entirety.

[0137] Each of the above-identified modules and applications corresponds to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (e.g., sets of instructions) need not be implemented as separate software programs (such as computer programs (e.g., including instructions)), procedures, or modules, and thus various subsets of these modules are, optionally, combined or otherwise rearranged in various embodiments. For example, video player module is, optionally, combined with music player module into a single module (e.g., video and music player module **152**, FIG. **1A**). In some embodiments, memory **102** optionally stores a subset of the modules and data structures identified above. Furthermore, memory **102** optionally stores additional modules and data structures not described above.

[0138] In some embodiments, device **100** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **100**, the number of physical input control devices (such as push buttons, dials, and the like) on device **100** is, optionally, reduced.

[0139] The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **100** to a main, home, or root menu from any user interface that is displayed on device **100**. In such embodiments, a "menu button" is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

[0140] FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some embodiments, memory **102** (FIG. 1A) or **370** (FIG. 3) includes event sorter **170** (e.g., in operating system **126**) and a respective application **136-1** (e.g., any of the aforementioned applications **137-151, 155, 380-390**).

[0141] Event sorter **170** receives event information and determines the application **136-1** and application view **191** of application **136-1** to which to deliver the event information. Event sorter **170** includes event monitor **171** and event dispatcher module **174**. In some embodiments, application **136-1** includes application internal state **192**, which indicates the current application view(s) displayed on touch-sensitive display **112** when the application is active or executing. In some embodiments, device/global internal state **157** is used by event sorter **170** to determine which application(s) is (are) currently active, and application internal state **192** is used by event sorter **170** to determine application views **191** to which to deliver event information.

[0142] In some embodiments, application internal state **192** includes additional information, such as one or more of: resume information to be used when application **136-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **136-1**, a state queue for enabling the user to go back to a prior state or view of application **136-1**, and a redo/undo queue of previous actions taken by the user.

[0143] Event monitor **171** receives event information from peripherals interface **118**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display **112**, as part of a multi-touch gesture). Peripherals interface **118** transmits information it receives from I/O subsystem **106** or a sensor, such as proximity sensor **166**, accelerometer(s) **168**, and/or microphone **113** (through audio circuitry **110**). Information that peripherals interface **118** receives from I/O subsystem **106** includes information from touch-sensitive display **112** or a touch-sensitive surface.

[0144] In some embodiments, event monitor **171** sends requests to the peripherals interface **118** at predetermined intervals. In response, peripherals interface **118** transmits event information. In other embodiments, peripherals interface **118** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

[0145] In some embodiments, event sorter **170** also includes a hit view determination module **172** and/or an active event recognizer determination module **173**.

[0146] Hit view determination module **172** provides software procedures for determining where a sub-event has taken place within one or more views when touch-sensitive display **112** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

[0147] Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected optionally correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected is, optionally, called the hit view, and the set of events that are recognized as proper inputs are, optionally, determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

[0148] Hit view determination module **172** receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **172** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (e.g., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module **172**, the hit view typically receives all sub-events related to the same touch or input source for which it was

identified as the hit view.

[0149] Active event recognizer determination module **173** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **173** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **173** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

[0150] Event dispatcher module **174** dispatches the event information to an event recognizer (e.g., event recognizer **180**). In embodiments including active event recognizer determination module **173**, event dispatcher module **174** delivers the event information to an event recognizer determined by active event recognizer determination module **173**. In some embodiments, event dispatcher module **174** stores in an event queue the event information, which is retrieved by a respective event receiver **182**.

[0151] In some embodiments, operating system **126** includes event sorter **170**. Alternatively, application **136-1** includes event sorter **170**. In yet other embodiments, event sorter **170** is a stand-alone module, or a part of another module stored in memory **102**, such as contact/motion module **130**.

[0152] In some embodiments, application **136-1** includes a plurality of event handlers **190** and one or more application views **191**, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view **191** of the application **136-1** includes one or more event recognizers **180**. Typically, a respective application view **191** includes a plurality of event recognizers **180**. In other embodiments, one or more of event recognizers **180** are part of a separate module, such as a user interface kit or a higher level object from which application **136-1** inherits methods and other properties. In some embodiments, a respective event handler **190** includes one or more of: data updater **176**, object updater **177**, GUI updater **178**, and/or event data **179** received from event sorter **170**. Event handler **190** optionally utilizes or calls data updater **176**, object updater **177**, or GUI updater **178** to update the application internal state **192**. Alternatively, one or more of the application views **191** include one or more respective event handlers **190**. Also, in some embodiments, one or more of data updater **176**, object updater **177**, and GUI updater **178** are included in a respective application view **191**.

[0153] A respective event recognizer **180** receives event information (e.g., event data **179**) from event sorter **170** and identifies an event from the event information. Event recognizer **180** includes event receiver **182** and event comparator **184**. In some embodiments, event recognizer **180** also includes at least a subset of: metadata **183**, and event delivery instructions **188** (which optionally include sub-event delivery instructions).

[0154] Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information optionally also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

[0155] Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined

sequences of sub-events), for example, event **1 (187-1)**, event **2 (187-2)**, and others. In some embodiments, sub-events in an event (e.g., **187-1** and/or **187-2**) include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1 (187-1)** is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first liftoff (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second liftoff (touch end) for a predetermined phase. In another example, the definition for event **2 (187-2)** is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display **112**, and liftoff of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **190**.

[0156] In some embodiments, event definitions **186** include a definition of an event for a respective user-interface object. In some embodiments, event comparator **184** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display **112**, when a touch is detected on touch-sensitive display **112**, event comparator **184** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **190**, the event comparator uses the result of the hit test to determine which event handler **190** should be activated. For example, event comparator **184** selects an event handler associated with the sub-event and the object triggering the hit test.

[0157] In some embodiments, the definition for a respective event (**187**) also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

[0158] When a respective event recognizer **180** determines that the series of sub-events do not match any of the events in event definitions **186**, the respective event recognizer **180** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

[0159] In some embodiments, a respective event recognizer **180** includes metadata **183** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

[0160] In some embodiments, a respective event recognizer **180** activates event handler **190** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **180** delivers event information associated with the event to event handler **190**. Activating an event handler **190** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **180** throws a flag associated with the recognized event, and event handler **190** associated with the flag catches the flag and performs a predefined process.

[0161] In some embodiments, event delivery instructions **188** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

[0162] In some embodiments, data updater **176** creates and updates data used in application **136-1**.

For example, data updater **176** updates the telephone number used in contacts module **137**, or stores a video file used in video player module. In some embodiments, object updater **177** creates and updates objects used in application **136-1**. For example, object updater **177** creates a new user-interface object or updates the position of a user-interface object. GUI updater **178** updates the GUI. For example, GUI updater **178** prepares display information and sends it to graphics module **132** for display on a touch-sensitive display.

[0163] In some embodiments, event handler(s) **190** includes or has access to data updater **176**, object updater **177**, and GUI updater **178**. In some embodiments, data updater **176**, object updater **177**, and GUI updater **178** are included in a single module of a respective application **136-1** or application view **191**. In other embodiments, they are included in two or more software modules.

[0164] It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **100** with input devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc. on touchpads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

[0165] FIG. **2** illustrates a portable multifunction device **100** having a touch screen **112** in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) **200**. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure) or one or more styluses **203** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward), and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device **100**. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

[0166] Device **100** optionally also include one or more physical buttons, such as “home” or menu button **204**. As described previously, menu button **204** is, optionally, used to navigate to any application **136** in a set of applications that are, optionally, executed on device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen **112**.

[0167] In some embodiments, device **100** includes touch screen **112**, menu button **204**, push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, subscriber identity module (SIM) card slot **210**, headset jack **212**, and docking/charging external port **124**. Push button **206** is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **100** also accepts verbal input for activation or deactivation of some functions through microphone **113**. Device **100** also, optionally, includes one or more contact intensity sensors **165** for detecting intensity of contacts on touch screen **112** and/or one or more tactile output generators **167** for generating tactile outputs for a user of device **100**.

[0168] FIG. **3** is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device **300** need not be portable. In some embodiments, device **300** is a laptop computer, a desktop computer, a tablet computer, a

multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device **300** typically includes one or more processing units (CPUs) **310**, one or more network or other communications interfaces **360**, memory **370**, and one or more communication buses **320** for interconnecting these components. Communication buses **320** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device **300** includes input/output (I/O) interface **330** comprising display **340**, which is typically a touch screen display. I/O interface **330** also optionally includes a keyboard and/or mouse (or other pointing device) **350** and touchpad **355**, tactile output generator **357** for generating tactile outputs on device **300** (e.g., similar to tactile output generator(s) **167** described above with reference to FIG. **1A**), sensors **359** (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) **165** described above with reference to FIG. **1A**). Memory **370** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory **370** optionally includes one or more storage devices remotely located from CPU(s) **310**. In some embodiments, memory **370** stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory **102** of portable multifunction device **100** (FIG. **1A**), or a subset thereof. Furthermore, memory **370** optionally stores additional programs, modules, and data structures not present in memory **102** of portable multifunction device **100**. For example, memory **370** of device **300** optionally stores drawing module **380**, presentation module **382**, word processing module **384**, website creation module **386**, disk authoring module **388**, and/or spreadsheet module **390**, while memory **102** of portable multifunction device **100** (FIG. **1A**) optionally does not store these modules.

[0169] Each of the above-identified elements in FIG. **3** is, optionally, stored in one or more of the previously mentioned memory devices. Each of the above-identified modules corresponds to a set of instructions for performing a function described above. The above-identified modules or computer programs (e.g., sets of instructions or including instructions) need not be implemented as separate software programs (such as computer programs (e.g., including instructions)), procedures, or modules, and thus various subsets of these modules are, optionally, combined or otherwise rearranged in various embodiments. In some embodiments, memory **370** optionally stores a subset of the modules and data structures identified above. Furthermore, memory **370** optionally stores additional modules and data structures not described above.

[0170] Attention is now directed towards embodiments of user interfaces that are, optionally, implemented on, for example, portable multifunction device **100**.

[0171] FIG. **4A** illustrates an exemplary user interface for a menu of applications on portable multifunction device **100** in accordance with some embodiments. Similar user interfaces are, optionally, implemented on device **300**. In some embodiments, user interface **400** includes the following elements, or a subset or superset thereof: [0172] Signal strength indicator(s) **402** for wireless communication(s), such as cellular and Wi-Fi signals; [0173] Time **404**; [0174] Bluetooth indicator **405**; [0175] Battery status indicator **406**; [0176] Tray **408** with icons for frequently used applications, such as: [0177] Icon **416** for telephone module **138**, labeled "Phone," which optionally includes an indicator **414** of the number of missed calls or voicemail messages; [0178] Icon **418** for e-mail client module **140**, labeled "Mail," which optionally includes an indicator **410** of the number of unread e-mails; [0179] Icon **420** for browser module **147**, labeled "Browser;" and [0180] Icon **422** for video and music player module **152**, also referred to as iPod (trademark of Apple Inc.) module **152**, labeled "iPod;" and [0181] Icons for other applications, such as: [0182] Icon **424** for IM module **141**, labeled "Messages;" [0183] Icon **426** for calendar module **148**, labeled "Calendar;" [0184] Icon **428** for image management module **144**, labeled "Photos;" [0185]

Icon **430** for camera module **143**, labeled “Camera;” [0186] Icon **432** for online video module **155**, labeled “Online Video;” [0187] Icon **434** for stocks widget **149-2**, labeled “Stocks;” [0188] Icon **436** for map module **154**, labeled “Maps;” [0189] Icon **438** for weather widget **149-1**, labeled “Weather;” [0190] Icon **440** for alarm clock widget **149-4**, labeled “Clock;” [0191] Icon **442** for workout support module **142**, labeled “Workout Support;” [0192] Icon **444** for notes module **153**, labeled “Notes;” and [0193] Icon **446** for a settings application or module, labeled “Settings,” which provides access to settings for device **100** and its various applications **136**.

[0194] It should be noted that the icon labels illustrated in FIG. **4A** are merely exemplary. For example, icon **422** for video and music player module **152** is labeled “Music” or “Music Player.” Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

[0195] FIG. **4B** illustrates an exemplary user interface on a device (e.g., device **300**, FIG. **3**) with a touch-sensitive surface **451** (e.g., a tablet or touchpad **355**, FIG. **3**) that is separate from the display **450** (e.g., touch screen display **112**). Device **300** also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors **359**) for detecting intensity of contacts on touch-sensitive surface **451** and/or one or more tactile output generators **357** for generating tactile outputs for a user of device **300**.

[0196] Although some of the examples that follow will be given with reference to inputs on touch screen display **112** (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. **4B**. In some embodiments, the touch-sensitive surface (e.g., touch-sensitive surface **451** in FIG. **4B**) has a primary axis (e.g., **452** in FIG. **4B**) that corresponds to a primary axis (e.g., **453** in FIG. **4B**) on the display (e.g., display **450**). In accordance with these embodiments, the device detects contacts (e.g., contact **460** and contact **462** in FIG. **4B**) with the touch-sensitive surface **451** at locations that correspond to respective locations on the display (e.g., in FIG. **4B**, contact **460** corresponds to **468** and contact **462** corresponds to **470**). In this way, user inputs (e.g., contacts **460** and **462**, and movements thereof) detected by the device on the touch-sensitive surface (e.g., touch-sensitive surface **451** in FIG. **4B**) are used by the device to manipulate the user interface on the display (e.g., display **450** in FIG. **4B**) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

[0197] Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse-based input or stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

[0198] FIG. **5A** illustrates exemplary personal electronic device **500**. Device **500** includes body **502**. In some embodiments, device **500** can include some or all of the features described with respect to devices **100** and **300** (e.g., FIGS. **1A-4B**). In some embodiments, device **500** has touch-sensitive display screen **504**, hereafter touch screen **504**. Alternatively, or in addition to touch screen **504**, device **500** has a display and a touch-sensitive surface. As with devices **100** and **300**, in some embodiments, touch screen **504** (or the touch-sensitive surface) optionally includes one or

more intensity sensors for detecting intensity of contacts (e.g., touches) being applied. The one or more intensity sensors of touch screen **504** (or the touch-sensitive surface) can provide output data that represents the intensity of touches. The user interface of device **500** can respond to touches based on their intensity, meaning that touches of different intensities can invoke different user interface operations on device **500**.

[0199] Exemplary techniques for detecting and processing touch intensity are found, for example, in related applications: International Patent Application Serial No. PCT/US2013/040061, titled “Device, Method, and Graphical User Interface for Displaying User Interface Objects Corresponding to an Application,” filed May 8, 2013, published as WIPO Publication No. WO/2013/169849, and International Patent Application Serial No. PCT/US2013/069483, titled “Device, Method, and Graphical User Interface for Transitioning Between Touch Input to Display Output Relationships,” filed Nov. 11, 2013, published as WIPO Publication No. WO/2014/105276, each of which is hereby incorporated by reference in their entirety.

[0200] In some embodiments, device **500** has one or more input mechanisms **506** and **508**. Input mechanisms **506** and **508**, if included, can be physical. Examples of physical input mechanisms include push buttons and rotatable mechanisms. In some embodiments, device **500** has one or more attachment mechanisms. Such attachment mechanisms, if included, can permit attachment of device **500** with, for example, hats, eyewear, earrings, necklaces, shirts, jackets, bracelets, watch straps, chains, trousers, belts, shoes, purses, backpacks, and so forth. These attachment mechanisms permit device **500** to be worn by a user.

[0201] FIG. 5B depicts exemplary personal electronic device **500**. In some embodiments, device **500** can include some or all of the components described with respect to FIGS. 1A, 1B, and 3. Device **500** has bus **512** that operatively couples I/O section **514** with one or more computer processors **516** and memory **518**. I/O section **514** can be connected to display screen **504**, which can have touch-sensitive component **522** and, optionally, intensity sensor **524** (e.g., contact intensity sensor). In addition, I/O section **514** can be connected with communication unit **530** for receiving application and operating system data, using Wi-Fi, Bluetooth, near field communication (NFC), cellular, and/or other wireless communication techniques. Device **500** can include input mechanisms **506** and/or **508**. Input mechanism **506** is, optionally, a rotatable input device or a depressible and rotatable input device, for example. Input mechanism **508** is, optionally, a button, in some examples.

[0202] Input mechanism **508** is, optionally, a microphone, in some examples. Personal electronic device **500** optionally includes various sensors, such as GPS sensor **532**, accelerometer **534**, directional sensor **540** (e.g., compass), gyroscope **536**, motion sensor **538**, and/or a combination thereof, all of which can be operatively connected to I/O section **514**.

[0203] Memory **518** of personal electronic device **500** can include one or more non-transitory computer-readable storage media, for storing computer-executable instructions, which, when executed by one or more computer processors **516**, for example, can cause the computer processors to perform the techniques described below, including processes **700**, **900**, **1100**, **1300**, and **1400** (FIGS. 7A, 7B, 9, 11, 13, and 14). A computer-readable storage medium can be any medium that can tangibly contain or store computer-executable instructions for use by or in connection with the instruction execution system, apparatus, or device. In some examples, the storage medium is a transitory computer-readable storage medium. In some examples, the storage medium is a non-transitory computer-readable storage medium. The non-transitory computer-readable storage medium can include, but is not limited to, magnetic, optical, and/or semiconductor storages. Examples of such storage include magnetic disks, optical discs based on CD, DVD, or Blu-ray® technologies, as well as persistent solid-state memory such as flash, solid-state drives, and the like. Personal electronic device **500** is not limited to the components and configuration of FIG. 5B, but can include other or additional components in multiple configurations.

[0204] As used here, the term “affordance” refers to a user-interactive graphical user interface

object that is, optionally, displayed on the display screen of devices **100**, **300**, and/or **500** (FIGS. **1A**, **3**, and **5A-5C**). For example, an image (e.g., icon), a button, and text (e.g., hyperlink) each optionally constitute an affordance.

[0205] As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **355** in FIG. **3** or touch-sensitive surface **451** in FIG. **4B**) while the cursor is over a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch screen display (e.g., touch-sensitive display system **112** in FIG. **1A** or touch screen **112** in FIG. **4A**) that enables direct interaction with user interface elements on the touch screen display, a detected contact on the touch screen acts as a “focus selector” so that when an input (e.g., a press input by the contact) is detected on the touch screen display at a location of a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch screen display) that is controlled by the user so as to communicate the user's intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

[0206] As used in the specification and claims, the term “characteristic intensity” of a contact refers to a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally, based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds optionally includes a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second threshold results in a third operation.

In some embodiments, a comparison between the characteristic intensity and one or more thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective operation or forgo performing the respective operation), rather than being used to determine whether to perform a first operation or a second operation.

[0207] In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface optionally receives a continuous swipe contact transitioning from a start location and reaching an end location, at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location is, optionally, based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm is, optionally, applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

[0208] The intensity of a contact on the touch-sensitive surface is, optionally, characterized relative to one or more intensity thresholds, such as a contact-detection intensity threshold, a light press intensity threshold, a deep press intensity threshold, and/or one or more other intensity thresholds. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

[0209] An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold to an intensity between the light press intensity threshold and the deep press intensity threshold is sometimes referred to as a “light press” input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold to an intensity above the deep press intensity threshold is sometimes referred to as a “deep press” input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold to an intensity between the contact-detection intensity threshold and the light press intensity threshold is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold to an intensity below the contact-detection intensity threshold is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments, the contact-detection intensity threshold is zero. In some embodiments, the contact-detection intensity threshold is greater than zero.

[0210] In some embodiments described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., a “down stroke” of the respective press

input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., an “up stroke” of the respective press input).

[0211] In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., an “up stroke” of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

[0212] For ease of explanation, the descriptions of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting either: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, and/or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold.

[0213] Attention is now directed towards embodiments of user interfaces (“UI”) and associated processes that are implemented on an electronic device, such as portable multifunction device **100**, device **300**, or device **500**.

[0214] FIG. 5C depicts an exemplary diagram of a communication session between electronic devices **500A**, **500B**, and **500C**. Devices **500A**, **500B**, and **500C** are similar to electronic device **500**, and each share with each other one or more data connections **510** such as an Internet connection, Wi-Fi connection, cellular connection, short-range communication connection, and/or any other such data connection or network so as to facilitate real time communication of audio and/or video data between the respective devices for a duration of time. In some embodiments, an exemplary communication session can include a shared-data session whereby data is communicated from one or more of the electronic devices to the other electronic devices to enable concurrent output of respective content at the electronic devices. In some embodiments, an exemplary communication session can include a video conference session whereby audio and/or video data is communicated between devices **500A**, **500B**, and **500C** such that users of the respective devices can engage in real time communication using the electronic devices.

[0215] In FIG. 5C, device **500A** represents an electronic device associated with User A.

[0216] Device **500A** is in communication (via data connections **510**) with devices **500B** and **500C**, which are associated with User B and User C, respectively. Device **500A** includes camera **501A**, which is used to capture video data for the communication session, and display **504A** (e.g., a touchscreen), which is used to display content associated with the communication session. Device **500A** also includes other components, such as a microphone (e.g., **113**) for recording audio for the communication session and a speaker (e.g., **111**) for outputting audio for the communication session.

[0217] Device **500A** displays, via display **504A**, communication UI **520A**, which is a user interface for facilitating a communication session (e.g., a video conference session) between device **500B** and device **500C**. Communication UI **520A** includes video feed **525-1A** and video feed **525-2A**. Video feed **525-1A** is a representation of video data captured at device **500B** (e.g., using camera **501B**) and communicated from device **500B** to devices **500A** and **500C** during the communication session. Video feed **525-2A** is a representation of video data captured at device **500C** (e.g., using camera **501C**) and communicated from device **500C** to devices **500A** and **500B** during the communication session.

[0218] Communication UI **520A** includes camera preview **550A**, which is a representation of video data captured at device **500A** via camera **501A**. Camera preview **550A** represents to User A the prospective video feed of User A that is displayed at respective devices **500B** and **500C**.

[0219] Communication UI **520A** includes one or more controls **555A** for controlling one or more aspects of the communication session. For example, controls **555A** can include controls for muting audio for the communication session, changing a camera view for the communication session (e.g., changing which camera is used for capturing video for the communication session, adjusting a zoom value), terminating the communication session, applying visual effects to the camera view for the communication session, activating one or more modes associated with the communication session. In some embodiments, one or more controls **555A** are optionally displayed in communication UI **520A**. In some embodiments, one or more controls **555A** are displayed separate from camera preview **550A**. In some embodiments, one or more controls **555A** are displayed overlaying at least a portion of camera preview **550A**.

[0220] In FIG. 5C, device **500B** represents an electronic device associated with User B, which is in communication (via data connections **510**) with devices **500A** and **500C**. Device **500B** includes camera **501B**, which is used to capture video data for the communication session, and display **504B** (e.g., a touchscreen), which is used to display content associated with the communication session. Device **500B** also includes other components, such as a microphone (e.g., **113**) for recording audio for the communication session and a speaker (e.g., **111**) for outputting audio for the communication session.

[0221] Device **500B** displays, via touchscreen **504B**, communication UI **520B**, which is similar to communication UI **520A** of device **500A**. Communication UI **520B** includes video feed **525-1B** and video feed **525-2B**. Video feed **525-1B** is a representation of video data captured at device **500A** (e.g., using camera **501A**) and communicated from device **500A** to devices **500B** and **500C** during the communication session. Video feed **525-2B** is a representation of video data captured at device **500C** (e.g., using camera **501C**) and communicated from device **500C** to devices **500A** and **500B** during the communication session. Communication UI **520B** also includes camera preview **550B**, which is a representation of video data captured at device **500B** via camera **501B**, and one or more controls **555B** for controlling one or more aspects of the communication session, similar to controls **555A**. Camera preview **550B** represents to User B the prospective video feed of User B that is displayed at respective devices **500A** and **500C**.

[0222] In FIG. 5C, device **500C** represents an electronic device associated with User C, which is in communication (via data connections **510**) with devices **500A** and **500B**. Device **500C** includes camera **501C**, which is used to capture video data for the communication session, and display **504C** (e.g., a touchscreen), which is used to display content associated with the communication session.

Device **500C** also includes other components, such as a microphone (e.g., **113**) for recording audio for the communication session and a speaker (e.g., **111**) for outputting audio for the communication session.

[0223] Device **500C** displays, via touchscreen **504C**, communication UI **520C**, which is similar to communication UI **520A** of device **500A** and communication UI **520B** of device **500B**.

Communication UI **520C** includes video feed **525-1C** and video feed **525-2C**. Video feed **525-1C** is a representation of video data captured at device **500B** (e.g., using camera **501B**) and communicated from device **500B** to devices **500A** and **500C** during the communication session. Video feed **525-2C** is a representation of video data captured at device **500A** (e.g., using camera **501A**) and communicated from device **500A** to devices **500B** and **500C** during the communication session. Communication UI **520C** also includes camera preview **550C**, which is a representation of video data captured at device **500C** via camera **501C**, and one or more controls **555C** for controlling one or more aspects of the communication session, similar to controls **555A** and **555B**. Camera preview **550C** represents to User C the prospective video feed of User C that is displayed at respective devices **500A** and **500B**.

[0224] While the diagram depicted in FIG. 5C represents a communication session between three electronic devices, the communication session can be established between two or more electronic devices, and the number of devices participating in the communication session can change as electronic devices join or leave the communication session. For example, if one of the electronic devices leaves the communication session, audio and video data from the device that stopped participating in the communication session is no longer represented on the participating devices. For example, if device **500B** stops participating in the communication session, there is no data connection **510** between devices **500A** and **500C**, and no data connection **510** between devices **500C** and **500B**. Additionally, device **500A** does not include video feed **525-1A** and device **500C** does not include video feed **525-1C**. Similarly, if a device joins the communication session, a connection is established between the joining device and the existing devices, and the video and audio data is shared among all devices such that each device is capable of outputting data communicated from the other devices.

[0225] The embodiment depicted in FIG. 5C represents a diagram of a communication session between multiple electronic devices, including the example communication sessions depicted in FIGS. 6A-6Q, 8A-8R, 10A-10J, and 12A-12U. In some embodiments, the communication sessions depicted in FIGS. 6A-6Q, 8A-8R, 10A-10J, and 12A-12U include two or more electronic devices, even if other electronic devices participating in the communication session are not depicted in the figures.

[0226] FIGS. 6A-6Q illustrate exemplary user interfaces for managing a live video communication session (e.g., a video conference), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. 7A and 7B.

[0227] FIGS. 6A-6Q illustrate device **600** displaying user interfaces on display **601** (e.g., a display device or display generation component) for managing a live video communication session. FIGS. 6A-6Q depict various embodiments in which device **600** automatically reframes a displayed portion of a camera field-of-view based on conditions detected in a scene that is within the field-of-view of the camera while an automatic framing mode is enabled. One or more of the embodiments discussed below with respect to FIGS. 6A-6Q can be combined with one or more of the embodiments discussed with respect to FIGS. 8A-8R, FIGS. 10A-10J, and FIGS. 12A-12U.

[0228] Device **600** includes one or more cameras **602** (e.g., front-facing cameras) for capturing image data and, optionally, depth data of a scene that is within the field-of-view of the camera. In some embodiments, camera **602** is a wide angle camera (e.g., a camera that includes a wide angle lens, or a lens that has a relatively short focal length and wide field-of-view). In some embodiments, device **600** includes one or more features of devices **100**, **300**, or **500**.

[0229] In FIG. 6A, device **600** displays video conference request interface **604-1** depicting an incoming request from “John” to participate in a live video conference. Video conference request interface **604-1** includes camera preview **606**, options menu **608**, framing mode affordance **610**, and background blur affordance **611**. Camera preview **606** is a real time representation of the video feed from camera **602** that is enabled for output for the video conference session (should the incoming request be accepted). In FIG. 6A, camera **602** is currently enabled, and camera preview **606** depicts a representation of “Jane,” who is currently positioned in front of device **600** and within the field-of-view of camera **602**.

[0230] Options menu **608** includes various selectable options for controlling one or more aspects of the video conference. For example, mute option **608-1** is selectable to mute the transmission of any audio detected by device **600**. Flip option **608-2** is selectable to switch the camera being used for the video conference between camera **602** and one or more different cameras, such as a camera on the opposite side of device **600** from camera **602** (e.g., a rear-facing camera). Accept option **608-3** is selectable to accept the request to participate in the live video conference. Decline option **608-4** is selectable to decline the request to participate in the live video conference.

[0231] Background blur affordance **611** is selectable to enable or disable a background blur mode for the video conference session. In the embodiment depicted in FIG. 6A, the background blur mode is disabled by default when device **600** receives or initiates a request to participate in a video conference. Background blur affordance **611** is, therefore, depicted having an unselected state, as indicated by the lack of bolding of the affordance in FIG. 6A. In some embodiments, the background blur mode is enabled by default when device **600** receives or initiates a request to participate in a video conference (e.g., and the affordance is bolded). The background blur feature is discussed in greater detail with respect to FIGS. 12A-12U.

[0232] Framing mode affordance **610** is selectable to enable or disable an automatic framing mode for the video conference session. In the embodiment depicted in FIG. 6A, the automatic framing mode is enabled by default when device **600** receives or initiates a request to participate in a video conference. Framing mode affordance **610** is, therefore, depicted having a selected state, as indicated by bolding of the affordance in FIG. 6A. In some embodiments, the automatic framing mode is disabled by default when device **600** receives or initiates a request to participate in a video conference (e.g., and there is no bolding of the affordance).

[0233] When the automatic framing mode is enabled, device **600** detects conditions of a scene that is within the field-of-view of the enabled camera (e.g., camera **602**) (e.g., the presence and/or position of one or more subjects within the field-of-view of the camera), and, in real time, adjusts the field-of-view of the video output for the video conference session (as represented in the camera preview) (e.g., without moving camera **602** or device **600**), based on the conditions of the scene or changes detected in the scene within the field-of-view of the camera (e.g., changes in the position and/or movement of subject(s) during the video conference session). Various embodiments of the automatic framing mode are discussed throughout the present disclosure.

[0234] For example, in the embodiments depicted in FIGS. 6A-6Q, device **600** automatically adjusts (e.g., reframes) the displayed output video feed field-of-view to maintain display of one or more subjects (e.g., Jane) within the field-of-view of the camera (e.g., camera **602**). Because device **600** automatically adjusts the displayed portion of the camera's field-of-view to include display of Jane, Jane is able to move about the scene while participating in the video conference, without having to manually adjust the perspective of the outgoing video feed to account for her movement or other changes in the scene. As a result, participants of the video conference require less interaction with device **600** because device **600** automatically reframes the outgoing video feed so that the remote participants, who receive the video feed from device **600**, are able to continuously view Jane as she moves about her environment. Other benefits of the automatic framing mode are noted in the disclosure below. Various features of the automatic framing mode are discussed with respect to the embodiments depicted in FIGS. 6A-6Q, FIGS. 8A-8R, and FIGS. 10A-10J. One or

more of these features can be combined with other features of the automatic framing mode, as discussed herein.

[0235] FIG. 6A depicts input **612** (e.g., a tap input) on framing mode affordance **610** and input **614** on accept option **608-3**. In response to detecting input **612**, device **600** disables the automatic framing mode. In response to detecting input **614** after input **612**, device **600** accepts the video conference call and joins the video conference session with the automatic framing mode disabled, as depicted in FIG. 6B. If device **600** does not detect input **612**, or if input **612** is an input to enable the automatic framing mode (e.g., framing mode affordance **610** was unselected when input **612** was received), device **600** accepts the video conference call in response to input **614** and joins the video conference session with the automatic framing mode enabled, as depicted in FIG. 6F.

[0236] FIG. 6B depicts scene **615**, which is the physical environment within field-of-view **620** of camera **602**. In the embodiment depicted in FIG. 6B, Jane **622** is sitting on couch **621** with device **600** positioned in front of her (e.g., on a table) with door **618** in the background. Field-of-view **620** represents the field-of-view of camera **602** (e.g., a maximum field-of-view of camera **602** or the wide angle field-of-view of camera **602**), which encompasses scene **615**. Portion **625** indicates a portion of field-of-view **620** that is currently outputted (or selected for output) for the video conference session (e.g., portion **625** represents the displayed portion of the camera field-of-view). As such, portion **625** indicates the portion of scene **615** that is currently represented in the displayed video feed depicted in camera preview **606**. Field-of-view **620** is sometimes referred to herein as the available field-of-view, entire field-of-view, or the camera field-of-view, and portion **625** is sometimes referred to herein as the video feed field-of-view.

[0237] When the incoming video conference request is accepted, video conference request interface **604-1** transitions to video conference interface **604**, as depicted in FIG. 6B. Video conference interface **604** is similar to video conference request interface **604-1**, but is updated, for example, to depict incoming video feed **623**, which includes the video data received at device **600** for a remote participant of the video conference. Video feed **623** includes representation **623-1** of John, who is the remote participant in the video conference with Jane **622**. Camera preview **606** is now reduced in size, compared to FIG. 6A, and shifted toward the upper-right corner of display **601**. Camera preview **606** includes representation **622-1** of Jane and a representation of the environment that is captured within portion **625** (e.g., the video feed field-of-view). Options menu **608** is updated to include framing mode affordance **610**. In some embodiments, framing mode affordance **610** is displayed in camera preview **606**, as illustrated in FIG. 6O, for example. As shown in FIG. 6B, framing mode affordance **610** is shown in an unselected state, indicating that the automatic framing mode is disabled.

[0238] In some embodiments, when the automatic framing mode is disabled, device **600** outputs a predetermined portion of the available field-of-view of camera **602** as the video feed field-of-view. An example of such an embodiment is depicted in FIGS. 6B-6D, where portion **625** represents a predetermined portion of the available field-of-view of camera **602** that is located in the center of field-of-view **620**. In some embodiments, when the automatic framing mode is disabled, device **600** outputs the entire field-of-view **620** as the video feed field-of-view. An example of such an embodiment is depicted in FIG. 10A.

[0239] In FIG. 6B, Jane is participating in a video conference with John using device **600**. Similarly, John is participating in the video conference with Jane using a device that includes one or more features of devices **100**, **300**, **500**, or **600**. For example, John is using a tablet similar to device **600** (e.g., John's tablet **600a** in FIGS. 10H-10J and 12B-12N). Accordingly, John's device displays a video conference interface similar to video conference interface **604**, except that the camera preview on John's device displays the video feed captured from John's device (what is currently depicted in video feed **623** in FIG. 6B), and the incoming video feed on John's device displays the video feed output from Jane's device **600** (what is currently depicted in camera preview **606** in FIG. 6B).

[0240] In FIG. 6C, device **600** is moved with respect to scene **615** and, as a result, field-of-view **620**, and portion **625**, pivot with device **600**. Because the automatic framing mode is disabled, device **600** does not automatically adjust the video feed field-of-view to remain fixed on Jane's position within field-of-view **620**. Instead, the perspective of the video feed moves with device **600**, and Jane **622** is no longer centered in the video feed field-of-view, as indicated by portion **625** and depicted in camera preview **606**, which shows the background of scene **615** and a portion of representation **622-1** of Jane. In the embodiment depicted in FIG. 6C, the movement of device **600** is a pivot, however, the movement of field-of-view **620** and portion **625** could be caused by other movements such as tilting, rotating, and/or moving (e.g., forward, backward, and/or side-to-side) device **600** in a manner such that Jane **622** does not remain located within portion **625**.

[0241] In FIG. 6D, device **600** is returned to its original position, and Jane **622** is bending down, moving out of portion **625**. A gain, because the automatic framing mode is disabled, device **600** does not automatically adjust the video feed field-of-view to follow Jane's movement as she moves out of portion **625**. The video feed field-of-view remains stationary while Jane **622** moves, and representation **622-1** of Jane is mostly out of frame in camera preview **606**.

[0242] In FIG. 6D, device **600** detects input **626** (e.g., a tap input) on framing mode affordance **610**. In response, device **600** bolds framing mode affordance **610** (to indicate its selected/enabled state) and enables the automatic framing mode, as shown in FIG. 6E. When automatic framing mode is enabled, device **600** automatically adjusts the displayed video feed field-of-view based on conditions detected within scene **615**. In the embodiment depicted in FIG. 6E, device **600** adjusts the displayed video feed field-of-view to center on Jane's face. Accordingly, device **600** updates camera preview **606** to include representation **622-1** of Jane centered in the frame and, in the background, representation **621-1** of the couch upon which she is sitting. Field-of-view **620** remains fixed because the position of camera **602** remains unchanged. However, the position of Jane's face within field-of-view **620** does change. As a result, device **600** adjusts (e.g., repositions) the displayed portion of field-of-view **620** so that Jane remains positioned within camera preview **606**. This is represented in FIG. 6E by the repositioning of portion **625** so that it is centered on Jane's face. In FIG. 6E, portion **627** corresponds to the prior location of portion **625** and, thus, represents the portion of field-of-view **620** that was previously displayed in camera preview **606** (before the adjustment resulting from enabling automatic framing mode).

[0243] FIG. 6F depicts scene **615** and device **600** when the automatic framing mode is enabled in response to input **614** to accept the incoming request to join the video conference while the automatic framing mode is enabled (or, alternatively, in response to input **626** to enable the automatic framing mode). Accordingly, device **600** displays representation **622-1** of Jane centered in camera preview **606**.

[0244] In FIG. 6G, device **600** is moved in a manner similar to that discussed above with respect to FIG. 6C. However, because the automatic framing mode is enabled in FIG. 6G, device **600** automatically adjusts the video feed field-of-view (portion **625**) relative to field-of-view **620** to remain fixed on Jane's face, which has changed position relative to device **600** and camera **602** in response to the pivot of device **600**. Accordingly, camera preview **606** continues to display representation **622-1** of Jane centered in the video feed field-of-view. The adjustment of the video feed field-of-view is represented by the change in the position of portion **625** within field-of-view **620**. For example, when compared to FIG. 6F, the relative position of portion **625** has moved from a centered location within field-of-view **620** (represented in FIG. 6G by portion **627**), to the shifted position depicted in FIG. 6G. In the embodiment depicted in FIG. 6G, the movement of device **600** is a pivot, however, device **600** can automatically adjust the displayed video feed field-of-view in response to other movements such as tilting, rotating, and/or moving (e.g., forward, backward, and/or side-to-side) device **600** in a manner such that Jane **622** remains located within field-of-view **620**.

[0245] In FIG. 6H, device **600** is returned to its original position, and Jane **622** has moved to a

standing position next to couch **621**. Device **600** detects the updated position of Jane **622** in scene **615**, and updates the video feed field-of-view to maintain its position on Jane **622**, as shown in camera preview **606**. Accordingly, portion **625** has moved from its prior position represented by portion **627** to the updated position around Jane's face, as depicted in FIG. **6H**.

[0246] In some embodiments, the transition from the field-of-view depicted in camera preview **606** in FIG. **6G** to the field-of-view depicted in camera preview **606** in FIG. **6H** is executed as a match cut. For example, the transition from camera preview **606** in FIG. **6G** to camera preview **606** in **6H** is a match cut that is executed when Jane **622** has moved from her seated position on couch **621** to her standing position adjacent the couch. The result of the match cut is that the camera preview **606** appears to transition from a first camera view in FIG. **6G**, to a different camera view in FIG. **6H** (the different camera view optionally having a same zoom level as the camera view in FIG. **6G**). However, the actual field-of-view of camera **602** (e.g., field-of-view **620**) has not changed. Rather, only the portion of the field-of-view that is displayed (portion **625**) has changed position within field-of-view **620**.

[0247] FIG. **6I** is an embodiment similar to that depicted in FIG. **6H**, but with camera preview **606** having a greater, zoomed out field-of-view when compared to that shown in FIG. **6H**. Specifically, the embodiment depicted in FIG. **6I** illustrates a jump cut transition from the camera preview in FIG. **6G** to the camera preview in FIG. **6O**. The jump cut transition is depicted by transitioning from camera preview **606** in FIG. **6G**, to camera preview **606** in FIG. **6I**, which has a larger (e.g., zoomed out) field-of-view. Accordingly, the video feed field-of-view in FIG. **6I** (represented by portion **625**) is a larger portion of field-of-view **620**. This is illustrated by the size difference between portion **625** (corresponding to the camera preview in FIG. **6I**) and portion **627** (corresponding to the camera preview in FIG. **6G**).

[0248] FIGS. **6H** and **6I** illustrate specific embodiments of a transition between different camera previews. In some embodiments, other transitions can be executed such as, for example, by continuously moving (e.g., panning and/or zooming) the video feed field-of-view within field-of-view **620** to follow Jane **622** as she moves about scene **615**.

[0249] In FIG. **6J**, Jane **622** has moved away from device **600**, behind couch **621**. In response to detecting the change in position of Jane **622**, device **600** performs a transition (e.g., a jump cut transition) where camera preview **606** depicts a zoomed in view of Jane in scene **615**. In the embodiment depicted in FIG. **6J**, device **600** zooms in on Jane **622** (e.g., reduces the field-of-view) when she moves away from the camera (e.g., by a threshold distance). In some embodiments, device **600** zooms out from Jane **622** (e.g., enlarges the displayed field-of-view) as she moves toward the camera (e.g., by a threshold distance). For example, if Jane **622** were to move from her position in FIG. **6J** to her previous position in FIG. **6I**, camera preview **606** will zoom out to the camera preview depicted in FIG. **6I**.

[0250] In FIG. **6K**, another subject, Jack **628**, walks into scene **615**. Device **600** continues to display video conference interface **604** with the same camera preview as depicted in FIG. **6J**. In the embodiment depicted in FIG. **6K**, device **600** detects Jack **628** within field-of-view **620**, but maintains the same video feed field-of-view while Jack **628** is moving about the scene or until Jack **628** moves to a particular location in the scene (e.g., closer to the center of the scene). In some embodiments, device **600** displays a prompt to adjust the camera preview when an additional subject is detected within field-of-view **620**. Examples of such prompts are discussed in greater detail below with respect to FIG. **6P** and the embodiments depicted in FIGS. **8A-8J**.

[0251] In FIG. **6L**, device **600** reframes camera preview **606** to include representation **628-1** of Jack **628**, who is now standing next to Jane **622** in scene **615**. In some embodiments, device **600** automatically adjusts camera preview **606** in response to determining that Jack **628** stops moving about scene **615** and/or that he is exhibiting behavior indicative of a desire to participate in the video conference. Examples of such behavior can include turning attention to device **600** and/or camera **602**, focusing/looking at, or in the general direction of, camera **602**, remaining still (e.g., for

at least a particular amount of time), being positioned next to participants of the video conference (e.g., Jane **622**), facing towards device **600**, speaking, and the like. In some embodiments, when the automatic framing mode is enabled, device **600** automatically adjusts the camera preview in response to detecting a change in the number of subjects detected within field-of-view **620** (such as when Jack **628** entered scene **615**). As depicted in FIG. **6L**, portion **625** represents the adjusted video feed field-of-view, and portion **627** represents the dimensions of the video feed field-of-view prior to being adjusted in FIG. **6L**. When compared to the video feed field-of-view in FIG. **6K**, the adjusted field-of-view in FIG. **6L** is zoomed out and re-centered on Jane **622** and Jack **628**, as depicted in camera preview **606**.

[0252] In FIG. **6M**, Jane **622** begins to move away from Jack **628** and out of the video feed field-of-view represented by portion **625** and camera preview **606**. While detecting Jane's movement, device **600** maintains (e.g., does not adjust) the field-of-view of camera preview **606**. In some embodiments, device **600** readjusts the size of the video feed field-of-view as Jane moves away from Jack, such that both subjects remain within the video feed field-of-view (the camera preview). In some embodiments, after Jane has moved away from Jack, device **600** readjusts the video feed field-of-view after Jane stops moving, such that both subjects are within the camera preview.

[0253] In FIG. **6N**, device **600** detects Jane **622** is no longer within portion **625** of FIG. **6M** (e.g., portion **627** in FIG. **6N**) and, in response, adjusts the displayed video feed field-of-view to zoom in on Jack **628**. Accordingly, device **600** displays video conference interface **604** with camera preview **606** having a zoomed in view of Jack **628**. FIG. **6N** depicts portion **625** having a smaller size than portion **627**, to indicate the change in the displayed video feed field-of-view.

[0254] In some embodiments, when the automatic framing mode is enabled, device **600** displays one or more prompts to adjust the video feed field-of-view to include additional participants, in response to detecting additional subjects within field-of-view **620**. Examples of such embodiments are described below with respect to FIGS. **6O-6Q**.

[0255] FIG. **6O** depicts an embodiment similar to that illustrated in FIG. **6N**, but with framing mode affordance **610** displayed in the camera preview region instead of in options menu **608**. Device **600** displays framing indicators **630** positioned around representation **628-1** of Jack, to indicate that device **600** detects the presence of a face (e.g., Jack's face) in the camera preview. In some embodiments, the framing indicators also indicate that the automatic framing mode is enabled and that the detected face is being tracked while the face is detected within portion **625**, camera preview **606**, and/or field-of-view **620**. Jack **628** is currently the only participant of the video conference who is located in scene **615**.

[0256] In FIG. **6P**, device **600** detects that Jane **622** has entered scene **615**, within field-of-view **620**. In response, device **600** updates video conference interface **604** by displaying add affordance **632** in the camera preview region. Add affordance **632** is selectable to adjust the displayed video feed field-of-view to include additional subjects detected within field-of-view **620**.

[0257] In FIG. **6P**, device **600** detects input **634** on add affordance **632** and, in response, adjusts portion **625** such that camera preview **606** includes representation **622-1** of Jane with representation **628-1** of Jack, as depicted in FIG. **6Q**. In some embodiments, Jane **622** is added as a participant of the video conference. Device **600** also recognizes the presence of Jane's face and displays framing indicators **630** around the representation of Jane's face (in addition to those around the representation of Jack's face) to indicate that the framing mode is enabled and that Jane's face is being tracked while it is detected within portion **625**, camera preview **606**, and/or field-of-view **620**.

[0258] FIGS. **7A-7B** depict a flow diagram illustrating a method for managing a live video communication session using an electronic device in accordance with some embodiments. Method **700** is performed at a computer system (e.g., a smartphone, a tablet) (e.g., **100**, **300**, **500**, **600**) that is in communication with a display generation component (e.g., **601**) (e.g., a display controller, a touch-sensitive display system), one or more cameras (e.g., **602**) (e.g., an infrared camera; a depth

camera; a visible light camera), and one or more input devices (e.g., a touch-sensitive surface). Some operations in method **700** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

[0259] As described below, method **700** provides an intuitive way for managing a live video communication session. The method reduces the cognitive burden on a user for managing a live video communication session, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to manage a live video communication session faster and more efficiently conserves power and increases the time between battery charges.

[0260] In method **700**, computer system (e.g., **600**) displays (**702**), via the display generation component (e.g., **601**), a communication request interface (e.g., **604-1** in FIG. **6A**) (e.g., an interface for an incoming or outgoing live video communication session (e.g., a live video chat session, a live video conference session)).

[0261] The computer system (e.g., **600**) displays (**704**) the communication request interface (e.g., **604-1** in FIG. **6A**) including a first selectable graphical user interface object (e.g., **608-3**) (e.g., an “accept” affordance) associated with a process for joining a live video communication session. In some embodiments, the accept affordance is selectable to initiate a process for accepting an incoming request to join a live video communication session. In some embodiments, the first selectable graphical user interface object is a “cancel” affordance that is selectable to initiate a process for canceling or terminating an outgoing request to join a live video communication session.

[0262] The computer system (e.g., **600**) displays (**706**) (e.g., concurrently with **704**) the communication request interface (e.g., **604-1** in FIG. **6A**) including a second selectable graphical user interface object (e.g., **610**) (e.g., a “framing mode” affordance; a “background blur” affordance; a “dynamic video quality” affordance) associated with a process for selecting between using a first camera mode for the one or more cameras (e.g., an automatic framing mode; a background blur mode; a dynamic video quality mode) and using a second camera mode for the one or more cameras (e.g., a mode different from the first camera mode (e.g., a mode in which the automatic framing mode is disabled, a mode in which the background blur mode is disabled, and/or a mode in which the dynamic video quality mode is disabled)) during a live video communication session.

[0263] In some embodiments, the framing mode affordance is selectable to enable/disable a mode (e.g., automatic framing mode) for: 1) tracking, during a live video communication session, a position and/or location of one or more subjects detected within a field-of-view of the one or more cameras, and 2) automatically adjusting a displayed view of the subject(s), during the live video communication session, based on the tracking of the subject.

[0264] In some embodiments, the background blur affordance is selectable to enable/disable a mode (e.g., background blur mode) in which a visual effect (e.g., a blurring, darkening, shading, obscuring, desaturating, or otherwise deemphasizing effect) is applied to a background portion of the camera field-of-view (e.g., **606**) (e.g., a camera preview; an output video feed of the camera field-of-view) during the live video communication session (e.g., without applying the visual effect to the portion of the camera field-of-view that includes the representation of the subject (e.g., a foreground portion) (e.g., **622-1**)).

[0265] In some embodiments, the dynamic video quality affordance is selectable to enable/disable a mode (e.g., dynamic video quality mode) for outputting (e.g., transmitting and, optionally, displaying) a camera field-of-view with portions having different degrees of compression and/or video qualities. For example, portions of the camera field-of-view that include a detected face (e.g., **622-1**) are compressed less than portions of the camera field-of-view that do not include a detected face. In some embodiments, there is an inverse relationship between the degree of compression and video quality (e.g., greater compression results in lower video quality; less compression results in higher video quality). As such, the video feed for the live video communication session can be

transmitted (e.g., by the computer system (e.g., **600**)) to a recipient device of a remote participant of the live video communication session so that the portions of the camera field-of-view that include a detected face can be displayed at the recipient device with a higher video quality than the portions that do not include a detected face (due to the reduced compression of the portions of the camera field-of-view that include a detected face and the increased compression of the portions of the camera field-of-view that do not include a detected face). In some embodiments, the computer system varies the amount of compression as the video bandwidth changes (e.g., increases, decreases). For example, the degree of compression of the portion(s) of the camera field-of-view (e.g., the camera feed) that does not include the detected face(s) varies (e.g., increases or decreases with the corresponding change in bandwidth) while the degree of compression of the portion(s) of the camera field-of-view that includes the detected face(s) remains constant (or, in some embodiments, varies at a lesser rate or by a lesser amount than the portion(s) of the camera field-of-view that does not include the face(s)).

[0266] While displaying the communication request interface (e.g., **604-1** in FIG. **6A**), the computer system (e.g., **600**) receives (**708**), via the one or more input devices (e.g., **601**), a set of one or more inputs (e.g., **612** and/or **614**) that includes a selection (e.g., **614**) of the first selectable graphical user interface object (e.g., **608-3**) (e.g., the set of one or more inputs includes a selection of the accept affordance and, optionally, a selection of the framing mode affordance, background blur affordance, and/or dynamic video quality affordance).

[0267] In response to receiving the set of one or more inputs (e.g., **612** and/or **614**) that includes a selection (e.g., **614**) of the first selectable graphical user interface object (e.g., **608-3**), the computer system (e.g., **600**) displays (**710**), via the display generation component (e.g., **601**), a live video communication interface (e.g., **604**) for the live video communication session.

[0268] While displaying the live video communication interface (e.g., **604**), the computer system (e.g., **600**) detects (**712**) a change in a scene (e.g., **615**) (e.g., a change in position of a subject) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**). In some embodiments, the scene includes a representation of the subject and, optionally, one or more additional subjects in the field of view of the one or more cameras.

[0269] In response (**714**) to detecting the change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**). The computer system (e.g., **600**) perform one or more of steps **716** and **718** in method **700**.

[0270] In accordance with a determination that the first camera mode is selected for use (e.g., enabled) (e.g., if the first camera mode is disabled by default, the set of one or more inputs includes a selection of the second selectable graphical user interface object; if the first camera mode is enabled by default, the set of one or more inputs does not include a selection of the second selectable graphical user interface object) (e.g., the framing mode affordance is in a selected state when the accept affordance is selected), the computer system (e.g., **600**) adjusts (**716**) (e.g., automatically; without user input) a representation of the field-of-view of the one or more cameras (e.g., **606**) (e.g., a displayed field-of-view of the one or more cameras) during the live video communication session based on the detected change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., automatically adjusting the representation of the field-of-view of the one or more cameras (e.g., based on a detected position of a subject) during the live video communication session). Adjusting a representation of the field-of-view of the one or more cameras during the live video communication based on the detected change in the scene in the field-of-view of the one or more cameras when the first camera mode is selected for use enhances the video communication session experience by automatically adjusting the field-of-view of the cameras (e.g., to maintain display of the subject/user) without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user

mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0271] In some embodiments, adjusting the representation of the field-of-view of the one or more cameras (e.g., **606**) during the live video communication session includes: 1) in accordance with a determination that a first set of criteria is met, including that the scene includes a subject (e.g., **622**) (e.g., one or more users of the computer system) detected at a first position (within the field-of-view **620** of the one or more cameras; in FIG. **6F**), displaying the live video communication interface **604** having a representation of a first field-of-view (e.g., **606** in FIG. **6F**) (e.g., the live video communication interface is displayed with a first digital zoom level and a first displayed portion of the field-of-view of the one or more cameras) (in some embodiments, the representation of the first field-of-view includes a representation of the subject while the subject is located at the first position); and 2) in accordance with a determination that a second set of criteria is met, including that the subject is detected at a second position (e.g., **625** in FIG. **6H**) different from the first position, displaying the live video communication interface having a representation of a second field-of-view (e.g., **606** in FIG. **6H**) different from the representation of the first field-of-view (e.g., the live video communication interface is displayed with a second digital zoom level and/or a second displayed portion of the field-of-view of the one or more cameras) (e.g., a representation of a field-of-view that is zoomed in, zoomed out, and/or panned in a direction relative to the representation of the first field-of-view) (in some embodiments, the representation of the second field-of-view includes a representation of the subject while the subject is located at the second position). In some embodiments, when the first camera mode is selected for use (e.g., enabled), the representation of the field-of-view changes automatically (e.g., without changing the actual field-of-view of the one or more cameras) in response to a detected change in position of the subject and/or in response to detecting a second subject entering or leaving the field-of-view of the one or more cameras. For example, the representation of the field-of-view changes to track the position of the subject and adjusts a displayed position and/or zoom level (e.g., digital zoom level) to more prominently display the subject (e.g., changing the digital zoom level to appear to be zooming in on the subject as they move away from the camera; changing the digital zoom level to appear to be zooming out from the subject as they move toward the camera; changing the displayed portion of the field-of-view of the one or more cameras to appear to be panning in a particular direction as the subject moves in that direction).)

[0272] In accordance with a determination that the second camera mode is selected for use (e.g., enabled) (e.g., the framing mode affordance is in an unselected or deselected state when the accept affordance is selected), the computer system (e.g., **600**) forgoes (**718**) adjusting a representation of the field-of-view of the one or more cameras during the live video communication session (e.g., as depicted in FIG. **6D**) (e.g., based on the detected change in the scene in the field-of-view of the one or more cameras) (e.g., when the first camera mode is disabled, the live video communication interface maintains a same (e.g., default) representation of the field-of-view, regardless of whether or not the subject is positioned within the scene in the field-of-view of the one or more cameras, and regardless of where the subject is positioned within the field-of-view of the one or more cameras). In some embodiments, forgoing adjusting the representation of the field-of-view of the one or more cameras during the live video communication session includes: 1) while (e.g., in accordance with a determination that) the subject has the first position within the scene in the field-of-view of the one or more cameras (e.g., as depicted in FIG. **6B**), displaying the live video communication interface having a representation of the first field-of-view (e.g., **606** in FIG. **6B**); and 2) while (e.g., in accordance with a determination that) the subject has the second position within the scene in the field-of-view of the one or more cameras (e.g., in FIG. **6D**), displaying the live video communication interface having the representation of the first field-of-view (e.g., **606** in FIG. **6D**). In some embodiments, the representation of the first field-of-view is a standard or default

representation of a field-of-view that does not change based on a change in the scene (e.g., a change in position of the subject with respect to the one or more cameras or a second subject entering or leaving the field-of-view of the one or more cameras).

[0273] In some embodiments, the detected change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) includes a detected change in a set of attention-based factors for one or more subjects (e.g., **622**; **628**) in the scene (e.g., a first subject turns their attention to (e.g., focuses on, looks at) the one or more cameras (e.g., based on a gaze position, head position, and/or body position of the first subject)). In some embodiments, the computer system (e.g., **600**) adjusts the representation of the field-of-view of the one or more cameras (e.g., **606**) during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras, including adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on (in some embodiments, in response to) the detected change in the set of attention-based factors for the one or more subjects in the scene (e.g., as depicted in FIG. **6L**). Adjusting the representation of the field-of-view of the one or more cameras during the live video communication based on the detected change in the set of attention-based factors for the one or more subjects in the scene enhances the video communication session experience by automatically adjusting the field-of-view of the cameras based on the set of attention-based factors of the subjects in the scene without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0274] In some embodiments, when the automatic framing mode is enabled, the computer system (e.g., **600**) adjusts (e.g., reframes) the displayed portion of the field-of-view of the one or more cameras (e.g., **606**) based on one or more attention-based factors of subjects (e.g., **622**; **628**) detected within the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**). For example, when the first subject turns attention to the one or more cameras, the representation of the field-of-view of the one or more cameras changes (e.g., zooms out) to include a representation of the first subject or to focus on the first subject. Conversely, when the first subject's attention shifts away from the one or more cameras, the representation of the field-of-view of the one or more cameras changes (e.g., zooms in) to exclude a representation of the first subject (e.g., if other subjects remain in the field-of-view of the one or more cameras) or to focus on another subject.

[0275] In some embodiments, the set of attention-based factors includes a first factor that is based on a detected focal plane of a first subject (e.g., **628**) of the one or more subjects in the scene (e.g., as depicted in FIG. **6L**). Adjusting the representation of the field-of-view of the one or more cameras during the live video communication based on the detected focal plane of a first subject of the one or more subjects in the scene enhances the video communication session experience by automatically adjusting the field-of-view of the cameras when the focal plane of the first subject meets criteria without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the first subject's attention is determined based on the first subject's focal plane. For example, if the first subject's focal plane aligns (e.g., is co-planar) with the focal plane of the one or more cameras or the focal plane of another subject participating in the live video communication session, then the first subject is considered to be paying attention to the one or more cameras. The first subject is,

therefore, considered to be an active participant in the live video communication session, and the computer system then adjusts the representation of the field-of-view of the one or more cameras to include the first subject in the live video communication interface.

[0276] In some embodiments, the set of attention-based factors includes a second factor that is based on whether a second subject (e.g., **628**) of the one or more subjects in the scene (e.g., **615**) (e.g., a subject other than the first subject) is determined to be looking at the one or more cameras (e.g., **602**). Adjusting the representation of the field-of-view of the one or more cameras during the live video communication based on whether a second subject in the scene is determined to be looking at the one or more cameras enhances the video communication session experience by automatically adjusting the field-of-view of the cameras when the second subject looks at the camera without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the second subject's attention is determined based on whether the second subject is looking at the one or more cameras. If so, the second subject is considered to be paying attention to the one or more cameras and is, therefore, considered to be an active participant in the live video communication session. Accordingly, the computer system adjusts the representation of the field-of-view of the one or more cameras to include the second subject in the live video communication interface.

[0277] In some embodiments, the detected change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) includes a detected change in a number (e.g., amount; quantity) of subjects (e.g., **622**; **628**) detected in the scene (e.g., a detected change in a number of subjects detected in the scene that satisfy a first set of criteria (e.g., the subject(s) is positioned in the field-of-view of the one or more cameras and, optionally, is stationary) (e.g., one or more subjects entering or exiting the scene in the field-of-view of the one or more cameras)). In some embodiments, adjusting the representation of the field-of-view of the one or more cameras (e.g., **606**) during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras includes adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on (in some embodiments, in response to) the detected change in the number of subjects detected in the scene (e.g., that satisfy the first set of criteria) (e.g., as depicted in FIG. 6L and/or FIG. 6N). Adjusting the representation of the field-of-view of the one or more cameras during the live video communication based on the detected change in the number of subjects detected in the scene enhances the video communication session experience by automatically adjusting the field-of-view of the cameras when the number of subjects in the scene changes without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, when the automatic framing mode is enabled, the computer system (e.g., **600**) adjusts (e.g., reframes) the displayed portion of the field-of-view of the one or more cameras based on the number of subjects detected within the field-of-view of the one or more cameras. For example, when the number of subjects detected in the scene increases, the representation of the field-of-view of the one or more cameras changes (e.g., zooms out) to include the additional subjects (e.g., along with the subjects that were previously detected). Similarly, when the number of subjects detected in the scene decreases, the representation of the field-of-view of the one or more cameras changes (e.g., zooms in) to capture the subject(s) remaining in the scene.

[0278] In some embodiments, adjusting the representation of the field-of-view of the one or more cameras (e.g., **606**) during the live video communication session based on the detected change in the number of subjects detected in the scene is based on a determination of whether a subject in the field-of-view (e.g., **620**) is stationary (e.g., relatively stationary; not moving more than a threshold amount of movement in the field-of-view of the one or more cameras). Adjusting the representation of the field-of-view of the one or more cameras during the live video communication based on whether a subject in the field-of-view is stationary enhances the video communication session experience by automatically adjusting the field-of-view of the cameras when the subject in the scene is stationary without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0279] In some embodiments, when the automatic framing mode is enabled, the computer system (e.g., **600**) considers a detected subject (e.g., **628**) to be a participant in the live video communication session when the subject does not move more than a threshold amount of movement. When the subject is considered an active participant, the computer system adjusts (e.g., reframes) the displayed portion of the field-of-view of the one or more cameras (e.g., **606**) to then include a representation of the subject (e.g., as depicted in FIG. 6L). This prevents the computer system from automatically reframing the displayed portion of the field-of-view of the one or more cameras based on extraneous movement in the scene (e.g., such as that caused by a subject passing in the background or a child jumping around in the field-of-view of the one or more cameras), which would be distracting to participants/viewers of the live video communication session.

[0280] In some embodiments, the representation of the field-of-view of the one or more cameras (e.g., **606**) has a first represented field-of-view before the computer system (e.g., **600**) detects the change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., the computer system is displaying a portion of the field-of-view of the one or more cameras before the change in the scene is detected). In some embodiments, the change in the scene in the field-of-view of the one or more cameras includes a detected movement of a third subject (e.g., **622**) from a first portion (e.g., **625** in FIG. 6G) of the field-of-view of the one or more cameras that corresponds to (e.g., is represented by; is included in) the first represented field-of-view (e.g., **606** in FIG. 6G) to a second portion of the field-of-view of the one or more cameras (e.g., portion **625** in FIG. 6H) that does not correspond to (e.g., is not represented by; is not included in) the first represented field-of-view (e.g., the third subject moves from a portion of the scene that corresponds to a portion of the field-of-view of the one or more cameras that is displayed prior to the third subject's movement to a portion of the scene that corresponds to a portion of the field-of-view of the one or more cameras that is not displayed prior to the third subject's movement). In some embodiments, adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on (in some embodiments, in response to) the detected change in the scene in the field-of-view of the one or more cameras includes: in accordance with a determination that a fourth subject (e.g., **628**) is not detected in the scene in the first portion of the field-of-view of the one or more cameras, adjusting the representation of the field-of-view from the first represented field-of-view to a second represented field-of-view (e.g., different from the first represented field-of-view) that corresponds to (e.g., represents; displays; includes) the second portion of the field-of-view of the one or more cameras (e.g., display camera preview **606** as depicted in FIG. 6H). In accordance with a determination that the fourth subject (e.g., **628**) is detected in the scene in the first portion of the field-of-view of the one or more cameras (e.g., Jack **628** is located in portion **625** in FIG. 6M as Jane **622** leaves the frame), forgoing adjusting the representation of the field-of-view from the first represented field-

of-view to the second represented field-of-view (e.g., continuing to display the first represented field-of-view) (e.g., in FIG. 6M, device 600 continues to display camera preview 606 depicting portion 625 as Jane 622 leaves and Jack 628 remains). Selectively adjusting the representation of the field-of-view of the one or more cameras during the live video communication session from the first represented field-of-view to the second represented field-of-view based on whether or not a subject (e.g., the fourth subject) is detected in the scene in the first portion of the field-of-view of the one or more cameras after another subject (e.g., the third subject) leaves the first portion of the field-of-view enhances the video communication session experience by automatically adjusting the field-of-view of the cameras based on whether or not additional subjects remain in the first portion of the field-of-view when another subject leaves without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, when the automatic framing mode is enabled, the computer system does not track (e.g., follow; adjust the representation of the field-of-view in response to) movement of a subject that leaves the displayed field-of-view when another subject remains in the displayed field-of-view.

[0281] In some embodiments, the representation of the field-of-view of the one or more cameras (e.g., 606) has a third represented field-of-view (e.g., in FIG. 6F) before detecting the change in the scene (e.g., 615) in the field-of-view (e.g., 620) of the one or more cameras (e.g., 602) (e.g., the computer system is displaying a portion of the field-of-view of the one or more cameras before the change in the scene is detected). In some embodiments, the change in the scene in the field-of-view of the one or more cameras includes movement of a fifth subject (e.g., 622) from a third portion (e.g., 625 in FIG. 6F) of the field-of-view of the one or more cameras that corresponds to (e.g., is represented by; is included in) the third represented field-of-view to a fourth portion (e.g., 625 in FIG. 6H) of the field-of-view of the one or more cameras that does not correspond to (e.g., is not represented by; is not included in) the third represented field-of-view. In some embodiments, adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on (in some embodiments, in response to) the detected change in the scene in the field-of-view of the one or more cameras includes: displaying the representation of the field-of-view of the one or more cameras having a fourth represented field-of-view (e.g., 606 in FIG. 6H) (e.g., different from the third represented field-of-view; in some embodiments, including a subset of the third represented field-of-view) in the live video communication interface (e.g., 604) that corresponds to the fourth portion of the field-of-view of the one or more cameras and includes a representation (e.g., 622-1) of the fifth subject (e.g., replacing display of the third represented field-of-view with the fourth represented field-of-view, which includes a representation of the fifth subject (and, in some embodiments, includes a subset of the third represented field-of-view)). Ceasing displaying the third represented field-of-view, and displaying the fourth represented field-of-view that corresponds to the fourth portion of the field-of-view and includes a representation of the fifth subject, enhances the video communication session experience by automatically adjusting the field-of-view of the cameras to maintain display of the subject when the subject moves to a different location in the scene without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0282] In some embodiments, adjusting the representation of the field-of-view of the one or more

cameras (e.g., **606**) during the live video communication session based on the detected change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) further includes ceasing displaying the representation of the field-of-view of the one or more cameras having the third represented field-of-view in the live video communication interface (e.g., **606** in FIG. **6F**). In some embodiments, when the automatic framing mode is enabled and the computer system (e.g., **600**) detects a subject (e.g., **622**) move out of frame (e.g., **606**) (e.g., out of a displayed represented field-of-view), the computer system cuts to a different frame (e.g., displays a representation of a portion of the camera field-of-view) that includes the subject. In some embodiments, the cut (e.g., jump cut) includes a change in zoom level (e.g., a zoom in or out). For example, the change in the represented field-of-view is a jump cut that includes a zoomed out view that includes the user (e.g., when in a single person tracking mode). In some embodiments, the cut (e.g., match cut) includes a change from displaying a first region of the camera field-of-view to displaying a second region of the camera field-of-view that includes the user and does not include the first region. In some embodiments, when a second subject remains in frame after a first subject moves out of frame, the computer system displays a jump cut to a zoomed view of the second subject (e.g., when the automatic framing mode is enabled).

[0283] In some embodiments, the representation of the field-of-view of the one or more cameras (e.g., **606**) has a first zoom value (e.g., a zoom setting (e.g., 1×, 0.5×, 0.7×)) before detecting the change in the scene in the field-of-view of the one or more cameras (e.g., as depicted in FIG. **6I**). In some embodiments, the change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) includes movement of a sixth subject (e.g., **622**) from a first position (e.g., **625** in FIG. **6I**) within the field-of-view of the one or more cameras that corresponds to (e.g., is represented by) the representation of the field-of-view and is a first distance from the one or more cameras to a second position (e.g., **625** in FIG. **6J**) within the field-of-view of the one or more cameras that corresponds to (e.g., is represented by) the representation of the field-of-view and is a threshold distance from the one or more cameras (e.g., the subject moves (e.g., toward the camera; away from the camera) within the displayed frame to a predetermined distance from the one or more cameras). In some embodiments, adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras includes: displaying the representation of the field-of-view of the one or more cameras having a second zoom value different from the first zoom value (e.g., **606** in FIG. **6J**) (e.g., a zoomed in view; a zoomed out view; in some embodiments, including the entire portion of the field-of-view of the one or more cameras that was previously displayed in the representation of the field-of-view having the first zoom value, but instead displayed at the second zoom value) in the live video communication interface (e.g., **604**) (e.g., jumping from the first zoom level to the second zoom level when the subject moves within the originally displayed frame to the predetermined distance from the one or more cameras). Ceasing displaying the representation of the field-of-view having the first zoom value, and displaying the representation of the field-of-view having a second zoom value, enhances the video communication session experience by automatically adjusting the zoom value of the representation of the field-of-view of the cameras to maintain prominent display of the subject when the subject moves in the scene to different distances from the camera without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0284] In some embodiments, adjusting the representation of the field-of-view of the one or more cameras (e.g., **606**) during the live video communication session based on the detected change in

the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) includes ceasing displaying the representation of the field-of-view of the one or more cameras having the first zoom value in the live video communication interface (e.g., **606** in FIG. **6I**). In some embodiments, when the subject (e.g., **622**) moves toward the camera to a first threshold distance from the camera, the representation of the field-of-view of the one or more cameras transitions to the second zoom value, which is a zoomed out view of the previously displayed portion of the field-of-view of the one or more cameras (e.g., a jump cut to a wide angle view). In some embodiments, when the subject moves away from the camera to a second threshold distance from the camera, the representation of the field-of-view of the one or more cameras transitions to the second zoom value, which is a zoomed in view of the previously displayed portion of the field-of-view of the one or more cameras.

[0285] In some embodiments, the computer system (e.g., **600**) concurrently displays the second selectable graphical user interface object (e.g., **610**) with the live video communication interface (e.g., **604**) that includes one or more other selectable controls (e.g., **608**) for controlling the live video communication (e.g., an end call button for ending the live video communication session, a switch camera button for switching which camera is used for the live video communication session, a mute button for muting/unmuting audio of the user of the device in the live video communication session, an effects button for adding/removing visual effects from the live video communication session, an add user button for adding a user to the live video communication session, and/or a camera on/off button for turning video of the user on/off in the live video communication session). In some embodiments, the second selectable graphical user interface object (e.g., “framing mode” affordance) is continuously displayed during the live video communication session.

[0286] In some embodiments, while displaying the live video communication interface (e.g., **604**) when a seventh subject (e.g., **628**) (e.g., a first participant in the live video communication session) is detected in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**), the computer system (e.g., **600**) detects an eighth subject (e.g., **622**) (e.g., a second participant in the live video communication session) in the scene in the field-of-view of the one or more cameras (e.g., detecting an increase in the number of subjects in the scene). In response to detecting the eighth subject in the scene in the field-of-view of the one or more cameras, the computer system displays, via the display generation component (e.g., **601**), a prompt (e.g., **632**) (e.g., text to add a second participant to the live video communication session, an affordance for adding a second participant, an indication of a second participant (e.g., a framing indication (e.g., **630**) in a potential preview (e.g., blurred region) to show recognition of the detected additional subject(s), stacked camera preview windows, or other prompts as discussed with respect to FIGS. **8A-8R**) to adjust the representation of the field-of-view of the one or more cameras to include a representation (e.g., **622-1**) of the eighth subject in the live video communication interface (e.g., **604**) (e.g., as depicted in FIG. **6Q**). Displaying a prompt to adjust the representation of the field-of-view of the one or more cameras to include a representation of the eighth subject in the live video communication interface, in response to detecting the eighth subject in the scene, provides feedback to a user of the computer system that an additional subject has been detected in the field-of-view of the one or more cameras, and reduces the number of user inputs at the computer system by providing an option for automatically adjusting the representation of the field-of-view to include the additional subject without requiring the user to navigate a settings menu or other additional interfaces to adjust the represented field-of-view. Providing improved feedback and reducing the number of inputs at the computer system enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0287] In some embodiments, the representation of the field-of-view of the one or more cameras

(e.g., **606**) has a fifth represented field-of-view (e.g., in FIG. **6K**) before detecting the change in the scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., the computer system (e.g., **600**) is displaying a portion of the field-of-view of the one or more cameras before the change in the scene is detected). In some embodiments, the change in the scene in the field-of-view of the one or more cameras includes movement of one or more subjects (e.g., **628**) detected in the scene. In some embodiments, adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on the detected change in the scene in the field-of-view of the one or more cameras includes: in accordance with a determination that the one or more subjects have less than a threshold amount of movement (e.g., a non-zero threshold of movement) for at least a threshold amount of time (e.g., a predetermined amount of time (e.g., one second, two seconds, three seconds)), displaying the representation of the field-of-view of the one or more cameras having a sixth represented field-of-view (e.g., **606** in FIG. **6L**) (e.g., different from the fifth represented field-of-view) in the live video communication interface (e.g., **604**) (e.g., adjusting the representation of the field-of-view of the one or more cameras after the one or more subjects have less than the threshold amount of movement of the predetermined amount of time). In accordance with a determination that the one or more subjects do not have less than the threshold amount of movement for at least the threshold amount of time, continuing displaying the representation of the field-of-view of the one or more cameras having the fifth represented field-of-view in the live video communication interface (e.g., until the one or more subjects do have less than the threshold amount of movement for at least the threshold amount of time) (e.g., maintaining the originally displayed frame while one or more of the subjects are moving). Selectively adjusting the representation of the field-of-view of the one or more cameras during the live video communication session from the fifth represented field-of-view to the sixth represented field-of-view based on whether or not one or more subjects detected in the scene have less than a threshold amount of movement for at least a threshold amount of time enhances the video communication session experience by automatically adjusting the field-of-view of the cameras when additional subjects enter the scene with the intent to participate in the live video communication session, without adjusting the field-of-view when subjects enter the scene without the intent to participate. This also reduces the number of computations performed by the computer system by eliminating extraneous adjustments to the represented field-of-view anytime there is a change in the number of participants in the scene. Performing an operation when a set of conditions has been met without requiring further user input, and reducing the number of computations performed by the computer system, enhance the operability of the computer system and make the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, when the automatic framing mode is enabled, the computer system maintains the originally displayed view until one or more of the subjects are stationary.

[0288] In some embodiments, the computer system (e.g., **600**, **600a**) displays, via the display generation component (e.g., **601**, **601a**), a representation of a first portion of a field-of-view of one or more cameras (e.g. **606**, **1006**, **1056**, **1208**, **1218**) of a respective device of a respective participant in the live video communication session (e.g., a portion of the field-of-view of a camera of a remote participant in the live video communication session that includes a detected face of a remote participant (e.g., **1220-1b** in FIG. **12L**; a portion of video feed **1210-1** that includes John's face; a portion of video feed **1023** that includes John's face; a portion of video feed **1053-2** that includes Jane's face)) (e.g., a portion of the field-of-view of the one or more cameras of the computer system includes a detected face of the subject (e.g., **1208-2** in FIG. **12L**; a portion of Camera preview **1218** that includes John's face; a portion of camera preview **1006** that includes Jane's face; a portion of camera preview **1056** that includes John's face)) and a representation of a

second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., a portion of the field-of-view of the camera of the remote participant that does not include a detected face of a remote participant (e.g., **1220-1a** in FIG. **12L**; a portion of video feed **1210-1** that does not include John's face; a portion of video feed **1023** that does not include John's face; a portion of video feed **1053-2** that does not include Jane's face)) (e.g., a portion of the field-of-view of the one or more cameras of the computer system that does not include a detected face of the subject (e.g., **1208-1** in FIG. **12L**; a portion of camera preview **1218** that does not include John's face; a portion of camera preview **1006** that does not include Jane's face; a portion of camera preview **1056** that does not include John's face)), including displaying the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant with a reduced degree of compression (e.g., a higher video quality) than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the first portion of the field-of-view of one or more cameras includes a detected feature of a respective type (e.g., a face; multiple different faces) while a detected feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., when a face (or multiple different faces) is detected in the first portion of the field-of-view and not in the second portion of the field-of-view, the second portion is compressed (e.g., by the sending device (e.g., the device of the remote participant (e.g., **600a**; **600**); the computer system of the subject (e.g., **600**; **600a**))) at a greater degree than the first portion such that the first portion of the field-of-view can be displayed (e.g., at the receiving device (e.g., the computer system; the device of the remote participant)) at a higher video quality than the second portion of the field-of-view when a face is detected in the first portion and not in the second portion (e.g., **1220-1b** is displayed having a higher video quality than **1220-1a** in FIG. **12L**; the portion of video feed **1210-1** that includes John's face is displayed having a higher video quality than a portion of video feed **1210-1** that does not include John's face; the portion of video feed **1053-2** that includes Jane's face is displayed having a higher video quality than a portion of video feed **1053-2** that does not include Jane's face; the portion of video feed **1023** that includes John's face is displayed having a higher video quality than a portion of video feed **1023** that does not include John's face)). Displaying the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant in the live video communication session with a reduced degree of compression than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the first portion of the field-of-view of the one or more cameras includes a detected feature of a respective type while a detected feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras conserves computational resources by conserving bandwidth and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0289] In some embodiments, the computer system (e.g., **600**, **600a**) enables a dynamic video quality mode for outputting (e.g., transmitting to a recipient device (e.g., **600a**; **600**), optionally while displaying at the sending device (e.g., **600**; **600a**)) the camera field-of-view (e.g., **606**, **1006**, **1056**, **1208**, **1210-1**, **1218**, **1220-1**, **1023**, **1053-2**) with portions having different degrees of video compression. In some embodiments, the computer system compresses portions of the camera field-of-view that do not include one or more faces (e.g., **1220-1a** in FIG. **12L**; a portion of video feed **1210-1** that does not include John's face; a portion of video feed **1023** that does not include John's

face; a portion of video feed **1053-2** that does not include Jane's face) more than portions of the camera field-of-view that do include one or more faces (e.g., **1220-1b** in FIG. **12L**; a portion of video feed **1210-1** that includes John's face; a portion of video feed **1023** that includes John's face; a portion of video feed **1053-2** that includes Jane's face). In some embodiments, the computer system optionally displays the compressed video feed in the camera preview. In some embodiments, the computer system transmits the video feed having the different degrees of compression during the live video communication session such that a recipient device (e.g., a remote participant) can display the video feed received from the sending device (e.g., the computer system) having higher-video-quality portions concurrently displayed with lower-video-quality portions, wherein the higher-video-quality portions of the video feed include the face(s) and the lower-video-quality portions of the video feed do not include the face(s) (e.g., **1220-1b** is displayed having a higher video quality than **1220-1a** in FIG. **12L**; the portion of video feed **1210-1** that includes John's face is displayed having a higher video quality than a portion of video feed **1210-1** that does not include John's face; the portion of video feed **1053-2** that includes Jane's face is displayed having a higher video quality than a portion of video feed **1053-2** that does not include Jane's face; the portion of video feed **1023** that includes John's face is displayed having a higher video quality than a portion of video feed **1023** that does not include John's face). Similarly, in some embodiments, the computer system receives compressed video data from a remote device (e.g., a device of a remote participant of the live video communication session) and displays the video feed from the remote device having the different degrees of compression such that the video feed of the remote device can be displayed with a higher-video-quality portion that includes the face of the remote participant and a lower-video-quality portion (displayed concurrently with the higher-quality portion) that does not include the face of the remote participant (e.g., **1220-1b** is displayed having a higher video quality than **1220-1a** in FIG. **12L**; the portion of video feed **1210-1** that includes John's face is displayed having a higher video quality than a portion of video feed **1210-1** that does not include John's face; the portion of video feed **1053-2** that includes Jane's face is displayed having a higher video quality than a portion of video feed **1053-2** that does not include Jane's face; the portion of video feed **1023** that includes John's face is displayed having a higher video quality than a portion of video feed **1023** that does not include John's face). In some embodiments, the different degrees of compression can be applied to a video feed where multiple faces are detected. For example, the video feed can have multiple higher-quality (less compressed) portions, each corresponding to a location of one of the detected faces.

[0290] In some embodiments, the dynamic video quality mode is independent of the automatic framing mode and background blur mode such that the dynamic video quality mode can be enabled and disabled separate from the automatic framing mode and the background blur mode. In some embodiments, the dynamic video quality mode is implemented with the automatic framing mode such that the dynamic video quality mode is enabled when the automatic framing mode is enabled and is disabled when the automatic framing mode is disabled. In some embodiments, the dynamic video quality mode is implemented with the background blur mode such that the dynamic video quality mode is enabled when the background blur mode is enabled and is disabled when the background blur mode is disabled.

[0291] In some embodiments, after the feature of the respective type has moved from the first portion of the field-of-view of one or more cameras (e.g., **606**, **1006**, **1023**, **1053-2**, **1056**, **1208**, **1210-1**, **1218**, **1220-1**) of the respective device of the respective participant to the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., detecting the movement of the feature of the respective type from the first portion of the field-of-view of the one or more cameras to the second portion of the field-of-view of the one or more cameras; and, in response to detecting the movement of the feature of the respective type from the first portion of the field-of-view of the one or more cameras to the second portion of the field-of-view of the one or more cameras), the computer system (e.g., **600**, **600a**) displays, via the display

generation component (e.g., **601**, **601a**), the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant and the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., a portion of the field-of-view that includes a detected face), including displaying the representation of the first portion the field-of-view of one or more cameras of the respective device of the respective participant with an increased degree of compression (e.g., a lower video quality) than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the second portion of the field-of-view of one or more cameras of the respective device of the respective participant includes a detected feature of the respective type while a detected feature of the respective type is not detected in the first portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., as the face moves within the field-of-view of the one or more cameras, the degrees of compression of respective portions of the field-of-view of the one or more cameras change such that the face (e.g., a portion of the field-of-view that includes the face) is (e.g., remains) output (e.g., transmitted and, optionally, displayed) having a lower degree of compression than portions of the field-of-view that do not include the face (e.g., as Jane's face moves, video feed **1053-2** and/or **1220-1** is updated so that her face continues to be displayed at a higher video quality and portions of the video feed that do not include her face (even portions that were previously displayed at a higher quality) are displayed at a lower video quality; as John's face moves, video feed **1023** and/or **1210-1** is updated so that his face continues to be displayed at a higher video quality and portions of the video feed that do not include his face (even portions that were previously displayed at a higher quality) are displayed at a lower video quality)). Displaying, after the feature of the respective type has moved from the first portion of the field-of-view of one or more cameras of the respective device of the respective participant to the second portion of the field-of-view of one or more cameras of the respective device of the respective participant, the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant in the live video communication session with an increased degree of compression than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the second portion of the field-of-view of the one or more cameras includes a detected feature of the respective type while a detected feature of the respective type is not detected in the first portion of the field-of-view of one or more cameras conserves computational resources by conserving bandwidth and decreasing the amount of image data that is processed for display and/or transmission at a high image quality as a face moves within the scene. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0292] In some embodiments, the feature of the respective type is a face (e.g., a face detected within a field-of-view of one or more cameras; a face of a remote participant (e.g., Jane's face in video feed **1220-1** and/or **1053-2**; John's face in video feed **1023** and/or **1210-1**); a face of the subject (e.g., Jane's face in camera preview **606**, **1006**, and/or **1208**; John's face in camera preview **1056** and/or **1218**)). In some embodiments, displaying the representation of the second portion of the field-of-view of one or more cameras (e.g., **606**, **1006**, **1023**, **1053-2**, **1056**, **1208**, **1210-1**, **1218**, **1220-1**) of the respective device of the respective participant includes displaying the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant having a lesser video quality than the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., **1220-1a** is displayed having a lower video quality than **1220-1b** in FIG. **12L**; the portion of video

feed **1210-1** that does not include John's face is displayed having a lower video quality than a portion of video feed **1210-1** that includes John's face; the portion of video feed **1053-2** that does not include Jane's face is displayed having a lower video quality than a portion of video feed **1053-2** that includes Jane's face; the portion of video feed **1023** that does not include John's face is displayed having a lower video quality than a portion of video feed **1023** that includes John's face) (e.g., due to a reduced compression of the representation of the first portion of the field-of-view of the one or more cameras) in accordance with a determination that the first portion of the field-of-view of one or more cameras includes the detected face while a face is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant. Displaying the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant having a lesser video quality than the representation of the first portion of the field-of-view in accordance with a determination that the first portion of the field-of-view includes the detected face while a face is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant conserves computational resources by conserving bandwidth and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0293] In some embodiments, portions of the camera field-of-view that do not include a detected face (e.g., **621-1**; **1220-1a**; **1208-1**; portions of **1218** and/or **1210-1** that do not include John's face; portions of **1006** and/or **1053-2** that do not include Jane's face) are output (e.g., transmitted and, optionally, displayed) having a lesser image quality than portions of the camera field-of-view that do include a detected face (e.g., **622-1**; **1220-1b**; **1208-2**; portions of **1218** and/or **1210-1** that include John's face; portions of **1006** and/or **1053-2** that include Jane's face) (due to the increased compression of the portions that do not include a detected face). In some embodiments, when no faces are detected in the field-of-view of the one or more cameras, the computer system (e.g., **600**; **600a**) applies a uniform or substantially uniform degree of compression to the first and second portions of the field-of-view of the one or more cameras such that the video feed (e.g., both the first and second portions) can be output having a uniform or substantially uniform video quality. In some embodiments, when multiple faces are detected in the camera field-of-view (e.g., multiple participants of the live video communication session are detected), the computer system applies the reduced compression concurrently to the portions of the field-of-view that correspond to the detected faces such that the faces can be displayed concurrently (e.g., at a recipient device) having the higher image quality. In some embodiments, the computer system applies the increased compression to the representation of the second portion of the field-of-view of one or more cameras, even if a face is detected in the second portion. For example, the computer system can determine that the face in the second portion is not a participant of the live video communication session (e.g., the person is a bystander in the background) and, therefore, does not reduce the degree of compression of the second portion having the face.

[0294] In some embodiments, after (e.g., in response to detecting) a change in bandwidth for transmitting a representation of the field-of-view of one or more cameras (e.g., **606**, **1006**, **1023**, **1053-2**, **1056**, **1208**, **1210-1**, **1218**, **1220-1**) of the respective device (e.g., **600**, **600a**) of the respective participant occurs (e.g., is detected), while a feature of the respective type (e.g., a face) is detected in the first portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., **622-1**; **1220-1b**; **1208-2**; portions of **1218** and/or **1210-1** that include John's face; portions of **1006** and/or **1053-2** that include Jane's face) and while a feature of the respective type is not detected in the second portion of the field-of-view of one or more

cameras of the respective device of the respective participant (e.g., **621-1**; **1220-1a**; **1208-1**; portions of **1218** and/or **1210-1** that do not include John's face; portions of **1006** and/or **1053-2** that do not include Jane's face), a degree of compression (e.g., an amount of compression) of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant is changed by an amount that is less than an amount of change of a degree of compression of the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., when a face is detected in the first portion of the field-of-view of one or more cameras, and a face is not detected in the second portion of the field-of-view of one or more cameras, the rate of change in compression (in response to a change in bandwidth (e.g., a decrease in bandwidth)) is less for the first portion of the field-of-view than for the second portion of the field-of-view). Changing a degree of compression of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant by an amount that is less than an amount of change of a degree of compression of the representation of the second portion while a feature of the respective type is detected in the first portion and a feature of the respective type is not detected in the second portion conserves computational resources by conserving bandwidth for the first portion of the representation of the field-of-view of the one or more cameras that includes the feature of the respective type and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0295] In some embodiments, after (e.g., in response to detecting) a change in bandwidth for transmitting a representation of the field-of-view of one or more cameras (e.g., **606**, **1006**, **1023**, **1053-2**, **1056**, **1208**, **1210-1**, **1218**, **1220-1**) of the respective device (e.g., **600**; **600a**) of the respective participant occurs (e.g., is detected), while a feature of the respective type is not detected in the first portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., **621-1**; **1220-1a**; **1208-1**; portions of **1218** and/or **1210-1** that do not include John's face; portions of **1006** and/or **1053-2** that do not include Jane's face) and while a feature of the respective type is detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., **622-1**; **1220-1b**; **1208-2**; portions of **1218** and/or **1210-1** that include John's face; portions of **1006** and/or **1053-2** that include Jane's face), a degree of compression (e.g., an amount of compression) of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant is changed by an amount that is more than an amount of change of a degree of compression of the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., when a face is detected in the second portion of the field-of-view of one or more cameras, and a face is not detected in the first portion of the field-of-view of one or more cameras, the rate of change in compression (in response to a change in bandwidth (e.g., a decrease in bandwidth)) is greater for the first portion of the field-of-view than for the second portion of the field-of-view). Changing a degree of compression of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant by an amount that is more than an amount of change of a degree of compression of the representation of the second portion while a feature of the respective type is not detected in the first portion and a feature of the respective type is detected in the second portion conserves computational resources by conserving bandwidth for the second portion of the representation of the field-of-view of the one or more cameras that includes the feature of the respective type and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the

operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0296] In some embodiments, in response to a change in bandwidth for transmitting a representation of the field-of-view of one or more cameras (e.g., **606**, **1006**, **1023**, **1053-2**, **1056**, **1208**, **1210-1**, **1218**, **1220-1**) of the respective device (e.g., **600**; **600a**) of the respective participant occurring (e.g., being detected), a quality (e.g., a video quality) (e.g., due to a change in the amount of video compression) of the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., **621-1**; **1220-1a**; **1208-1**; portions of **1218** and/or **1210-1** that do not include John's face; portions of **1006** and/or **1053-2** that do not include Jane's face) is changed by an amount that is greater than an amount of change of quality (in some embodiments, the representation of the first portion does not change in quality or has a nominal amount of change in quality) of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., **622-1**; **1220-1b**; **1208-2**; portions of **1218** and/or **1210-1** that include John's face; portions of **1006** and/or **1053-2** that include Jane's face) (e.g., when a face is detected in the first portion of the field-of-view of one or more cameras, and a face is not detected in the second portion of the field-of-view of one or more cameras, the image quality of the second portion varies more than the image quality of the first portion in response to a change in bandwidth (e.g., a decrease in bandwidth)). Changing a quality of the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant by an amount that is greater than an amount of change of quality of the representation of the first portion conserves computational resources by conserving bandwidth for the first portion of the representation of the field-of-view of the one or more cameras and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0297] In some embodiments, while a face is detected in the first portion of the field-of-view of one or more cameras (e.g., **622-1**; **1220-1b**; **1208-2**; portions of **1218** and/or **1210-1** that include John's face; portions of **1006** and/or **1053-2** that include Jane's face), and is not detected in the second portion of the field-of-view (e.g., **621-1**; **1220-1a**; **1208-1**; portions of **1218** and/or **1210-1** that do not include John's face; portions of **1006** and/or **1053-2** that do not include Jane's face), the computer system (e.g., **600**; **600a**) detects a change in available bandwidth (e.g., an increase in bandwidth; a decrease in bandwidth) and, in response, adjusts (e.g., increases; decreases) the compression of the second portion of the representation of the field-of-view of the one or more cameras without adjusting the compression of the first portion of the representation of the field-of-view of the one or more cameras. In some embodiments, when detecting a change in bandwidth, the computer system adjusts the compression of the first portion at a lesser rate than the adjustment to the second portion. In some embodiments, the method includes detecting (e.g., at the respective device of the respective participant) a change in bandwidth for transmitting a representation of the field-of-view of one or more cameras of the respective device of the respective participant while a feature of the respective type (e.g., a face) is detected in the first portion of the field-of-view of one or more cameras of the respective device of the respective participant and while a feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant.

[0298] Note that details of the processes described above with respect to method **700** (e.g., FIGS. **7A-7B**) are also applicable in an analogous manner to methods **900**, **1100**, **1300**, and **1400**

described below. For example, method **900**, method **1100**, method **1300**, and/or method **1400** optionally include one or more of the characteristics of the various methods described above with reference to method **700**. For brevity, these details are not repeated below.

[0299] FIGS. **8A-8R** illustrate exemplary user interfaces for managing a live video communication session (e.g., a video conference), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described herein, including the processes in FIG. **9**.

[0300] FIGS. **8A-8R** illustrate device **600** displaying user interfaces on display **601** for managing a live video communication session, similar to that discussed above with respect to FIGS. **6A-6Q**.

FIGS. **8A-8R** depict various embodiments in which device **600** prompts a user to adjust the displayed portion of a camera field-of-view (e.g., the camera preview) in response to detecting another subject in a scene when an automatic framing mode is enabled. One or more of the embodiments discussed below with respect to FIGS. **8A-8R** can be combined with one or more of the embodiments discussed with respect to FIGS. **6A-6Q**, FIGS. **10A-10J**, and FIGS. **12A-12U**.

[0301] FIGS. **8A-8J** depict example embodiments in which device **600** displays a prompt to adjust the video feed field-of-view to include additional participants, in response to detecting additional subjects in scene **615**. FIGS. **8A-8D** illustrate an embodiment in which the prompt includes displaying stacked camera preview options. FIGS. **8E-8G** illustrate an embodiment in which the prompt includes displaying a camera preview having obscured and unobscured regions. FIGS. **8H-8J** illustrate an embodiment in which the prompt includes displaying an option to switch between a single-person framing mode and a multi-person framing mode. Other embodiments, such as that described above with respect to FIG. **6P**, are provided in which device **600** displays a prompt that includes an affordance (e.g., add affordance **632**) that is selectable to adjust the displayed field-of-view to include additional subjects.

[0302] FIG. **8A** depicts an embodiment similar to that discussed above with respect to FIG. **6O**, except that video feed **623** now includes representation **623-2** of Pam instead of representation **623-1** of John. The automatic framing mode is enabled, as indicated by the bolded state of framing mode affordance **610** and the display of framing indicators **630**.

[0303] In FIG. **8A**, Jack is participating in a video conference with Pam using device **600**.

Similarly, Pam is participating in the video conference with Jack using a device that includes one or more features of devices **100**, **300**, **500**, or **600**. For example, Pam is using a tablet similar to device **600**. Accordingly, Pam's device displays a video conference interface similar to video conference interface **604**, except that the camera preview on Pam's device displays the video feed captured from Pam's device (what is currently depicted in video feed **623** in FIG. **8A**), and the incoming video feed on Pam's device displays the video feed output from device **600** (what is currently depicted in camera preview **606** in FIG. **8A**).

[0304] In FIG. **8B**, device **600** detects Jane **622** entering scene **615**, within field-of-view **620**. In response, device **600** updates video conference interface **604** by displaying secondary camera preview **806** positioned behind, and offset from, camera preview **606**. The stacked appearance of camera preview **606** and secondary camera preview **806** indicates that multiple video feed fields-of-view are available for the video conference, and that the user can change the displayed field-of-view. Device **600** indicates that camera preview **606** is the currently selected or enabled video feed field-of-view because it is positioned on top of secondary camera preview **806**. Thus, secondary camera preview **806** represents an option for adjusting the video feed field-of-view, which, in this embodiment, is an alternate field-of-view that includes both Jack **628** and Jane **622** (the additional subject who has entered the scene). In some embodiments, the different camera previews represent different zoom values and, as such, the different camera preview options can also be considered different zoom controls/options.

[0305] Device **600** detects input **804** (e.g., a tap input) on the stacked previews (e.g., on secondary camera preview **806**) and, in response, updates video conference interface **604** by shifting the position of secondary camera preview **806** so that it is no longer positioned behind camera preview

606, as depicted in FIG. 8C.

[0306] In FIG. 8C, device **600** displays both camera preview **606** and secondary camera preview **806** separated (unstacked) in video conference interface **604**. Device **600** also displays bolded outline **807** to indicate the currently selected video feed field-of-view, which, in FIG. 8C, is camera preview **606**. Secondary camera preview **806** represents an available video feed field-of-view offered by device **600**. Portion **825** represents the portion of field-of-view **620** that is displayed in secondary camera preview **806**, whereas portion **625** represents the portion of field-of-view **620** that is currently displayed in camera preview **606**. While camera preview **806** shows a rendering of portion **825**, camera preview **806** is not currently selected and, therefore, device **600** is not currently outputting a view of portion **825** for the video conference.

[0307] Camera preview **606** includes representation **628-1** of Jack and a portion of representation **622-1** of Jane. Secondary camera preview **806** is a zoomed out view (compared to the view in camera preview **606**) that includes representation **628-1** of Jack and representation **622-1** of Jane. As previously discussed, framing indicators **630** are depicted in camera preview **606** and secondary camera preview **806** to indicate Jane's and Jack's faces are detected within the respective video feed fields-of-view.

[0308] While the camera preview options are displayed in the unstacked configuration depicted in FIG. 8C, device **600** can maintain or switch between the available preview options in response to user inputs. For example, if device **600** detects input **811** on camera preview **606**, the device continues to use (e.g., output) the video feed field-of-view represented by camera preview **606**, and video conference interface **604** returns to the view depicted in FIG. 8B. If device **600** detects input **812** on secondary camera preview **806**, device **600** switches to (e.g., outputs) the video feed field-of-view represented by secondary camera preview **806**, and the camera previews return to the stacked configuration with secondary camera preview **806** on top and camera preview **606** on bottom, as depicted in FIG. 8D. In some embodiments, when device **600** switches from camera preview **606** to secondary camera preview **806**, bolded outline **807** moves from camera preview **606** to secondary camera preview **806** to indicate the switch from outputting camera preview **606** to outputting secondary camera preview **806**.

[0309] In FIG. 8D, portion **625** represents the portion of field-of-view **620** that is currently being output for the video conference. Because secondary camera preview **806** was selected in response to input **812**, portion **625** now corresponds to secondary camera preview **806**. Portion **627** represents the previous video feed field-of-view, which now corresponds to camera preview **606**.

[0310] In FIG. 8E, device **600** detects Jane **622** entering scene **615**. Device **600** displays camera preview **606** having unblurred region **606-1** (denoted by boundary **808** and no hatching) and blurred region **606-2** (denoted by boundary **809** and hatching). Unblurred region **606-1** represents the current video feed field-of-view, whereas blurred region **606-2** represents additional video feed field-of-view that is available, but not currently being output, for the video conference.

Accordingly, portion **625** corresponds to the field-of-view of the unblurred region, and portion **825** corresponds to the available field-of-view of the blurred and unblurred regions combined. The display of blurred and unblurred regions in camera preview **606** indicates that the video feed field-of-view is capable of being adjusted. The use of blurring is described as one manner in which to distinguish the current video feed field-of-view from the additional available video feed field-of-view. However, these regions can be distinguished by other visual indications and appearances such as shading, darkening, highlighting, or other visual obscuring to either emphasize or deemphasize the various regions. Boundaries **808** and **809** are also used to visually distinguish these regions.

[0311] In FIG. 8E, unblurred region **606-1** depicts unobscured representation **628-1a** of Jack—specifically, Jack's face—that is being output for the video conference. Blurred region **606-2** depicts an obscured (e.g., blurred) representation of the available video feed field-of-view that is included in portion **825** of field-of-view **620** and not included in portion **625**. For example, in FIG. 8E, blurred region **606-2** depicts obscured representation **628-1b** of Jack's body. In some

embodiments, the blurred and/or unblurred regions include framing indicators when device **600** detects a face in the corresponding region.

[0312] In FIG. **8F**, Jane **622** has entered portion **825** of field-of-view **620**, and device **600** displays obscured representation **622-1b** of Jane in blurred region **606-2** of the camera preview. Device **600** detects input **813** on blurred region **606-2** (or on framing indicators positioned around Jane's face in blurred region **606-2**) and, in response, adjusts (e.g., expands) the video feed field-of-view to include the previously blurred region **606-2**, as depicted in FIG. **8G**. In some embodiments, the blurred/unblurred regions of the camera preview represent different zoom values for the video feed field-of-view. As such, the camera preview **606**, which can be selected to switch to a field-of-view with a different zoom value (e.g., by expanding the unblurred region), can also be considered a zoom control.

[0313] Portion **625**, in FIG. **8G**, represents the expanded portion of field-of-view **620** that is now being output for the video conference, and portion **627** represents the prior displayed portion of field-of-view **620** corresponding to unblurred portion **606-1** in FIG. **8F**. Camera preview **606** now depicts unobscured representation **628-1** of Jack and unobscured representation **622-1** of Jane.

[0314] In some embodiments, the adjustment of the video feed field-of-view discussed above with respect to FIGS. **8E-8G** is reversed when the conditions that triggered the adjustment are no longer met. For example, if Jane leaves frame **625** in FIG. **8G**, then device **600** returns to the state depicted in FIG. **8E**, where camera preview **606** includes unblurred region **606-1** and blurred region **606-2**.

[0315] FIGS. **8H-8J** depict various interfaces for an embodiment in which device **600** switches the automatic framing mode between a single-person framing mode setting and a multi-person framing mode setting. In FIG. **8H**, while the automatic framing mode is enabled, device **600** detects Jack **628** in scene **615** and displays video conference interface **604** with framing mode options **830** depicted in camera preview **606**. Framing mode options **830** include single-person option **830-1** and multi-person option **830-2**. When single-person option **830-1** is in a selected state, as depicted in FIG. **8H**, the single-person framing mode setting is enabled and device **600** keeps the video feed field-of-view focused on a single user's face, even when another person is detected in field-of-view **620**. For example, in FIG. **8I**, although Jane **622** is now positioned next to Jack **628** in scene **615**, device **600** maintains the video feed field-of-view that features Jack **628** (represented in camera preview **606** and portion **625**), instead of automatically adjusting the video feed field-of-view to include Jane.

[0316] In FIG. **8I**, device **600** detects input **832** on multi-person option **830-2**. In response, device **600** switches from the single-person framing mode setting to the multi-person framing mode setting. When the multi-person framing mode setting is enabled, device **600** automatically adjusts the video feed field-of-view to include additional subjects detected in field-of-view **620** (or a subset thereof). For example, when device **600** switches to the multi-person framing mode setting, device **600** expands the video feed field-of-view to include representations **628-1** and **622-1** of both Jack and Jane, as depicted in camera preview **606** in FIG. **8J**. Accordingly, portion **625** in FIG. **8J** represents the expanded video feed field-of-view resulting from enabling the multi-person framing mode setting, and portion **627** represents the prior video feed field-of-view corresponding to the single-person framing mode setting. In some embodiments, the framing mode options **830** correspond to video feed fields-of-view having different zoom values and, as such, framing mode options **830** can also be considered zoom controls/options.

[0317] In some embodiments, the transition depicted in FIGS. **8H-8J** can be combined with the camera preview having blurred and unblurred regions as discussed with respect to FIGS. **8E-8G**. For example, device **600** can display camera preview **606** having blurred and unblurred regions, similar to that depicted in FIG. **8E**, but also including framing mode options **830** similar to those depicted in FIG. **8H**. When device **600** is in the single-person framing mode setting, device **600** displays camera preview **606** having both blurred and unblurred regions, regardless of whether

anybody is detected in the blurred portion of the frame (similar to that depicted in FIGS. 8E and 8F). However, when device **600** is in the multi-person framing mode setting, device **600** can transition the camera preview **606** from the blurred and unblurred appearance to an unblurred appearance (similar to the transition in FIGS. 8F and 8G) in response to detecting another person in the blurred region. In a similar manner, if a person is detected in the blurred region (as shown in FIG. 8F) when device **600** switches from single-person framing mode to the multi-person framing mode, device **600** adjusts the video feed field-of-view to include the previously blurred region that includes the person who was previously detected in the blurred region (similar to the transition depicted in FIGS. 8F and 8G). In some embodiments, device **600** can reverse the transitions discussed above. For example, if device **600** is displaying camera preview **606** with both subjects in the field-of-view (similar to that depicted in FIG. 8J), and device **600** detects a selection of single-person framing option **830-1**, device **600** can adjust the video feed field-of-view to return to the blurred/unblurred appearance, similar to that depicted in FIG. 8F.

[0318] Referring now to FIG. 8K, device **600** displays video conference interface **834**, which depicts an incoming request to join a live video conference with John and two other remote participants. Video conference interface **834** is similar to video conference interface **604**, except that multiple participants are active on the video conference session depicted in video conference interface **834**. Therefore, the embodiments described herein with respect to video conference interface **604** can be applied in an analogous manner to video conference interface **834**. Similarly, the embodiments described herein with respect to video conference interface **834** can be applied in an analogous manner to video conference interface **604**, and the like.

[0319] In FIG. 8K, device **600** detects input **835** on accept option **608-3**, while the automatic framing mode is enabled (as indicated by the bolded appearance of framing mode affordance **610**) and the background blur mode is disabled (as indicated by the unbolded appearance of background blur affordance **611**). In response, device **600** accepts the live video conference call and joins the video conference session with the automatic framing mode enabled and the background blur mode disabled, as depicted in FIG. 8L.

[0320] FIG. 8L depicts device **600** displaying video conference interface **834** with camera preview **836** (similar to camera preview **606**), and incoming video feeds **840-1**, **840-2**, and **840-3** for each of the respective remote participants of the live video conference session. Camera preview **836** includes representation **622-1** of Jane and framing mode affordance **610**. In some embodiments, framing mode affordance **610** is selectable in camera preview **836** to enable or disable the automatic framing mode. In some embodiments, framing mode affordance **610** is not selectable until camera preview **836** is displayed in an enlarged state, such as that depicted in FIG. 8M. In some embodiments, device **600** displays framing mode affordance **610** in camera preview **836** when the automatic framing mode is enabled and does not display the affordance when the automatic framing mode is disabled. In some embodiments, device **600** persistently displays framing mode affordance **610**, and indicates whether or not the automatic framing mode is enabled by changing the appearance of the framing mode affordance (e.g., bolding the affordance when the mode is enabled). In some embodiments, framing mode affordance **610** is displayed in options menu **608**.

[0321] In FIG. 8L, Jane is participating in a video conference with Pam, John, and Jack using device **600**. Similarly, Pam, John, and Jack are each participating in the video conference with Jane and the other respective participants using respective devices that include one or more features of devices **100**, **300**, **500**, or **600**. For example, John, Jack, and Pam are each using a tablet similar to device **600**. Accordingly, the devices of the other participants (John, Jack, and Pam) each display a video conference interface similar to video conference interface **834**, except that the camera preview on each respective device displays the video feed captured from that user's respective device (e.g., Pam's camera preview displays what is currently depicted in video feed **840-3**, John's camera preview displays what is currently depicted in video feed **840-1**, and Jack's camera preview

displays what is currently depicted in video feed **840-2**), and the incoming video feed on the devices of the other participants (John, Jack, and Pam) include the video feed output from device **600** (what is currently depicted in camera preview **836** in FIG. **8L**) and the video feeds output from the devices of the other participants.

[0322] In FIG. **8L**, device **600** detects input **837** on camera preview **836** and, in response, enlarges camera preview **836**, as depicted in FIG. **8M**. In FIG. **8M**, device **600** displays framing mode affordance **610** in two locations in video conference interface **834**. Framing mode affordance **610-1** is displayed in camera preview **836**, and framing mode affordance **610-2** is displayed in options menu **608**. In some embodiments, framing mode affordance **610** is only displayed in one location (e.g., either options menu **608** or in camera preview **836**) at any given time.

[0323] In some embodiments, device **600** displays framing mode affordance **610** having an altered appearance when the automatic framing mode is unavailable. For example, in FIG. **8N**, the lighting conditions in scene **615** are poor and, in response to detecting the poor lighting conditions, device **600** displays framing mode affordance **610-1** and framing mode affordance **610-2** having a greyed out appearance to indicate that the automatic framing mode is currently unavailable. When the lighting conditions improve, device **600** displays framing mode affordance **610-1** and **610-2** having the appearance shown in FIG. **8M**.

[0324] In FIG. **8N**, device **600** detects input **839** (e.g., a tap input or a drag gesture) on options menu **608** and, in response, displays the interface depicted in FIG. **8O**. In some embodiments, device **600** displays video conference interface **834** depicted in FIG. **8L** in response to detecting an input on other locations of the video conference interface **834** depicted in FIG. **8N** such as, for example, on camera preview **836** or on a location of the interface other than options menu **608**.

[0325] In FIG. **8O**, device **600** displays video conference interface **834** having expanded options menu **845**, incoming video feeds **840-2** and **840-3**, and camera preview **836**. Expanded options menu **845** includes information and various options for the video conference, including framing mode option **845-1**, which is similar to framing mode affordance **610**.

[0326] Referring now to FIG. **8P**, device **600** displays video conference interface **834** with an enlarged camera preview **836** and control options **850**. In some embodiments, the interface depicted in FIG. **8P** is displayed in response to an input on camera preview **836** in FIG. **8O**. Control options **850** include framing mode option **850-1**, $1\times$ zoom option **850-2**, and $0.5\times$ zoom option **850-3**. Framing mode option **850-1** is similar to framing mode affordance **610**, and is displayed in a bolded state to indicate that the automatic framing mode is enabled. Because the automatic framing mode is enabled, camera preview **836** includes framing indicators **852** (similar to framing indicators **630**) positioned around the face of representation **622-1** of Jane. Zoom options **850-2** and **850-3** are selectable to manually change the digital zoom level of the video feed field-of-view. Because zoom options **850-2** and **850-3** manually adjust the digital zoom of camera preview **836**, selecting the zoom options disables the automatic framing mode, as discussed below.

[0327] In FIG. **8P**, device **600** detects input **853** on zoom option **850-2**. In response, device **600** emphasizes (e.g., bolds and optionally enlarges) zoom option **850-2** and disables the automatic framing mode. In the embodiment depicted in FIG. **8P**, the $1X$ zoom level was the zoom setting prior to detecting input **853**. Therefore, device **600** continues to display representation **622-1** at the $1X$ zoom level. Because the automatic framing mode is disabled, framing mode option **850-1** is deemphasized (e.g., no longer bolded) and framing indicators **852** are no longer displayed in FIG. **8Q**.

[0328] In FIG. **8Q**, device **600** detects input **855** on zoom option **850-3** and, in response, adjusts the digital zoom level as indicated in FIG. **8R**. Accordingly, device **600** emphasizes zoom option **850-3**, deemphasizes zoom option **850-2**, and displays camera preview **836** having a $0.5\times$ digital zoom value (zoomed out compared to camera preview **836** in FIG. **8Q**). Portion **625** represents the portion of field-of-view **620** that is displayed after the video feed field-of-view is zoomed out, and portion **627** represents the portion of field-of-view **620** that was previously displayed when zoom

option **850-2** was selected.

[0329] FIG. **9** is a flow diagram illustrating a method for managing a live video communication session using an electronic device in accordance with some embodiments. Method **900** is performed at a computer system (e.g., a smartphone; a tablet) (e.g., **100, 300, 500, 600**) that is in communication with a display generation component (e.g., a display controller, a touch-sensitive display system), one or more cameras (e.g., **602**) (e.g., a visible light camera; an infrared camera; a depth camera), and one or more input devices (e.g., a touch-sensitive surface). Some operations in method **900** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

[0330] As described below, method **900** provides an intuitive way for managing a live video communication session. The method reduces the cognitive burden on a user for managing a live video communication session, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to manage a live video communication session faster and more efficiently conserves power and increases the time between battery charges.

[0331] In method **900**, computer system (e.g., **600**) displays (**902**), via the display generation component (e.g., **601**), a live video communication interface (e.g., **604; 834**) for a live video communication session (e.g., an interface for a live video communication session (e.g., a live video chat session, a live video conference session, etc.)). In some embodiments, the live video communication interface includes a live preview of the user of the computer system and a live representation of one or more participants (e.g., remote users) of the live video communication session.

[0332] The computer system (e.g., **600**) displays the live video communication interface (e.g., **604; 834**) including (**904**) a representation (e.g., **623; 623-1; 840-1; 840-2; 840-3**) of one or more participants (e.g., remote participant(s) of the live video communication session) in the live video communication session other than participants (e.g., **622; 628**) visible via the one or more cameras (e.g., **602**). In some embodiments, participants visible via the one or more cameras are subjects positioned within a field-of-view (e.g., **620**) of the one or more cameras and represented (e.g., displayed) in the live video communication session (e.g., **606; 806**) via the display generation component (e.g., **601**).

[0333] The computer system (e.g., **600**) displays the live video communication interface (e.g., **640; 834**) including (**904**) (e.g., concurrently with the representation of the one or more participants) a representation of a field-of-view of the one or more cameras (e.g., **606; 806; 836**) that is visually associated with (e.g., displayed adjacent to; displayed grouped together with) a visual indication (e.g., **610; 610-1; 610-2; 630; 632; 806; 808; 809; 606-1; 606-2; 830; 830-1; 830-2; 845-1; 850; 850-1; 850-2; 850-3; 852**) (e.g., a prompt (e.g., text); a selectable graphical user interface object (e.g., zoom controls; a framing mode affordance; a framing indication; an affordance for selecting a single-person framing mode; an affordance for selecting a multi-person framing mode); a representation of a camera preview (e.g., an alternate camera preview); a framing indication) of an option to change (e.g., adjust) the representation (e.g., change a digital zoom level/value; expand the displayed field-of-view; contracting the displayed field-of-view) of the field-of-view of the one or cameras during the live video communication session (e.g., the representation of the field-of-view of the one or more cameras is displayed with a first digital zoom level and a first displayed portion of the field-of-view of the one or more cameras). Displaying a representation of a field-of-view of the one or more cameras that is visually associated with a visual indication of an option to change the representation of the field-of-view of the one or more cameras during the live video communication session provides feedback to a user of the computer system that alternative representations of the field-of-view of the one or more cameras are available for selection, and reduces the number of user inputs at the computer system by providing an option for adjusting the representation of the field-of-view without requiring the user to navigate a settings menu or other additional interfaces to adjust the represented field-of-view. Providing improved feedback and

reducing the number of inputs at the computer system enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0334] In some embodiments, the representation of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) is a preview (e.g., **606**; **806**; **836**) of image data outputted, or capable of being outputted, by the computer system (e.g., **600**) to one or more electronic devices associated with the one or more participants (e.g., the remote participants) of the live video communication session. In some embodiments, the representation of the field-of-view of the one or more cameras includes a representation (e.g., **622-1**; **628-1**) of a subject (e.g., **622**; **628**) (e.g., a participant; a user of the computer system that is detected within a field-of-view (e.g., **620**) of the one or more cameras during the live video communication session) participating in the live video communication session (e.g., a camera preview of the user of the computer system for the live video communication session). In some embodiments, the visual indication (e.g., **850-2**; **850-3**; **806**; **606**; **632**) of the option to change the representation of the field-of-view of the one or more cameras is selectable to manually adjust a framing (e.g., digital zoom level) of the representation of the field-of-view of the one or more cameras during the live video communication session. In some embodiments, the visual indication (e.g., **610**; **610-1**; **610-2**; **845-1**; **830-1**; **830-2**; **850-1**) of the option to change the representation of the field-of-view of the one or more cameras is selectable to enable or disable a mode for automatically adjusting the representation of the field-of-view of the one or more cameras, which, in some embodiments, includes a representation of the subject and, optionally, one or more additional subjects, during the live video communication session.)

[0335] While displaying the live video communication interface (e.g., **604**; **834**) for the live video communication session, the computer system (e.g., **600**) detects (**908**), via the one or more input devices (e.g., **601**), a set of one or more inputs (e.g., **626**; **634**; **804**; **811**; **812**; **813**; **832**; **850-2**; **850-3**) that corresponds to a request to initiate a process for adjusting (in some embodiments, manually; in some embodiments, automatically (e.g., without user input)) the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**) during the live video communication session.

[0336] In response to detecting the set of one or more inputs (e.g., **626**; **634**; **804**; **811**; **812**; **813**; **832**; **850-2**; **850-3**), the computer system (e.g., **600**) initiates (**910**) the process for adjusting the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**) during the live video communication session (e.g., manually adjusting a framing (e.g., digital zoom level) of the representation of the field-of-view of the one or more cameras during the live video communication session) (e.g., enabling (or disabling) a mode (e.g., an automatic framing mode) for automatically adjusting the representation of the field-of-view of the one or more cameras while the live video communication session is active). In some embodiments, adjusting the representation of the field-of-view of the one or more cameras during the live video communication session includes outputting (e.g., to an electronic device (e.g., John's tablet **600a**) of the one or more participants (the remote participants)) image data corresponding to the adjusted representation of the field-of-view of the one or more cameras during the live video communication session.

[0337] In some embodiments, when displaying the live video communication session (e.g., via the live video communication interface), the computer system (e.g., **600**) displays, via the display generation component (e.g., **601**), a set of one or more controls (e.g., **850-2**; **850-3**; **606-2**; **630**; **806**) (e.g., one or more controls to increase or decrease a zoom level, and/or one of more controls to set a predetermined zoom level such as a 2× zoom affordance, a 1× zoom affordance and/or a 0.5× zoom affordance; a framing indication; a representation of an alternate camera preview) for adjusting a zoom level (e.g., a digital zoom) of the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**), wherein the set of one or more controls is displayed

concurrently with the visual indication (e.g., **610**; **850-1**) (e.g., framing mode affordance) of the option to change the representation of the field-of-view of the one or more cameras during the live video communication session. Displaying a set of one or more controls for adjusting a zoom level of the representation of the field-of-view of the one or more cameras concurrently with the visual indication of the option to change the representation of the field-of-view of the one or more cameras during the live video communication session provides feedback to a user of the computer system that alternative zoom levels are selectable along with alternative representations of the field-of-view of the one or more cameras, and reduces the number of user inputs at the computer system by providing an option for adjusting the zoom level and the representation of the field-of-view of the one or more cameras without requiring the user to navigate a settings menu or other additional interfaces to adjust the zoom level and/or represented field-of-view. Providing improved feedback and reducing the number of inputs at the computer system enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the live video communication interface includes an option to enable an automatic framing mode (e.g., the framing mode affordance) and one or more zoom controls for adjusting a digital zoom level of the representation of the field-of-view of the one or more cameras being output by the computer system for the live video communication session.

[0338] In some embodiments, the computer system (e.g., **600**) detects, via the one or more input devices (e.g., **601**), a first input (e.g., **804**) directed to the set of one or more controls (e.g., **806**) for adjusting a zoom level of the representation of the field-of-view of the one or more cameras (e.g., **606**). In response to detecting the first input directed to the set of one or more controls, the computer system displays the set of one or more controls (e.g., **606**; **806**) such that a first control option (e.g., **606**) is displayed separately from (e.g., visually distinct from) a second control option (e.g., **806**) (e.g., wherein the first control option is selectable to adjust the zoom level of the representation of the field-of-view of the one or more cameras to a first zoom value, and the second control option is selectable to adjust the zoom level of the representation of the field-of-view of the one or more cameras to a second zoom value different from the first zoom value). Displaying the set of one or more controls such that a first control option is displayed separately from a second control option in response to detecting the first input directed to the set of one or more controls provides additional control options without cluttering the user interface with additional displayed controls until they are desired and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the first control option is a preview of the representation of the field-of-view of the one or more cameras having the first zoom value, and the second control option is a preview of the representation of the field-of-view of the one or more cameras having the second zoom value.

[0339] In some embodiments, while displaying the set of one or more controls (e.g., **606**; **806**), the computer system (e.g., **600**) detects a second input (e.g., **811**; **812**) corresponding to a selection of the first control option (e.g., **606**) or the second control option (e.g., **806**). In response to detecting the second input, the computer system adjusts the representation of the field-of-view of the one or more cameras during the live video communication session based on the selection of the first control option or the second control option (e.g., as depicted in FIG. **8B** or **8D**) (e.g., in accordance with a determination that the first control option is selected, outputting (e.g., to an electronic device

of the one or more participants) image data corresponding to the representation of the field-of-view of the one or more cameras having the first zoom value; and in accordance with a determination that the second control option is selected, outputting (e.g., to the electronic device of the one or more participants) image data corresponding to the representation of the field-of-view of the one or more cameras having the second zoom value). Adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on the selection of the first control option or the second control option provides feedback to a user of the computer system indicating that a different represented field-of-view of the one or more cameras is selected for the live video communication session, and reduces the number of user inputs at the computer system by quickly adjusting the representation of the field-of-view without requiring the user to navigate a settings menu or other additional interfaces to adjust the represented field-of-view. Providing improved feedback and reducing the number of inputs and the computer system enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0340] In some embodiments, the set of one or more controls (e.g., **850-2**; **850-3**) for adjusting a zoom level of the representation of the field-of-view of the one or more cameras includes a first zoom control (e.g., **850-2**) (e.g., one or more controls to increase a zoom level and/or one or more controls to set a predetermined zoom level such as a 2× zoom affordance or 1× zoom affordance) having a first fixed position (e.g., relative to the visual indication of the option to change the representation of the field-of-view of the one or more cameras during the live video communication session (e.g., framing mode affordance **850-1**)) and a second zoom control (e.g., **850-3**) (e.g., one or more controls to decrease a zoom level and/or one or more controls to set a predetermined zoom level such as a 1× zoom affordance or a 0.5× zoom affordance) having a second fixed position (e.g., relative to the visual indication of the option to change the representation of the field-of-view of the one or more cameras during the live video communication session (e.g., framing mode affordance)) (e.g., wherein the first zoom control is selectable to adjust the zoom level of the representation of the field-of-view of the one or more cameras to a first zoom value, and the second zoom control is selectable to adjust the zoom level of the representation of the field-of-view of the one or more cameras to a second zoom value different from the first zoom value). The computer system (e.g., **600**) detects (e.g., while displaying the live video communication interface), via the one or more input devices (e.g., **601**), a third input (e.g., **853**; **855**) corresponding to a selection of the first zoom control or the second zoom control. While continuing to display the first zoom control having the first fixed position and the second zoom control having the second fixed position (e.g., the first and second zoom controls are displayed having a position relative to (e.g., adjacent) the visual indication that does not change in response to a selection of the first or second zoom control), and in response to detecting the third input, the computer system adjusts the representation **836** of the field-of-view of the one or more cameras during the live video communication session based on the selection of the first zoom control or the second zoom control (e.g., in accordance with a determination that the first zoom control is selected, outputting (e.g., to an electronic device of the one or more participants) image data corresponding to the representation of the field-of-view of the one or more cameras having the first zoom value; and in accordance with a determination that the second zoom control is selected, outputting (e.g., to the electronic device of the one or more participants) image data corresponding to the representation of the field-of-view of the one or more cameras having the second zoom value). Adjusting the representation of the field-of-view of the one or more cameras during the live video communication session based on the selection of the first zoom control or the second zoom control while continuing to display the first and second zoom controls having the first and second fixed positions, and in response to detecting the third input, provides feedback to a user of the computer system indicating that a

different zoom level is selected for the represented field-of-view of the one or more cameras, and reduces the number of user inputs at the computer system by quickly adjusting the zoom level of the representation of the field-of-view of the one or more cameras without requiring the user to navigate a settings menu or other additional interfaces to adjust the zoom level. Providing improved feedback and reducing the number of inputs and the computer system enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0341] In some embodiments, as a part of the process for adjusting the representation of the field-of-view of the one or more cameras (e.g., **606; 806; 836**) during the live video communication session, the computer system (e.g., **600**) detects a number of subjects (e.g., **622; 628**) within the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) during the live video communication session. The computer system adjusts the representation of the field-of-view of the one or more cameras based on the number of subjects detected in the field-of-view of the one or more cameras during the live video communication session (e.g., zooming out and/or expanding the representation of the field-of-view when multiple subjects are detected or when the number of subjects detected increases; zooming in and/or contracting the representation of the field-of-view when a single subject is detected or when the number of subjects detected decreases). Adjusting the representation of the field-of-view of the one or more cameras based on the number of subjects detected in the field-of-view of the one or more cameras during the live video communication session enhances the video communication session experience by automatically adjusting the field-of-view of the cameras when the number of subjects in the scene changes without requiring further input from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0342] In some embodiments, the visual indication of the option to change the representation of the field-of-view of the one or more cameras during the live video communication session (e.g., framing mode affordance **610**) is selectable to enable a mode for which the representation of the field-of-view of the one or more cameras is automatically adjusted based on a number of subjects detected within the field-of-view of the one or more cameras, such as that discussed with respect to FIGS. **8C, 8G, and 8J**, for example. In some embodiments, the visual indication of the option to change the representation of the field-of-view of the one or more cameras during the live video communication session includes a toggle (e.g., single/multi-person framing mode affordance **830-1/830-2**) for selecting between a single-person framing mode and a multi-person framing mode.

[0343] In some embodiments, as part of the process for adjusting the representation of the field-of-view of the one or more cameras (e.g., **606; 806; 836**) during the live video communication session, the computer system (e.g., **600**) adjusts a zoom level (e.g., a digital zoom) of the representation of the field-of-view of the one or more cameras during the live video communication session based on one or more characteristics of the scene (e.g., **615**) (e.g., a distance to one or more of the subjects and/or a number of subjects in the field-of-view of the one or more cameras).

Adjusting a zoom level of the representation of the field-of-view of the one or more cameras during the live video communication session based on one or more characteristics of the scene (such as the detected distance of one or more subjects from the one or more cameras and/or a number of subjects in the field-of-view of the one or more cameras) enhances the video communication session experience by automatically adjusting the field-of-view of the cameras when a subject moves closer to, or farther away from, the one or more cameras without requiring further input

from the user. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0344] In some embodiments, the visual indication of the option to change the representation of the field-of-view of the one or more cameras during the live video communication session (e.g., framing mode affordance **610** and/or **850-1**) is selectable to enable a mode for which the zoom level of the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**) is automatically adjusted based on the distance of one or more subjects (e.g., **622**) from the one or more cameras (e.g., **602**) as discussed, for example, with respect to FIGS. **6H-6J**.

[0345] In some embodiments, the visual indication (e.g., **830**; **830-1**; **830-2**) of the option to change the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**) during the live video communication session is selectable to enable (e.g., toggle between) a first camera mode (e.g., a mode in which the representation of the field-of-view of the one or more cameras changes (e.g., zooms in/zooms out/expands/contracts) based on a number of subjects detected within the field-of-view of the one or more cameras; a multi-person framing mode) or a second camera mode (e.g., a mode in which the representation of the field-of-view of the one or more cameras does not change based on a number of subjects detected within a field-of-view of the one or more cameras; a single-person framing mode). In some embodiments, while displaying the live video communication interface (e.g., **604**; **834**) for the live video communication session, the computer system (e.g., **600**) detects a change in a scene (e.g., **615**) in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**), including a change in a number of subjects (e.g., **622**; **628**) in the scene (e.g., the number of subjects in the scene increases from one subject to two subjects). In response to detecting the change in the scene in the field-of-view of the one or more cameras, in accordance with a determination that the first camera mode is enabled, the computer system adjusts the representation of the field-of-view of the one or more cameras based on the change in the number of subjects in the scene (e.g., zooming out and/or expanding the representation of the field-of-view when multiple subjects are detected or when the number of subjects detected increases; zooming in and/or contracting the representation of the field-of-view when a single subject is detected or when the number of subjects detected decreases). In accordance with a determination that the second camera mode is enabled, the computer system forgoes adjusting the representation of the field-of-view of the one or more cameras based on the change in the number of subjects in the scene (e.g., adjusting the representation of the field-of-view of the one or more cameras based on changes in the scene other than the change in the number of subjects (e.g., displaying image data showing movement of a single subject in the scene)). Selectively adjusting the representation of the field-of-view of the one or more cameras based on the change in the number of subjects in the scene, depending upon whether the first camera mode or the second camera mode is enabled, enhances the video communication session experience by permitting the user to enable or disable a mode in which the representation of the field-of-view of the one or more cameras is automatically adjusted when additional participants are detected within the field-of-view of the one or more cameras, without requiring additional input from the user. This also reduces the number of computations performed by the computer system by eliminating extraneous adjustments to the represented field-of-view anytime additional participants are detected in the scene and the second camera mode is enabled. Performing an operation when a set of conditions has been met without requiring further user input, and reducing the number of computations performed by the computer system, enhance the operability of the computer system and make the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and

improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0346] In some embodiments, the live video communication interface (e.g., **604**; **834**) includes a first representation (e.g., **606**) of a first participant (e.g., **628**) in the live video communication session. The first representation corresponds to a first portion (e.g., **625** in FIG. **8C**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**). In some embodiments, the live video communication interface includes a second representation (e.g., **806**) of a second participant (e.g., **622**) in the live video communication session different from the first participant. The second representation corresponds to a second portion (e.g., **825** in FIG. **8C**) of the field-of-view of the one or more cameras, where the second portion of the field-of-view of the one or more cameras is different from the first portion of the field-of-view of the one or more cameras (e.g., and, in some embodiments, includes at least some of the first portion), and wherein the second representation is separate from the first representation (e.g., the first and second representations are visually distinguished from each other (e.g., by a visible boundary (e.g., a line, border, or discontinuity separating the representations) between the first and second representations)) (e.g., the first representation of the first participant and the second representation of the second participant are displayed concurrently with the representation of the field-of-view of the one or more cameras (e.g., the camera preview)). Displaying a first representation of a first participant corresponding to a first portion of the field-of-view of the one or more cameras and a second representation of a second participant corresponding to a second portion of the field-of-view of the one or more cameras that is different from the first portion of the one or more cameras and, where the second representation is separate from the first representation, provides feedback to a user of the computer system indicating that different video feeds are available for capturing different sets of participants for the live video communication session. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0347] In some embodiments, the first and second representations (e.g., **606**; **806**) have different represented fields-of-view (e.g., different zoom levels) for the respective representations. In some embodiments, the first representation includes a representation of the first participant, and the second representation includes a representation of the first participant and a representation of the second participant.

[0348] In some embodiments, the computer system (e.g., **600**) displays (concurrently) the first representation (e.g., **606**) of the first participant (e.g., **628**) and the second representation (e.g., **806**) of the second participant (e.g., **622**) in response to detecting an input (e.g., **804**) (e.g., a tap input) on the live video communication interface (e.g., **604**) for the live video communication session (e.g., the camera preview; the representation of the field-of-view of the one or more cameras; the stacked camera preview).

[0349] In some embodiments, the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**) (e.g., the camera preview, which optionally includes a representation of a participant of the live video communication session) includes a graphical indication (e.g., **630**; **610**) of whether the option to change the representation of the field-of-view of the one or more cameras during the live video communication session is enabled (e.g., the framing mode affordance is highlighted or has a selected appearance when the automatic framing mode is enabled, and is not highlighted or has an unselected appearance when the automatic framing mode is not enabled) (e.g., the framing mode affordance is displayed when the automatic framing mode is enabled and is not displayed when the automatic framing mode is not enabled). Displaying the representation of the field-of-view of the one or more cameras including a graphical indication of whether the option to change the representation of the field-of-view of the one or more cameras during the live video

communication session is enabled provides feedback to a user of the computer system indicating whether or not the option to change the representation of the field-of-view of the one or more cameras is enabled without requiring the user to access a separate menu interface or to move within the field-of-view of the one or more cameras to test whether the option is enabled. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0350] In some embodiments, while displaying the representation of the field-of-view of the one or more cameras (e.g., **836**), the computer system (e.g., **600**) detects an input (e.g., **837**) directed to the representation of the field-of-view of the one or more cameras (e.g., a tap input on the camera preview). In response to detecting the input directed to the representation of the field-of-view of the one or more cameras, the computer system displays, via the display generation component (e.g., **601**), a selectable graphical user interface object (e.g., **610-1**; **610-2**) (e.g., the framing mode affordance) that is selectable to enable (or disable) the option to change (e.g., automatically; without user input) the representation of the field-of-view of the one or more cameras during the live video communication session to a different framing option for the field-of-view of the one or more cameras (e.g., the framing mode affordance is displayed in response to an input on the camera preview, and is then selectable to enable or disable the automatic framing mode).

[0351] In some embodiments, the graphical indication (e.g., **610-1**; **610-2**) of whether the option to enable automatically changing which portion of the field-of-view of the one or more cameras is used for the live video communication session has a first appearance (e.g., as depicted in FIG. **8M**) (e.g., the framing mode affordance is displayed and/or has a non-obscured appearance when the automatic framing mode is available) when the ability to automatically change which portion of the field-of-view of the one or more cameras is used for the live video communication session is available to be used (e.g., conditions (e.g., lighting) are favorable or suitable for adjusting the representation of the field-of-view of the one or more cameras). In some embodiments, the graphical indication of whether the option to enable automatically changing which portion of the field-of-view of the one or more cameras is used for the live video communication session has a second appearance different from the first appearance (e.g., as depicted in FIG. **8N**) (e.g., the framing mode affordance is greyed out, obscured, not displayed, or otherwise unavailable when the automatic framing mode is unavailable) when the ability to automatically change which portion of the field-of-view of the one or more cameras is used for the live video communication session is unavailable to be used (e.g., conditions (e.g., lighting) are not favorable or are unsuitable for adjusting the representation of the field-of-view of the one or more cameras). Displaying the graphical indication having the first or second appearance provides feedback to a user of the computer system indicating whether the ability to automatically change which portion of the field-of-view of the one or more cameras is used for the live video communication session is available or unavailable to be used. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, when the automatic framing mode is enabled, but conditions (e.g., lighting conditions) are poor or unsuitable for automatically adjusting the representation of the field-of-view of the one or more cameras, the computer system does not display the framing mode affordance or displays the framing mode affordance having an appearance indicating that the automatic framing mode is currently unavailable.

[0352] In some embodiments, the representation of the field-of-view of the one or more cameras

(e.g., **606**; **806**; **836**) includes a first displayed region (e.g., **606-1**) (e.g., an unblurred, undarkened, unshaded, or otherwise emphasized region) of the representation of the field-of-view of the one or more cameras corresponding to a first portion (e.g., **625** in FIG. **8F**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., a portion of the field-of-view of the one or more cameras that is currently selected/outputted for the live video communication session). In some embodiments, the representation of the field-of-view of the one or more cameras includes a second displayed region (e.g., **606-2**) (e.g., a blurred, darkened, shaded, or otherwise deemphasized region) of the representation of the field-of-view of the one or more cameras corresponding to a second portion (e.g., **825** in FIG. **8F**) of the field-of-view of the one or more cameras different from the first portion of the field-of-view, wherein the second displayed region is visually distinguished from the first displayed region (e.g., the first displayed region is unblurred, undarkened, unshaded, or otherwise emphasized, and the second displayed region is blurred, darkened, shaded, or otherwise deemphasized) (e.g., the second portion of the field-of-view is greater (e.g., wider) than the first portion of the field-of-view). In some embodiments, the first displayed region is visually distinguished from the second displayed region by a border (e.g., **808**) around the first displayed region. In some embodiments, the second displayed region includes (e.g., encompasses) the first displayed region plus additional displayed regions not included in the first displayed region. In some embodiments, the second portion of the field-of-view includes (e.g., encompasses) the first portion of the field-of-view plus additional portions of the field-of-view not in the first portion of the field-of-view.

[0353] In some embodiments, in accordance with a determination that the first portion (e.g., **625** in FIG. **8F**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) is selected (e.g., currently selected/outputted) for the live video communication session, the computer system (e.g., **600**) displays the first displayed region (e.g., **606-1**) having a visually unobscured (e.g., unblurred, undarkened, unshaded, or otherwise emphasized) appearance, and displays the second displayed region (e.g., **606-2**) of the representation of the field-of-view with an obscured appearance (e.g., having a visually obscured (e.g., blurred, darkened, shaded, or otherwise deemphasized) appearance).

[0354] In some embodiments, in accordance with a determination that the second portion (e.g., **625** in FIG. **8G**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) is selected (e.g., currently selected/outputted) for the live video communication session, the computer system (e.g., **600**) displays the second displayed region having a visually unobscured (e.g., unblurred) appearance (e.g., **606** as depicted in FIG. **8G**) (e.g., and optionally displaying the first displayed region having the visually unobscured appearance) (e.g., and optionally displaying the first displayed region having a visually obscured appearance). Displaying the first displayed region and/or the second displayed region having a visually unobscured appearance in accordance with a determination that the first and/or second portion of the field-of-view of the one or more cameras is selected for the live video communication session provides feedback to a user of the computer system indicating the portion of the field-of-view that is selected for the live video communication session. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0355] In some embodiments, the computer system (e.g., **600**) indicates the currently selected portion (e.g., **625**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) for the live video communication session by displaying the region (e.g., **606**; **606-1**) corresponding to the currently selected portion of the field-of-view having an unobscured appearance (e.g., unblurred). Incidentally, the computer system displays portions (e.g., **825**) of the representation of the field-of-view of the one or more cameras that are not currently selected for the live video communication

session as having an obscured (e.g., blurred) appearance (e.g., **606-2**). For example, when the first portion of the field-of-view is selected, the first displayed region is displayed unblurred, while the second displayed region is blurred, thereby indicating that the first displayed region (the first portion of the field-of-view) is selected for being outputted for the live video communication session, but the second displayed region (the second portion of the field-of-view (the portion that does not include the first portion of the field-of-view)) is not.

[0356] In some embodiments, the representation of the field-of-view of the one or more cameras (e.g., **606**) includes a graphical element (e.g., **808**) (e.g., boundary) displayed to separate the first displayed region (e.g., **606-1**) from the second displayed region (e.g., **606-2**) (in some embodiments, the second displayed region (including the second portion of the field-of-view) includes a border (e.g., **809**) to visually distinguish it from the representation of one or more participants (e.g., remote participants) in the live video communication session other than participants visible via the one or more cameras). Displaying the representation of the field-of-view including a graphical element displayed to separate the first displayed region from the second displayed region provides feedback to a user of the computer system indicating that the first displayed region is separate from the second displayed region. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0357] In some embodiments, the computer system (e.g., **600**) displays one or more indications (e.g., **630**) (e.g., framing indications) of one or more faces in the second portion (e.g., **825** in FIG. **8F**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., framing indications are displayed at least partially in the blurred region (e.g., **606-2**) of the camera preview to indicate the presence of faces detected in the field-of-view of the one or more cameras (e.g., in the second portion of the field-of-view of the one or more cameras)) (e.g., framing indications are displayed framing the faces detected in the second portion of the field-of-view of the one or more cameras). In some embodiments, the one or more indications are selectable to initiate a process for adjusting the representation of the field-of-view of the one or more cameras (e.g., **606**) during the live video communication session (e.g., the representation of the field-of-view is adjusted to include a representation of a face corresponding to the selected indication) (e.g., switching from the first portion of the field-of-view of the one or more cameras to the second portion of the field-of-view of the one or more cameras for the live video communication session). Displaying one or more indications of the one or more faces in the second portion of the field-of-view of the one or more cameras that are selectable to initiate a process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session provides the user with easily accessible controls for adjusting the representation of the field-of-view without cluttering the UI with additional displayed controls for manually adjusting the representation of the field-of-view to fit the additional faces, and provides feedback to a user of the computer system indicating that the one or more faces are detected in the field-of-view of the one or more cameras and that the computer system is capable of adjusting the representation of the field-of-view of the one or more cameras during the live video communication session to include representations of the one or more faces. Providing additional controls without cluttering the UI and providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0358] In some embodiments, the one or more indications (e.g., **630**) of the one or more faces in

the second portion (e.g., **825** in FIG. **8F**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) are displayed while a face of a first subject (e.g., **628**) is detected in the field-of-view (e.g., **620**) of the one or more cameras (e.g., in the first portion (e.g., **625** in FIG. **8F**) of the field-of-view) and the first portion (e.g., **625**) of the field-of-view of the one or more cameras is selected for the live video communication session. In some embodiments, the one or more indications of the one or more faces are displayed in response to detecting the one or more faces of subjects (e.g., **622**) other than the first subject in the second portion (e.g., **825**) of the field-of-view of the one or more cameras.

[0359] In some embodiments, while the first portion (e.g., **625** in FIG. **8F**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) is selected for the live video communication session, the computer system (e.g., **600**) detects a selection (e.g., **813**) of one or more of the indications (e.g., **630**) of the one or more faces in the second portion (e.g., **825**) of the field-of-view of the one or more cameras. In response to detecting the selection of one or more of the indications, the computer system initiates a process for adjusting (e.g., expanding; unblurring additional regions of) the representation of the field-of-view of the one or more cameras during the live video communication session to include one or more representations of the one or more faces corresponding to the selected indications (e.g., as depicted in FIG. **8G**) (e.g., the second region becomes unblurred to indicate the second portion of the field-of-view of the one or more cameras is selected/outputted for the live video communication session). In some embodiments, as the indications are selected, the computer system expands (e.g., indicated by the unblurring of) the representation of the field-of-view of the one or more cameras (the camera preview) to include representations of the faces corresponding to the selected indications. In some embodiments, in response to a selection of one of the indications, the computer system includes the second portion of the field-of-view of the one or more cameras for the live video communication session.

[0360] In some embodiments, the representation of the field-of-view of the one or more cameras (e.g., **606**) includes a representation of a first subject (e.g., **628-1**) detected in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**). In some embodiments, as a part of initiating the process for adjusting the representation of the field-of-view of the one or more cameras during the live video communication session, the computer system (e.g., **600**) automatically (e.g., without user input) adjusts (e.g., enlarging and/or shifting) the representation of the field-of-view of the one or more cameras to include a representation of a second subject (e.g., **622-1**) detected in the field-of-view of the one or more cameras that meet a set of criteria (e.g., as depicted in FIG. **8J**), wherein the representation of the second subject is displayed concurrently with the representation of the first subject (e.g., the subject(s) is visible in the field-of-view of the one or more cameras; the subject(s) is stationary for a predetermined period of time). In some embodiments, the computer system automatically adjusts the representation of the field-of-view of the one or more cameras based on the number of subjects (e.g., when the multi-person framing mode is enabled). Automatically adjusting the representation of the field-of-view of the one or more cameras to include the representation of the second subject that is displayed concurrently with the representation of the first subject enhances the live video communication session experience by automatically adjusting the representation of the field-of-view of the one or more cameras when additional subjects are detected in the scene. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0361] In some embodiments, while displaying the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**) having a first displayed state (e.g., **606** in FIG. **6P**) (e.g., a first zoom level), and while a face of a subject (e.g., **628**) is detected in a first region (e.g., **625**) of the

field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**), detecting a second subject (e.g., **622**) in a second region of the field-of-view of the one or more cameras (e.g., a region of the field-of-view that is outside the first region). In response to detecting the second subject in the second region of the field-of-view of the one or more cameras, the computer system (e.g., **600**) displays a second selectable graphical user interface object (e.g., **632**) (e.g., an affordance and/or text). The computer system detects a selection (e.g., **634**) of the second selectable graphical user interface object. In response to detecting the selection of the second selectable graphical user interface object, the computer system adjusts the representation of the field-of-view of the one or more cameras from having the first displayed state to having a second displayed state (e.g., a second zoom level) that is different from the first displayed state and includes a representation of the second subject (e.g., as depicted in FIG. **6Q**). Displaying a second selectable graphical user interface object that causes the device to adjust the representation of the field-of-view of the one or more cameras from having the first displayed state to having a second displayed state that is different from the first displayed state and includes a representation of the second subject provides controls as needed for adjusting the representation of the field-of-view of the one or more cameras when additional participants are detected in the field-of-view of the one or more cameras. Providing additional control options without cluttering the UI with additional displayed controls enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, when a second subject (e.g., a potential participant of the live video communication session) is detected within the field-of-view of the one or more cameras, the computer system displays an option that can be selected to adjust (e.g., expand) the field-of-view of the representation of the field-of-view of the one or more cameras to include both the first subject and the second subject.

[0362] In some embodiments, while a mode (e.g., automatic framing mode) is enabled for automatically adjusting the representation of the field-of-view of the one or more cameras (e.g., **606**; **806**; **836**) during the live video communication session based on a change in position of a subject (e.g., **622**; **628**) detected in the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**), the computer system (e.g., **600**) detects a selection (e.g., **853**) of an option (e.g., **850-2**) for changing a zoom level (e.g., an option for selecting a predetermined zoom level such as a 2× zoom affordance, a 1× zoom affordance, or a 0.5× zoom affordance changing a digital and/or optical zoom) of the representation of the field-of-view of the one or more cameras (e.g., **836**) during the live video communication session. In response to detecting the selection of the option for changing the zoom level, the computer system disables the mode for automatically adjusting the representation of the field-of-view of the one or more cameras during the live video communication session and adjusts a zoom level of the representation of the field-of-view of the one or more cameras (e.g., as depicted in FIG. **8Q**).

[0363] Note that details of the processes described above with respect to method **900** (e.g., FIG. **9**) are also applicable in an analogous manner to the methods described above and below. For example, method **700**, method **1100**, method **1300**, and/or method **1400** optionally include one or more of the characteristics of the various methods described above with reference to method **900**. For brevity, these details are not repeated.

[0364] FIGS. **10A-10J** illustrate exemplary user interfaces for managing a live video communication session (e.g., a video conference), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described herein, including the processes in FIG. **11**.

[0365] FIGS. **10A-10J** illustrate device **600** displaying user interfaces on display **601** for managing a live video communication session, similar to that discussed above with respect to FIGS. **6A-6Q**

and FIGS. 8A-8R. FIGS. 10A-10J depict various embodiments in which device 600, when an automatic framing mode is enabled, can emphasize or more prominently display the portions of the field-of-view of the camera that include more important or relevant content, such as participants of the video conference session, and exclude or deemphasize portions of the field-of-view of the camera that do not include the more important or relevant content. One or more of the embodiments discussed below with respect to FIGS. 10A-10J can be combined with one or more of the embodiments discussed herein with respect to FIGS. 6A-6Q, FIGS. 8A-8R, and FIGS. 12A-12U.

[0366] FIG. 10A depicts an embodiment similar to those discussed with respect to FIGS. 6A-6Q and FIGS. 8A-8R, except that the automatic framing feature is not provided (e.g., the automatic framing mode is disabled or device 600 is not configured to provide the automatic framing feature). FIG. 10A is used to illustrate the differences in the video feed field-of-view that is output by device 600 for the video conference, in comparison to embodiments in which the automatic framing feature is provided.

[0367] FIG. 10A depicts scene 615 with Jane 622 and Jack 628 sitting on couch 621. Device 600 displays video conference interface 1004, which is similar to video conference interfaces 604 and 834. Video conference interface 1004 includes camera preview 1006 (similar to camera previews 606 and 836), options menu 1008 (similar to options menu 608), and video feed 1023 (similar to video feed 623). In some embodiments, device 600 does not display a framing mode affordance in video conference interface 1004 when the automatic framing mode is not provided. In some embodiments, device 600 displays a framing mode affordance having an unselected state when the automatic framing mode is not provided. In some embodiments, device 600 displays camera preview 1006 having the appearance depicted in FIG. 10A when the automatic framing feature is not provided, or when the automatic framing feature is provided, but not enabled.

[0368] In FIG. 10A, Jane and Jack are participating in a video conference with John using device 600. Similarly, John is participating in the video conference with Jane and Jack using a device that includes one or more features of devices 100, 300, 500, or 600. For example, John is using a tablet similar to device 600 (e.g., John's tablet 600a in FIGS. 10H-10I and 12B-12N). Accordingly, John's device displays a video conference interface similar to video conference interface 1004, except that the camera preview on John's device displays the video feed captured from John's device (what is currently depicted in video feed 1023 in FIG. 10A), and the incoming video feed on John's device displays the video feed output from device 600 (what is currently depicted in camera preview 1006 in FIG. 10A).

[0369] In the embodiment depicted in FIG. 10A, Jane and Jack are participants of a video conference with John, who is depicted as representation 1023-1 in video feed 1023. In this embodiment, because the automatic framing mode is not provided, the video feed field-of-view for the video conference is the same as (or substantially similar to) the field-of-view of camera 602, as depicted in camera preview 1006. Accordingly, camera preview 1006 depicts representation 615-1 of scene 615, which is shrunk down to fit within the boundaries of camera preview 1006, resulting in a compressed view of the scene that deemphasizes the participants and clutters the camera preview by displaying extraneous portions of the scene that are not relevant to other participants of the video conference (e.g., John). As will be described in greater detail below, when the automatic framing mode is enabled, device 600 optimizes the displayed video feed field-of-view in order to emphasize or more prominently display the portions of the field-of-view of camera 602 that include more important or relevant content, such as participants of the video conference session, and to exclude or deemphasize portions of the field-of-view of camera 602 that do not include the more important or relevant content.

[0370] FIG. 10B depicts an embodiment similar to that shown in FIG. 10A, except that the automatic framing feature is now provided by device 600. In some embodiments, the provision of the automatic framing feature is indicated, for example, by the display of framing mode affordance

1010 (similar to framing mode affordance **610**), or by the bolding of framing mode affordance **1010** to indicate an enabled state of the automatic framing mode. Moreover, because the automatic framing feature is now enabled, device **600** automatically reframes the video feed field-of-view depicted in camera preview **1006** based on detected changes in scene **615** (e.g., to emphasize participants detected within the available field-of-view of camera **602**). Portion **625** represents the portion of field-of-view **620** that is currently displayed for the video conference (as depicted in camera preview **1006**).

[0371] When the automatic framing mode is enabled, device **600** is capable of detecting conditions of scene **615** and, in response, automatically adjusting (e.g., zooming in/out, panning, resizing, reframing, splitting, merging, etc.) the displayed video feed field-of-view based on the conditions detected in the scene. In the embodiments illustrated in FIGS. **10B-10J**, the conditions that affect the displayed video feed field-of-view can include a number of subjects detected in the scene, a spacing of the subjects, and/or positioning of subjects. In some embodiments, other conditions discussed throughout the present disclosure can also be considered, such as movement of the subjects, inputs at device **600**, and various device settings such as whether a single-person framing mode or multi-person framing mode is enabled.

[0372] In FIG. **10B**, device **600** detects the presence of Jane **622** and Jack **628** in scene **615** and, in response, adjusts the displayed video feed field-of-view to more prominently display representations of Jane **622** and Jack **628**, based on a spacing of the subjects. In FIG. **10B**, device **600** detects that Jane **622** and Jack **628** are sitting close together. In response, device **600** displays portion **625** of field-of-view **620**, which is a continuous portion of field-of-view **620** that includes the detected participants and the portion of the scene between them. Camera preview **1006** represents a continuous video feed field-of-view that depicts representation **622-1** of Jane adjacent representation **628-1** of Jack, with representation **618-1** of the door and representation **1016-1** of picture **1016** in the background. When compared to the embodiment in FIG. **10A**, where the automatic framing feature is not provided, the camera preview in FIG. **10B** depicts an output video feed that is zoomed in on participants Jack **628** and Jane **622**, eliminating the display of extraneous portions of scene **615** that are not relevant for the video conference.

[0373] In FIG. **10C**, device **600** detects that Jane **622** has moved away from Jack **628** (she is separate from Jack by a threshold amount). In response, device **600** transitions the outputted video feed field-of-view from the continuous field-of-view depicted in FIG. **10B** to a split field-of-view, as depicted in FIG. **10C**. For example, device **600** displays the camera preview with first preview portion **1006-1** separated from second preview portion **1006-2** by line **1015**. In some embodiments, line **1015** is depicted in video conference interface **1004**, but is not included in the output video feed field-of-view. In some embodiments, line **1015** is included in the output video feed field-of-view. First preview portion **1006-1** represents the content of portion **625-1** of field-of-view **620** that includes Jane **622**. Accordingly, first preview portion **1006-1** includes representation **622-1** of Jane **622** and representation **618-1** of door **618** in the background behind her. Second preview portion **1006-2** represents the content of portion **625-2** of field-of-view **620** that includes Jack **628**. Accordingly, second preview portion **1006-2** includes representation **628-1** of Jack **628** and representation **1016-1** of picture **1016** in the background behind him. Portion **1027** represents the portion of field-of-view **620** that was previously displayed in camera preview **1006** in FIG. **10B** and is now excluded from the camera preview, as illustrated in FIG. **10C**.

[0374] As depicted in FIG. **10C**, Jane **622** is standing while Jack **628** is sitting, placing Jane's head higher in the scene than Jack's head. In the embodiment in FIG. **10C**, device **600** accounts for the vertical offset by framing the portions of the video feed field-of-view about the respective participants' faces. Therefore, portion **625-1** is vertically offset from portion **625-2** within camera field-of-view **620**. The result is that representation **622-1** of Jane **622** and representation **628-1** of Jack **628** are not vertically offset in the camera preview, which could be distracting to viewers of the camera preview (e.g., Jane or Jack) or output video feed (e.g., John).

[0375] As illustrated in FIGS. **10B** and **10C**, device **600** accounts for changes in the scene that is within field-of-view **620** by switching between a continuous video feed field-of-view and a split video feed field-of-view, in order to more prominently feature the participants of the video conference while also eliminating the display of portions of the scene that are not relevant to the video conference. The embodiments depicted in FIGS. **10D-10G** illustrated examples of additional scenarios for which device **600** switches between the split and continuous fields-of-view.

[0376] In FIG. **10D**, Jake **1031** is now sitting on the couch in between Jane **622** and Jack **628**. Device **600** detects the addition of Jake **1031** between Jane and Jack and, in response, transitions from the split field-of-view in FIG. **10C** to the continuous field-of-view depicted in FIG. **10D**. Device **600** now displays portion **625** of field-of-view **620** in camera preview **1006**, which includes representations **622-1**, **1031-1**, and **628-1** of Jane, Jake, and Jack, respectively. Portions **1027-1** and **1027-2** represent the portions of field-of-view **620** that were previously displayed in the split field-of-view depicted in FIG. **10C**.

[0377] In FIG. **10E**, Jake leaves scene **615**, and Jane **622** and Jack **628** remain seated on the couch. In response to detecting the departure of Jake from between Jane and Jack, device **600** transitions from the continuous video feed field-of-view depicted in **10D** to the split video feed field-of-view depicted in the camera preview in FIG. **10E**. The split field-of-view is similar to that depicted in FIG. **10C**. In FIG. **10E**, portions **625-1** and **625-2** of field-of-view **620** are displayed in first preview portion **1006-1** and second preview portion **1006-2**, respectively, and portion **1027** represents the portion of field-of-view **620** that was previously displayed in the continuous video feed field-of-view depicted in FIG. **10D**.

[0378] In FIG. **10F**, Jane **622** moves back to her position on the couch next to Jack **628**, similar to that depicted in FIG. **10B**. In response to detecting Jane positioned next to Jack (less than a threshold distance from Jack), device **600** transitions from the split video feed field-of-view depicted in FIG. **10E** to the continuous video feed field-of-view depicted in camera preview **1006** in FIG. **10F**. The continuous field-of-view is similar to that depicted in FIG. **10B**. In FIG. **10F**, portion **625** of field-of-view **620** is displayed in camera preview **1006**, and portions **1027-1** and **1027-2** represent the portions of field-of-view **620** that were previously displayed in the split video feed field-of-view depicted in FIG. **10E**.

[0379] In FIG. **10G**, Jack **628** has left the frame of camera preview **1006** in FIG. **10F** (represented by portion **1027** of field-of-view **620**). In response to detecting Jack leaving the frame, device **600** automatically readjusts the frame of the video feed field-of-view to zoom in on Jane **622**, as depicted in FIG. **10G**. Accordingly, portion **625** of field-of-view **620** is now displayed in camera preview **1006**, depicting a larger view of representation **622-1** of Jane.

[0380] FIGS. **10H-10J** depict embodiments in which the split video feed field-of-view includes more than two portions. In these embodiments, participants of the video conference include Jane, Jack, Jake, John, and Pam. In FIG. **10H**, Jane, Jack, and Jake are participating in the video conference using device **600**, whereas John and Pam are participating in the video conference each using a respective device that includes one or more features of devices **100**, **300**, **500**, or **600**. For example, John is using device **600a** (also referred to herein as “John's tablet”), which is depicted with device **600** in FIG. **10H**. Device **600a** is similar to device **600** and includes components such as display **601a** and camera **602a**. Similarly, Pam is using a device similar to device **600** and device **600a**. In FIG. **10H**, the video feed from Pam's device, which includes a representation of Pam, is displayed on device **600** as video feed **1024** and is displayed on John's device **600a** as video feed **1025**.

[0381] In FIG. **10H**, Jake **1031** is seated in scene **615** with Jane **622** and Jack **628**. Device **600** detects that Jane, Jack, and Jake are each separated from each other by at least a threshold distance and, in response, outputs a video feed that is split into three portions. Video conference interface **1004** includes lines **1015-1** and **1015-2** separating camera preview **1006** into three distinct portions each corresponding to a displayed portion of field-of-view **620**. First preview portion **1006-1**

displays portion **625-1** of field-of-view **620**, which includes Jake **1031** who is depicted in first preview portion **1006-1** by representation **1031-1**. Second preview portion **1006-2** displays portion **625-2** of field-of-view **620**, which includes Jane **622** who is depicted in second preview portion **1006-2** by representation **622-1**. Third preview portion **1006-3** displays portion **625-3** of field-of-view **620**, which includes Jack **628** who is depicted in third preview portion **1006-3** by representation **628-1**.

[0382] John's device **600a** depicts video conference interface **1054**, which is similar to video conference interface **1004** and video conference interface **834**. Video conference interface **1054** includes camera preview **1056**, which depicts a representation of John, who is positioned with the field-of-view of camera **602a**. In addition to receiving the video feed from Pam's device, John's device **600a** is receiving the video feed output from device **600**. However, instead of displaying the received video feed from device **600** in a split field-of-view similar to camera preview **1006**, device **600a** displays each portion of the video feed as a separate video feed that is visually distinct and separate from the others, similar to Pam's video feed **1025** and similar to other embodiments (such as that shown in FIG. **8L**) where multiple video feeds are displayed when the device is participating in a video conference session with multiple remote devices and participants. Accordingly, video conference interface **1054** displays video feeds **1053-1**, **1053-2**, and **1053-3** along with Pam's video feed **1025**, as depicted in FIG. **10H**. Video feed **1053-1** corresponds to first preview portion **1006-1** and, therefore, displays a representation of portion **625-1** of field-of-view **620**. Video feed **1053-2** corresponds to second preview portion **1006-2** and, therefore, displays a representation of portion **625-2** of field-of-view **620**. Video feed **1053-3** corresponds to third preview portion **1006-3** and, therefore, displays a representation of portion **625-3** of field-of-view **620**.

[0383] In some embodiments, the displayed video feeds change size based on a detected level of activity within the respective video feed. For example, in FIG. **10H**, the level of activity detected in video feed **1023** is greater than the level of activity detected in video feed **1024**. Thus, device **600** displays John's video feed **1023** having a larger size and/or more prominent position than (for example, partially overlapping) Pam's video feed **1024**. Similarly, the level of activity detected in Pam's video feed **1025** is greater than the level of activity detected in video feeds **1053-1**, **1053-2**, and **1053-3**. Therefore, Pam's video feed **1025** is displayed having a larger size and/or more prominent position than video feeds **1053-1**, **1053-2**, and **1053-3**.

[0384] FIG. **10I** depicts an embodiment similar to that shown in FIG. **10H**, except that Pam has ended her participation in the video conference via her respective device (Pam ended the video conference call on her device), and has now physically entered scene **615** and is standing next to Jack **628**. Because Pam ended the video conference on her device, the video feed from Pam's device is no longer displayed on device **600** and device **600a**. Additionally, device **600** detects the presence of Pam **1032** next to Jack **628** and, in response, automatically adjusts the displayed video feed field-of-view to include Pam **1032**, who is determined to be an additional participant of the video conference. Because Pam **1032** is less than a threshold distance from Jack **628** in the embodiment depicted in FIG. **10I**, device **600** reframes (e.g., pans) the displayed portion of field-of-view **620** that previously included Jack **628** to include both Jack **628** and Pam **1032**. In some embodiments, the reframing can include panning, zooming, and/or resizing the displayed video feed field-of-view (or a portion thereof). Portion **625-3** represents the displayed field-of-view **620** after the adjustment, and portion **1027** represents the field-of-view that was displayed prior to the adjustment.

[0385] As a result of the adjusted video feed field-of-view, device **600** updates third preview portion **1006-3** to include representation **1032-1** of Pam with representation **628-1** of Jack, and device **600a** updates video feed **1053-3** in an analogous manner. Additionally, due to Pam's entering video feed **1053-3**, video feed **1053-3** has a greater level of activity than video feeds **1053-1** and **1053-2**. As a result, John's device **600a** displays video feed **1053-3** having an enlarged size.

[0386] FIG. **10J** depicts an embodiment similar to that shown in FIG. **10I**, except that Pam **1032**

has moved to a position on the couch, separated from the other subjects in the scene. In response to detecting Pam **1032** moving from her position next to Jack **628** to her position on the couch, device **600** automatically splits the displayed video field-of-view into four portions, each including one of the subjects in the scene, and resizes the displayed portions as needed. The previously displayed portions of field-of-view **620** are represented by portions **1027-1**, **1027-2**, and **1027-3**. The currently displayed portions of field-of-view **620** are represented by portions **625-1**, **625-2**, **625-3**, and **625-4**.

[0387] As a result of the adjusted video feed field-of-view, device **600** updates camera preview **1006** to include fourth preview portion **1006-4**, and resizes the other preview portions to fit within camera preview **1006**. Third preview portion **1006-3** now corresponds to portion **625-3**, which includes Pam **1032**, and fourth preview portion **1006-4** corresponds to portion **625-4**, which includes Jack **628**. Device **600a** updates video conference interface **1054** in an analogous manner by adding video feed **1053-4**. Video feed **1053-3** corresponds to third preview portion **1006-3**, and video feed **1053-4** corresponds to fourth preview portion **1006-4**. Additionally, due to Pam's movement within the scene (specifically, within the portions of the scene corresponding to video feeds **1053-3** and **1053-4**), video feeds **1053-3** and **1053-4** have a greater level of activity than video feeds **1053-1** and **1053-2**. As a result, John's device **600a** displays video feeds **1053-3** and **1053-4** having an enlarged size.

[0388] The embodiments discussed herein and depicted in FIGS. **6A-6Q**, FIGS. **8A-8R**, FIGS. **10A-10J**, and FIGS. **12A-12U** provide representative, non-limiting examples of the adjustments performed by device **600** in response to detecting changes within a field-of-view of the camera when various modes of operation, such as the automatic framing mode or the background blur mode, are enabled. As such, the adjustments are not intended to be limiting and can be combined, reversed, or modified in accordance with the scope of the present disclosure. For example, with reference to FIGS. **10I** and **10J**, if Pam **1032** were to move from the couch to her prior position next to Jack **628**, device **600** could merge the third and fourth preview portions to display camera preview having the appearance depicted in FIG. **10I**.

[0389] FIG. **11** is a flow diagram illustrating a method for managing a live video communication session using an electronic device in accordance with some embodiments. Method **1100** is performed at a computer system (e.g., a smartphone, a tablet) (e.g., **100**, **300**, **500**, **600**, **600a**) that is in communication with a display generation component (e.g., a display controller, a touch-sensitive display system) (e.g., **601**) and one or more cameras (e.g., a visible light camera; an infrared camera; a depth camera) (e.g., **602**). Some operations in method **1100** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

[0390] As described below, method **1100** provides an intuitive way for managing a live video communication session. The method reduces the cognitive burden on a user for managing a live video communication session, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to manage a live video communication session faster and more efficiently conserves power and increases the time between battery charges.

[0391] In method **1100**, computer system (e.g., **600**) displays (**1102**) via the display generation component (e.g., **601**), a live video communication interface (e.g., **1004**) for a live video communication session (e.g., an interface for a live video communication session (e.g., a live video chat session, a live video conference session, etc.)), the live video communication interface including one or more representations (e.g., **1006**) of a field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., the live video communication interface is displayed with a first digital zoom level and a first displayed portion of the field-of-view of the one or more cameras).

[0392] While the live video communication session is active, the computer system (e.g., **600**) captures (**1104**), via the one or more cameras (e.g., **602**), image data for the live video communication session (e.g., data captured in camera field-of-view **620**).

[0393] In accordance with a determination (**1106**), based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that an amount of separation (e.g., distance and/or angle) between a first participant (e.g., **622**) (e.g., of the live video communication session) and a second participant (e.g., **628**) (e.g., of the live video communication session) (e.g., a detected distance and/or angle within the field-of-view of the one or more cameras and between the first participant and the second participant) meets separation criteria (e.g., as depicted in FIG. **10C**) (e.g., is greater than a first threshold amount (e.g., distance and/or angle)), computer system (e.g., **600**) concurrently displays, via the display generation component (e.g., **601**), the items noted in **1108** and **1110**.

[0394] At **1108** of method **1100**, the computer system (e.g., **600**) displays a representation (e.g., content (e.g., **622-1**) depicted in first preview **1006-1**) (e.g., live video) of a first portion (e.g., **625-1**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., a first portion that includes image data for (e.g., representing) the first participant (e.g., and excludes image data for the second participant)) (e.g., the representation of the first portion of the field-of-view of the one or more cameras includes a representation of the first participant, but not a representation of the second participant) at a first region (e.g., **1006-1**) of the live video communication interface (e.g., **1004**).

[0395] At **1110** of method **1100**, the computer system (e.g., **600**) displays a representation (e.g., content (e.g., **628-1**) depicted in second preview **1006-2**) (e.g., live video) of a second portion (e.g., **625-2**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) (e.g., a second portion that includes image data for (e.g., representing) the second participant (e.g., and excludes image data for the first participant)) (e.g., the representation of the second portion of the field-of-view of the one or more cameras includes a representation of the second participant, but not a representation of the first participant) at a second region (e.g., **1006-2**) of the live video communication interface (e.g., **1004**) that is distinct from the first region (e.g., **1006-1**) (e.g., the first and second regions are visually distinguished from each other (e.g., by a visible boundary (e.g., a line **1015** or discontinuity separating the regions) between the first and second regions); the first and second regions do not overlap (but, in some embodiments, share a boundary)). The representation of the first portion of the field-of-view of the one or more cameras and the representation of the second portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a third portion (e.g., **1027**) of the field-of-view of the one or more cameras that is in between the first portion (e.g., **625-1**) of the field-of-view of the one or more cameras and the second portion (e.g., **625-2**) of the field-of-view of the one or more cameras (e.g., the live video communication interface has a split field-of-view that includes the first and second portions of the field-of-view of the one or more cameras and omits the third portion of the field-of-view of the one or more cameras, as depicted in FIG. **10C**, for example). Displaying the representation of the first portion of the field-of-view of the one or more cameras at a first region of the live video communication interface, and displaying a representation of a second portion of the field-of-view of the one or more cameras at a second region of the live video communication interface, without displaying a representation of a third portion of the field-of-view of the one or more cameras that is in between the first and second portions optimizes use of the display to present more relevant information to the user and to present the relevant information with a larger view than would otherwise be available, and conserves computational resources by using fewer pixels to display information that is not relevant to the user. Optimizing use of the display and conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the live video communication interface does not include (e.g., omits; forgoes displaying) a representation of image data for at least a

portion of the field-of-view of the one or more cameras that is positioned between the first participant and the second participant. In other words, in some embodiments, when the first and second participants are physically separated in the physical environment by more than the threshold amount within the field-of-view of the one or more cameras, the live video communication interface does not show a representation of at least some of the physical environment positioned between the first and second participants.

[0396] In accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that the amount of separation between the first participant (e.g., **622**) and the second participant (e.g., **628**) does not meet the separation criteria (e.g., as depicted in FIG. **10B**) (e.g., is less than the first threshold amount (e.g., distance and/or angle)), the computer system (e.g., **600**) displays (**1112**), via the display generation component (e.g., **601**), a representation (e.g., content (e.g., **618-1**, **622-1**, **628-1**, **1016-1**) depicted in camera preview **1006**) (e.g., live video) of a fourth portion (e.g., **625** in FIG. **10B**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) that includes the first participant (e.g., **622**) and the second participant (e.g., **628**) while maintaining display of a portion (e.g., **1027** in FIG. **10C**) (e.g., the third portion) of the field-of-view of the one or more cameras that is in between the first participant and the second participant (e.g., without excluding any of the portion of the field-of-view of the one or more cameras that is between the first participant and the second participant) (e.g., including all of the field-of-view of the one or more cameras that is between the first participant and the second participant) (e.g., wherein the fourth portion of the field-of-view of the one or more cameras is a continuous portion of the field-of-view of the one or more cameras (e.g., the live video communication interface has a continuous field-of-view that includes the first and second participants)) (e.g., the fourth portion of the field-of-view of the one or more cameras is different from the first portion of the field-of-view of the one or more cameras and the second portion of the field-of-view of the one or more cameras; in some embodiments the fourth portion of the field-of-view of the one or more cameras includes both the first and second portions of the field-of-view of the one or more cameras and at least a portion of the field-of-view of the one or more cameras that is not included in the first and second portions (e.g., the third portion)) (e.g., the fourth portion of the field-of-view of the one or more cameras includes image data for (e.g., representing) the first participant and the second participant) (e.g., the representation of the fourth portion of the field-of-view of the one or more cameras includes a representation of the first participant and a representation of the second participant). In some embodiments, the representation of the fourth portion of the field-of-view of the one or more cameras includes a representation of image data for the field-of-view of the one or more cameras that is positioned between the first participant and the second participant. In other words, in some embodiments, when the first and second participants are physically separated in the physical environment by less than the threshold amount within the field-of-view of the one or more cameras, the live video communication interface (e.g., **1004**) does not exclude a representation of the physical environment between the first and second participants.

[0397] In some embodiments, a representation (e.g., **622-1**) of the first participant (e.g., **622**) is capable of being displayed (e.g., by the display generation component (e.g., **601**) of the computer system (e.g., **600**)) in the representation (e.g., **1006-1**) of the first portion of the field-of-view of the one or more cameras and in the representation (e.g., **1006** in FIG. **10B**) of the fourth portion of the field-of-view of the one or more cameras. In some embodiments, the representation of the first participant is more largely/prominently/clearly displayed in the representation of the first portion than in the representation of the fourth portion. This is because the continuous field-of-view provided by the representation of the fourth portion is a zoomed out view so that the representations (e.g., **622-1** and **628-1**) of both the first and second participants (e.g., **622** and **628**), as well as the portion of the field-of-view of the one or more cameras that is between the first and second participants, can be displayed in the representation of the fourth portion of the field-of-view

of the one or more cameras, whereas the representation of the first participant can be displayed with a more zoomed in view because the third portion of the field-of-view of the one or more cameras that is between the first and second participants is omitted when the representations of the first and second portions of the field-of-view of the one or more cameras are displayed. For similar reasons, the representation of the second participant is more largely/prominently/clearly displayed in the representation of the second portion than in the representation of the fourth portion.

[0398] In some embodiments, the representation of the first portion (e.g., **625-1**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**), the representation of the second portion (e.g., **625-2**) of the field-of-view of the one or more cameras, and the representation of the fourth portion (e.g., **625** in FIG. **10B**) of the field-of-view of the one or more cameras are generated from a set of data (e.g., image data within field-of-view **620**) captured from a first camera (e.g., **602**) (e.g., a wide angle camera (e.g., a single camera with a wide angle lens) (e.g., the representations of the portions of the field-of-view of the one or more cameras are all generated from a same set of image data obtained at the same time from a single camera).

[0399] In some embodiments, the amount of separation between the first participant (e.g., **622**) and the second participant (e.g., **628**) does not meet the separation criteria in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that a third participant (e.g., **1031**) (e.g., a participant other than the first or second participant) is detected between the first participant and the second participant (e.g., as depicted in FIG. **10D**) (e.g., the split field-of-view is not displayed when there is at least one participant between the first and second participants in the live video communication session) (e.g., the continuous field-of-view is displayed when there is at least one participant between the first and second participants in the live video communication session).

[0400] In some embodiments, the amount of separation between the first participant (e.g., **622**) and the second participant (e.g., **622**) does not meet the separation criteria in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that a distance between the first participant and a middle participant (e.g., **1031**) (e.g., a participant positioned between the first and second participants) is less than a first threshold distance (e.g., 3 feet, 2 feet, 1 foot) and a distance between the second participant (e.g., **628**) and the middle participant is less than the first threshold distance (e.g., as depicted in FIG. **10D**) (e.g., the split field-of-view is not displayed when there is at least one participant between the first and second participants in the live video communication session, and the distance between the middle participant and the first and second participants is less than a threshold distance) (e.g., the continuous field-of-view is displayed when there is at least one participant between the first and second participants in the live video communication session and the distance between the middle participant and the first and second participants is less than a threshold distance).

[0401] In some embodiments, in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that the first participant (e.g., **622**) is the only participant detected (e.g., see FIG. **10G**) (e.g., there is only one participant detected in the live video communication session), the computer system (e.g., **600**) displays, via the display generation component (e.g., **601**), a representation (e.g., **1006** in FIG. **10G**) of a fifth portion (e.g., **625** in FIG. **10G**) of the field-of-view (e.g., **620**) of the one or more cameras that includes a view of the first participant (e.g., **622-1** in FIG. **10G**) in which the first participant is larger than when the first participant is displayed along with the second participant (e.g., **622-1** in FIG. **10F**). Displaying a representation of a fifth portion of the field-of-view of the one or more cameras that includes a view of the first participant in which the first participant is larger than when the first participant is displayed along with the second participant optimizes use of the display to present more relevant information to the user and conserves computational resources by using fewer pixels to display information that is not relevant to the user. Optimizing use of the

display and conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, when only a single participant of the live video communication session is detected in the field-of-view of the one or more cameras, the computer system displays a zoomed in view of the single participant.

[0402] In some embodiments, while displaying the representation of the first portion of the field-of-view (e.g., **1006-1** in FIG. **10E**) and the representation of the second portion of the field-of-view (e.g., **1006-2** in FIG. **10E**) without displaying the representation of the third portion (e.g., a portion of **1027** in FIG. **10E** that is in between, and does not include, portions **625-1** and **625-2**) of the field-of-view of the one or more cameras that is in between the first portion (e.g., **625-1**) of the field-of-view (e.g., **620**) and the second portion (e.g., **625-2**) of the field-of-view, the computer system (e.g., **600**) detects (e.g., based on the image data for the live communication session) a change in the amount of separation between the first participant and the second participant (e.g., Jane **622** moves next to Jack **628** as depicted in FIG. **10F**) (e.g., while displaying the split field-of-view, the first participant and the second participant move closer to each other). In accordance with a determination that the amount of separation between the first participant (e.g., **622**) and the second participant (e.g., **628**) does not meet the separation criteria (e.g., and in response to the change in the amount of separation between the first participant and the second participant), the computer system displays, via the display generation component, a representation (e.g., **1006** in FIG. **10F**) of a fifth portion (e.g., **625** in FIG. **10F**) of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant (e.g., when the first and second participants are no longer separated by the predetermined amount, the computer system merges the split field-of-view together to display the continuous field-of-view). Displaying the representation of a fifth portion of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant in accordance with a determination that the amount of separation between the first and second participants does not meet the separation criteria enhances the live video communication session experience by automatically adjusting the representation of the field-of-view of the one or more cameras to include representations of both the first and second participants when they are positioned close to each other. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0403] In some embodiments, while displaying the representation of the first portion of the field-of-view (e.g., **1006-1** in FIG. **10C**) and the representation of the second portion of the field-of-view (e.g., **1006-2** in FIG. **10C**) without displaying the third portion (e.g., **1027** in FIG. **10C**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) that is in between the first portion (e.g., **625-1**) of the field-of-view and the second portion (e.g., **625-2**) of the field-of-view, the computer system (e.g., **600**) detects a fourth participant (e.g., **1031**) (e.g., a participant other than the first or second participant) positioned between the first participant and the second participant and (optionally) positioned less than a second threshold distance (e.g., 3 feet, 2 feet, 1 foot) from the first participant and less than the second threshold distance from the second participant in the image data for the live video communication session (e.g., while displaying the split field-of-view, detecting an additional participant positioned between, and less than a threshold distance from, the

first participant and the second participant). In some embodiments, the fourth participant is detected in the third portion of the field-of-view of the one or more cameras that is in between the first portion of the field-of-view and the second portion of the field-of-view. In response to detecting the fourth participant positioned between the first participant and the second participant and (optionally) positioned less than the second threshold distance from the first participant and less than the second threshold distance from the second participant in the image data for the live video communication session, the computer system displays, via the display generation component (e.g., **601**), a representation (e.g., **1006** in FIG. **10D**) of a sixth portion (e.g., **625** in FIG. **10D**) of the field-of-view of the one or more cameras that includes the first participant (e.g., **622**) and the second participant (e.g., **628**) while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant and includes the fourth participant (e.g., **1031**) (e.g., when the fourth participant is detected between the first and second participants (and less than the threshold distance from the first and second participants), the computer system merges the split field-of-view together to display the continuous field-of-view that includes the first, second, and fourth participants). Displaying a representation of a sixth portion of the field-of-view of the one or more cameras that includes the first participant and the second participant while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first and second participants and includes the fourth participant in response to detecting the fourth participant positioned between, and less than the second threshold distance from, the first and second participants enhances the live video communication session experience by automatically adjusting the representation of the field-of-view of the one or more cameras to include the portion of the field-of-view of the one or more cameras that includes the fourth participant when the fourth participant is positioned less than the threshold distance from both the first and second participants. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0404] In some embodiments, while displaying the representation (e.g., **1006** in FIG. **10B**) of the fourth portion (e.g., **625** in FIG. **10B**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., **602**) that includes the first participant (e.g., **622**) and the second participant (e.g., **628**) while maintaining display of the portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant, the computer system (e.g., **600**) detects (e.g., based on the image data for the live video communication session) a change in the amount of separation between the first participant and the second participant (e.g., while displaying the continuous field-of-view, the first participant and the second participant move away from each other). In accordance with a determination (e.g., based on the image data for the live video communication session) that the amount of separation between the first participant and the second participant meets the separation criteria (e.g., and in response to detecting the change in the amount of separation between the first participant and the second participant), the computer system displays, via the display generation component (e.g., **601**), a representation (e.g., **1006-1** in FIG. **10C**) of a seventh portion (e.g., **625-1** in FIG. **10C**) of the field-of-view and a representation (e.g., **1006-2** in FIG. **10C**) of an eighth portion (e.g., **625-2** in FIG. **10C**) of the field-of-view without displaying a ninth portion (e.g., **1027** in FIG. **10C**) of the field-of-view of the one or more cameras that is in between the seventh portion of the field-of-view and the eighth portion of the field-of-view (e.g., when the first and second participants become separated by the predetermined amount, the computer system switches from the continuous field-of-view to the split field-of-view). Displaying a representation of a seventh portion of the field-of-view and a representation of an eighth portion of the field-of-view without displaying a ninth portion of the field-of-view of the one

or more cameras that is in between the seventh and eighth portions of the field-of-view in accordance with a determination that the changed amount of separation between the first and second participants meets the separation criteria enhances the live video communication session experience by automatically adjusting the representation of the field-of-view of the one or more cameras to a split field-of-view when the first and second participants move away from each other by at least a threshold amount, optimizes use of the display to present more relevant information to the user, and conserves computational resources by using fewer pixels to display information that is not relevant to the user. Performing an operation when a set of conditions has been met without requiring further user input, optimizing use of the display, and conserving computations resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0405] In some embodiments, while displaying the representation of the fourth portion of the field-of-view of the one or more cameras (e.g., **1006** in FIG. **10D**) that includes the first participant (e.g., **622**) and the second participant (e.g., **628**) while maintaining display of a portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant and includes a fifth participant (e.g., **1031**) that is detected, based on the image data for the live video communication session, in between the first participant and the second participant and (optionally) positioned less than a third threshold distance from the first participant and less than the third threshold distance from the second participant (e.g., while displaying the continuous field-of-view when there is an additional participant positioned between, and less than a threshold distance from, the first participant and the second participant), the computer system (e.g., **600**) detects (e.g., based on the image data for the live video communication session) a change in position of the fifth participant (e.g., Jake **1031** leaves scene **615** as depicted in FIG. **10E**). In accordance with a determination (e.g., based on the change in the image data for the live video communication session) that the fifth participant is no longer detected in between the first participant and the second participant and (optionally) positioned less than the third threshold distance from the first participant and less than the third threshold distance from the second participant (e.g., and in response to detecting the change in position of the fifth participant), the computer system displays, via the display generation component (e.g., **601**), the representation of the first portion of the field-of-view (e.g., **1006-1** in FIG. **10E**) (e.g., that includes the first participant) and the representation of the second portion of the field-of-view (e.g., **1006-2** in FIG. **10E**) (e.g., that includes the second participant) without displaying the portion of the field-of-view of the one or more cameras that is in between the first participant and the second participant (e.g., when the fifth participant is no longer detected between the first and second participants, the computer system switches from the continuous field-of-view to the split field-of-view). Displaying the representation of the first portion of the field-of-view and the representation of the second portion of the field-of-view without displaying the portion of the field-of-view of the one or more cameras that is in between the first and second participants in accordance with a determination that the fifth participant is no longer detected in between and less than the third threshold distance from the first and second participants enhances the live video communication session experience by automatically adjusting the representation of the field-of-view of the one or more cameras to a split field-of-view when a participant that was previously in between the first and second participants is no longer positioned between the first and second participants, optimizes use of the display to present more relevant information to the user, and conserves computational resources by using fewer pixels to display information that is not relevant to the user. Performing an operation when a set of conditions has been met without requiring further user input, optimizing use of the display, and conserving computational resources enhances the operability of the computer system and

makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0406] In some embodiments, while displaying the live video communication interface (e.g., **1004**) for the live video communication session: in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that an amount of separation between the first participant (e.g., **622**), the second participant (e.g., **628**), and a sixth participant (e.g., **1031**) meets the separation criteria (e.g., the first, second, and sixth participants are each spaced apart from each other by at least a threshold amount (e.g., distance and/or angle) as depicted in FIG. **10H**), the computer system (e.g., **600**) concurrently displays, via the display generation component (e.g., **601**), the following items (e.g., as depicted in FIG. **10H**). The computer system displays a representation (e.g., **622-1**) of a tenth portion (e.g., **625-2**) of the field-of-view of the one or more cameras (e.g., that includes the first participant (e.g., and excludes the second participant and the sixth participant)) at a third region (e.g., **1006-2** in FIG. **10H**) of the live video communication interface (e.g., **1004**). The computer system also displays a representation (e.g., **628-1**) of an eleventh portion (e.g., **625-3**) of the field-of-view of the one or more cameras (e.g., that includes the second participant (e.g., and excludes the first participant and the sixth participant)) at a fourth region (e.g., **1006-3** in FIG. **10H**) of the live video communication interface that is distinct from the third region. The computer system also displays a representation (e.g., **1031-1**) of a twelfth portion (e.g., **625-1**) of the field-of-view of the one or more cameras (e.g., that includes the sixth participant (e.g., and excludes the first participant and the second participant)) at a fifth region (e.g., **1006-1** in FIG. **10H**) of the live video communication interface that is distinct from the third region and the fourth region, wherein the representation of the tenth portion of the field-of-view of the one or more cameras, the representation of the eleventh portion of the field-of-view of the one or more cameras, and the representation of the twelfth portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a thirteenth portion (e.g., a portion of door **618** located between, and not included in, portions **625-1** and **625-2**) of the field-of-view (e.g., **620**) of the one or more cameras that is in between at least two of the tenth, eleventh, and twelfth portions of the field-of-view of the one or more cameras (e.g., the live video communication interface has a split field-of-view that includes the tenth, eleventh, and twelfth portions of the field-of-view of the one or more cameras). Displaying the representation of the tenth portion of the field-of-view of the one or more cameras at a third region of the live video communication interface, displaying the representation of the eleventh portion of the field-of-view at a fourth region of the live video communication interface, and displaying the representation of the twelfth portion of the field-of-view of the one or more cameras at a fifth region of the live video communication interface, without displaying a representation of a thirteenth portion of the field-of-view of the one or more cameras that is in between at least two of the tenth, eleventh, and twelfth portions optimizes use of the display to present more relevant information to the user and to present the relevant information with a larger view than would otherwise be available, and conserves computational resources by using fewer pixels to display information that is not relevant to the user. Optimizing use of the display and conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0407] In some embodiments, in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that the amount of separation between the first participant (e.g., **622**), the second participant (e.g., **628**), and the

sixth participant (e.g., **1031**) does not meet the separation criteria (e.g., see FIG. **10D**), displaying, via the display generation component, a representation of a fourteenth portion (e.g., **625** in FIG. **10D**) of the field-of-view of the one or more cameras that includes the first participant (e.g., **622**), the second participant (e.g., **628**), and the sixth participant (e.g., **1031**) while maintaining display of a portion of the field-of-view of the one or more cameras that is in between at least two of the first participant, the second participant, and the sixth participant (e.g., the live video communication interface has a continuous field-of-view that includes the first, second, and sixth participants). In some embodiments, subsets (e.g., two or more) of the participants can be grouped together in a single field-of-view, and separate from other subsets of participants. For example, a representation of a portion of the field-of-view of the one or more cameras can include a representation of two subjects, and be displayed separate from a representation of another portion of the field-of-view of the one or more cameras that includes a representation of a different subject.

[0408] In some embodiments, while displaying the live video communication interface (e.g., **1004**) for the live video communication session: in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that an amount of separation between the first participant (e.g., **622**), the second participant (e.g., **628**), a seventh participant (e.g., **1031**), and an eighth participant (e.g., **1032**) meets the separation criteria (e.g., the first, second, seventh, and eighth participants are each spaced apart from each other by at least a threshold amount (e.g., distance and/or angle)), the computer system (e.g., **600**) concurrently displays, via the display generation component (e.g., **601**), the following items (e.g., as depicted in FIG. **10J**). The computer system displays a representation (e.g., **622-1**) of a fifteenth portion (e.g., **625-2**) of the field-of-view (e.g., **620**) of the one or more cameras (e.g., that includes the first participant (e.g., and excludes the second, seventh, and eighth participants)) at a sixth region (e.g., **1006-2** in FIG. **10J**) of the live video communication interface. The computer system displays a representation (e.g., **628-1**) of a sixteenth portion (e.g., **625-4**) of the field-of-view of the one or more cameras (e.g., that includes the second participant (e.g., and excludes the first, seventh, and eighth participants)) at a seventh region (e.g., **1006-4** in FIG. **10J**) of the live video communication interface that is distinct from the sixth region. The computer system displays a representation (e.g., **1031-1**) of a seventeenth portion (e.g., **625-1**) of the field-of-view of the one or more cameras (e.g., that includes the seventh participant (e.g., and excludes the first, second, and eighth participants)) at an eighth region (e.g., **1006-1** in FIG. **10J**) of the live video communication interface that is distinct from the sixth region and the seventh region. The computer system displays a representation (e.g., **1032-1**) of an eighteenth portion (e.g., **625-3**) of the field-of-view of the one or more cameras (e.g., that includes the eighth participant (e.g., and excludes the first, second, and seventh participants)) at a ninth region (e.g., **1006-3** in FIG. **10J**) of the live video communication interface that is distinct from the sixth region, the seventh region, and the eighth region, wherein the representation of the fifteenth portion of the field-of-view of the one or more cameras, the representation of the sixteenth portion of the field-of-view of the one or more cameras, the representation of the seventeenth portion of the field-of-view of the one or more cameras, and the representation of the eighteenth portion of the field-of-view of the one or more cameras are displayed without displaying a representation of a nineteenth portion (e.g., representation **618-1** of door **618** that is positioned between, but not included in, portion **625-1** and **625-2**) of the field-of-view of the one or more cameras that is in between at least two of the fifteenth, sixteenth, seventeenth, and eighteenth portions of the field-of-view of the one or more cameras (e.g., the live video communication interface has a split field-of-view that includes the fifteenth, sixteenth, seventeenth, and eighteenth portions of the field-of-view of the one or more cameras). Displaying the representation of the fifteenth portion of the field-of-view of the one or more cameras at a sixth region of the live video communication interface, displaying the representation of the sixteenth portion of the field-of-view at a seventh region of the live video communication interface, displaying the representation of the seventeenth portion of the field-of-view of the one or more

cameras at an eighth region of the live video communication interface, and displaying the representation of the eighteenth portion of the field-of-view of the one or more cameras at a ninth region of the live video communication interface, without displaying a representation of a nineteenth portion of the field-of-view of the one or more cameras that is in between at least two of the fifteenth, sixteenth, seventeenth, and eighteenth portions optimizes use of the display to present more relevant information to the user and to present the relevant information with a larger view than would otherwise be available, and conserves computational resources by using fewer pixels to display information that is not relevant to the user. Optimizing use of the display and conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0409] In some embodiments, in accordance with a determination, based on the image data for the live video communication session captured via the one or more cameras (e.g., **602**), that the amount of separation between the first participant (e.g., **622**), the second participant (e.g., **628**), the seventh participant (e.g., **1031**), and the eighth participant (e.g., **1032**) does not meet the separation criteria, displaying, via the display generation component, a representation of a twentieth portion of the field-of-view (e.g., **620**) of the one or more cameras that includes the first participant, the second participant, the seventh participant, and the eighth participant while maintaining display of a portion of the field-of-view of the one or more cameras that is in between at least two of the first participant, the second participant, the seventh participant, and the eighth participant (e.g., the live video communication interface has a continuous field-of-view that includes the first, second, seventh, and eighth participants). In some embodiments, subsets (e.g., two or more) of the participants can be grouped together in a single field-of-view (e.g., as depicted in **1006-3** in FIG. **10I**), and separate from other subsets of participants. For example, a representation of a portion of the field-of-view of the one or more cameras can include a representation of two subjects (e.g., **628-1** and **1032-1** in FIG. **10I**), and be displayed separate from a representation of another portion of the field-of-view of the one or more cameras (e.g., **1006-2** in FIG. **10I**) that includes a representation (e.g., **622-1**) of a different subject.

[0410] Note that details of the processes described above with respect to method **1100** (e.g., FIG. **11**) are also applicable in an analogous manner to the methods described above and below for methods **700**, **900**, **1300**, and **1400**. For example, method **700**, method **900**, method **1300**, and/or method **1400** optionally includes one or more of the characteristics of the various methods described above with reference to method **1100**. For brevity, these details are not repeated.

[0411] FIGS. **12A-12U** illustrate exemplary user interfaces for managing a live video communication session (e.g., a video conference), in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described herein, including the processes in FIGS. **13** and **14**.

[0412] FIGS. **12A-12R** illustrate device **600** displaying user interfaces on display **601** for managing a live video communication session, similar to that discussed above with respect to FIGS. **6A-6Q**, FIGS. **8A-8R**, and FIGS. **10A-10J**, including displaying various user interfaces for changing video and audio settings for device **600**. One or more of the embodiments discussed below with respect to FIGS. **12A-12U** can be combined with one or more of the embodiments discussed with respect to FIGS. **6A-6Q**, FIGS. **8A-8R**, and FIGS. **10A-10J**. For example, the background blur feature discussed with respect to FIGS. **12A-12U** (and the corresponding background blur affordance **611**) can be incorporated in one or more of the interfaces depicted in FIGS. **6A-6Q**, FIGS. **8A-8R**, and FIGS. **10A-10J**.

[0413] FIG. **12A** depicts an embodiment in which device **600** (also referred to herein as Jane's tablet) displays UI **1201** for an incoming video conference call (similar to those depicted in FIGS.

6A and 8K discussed above). UI **1201** includes framing mode affordance **610** and background blur affordance **611**. A background blur mode can be enabled or disabled in response to, for example, input **1202** on background blur affordance **611**, and the automatic framing mode can be enabled or disabled in response to, for example, input **1204** on framing mode affordance **610**. As discussed in greater detail below, when the background blur mode is enabled, device **600** blurs (or otherwise obstructs) a background portion of the video feed output for the video conference call without blurring the portion of the video feed that includes the participant.

[0414] In FIG. **12B**, device **600** displays video conference UI **1205** in response to detecting input **1206** on accept option **608-3**. Video conference UI **1205** is a user interface for an ongoing video conference between Jane, John, and Pam. Jane is depicted in camera preview **1208** (similar to camera previews **606** and **836**), which is a representation of the video feed captured using camera **602** and being transmitted from device **600** (Jane's tablet) to the other participants of the video conference (e.g., to John's tablet **600a**). John is depicted in video feed **1210-1**, which is the video feed transmitted from John's tablet **600a** to Jane's tablet and Pam's device for the video conference. Similarly, Pam is depicted in video feed **1210-2**, which is the video feed transmitted from Pam's device to John's and Jane's tablets.

[0415] Video conference UI **1205** also includes options menu **1211** (similar to options menu **1008**). Options menu **1211** includes background blur affordance **611**, mute option **1212**, framing mode affordance **610**, camera option **1213**, and end call option **1214**. Background blur affordance **611** is selectable to enable or disable the background blur mode for the video conference call. Mute option **1212** is selectable to mute or unmute audio detected by device **600** for the video conference call. Framing mode affordance **610** is selectable to enable or disable the automatic framing mode for the video conference call. Camera option **1213** is selectable to enable or disable camera **602** for the video conference call (e.g., disabling/enabling the video feed captured via camera **602**). End call option **1214** is selectable to terminate the video conference call.

[0416] Video conference UI **1205** includes effects affordance **1216** and camera flip affordance **1217** overlaying camera preview **1208**. Effects affordance **1216** is selectable to enable or disable the display of various visual effects with the video feed captured by device **600** such as, for example, virtual avatars, stickers, color filters, and the like. Camera flip affordance **1217** is selectable to change which camera is used for the video feed for the video conference call. For example, selecting camera flip affordance **1217** alternates between using camera **602** and a camera positioned on a different side (e.g., backside) of device **600**.

[0417] In the embodiment depicted in FIG. **12B**, the background blur and automatic framing modes are both disabled for device **600**. However, if the framing mode affordance **610** was in a selected state when input **1206** was detected on accept option **608-3**, the automatic framing mode would be enabled for Jane's tablet and framing mode affordance **610** would be displayed in menu options **1211** having a selected appearance (e.g., bolded). Similarly, if the background blur affordance **611** was in a selected state when input **1206** was detected, the background blur mode would be enabled for Jane's tablet and background blur affordance **611** would be displayed in menu options **1211** having a selected appearance.

[0418] FIG. **12B** also depicts John's tablet **600a** having video conference UI **1215** (similar to video conference UI **1205**). John is depicted in camera preview **1218** (similar to camera preview **1208**), which is a representation of the video feed captured using camera **602a** and being transmitted from John's tablet **600a** to the other participants of the video conference (e.g., Jane's tablet (device **600**)). Jane is depicted in video feed **1220-1**, which is the video feed transmitted from device **600** to John's tablet **600a** and Pam's device for the video conference. Similarly, Pam is depicted in video feed **1220-2**, which is the video feed transmitted from Pam's device to John's and Jane's tablets.

[0419] In FIG. **12B**, device **600** detects input **1222** (e.g., a drag gesture). In response to detecting input **1222**, device **600** displays control settings interface **1225**, as depicted in FIG. **12C**.

[0420] In FIG. **12C**, device **600** displays control settings interface **1225** over video conference UI

1205, which is blurred in the background behind control settings interface **1225**. Control settings interface **1225** includes information and controls for changing various settings of device **600**. [0421] As shown in FIG. **12C**, control settings interface **1225** includes identifier **1227**, which provides an indication (e.g., text and/or icon) of an application operating on device **600** that is currently accessing, or has recently accessed (e.g., accessed less than a threshold amount of time ago (e.g., two minutes ago, five minutes ago, or ten minutes ago)), the camera and/or microphone of device **600**. For example, because camera **602** and a microphone of device **600** are being used by device **600** for the video conference call, the video conference app is listed by identifier **1227**. In some embodiments, control settings interface **1225** includes a listing of applications that recently used or accessed the camera and/or microphone of device **600**, even if the application is not currently in use or accessing the camera or microphone.

[0422] Control settings interface **1225** also includes video effects control **1231** and microphone mode control **1232**. Video effects control **1231** is selectable to display a listing of video settings that can be applied to applications that access (e.g., operate, control, and/or use images captured by) a camera of device **600** (e.g., camera **602**). Video effects control **1231** includes indication **1231-1** of a currently selected video effects setting, which, in FIG. **12C**, is the default video effects setting. Microphone mode control **1232** is selectable to display a listing of audio settings that can be applied to applications that access the microphone of device **600**. Microphone mode control **1232** includes indication **1232-1** of a currently selected microphone mode setting, which, in FIG. **12C**, is the default microphone mode setting.

[0423] In some embodiments, video effects control **1231** is displayed if the camera has been recently used, even if the camera is currently not in use. If the camera has not been recently used, video effects control **1231** is not displayed in control settings interface **1225**. In some embodiments, video effects control **1231** is displayed without microphone mode control **1232** (e.g., microphone mode control **1232** is hidden or not displayed if the microphone is not in use or has not been recently used). In some embodiments, microphone mode control **1232** is displayed if the microphone has been recently used, even if the microphone is currently not in use. If the microphone has not been recently used, microphone mode control **1232** is not displayed in control settings interface **1225**. In some embodiments, microphone mode control **1232** is displayed without video effects control **1231** (e.g., video effects control **1231** is hidden or not displayed if the camera is not in use or has not been recently used).

[0424] As depicted in FIG. **12C**, device **600** displays identifier **1227**, video effects control **1231**, and microphone mode control **1232** in region **1225-1** of control settings interface **1225**. Region **1225-1** is a region of the control settings interface that is not user-configurable. Conversely, region **1225-2** is a region of the control settings interface that is user-configurable. As shown in FIG. **12C**, when identifier **1227**, video effects control **1231**, or microphone mode control **1232** is displayed in control settings interface **1225**, the controls and information in region **1225-2** are shifted down from a default position in the control settings interface (e.g., the default position shown in FIG. **12I**).

[0425] In FIG. **12C**, Jane has moved her face partially outside the field-of-view of camera **602** and, therefore, is shown in video feed **1220-1** of John's tablet **600a** with her face partly out of frame.

[0426] In FIG. **12D**, device **600** displays expanded video effects controls **1236** in response to input **1234** on video effects control **1231** in FIG. **12C**. Expanded video effects controls **1236** provides an expanded listing of the video effect options that are selectable for the application(s) accessing the camera of device **600**. Expanded video effects controls **1236** also includes settings option **1237**, which is selectable to access an audio/video settings menu (e.g., see FIG. **12S** or **12T**). In some embodiments, control settings interface **1225** is blurred or otherwise obscured in the background behind expanded video effects controls **1236**.

[0427] The video effects options include default option **1236-1**, framing mode option **1236-2**, and background blur option **1236-3**. Default option **1236-1** corresponds to a default video setting for

the camera in which the automatic framing mode and the background blur mode are both disabled. In some embodiments, selecting default option **1236-1** disables the automatic framing mode and the background blur mode. Framing mode option **1236-2** corresponds to the automatic framing mode for the camera. Selecting framing mode option **1236-2** enables the automatic framing mode, similar to selecting framing mode affordance **610**. Background blur option **1236-3** corresponds to the background blur mode for the camera. Selecting background blur option **1236-3** enables the background blur mode, similar to selecting background blur affordance **611**. When a video effects option is selected, the corresponding video effects settings are applied to applications (e.g., video conference application) that are currently using, or recently used, the camera of device **600**.

[0428] In the embodiment depicted in FIG. **12D**, indication **1231-1** shows that default option **1236-1** is currently selected; however, this selection can also be indicated in different ways such as, e.g., by displaying a checkmark, highlighting, or other visual indication of which setting(s) is currently selected or enabled. In some embodiments, one or more of the video effects options are disabled if they are not supported by the currently active camera. For example, if camera **602** does not support the automatic framing mode, framing mode option **1236-2** can be omitted or shown struck through, greyed out, or otherwise not available for selection. In some embodiments, more than one video effects option can be concurrently enabled. For example, framing mode option **1236-2** can be enabled concurrently with background blur option **1236-3**.

[0429] In FIG. **12D**, device **600** detects input **1238** on framing mode option **1236-2** and input **1240** on microphone mode control **1232**. In response to detecting input **1238** on framing mode option **1236-2**, device **600** enables the automatic framing mode. When the automatic framing mode is enabled, device **600** automatically reframes Jane's face in the outgoing video feed of device **600** in a manner similar to that discussed above with respect to FIGS. **6D** and **6E**. The reframing of Jane's face is depicted in video feed **1220-1** of John's tablet **600a** in FIG. **12E**. Additionally, device **600** updates indication **1231-1** to show framing mode is selected and bolds framing mode affordance **610**, as shown in FIG. **12E**.

[0430] In FIG. **12E**, device **600** displays expanded microphone mode controls **1242** in response to input **1240** on microphone mode control **1232** in FIG. **12D**. Expanded microphone mode controls **1242** provides an expanded listing of the audio options that are selectable for the application(s) accessing the microphone of device **600**. Expanded microphone mode controls **1242** also includes settings option **1243** (similar to settings option **1237**), which is selectable to access an audio/video settings menu (e.g., see FIG. **12S** or **12U**). In some embodiments, control settings interface **1225** is blurred or otherwise obscured in the background behind expanded microphone mode controls **1242**.

[0431] The microphone mode options include default option **1242-1**, voice isolation option **1242-2**, and music option **1242-3**. Default option **1242-1** corresponds to a default audio setting for the microphone in which the voice isolation setting and the music setting are both disabled. In some embodiments, selecting default option **1242-1** disables the voice isolation setting and the music setting. In some embodiments, when the default setting is enabled, device **600** filters out background audio detected using the microphone. Voice isolation option **1242-2** corresponds to a setting in which device **600** isolates audio that is identified as being a voice, such as a voice of a participant within frame of the camera (e.g., camera **602**). For example, audio from Jane is isolated from background audio and/or voices of people who are not identified as being within the frame of camera preview **1208**. Music option **1242-3** corresponds to a setting in which device **600** does not filter out audio and, in some embodiments, amplifies the audio detected via the microphone. When a microphone mode option is selected, the corresponding audio settings are applied to applications (e.g., a video conference application) that are currently using, or recently used, the microphone of device **600**.

[0432] In the embodiment depicted in FIG. **12E**, indication **1232-1** shows that default option **1242-1** is currently selected; however, this selection can also be indicated in different ways such as, e.g.,

by displaying a checkmark, highlighting, or other visual indication of which setting is currently selected or enabled. In some embodiments, one or more of the microphone mode options are disabled if they are not supported by the currently active microphone. For example, if the microphone does not support the voice isolation setting, voice isolation option **1242-2** can be omitted or shown struck through, greyed out, or otherwise not available for selection. In some embodiments, more than one microphone mode option can be concurrently enabled.

[0433] In FIG. **12E**, device **600** detects input **1244** on music option **1242-3** and, in response, enables the music setting, as indicated by indication **1232-1** of microphone mode control **1232** in FIG. **12F**.

[0434] In FIG. **12F**, device **600** detects input **1246** and, in response, ceases displaying control settings interface **1225**, as depicted in FIG. **12G**.

[0435] In FIG. **12G**, device **600** displays video conference UI **1205** while the automatic framing mode and the music setting are enabled. Device **600** detects input **1248** on mute option **1212**, input **1250** on camera option **1213**, and drag gesture input **1252**. In response to the inputs in FIG. **12G**, device **600** mutes and disables the respective audio and video transmitted for the video conference, and displays control settings interface **1225**.

[0436] In FIG. **12H**, device **600** displays control settings interface **1225**. Video effects control **1231** includes an indication **1231-2** of the disabled state of camera **602**, and microphone mode control **1232** includes an indication **1232-2** of the disabled state of the microphone. In the embodiment shown in FIG. **12H**, indication **1231-2** indicates that the camera (e.g., camera **602**) of device **600** is turned off. Accordingly, the video conference application (or any other application that uses the camera) is not able to access the camera. Similarly, indication **1232-2** indicates that the microphone of device **600** is turned off and currently is not accessible to the video conference application or any other application that uses the microphone. Accordingly, video conference interface **1215** of John's tablet **600a** displays no video data in video feed **1220-1** and displays mute glyph **1254** and camera off glyph **1256** to denote the muted audio and disabled video feed of Jane's tablet.

[0437] In some embodiments, after the camera and microphone have not been accessed by an application for a specific period of time (e.g., three minutes, five minutes, ten minutes), device **600** does not display identifier **1227**, video effects control **1231**, and/or microphone mode control **1232** in control settings interface **1225**. For example, FIG. **12I** depicts an embodiment in which the video conference has been over for more than five minutes and no other application has accessed the camera or microphone during the five minute period. In this embodiment, device **600** displays control settings interface **1225** over home screen interface **1255**, and identifier **1227**, video effects control **1231**, and microphone mode control **1232** are not displayed.

[0438] Referring now to FIG. **12J**, device **600** displays video conference UI **1205** and detects input **1258** on camera preview **1208**. In some embodiments, input **1258** is a tap gesture. In some embodiments, input **1258** is a de-pinch gesture.

[0439] In response to detecting input **1258**, device **600** enlarges the camera preview and displays different controls, as depicted in FIG. **12K**. For example, device **600** displays background blur affordance **611**, zoom affordance **1260** (similar to zoom options **850-2** and **850-3**), framing mode affordance **610**, and camera flip affordance **1217** overlaid on camera preview **1208**. Additionally, device **600** replaces effects affordance **1216** with effects menu **1262**, which is displayed adjacent (e.g., below) camera preview **1208**. Effects menu **1262** includes various effects options that can be selected to enable (or disable) a type of visual effect that is applied to the video feed of device **600**. For example, effects option **1262-1** is selectable to enable or disable the display of virtual effects such as virtual avatars and/or virtual stickers in the camera feed.

[0440] In FIG. **12K**, device **600** detects input **1264** on background blur affordance **611** and, in response, enables the background blur mode, as depicted in FIG. **12L**.

[0441] In FIG. **12L**, device **600** temporarily displays banner **1265** to inform the user (e.g., Jane) that the background blur mode was enabled on device **600**. In some embodiments, a similar banner

is displayed when the automatic framing mode is enabled. When the background blur mode is enabled, device **600** applies a visual effect (e.g., a blurring effect) to a background portion of the video feed for the video conference, without applying the visual effect to a portion of the video feed that includes the participant of the video conference. For example, in FIG. **12L**, the blurred background effect is depicted in camera preview **1208** of device **600** and in video feed **1220-1** of John's tablet **600a**. In the camera preview of device **600**, background portion **1208-1** has a blurred effect (indicated by hatching), and portion **1208-2**, which includes a representation of Jane, does not have a blurred effect (indicated by the absence of hatching). Similarly, in Jane's video feed on John's tablet **600a**, background portion **1220-1a** has the blurred effect (indicated by hatching), and portion **1220-1b**, which includes a representation of Jane, does not have the blurred effect (indicated by the absence of hatching).

[0442] In some embodiments, the background blur mode is dynamic. For example, as Jane moves within the field-of-view of camera **602**, device **600** updates the video feed in real time such that Jane remains displayed without the blurring effect, and the background portion (or any portion of the camera frame that does not include a portion of Jane) remains blurred. In FIG. **12M**, Jane has moved within the field-of-view of camera **602**, yet camera preview **1208** and video feed **1220-1** continue to show the background portion blurred while Jane remains unblurred.

[0443] In FIG. **12M**, device **600** detects input **1268** on framing mode affordance **610** and, in response, enables the automatic framing mode concurrently with the background blur mode. As such, device **600** automatically reframes the position of Jane's face within the video feed while continuing to blur the background, as illustrated in camera preview **1208** and video feed **1220-1**. In some embodiments, when the automatic framing mode (and, in some embodiments, the background blur mode) is enabled, device **600** disables various visual effect options. For example, in FIG. **12N**, device **600** displays effects option **1262-1** having a greyed out appearance indicating that device **600** has disabled the display of the virtual effects associated with effects option **1262-1** (e.g., virtual avatars and/or virtual stickers) while the automatic framing mode is enabled.

[0444] The various video effect and microphone mode settings can be applied to different applications operating on device **600**. For example, FIGS. **12O** and **12P** depict an embodiment in which control settings interface **1225** displays video effects control **1231** and microphone mode control **1232** while the camera and/or microphone is being accessed (or has been recently accessed) by multiple different applications (e.g., the video conference application and a messages application, as indicated by identifications **1227-1** and **1227-2**, respectively). Control settings interface **1225** is displayed over messages application interface **1270** and includes video effects control **1231** and microphone mode control **1232**. Video effects control **1231** includes indication **1231-1** indicating that the video effects settings are being applied to multiple applications. Similarly, microphone mode control **1232** includes indication **1232-1** indicating that the audio settings are being applied to multiple applications.

[0445] FIG. **12P** depicts expanded video effects controls **1236**, which are displayed in response to input **1272** in FIG. **12O**, and expanded microphone mode controls **1242**, which are displayed in response to input **1274** in FIG. **12O**. In some embodiments, the expanded video effects controls and the expanded microphone mode controls are displayed sequentially (in response to respective inputs **1272** and **1274**), and in some embodiments, they are displayed concurrently as shown in FIG. **12P**.

[0446] Expanded video effects controls **1236** includes first region **1276-1** that includes the video effects options (similar to video effects options **1236-1** to **1236-3**) for the video conference application and second region **1276-2** that includes the video effects options for the messages application. Similarly, expanded microphone mode controls **1242** includes first region **1278-1** that includes the microphone mode options (similar to microphone mode options **1242-1** to **1242-3**) for the video conference application and second region **1278-2** that includes the microphone mode options for the messages application.

[0447] In some embodiments, the various video effect and microphone mode settings can be applied to applications operating on a different device such as, for example, laptop **1200**. In some embodiments, laptop **1200** includes one or more features of devices **100**, **300**, **500**, or **600**. For example, FIGS. **12Q** and **12R** depict an embodiment in which laptop **1200** displays, on display **1200-1**, control settings interface **1280** (similar to control settings interface **1225**) having video effects control **1281** (similar to video effects control **1231**) and microphone mode control **1282** (similar to microphone mode control **1232**) while camera **1200-2** and/or microphone of laptop **1200** is being accessed (or has been recently accessed) by multiple different applications (e.g., a movies application and a voice recorder application as indicated by identifications **1284-1** and **1284-2**, respectively). Control settings interface **1280** is displayed partially over voice recorder application window **1285** and includes video effects control **1281** and microphone mode control **1282**. Video effects control **1281** includes indication **1281-1** indicating that the video effects settings are being applied to multiple applications operating at laptop **1200**. Similarly, microphone mode control **1282** includes indication **1282-1** indicating that the audio settings are being applied to multiple applications operating at laptop **1200**.

[0448] In FIG. **12Q**, control settings interface **1280** includes expanded video effects controls **1286**, which are displayed in response to an input (e.g., a mouse click) on video effects control **1281**. Expanded video effects controls **1286** are similar to the expanded video effects controls **1236** in FIG. **12P**. In FIG. **12R**, control settings interface **1280** includes expanded microphone mode controls **1288**, which are displayed in response to an input (e.g., a mouse click) on microphone mode control **1282**. Expanded microphone mode controls **1288** are similar to the expanded microphone mode controls **1242** in FIG. **12P**.

[0449] FIGS. **12S-12T** depict example interfaces of a settings user interface on device **600**. In some embodiments, the settings interface is displayed in response to an input on settings option **1237** or settings option **1243**. For example, in response to input **1290** on settings option **1237** in FIG. **12D**, device **600** displays audio/video settings interface **1291** in FIG. **12S** or video effects settings interface **1292** in FIG. **12T**. In some embodiments, in response to an input on settings option **1243** in FIG. **12E**, device **600** displays audio/video settings interface **1291** in FIG. **12S** or microphone mode settings interface **1293** in FIG. **12U**. In some embodiments, the settings depicted in FIGS. **12S-12T** can be accessed to control the video effects and microphone mode settings even when the camera and/or microphone of device **600** is not in use or has not been recently used.

[0450] FIG. **12S** depicts audio/video settings interface **1291**, which includes video effects settings option **1291-1** and microphone mode settings option **1291-2**.

[0451] FIG. **12T** depicts video effects settings interface **1292**, which, in some embodiments, is displayed in response to detecting input **1294** on video effects settings option **1291-1**. Video effects settings interface **1292** includes background blur settings **1292-1**, which include toggle switches (e.g., **1292-1a**) for globally enabling or disabling the background blur mode (e.g., similar to selecting background blur affordance **611**) and for selectively enabling or disabling the background blur mode feature for specific applications. Video effects settings interface **1292** also includes framing mode settings **1292-2**, which include toggle switches (e.g., **1292-2a**) for globally enabling or disabling the automatic framing mode (e.g., similar to selecting framing mode affordance **610**) and for selectively enabling or disabling the automatic framing mode feature for specific applications.

[0452] FIG. **12U** depicts microphone mode settings interface **1293**, which, in some embodiments, is displayed in response to detecting input **1295** on microphone mode settings option **1291-2**. Microphone mode settings interface **1293** includes voice isolation settings **1293-1**, which include toggle switches (e.g., **1293-1a**) for globally enabling or disabling the voice isolation mode and for selectively enabling or disabling the voice isolation mode feature for specific applications. Microphone mode settings interface **1293** also includes music mode settings **1293-2**, which include toggle switches (e.g., **1293-2a**) for globally enabling or disabling the music mode feature and for

selectively enabling or disabling the music mode feature for specific applications.

[0453] In some embodiments, device **600** can enable or disable a dynamic video quality mode in which portions of the video feed captured from device **600** for the video conference are compressed by different amounts, which can result in the video feed received from device **600** having different video qualities for different portions of the video feed. For example, device **600** compresses portions of the video feed that do not include a detected face and does not compress (or compresses by a lesser amount) portions of the video feed that include a detected face. In some embodiments, the degree of compression is inversely related to video quality. As a result, the video feed that is transmitted for the video conference is displayed at the recipient device having an increased video quality for the portions of the video feed that include a detected face and having a reduced video quality for the portions of the video feed that do not include a detected face.

[0454] The dynamic video quality mode can be enabled for device **600** and/or device **600a**. For example, referring to the embodiments discussed with respect to FIGS. **12A-12U**, when the dynamic video quality feature is enabled, device **600** transmits the video feed from Jane's tablet to John's tablet **600a** such that video feed **1220-1** has increased video quality for a portion that includes Jane's face (e.g., portion **1220-1b**), and has reduced video quality for portions that do not include Jane's face (e.g., portion **1220-1a**). As another example, and with reference to the embodiments discussed with respect to FIGS. **10H-10J**, when the dynamic video quality feature is enabled for John's device **600a**, device **600a** transmits the video feed from John's device **600a** to device **600** such that video feed **1023** has increased video quality for a portion that includes John's face (e.g., a foreground portion of the video feed), and has reduced video quality for portions that do not include John's face (e.g., a background portion of the video feed).

[0455] In some embodiments, when the dynamic video quality mode is enabled, device **600** (or device **600a**) automatically adjusts the amounts by which the various portions of the video feed are compressed based on a change (e.g., increase or decrease) in the bandwidth available for transmitting the video feed for the video conference. As a result, as the bandwidth increases or decreases, the video quality of the portions of the video feed that do not include the face (e.g., the background portion) varies (increases or decreases) more than the video quality of the face (which is held at a relatively constant, relatively high quality, even as the quality of the background portion increases/decreases).

[0456] In some embodiments, when the dynamic video quality mode is enabled and device **600** (or device **600a**) does not detect any faces within the field-of-view of the camera (e.g., camera **602**), device **600** (or device **600a**) compresses the video feed at a relatively uniform amount so that the quality of the video feed remains relatively uniform. In some embodiments, when the dynamic video quality mode is enabled and device **600** (or device **600a**) detects one or more faces, device **600** (or device **600a**) dynamically varies the compression of the different portions of the video feed as the face(s) moves such that the resulting display of the video feed (e.g., video feed **1220-1** at John's device **600a**) maintains a relatively high video quality of the face as it moves within the frame, while also displaying the other portions of the video feed at the lower video quality. In some embodiments, the lower compression amount (e.g., the higher video quality) is optionally applied to a single face (e.g., when either one face or multiple faces are detected within the field-of-view of camera **602**). In some embodiments, the lower compression amount (e.g., the higher video quality) is optionally applied to multiple faces concurrently.

[0457] In some embodiments, the dynamic video quality mode is implemented independently from the background blur feature and the automatic framing feature. In some embodiments, device **600** displays a separate affordance (e.g., similar to framing mode affordance **610** or background blur affordance **611**) that is selectable to enable or disable the dynamic video quality mode. In some embodiments, the dynamic video quality mode is integrated with the background blur feature or the automatic framing feature such that the dynamic video quality mode is enabled/disabled when the background blur mode or automatic framing mode is enabled/disabled.

[0458] FIG. 13 is a flow diagram illustrating a method for managing a live video communication session using a computer system in accordance with some embodiments. Method **1300** is performed at a computer system (e.g., **600**, **1200**) (e.g., a smartphone, a tablet, a wearable device (e.g., a smartwatch), a desktop or laptop computer) that is in communication with one or more output generation components (e.g., **601**, **1200-1**) (e.g., a display controller, a touch-sensitive display system, a speaker, a bone conduction audio output device, a tactile output generator, a projector, and/or a holographic display) and one or more input devices (e.g., **601**) (e.g., a touch-sensitive surface, a keyboard, mouse, trackpad, one or more optical sensors for detecting gestures, one or more capacitive sensors for detecting hover inputs, and/or accelerometer/gyroscope/inertial measurement units). In some embodiments, the computer system is in communication with one or more media recording devices (e.g., a microphone, a camera (e.g., an infrared camera, a depth camera, a visible light camera)). Some operations in method **1300** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

[0459] As described below, method **1300** provides an intuitive way for managing a live video communication session. The method reduces the cognitive burden on a user for managing a live video communication session, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to manage a live video communication session faster and more efficiently conserves power and increases the time between battery charges.

[0460] The computer system (e.g., **600**) detects (**1302**), via the one or more input devices (e.g., **601**), a request (e.g., **1222**, **1252**) to display a system interface (e.g., **1225**, **1280**) (e.g., a control settings interface that includes selectable options for controlling various settings associated with the computer system).

[0461] In response to detecting the request to display the system interface (e.g., **1225**, **1280**), the computer system (e.g., **600**) displays (**1304**), via the one or more output generation components (e.g., **601**), the system interface that includes a plurality of concurrently displayed controls for controlling different system functions of the computer system (e.g., display brightness, media controls, system volume, do not disturb, flashlight, wireless communication modes), including: in accordance with a determination (**1306**) that a media communication session (e.g., a video communication session, a video chat session, a phone call) (e.g., the microphone and/or camera are currently active (e.g., the microphone is recording audio data) (e.g., the camera is recording video data)) has been active within a predetermined amount of time, the plurality of concurrently displayed controls includes a set of one or more media communication controls (e.g., **1231**, **1232**) (e.g., a graphical user interface object that is selectable to control (e.g., select, change, enable, disable) one or more settings of the microphone; a graphical user interface object that is selectable to control (e.g., select, change, enable, disable) one or more settings of the camera), wherein the media communication controls provide access to media communication settings that determine how media (e.g., audio and/or image (e.g., video) data) is handled (e.g., controlled, modified, generated, produced, filtered, displayed, processed) by the computer system (e.g., while using one or more media recording devices) during media communication sessions (e.g., real-time communication sessions such as phone calls or video calls); and in accordance with a determination (**1308**) that a media communication session has not been active within the predetermined amount of time, the plurality of concurrently displayed controls (e.g., the controls in control settings interface **1225**) are displayed without the set of one or more media communication controls (e.g., controls **1231** and/or **1232** are not displayed in control settings interface **1225** of FIG. 12I).

[0462] While displaying (**1310**) the system interface (e.g., **1225**) having the set of one or more media communication controls (e.g., **1231**, **1232**), the computer system (e.g., **600**) detects, via the one or more input devices (e.g., **601**), a set of one or more inputs including an input (e.g., **1234**, **1240**, **1272**, **1274**) directed to the set of one or more media communication controls (e.g., a selection of one or more of the media controls).

[0463] In response to detecting (**1312**) the set of one or more inputs including the input (e.g., **1234**,

1240, 1272, 1274) directed to the set of one or more media communication controls (e.g., **1231, 1232**) when a respective media communication session has been active within the predetermined amount of time, the computer system (e.g., **600**) adjusts the media communication settings for the respective media communication session (e.g., adjusting a microphone setting for recording audio data; adjusting a camera setting for recording video data). Displaying the plurality of concurrently displayed controls with or without the media communication controls, depending on whether or not a media communication session has been active within a predetermined amount of time provides additional controls for accessing media communication settings without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0464] In some embodiments, the set of one or more media communication controls includes a camera control (e.g., **1231, 1236, 1281, 1286**) (e.g., a graphical user interface object that is selectable to control one or more settings of the camera) (e.g., without displaying a microphone control). Displaying the set of one or more media communication controls including a camera control provides feedback to a user of the computer system that the camera has been accessed during the media communication session and provides additional controls for accessing camera settings without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing improved feedback, providing additional control options without cluttering the user interface with additional displayed controls, and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0465] In some embodiments, the set of one or more media communication controls includes a microphone control (e.g., **1232, 1242, 1282, 1288**) (e.g., a graphical user interface object that is selectable to control one or more settings of the microphone) (e.g., without displaying a camera control). Displaying the set of one or more media communication controls including a microphone control provides feedback to a user of the computer system that the microphone has been accessed during the media communication session and provides additional controls for accessing microphone settings without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing improved feedback, providing additional control options without cluttering the user interface with additional displayed controls, and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0466] In some embodiments, displaying the set of one or more media communication controls includes concurrently displaying a camera control (e.g., **1231, 1236, 1281, 1286**) and a microphone control (e.g., **1232, 1242, 1282, 1288**) (e.g., the camera control and the microphone control are displayed concurrently in the system interface). Displaying the set of one or more media communication controls including concurrently displaying a camera control and a microphone control provides feedback to a user of the computer system that the camera and microphone have

been accessed during the media communication session and provides additional controls for accessing camera and microphone settings without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing improved feedback, providing additional control options without cluttering the user interface with additional displayed controls, and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0467] In some embodiments, the set of one or more media communication controls includes a camera control (e.g., **1231**, **1236**, **1281**, **1286**) (e.g., a graphical user interface object that is selectable to control one or more settings of the camera) that, when selected, changes a communication setting of a camera (e.g., **602**) (e.g., initiates a process for changing a communication setting (e.g., a visual effects mode) of the camera), and displaying the set of one or more media communication controls includes: in accordance with a determination that the camera is in an enabled state (e.g., is currently in use; is currently enabled) (e.g., and the media communication session has been active within the predetermined amount of time), displaying the camera control having a first visual appearance indicative of the enabled state of the camera (e.g., **1231** in FIG. 12C) (e.g., having a visual effect that indicates that the camera is enabled (e.g., the camera control is highlighted, bolded, emphasized, or is displayed having a default appearance)); and in accordance with a determination that the camera is in a disabled state (e.g., is not currently in use; is currently disabled or turned off) (e.g., and the media communication session has been active within the predetermined amount of time), displaying the camera control having a second visual appearance, different from the first visual appearance, indicative of the disabled state of the camera (e.g., **1231** in FIG. 12H) (e.g., the camera control is displayed having a visual effect (e.g., a strikethrough, blurring, darkening, shading, desaturating, or otherwise deemphasizing effect) that indicates the camera is disabled). Displaying the camera control having a visual appearance indicative of an enabled or disabled state of the camera provides feedback to a user of the computer system whether or not the camera is currently enabled for the media communication session. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0468] In some embodiments, the set of one or more media communication controls includes a microphone control (e.g., **1232**, **1242**, **1282**, **1288**) (e.g., a graphical user interface object that is selectable to control one or more settings of the microphone) that, when selected, changes a communication setting of a microphone (e.g., initiates a process for changing a communication setting (e.g., an audio processing mode or audio effects mode) of the microphone), and displaying the set of one or more media communication controls includes: in accordance with a determination that the microphone is in an enabled state (e.g., is currently in use; is currently enabled) (e.g., and the media communication session has been active within the predetermined amount of time), displaying the microphone control having a third visual appearance indicative of the enabled state of the microphone (e.g., **1232** in FIG. 12C) (e.g., having a visual effect that indicates that the microphone is enabled (e.g., the microphone control is highlighted, bolded, emphasized, or is displayed having a default appearance)); and in accordance with a determination that the microphone is in a disabled state (e.g., is not currently in use; is currently disabled or turned off) (e.g., and the media communication session has been active within the predetermined amount of time), displaying the microphone control having a fourth visual appearance, different from the third

visual appearance, indicative of the disabled state of the microphone (e.g., **1232** in FIG. **12H**) (e.g., the microphone control is displayed having a visual effect (e.g., a strikethrough, blurring, darkening, shading, desaturating, or otherwise deemphasizing effect) that indicates the microphone is disabled). Displaying the microphone control having a visual appearance indicative of an enabled or disabled state of the microphone provides feedback to a user of the computer system whether or not the microphone is currently enabled for the media communication session. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0469] In some embodiments, displaying the system interface (e.g., **1225**, **1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls includes: in accordance with a determination that one or more media communication settings (e.g., **1236-1**, **1236-2**, **1236-3**, **1242-1**, **1242-2**, **1242-3**) (e.g., camera settings (e.g., a framing mode setting, a background blur setting, a default setting) and/or microphone settings (e.g., a default setting, a voice isolation setting, a music setting)) are enabled (e.g., selected), displaying the set of one or more media communication controls (e.g., **1236**, **1242**) (e.g., a camera control and/or a microphone control) having a visual appearance indicative of an enabled state of the set of one or more media communication settings (e.g., displaying text, highlighting, a checkmark (e.g., in region **1276-1**, **1276-2**, **1278-1**, and/or **1278-2** of FIG. **12P**), bolding, an emphasizing visual effect, and/or other visual indication of the enabled media communication setting(s)); and in accordance with a determination that one or more media communication settings are disabled (e.g., not selected, not enabled), displaying the set of one or more media communication controls having a visual appearance indicative of a disabled state of the one or more media communication settings (e.g., displaying text, strikethrough, a deemphasizing visual effect, and/or other visual indication of the disabled media communication setting(s) (e.g., not displaying a checkmark or other visual indication as depicted in FIG. **12P**)). Displaying the set of one or more media communication controls having a visual appearance indicative of an enabled or disabled state of the one or more media communication settings provides feedback to a user of the computer system whether or not media communication settings are currently enabled for the media communication session. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the visual appearance indicative of the enabled or disabled state of the set of one or more media communication settings is independent of the visual appearance indicating whether or not the microphone and/or camera is enabled or disabled. For example, the camera control can be displayed with an indication of the enabled or disabled state of the media communication settings (e.g., showing a default, background blur, or framing mode is enabled or disabled) and an indication that the camera is disabled or enabled (e.g., showing the camera control in a shaded appearance when the camera is disabled and a non-shaded appearance when the camera is enabled). Similarly, the microphone control can be displayed with an indication of the enabled or disabled state of the media communication settings (e.g., showing a default, voice isolation, or music mode is enabled or disabled) and an indication that the microphone is disabled or enabled (e.g., showing the microphone control in a shaded appearance when the microphone is disabled and a non-shaded appearance when the microphone is enabled).

[0470] In some embodiments, displaying the system interface (e.g., **1225**, **1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls (e.g., **1231**, **1232**) includes: in accordance with a determination that a first media

communication setting (e.g., **1236-1**, **1236-2**, **1236-3**, **1242-1**, **1242-2**, **1242-3**) (e.g., a camera setting (e.g., a framing mode setting, a background blur setting, a default setting); a microphone setting (e.g., a default setting, a voice isolation setting, a music setting)) associated with a first media communication control (e.g., **1231**, **1232**) (e.g., a camera control, a microphone control) is enabled (e.g., selected), displaying the first media communication control having a first visual appearance (e.g., **1231-1** in FIG. 12C; **1232-1** in FIG. 12C) indicative of the enabled state of the first media communication setting (e.g., displaying text, highlighting, a checkmark, and/or other visual indication of the enabled media communication setting); and in accordance with a determination that a second media communication setting associated with the first media communication control, different from the first media communication setting, is enabled (e.g., the first media communication setting is not selected; a different media communication setting is selected), displaying the first media communication control having a second visual appearance (e.g., **1231-1** in FIG. 12E; **1232-1** in FIG. 12F), different from the first visual appearance, indicative of the enabled state of the second media communication setting (e.g., displaying text, highlighting, a checkmark, and/or other visual indication that the second set of media communication settings are enabled). Displaying the first media communication control having a first visual appearance indicative of an enabled state of the first or second media communication setting provides feedback to a user of the computer system of whether the first media communication setting is enabled or the second media communication setting is enabled. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0471] In some embodiments, the set of one or more media communication controls includes a first camera control option (e.g., **1236-3**) (e.g., a background blur option) that is selectable to initiate a process for changing an appearance (e.g., applying a visual effect that blurs, obscures, darkens, shades, or otherwise deemphasizes) of a representation of a background portion (e.g., **1208-1**, **1220-1a**) of a field-of-view of a camera (e.g., **602**) (e.g., a portion of the camera field-of-view that does not include a subject) (e.g., without applying the visual effect to a foreground portion (e.g., a portion that includes the subject) of the camera field-of-view) (e.g., as discussed with respect to FIGS. 12K-12N and FIG. 14). Displaying the set of one or more media communication controls including the first camera control option provides additional controls for quickly and easily changing an appearance of a representation of a background portion of a field-of-view of a camera without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Easily changing the appearance of (e.g., hiding) the background provides privacy benefits to the user of the computer system by preventing the display of the background (e.g., to other participants of the live video communication session and, in some embodiments, to the application hosting the live video communication session). Providing privacy benefits and additional control options without cluttering the user interface with additional displayed controls, and avoiding accidental inputs, enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system (e.g., **600**) detects a selection of the first camera control option (e.g., **1264**) and, in response, initiates a process for changing an appearance of a representation of a background portion of a field-of-view of a camera (e.g., **1208-1**, **1220-1a**), including applying a visual effect to the representation of the background portion of the field-of-view of the camera.

[0472] In some embodiments, the set of one or more media communication controls includes a second camera control option (e.g., **1236-2**) (e.g., a framing mode option) that is selectable to enable a mode (e.g., automatic framing mode) for automatically adjusting a representation of a field-of-view of one or more cameras (e.g., **1208**, **1220-1**) (e.g., during a live video communication session) based on a change in position of a subject detected in the field-of-view of the one or more cameras (e.g., **602**) (e.g., as discussed with respect to FIGS. 6A-6Q and FIGS. 7A-7B). Displaying the set of one or more media communication controls including the second camera control option provides additional controls for enabling a mode for automatically adjusting a representation of a field-of-view of one or more cameras based on a change in position of a subject detected in the field-of-view without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the framing mode option is selectable to enable/disable a mode for: 1) tracking (e.g., during a live video communication session) a position and/or location of one or more subjects detected within a field-of-view of the one or more cameras, and 2) automatically adjusting a displayed view of the subject(s) (e.g., during the live video communication session) based on the tracking of the subject. In some embodiments, the computer system (e.g., **600**) detects a selection of the second camera control option and, in response, enables (or disables) the mode for automatically adjusting the representation of the field-of-view of the one or more cameras based on a change in position of a subject detected in the field-of-view of the one or more cameras.

[0473] In some embodiments, the second camera control option (e.g., **1236-2**) is disabled (e.g., not displayed; displayed having a visual appearance indicative of the disabled state (e.g., greyed out, struck through, or otherwise visually deemphasized)) when the one or more cameras (e.g., **602**) are not compatible with the mode for automatically adjusting a representation of a field-of-view of the one or more cameras (e.g., the camera is not a wide angle camera). Disabling the second camera control option when the one or more cameras are not compatible with the mode for automatically adjusting a representation of a field-of-view of the one or more cameras provides feedback to a user of the computer system that the mode is not available and reduces inputs at the computer system by informing the user that the second camera control option is not selectable. Providing improved feedback and reducing inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0474] In some embodiments, the set of one or more media communication controls includes a first microphone control option (e.g., **1242-2**) (e.g., a voice isolation mode option) that is selectable to enable a voice isolation mode for a microphone (e.g., a mode for isolating audio (e.g., a voice) that is identified as being within frame of a camera (e.g., the audio is originating from a source (e.g., a person) that is positioned within a field-of-view of a camera); a mode for filtering out audio that is not identified as being within frame of the camera). Displaying the set of one or more media communication controls including the first microphone control option provides additional controls for enabling a voice isolation mode for a microphone without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the

operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system (e.g., **600**) detects a selection of the first microphone control option and, in response, enables (or disables) the voice isolation mode for the microphone.

[0475] In some embodiments, the set of one or more media communication controls includes a second microphone control option (e.g., **1242-3**) (e.g., a music mode option) that is selectable to enable a music emphasis mode for a microphone (e.g., a mode that does not filter out audio and, optionally, amplifies audio (e.g., background audio)). Displaying the set of one or more media communication controls including the second microphone control option provides additional controls for enabling a music emphasis mode for a microphone without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the second microphone control option and, in response, enables (or disables) the music emphasis mode for the microphone.

[0476] In some embodiments, the set of one or more media communication controls includes a third microphone control option (e.g., **1242-1**) (e.g., a default mode option) that is selectable to enable a mode (e.g., a default mode) for filtering background noise using a microphone (e.g., a mode for filtering out audio (e.g., background audio)). Displaying the set of one or more media communication controls including the third microphone control option provides additional controls for enabling a mode for filtering background noise using a microphone without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the third microphone control option and, in response, enables (or disables) the mode for filtering background noise using a microphone.

[0477] In some embodiments, the computer system (e.g., **600**) receives an input directed to the set of one or more media communication controls (e.g., **1238**, **1244**) (e.g., a selection of a camera setting option; a selection of a microphone mode option). In response to receiving the input directed to the set of one or more media communication controls, the computer system changes media communication settings in a first manner (e.g., enabling a default camera mode; enabling an automatic framing mode for a camera; enabling a background blur option for a camera; enabling a default microphone mode; enabling a voice isolation mode for a microphone; enabling a music mode for a microphone) for a first application (e.g., a camera application) operating at the computer system, and changes media communication settings in the first manner for a second application (e.g., a video conference application) operating at the computer system different from the first application. Changing media communication settings in the first manner for both the first application and the second application conserves computational resources and reduces inputs at the computer system by applying a selected media communication setting for multiple applications

without requiring the user to select the settings individually for each application. Reducing inputs and conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0478] In some embodiments, displaying the system interface (e.g., **1225**, **1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls (e.g., **1231**, **1232**) includes: in accordance with a determination that a camera (e.g., **602**) (optionally, and/or microphone) has been active within the predetermined amount of time, displaying the set of one or more media communication controls (e.g., a microphone control (e.g., **1232**) and/or text (e.g., **1227**) indicating a name of an application that is currently using (or has recently used) the camera and/or microphone) concurrently with a camera control (e.g., **1231**) (e.g., a graphical user interface object that is selectable to control (e.g., select, change, enable, disable) one or more settings of the camera); and in accordance with a determination that the camera has not been active within the predetermined amount of time, displaying the set of one or more media communication controls without displaying the camera control (e.g., forgoing displaying the camera control while displaying other controls for controlling different system functions of the computer system). Displaying the set of one or more media communication controls concurrently with the camera control, or without displaying the camera control, depending on whether or not the camera has been active within the predetermined amount of time provides additional controls for the camera without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the camera control is displayed if the camera has been used recently, even if the camera is not currently in use. In some embodiments, displaying the set of one or more media communication controls includes displaying text that indicates the name of the application that is currently (or was recently) using the camera and/or microphone.

[0479] In some embodiments, displaying the system interface (e.g., **1225**, **1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls (e.g., **1231**, **1232**) includes: in accordance with a determination a microphone (optionally, and/or camera) has been active within the predetermined amount of time, displaying the set of one or more media communication controls (e.g., a camera control (e.g., **1231**) and/or text (e.g., **1227**) indicating a name of an application that is currently using (or has recently used) the camera (e.g., **602**) and/or microphone) concurrently with a microphone audio control (e.g., **1232**) (e.g., a graphical user interface object that is selectable to control (e.g., select, change, enable, disable) one or more settings of the microphone); and in accordance with a determination that the microphone has not been active within the predetermined amount of time, displaying the set of one or more media communication controls without displaying the microphone audio control (e.g., forgoing displaying the microphone control while displaying other controls for controlling different system functions of the computer system). Displaying the set of one or more media communication controls with or without the microphone audio control depending on whether or not the microphone has been active within the predetermined amount of time provides additional controls for the microphone without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed.

Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the microphone control is displayed if the microphone has been used recently, even if the microphone is not currently in use. In some embodiments, displaying the set of one or more media communication controls includes displaying text that indicates the name of the application that is currently (or was recently) using the camera and/or microphone.

[0480] In some embodiments, displaying the system interface (e.g., **1225, 1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls (e.g., **1231, 1232**) includes displaying a representation (e.g., **1227, 1227-1, 1227-2**) of one or more applications (e.g., text identifying the application(s) (e.g., “camera” and/or “video conference”)) associated with a media communication session that has been active within the predetermined amount of time (e.g., the system interface displays the names of applications that are, or have been recently, using the camera and/or microphone during the media communication session). Displaying a representation of one or more applications associated with a media communication session that has been active within the predetermined amount of time provides feedback to a user of the computer system indicating which applications have recently been active for a media communication session. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0481] In some embodiments, displaying the system interface (e.g., **1225, 1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls (e.g., **1231, 1232**) includes displaying a graphical user interface object (e.g., **1237, 1243**) (e.g., a link to a settings interface) that is selectable to display a user interface (e.g., **1291, 1292, 1293**) (e.g., a settings interface) that includes the media communication settings (e.g., **1291-1, 1291-2, 1292-1, 1292-2, 1293-1, 1293-2**) that determine how media is handled by the computer system (e.g., **600**) during media communication sessions. Displaying a graphical user interface object that is selectable to display a user interface that includes the media communication settings provides additional controls for accessing the media communication settings without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the graphical user interface object and, in response, displays the user interface that includes the media communication settings that determine how media is handled by the computer system during media communication sessions.

[0482] In some embodiments, displaying the system interface (e.g., **1225, 1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls includes: displaying a first set of media communication controls (e.g., **1292-1, 1293-1**) for a first media communication device (e.g., a camera (e.g., **602**); a microphone), wherein the first set of media communication controls provides access to media communication settings that determine

how media (e.g., video data; audio data) is handled using the first media communication device during a media communication session provided via a first application (e.g., a “video conferencing” application (e.g., see FIG. 12T)); and displaying a second set of media communication controls for the first media communication device (e.g., **1292-2**, **1293-2**), wherein the second set of media communication controls provides access to media communication settings that determine how media is handled using the first media communication device during a media communication session provided via a second application different from the first application (e.g., a “messages” application (e.g., see FIG. 12T)). Displaying a first set of media communication controls for a first media communication device that provides access to media communication settings that determine how media is handled for a first application, and displaying a second set of media communication controls for the first media communication device that provides access to media communication settings that determine how media is handled for a second application provides additional application-specific controls for the first media communication device without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0483] In some embodiments, while a media communication session has not been active within the predetermined amount of time: the computer system (e.g., **600**) receives, via the one or more input devices (e.g., **601**), an input (e.g., **1290**, **1294**, **1295**) corresponding to a request to display a settings user interface (e.g., a selection of the link to the settings interface displayed with the media communication controls; a selection of a menu option in a settings application for the computer system). In response to receiving the input corresponding to the request to display the settings user interface, the computer system displays, via the one or more output generation components (e.g., **601**), a settings user interface (e.g., **1291**, **1292**, **1293**) that includes the media communication settings that determine how media is handled by the computer system during media communication sessions. Displaying the settings user interface that includes the media communication settings in response to the input corresponding to the request to display the settings user interface provides additional controls for determining how media is handled by the computer system during media communication sessions when a media communication session has not been active within the predetermined amount of time without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0484] In some embodiments, the settings user interface (e.g., **1292**) includes a selectable option (e.g., **1292-1a**) for enabling (and/or disabling) a first media communication setting for changing an appearance (e.g., applying a visual effect that blurs, obscures, darkens, shades, or otherwise deemphasizes) of a representation of a background portion (e.g., **1208-1**, **1220-1a**) of a field-of-view of a camera (e.g., **602**) (e.g., a portion of the camera field-of-view that does not include a subject) (e.g., without applying the visual effect to a foreground portion (e.g., a portion that includes the subject) of the camera field-of-view) (e.g., as discussed with respect to FIGS. 12K-12N and FIG. 14), wherein the first media communication setting corresponds to (e.g., applies to,

controls; affects) applications (e.g., all applications) operating at the computer system that use the camera. Displaying the settings user interface having a selectable option for enabling a first media communication setting for changing an appearance of a representation of a background portion of a field-of-view of a camera for applications operating at the computer system that use the camera provides additional controls for quickly and easily enabling the first media communication setting without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Easily changing the appearance of (e.g., hiding) the background provides privacy benefits to the user of the computer system by preventing the display of the background (e.g., to other participants of the live video communication session and, in some embodiments, to the applications operating at the computer system that use the camera). Providing privacy benefits and additional control options without cluttering the user interface with additional displayed controls, and avoiding accidental inputs, enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the selectable option and, in response, enables (or disables) the first media communication setting for changing an appearance of a representation of a background portion of a field-of-view of a camera.

[0485] In some embodiments, the settings user interface (e.g., **1293**) includes a selectable option (e.g., **1293-1a**, **1293-2a**) for enabling (and/or disabling) a third media communication setting for changing an audio setting of a microphone (e.g., a default setting, a voice isolation setting, a music emphasis setting), wherein the third media communication setting corresponds to (e.g., applies to; controls; affects) applications (e.g., all applications) operating at the computer system that use the microphone. Displaying the settings user interface having a selectable option for enabling a third media communication setting for changing an audio setting of a microphone for applications operating at the computer system that use the microphone provides additional controls for quickly and easily changing an audio setting of the microphone without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Easily changing the audio setting of the microphone reduces computational resources used by the computer system to generate and/or process unnecessary audio. Providing additional control options without cluttering the user interface with additional displayed controls, avoiding accidental inputs, and reducing computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the selectable option and, in response, enables (or disables) the third media communication setting for changing an audio setting of a microphone.

[0486] In some embodiments, the settings user interface (e.g., **1292**) includes a plurality of controls (e.g., **1292-2**) corresponding to a mode (e.g., automatic framing mode) for automatically adjusting a representation (e.g., **1208**, **1220-1**) of a field-of-view of one or more cameras (e.g., **602**) (e.g., during a live video communication session) based on a change in position of a subject detected in the field-of-view of the one or more cameras (e.g., as discussed with respect to FIGS. **6A-6Q** and FIGS. **7A-7B**). In some embodiments, the plurality of controls includes a first control (e.g., **1292-2b**) that is selectable to enable (and/or disable) the mode for a first application (e.g., a “messages” application) operating at the computer system (e.g., **600**) that uses the camera. In some embodiments, the computer system detects a selection of the first control and, in response, enables (or disables) the mode for the first application operating at the computer system that uses the

camera. In some embodiments, the plurality of controls includes a second control (e.g., **1292-2c**) that is selectable to enable (and/or disable) the mode for a second application (e.g., a “video conferencing” application), different from the first application, operating at the computer system that uses the camera. In some embodiments, the computer system detects a selection of the second control and, in response, enables (or disables) the mode for the second application operating at the computer system that uses the camera.

[0487] In some embodiments, displaying the system interface (e.g., **1225**, **1280**) with the plurality of concurrently displayed controls that include the set of one or more media communication controls (e.g., **1231**, **1232**) includes: in accordance with a determination that a media communication session has been active within the predetermined amount of time, displaying the set of one or more media communication controls in a first region (e.g., **1225-1**) of the system interface (e.g., a region located at a top portion of the system interface) and displaying a set of one or more system controls in a second region (e.g., **1225-2**) of the system interface (e.g., a region that is positioned below (e.g., and does not overlap) the first region of the system interface); and in accordance with a determination that a media communication session has not been active within the predetermined amount of time, displaying the set of one or more system controls at least partially in the first region of the system interface (e.g., one or more of the system controls are shifted upward into the first region when the media communication controls are not displayed (e.g., see FIG. **12I**)). Displaying the set of one or more media communication controls at least partially in the first region of the system interface and displaying the set of one or more system controls in a second region of the system interface when a media communication session has been active within the predetermined amount of time provides additional controls for the media communication session without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0488] In some embodiments, the first region (e.g., **1225-1**) of the system interface (e.g., **1225**) is not user configurable (e.g., the user cannot change, customize, and/or select the configuration of the controls that are displayed in the first region). In some embodiments, regions of the system interface other than the first region (e.g., the second region (e.g., **1225-2**)) are user configurable.

[0489] Note that details of the processes described above with respect to method **1300** (e.g., FIG. **13**) are also applicable in an analogous manner to the methods described below and above. For example, method **700**, method **900**, method **1100**, and/or method **1400** optionally includes one or more of the characteristics of the various methods described above with reference to method **1300**. For brevity, these details are not repeated.

[0490] FIG. **14** is a flow diagram illustrating a method for managing a live video communication session using a computer system (e.g., a smartphone, a smartwatch) in accordance with some embodiments. Method **1400** is performed at a computer system (e.g., **600**, **1200**) that is in communication with one or more output generation components (e.g., **601**, **1200-1**) (e.g., a display controller, a touch-sensitive display system, a speaker, a bone conduction audio output device, a tactile output generator, a projector, and/or a holographic display), one or more cameras (e.g., **602**, **1200-2**) (e.g., an infrared camera; a depth camera; a visible light camera), and one or more input devices (e.g., **601**) (e.g., a touch-sensitive surface, a keyboard, mouse, trackpad, one or more optical sensors for detecting gestures, one or more capacitive sensors for detecting hover inputs, and/or accelerometer/gyroscope/inertial measurement units). Some operations in method **1400** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations

are, optionally, omitted.

[0491] As described below, method **1400** provides an intuitive way for managing a live video communication session. The method reduces the cognitive burden on a user for managing a live video communication session, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to manage a live video communication session faster and more efficiently conserves power and increases the time between battery charges.

[0492] The computer system (e.g., **600**) displays (**1402**) via the one or more output generation components (e.g., **601**), a live video communication interface (e.g., **1205**) for a live video communication session (e.g., an interface for a live video communication session (e.g., a live video chat session, a live video conference session, etc.)), wherein displaying the live video communication interface includes concurrently displaying (**1404**) (in some embodiments, the live video communication interface includes a live preview (e.g., **1208**) of the user of the computer system and a live representation (e.g., **1210-1**, **1210-2**) of one or more participants (e.g., remote users) of the live video communication session.) a representation of a field-of-view of the one or more cameras of the computer system (e.g., **1208**) (e.g., a camera preview of the computer system for the live video communication session (optionally including a representation of a subject participating in the live video communication session); in some embodiments, the representation of the field-of-view of the one or more cameras of the computer system corresponds to a participant of the live video communication session who is associated with the computer system (e.g., based on a user account of the computer system).), wherein the representation of the field-of-view of the one or more cameras is visually associated with (e.g., displayed adjacent to; displayed grouped together with) an indication (e.g., **610**, **611**) (e.g., a graphical user interface object (e.g., a “background blur” affordance; a “framing mode” affordance; a “dynamic video quality” affordance)) of an option to initiate a process for changing an appearance of a portion (e.g., a background portion of the camera preview; a portion of the camera preview that does not include a representation of the subject (e.g., a face of the subject), a portion of the camera preview that at least partially surrounds the subject) of the representation of the field-of-view of the one or more cameras other than a subject (e.g., **1208-1**) (e.g., other than a portion of the representation of the field-of-view of the one or more cameras that includes a subject (or a face of the subject)) that is displayed in the representation of the field-of-view of the one or more cameras (e.g., a participant of the live video communication session; a user of the computer system that is detected within a field-of-view of the one or more cameras during the live video communication session) during the live video communication session (e.g., the background blur affordance (or, in some embodiments, the dynamic video quality affordance) is selectable for enabling/disabling a visual effect (e.g., a blurring, darkening, shading, desaturating, or otherwise deemphasizing effect (e.g., a reduced video quality)) that is applied to a background portion of the camera preview during the live video communication session (e.g., without applying the visual effect to the portion of the camera preview that includes the representation of the subject (e.g., a foreground portion; a portion that includes the subject's face))). Displaying a representation of a field-of-view of the one or more cameras that is visually associated with an indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras provides feedback to a user of the computer system that the appearance of the representation of the field-of-view of the one or more cameras is capable of being modified, and reduces the number of user inputs at the computer system by providing an option for changing the appearance of the portion of the representation of the field-of-view other than a subject without requiring the user to navigate a settings menu or other additional interfaces to change the appearance. Providing improved feedback and reducing the number of inputs at the computer system enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which,

additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0493] The computer system also concurrently displays (**1406**) (in some embodiments, the representation of the field-of-view of the one or more cameras is a preview of image data outputted, or capable of being outputted, by the computer system to one or more electronic devices associated with one or more participants (e.g., remote participants) of the live video communication session) a representation of one or more participants (e.g., **1210-1**, **1210-2**) (e.g., remote participant(s)) in the live video communication session that is different from (e.g., not included with; displayed separate from) the representation of the field-of-view of the one or more cameras of the computer system (e.g., one or more video feeds of participants in the live video communication session).

[0494] While displaying the live video communication interface for the live video communication session (e.g., **1205**), the computer system (e.g., **600**) detects (**1408**), via the one or more input devices (e.g., **601**), a set of one or more inputs (e.g., **1202**, **1264**) (e.g., a selection of the background blur affordance and/or dynamic video quality affordance) that corresponds to a request to change (in some embodiments, automatically (e.g., without further user input)) an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras (e.g., the set of one or more inputs including an input directed to the indication of the option to initiate the process for changing the appearance of the portion of the representation of the field of view of the one or more cameras or an input directed to the representation of a field-of-view of the one or more cameras of the computer system).

[0495] In response to detecting (**1410**) the set of one or more inputs (e.g., **1202**, **1264**), the computer system (e.g., **600**) changes the appearance of the portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation (e.g., **1208**) of the field-of-view of the one or more cameras (e.g., enabling/disabling a visual effect (e.g., a blurring, darkening, shading, obscuring, desaturating, or otherwise deemphasizing effect (e.g., a reduced video quality)) that is applied to a background portion of the camera preview during the live video communication session (e.g., without applying the visual effect to the portion of the camera preview that includes the representation of the subject (e.g., **1208-2**) (e.g., a foreground portion; a portion that includes the subject's face))). Changing the appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras provides enhanced privacy control for a user of the computer system by preventing the display of the background (e.g., to other participants of the live video communication session and, in some embodiments, to the application hosting the live video communication session), and reduces the number of user inputs at the computer system by changing the appearance of the portion of the representation of the field-of-view other than a subject without requiring the user to navigate a settings menu or other additional interfaces to change the appearance. Reducing the number of inputs at the computer system enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0496] In some embodiments, changing the appearance of the portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras (e.g., **1208**) during the live video communication session includes outputting (e.g., to an electronic device (e.g., **600a**) of the one or more participants (the remote participants)) image data corresponding to the representation of the field-of-view of the one or more cameras including the subject (e.g., **1220-1b**) and the

portion of the representation of the field-of-view having the changed appearance during the live video communication session (e.g., **1220-1a**). In some embodiments, in response to the set of one or more inputs, the computer system enables a mode (e.g., dynamic video quality mode) for outputting (e.g., transmitting and, optionally, displaying) a camera field-of-view with portions having different degrees of compression and/or video qualities. For example, portions of the camera field-of-view that include a detected face of the subject (e.g., **1208-2**, **1220-1b**) (or detected faces of subjects) are compressed less than portions of the camera field-of-view that do not include a detected face (e.g., **1208-1**, **1220-1a**). As such, the video feed for the live video communication session can be transmitted (e.g., by the computer system (e.g., **600**)) to a recipient device (e.g., **600a**) of a remote participant of the live video communication session so that the portions (e.g., **1220-1b**) of the camera field-of-view that include a detected face can be displayed at the recipient device with a higher video quality than the portions (e.g., **1220-1a**) that do not include a detected face (due to the reduced compression of the portions of the camera field-of-view that include a detected face and the increased compression of the portions of the camera field-of-view that do not include a detected face). In some embodiments, the computer system varies the amount of compression as the video bandwidth changes (e.g., increases, decreases). For example, the degree of compression of the portion(s) of the camera field-of-view (e.g., the camera feed) that does not include the detected face(s) varies (e.g., increases or decreases with the corresponding change in bandwidth) while the degree of compression of the portion(s) of the camera field-of-view that includes the detected face(s) remains constant (or, in some embodiments, varies at a lesser rate or by a lesser amount than the portion(s) of the camera field-of-view that does not include the face(s)). [0497] In some embodiments, prior to displaying the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject, the computer system (e.g., **600**) detects an input (e.g., **1258**) directed to the representation of the field-of-view of the one or more cameras (e.g., **1208**) (e.g., the input is detected while the camera preview is displayed without the indication of the option (e.g., without the background blur affordance)). In response to detecting the input directed to the representation of the field-of-view of the one or more cameras, the computer system displays the indication (e.g., **611** in FIG. **12K**) (e.g., displaying the camera preview visually associated with the indication) of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject. Displaying the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject in response to detecting the input directed to the representation of the field-of-view of the cameras provides additional control options for changing an appearance of the portion of the representation of the field-of-view without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the indication of the option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject and, in response, initiates the process, including changing the appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras (e.g., blurring portion **1208-1**, as illustrated in FIG. **12L**).

[0498] In some embodiments, the indication (e.g., **611**) of an option to initiate a process for

changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject is displayed (e.g., in FIG. **12K**) over at least a portion of the representation (e.g., **1208**) of the field-of-view of the one or more cameras of the computer system (e.g., the indication (e.g., the background blur affordance) is displayed overlaid on the camera preview). Displaying the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject over at least a portion of the representation of the field-of-view of the one or more cameras provides feedback to a user of the computer system that the option is applicable to the representation of the camera preview (and an outgoing video feed) without cluttering the UI with additional content to describe operation of the option. Providing improved feedback and avoiding cluttering the user interface with additional displayed content enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0499] In some embodiments, displaying the live video communication interface (e.g., **1205**) includes: displaying, via the one or more output generation components (e.g., **601**), a camera control (e.g., **1217**) (e.g., a camera flip affordance) that is selectable to change the representation of the field-of-view of the one or more cameras (e.g., **1208**) from a representation of a field-of-view of a first camera (e.g., **602**) (e.g., a camera preview for a first camera (e.g., a camera on a front side of the computer system)) to a representation of a field-of-view of a second camera different from the first camera (e.g., a camera preview for a second camera (e.g., a camera on a back side of the computer system)). In some embodiments, the camera control is displayed concurrently with the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject. Displaying a camera control concurrently with the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject provides feedback to a user of the computer system that the camera control and the option for changing the appearance of the representation of the field-of-view are applicable to the representation of the camera preview (and an outgoing video feed) without cluttering the UI with additional content to describe operation of the controls. Providing improved feedback and avoiding cluttering the user interface with additional displayed content enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the camera control and, in response, changes the representation of the field-of-view of the one or more cameras from a representation of a field-of-view from the first camera to a representation of a field-of-view of the second camera.

[0500] In some embodiments, displaying the live video communication interface (e.g., **1205**) includes: displaying, via the one or more output generation components (e.g., **601**), a visual effects control (e.g., **1216**) (e.g., a visual effects affordance) that is selectable to enable (and/or disable) a mode for displaying the representation of the field-of-view of the one or more cameras (e.g., **1208**) with one or more visual effects (e.g., graphical visual effects (e.g., avatar effects, filter effects, text effects, and/or sticker effects) that are displayed in the camera preview, but are not part of the image data that is obtained using the camera). In some embodiments, the visual effects control is displayed concurrently with the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject. Displaying a visual effects control concurrently with the indication of an option to initiate a process for changing an appearance of a portion of the

representation of the field-of-view of the one or more cameras other than a subject provides feedback to a user of the computer system that the visual effects control and the option for changing the appearance of the representation of the field-of-view are applicable to the representation of the camera preview (and an outgoing video feed) without cluttering the UI with additional content to describe operation of the controls. Providing improved feedback and avoiding cluttering the user interface with additional displayed content enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system (e.g., **600**) detects a selection of the visual effects control and, in response, enables (or disables) the mode for displaying the representation of the field-of-view of the one or more cameras with one or more visual effects.

[0501] In some embodiments, displaying the live video communication interface (e.g., **1205**) includes: displaying, via the one or more output generation components (e.g., **601**), a camera zoom control (e.g., **1260**) (e.g., a camera zoom affordance) that is selectable to change a zoom level (e.g., a digital zoom and/or optical zoom) of the representation of the field-of-view of the one or more cameras (e.g., **1208**). In some embodiments, the camera zoom control is displayed concurrently with the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject. Displaying a camera zoom control concurrently with the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject provides feedback to a user of the computer system that the camera zoom control and the option for changing the appearance of the representation of the field-of-view are applicable to the representation of the camera preview (and an outgoing video feed) without cluttering the UI with additional content to describe operation of the controls. Providing improved feedback and avoiding cluttering the user interface with additional displayed content enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the camera zoom control and, in response, changes the zoom level of the representation of the field-of-view of the one or more cameras.

[0502] In some embodiments, displaying the live video communication interface (e.g., **1205**) includes: displaying, via the one or more output generation components (e.g., **601**), a camera framing control (e.g., **610**) (e.g., a framing mode option) that is selectable to enable (and/or disable) a mode (e.g., automatic framing mode) for automatically adjusting the representation of the field-of-view of the one or more cameras (e.g., **1208**) (e.g., during a live video communication session) based on a change in position of a subject detected in the field-of-view of the one or more cameras (e.g., **602**) (e.g., as discussed with respect to FIGS. **6A-6Q** and FIGS. **7A-7B**). In some embodiments, the camera framing control is displayed concurrently with the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject. Displaying a camera framing control concurrently with the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject provides feedback to a user of the computer system that the camera framing control and the option for changing the appearance of the representation of the field-of-view are applicable to the representation of the camera preview (and an outgoing video feed) without cluttering the UI with additional content to describe operation of the controls. Providing

improved feedback and avoiding cluttering the user interface with additional displayed content enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the framing mode option is selectable to enable/disable a mode for: 1) tracking (e.g., during a live video communication session) a position and/or location of one or more subjects detected within a field-of-view of the one or more cameras, and 2) automatically adjusting a displayed view of the subject(s) (e.g., during the live video communication session) based on the tracking of the subject. In some embodiments, the computer system detects a selection of the camera framing control and, in response, enables (or disables) the mode for automatically adjusting the representation of the field-of-view of the one or more cameras based on a change in position of a subject detected in the field-of-view of the one or more cameras. [0503] In some embodiments, while displaying the live video communication interface (e.g., **1205**) for the live video communication session with the indication (e.g., **1216**) of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras (e.g., **1208**) other than a subject, wherein the indication (e.g., **1216**) has a first displayed state (e.g., shown in FIG. **12J**) (e.g., a non-expanded state; a state that includes a single visual effect control (e.g., visual effects affordance)), the computer system (e.g., **600**) detects, via the one or more input devices (e.g., **601**), a first input (e.g., **1258**) (e.g., an input on the camera preview (the representation of the field-of-view of the one or more cameras)). In response to detecting the first input, the computer system displays the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject, wherein the indication (e.g., **1262**) has a second displayed state (e.g., an expanded state (e.g., shown in FIG. **12K**)) that includes a plurality of visual effect controls (e.g., **1262-1**) (e.g., graphical visual effect controls (e.g., avatar effect controls, filter effect controls, text effect controls, and/or sticker effect controls) that are each selectable to enable display of a visual effect that is displayed in the camera preview, but is not part of the image data that is obtained using the camera) displayed (e.g., concurrently) adjacent (e.g., below, above, to a side of) the representation of the field-of-view of the one or more cameras of the computer system (e.g., **1208**). Displaying, in response to the first input, the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject, wherein the indication has a second displayed state that includes a plurality of visual effect controls displayed adjacent the representation of the field-of-view of the one or more cameras, provides additional visual effect controls without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the first displayed state of the indication is an affordance that is selectable to enable or disable display of visual effects in general, whereas the second displayed state of the indication includes a plurality of affordances that are individually selectable to enable or disable display of individual types of visual effects. For example, the first displayed state is a visual effects affordance that enables display of filters, text, avatars, stickers, and the like, and the second displayed state includes a filter affordance that is selectable to enable display of a filter, a text affordance that is selectable to enable display of text, an avatar affordance that is selectable to enable display of an avatar, and/or a sticker affordance that is selectable to enable

display of a sticker.

[0504] In some embodiments, displaying the live video communication interface (e.g., **1205**) for the live video communication session with the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject includes concurrently displaying: the representation of a field-of-view of the one or more cameras of the computer system (e.g., **1208**) (in some embodiments, the representation of the field-of-view of the camera is displayed having a first displayed size (e.g., a reduced or small size)); a camera control (e.g., **1217**) (e.g., a camera flip affordance) that is selectable to change the representation of the field-of-view of the one or more cameras from a representation of a field-of-view of a third camera (e.g., **602**) (e.g., a camera preview for a camera (e.g., a camera on a front side of the computer system (e.g., **600**))) to a representation of a field-of-view of a fourth camera different from the third camera (e.g., a camera preview for a different camera (e.g., a camera on a back side of the computer system)) (in some embodiments, the computer system detects a selection of the camera control and, in response, changes the representation of the field-of-view of the one or more cameras from a representation of a field-of-view from the third camera to a representation of a field-of-view of the fourth camera); and a visual effects control (e.g., **1216**) (e.g., a visual effects affordance) that is selectable to enable (and/or disable) a mode for displaying the representation of the field-of-view of the one or more cameras with one or more visual effects (e.g., graphical visual effects (e.g., avatar effects, filter effects, text effects, and/or sticker effects) that are displayed in the camera preview, but are not part of the image data that is obtained using the camera) (In some embodiments, the computer system detects a selection of the visual effects control and, in response, enables the mode for displaying the representation of the field-of-view of the one or more cameras with one or more visual effects).

Displaying the representation of the field-of-view of the one or more cameras with a camera control and visual effects control provides feedback to a user of the computer system that the camera control and the visual effects control are applicable to the representation of the camera preview (and an outgoing video feed) without cluttering the UI with additional content to describe operation of the controls. Providing improved feedback and avoiding cluttering the user interface with additional displayed content enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, in response to detecting an input (e.g., an input on the camera preview), the representation of the field-of-view of the one or more cameras is displayed having an enlarged size with the camera control and the visual effects control (and, optionally, one or more additional controls (e.g., a zoom control, a background blur control, a framing mode control)). In some embodiments, when the representation of the field-of-view of the one or more cameras is enlarged, the visual effects control is displayed having an expanded state.

[0505] In some embodiments, while displaying the live video communication interface (e.g., **1205**) for the live video communication session and a first mode is enabled for displaying one or more visual effects (e.g., the representation of the field-of-view of the one or more cameras of the computer system (e.g., **600**) detects an input (e.g., **1268**) corresponding to a request to enable a second mode (e.g., automatic framing mode) for automatically adjusting the representation of the field-of-view of the one or more cameras (e.g., during a live video communication session) based on a change in position of a subject detected in the field-of-view of the one or more cameras (e.g., **602**). In response to detecting the input corresponding to the request to enable the second mode, the computer system disables the first mode for displaying one or more visual effects (e.g., ceasing display of the visual effects (e.g., indicated by greying out of effects option **1262-1** in FIG. **12N**)) and enables the second mode for automatically adjusting the representation of the field-of-view of

the one or more cameras based on a change in position of a subject detected in the field-of-view of the one or more cameras. Disabling the first mode and enabling the second mode in response to detecting the input corresponding to the request to enable the second mode conserves computational resources by eliminating processes performed when the first mode is enabled. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the visual effects are effects that are displayed using depth data and enabling the second mode disables use of one or more sensors (e.g., depth sensors, depth cameras, multiple cameras that are spaced apart on the device, etc.) that are used to obtain the depth data.

[0506] In some embodiments, while displaying the live video communication interface (e.g., **1205**) for the live video communication session: the computer system (e.g., **600**) receives, via the one or more input devices (e.g., **601**), a set of one or more inputs that includes a request (e.g., **1258**) to adjust a displayed size of the representation of the field-of-view of the one or more cameras (e.g., **1208**) (e.g., an input for resizing the camera preview). In response to receiving the set of one or more inputs that includes a request to adjust a displayed size of the representation of the field-of-view of the one or more cameras, the computer system adjusts a displayed size of the representation of the field-of-view of the one or more cameras (e.g., as shown in FIG. **12K**), including: in accordance with a determination that the representation of the field-of-view of the one or more cameras has a first displayed size (e.g., a reduced size (e.g., shown in FIG. **12J**)) (e.g., when the request to adjust the displayed size is received), displaying the representation of the field-of-view of the one or more cameras having a second displayed size (e.g., an enlarged size (e.g., shown in FIG. **12K**)) different from (e.g., larger than) the first displayed size and displaying a selectable control (e.g., **611**) (e.g., a background blur affordance) (e.g., the indication includes a background blur affordance) for changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject, wherein the selectable control is visually associated with the representation of the field-of-view of the one or more cameras having the second displayed size (e.g., the background blur affordance is displayed on the camera preview) (in some embodiments, the computer system detects a selection of the selectable control and, in response, changes an appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject.); and in accordance with a determination that the representation of the field-of-view of the one or more cameras has the second displayed size (e.g., an enlarged size (e.g., **12K**)) (e.g., when the request to adjust the displayed size is received), displaying the representation of the field-of-view of the one or more cameras having the first displayed size (e.g., a reduced size (e.g., **12J**)) and forgoing displaying the selectable control (e.g., a background blur affordance) (e.g., the indication does not include a background blur affordance) for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras other than a subject. Displaying the selectable control visually associated with the representation of the field-of-view of the one or more cameras when the representation of the field-of-view of the one or more cameras has the second displayed size, and forgoing displaying the selectable control when the representation of the field-of-view of the one or more cameras has the first displayed size, provides additional controls for changing an appearance of the representation of the field-of-view of the one or more cameras without cluttering the user interface with additional displayed controls until an input is detected and avoids accidental inputs while the additional control options are not displayed. Providing additional control options without cluttering the user interface with additional displayed controls and avoiding accidental inputs enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when

operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0507] In some embodiments, while displaying the live video communication interface (e.g., **1205**) for the live video communication session: the computer system (e.g., **600**) detects, via the one or more input devices (e.g., **601**), a tap gesture (e.g., **1258**) directed to the representation of the field-of-view of the one or more cameras (e.g., **1208**) (e.g., a tap gesture on the representation of the field-of-view of the one or more cameras). In response to detecting the tap gesture directed to the representation of the field-of-view of the one or more cameras, the computer system adjusts the representation of the field-of-view of the one or more cameras from a third displayed size to a fourth displayed size larger than the third displayed size (e.g., enlarging the camera preview in response to the tap gesture (e.g., FIG. **12K**)). Adjusting the representation of the field-of-view of the one or more cameras from the third displayed size to the fourth displayed size in response to detecting a tap gesture directed to the representation of the field-of-view of the one or more cameras provides feedback to a user of the computer system that the tap gesture was received by enlarging the representation of the field-of-view of the one or more cameras. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0508] In some embodiments, while displaying the live video communication interface (e.g., **1205**) for the live video communication session: the computer system (e.g., **600**) detects, via the one or more input devices (e.g., **601**), a de-pinch gesture directed to the representation of the field-of-view of the one or more cameras (e.g., **1208**) (e.g., a de-pinch gesture that is initiated on the representation of the field-of-view of the one or more cameras). In response to detecting the de-pinch gesture directed to the representation of the field-of-view of the one or more cameras, the computer system adjusts the representation of the field-of-view of the one or more cameras from a fifth displayed size to a sixth displayed size larger than the fifth displayed size (e.g., enlarging the camera preview in response to the de-pinch gesture). Adjusting the representation of the field-of-view of the one or more cameras from the fifth displayed size to the sixth displayed size in response to detecting a de-pinch gesture directed to the representation of the field-of-view of the one or more cameras provides feedback to a user of the computer system that the de-pinch gesture was received by enlarging the representation of the field-of-view of the one or more cameras. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the adjustment of the representation of the field-of-view of the one or more cameras is based on a magnitude of the de-pinch gesture. For example, when the de-pinch gesture is a first magnitude, the computer system adjusts the representation of the field-of-view of the one or more cameras by a first amount (e.g., the camera preview is resized (e.g., enlarged) by a first amount), and when the de-pinch gesture is a second magnitude different from the first magnitude, the computer system adjusts the representation of the field-of-view of the one or more cameras by a second amount different from the first amount (e.g., the camera preview is resized (e.g., enlarged) by a second amount).

[0509] In some embodiments, after changing the appearance of the portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras (e.g., **1208**): the computer system (e.g., **600**) displays, via the one or more output generation components (e.g., **601**), an

indication (e.g., **1265**) (e.g., a banner, a notification, an alert, text) of the changed appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras; and after expiration of a predetermined amount of time (e.g., after displaying the indication of the changed appearance for a predetermined amount of time), the computer system ceases displaying the indication of the changed appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras (e.g., while continuing to display the portion of the representation of the field-of-view of the one or more cameras other than a subject having the changed appearance). Displaying the indication of the changed appearance of the portion of the representation of the field-of-view of the one or more cameras other than a subject provides feedback to a user of the computer system that the appearance was changed. Providing improved feedback enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0510] In some embodiments, prior to displaying the live video communication interface (e.g., **1205**) for a live video communication session: the computer system (e.g., **600**) displays, via the one or more output generation components (e.g., **601**), a user interface for a request to join a first live video communication session (e.g., **1201**), wherein the user interface includes a camera control (e.g., **611**) (e.g., a background blur affordance) that is selectable to enable (or disable) a mode (e.g., a background blur mode) for applying a visual effect (e.g., a blurring, darkening, shading, obscuring, desaturating, or otherwise deemphasizing effect) to a portion (e.g., **1208-1**) of a representation of the field-of-view of the one or more cameras other than a subject during the first live video communication session (e.g., the background portion of the camera preview). In some embodiments, the user interface includes a second camera control (e.g., a framing mode affordance) that is selectable to enable (or disable) a mode (e.g., an automatic framing mode) for automatically adjusting a representation of a field-of-view of the one or more cameras (e.g., during a live video communication session) based on a change in position of a subject detected in the field-of-view of the one or more cameras. In some embodiments, the background blur mode is enabled while the automatic framing mode is disabled. In some embodiments, automatic framing mode is enabled while the background blur mode is disabled. In some embodiments, both the automatic framing mode and the background blur mode are enabled concurrently (e.g., during the live video communication session). In some embodiments, the method further comprises: receiving a set of one or more inputs that includes a request to join the first video communication session; and in response to receiving the set of one or more inputs that includes a request to join the first video communication session, displaying the live video communication interface, including: in accordance with a determination that the set of one or more inputs includes a selection of the camera control (e.g., the camera control is in a selected state when the request to join the first video communication session is received), displaying the portion of the representation of the field-of-view of the one or more cameras other than a subject having the visual effect (e.g., the changed appearance; the blurred appearance) (e.g., the visual effect is applied to the background of the camera preview); in accordance with a determination that the set of one or more inputs does not include a selection of the camera control (e.g., the camera control is in a deselected state when the request to join the first video communication session is received), displaying the portion of the representation of the field-of-view of the one or more cameras other than a subject without displaying the visual effect (e.g., the visual effect is not applied to the background of the camera preview); in accordance with a determination that the set of one or more inputs includes a selection of the second camera control (e.g., the second camera control is in a selected state when the request to join the first video communication session is received), displaying the live video communication

interface with the mode enabled for automatically adjusting a representation of a field-of-view of the one or more cameras based on a change in position of a subject detected in the field-of-view of the one or more cameras (e.g., in some embodiments, while concurrently displaying the portion of the representation of the field-of-view of the one or more cameras other than a subject having the visual effect); and in accordance with a determination that the set of one or more inputs does not include a selection of the second camera control (e.g., the second camera control is in a deselected state when the request to join the first video communication session is received), displaying the live video communication interface with the mode disabled for automatically adjusting a representation of a field-of-view of the one or more cameras based on a change in position of a subject detected in the field-of-view of the one or more cameras (e.g., in some embodiments, while displaying the portion of the representation of the field-of-view of the one or more cameras other than a subject having the visual effect).

[0511] In some embodiments, the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras during the live video communication session is displayed concurrently with one or more controls (e.g., **1212**, **1213**, **1214**) for the live video communication session (e.g., a microphone mute control, a call end control, and/or a camera on/off control) while the live video communication session is currently active (e.g., an ongoing call).

[0512] In some embodiments, the indication (e.g., **611**) of an option to initiate a process for changing an appearance of a portion (e.g., **1208-1**) of the representation of the field-of-view of the one or more cameras other than a subject that is displayed in the representation of the field-of-view of the one or more cameras during the live video communication session includes a camera control (e.g., **611**) (e.g., a background blur affordance) that is selectable to apply a visual effect (e.g., a blurring, darkening, shading, obscuring, desaturating, or otherwise deemphasizing effect) to the portion of the representation of the field-of-view of the one or more cameras other than a subject during the live video communication session. Displaying the indication of an option to initiate a process for changing an appearance of a portion of the representation of the field-of-view of the one or more cameras during the live video communication session including a camera control that is selectable to apply a visual effect to the portion of the representation of the field-of-view of the one or more cameras other than a subject during the live video communication session provides additional controls for quickly and easily changing an appearance of a background portion of a field-of-view of a camera. Easily changing the appearance of (e.g., hiding) the background provides privacy benefits to the user of the computer system by preventing the display of the background (e.g., to other participants of the live video communication session and, in some embodiments, to the application hosting the live video communication session). Providing privacy benefits and additional control options without cluttering the user interface with additional displayed controls enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the computer system detects a selection of the camera control and, in response, applies a visual effect to the portion of the representation of the field-of-view of the one or more cameras other than a subject during the live video communication session.

[0513] In some embodiments, the computer system (e.g., **600**, **600a**) displays, via the one or more output generation components (e.g., **601**, **601a**), a representation of a first portion (e.g., **1220-1b**) of a field-of-view of one or more cameras of a respective device of a respective participant in the live video communication session (e.g., a portion of the field-of-view of a camera of a remote participant in the live video communication session that includes a detected face of a remote

participant) (e.g., a portion of the field-of-view of the one or more cameras of the computer system that includes a detected face of the subject) and a representation of a second portion (e.g., **1220-1a**) of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., a portion of the field-of-view of the camera of the remote participant that does not include a detected face of a remote participant) (e.g., a portion of the field-of-view of the one or more cameras of the computer system that does not include a detected face of the subject), including displaying the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant with a reduced degree of compression (e.g., a higher video quality) than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the first portion of the field-of-view of one or more cameras includes a detected feature of a respective type (e.g., a face; multiple different faces) while a detected feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., when a face (or multiple different faces) is detected in the first portion of the field-of-view and not in the second portion of the field-of-view, the second portion is compressed (e.g., by the sending device (e.g., the device of the remote participant; the computer system of the subject)) at a greater degree than the first portion such that the first portion of the field-of-view can be displayed (e.g., at the receiving device (e.g., the computer system; the device of the remote participant)) at a higher video quality than the second portion of the field-of-view when a face is detected in the first portion and not in the second portion). Displaying the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant in the live video communication session with a reduced degree of compression than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the first portion of the field-of-view of the one or more cameras includes a detected feature of a respective type while a detected feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras conserves computational resources by conserving bandwidth and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, the set of one or more inputs enable a dynamic video quality mode for outputting (e.g., transmitting to a recipient device, optionally while displaying at the sending device) the camera field-of-view with portions having different degrees of video compression. In some embodiments, the computer system compresses portions of the camera field-of-view that do not include one or more faces more than portions of the camera field-of-view that do include one or more faces. In some embodiments, the computer system optionally displays the compressed video feed in the camera preview. In some embodiments, the computer system transmits the video feed having the different degrees of compression during the live video communication session such that a recipient device (e.g., a remote participant) can display the video feed received from the sending device (e.g., the computer system) having higher-video-quality portions concurrently displayed with lower-video-quality portions, wherein the higher-video-quality portions of the video feed include the face(s) and the lower-video-quality portions of the video feed do not include the face(s). Similarly, in some embodiments, the computer system receives compressed video data from a remote device (e.g., a device of a remote participant of the live video communication session) and displays the video feed from the remote device having the different degrees of compression such that the video feed of the remote device can be displayed with a higher-video-quality portion that includes the face of the remote participant and a lower-video-quality portion (displayed

concurrently with the higher-quality portion) that does not include the face of the remote participant. In some embodiments, the different degrees of compression can be applied to a video feed where multiple faces are detected. For example, the video feed can have multiple higher-quality (less compressed) portions, each corresponding to a location of one of the detected faces. In some embodiments, the dynamic video quality mode is independent of the automatic framing mode and background blur mode such that the dynamic video quality mode can be enabled and disabled separate from the automatic framing mode and the background blur mode. In some embodiments, the dynamic video quality mode is implemented with the automatic framing mode such that the dynamic video quality mode is enabled when the automatic framing mode is enabled and is disabled when the automatic framing mode is disabled. In some embodiments, the dynamic video quality mode is implemented with the background blur mode such that the dynamic video quality mode is enabled when the background blur mode is enabled and is disabled when the background blur mode is disabled.

[0514] In some embodiments, after the feature of the respective type has moved from the first portion of the field-of-view of one or more cameras of the respective device of the respective participant to the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., detecting the movement of the feature of the respective type from the first portion of the field-of-view of the one or more cameras to the second portion of the field-of-view of the one or more cameras; and, in response to detecting the movement of the feature of the respective type from the first portion of the field-of-view of the one or more cameras to the second portion of the field-of-view of the one or more cameras), the computer system (e.g., **600**, **600a**) displays, via the one or more output generation components (e.g., **601**, **601a**), the representation of the first portion (e.g., **1220-1a**) of the field-of-view of one or more cameras of the respective device of the respective participant and the representation of the second portion (e.g., **1220-1b**) of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., a portion of the field-of-view that includes a detected face), including displaying the representation of the first portion the field-of-view of one or more cameras of the respective device of the respective participant with an increased degree of compression (e.g., a lower video quality) than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the second portion of the field-of-view of one or more cameras of the respective device of the respective participant includes a detected feature of the respective type while a detected feature of the respective type is not detected in the first portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., as the face moves within the field-of-view of the one or more cameras, the degrees of compression of respective portions of the field-of-view of the one or more cameras change such that the face (e.g., a portion of the field-of-view that includes the face) is (e.g., remains) output (e.g., transmitted and, optionally, displayed) having a lower degree of compression than portions of the field-of-view that do not include the face). Displaying, after the feature of the respective type has moved from the first portion of the field-of-view of one or more cameras of the respective device of the respective participant to the second portion of the field-of-view of one or more cameras of the respective device of the respective participant, the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant in the live video communication session with an increased degree of compression than the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant in accordance with a determination that the second portion of the field-of-view of the one or more cameras includes a detected feature of the respective type while a detected feature of the respective type is not detected in the first portion of the field-of-view of one or more cameras conserves computational resources by conserving bandwidth and decreasing the amount of image data that is processed for display and/or transmission at a high image quality as a face moves within the scene. Conserving

computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0515] In some embodiments, the feature of the respective type is a detected face (e.g., a face detected within a field-of-view of one or more cameras; a face of a remote participant; a face of the subject). In some embodiments, displaying the representation of the second portion (e.g., **1220-1a**) of the field-of-view of one or more cameras of the respective device of the respective participant includes displaying the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant having a lesser video quality than the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., due to a reduced compression of the representation of the first portion of the field-of-view of the one or more cameras) in accordance with a determination that the first portion of the field-of-view of one or more cameras includes the detected face while a face is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant. Displaying the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant having a lesser video quality than the representation of the first portion of the field-of-view in accordance with a determination that the first portion of the field-of-view includes the detected face while a face is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant conserves computational resources by conserving bandwidth and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, portions of the camera field-of-view that do not include a detected face are output (e.g., transmitted and, optionally, displayed) having a lesser image quality than portions of the camera field-of-view that do include a detected face (due to the increased compression of the portions that do not include a detected face). In some embodiments, when no faces are detected in the field-of-view of the one or more cameras, the computer system applies a uniform or substantially uniform degree of compression to the first and second portions of the field-of-view of the one or more cameras such that the video feed (e.g., both the first and second portions) can be output having a uniform or substantially uniform video quality. In some embodiments, when multiple faces are detected in the camera field-of-view (e.g., multiple participants of the live video communication session are detected), the computer system applies the reduced compression concurrently to the portions of the field-of-view that correspond to the detected faces such that the faces can be displayed concurrently (e.g., at a recipient device) having the higher image quality. In some embodiments, the computer system applies the increased compression to the representation of the second portion of the field-of-view of the one or more cameras, even if a face is detected in the second portion. For example, the computer system can determine that the face in the second portion is not a participant of the live video communication session (e.g., the person is a bystander in the background) and, therefore, does not reduce the degree of compression of the second portion having the face.

[0516] In some embodiments, after (e.g., in response to detecting) a change in bandwidth for transmitting a representation (e.g., **1208**, **1220-1**) of the field-of-view of one or more cameras of the respective device of the respective participant occurs (e.g., is detected), while a feature of the respective type (e.g., a face) is detected in the first portion (e.g., **1220-1b**) of the field-of-view of

one or more cameras of the respective device of the respective participant and while a feature of the respective type is not detected in the second portion (e.g., **1220-1a**) of the field-of-view of one or more cameras of the respective device of the respective participant, a degree of compression (e.g., an amount of compression) of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant is changed by an amount that is less than an amount of change of a degree of compression of the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., when a face is detected in the first portion of the field-of-view of one or more cameras, and a face is not detected in the second portion of the field-of-view of one or more cameras, the rate of change in compression (in response to a change in bandwidth (e.g., a decrease in bandwidth)) is less for the first portion of the field-of-view than for the second portion of the field-of-view). Changing a degree of compression of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant by an amount that is less than an amount of change of a degree of compression of the representation of the second portion while a feature of the respective type is detected in the first portion and a feature of the respective type is not detected in the second portion conserves computational resources by conserving bandwidth for the first portion of the representation of the field-of-view of the one or more cameras that includes the feature of the respective type and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0517] In some embodiments, after (e.g., in response to detecting) a change in bandwidth for transmitting a representation (e.g., **1208**, **1220-1**) of the field-of-view of one or more cameras of the respective device (e.g., **600**) of the respective participant occurs (e.g., is detected), while a feature of the respective type is not detected in the first portion (e.g., **1220-1a**) of the field-of-view of one or more cameras of the respective device of the respective participant and while a feature of the respective type is detected in the second portion (e.g., **1220-1b**) of the field-of-view of one or more cameras of the respective device of the respective participant, a degree of compression (e.g., an amount of compression) of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant is changed by an amount that is more than an amount of change of a degree of compression of the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., when a face is detected in the second portion of the field-of-view of one or more cameras, and a face is not detected in the first portion of the field-of-view of one or more cameras, the rate of change in compression (in response to a change in bandwidth (e.g., a decrease in bandwidth)) is greater for the first portion of the field-of-view than for the second portion of the field-of-view). Changing a degree of compression of the representation of the first portion of the field-of-view of one or more cameras of the respective device of the respective participant by an amount that is more than an amount of change of a degree of compression of the representation of the second portion while a feature of the respective type is not detected in the first portion and a feature of the respective type is detected in the second portion conserves computational resources by conserving bandwidth for the second portion of the representation of the field-of-view of the one or more cameras that includes the feature of the respective type and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power

usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently.

[0518] In some embodiments, in response to a change in bandwidth for transmitting a representation (e.g., **1208**, **1220-1**) of the field-of-view of one or more cameras of the respective device (e.g., **600**) of the respective participant occurring (e.g., being detected), a quality (e.g., a video quality) (e.g., due to a change in the amount of video compression) of the representation of the second portion (e.g., **1220-1a**) of the field-of-view of one or more cameras of the respective device of the respective participant is changed by an amount that is greater than an amount of change of quality (in some embodiments, the representation of the first portion does not change in quality or has a nominal amount of change in quality) of the representation of the first portion (e.g., **1220-1b**) of the field-of-view of one or more cameras of the respective device of the respective participant (e.g., when a face is detected in the first portion of the field-of-view of one or more cameras, and a face is not detected in the second portion of the field-of-view of one or more cameras, the image quality of the second portion varies more than the image quality of the first portion in response to a change in bandwidth (e.g., a decrease in bandwidth)). Changing a quality of the representation of the second portion of the field-of-view of one or more cameras of the respective device of the respective participant by an amount that is greater than an amount of change of quality of the representation of the first portion conserves computational resources by conserving bandwidth for the first portion of the representation of the field-of-view of the one or more cameras and decreasing the amount of image data that is processed for display and/or transmission at a high image quality. Conserving computational resources enhances the operability of the computer system and makes the user-system interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the computer system) which, additionally, reduces power usage and improves battery life of the computer system by enabling the user to use the system more quickly and efficiently. In some embodiments, while a face is detected in the first portion of the field-of-view of one or more cameras, and is not detected in the second portion of the field-of-view, the computer system detects a change in available bandwidth (e.g., an increase in bandwidth; a decrease in bandwidth) and, in response, adjusts (e.g., increases; decreases) the compression of the second portion of the representation of the field-of-view of the one or more cameras without adjusting the compression of the first portion of the representation of the field-of-view of the one or more cameras. In some embodiments, when detecting a change in bandwidth, the computer system adjusts the compression of the first portion at a lesser rate than the adjustment to the second portion. In some embodiments, the method includes detecting (e.g., at the respective device of the respective participant) a change in bandwidth for transmitting a representation of the field-of-view of one or more cameras of the respective device of the respective participant while a feature of the respective type (e.g., a face) is detected in the first portion of the field-of-view of one or more cameras of the respective device of the respective participant and while a feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras of the respective device of the respective participant.

[0519] Note that details of the processes described above with respect to method **1400** (e.g., FIG. **14**) are also applicable in an analogous manner to the methods described above. For example, method **700**, method **900**, method **1100**, and/or method **1300** optionally includes one or more of the characteristics of the various methods described above with reference to method **1400**. For brevity, these details are not repeated.

[0520] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the techniques and their practical applications.

Others skilled in the art are thereby enabled to best utilize the techniques and various embodiments with various modifications as are suited to the particular use contemplated.

[0521] Although the disclosure and examples have been fully described with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art. Such changes and modifications are to be understood as being included within the scope of the disclosure and examples as defined by the claims.

[0522] As described above, one aspect of the present technology is the gathering and use of data available from various sources to enhance a user's video conferencing experience. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, social network IDs, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

[0523] The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to customize user profiles for a video conference experience. Accordingly, use of such personal information data enables users to have calculated control of the video conference experience. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user's general wellness, or may be used as positive feedback to individuals using technology to pursue wellness goals.

[0524] The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

[0525] Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of video conference interfaces, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services or anytime thereafter. In addition to providing “opt in” and “opt out” options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be

notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

[0526] Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

[0527] Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, general user profiles can be created for video conference applications based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information available to the video conference provider, or publicly available information.

Claims

1. A computer system configured to communicate with a display generation component, one or more cameras, and one or more input devices, comprising: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying, via the display generation component, a communication request interface that includes concurrently displaying: a representation of a field-of-view of the one or more cameras; a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras; while displaying the communication request interface, receiving, via the one or more input devices, a set of one or more inputs that includes a selection of the second selectable graphical user interface object; in response to receiving the set of one or more inputs that includes a selection of the second selectable graphical user interface object, selecting the first camera mode or the second camera mode for use; while displaying the communication request interface, detecting a change in a scene in a field-of-view of the one or more cameras; and in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting the representation of the field-of-view of the one or more cameras in the communication request interface.

2. The computer system of claim 1, wherein selecting the first camera mode or the second camera mode for use includes: in accordance with a determination that the first camera mode was selected for use when the second selectable graphical user interface object was selected, selecting the second camera mode for use; and in accordance with a determination that the second camera mode was selected for use when the second selectable graphical user interface object was selected, selecting the first camera mode for use.

3. The computer system of claim 1, the one or more programs further including instructions for:

receiving a selection of the first selectable graphical user interface object; and in response to receiving the selection of the first selectable graphical user interface object, displaying, via the display generation component, a live video communication interface for the live video communication session, wherein the live video communication interface includes the representation of the field-of-view of the one or more cameras having the first camera mode or second camera mode selected for use.

4. The computer system of claim 1, wherein: the detected change in the scene in the field-of-view of the one or more cameras includes a detected change in a set of attention-based factors for one or more subjects in the scene; and adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras includes adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the set of attention-based factors for the one or more subjects in the scene.

5. The computer system of claim 1, wherein: the detected change in the scene in the field-of-view of the one or more cameras includes a detected change in a number of subjects detected in the scene, and adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras includes adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the number of subjects detected in the scene.

6. The computer system of claim 5, wherein adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the number of subjects detected in the scene is based on a determination of whether a subject in the field-of-view is stationary.

7. The computer system of claim 1, wherein: the representation of the field-of-view of the one or more cameras has a first represented field-of-view before detecting the change in the scene in the field-of-view of the one or more cameras; the change in the scene in the field-of-view of the one or more cameras includes a detected movement of a third subject from a first portion of the field-of-view of the one or more cameras that corresponds to the first represented field-of-view to a second portion of the field-of-view of the one or more cameras that does not correspond to the first represented field-of-view; and adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras includes: in accordance with a determination that a fourth subject is not detected in the scene in the first portion of the field-of-view of the one or more cameras, adjusting the representation of the field-of-view from the first represented field-of-view to a second represented field-of-view that corresponds to the second portion of the field-of-view of the one or more cameras; and in accordance with a determination that the fourth subject is detected in the scene in the first portion of the field-of-view of the one or more cameras, forgoing adjusting the representation of the field-of-view from the first represented field-of-view to the second represented field-of-view.

8. The computer system of claim 1, wherein: the representation of the field-of-view of the one or more cameras has a third represented field-of-view before detecting the change in the scene in the field-of-view of the one or more cameras; the change in the scene in the field-of-view of the one or more cameras includes movement of a fifth subject from a third portion of the field-of-view of the one or more cameras that corresponds to the third represented field-of-view to a fourth portion of the field-of-view of the one or more cameras that does not correspond to the third represented field-of-view; and adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras includes: displaying the representation of the field-of-view of the one or more cameras having a fourth represented field-of-view in the communication request interface that

corresponds to the fourth portion of the field-of-view of the one or more cameras and includes a representation of the fifth subject.

9. The computer system of claim 1, wherein: the representation of the field-of-view of the one or more cameras has a first zoom value before detecting the change in the scene in the field-of-view of the one or more cameras; the change in the scene in the field-of-view of the one or more cameras includes movement of a sixth subject from a first position within the field-of-view of the one or more cameras that corresponds to the representation of the field-of-view and is a first distance from the one or more cameras to a second position within the field-of-view of the one or more cameras that corresponds to the representation of the field-of-view and is a threshold distance from the one or more cameras; and adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras includes: displaying the representation of the field-of-view of the one or more cameras having a second zoom value different from the first zoom value in the communication request interface.

10. The computer system of claim 1, wherein: the representation of the field-of-view of the one or more cameras has a fifth represented field-of-view before detecting the change in the scene in the field-of-view of the one or more cameras; the change in the scene in the field-of-view of the one or more cameras includes movement of one or more subjects detected in the scene; and adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras includes: in accordance with a determination that the one or more subjects have less than a threshold amount of movement for at least a threshold amount of time, displaying the representation of the field-of-view of the one or more cameras having a sixth represented field-of-view in the live video communication interface; and in accordance with a determination that the one or more subjects do not have less than the threshold amount of movement for at least the threshold amount of time, continuing displaying the representation of the field-of-view of the one or more cameras having the fifth represented field-of-view in the live video communication interface.

11. The computer system of claim 1, wherein displaying the field-of-view of the one or more cameras includes: displaying, via the display generation component, a representation of a first portion of the field-of-view of the one or more cameras and a representation of a second portion of the field-of-view of one or more cameras, including: in accordance with a determination that the first portion of the field-of-view of one or more cameras includes a detected feature of a respective type while a feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras, displaying the representation of the first portion of the field-of-view of one or more cameras with a reduced degree of compression than the representation of the second portion of the field-of-view of one or more cameras.

12. The computer system of claim 11, the one or more programs further including instructions for: in accordance with a determination that the detected feature of the respective type has moved from the first portion of the field-of-view of one or more cameras to the second portion of the field-of-view of one or more cameras and a feature of the respective type is not detected in the first portion of the field-of-view of one or more cameras, displaying, via the display generation component, the representation of the first portion the field-of-view of one or more cameras with an increased degree of compression than the representation of the second portion of the field-of-view of one or more cameras.

13. The computer system of claim 11, wherein: the detected feature of the respective type is a detected face; and displaying the representation of the second portion of the field-of-view of one or more cameras includes displaying the representation of the second portion of the field-of-view of one or more cameras having a lesser video quality than the representation of the first portion of the field-of-view of one or more cameras in accordance with a determination that the first portion of

the field-of-view of one or more cameras includes the detected face while a face is not detected in the second portion of the field-of-view of one or more cameras.

14. The computer system of claim 11, the one or more programs further including instructions for: in response to detecting a change in bandwidth for transmitting a representation of the field-of-view of one or more cameras while a feature of the respective type is detected in the first portion of the field-of-view of one or more cameras and while a feature of the respective type is not detected in the second portion of the field-of-view of one or more cameras, changing a degree of compression of the representation of the first portion of the field-of-view of one or more cameras by an amount that is less than an amount of change of a degree of compression of the representation of the second portion of the field-of-view of one or more cameras.

15. The computer system of claim 11, the one or more programs further including instructions for: in response to detecting a change in bandwidth for transmitting a representation of the field-of-view of one or more cameras while a feature of the respective type is not detected in the first portion of the field-of-view of one or more cameras and while a feature of the respective type is detected in the second portion of the field-of-view of one or more cameras, changing a degree of compression of the representation of the first portion of the field-of-view of one or more cameras by an amount that is more than an amount of change of a degree of compression of the representation of the second portion of the field-of-view of one or more cameras.

16. A non-transitory computer-readable storage medium storing one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices, the one or more programs including instructions for: displaying, via the display generation component, a communication request interface that includes concurrently displaying: a representation of a field-of-view of the one or more cameras; a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras; while displaying the communication request interface, receiving, via the one or more input devices, a set of one or more inputs that includes a selection of the second selectable graphical user interface object; in response to receiving the set of one or more inputs that includes a selection of the second selectable graphical user interface object, selecting the first camera mode or the second camera mode for use; while displaying the communication request interface, detecting a change in a scene in a field-of-view of the one or more cameras; and in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting the representation of the field-of-view of the one or more cameras in the communication request interface.

17. A method, comprising: at a computer system that is in communication with a display generation component, one or more cameras, and one or more input devices: displaying, via the display generation component, a communication request interface that includes concurrently displaying: a representation of a field-of-view of the one or more cameras; a first selectable graphical user interface object associated with a process for joining a live video communication session; and a second selectable graphical user interface object associated with a process for selecting between using a first camera mode for the one or more cameras and using a second camera mode for the one or more cameras; while displaying the communication request interface, receiving, via the one or more input devices, a set of one or more inputs that includes a selection of the second selectable graphical user interface object; in response to receiving the set of one or more inputs that includes a selection of the second selectable graphical user interface object, selecting the first camera mode or

the second camera mode for use; while displaying the communication request interface, detecting a change in a scene in a field-of-view of the one or more cameras; and in response to detecting the change in the scene in the field-of-view of the one or more cameras: in accordance with a determination that the first camera mode is selected for use, adjusting the representation of the field-of-view of the one or more cameras in the communication request interface based on the detected change in the scene in the field-of-view of the one or more cameras; and in accordance with a determination that the second camera mode is selected for use, forgoing adjusting the representation of the field-of-view of the one or more cameras in the communication request interface.
