

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280875

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ALLER; Jared et al.

AEROSOL DELIVERY DEVICE WITH IMPROVED MOUTHPIECES

Abstract

Disclosed are aerosol delivery devices for use with a removable and replaceable cartridge, where the device includes an improved mouthpiece, such as one that is removable or customizable. The device includes a holder defining a receiving chamber configured to receive a removable cartridge comprising an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto and a first aerosol passageway and a mouthpiece with a first end and a longitudinally opposed second end defining a second aerosol passageway, where the first end is configured to engage with a user's mouth and the second end is coupleable to the proximal end of the holder. The mouthpiece can be removed for cleaning and then reattached for continued use or, in some cases, a different mouthpiece may be attached to customize the user's experience.

Inventors: ALLER; Jared (Winston-Salem, NC), JACKSON; Thaddeus (Summerfield, NC), CLECKLEY; Karen H. (Kernersville, NC), RENNECKER; Daniel W. (Naperville, IL), NETTENSTROM; Matthew J. (Bartlett, IL), SCHENNUM; Steven M. (Plainfield, IL)

Applicant: R.J. Reynolds Tobacco Company (Winston-Salem, NC)

Family ID: 87974324

Appl. No.: 19/217057

Filed: May 23, 2025

Related U.S. Application Data

parent US division 17898839 20220830 parent-grant-document US 12329199 child US 19217057

Publication Classification

Int. Cl.: A24F40/42 (20200101); A24F40/46 (20200101); A24F40/50 (20200101)

U.S. Cl.:

CPC A24F40/42 (20200101); A24F40/46 (20200101); A24F40/50 (20200101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a divisional application of U.S. patent application Ser. No. 17/898,839, filed on Aug. 30, 2022, which is incorporated herein in its entirety by reference.

FIELD OF THE DISCLOSURE

[0002] The present disclosure relates to aerosol delivery devices and systems, such as smoking articles; and more particularly, to aerosol delivery devices and systems that utilize heat sources, such as combustible carbon-based ignition sources, for the production of an aerosol (e.g., smoking articles for purposes of yielding components of tobacco, tobacco extracts, nicotine, synthetic nicotine, non-nicotine flavoring, and other materials in an inhalable form, commonly referred to as heat-not-burn systems or electronic cigarettes). Components of such articles may be made or derived from tobacco, or those articles may be characterized as otherwise incorporating tobacco for human consumption, and which may be capable of vaporizing components of tobacco and/or other tobacco related materials to form an inhalable aerosol for human consumption.

BACKGROUND

[0003] Many smoking articles have been proposed through the years as improvements upon, or alternatives to, smoking products based upon combusting tobacco. Example alternatives have included devices wherein a solid or liquid fuel is combusted to transfer heat to tobacco or wherein a chemical reaction is used to provide such heat source. Examples include the smoking articles described in U.S. Pat. No. 9,078,473 to Worm et al., which is incorporated herein by reference in its entirety.

[0004] The point of the improvements or alternatives to smoking articles typically has been to provide the sensations associated with cigarette, cigar, or pipe smoking, without delivering considerable quantities of incomplete combustion and pyrolysis products. To this end, there have been proposed numerous smoking products, flavor generators, and medicinal inhalers which utilize electrical energy to vaporize or heat a volatile material, or attempt to provide the sensations of cigarette, cigar, or pipe smoking without burning tobacco to a significant degree. See, for example, the various alternative smoking articles, aerosol delivery devices and heat generating sources set forth in the background art described in U.S. Pat. No. 7,726,320 to Robinson et al.; and U.S. Pat. App. Pub. Nos. 2013/0255702 to Griffith, Jr. et al.; and 2014/0096781 to Sears et al., which are incorporated herein by reference. See also, for example, the various types of smoking articles, aerosol delivery devices and electrically powered heat generating sources referenced by brand name and commercial source in U.S. Pat. App. Pub. No. 2015/0220232 to Bless et al., which is incorporated herein by reference. Additional types of smoking articles, aerosol delivery devices and electrically powered heat generating sources referenced by brand name and commercial source are listed in U.S. Pat. App. Pub. No. 2015/0245659 to DePiano et al., which is also incorporated herein by reference in its entirety. Other representative cigarettes or smoking articles that have been described and, in some instances, been made commercially available include those described in U.S. Pat. No. 4,735,217 to Gerth et al.; U.S. Pat. Nos. 4,922,901, 4,947,874, and 4,947,875 to Brooks et al.; U.S. Pat. No. 5,060,671 to Counts et al.; U.S. Pat. No. 5,249,586 to Morgan et al.; U.S. Pat. No. 5,388,594 to Counts et al.; U.S. Pat. No. 5,666,977 to Higgins et al.; U.S. Pat. No.

6,053,176 to Adams et al.; U.S. Pat. No. 6,164,287 to White; U.S. Pat. No. 6,196,218 to Voges; U.S. Pat. No. 6,810,883 to Felter et al.; U.S. Pat. No. 6,854,461 to Nichols; U.S. Pat. No. 7,832,476 to Hon; U.S. Pat. No. 7,513,253 to Kobayashi; U.S. Pat. No. 7,726,320 to Robinson et al.; U.S. Pat. No. 7,896,006 to Hamano; U.S. Pat. No. 6,772,756 to Shayan; U.S. Pat. App. Pub. No. 2009/0095311 to Hon; U.S. Pat. App. Pub. Nos. 2006/0196518, 2009/0126745, and 2009/0188490 to Hon; U.S. Pat. App. Pub. No. 2009/0272379 to Thorens et al.; U.S. Pat. App. Pub. Nos. 2009/0260641 and 2009/0260642 to Monsees et al.; U.S. Pat. App. Pub. Nos. 2008/0149118 and 2010/0024834 to Oglesby et al.; U.S. Pat. App. Pub. No. 2010/0307518 to Wang; and WO 2010/091593 to Hon, which are incorporated herein by reference.

[0005] Various manners and methods for assembling smoking articles that possess a plurality of sequentially arranged segmented components have been proposed. See, for example, the various types of assembly techniques and methodologies set forth in U.S. Pat. No. 5,469,871 to Barnes et al. and U.S. Pat. No. 7,647,932 to Crooks et al.; and U.S. Pat. App. Pub. Nos. 2010/0186757 to Crooks et al.; 2012/0042885 to Stone et al., and 2012/00673620 to Conner et al.; each of which is incorporated by reference herein in its entirety.

[0006] Certain types of cigarettes that employ carbonaceous fuel elements have been commercially marketed under the brand names “Premier,” “Eclipse” and “Revo” by R. J. Reynolds Tobacco Company. See, for example, those types of cigarettes described in Chemical and Biological Studies on New Cigarette Prototypes that Heat Instead of Burn Tobacco, R. J. Reynolds Tobacco Company Monograph (1988) and Inhalation Toxicology, 12:5, p. 1-58 (2000). Additionally, a similar type of cigarette has been marketed in Japan by Japan Tobacco Inc. under the brand name “Steam Hot One.”

[0007] In some instances, some smoking articles, particularly those that employ a traditional paper wrapping material, are also prone to scorching of the paper wrapping material overlying an ignitable fuel source, due to the high temperature attained by the fuel source in proximity to the paper wrapping material. This can reduce enjoyment of the smoking experience for some consumers and can mask or undesirably alter the flavors delivered to the consumer by the aerosol delivery components of the smoking articles. In further instances, traditional types of smoking articles can produce relatively significant levels of gasses, such as carbon monoxide and/or carbon dioxide, during use (e.g., as products of carbon combustion). In still further instances, traditional types of smoking articles may suffer from poor performance with respect to aerosolizing the aerosol forming component(s).

[0008] As such, it would be desirable to provide smoking articles that address one or more of the technical problems sometimes associated with traditional types of smoking articles. In particular, it would be desirable to provide a smoking article that is easy to use and that provides reusable and/or replaceable components.

BRIEF SUMMARY

[0009] In various implementations, the present disclosure relates to aerosol delivery devices for use with removable and replaceable cartridges (i.e., consumables), where the devices include a removable mouthpiece. The mouthpiece may be removable for cleaning and reuse or interchangeable for customization purposes. The present disclosure includes, without limitation, the following example implementations.

[0010] Embodiment 1: An aerosol delivery device comprising a holder having a main body defining a proximal end and a distal end, where the main body further defines a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body; a removable mouthpiece including a first end and a longitudinally opposed second end with a second aerosol passageway extending longitudinally therebetween, where the first end is configured to engage with a user's mouth and the second end is coupleable to the proximal end of the holder; and a collar disposed between the holder and the mouthpiece, where the collar comprises a first end configured to sealingly engage the proximal end of the

holder, a second end configured to sealingly engage the second end of the mouthpiece, and a first channel extending therethrough that is configured to fluidly couple the first and second aerosol passageways. The collar may include a second channel extending therethrough. The second channel configured for access to a charging port. In some embodiments, the removable cartridge comprises an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto.

[0011] Embodiment 2: The aerosol delivery device of the preceding embodiment, wherein the collar further comprises a base portion defining an opening in fluid communication with the first channel and having a first sealing mechanism disposed about an exterior surface thereof, the base portion sized and shaped to engage an opening in the proximal end of the holder; and a body portion defining an opening in fluid communication with the first channel and having a second sealing mechanism disposed about an exterior surface thereof, the body portion sized and shaped to engage a recess disposed within the second end of the mouthpiece.

[0012] Embodiment 3: The aerosol delivery device of any of Embodiments 1 and 2, or any combination thereof, wherein the base portion is disposed within the proximal end of the holder. In some cases, the base portion is fully disposed within the holder so as to not be visible when the device is assembled.

[0013] Embodiment 4: The aerosol delivery device of any of Embodiments 1 to 3, or any combination thereof, wherein the base portion is coupled to the holder via at least one fastener.

[0014] Embodiment 5: The aerosol delivery device of any of Embodiments 1 to 4, or any combination thereof, further comprising an inner housing configured to secure one or more components therein, wherein the base portion is secured to the inner housing via at least one fastener.

[0015] Embodiment 6: The aerosol delivery device of any of Embodiments 1 to 5, or any combination thereof, wherein the body portion is disposed within the recess of the mouthpiece. In some cases, the body portion is fully disposed within the mouthpiece so as to not be visible when the device is assembled.

[0016] Embodiment 7: The aerosol delivery device of any of Embodiments 1 to 6, or any combination thereof, wherein the first sealing mechanism comprises an O-ring disposed within a groove defined by the exterior surface of the base portion.

[0017] Embodiment 8: The aerosol delivery device of any of Embodiments 1 to 7, or any combination thereof, wherein the second sealing mechanism comprises at least one O-ring disposed within one or more grooves defined by the exterior surface of the body portion.

[0018] Embodiment 9: The aerosol delivery device of any of Embodiments 1 to 8, or any combination thereof, further comprising an actuator assembly coupled to the holder and configured to eject the removable cartridge therefrom.

[0019] Embodiment 10: The aerosol delivery device of any of Embodiments 1 to 9, or any combination thereof, further comprising a power source disposed within the main body.

[0020] Embodiment 11: The aerosol delivery device of any of Embodiments 1 to 10, or any combination thereof, further comprising an inner housing disposed within the main body of the holder; and a printed circuit board in electrical communication with the power source and comprising a controller, wherein the inner housing is configured to receive the power source and the printed circuit board.

[0021] Embodiment 12: The aerosol delivery device of any of Embodiments 1 to 11, or any combination thereof, wherein the printed circuit board further comprises a charging port and the printed circuit board is oriented within the inner housing so that the charging port is disposed at the proximal end of the holder.

[0022] Embodiment 13: The aerosol delivery device of any of Embodiments 1 to 12, or any combination thereof, wherein the collar further defines a second channel extending therethrough, the second channel configured to at least partially house or receive the charging port so that the

charging port is accessible after removal of the mouthpiece.

[0023] Embodiment 14: The aerosol delivery device of any of Embodiments 1 to 13, or any combination thereof, wherein the collar further comprises a base portion defining an opening in fluid communication with the first channel, the base portion sized and shaped to engage an opening in the proximal end of the holder; and a body portion defining an opening in fluid communication with the first channel and having a sealing mechanism disposed about an exterior surface thereof, the body portion sized and shaped to engage a recess disposed within the second end of the mouthpiece.

[0024] Embodiment 15: The aerosol delivery device of any of Embodiments 1 to 14, or any combination thereof, wherein the base portion is configured to engage the opening in the proximal end of the holder via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement.

[0025] Embodiment 16: The aerosol delivery device of any of Embodiments 1 to 15, or any combination thereof, wherein the sealing mechanism comprises at least one O-ring disposed within one or more grooves defined by the exterior surface of the body portion.

[0026] Embodiment 17: The aerosol delivery device of any of Embodiments 1 to 16, or any combination thereof, further comprising an inner housing disposed within the main body of the holder and configured to secure one or more components therein, wherein the inner housing further defines at least a portion of the first aerosol passageway and the base portion of the collar includes a stem extending distally therefrom and configured to engage the at least a portion of the first aerosol passageway in the inner housing.

[0027] Embodiment 18: An aerosol delivery device comprising a holder comprising a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body and a removable mouthpiece comprising a hollow body including a first end and a longitudinally opposed second end with a stem disposed within the hollow body and extending from the first end to the second end, the stem defining a second aerosol passageway extending therethrough, wherein the first end is configured to engage with a user's mouth and the second end is configured to engage the proximal end of the holder. In some embodiments, the removable cartridge comprises an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto. In some embodiments, a central axis of the stem is offset from a central axis of the mouthpiece.

[0028] Embodiment 19: The aerosol delivery device of the preceding embodiment, wherein the longitudinally opposed second end is configured to engage an opening in the proximal end of the holder via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement.

[0029] Embodiment 20: The aerosol delivery device of any of Embodiments 18 and 19, or any combination thereof, wherein the stem is sealingly engaged with the first aerosol passageway in the holder.

[0030] Embodiment 21: The aerosol delivery device of any of Embodiments 18 to 20, or any combination thereof, wherein the stem includes a sealing mechanism disposed about an exterior surface thereof.

[0031] Embodiment 22: The aerosol delivery device of any of Embodiments 18 to 21, or any combination thereof, wherein the sealing mechanism comprises an O-ring disposed within a groove defined by the exterior surface of the stem.

[0032] Embodiment 23: The aerosol delivery device of any of Embodiments 18 to 22, or any combination thereof, further comprising an inner housing disposed within the main body of the holder and defining at least a portion of the first aerosol passageway, wherein the stem is partially disposed within the inner housing and in fluid communication with the at least a portion of the first

aerosol passageway in the inner housing.

[0033] Embodiment 24: The aerosol delivery device of any of Embodiments 18 to 23, or any combination thereof, further comprising an inner housing disposed within the main body of the holder and comprising a retention structure disposed on a proximal end thereof, wherein the longitudinally opposed second end of the mouthpiece defines a mating retention structure configured to engage the retention structure on the inner housing.

[0034] Embodiment 25: The aerosol delivery device of any of Embodiments 18 to 24, or any combination thereof, wherein the mouthpiece further comprises an insert removably disposed within a recess formed within the first end of the mouthpiece.

[0035] Embodiment 26: The aerosol delivery device of any of Embodiments 18 to 25, or any combination thereof, wherein the insert is configured to reduce an aerosol outlet in the mouthpiece.

[0036] Embodiment 27: An aerosol delivery device comprising a holder having a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body; a mouthpiece including a first end and a longitudinally opposed second end with a second aerosol passageway extending longitudinally therebetween, wherein the first end is configured to engage with a user's mouth and the second end is configured to engage the proximal end of the holder; and a removable flow restrictor comprising an outer surface configured to be removably secured within the holder and an inner surface defining a third aerosol passageway.

[0037] Embodiment 28: The aerosol delivery device of the preceding embodiment, wherein the flow restrictor is configured to be at least partially disposed within the first aerosol passageway, the second aerosol passageway, or both.

[0038] Embodiment 29: The aerosol delivery device of any of Embodiments 27 and 28, or any combination thereof, wherein the removable flow restrictor is configured to sealingly engage the first aerosol passageway, the second aerosol passageway, or both.

[0039] Embodiment 30: The aerosol delivery device of any of Embodiments 27 to 29, or any combination thereof, wherein the flow restrictor comprises a body portion and a lip portion disposed at a proximal end thereof, the lip portion configured to engage the proximal end of the main body.

[0040] Embodiment 31: The aerosol delivery device of any of Embodiments 27 to 30, or any combination thereof, wherein the body portion is disposed within the first aerosol passageway.

[0041] Embodiment 32: The aerosol delivery device of any of Embodiments 27 to 31, or any combination thereof, wherein the lip portion is disposed within the second aerosol passageway.

[0042] Embodiment 33: The aerosol delivery device of any of Embodiments 27 to 32, or any combination thereof, wherein the removable flow restrictor is configured to provide fluid communication between the first aerosol passageway and the second aerosol passageway.

[0043] Embodiment 34: The aerosol delivery device of any of Embodiments 27 to 33, or any combination thereof, wherein the inner surface of the flow restrictor is tapered along a length thereof.

[0044] Embodiment 35: The aerosol delivery device of any of Embodiments 27 to 34, or any combination thereof, wherein the inner surface of the removable flow restrictor defines an orifice configured to provide a pressure drop between the first aerosol passageway and the second aerosol passageway.

[0045] Embodiment 36: The aerosol delivery device of any of Embodiments 27 to 35, or any combination thereof, wherein the mouthpiece comprises a body portion configured to engage the proximal end of the main body and a hollow stem extending therethrough, the stem at least partially defining the second aerosol passageway and configured to receive the flow restrictor therein.

[0046] Embodiment 37: The aerosol delivery device of any of Embodiments 27 to 36, or any

combination thereof, further comprising a plurality of interchangeable removable flow restrictors. The flow restrictors may comprise different sizes and shapes to, for example, allow a user to customize their experience by optimizing a vapor flow rate, pressure drop, flavoring, or other sensation.

[0047] Embodiment 38: The aerosol delivery device of any of Embodiments 27 to 37, or any combination thereof, further comprising an access door assembly sealingly coupled to the main body and defining the receiving chamber, where the access door assembly is movable between an open configuration providing access to the receiving chamber for loading the removable cartridge therein and a closed configuration securing the cartridge in fluid communication with first aerosol passageway.

[0048] Embodiment 39: The aerosol delivery device of any of Embodiments 27 to 38, or any combination thereof, wherein the access door assembly is pivotably coupled to the holder.

[0049] Embodiment 40: The aerosol delivery device of any of Embodiments 1 to 39, or any combination thereof, further comprising a latching mechanism configured to secure the access door assembly in the closed configuration.

[0050] Embodiment 41: The aerosol delivery device of any of Embodiments 27 to 40, or any combination thereof, further comprising an actuator assembly configured to release the access door assembly from the closed configuration. For example, the access door assembly is biased into an open configuration and the actuator is a spring-loaded slide button that includes a latching edge that engages an inner surface of the holder to maintain the access door in the closed configuration until slid forward.

[0051] Embodiment 42: The aerosol delivery device of any of Embodiments 27 to 41, or any combination thereof, further comprising a power source disposed within the main body and a pair of ignitor contacts in electrical communication with the power supply, disposed proximate the distal end of the main body, and configured to engage an ignitable heat source portion of the removable cartridge when the removable cartridge is secured within the receiving chamber.

[0052] Embodiment 43: The aerosol delivery device of any of Embodiments 27 to 42, or any combination thereof, wherein the holder further comprises a printed circuit board disposed therein and in electrical communication with the power source and comprising a charging port, wherein the printed circuit board is oriented so that the charging port is disposed at the distal end of the main body.

[0053] Embodiment 44: The aerosol delivery device of any of Embodiments 27 to 43, or any combination thereof, further comprising a button assembly configured to deliver electrical energy to the ignitable heat source when actuated.

[0054] Embodiment 45: The aerosol delivery device of any of Embodiments 27 to 44, or any combination thereof, wherein the removable cartridge comprises an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto.

[0055] Embodiment 46: The aerosol delivery device of any of Embodiments 27 to 45, or any combination thereof, wherein the access door assembly includes an insert disposed therein and configured to receive the cartridge and provide thermal insulation thereto.

[0056] Embodiment 47: An aerosol delivery device comprising a holder having a main body defining a proximal end and a distal end, where the main body further defines a receiving chamber configured to receive a removable cartridge (e.g., one comprising an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto) and a first aerosol passageway that extends through at least a portion of the main body; a mouthpiece including a first end and a longitudinally opposed second end with a second aerosol passageway extending longitudinally therebetween, wherein the first end is configured to engage with a user's mouth and the second end is configured to engage the proximal end of the holder; and an inner housing disposed within the

main body of the holder and defining a first port disposed proximate a first end of the inner housing, a second port disposed proximate a second end of the inner housing, and a first channel disposed in an outer surface of the inner housing and fluidly coupling the first port and the second port to form a third aerosol passageway, wherein the first port is in fluid communication with the first aerosol passageway, the second port is in fluid communication with the second aerosol passageway. The first, second, and third aerosol passageways are configured to form a continuous vapor path from the distal end of the main body to the first end of the mouthpiece for passing an aerosol generated from the removable cartridge to a user.

[0057] Embodiment 48: The aerosol delivery device of the preceding embodiment, wherein the inner housing defines a second channel disposed in the outer surface thereof and oriented opposite of the first channel.

[0058] Embodiment 49: The aerosol delivery device of any of Embodiments 47 and 48, or any combination thereof, wherein the first and second channels merge at the first port and the second port.

[0059] Embodiment 50: The aerosol delivery device of any of Embodiments 47 to 49, or any combination thereof, wherein the inner housing is disposed within the main body so that an inner surface of the holder encloses the first and second channels.

[0060] Embodiment 51: The aerosol delivery device of any of Embodiments 47 to 50, or any combination thereof, further comprising an actuator assembly coupled to the holder and configured to eject the removable cartridge therefrom.

[0061] Embodiment 52: The aerosol delivery device of any of Embodiments 47 to 51, or any combination thereof, wherein the actuator assembly comprises a slider body slidably disposed within the main body of the holder and configured to sealingly engage the first end of the inner housing, the slider body defining a receptacle configured to at least partially receive the removable cartridge and an inner stem engageable with one end of the removable cartridge and defining a fourth aerosol passageway therethrough configured to pass the aerosol generated from the removable cartridge, wherein the first, second, third, and fourth aerosol passageways are configured to define the continuous vapor path from the distal end of the main body to the first end of the mouthpiece.

[0062] Embodiment 53: The aerosol delivery device of any of Embodiments 47 to 52, or any combination thereof, further comprising a collar disposed between the holder and the mouthpiece, the collar comprising a first end configured to sealingly engage the proximal end of the holder, a second end configured to sealingly engage the second end of the mouthpiece, and defining a first channel therethrough fluidly coupling the third aerosol passageway and the second aerosol passageway.

[0063] Embodiment 54: The aerosol delivery device of any of Embodiments 47 to 53, or any combination thereof, wherein the mouthpiece is removable

[0064] Embodiment 55: The aerosol delivery device of any of Embodiments 47 to 54, or any combination thereof, further comprising a power source disposed within the main body; and a printed circuit board in electrical communication with the power source and comprising a controller, wherein the inner housing defines a cavity configured to receive the power source and the printed circuit board therein. In some implementations, the vapor splits in the inner housing so as to travel around the cavity and any electronics disposed therein.

[0065] Embodiment 56: The aerosol delivery device of any of Embodiments 48 to 55, or any combination thereof, wherein the printed circuit board further comprises a charging port and the printed circuit board is oriented within the inner housing so that the charging port is disposed at the proximal end of the holder.

[0066] Embodiment 57: An aerosol delivery device comprising a holder having a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at

least a portion of the main body, and a mouthpiece assembly comprising a mouthpiece including a first end configured to engage with a user's mouth and a longitudinally opposed second end configured to engage the proximal end of the holder with a second aerosol passageway extending between the first and second ends, wherein a central longitudinal axis of the second aerosol passageway is offset from a central longitudinal axis of the first aerosol passageway and the first and second aerosol passageways define a unitary offset vapor path from the distal end of the main body to the first end of the mouthpiece for passing an aerosol generated from the removable cartridge to a user.

[0067] Embodiment 58: The aerosol delivery device of the preceding embodiment, wherein the mouthpiece assembly further comprises an insert at least partially disposed within a recess formed within the second end of the mouthpiece and defining a third aerosol passageway configured to fluidly couple the first aerosol passageway and the second aerosol passageway.

[0068] Embodiment 59: The aerosol delivery device of any of Embodiments 57 and 58, or any combination thereof, further comprising an access door assembly sealingly coupled to the main body and defining the receiving chamber, wherein the access door assembly is movable between an open configuration providing access to the receiving chamber for loading the removable cartridge therein and a closed configuration securing the cartridge in fluid communication with the first aerosol passageway.

[0069] Embodiment 60: The aerosol delivery device of any of Embodiments 57 to 59, or any combination thereof, wherein the access door assembly is pivotably coupled to the holder.

[0070] Embodiment 61: An aerosol delivery device comprising a holder having a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body and a removable mouthpiece comprising a hollow body including a first end and a longitudinally opposed second end with an offset stem disposed within the hollow body and extending from the first end to the second end, the offset stem defining a second aerosol passageway extending therethrough, wherein the first end is configured to engage with a user's mouth, the second end is configured to engage the proximal end of the holder, and the offset stem is sealingly engaged with the first aerosol passageway in the holder to define a linear vapor pathway.

[0071] Embodiment 62: An aerosol delivery device comprising a holder having an upper body portion and a lower body portion, each defining a proximal end and a distal end, wherein: the lower body portion further defines a receiving chamber disposed in the proximal end thereof and configured to receive a removable cartridge comprising an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto and the upper body portion further defines a first aerosol passageway extending therethrough and comprises a sliding actuator assembly slidably disposed within the first aerosol passageway, the sliding actuator configured to eject the removable cartridge from the lower body portion, wherein the upper body portion and the lower body portion are coupled together so as to be movable between an open configuration and a closed configuration; and a mouthpiece including a first end and a longitudinally opposed second end with a second aerosol passageway extending longitudinally therebetween, wherein the first end is configured to engage with a user's mouth and the second end is configured to engage the proximal end of the upper body portion, wherein the first and second aerosol passageways are configured to define a linear vapor path from the distal end of the lower body portion to the first end of the mouthpiece for passing the aerosol generated from the removable cartridge to a user when in the closed configuration.

[0072] Embodiment 63: The aerosol delivery device of the preceding embodiment, wherein the sliding actuator assembly comprises a tubular body defining a third aerosol passageway and configured to slide along a portion of the upper body portion in a first direction and a second direction, wherein the tubular body comprises a longitudinally oriented baffle extending inwardly

from an interior wall thereof, where the baffle divides the aerosol traveling through the third aerosol passageway portion of the linear vapor path.

[0073] Embodiment 64: The aerosol delivery device of any of Embodiments 62 and 63, or any combination thereof, wherein the sliding actuator assembly comprises a tubular body defining a third aerosol passageway and configured to slide along a portion of the upper body portion in a first direction and a second direction; a first protrusion extending from an outer surface of the tubular body and configured to extend through an opening in a wall of the upper body portion to provide for moving the tubular body in the first and second directions; and a second protrusion extending from a distal end of the tubular body and configured to engage the removable cartridge so as to advance the removable cartridge through the distal end of the lower body portion when the tubular body is moved in the first or second direction.

[0074] Embodiment 65: The aerosol delivery device of any of Embodiments 62 to 64, or any combination thereof, wherein one or more portions of the first protrusion, the second protrusion, or both extend into the third aerosol passageway defined by the tubular body so that the aerosol generated by the cartridge is split by the one or more portions when traveling through the tubular body.

[0075] Embodiment 66: The aerosol delivery device of any of Embodiments 62 to 65, or any combination thereof, wherein the sliding actuator further comprises a sealing arrangement for sealingly engaging an internal surface of the upper body portion.

[0076] Embodiment 67: The aerosol delivery device of any of Embodiments 62 to 66, or any combination thereof, further comprising a locking mechanism disposed on at least one of the lower body portion or the upper body portion and configured to maintain the device in the closed configuration.

[0077] Embodiment 68: The aerosol delivery device of any of Embodiments 62 to 67, or any combination thereof, further comprising a sealing mechanism disposed between the proximal end of the lower body portion and the distal end of the upper body portion and configured to seal the receiving chamber with the first aerosol passageway so as to prevent leakage from the vapor path.

[0078] Embodiment 69: The aerosol delivery device of any of Embodiments 62 to 68, or any combination thereof, wherein the lower body portion comprises a window disposed therein and configured to provide a view of at least a portion of the removable cartridge.

[0079] Embodiment 70: The aerosol delivery device of any of Embodiments 62 to 69, or any combination thereof, wherein the lower body portion is rotatable relative to the upper body portion to expose the receiving chamber and load the removable cartridge therein.

[0080] Embodiment 71: An aerosol delivery device comprising a holder having a main body defining a proximal end and a distal end, where the main body further defines a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body and a removable mouthpiece that comprises a first portion defined by a first end and a longitudinally opposed second end and a second portion that extends from the longitudinally opposed second end, wherein the first and second portions define a second aerosol passageway extending therethrough, the first end of the first portion is configured to engage with a user's mouth, the second end of the first portion is configured to engage with the proximal end of the holder, and the second portion is configured to extend within the holder. In some embodiments, the removable cartridge comprises an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto

[0081] Embodiment 72: The aerosol delivery device of the preceding embodiment, wherein the second end of the first portion is configured to engage the opening in the proximal end of the holder via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement.

[0082] Embodiment 73: The aerosol delivery device of any of Embodiments 71 and 72, or any

combination thereof, wherein the second portion of the mouthpiece is sealingly engaged with the first aerosol passageway in the holder.

[0083] Embodiment 74: The aerosol delivery device of any of Embodiments 71 to 73, or any combination thereof, wherein the second portion of the mouthpiece includes a scaling mechanism disposed about an exterior surface thereof.

[0084] Embodiment 75: The aerosol delivery device of any of Embodiments 71 to 74, or any combination thereof, wherein the sealing mechanism comprises an O-ring disposed within a groove defined by the exterior surface of the second portion of the mouthpiece.

[0085] Embodiment 76: The aerosol delivery device of any of Embodiments 71 to 75, or any combination thereof further comprising an actuator assembly at least partially disposed within the main body of the holder and configured to eject the removable cartridge therefrom.

[0086] Embodiment 77: The aerosol delivery device of any of Embodiments 71 to 76, or any combination thereof, wherein the actuator assembly comprises a sliding body that defines at least a portion of the first aerosol passageway and the second portion of the mouthpiece is slidably disposed within the sliding body and in fluid communication with the at least a portion of the first aerosol passageway in the sliding body.

[0087] Embodiment 78: The aerosol delivery device of any of Embodiments 71 to 77, or any combination thereof further comprising an inner housing disposed within the main body of the holder and comprising a first retention structure disposed on a proximal end thereof, wherein the second end of the first portion of the mouthpiece defines a mating retention structure (e.g., a gap or groove disposed about the inner perimeter of the second end) configured to engage the retention structure on the inner housing. In some implementations, the inner housing may include a second retention structure configured to mate with the holder and secure the inner housing therein or the first retention structure may be disposed on the proximal end of the holder.

[0088] Embodiment 79: The aerosol delivery device of any of Embodiments 71 to 78, or any combination thereof, wherein a central axis of the second portion of the mouthpiece is offset from a central axis of the first portion of the mouthpiece.

[0089] Embodiment 80: An aerosol delivery device including a holder comprising a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge comprising an aerosol precursor composition configured to form an aerosol upon application of heat thereto and a removable mouthpiece comprising an elongate body portion defined by a first end and a longitudinally opposed second end and defining an aerosol passageway extending therethrough, a first retention mechanism disposed about an exterior surface of the elongate body portion, the first retention mechanism configured to removably secure the second end of the mouthpiece within the holder, and a second retention mechanism disposed within a receptacle defined by the second end of the elongate body member, the second retention mechanism configured to removably secure a portion of the cartridge therein, wherein the first end of the mouthpiece is configured to engage with a user's mouth. In some implementations, the first retention mechanism is located proximate the first end of the elongate body portion.

[0090] Embodiment 81: The aerosol delivery device of the preceding embodiment, further comprising an inner housing disposed within the main body of the holder and defining a passageway therethrough configured to receive a portion of the mouthpiece therein.

[0091] Embodiment 82: The aerosol delivery device of any of Embodiments 80 and 81, or any combination thereof further comprising a pair of ignitor contacts disposed within the holder and proximate the distal end thereof, wherein the contacts are configured to receive an ignitable heat source portion of the cartridge therebetween.

[0092] Embodiment 83: The aerosol delivery device of any of Embodiments 80 to 82, or any combination thereof, wherein the inner housing comprises a stop configured to limit insertion of the mouthpiece so as to operatively engage the ignitable heat source with the ignitor

contacts.

[0093] Embodiment 84: The aerosol delivery device of any of Embodiments 80 to 83, or any combination thereof, wherein the first retention mechanism is configured to sealingly engage with the passageway in the inner housing.

[0094] Embodiment 85: The aerosol delivery device of any of Embodiments 80 to 84, or any combination thereof, wherein the first retention mechanism includes an elastomeric seal disposed about an exterior surface thereof and configured to frictionally engage with the inner housing passageway.

[0095] Embodiment 86: The aerosol delivery device of any of Embodiments 80 to 85, or any combination thereof, wherein the second retention mechanism is configured to sealingly engage with a substrate portion of the cartridge.

[0096] Embodiment 87: The aerosol delivery device of any of Embodiments 80 to 86, or any combination thereof, wherein the second retention mechanism includes an elastomeric seal disposed about an interior surface thereof and configured to frictionally engage with the cartridge.

[0097] Embodiment 88: The aerosol delivery device of any of Embodiments 80 to 87, or any combination thereof further comprising an ignitor push button configured to activate the ignitor contacts thereby igniting the heat source when pressed by a user.

[0098] Embodiment 89: The aerosol delivery device of any of Embodiments 80 to 88, or any combination thereof, wherein the ignitor contacts will be deactivated when the ignitor push button is released.

[0099] Embodiment 90: The aerosol delivery device of any of Embodiments 80 to 89, or any combination thereof, wherein the ignitor contacts will be deactivated after a set time (e.g., about 2 to 60 seconds, about 5 to 30 seconds, or about 20 seconds), either after the ignitor push button is activated or after it is released.

[0100] Embodiment 91: An aerosol delivery device including a holder comprising a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge comprising an aerosol precursor composition configured to form an aerosol upon application of heat thereto and a removable mouthpiece configured to engage the proximal end of the holder. The mouthpiece comprises a first portion comprising an elongate body defined by a first end and a longitudinally opposed second end and defining a passageway extending therethrough; a second portion defined by a first end and a longitudinally opposed second end and defining a first aerosol passageway therethrough, wherein the first end of the second portion is configured to engage with a user's mouth and the second end is partially disposed within the passageway of the first portion of the mouthpiece proximate the first end of the first portion; a slider body defined by a first end and a longitudinally opposed second end and defining a second aerosol passageway therethrough, wherein the slider body is slidably disposed within the first portion of the mouthpiece and the first end of the slider body is coupled to the second end of the second portion of the mouthpiece and the second end of the slider body is configured to engage the removable cartridge; an inner tubular body defined by a first end and a longitudinally opposed second end and defining a receptacle comprising a first biasing mechanism disposed therein, the receptacle configured to at least partially receive the slider body, the slider body slidably coupled to the inner tubular body, wherein the second end of the inner tubular body is configured to engage the first portion of the mouthpiece proximate the second end of the first portion and the biasing mechanism is configured to maintain the slider body in a loading configuration; and an outlet guide coupled to the second end of the first portion of the mouthpiece and partially received within the second end of the inner tubular body, wherein the outlet guide defines a cavity configured to sealingly engage and removably secure the removable cartridge therein. The slider body may be configured to slide along a length of the first portion of the mouthpiece in a first direction and a second direction.

[0101] Embodiment 92: The aerosol delivery device of any of Embodiments 1 to 91, or any

combination thereof, further comprising the removable cartridge. The removable cartridge comprises an ignitable heat source and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto.

[0102] Embodiment 93: The aerosol delivery device of any of Embodiments 1 to 92, or any combination thereof, wherein the holder comprises a window disposed therein, the window configured to provide a view of at least a portion of the removable cartridge.

[0103] These and other features, aspects, and advantages of the disclosure will be apparent from a reading of the following detailed description together with the accompanying drawings, which are briefly described below. The invention includes any combination of two, three, four, or more of the above-noted embodiments as well as combinations of any two, three, four, or more features or elements set forth in this disclosure, regardless of whether such features or elements are expressly combined in a specific embodiment description herein. This disclosure is intended to be read holistically such that any separable features or elements of the disclosed invention, in any of its various aspects and embodiments, should be viewed as intended to be combinable unless the context clearly dictates otherwise.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0104] Having thus described the disclosure in the foregoing general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

[0105] FIGS. 1A and 1B illustrate a perspective view and a cross-sectional perspective view, respectively, of an aerosol delivery device comprising a removable mouthpiece and a removable cartridge, with an improved vapor path, according to one implementation of the present disclosure;

[0106] FIG. 2 illustrates an exploded view of the aerosol delivery device of FIG. 1A, according to one implementation of the present disclosure;

[0107] FIGS. 3A and 3B illustrate a cross-sectional side view and a pictorial perspective view, respectively, of the aerosol delivery device of FIG. 1A, according to one implementation of the present disclosure;

[0108] FIGS. 4A-4C illustrate a series of perspective views of the mouthpiece end of the aerosol delivery device of FIG. 1A, according to one implementation of the present disclosure;

[0109] FIG. 5 illustrates a partially exploded perspective view of the aerosol delivery device of FIG. 1A, according to one implementation of the present disclosure;

[0110] FIGS. 6A and 6B illustrate a cross-sectional side view and a cross-sectional perspective view, respectively, of a portion of the aerosol delivery device of FIG. 1A with an alternative removable mouthpiece configuration, according to one implementation of the present disclosure;

[0111] FIG. 7A illustrates an exploded view of the proximal end of the aerosol delivery device of FIG. 6A, according to one implementation of the present disclosure;

[0112] FIG. 7B illustrates a partially exploded perspective view of the aerosol delivery device of FIG. 6A, according to one implementation of the present disclosure;

[0113] FIGS. 8A and 8B illustrate a perspective view and a cross-sectional perspective view, respectively, of an alternative aerosol delivery device comprising a removable mouthpiece and a removable cartridge, according to one implementation of the present disclosure;

[0114] FIG. 9 illustrates an exploded view of the aerosol delivery device of FIG. 8A, according to one implementation of the present disclosure;

[0115] FIG. 10 illustrates an enlarged perspective end view of the aerosol delivery device of FIG. 8A, according to one implementation of the present disclosure;

[0116] FIGS. 11A and 11B illustrate a perspective view and a cross-sectional side view, respectively, of an alternative aerosol delivery device comprising a removable cartridge and

defining an improved vapor path, according to one implementation of the present disclosure;

[0117] FIG. 12 illustrates an exploded view of the aerosol delivery device of FIG. 11A, according to one implementation of the present disclosure;

[0118] FIG. 13 illustrates an enlarged cross-sectional view of the mouthpiece end of the aerosol delivery device of FIG. 11A, according to one implementation of the present disclosure;

[0119] FIGS. 14A and 14B illustrate a perspective view and a cross-sectional side view, respectively, of an aerosol delivery device comprising a removable flow restrictor, according to one implementation of the present disclosure;

[0120] FIG. 15 illustrates an exploded perspective view of the aerosol delivery device of FIG. 14A, according to one implementation of the present disclosure;

[0121] FIGS. 16A and 16B illustrate an end view and a cross-sectional side view, respectively, of a removable flow restrictor for use in an aerosol delivery device, according to one implementation of the present disclosure;

[0122] FIGS. 17A-17C illustrate a series of perspective views of the aerosol delivery device of FIG. 14A in various states or operation, according to one implementation of the present disclosure;

[0123] FIGS. 18A and 18B illustrate a perspective view and a cross-sectional perspective view, respectively, of another alternative aerosol delivery device comprising a removable cartridge and defining an improved vapor path, according to one implementation of the present disclosure;

[0124] FIG. 19 illustrates an exploded view of the aerosol delivery device of FIG. 18A, according to one implementation of the present disclosure;

[0125] FIGS. 20A-20C illustrate a perspective view and two cross-sectional perspective views, respectively, of the aerosol delivery device of FIG. 18A in different operational stages, according to one implementation of the present disclosure;

[0126] FIG. 21 illustrates a perspective view of a removable cartridge, according to one implementation of the present disclosure; and

[0127] FIG. 22 illustrates a longitudinal cross-section view of a removable cartridge, according to one implementation of the present disclosure.

DETAILED DESCRIPTION

[0128] Some implementations of the present disclosure will now be described more fully hereinafter with reference to the accompanying figures, in which some, but not all implementations of the disclosure are shown. Indeed, various implementations of the disclosure may be embodied in many different forms and should not be construed as limited to the implementations set forth herein; rather, these example implementations are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. Like reference numerals refer to like elements throughout.

[0129] Unless specified otherwise or clear from context, references to first, second or the like should not be construed to imply a particular order. A feature described as being above another feature (unless specified otherwise or clear from context) may instead be below, and vice versa; and similarly, features described as being to the left of another feature else may instead be to the right, and vice versa. Also, while reference may be made herein to quantitative measures, values, geometric relationships or the like, unless otherwise stated, any one or more if not all of these may be absolute or approximate to account for acceptable variations that may occur, such as those due to engineering tolerances or the like.

[0130] As used herein, unless specified otherwise or clear from context, the “or” of a set of operands is the “inclusive or” and thereby true if and only if one or more of the operands is true, as opposed to the “exclusive or” which is false when all of the operands are true. Thus, for example, “[A] or [B]” is true if [A] is true, or if [B] is true, or if both [A] and [B] are true. Further, the articles “a” and “an” mean “one or more,” unless specified otherwise or clear from context to be directed to a singular form. Furthermore, it should be understood that unless otherwise specified, the terms “data,” “content,” “digital content,” “information,” and similar terms may be at times

used interchangeably. Additionally, where multiples of the same components are described, the multiples may be referred to individually (e.g., ##a, ##b, ##c, etc.) or collectively (##).

[0131] The present disclosure provides descriptions of articles (and the assembly and/or manufacture thereof) in which a material is heated (preferably without combusting the material to any significant degree) to form an aerosol and/or an inhalable substance; such articles most preferably being sufficiently compact to be considered “hand-held” devices. In some aspects, the articles are characterized as smoking articles. As used herein, the term “smoking article” is intended to mean an article and/or device that provides many of the sensations (e.g., inhalation and exhalation rituals, types of tastes or flavors, organoleptic effects, physical feel, use rituals, visual cues such as those provided by visible aerosol, and the like) of smoking a cigarette, cigar, or pipe, without any substantial degree of combustion of any component of that article and/or device. As used herein, the term “smoking article” does not necessarily mean that, in operation, the article or device produces smoke in the sense of an aerosol resulting from by-products of combustion or pyrolysis of tobacco, but rather, that the article or device yields vapors (including vapors within aerosols that are considered to be visible aerosols that might be considered to be described as smoke-like) resulting from volatilization or vaporization of certain components, elements, and/or the like of the article and/or device. In some aspects, articles or devices characterized as smoking articles incorporate tobacco and/or components derived from tobacco.

[0132] As noted, aerosol delivery devices may provide many of the sensations (e.g., inhalation and exhalation rituals, types of tastes or flavors, organoleptic effects, physical feel, use rituals, visual cues such as those provided by visible aerosol, and the like) of smoking a cigarette, cigar or pipe that is employed by lighting and burning tobacco (and hence inhaling tobacco smoke), without any substantial degree of combustion of any component thereof. For example, the user of an aerosol delivery device in accordance with some example implementations of the present disclosure can hold and use that device much like a smoker employs a traditional type of smoking article, draw on one end of that piece for inhalation of aerosol produced by that piece, take or draw puffs at selected intervals of time, and the like.

[0133] Articles or devices of the present disclosure are also characterized as being vapor-producing articles, aerosol delivery articles, or medicament delivery articles. Thus, such articles or devices are adaptable so as to provide one or more substances in an inhalable form or state. For example, inhalable substances are substantially in the form of a vapor (e.g., a substance that is in the gas phase at a temperature lower than its critical point). Alternatively, inhalable substances are in the form of an aerosol (e.g., a suspension of fine solid particles or liquid droplets in a gas). For purposes of simplicity, the term “aerosol” as used herein is meant to include vapors, gases, and aerosols of a form or type suitable for human inhalation, whether or not visible, and whether or not of a form that might be considered to be smoke-like. In some implementations, the terms “vapor” and “aerosol” may be interchangeable. Thus, for simplicity, the terms “vapor” and “aerosol” as used to describe the disclosure are understood to be interchangeable unless stated otherwise.

[0134] Examples of suitable vapor-producing articles, aerosol delivery articles, or medicament delivery articles include vapor products, heat-not-burn products, hybrid products and the like. Vapor products are commonly known as “electronic cigarettes,” “e-cigarettes” or electronic nicotine delivery systems (ENDS), although the aerosol-generating material need not include nicotine. Many vapor products are designed to heat a liquid material to generate an aerosol. Other vapor products are designed to break up an aerosol-generating material into an aerosol without heating, or with only secondary heating. Heat-not-burn products include tobacco heating products and carbon-tipped tobacco heating products, and many are designed to heat a solid material to generate an aerosol without combusting the material.

[0135] Hybrid products use a combination of aerosol-generating materials, one or a plurality of which may be heated. Each of the aerosol-generating materials may be, for example, in the form of a solid, semi-solid, liquid, or gel. Some hybrid products are similar to vapor products except that

the aerosol generated from a liquid or gel aerosol-generating material passes through a second material (such as tobacco) to pick up additional constituents before reaching the user. In some example implementations, the hybrid system includes a liquid or gel aerosol-generating material, and a solid aerosol-generating material. The solid aerosol-generating material may include, for example, tobacco or a non-tobacco product.

[0136] In use, smoking articles of the present disclosure are subjected to many of the physical actions of an individual in using a traditional type of smoking article (e.g., a cigarette, cigar, or pipe that is employed by lighting with a flame and used by inhaling tobacco that is subsequently burned and/or combusted). For example, the user of a smoking article of the present disclosure holds that article much like a traditional type of smoking article, draws on one end of that article for inhalation of an aerosol produced by that article, and takes puffs at selected intervals of time.

[0137] While the systems are generally described herein in terms of implementations associated with smoking articles such as so-called “tobacco heating products,” it should be understood that the mechanisms, components, features, and methods may be embodied in many different forms and associated with a variety of articles. For example, the description provided herein may be employed in conjunction with implementations of traditional smoking articles (e.g., cigarettes, cigars, pipes, etc.), heat-not-burn cigarettes, and related packaging for any of the products disclosed herein. Accordingly, it should be understood that the description of the mechanisms, components, features, and methods disclosed herein are discussed in terms of implementations relating to aerosol delivery devices by way of example only, and may be embodied and used in various other products and methods.

[0138] Aerosol delivery devices of the present disclosure generally include a number of components provided within an outer body or shell, which may be referred to as a housing. The overall design of the outer body or shell can vary, and the format or configuration of the outer body that can define the overall size and shape of the aerosol delivery device can vary. In some example implementations, an elongated body resembling the shape of a cigarette or cigar can be formed from a single, unitary housing or the elongated housing can be formed of two or more separable bodies. For example, an aerosol delivery device can comprise an elongated shell or body that can be substantially tubular in shape and, as such, resemble the shape of a conventional cigarette or cigar. In another example, an aerosol delivery device may be substantially rectangular or have a substantially rectangular cuboid shape. In one example, all of the components of the aerosol delivery device are contained within one housing. Alternatively, an aerosol delivery device can comprise two or more housings that are joined and are separable. For example, an aerosol delivery device can possess one portion comprising a housing containing one or more reusable components (e.g., an accumulator such as a rechargeable battery and/or rechargeable supercapacitor, and various electronics for controlling the operation of that article), and removably coupleable thereto, another second portion (e.g., a mouthpiece) and/or a disposable component (e.g., a disposable flavor-containing cartridge containing aerosol precursor material, flavorant, etc.). More specific formats, configurations and arrangements of components within the single housing type of unit or within a multi-piece separable housing type of unit will be evident in light of the further disclosure provided herein. Additionally, various aerosol delivery device designs and component arrangements can be appreciated upon consideration of the commercially available electronic aerosol delivery devices.

[0139] As will be discussed in more detail below, holders of aerosol delivery devices of the present disclosure may comprise some combination of a power source (e.g., an electrical power source), at least one control component (e.g., means for actuating, controlling, regulating and ceasing power, such as by controlling electrical current flow from the power source to other components of the article—e.g., a microprocessor, individually or as part of a microcontroller, a printed circuit board (PCB) that includes a microprocessor and/or microcontroller, etc.), a lighter portion configured heat a heat source and/or substrate material of a cartridge, and a receiving chamber. Such holders may

be configured to accept one or more substrate cartridges that include a substrate material capable of yielding an aerosol upon application of sufficient heat. In some implementations, the holder may include a mouthpiece portion configured to allow drawing upon the holder for aerosol inhalation (e.g., a defined airflow path through the holder such that aerosol generated can be withdrawn therefrom upon draw).

[0140] In various aspects, the heat source of a cartridge may be capable of generating heat to aerosolize a substrate material of the cartridge that comprises, for example, an extruded structure and/or substrate, a substrate material associated with an aerosol precursor composition, tobacco and/or a tobacco related material, such as a material that is found naturally in tobacco that is isolated directly from the tobacco or synthetically prepared, in a solid or liquid form (e.g., beads, sheets, shreds, a wrap), or the like. As will be described in more detail below, in some implementations, an extruded structure may comprise tobacco products or a composite of tobacco with other materials such as, for example, ceramic powder. In other implementations, a tobacco extract/slurry may be loaded into porous ceramic beads. Other implementations may use non-tobacco products. In some implementations aerosol precursor composition-loaded porous beads/powders (ceramics) may be used. In other implementations, rods/cylinders made of extruded slurry of ceramic powder and aerosol precursor composition may be used.

[0141] In some implementations, the substrate material may comprise a liquid including an aerosol precursor composition and/or a gel including an aerosol precursor composition. Some examples of liquid compositions can be found in U.S. Pat. Pub. No. US 2020/0113239 to Aller et al., which is incorporated herein by reference in its entirety. As noted above, in various implementations, one or more of the substrate materials may have an aerosol precursor composition associated therewith. For example, in some implementations the aerosol precursor composition may comprise one or more different components, such as polyhydric alcohol (e.g., glycerin, propylene glycol, or a mixture thereof). Representative types of further aerosol precursor compositions are set forth in U.S. Pat. No. 4,793,365 to Sensabaugh, Jr. et al.; U.S. Pat. No. 5,101,839 to Jakob et al.; PCT WO 98/57556 to Biggs et al.; and Chemical and Biological Studies on New Cigarette Prototypes that Heat Instead of Burn Tobacco, R. J. Reynolds Tobacco Company Monograph (1988); the disclosures of which are incorporated herein by reference. In some aspects, a substrate material may produce a visible aerosol upon the application of sufficient heat thereto (and cooling with air, if necessary), and the substrate material may produce an aerosol that is “smoke-like.” In other aspects, the substrate material may produce an aerosol that is substantially non-visible but is recognized as present by other characteristics, such as flavor or texture. Thus, the nature of the produced aerosol may be variable depending upon the specific components of the aerosol delivery component. The substrate material may be chemically simple relative to the chemical nature of the smoke produced by burning tobacco.

[0142] In some implementations, the aerosol precursor composition may incorporate nicotine, which may be present in various concentrations. The source of nicotine may vary, and the nicotine incorporated in the aerosol precursor composition may derive from a single source or a combination of two or more sources. For example, in some implementations the aerosol precursor composition may include nicotine derived from tobacco. In other implementations, the aerosol precursor composition may include nicotine derived from other organic plant sources, such as, for example, non-tobacco plant sources including plants in the Solanaceae family. In other implementations, the aerosol precursor composition may include synthetic nicotine. In some implementations, nicotine incorporated in the aerosol precursor composition may be derived from non-tobacco plant sources, such as other members of the Solanaceae family. The aerosol precursor composition may additionally, or alternatively, include other active ingredients including, but not limited to, botanical ingredients (e.g., lavender, peppermint, chamomile, basil, rosemary, thyme, eucalyptus, ginger, cannabis, ginseng, maca, and tisanes), stimulants (e.g., caffeine and guarana), amino acids (e.g., taurine, theanine, phenylalanine, tyrosine, and tryptophan) and/or

pharmaceutical, nutraceutical, and medicinal ingredients (e.g., vitamins, such as B6, B12, and C and cannabinoids, such as tetrahydrocannabinol (THC) and cannabidiol (CBD)). It should be noted that the aerosol precursor composition may comprise any constituents, derivatives, or combinations of any of the above.

[0143] As noted herein, the aerosol precursor composition may comprise or be derived from one or more botanicals or constituents, derivatives, or extracts thereof. As used herein, the term “botanical” includes any material derived from plants including, but not limited to, extracts, leaves, bark, fibers, stems, roots, seeds, flowers, fruits, pollen, husk, shells or the like. Alternatively, the material may comprise an active compound naturally existing in a botanical, obtained synthetically. The material may be in the form of liquid, gas, solid, powder, dust, crushed particles, granules, pellets, shreds, strips, sheets, or the like. Example botanicals are tobacco, eucalyptus, star anise, hemp, cocoa, cannabis, fennel, lemongrass, peppermint, spearmint, rooibos, chamomile, flax, ginger, ginkgo biloba, hazel, hibiscus, laurel, licorice (liquorice), matcha, mate, orange skin, papaya, rose, sage, tea such as green tea or black tea, thyme, clove, cinnamon, coffee, aniseed (anise), basil, bay leaves, cardamom, coriander, cumin, nutmeg, oregano, paprika, rosemary, saffron, lavender, lemon peel, mint, juniper, elderflower, vanilla, wintergreen, beefsteak plant, curcuma, turmeric, sandalwood, cilantro, bergamot, orange blossom, myrtle, cassis, valerian, pimento, mace, damien, marjoram, olive, lemon balm, lemon basil, chive, carvi, verbena, tarragon, geranium, mulberry, ginseng, theanine, theacrine, maca, ashwagandha, damiana, guarana, chlorophyll, baobab or any combination thereof. The mint may be chosen from the following mint varieties: *Mentha Arvensis*, *Mentha c.v.*, *Mentha niliaca*, *Mentha piperita*, *Mentha piperita citrata c.v.*, *Mentha piperita c.v.*, *Mentha spicata crispa*, *Mentha cardifolia*, *Mentha longifolia*, *Mentha suaveolens variegata*, *Mentha pulegium*, *Mentha spicata c.v.* and *Mentha suaveolens*.

[0144] A wide variety of types of flavoring agents, or materials that alter the sensory or organoleptic character or nature of the mainstream aerosol of the smoking article may be suitable to be employed. In some implementations, such flavoring agents may be provided from sources other than tobacco and may be natural or artificial in nature. For example, some flavoring agents may be applied to, or incorporated within, the substrate material and/or those regions of the smoking article where an aerosol is generated. In some implementations, such agents may be supplied directly to a heating cavity or region proximate to the heat source or are provided with the substrate material. Example flavoring agents may include, for example, vanillin, ethyl vanillin, cream, tea, coffee, fruit (e.g., apple, cherry, strawberry, peach and citrus flavors, including lime and lemon), maple, menthol, mint, peppermint, spearmint, wintergreen, nutmeg, clove, lavender, cardamom, ginger, honey, anise, sage, cinnamon, sandalwood, jasmine, cascarilla, cocoa, licorice, and flavorings and flavor packages of the type and character traditionally used for the flavoring of cigarette, cigar, and pipe tobaccos. Syrups, such as high fructose corn syrup, may also be suitable to be employed.

[0145] As used herein, the terms “flavor,” “flavorant,” “flavoring agents,” etc. refer to materials which, where local regulations permit, may be used to create a desired taste, aroma, or other somatosensorial sensation in a product for adult consumers. They may include naturally occurring flavor materials, botanicals, extracts of botanicals, synthetically obtained materials, or combinations thereof (e.g., tobacco, cannabis, licorice (liquorice), hydrangea, eugenol, Japanese white bark magnolia leaf, chamomile, fenugreek, clove, maple, matcha, menthol, Japanese mint, aniseed (anise), cinnamon, turmeric, Indian spices, Asian spices, herb, wintergreen, cherry, berry, red berry, cranberry, peach, apple, orange, mango, clementine, lemon, lime, tropical fruit, papaya, rhubarb, grape, durian, dragon fruit, cucumber, blueberry, mulberry, citrus fruits, Drambuie, bourbon, scotch, whiskey, gin, tequila, rum, spearmint, peppermint, lavender, aloe vera, cardamom, celery, cascarilla, nutmeg, sandalwood, bergamot, geranium, khat, naswar, betel, shisha, pine, honey essence, rose oil, vanilla, lemon oil, orange oil, orange blossom, cherry blossom, cassia, caraway, cognac, jasmine, ylang-ylang, sage, fennel, wasabi, piment, ginger, coriander, coffee, hemp, a mint oil from any species of the genus *Mentha*, eucalyptus, star anise, cocoa, lemongrass,

rooibos, flax, ginkgo biloba, hazel, hibiscus, laurel, mate, orange skin, rose, tea such as green tea or black tea, thyme, juniper, elderflower, basil, bay leaves, cumin, oregano, paprika, rosemary, saffron, lemon peel, mint, beefsteak plant, curcuma, cilantro, myrtle, cassis, valerian, pimento, mace, damien, marjoram, olive, lemon balm, lemon basil, chive, carvi, verbena, tarragon, limonene, thymol, camphene), flavor enhancers, bitterness receptor site blockers, sensorial receptor site activators or stimulators, sugars and/or sugar substitutes (e.g., sucralose, acesulfame potassium, aspartame, saccharine, cyclamates, lactose, sucrose, glucose, fructose, sorbitol, or mannitol), and other additives such as charcoal, chlorophyll, minerals, botanicals, or breath freshening agents. They may be imitation, synthetic or natural ingredients or blends thereof. They may be in any suitable form, for example, liquid such as an oil, solid such as a powder, or gas.

[0146] In some implementations, the flavor comprises menthol, spearmint and/or peppermint. In some embodiments, the flavor comprises flavor components of cucumber, blueberry, citrus fruits and/or redberry. In some embodiments, the flavor comprises eugenol. In some embodiments, the flavor comprises flavor components extracted from tobacco. In some embodiments, the flavor comprises flavor components extracted from cannabis.

[0147] In some implementations, the flavor may comprise a sensate, which is intended to achieve a somatosensorial sensation which are usually chemically induced and perceived by the stimulation of the fifth cranial nerve (trigeminal nerve), in addition to or in place of aroma or taste nerves, and these may include agents providing heating, cooling, tingling, numbing effect. A suitable heat effect agent may be, but is not limited to, vanillyl ethyl ether and a suitable cooling agent may be, but not limited to eucalyptol, WS-3.

[0148] Flavoring agents may also include acidic or basic characteristics (e.g., organic acids, such as levulinic acid, succinic acid, pyruvic acid, and benzoic acid). In some implementations, flavoring agents may be combinable with the elements of the substrate material if desired. Example plant-derived compositions that may be suitable are disclosed in U.S. Pat. No. 9,107,453 and U.S. Pat. App. Pub. No. 2012/0152265 both to Dube et al., the disclosures of which are incorporated herein by reference in their entireties. Any of the materials, such as flavorings, casings, and the like that may be useful in combination with a tobacco material to affect sensory properties thereof, including organoleptic properties, such as described herein, may be combined with the substrate material. Organic acids particularly may be able to be incorporated into the substrate material to affect the flavor, sensation, or organoleptic properties of medicaments, such as nicotine, that may be able to be combined with the substrate material. For example, organic acids, such as levulinic acid, lactic acid, pyruvic acid, and benzoic acid may be included in the substrate material with nicotine in amounts up to being equimolar (based on total organic acid content) with the nicotine. Any combination of organic acids may be suitable. For example, in some implementations, the substrate material may include approximately 0.1 to about 0.5 moles of levulinic acid per one mole of nicotine, approximately 0.1 to about 0.5 moles of pyruvic acid per one mole of nicotine, approximately 0.1 to about 0.5 moles of lactic acid per one mole of nicotine, or combinations thereof, up to a concentration wherein the total amount of organic acid present is equimolar to the total amount of nicotine present in the substrate material. Various additional examples of organic acids employed to produce a substrate material are described in U.S. Pat. App. Pub. No. 2015/0344456 to Dull et al., which is incorporated herein by reference in its entirety.

[0149] The selection of such further components may be variable based upon factors such as the sensory characteristics that are desired for the smoking article, and the present disclosure is intended to encompass any such further components that are readily apparent to those skilled in the art of tobacco and tobacco-related or tobacco-derived products. See, Gutcho, Tobacco Flavoring Substances and Methods, Noyes Data Corp. (1972) and Leffingwell et al., Tobacco Flavoring for Smoking Products (1972), the disclosures of which are incorporated herein by reference in their entireties.

[0150] In other implementations, the substrate material may include other materials having a

variety of inherent characteristics or properties. For example, the substrate material may include a plasticized material or regenerated cellulose in the form of rayon. As another example, viscose (commercially available as VISIL®), which is a regenerated cellulose product incorporating silica, may be suitable. Some carbon fibers may include at least 95 percent carbon or more. Similarly, natural cellulose fibers such as cotton may be suitable, and may be infused or otherwise treated with silica, carbon, or metallic particles to enhance flame-retardant properties and minimize off-gassing, particularly of any undesirable off-gassing components that would have a negative impact on flavor (and especially minimizing the likelihood of any toxic off-gassing products). Cotton may be treatable with, for example, boric acid or various organophosphate compounds to provide desirable flame-retardant properties by dipping, spraying or other techniques known in the art. These fibers may also be treatable (coated, infused, or both by, e.g., dipping, spraying, or vapor-deposition) with organic or metallic nanoparticles to confer the desired property of flame-retardancy without undesirable off-gassing or melting-type behavior.

[0151] More specific formats, configurations and arrangements of components within the non-combustible aerosol provision systems of the present disclosure will be evident in light of the further disclosure provided hereinafter. Additionally, the selection and arrangement of various non-combustible aerosol provision system components can be appreciated upon consideration of the commercially available electronic non-combustible aerosol provision systems, such as those representative products referenced in the background art section of the present disclosure.

[0152] According to certain aspects of the present disclosure, it may be advantageous to provide an aerosol delivery device that is easy to use and provides improved performance. FIGS. 1A, 1B, 2, 3A, and 3B illustrate one example implementation of such a device. In particular, FIGS. 1A and 1B illustrate a perspective view and a cross-sectional perspective view, respectively, of an aerosol delivery device **100** that includes an optional actuator assembly **108** and a mouthpiece **104**.

Specifically, the aerosol delivery device **100** comprises a holder **102** having a main body defining a proximal end **102a** and a distal end **102b**, where the holder **102** further defines a receiving chamber **110** configured to receive a removable cartridge (**106** in FIG. 3A) and a first aerosol passageway **150** that extends through at least a portion of the main body. The removable cartridge **106** comprises an ignitable heat source **120** and a substrate portion **122** that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto. The mouthpiece **104** has a first end and a longitudinally opposed second end with a second aerosol passageway **154** extending longitudinally therebetween. In the depicted implementation, the mouthpiece **104** is located proximate the proximal end **102a** of the holder **102** with the first end configured to engage with a user's mouth and the second end configured to be coupled to the proximal end of the holder **102**. The device **100** also includes a power source **112** disposed within the holder **102**. The slider actuator assembly **108** is coupled to the holder **102** and configured to ignite the ignitable heat source and/or eject the removable cartridge **106**.

[0153] As further illustrated by the exploded view of FIG. 2, the actuator assembly **108** comprises a slider body **130** slidably disposed within the main body of the holder **102** and having an upper track **132**, a lower track **134**, and a slider body collar **136** coupling the upper and lower tracks and defining a receptacle **138** (see FIG. 1A or 3A) configured to at least partially receive the removable cartridge, a spring-loaded push button **140** engaged with the upper track **132** of the slider body **130** so as to move the actuator assembly **108** between a loading position, a lighting position, and an ejecting position, and a spring assembly **142** configured to engage the slider body **130** and bias the actuator assembly **108** into the loading or other “neutral” position. The slider body **130** is configured to slide along a length of the main body in a first direction and a second direction. The push button **140** is configured to engage an electrical contact **129** when in the lighting position. In one implementation, the push button **140** extends through an opening in a top surface of the upper track **132** and is slideably secured thereto. The button **140** is spring loaded so as to return to an off position after igniting the heat source. The holder **102** defines a slot **116** through a surface thereof

that is sized and shaped to slidably receive the spring-loaded push button **140** therein. In some implementations, the upper track **132** of the slider body **130** is sealingly engaged with the holder about the slot **116**, for example, via a gasket **117** disposed within a recess formed in the top surface of the slider body **130**.

[0154] The actuator assembly **108** further comprises a pair of actuatable ignitor contacts **128a**, **128b** (collectively **128**) disposed proximate the distal end **102a** of the holder and configured to be engaged with the ignitable heat source when the removable cartridge is secured within the receiving chamber **110** and when the actuatable ignitor contacts **128** are actuated by a user. The ignitor contacts **128** are coupled to and disposed at the distal ends of a pair of elongate bodies **125**; however, in other implementations, the contacts **128** and elongate bodies **125** are a single piece formed into an appropriate configuration. The ignitor contacts **128** are coupled to the slider body **130** via a pair of contact arms **126** that are disposed within grooves **135** defined by the upper and lower tracks **132**, **134**. Specifically, a first contact arm **126a** is pivotably coupled to the main body of the holder **102** and configured to receive one of the pair of actuatable ignitor contacts **128a** in a retaining groove **127a** formed within an inner surface of the contact arm **126a** and a second contact arm **126b** is pivotably coupled to the main body of the holder **102** and configured to receive the other one of the pair of actuatable ignitor contacts **128b** in a retaining groove **127b** (not shown, but mirror image of **127a**) formed within an inner surface of the second contact arm **126b**. The contact arms **126** are further coupled to the sliding body **130** (e.g., via pivot pins **180**) so that sliding movement of the sliding body **130** into the lighting position causes the contact arms **126** to pivot into a closed configuration where the ignitor contacts **128** move into contact with the ignitable heat source **120**. Additionally, the contact arms **126** may be chamfered at the ends thereof that engage the slider body **130** so as to accommodate the pivoting of the arms **126** within the holder **102**.

[0155] The receiving chamber **110** of the device **100** is further defined by an end cap **114** engaged with the distal end **102b** of the holder and defining an opening **115** configured to receive the removable cartridge **106** therethrough, an outlet guide **144** coupled to the slider body slider body collar **136** and slidably disposed within the main body of the holder **102** and through the end cap **114**, and an inner slider seal body **146** disposed within the receptacle **138** of the slider body **130** and coupled thereto (e.g., frictionally engaged therewith via a sealing surface), the inner slider seal body **146** defining a cavity configured to sealingly engage and removably secure the removable cartridge **106** therein. For example, the inner slider seal body **146** may include an elastomeric sleeve **148** disposed therein that includes a protuberance or ring **176** extending radially inwardly from a wall of the sleeve that is configured to frictionally and/or sealingly engage an outer surface of the removable cartridge **106**. In some implementations, the elastomeric sleeve **148** may be integral with the inner slider seal body **146**, such as, for example, as part of an over-molded part. The inner slider seal body **146** may include a leading edge or lip **149** configured to contact or otherwise engage with the spring assembly **142** with a protuberance or ring **172** disposed about an outer surface of the seal body **146** proximate an end opposite of the leading edge that is configured to engage an edge of the end cap **114** that extends within the holder **102**. Additionally, the elastomeric sleeve **148** includes a protuberance or ring **170** extending radially outwardly from an exterior wall of the sleeve **148** that is configured to frictionally and/or sealingly engage with an inner wall of the receptacle **138**.

[0156] The outlet guide **144** defines a passageway that forms a portion of the receiving chamber **110** configured to pass the removable cartridge therethrough and comprises a pair of opposing slots **145** through a wall of the outlet guide **144** that are configured to allow the ignitor contacts **128** to pass therethrough to engage the ignitable heat source **120**. The outlet guide **144** may be snap fit to the slider body collar **136** via, for example, mating slots and protuberances. The slider body collar **136** of the slider body **130** includes an inner stem **133** disposed within the receptacle **138** and engageable with one end of the removable cartridge and defining a passageway **139** (part of the first aerosol passageway **150**) therethrough for passing an aerosol generated from the removable

cartridge. The end cap **114** removably engages the holder **102** via, for example, one or more of a snap-fit, interference fit, screw thread, magnetic, and/or bayonet connection. In other implementations, the end cap may be permanently engaged with the holder **102** after assembly to secure the various components therein. The end cap **114** may be translucent or transparent so as to allow light from the ignitable heat source to pass therethrough when lit. Similarly, the push button **140** may also be translucent or transparent to allow, for example, light from an LED to pass therethrough that is indicative of a state of the device **100**.

[0157] The device **100** further comprises an inner housing **124** disposed within the holder **102** and defining an inner cavity **123** configured to receive the power source **112** and a printed circuit board **118** therein. The printed circuit board **118** is in electrical communication with the power source **112** and includes the electrical contact **129** disposed thereon for actuation by the slider push button **140** when the actuator assembly **108** is in the lighting position. The power source **112** is in electrical communication with the ignitor contacts **128** via a pair of wires **168** or other electrical connection mechanism. In one implementation, the wires **168** run at least partially within grooves **166** defined by a pair of fingers **164** that extend from a distal end of the inner housing **124**. The printed circuit board may further comprise a charging port **119** that is oriented on the printed circuit board so as to be disposed at the proximal end of the holder **102** and accessible by, for example, removing the mouthpiece **104**.

[0158] The inner housing **124** further defines a third aerosol passageway **147**. In the depicted implementation of FIGS. 3A and 3B, the third aerosol passageway is made up of a first port **151a** disposed in a first or proximal end **124a** of the inner housing, a second port **151b** disposed in a second or distal end **124b** of the inner housing with one or more channels **151** disposed in an outer surface of the inner housing **124**. As shown in FIGS. 4A-4C, two channels **151** are disposed in opposing side of the inner housing **124** and enclosed by an inner surface of the holder **102**, thereby defining two parallel third aerosol passageways **147** (see FIG. 4A) that extend around the battery **112**, the printed circuit board **118**, and associated electronics disposed in the inner housing **124**. In addition, the distal end **124b** of the inner housing sealingly engages with the slider body **130** (e.g., with a gasket or O-ring **178**) when the actuator assembly is in the lighting position so as to be in fluid communication with the passageway **139** defined by the inner stem **133** (i.e., a fourth aerosol passageway **139**) and to provide the aerosol from the cartridge **106**/first aerosol passageway **150** to the third aerosol passageway **147** further defined by the inner housing **124**. Generally, the aerosol (vapor path **143**) enters the third aerosol passageway **147** via the second port **151b**, where it is divided into two vapor paths **143** that run along the channels **151** disposed in each side of the inner housing **124**. The two vapor paths merge at the proximal end **124a** of the inner housing and exit through the first port **151a**, which is in fluid communication with a second aerosol passageway **154** within the mouthpiece **104**.

[0159] In some implementations, the opening **115** in the end cap **114** allows for the introduction of ambient air to the receiving chamber **110** and cartridge **106**. However, in other implementations not depicted, the holder may include one or more apertures therein for allowing entrance of ambient air to be directed into the receiving chamber and/or the aerosol passageway (such as, for example, through the substrate cartridge and/or downstream from the substrate cartridge). Thus, when a user draws on the holder (e.g., via the mouthpiece portion thereof), air may be drawn into the receiving chamber and/or the aerosol passageway for inhalation by the user (e.g., by traveling through the first, second, third, and optionally fourth aerosol passageways and out the first end **104a** of the mouthpiece). In some implementations, for example where the mouthpiece **104** is removable, the aerosol delivery device **100** includes a collar **152** that sealingly engages with the proximal end **102a** of the holder at one end and sealingly engages with the mouthpiece **104** at the other end, as described in greater detail below. The collar **152** defines a channel or fifth aerosol passageway **153** that fluidly couples the third aerosol passageway **147** with the second aerosol passageway **154**, further defining the vapor path **143**.

[0160] The removable mouthpiece **104** is described in greater detail with respect to FIGS. **4C** and **5**. In the depicted implementation, the mouthpiece **104** is coupled to the holder **102** via the collar **152** that sealingly engages with the proximal end **102a** of the holder at one end and sealingly engages with the mouthpiece **104** at the other end. Specifically, the collar comprises a base portion **155** and a body portion **157**, each of which defines an opening in fluid communication with a first channel **153** that extends through the collar **152**. The base portion **155** includes a first sealing mechanism **163a** that is disposed about an exterior surface thereof. As shown, the first sealing mechanism **163a** comprises an O-ring **160** disposed within a groove **161** defined by the exterior surface of the base portion. The base portion **155** is sized and shaped to engage an opening in the proximal end of the holder **102**, such that the base portion is disposed within the proximal end of the holder and the first sealing mechanism **163a** engages an inner wall of the holder **102**. In some implementations, the base portion **155** may be coupled to the holder **102** via at least one fastener **162**. For example, the inner housing **124** may be configured such that the base portion **155** is secured to the inner housing via the at least one fastener **162** (e.g., a screw).

[0161] The body portion **157** includes a second sealing mechanism **163b** disposed about an exterior surface thereof. As shown, the second sealing mechanism **163b** comprises at least one O-ring **160** disposed within one or more grooves **161** defined by the exterior surface of the body portion. The body portion **157** is sized and shaped to engage a recess **156** disposed within the second end **104b** of the mouthpiece **104**, such that the body portion is substantially fully disposed within the recess **156** with the second sealing mechanism **163b** engaging an inner wall of the recess **156**. The second sealing mechanism **163b** provides frictional resistance between the mouthpiece **104** and the collar **152**, which is sufficient to secure the mouthpiece **104** to the holder **102** via the collar **152**, but minimal enough so that a user may remove the mouthpiece **104** without significant effort. The mouthpiece can be removed for cleaning and then reattached for continued use or, in some cases, a different mouthpiece may be attached to customize the user's experience.

[0162] As shown in FIGS. **4C** and **5**, the first channel **153** extends through the collar **152** so as to fluidly couple the third aerosol passageway **147** of the inner housing **124** and the second aerosol passageway **154** of the mouthpiece **104**, thereby completing the vapor path **143** extending from the receiving chamber **110**, through the first aerosol passageway **150**, the fourth aerosol passageway **139**, the third aerosol passageway **147**, the fifth aerosol passageway **153**, and the second aerosol passageway **154**, and out through the opening **158** in the mouthpiece portion **104**. Generally, the first, second, third, and fourth aerosol passageways (and the fifth aerosol passageway of present) are configured to define the continuous vapor path **143** from the distal end **102b** of the main body to the first end **104a** of the mouthpiece.

[0163] In some implementations, the collar **152** includes a second channel **159** extending therethrough that is sized and shaped to at least partially receive the charging port **119** (e.g., a micro-USB connector) therein, so that a user may access the port **119** by removing the mouthpiece **104**. In some implementations, the second channel **159** is at least partially defined by a portion of the inner housing **124**, which may separate the second channel **159** from the first channel **153**.

[0164] FIGS. **6A** and **6B** illustrate cross-sectional side and perspective views, respectively, of another implementation of an aerosol delivery device **400** similar to the device **100** described with respect to FIGS. **1A** and **1B**. Specifically, the device **400** includes an alternative arrangement for a removable mouthpiece **404**. The figures are limited to the proximal end of the device **400** for illustrative purposes only. Specifically, the figures depict the aerosol delivery device **400** comprising a holder **402** having a main body defining a proximal end **402a** and a distal end (not shown), where the holder **402** further defines a receiving chamber (not shown, but similar to those described hereinabove) that is configured to receive a removable cartridge therein. The device further defines an aerosol passageway **450** that extends through at least a portion of the main body and to the mouthpiece **404**. The mouthpiece **404** has a first end **404a** and a longitudinally opposed second end **404b** with a second aerosol passageway **454** extending longitudinally therebetween. In

the depicted implementation, the mouthpiece **404** is located proximate the proximal end **402a** of the holder **402** with the first end configured to engage with a user's mouth and the second end coupleable to the proximal end of the holder **402**. The device **400** also includes a power source **412** and associated electronics or other controls disposed within the holder **402**.

[0165] With reference to FIGS. **6A**, **6B**, **7A**, and **7B**, the mouthpiece **404** is coupled to the holder **402** via a collar **452** that engages with the proximal end **402a** of the holder **402** at one end and sealingly engages with the mouthpiece **404** at the other end. Specifically, the collar comprises a base portion **455** and a body portion **457**, each of which defines an opening in fluid communication with a channel **453** that extends through the collar **452**. The base portion **455** is sized and shaped to engage an opening in the proximal end of the holder **402** via, for example, at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement. In some implementations, the base portion **455** may include a sealing mechanism for sealingly engaging with the holder **402**. In some implementations, the base portion **455** may also be coupled to the holder **402** via at least one fastener **462**.

[0166] The body portion **457** includes a sealing mechanism **463** disposed about an exterior surface thereof. As shown, the sealing mechanism **463** comprises at least one O-ring **460** disposed within one or more grooves **461** defined by the exterior surface of the body portion. The body portion **457** is sized and shaped to engage a recess **456** disposed within the second end **404b** of the mouthpiece **404**, such that the body portion is substantially fully disposed within the recess **456** with the sealing mechanism **463** engaging an inner wall of the recess **456**. The scaling mechanism **463** provides frictional resistance between the mouthpiece **404** and the collar **452**, which is sufficient to removably secure the mouthpiece **404** to the holder **402** via the collar **452**, but minimal enough so that a user may remove the mouthpiece **404** without significant effort. The mouthpiece can be removed for cleaning and then reattached for continued use or, in some cases, a different mouthpiece may be attached to customize the user's experience.

[0167] As shown in FIG. **6A**, the channel **453** extends through the collar **452** so as to fluidly couple the aerosol passageway **450** of the inner housing **424** and the aerosol passageway **454** extending through the mouthpiece **404**, thereby completing an aerosol path extending from the receiving chamber, through the inner housing **424**, and out through the opening **458** in the mouthpiece portion **404**. In addition, the collar **452** includes a stem **473** extending distally from the base portion **455** and further defining the channel **453** extending through the collar **452**. When assembled, the stem **473** extends into the holder and engages the inner housing **424**. Specifically, the stem **473** is at least partially inserted into the aerosol passageway **450** defined by the inner housing **424**. The stem **473** may be coupled to the inner housing **424** via, for example, a press-fit or snap-fit engagement.

[0168] Generally, when the actuator assembly **108** is moved into the lighting position, the lower track **134** of the slider body **130** forces the contact arms **126** into their closed configuration (i.e., the ignitor contacts **128** are in contact with the heat source **120**). Specifically, the contact arms **126** are engaged with the slider body **130** and pivotably coupled to the holder **102** so that when the actuator assembly **108** is moved into the lighting position, the outlet guide **144** is translated toward the proximal end **102a** of the holder **102**. In this manner, the contact arms **126** are no longer supported in their open configuration by the outlet guide **144** and are able to pivot into the closed configuration so that the ignitor contacts **128** are in contact with the heat source **120**. Once the push button **140** is actuated, the electrical circuit is completed and the electricity is delivered to the ignitor contacts **128**.

[0169] In some alternative implementations, the aerosol is generated by an electric heater configured to perform electric heating in which electrical energy from the power source is delivered to the heater when the actuator assembly is moved into the lighting/use position. Subjecting the aerosol-generating material (substrate **122**) to heat releases one or more volatiles from the aerosol-generating material to form an aerosol. Examples of suitable forms of electric heating include resistance (Joule) heating, induction heating, dielectric and microwave heating,

radiant heating, arc heating and the like. More particular examples of suitable electric heaters include resistive heating elements such as wire coils, flat plates, prongs, micro heaters or the like. [0170] In some examples, the cartridge **106** may include a susceptor (e.g., the susceptor may be part of the substrate **122**). The susceptor is a material that is heatable by penetration with a varying magnetic field generated by a magnetic field generator that may be separate from or part of the aerosol generator. The susceptor may be an electrically-conductive material, so that penetration thereof with a varying magnetic field causes induction heating of the heating material. The heating material may be magnetic material, so that penetration thereof with a varying magnetic field causes magnetic hysteresis heating of the heating material. The susceptor in some examples may be both electrically-conductive and magnetic, so that the susceptor of these examples is heatable by both heating mechanisms.

[0171] FIGS. **8A**, **8B**, **9**, and **10** illustrate another example implementation of an aerosol delivery device **200**. In particular, FIGS. **8A** and **8B** illustrate a perspective view and a cross-sectional perspective view, respectively, of an aerosol delivery device **200** that includes a removable mouthpiece **204**. Specifically, the aerosol delivery device **200** comprises a holder **202** having a main body defining a proximal end **202a** and a distal end **202b**, where the holder **202** further defines a receiving chamber **210** configured to receive a removable cartridge (**206** in FIG. **9**) and an aerosol passageway **250** that extends through at least a portion of the main body. In some implementations, the removable cartridge **206** comprises an ignitable heat source **220** and a substrate portion **222** that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto. The device **200** further comprises an optional actuator assembly **208** configured to be movable between different positions, such as a loading position and an ejecting position. The mouthpiece **204** is removably secured to the holder **202** as described in greater detail below.

[0172] As further illustrated by the exploded view of FIG. **9**, the actuator assembly **208** comprises a slider body **230** slidably disposed within the main body of the holder **202** and having an upper track **232** and a lower track **234** coupled together via a generally cylindrical body that defines an interior space including a receptacle **238** configured to at least partially receive the removable cartridge, a slider button **231** engaged with the upper track **232** of the slider body **230** so as to move the actuator assembly **208** between a loading position, a lighting position, and an ejecting position. The slider body **230** is configured to slide along a length of the main body in a first direction and a second direction. A locating feature **237** (such as, for, example, a spring-loaded ball plunger mechanism) and one or more corresponding detents may be included to temporarily locate the actuator assembly **208** in one or more of the loading, lighting, and ejecting positions.

[0173] In one implementation, the slider button **231** extends through an opening in a top surface of the upper track **232** and is secured thereto to allow a user to slide the slider body **230** relative to the holder. The holder **202** defines a slot **216** through a surface thereof that is sized and shaped to slidably receive the slider button **231** therein. In some implementations, the upper track **232** of the slider body **230** is sealingly engaged with the holder about the slot **216**.

[0174] The actuator assembly **208** further comprises a pair of static ignitor contacts **228** disposed proximate the distal end **202a** of the holder and configured to be engaged with the ignitable heat source when the removable cartridge is secured within the receiving chamber **210**. The ignitor contacts **228** are coupled to the printed circuit board **218** via a pair of contact arms **226** that allow the contacts **228** to flex outwardly via insertion of the cartridge **206** so that they contact the ignitable heat source **220** of the cartridge after loading. In one implementation, an ignitor push button **240** is included that is configured, when pressed by a user, to activate the ignitor contacts **228** thereby igniting the heat source **220** (i.e., the electrical circuit is completed and the electricity is delivered to the ignitor contacts **228**). In some implementations, the ignitor contacts **228** will only remain activated while the ignitor push button **240** is depressed. As such, in some implementations, the ignitor contacts **228** will be deactivated when the ignitor push button **240** is

released and/or the contacts may stay activated for a specific period of time.

[0175] The receiving chamber **210** of the device **200** is further defined by an end cap **214** engaged with the distal end **202b** of the holder and defining an opening **215** configured to receive the removable cartridge **206** therethrough, a heat sink **286** disposed in the distal end of the holder **202** and secured to the end cap **214** or the holder **202**, and an inner slider seal body **246** disposed within the receptacle **238** of the slider body **230** and coupled thereto (e.g., frictionally engaged therewith via a sealing surface). The inner slider seal body **246** defines a cavity configured to sealingly engage and removably secure the removable cartridge **206** therein. For example, the inner slider seal body **246** may include an elastomeric sleeve **248** disposed therein that includes a protuberance or ring **276** extending radially inwardly from a wall of the sleeve that is configured to frictionally and/or sealingly engage an outer surface of the removable cartridge **206**. In some implementations, the elastomeric sleeve **248** may be integral with the inner slider seal body **246**, such as, for example, as part of an over-molded part. Additionally, the elastomeric sleeve **248** includes a protuberance or ring **270** extending radially outwardly from an exterior wall of the sleeve **248** that is configured to frictionally and/or sealingly engage with an inner wall of the receptacle **238**. The heat sink **286** defines a passageway that forms a portion of the receiving chamber **210** configured to pass the removable cartridge therethrough and to accommodate the ignitor contacts **228** positioned therein to engage the ignitable heat source **220**. The heat sink **286** may be snap fit to the end cap **214** or the distal end **202b** of the holder.

[0176] The slider body **230** includes an inner stem **233** disposed within the receptacle **238** that is configured to engage one end of the removable cartridge **206** and define a passageway **250** therethrough for passing an aerosol generated from the removable cartridge to the mouthpiece **204**. The end cap **214** removably engages the holder **202** via, for example, one or more of a snap-fit, interference fit, screw thread, magnetic, and/or bayonet connection. In other implementations, the end cap may be permanently engaged with the holder **202** after assembly to secure the various components therein. The end cap **214** may be translucent or transparent so as to allow light from the ignitable heat source to pass therethrough when lit. Similarly, the slider button **231** may also be translucent or transparent to allow, for example, light from an LED to pass therethrough that is indicative of a state of the device **200**.

[0177] In some implementations, the opening **215** in the end cap **214** allows for the introduction of ambient air to the receiving chamber **210** and cartridge **206**. However, in other implementations not depicted, the holder may include one or more apertures therein for allowing entrance of ambient air to be directed into the receiving chamber and/or the aerosol passageway (such as, for example, through the substrate cartridge and/or downstream from the substrate cartridge). Thus, when a user draws on the holder (e.g., via the mouthpiece portion thereof), air may be drawn into the receiving chamber and/or the aerosol passageway for inhalation by the user.

[0178] FIG. **10** provides an enlarged view illustrating additional details of the mouthpiece **204**. In the depicted implementation, the mouthpiece **204** has a first portion **207** having a first end **207a** and a longitudinally opposed second end **207b**, and a second portion **205** that extends distally from the longitudinally opposed second end **207b** of the first portion. The first and second portions **207**, **205** define a second aerosol passageway **254** that extends therethrough. The first end **207a** of the first portion **207** is configured to engage with a user's mouth, while the second end **207b** of the first portion **207** is configured to engage with the proximal end of the holder **202**. The second end **207b** of the first portion may be configured to engage the opening in the proximal **202a** end of the holder **202** via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement.

[0179] The second portion **205** of the mouthpiece **204** is essentially a hollow stem or tube that extends from the second end **207b** of the first portion **207** of the mouthpiece **204** and is configured to slidably engage with the slider body **230**, which partially defines the aerosol passageway **250**, so as to provide fluid communication between the first aerosol passageway and the second aerosol

passageway **245**. In some implementations, the second portion **205** of the mouthpiece **204** passes through an opening **215'** in an endcap **214'**. The first portion **207** of the mouthpiece defines a first portion **254a** of the second aerosol passageway **254** and the second portion **205** of the mouthpiece **204** defines a second portion **254b** of the second aerosol passageway **254**. The second portion **205** of the mouthpiece is offset from a central axis of the device **200**. Specifically, the second portion **205** comprises a centrally located longitudinal axis **297b** offset from and generally in parallel with a centrally located longitudinal axis **297a** of the device **200**, such that the second portion **205** of the mouthpiece, and the second aerosol passageway portion **254b**, is aligned with the first aerosol passageway **250** in the sliding body **230** to define a direct vapor path from the cartridge **206** to the mouthpiece **204**. As shown in FIG. **8B**, the second portion of the second aerosol passageway **254b** opens into the first portion of the second aerosol passageway **254a** for delivery to the user. The offset arrangement simplifies the vapor path so as to minimize and/or eliminate loss of vapor (e.g., fewer joints or interfaces results in fewer leak points).

[0180] The second portion **205** of the mouthpiece **204** includes a sealing mechanism **263** disposed about an exterior surface thereof, so as to sealingly engage the second portion **205** with the portion of the first aerosol passageway defined by the slider body **230**. In some implementations, the sealing mechanism **263** comprises an O-ring **260** disposed within a groove **261** defined by the exterior surface of the second portion of the mouthpiece. In the depicted implementation, the mouthpiece **204** is removably secured to the holder **202** via the scaling mechanism **263**, which provides frictional resistance between the mouthpiece **204** (specifically, the second portion **205**) and the sliding body **230**. In some implementations, the inner housing **224** includes a retention structure **269a** disposed on a proximal end thereof (e.g., formed in the end cap **214'**) and the second end **207b** of the first portion **207** of the mouthpiece **204** defines a mating retention structure **269b** configured to engage the retention structure **269a** on the inner housing **224**. The retention structure **269** may be a snap-fit mechanism or other type of reversible coupling mechanism. The retention structure **269** may further removably secure the mouthpiece **204** to the holder **202**. The mouthpiece **204** can be removed from the holder **202** for, for example, cleaning or customization of the device **200** (e.g., the use of interchangeable mouthpieces).

[0181] FIGS. **11A**, **11B**, **12**, and **13** illustrate another example implementation of an aerosol delivery device **300**. In particular, FIGS. **11A** and **11B** illustrate a perspective view and a cross-sectional side view, respectively, of an aerosol delivery device **300** that includes a removable mouthpiece **304**. Specifically, the aerosol delivery device **300** comprises a holder **302** having a main body defining a proximal end **302a** and a distal end **302b**, where the holder **302** further defines a receiving chamber **310** configured to receive a removable cartridge (**306** in FIG. **12**) and a first aerosol passageway **350** that extends through at least a portion of the main body. In some implementations, the removable cartridge **306** comprises an ignitable heat source **320** and a substrate portion **322** that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto. The holder **302** further comprises an access door **388** that may be slidably or hingedly coupled to the holder **302** and configured to be opened for loading the cartridge **306** into the receiving chamber **310** via the receptacle **338** in the inner housing **324** (see FIG. **12**). The device **300** also includes a mouthpiece **304** removably secured to the holder **302** and described in greater detail below.

[0182] As further illustrated by the exploded view of FIG. **12**, the device **300** includes an inner housing **324** disposed within the holder **302** and further defining the receiving chamber **310** and a receptacle **338** for receiving the cartridge **306**. A proximal end of the inner housing **324** includes a retention mechanism **369** configured to engage with the mouthpiece **304** as described below. The inner housing **324** includes a tubular structure **325** disposed therein and extending along a length of the housing **324**. The tubular structure **325** defines the first aerosol passageway **350** and extends partially beyond the proximal end of the inner housing **324** and is configured to engage at least a portion of the mouthpiece **304** to provide fluid communication between the first and second aerosol

passageways **350**, **354** and deliver the aerosol to a user via an opening **358** in the mouthpiece **304**. [0183] The receiving chamber **310** of the device **300** is further defined by an end cap **314** engaged with the distal end **302b** of the holder **302** and defining an opening **315** configured to pass the removable cartridge **306** therethrough when ejected. The actuator assembly **308** is slidably disposed within the main body of the holder **302** and configured to eject the cartridge **306** when slid forward towards the distal end of the holder **302**. In some implementations, the actuator assembly **308** is spring-loaded so as to return the actuator assembly **308** to a neutral position. The cartridge **306** may be removably secured within the receiving chamber **310** and sealed relative to the first aerosol passageway **350** via any of the mechanisms or manners disclosed herein (e.g., frictionally engaged via an elastomeric seal).

[0184] The device **300** further includes a power source **312** and a printed circuit board **318** disposed within the inner housing **324**. The power source **312** is in electrical communication with the printed circuit board **318** and a pair of static ignitor contacts **328** disposed thereon that may be energized via a push button **340** disposed on a side wall of the holder **302**. Specifically, once the push button **340** is actuated, the electrical circuit is completed and electricity is delivered to the ignitor contacts **328**. The printed circuit board **318** may further comprise a charging port **319** that is oriented on the printed circuit board so as to be disposed at one end of the holder **302**.

[0185] FIG. **13** provides an enlarged cross-sectional view illustrating additional details of the mouthpiece **304**. In the depicted implementation, the mouthpiece **304** has a first end **304a** and a longitudinally opposed second end **304b** with a second aerosol passageway **354** extending longitudinally therebetween. In the depicted implementation, the mouthpiece **304** is located at the proximal end of the holder **302**, with the first end **304a** configured to engage with a user's mouth and the second end **304b** configured to engage the proximal end of the holder **302**. The mouthpiece **304** is configured to sealingly engage with the holder **302** so that the first and second aerosol passageways **350**, **354** are in fluid communication so as to deliver the aerosol generated in the receiving chamber to the user.

[0186] In the depicted implementation, the removable mouthpiece **304** comprises a hollow body **356** (i.e., recess) and a stem **305** (or similar tubular structure) disposed within the hollow body **356** and extending from the first end **304a** to the second end **304b**. The stem **305** defines the second aerosol passageway **354** extending therethrough and is engaged with the inner housing **324** so as to fluidly couple with the aerosol passageway **350** of the inner housing **324**. The stem **305** may be coupled to the inner housing **324** via, for example, a press-fit or snap-fit engagement with the tubular structure **325** within the inner housing **324**. In some implementations, the stem **305** is sealingly engaged with the first aerosol passageway **350** in the holder **302**. For example, the stem **305** may include a sealing mechanism **359** similar to any of those disclosed herein.

[0187] In some implementations, the stem **305** of the mouthpiece **304** is offset from a central axis of the device **300**. Specifically, the stem **305** comprises a centrally located longitudinal axis **397b** offset from and generally in parallel with a centrally located longitudinal axis **397a** of the device **300**, such that the stem **305** of the mouthpiece, and the second aerosol passageway **354**, is aligned with the first aerosol passageway **350** in the inner housing **324** to define a direct vapor path from the cartridge **306** to the mouthpiece **304**. As shown in FIG. **13**, the second aerosol passageway **354** opens into a recess or receptacle **367** disposed within the proximal end of the mouthpiece **304** for delivery of the aerosol to the user. The offset arrangement simplifies the vapor path so as to minimize and/or eliminate loss of vapor (e.g., fewer joints or interfaces results in fewer leak points).

[0188] FIGS. **12** and **13** further depict the incorporation of an insert **365** into the proximal end of the mouthpiece **304**. Specifically, the receptacle **367** formed in the proximal end **304a** of the mouthpiece **304** is configured to secure the insert **365** therein. The insert **365** may be removably secured in the receptacle **367** via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement. The insert

365 defines a cavity **371** in fluid communication with the second aerosol passageway **354** and an outlet **358** for delivering the aerosol to the user. Generally, the insert **365** allows for customization of the device **300** (e.g., different size outlets, aerosol conditioning, incorporation of a flavoring, etc.) and may be easily removed for cleaning.

[0189] In some implementations, the longitudinally opposed second end **304b** is configured to engage an opening in the proximal end **302a** of the holder via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement. In other implementations, the mouthpiece **304** is removable secured to the holder **302** via a sealing mechanism that provides frictional resistance between the mouthpiece **304** and the holder **302** or other component therein. In some implementations, the inner housing **324** includes a retention structure **369a** disposed on a proximal end thereof and the second end **304b** of the mouthpiece **304** defines a mating retention structure **369b** configured to engage the retention structure **369a** on the inner housing **324**. The retention structure **369** may be a snap-fit mechanism or other type of reversible coupling mechanism. The retention structure **369** may further removably secure the mouthpiece **304** to the holder **302**. The mouthpiece **304** can be removed from the holder **302** for, for example, cleaning or customization of the device **300** (e.g., the use of interchangeable mouthpieces) by, for example, application of a pulling or twisting action to the mouthpiece **304** or actuating a release.

[0190] FIGS. **14A**, **14B**, and **15** illustrate another example implementation of an aerosol delivery device **500**. In particular, FIGS. **14A** and **14B** illustrate a perspective view and a cross-sectional perspective view, respectively, of an aerosol delivery device **500** that includes a removable mouthpiece **504** and a removable flow restrictor **565**. Specifically, the aerosol delivery device **500** comprises a holder **502** having a main body defining a proximal end **502a** and a distal end **502b**, where the holder **502** further defines a receiving chamber **510** configured to receive a removable cartridge **506** and an aerosol passageway **550** that extends through at least a portion of the main body. The removable cartridge **506** comprises an ignitable heat source **520** and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto. The mouthpiece **504** has a first end configured to engage with a user's mouth and a longitudinally opposed second end with a second aerosol passageway **554** extending longitudinally therebetween. In the depicted implementation, the mouthpiece **504** is coupled to the proximal end **502a** of the holder **502** via a body portion **555** disposed at the distal end of the mouthpiece **504**. The body portion **555** is configured to removably and/or sealingly engage an opening in the proximal end of the holder **502**.

[0191] Disposed generally between the holder **502** and the mouthpiece **504** is the removable flow restrictor **565** (see FIGS. **16A** and **16B**). The flow restrictor **565** comprises an outer surface **565c** configured to be removably secured within the holder and an inner surface **565d** defining a third aerosol passageway **553**, where the flow restrictor is configured to be at partially disposed within the first aerosol passageway **550**, the second aerosol passageway **554**, or both. In some embodiments, the inner surface **565d** of the flow restrictor **565** is tapered along a length thereof and defines an orifice **515** at the proximal end thereof that can be configured to provide a pressure drop between the first aerosol passageway **550** and the second aerosol passageway **554** when installed. However, the inner surface **565d** may define a variety of profiles (e.g., cylindrical, stepped, etc.) to suit a particular application. In some embodiments, the removable flow restrictor **565** is configured to sealingly engage with the first aerosol passageway, the second aerosol passageway, or both. Alternatively, or additionally, the flow restrictor **565** may be removably secured in the holder **502** via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, a frictional engagement, or a magnetic engagement.

[0192] As shown in FIGS. **16A** and **16B**, the flow restrictor **565** comprises a body portion **565a** and a lip portion **565b** disposed at a proximal end thereof with both defined by the outer surface **565c**. As can be seen in FIG. **14B**, the body portion **565a** is disposed within the first aerosol passageway

550 with the lip portion **565b** configured to engage the proximal end **502a** of the main body and disposed within the second aerosol passageway **554** as described in greater detail below. The third aerosol passageway **553** provides fluid communication between the first aerosol passageway **550** and the second aerosol passageway **554**. The overall size, shape, and finish of the flow restrictor **565** will be selected to suit a particular application (e.g., manner and location of installation, performance characteristics, etc.) For example, the outer surface **565c** may have a surface finish that enhances the fit and scaling of the flow restrictor **565** with the first and/or second aerosol passageways **550**, **554**, or include one or more grooves for holding a sealing arrangement (e.g., an O-ring) for sealing and/or frictionally engaging with the passageways **550**, **554**.

[0193] The mouthpiece **504** is removable so that the flow restrictor **565** may be easily removed for cleaning or replacement to, for example, change an operating characteristic of the device. Generally, the removable flow restrictor **565** allows for customization of the device **500**, specifically, the user's experience with the device **500**. For example, the flow restrictor **565** may have different size outlets, aerosol passageway configurations, thermal properties (e.g., for enhanced temperature control of the aerosol delivered to the user), or even the incorporation of a flavoring.

[0194] In the depicted implementation, the mouthpiece **504** is coupled to the holder **502** via the body portion **555** as disclosed above. The body portion **555** is sized and shaped to engage an opening in the proximal end of the holder **502**, such that the body portion **555** is disposed within the proximal end of the holder **502**, with or without a sealing mechanism, so as to be substantially flush with the proximal end **502a** of the holder. In some implementations, the body portion **555** may be coupled to the holder **502** via at least one fastener (e.g., a screw) and/or physically engage an inner wall of the holder **502**. The mouthpiece **504** further comprises a nozzle or extension **505** that makes up the first end of the mouthpiece and is configured to be engaged by the user's mouth. The nozzle **505** partially defines the second aerosol passageway **554** and terminates at an opening **558** configured to pass the generated aerosol to the user.

[0195] At the opposing side of the body portion **555**, a hollow stem **507** extends into the holder when assembled. Specifically, in some implementations, the main body of the holder **502** includes a tubular structure **521** disposed therein and extending along a length of the holder **502**. The tubular structure **521** at least partially defines the first aerosol passageway **550** and extends towards the proximal end of the holder **502** and is configured to engage at least a portion of the mouthpiece **504** to provide fluid communication between the first and second aerosol passageways **550**, **554** and deliver the aerosol to a user via the opening **558**. In the depicted implementation, the stem **507** engages with the tubular structure **521** with the flow restrictor essentially “sandwiched” therebetween. In some implementations, the flow restrictor **565** is first inserted into the tubular structure **521** of the holder so that the lip thereof abuts the proximal end of the tubular structure **521**, and then the mouthpiece **504** is secured to the proximal end of the holder **502** such that the stem **507** passes over the flow restrictor **565** and the proximal end of the tubular structure **521**, fluidly coupling the first, second, and third aerosol passageways **550**, **554**, **553**.

[0196] The mouthpiece **504** may be coupled to the holder **502** via an amount of frictional resistance sufficient to secure the mouthpiece **504** to the holder **502**, but minimal enough so that a user may remove the mouthpiece **504** without significant effort. For example, the mouthpiece may be removed from the holder by, for example, application of a pulling or twisting action to the mouthpiece **504** or actuating a release. The mouthpiece can be removed for access to the flow restrictor, which can then be removed for cleaning or replacement to customize the user's experience. The mouthpiece **504** may also be cleaned and/or replaced after removal.

[0197] The holder **502** further comprises an access door assembly **589** pivotably coupled to the main body via a pivot assembly **584** (e.g., pivot pin **584a**, receptacle **584b**), although in some implementations, the door assembly **589** may be slidingly or hingedly coupled to the holder **502**. As depicted in FIGS. **14A** and **15**, the door assembly **589** includes a door **588** configured to fit

substantially flush with an outer surface of the holder **502** in a closed configuration and sized and shaped to receive a chassis or inner housing **524** defining the receiving chamber **510** for receiving the cartridge **506** therein. The chassis **524** may comprise a plurality of material layers that provide for temperature control of the device, for example, thermal insulation to prevent heat from the cartridge being transferred to the holder and a user contacting a “hot” device. The assembly **589** further comprises a pair of static ignitor contacts **528** disposed proximate the distal end **502b** of the holder, a seal mechanism **560** configured to sealingly engage the receiving chamber **510** with the first aerosol passageway, and a biasing mechanism **542** configured to urge a loaded cartridge into contact with the ignitor contacts **528** when in the closed configuration. The door assembly **589** is moved between its open configuration and closed configuration via a spring-loaded slider button as discussed in greater detail with respect to FIGS. **17A-17C**.

[0198] The device **500** further comprises a power source **512** and a printed circuit board **518** disposed within the holder **502**. The power source **512** is in electrical communication with the printed circuit board **518** and the static ignitor contacts **528**. The printed circuit board **518** includes electrical contacts **529** (e.g., pogo pins) that contact the ignitor contacts **528** when the door assembly **589** is in the closed configuration. The printed circuit board **518** may further comprise a charging port **519** (e.g., a micro-USB connector) that is oriented on the printed circuit board so as to be disposed at one end of the holder **502**.

[0199] In the depicted implementation, an ignitor push button **540** is disposed in a side wall of the holder **502** and configured, so that when pressed by a user, activates the ignitor contacts **528** thereby igniting the heat source **520** of the cartridge **506** to produce the aerosol. Specifically, once the push button **540** is actuated, the electrical circuit is completed and electricity is delivered to the ignitor contacts **528**. In some implementations, the ignitor contacts **528** will only remain activated while the ignitor push button **540** is depressed. As such, in some implementations, the ignitor contacts **528** will be deactivated when the ignitor push button **540** is released. In some implementations, the ignitor push button **540** may be configured to activate the ignitor contacts **528** for a set time after release. In one implementation, the push button **540** extends through an opening **563** in the holder **502**. In some implementations, the button **540** is spring loaded and may return to an off position after igniting the heat source. The device **500** may further include an LED ring **541** proximate the push button **540** that may illuminate during ignition and/or change colors to indicate a state of the device **500**.

[0200] FIGS. **17A-17C** illustrate the loading and ejecting of the cartridge (i.e., consumable) **506** relative to the device **500**. Specifically, FIG. **17A** depicts the door assembly **589** in the closed configuration with the door assembly **589** enclosing the receiving chamber **510** within the holder **502**. In order to move the door assembly into the open configuration, the spring-loaded slider button **508** is slid forward or distally so as to release the door assembly **589** from the holder **502**. The door assembly **589** is biased into the open configuration as shown in FIG. **17B**, thereby exposing the chassis **524** and the receiving chamber **510** disposed therein. As further shown, the cartridge is inserted into the receiving chamber **510** with the ignitable heat source **520** end inserted first. Once the cartridge **506** is loaded, the door assembly **589** is pushed closed (the biasing force is small enough that a user may close the door assembly with a single finger) and the slide button **508** reconnects to the holder **502** to secure the door assembly **589** in the closed configuration as shown in FIG. **17A**.

[0201] In the closed configuration, the cartridge **506** is secured within the holder so as to be in fluid communication with the first aerosol passageway **550** (see FIG. **14B**). The ignitable heat source **520** is in contact with the ignitor contacts **528** via the biasing mechanism **542** and may be ignited so that the cartridge may be consumed (i.e., aerosol generated and delivered to the user via the aerosol passageways). After which, the cartridge **506** may be ejected from the device **500** as shown in FIG. **17C**. Specifically, the slide button **508** is slid forward or distally so as to release the door assembly **589** and expose the cartridge **506**. Once in the open configuration, the device **500** may be

turned upside-down, which allows the cartridge to fall out of the receiving chamber **510**. After ejection, a user may insert a new cartridge or simply close the door assembly **589** for later use. In some implementations, the device **500** may include a latching mechanism (not shown) configured to further secure the access door assembly **589** in the closed configuration. In some implementations, the latching mechanism may include a magnetic engagement, a threaded interface, a snap-fit, a detent, and/or be spring-loaded into the closed configuration.

[0202] FIGS. **18A**, **18B**, **19**, and **20A-20C** illustrate another example implementation of an aerosol delivery device **700**. In particular, FIGS. **18A** and **18B** illustrate a perspective view and a cross-sectional perspective view, respectively, of an aerosol delivery device **700** that includes a removable cartridge **706**, a mouthpiece **704**, a slider assembly **708**, and an ignition push button **740**. The aerosol delivery device **700** includes a two-part holder **702** defining a linear vapor path **743** and comprising an upper body portion **701** and a lower body portion **703**, each defining a proximal end and a distal end.

[0203] The lower body portion **703** defines a receiving chamber **710** disposed therein and configured to receive a removable cartridge **706** comprising an ignitable heat source **720** and a substrate portion that includes a substrate material having an aerosol precursor composition configured to form an aerosol upon application of heat thereto. The lower body portion **703** includes a pair of actuatable ignitor contacts **728** disposed proximate the distal end thereof and coupled thereto via a pair of contact arms **726**. The actuatable ignitor contacts **728** are configured to be engaged with the ignitable heat source **720** when the removable cartridge **706** is secured within the receiving chamber **710**. Additionally, the lower body portion **703** includes a window **782** disposed therein and configured to provide a view of at least a portion of the receiving chamber **710** so that a user may observe the cartridge **708** and/or electrical contacts **728**. All or a portion of the window **782** may comprise a transparent or translucent material (e.g., a polycarbonate, polyethylene terephthalate, acrylic, or the like). In some implementations, a portion of the lower body portion **703** may be made from a transparent or translucent material.

[0204] The upper body portion **701** defines a first aerosol passageway **750** extending therethrough and houses a power source **712**, a printed circuit board **718** with associated electronics, and the sliding actuator assembly **708**. The sliding actuator assembly **708** is slidably disposed within the upper body portion **701**, specifically within the first aerosol passageway **750**, and is configured to eject the removable cartridge from the lower body portion **703**. The upper body portion **701** and the lower body portion **703** are movably coupled together via one or more mechanisms **784** (e.g., a swivel joint), so that the lower body portion **703** may rotate relative to the upper body portion **701** between an open configuration exposing the receiving chamber **710** so that the removable cartridge may be loaded therein, and a closed configuration where the receiving chamber **710** and the first aerosol passageway **750** are in fluid communication and configured to deliver the aerosol generated from the cartridge to the mouthpiece **704**.

[0205] Additionally, the device **700** may include a sealing mechanism **772** disposed between the proximal end of the lower body portion **703** and the distal end of the upper body portion **701** (e.g., an O-ring disposed within a groove in the face of the proximal end of the lower body **703**) and configured to seal the receiving chamber **710** with the first aerosol passageway **750** so as to prevent aerosol leakage from the vapor path **743** and/or the ingress of ambient air. In some implementations, the aerosol delivery device **700** further comprises a locking mechanism **785** disposed on at least one of the lower body portion **703** or the upper body portion **701** that is configured to maintain the device in a closed orientation (i.e., the upper and lower body portions aligned and in fluid and/or electrical communication. The locking mechanism **785** may include, for example, one or more of magnets, friction, a snap fit, or a detent. However, in some other implementations, the upper body portion **701** and the lower body portion **703** are integrally formed together, or may be fixedly coupled with one another. Other manners of movably coupling the upper body portion **701** and the lower body portion **703** include a hinge joint, a sliding track, and

the like.

[0206] The mouthpiece **704** is located at the proximal end of the upper body portion **701** and has a first end and a longitudinally opposed second end with a second aerosol passageway **754** extending longitudinally therebetween. In the depicted implementation, the first end of the mouthpiece **704** is configured to engage with a user's mouth and the second end is configured to engage the proximal end of the upper body portion **703**. The mouthpiece **704** is configured to sealingly engage with the upper body portion **701** so that the first and second aerosol passageways **750**, **754** are in fluid communication so as to deliver the aerosol generated in the receiving chamber **710** to the user via the vapor path **743**. The mouthpiece **704** may be removably coupled to the upper body portion **701** to, for example, provide for cleaning or customization of the device **700**. However, in other implementations, the mouthpiece **704** may be integrally formed with the upper body portion **701**.

[0207] As further illustrated by the exploded view of FIG. **19**, the slider actuator assembly **708** comprises a generally tubular slider body **730** disposable within the upper body portion **701** so as to slide along a length of the upper body portion **701** in a first direction and a second direction. The slider body **730** defines a passageway extending therethrough that forms a third aerosol passageway **738** aligned with and extending through the first aerosol passageway **750** of the upper body portion **701**. The slider body **730** includes a first protrusion **731** extending from an outer surface thereof and extending through an opening **716** in a wall of the upper body portion **701** that is configured to move the slider body **730** between a loading position (e.g., slider body **730** fully disposed within the upper body portion **701**) and an ejecting position (e.g., the slider body **730** moved distally within the device **700**). The slider body **730** further includes a second protrusion or stem **733** extending from a distal end thereof. The stem **733** is configured to engage the removable cartridge **706** so as to advance the removable cartridge through the distal end of the lower body portion **703** when the actuator assembly **708** is moved into the ejecting position. Portions of the protrusions **731**, **733** extend into the third aerosol passageway **738** such that the vapor path **743** splits around those portions. Specifically, one or more portions of the first protrusion, the second protrusion, or both may extend into the portion of the third aerosol passageway **738** within the slider body **730** so that the aerosol generated by the cartridge **706** and pulled into the mouthpiece **704** is split by the one or more portions when traveling through the tubular body. In some implementations, the slider body **730** comprises a longitudinally oriented baffle **739** extending inwardly from an interior wall thereof, where the baffle divides the aerosol passageway **738** extending through slider body.

[0208] The upper body portion **701** further defines two cavities **707**, **709**, where the first cavity **707** further defines the first aerosol passageway **750** and is configured to receive the slider body **730** therein, and the second cavity is configured to house the power source **712** and the printed circuit board **718**. Additionally, the actuator assembly **708**, specifically the slider body **730**, includes a sealing arrangement for sealingly engaging with an internal surface of the first cavity **707** (e.g., to avoid aerosol leakage or undesirable air ingress). In the depicted implementation, the sealing arrangement comprises a pair of O-rings **760** disposed within grooves **761** disposed proximate the distal and proximal ends of the slider body **730**. However, other configurations of the sealing arrangement are contemplated and considered within the scope of the disclosure.

[0209] The lower body portion **703** also defines two cavities **707'**, **709'** that are generally aligned with the cavities **707**, **709** of the upper body portion **701** when in the closed configuration. Specifically, the first cavity **707'** at least partially defines the receiving chamber **710** and opposing openings **715**, **715'** and in some implementations includes a bar **711** or other structure for supporting the window **782** and/or guiding the cartridge **706** during insertion. In the depicted implementation, the lower body portion **703** defines a cut-out or other opening that exposes the receiving chamber **710** and is configured to receive the window **782** therein. The window **782** may be installed or otherwise coupled to the lower body portion **703** via an adhesive, snap fit, or other means known in the art. The cavity **707'**/receiving chamber **710** includes a groove or other structure

for securing a retention mechanism **776** therein that frictionally and/or sealingly engages with an outer surface of the cartridge **706** as described below. In the depicted implementation, the retention mechanism **776** is an O-ring.

[0210] The second cavity **709'** is generally configured to house various electronics and other mechanisms necessary to provide power to the ignitor contacts **728** and actuate same for igniting the heat source **720** of the cartridge **706**. For example, the contact arms **726** are electrically coupled to the power source within the second cavity **709'** and extend through a wall of the second cavity **709'** so as to position the ignitor contacts **728** within the receiving chamber **710**. The lower body portion **703** further defines a set of openings **763** therethrough that are configured to engage with the actuator buttons **740** and light emitting diodes (LED) **741** that are disposed on both sides of the lower body portion **703** and are described below.

[0211] The operation of the device **700** generally, and the slider actuator assembly **708** specifically, is described with respect to FIGS. **20A-20C**. Specifically, FIG. **20A** represents the cartridge **706** being loaded into the device **700** (i.e., the actuator assembly in the loading position), FIG. **PA3-11B** represents the device **700** during ignition and smoking, and FIG. **20C** represents the cartridge **706** being ejected from the device **700** (i.e., the actuator assembly in the ejection position).

[0212] Referring to FIG. **20A**, in order to load the cartridge **706** into the receiving chamber **710**, the lower body portion **703** is rotated or otherwise offset (e.g., twisted) from the upper body portion **701** so as to expose the receiving chamber via opening **715'**. Prior to rotating the body portions, the actuator assembly **708** is moved into the loading position (i.e., fully retracted towards the mouthpiece **704**) so that the sliding body **730** is fully disposed within the first cavity **707** of the upper body portion **701**. The cartridge **706** is manually inserted into the receiving chamber **710** of the lower body portion **703**, so as to locate the cartridge **706** into a lighting and/or use position, where the cartridge is sealingly secured within the chamber **710** via the retention mechanism **776** so that the ignitable heat source **720** operatively aligns with the ignitor contacts **728**. After loading, the upper and lower body portions are moved back into alignment so that the sealed end of the cartridge **706** is in fluid communication with the first aerosol passageway **750**. The fit between the upper and lower body portions is such that there is no aerosol leakage or air ingress therebetween, with or without the use of additional sealing arrangements as described above.

[0213] With reference to FIG. **20B**, in the lighting/use position, the distal end of the cartridge **706** is located proximate the distal end of the lower body portion **703** such that the entire cartridge **706** is located inside of the receiving chamber **710**. In particular, in the lighting/use position of the depicted implementation, the heat source **720** portion of the cartridge **706** is also positioned proximate the distal end of the lower body portion **703** and aligned with the ignitor contacts **728** in the lighting position. The heat source **720** is ignited via the aligned push buttons **740** disposed on the opposite sides of the lower body portion **703** of the aerosol delivery device **700**. The buttons **740** are movably coupled to the lower body portion, with or without a sealing arrangement, so that a user may depress both buttons simultaneously (e.g., via a pinching action) so as to engage and deflect the contact arms **726** and by extension move the ignitor contacts **728** into contact with the ignitable heat source **720**. Once released, the buttons **740** return to their original position, at least in part via a spring action from the deflected contact arms **726** and/or a return biasing element. In some implementations, the ignitor contacts **728** will only remain activated while the ignitor push buttons **740** are depressed. As such, in some implementations, the ignitor contacts **728** will be deactivated when the ignitor push buttons **740** are released. In some implementations, the ignitor push buttons **740** may be configured to activate the ignitor contacts **728** for a set time after release. The device **700** also includes a pair of LEDs **741** that may illuminate during ignition and/or change colors to indicate a state of the device **700**. Additionally, a user may be able to observe ignition via the window **782**.

[0214] In some implementations, the device **700** may include an ejection mechanism as shown in FIG. **20C**. Generally, the ejection mechanism is configured to eject the cartridge **706** from the distal

end of lower body portion **703** via opening **715**. Between loading and ejection, the cartridge **706** passes through the second cavity **709'**. In one implementation, the ejection mechanism is incorporated in to the actuator assembly **708**, so that when the slider protrusion **731** (and actuator assembly **708**) is moved forward, the ejection mechanism engages one end of the cartridge **706** and pushes the cartridge out of the receiving chamber **710** and out of the aerosol delivery device **700** through the opening **715** in the lower body portion **703**. Specifically, a user can slide the actuator assembly **708** forward (i.e., away from the mouthpiece) using, for example, their thumb and the protrusion **731** so that the inner stem **733** of the slider body **730** enters into the cavity **707'** of the lower body portion **703** and engages the cartridge **706** pushing it forward and disengaging the cartridge from the retention mechanism **776**. After which, the cartridge **706** may be pulled out of or allowed to drop out of the device **700**.

[0215] In the depicted implementations, the outer housing or holder may comprise a rigid material. For example, the holders **102**, **202**, **302**, **402**, **502**, **702** of the depicted implementations may be constructed of an aluminum material; however, in other implementations, the holders may be constructed of other materials, including other metal materials (such as, for example, stainless steel, aluminum, brass, copper, silver, gold, bronze, titanium, various alloys, etc.), or graphite materials, or ceramic materials, or plastic materials, or any combinations thereof. In some implementations, at least a portion of the heat source and/or at least a portion of the substrate material may be circumscribed by a paper foil laminate. In some implementations, the cartridge may comprise an enclosure comprising a laminate that contains a heat source and a beaded substrate material. Some examples of laminates and/or enclosures that may be applicable to the present disclosure can be found in U.S. Pat. App. Pub. No. 2020/0128880 to Gage et al., which is incorporated herein by reference in its entirety. Other examples of cartridges are described herein below with respect to FIGS. **21** and **22**.

[0216] In some implementations, the holder (or any components thereof, such as inner housings, collars, etc.) may be made of moldable plastic materials such as, for example, polycarbonate, polyethylene, acrylonitrile butadiene styrene (ABS), polyamide (Nylon), or polypropylene. In other implementations, the holder may be made of a different material, such as, for example, a different plastic material, a metal material (such as, but not limited to, stainless steel, aluminum, brass, copper, silver, gold, bronze, titanium, various alloys, etc.), a graphite material, a glass material, a ceramic material, a natural material (such as, but not limited to, a wood material), a composite material, or any combinations thereof. The holders may be formed via extrusion. As noted above, the mouthpiece portion of some implementations is separable from the main body, while in other implementations, the mouthpiece portion may be integral with the main body. In any event, the mouthpiece portion and the main body may be made of the same material or different materials. In various implementations comprising a separable mouthpiece portion, the mouthpiece portion may be coupled to the main body in a variety of ways, including, for example, via one or more of a snap-fit, interference fit, screw thread, magnetic, and/or bayonet connection. In other implementations, the mouthpiece portion may be integral with the main body and thus may not be separable.

[0217] In the depicted implementations, the holder includes walls that are substantially solid and non-porous; however, in other implementations one or more of these walls of a holder may have other configurations. For example, in some implementations one or more of the walls of a holder may be non-solid and/or substantially porous or may include one or more non-solid and/or substantially porous portions. In some implementations, for example, the holder may include one or more apertures that may facilitate access of oxygen to the heat source. Alternatively, or additionally, other implementations may include one or more apertures that may mix with the aerosol generated during a draw. In such a manner, in the use position the one or more apertures may be located proximate the heat source, thus providing the heat source with additional access to oxygen during combustion. In some implementations, the holder may include one or more

apertures downstream from the heat source. For example, in some implementations the holder may include apertures that extend into the aerosol passage of the holder that may mix with aerosol generated by the substrate material of the cartridge.

[0218] As described above, the holder of various implementations of the present disclosure includes a lighting/use position. In some implementations, the holder may also have an extinguishment position. In such a manner, the extinguishment position may be configured such that the heat source of a cartridge is deprived of sufficient oxygen to sustain combustion. In some implementations, the extinguishment position may be obtained by a further action of the holder. In other implementations, one or more additional features may be included such that an extinguishment position may be achieved by actuating the one or more additional features. In particular, the holder of one implementation may include an air impermeable cover feature located proximate the distal end of the holder that may be mechanically or manually actuatable (e.g., by rotating the cover feature over the end of the main body and/or by sliding the cover feature across the end of the main body) such that in the extinguishment position, the cover feature substantially covers the open end of the holder and the heat source of the cartridge is deprived of sufficient oxygen to sustain combustion. In another implementation, the holder may include a detachable feature, such as, for example, an end cap, that may be used to achieve the extinguishment position. For example, in some implementations a separate end cap may be attachable over the distal end of the holder such that, once attached, the heat source of the cartridge is deprived of sufficient oxygen to sustain combustion. Such an end cap could also be used to cover the end of the second body portion when not in use, such as, for example, to prevent dirt and/or foreign objects from entering into the device. Additionally, or alternatively, in some implementations the holder of the present disclosure may include an air permeable cover feature (e.g., a cover feature comprising a plurality of openings or a cover feature comprising a mesh) that protects the heat source of the cartridge in the lighting/use position. For example, the holder of one implementation may include an air permeable cover feature located proximate the distal end of the holder that may be mechanically or manually actuatable (e.g., by rotating the cover feature over the end of the holder and/or by sliding the cover feature across the end of the holder) such that once ignited, the cover feature may be actuated to substantially cover the open end of the holder while maintaining sufficient access of oxygen to the heat source.

[0219] In various implementations, a removable cartridge may have other configurations for use with a holder of the present disclosure. For example, FIG. 21 illustrates a perspective view of a removable cartridge **606**, according to another example implementation of the present disclosure. In the depicted implementation, the cartridge **606** defines a proximal end **690** and a distal end **692**. The cartridge **606** of the depicted implementation further includes an ignitable heat source **620**, which comprises a fuel element **694**, a substrate portion **622**, which comprises a substrate material **696** (see FIG. 22), and an outer housing **698** configured to circumscribe at least a portion of the ignitable heat source **620** and the substrate material **622**. It should be noted that although in the depicted implementation the cartridge **606** has a substantially cylindrical overall shape, in various other implementations, the cartridge or any of its components may have a different shape. For example, in some implementations the cartridge (and/or any of its components) may have a substantially rectangular shape, such as a substantially rectangular cuboid shape. In other implementations, the cartridge (and/or any of its components) may have other hand-held shapes. Some examples of cartridge configurations that may be applicable to the present disclosure can be found in U.S. patent application Ser. No. 16/515,637, filed on Jul. 18, 2019, and titled Aerosol Delivery Device with Consumable Cartridge, which is incorporated herein by reference in its entirety.

[0220] In some implementations, a barrier may exist between the heat source and the substrate material. In some implementations, such a barrier may comprise a disc that may include one or more apertures therethrough. In some implementations, the barrier may be constructed of a metal

material (such as, for example, stainless steel, aluminum, brass, copper, silver, gold, bronze, titanium, various alloys, etc.), or a graphite material, or a ceramic material, or a plastic material, or any combinations thereof. In some implementations, a heat transfer component, which may or may not comprise a barrier, may exist between the heat source and the substrate material. Some examples of heat transfer components are described in U.S. Pat. App. Pub. No. 2019/0281891 to Hejazi et al., which is incorporated herein by reference in its entirety. In some implementations, a barrier and/or a heat transfer component may prevent or inhibit combustion gasses from being drawn through the substrate material (and/or from being drawn through air passageways through which aerosol is drawn).

[0221] In various implementations, the heat source may be configured to generate heat upon ignition thereof. In the depicted implementation, the ignitable heat source **620** comprises a combustible fuel element **694** that has a generally cylindrical shape and that incorporates a combustible carbonaceous material. In other implementations, the heat source may have a different shape, for example, a prism shape having a cubic or hexagonal cross-section. Carbonaceous materials generally have a high carbon content. Some carbonaceous materials may be composed predominately of carbon, and/or typically have carbon contents of greater than about 60 percent, generally greater than about 70 percent, often greater than about 80 percent, and frequently greater than about 90 percent, on a dry weight basis.

[0222] In some instances, the heat source may incorporate elements other than combustible carbonaceous materials (e.g., tobacco components, such as powdered tobaccos or tobacco extracts; flavoring agents; salts, such as sodium chloride, potassium chloride and sodium carbonate; heat stable graphite a hollow cylindrical (e.g., tube) fibers; iron oxide powder; glass filaments; powdered calcium carbonate; alumina granules; ammonia sources, such as ammonia salts; and/or binding agents, such as guar gum, ammonium alginate and sodium alginate). In other implementations, the heat source may comprise a plurality of ignitable objects, such as, for example, a plurality of ignitable beads. It should be noted that in other implementations, the heat source may differ in composition or relative content amounts from those listed above. For example, in some implementations different forms of carbon could be used as a heat source, such as graphite or graphene. In other implementations, the heat source may have increased levels of activated carbon, different porosities of carbon, different amounts of carbon, blends of any above mentioned components, etc. In still other implementations, the heat source may comprise a non-carbon heat source, such as, for example, a combustible liquefied gas configured to generate heat upon ignition thereof. For example, in some implementations, the liquefied gas may comprise one or more of petroleum gas (LPG or LP-gas), propane, propylene, butylenes, butane, isobutene, methyl propane, or n-butane. In still other implementations, the heat source may comprise a chemical reaction based heat source, wherein ignition of the heat source comprises the interaction of two or more individual components. For example, a chemical reaction based heat source may comprise metallic agents and an activating solution, wherein the heat source is activated when the metallic agents and the activating solution come in contact. Some examples of chemical based heat sources can be found in U.S. Pat. No. 7,290,549 to Banerjee et al., which is incorporated herein by reference in its entirety. Combinations of heat sources are also possible. Although specific dimensions of an applicable heat source may vary, in the depicted implementation, the ignitable heat source **620** has a length in an inclusive range of approximately 5 mm to approximately 20 mm, and in some implementations may be approximately 12 mm, and an overall diameter in an inclusive range of approximately 3 mm to approximately 8 mm, and in some implementations may be approximately 4.8 mm (and in some implementations, approximately 7 mm).

[0223] Although in other implementations the heat source may be constructed in a variety of ways, in the depicted implementation, the ignitable heat source **620** is extruded or compounded using a ground or powdered carbonaceous material, and has a density that is greater than about 0.5 g/cm.³, often greater than about 0.7 g/cm.³, and frequently greater than about 1

g/cm.sup.3, on a dry weight basis. See, for example, the types of fuel source components, formulations and designs set forth in U.S. Pat. No. 5,551,451 to Riggs et al. and U.S. Pat. No. 7,836,897 to Borschke et al., which are incorporated herein by reference in their entireties.

[0224] In various implementations, the heat source may have a variety of forms, including, for example, a substantially solid cylindrical shape or a hollow cylindrical (e.g., tube) shape. In other implementations, the heat source may comprise a plurality of hollow or substantially solid spheres, which in some implementations may comprise substantially the same size, and in other implementations may comprise more than one size. In various implementations, the heat source may be made in variety of ways, including, but not limited to, via extrusion, injection molding, compression molding, etc. The ignitable heat source **620** of the depicted implementation comprises an extruded monolithic carbonaceous material that has a generally cylindrical shape that includes a plurality of internal passages **691** extending longitudinally from a first end of the ignitable heat source **620** to an opposing second end of the ignitable heat source **620**. In the depicted implementation there are approximately thirteen internal passages **691** comprising a single central internal passage **691a**, six surrounding internal passages **680b**, which are spaced from the central internal passages **691a** and have a similar size (e.g., diameter) to that of the central internal passage **691a**, and six peripheral internal passages **691c**, which are spaced from an outer surface of the ignitable heat source **620** and are smaller in diameter than that of the central internal passage **691a**. It should be noted that in other implementations, there need not be a plurality of internal passages and/or the plurality of internal passages may take other forms and/or sizes. For example, in some implementations, there may be as few as two internal passages, and still other implementations may include as few as a single internal passage. Still other implementations may include no internal passages at all. Additional implementations may include multiple internal passages that may be of unequal diameter and/or shape and which may be unequally spaced and/or located within the heat source.

[0225] Some implementations may alternatively, or additionally, include one or more peripheral grooves that extend longitudinally from a first end of the heat source to an opposing second end, although in other implementations the grooves need not extend the full length of the heat source. In some implementations, such grooves may be substantially equal in width and depth and may be substantially equally distributed about a circumference of the heat source. In such implementations, there may be as few as two grooves, and still other implementations may include as few as a single groove. Still other implementations may include no grooves at all. Additional implementations may include multiple grooves that may be of unequal width and/or depth, and which may be unequally spaced around a circumference of the heat source. In still other implementations, the heat source may include flutes and/or slits extending longitudinally from a first end of the extruded monolithic carbonaceous material to an opposing second end thereof. In some implementations, the heat source may comprise a foamed carbon monolith formed in a foam process of the type disclosed in U.S. Pat. No. 7,615,184 to Lobovsky, which is incorporated herein by reference in its entirety. As such, some implementations may provide advantages with regard to reduced time taken to ignite the heat source. In some other implementations, the heat source may be co-extruded with a layer of insulation (not shown), thereby reducing manufacturing time and expense. Other implementations of fuel elements include carbon fibers of the type described in U.S. Pat. No. 4,922,901 to Brooks et al. or other heat source implementations such as is disclosed in U.S. Pat. App. Pub. No. 2009/0044818 to Takeuchi et al., each of which is incorporated herein by reference in its entirety. Further examples of heat sources including debossed heat source systems, methods, and smoking articles that include such heat sources are disclosed in U.S. Pat. App. Pub. No. 2019/0254335 to Spicer et al., which is incorporated herein by reference in its entirety.

[0226] Generally, the heat source is positioned sufficiently near an aerosol delivery component (e.g., the substrate portion) having one or more aerosolizable components so that the aerosol formed/volatilized by the application of heat from the heat source to the aerosolizable components

(as well as any flavorants, medicaments, and/or the like that are likewise provided for delivery to a user) is deliverable to the user by way of the mouthpiece. That is, when the heat source heats the substrate component, an aerosol is formed, released, or generated in a physical form suitable for inhalation by a consumer. It should be noted that the foregoing terms are meant to be interchangeable such that reference to release, releasing, releases, or released includes form or generate, forming or generating, forms or generates, and formed or generated. Specifically, an inhalable substance is released in the form of a vapor or aerosol or mixture thereof. Additionally, the selection of various smoking article elements is appreciated upon consideration of commercially available electronic smoking articles, such as those representative products listed in the background art section of the present disclosure.

[0227] FIG. 22 illustrates a longitudinal cross-section view of the cartridge **606** of FIG. 21. As shown in the figure, the substrate material **622** of the depicted implementation has opposed first and second ends, with the ignitable heat source **620** disposed adjacent the first end of the substrate material **622**. Although dimensions and cross-section shapes of the various components of the cartridge may vary due to the needs of a particular application, in the depicted implementation the cartridge **606** may have an overall length in an inclusive range of approximately 10 mm to approximately 50 mm and a diameter in an inclusive range of approximately 2 mm to approximately 20 mm. In addition, in the depicted implementation the outer housing **698** may have a thickness in the inclusive range of approximately 0.05 mm to 0.5 mm. Furthermore, in the depicted implementation the substrate portion **622** may have a length in the inclusive range of approximately 5 mm to 30 mm and a diameter slightly less than that of the overall cartridge in order to accommodate the thickness of the housing **698**, such as, for example, a diameter in an inclusive range of approximately 2.9 mm to approximately 9.9 mm. In the depicted implementation, the substrate material **622** comprises tobacco beads, which may have diameter sizes in range of approximately 0.5 mm to 2.0 mm, although in other implementations the size may differ. In other implementations, the substrate material may be a granulated tobacco material or cut filler tobacco. Although other implementations may differ, in the depicted implementation the outer housing **698** of the cartridge **606** is filled to about 80-90% capacity to allow for insertion of the fuel element **694**.

[0228] In the depicted implementation, the substrate portion **622** comprises a substrate material **696** having a single segment, although in other implementations the substrate portion may include one or more additional substrate material segments. For example, in some implementations, the aerosol delivery device may further comprise a second substrate material segment (not shown) having opposed first and second ends. As described above, in various implementations, one or more of the substrate materials may include a tobacco or tobacco related material, with an aerosol precursor composition associated therewith. In other implementations, non-tobacco materials may be used, such as a cellulose pulp material. In other implementations, the non-tobacco substrate material may not be a plant-derived material. Other possible compositions and/or components for use in a substrate material (and/or substrate materials) are described above. Reference is also made to the discussion above regarding various possible shapes, aerosol precursor compositions, additives, flavorants, etc. of the substrate material.

[0229] As shown in FIGS. 21 and 22, the outer housing **698** of the cartridge **606** of the depicted implementation is configured to circumscribe at least a portion of the substrate portion **622**, including the substrate material **696**. In the depicted implementation, the outer housing **698** is also configured to circumscribe a portion of the ignitable heat source **620**. In some implementations, the outer housing may circumscribe the entire heat source. In the depicted implementation, the outer housing comprises a rigid material. For example, the outer housing **698** of the depicted implementation is constructed of an aluminum material; however, in other implementations the outer housing may be constructed of other materials, including other metal materials (such as, for example, stainless steel, aluminum, brass, copper, silver, gold, bronze, titanium, various alloys,

etc.), or graphite materials, or ceramic materials, or plastic materials, or any combinations thereof. In some implementations, at least a portion of the heat source and/or at least a portion of the substrate material may be circumscribed by a paper foil laminate. In some implementations, the cartridge may comprise an enclosure comprising a laminate that contains a heat source and a beaded substrate material. Some examples of laminates and/or enclosures that may be applicable to the present disclosure can be found in U.S. Pat. App. Pub. No. 2020/0128880 to Gage et al., which is incorporated herein by reference in its entirety.

[0230] In the depicted implementation, the outer housing **698** is constructed as a tube structure that substantially encapsulates the substrate material **622**; however, as noted above, in other implementations the outer housing may have other shapes. Although the shape of the outer housing may vary, in the depicted implementation the outer housing **698** comprises a tube structure having an open end and a closed end. The depicted implementation of the outer housing **698** also includes one or more end apertures **693** located on the closed end of the outer housing **698** that are configured to allow aerosolized vapor (herein alternatively referred to as a “vapor” or “aerosol”) to pass therethrough. The end apertures **693** of the depicted implementation are in the form of a pair of elongate rounded slots; however, in other implementations the end apertures may have any form that permits passage of the aerosol therethrough. As such, it will be appreciated that the end apertures **693** can comprise fewer or additional apertures and/or alternative shapes and sizes of apertures than those illustrated.

[0231] In various implementations, the present disclosure may also be directed to kits that provide a variety of components as described herein. For example, a kit may comprise a holder with one or more cartridges. In another implementation, a kit may comprise a plurality of holders. In further implementations, a kit may comprise a plurality of cartridges. In yet another implementation, a kit may comprise a plurality of holders and a plurality of cartridges. The inventive kits may further include a case (or other packaging, carrying, or storage component) that accommodates one or more of the further kit components. The case could be a reusable hard or soft container. Further, the case could be simply a box or other packaging structure. In some implementations, a brush or other cleanout accessory may be included in a kit. The cleanout accessory may be configured to be inserted in a cartridge receiving chamber of the holder, or, in other implementations, inserted in a separate aperture that enables a user to remove debris from the cartridge receiving chamber.

[0232] Many modifications and other embodiments of the disclosure will come to mind to one skilled in the art to which this disclosure pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the disclosure is not to be limited to the specific embodiments disclosed herein and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

Claims

1. An aerosol delivery device comprising: a holder comprising a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body; a mouthpiece including a first end and a longitudinally opposed second end with a second aerosol passageway extending longitudinally therebetween, wherein the first end is configured to engage with a user's mouth and the second end is configured to engage the proximal end of the holder; and a removable flow restrictor comprising an outer surface configured to be removably secured within the holder and an inner surface defining a third aerosol passageway.
2. The aerosol delivery device of claim 1, wherein the flow restrictor is configured to be at least partially disposed within the first aerosol passageway, the second aerosol passageway, or both.

3. The aerosol delivery device of claim 1, wherein the removable flow restrictor is configured to sealingly engage the first aerosol passageway, the second aerosol passageway, or both.
4. The aerosol delivery device of claim 1, wherein the flow restrictor comprises a body portion and a lip portion disposed at a proximal end thereof, the lip portion configured to engage the proximal end of the main body.
5. The aerosol delivery device of claim 4, wherein the body portion is disposed within the first aerosol passageway.
6. The aerosol delivery device of claim 1, wherein the removable flow restrictor is configured to provide fluid communication between the first aerosol passageway and the second aerosol passageway.
7. The aerosol delivery device of claim 1, wherein the inner surface of the flow restrictor is tapered along a length thereof.
8. The aerosol delivery device of claim 7, wherein the inner surface of the removable flow restrictor defines an orifice configured to provide a pressure drop between the first aerosol passageway and the second aerosol passageway.
9. The aerosol delivery device of claim 1, wherein the mouthpiece comprises a body portion configured to engage the proximal end of the main body and a hollow stem extending therethrough, the stem at least partially defining the second aerosol passageway and configured to receive the flow restrictor therein.
10. The aerosol delivery device of claim 1 further comprising a plurality of interchangeable removable flow restrictors.
11. An aerosol delivery device comprising: a holder comprising a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body; a mouthpiece including a first end and a longitudinally opposed second end with a second aerosol passageway extending longitudinally therebetween, wherein the first end is configured to engage with a user's mouth and the second end is configured to engage the proximal end of the holder; and an inner housing disposed within the main body of the holder and defining a first port disposed proximate a first end of the inner housing, a second port disposed proximate a second end of the inner housing, and a first channel disposed in an outer surface of the inner housing and fluidly coupling the first port and the second port to form a third aerosol passageway, wherein the first port is in fluid communication with the first aerosol passageway, the second port is in fluid communication with the second aerosol passageway and the first, second, and third aerosol passageways are configured to form a continuous vapor path from the distal end of the main body to the first end of the mouthpiece for passing an aerosol generated from the removable cartridge to a user.
12. The aerosol delivery device of claim 11, wherein the inner housing defines a second channel disposed in the outer surface thereof and oriented opposite of the first channel.
13. The aerosol delivery device of claim 12, wherein the first and second channels merge at the first port and the second port.
14. The aerosol delivery device of claim 12, wherein the inner housing is disposed within the main body so that an inner surface of the holder encloses the first and second channels.
15. An aerosol delivery device comprising: a holder comprising a main body defining a proximal end and a distal end, the main body further defining a receiving chamber configured to receive a removable cartridge and a first aerosol passageway that extends through at least a portion of the main body; and a removable mouthpiece comprising: a first portion defined by a first end and a longitudinally opposed second end; and a second portion that extends from the longitudinally opposed second end, wherein the first and second portions define a second aerosol passageway extending therethrough, the first end of the first portion is configured to engage with a user's mouth, the second end of the first portion is configured to engage with the proximal end of the

holder, and the second portion is configured to extend within the holder.

16. The aerosol delivery device of claim 15, wherein the second end of the first portion is configured to engage an opening in the proximal end of the holder via at least one of complementary-threaded surfaces for a screw-type engagement, a press-fit engagement, a snap-fit engagement, or a magnetic engagement.

17. The aerosol delivery device of claim 15, wherein a central axis of the second portion of the mouthpiece is offset from a central axis of the first portion of the mouthpiece.

18. The aerosol delivery device of claim 15, wherein the second portion of the mouthpiece is sealingly engaged with the first aerosol passageway in the holder.

19. The aerosol delivery device of claim 18, wherein the second portion of the mouthpiece includes a sealing mechanism disposed about an exterior surface thereof.

20. The aerosol delivery device of claim 19, wherein the sealing mechanism comprises an O-ring disposed within a groove defined by the exterior surface of the second portion of the mouthpiece.
