

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286989

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

LEE; Yongjune et al.

DISPLAY DEVICE

Abstract

A display apparatus includes: a first display panel; a second display panel, each of the first display panel and the second display panel including a light-emitting area and a transmission area through which light is transmitted; a first driving device including a first motor, the first driving device configured to move at least one of the first display panel or the second display panel to at least partially overlap each other; and a second driving device including a second motor, the second driving device configured to move at least one of the first display panel or the second display panel in a front and rear direction to adjust a distance between the first display panel and the second display panel.

Inventors: LEE; Yongjune (Suwon-si, KR), Park; Jaehoo (Suwon-si, KR), Im; Sangkyun (Suwon-si, KR), Jung; Kilsoo (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 91589036

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 19/217820

Filed: May 23, 2025

Foreign Application Priority Data

KR

10-2022-0182350

Dec. 22, 2022

Related U.S. Application Data

parent WO continuation PCT/KR2023/016027 20231017 PENDING child US 19217820

Publication Classification

Int. Cl.: H04N13/395 (20180101); H04N13/302 (20180101); H04N13/398 (20180101)

U.S. Cl.:

CPC H04N13/395 (20180501); H04N13/302 (20180501); H04N13/398 (20180501);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] This application is a continuation of International Application No. PCT/KR2023/016027, filed on Oct. 17, 2023, in the Korean Intellectual Property Receiving Office, which is based on and claims priority to Korean Patent Application No. 10-2022-0182350, filed on Dec. 22, 2022, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

[0002] The disclosure relates to a display apparatus, and more particularly, to a display apparatus configured to move a display panel.

2. Description of Related Art

[0003] In general, a display apparatus may be a device for displaying images, and recently transparent displays and three-dimensional image displays are being developed.

[0004] The transparent display apparatus may be used in various fields by increasing a transmittance of a display panel to allow objects located behind the display panel to be seen.

[0005] In order to provide the three-dimensional effect to an image displayed on the transparent display, a plurality of transparent displays may be overlapped and used, but there is a characteristic that the transmittance decreases as the image passes through the display.

[0006] Therefore, it may be required to move the display panel depending on the image that the transparent display wants to display, and a display apparatus suitable for a wider range of purposes may be provided through variable arrangement of the transparent display.

SUMMARY

[0007] Provided is a display apparatus capable of moving a display panel.

[0008] Further, provided is a display apparatus capable of providing a three-dimensional image by overlapping a plurality of display panels.

[0009] Further still, provided is a display apparatus capable of providing a wide screen by expanding a plurality of display panels.

[0010] Further still, provided is a display apparatus capable of providing an image having the high resolution by overlapping a plurality of display panels.

[0011] Additional aspects of the disclosure will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the disclosure.

[0012] According to an aspect of the disclosure, a display apparatus may include: a first display panel; a second display panel, each of the first display panel and the second display panel including a light-emitting area and a transmission area through which light is transmitted; a first driving device including a first motor, the first driving device configured to move at least one of the first display panel or the second display panel to at least partially overlap each other;

[0013] and a second driving device including a second motor, the second driving device configured to move at least one of the first display panel or the second display panel in a front and rear direction to adjust a distance between the first display panel and the second display panel.

[0014] The light-emitting area of the second display panel may be positioned to correspond to the transmission area of the first display panel.

[0015] Each of the first display panel and the second display panel may include: a first wiring portion in which the light-emitting area is positioned; and a second wiring portion that intersects the first wiring portion and forms the transmission area with the first wiring portion, where the light-emitting area of the second display panel is positioned to overlap with at least a portion of the first wiring portion of the first display panel.

[0016] With respect to each of the first display panel and the second display panel, the first wiring portion and the second wiring portion may intersect each other vertically.

[0017] The first display panel and the second display panel may be movable to be arranged side by side to form a continuous screen.

[0018] At least one of the first display panel and the second display panel may be movable so that the first display panel and the second display panel to completely overlap each other.

[0019] Based on the overlap of the first display panel and the second display panel, the light-emitting area of the second display panel may be positioned to correspond to the transmission area of the first display panel.

[0020] Each of the first display panel and the second display panel may include: a first wiring portion in which the light-emitting area is positioned; and a second wiring portion that intersects the first wiring portion and forms the transmission area with the first wiring portion, where, based on the second display panel overlapping the first display panel, the light-emitting area of the second display panel is positioned to overlap at least a portion of the first wiring portion of the first display panel.

[0021] A size of the first display panel may be different from a size of the second display panel.

[0022] The second display panel may be smaller than the first display panel.

[0023] The display apparatus may further include: a third display panel that is movable to overlap at least a portion of the first display panel or the second display panel, where the third display panel is movable to be arranged side by side with the first display panel and the second display panel to form a continuous screen.

[0024] The first driving device may further include: a motor gear configured to be rotated by the first motor; a first gear configured to be rotated by a rotation of the motor gear; a first screw configured to be rotated together with the first gear; and a first transfer unit configured to be movable along the first screw.

[0025] The first driving device may further include: a second gear configured to be rotated by a rotation of the motor gear; a second screw configured to be rotated together with the second gear and positioned parallel to the first screw; and a second transfer unit configured to be movable along the second screw, where a thread of the second screw is in a different direction from a thread of the first screw.

[0026] The second driving device may further include: a moving block on the second display panel and movably coupled to the second transfer unit, where the moving block is movable in the front and rear direction based on a rotation of the second motor.

[0027] The display apparatus may further include: a controller configured to control the first driving device or the second driving device based on a user input, where the controller is further configured to, based on a control of the first driving device or the second driving device, operate in a first mode to expand an image display region and a second mode to increase a resolution.

[0028] Another aspect of the present disclosure provides a display apparatus including: a first display panel and a second display panel, each of the first display panel and the second display panel including a first wiring portion in which a light-emitting area is positioned, and a second wiring portion that intersects the first wiring portion and forms a transmission area together with the first wiring portion; a first driving device configured to move at least one of the first display panel or the second display panel to allow the first display panel to overlap at least a portion of the second display panel, and a second driving device configured to move at least one of the first display panel or the second display panel in a front and rear direction so as to adjust a distance

between the first display panel and the second display panel; and a controller configured to control the first driving device or the second driving device based on a user input. The controller may control the first driving device or the second driving device to allow the display apparatus to be operated in a first mode for expanding an image display region. The controller may control the first driving device or the second driving device to allow the display apparatus to be operated in a second mode for increasing the resolution. The controller may control the first driving device or the second driving device to allow the display apparatus to be operated in a third mode for increasing a transmittance in the second mode.

[0029] In response to the display apparatus being operated in the first mode, the controller may control the first driving device or the second driving device to allow the first display panel and the second display panel to be arranged side by side to form a single continuous screen. In response to the display apparatus being operated in the second mode, the controller may control the first driving device or the second driving device to allow the light-emitting area of the second display panel to be positioned to correspond to the transmission area of the first display panel. In response to the display apparatus being operated in the third mode, the controller may control the first driving device or the second driving device to allow at least a portion of the light-emitting area of the second display panel to be positioned to correspond to the first wiring portion of the first display panel.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0031] FIG. 1 is a view illustrating a display apparatus according to an embodiment;

[0032] FIG. 2 is a control block diagram of the display apparatus according to an embodiment;

[0033] FIG. 3 is a view illustrating a state in which display panels of the display apparatus of FIG. 1 are expanded and arranged according to an embodiment;

[0034] FIG. 4 is a view illustrating a light-emitting area and a transmission area forming the display panel of FIG. 3 according to an embodiment;

[0035] FIG. 5 is an enlarged view of a portion A, which is a portion of the light-emitting area and the transmission area of the display panel of FIG. 3 according to an embodiment;

[0036] FIG. 6 is a view illustrating a state in which the display panels of the display apparatus of FIG. 1 are overlapped and arranged according to an embodiment;

[0037] FIG. 7 is a view illustrating the light-emitting area and the transmission area forming the display panel of FIG. 6 according to an embodiment;

[0038] FIG. 8 is a view illustrating a structure of a light-emitting area and a transmission area forming a display panel of a display apparatus according to an embodiment;

[0039] FIG. 9 is a view illustrating a state in which the display panels of the display apparatus of FIG. 8 are overlapped and arranged according to an embodiment;

[0040] FIG. 10 is a view illustrating a state in which the display panels of the display apparatus of FIG. 8 are arranged in a manner different from that of FIG. 9 according to an embodiment;

[0041] FIG. 11 is a view illustrating a state in which a portion of the display panels of the display apparatus of FIG. 1 are overlapped and arranged according to an embodiment;

[0042] FIG. 12 is a view illustrating a state in which a first display panel is provided to be smaller than a second display panel according to an embodiment;

[0043] FIG. 13 is a view illustrating a state in which a first display panel is provided to be larger than a second display panel according to an embodiment;

[0044] FIG. **14** is a view illustrating a state in which a display apparatus according to one embodiment includes three display panels according to an embodiment; and
[0045] FIG. **15** is a view illustrating a state in which the display panels of the display apparatus of FIG. **14** are overlapped according to an embodiment.

DETAILED DESCRIPTION

[0046] Embodiments described in the disclosure and configurations shown in the drawings are merely examples of the embodiments of the disclosure, and may be modified in various different ways at the time of filing of the present application to replace the embodiments and drawings of the disclosure.

[0047] In addition, the same reference numerals or signs shown in the drawings of the disclosure indicate elements or components performing substantially the same function.

[0048] Also, the terms used herein are used to describe the embodiments and are not intended to limit and/or restrict the disclosure. The singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. In this disclosure, the terms “comprising”, “including”, “having”, and the like are used to specify features, numbers, steps, operations, elements, components, or combinations thereof, but do not preclude the presence or addition of one or more of the features, numbers, steps, operations, elements, components, or combinations thereof.

[0049] It will be understood that, although the terms first, second, third, etc., may be used herein to describe various elements, but elements are not limited by these terms. These terms are only used to distinguish one element from another element. For example, without departing from the scope of the disclosure, a first element may be termed as a second element, and a second element may be termed as a first element. The term of “and/or” includes a plurality of combinations of relevant items or any one item among a plurality of relevant items.

[0050] In the following detailed description, the terms of “up and down direction”, “lower side”, “front and rear direction”, and the like may be defined by the drawings, but the shape and the location of the component is not limited by the term.

[0051] The disclosure will be described more fully hereinafter with reference to the accompanying drawings.

[0052] FIG. **1** is a view illustrating a display apparatus according to one embodiment. FIG. **2** is a control block diagram of the display apparatus **1** according to one embodiment.

[0053] Referring to FIG. **1**, a display apparatus **1** according to one embodiment may be a self-luminous display apparatus in which a light-emitting element is arranged for each pixel to allow each pixel to emit light by itself. However, the present disclosure is not limited thereto, and the display apparatus **1** may be a non-self-luminous display apparatus that emits light using external light, such as a liquid crystal display (LCD). For convenience of description, the present disclosure will be described based on a self-luminous display apparatus that employs a light emitting diode (LED).

[0054] A display apparatus provided with micro-LEDs may be applied to various fields by utilizing their ultra-small pixel size and thin thickness. For example, as shown in FIG. **3**, a large-screen may be implemented through display panels **10** and **20** onto which a plurality of LEDs is transferred, and the screen may be used as a signage, an electronic board, etc.

[0055] The display apparatus **1** may implemented with a thin thickness to allow light to pass therethrough, and have a simple structure to allow various design changes. In addition, the display apparatus **1** may be implemented as a flexible display apparatus.

[0056] The display apparatus **1** according to one embodiment may not need a backlight unit, a liquid crystal layer, or an encapsulating layer, but need an ultra-small micro-LED and a driving circuit and wiring for driving the micro-LED. Accordingly, it is more advantageous in securing an aperture ratio, which is an important factor in implementing a transparent display apparatus.

[0057] In embodiments described below, it is assumed that the display apparatus **1** is implemented

as a transparent display apparatus.

[0058] Meanwhile, the three-dimensional coordinate system of the XYZ axes illustrated in FIG. 1 is based on the display apparatus 1, and a plane on which a screen of the display apparatus 1 is located is the YZ plane, and a direction in which an image is output or a light-emitting direction of a light-emitting element is the +X direction.

[0059] Generally, the display apparatus 1 is used in an upright state, and a user views an image from the front of the display apparatus 1. Accordingly, the +X direction in which the image is output may be the front, and the opposite direction may be the rear.

[0060] Because the illustrated coordinate system is based on the display apparatus 1, the same coordinate system may be applied whether the display apparatus 1 is lying down or standing up.

[0061] The display apparatus 1 may be composed of a plurality of pixels arranged two-dimensionally. A single pixel may be composed of at least three sub-pixels that output light of different colors. For example, a single pixel may include a red sub-pixel configured to output red light, a green sub-pixel configured to output green light, and a blue sub-pixel configured to output blue light.

[0062] The sub-pixels may be arranged along the X-axis, along the Z-axis, or not arranged in a row. In addition, the sub-pixels may be implemented with different sizes. A single pixel only needs to include a plurality of sub-pixels to implement multiple colors, and there are no limitations on the size or arrangement of each sub-pixel.

[0063] In addition, a pixel does not necessarily have to be composed of a red sub-pixel configured to output red light, a green sub-pixel configured to output green light, and a blue sub-pixel configured to output blue light, and it is also possible to include a sub-pixel configured to output yellow light or white light. In other words, there is no limitation on the color or type of light output from each sub-pixel, or the number of sub-pixels. However, in the embodiments described below, for the specific description, a case in which a pixel is composed of a red sub-pixel, a green sub-pixel, and a blue sub-pixel will be described as an example.

[0064] The display apparatus 1 may include a first display panel 10 and a second display panel 20 that may be positioned to overlap at least a portion of the first display panel 10. For convenience of description, the following description will be based on the assumption that the first display panel 10 is positioned in front of the second display panel 20.

[0065] The first display panel 10 and the second display panel 20 may include a transmission area TA through which light may pass. The first display panel 10 and the second display panel 20 may include a light-emitting area that emits light. That is, the first display panel 10 and the second display panel 20 may be transparent display panels that display images while allowing objects located behind the display panels to be seen.

[0066] The first display panel 10 and the second display panel 20 may be provided with the same size. That is, the first display panel 10 and the second display panel 20 may completely overlap each other when positioned along the front and rear direction.

[0067] An image displayed by the second display panel 20 may pass through the first display panel 10. When a user is positioned in front of the display apparatus 1, the user can recognize the image displayed by the second display panel 20 together with an image displayed by the first display panel 10. In this way, the user can recognize the image in three dimensions by simultaneously recognizing the images displayed by the first display panel 10 and the second display panel 20. In other words, the display apparatus 1 may provide a three-dimensional effect to the image by overlapping the first display panel 10 and the second display panel 20.

[0068] It is illustrated that the first display panel 10 and the second display panel 20 are formed long in the up and down direction, but are not limited thereto and may have various sizes and shapes. The display panels 10 and 20 illustrated in the drawing are merely examples. Accordingly, when there is an overlapping portion although the first display panel 10 and the second display panel 20 have different shapes, a three-dimensional image may be implemented.

[0069] The display apparatus **1** may include a first driving device **100** configured to move at least one of a first display panel **10** and a second display panel **20**. The first driving device **100** may move at least one of the first display panel **10** and the second display panel **20** to allow the first display panel **10** to overlap at least a portion of the second display panel **20**. That is, by the first driving device **100**, the first display panel **10** and the second display panel **20** may be moved to be completely overlapped or partially overlapped, or to have no overlapping area.

[0070] The first driving device **100** may move the first display panel **10** and the second display panel **20** in the left and right direction. The first driving device **100** may include a base **110** that extends in the left and right direction to allow the first display panel **10** and the second display panel **20** to move on the first driving device **100**. The base **110** may include a left support **111** and a right support **112** which extend upward from left and right ends of the base **110**, respectively. In the drawing, it is illustrated that a first motor **120**, a motor gear **130**, a first gear **131**, a second gear **132**, etc., which will be described later are coupled to the left support **111**, but the present disclosure is not limited thereto and may be coupled to the right support **112**.

[0071] The first driving device **100** may include the first motor **120** configured to generate rotational force to move the first display panel **10** or the second display panel **20**, and the first motor **120** may include the motor gear **130** rotated by the first motor **120**. The motor gear **130** may be rotated together with the first motor **120** as the first motor **120** generates rotational force.

[0072] The first driving device **100** may include the first gear **131** configured to be rotated by the rotation of the motor gear **130**, and a first screw **141** connected to the first gear **131** and provided to extend from the left support **111** to the right support **112**. The first gear **131** may be configured to mesh with the motor gear **130**. However, the present disclosure is not limited thereto, and power may be transmitted via one or more other gears.

[0073] When the first gear **131** is configured to mesh with the motor gear **130**, the first gear may rotate in a direction opposite to the rotational direction of the motor gear **130**. When the first gear **131** rotates, the first screw **141** may also rotate. The first screw **141** may include a male thread formed along an outer circumferential surface thereof.

[0074] The first driving device **100** may include a first transfer unit **151** including a female thread formed to be coupled to the first screw **141**. The first transfer unit **151** may include a mounting portion provided to allow the first display panel **10** to be mounted thereon, but any structure may be used as long as the first display panel **10** may be coupled thereto. The first transfer unit **151** may be formed to allow the first screw **141** to penetrate therethrough. The first transfer unit **151** may be moved while maintaining the coupling between the male thread formed along the outer circumferential surface of the first screw **141** and the female thread formed on the first transfer unit **151** as the first screw **141** rotates. An inside of the first transfer unit **151** may include a ball bearing to facilitate movement with the first screw **141**.

[0075] The first driving device **100** may include the second gear **132** configured to be rotated by the rotation of the motor gear **130**, and a second screw **142** connected to the second gear **132** and provided to extend from the left support **111** to the right support **112**. The second gear **132** may be configured to mesh with the motor gear **130**. However, the present disclosure is not limited thereto, and power may be transmitted via one or more other gears. When the first gear **131** is configured to mesh with the motor gear **130**, the first gear **131** may rotate in a direction opposite to the rotational direction of the motor gear **130**. That is, when the motor gear **130** rotates, the first gear **131** and the second gear **132** may rotate in the opposite direction to the motor gear **130**, but may also rotate in the same direction. When the second gear **132** rotates, the second screw **142** may also rotate, and the first screw **141** and the second screw **142** may rotate in the same direction.

[0076] The first driving device **100** may include a second transfer unit **152** configured to be movable along the second screw **142**. The second transfer unit **152** may be formed to allow the second screw **142** to penetrate therethrough. The second transfer unit **152** may be moved while maintaining the coupling between a male thread formed along an outer circumferential surface of

the second screw **142** and a female thread formed in the second transfer unit **152** as the second screw **142** rotates. The second transfer unit **152** may include a ball bearing inside the second transfer unit **152** to facilitate movement with the second screw **142**, similar to the first transfer unit **151**. The ball bearing may be provided at a location in which the first screw **141** or the second screw **142** is coupled to the left support **111** and the right support **112**. This is to reduce friction and to facilitate rotation when the first screw **141** and the second screw **142** rotate.

[0077] In addition, the first screw **141** and the second screw **142** may be provided at different heights. In order to form a single continuous screen or display by being arranged side by side with the first display panel **10** positioned on the first screw **141**, the second display panel **20** positioned on the second screw **142** needs to be moved forward by a second driving device **200**.

[0078] At this time, the first screw **141** and the second screw **142** may be disposed at different heights to prevent the second driving device **200** from colliding with the first screw **141** or a first guide bar **161**. In the drawing, it is illustrated that the second screw **142** is disposed above the first screw **141**, but is not limited thereto. Alternatively, the first screw **141** may be disposed above the second screw **142**.

[0079] However, when a moving block **210** of the second driving device **200** is disposed so as not to collide with the first screw **141** or the first guide bar **161** even when the first screw **141** and the second screw **142** are positioned at the same height, the first screw **141** and the second screw **142** may be allowed to be positioned at the same height. In this way, positions at which the first screw **141** and the second screw **142** are provided may have any structure as long as the positions do not interfere with the movement of the first display panel **10** and the second display panel **20**.

[0080] As described above, the first screw **141** and the second screw **142** may include a male thread, and the first transfer unit **151** and the second transfer unit **152** may include a female thread. Conversely, the first screw **141** and the second screw **142** may include a female thread, and the first transfer unit **151** and the second transfer unit **152** may include a male thread.

[0081] Meanwhile, when the first screw **141** and the second screw **142** rotate in the same direction due to the rotation of the motor gear **130** and the rotation of the first gear **131** and the second gear **132** engaged with the motor gear **130**, the first transfer unit **151** and the second transfer unit **152** may also move in the same direction. In this case, the first display panel **10** and the second display panel **20** may not be overlapped or arranged side by side, and thus the first transfer unit **151** and the second transfer unit **152** need to move in opposite directions.

[0082] Accordingly, the first screw **141** and the second screw **142** may include threads in opposite directions. For example, when the male thread of the first screw **141** is formed in a right-hand thread shape, the male thread of the second screw **142** may be formed in a left-hand thread shape. Conversely, when the male thread of the first screw **141** is formed in a left-hand thread shape, the male thread of the second screw **142** may be formed in a right-hand thread shape.

[0083] Meanwhile, when the display apparatus **1** is in the upright state, that is, when the base **110** is positioned in the up and down direction, the first display panel **10** and the second display panel **20** may move in the up and down direction. In this case, the method by which the first driving device **100** moves the first display panel **10** is the same as the method by which the first driving device **100** moves the second display panel **20**.

[0084] The first driving device **100** may include the first guide bar **161** positioned parallel to the first screw **141** and a second guide bar **162** positioned parallel to the second screw **142**. The first guide bar **161** and the second guide bar **162** may be coupled to the first transfer unit **151** and the second transfer unit **152**, respectively. The first guide bar **161** and the second guide bar **162** may be positioned parallel to the first screw **141** and the second screw **142** so as not to interfere with the movement of the first transfer unit **151** and the second transfer unit **152**.

[0085] At least one first guide bar **161** and at least one second guide bar **162** may be provided to prevent the rotation of the first transfer unit **151** and the second transfer unit **152**. That is, when the first transfer unit **151** is supported only by the first screw **141**, the first transfer unit **151** may rotate

about the first screw **141** as a rotation axis, which may be structurally unstable. Therefore, in addition to the first screw **141**, it is required to install at least one first guide bar **161** to prevent the rotation of the first transfer unit **151**. Similarly, at least one second guide bar **162** may also be provided.

[0086] The display apparatus **1** may include the second driving device **200** configured to move at least one of the first display panel **10** or the second display panel **20** in the front and rear direction so as to adjust a distance between the first display panel **10** and the second display panel **20**.

[0087] The second driving device **200** may include a second motor **220** configured to generate rotational force to move the first display panel **10** or the second display panel **20**, and the moving block **210** to which the second transfer unit **152** and the first display panel **10** or the second display panel **20** are mounted and movably coupled. The second transfer unit **152** may include a moving guide **152a** extending in the front and rear direction to allow the moving block **210** to be movably coupled in the front and rear direction. The moving guide **152a** may extend to have a substantially rectangular cross-section, but is not limited thereto.

[0088] The second motor **220** may move the moving block **210** in the front and rear direction by the rotation of the second motor **220**. As a motor screw **230** rotates, the moving block **210** may be moved while maintaining the coupling between a male thread formed along an outer circumferential surface of the motor screw **230** and a female thread formed on the moving block **210**.

[0089] The second motor **220** may include the motor screw **230** connected to the second motor **220** so as to rotate by the rotational force of the second motor **220**. The motor screw **230** may include the male thread on the outer circumferential surface thereof. The motor screw **230** may penetrate an inside of the moving block **210**. The moving block **210** may include the female thread formed therein corresponding to the male thread of the motor screw **230**. It should be understood that the motor screw **230** includes a female thread, and the moving block **210** includes a female thread.

[0090] In the drawing, it is illustrated that the first gear **131** and the second gear **132** are engaged with the motor gear **130** and rotated together by the rotation of the motor gear **130**. However, the first gear **131** may include a separate motor, and the second gear **132** may also include a separate motor. Accordingly, the first gear **131** and the second gear **132** may rotate independently of each other. That is, when the first display panel **10** does not need to be moved, only the motor configured to drive the second gear **132** may be operated to move only the second display panel **20**.

[0091] Referring to FIG. 2, the display apparatus **1** according to one embodiment may include an inputter **400** configured to receive an input from a user, a sensor configured to detect a position of a user, a controller **500** configured to control the first driving device **100** or the second driving device **200**, and the first driving device **100** and the second driving device **200** configured to move the first display panel **10** and the second display panel **20**.

[0092] The display apparatus **1** may include the inputter **400** configured to receive a user input. The inputter **400** may receive various commands from a user to control the display apparatus **1**, such as turning on/off the display apparatus **1**, adjusting a volume, adjusting a channel, adjusting a screen, and changing various settings.

[0093] The inputter **400** may include a button or a touch pad disposed in an area of the display apparatus **1**, and when the display panels **10** and **20** are implemented as a touch screen, the inputter **400** may include a touch pad disposed on the front surface of the display panels **10** and **20**. In addition, the inputter **400** may also include a physical button, a switch, a knob, a remote controller, etc.

[0094] The display apparatus **1** may include a position sensor **300** configured to recognize a position of a nearby person. The display apparatus **1** may recognize a position of a person and detect a distance between the person and the display panels **10** and **20**. The position sensor **300** may transmit information to the controller **500** to drive the second driving device **200** to adjust the distance between the first display panel **10** and the second display panel **20** according to the

distance between the person and the display panels **10** and **20**. For this, the position sensor **300** may be located in front of the display apparatus **1**.

[0095] The display apparatus **1** may include the controller **500** configured to control the first driving device **100** or the second driving device **200** based on a user input received through the inputter **400**. The controller **500** may control the first driving device **100** or the second driving device **200** to move the positions of the first display panel **10** and the second display panel **20**.

[0096] Particularly, the controller **500** may control the start of operation of the first motor **120**. When the left and right positions of the first display panel **10** and the second display panel **20** are appropriate, the controller **500** may stop the operation of the first motor **120**. At this time, the controller **500** may control the start of operation of the second motor **220**. By starting the operation of the second motor **220**, the controller **500** may allow the second display panel **20** to be positioned on the same line as the first display panel **10**, or may adjust the distance between the first display panel **10** and the second display panel **20**.

[0097] However, the present disclosure is not limited thereto, and the controller **500** may simultaneously start the operations of the first motor **120** and the second motor **220** when the first display panel **10** and the second display panel **20** are disposed at positions which are determined that the collision does not occur.

[0098] The display apparatus **1** may be operated in a first mode that expands an image display region of the first display panel **10** and the second display panel **20**, and a second mode that increases the resolution of an image displayed by the first display panel **10** and the second display panel **20**. The controller **500** may control the first driving device **100** or the second driving device **200** to allow the display apparatus **1** to be operated in the first mode and the second mode. A specific description of the first mode that expands the image display region and the second mode that increases the resolution will be described later.

[0099] Meanwhile, in FIG. **1**, the first display panel **10** and the second display panel **20** may be moved in the left and right direction by the first driving device **100**, but only the second display panel **20** may be moved in the front and rear direction by the second driving device **200**. However, in FIG. **13** described later, both the first display panel **10** and the second display panel **20** may be moved in the front and rear direction by the second driving device **200**.

[0100] Hereinafter the expanded or overlapping state of the first display panel **10** and the second display panel **20** will be described.

[0101] FIG. **3** is a view illustrating a state in which display panels of the display apparatus of FIG. **1** are expanded and arranged. FIG. **4** is a view illustrating a light-emitting area and a transmission area forming the display panel of FIG. **3**. FIG. **5** is an enlarged view of a portion A, which is a portion of the light-emitting area and the transmission area of the display panel of FIG. **3**.

[0102] Referring to FIGS. **3** to **5**, in the display apparatus **1**, the first display panel **10** and the second display panel **20** may be arranged side by side to expand the image display region.

[0103] A user can input a command, in which the display apparatus **1** is operated in the first mode to expand the image display region, to the inputter **400**. The command received through the inputter **400** may be transmitted to the controller **500**.

[0104] The controller **500** may operate the first driving device **100** and the second driving device **200** to allow the first display panel **10** and the second display panel **20** to be arranged side by side. The controller **500** may control the first motor **120** to start an operation so as to move the first display panel **10** and the second display panel **20** in the left and right direction. When the first display panel **10** and the second display panel **20** move to appropriate positions, the controller **500** may control the first motor **120** to stop the operation. Thereafter, the controller **500** may control the second motor **220** to start an operation so as to move the second display panel **20** to be arranged side by side with the first display panel **10**. When the second display panel **20** is arranged side by side with the first display panel **10**, that is, positioned in a straight line along the left and right direction, the controller **500** may control the second motor **220** to stop the operation.

[0105] However, when the first display panel **10** and the second display panel **20** are already in appropriate positions based on the left and right direction, that is, when the first display panel **10** and the second display panel **20** are arranged so as to be in contact with each other on the same line by moving in the front and rear direction, the controller **500** may control only the operation of the second motor **220**. In this case, the controller **500** may start the operation of the second motor **220** and then stop the operation of the second motor **220** in response to the first display panel **10** and the second display panel **20** being arranged side by side to be located on the same line.

[0106] Accordingly, the first display panel **10** and the second display panel **20** may form a single continuous screen. The first display panel **10** and the second display panel **20** may be arranged side by side in the same line so as to form a single continuous screen. In other words, the first display panel **10** and the second display panel **20** may be arranged on the same line, that is, on the first screw **141** or the second screw **142**, so as to be in contact with each other. The first display panel **10** and the second display panel **20** may form one continuous screen to display one image.

[0107] As the first display panel **10** and the second display panel **20** form a single extended display panel **10** and **20**, a larger image display screen may be provided.

[0108] Hereinafter the structure inside the display panels **10** and **20** will be described in detail with reference to FIGS. **4** and **5**.

[0109] Referring to FIG. **4**, the first display panel **10** and the second display panel **20** may each include a light-emitting area **50** and a transmission area TA. The first display panel **10** and the second display panel **20** may each include a first wiring portion **41** and a second wiring portion **42** for supplying a control signal, power, etc. In order to secure the transmittance, it is required that the transmission area TA, through which light passes, be secured, and thus the first wiring portion **41** and the second wiring portion **42** may be arranged to intersect each other. For example, the first wiring portion **41** and the second wiring portion **42** may be arranged to intersect each other vertically.

[0110] The first wiring portion **41** and the second wiring portion **42** may be formed of a material that allows light to pass through. However, because the transmission area TA includes a configuration formed of a material with a high transmittance, such as a transparent substrate, a transmittance of the first wiring portion **41** and the second wiring portion **42** may not be greater than that of the transmission area TA. Therefore, in order to secure the transmittance, a region of the transmission area TA may be large.

[0111] For example, because the first display panel **10** and the second display panel **20** have a rectangular shape, the first wiring portion **41** and the second wiring portion **42** may be arranged in a two-dimensional grid shape. Each area formed by the intersection of the first wiring portion **41** and the second wiring portion **42** is a transparent area, and thus may become a transmission area TA through which light passes. An image displayed on the second display panel **20** may pass through the transmission area TA. All areas except the first wiring portion **41** and the second wiring portion **42** may become transmission areas TA, and thus a ratio of the transmission area TA may be maximized by adjusting a thickness and arrangement of the first wiring portion **41** and the second wiring portion **42**.

[0112] As for the display panels **10** and **20** according to one embodiment, the first wiring portion **41** may be arranged in the up and down direction and the second wiring portion **42** may be connected in the left and right direction. The first wiring portion **41** and the second wiring portion **42** may be arranged in a grid shape and thus the first wiring portion **41** and the second wiring portion **42** may be provided in plurality. FIG. **3** illustrates that the first display panel **10** and the second display panel **20** includes five first wiring portions **41** and seven second wiring portions **42**, respectively.

[0113] The first display panel **10** and the second display panel **20** may be provided in shapes other than rectangles. For example, the first display panel **10** and the second display panel **20** may be provided in various shapes such as circles, ovals, and polygons. In this case, a wiring structure of

the first display panel **10** and the second display panel **20** may not necessarily be a two-dimensional grid shape, and may be provided in various shapes such as a mesh structure and a radial structure. [0114] The light-emitting area **50** may be arranged on the first wiring portion **41**. The light-emitting area **50** may be arranged while maintaining a predetermined interval. In the drawing, it is illustrated that the light-emitting area **50** is arranged lengthwise along a longitudinal direction of the first wiring portion **41**, but is not limited thereto. Alternatively, each of light-emitting elements **50R**, **50G** and **50B** may be arranged in various shapes such as a triangle.

[0115] Referring to FIG. 5, the light-emitting elements **50R**, **50G** and **50B** may be provided in the light emitting area **50**. One light emitting element may include a red light-emitting element **50R**, a green-light emitting element **50G**, and a blue-light emitting element **50B**. The red light-emitting element **50R**, the green light-emitting element **50G**, and the blue light-emitting element **50B** may be mounted on the light-emitting area **50**. The red light-emitting element **50R**, the green light-emitting element **50G**, and the blue light-emitting element **50B** may form a single pixel.

[0116] The light-emitting area **50** may be provided to allow the red light-emitting element **50R**, the green light-emitting element **50G**, and the blue light-emitting element **50B** to be mounted thereon, respectively. That is, a light-emitting area **50** in which the red light-emitting element **50R** is mounted, a light-emitting area **50** in which the green light-emitting element **50G** is mounted, and a light-emitting area **50** in which the blue light-emitting element **50B** is mounted may be individually provided.

[0117] FIG. 6 is a view illustrating a state in which the display panels of the display apparatus of FIG. 1 are overlapped and arranged. FIG. 7 is a view illustrating the light-emitting area and the transmission area forming the display panel of FIG. 6.

[0118] Referring to FIGS. 6 and 7, in the display apparatus **1**, the first display panel **10** and the second display panel **20** may overlap each other to provide a three-dimensional effect to an image displayed thereon. The image displayed on the second display panel **20** located further rearward may pass through the transmission area TA of the first display panel **10** and be recognized by a user. The user can recognize the perspective of the image displayed by the first display panel **10** and the image displayed by the second display panel **20** and thus the user can feel the three-dimensional effect of the image.

[0119] In addition, the light-emitting area **50** located in the first display panel **10** and the light-emitting area **50** located in the second display panel **20** may be positioned alternately. Particularly, the light-emitting area **50** of the first display panel **10** may be positioned to correspond to the transmission area TA of the second display panel **20**. Conversely, the light-emitting area **50** of the second display panel **20** may be positioned to correspond to the transmission area TA of the first display panel **10**. Because internal structures of the first display panel **10** and the second display panel **20** have the same shape, the light-emitting areas **50** may be uniformly distributed over the entire areas of the first display panel **10** and the second display panel **20**.

[0120] The resolution of the display is calculated by the number of pixels displayed on the screen, and thus the higher the number of pixels displayed in the same region, that is, the greater the number of light-emitting areas **50**, the higher the resolution. When the first display panel **10** and the second display panel **20** completely overlap, a user can recognize only the first display panel **10**, which is located further in front, as a screen display area. However, the light-emitting area **50** of the second display panel **20** may be seen through the screen display area of the first display panel **10**, and thus a larger number of pixels may be displayed.

[0121] In other words, the number of light-emitting areas **50** displayed on a screen having the same size as the first display panel **10** may be the total of the number of light-emitting areas **50** of the first display panel **10** and the number of light-emitting areas **50** of the second display panel **20**. Accordingly, the resolution of the screen displayed by the display panels **10** and **20** may be approximately doubled.

[0122] In order to increase the resolution, the positions of the first display panel **10** and the second

display panel **20** may be intentionally arranged to cross each other. This is because when the first display panel **10** and the second display panel **20** completely overlap, the light-emitting area **50** of the second display panel **20** may not be positioned to correspond to the transmission area TA of the first display panel **10** because the first display panel **10** and the second display panel **20** are formed with the same structure.

[0123] Meanwhile, when the first display panel **10** and the second display panel **20** completely overlap, the internal structure thereof may be intentionally moved to allow the light-emitting area **50** of the second display panel **20** to be positioned to correspond to the transmission area TA of the first display panel **10**.

[0124] A user can input a command, in which the display apparatus **1** is operated in the second mode to increase the resolution of an image displayed thereon, to the inputter **400**. The command received through the inputter **400** may be transmitted to the controller **500**. The controller **500** may operate the first driving device **100** and the second driving device **200** to completely overlap the first display panel **10** and the second display panel **20** or intentionally position the first display panel **10** and the second display panel **20** to be cross.

[0125] The controller **500** may control the first motor **120** to be operated. By the operation of the first motor **120**, the first display panel **10** and the second display panel **20** may be moved in the left and right direction. When the light-emitting area **50** of the second display panel **20** is moved to be positioned in the transmission area TA of the first display panel **10**, the controller **500** may control the first motor **120** to stop the operation thereof.

[0126] A user can input a command, in which the display apparatus **1** is operated in a third mode to prevent a decrease in transmittance while increasing the resolution of an image displayed thereon, to the inputter **400**. The command received through the inputter **400** may be transmitted to the controller **500**.

[0127] The controller **500** may control the display apparatus **1** to be operated in the third mode to prevent a decrease in transmittance while increasing the resolution of the displayed image. That is, the controller **500** may control the display apparatus **1** to be operated in the third mode to increase the transmittance in the second mode that increases the resolution of the displayed image.

Particularly, the controller **500** may control the first motor **120** to be operated, and when the light-emitting area **50** of the second display panel **20** overlaps at least a portion of the first wiring portion **41** of the first display panel **10** due to the operation of the first motor **120**, the controller **500** may control the first motor **120** to stop the operation thereof.

[0128] The first display panel **10** and the second display panel **20** may be arranged in the front and rear direction to display images respectively, thereby providing a three-dimensional image. In addition, the resolution may be increased by allowing the light-emitting area **50** of the second display panel **20** to be positioned in the transmission area TA of the first display panel **10**.

[0129] The display apparatus **1** may adjust the distance between the first display panel **10** and the second display panel **20** in a state in which the first display panel **10** and the second display panel **20** are overlapped. When the distance between the first display panel **10** and the second display panel **20** is reduced, the three-dimensional effect may decrease. When the distance thereof is increased, the three-dimensional effect may increase, but a cardboard effect may occur, thereby causing an unnatural feeling. Therefore, the distance between the first display panel **10** and the second display panel **20** needs to be appropriately maintained.

[0130] The position sensor **300** may detect a user's position. The position sensor **300** may detect the distance from the display apparatus **1** to the user's position and transmit the information to the controller **500**.

[0131] The controller **500** may control the operation of the second driving device **200** to adjust the distance between the first display panel **10** and the second display panel **20**. Particularly, when the controller **500** determines that the distance from the display apparatus **1** to the user's position is close, the controller **500** may control the second motor **220** to be rotated so as to move the second

display panel **20** forward. When the distance is adjusted to an appropriate level, the controller **500** may control the second motor **220** to stop the operation thereof.

[0132] Meanwhile, when the controller **500** determines that the distance from the display apparatus **1** to the user's position is far, the controller **500** may control the second motor **220** to be rotated in the opposite direction so as to move the second display panel **20** backward. Similarly, when the distance is adjusted to an appropriate level, the controller **500** may control the second motor **220** to stop the operation thereof.

[0133] FIG. **8** is a view illustrating a structure of a light-emitting area and a transmission area forming a display panel of a display apparatus according to one embodiment. FIG. **9** is a view illustrating a state in which the display panels of the display apparatus of FIG. **8** are overlapped and arranged. FIG. **10** is a view illustrating a state in which the display panels of the display apparatus of FIG. **8** are arranged in a manner different from that of FIG. **9**.

[0134] Referring to FIGS. **8** to **10**, internal structures of a first display panel **10** and a second display panel **20** may be provided differently from each other. For example, as illustrated in FIG. **8**, a light-emitting area **50** of a second display panel **20a** may be provided at a different height from a light-emitting area **50** of the first display panel **10**. In other words, the light-emitting area **50** of the second display panel **20a** may be located in a first wiring portion **41**, but may be located close to a second wiring portion **42** passing under the transmission area TA. In other words, a wiring structure of the second display panel **20a** may be the same as that of rotating a wiring structure of the first display panel **10** by 180 degrees clockwise. It is sufficient for the wiring structures of the first display panel **10** and the second display panel **20a** to be formed opposite each other, and it is sufficient for the structure of the first display panel **10** to be changed.

[0135] As the wiring structures of the first display panel **10** and the second display panel **20a** are provided differently from each other, it is possible to obtain the effect of increasing the transmittance when the first display panel **10** and the second display panel **20** are overlapped.

[0136] Particularly, referring to FIG. **7**, as the light-emitting area **50** of the second display panel **20** is positioned to correspond to the transmission area TA of the first display panel **10**, the transmission area TA of the first display panel **10** may be narrower than before overlapping. Accordingly, the wiring structure of the second display panel **20a** may be provided as illustrated in FIG. **8**.

[0137] The first display panel **10** and the second display panel **20a** including the wiring structure of FIG. **8** may provide an image with uniform and increased resolution by positioning the light-emitting area **50** of the second display panel **20a** to correspond to the transmission area TA of the first display panel **10**.

[0138] Further, referring to FIG. **10**, the light-emitting area **50** of the second display panel **20** may be positioned to overlap at least a portion of the first wiring portion **41** of the first display panel **10**. In this case, a region of the transmission area TA of the first display panel **10** covered by the light-emitting area **50** of the second display panel **20a** and the first wiring portion **41** may be reduced. The first wiring portion **41** and the second wiring portion **42** may also be formed of a material that allows light to be transmitted. However, even when light is transmitted, a transmittance of the first wiring portion **41** and the second wiring portion **42** may not be greater than that of the transmission area TA, and thus it may be more advantageous to secure the region of the transmission area TA.

[0139] Accordingly, by overlapping the first display panel **10** and the second display panel **20a**, the resolution of the display may be increased while preventing a decrease in the transmittance. Accordingly, the function as a transparent display may be maintained while providing the more increased resolution.

[0140] FIG. **11** is a view illustrating a state in which a portion of the display panels of the display apparatus of FIG. **1** are overlapped and arranged.

[0141] Referring to FIG. **11**, the second display panel **20** may be positioned to overlap at least a portion of the first display panel **10**. A portion of an area where the second display panel **20**

overlaps the first display panel **10** may display a three-dimensional image. An area of the second display panel **20** that do not overlap the first display panel **10** and an area of the first display panel **10** that do not overlap the second display panel **20** may display general images.

[0142] For example, when an image to be displayed is a person or object requiring a three-dimensional effect and a text requiring readability, the display apparatus **1** may overlap only a portion of the first display panel **10** and a portion of the second display panel **20** to display the image of the person or object in the overlapping area and display the text in the non-overlapping area. As another example, when an image to be displayed is a moving image expressing a moving object, etc., the display apparatus **1** may move the area displaying the three-dimensional image while moving the overlapping area between the first display panel **10** and the second display panel **20**. As described above, the method of moving the overlapping area between the first display panel **10** and the second display panel **20** may utilize the method of operating the first driving device **100** or the second driving device **200**. However, even in the case of the text in the above example, when a three-dimensional effect is required, the text may be displayed in the overlapping area.

[0143] Hereinafter detailed descriptions of the same configurations as those described in FIGS. **1** to **11** may be omitted. In addition, the same reference numerals may be assigned to the same configurations, and descriptions will be given to configurations that are different from those of the above embodiments.

[0144] FIG. **12** is a view illustrating a state in which sizes of display panels of a display apparatus are different from each other. FIG. **13** is a view illustrating a state in which sizes of display panels of a display apparatus are different from each other.

[0145] Referring to FIGS. **12** and **13**, first display panels **11** and **12** and second display panels **21** and **22** of display apparatuses **2** and **3** may be provided with different sizes. In addition, the first display panels **11** and **12** and the second display panels **21** and **22** may be provided with different shapes. For example, the second display panels **21** and **22** may be provided with a large rectangular shape, and the first display panels **11** and **12** may be provided with different shapes such as a circle, an ellipse, a polygon, etc. Accordingly, as the first display panels **11** and **12** move, an area, on which a three-dimensional image is displayed, i.e., an overlapping area, may move while having various shapes.

[0146] As illustrated in FIG. **12**, a first display panel **11** of a display apparatus **2** may be formed to have a smaller size than a second display panel **21**. It is illustrated that the first display panel **11** has a narrower width in the left and right direction than the second display panel **21** but has the same height as the second display panel **21**. Alternatively, the first display panel **11** may have the same width in the left and right direction as the second display panel **21**, but may have a shorter height than the second display panel **21**.

[0147] The second display panel **21** may display a large screen, and thus the second display panel **21** may display a background screen. The first display panel **11** may display a small screen, and thus the first display panel **11** may display an image that is intended to be displayed using the second display panel **21** as a background.

[0148] As illustrated in FIG. **13**, a first display panel **12** of a display apparatus **3** may be formed to have a larger size than a second display panel **22**. It is illustrated that the first display panel **12** has a narrower width in the left and right direction than the second display panel **22** but has the same height as the second display panel **22**. Alternatively, the first display panel **12** may have the same width in the left and right direction as the second display panel **22**, but may have a shorter height than the second display panel **22**.

[0149] In this case, the first display panel **12** may be used as a background, and an image to be displayed beyond the background of the first display panel **12** may be displayed on the second display panel **22**.

[0150] The above description is only an example, and the first display panels **11** and **12** or the second display panels **21** and **22** may move relative to each other to provide various three-

dimensional images.

[0151] FIG. **14** is a view illustrating a state in which a display apparatus according to one embodiment includes three display panels. FIG. **15** is a view illustrating a state in which the display panels of the display apparatus of FIG. **14** are overlapped.

[0152] Referring to FIGS. **14** and **15**, a display apparatus **4** may include a third display panel **30** positioned to overlap at least a portion of a first display panel **10** or a second display panel **20**. It is illustrated that the third display panel **30** has the same size and shape as the first display panel **10** and the second display panel **20**, but is not limited thereto. Alternatively, the third display panel **30** may have a different size or shape. In addition, the third display panel **30** may include a first wiring portion **41** and a second wiring portion **42** in the same manner as the first display panel **10** and the second display panel **20**, and may include a light-emitting area **50** and a transmission area TA.

[0153] The display apparatus **4** may include a first driving device **101** or a second driving device to move the third display panel **30**. The first driving device **101** may include a third screw, a third transfer unit, etc. A driving method of the first driving device **101** or the second driving device may be the same as the driving method of the first driving device **100** or the second driving device **200** described above. In addition, the third display panel **30** may be fixedly positioned without moving, and the first display panel **10** or the second display panel **20** may be positioned to be moved and overlapped by the first driving device **101** and the second driving device, respectively.

[0154] The first display panel **10**, the second display panel **20**, and the third display panel **30** may be arranged side by side on the same line to form one extended display panel **10**, **20**, and **30**. That is, the first display panel **10**, the second display panel **20**, and the third display panel **30** may be arranged side by side to form a single continuous screen. In addition, the first display panel **10** and the second display panel **20** may be overlapped to display a three-dimensional image, and may be arranged to increase the resolution.

[0155] Among the first to third display panels **10**, **20**, and **30**, two display panels may form a single continuous screen and the remaining one display panel may be arranged at the front or the rear of the continuous screen. Accordingly, the first to third display panels **10**, **20**, and **30** may be configured to be the same as the display apparatus **2** or **3** including the first display panel **10** and the second display panel **20** having the different sizes. For example, the first display panel **10** and the second display panel **20** may be arranged side by side at the front to form one continuous screen, and the third display panel **30** may be arranged at the rear. Conversely, the second display panel **20** and the third display panel **30** may be arranged side by side at the rear to form one continuous screen, and the first display panel **10** may be arranged at the front. Accordingly, it is possible to have the effect of having the different sizes with the display panels **10**, **20** and **30** having the same size and shape.

[0156] The effect and structure according to the arrangement of the first display panel **10** and the second display panel **20** described above may be equally applied even when the third display panel **30** is provided together, and the moving method may be equally applied.

[0157] For example, the wiring structure of the third display panel **30** may be a form in which the wiring structure of the second display panel **20** shown in FIG. **8** is inverted left and right. In this case, as illustrated in FIG. **16**, when the display panels **10**, **20**, and **30** overlap, the number of pixels displayed within the same region may increase and thus a higher resolution screen may be displayed. In this way, even when the display panels **10**, **20**, and **30** are composed of three or more display panels, the effect of increasing the resolution may be obtained while securing the transmittance.

[0158] It may be possible to move a display panel.

[0159] Further, it may be possible to provide a three-dimensional effect to an image by overlapping display panels.

[0160] Further, it may be possible to provide an image on a wide screen.

[0161] Further, it may be possible to increase the resolution by overlapping display panels.

[0162] While the present disclosure has been particularly described with reference to exemplary embodiments, it should be understood by those of skilled in the art that various changes in form and details may be made without departing from the spirit and scope of the present disclosure.

Claims

1. A display apparatus comprising: a first display panel; a second display panel, each of the first display panel and the second display panel comprising a light-emitting area and a transmission area through which light is transmitted; a first driving device comprising a first motor, the first driving device configured to move at least one of the first display panel or the second display panel to at least partially overlap each other; and a second driving device comprising a second motor, the second driving device configured to move at least one of the first display panel or the second display panel in a front and rear direction to adjust a distance between the first display panel and the second display panel.
2. The display apparatus of claim 1, wherein the light-emitting area of the second display panel is positioned to correspond to the transmission area of the first display panel.
3. The display apparatus of claim 1, wherein each of the first display panel and the second display panel comprises: a first wiring portion in which the light-emitting area is positioned; and a second wiring portion that intersects the first wiring portion and forms the transmission area with the first wiring portion, and wherein the light-emitting area of the second display panel is positioned to overlap with at least a portion of the first wiring portion of the first display panel.
4. The display apparatus of claim 3, wherein with respect to each of the first display panel and the second display panel, the first wiring portion and the second wiring portion intersect each other vertically.
5. The display apparatus of claim 1, wherein the first display panel and the second display panel are movable to be arranged side by side to form a continuous screen.
6. The display apparatus of claim 1, wherein at least one of the first display panel and the second display panel is movable so that the first display panel and the second display panel to completely overlap each other.
7. The display apparatus of claim 6, wherein, based on the overlap of the first display panel and the second display panel, the light-emitting area of the second display panel is positioned to correspond to the transmission area of the first display panel.
8. The display apparatus of claim 6, wherein each of the first display panel and the second display panel comprises: a first wiring portion in which the light-emitting area is positioned; and a second wiring portion that intersects the first wiring portion and forms the transmission area with the first wiring portion, and wherein, based on the second display panel overlapping the first display panel, the light-emitting area of the second display panel is positioned to overlap at least a portion of the first wiring portion of the first display panel.
9. The display apparatus of claim 1, wherein a size of the first display panel is different from a size of the second display panel.
10. The display apparatus of claim 9, wherein the second display panel is smaller than the first display panel.
11. The display apparatus of claim 1, further comprising: a third display panel that is movable to overlap at least a portion of the first display panel or the second display panel, wherein the third display panel is movable to be arranged side by side with the first display panel and the second display panel to form a continuous screen.
12. The display apparatus of claim 1, wherein the first driving device further comprises: a motor gear configured to be rotated by the first motor; a first gear configured to be rotated by a rotation of the motor gear; a first screw configured to be rotated together with the first gear; and a first transfer unit configured to be movable along the first screw.

13. The display apparatus of claim 12, wherein the first driving device further comprises: a second gear configured to be rotated by a rotation of the motor gear; a second screw configured to be rotated together with the second gear and positioned parallel to the first screw; and a second transfer unit configured to be movable along the second screw, and wherein a thread of the second screw is in a different direction from a thread of the first screw.

14. The display apparatus of claim 13, wherein the second driving device further comprises: a moving block on the second display panel and movably coupled to the second transfer unit, and wherein the moving block is movable in the front and rear direction based on a rotation of the second motor.

15. The display apparatus of claim 1, further comprising: a controller configured to control the first driving device or the second driving device based on a user input, wherein the controller is further configured to, based on a control of the first driving device or the second driving device, operate in a first mode to expand an image display region and a second mode to increase a resolution.
