

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287749

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

YANAI; Takahide et al.

LIGHT-EMITTING DEVICE AND METHOD FOR MANUFACTURING LIGHT-EMITTING DEVICE

Abstract

In a method for making a light-emitting device, a plurality of windows (20) on which light source (10) are mounted is prepared, an block (AG1) in which a plurality of packages (30) are connected in an array is prepared, the window (20) is mounted in each package (30) of the block (AG1) to electrically connect a first pad (25) and a second pad (36) corresponding to each other, and the block (AG1) is separated to obtain the plurality of packages (30) on which the corresponding window (20) are mounted.

Inventors: YANAI; Takahide (Hamamatsu-shi, JP), Okuyama; Yoshihiro (Hamamatsu-shi, JP)

Applicant: HAMAMATSU PHOTONICS K.K. (Hamamatsu-shi, JP)

Family ID: 73544685

Assignee: HAMAMATSU PHOTONICS K.K. (Hamamatsu-shi, JP)

Appl. No.: 19/197252

Filed: May 02, 2025

Foreign Application Priority Data

JP	2019-104874	Jun. 04, 2019
----	-------------	---------------

Related U.S. Application Data

parent US continuation 17615159 20211130 parent-grant-document US 12364078 WO
continuation PCT/JP2020/020979 20200527 child US 19197252

Publication Classification

Int. Cl.: H10H20/857 (20250101); H10H20/01 (20250101); H10H20/814 (20250101)

U.S. Cl.:

CPC H10H20/857 (20250101); H10H20/01 (20250101); H10H20/814 (20250101); H10H20/0364 (20250101)

Background/Summary

TECHNICAL FIELD

[0001] One aspect of the present invention relates to a light-emitting device. Another aspect of the present invention relates to a method for making a light-emitting device.

BACKGROUND ART

[0002] Carbon dioxide and methane are environmental gases having absorption in an infrared region. It is desired to analyze these environmental gases with high sensitivity. To meet this desire, a light-emitting device emitting infrared light with high output has been in a process of development. High-output infrared light having a wavelength region of, for example, 3 to 5 μm is obtained by focusing light from a light source including, for example, a light-emitting diode. However, it is not practical from an economic point of view to use a lens as an element focusing infrared light. High-output infrared light is effectively obtained through a reflector as the element focusing infrared light from the light source.

[0003] Some proposals have been made for a device focusing light from a light source through a reflecting mirror. Patent Literature 1 discloses a light-emitting device. The light-emitting device includes a light-emitting diode, a phosphor that wavelength-converts light from the light-emitting diode to generate white light, a reflecting plate that reflects the white light, a transparent plate that emits the white light from the reflecting plate to the outside, and a case housing the light-emitting diode, the phosphor, the reflecting plate, and the transparent plate. Patent Literature 2 discloses a light-emitting diode. The light-emitting diode includes a light-emitting diode element and a metal reflecting mirror that reflects light from the light-emitting diode element. Patent Literature 3 discloses a light-emitting diode lamp. The light-emitting diode lamp includes a light-emitting diode chip, a reflection surface of a concave curved surface that reflects light from the light-emitting diode chip, a light transmissive substrate that transmits light from the reflection surface to the outside, and a fixed cover that covers these ones.

CITATION LIST

Patent Literature

[0004] Patent Literature 1: Japanese Unexamined Patent Publication No. 2000-347601 [0005]

Patent Literature 2: Japanese Unexamined Patent Publication No. 2002-280614 [0006] Patent

Literature 3: Japanese Unexamined Patent Publication No. H10-335706

SUMMARY OF INVENTION

Technical Problem

[0007] A light-emitting element including a light-emitting diode emits light upon receiving electric power supplied from an electric power supply. For this reason, a light output of the light-emitting element may be reduced, and a life of the light-emitting element may be shortened by a heat generated in the light-emitting element due to light emission and a heat from an electric line portion that transmits the electric power. It is important to effectively dissipate the heat generated in the light-emitting element.

[0008] In the light-emitting device of Patent Literature 1, the transparent plate is disposed on the case to cover an entire one surface of the case. Therefore, the transparent plate tends not to

dissipate the heat generated in the light-emitting diode to the outside of the case effectively. In the light-emitting diode of Patent Literature 2, the amount of electrodes that perform a heat dissipation function is small. Therefore, the heat generated in the light-emitting diode element tends not to be dissipated toward the outside of the light-emitting diode. In the light-emitting diode lamp of Patent Literature 3, a wire (lead) that supplies power to the light-emitting diode chip is positioned in the fixed cover that covers the light-emitting diode chip. The wire is not exposed to the outside of the fixed cover, and thus the wire tends not to dissipate the heat generated in the light-emitting diode chip.

[0009] An object of one aspect of the present invention is to provide a light-emitting device that effectively dissipates heat generated in a light source. An object of another aspect of the present invention to provide a method for making a light-emitting device that effectively dissipates heat generated in a light source.

Solution to Problem

[0010] A light-emitting device according to one aspect includes: a light source; a window mounting the light source; and a package defining a space with the window, the light source being disposed in the space. The window includes: a window base including a light exit surface, a lower surface opposing the light exit surface, and a side surface coupling the light exit surface and the lower surface; and an electrically conductive body disposed on the lower surface of the window base. The package includes: a base portion formed with a recess open toward the lower surface, the base portion including a placement surface disposed along an edge of the recess and opposing the lower surface, a bottom surface opposing the placement surface, and an outer side surface coupled to the bottom surface; a wall portion including an inner wall surface coupled to the placement surface and opposing the side surface, an outer wall surface opposing the inner wall surface and coupled to the outer side surface, and an upper wall surface coupling the inner wall surface and the outer wall surface, the wall portion disposed along the window base when viewed from a direction orthogonal to the light exit surface; a reflection portion disposed on a surface of the recess, being configured to reflect light emitted from the light source to the window; and an electric conductor disposed on the placement surface, the inner wall surface, the upper wall surface, the outer wall surface, and the outer side surface. The window base is configured to transmit the light reflected on the reflection portion. The electrically conductive body includes a plurality of first pads opposing the placement surface, and a plurality of connectors electrically connecting the light source and the plurality of first pads. The electric conductor includes a plurality of second pads disposed on the placement surface to oppose corresponding first pads of the plurality of first pads and electrically connected to the corresponding first pads.

[0011] According to the one aspect, the light source mounted on the window emits light to the reflection portion disposed in the recess open toward the lower surface of the window base. The reflection portion reflects the light to the window. The window transmits the light reflected on the reflection portion toward the outside. The reflection portion is disposed on the surface of the recess, and thus the light to be reflected is focused due to the recessed shape of the reflection portion. As a result, the light transmitted through the window has an improved light density, and the improved light density provides the light-emitting device for analyzing the environmental gas with high sensitivity.

[0012] In the one aspect, the light source is electrically connected to the plurality of first pads through the plurality of connectors. The plurality of first pads are electrically connected to the electric conductor through the corresponding second pads. The light source is electrically connected to the electric conductor through the first pad and the second pad. The electric conductor is disposed on the placement surface, the inner wall surface, the upper wall surface, the outer wall surface, and the outer side surface. This disposal of the electric conductor provides a large area in contact with the outside of the light-emitting device. The heat generated in the light source due to the supply of power is effectively dissipated through the electric conductor having the large area in

contact with the outside.

[0013] In the one aspect, the electric conductor may be further disposed on the bottom surface.

[0014] The configuration in which the electric conductor is disposed on the bottom surface further increases the area where the electric conductor is in contact with the outside of the light-emitting device. As a result, this configuration further improves heat dissipation through the electric conductor.

[0015] In the one aspect, a height from the placement surface to the upper wall surface may be larger than a height from the placement surface to the light exit surface.

[0016] In the configuration in which the height from the placement surface to the upper wall surface is larger than the height from the placement surface to the light exit surface, the wall portion disposed along the window base prevents the window base from coming into contact with an external object of the light-emitting device. Damage to the window base is reduced, and thus the window base favorably transmits the light reflected on the reflection portion toward the outside. On the inner wall surface, the electric conductor is disposed in a region from the placement surface to the upper wall surface. Therefore, this disposal further improves the heat dissipation through the electric conductor.

[0017] In the one aspect, the package may have a polygonal shape when viewed from the direction orthogonal to the light exit surface. The number of the outer side surfaces and the outer wall surfaces may be plural, respectively. The electric conductor may not be disposed on the corner portion defined by the upper wall surface and the outer wall surfaces adjacent to each other, on a ridge portion defined by the outer wall surfaces adjacent to each other, and on a ridge portion defined by the outer side surfaces adjacent to each other.

[0018] The configuration in which the electric conductor is not disposed on the corner portion and the ridge portion of the package reduces peeling of the electric conductor starting from the corner portion and the ridge portion.

[0019] In the one aspect, the electric conductor may be disposed on the upper wall surface such that the ratio of the area of the electric conductor to the area of the upper wall surface is 50% or more.

[0020] The configuration in which the ratio of the area of the electric conductor to the area of the upper wall surface is 50% or more enhances the heat dissipation through the electric conductor.

[0021] In the one aspect, the electric conductor may be disposed on the outer wall surface and the outer side surface such that the ratio of the area of the electric conductor to the sum of the area of the outer wall surface and the area of the outer side surface is 50% or more.

[0022] The configuration in which the ratio of the area of the electric conductor to the sum of the area of the outer wall surface and the area of the outer side surface is 50% or more further enhances the heat dissipation through the electric conductor.

[0023] In the one aspect, the window may include a dummy pad disposed on the lower surface and mounting the light source.

[0024] The light source is stably mounted on the window through the dummy pad. The dummy pad mounts the light source, and thus the dummy pad efficiently receives and dissipates the heat generated in the light source.

[0025] In the one aspect, each of the connectors may include a third pad mounting the light source, and the electrically conductive line electrically connecting the first pad and the third pad.

[0026] The light source is mounted through the third pad, and the first pad and the third pad are electrically connected through the electrically conductive line. The light source is mounted on the third pad, and is electrically connected to the first pad.

[0027] In the one aspect, one connector of the plurality of connectors may include the third pad mounting the light source, and the electrically conductive line electrically connecting the first pad and the third pad. Another connector of the plurality of connectors may include a fourth pad electrically connected to the first pad, and a wire electrically connecting the light source and the fourth pad.

[0028] The light source is mounted on the third pad of one connector, and the first pad and the third pad are electrically connected through the electrically conductive line of one connector. The light source is mounted on the third pad and is electrically connected to the first pad. The light source and the fourth pad are electrically connected through the wire of another connector. The fourth pad is electrically connected to the first pad. The light source is electrically connected to the first pad through the wire.

[0029] In the one aspect, each of the connectors may include the fourth pad electrically connected to the first pad, and a wire electrically connecting the light source and the fourth pad.

[0030] The light source and the fourth pad are electrically connected through the wire of each connector. The fourth pad is electrically connected to the first pad. The light source is electrically connected to the first pad through the wire.

[0031] In the one aspect, the window base may be a silicon substrate.

[0032] The silicon substrate has high thermal conductivity. The window base increases thermal conduction to the electric conductor. This increase of thermal conduction enables a decrease in the area of the electrically conductive body. In a case where the area of the electrically conductive body is decreased, the electrically conductive body decreases an amount of the light from the reflection portion blocked through the electrically conductive body itself.

[0033] In the one aspect, the window may include an antireflection film disposed on at least one surface of the lower surface and the light exit surface.

[0034] The antireflection film effectively reduces light reflection on the window base.

[0035] A method for making a light-emitting device according to another aspect includes: preparing a plurality of windows mounting the light source; preparing a block including a plurality of the packages coupled each other in an array; mounting the window on each of the packages of the block to electrically connect a second pad and a third pad corresponding to each other; and separating the block to obtain the plurality of packages mounting the corresponding window.

[0036] According to the other aspect, the wall portion of the package is disposed along the window base. Thus, when the window is mounted in each package of the block, the window is mounted with the wall portion of the package as a mark. Since the mark exists, the window is easily mounted on each package of the block such that the second pad and the third pad corresponding to each other are electrically connected.

[0037] In the other aspect, a height from the placement surface to the upper wall surface may be larger than a height from the placement surface to the light exit surface in a state where the window is mounted to correspond to each package of the block. When the block is separated, the block may be diced along cutting planned lines set between the packages adjacent to each other after the upper wall surface is attached to a dicing tape.

[0038] In a case where the height from the placement surface to the upper wall surface may be larger than the height from the placement surface to the light exit surface, only the upper wall surface is attached to the dicing tape when the block is separated due to dicing. The lower surface of the window base does not come into contact with the dicing tape, and the window base is prevented from being deteriorated due to adhesion of the adhesive.

Advantageous Effects of Invention

[0039] The one aspect provides the light-emitting device that effectively dissipates the heat generated in the light source. The other aspect provides the method for making the light-emitting device that effectively dissipates the heat generated in the light source.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0040] FIG. 1A is a view schematically illustrating a configuration of a light-emitting device

according to a first embodiment, and FIG. 1B is an enlarged view of a light source in FIG. 1A.

[0041] FIG. 2A is a plan view of the light-emitting device according to the first embodiment, and FIG. 2B is a cross-sectional view taken along a line IIb-IIb in FIG. 2A.

[0042] FIG. 3 is an enlarged view of a region E1 in FIG. 2B.

[0043] FIG. 4A is a plan view of the light-emitting device according to the first embodiment, and FIG. 4B is a side view of the light-emitting device according to the first embodiment. FIG. 4C is a front view of the light-emitting device according to the first embodiment, and FIG. 4D is a bottom view of the light-emitting device according to the first embodiment.

[0044] FIG. 5A is a plan view of a package according to the first embodiment, and FIG. 5B is a cross-sectional view taken along a line Vb-Vb in FIG. 5A.

[0045] FIG. 6A is a plan view of a window according to the first embodiment, and FIG. 6B is a front view of the window according to the first embodiment.

[0046] FIG. 7 is a flowchart illustrating a method for making the light-emitting device according to the first embodiment.

[0047] FIGS. 8A, 8B and 8C are views schematically illustrating a main process in the method for making the light-emitting device according to the first embodiment.

[0048] FIGS. 9A and 9B are views schematically illustrating the main process in the method for making the light-emitting device according to the first embodiment.

[0049] FIGS. 10A and 10B are views schematically illustrating the main process in the method for making the light-emitting device according to the first embodiment.

[0050] FIG. 11 is a view schematically illustrating the main process in the method for making the light-emitting device according to the first embodiment.

[0051] FIG. 12A is a plan view of a window according to a second embodiment, and FIG. 12B is a front view of the window according to the second embodiment. FIG. 12C is a plan view of the window on which a light source according to the second embodiment is mounted, and FIG. 12D is a front view of the window on which the light source according to the second embodiment is mounted.

[0052] FIG. 13A is a plan view of a window according to a third embodiment, and FIG. 13B is a front view of the window according to the third embodiment. FIG. 13C is a plan view of the window on which a light source according to the third embodiment is mounted, and FIG. 13D is a front view of the window on which the light source according to the third embodiment is mounted.

[0053] FIG. 14A is a plan view of a light-emitting device according to a fourth embodiment, and FIG. 14B is a side view of the light-emitting device according to the fourth embodiment. FIG. 14C is a front view of the light-emitting device according to the fourth embodiment, and FIG. 14D is a bottom view of the light-emitting device according to the fourth embodiment.

[0054] FIG. 15A is a plan view of a light-emitting device according to a fifth embodiment, and FIG. 15B is a side view of the light-emitting device according to the fifth embodiment. FIG. 15C is a front view of the light-emitting device according to the fifth embodiment, and FIG. 15D is a bottom view of the light-emitting device according to the fifth embodiment.

DESCRIPTION OF EMBODIMENTS

[0055] Hereinafter, embodiments of the present invention will be described in detail with reference to the accompanying drawings. Note that, in the description, the same reference signs will be used for the same elements or elements having the same function, and redundant description will be omitted.

First Embodiment

[0056] A configuration of a light-emitting device D1 according to a first embodiment will be described with reference to FIGS. 1 to 6. FIG. 1A is a view schematically illustrating a configuration of a light-emitting device according to a first embodiment, and FIG. 1B is an enlarged view of a light source in FIG. 1A. FIG. 2A is a plan view of the light-emitting device according to the first embodiment, and FIG. 2B is a cross-sectional view taken along line a IIb-IIb

in FIG. 2A. FIG. 3 is an enlarged view of a region E1 in FIG. 2B. FIG. 4A is a plan view of the light-emitting device according to the first embodiment, and FIG. 4B is a side view of the light-emitting device according to the first embodiment. FIG. 4C is a front view of the light-emitting device according to the first embodiment, and FIG. 4D is a bottom view of the light-emitting device according to the first embodiment. FIG. 5A is a plan view of a package according to the first embodiment, and FIG. 5B is a cross-sectional view taken along line a Vb-Vb in FIG. 5A. FIG. 6A is a plan view of a window according to the first embodiment, and FIG. 6B is a front view of the window according to the first embodiment.

[0057] The light-emitting device D1 includes a light source 10, a window 20, and a package 30. The window 20 is mounted with the light source 10. The package 30 defines a space SC1 with the window 20. The light source 10 is disposed in the space SC1.

[0058] The light source 10 includes a light-emitting element. In the present embodiment, the light-emitting element includes a light-emitting diode (LED). The light-emitting diode used in the light-emitting element emits light in an infrared region having wavelengths of 3 to 5 μm , for example. The light source 10 has, for example, a surface mounting type rectangular parallelepiped shape or a substantially cubic shape. In the light source 10, for example, one of six surfaces having a rectangular parallelepiped shape is a terminal surface 12, and an anode terminal 14 and a cathode terminal 16 are disposed on the terminal surface 12, for example. The light source 10 includes a radiation surface 18 on the opposite side of the terminal surface 12, and light is emitted from the radiation surface 18.

[0059] The window 20 includes a window base 21 and an electrically conductive body WD1. The window base 21 includes a light exit surface 22, a lower surface 23, and a side surface 24. The lower surface 23 opposes the light exit surface 22. The side surface 24 couples the light exit surface 22 and the lower surface 23. The electrically conductive body WD1 is disposed on the lower surface 23 of the window base 21. The coupling between the light exit surface 22 and the lower surface 23 includes a configuration in which the light exit surface 22 and the lower surface 23 are directly coupled and a configuration in which the light exit surface 22 and the lower surface 23 are indirectly coupled with another surface interposed therebetween. Hereinafter, in this specification, coupling between surfaces includes direct coupling and indirect coupling.

[0060] The package 30 includes a base portion 40 and a wall portion 50, and the wall portion 50 is positioned on the base portion 40, for example. The base portion 40 includes a recess 42, a placement surface 44, a bottom surface 46, and an outer side surface 48. The recess 42 is formed to open toward the lower surface 23 of the window base 21. The placement surface 44 is disposed along an edge 47 of the recess 42 and opposes the lower surface 23 of the window base 21. The bottom surface 46 opposes the placement surface 44. The outer side surface 48 is coupled to the bottom surface 46.

[0061] The wall portion 50 includes an inner wall surface 52, an outer wall surface 54, and an upper wall surface 56, and is disposed along the window base 21 when viewed from a direction Ax1 orthogonal to the light exit surface 22. The inner wall surface 52 is coupled to the placement surface 44 and opposes the side surface 24 of the window 20. The outer wall surface 54 opposes the inner wall surface 52 and is coupled to the outer side surface 48. The upper wall surface 56 couples the inner wall surface 52 and the outer wall surface 54.

[0062] The package 30 may have a polygonal shape when viewed from the direction Ax1 orthogonal to the light exit surface 22. The package 30 has, for example, a quadrangular shape including a square shape and a rectangular shape, a hexagonal shape, or an octagonal shape. The number of each of the outer side surfaces 48 and the outer wall surfaces 54 may be plural. The number of each of the outer side surfaces 48 and the outer wall surfaces 54 is, for example, four, six, or eight.

[0063] The package 30 includes a reflection portion 32 and an electric conductor 34. The reflection portion 32 is disposed on a surface 43 of the recess 42. In the light-emitting device D1, light is

emitted from the radiation surface **18** of the light source **10** to the reflection portion **32**, and the reflection portion **32** reflects the light emitted from the light source **10** to the window **20**. The light reflected on the reflection portion **32** is transmitted through the window base **21** of the window **20** and emitted to the outside of the light-emitting device **D1**. The electric conductor **34** is disposed on the placement surface **44**, the inner wall surface **52**, the upper wall surface **56**, the outer wall surface **54**, and the outer side surface **48**.

[0064] The window base **21** is made of a material suitable for transmitting the light reflected on the reflection portion **32**. This material includes, for example, silicon (Si), sapphire, and germanium. Among the materials of the window base **21**, the silicon substrate has a high thermal conductivity of about 150 W/(mK), and favorably transmits infrared light having a wavelength region of, for example, 3 to 5 μm . The silicon substrate may include, on the substrate, an antireflection film that effectively reduces reflection of infrared light having wavelengths of 3 to 5 μm . The silicon substrate disposed with the antireflection film has high light transmittance at wavelengths of 3 to 5 μm , for example, in addition to high thermal conductivity.

[0065] The electrically conductive body **WD1** on the window base **21** includes a plurality of first pads **25** and connectors **CN1**. The plurality of first pads **25** oppose the placement surface **44**. The connectors **CN1** electrically connect the light source **10** and the plurality of first pads **25**. In the present embodiment, each connector **CN1** includes, for example, a third pad **26** and an electrically conductive line **27**. The light source **10** is mounted through the third pad **26**. The electrically conductive line **27** connects the first pad **25** and the third pad **26**. The third pad **26** is disposed on a region where the light source **10** is mounted on the window base **21**, for example, a central region of the window base **21**. The plurality of first pads **25** are disposed, for example, in a peripheral region surrounding the central region.

[0066] The third pad **26** may include one or a plurality of pads. The third pad **26** includes, for example, a first mounting pad body **61** and a second mounting pad body **62**. One of the plurality of third pads **26** is connected to the anode terminal **14** or the cathode terminal **16** of the light source **10**. For example, the first mounting pad body **61** and the second mounting pad body **62** are connected to the anode terminal **14** and the cathode terminal **16** of the light source **10**, respectively.

[0067] The material of the third pad **26** includes, for example, metal plating containing Cu—Ni—Au and a solder. The solder may be disposed on Cu—Ni—Au. A Au layer is positioned as the uppermost layer of the metal-plated Cu—Ni—Au. The material of the first pad **25** and the electrically conductive line **27** is metal plating containing Cu—Ni—Au, Al—Ni—Au, and Ti—Pt—Au. The Au layer is positioned on the uppermost layer of the metal plating.

[0068] The window **20** includes a dummy pad **28** disposed on the lower surface **23**. The light source **10** is mounted on the dummy pad **28**. The dummy pad **28** may include one or a plurality of pads. The dummy pad **28** may include, for example, a first dummy pad body **71** and a second dummy pad body **72**. The first dummy pad body **71** and the second dummy pad body **72** support the light source **10** together with the first mounting pad body **61** and the second mounting pad body **62**. In the present embodiment, the first dummy pad body **71** and the second dummy pad body **72** support the light source **10**, but are not electrically connected to the light source **10**. The dummy pad **28** may be made of the same material as the third pad **26**.

[0069] For example, the first mounting pad body **61**, the second mounting pad body **62**, the first dummy pad body **71**, and the second dummy pad body **72** may be positioned in this order at respective vertexes of a quadrangle virtually drawn in a region of the lower surface **23** where the light source **10** is mounted.

[0070] In the present embodiment, the plurality of third pads **26** include two pad bodies, that is, the first mounting pad body **61** and the second mounting pad body **62**, and the plurality of dummy pads **28** include two dummy pad bodies, that is, the first dummy pad body **71** and the second dummy pad body **72**. In the light-emitting device, the number of pad bodies included in the third pad **26** and the dummy pad **28** is not particularly limited, in a case where power is supplied to the light

source **10** and the light source **10** is stably supported. For example, the number of pad bodies included in the third pad **26** may be two, and the number of pad bodies included in the dummy pad **28** may be one. The number of pad bodies included in the third pad **26** may be two, and the number of pad bodies included in the dummy pad **28** may be three.

[0071] The window base **21** has, for example, a shape like a flat plate, and may have a substantially square shape in plan view. The window base **21** includes, for example, a first side portion **21a**, a second side portion **21b**, a third side portion **21c**, and a fourth side portion **21d**. The first side portion **21a** is positioned on the opposite side of the third side portion **21c**. The second side portion **21b** is positioned on the opposite side of the fourth side portion **21d**.

[0072] The window base **21** includes, for example, four corner portions. The window base **21** includes a first corner portion **29a** defined by the fourth side portion **21d** and the first side portion **21a**, and includes a second corner portion **29b** defined by the first side portion **21a** and the second side portion **21b**. The window base **21** includes a third corner portion **29c** defined by the second side portion **21b** and the third side portion **21c**, and includes a fourth corner portion **29d** defined by the third side portion **21c** and the fourth side portion **21d**.

[0073] The first pad **25** includes, for example, a first pad body **63** and a second pad body **64**. The first pad **25** is disposed in, for example, a peripheral region. For example, the first pad body **63** is disposed from the first corner portion **29a** to the second corner portion **29b** on the first side portion **21a**. For example, the second pad body **64** is disposed from the third corner portion **29c** to the fourth corner portion **29d** on the third side portion **21c**.

[0074] The first pad body **63** includes, for example, a first connection portion **63a** and a second connection portion **63b**. The first connection portion **63a** is positioned at one end edge of the first pad body **63**. The second connection portion **63b** is positioned at another end edge of the first pad body **63**. The first connection portion **63a** is disposed, for example, at the first corner portion **29a**. The second connection portion **63b** is disposed, for example, at the second corner portion **29b**. The first connection portion **63a** and the second connection portion **63b** connect the first pad body **63** and the electric conductor disposed in the package **30**.

[0075] The second pad body **64** includes, for example, a third connection portion **64a** and a fourth connection portion **64b**. The third connection portion **64a** is positioned at one end edge of the second pad body **64**. The fourth connection portion **64b** is positioned at another end edge of the second pad body **64**. The third connection portion **64a** is disposed, for example, at the third corner portion **29c**. The fourth connection portion **64b** is disposed, for example, at the fourth corner portion **29d**. The third connection portion **64a** and the fourth connection portion **64b** connect the second pad body **64** and the electric conductor disposed in the package **30**.

[0076] In the present embodiment, the window **20** includes an underfill UF. The underfill UF is disposed to fill a gap generated between the lower surface **23**, the third pad **26**, the dummy pad **28**, and the light source **10**.

[0077] The electrically conductive line **27** may be one or more. The electrically conductive line **27** electrically connects the first pad **25** and the third pad **26** corresponding to each other. The plurality of electrically conductive lines **27** include, for example, a first electrically conductive line **81** and a second electrically conductive line **82**. The first electrically conductive line **81** electrically connects the first mounting pad body **61** and the first pad body **63**, for example. The second electrically conductive line **82** electrically connects the second mounting pad body **62** and the second pad body **64**, for example.

[0078] The first electrically conductive line **81** is connected to the first pad body **63** and the first mounting pad body **61**. For example, one end edge of the first electrically conductive line **81** is connected to the first pad body **63** to cross the first pad body **63**. For example, another end edge of the first electrically conductive line **81** is connected to the first mounting pad body **61**. The one end edge of the first electrically conductive line **81** and the first pad body **63** intersect, for example, near the center of the first pad body **63**. The other end edge of the first electrically conductive line

81 is positioned, for example, between the window base **21** and the first mounting pad body **61** in the direction **Ax1**.

[0079] The second electrically conductive line **82** is connected to the second pad body **64** and the second mounting pad body **62**. For example, one end edge of the second electrically conductive line **82** is connected to the second pad body **64** to cross the second pad body **64**. For example, another end edge of the second electrically conductive line **82** is connected to the second mounting pad body **62**. The one end edge of the second electrically conductive line **82** and the second pad body **64** intersect, for example, near the center of the second pad body **64**. The other end edge of the second electrically conductive line **82** is positioned, for example, between the window base **21** and the second mounting pad body **62** in the direction **Ax1**.

[0080] The outer side surface **48** of the package **30** includes, for example, a first outer side surface **48a**, a second outer side surface **48b**, a third outer side surface **48c**, and a fourth outer side surface **48d**. The first outer side surface **48a** opposes the third outer side surface **48c**. The second outer side surface **48b** opposes the fourth outer side surface **48d**. The first outer side surface **48a** connects the fourth outer side surface **48d** and the second outer side surface **48b**. The second outer side surface **48b** connects the first outer side surface **48a** and the third outer side surface **48c**. The third outer side surface **48c** connects the second outer side surface **48b** and the fourth outer side surface **48d**, and the fourth outer side surface **48d** connects the third outer side surface **48c** and the first outer side surface **48a**. The first outer side surface **48a**, the second outer side surface **48b**, the third outer side surface **48c**, and the fourth outer side surface **48d** are coupled to the bottom surface **46**.

[0081] The outer wall surface **54** includes, for example, a first outer wall surface **54a**, a second outer wall surface **54b**, a third outer wall surface **54c**, and a fourth outer wall surface **54d**. The first outer wall surface **54a** opposes the third outer wall surface **54c**. The second outer wall surface **54b** opposes the fourth outer wall surface **54d**. The first outer wall surface **54a** connects the fourth outer wall surface **54d** and the second outer wall surface **54b**. The second outer wall surface **54b** connects the first outer wall surface **54a** and the third outer wall surface **54c**. The third outer wall surface **54c** connects the second outer wall surface **54b** and the fourth outer wall surface **54d**. The fourth outer wall surface **54d** connects the third outer wall surface **54c** and the first outer wall surface **54a**.

[0082] The first outer side surface **48a** is coupled to the first outer wall surface **54a**. The second outer side surface **48b** is coupled to the second outer wall surface **54b**. The third outer side surface **48c** is coupled to the third outer wall surface **54c**. The fourth outer side surface **48d** is coupled to the fourth outer wall surface **54d**.

[0083] The inner wall surface **52** includes, for example, a first inner wall surface **52a**, a second inner wall surface **52b**, a third inner wall surface **52c**, and a fourth inner wall surface **52d**. The first inner wall surface **52a** opposes the third inner wall surface **52c**. The second inner wall surface **52b** opposes the fourth inner wall surface **52d**. The first inner wall surface **52a** connects the fourth inner wall surface **52d** and the second inner wall surface **52b**. The second inner wall surface **52b** connects the first inner wall surface **52a** and the third inner wall surface **52c**. The third inner wall surface **52c** connects the second inner wall surface **52b** and the fourth inner wall surface **52d**. The fourth inner wall surface **52d** connects the third inner wall surface **52c** and the first inner wall surface **52a**. The first inner wall surface **52a**, the second inner wall surface **52b**, the third inner wall surface **52c**, and the fourth inner wall surface **52d** are coupled to the mounting surface **44**. The first inner wall surface **52a** opposes the first outer wall surface **54a**. The second inner wall surface **52b** opposes the second outer wall surface **54b**. The third inner wall surface **52c** opposes the third outer wall surface **54c**. The fourth inner wall surface **52d** opposes the fourth outer wall surface **54d**.

[0084] The upper wall surface **56** includes, for example, a first upper wall surface **56a**, a second upper wall surface **56b**, a third upper wall surface **56c**, and a fourth upper wall surface **56d**. The first upper wall surface **56a** is positioned on the opposite side of the third upper wall surface **56c**. The second upper wall surface **56b** is positioned on the opposite side of the fourth upper wall

surface **56d**. The first upper wall surface **56a** connects the first inner wall surface **52a** and the first outer wall surface **54a**. The second upper wall surface **56b** connects the second inner wall surface **52b** and the second outer wall surface **54b**. The third upper wall surface **56c** connects the third inner wall surface **52c** and the third outer wall surface **54c**. The fourth upper wall surface **56d** connects the fourth inner wall surface **52d** and the fourth outer wall surface **54d**.

[0085] The electric conductor **34** includes a plurality of second pads **36**. The plurality of second pads **36** are disposed on the placement surface **44** to oppose the corresponding first pads **25** of the plurality of first pads **25**. The plurality of second pads **36** are electrically connected to the corresponding first pads **25**.

[0086] The placement surface **44** includes, for example, four corners. For example, the placement surface **44** includes a first corner **44a**. The first corner **44a** is defined by the placement surface **44**, the fourth inner wall surface **52d**, and the first inner wall surface **52a**. The placement surface **44** includes a second corner **44b**. The second corner **44b** is defined by the placement surface **44**, the first inner wall surface **52a**, and the second inner wall surface **52b**. The placement surface **44** includes a third corner **44c**. The third corner **44c** is defined by the placement surface **44**, the second inner wall surface **52b**, and the third inner wall surface **52c**. The placement surface **44** includes a fourth corner **44d**. The fourth corner **44d** is defined by the placement surface **44**, the third inner wall surface **52c**, and the fourth inner wall surface **52d**.

[0087] In the present embodiment, for example, the second pads **36** of the electric conductor **34** are disposed at the four corners. The second pad **36** is electrically connected to a connection portion of each pad body disposed on the window **20**. For example, the second pads **36** include a first electric conductor **37a**, a second electric conductor **37b**, a third electric conductor **37c**, and a fourth electric conductor **37d** at the corners. The first electric conductor **37a** is disposed on the first corner **44a**. The first electric conductor **37a** is electrically connected to the fourth connection portion **64b** of the second pad body **64**. The second electric conductor **37b** is disposed on the second corner **44b**. The second electric conductor **37b** is electrically connected to the third connection portion **64a** of the second pad body **64**. The third electric conductor **37c** is disposed on the third corner **44c**. The third electric conductor **37c** is electrically connected to the second connection portion **63b** of the first pad body **63**. The fourth electric conductor **37d** is disposed on the fourth corner **44d**. The fourth electric conductor **37d** is electrically connected to the first connection portion **63a** of the first pad body **63**.

[0088] The fourth connection portion **64b** of the second pad body **64** of the window **20** is electrically connected to the first electric conductor **37a** of the placement surface **44** through an electrically conductive resin. The third connection portion **64a** of the second pad body **64**, and the second connection portion **63b** and the first connection portion **63a** of the first pad body **63** in the window **20** are electrically connected to the second electric conductor **37b**, the third conductor **37c**, and the fourth electric conductor **37d** of the placement surface **44**, respectively, through an electrically conductive resin.

[0089] The electric conductor **34** includes, for example, a first inner electric conductor **38a**, a second inner electric conductor **38b**, a third inner electric conductor **38c**, and a fourth inner electric conductor **38d** on the inner wall surface **52**. For example, the package **30** includes, on the inner wall surface **52**, a first edge portion defined by the fourth inner wall surface **52d** and the first inner wall surface **52a**, and a second edge portion defined by the first inner wall surface **52a** and the second inner wall surface **52b**. The first inner electric conductor **38a** is disposed on the first edge portion. The first inner electric conductor **38a** is electrically connected to the first electric conductor **37a**. The second inner electric conductor **38b** is disposed on the second edge portion. The second inner electric conductor **38b** is electrically connected to the second electric conductor **37b**.

[0090] The package **30** includes a third edge portion defined by the second inner wall surface **52b** and the third inner wall surface **52c**, and a fourth edge portion defined by the third inner wall

surface **52c** and the fourth inner wall surface **52d** on the inner wall surface **52**. The third inner electric conductor **38c** electrically connected to the third electric conductor **37c** is disposed on the third edge portion. The fourth inner electric conductor **38d** electrically connected to the fourth electric conductor **37d** is disposed on the fourth edge portion.

[0091] The package **30** includes a corner portion **31** defined by the upper wall surface **56** and the outer wall surfaces **54** adjacent to each other. For example, in a case where the package **30** has a quadrangular shape when viewed from the direction **Ax1** orthogonal to the light exit surface **22**, the package **30** includes four corner portions **31**. On the upper wall surface **56**, the package **30** includes a first corner portion **31a** defined by the upper wall surface **56**, the fourth outer wall surface **54d**, and the first outer wall surface **54a**. On the upper wall surface **56**, the package **30** includes a second corner portion **31b** defined by the upper wall surface **56**, the first outer wall surface **54a**, and the second outer wall surface **54b**. On the upper wall surface **56**, the package **30** includes a third corner portion **31c** defined by the upper wall surface **56**, the second outer wall surface **54b**, and the third outer wall surface **54c**. On the upper wall surface **56**, the package **30** includes a fourth corner portion **31d** defined by the upper wall surface **56**, the third outer wall surface **54c**, and the fourth outer wall surface **54d**.

[0092] The electric conductor **34** includes, for example, a first upper electric conductor **39a** and a third upper electric conductor **39c** on the upper wall surface **56**. The first upper electric conductor **39a** is disposed on the first upper wall surface **56a**, the second upper wall surface **56b**, and the fourth upper wall surface **56d** except for the first corner portion **31a** and the second corner portion **31b**. The third upper electric conductor **39c** is disposed on the second upper wall surface **56b**, the third upper wall surface **56c**, and the fourth upper wall surface **56d** except for the third corner portion **31c** and the fourth corner portion **31d**. The electric conductor **34** is not disposed on the corner portion **31**.

[0093] The first upper electric conductor **39a** may be disposed in a region of 50% or more of an area of the first upper wall surface **56a** on the first upper wall surface **56a**. The third upper electric conductor **39c** may be disposed in a region of 50% or more of an area of the third upper wall surface **56c** on the third upper wall surface **56c**. The electric conductor **34** may be disposed on the upper wall surface **56** such that the ratio of an area of the electric conductor **34** to an area of the upper wall surface **56** is 50% or more.

[0094] In the present embodiment, the first upper electric conductor **39a** is not disposed in an inner region **56s** of the first upper wall surface **56a**. The first upper electric conductor **39a** may be disposed in the inner region **56s**. In the present embodiment, the third upper electric conductor **39c** is not disposed in an inner region **56t** of the third upper wall surface **56c**. The second upper electric conductor **39b** may be disposed in the inner region **56t**.

[0095] The package **30** includes a ridge portion **33** defined by the outer wall surfaces **54** adjacent to each other. For example, in a case where the package **30** includes a quadrangular shape when viewed from the direction **Ax1** orthogonal to the light exit surface **22**, the package **30** includes four ridge portions **33**. On the outer wall surface **54**, the package **30** includes a first ridge portion **33a** defined by the fourth outer wall surface **54d** and the first outer wall surface **54a**. On the outer wall surface **54**, the package **30** includes a second ridge portion **33b** defined by the first outer wall surface **54a** and the second outer wall surface **54b**. On the outer wall surface **54**, the package **30** includes a third ridge portion **33c** defined by the second outer wall surface **54b** and the third outer wall surface **54c**. On the outer wall surface **54**, the package **30** includes a fourth ridge portion **33d** defined by the third outer wall surface **54c** and the fourth outer wall surface **54d**. These ridge portions **33** are disposed, for example, from the boundary between the upper wall surface **56** and the outer wall surface **54** to the boundary between the outer side surface **48** and the bottom surface **46**.

[0096] The package **30** includes a first outer electric conductor **35a** disposed on the first outer wall surface **54a** and the first outer side surface **48a**. The package **30** includes a third outer electric

conductor **35c** on the third outer wall surface **54c** and the third outer side surface **48c**. The first outer electric conductor **35a** is electrically connected to the first upper electric conductor **39a**. The third outer electric conductor **35c** is electrically connected to the third upper electric conductor **39c**. The first outer electric conductor **35a** is not disposed on the first ridge portion **33a** and the second ridge portion **33b**. The third outer electric conductor **35c** is not disposed on the third ridge portion **33c** and the fourth ridge portion **33d**. The electric conductor **34** is not disposed on the ridge portion **33**.

[0097] The first outer electric conductor **35a** may be disposed in a region of 50% or more of an area of the first outer wall surface **54a** on the first outer wall surface **54a**. The third outer electric conductor **35c** may be disposed in a region of 50% or more of an area of the third outer wall surface **54c** on the third outer wall surface **54c**. The electric conductor **34** may be disposed on the outer wall surface **54** such that the ratio of the area of the electric conductor **34** to an area of the outer wall surface **54** is 50% or more.

[0098] The first outer electric conductor **35a** may be disposed in a region of 50% or more of a sum of the area of the first outer wall surface **54a** and an area of the first outer side surface **48a** on the first outer wall surface **54a** and the first outer side surface **48a**. The third outer electric conductor **35c** may be disposed in a region of 50% or more of a total area of an area of the third outer wall surface **54c** and an area of the third outer side surface **48c** on the third outer wall surface **54c** and the third outer side surface **48c**. The electric conductor **34** may be disposed on the outer wall surface **54** and the outer side surface **48** such that the ratio of the area of the electric conductor **34** to the sum of the area of the outer wall surface **54** and an area of the outer side surface **48** is 50% or more.

[0099] The package **30** includes, for example, a first bottom electric conductor **41a** and a third bottom electric conductor **41c** on the bottom surface **46**. The electric conductor may be further disposed over the bottom surface **46**. The first bottom electric conductor **41a** may be one of an anode electrode and a cathode electrode. The third bottom electric conductor **41c** may be the other of the anode electrode and the cathode electrode. The first bottom electric conductor **41a** is electrically connected to the first outer electric conductor **35a**. The third bottom electric conductor **41c** is electrically connected to the third outer electric conductor **35c**.

[0100] The first bottom electric conductor **41a** may have a two-dimensional shape such as a rectangular shape. The third bottom electric conductor **41c** may have a two-dimensional shape in which a rectangular shape and a triangular shape are integrated. Due to the difference in these two-dimensional shapes, the anode electrode and the cathode electrode are easily identified visually.

[0101] The package **30** includes a reflection portion electric conductor **45**. The reflection portion electric conductor **45** is disposed on the recess **42**, the placement surface **44**, the inner wall surface **52**, and the upper wall surface **56**. The reflection portion electric conductor **45** includes, for example, a first reflection portion electric conductor **45a** and a second reflection portion electric conductor **45b**. The second reflection portion electric conductor **45b** is disposed to oppose the first reflection portion electric conductor **45a**.

[0102] The first reflection portion electric conductor **45a** is disposed on the recess **42**, the placement surface **44**, the second inner wall surface **52b**, and the second upper wall surface **56b**. The second reflection portion electric conductor **45b** is disposed on the recess **42**, the placement surface **44**, the fourth inner wall surface **52d**, and the fourth upper wall surface **56d**. Both the first reflection portion electric conductor **45a** and the second reflection portion electric conductor **45b** are disposed on the recess **42** and are electrically connected to the upper end of the reflection portion **32** disposed on the recess **42**. The first reflection portion electric conductor **45a** and the second reflection portion electric conductor **45b** are made of, for example, electrically conductive materials obtained at the time of forming the reflection portion **32** including metal plating. The reflection portion **32** includes metal plating containing Cu—Ni—Au. In the present embodiment, the Au layer is positioned on the uppermost layer of the metal plating.

[0103] The edge **47** of the recess **42** defines a boundary with the placement surface **44**. The edge **47** has, for example, a substantially circular shape when viewed from the direction **Ax1** orthogonal to the light exit surface **22**. The shape of the edge **47** may be a substantially circular shape or may be any shape as long as the light from the light source **10** is reflected on the reflection portion **32** to the window **20**. The shape of the edge **47** may be, for example, an elliptical shape or a quadrangular shape including a square shape and a rectangular shape when viewed from the direction **Ax1**. The shape of the edge **47** viewed from the direction **Ax1** may be a polygon including a pentagon.

[0104] The recess **42** includes an edge portion **49** along the edge **47** on the surface **43**. The edge portion **49** includes the edge **47**. The reflection portion **32** is not disposed on the edge portion **49** but is disposed on the surface **43** of the recess **42** excluding the edge portion **49**. The first reflection portion electric conductor **45a** and the second reflection portion electric conductor **45b** are also disposed on the edge portion **49**, and are disposed from the upper end edge of the reflection portion **32** to the upper wall surface **56**.

[0105] The reflection portion **32** has a cross-sectional shape corresponding to the surface **43** of the recess **42**. The reflecting portion **32** may have any cross-sectional shape as long as it reflects light from the light source portion **10** to the window portion **20**. The reflection portion **32** has, for example, an elliptical shape or a parabolic shape. According to these shapes, the beam of the light reflected on the reflection portion **32** is, for example, a focused beam. If necessary, the beam of the light reflected on the reflection portion **32** may be a parallel beam or a diffused beam. In addition to the elliptical shape or the parabolic shape, the cross-sectional shape of the reflection portion **32** may have another shape in which the light from the light source **10** is reflected to the window **20**, for example. The other shape may be formed by combining a plurality of planar shapes.

[0106] In the present embodiment, the package **30** is made of, for example, a ceramic or a PPA resin. The electric conductor **34** is made of, metal plating. The metal plating is, for example, Cu—Ni—Au plating. In the present embodiment, the Au layer is positioned on the uppermost layer of the metal plating.

[0107] In the light-emitting device **D1**, a height from the placement surface **44** to the upper wall surface **56** may be larger than a height from the placement surface **44** to the light exit surface **22**. The height from the placement surface **44** to the upper wall surface **56** may be about the same as the height from the placement surface **44** to the light exit surface **22**. The height from the placement surface **44** to the upper wall surface **56** may be smaller than the height from the placement surface **44** to the light exit surface **22**.

[0108] In the light-emitting device **D1**, the light source **10** mounted on the window **20** emits light to the reflection portion **32** disposed in the recess **42** opposing the lower surface **23** of the window base **21**. The reflection portion **32** reflects the light to the window **20**. The window **20** transmits the light reflected on the reflection portion **32** toward the outside. The reflection portion **32** is disposed on the surface **43** of the recess **42**, and the light to be reflected is focused due to the recessed shape of the reflection portion **32**. As a result, the light transmitted through the window **20** has an improved light density, and the improved light density provides the light-emitting device **D1** for analyzing the environmental gas with high sensitivity.

[0109] In the light-emitting device **D1**, the light source **10** is electrically connected to the plurality of first pads **25** through a plurality of connectors **CN1**. The plurality of first pads **25** are electrically connected to the electric conductor **34** through the corresponding second pads **36**. The light source **10** is electrically connected to the electric conductor **34** through the first pad **25** and the second pad **36**. The electric conductor **34** is disposed on the placement surface **44**, the inner wall surface **52**, the upper wall surface **56**, the outer wall surface **54**, and the outer side surface **48**. This disposal of the electric conductor **34** provides a large area in contact with the outside of the light-emitting device **D1**. The heat generated in the light source **10** due to the supply of power is effectively dissipated through the electric conductor **34** having the large area in contact with the outside.

[0110] In the present embodiment, for example, the light source **10** is supported with the four pads,

that is, the first mounting pad body **61**, the second mounting pad body **62**, the first dummy pad body **71**, and the second dummy pad body **72**. The light source **10** is stably mounted on the pad. The heat generated from the light source **10** is efficiently conducted to the electrically conductive body **WD1** particularly through the first mounting pad body **61** and the second mounting pad body **62**.

[0111] In the light-emitting device **D1**, the electric conductor **34** is further disposed on the bottom surface **46**. Therefore, this disposal further increases the area where the electric conductor **34** is in contact with the outside of the light-emitting device **D1**. As a result, the light-emitting device **D1** further improves heat dissipation through the electric conductor **34**.

[0112] In the present embodiment, the thickness of the electric conductor **34** is, for example, 100 Å to 100 μm. In a case where the electric conductor **34** has a thickness in this range, the heat dissipation through the electric conductor **34** is further increased. The thickness of the electric conductor **34** may be, for example, 1 μm to 30 μm. In a case where the electric conductor **34** has a thickness in this range, the heat dissipation through the electric conductor **34** is further increased.

[0113] In the present embodiment, the thermal conductivity of the electric conductor **34** is, for example, 50 to 500 W/(mK). In a case where the electric conductor **34** has a thermal conductivity in this range, the heat dissipation through the electric conductor **34** is further increased. The thermal conductivity of the electric conductor **34** may be, for example, 300 to 450 W/(mK). In a case where the electric conductor **34** has a thermal conductivity in this range, the heat dissipation through the electric conductor **34** is further increased.

[0114] In the light-emitting device **D1**, the height from the placement surface **44** to the upper wall surface **56** is larger than the height from the placement surface **44** to the light exit surface **22**. Therefore, in the configuration in which the height from the placement surface **44** to the upper wall surface **56** is larger than the height from the placement surface **44** to the light exit surface **22**, the wall portion disposed along the window base **21** prevents the window base **21** from coming into contact with an external object of the light-emitting device **D1**. Damage to the window base **21** is reduced, and thus the window base **21** favorably transmits the light reflected on the reflection portion **32** toward the outside. On the inner wall surface **52**, the electric conductor **34** is disposed in a region from the placement surface **44** to the upper wall surface **56**. Therefore, this disposal further improves the heat dissipation through the electric conductor **34**. For example, in a light-emitting device including an LED, generally, the size of the electric conductor tends to be reduced from the viewpoint of reducing the generation of noise. But, in the light-emitting device **D1** of the present embodiment, the electric conductor **34** is disposed in the region from the placement surface **44** to the upper wall surface **56** to improve the heat dissipation through the electric conductor **34**.

[0115] In the light-emitting device **D1**, the electric conductor **34** is disposed on the upper wall surface **56** such that the ratio of the area of the electric conductor **34** to the area of the upper wall surface **56** is 50% or more. Therefore, the heat dissipation through the electric conductor **34** is enhanced in the light-emitting device **D1**.

[0116] In the light-emitting device **D1**, the electric conductor **34** is disposed on the outer wall surface **54** such that the ratio of the area of the electric conductor **34** to the area of the outer wall surface **54** is 50% or more. Therefore, the heat dissipation through the electric conductor **34** is further enhanced in the light-emitting device **D1**.

[0117] In the light-emitting device **D1**, the electric conductor **34** is disposed on the outer wall surface **54** and the outer side surface **48** such that the ratio of the area of the electric conductor **34** to the sum of the area of the outer wall surface **54** and the area of the outer side surface **48** is 50% or more. Therefore, the heat dissipation through the electric conductor **34** is further enhanced in the light-emitting device **D1**.

[0118] In the light-emitting device **D1**, the electric conductor **34** is not disposed to the corner portion **31** and the ridge portion **33** of the package **30**. Therefore, peeling of the electric conductor **34** starting from the corner portion **31** and the ridge portion **33** is reduced in the light-emitting

device D1.

[0119] In the light-emitting device D1, the light source 10 is stably mounted on the window 20 through the dummy pad 28. The dummy pad 28 mounts the light source 10, and thus the dummy pad 28 efficiently receives and dissipates the heat generated in the light source 10.

[0120] In the light-emitting device D1, each of the connectors CN1 include the third pad 26 mounting the light source 10, and the electrically conductive line 27 electrically connecting the first pad 25 and the third pad 26. The light source 10 is mounted through the third pad 26, and the first pad 25 and the third pad 26 are electrically connected through the electrically conductive line 27. The light source 10 is mounted on the third pad 26, and is electrically connected to the first pad 25.

[0121] In the light-emitting device D1, the silicon substrate of the window base 21 has high thermal conductivity. The window base 20 increases thermal conduction to the electric conductor 34. This increase of thermal conduction enables a decrease in the area of the electrically conductive body WD1. In a case where the area of the electrically conductive body WD1 is decreased, the electrically conductive body WD1 decreases an amount of the light from the reflection portion 32 blocked through the electrically conductive body WD1 itself.

[0122] Hereinafter, a method for making the light-emitting device D1 will be described with reference to FIGS. 7 to 11. FIG. 7 is a flowchart illustrating a method for making the light-emitting device according to the first embodiment. FIGS. 8, 9, 10, and 11 are views schematically illustrating a main process in the method for making the light-emitting device according to the first embodiment. FIG. 8A is a schematic view illustrating a cross-sectional configuration of a window base used in the method for making the light-emitting device according to the first embodiment. FIG. 8B is a view illustrating an electric conductor pattern on the window in the method for making the light-emitting device according to the first embodiment, and FIG. 8C is a view illustrating a light source mounted on the electric conductor pattern in FIG. 8B. FIG. 9A is a view illustrating a block in which a plurality of packages are connected in an array from an upper wall surface side of the package, and FIG. 9B is an enlarged view illustrating the packages of FIG. 9A. FIG. 10A is a view illustrating the block from a bottom surface side of the package, and FIG. 10B is an enlarged view illustrating the packages of FIG. 10A. FIG. 11 is a diagram illustrating separation of the block.

Preparation of Window

[0123] In process S1, the window 20 is prepared. First, in process S1a, a transparent substrate for forming the window base 21 is prepared. The window base 21 of the transparent substrate is, for example, a silicon substrate. If necessary, an antireflection film AR is formed on the lower surface 23 of the window base 21. In this case, the window 20 includes the antireflection film AR disposed on the lower surface 23. The antireflection film AR effectively reduces light reflection of infrared light having wavelengths of 3 to 5 μm generated in a transparent substrate, for example. The antireflection film AR may be formed on the light exit surface 22 of the window base 21. In this case, the window 20 includes the antireflection film AR disposed on the light exit surface 22. The antireflection film AR may be formed on the lower surface 23 and the light exit surface 22. In this case, the window 20 includes the antireflection film AR disposed on the lower surface 23 and the antireflection film AR disposed on the light exit surface 22. The configuration in which the antireflection film AR is disposed on the lower surface 23 and the light exit surface 22 more effectively reduces light reflection of infrared light having wavelengths of 3 to 5 μm generated in a transparent substrate, for example.

[0124] Next, in process S1b, first, a plurality of first pads 25 and a plurality of electrically conductive lines 27 of the electrically conductive body WD1 are formed on the lower surface 23 of the window base 21. In forming the electrically conductive body WD1, for example, Cu plating, Ni plating, and Au plating are performed in this order to form a electric conductor pattern of Cu—Ni—Au metal plating. The Au layer is positioned on the uppermost layer of the metal plating of the electric conductor pattern. The electric conductor pattern is formed, for example, such that one

section of electrically conductive bodies **WD1** are arranged one-dimensionally or two-dimensionally. The first pad **25** includes, for example, the first pad body **63** and the second pad body **64**, and the electrically conductive line **27** includes the first electrically conductive line **81** and the second electrically conductive line **82**.

[0125] Next, in process **S1b**, a plurality of third pads **26** and dummy pads **28** in the electrically conductive body **WD1** are formed to mount the light source **10** on the lower surface **23** of the window base **21**. The third pad **26** includes, for example, the first mounting pad body **61** and the second mounting pad body **62**. The dummy pad **28** includes, for example, the first dummy pad body **71** and the second dummy pad body **72**. In forming the electrically conductive body **WD1**, for example, a cream solder is applied on the electric conductor pattern. A cream solder **26a** for forming the third pad **26** includes, for example, a solder **61a** for forming the first mounting pad body **61** and a solder **62a** for forming the second mounting pad body **62**. A cream solder **28a** for forming the dummy pads **28** includes a solder **71a** for forming the first dummy pad body **71** and a solder **72a** for forming the second dummy pad body **72**. The solder **61a** and the solder **62a** are applied to be positioned on the end edge of the electrically conductive line **27**. For example, the end edge of the first electrically conductive line **81** is positioned between the window base **21** and the solder **61a** along the direction **Ax1**. The cream solder includes, for example, Sn, a metal having a melting point higher than the melting point of Sn, and a flux.

[0126] In process **S1c**, the light source **10** is mounted on the applied cream solder. In this mounting, heat treatment (reflow) is performed to melt the printed cream solder, whereby the light source **10** is mounted on the cream solder. The light source **10** is mounted such that the anode terminal **14** and the cathode terminal **16** of the light source **10** are electrically connected to, for example, the first mounting pad body **61** and the second mounting pad body **62**, respectively. The cream solder is cooled after the light source **10** is mounted. From this cooling, the cream solder is solidified, and the light source **10** is fixed on the pad. The light source **10** is also fixed with the first dummy pad body **71** and the second dummy pad body **72** together with the first mounting pad body **61** and the second mounting pad body **62**.

[0127] In process **S1c**, next, the underfill **UF** is injected into a gap generated between the lower surface **23**, the third pad **26**, the dummy pad **28**, and the light source **10** to form a substrate product **SP1**. The substrate product **SP1** includes a plurality of one-section electrically conductive bodies **WD1** arranged one-dimensionally or two-dimensionally. The underfill **UF** includes, for example, an epoxy resin.

[0128] In process **S1d**, the substrate product **SP1** is separated to form a plurality of windows **20** separated for each section. The separation of the substrate product **SP1** is performed, for example, using a blade dicing method, and the substrate product **SP1** is cut along cutting lines **C1** to **C4** such that the substrate product **SP1** is separated by one section. Electric conductor pattern may or may not be formed on the cutting lines **C1** to **C4**. When electric conductor patterns are not formed on the cutting lines **C1** to **C4**, an interval between the electric conductor patterns adjacent to each other with the cutting lines **C1** to **C4** interposed therebetween may be, for example, wider than the width of the blade used in the blade dicing method. Each of the windows **20** of one section separated by cutting is two-dimensionally arranged on a chip tray, for example. After process **S1b**, the window **20** is prepared.

Preparation of Block

[0129] In process **S2**, a block **AG1** is prepared. First, in process **S2a**, a preparation body of the block **AG1** is formed such that a plurality of packages **30** are connected in an array. In the preparation body, a plurality of package preparation bodies prepared to form the package **30** before the reflection portion and the electric conductor are coupled in an array, and are made using, for example, an injection molding method. The preparation body includes a plurality of package preparation bodies and a substrate portion **SB1** supporting the package preparation bodies. The substrate portion **SB1** is installed to surround the plurality of package preparation bodies. The

preparation body includes a plurality of package preparation bodies arranged one-dimensionally or two-dimensionally in the substrate portion SB1.

[0130] In the present embodiment, the preparation body includes, for example, four package preparation bodies, and these package preparation bodies are arranged in two rows and two columns. The package preparation body has the same outer shape as the package 30 except for the reflection portion and the electric conductor disposed on the surface of the package 30. The material contained in the package preparation body may be the same as the material of the substrate portion SB1, and is, for example, a ceramic or a polyphthalamide (PPA) resin.

[0131] In the preparation body, the upper wall surface 56 of the package preparation body may be substantially flush with a front surface FP of the substrate portion SB1. A distance from a back surface BP of the substrate portion SB1 to the bottom surface 46 of the package preparation body is larger than, for example, a distance from the front surface FP of the substrate portion SB1 to the back surface BP, that is, the thickness of the substrate portion SB1. In process S2a, plasma treatment is performed on the surface of the preparation body for activating the surface as necessary.

[0132] Next, in process S2b, metallizing for forming a metal thin film containing Cu, for example, is performed on the surface of the preparation body subjected to process S2a. After preparation of the thin film, patterning for forming the reflection portion 32 and the electric conductor 34 is performed using, for example, a laser patterning method. Due to patterning, in process S2b, for example, metal plating is formed by using an electrically conductive base BW1 disposed on the surface of the preparation body. The electrically conductive base BW1 is disposed to surround the four package preparation bodies, and is electrically connected to the four package preparation bodies. The electrically conductive base BW1 conducts electricity necessary for forming metal plating for the four package preparation bodies. Due to conducting electricity from the electrically conductive base BW1, electric Cu plating is formed in a region where the electric conductor 34 is disposed. The electrically conductive base BW1 includes an electrically conductive body of the reflection portion 45p for forming the first reflection portion electric conductor 45a and the second reflection portion electric conductor 45b. The reflection portion 32 is formed due to conducting electricity from the electrically conductive body of the reflection portion 45p.

[0133] For example, Ni plating and subsequent Au plating are further formed on the disposed Cu plating. The reflection portion 32 and the electric conductor 34 including Cu—Ni—Au metal plating are formed. In the present embodiment, the Au layer is positioned on the uppermost layer of the metal plating. The block AG1 including the package 30 is prepared after forming the metal plating.

[0134] In the block AG1, in each package 30, the first outer electric conductor 35a is formed on the first outer wall surface 54a, and the third outer electric conductor 35c is formed on the third outer wall surface 54c. In the block AG1, a gap GP1 exists between one package 30 and another package 30 arranged along a direction Bx1 from the first outer wall surface 54a to the third outer wall surface 54c. The package 30 and the gap GP1 are alternately arranged. The gap GP1 is, for example, a work region for forming the first outer electric conductor 35a and the third outer electric conductor 35c on the first outer wall surface 54a and the third outer wall surface 54c, respectively.

Mounting of Window

[0135] In process S3, the window 20 is mounted on each package 30 of the block AG1. In process S3, the window 20 is mounted on the placement surface 44 such that the first pad 25 of the window 20 is electrically connected to the second pad 36 of the placement surface 44. The window 20 is mounted on the placement surface 44 through, for example, an electrically conductive resin. The window 20 is fixed to the package 30 through the adhesiveness of the electrically conductive resin.

Separation of Block

[0136] In process S4, the block AG1 is separated to obtain a plurality of packages 30 on which the

corresponding windows **20** are mounted. The separation of the block **AG1** is performed due to, for example, blade dicing. In the present embodiment, when the block **AG1** is separated, the block **AG1** is diced along cutting planned lines **CT1** to **CT4** set between the packages **30** adjacent to each other after the upper wall surface **56** is attached to a dicing tape **DT1**.

[0137] The cutting planned lines **CT1** to **CT4** are positioned in the direction **Bx1** from the first outer wall surface **54a** to the third outer wall surface **54c**. From cutting due to dicing, the second outer wall surface **54b** and the fourth outer wall surface **54d** are separated from the block **AG1**. After this separation, the plurality of packages **30** on which the corresponding windows **20** are mounted are cut for each section, and the making of the light-emitting device **D1** is completed.

[0138] In a method **MT1** for making the light-emitting device, the wall portion **50** of the package **30** is disposed along the window base **21**. Thus, when the window **20** is mounted in each package **30** of the block **AG1**, the window **20** is mounted with the wall portion **50** (among these, in particular, the inner wall surface **52**) of the package **30** as a mark. Since the mark exists, the window **20** is easily mounted on each package **30** of the block **AG1** such that the first pad **25** and the second pad **36** corresponding to each other are electrically connected.

[0139] In the method **M1** for making the light-emitting device, the height from the placement surface **44** to the upper wall surface **56** is larger than the height from the placement surface **44** to the light exit surface **22** in a state where the window **20** is mounted to correspond to each package **30** of the block **AG1**.

[0140] According to the method **M1** for making the light-emitting device, the height from the placement surface **44** to the upper wall surface **56** is larger than the height from the placement surface **44** to the light exit surface **22**. Thus, only the upper wall surface **56** is attached to the dicing tape when the block **AG1** is separated due to dicing. The lower surface **23** of the window base **21** does not come into contact with the dicing tape **DT1**, and the window base **21** is prevented from being deteriorated due to adhesion of the adhesive. When the block **AG1** is separated due to dicing, water may be poured on the block **AG1** for washing away dicing powder generated due to dicing and cooling, for example. However, the height from the placement surface **44** to the upper wall surface **56** may be larger than the height from the placement surface **44** to the light exit surface **22**. Thus, entry of water into the window base **21** is effectively suppressed through the wall portion **50** disposed along the window base **21**. An occurrence of an electrical short circuit due to adhesion of water, an increase in light absorption due to water, or deterioration of the window base **21** due to adhesion of water is reduced.

Second Embodiment

[0141] Next, a configuration of a light-emitting device according to a second embodiment will be described. FIG. **12A** is a plan view of a window according to the second embodiment, and FIG. **12B** is a front view of the window according to the second embodiment. FIG. **12C** is a plan view of the window on which a light source according to the second embodiment is mounted, and FIG. **12D** is a front view of the window on which the light source according to the second embodiment is mounted. The light-emitting device according to the second embodiment has the same configuration as the light-emitting device **D1** according to the first embodiment except for the window **20**.

[0142] A window **20p** according to the second embodiment will be described below with reference to FIGS. **12A** to **12D**. The window **20p** includes the window base **21** and an electrically conductive body **WD1p**. The window base **21** includes the light exit surface **22** and the lower surface **23** opposing the light exit surface **22**. The electrically conductive body **WD1p** is disposed on the lower surface **23** of the window base **21**.

[0143] A light source **10p** of the present embodiment includes, for example, a light-emitting diode and has a surface mounting type rectangular parallelepiped shape. One surface of the light source **10p** is a terminal surface **12p**. One of the anode terminal **14** and a cathode terminal **16p**, for example, the anode terminal **14** is disposed on the terminal surface **12p**. The light source **10p**

includes a radiation surface **18p** on the opposite side of the terminal surface **12p**. In the present embodiment, for example, the other of the anode terminal **14** and the cathode terminal **16p**, for example, the cathode terminal **16p** is disposed on the radiation surface **18p**.

[0144] The electrically conductive body **WD1p** on the window base **21** includes a plurality of first pads **25p**. The plurality of first pads **25p** oppose the placement surface **44** and are disposed in a peripheral region surrounding the central region in the window **20p**. In the present embodiment, the plurality of first pads **25p** include, for example, a first pad body **63p** and a second pad body **64p**. For example, the first pad body **63p** is disposed from the first corner portion **29a** to the second corner portion **29b** on the first side portion **21a**. The second pad body **64p** is disposed from the third corner portion **29c** to the fourth corner portion **29d** on the third side portion **21c**.

[0145] For example, the first pad body **63p** includes the first connection portion **63a** at one end edge of the first pad body **63p**, and the second connection portion **63b** at another end edge of the first pad body **63p**. The first connection portion **63a** is disposed at the first corner portion **29a**. The second connection portion **63b** is disposed at the second corner portion **29b**. The first connection portion **63a** and the second connection portion **63b** electrically connect the first pad body **63p** and the electric conductor **34** disposed in the package **30**.

[0146] For example, the second pad body **64p** includes the third connection portion **64a** at one end edge of the second pad body **64p**, and the fourth connection portion **64b** at another end edge of the second pad body **64p**. The third connection portion **64a** is disposed at the third corner portion **29c**. The fourth connection portion **64b** is disposed at the fourth corner portion **29d**. The third connection portion **64a** and the fourth connection portion **64b** connect the second pad body **64p** and the electric conductor **34** disposed in the package **30**.

[0147] The electrically conductive body **WD1p** on the window base **21** further includes a plurality of connectors **CN1p**. One connector **CN1a** of the plurality of connectors **CN1p** includes a third pad **26p**. The light source **10p** is mounted on the third pad **26p**. The third pad **26p** is disposed on a region where the light source **10p** is mounted on the window base **21**, for example, a central region of the window base **21**. In the present embodiment, the third pad **26p** includes, for example, the first mounting pad body **61**. For example, the first mounting pad body **61** is electrically connected to the anode terminal **14** positioned on the terminal surface **12p** of the light source **10p**.

[0148] The window **20p** includes a dummy pad **28p** disposed on the lower surface **23**. The light source **10p** is mounted on the dummy pad **28p**. The dummy pad **28p** includes, for example, the first dummy pad body **71**, the second dummy pad body **72**, and a third dummy pad body **73**. The first dummy pad body **71**, the second dummy pad body **72**, and the third dummy pad body **73** support the light source **10p** together with the first mounting pad body **61**. The first dummy pad body **71**, the second dummy pad body **72**, and the third dummy pad body **73** support the light source **10p**, but are not electrically connected to the light source **10p**.

[0149] For example, the first mounting pad body **61**, the first dummy pad body **71**, the second dummy pad body **72**, and the third dummy pad body **73** may be positioned in this order at respective vertexes of a quadrangle virtually drawn in a region of the lower surface **23** where the light source **10p** is mounted. If necessary, the window **20p** includes the underfill **UF**. The underfill **UF** is disposed to fill a gap generated between the lower surface **23**, the third pad **26p**, the dummy pad **28p**, and the light source **10p**.

[0150] In the present embodiment, for example, the light source **10p** is supported with the four pads, that is, the first mounting pad body **61**, the first dummy pad body **71**, the second dummy pad body **72**, and the third dummy pad body **73**. Thus, the light source **10p** is stably mounted on the window **20p**. The heat generated from the light source **10p** is efficiently conducted to the electrically conductive body **WD1p** particularly through the first mounting pad body **61**.

[0151] One connector **CN1a** of the plurality of connectors **CN1p** further includes an electrically conductive line **27p**. The electrically conductive line **27p** electrically connects the first pad **25p** and the third pad **26p** corresponding to each other. For example, the electrically conductive line **27p**

electrically connects the first pad body **63p** of the first pad **25p** and the first mounting pad body **61** of the third pad **26p**.

[0152] The electrically conductive line **27p** includes, for example, the first electrically conductive line **81**. The first electrically conductive line **81** electrically connects the first pad body **63p** and the first mounting pad body **61**. For example, one end edge of the first electrically conductive line **81** is connected to the first pad body **63p** to cross the first pad body **63p**. For example, another end edge of the first electrically conductive line **81** is connected to the first mounting pad body **61**. One end edge of the first electrically conductive line **81** and the first pad body **63p** intersect, for example, near the center of the first pad body **63p**. The other end edge of the first electrically conductive line **81** is positioned, for example, between the window base **21** and the first mounting pad body **61** in the direction **Ax1**.

[0153] Among the plurality of connectors **CN1p**, a connector **CN1b** different from the one connector **CN1a** includes a fourth pad **65p** and a line **82p**. The fourth pad **65p** includes, for example, a second connection pad **65b**. The second connection pad **65b** is electrically connected to the first pad **25p** (first pad body **63p**) in the middle of the third connection portion **64a** and the fourth connection portion **64b**. The line **82p** electrically connects the fourth pad **65p** (second connection pad **65b**) and the light source **10p**. The first pad **25p** and the light source **10p** are electrically connected through the fourth pad **65p** and the line **82p**. For example, one end edge of the line **82p** is connected to the fourth pad **65p** (second connection pad **65b**). For example, the other end edge of the line **82p** is connected to the cathode terminal **16p** of the light source **10p**. For example, the line **82p** electrically connects the cathode terminal **16p** positioned on the radiation surface **18p** of the light source **10p** and the fourth pad **65p** (second connection pad **65b**). The line **82p** is, for example, a second bonding line **82b**.

[0154] In the light-emitting device according to the present embodiment, the light source **10p** is mounted on the third pad **26p** of one connector **CN1a**, and the first pad **25p** and the third pad **26p** are electrically connected through the electrically conductive line **27p** of one connector **CN1a**. The light source **10p** is mounted on the third pad **26p**, and is electrically connected to the first pad **25p**. The light source **10p** and the fourth pad **65p** are electrically connected through the wire **82p** of another connector **CN1b**. The fourth pad **65p** is electrically connected to the first pad **25p**. The light source **10p** is electrically connected to the first pad **25p** through the wire **82p**.

Third Embodiment

[0155] Next, a configuration of a light-emitting device according to a third embodiment will be described. FIG. **13A** is a plan view of a window according to the third embodiment, and FIG. **13B** is a front view of the window according to the third embodiment. FIG. **13C** is a plan view of the window on which a light source according to the third embodiment is mounted, and FIG. **13D** is a front view of the window on which the light source according to the third embodiment is mounted. The light-emitting device according to the third embodiment has the same configuration as the light-emitting device **D1** according to the first embodiment except for the window **20**.

[0156] Hereinafter, a window **20q** according to the third embodiment will be described with reference to FIGS. **13A** to **13D**. The window **20q** includes the window base **21** and an electrically conductive body **WD1q**. The window base **21** includes the light exit surface **22** and the lower surface **23** opposing the light exit surface **22**. The electrically conductive body **WD1q** is disposed on the lower surface **23** of the window base **21**.

[0157] A light source **10q** of the present embodiment includes, for example, a light-emitting diode and has a surface mounting type rectangular parallelepiped shape. One surface of the light source **10q** is a terminal surface **12q**. The light source **10q** includes a radiation surface **18q** on the opposite side of the terminal surface **12q**, and light is emitted from the radiation surface **18q** to the reflection portion **32**. In the present embodiment, for example, an anode terminal **14q** and a cathode terminal **16q** are disposed on the radiation surface **18q**.

[0158] The electrically conductive body **WD1p** on the window base **21** includes a plurality of first

pads **25q**. The plurality of first pads **25q** oppose the placement surface **44** and are disposed in a peripheral region surrounding the central region in the window **20q**. In the present embodiment, the plurality of first pads **25q** include for example, a first pad body **63q** and a second pad body **64q**. For example, the first pad body **63q** is disposed from the first corner portion **29a** to the second corner portion **29b** on the first side portion **21a**. The second pad body **64q** is disposed from the third corner portion **29c** to the fourth corner portion **29d** on the third side portion **21c**.

[0159] For example, the first pad body **63q** includes the first connection portion **63a** at one end edge of the first pad body **63q**, and the second connection portion **63b** at the other end edge of the first pad body **63q**. The first connection portion **63a** is disposed at the first corner portion **29a**. The second connection portion **63b** is disposed at the second corner portion **29b**. The first connection portion **63a** and the second connection portion **63b** electrically connect the first pad body **63q** and the electric conductor **34** disposed in the package **30**.

[0160] The second pad body **64q** includes, for example, the third connection portion **64a** and the fourth connection portion **64b**. The third connection portion **64a** is positioned at one end edge of the second pad body **64q**. The fourth connection portion **64b** is positioned at another end edge of the second pad body **64q**. The third connection portion **64a** is disposed at the third corner portion **29c**. The fourth connection portion **64b** is disposed at the fourth corner portion **29d**. The third connection portion **64a** and the fourth connection portion **64b** connect the second pad body **64q** and the electric conductor **34** disposed in the package **30**.

[0161] The window **20q** includes a dummy pad **28q** disposed on the lower surface **23**. The light source **10q** is mounted on the dummy pad **28q**. The dummy pad **28q** includes, for example, the first dummy pad body **71**, the second dummy pad body **72**, the third dummy pad body **73**, and a fourth dummy pad body **74**. The first dummy pad body **71**, the second dummy pad body **72**, the third dummy pad body **73**, and the fourth dummy pad body **74** support the light source **10q**. The first dummy pad body **71**, the second dummy pad body **72**, the third dummy pad body **73**, and the fourth dummy pad body **74** support the light source **10q** but are not electrically connected to the light source **10q**.

[0162] The first dummy pad body **71**, the second dummy pad body **72**, the third dummy pad body **73**, and the fourth dummy pad body **74** are positioned, for example, in this order at respective vertexes of a quadrangle virtually drawn in a region of the lower surface **23** where the light source **10q** is mounted. If necessary, the window **20q** includes the underfill UF. The underfill UF is disposed to fill a gap generated between the lower surface **23**, the dummy pad **28q**, and the light source **10q**.

[0163] In the present embodiment, for example, the light source **10q** is supported with four dummy pads, that is, the first dummy pad body **71**, the second dummy pad body **72**, the third dummy pad body **73**, and the fourth dummy pad body **74**. Therefore, the light source **10q** is stably mounted on the window **20q**.

[0164] The electrically conductive body **WD1q** on the window base **21** further includes a plurality of connectors **CN1q**, and each of the connectors **CN1q** includes a fourth pad **65q** and a wire **82q**. The fourth pad **65q** includes, for example, a first connection pad **65a** and a second connection pad **65b**. The wire **82q** includes, for example, the first bonding wire **82a** and the second bonding wire **82b**.

[0165] The first connection pad **65a** is electrically connected to the first pad **25q** (first pad body **63q**) in the middle between the first connection portion **63a** and the second connection portion **63b**. The second connection pad **65b** is electrically connected to the first pad **25q** (second pad body **64q**) in the middle between the third connection portion **64a** and the fourth connection portion **64b**. The wire **82q** electrically connects the fourth pad **65q** and the light source **10q**. The first pad **25q** and the light source **10q** are electrically connected through the fourth pad **65q** and the wire **82q**. For example, one end edge of the first bonding wire **82a** is connected to the fourth pad **65q** (first connection pad **65a**). For example, another end edge of the first bonding wire **82a** is connected to

the anode terminal **14q** of the light source **10q**. For example, the second bonding wire **82b** electrically connects the cathode terminal **16q** positioned on the radiation surface **18q** of the light source **10q** and the fourth pad **65q** (second connection pad **65b**).

[0166] In the light-emitting device according to the present embodiment, the light source **10q** and the fourth pad **65q** are electrically connected through the wire **82q** of each connector **CN1q**. The fourth pad **65q** is electrically connected to the first pad **25q**. The light source **10q** is electrically connected to the first pad **25q** through the wire **82q**.

Fourth Embodiment

[0167] Next, a configuration of a light-emitting device **D2** according to a fourth embodiment will be described. FIG. **14A** is a plan view of a light-emitting device according to the fourth embodiment, and FIG. **14B** is a side view of the light-emitting device according to the fourth embodiment. FIG. **14C** is a front view of the light-emitting device according to the fourth embodiment, and FIG. **14D** is a bottom view of the light-emitting device according to the fourth embodiment. The light-emitting device **D2** according to the fourth embodiment has the same configuration as the light-emitting device **D1** according to the first embodiment except for an electric conductor **34m**.

[0168] As illustrated in FIGS. **14A** to **14D**, a package **30m** according to the fourth embodiment includes the electric conductor **34m**. The electric conductor **34m** is disposed on the placement surface **44**, the inner wall surface **52**, and the upper wall surface **56**. In the present embodiment, unlike the first embodiment, the electric conductor **34m** is disposed on the placement surface **44**, the inner wall surface **52**, and the upper wall surface **56**, but is not disposed on the outer wall surface **54** and the outer side surface **48**.

[0169] The electric conductor **34m** includes, for example, a first upper electric conductor **39e** and a third upper electric conductor **39f** on the upper wall surface **56**. The first upper electric conductor **39e** is disposed on the first upper wall surface **56a**, the second upper wall surface **56b**, and the fourth upper wall surface **56d** except for the first corner portion **31a** and the second corner portion **31b**. The third upper electric conductor **39f** is disposed on the second upper wall surface **56b**, the third upper wall surface **56c**, and the fourth upper wall surface **56d** except for the third corner portion **31c** and the fourth corner portion **31d**. The electric conductor **34m** is not disposed on the corner portion **31**.

[0170] The first upper electric conductor **39e** may be disposed in a region of 50% or more of the area of the first upper wall surface **56a** on the first upper wall surface **56a**. The third upper electric conductor **39f** may be disposed in a region of 50% or more of the area of the third upper wall surface **56c** on the third upper wall surface **56c**. That is, the electric conductor **34m** may be disposed on the upper wall surface **56** such that the ratio of the area of the electric conductor **34m** to the area of the upper wall surface **56** is 50% or more. On the upper wall surface **56**, a configuration in which the ratio of the area of the electric conductor **34m** to the area of the upper wall surface **56** is 50% or more enhances the heat dissipation through the electric conductor **34m**.

Fifth Embodiment

[0171] Next, a configuration of a light-emitting device **D3** according to a fifth embodiment will be described. FIG. **15A** is a plan view of a light-emitting device according to the fifth embodiment, and FIG. **15B** is a side view of the light-emitting device according to the fifth embodiment. FIG. **15C** is a front view of the light-emitting device according to the fifth embodiment, and FIG. **15D** is a bottom view of the light-emitting device according to the fifth embodiment. The light-emitting device **D3** according to the fifth embodiment has the same configuration as the light-emitting device **D1** according to the first embodiment except for an electric conductor **34n**.

[0172] As illustrated in FIGS. **15A** to **15D**, a package **30n** according to the fifth embodiment includes the electric conductor **34n**, and the electric conductor **34n** is disposed on the placement surface **44**, the inner wall surface **52**, the upper wall surface **56**, and the outer wall surface **54**. In the present embodiment, unlike the first embodiment, the electric conductor **34n** is disposed on the

placement surface **44**, the inner wall surface **52**, the upper wall surface **56**, and the outer wall surface **54**, but is not disposed on the outer side surface **48**.

[0173] The electric conductor **34n** includes, for example, a first upper electric conductor **39g** and a third upper electric conductor **39h** on the upper wall surface **56**. The first upper electric conductor **39g** is disposed on the first upper wall surface **56a**, the second upper wall surface **56b**, and the fourth upper wall surface **56d** except for the first corner portion **31a** and the second corner portion **31b**. The third upper electric conductor **39h** is disposed on the second upper wall surface **56b**, the third upper wall surface **56c**, and the fourth upper wall surface **56d** except for the third corner portion **31c** and the fourth corner portion **31d**. The electric conductor **34n** is not disposed on the corner portion **31**.

[0174] The first upper electric conductor **39g** may be disposed in a region of 50% or more of the area of the first upper wall surface **56a** on the first upper wall surface **56a**. The third upper electric conductor **39h** may be disposed in a region of 50% or more of the area of the third upper wall surface **56c** on the third upper wall surface **56c**. That is, the electric conductor **34n** may be disposed on the upper wall surface **56** such that the ratio of the area of the electric conductor **34n** to the area of the upper wall surface **56** is 50% or more. On the upper wall surface **56**, a configuration in which the ratio of the area of the electric conductor **34n** to the area of the upper wall surface **56** is 50% or more enhances the heat dissipation through the electric conductor **34n**.

[0175] The package **30** includes a first outer electric conductor **35g** disposed on the first outer wall surface **54a**. The package **30** includes a third outer electric conductor **35h** on the third outer wall surface **54c**. The first outer electric conductor **35g** is electrically connected to the first upper electric conductor **39g**. The third outer electric conductor **35h** is electrically connected to the third upper electric conductor **39h**. The first outer electric conductor **35g** is not disposed on the first ridge portion **33a** and the second ridge portion **33b**. The third outer electric conductor **35h** is not disposed on the third ridge portion **33c** and the fourth ridge portion **33d**. The electric conductor **34n** is not disposed on the ridge portion **33**.

[0176] The first outer electric conductor **35g** may be disposed in a region of 50% or more of the area of the first outer wall surface **54a** on the first outer wall surface **54a**. The third outer electric conductor **35h** may be disposed in a region of 50% or more of the area of the third outer wall surface **54c** on the third outer wall surface **54c**. That is, the electric conductor **34n** may be disposed on the outer wall surface **54** such that the ratio of the area of the electric conductor **34n** to the area of the outer wall surface **54** is 50% or more. A configuration in which the ratio of the area of the electric conductor **34n** to the area of the outer wall surface **54** is 50% or more enhances the heat dissipation through the electric conductor **34n** on the outer wall surface **54**.

[0177] Although the embodiments of the present invention have been described above, the present invention is not necessarily limited to the above-described embodiments, and various modifications can be made without departing from the gist thereof.

[0178] This specification discloses the following supplementary notes.

Supplementary Note 1

[0179] A light-emitting device including: [0180] a light source; [0181] a window mounting the light source; and [0182] a package defining a space with the window, the light source being disposed in the space, wherein [0183] the window includes [0184] a window base including a light exit surface, a lower surface, opposing the light exit surface, and a side surface coupling the light exit surface and the lower surface, and [0185] an electrically conductive body disposed on the lower surface of the window base, [0186] the package includes [0187] a base portion formed with a recess open toward the lower surface, the base portion including a placement surface disposed along an edge of the recess and opposing the lower surface, a bottom surface opposing the placement surface, and an outer side surface coupled to the bottom surface, [0188] a wall portion including an inner wall surface coupled to the placement surface and opposing the side surface, an outer wall surface opposing the inner wall surface and coupled to the outer side surface, and an

upper wall surface coupling the inner wall surface and the outer wall surface, the wall portion disposed along the window base when viewed from a direction orthogonal to the light exit surface, [0189] a reflection portion disposed on a surface of the recess, being configured to reflect light emitted from the light source to the window, and [0190] an electric conductor disposed on the placement surface, the inner wall surface, and the upper wall surface, [0191] the window base is configured to transmit the light reflected on the reflection portion, [0192] the electrically conductive body includes a plurality of first pads opposing the placement surface, and a plurality of connectors electrically connecting the light source and the plurality of first pads, and [0193] the electric conductor includes a plurality of second pads disposed on the placement surface to oppose corresponding first pads of the plurality of first pads and electrically connected to the corresponding first pads.

Supplementary Note 2

[0194] The light-emitting device according to supplementary note 1, wherein the electric conductor is further disposed on the bottom surface.

Supplementary Note 3

[0195] The light-emitting device according to supplementary note 1 or 2, wherein height from the placement surface to the upper wall surface is larger than height from the placement surface to the light exit surface.

Supplementary Note 4

[0196] The light-emitting device according to any one of supplementary notes 1 to 3, wherein [0197] the package has a polygonal shape when viewed from the direction orthogonal to the light exit surface, [0198] the number of the outer side surfaces and the outer wall surfaces is plural, respectively, and [0199] the electric conductor is not disposed on a corner portion defined by the upper wall surface and the outer wall surfaces adjacent to each other, on a ridge portion defined by the outer wall surfaces adjacent to each other, and on a ridge portion defined by the outer side surfaces adjacent to each other.

Supplementary Note 5

[0200] The light-emitting device according to any one of supplementary notes 1 to 4, wherein the electric conductor is disposed on the upper wall surface such that a ratio of an area of the electric conductor to an area of the upper wall surface is 50% or more.

Supplementary Note 6

[0201] The light-emitting device according to any one of supplementary notes 1 to 5, wherein the window includes a dummy pad disposed on the lower surface and mounting the light source.

Supplementary Note 7

[0202] The light-emitting device according to any one of supplementary notes 1 to 6, wherein each of the connectors includes a third pad mounting the light source is mounted, and an electrically conductive line electrically connecting the first pad and the third pad.

Supplementary Note 8

[0203] The light-emitting device according to any one of supplementary notes 1 to 6, wherein [0204] one connector of the plurality of connectors includes a third pad mounting the light source is mounted, and an electrically conductive line electrically connecting the first pad and the third pad, and [0205] another connector of the plurality of connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the light source and the fourth pad.

Supplementary Note 9

[0206] The light-emitting device according to any one of supplementary notes 1 to 6, wherein each of the connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the light source and the fourth pad.

Supplementary Note 10

[0207] The light-emitting device according to any one of supplementary notes 1 to 9, wherein the window base is a silicon substrate.

Supplementary Note 11

[0208] The light-emitting device according to supplementary note 10, wherein [0209] the window includes an antireflection film disposed on at least one surface of the light exit surface and the lower surface.

[0210] In the present embodiment of supplementary note 1, the electric conductor is disposed on the placement surface, the inner wall surface, and the upper wall surface, but is not disposed on the outer wall surface and the outer side surface.

[0211] This specification also discloses the following supplementary notes.

Supplementary Note 12

[0212] A light-emitting device including: [0213] a light source; [0214] a window mounting the light source; and [0215] a package defining a space with the window, the light source being disposed in the space, wherein [0216] the window includes [0217] a window base including a light exit surface, a lower surface opposing the light exit surface, and a side surface coupling the light exit surface and the lower surface, and [0218] an electrically conductive body disposed on the lower surface of the window base, [0219] the package includes [0220] a base portion formed with a recess open toward the lower surface, the base portion including a placement surface disposed along an edge of the recess and opposing the lower surface, a bottom surface opposing the placement surface, and an outer side surface coupled to the bottom surface, [0221] a wall portion including an inner wall surface coupled to the placement surface and opposing the side surface, an outer wall surface opposing the inner wall surface and coupled to the outer side surface, and an upper wall surface coupling the inner wall surface and the outer wall surface, the wall portion disposed along the window base when viewed from a direction orthogonal to the light exit surface, [0222] a reflection portion disposed on a surface of the recess, being configured to reflect light emitted from the light source to the window, and [0223] an electric conductor disposed on the placement surface, the inner wall surface, the upper wall surface, and the outer wall surface, [0224] the window base is configured to transmit the light reflected on the reflection portion, [0225] the electrically conductive body includes a plurality of first pads opposing the placement surface, and a plurality of connectors electrically connecting the light source and the plurality of first pads, and [0226] the electric conductor includes a plurality of second pads disposed on the placement surface to oppose corresponding first pads of the plurality of first pads and electrically connected to the corresponding first pads.

Supplementary Note 13

[0227] The light-emitting device according to supplementary note 12, wherein the electric conductor is further disposed on the bottom surface.

Supplementary Note 14

[0228] The light-emitting device according to supplementary note 12 or 13, wherein height from the placement surface to the upper wall surface is larger than height from the placement surface to the light exit surface.

Supplementary Note 15

[0229] The light-emitting device according to any one of supplementary notes 12 to 14, wherein [0230] the package has a polygonal shape when viewed from the direction orthogonal to the light exit surface, [0231] the number of the outer side surfaces and the outer wall surfaces is plural, respectively, and [0232] the electric conductor is not disposed on a corner portion defined by the upper wall surface and the outer wall surfaces adjacent to each other, on a ridge portion defined by the outer wall surfaces adjacent to each other, and on a ridge portion defined by the outer side surfaces adjacent to each other.

Supplementary Note 16

[0233] The light-emitting device according to any one of supplementary notes 12 to 15, wherein the electric conductor is disposed on the upper wall surface such that a ratio of an area of the electric conductor to an area of the upper wall surface is 50% or more.

Supplementary Note 17

[0234] The light-emitting device according to any one of supplementary notes 12 to 16, wherein the electric conductor is disposed on the outer wall surface such that a ratio of an area of the electric conductor to an area of the outer wall surface is 50% or more.

Supplementary Note 18

[0235] The light-emitting device according to any one of supplementary notes 12 to 17, wherein the window includes a dummy pad disposed on the lower surface and mounting the light source.

Supplementary Note 19

[0236] The light-emitting device according to any one of supplementary notes 12 to 18, wherein each of the connectors includes a third pad mounting the light source is mounted, and an electrically conductive line electrically connecting the first pad and the third pad.

Supplementary Note 20

[0237] The light-emitting device according to any one of supplementary notes 12 to 18, wherein [0238] one connector of the plurality of connectors includes a third pad mounting the light source is mounted, and an electrically conductive line electrically connecting the first pad and the third pad, and [0239] another connector of the plurality of connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the light source and the fourth pad.

Supplementary Note 21

[0240] The light-emitting device according to any one of supplementary notes 12 to 18, wherein each of the connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the light source and the fourth pad.

Supplementary Note 22

[0241] The light-emitting device according to any one of supplementary notes 12 to 21, wherein the window base is a silicon substrate.

Supplementary Note 23

[0242] The light-emitting device according to supplementary note 22, wherein [0243] the window includes an antireflection film disposed on at least one surface of the light exit surface and the lower surface.

[0244] In the embodiment of supplementary note 12, the electric conductor is disposed on the placement surface, the inner wall surface, the upper wall surface, and the outer wall surface, but is not disposed on the outer side surface.

[0245] This specification also discloses the following supplementary notes.

Supplementary Note 24

[0246] A light detection device comprising: [0247] a photodetector; [0248] a window mounting the photodetector; and [0249] a package defining a space with the window, the photodetector being disposed in the space, wherein [0250] the window includes [0251] a window base including a light incident surface, a lower surface opposing the light incident surface, and a side surface coupling the light incident surface and the lower surface, and [0252] an electrically conductive body disposed on the lower surface of the window base, [0253] the package includes [0254] a base portion formed with a recess open toward the lower surface, the base portion including a placement surface disposed along an edge of the recess and opposing the lower surface, a bottom surface opposing the placement surface, and an outer side surface coupled to the bottom surface, [0255] a wall portion including an inner wall surface coupled to the placement surface and opposing the side surface, an outer wall surface opposing the inner wall surface and coupled to the outer side surface, and an upper wall surface coupling the inner wall surface and the outer wall surface, the wall portion disposed along the window base when viewed from a direction orthogonal to the light incident surface, [0256] a reflection portion disposed on a surface of the recess, being configured to reflect light incident from the window to the photodetector, and [0257] an electric conductor disposed on the placement surface, the inner wall surface, the upper wall surface, the outer wall surface, and the outer side surface, [0258] the window base is configured to transmit light incident from an outside,

[0259] the electrically conductive body includes a plurality of first pads opposing the placement surface, and a plurality of connectors electrically connecting the photodetector and the plurality of first pads, and [0260] the electric conductor includes a plurality of second pads disposed on the placement surface to oppose corresponding first pads of the plurality of first pads and electrically connected to the corresponding first pads.

Supplementary Note 25

[0261] The light detection device according to supplementary note 24, wherein the electric conductor is further disposed on the bottom surface.

Supplementary Note 26

[0262] The light detection device according to supplementary note 24 or 25, wherein height from the placement surface to the upper wall surface is larger than height from the placement surface to the light incident surface.

Supplementary Note 27

[0263] The light detection device according to any one of supplementary notes 24 to 26, wherein [0264] the package has a polygonal shape when viewed from the direction orthogonal to the light incident surface, [0265] the number of the outer side surfaces and the outer wall surfaces is plural, respectively, and [0266] the electric conductor is not disposed on a corner portion defined by the upper wall surface and the outer wall surfaces adjacent to each other, on a ridge portion defined by the outer wall surfaces adjacent to each other, and on a ridge portion defined by the outer side surfaces adjacent to each other.

Supplementary Note 28

[0267] The light detection device according to any one of supplementary notes 24 to 27, wherein the electric conductor is disposed on the upper wall surface such that a ratio of an area of the electric conductor to an area of the upper wall surface is 50% or more.

Supplementary Note 29

[0268] The light detection device according to any one of supplementary notes 24 to 28, wherein the electric conductor is disposed on the outer wall surface and the outer side surface such that a ratio of an area of the electric conductor to a sum of an area of the outer wall surface and an area of the outer side surface is 50% or more.

Supplementary Note 30

[0269] The light detection device according to any one of supplementary notes 24 to 29, wherein the window includes a dummy pad disposed on the lower surface and mounting the photodetector.

Supplementary Note 31

[0270] The light detection device according to any one of supplementary notes 24 to 30, wherein each of the connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad.

Supplementary Note 32

[0271] The light detection device according to any one of supplementary notes 24 to 30, wherein [0272] one connector of the plurality of connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad, and [0273] another connector of the plurality of connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the photodetector and the fourth pad.

Supplementary Note 33

[0274] The light detection device according to any one of supplementary notes 24 to 30, wherein each of the connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the photodetector and the fourth pad.

Supplementary Note 34

[0275] The light detection device according to any one of supplementary notes 24 to 33, wherein the window base is a silicon substrate.

Supplementary Note 35

[0276] The light detection device according to supplementary note 34, wherein the window includes an antireflection film disposed on at least one surface of the light incident surface and the lower surface.

[0277] An embodiment of the supplementary note 24 is the light detection device including the photodetector, the window **20**, and the package **30**. The light detection device includes, for example, the same configuration as the light-emitting device **D1** except for the photodetector. The photodetector includes a light detection element. Examples of the light detection element include a photodiode element capable of sensing infrared light. Light incident from the outside is reflected on the reflection portion **32**, and the photodetector receives the light reflected from the reflection portion **32**. The photodetector may be connected to the electric conductor **34** having a high heat dissipation effect, and heat generated in the light detection device is effectively dissipated through the electric conductor **34**.

[0278] For example, in the light detection device including a photodiode, generally, the size of the electric conductor tends to be reduced from the viewpoint of reducing the generation of noise, for example. However, in the light detection device of this supplementary note, the electric conductor is disposed in a region from the placement surface to the upper wall surface to improve the heat dissipation through the electric conductor.

[0279] This specification also discloses the following supplementary notes.

Supplementary Note 36

[0280] A light detection device comprising: [0281] a photodetector; [0282] a window mounting the photodetector; and [0283] a package defining a space with the window, the photodetector being disposed in the space, wherein [0284] the window includes [0285] a window base including a light incident surface, a lower surface opposing the light incident surface, and a side surface coupling the light incident surface and the lower surface, and [0286] an electrically conductive body disposed on the lower surface of the window base, [0287] the package includes [0288] a base portion formed with a recess open toward the lower surface, the base portion including a placement surface disposed along an edge of the recess and opposing the lower surface, a bottom surface opposing the placement surface, and an outer side surface coupled to the bottom surface, [0289] a wall portion including an inner wall surface coupled to the placement surface and opposing the side surface, an outer wall surface opposing the inner wall surface and coupled to the outer side surface, and an upper wall surface coupling the inner wall surface and the outer wall surface, the wall portion disposed along the window base when viewed from a direction orthogonal to the light incident surface, [0290] a reflection portion disposed on a surface of the recess, being configured to reflect light incident from the window to the photodetector, and [0291] an electric conductor disposed on the placement surface, the inner wall surface, and the upper wall surface, [0292] the window base is configured to transmit light incident from an outside, [0293] the electrically conductive body includes a plurality of first pads opposing the placement surface, and a plurality of connectors electrically connecting the photodetector and the plurality of first pads, and [0294] the electric conductor includes a plurality of second pads disposed on the placement surface to oppose corresponding first pads of the plurality of first pads and electrically connected to the corresponding first pads.

Supplementary Note 37

[0295] The light detection device according to supplementary note 36, wherein the electric conductor is further disposed on the bottom surface.

Supplementary Note 38

[0296] The light detection device according to supplementary note 36 or 37, wherein height from the placement surface to the upper wall surface is larger than height from the placement surface to the light incident surface.

Supplementary Note 39

[0297] The light detection device according to any one of supplementary notes 36 to 38, wherein

[0298] the package has a polygonal shape when viewed from the direction orthogonal to the light incident surface, [0299] the number of the outer side surfaces and the outer wall surfaces is plural, respectively, and [0300] the electric conductor is not disposed on a corner portion defined by the upper wall surface and the outer wall surfaces adjacent to each other, on a ridge portion defined by the outer wall surfaces adjacent to each other, and on a ridge portion defined by the outer side surfaces adjacent to each other.

Supplementary Note 40

[0301] The light detection device according to any one of supplementary notes 36 to 39, wherein the electric conductor is disposed on the upper wall surface such that a ratio of an area of the electric conductor to an area of the upper wall surface is 50% or more.

Supplementary Note 41

[0302] The light detection device according to any one of supplementary notes 36 to 40, wherein the window includes a dummy pad disposed on the lower surface and mounting the photodetector.

Supplementary Note 42

[0303] The light detection device according to any one of supplementary notes 36 to 41, wherein each of the connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad.

Supplementary Note 43

[0304] The light detection device according to any one of supplementary notes 36 to 41, wherein [0305] one connector of the plurality of connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad, and [0306] another connector of the plurality of connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the photodetector and the fourth pad.

Supplementary Note 44

[0307] The light detection device according to any one of supplementary notes 36 to 41, wherein each of the connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the photodetector and the fourth pad.

Supplementary Note 45

[0308] The light detection device according to any one of supplementary notes 36 to 44, wherein the window base is a silicon substrate.

Supplementary Note 46

[0309] The light detection device according to supplementary note 45, wherein [0310] the window includes an antireflection film disposed on at least one surface of the light incident surface and the lower surface.

[0311] In the embodiment of supplementary note 36, the electric conductor is disposed on the placement surface, the inner wall surface, and the upper wall surface, but is not disposed on the outer wall surface and the outer side surface.

[0312] This specification also discloses the following supplementary notes.

Supplementary Note 47

[0313] A light detection device comprising: [0314] a photodetector; [0315] a window mounting the photodetector; and [0316] a package defining a space with the window, the photodetector being disposed in the space, wherein [0317] the window includes [0318] a window base including a light incident surface, a lower surface opposing the light incident surface, and a side surface coupling the light incident surface and the lower surface, and [0319] an electrically conductive body disposed on the lower surface of the window base, [0320] the package includes [0321] a base portion formed with a recess open toward the lower surface, the base portion including a placement surface disposed along an edge of the recess and opposing the lower surface, a bottom surface opposing the placement surface, and an outer side surface coupled to the bottom surface, [0322] a wall portion including an inner wall surface coupled to the placement surface and opposing the side surface, an outer wall surface opposing the inner wall surface and coupled to the outer side surface, and an

upper wall surface coupling the inner wall surface and the outer wall surface, the wall portion disposed along the window base when viewed from a direction orthogonal to the light incident surface, [0323] a reflection portion disposed on a surface of the recess, being configured to reflect light incident from the window to the photodetector, and [0324] an electric conductor disposed on the placement surface, the inner wall surface, the upper wall surface, and the outer wall surface, [0325] the window base is configured to transmit light incident from an outside, [0326] the electrically conductive body includes a plurality of first pads opposing the placement surface, and a plurality of connectors electrically connecting the photodetector and the plurality of first pads, and [0327] the electric conductor includes a plurality of second pads disposed on the placement surface to oppose corresponding first pads of the plurality of first pads and electrically connected to the corresponding first pads.

Supplementary Note 48

[0328] The light detection device according to supplementary note 47, wherein the electric conductor is further disposed on the bottom surface.

Supplementary Note 49

[0329] The light detection device according to supplementary note 47 or 48, wherein height from the placement surface to the upper wall surface is larger than height from the placement surface to the light incident surface.

Supplementary Note 50

[0330] The light detection device according to any one of supplementary notes 47 to 49, wherein [0331] the package has a polygonal shape when viewed from the direction orthogonal to the light incident surface, [0332] the number of the outer side surfaces and the outer wall surfaces is plural, respectively, and [0333] the electric conductor is not disposed on a corner portion defined by the upper wall surface and the outer wall surfaces adjacent to each other, on a ridge portion defined by the outer wall surfaces adjacent to each other, and on a ridge portion defined by the outer side surfaces adjacent to each other.

Supplementary Note 51

[0334] The light detection device according to any one of supplementary notes 47 to 50, wherein the electric conductor is disposed on the upper wall surface such that a ratio of an area of the electric conductor to an area of the upper wall surface is 50% or more.

Supplementary Note 52

[0335] The light detection device according to any one of supplementary notes 47 to 51, wherein the electric conductor is disposed on the outer wall surface such that a ratio of an area of the electric conductor to an area of the outer wall surface is 50% or more.

Supplementary Note 53

[0336] The light detection device according to any one of supplementary notes 47 to 52, wherein the window includes a dummy pad disposed on the lower surface and mounting the photodetector.

Supplementary Note 54

[0337] The light detection device according to any one of supplementary notes 47 to 53, wherein each of the connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad.

Supplementary Note 55

[0338] The light detection device according to any one of supplementary notes 47 to 53, wherein [0339] one connector of the plurality of connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad, and [0340] another connector of the plurality of connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the photodetector and the fourth pad.

Supplementary Note 56

[0341] The light detection device according to any one of supplementary notes 47 to 53, wherein each of the connectors includes a fourth pad electrically connected to the first pad, and a wire

electrically connecting the photodetector and the fourth pad.

Supplementary Note 57

[0342] The light detection device according to any one of supplementary notes 47 to 56, wherein the window base is a silicon substrate.

Supplementary Note 58

[0343] The light detection device according to supplementary note 57, wherein the window includes an antireflection film disposed on at least one surface of the light incident surface and the lower surface.

[0344] In the embodiment of supplementary note 47, the electric conductor is disposed on the placement surface, the inner wall surface, the upper wall surface, and the outer wall surface, but is not disposed on the outer side surface.

REFERENCE SIGNS LIST

[0345] **10** LIGHT SOURCE [0346] **20** WINDOW [0347] **22** LIGHT EXIT SURFACE [0348] **23** LOWER SURFACE [0349] **24** SIDE SURFACE [0350] **25** FIRST PAD [0351] **26** THIRD PAD [0352] **27** ELECTRICALLY CONDUCTIVE LINE [0353] **28** DUMMY PAD [0354] **30** PACKAGE [0355] **31** CORNER PORTION [0356] **32** REFLECTION PORTION [0357] **33** RIDGE PORTION [0358] **34** ELECTRIC CONDUCTOR [0359] **36** SECOND PAD [0360] **40** BASE PORTION [0361] **42** RECESS [0362] **44** PLACEMENT SURFACE [0363] **46** BOTTOM SURFACE [0364] **47** EDGE [0365] **48** OUTER SIDE SURFACE [0366] **50** WALL PORTION [0367] **52** INNER WALL SURFACE [0368] **54** OUTER WALL SURFACE [0369] **56** UPPER WALL SURFACE [0370] **65p** FOURTH PAD [0371] **AG1** BLOCK [0372] **AR** ANTIREFLECTION FILM [0373] **Ax1** DIRECTION [0374] **CT1** to **CT4** CUTTING PLANNED LINE [0375] **D1, D2, D3** LIGHT-EMITTING DEVICE [0376] **SC1** SPACE [0377] **CN1** CONNECTOR [0378] **WD1** ELECTRICALLY CONDUCTIVE BODY

Claims

1. A light detection device comprising: a photodetector; a window mounting the photodetector; and a package defining a space with the window, the photodetector being disposed in the space, wherein the window includes a window base including a light incident surface, a lower surface opposing the light incident surface, and a side surface coupling the light incident surface and the lower surface, and an electrically conductive body disposed on the lower surface of the window base, the package includes a base portion formed with a recess open toward the lower surface, the base portion including a placement surface disposed along an edge of the recess and opposing the lower surface, a bottom surface opposing the placement surface, and an outer side surface coupled to the bottom surface, a wall portion including an inner wall surface coupled to the placement surface and opposing the side surface, an outer wall surface opposing the inner wall surface and coupled to the outer side surface, and an upper wall surface coupling the inner wall surface and the outer wall surface, the wall portion disposed along the window base when viewed from a direction orthogonal to the light incident surface, a reflection portion disposed on a surface of the recess, being configured to reflect light incident from the window to the photodetector, and an electric conductor disposed on the placement surface, the inner wall surface, the upper wall surface, the outer wall surface, and the outer side surface, the window base is configured to transmit light incident from an outside, the electrically conductive body includes a plurality of first pads opposing the placement surface, and a plurality of connectors electrically connecting the photodetector and the plurality of first pads, and the electric conductor includes a plurality of second pads disposed on the placement surface to oppose corresponding first pads of the plurality of first pads and electrically connected to the corresponding first pads.

2. The light detection device according to claim 1, wherein the electric conductor is further disposed on the bottom surface.

3. The light detection device according to claim 1, wherein a height from the placement surface to the upper wall surface is larger than a height from the placement surface to the light incident surface.
 4. The light detection device according to claim 1, wherein the package has a polygonal shape when viewed from the direction orthogonal to the light incident surface, the number of the outer side surfaces and the outer wall surfaces is plural, respectively, and the electric conductor is not disposed on a corner portion defined by the upper wall surface and the outer wall surfaces adjacent to each other, on a ridge portion defined by the outer wall surfaces adjacent to each other, and on a ridge portion defined by the outer side surfaces adjacent to each other.
 5. The light detection device according to claim 1, wherein the electric conductor is disposed on the upper wall surface such that a ratio of an area of the electric conductor to an area of the upper wall surface is 50% or more.
 6. The light detection device according to claim 1, wherein the electric conductor is disposed on the outer wall surface and the outer side surface such that a ratio of an area of the electric conductor to a sum of an area of the outer wall surface and an area of the outer side surface is 50% or more.
 7. The light detection device according to claim 1, wherein the window includes a dummy pad disposed on the lower surface and mounting the photodetector.
 8. The light detection device according to claim 1, wherein each of the connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad.
 9. The light detection device according to claim 1, wherein one connector of the plurality of connectors includes a third pad mounting the photodetector, and an electrically conductive line electrically connecting the first pad and the third pad, and another connector of the plurality of connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the photodetector and the fourth pad.
 10. The light detection device according to claim 1, wherein each of the connectors includes a fourth pad electrically connected to the first pad, and a wire electrically connecting the photodetector and the fourth pad.
 11. The light detection device according to claim 1, wherein the window base is a silicon substrate.
 12. The light detection device according to claim 11, wherein the window includes an antireflection film disposed on at least one surface of the light incident surface and the lower surface.
 13. A method for making the light detection device according to claim 1, the method comprising: preparing a plurality of the windows mounting the photodetector; preparing a block including a plurality of the packages coupled each other in an array; mounting the window on each of the packages of the block to electrically connect the first pad and the second pad corresponding to each other; and separating the block to obtain the plurality of packages mounting the corresponding window.
 14. The method for making the light detection device according to claim 13, wherein a height from the placement surface to the upper wall surface is larger than a height from the placement surface to the light incident surface in a state where the window is mounted to correspond to each package of the block, and when the block is separated, the block is diced along a cutting planned line set between the packages adjacent to each other after the upper wall surface is attached to a dicing tape.
-