

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250268395

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Scott; Zachary Wayne

Child Carrying Backpack Device

Abstract

A child carrying backpack device for includes a frame that includes a pair of first legs. A panel is attached to the frame such that the panel extends between the pair of first legs. A shoulder harness is attached to the panel for wearing over shoulders of a user in the convention of a backpack. A pair of second legs is each pivotally attached to a respective one of the first legs which can be positioned in a deployed position having each of the second legs angling away from the respective first leg for standing upon a support surface. A child chair is attached to the panel which can have a child seated in the child chair thereby facilitating the user to carry the child on their back when the shoulder harness is worn over the user's shoulders.

Inventors: Scott; Zachary Wayne (Millbrook, AL)

Applicant: Scott; Zachary Wayne (Millbrook, AL)

Family ID: 1000007713920

Appl. No.: 18/584662

Filed: February 22, 2024

Publication Classification

Int. Cl.: A47D13/02 (20060101); A47D11/00 (20060101)

U.S. Cl.:

CPC A47D13/027 (20220801); A47D11/00 (20130101); A47D13/025 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] Not Applicable

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

[0003] Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

[0004] Not Applicable

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT INVENTOR

[0005] Not Applicable

BACKGROUND OF THE INVENTION

(1) Field of the Invention

[0006] The disclosure relates to child carrying devices and more particularly pertains to a new child carrying device for carrying a child on a user's back as well as facilitating the child to be placed in a stationary seated position. The device includes a frame and a child seat attached to the frame in which a child can be seated. The device includes shoulder straps for wearing over a user's shoulders to carry the child in the convention of a backpack. The frame includes first legs and second legs pivotally attached to the first legs which can be positioned in a deployed position to facilitate the frame to be positioned on a support surface in the convention of a chair.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

[0007] The prior art relates to child carrying devices including a variety of chairs that have a collapsible frame and shoulder straps for carrying a child on a user's back, a plurality of backpacks that has a seating element for accommodating a child. In no instance does the prior art disclose a child chair attached to rigid frame and a shoulder harness attached to the rigid frame for wearing on a user's shoulders.

BRIEF SUMMARY OF THE INVENTION

[0008] An embodiment of the disclosure meets the needs presented above by generally comprising a frame that includes a pair of first legs. A panel is attached to the frame such that the panel extends between the pair of first legs. A shoulder harness is attached to the panel for wearing over shoulders of a user in the convention of a backpack. A pair of second legs is each pivotally attached to a respective one of the first legs which can be positioned in a deployed position having each of the second legs angling away from the respective first leg for standing upon a support surface. A child chair is attached to the panel which can have a child seated in the child chair thereby facilitating the user to carry the child on their back when the shoulder harness is worn over the user's shoulders.

[0009] There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

[0010] The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

[0011] The disclosure will be better understood and objects other than those set forth above will

become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

[0012] FIG. **1** is a back view of a child carrying backpack device according to an embodiment of the disclosure.

[0013] FIG. **2** is a front view of an embodiment of the disclosure.

[0014] FIG. **3** is a right side view of an embodiment of the disclosure.

[0015] FIG. **4** is a left side view of an embodiment of the disclosure showing second legs in a deployed position.

[0016] FIG. **5** is a top view of an embodiment of the disclosure.

[0017] FIG. **6** is a left side view of an embodiment of the disclosure showing second legs in deployed position and being extended for reclining a child chair.

[0018] FIG. **7** is a perspective in-use view of an embodiment of the disclosure.

[0019] FIG. **8** is a perspective view of an embodiment of the disclosure showing an accessory hanger.

[0020] FIG. **9** is perspective in-use view of an embodiment of the disclosure showing a panel and a child chair positioned on a seat of a vehicle.

[0021] FIG. **10** is a top view of a tray of an embodiment of the disclosure.

DETAILED DESCRIPTION OF THE INVENTION

[0022] With reference now to the drawings, and in particular to FIGS. **1** through **10** thereof, a new child carrying device embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral **10** will be described.

[0023] As best illustrated in FIGS. **1** through **10**, the child carrying backpack device **10** generally comprises a frame **12** that is curved into a U-shape defining a pair of first legs **14** of the frame **12** and a central portion **16** of the frame **12** extending between the pair of first legs **14** of the frame **12**. Each of the first legs **14** has a distal end **18** with respect to the central portion **16** and the central portion **16** curves upwardly between each of the pair of first legs **14**. A panel **20** is attached to the frame **12** such that the panel **20** extends between the pair of first legs **14**. The panel **20** has a front side **22**, a back side **24** and a perimeter edge **26** extending between the front side **22** and the back side **24**. The perimeter edge **26** is attached to each of the first legs **14** and the central portion **16** of the frame **12** and the perimeter edge **26** has a bottom side **28** that is spaced upwardly from the distal end **18** of each of the first legs **14**. The panel **20** has a hole **30** extending through the front side **22** and the back side **24** thereby facilitating the panel **20** to be gripped for carrying the frame **12** and the panel **20**. Additionally, the hole **30** is centrally positioned between the pair of first legs **14** and the hole **30** is spaced from the central portion **16** of the frame **12**.

[0024] A shoulder harness **32** is attached to the panel **20** such that the shoulder harness **32** can be worn over shoulders **34** of a user **36** having the panel **20** resting against the user's back **38** thereby facilitating the frame **12** to be transported in the convention of a backpack. Conversely, the shoulder harness **32** can be worn on the user's shoulders **34** such that the panel **20** rests against the user's chest **39**. The shoulder harness **32** comprises a pair of shoulder straps **40** that each has a first end **42** and a second end **44** which are each attached to the front side **22** of the panel **20**. The first end **42** of each of the shoulder straps **40** is positioned proximate the central portion **16** of the frame **12** and the second end **44** of each of the shoulder straps **40** is positioned proximate the bottom side **28** of the perimeter edge **26** of the panel **20**. Each of the shoulder straps **40** is positioned adjacent to a respective one of the pair of first legs **14** of the frame **12**.

[0025] Each of the pair of shoulder straps **40** comprises an upper strap **46**, a lower strap **48** and a middle strap **50** that is removably attachable between the upper strap **46** and the lower strap **48**. Each of the pair of shoulder straps **40** includes a first buckle **52** that is attached between the upper strap **46** and the middle strap **50** for releasably attaching the upper strap **46** to the middle strap **50**. Each of the pair of shoulder straps **40** includes a second buckle **54** which is attached between the lower strap **48** and the middle strap **50** for releasably attaching the lower strap **48** to the middle

strap 50. Each of the pair of shoulder straps 40 includes a cushion 56 that is disposed on the middle strap 50. The cushion 56 associated with each of the pair of shoulder straps 40 is comprised of a resiliently compressible material to enhance comfort for the user 36. A smart phone pouch 58 is provided and a respective one of the shoulder straps 40 extends through the smart phone pouch 58 thereby facilitating a personal electronic device 55, such as a smart phone for example, to be secured to the respective shoulder strap 40.

[0026] The shoulder harness 32 includes a chest strap 60 which has a pair of ends 62 that is each attached to a respective one of the pair of first legs 14. The chest strap 60 extends across the user's chest 63 when the pair of shoulder straps 40 is worn over the user's shoulders 34. The chest strap 60 comprises a first half 64 and a second half 65 and the chest strap 60 includes a chest buckle 66 that is attached between the first half 64 and the second half 65 for releasably attaching the first half 64 to the second half 65. A pair of pivots 67 is provided and each of the pivots 67 comprises a first tube 69 that is positioned around a respective one of the first legs 14 of the frame 12. Each of the pivots 67 includes a second tube 70 angling away from the first tube 69. Furthermore, each of the pair of pivots 67 is positioned closer to the central portion 16 of the frame 12 than the distal end 18 of the respective first leg 14.

[0027] A pair of second legs 71 is provided and each of the second legs 71 is pivotally attached to a respective one of the first legs 14. Each of the pair of second legs 71 is positionable in a stored position having the second legs 71 lying against the respective first leg 14. Each of the pair of second legs 71 is positionable in a deployed position having each of the second legs 71 angling away from the respective first leg 14. In this way the pair of first legs 14 and the pair of second legs 71 can be stood upon a support surface 72. Each of the pair of second legs 71 has an upper end 73 which extends into the second tube 70 of a respective one of the pair of pivots 67. Each of the pair of pivots 67 has a pivot point 74 that is disposed on the second tube 70 which pivotally engages a respective one of the second legs 71.

[0028] Each of the pair of second legs 71 comprises an upper portion 76 which slidably receives a lower portion 77 such that each of the pair of second legs 71 has a telescopically adjustable length. The upper portion 76 has a plurality of holes 78 which are spaced apart from each other and are distributed along a full length of the upper portion 76. Each of the pair of second legs 71 includes a lock 79 that is movably disposed on the lower portion 77. The lock 79 is biased outwardly from the lower portion 77 thereby facilitating the lock 79 to extend outwardly through a respective one of the plurality of holes 78 in the upper portion 76 for adjusting a length of the second legs 71. Thus, each of the second legs 71 can be extended to a maximum length to facilitate the panel 20 to be reclined approximately 40.0 degrees from vertical to position the panel 20 in a reclined orientation. The lock 79 may comprise a spring loaded ball that can be pushed inwardly to facilitate the spring loaded ball to disengage the respective hole 30 to adjust the lower portion 77.

[0029] A pair of first feet 80 is attached to the distal end 18 of a respective one of the first legs 14 and each of the first feet 80 has a first well 81 extending upwardly into a bottom end 82 of the first feet 80. A pair of second feet 83 is provided and each of the second feet 83 is attached to a bottom end 84 of the lower portion 77 of a respective one of the pair of second legs 71. Each of the second feet 83 has a second well 85 extending upwardly into a bottom end 85 of the second feet 83. Additionally, each of the first feet 80 and the second feet 83 may be comprised of a resiliently compressible material, such as rubber for example, to inhibit the first feet 80 and the second feet 83 from sliding on the support surface 72 when the first feet 80 and the second feet 83 abut the support surface 72.

[0030] A child chair 86 is attached to the panel 20 to have a child 87 seated in the child chair 86 thereby facilitating the user 36 to carry the child 87 on their back 89 when the shoulder harness 32 is worn over the user's shoulders 34. The child chair 86 comprises a seat 90 that is coupled to and curves away from the back side 24 of the panel 20. The seat 90 has a lower wall 91 that is perpendicularly oriented with the back side 24 of the panel 20 to facilitate the child 87 to sit on the

lower wall **91**. The seat **90** has a pair of leg holes **92** each extending through a distal wall **93** of the seat **90** with respect to the back side **24** of the panel **20** to have a respective one of the child's legs **94** extended through a respective one of the leg holes **92**. The seat **90** is oriented on the panel **20** such that the lower wall **91** of the seat **90** is positioned adjacent to the bottom side **28** of the perimeter edge **26** of the panel **20**.

[0031] A back cushion **95** is attached to the back side **24** of the panel **20** to have the child **87** rest against the back cushion **95** when the child **87** is seated in the seat **90**. The back cushion **95** extends between the seat **90** and the hole **30** in the panel **20** and the back cushion **95** has a distal surface **96** with respect to the panel **20**. The back cushion **95** is comprised of a resiliently compressible material, including but not being limited to foam rubber, memory foam or silicone, for enhancing comfort for the child **87**. A head cushion **97** is recessed into the distal surface **96** of the back cushion **95** to have the child's head **99** positioned against the head cushion **97** when the child **87** is seated in the seat **90**. The head cushion **97** is comprised of a resiliently compressible material, including but not being limited to foam rubber, memory foam or silicone, to enhance comfort for the child **87**. Furthermore, the back cushion **95** and the head cushion **97** are a unitary structure to inhibit the head cushion **97** from being displaced on the back cushion **95**.

[0032] A pair of child straps **100** is each coupled to and curves away from the distal surface **96** of the back cushion **95** to extend over the child's torso **101** when the child **87** is seated in the seat **90** to inhibit the child **87** from falling out of the seat **90**. Additionally, the pair of child straps **100** is oriented to cross each other. A pair of couplers **102** is each coupled to a respective one of a first lateral surface **103** and a second lateral surface **104** of the back cushion **95**. Each of the couplers **102** has a pin **105** extending laterally away from the couplers **102** and each of the couplers **102** is aligned with the head cushion **97**. As is most clearly shown in FIG. 3, bracket **106** is provided that is removably attachable to the pair of couplers **102** and a head cover **107** is attached to the bracket **106** such that the head cover **107** extends over the child's head **99** to shade the child **87**. As is additionally shown in FIG. 3, an insect net **109** is provided that can be attached to an attachment point **108** disposed on the central portion **16** of the frame **12** to facilitate the insect net **109** to be draped over the child **87** to protect the child **87** from biting insects. Additionally, the attachment point **108** is positioned beneath the head cover **107**.

[0033] A bar **110** is provided that is curved between each of a primary end **111** and a secondary end **112** of the bar **110** such that the bar **110** has a U-shape. Each of the primary end **111** and the secondary end **112** are removably attachable to the back side **24** of the panel **20** such that the bar **110** curves around the child **87** when the child **87** is seated in the child seat **90**. A pair of cameras **114** may be attached to the bar **110** which each faces upwardly toward the child's head **108** when the bar **110** is attached to the back side **24** of the panel **20**. Additionally, each of the cameras **114** may have wireless communication capabilities which may employ Bluetooth communication protocols to facilitate imagery captured by the cameras **114** to be viewed on the personal electronic device **55**. In this way the user **36** can view the child **87** on their personal electronic device **55** while the user **36** is wearing the shoulder harness **32**. Each of the cameras **114** might include a data port to facilitate a wired connection to the personal electronic device **55**.

[0034] A foot tray **115** is attached to and extends away from the back side **24** of the panel **20**. The foot tray **115** is aligned with the bottom side **28** of the perimeter edge **26** of the panel **20** such that the foot tray **115** is positioned beneath the lower wall **91** of the seat **90**. The foot tray **115** has a distal end **116** with respect to the back side **24**, the foot tray **115** is substantially hollow and the distal end **116** of the foot tray **115** is open. A footrest **117** is slidably positioned in the foot tray **115** and the footrest **117** is slidable outwardly from the distal end **116** of the foot tray **115** to have the child's feet **118** positioned thereon when the child **87** is seated in the seat **90**. A plurality of rollers **119** is provided and each of the plurality of rollers **119** has a stem **120** extending upwardly from rollers **119**. The stem **120** associated with a respective one of the plurality of rollers **119** is insertable into the first well **81** in a respective one of the first feet **80** and the stem **120** associated

with a respective one of the plurality of rollers **119** is insertable into the second well **75** in a respective one of the second feet **83**. In this way the rollers **119** facilitate the child **87** to be rocked back and forth to soothe the child **87**.

[0035] As is most clearly shown in FIG. **8**, an accessory hanger **121** is provided that includes a member **122** which is curved between a first end **123** and a second end **124** of the member **122** such that the member **122** is U-shaped. The accessory hanger **121** includes a pair of cylinders **125** that are each attached to a respective one of the first end **123** and second end **124** of the member **122**. Each of the cylinders **125** has an outer surface **126** and an attaching face **127**; the outer surface **126** of each cylinder **125** is attached to the respective first end **123** and second end **124** of the member **122** having the attaching face **127** of each cylinder **125** being directed away from each other. Additionally, the attaching face **127** of each cylinder **125** has a well **128** that insertably receives the pin **105** associated with a respective one of the couplers **102** that are attached to the back cushion **95**. The accessory hanger **121** includes a plurality of toys **129** that are suspended from the member **122** for visually stimulating the child **87**.

[0036] The child chair **86** includes a curved member **130** that curves upwardly from the distal wall **93** of the seat **90** associated with the child chair **86** such that the curved member **130** extends to approximately chest height on the child **87**. In this way the curved member **130** inhibits the child **87** from tipping forwardly from the child chair **86** and potentially falling out of the child chair **86**. The curved member **130** lies on a plane that is oriented parallel to back side **24** of the panel **20** and the curved member **130** may be cushioned to enhance comfort for the child **87**. A pair of leg cushions **131** is each attached to a bounding edge **132** of a respective one of the leg holes **32** in the distal wall **93** of the seat **90** to enhance comfort for the child's legs **94**. A cover **133** is attached between the curved member **130** and an upper edge **134** of the distal wall **93** of the seat **90** and indicia **135** may be applied to the cover **133** which may comprise images of flowers or other ornamental images. Indicia **137** are applied to an outwardly facing surface **138** of the distal wall **93** of the seat **90** and the indicia **137** associated with the seat **90** may comprise an image of a heart **139** and a rose **140** growing from the heart **139**. Additionally, the indicia **137** associated with the seat may be centrally positioned between the pair of leg holes **92**.

[0037] As is most clearly shown in FIG. **10**, a tray **141** is provided which has a cup recess **142** and a snack recess **144** each extending downwardly into a top surface **145** of the tray **141** for holding a beverage cup **147** and snacks **148**. A pacifier holder **149** is attached to an outer edge **150** of the tray **149** for holding a pacifier **151** for the child **87**. The tray **141** can be removably attached to the child chair **86** such that the tray **141** is accessible to the child when the child is seated in the child chair **86**.

[0038] As is most clearly shown in FIG. **1**, the back cushion **95** includes a lower portion **155** and an upper portion **156**; the lower portion **155** may have a rounded shape and the upper portion may have a rectangular shape. The lower portion **155** has a pair of wings **157** that each extends forward from the lower portion **155** and which are each positioned on respective lateral sides of the lower portion **155** such that each of the pair of wings **157** laterally restrains the child **87** in the lower portion **155**. The head cushion **97** is centrally positioned on the upper portion **156** such that the upper portion **156** surrounds the child's head **99** thereby inhibiting the child's head **99** from rolling from side to side. Indicia **158** may be printed on each of the upper portion **156** and the lower portion **155** and the indicia **158** on the upper portion **156** and the lower portion **155** may comprise images of flowers or other ornamental images.

[0039] A pair of cameras **159** may be attached to the curved member **130** and each of the pair of cameras **159** on the curved member are oriented to face toward the child **87** when the child **87** is seated in the child chair **86**. Additionally, each of the cameras **159** on the curved member **130** may have wireless communication capabilities which may employ Bluetooth communication protocols to facilitate imagery captured by the cameras **159** on the curved member **130** to be viewed on the personal electronic device **55**. In this way the user **36** can view the child **87** on their personal

electronic device 55 while the user 36 is wearing the shoulder harness 32. Each of the cameras 159 on the curved member 156 might include a data port to facilitate a wired connection to the personal electronic device 55.

[0040] As is most clearly shown in FIGS. 3 and 8, a data port 160 is integrated into a lateral side of the foot tray 115 and the data port 160 may be in electrical communication with the cameras 114 on the bar 110 and the cameras 159 on the curved member 130 to facilitate imagery captured by the cameras 114 on the bar 110 and the cameras 159 on the curved member 130 to be downloaded into an external electronic device. The data port 160 may comprise a universal serial bus port or other type of common data port. As is most clearly shown in FIG. 10, a camera 161 may be integrated into the top surface 145 of the tray 141. The camera 161 on the top surface 145 of the tray 141 may have wireless communication capabilities which may employ Bluetooth communication protocols to facilitate imagery captured by the camera 161 on the tray 141 be viewed on the personal electronic device 55. In this way the user 36 can view the child 87 on their personal electronic device 55 while the user 36 is wearing the shoulder harness 32. Furthermore, the camera 161 on the tray 141 might include a data port to facilitate a wired connection to the personal electronic device 55.

[0041] In use, the second legs 71 are positioned in the stored position and the shoulder harness 32 is worn over the user's shoulders 34 such that the panel 20 rests against the user's back 38. In this way the user 36 can transport the child 87 while the child 87 is seated in the child seat 90 in the convention of wearing a backpack. Furthermore, the child 87 has an unimpeded view of the environment through which the user 36 is walking thereby enhancing enjoyment for the child 87. Additionally, the should harness 32 can be worn such that the panel 20 rests against the user's chest 92. The second legs 71 can be positioned in the deployed position to facilitate the frame 12 and the child seat 90 to be placed on the support surface 72 in the convention of a chair. In this way the child 87 can be seated in a stationary condition without being carried on the user 36. As is shown in FIG. 6, the second legs 71 can be extended to a maximum length to recline the child chair 86 thereby facilitating the child 87 to take a nap. As shown in FIG. 9, the child seat 90 can be placed on a seat 152 of a vehicle 154 and the shoulder harness 32 can be attached to seatbelts 155 of the vehicle 154 thereby facilitating the child seat 90 to function as a car seat for securing the child 87 in the vehicle 154.

[0042] With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, device and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

[0043] Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word "comprising" is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article "a" does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A child carrying backpack device being convertible between a backpack for carrying a child and a chair for seating the child, said device comprising: a frame being curved into a U-shape defining

a pair of first legs of said frame and a central portion of said frame extending between said pair of first legs of said frame; a panel being attached to said frame such that said panel extends between said pair of first legs; a shoulder harness being attached to said panel wherein said shoulder harness is configured to be worn over shoulders of a user having said panel resting against the user's back thereby facilitating said frame to be transported in the convention of a backpack; a pair of second legs, each of said second legs being pivotally attached to a respective one of said first legs, each of said pair of second legs being positionable in a stored position having said second legs lying against said respective first leg, each of said pair of second legs being positionable in a deployed position having each of said second legs angling away from said respective first leg wherein said pair of first legs and said pair of second legs is configured to be stood upon a support surface; and a child chair being attached to said panel wherein said child chair is configured to have a child seated in said child chair thereby facilitating the user to carry the child on their back when said shoulder harness is worn over the user's shoulders.

2. The device according to claim 1, wherein: each of said first legs having a distal end with respect to said central portion; said device includes a pair of first feet, each of said first feet being attached to said distal end of a respective one of said first legs, each of said first feet having a first well extending upwardly into a bottom end of said first feet; each of said pair of second legs comprises an upper portion which slidably receives a lower portion such that each of said pair of second legs has a telescopically adjustable length; said device includes a pair of second feet, each of said second feet being attached to a bottom end of said lower portion of a respective one of said pair of second legs, each of said second feet having a second well extending upwardly into a bottom end of said second feet; and said device includes a plurality of rollers, each of said plurality of rollers having a stem extending upwardly from rollers, said stem associated with a respective one of said plurality of rollers being insertable into said first well in a respective one of said first feet, said stem associated with a respective one of said plurality of rollers being insertable into said second well in a respective one of said second feet.

3. The device according to claim 1, wherein: said device includes a pair of pivots, each of said pivots comprising a first tube being positioned around a respective one of said first legs of said frame, each of said pivots including a second tube angling away from said first tube, each of said pair of pivots being positioned closer to said central portion of said frame than said distal end of said respective first leg; and each of said pair of second legs has an upper end extending into said second tube of a respective one of said pair of pivots, each of said pair of pivots having a pivot point being disposed on said second tube which pivotally engages a respective one of said second legs.

4. The device according to claim 1, wherein: said panel has a front side, a back side and a perimeter edge extending between said front side and said back side, said perimeter edge being attached to each of said first legs and said central portion of said frame, said perimeter edge having a bottom side being spaced upwardly from a distal end of each of said first legs; and said panel has a hole extending through said front side and said back side thereby facilitating said panel to be gripped for carrying said frame and said panel, said hole being centrally positioned between said pair of first legs, said hole being spaced from said central portion of said frame.

5. The device according to claim 1, wherein: said panel has a front side and a perimeter edge, said perimeter edge having a bottom side; and said shoulder harness comprises: a pair of shoulder straps, each of said shoulder straps having a first end and a second end each being attached to said front side of said panel, said first end of each of said shoulder straps being positioned proximate said central portion of said frame, said second end of each of said shoulder straps being positioned proximate said bottom side of said perimeter edge of said panel, each of said shoulder straps being positioned adjacent to a respective one of said pair of first legs of said frame; and a chest strap having a pair of ends each being attached to a respective one of said pair of first legs wherein said chest strap is configured to extend across the user's chest when said pair of shoulder straps is worn over the user's shoulders, said chest strap comprising a first half and a second half, said chest strap

including a second buckle being attached between said first half and said second half for releasably attaching said first half to said second half.

6. The device according to claim 5, wherein each of said pair of shoulder straps includes: an upper strap and a lower strap and a middle strap being removably attachable between said upper strap and said lower strap; a first buckle being attached between said upper strap and said middle strap for releasably attaching said upper strap to said middle strap; a second buckle being attached between said lower strap and said middle strap for releasably attaching said lower strap to said middle strap; and a cushion being disposed on said middle strap, said cushion associated with each of said pair of shoulder straps being comprised of a resiliently compressible material wherein said cushion associated with each of said pair of shoulder straps is configured to enhance comfort for the user.

7. The device according to claim 1, wherein: said panel has a back side and a perimeter edge, said perimeter edge having a bottom side; said child chair comprises: a seat being coupled to and curving away from said back side of said panel, said seat having a lower wall being perpendicularly oriented with said back side of said panel wherein said lower wall is configured to have the child sit on said lower wall, said seat having a pair of leg holes each extending through a distal wall of said seat with respect to said back side of said panel wherein each of said leg holes is configured to have a respective one of the child's legs being extended through a respective one of said leg holes, said seat being oriented on said panel such that said lower wall of said seat is positioned adjacent to said bottom side of said perimeter edge of said panel; a back cushion being attached to said back side of said panel wherein said back cushion is configured to have the child rest against said back cushion when the child is seated in said seat, said back cushion extending between said seat and said hole in said panel, said back cushion having a distal surface with respect to said panel; and a head cushion being recessed into said distal surface of said back cushion wherein said head cushion is configured to have the child's head being positioned against said head cushion when the child is seated in said seat.

8. The device according to claim 7, wherein said child chair includes: a pair of child straps, each of said child straps being coupled to and curving away from said distal surface of said back cushion wherein each of said child straps is configured to extend over the child's torso when the child is seated in said seat to inhibit the child from falling out of said seat, said pair of child straps being oriented to cross each other; and a pair of couplers, each of said couplers being coupled to a respective one of a first lateral surface and a second lateral surface of said back cushion, each of said couplers having a pin extending laterally away from said couplers, each of said couplers being aligned with said head cushion.

9. The device according to claim 1, wherein: said panel has a back side and a perimeter edge, said perimeter edge having a bottom side; said child chair includes a seat having a lower wall; said device includes a foot tray being attached to and extending away from said back side of said panel, said foot tray being aligned with said bottom side of said perimeter edge of said panel such that said foot tray is positioned beneath said lower wall of said seat, said foot tray having a distal end with respect to said back side, said foot tray being substantially hollow, said distal end of said foot tray being open; and said device includes a footrest being slidably positioned in said foot tray, said footrest being slidable outwardly from said distal end of said foot tray wherein said footrest is configured to have the child's feet being positioned thereon when the child is seated in said seat.

10. A child carrying backpack device being convertible between a backpack for carrying a child and a chair for seating the child, said device comprising: a frame being curved into a U-shape defining a pair of first legs of said frame and a central portion of said frame extending between said pair of first legs of said frame, each of said first legs having a distal end with respect to said central portion, said central portion curving upwardly between each of said pair of first legs; a pair of first feet, each of said first feet being attached to said distal end of a respective one of said first legs, each of said first feet having a first well extending upwardly into a bottom end of said first feet; a panel being attached to said frame such that said panel extends between said pair of first legs, said

panel having a front side, a back side and a perimeter edge extending between said front side and said back side, said perimeter edge being attached to each of said first legs and said central portion of said frame, said perimeter edge having a bottom side being spaced upwardly from said distal end of each of said first legs, said panel having a hole extending through said front side and said back side thereby facilitating said panel to be gripped for carrying said frame and said panel, said hole being centrally positioned between said pair of first legs, said hole being spaced from said central portion of said frame; a shoulder harness being attached to said panel wherein said shoulder harness is configured to be worn over shoulders of a user having said panel resting against the user's back thereby facilitating said frame to be transported in the convention of a backpack, said shoulder harness comprising: a pair of shoulder straps, each of said shoulder straps having a first end and a second end each being attached to said front side of said panel, said first end of each of said shoulder straps being positioned proximate said central portion of said frame, said second end of each of said shoulder straps being positioned proximate said bottom side of said perimeter edge of said panel, each of said shoulder straps being positioned adjacent to a respective one of said pair of first legs of said frame, each of said pair of shoulder straps comprising an upper strap and a lower strap and a middle strap being removably attachable between said upper strap and said lower strap, each of said pair of shoulder straps including a first buckle being attached between said upper strap and said middle strap for releasably attaching said upper strap to said middle strap, each of said pair of shoulder straps including a second buckle being attached between said lower strap and said middle strap for releasably attaching said lower strap to said middle strap, each of said pair of shoulder straps including a cushion being disposed on said middle strap, said cushion associated with each of said pair of shoulder straps being comprised of a resiliently compressible material wherein said cushion associated with each of said pair of shoulder straps is configured to enhance comfort for the user; and a chest strap having a pair of ends each being attached to a respective one of said pair of first legs wherein said chest strap is configured to extend across the user's chest when said pair of shoulder straps is worn over the user's shoulders, said chest strap comprising a first half and a second half, said chest strap including a second buckle being attached between said first half and said second half for releasably attaching said first half to said second half; a pair of pivots, each of said pivots comprising a first tube being positioned around a respective one of said first legs of said frame, each of said pivots including a second tube angling away from said first tube, each of said pair of pivots being positioned closer to said central portion of said frame than said distal end of said respective first leg; a pair of second legs, each of said second legs being pivotally attached to a respective one of said first legs, each of said pair of second legs being positionable in a stored position having said second legs lying against said respective first leg, each of said pair of second legs being positionable in a deployed position having each of said second legs angling away from said respective first leg wherein said pair of first legs and said pair of second legs is configured to be stood upon a support surface, each of said pair of second legs having an upper end extending into said second tube of a respective one of said pair of pivots, each of said pair of pivots having a pivot point being disposed on said second tube which pivotally engages a respective one of said second legs, each of said pair of second legs comprising an upper portion which slidably receives a lower portion such that each of said pair of second legs has a telescopically adjustable length, said upper portion having a plurality of holes being spaced apart from each other and being distributed along a full length of said upper portion, each of said pair of second legs including a lock being movably disposed on said lower portion, said lock being biased outwardly from said lower portion thereby facilitating said lock to extend outwardly through a respective one of said plurality of holes in said upper portion for adjusting a length of said second legs; a pair of second feet, each of said second feet being attached to a bottom end of said lower portion of a respective one of said pair of second legs, each of said second feet having a second well extending upwardly into a bottom end of said second feet; a child chair being attached to said panel wherein said child chair is configured to have a child seated in said child chair thereby

facilitating the user to carry the child on their back when said shoulder harness is worn over the user's shoulders, said child chair comprising: a seat being coupled to and curving away from said back side of said panel, said seat having a lower wall being perpendicularly oriented with said back side of said panel wherein said lower wall is configured to have the child sit on said lower wall, said seat having a pair of leg holes each extending through a distal wall of said seat with respect to said back side of said panel wherein each of said leg holes is configured to have a respective one of the child's legs being extended through a respective one of said leg holes, said seat being oriented on said panel such that said lower wall of said seat is positioned adjacent to said bottom side of said perimeter edge of said panel; a back cushion being attached to said back side of said panel wherein said back cushion is configured to have the child rest against said back cushion when the child is seated in said seat, said back cushion extending between said seat and said hole in said panel, said back cushion having a distal surface with respect to said panel; a head cushion being recessed into said distal surface of said back cushion wherein said head cushion is configured to have the child's head being positioned against said head cushion when the child is seated in said seat; a pair of child straps, each of said child straps being coupled to and curving away from said distal surface of said back cushion wherein each of said child straps is configured to extend over the child's torso when the child is seated in said seat to inhibit the child from falling out of said seat, said pair of child straps being oriented to cross each other; and a pair of couplers, each of said couplers being coupled to a respective one of a first lateral surface and a second lateral surface of said back cushion, each of said couplers having a pin extending laterally away from said couplers, each of said couplers being aligned with said head cushion; a foot tray being attached to and extending away from said back side of said panel, said foot tray being aligned with said bottom side of said perimeter edge of said panel such that said foot tray is positioned beneath said lower wall of said seat, said foot tray having a distal end with respect to said back side, said foot tray being substantially hollow, said distal end of said foot tray being open; a footrest being slidably positioned in said foot tray, said footrest being slidable outwardly from said distal end of said foot tray wherein said footrest is configured to have the child's feet being positioned thereon when the child is seated in said seat; and a plurality of rollers, each of said plurality of rollers having a stem extending upwardly from rollers, said stem associated with a respective one of said plurality of rollers being insertable into said first well in a respective one of said first feet, said stem associated with a respective one of said plurality of rollers being insertable into said second well in a respective one of said second feet.
