

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250270920

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Anifowose; Fatai A. et al.

Determining Core-Log Depth Corrections for Hydrocarbon Exploration

Abstract

A method for determining a core-log depth correction between one or more wireline log measurements and one or more core sample measurements of a well, where the well is drilled for hydrocarbon exploration or extraction. The method includes training a machine learning model to determine a correlation between wireline logs obtained with down-hole logging tools and rock properties of a subsurface evaluated in the region of the well.

Inventors: Anifowose; Fatai A. (Al-Khobar, SA), Washie; Maimona Mohamed Ibrahim (Dhahran, SA)

Applicant: Saudi Arabian Oil Company (Dhahran, SA)

Family ID: 1000007715098

Appl. No.: 18/588721

Filed: February 27, 2024

Publication Classification

Int. Cl.: E21B47/04 (20120101); E21B47/09 (20120101); E21B47/12 (20120101); E21B49/02 (20060101); E21B49/08 (20060101)

U.S. Cl.:

CPC E21B47/04 (20130101); E21B47/09 (20130101); E21B47/12 (20130101); E21B49/02 (20130101); E21B49/08 (20130101); E21B2200/22 (20200501)

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates to wellbore drilling, such as for hydrocarbon extraction. More specifically, the disclosure describes techniques for determining a core-log depth correction for core measurements of rock properties.

BACKGROUND

[0002] Wireline logging is a technique in the field of hydrocarbon exploration and extraction that includes lowering measurement tools into a well on a wireline to record continuous measurements of various physical properties of the rock and fluid contents of the subsurface environment. The tools can measure properties such as electrical resistivity, gamma radiation, and acoustic properties. Information obtained from wireline logs can help plan the trajectory of future drilling operations and selecting zones for hydrocarbon extraction.

[0003] Core sample extraction is a technique in the field of hydrocarbon exploration and extraction that includes extracting cylindrical sections of rock directly from the subsurface at various depths of the well. The core samples are extracted with a specialized drill bit and brought to the surface inside a core barrel, where the core sample is preserved and labeled according to the corresponding depth of extraction. Evaluation of the core samples provides measurements of physical rock properties that include porosity, permeability, grain density, and elemental data of the subsurface.

SUMMARY

[0004] This specification describes techniques that can be used for core-log depth correction, where an evaluation of rock properties from core samples are correlated with predicted values of the same rock properties determined by wireline logs. Wireline logs are often obtained after a well has been drilled, where one or more logging tools are lowered into the well to collect measurements corresponding to multiple properties of the subsurface including gamma ray levels, neutron porosity, density, spontaneous potential, and sonic shear. In addition, core samples, often obtained while drilling, can be analyzed to evaluate multiple rock properties of the subsurface including porosity, permeability, grain density, and other elemental characteristics. The data from core samples and wireline logs are obtained under different environments, with different crew members, and with a different set of tools. Therefore, a depth correction (e.g., a core-log depth correction) is necessary when comparing the data obtained by core sample analysis with data obtained by a wireline log.

[0005] A common approach to align a set of corresponding measurements along the depth of the well between the core sample evaluation and the wireline logs is with core gamma measurements. For example, by analyzing the gamma ray levels of core samples and correlating the levels with a set of gamma ray wireline log measurements, a core-log depth correction can be obtained. A multivariate approach that correlates multiple parameters of wireline logs with associated rock properties (e.g., the rock properties obtained from core samples) provides core-log depth correction in wells and sections of wells without core samples.

[0006] This specification describes a multivariate approach to determine a correlation between a set of rock properties from core samples with a set of pseudo-logs corresponding to the same rock properties as determined by a corresponding set of wireline logs from one or more wells. The correlation can be determined by training a machine learning model to learn a pattern between a wireline log, where the wireline log includes measurements of various subsurface properties, and a predicted set of rock properties. The correlation can provide a core-log depth correction for wells without core samples and for sections of wells without core samples. By identifying a relationship between wireline logs and rock properties through training a machine learning model using core sample data and wireline logs as training data, a predicted core-log depth correction is obtained without requiring core samples from additional wells.

[0007] Implementations of the systems and methods of this disclosure can provide various technical benefits. A core-log depth correction can be obtained for wells without core samples and

for sections of wells without core samples, which reduces a necessity for collecting core samples from every section of every well in a region. In addition, gamma ray levels are not always measured for collected core samples in the field. The systems and methods of this disclosure offer a solution for determining core-log depth correction for wells with core samples but without gamma ray measurements. The systems and methods of this disclosure offer a predictive core-log depth correction for a well without the need for core samples from the particular well. Using multiple rock properties inferred from wireline logs (e.g., pseudo-logs), a multivariate correlation between the predicted multiple rock properties and measured rock properties from core samples offers a more precise correlation compared to previous approaches that use a single variable (e.g., correlating gamma ray levels).

[0008] The details of one or more implementations of these systems and methods are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of these systems and methods will be apparent from the description and drawings, and from the claims.

Description

DESCRIPTION OF DRAWINGS

[0009] FIG. 1 is a schematic view of a exploration activities being performed to map subsurface features of a reservoir.

[0010] FIG. 2 is a block diagram showing an example process for correcting the depth values of a core-log measurement of a well.

[0011] FIG. 3 is a schematic illustrating a process for training and validating a machine learning model to predict a set of rock properties of a well.

[0012] FIG. 4 is a schematic illustrating the input data and output predictions for a machine learning model trained to predict a set of rock properties of a well.

[0013] FIG. 5 illustrates a difference between a set of core-log measurements of a well and a set of predicted values from a machine learning model for an evaluation of titanium dioxide (TiO.sub.2).

[0014] FIG. 6 illustrates a difference between a set of core-log measurements of a well and a set of predicted values from a machine learning model for an evaluation of silicon dioxide (SiO.sub.2).

[0015] FIG. 7 illustrates a difference between a set of core-log measurements of a well and a set of predicted values from a machine learning model for an evaluation of potassium oxide (K.sub.2O).

[0016] FIG. 8 illustrates a difference between a set of core-log measurements of a well and a set of predicted values from a machine learning model for an evaluation of uranium.

[0017] FIG. 9 is a schematic illustrating field operations to produce hydrocarbons.

[0018] FIG. 10 is a diagram of an example computing system.

[0019] Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

[0020] This specification describes techniques that can be used for core-log depth correction, where an evaluation of rock properties from core samples are correlated with predicted values of the same rock properties determined by wireline logs. Wireline logs are often obtained after a well has been drilled, where one or more logging tools are lowered into the well to collect measurements corresponding to multiple properties of the subsurface including gamma ray levels, neutron porosity, density, spontaneous potential, and sonic shear. In addition, core samples, often obtained while drilling, can be analyzed to evaluate multiple rock properties of the subsurface including porosity, permeability, grain density, and other elemental characteristics. The data from core samples and wireline logs are obtained under different environments, with different crew members, and with a different set of tools. Therefore, a depth correction (e.g., a core-log depth correction) is necessary when comparing the data obtained by core sample analysis with data obtained by a

wireline log.

[0021] This specification describes a multivariate approach to determine a correlation between a set of rock properties from core samples with a set of pseudo-logs corresponding to the same rock properties as determined by a corresponding set of wireline logs from one or more wells. The correlation can be determined by training a machine learning model to learn a pattern between a wireline log, where the wireline log includes measurements of various subsurface properties, and a predicted set of rock properties. The correlation can provide a core-log depth correction for wells without core samples and for sections of wells without core samples. By identifying a relationship between wireline logs and rock properties through training a machine learning model using core sample data and wireline logs as training data, a predicted core-log depth correction is obtained without requiring core samples from additional wells.

[0022] FIG. 1 is a schematic view of exploration activities being performed to map subsurface features in a subsurface formation **100**. Seismic surveys along with wireline logs and core samples from wells in the subsurface can provide a comprehensive evaluation of the structure of the subsurface formation **100**. For example, correlating the seismic survey with wireline logs and core samples can lead to a prediction of the subsurface rock properties at multiple depths of the subsurface, and help identify regions for further exploring and extraction of hydrocarbons from a reservoir.

[0023] The subsurface formation **100** includes a layer of impermeable cap rock **102** at the surface. Facies underlying the impermeable cap rocks **102** include a sandstone layer **104**, a limestone layer **106**, and a sand layer **108**. A fault line **110** extends across the sandstone layer **104** and the limestone layer **106**.

[0024] Oil and gas tend to rise through permeable reservoir rock until further upward migration is blocked, for example, by the layer of impermeable cap rock **102**. Seismic surveys attempt to identify locations where interaction between layers of the subsurface formation **100** are likely to trap oil and gas by limiting this upward migration. For example, FIG. 1 shows an anticline trap **107**, where the layer of impermeable cap rock **102** has an upward convex configuration, and a fault trap **109**, where the fault line **110** might allow oil and gas to flow in with clay material between the walls traps the petroleum. Other traps include salt domes and stratigraphic traps.

[0025] A seismic source **112** (for example, a seismic vibrator or an explosion) generates seismic waves that propagate in the earth. Although illustrated as a single component in FIG. 1, the source or sources **112** are typically a line or an array of sources **112**. The generated seismic waves include seismic body waves **114** that travel into the ground and seismic surface waves **115** travel along the ground surface and diminish as they get further from the surface.

[0026] The velocity of these seismic waves depends on properties, for example, density, porosity, and fluid content of the medium through which the seismic waves are traveling. Different geologic bodies or layers in the earth are distinguishable because the layers have different properties and, thus, different characteristic seismic velocities. For example, in the subsurface formation **100**, the velocity of seismic waves traveling through the subsurface formation **100** will be different in the sandstone layer **104**, the limestone layer **106**, and the sand layer **108**. As the seismic body waves **114** contact interfaces between geologic bodies or layers that have different velocities, each interface reflects some of the energy of the seismic wave and refracts some of the energy of the seismic wave. Such interfaces are sometimes referred to as horizons.

[0027] The seismic body waves **114** are received by a sensor or sensors **116**. Although illustrated as a single component in FIG. 1, the sensor or sensors **116** are typically a line or an array of sensors **116** that generate an output signal in response to received seismic waves including waves reflected by the horizons in the subsurface formation **100**. The sensors **116** can be geophone-receivers that produce electrical output signals transmitted as input data, for example, to a computer **118** on a seismic control truck **120**. Based on the input data, the computer **118** may generate a seismic data output, for example, a seismic two-way response time plot.

[0028] The seismic surface waves **115** travel more slowly than seismic body waves **114**. Analysis of the time it takes seismic surface waves **115** to travel from source to sensor can provide information about near surface features.

[0029] A control center **122** can be operatively coupled to the seismic control truck **120** and other data acquisition and wellsite systems. The control center **122** may have computer facilities for receiving, storing, processing, and analyzing data from the seismic control truck **120** and other data acquisition and wellsite systems that provide additional information about the subsurface formation. For example, the control center **122** can receive data from a computer **119** associated with a well logging unit **121**.

[0030] The computer systems **124** can be located in a different location than the control center **122**. Some computer systems are provided with functionality for manipulating and analyzing the data, such as performing seismic interpretation or borehole resistivity image log interpretation to identify geological surfaces in the subsurface formation or performing simulation, planning, and optimization of production operations of the wellsite systems.

[0031] In some embodiments, a wellbore **130** that has been drilled in the subsurface formation **100** is logged in a well logging operation **128**. The wellbore **130** extends downhole from a wellhead **132**. The wellbore **130** is a vertical wellbore but well logging can also be performed in other wellbores, for example, slanted or horizontal wellbores. In the well logging operation **128**, the wellbore **130** penetrates through three layers **102**, **104**, and **106** of a subsurface formation **100**. A control truck **121** lowers a logging tool **134** down the wellbore **130** on a wireline **136**.

[0032] The logging tool **134** is string of one or more instruments with sensors operable to measure geophysical properties of the subsurface formation **100**. For example, logging tools can include resistivity logs, borehole image logs, porosity logs, density logs, or sonic logs. Resistivity logs measure the subsurface electrical resistivity, which is the ability to impede the flow of electric current. These logs can help differentiate between formations filled with salty waters (good conductors of electricity) and those filled with hydrocarbons (poor conductors of electricity). Porosity logs measure the fraction or percentage of pore volume in a volume of rock using acoustic or nuclear technology. Acoustic logs measure characteristics of sound waves propagated through the well-bore environment. Nuclear logs utilize nuclear reactions that take place in the downhole logging instrument or in the formation. Density logs measure the bulk density of a formation by bombarding it with a radioactive source and measuring the resulting gamma ray count after the effects of Compton scattering and photoelectric absorption. Sonic logs provide a formation interval transit time, which typically a function of lithology and rock texture but particularly porosity. The logging tool consists of a piezoelectric transmitter and receiver and the time taken for the sound wave to travel the fixed distance between the two is recorded as an interval transit time.

[0033] As the logging tool **134** travels downhole, measurements of formations properties are recorded to generate a well log. In the illustrated operation, the data are recorded at the control truck **121** in real-time. Real-time data are recorded directly against measured cable depth. In some well-logging operations, the data is recorded at the logging tool **134** and downloaded later. In this approach, the downhole data and depth data are both recorded against time. The two data sets are then merged using the common time base to create an instrument response versus depth log.

[0034] In the well logging operation **128**, the well logging is performed on a wellbore **110** that has already been drilled. In some operations, well logging is performed in the form of logging while drilling techniques. In these techniques, the sensors are integrated into the drill string and the measurements are made in real-time, during drilling rather than using sensors lowered into a well after drilling.

[0035] The computer systems **124** in the control center **122** can be configured to analyze, model, control, optimize, or perform management tasks of field operations associated with development and production of resources such as oil and gas from the subsurface formation **100**. For example, an injection well **123** and a production well **125** extend into layer **104** of the subsurface formation

100. Based on data gathered by the exploratory field operations, the computer systems **124** can generate models such as a reservoir model for portions of the subsurface formation **100**. These models can simulate the effects of production field operations (e.g., injecting water or carbon dioxide through the injection well **123** to increase the production of hydrocarbons through the production well **125**). The simulations can be used to plan and, in some instances, control field operations (e.g., the operation of pumps associated with the injection well **123** and the production well **125**).

[0036] In some embodiments, results generated by the computer systems **124** may be displayed for user viewing using local or remote monitors or other display units. One approach to analyzing seismic data is to associate the data with portions of a seismic cube representing the subsurface formation **100**. The seismic cube can also display results of the analysis of the seismic data associated with the seismic survey.

[0037] FIG. 2 is a block diagram illustrating an example process **200** for generating a pseudo-log of rock properties of a well using a machine learning model trained using correlations between wireline logs and core samples from one or more wells, according to some implementations of the present disclosure. For clarity of presentation, the description that follows generally describes process **200** in the context of the other figures in this description. However, it will be understood that process **200** can be performed, for example, by any suitable system, environment, software, and hardware, or a combination of systems, environments, software, and hardware, as appropriate. In some implementations, various steps of process **200** can be run in parallel, in combination, in loops, or in any order.

[0038] The process **200** includes a system that obtains (**202**) wireline logs from one or more first wells. Wireline logging is a method used to obtain detailed reservoir rock properties of a subsurface formation (i.e., subsurface formation **100**) in a well. The method includes lowering a logging tool, where the logging tool can be a string of measurement instruments, down a well (i.e., wellbore **130**) on a wireline. The wireline is a thin cable used to lower and raise the logging tool. In some cases, the wireline logs are stored in a database from previous logging activities. In some other cases, the wireline logs are obtained from new wells during new logging activities.

[0039] In some implementations, the wireline logs from each of the one or more first wells provide measurements of properties of the corresponding subsurface formation that include gamma ray emission, neutron porosity, density, spontaneous potential, sonic compression, and sonic shear. Measurement devices on the logging tool that is lowered down each of the one or more first wells obtain the properties of the corresponding subsurface formation. For example, a gamma ray logging tool that can include a scintillation detector can evaluate the gamma ray emission of a portion of the subsurface by measuring the natural radioactivity of the subsurface material. In some cases, shale and non-shale formations emit different levels of radioactivity, which can provide insight into the composition of the subsurface as a function of depth. As another example, by evaluating the thermalization rate of neutrons sent through the subsurface material, the neutron porosity of a portion of the subsurface can be obtained, where a Helium-3 (He-3) detector measures the thermalized neutrons and an Americium-Beryllium (Am—Be) neutron source generates the emitted neutrons. In general, the logging tool can include one or more source of neutrons, acoustic signals, electrical current and detectors to detect radioactivity, reflected sonic waves, electrical resistivity, or any other source or detector to evaluate properties of the subsurface formation.

[0040] The wireline logs of the subsurface formation from each of the one or more first wells include one or more sequence of ordered pairs, where each sequence corresponds to a physical property of the subsurface as evaluated by a measurement device on the logging tool. Each ordered pair includes a depth value and a measured physical property value. For example, an ordered pair corresponding to the gamma ray emission at a first well of the one or more first wells at a particular depth d_i is (d_i, g_i) , where g_i is the measured gamma ray emission at depth d_i according to the wireline log. In this example, the sequence of ordered pairs corresponding to the gamma ray

emission at all depths of the first well includes all values of di corresponding to the full measured depth of the first well. The logging tool can obtain a similar sequence of ordered pairs for each physical property of the subsurface for the first well, and the same set of sequences of ordered pairs for each well of the one or more first wells.

[0041] The system obtains **(204)** reservoir rock property data from core samples from the one or more first wells. The core reservoir rock property data can be stored in a database or collected directly from wells. Core samples provide direct physical measurements of the subsurface rock formation. In some cases, the core samples are cylindrical sections of rock extracted from the subsurface through drilling operations. Core samples can provide a measurement of the subsurface porosity, permeability, grain density, and elemental data properties at the depth from which the core sample is collected.

[0042] The system correlates **(206)** the wireline logs with the measured reservoir rock properties. In some cases, the measured values from the wireline logs are different from the measured values from the core samples. However, one or more measured values from the wireline logs can be correlated to one or more measured values from the core samples. For example, as an example of a wireline log, a neutron log may correlate closely with a porosity measurement of a core sample at corresponding depths, because the values measured in a neutron log can be affected by the porosity of the subsurface.

[0043] The system trains a machine learning model to identify correlations between the wireline logs and the measured reservoir rock properties. In some implementations, the machine learning model is an artificial neural network. The artificial neural network includes one or more hidden layers, the one or more hidden layers including a summation layer as a linear function and an activation layer as a sigmoid function. In addition, in some implementations, the system trains the artificial neural network using a Levenberg-Marquardt algorithm and a Bayesian regularization backpropagation algorithm. The system iteratively determines the weights of each layer of the artificial neural network by minimizing a difference between the predicted rock properties, where the predicted rock properties are the outputs of the artificial neural network, and the measured rock properties from the core samples.

[0044] In general, and specifically for the case of the artificial neural network, the system trains and validates the machine learning on a dataset that includes historical wireline data (i.e., wireline logs from the one or more first wells) and a corresponding core-log dataset (i.e., the core sample measurements from each of the one or more first wells). The core-log data from the one or more first wells represent a set of ground truth values corresponding to a set of predicted rock properties.

[0045] The system runs **(208)** a logging tool down a second well and, using the machine learning model trained on the correlated wireline logs-reservoir rock properties data of the one or more first wells, generates a set of predicted rock properties of the second well. The machine learning model learns the relationship between the wireline logs, where the wireline logs are obtained from one or more first wells, and the reservoir rock properties data, where the reservoir rock properties data is obtained from core samples from the one or more first wells.

[0046] In some implementations, the machine learning model is an artificial neural network. The artificial neural network includes a set of parameters that transforms a wireline log obtained from the second well into a predicted set of rock properties of the second well, where the parameters are learned from the correlation between the wireline logs and rock properties from core samples from the one or more first wells.

[0047] The system determines **(210)** a difference between the predicted rock properties of the second well and measured rock properties. The system can compare the peaks and valleys of the predicted rock properties to the peaks and valleys of the measured rock properties. By overlaying the predicted rock properties on the same plot as the measured rock properties on the same depth axis, the difference between each peak and valley correlates to a core-log shift at the corresponding well depth. In some implementations, the measured rock properties include core samples taken

from the second well. In some other implementations, the measured rock properties include the wireline log measurement of a correlated property of the second well.

[0048] The system applies **(212)** the difference to generate log depth corrections for each of the rock properties. The system determines the difference by comparing the predicted values of the measured rock properties with the measured values of the rock properties. The system can add the difference to the core measurements to generate a more accurate representation of the rock properties of the second well.

[0049] The system generates **(214)** a pseudo-log of rock properties of the second well based at least in part on applying the log depth corrections to the predicted rock properties. The output of the machine learning model is a continuous representation of one or more predicted rock properties of the second well. The continuous representation is a pseudo-log, where the pseudo-log is a continuous representation of a predicted physical property of the subsurface, and it can be depth-corrected by adding the corresponding log depth corrections as determined by the method described above.

[0050] FIG. **3** is a schematic that describes a system **300**, where the system **300** implements a series of steps to train a machine learning model to correlate a set of wireline logs **302** from one or more first wells with a set of rock properties from core samples **304** from the one or more first wells.

[0051] For each of the one or more first wells, the system **300** combines a dataset of wireline logs **302** (i.e., archival wireline logs) and a data set of rock properties from core samples **304** in the same sampled interval as the wireline logs to form a calibration dataset **306**. In some cases, the core samples **304** that produce the set of rock properties are sampled from discrete locations in the well at various depths. Contrastingly, wireline logs (i.e., the wireline logs **302**) are often represented as continuous distributions along the depth of the well as the logging tool can evaluate subsurface properties at precise depth intervals.

[0052] The system **300** can use the calibration dataset **306** to train a machine learning model **308** to determine a correlation between the wireline logs **302** and core sample **304** dataset. In some implementations, the system **300** can configure the machine learning model **308** as an artificial neural network, a support vector machine, a regression tree, a random forest, an extreme learning algorithm, or type I and type II fuzzy logic. Regardless of the specific architecture used as the machine learning model **308**, the system **300** implements a training procedure to determine the parameters of the machine learning model **308** that can be used to map an input wireline log to an output set of physical rock properties. In addition, regardless of the specific architecture used as the machine learning model **308**, the system **300** uses the wireline logs **302** of the calibration dataset **306** as the input features to predict a representation of the ground truth values, where the ground truth values are represented by the core sample **304** dataset. The machine learning model generates a continuous set of predicted rock properties along the main axis of the well.

[0053] The system can initialize the parameters of the machine learning model, where the initialization can be done randomly or using any other technique. In a first training run, machine learning model **308** generates an output of predicted rock properties **310** and the system **300** determines an error between the values of the predicted rock properties **310** and the ground truth values of the core samples **304** dataset from the calibration dataset **306**. For example, the system **300** can determine the error by evaluating the mean square error between the predicted rock properties **310** and the core sample **304** dataset at one or more depths that corresponds to a well from the set of one or more first wells that corresponds to the first training run.

[0054] In some implementations, the system **300** can split the calibration dataset **306** into a training dataset and a validation dataset. The training dataset is a first subset of the calibration dataset **306**, and the system **300** can use it to train the artificial neural network. The validation dataset is a second subset of the calibration dataset **360**, and the system **300** can use it to validate a set of outputs of the artificial neural network.

[0055] If the error is greater than a defined error threshold **312**, the system **300** can adjust the

weights such that it reduces the error on a subsequent training run (i.e., a training run corresponding to a second well of the one or more first wells). In addition, the system **300** can optimize a set of learning parameters **314** such as the learning rate, the number of neurons in the case of a neural network machine learning model, the activation function in the case of a neural network machine learning model, and the weights of the machine learning model. In the case of an artificial neural network architecture as an implementation of the machine learning model **308**, the artificial neural network can include one or more hidden layers, where the one or more hidden layers includes a summation layer with a linear function and an activation layer with a sigmoid function. In addition, the system **300** can train the artificial neural using a Levenberg-Marquardt algorithm and a Bayesian regularization backpropagation algorithm, where the system **300** adjusts the weights of each layer of the artificial neural network according to the implemented training algorithms.

[0056] If the error is less than or equal to the defined error threshold **312**, the training process is complete and the system **300** considers the weights of the machine learning model **308** to be learned. The system **300** can use the validated machine learning model **316** to determine a set of predicted rock values based on an input wireline log. For example, the validated machine learning model **316** can process a wireline log from a unsampled or un-cored well interval **318** to generate a predicted rock property distribution **320** from the same interval.

[0057] As new wireline data and corresponding core samples are available, the system **300** can retrain the artificial neural network with new training data, where the training data is a subset of an updated calibration dataset (i.e., calibration dataset **306**) to update a set of weights corresponding to a nonlinear function of the artificial neural network.

[0058] FIG. **4** is an illustration of the training data used to train the machine learning model and the input and output data processed by the trained machine learning model. As described in relation to FIG. **3**, the machine learning model is trained on a calibration dataset (i.e., the calibration dataset **306**), where the calibration dataset includes wireline logs and corresponding core samples of the one or more first wells.

[0059] A set of wireline logs **402** corresponding to a first well of the one or more first wells is an example of one of the entries of the calibration dataset used to train the machine learning model **404**. The set of wireline logs **402** can include logs obtained from multiple wireline logging tools to reflect wireline log parameters such as gamma ray (GR), neutron porosity (NPHI), density (RHOB), spontaneous potential (SP), sonic compression (DTC), and sonic shear (DTS). Each wireline log of the set of wireline logs **402** displays a vertical axis that represents the well depth and a horizontal axis that represents the value of the corresponding wireline log parameter. In some implementations, the set of wireline logs **402** is an example of a set of wireline logs from a wireline log archive.

[0060] A set of core samples **404** corresponding to the first well of the one or more first wells is an example of an entry of the calibration dataset used to train the machine learning model **404**, where the set of core samples **404** corresponds to the same first well described by the set of wireline logs **402**. The set of core samples **404** include measurements of rock properties of the subsurface such as porosity, permeability, and elemental composition (i.e., Thorium, Vanadium, and Uranium). Each core sample from the set of core samples **404** displays a vertical axis that represents the well depth and a horizontal axis that represents the value of the corresponding rock property. The well depth represented by the vertical axis is the same well depth as depicted in the set of wireline logs **402**.

[0061] The set of wireline logs **402** and the set of core samples **404**, each corresponding to the same first well of the one or more first wells, is an example entry of a training dataset used to train the machine learning model **406**. The set of core samples **404** represents the ground truth data, where the machine learning model **406** learns to correlate the features of an input set of wireline logs **408** to predict an output set of rock properties **410**.

[0062] In some implementations, the input set of wireline logs **408** may be from an input well with no core samples or un-cored intervals. The machine learning model **406** can generate the output set of rock properties **410** for the entire input well despite not being provided the core samples for the entire depth of the input well.

[0063] As more wireline logs and corresponding core samples become available to train the machine learning model **404**, the machine learning model **404** will more accurately identify the patterns hidden in them. For example, the data represented in FIG. **4** include wireline logs from more than 3,000 wells.

[0064] An accurate core-log depth correction ensures the properties represented by the wireline logs (e.g., wireline logs **402**) correspond to the respective rock properties **410** at the appropriate depths. By processing the wireline logs **402** with the machine learning model **404** that takes advantage of multiple variables and features to predict the corresponding rock properties **410** (e.g., not relying solely on gamma ray levels), the approach can take advantage of core samples that have not been scanned for gamma ray levels.

[0065] FIG. **5** is a plot **500** of a first dataset **502** that represents measured values at multiple depths of TiO.sub.2 in a subsurface of a well obtained through core samples and a second dataset **504** that represents predicted values at multiple depths of TiO.sub.2 in the subsurface of the well obtained through processing a wireline log with a machine learning model.

[0066] The horizontal axis **510** represents the measured value of TiO.sub.2 in the subsurface and the vertical axis **512** represents the well depth where the logging tool obtained the wireline log measurement and core extraction tool obtained the core sample.

[0067] The plot **500** displays the two datasets (the first dataset **502** and the second dataset **504**) on the same axis to demonstrate the vertical shift between the two datasets. By comparing the vertical position in the well where a peak occurs in the first dataset **502** to the vertical position in the well where a peak occurs in the second dataset **504**, a core-log depth correction for the evaluation of TiO.sub.2 can be determined. For example, a shift down **506** between the first dataset **502** and the second dataset **504** is illustrated by comparing the vertical positions of the peak value of TiO.sub.2. As another example, a shift up **508** between the first dataset **502** and the second dataset **504** is illustrated by comparing the vertical positions of the peak values of TiO.sub.2. Multiple shifts, where each shift includes a direction and a magnitude, can be determined throughout the full depth of the well by comparing the vertical positions of minima and maxima between the first dataset **502** and the second dataset **504**, where the first dataset **502** corresponds to a set of measurements obtained from core samples and the second dataset **504** corresponds to a set of predicted rock values obtained through processing a wireline log with a machine learning model.

[0068] FIG. **6** is a plot **600** of a first dataset **602** that represents measured values at multiple depths of SiO.sub.2 in a subsurface of a well obtained through core samples and a second dataset **604** that represents predicted values at multiple depths of SiO.sub.2 in the subsurface of the well obtained through processing a wireline log with a machine learning model.

[0069] The horizontal axis **610** represents the measured value of SiO.sub.2 in the subsurface and the vertical axis **612** represents the well depth where the logging tool obtained the wireline log measurement and core extraction tool obtained the core sample.

[0070] The plot **600** displays the two datasets (the first dataset **602** and the second dataset **604**) on the same axis to demonstrate the vertical shift between the two datasets. By comparing the vertical position in the well where a peak occurs in the first dataset **602** to the vertical position in the well where a peak occurs in the second dataset **604**, a core-log depth correction for the evaluation of SiO.sub.2 can be determined. In this example, the second dataset **604** is consistently shifted down relative to the first dataset **602** over the full depth of the well, unlike the example illustrated in relation to FIG. **5**. For example, multiple shifts down **606** between the first dataset **602** and the second dataset **604** are illustrated by comparing the vertical positions of the peak value of SiO.sub.2. Multiple shifts, where each shift includes a direction and a magnitude, can be

determined throughout the full depth of the well by comparing the vertical positions of minima and maxima between the first dataset **602** and the second dataset **604**, where the first dataset **602** corresponds to a set of measurements obtained from core samples and the second dataset **604** corresponds to a set of predicted rock values obtained through processing a wireline log with a machine learning model.

[0071] FIG. **7** is a plot **700** of a first dataset **702** that represents measured values at multiple depths of K.sub.2O in a subsurface of a well obtained through core samples and a second dataset **704** that represents predicted values at multiple depths of K.sub.2O in the subsurface of the well obtained through processing a wireline log with a machine learning model.

[0072] The horizontal axis **710** represents the measured value of K.sub.2O in the subsurface and the vertical axis **712** represents the well depth where the logging tool obtained the wireline log measurement and core extraction tool obtained the core sample.

[0073] The plot **700** displays the two datasets (the first dataset **702** and the second dataset **704**) on the same axis to demonstrate the vertical shift between the two datasets. By comparing the vertical position in the well where a peak occurs in the first dataset **702** to the vertical position in the well where a peak occurs in the second dataset **704**, a core-log depth correction for the evaluation of K.sub.2O can be determined. For example, a shift down **708** between the first dataset **702** and the second dataset **704** is illustrated by comparing the vertical positions of the peak value of K.sub.2O. As another example, a significant shift down **714** between the first dataset **702** and the second dataset **704** is illustrated by comparing the vertical positions of the minima values of K.sub.2O. As another example, the maxima and minima of the measured value of K.sub.2O can be vertically aligned between the first dataset **702** and the second dataset **704** as illustrated by the no shift **706**. Multiple shifts, where each shift includes a direction and a magnitude, where the magnitude includes zero shift, can be determined throughout the full depth of the well by comparing the vertical positions of minima and maxima between the first dataset **702** and the second dataset **704**, where the first dataset **702** corresponds to a set of measurements obtained from core samples and the second dataset **704** corresponds to a set of predicted rock values obtained through processing a wireline log with a machine learning model.

[0074] FIG. **8** is a plot **800** of a first dataset **802** that represents measured values at multiple depths of Uranium in a subsurface of a well obtained through core samples and a second dataset **804** that represents predicted values at multiple depths of Uranium in the subsurface of the well obtained through processing a wireline log with a machine learning model.

[0075] The horizontal axis **810** represents the measured value of Uranium in the subsurface and the vertical axis **812** represents the well depth where the logging tool obtained the wireline log measurement and core extraction tool obtained the core sample.

[0076] The plot **800** displays the two datasets (the first dataset **802** and the second dataset **804**) on the same axis to demonstrate the vertical shift between the two datasets. By comparing the vertical position in the well where a peak occurs in the first dataset **802** to the vertical position in the well where a peak occurs in the second dataset **804**, a core-log depth correction for the evaluation of Uranium can be determined. For example, multiple shifts up **806** between the first dataset **802** and the second dataset **804** are illustrated by comparing the vertical positions of the peak values of Uranium. In this example, there is a consistent shift up between the two datasets throughout the full depth of the well. Multiple shifts, where each shift includes a direction and a magnitude, can be determined throughout the full depth of the well by comparing the vertical positions of minima and maxima between the first dataset **802** and the second dataset **804**, where the first dataset **802** corresponds to a set of measurements obtained from core samples and the second dataset **804** corresponds to a set of predicted rock values obtained through processing a wireline log with a machine learning model.

[0077] FIG. **9** illustrates hydrocarbon production operations **900** that include both one or more field operations **910** and one or more computational operations **912**, which exchange information and

control exploration to produce hydrocarbons. In some implementations, outputs of techniques of the present disclosure (e.g., the method **200**) can be performed before, during, or in combination with the hydrocarbon production operations **900**, specifically, for example, either as field operations **910** or computational operations **912**, or both. For example, the process **200** collect data during field operations, processes the data in computational operations, and can determine locations to perform additional field operations.

[0078] Examples of field operations **910** include forming/drilling a wellbore, hydraulic fracturing, producing through the wellbore, injecting fluids (such as water) through the wellbore, to name a few. In some implementations, methods of the present disclosure can trigger or control the field operations **910**. For example, the methods of the present disclosure can generate data from hardware/software including sensors and physical data gathering equipment (e.g., seismic sensors, well logging tools, flow meters, and temperature and pressure sensors). The methods of the present disclosure can include transmitting the data from the hardware/software to the field operations **910** and responsively triggering the field operations **910** including, for example, generating plans and signals that provide feedback to and control physical components of the field operations **910**. Alternatively, or in addition, the field operations **910** can trigger the methods of the present disclosure. For example, implementing physical components (including, for example, hardware, such as sensors) deployed in the field operations **910** can generate plans and signals that can be provided as input or feedback (or both) to the methods of the present disclosure.

[0079] Examples of computational operations **912** include one or more computer systems **920** that include one or more processors and computer-readable media (e.g., non-transitory computer-readable media) operatively coupled to the one or more processors to execute computer operations to perform the methods of the present disclosure. The computational operations **912** can be implemented using one or more databases **918**, which store data received from the field operations **910** and/or generated internally within the computational operations **912** (e.g., by implementing the methods of the present disclosure) or both. For example, the one or more computer systems **920** process inputs from the field operations **910** to assess conditions in the physical world, the outputs of which are stored in the databases **918**. For example, seismic sensors of the field operations **910** can be used to perform a seismic survey to map subterranean features, such as facies and faults. In performing a seismic survey, seismic sources (e.g., seismic vibrators or explosions) generate seismic waves that propagate in the earth and seismic receivers (e.g., geophones) measure reflections generated as the seismic waves interact with boundaries between layers of a subsurface formation. The source and received signals are provided to the computational operations **912** where they are stored in the databases **918** and analyzed by the one or more computer systems **920**.

[0080] In some implementations, one or more outputs **922** generated by the one or more computer systems **920** can be provided as feedback/input to the field operations **910** (either as direct input or stored in the databases **918**). The field operations **910** can use the feedback/input to control physical components used to perform the field operations **910** in the real world.

[0081] For example, the computational operations **912** can process the seismic data to generate three-dimensional (3D) maps of the subsurface formation. The computational operations **912** can use these 3D maps to provide plans for locating and drilling exploratory wells. In some operations, the exploratory wells are drilled using logging-while-drilling (LWD) techniques which incorporate logging tools into the drill string. LWD techniques can enable the computational operations **912** to process new information about the formation and control the drilling to adjust to the observed conditions in real-time.

[0082] The one or more computer systems **920** can update the 3D maps of the subsurface formation as information from one exploration well is received and the computational operations **912** can adjust the location of the next exploration well based on the updated 3D maps. Similarly, the data received from production operations can be used by the computational operations **912** to control components of the production operations. For example, production well and pipeline data can be

analyzed to predict slugging in pipelines leading to a refinery and the computational operations **912** can control machine operated valves upstream of the refinery to reduce the likelihood of plant disruptions that run the risk of taking the plant offline.

[0083] In some implementations of the computational operations **912**, customized user interfaces can present intermediate or final results of the above-described processes to a user. Information can be presented in one or more textual, tabular, or graphical formats, such as through a dashboard. The information can be presented at one or more on-site locations (such as at an oil well or other facility), on the Internet (such as on a webpage), on a mobile application (or app), or at a central processing facility.

[0084] The presented information can include feedback, such as changes in parameters or processing inputs, that the user can select to improve a production environment, such as in the exploration, production, and/or testing of petrochemical processes or facilities. For example, the feedback can include parameters that, when selected by the user, can cause a change to, or an improvement in, drilling parameters (including drill bit speed and direction) or overall production of a gas or oil well. The feedback, when implemented by the user, can improve the speed and accuracy of calculations, streamline processes, improve models, and solve problems related to efficiency, performance, safety, reliability, costs, downtime, and the need for human interaction.

[0085] In some implementations, the feedback can be implemented in real-time, such as to provide an immediate or near-immediate change in operations or in a model. The term real-time (or similar terms as understood by one of ordinary skill in the art) means that an action and a response are temporally proximate such that an individual perceives the action and the response occurring substantially simultaneously. For example, the time difference for a response to display (or for an initiation of a display) of data following the individual's action to access the data can be less than 1 millisecond (ms), less than 1 second(s), or less than 10 s. While the requested data need not be displayed (or initiated for display) instantaneously, it is displayed (or initiated for display) without any intentional delay, accounting for processing limitations of a described computing system and time required to, for example, gather, accurately measure, analyze, process, store, or transmit the data.

[0086] Events can include readings or measurements captured by downhole equipment such as sensors, pumps, bottom hole assemblies, or other equipment. The readings or measurements can be analyzed at the surface, such as by using applications that can include modeling applications and machine learning. The analysis can be used to generate changes to settings of downhole equipment, such as drilling equipment. In some implementations, values of parameters or other variables that are determined can be used automatically (such as through using rules) to implement changes in oil or gas well exploration, production/drilling, or testing. For example, outputs of the present disclosure can be used as inputs to other equipment and/or systems at a facility. This can be especially useful for systems or various pieces of equipment that are located several meters or several miles apart or are in different countries or other jurisdictions.

[0087] FIG. **10** is a block diagram of an example computer system **1000** used to provide computational functionalities associated with described algorithms, methods, functions, processes, flows, and procedures described in the present disclosure, according to some implementations of the present disclosure. The illustrated computer **1002** is intended to encompass any computing device such as a server, a desktop computer, a laptop/notebook computer, a wireless data port, a smart phone, a personal data assistant (PDA), a tablet computing device, or one or more processors within these devices, including physical instances, virtual instances, or both. The computer **1002** can include input devices such as keypads, keyboards, and touch screens that can accept user information. Also, the computer **1002** can include output devices that can convey information associated with the operation of the computer **1002**. The information can include digital data, visual data, audio information, or a combination of information. The information can be presented in a graphical user interface (UI) (or GUI).

[0088] The computer **1002** can serve in a role as a client, a network component, a server, a database, a persistency, or components of a computer system for performing the subject matter described in the present disclosure. The illustrated computer **1002** is communicably coupled with a network **1024**. In some implementations, one or more components of the computer **1002** can be configured to operate within different environments, including cloud-computing-based environments, local environments, global environments, and combinations of environments.

[0089] At a high level, the computer **1002** is an electronic computing device operable to receive, transmit, process, store, and manage data and information associated with the described subject matter. According to some implementations, the computer **1002** can also include, or be communicably coupled with, an application server, an email server, a web server, a caching server, a streaming data server, or a combination of servers.

[0090] The computer **1002** can receive requests over network **1024** from a client application (for example, executing on another computer **1002**). The computer **1002** can respond to the received requests by processing the received requests using software applications. Requests can also be sent to the computer **1002** from internal users (for example, from a command console), external (or third) parties, automated applications, entities, individuals, systems, and computers.

[0091] Each of the components of the computer **1002** can communicate using a system bus **1004**. In some implementations, any or all of the components of the computer **1002**, including hardware or software components, can interface with each other or the interface **1006** (or a combination of both), over the system bus **1004**. Interfaces can use an application programming interface (API) **1014**, a service layer **1016**, or a combination of the API **1014** and service layer **1016**. The API **1014** can include specifications for routines, data structures, and object classes. The API **1014** can be either computer-language independent or dependent. The API **1014** can refer to a complete interface, a single function, or a set of APIs.

[0092] The service layer **1016** can provide software services to the computer **1002** and other components (whether illustrated or not) that are communicably coupled to the computer **1002**. The functionality of the computer **1002** can be accessible for all service consumers using this service layer. Software services, such as those provided by the service layer **1016**, can provide reusable, defined functionalities through a defined interface. For example, the interface can be software written in JAVA, C++, or a language providing data in extensible markup language (XML) format. While illustrated as an integrated component of the computer **1002**, in alternative implementations, the API **1014** or the service layer **1016** can be stand-alone components in relation to other components of the computer **1002** and other components communicably coupled to the computer **1002**. Moreover, any or all parts of the API **1014** or the service layer **1016** can be implemented as child or sub-modules of another software module, enterprise application, or hardware module without departing from the scope of the present disclosure.

[0093] The computer **1002** includes an interface **1006**. Although illustrated as a single interface **1006** in FIG. 10, two or more interfaces **1006** can be used according to implementations of the computer **1002** and the described functionality. The interface **1006** can be used by the computer **1002** for communicating with other systems that are connected to the network **1024** (whether illustrated or not) in a distributed environment. Generally, the interface **1006** can include, or be implemented using, logic encoded in software or hardware (or a combination of software and hardware) operable to communicate with the network **1024**. More specifically, the interface **1006** can include software supporting one or more communication protocols associated with communications. As such, the network **1024** or the interface's hardware can be operable to communicate physical signals within and outside of the illustrated computer **1002**.

[0094] The computer **1002** includes a processor **1008**. Although illustrated as a single processor **1008** in FIG. 10, two or more processors **1008** can be used according to implementations of the computer **1002** and the described functionality. Generally, the processor **1008** can execute instructions and can manipulate data to perform the operations of the computer **1002**, including

operations using algorithms, methods, functions, processes, flows, and procedures as described in the present disclosure.

[0095] The computer **1002** also includes a database **1020** that can hold data (such geomechanics data **1022**) for the computer **1002** and other components connected to the network **1024** (whether illustrated or not). For example, database **1020** can be in-memory or a database storing data consistent with the present disclosure. In some implementations, database **1020** can be a combination of two or more different database types (for example, hybrid in-memory and conventional databases) according to implementations of the computer **1002** and the described functionality. Although illustrated as a single database **1020** in FIG. **10**, two or more databases (of the same, different, or combination of types) can be used according to implementations of the computer **1002** and the described functionality. While database **1020** is illustrated as an internal component of the computer **1002**, in alternative implementations, database **1020** can be external to the computer **1002**.

[0096] The computer **1002** also includes a memory **1010** that can hold data for the computer **1002** or a combination of components connected to the network **1024** (whether illustrated or not). Memory **1010** can store any data consistent with the present disclosure. In some implementations, memory **1010** can be a combination of two or more different types of memory (for example, a combination of semiconductor and magnetic storage) according to implementations of the computer **1002** and the described functionality. Although illustrated as a single memory **1010** in FIG. **10**, two or more memories **1010** (of the same, different, or combination of types) can be used according to implementations of the computer **1002** and the described functionality. While memory **1010** is illustrated as an internal component of the computer **1002**, in alternative implementations, memory **1010** can be external to the computer **1002**.

[0097] The application **1012** can be an algorithmic software engine providing functionality according to implementations of the computer **1002** and the described functionality. For example, application **1012** can serve as one or more components, modules, or applications. Further, although illustrated as a single application **1012**, the application **1012** can be implemented as multiple applications **1018** on the computer **1002**. In addition, although illustrated as internal to the computer **1002**, in alternative implementations, the application **1012** can be external to the computer **1002**.

[0098] The computer **1002** can also include a power supply **1018**. The power supply **1018** can include a rechargeable or non-rechargeable battery that can be configured to be either user- or non-user-replaceable. In some implementations, the power supply **1018** can include power-conversion and management circuits, including recharging, standby, and power management functionalities. In some implementations, the power-supply **1018** can include a power plug to allow the computer **1002** to be plugged into a wall socket or a power source to, for example, power the computer **1002** or recharge a rechargeable battery.

[0099] There can be any number of computers **1002** associated with, or external to, a computer system including the computer **1002**, with each computer **1002** communicating over network **1024**. Further, the terms “client,” “user,” and other appropriate terminology can be used interchangeably, as appropriate, without departing from the scope of the present disclosure. Moreover, the present disclosure contemplates that many users can use one computer **1002** and one user can use multiple computers **1002**.

[0100] Implementations of the subject matter and the functional operations described in this specification can be implemented in digital electronic circuitry, in tangibly embodied computer software or firmware, in computer hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. Software implementations of the described subject matter can be implemented as one or more computer programs. Each computer program can include one or more modules of computer program instructions encoded on a tangible, non-transitory, computer-readable computer-storage medium for

execution by, or to control the operation of, data processing apparatus. Alternatively, or additionally, the program instructions can be encoded in/on an artificially generated propagated signal. The example, the signal can be a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus for execution by a data processing apparatus. The computer-storage medium can be a machine-readable storage device, a machine-readable storage substrate, a random or serial access memory device, or a combination of computer-storage mediums.

[0101] The terms “data processing apparatus,” “computer,” and “electronic computer device” (or equivalent as understood by one of ordinary skill in the art) refer to data processing hardware. For example, a data processing apparatus can encompass all kinds of apparatus, devices, and machines for processing data, including by way of example, a programmable processor, a computer, or multiple processors or computers. The apparatus can also include special purpose logic circuitry including, for example, a central processing unit (CPU), a field programmable gate array (FPGA), or an application specific integrated circuit (ASIC). In some implementations, the data processing apparatus or special purpose logic circuitry (or a combination of the data processing apparatus or special purpose logic circuitry) can be hardware- or software-based (or a combination of both hardware- and software-based). The apparatus can optionally include code that creates an execution environment for computer programs, for example, code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of execution environments. The present disclosure contemplates the use of data processing apparatuses with or without conventional operating systems, for example LINUX, UNIX, WINDOWS, MAC OS, ANDROID, or IOS.

[0102] The methods, processes, or logic flows described in this specification can be performed by one or more programmable computers executing one or more computer programs to perform functions by operating on input data and generating output. The methods, processes, or logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, for example, a CPU, an FPGA, or an ASIC.

[0103] Computer readable media (transitory or non-transitory, as appropriate) suitable for storing computer program instructions and data can include all forms of permanent/non-permanent and volatile/non-volatile memory, media, and memory devices. Computer readable media can include, for example, semiconductor memory devices such as random-access memory (RAM), read only memory (ROM), phase change memory (PRAM), static random-access memory (SRAM), dynamic random-access memory (DRAM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), and flash memory devices. Computer readable media can also include, for example, magnetic devices such as tape, cartridges, cassettes, and internal/removable disks.

[0104] While this specification contains many specific implementation details, these should not be construed as limitations on the scope of what may be claimed, but rather as descriptions of features that may be specific to implementations. Certain features that are described in this specification in the context of separate implementations can also be implemented, in combination, in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations, separately, or in any suitable sub-combination. Moreover, although previously described features may be described as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can, in some cases, be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

[0105] Several implementations of the subject matter have been described. Other implementations, alterations, and permutations of the described implementations are within the scope of the following claims as will be apparent to those skilled in the art. While operations are depicted in the drawings or claims in a particular order, this should not be understood as requiring that such

operations be performed in the order shown or in sequential order, or that all illustrated operations be performed (some operations may be considered optional), to achieve desirable results. In certain circumstances, multitasking or parallel processing (or a combination of multitasking and parallel processing) may be advantageous and performed as deemed appropriate.

[0106] Moreover, the separation or integration of various system modules and components in the previously described implementations should not be understood as requiring such separation or integration in all implementations, and the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

[0107] Accordingly, the previously described example implementations do not define or constrain the present disclosure. Other changes, substitutions, and alterations are also possible without departing from the spirit and scope of the present disclosure.

[0108] Furthermore, any claimed implementation is applicable to at least a computer-implemented method; a non-transitory, computer-readable medium storing computer-readable instructions to perform the computer-implemented method; and a computer system comprising a computer memory interoperably coupled with a hardware processor configured to perform the computer-implemented method or the instructions stored on the non-transitory, computer-readable medium.

[0109] Several embodiments of these systems and methods have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of this disclosure. Accordingly, other embodiments are within the scope of the following claims.

Examples

[0110] In some implementations, methods include exploring for hydrocarbons in a reservoir, the method comprising obtaining wireline logs for one or more first wells, obtaining reservoir rock property data from core samples from the one or more first wells, correlating the wireline logs with the measured reservoir rock properties, running a logging tool down a second well to generate wireline logs for the second well, processing the wireline logs for the second well using a machine learning model trained on the correlated wireline logs-reservoir rock properties data of the one or more first wells to generate a set of predicted rock properties of the second well, determining a difference between the predicted rock properties of the second well and measured rock properties, applying the difference to generate log depth corrections for each of the rock properties, and generating a pseudo-log of rock properties of the second well based at least in part on applying the log depth corrections to the predicted rock properties.

[0111] In an example implementation combinable with any other implementation, the reservoir rock property data includes porosity, permeability, grain density, and geochemical and elemental data,

[0112] In an example implementation combinable with any other implementation, the machine learning model generates a continuous set of predicted rock properties along the main axis of the well.

[0113] In an example implementation combinable with any other implementation, the machine learning model is an artificial neural network.

[0114] In an example implementation combinable with any other implementation, the artificial neural network includes one or more hidden layers, the one or more hidden layers including a summation layer comprising a linear function and an activation layer comprising a sigmoid function.

[0115] In an example implementation combinable with any other implementation, the artificial neural network is trained using a Levenberg-Marquardt algorithm and a Bayesian regularization backpropagation algorithm.

[0116] In an example implementation combinable with any other implementation, a dataset comprising wireline data from one or more wells and a corresponding core sample dataset from the

one or more wells are used to train and validate the artificial neural network, the wireline data representing input data processed by the artificial neural network, the core sample data representing a set of ground truth values corresponding to a set of predicted rock values.

[0117] In an example implementation combinable with any other implementation, the dataset is split into a training dataset and a validation dataset, the training dataset used to train the artificial neural network, the validation dataset used to validate a set of outputs of the artificial neural network.

[0118] In an example implementation combinable with any other implementation, the artificial neural network is retrained with new training data to update a set of weights corresponding to a nonlinear function of the artificial neural network.

[0119] In some implementations, methods include exploring a reservoir containing hydrocarbons, the method comprising obtaining wireline log data from a well, processing the wireline log data using a machine learning model to generate a set of predicted rock properties of the well, determining a difference between the wireline log data and the set of predicted rock properties of the well, applying the difference to generate log depth corrections for each of the rock properties, and generating a pseudo-log of rock properties of the second well based at least in part on applying the log depth corrections to the predicted rock properties.

[0120] In an example implementation combinable with any other implementation, rock properties include porosity, permeability, grain density, and geochemical and elemental data.

[0121] In an example implementation combinable with any other implementation, the machine learning model generates a continuous set of predicted rock properties along the main axis of the well.

[0122] In an example implementation combinable with any other implementation, the machine learning model is an artificial neural network.

[0123] In an example implementation combinable with any other implementation, the artificial neural network includes one or more hidden layers, the one or more hidden layers including a summation layer comprising a linear function and an activation layer comprising a sigmoid function.

[0124] In an example implementation combinable with any other implementation, the artificial neural network is trained using a Levenberg-Marquardt algorithm and a Bayesian regularization backpropagation algorithm.

[0125] In an example implementation combinable with any other implementation, a dataset comprising wireline data from one or more wells and a corresponding core sample dataset from the one or more wells are used to train and validate the artificial neural network, the wireline data representing input data processed by the artificial neural network, the core sample data representing a set of ground truth values corresponding to a set of predicted rock values.

[0126] In an example implementation combinable with any other implementation, the dataset is split into a training dataset and a validation dataset, the training dataset used to train the artificial neural network, the validation dataset used to validate a set of outputs of the artificial neural network.

[0127] In an example implementation combinable with any other implementation, the artificial neural network is retrained with new training data to update a set of weights corresponding to a nonlinear function of the artificial neural network.

Claims

1. A method of exploring for hydrocarbons in a reservoir, the method comprising: obtaining wireline logs for one or more first wells; obtaining reservoir rock property data from core samples from the one or more first wells; correlating the wireline logs with the measured reservoir rock properties; running a logging tool down a second well to generate wireline logs for the second well;

processing the wireline logs for the second well using a machine learning model trained on the correlated wireline logs-reservoir rock properties data of the one or more first wells to generate a set of predicted rock properties of the second well; determining a difference between the predicted rock properties of the second well and measured rock properties; applying the difference to generate log depth corrections for each of the rock properties; and generating a pseudo-log of rock properties of the second well based at least in part on applying the log depth corrections to the predicted rock properties.

2. The method of claim 1, wherein reservoir rock property data includes porosity, permeability, grain density, and geochemical and elemental data.

3. The method of claim 1, wherein the machine learning model generates a continuous set of predicted rock properties along the main axis of the well.

4. The method of claim 1, wherein the machine learning model is an artificial neural network.

5. The method of claim 4, wherein the artificial neural network includes one or more hidden layers, the one or more hidden layers including a summation layer comprising a linear function and an activation layer comprising a sigmoid function.

6. The method of claim 4, wherein the artificial neural network is trained using a Levenberg-Marquardt algorithm and a Bayesian regularization backpropagation algorithm.

7. The method of claim 4, wherein a dataset comprising wireline data from one or more wells and a corresponding core sample dataset from the one or more wells are used to train and validate the artificial neural network, the wireline data representing input data processed by the artificial neural network, the core sample data representing a set of ground truth values corresponding to a set of predicted rock values.

8. The method of claim 7, wherein the dataset is split into a training dataset and a validation dataset, the training dataset used to train the artificial neural network, the validation dataset used to validate a set of outputs of the artificial neural network.

9. The method of claim 7, wherein the artificial neural network is retrained with new training data to update a set of weights corresponding to a nonlinear function of the artificial neural network.

10. A method for exploring a reservoir containing hydrocarbons, the method comprising: obtaining wireline log data from a well; processing the wireline log data using a machine learning model to generate a set of predicted rock properties of the well; determining a difference between the wireline log data and the set of predicted rock properties of the well; applying the difference to generate log depth corrections for each of the rock properties; and generating a pseudo-log of rock properties of the second well based at least in part on applying the log depth corrections to the predicted rock properties.

11. The method of claim 10, wherein rock properties include porosity, permeability, grain density, and geochemical and elemental data.

12. The method of claim 10, wherein the machine learning model generates a continuous set of predicted rock properties along the main axis of the well.

13. The method of claim 10, wherein the machine learning model is an artificial neural network.

14. The method of claim 13, wherein the artificial neural network includes one or more hidden layers, the one or more hidden layers including a summation layer comprising a linear function and an activation layer comprising a sigmoid function.

15. The method of claim 13, wherein the artificial neural network is trained using a Levenberg-Marquardt algorithm and a Bayesian regularization backpropagation algorithm.

16. The method of claim 13, wherein a dataset comprising wireline data from one or more wells and a corresponding core sample dataset from the one or more wells are used to train and validate the artificial neural network, the wireline data representing input data processed by the artificial neural network, the core sample data representing a set of ground truth values corresponding to a set of predicted rock values.

17. The method of claim 16, wherein the dataset is split into a training dataset and a validation

dataset, the training dataset used to train the artificial neural network, the validation dataset used to validate a set of outputs of the artificial neural network.

18. The method of claim 16, wherein the artificial neural network is retrained with new training data to update a set of weights corresponding to a nonlinear function of the artificial neural network.
