

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250280987

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Starkey; David Phillip et al.

---

## LIQUID DISPENSING APPARATUS AND METHODS

---

### Abstract

A liquid dispensing apparatus includes a container including a downwardly extending wall portion that defines a bottom opening through which a liquid in the container is dispensed; a valve; and an actuator connected to the valve for controlling dispensing of the fluid from the container. The actuator is movable along an axis between a dispensing position, in which liquid from the container is dispensed, the valve being open when the actuator is in the dispensing position; and a non-dispensing position, in which liquid from the container is not dispensed, the valve being closed when the actuator is in the non-dispensing position, and the actuator in the non-dispensing position being located further from the container than when in the dispensing position. A spring biases the actuator in a direction away from the container. The liquid may be dispensed into a bottle containing a hard seltzer for flavoring of the seltzer.

---

**Inventors:** Starkey; David Phillip (Sandy, UT), Kuhn; Alyssa Marie (Sandy, UT), Starkey; Michael Morgan (Kent, OH)

**Applicant:** Avanelle Ventures LLC (Sheridan, WY)

**Family ID:** 88792517

**Appl. No.:** 19/218255

**Filed:** May 24, 2025

### Related U.S. Application Data

parent US continuation 18200696 20230523 PENDING child US 19218255

us-provisional-application US 63344712 20220523

---

### Publication Classification

**Int. Cl.:** A47J31/00 (20060101); A47J31/44 (20060101); A47J31/46 (20060101)

U.S. Cl.:

CPC      **A47J31/005** (20130101); **A47J31/4407** (20130101); **A47J31/461** (20180801);  
**A47J31/462** (20130101);

---

## Background/Summary

### COPYRIGHT STATEMENT

[0001] Any new and original work of authorship in this document—including any source code—is subject to copyright protection under the copyright laws of the United States and other countries. Reproduction by anyone of this document as it appears in official governmental records is permitted, but otherwise all other copyright rights whatsoever are reserved.

### INCORPORATION OF COMPUTER PROGRAM LISTING APPENDIX

[0002] Submitted concurrently herewith via the USPTO's electronic filing system, and hereby incorporated herein by reference, is a computer program listing appendix representing computer program files including instructions, routines, and/or other contents of several computer programs. A table setting forth the name and size of files included in the computer program listing appendix is included below.

| TABLE-US-00001 | File Name  | Creation Date           | File Size (bytes) |
|----------------|------------|-------------------------|-------------------|
|                | ascify.txt | May 22, 2023 6:26:33 PM | 37,473            |
|                | readme.txt | May 22, 2023 6:26:25 PM | 2,890             |
|                | disp.txt   | May 22, 2023 6:26:23 PM | 1,235,857         |

[0003] One of these files, “readme.txt”, contains instructions for utilizing “ascify.txt” to convert “disp.txt” in this computer program listing into a compressed “.zip” file. The resulting compressed “.zip” file contains “dispenser.easm” which is an eDrawing file and which illustrates aspects and features in accordance with one or more preferred embodiments of the invention. This eDrawing file can be viewed using a free viewer available online from Dassault Systèmes SolidWorks Corporation using MacOS or Microsoft Windows respectively on a Mac or PC.

### BACKGROUND OF THE INVENTION

[0004] The invention generally relates to liquid dispensing apparatus and methods and, in particular, to such apparatus and methods wherein a liquid—such as for example a flavoring liquid or an alcohol for human consumption—is added to a liquid that is already in a primary container, such as a bottle.

[0005] In recent years, carbonated non-beer refreshments, commonly referred to as “hard seltzers”, have become widely popular. In making a homemade hard seltzer, a user adds a measured volume of alcohol to a nonalcoholic liquid, such as adding a flavored vodka to a bottle of club soda. Unfortunately, avoiding spills when pouring a measured liquid into a bottle can be tricky. One solution is to use a funnel; however, this can be cumbersome, especially if a funnel is not immediately at hand and must be located. The funnel also must be cleaned after use, which is in addition to cleaning the apparatus used to measure out the desired amount of the liquid to be added to the bottle.

[0006] In view of the foregoing, it is believed that a need exists for improvement in dispensing apparatus and methods, especially when adding a measured liquid to a container such as a bottle. This, and other needs, are addressed by one or more aspects of the invention.

### SUMMARY OF THE INVENTION

[0007] The invention includes many aspects and features. Moreover, while many aspects and features relate to, and are described in, the context of hard seltzers, the invention is not limited to use only with hard seltzers and preferably is used with other beverages and even outside of the beverage context. The full utility of the invention will become apparent from the following summaries and detailed descriptions of aspects, features, and one or more embodiments of the

invention.

[0008] In an aspect, a liquid dispensing apparatus comprises: a container including a downwardly extending wall portion that defines a bottom opening through which a liquid in the container is dispensed; a valve; an actuator connected to the valve for controlling dispensing of the fluid from the container, the actuator being movable along an axis between a dispensing position, in which liquid from the container is dispensed, the valve being fully open when the actuator is in the dispensing position, and a non-dispensing position, in which liquid from the container is not dispensed, the valve being closed when the actuator is in the non-dispensing position, and the actuator in the non-dispensing position being located further from the container than when in the dispensing position; and a spring biasing the actuator in a direction away from the container for biasing the actuator into the non-dispensing position in which the valve is closed.

[0009] In a feature, the actuator is movable along the axis between a plurality of dispensing positions, in each of which the valve is at least partially open for dispensing of liquid from the container.

[0010] In a feature, the apparatus further comprises an O-ring for sealing engagement between the valve and the container.

[0011] In a feature, the apparatus further comprises a lid that snap-fits or screws onto a rim of the container in covering relation to a mouth of the container so as to seal the top of the container. The lid may be retained to the container by a tether.

[0012] In a feature, the actuator comprises a funnel-shaped, downwardly extending wall portion for insertion into a mouth of a bottle in which the liquid is to be dispensed from the container. The funnel-shaped wall portion preferably defines an interior space within which is received the downwardly extending wall portion defining the bottom opening in the container; and the apparatus preferably further comprises a lid that covers a mouth of the container so as to seal the top of the container, wherein the lid includes a recess configured to receive and retain in frictional fit the funnel-shaped, downwardly extending wall portion of the actuator.

[0013] In a feature, the apparatus further comprises a locking mechanism for precluding the actuator from transitioning from the non-dispensing position toward the dispensing position. The locking mechanism preferably comprises downwardly extending tabs that engage an annular portion of the actuator and block displacement of the actuator from the non-dispensing position toward the container, wherein the actuator includes openings for accommodating passage therethrough of the tabs, and wherein the actuator is rotatable about the axis between an unlocked position in which the openings are aligned with the tabs and an unlocked position in which the tabs are aligned with the openings.

[0014] In another feature, the actuator moves radially relative to the axis.

[0015] In another feature, the actuator moves rotationally about the axis.

[0016] Another aspect comprises a liquid dispensing apparatus as disclosed herein.

[0017] Another aspect comprises an apparatus having means for dispensing a liquid, means for positioning the apparatus for filling, and means for locking the apparatus so that the liquid is not accidentally dispensed.

[0018] In another aspect, a method of using a liquid dispensing apparatus for adding a liquid from the apparatus to a second liquid in a bottle comprises the steps of: filling the liquid dispensing apparatus; positioning the liquid dispensing apparatus such that a funnel-shaped, downwardly extending portion thereof is received through a mouth of the bottle; and actuating a valve of the apparatus such that the liquid is dispensed from the apparatus into the bottle through the funnel-shaped portion.

[0019] In a feature, the method further comprises unlocking the liquid dispensing apparatus to enable actuating of the valve. Unlocking the liquid dispensing apparatus may comprise rotating an actuator such that openings defined in an annular portion of the actuator align with locking tabs that extend downwardly from a bottom of the container.

[0020] In a feature, actuating the valve of the apparatus comprising depressing a container of the apparatus toward a portion of the apparatus that abuts a rim of the bottle.

[0021] In a feature, the apparatus comprises a lid and wherein filling the liquid dispenser comprises positioning in frictional fit the funnel-shaped portion within a recess of the lid with the lid placed on a surface, whereby the liquid dispenser is free standing. In this respect, the recess of the lid is shaped and dimensioned to receive the actuator for handsfree standing of the apparatus on a surface such as a table top for pouring of a liquid into the container.

[0022] In a feature, the method further comprises, after performing said step (a), covering a container of the apparatus with a lid and storing or transporting the apparatus prior to performing said steps (b) and (c). The step of storing or transporting the apparatus may comprise placing the apparatus in a bag, purse, or backpack.

[0023] Another aspect comprises a method of using a liquid dispensing apparatus as disclosed herein.

[0024] Another aspect comprises a method of filling a liquid dispensing apparatus as disclosed herein.

[0025] Additional aspects and features are disclosed in the eDrawings of the computer program listing, which is incorporated herein by reference.

[0026] In addition to the aforementioned aspects and features of the invention, it should be noted that the invention further encompasses the various logical combinations and subcombinations of such aspects and features. Thus, for example, claims in this or a divisional or continuing patent application or applications may be separately directed to any aspect, feature, or embodiment disclosed herein, or combination thereof, without requiring any other aspect, feature, or embodiment.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0027] One or more preferred embodiments of the invention now will be described in detail with reference to the accompanying drawings, wherein the same elements are referred to with the same reference numerals.

[0028] FIG. **1** is a perspective view of a liquid dispensing apparatus **100** in accordance with one or more aspects and features of the invention.

[0029] FIG. **2** is a top plan view of the dispensing apparatus **100**.

[0030] FIG. **3** is a bottom plan view of the dispensing apparatus **100**.

[0031] FIG. **4** is an elevational view of a first side of the dispensing apparatus **100**.

[0032] FIG. **5** is an elevational view of a rear of the dispensing apparatus **100**.

[0033] FIG. **6** is an elevational view of a second side of the dispensing apparatus **100**.

[0034] FIG. **7** is an elevational view of a front side of the dispensing apparatus **100**.

[0035] FIG. **8** is an exploded elevational view of the front side of the dispensing apparatus **100**.

[0036] FIG. **9** is an exploded perspective view of the dispensing apparatus **100**.

[0037] FIG. **10** is a perspective view of a top of an actuator **108** of the dispensing apparatus **100**.

[0038] FIG. **11** is a top plan view of the actuator **108**.

[0039] FIG. **12** is a perspective view looking downwardly of a valve **110** of the dispensing apparatus **100**.

[0040] FIG. **13** is a perspective view looking upwardly of the valve **110**.

[0041] FIG. **14** is a top plan view of the container **102** of the dispensing apparatus **100**.

[0042] FIG. **15** is a cross-sectional view of the container **102**.

[0043] FIG. **16** is a cross-sectional view of the dispensing apparatus **100**.

[0044] FIGS. **17-19** illustrate a method of using the dispensing apparatus **100** in accordance with

one or more aspects and features of the invention.

[0045] FIGS. **20-22** are perspective views of a working prototype of a dispensing apparatus **1000** in accordance with one or more aspects and features of the invention.

[0046] Additionally, FIGS. **1A, 2A, 3A, 4A, 5A, 6A, 7A, 8A, 9A, 10A, 11A, 12A, 13A, 14A, 15A, and 16A** are shaded views with edges outlined of FIGS. **1-16**, respectively; and FIGS. **1B, 2B, 3B, 4B, 5B, 6B, 7B, 8B, 9B, 10B, 11B, 12B, 13B, 14B, 15B, and 16B** are shaded views of FIGS. **1-16**, respectively.

#### DETAILED DESCRIPTION

[0047] As a preliminary matter, it will readily be understood by one having ordinary skill in the relevant art (“Ordinary Artisan”) that the invention has broad utility and application. Furthermore, any embodiment discussed and identified as being “preferred” is considered to be part of a best mode contemplated for carrying out the invention. Other embodiments also may be discussed for additional illustrative purposes in providing a full and enabling disclosure of the invention. Furthermore, an embodiment of the invention may incorporate only one or a plurality of the aspects of the invention disclosed herein; only one or a plurality of the features disclosed herein; or combination thereof. As such, many embodiments are implicitly disclosed herein and fall within the scope of what is regarded as the invention.

[0048] Accordingly, while the invention is described herein in detail in relation to one or more embodiments, it is to be understood that this disclosure is illustrative and exemplary of the invention and is made merely for the purposes of providing a full and enabling disclosure of the invention. The detailed disclosure herein of one or more embodiments is not intended, nor is to be construed, to limit the scope of patent protection afforded the invention in any claim of a patent issuing here from, which scope is to be defined by the claims and the equivalents thereof. It is not intended that the scope of patent protection afforded the invention be defined by reading into any claim a limitation found herein that does not explicitly appear in the claim itself.

[0049] Thus, for example, any sequence(s) and/or temporal order of steps of various processes or methods that are described herein are illustrative and not restrictive. Accordingly, it should be understood that, although steps of various processes or methods may be shown and described as being in a sequence or temporal order, the steps of any such processes or methods are not limited to being carried out in any particular sequence or order, absent an indication otherwise. Indeed, the steps in such processes or methods generally may be carried out in various different sequences and orders while still falling within the scope of the invention. Accordingly, it is intended that the scope of patent protection afforded the invention be defined by the issued claim(s) rather than the description set forth herein.

[0050] Additionally, it is important to note that each term used herein refers to that which the Ordinary Artisan would understand such term to mean based on the contextual use of such term herein. To the extent that the meaning of a term used herein—as understood by the Ordinary Artisan based on the contextual use of such term—differs in any way from any particular dictionary definition of such term, it is intended that the meaning of the term as understood by the Ordinary Artisan should prevail.

[0051] With regard solely to construction of any claim with respect to the United States, no claim element is to be interpreted under 35 U.S.C. 112(f) unless the explicit phrase “means for” or “step for” is actually used in such claim element, whereupon this statutory provision is intended to and should apply in the interpretation of such claim element. With regard to any method claim including a condition precedent step, such method requires the condition precedent to be met and the step to be performed at least once but not necessarily every time during performance of the claimed method.

[0052] Furthermore, it is important to note that, as used herein, “comprising” is open-ended insofar as that which follows such term is not exclusive. Additionally, “a” and “an” each generally denotes “at least one” but does not exclude a plurality unless the contextual use dictates otherwise. Thus,

reference to “a picnic basket having an apple” is the same as “a picnic basket comprising an apple” and “a picnic basket including an apple”, each of which identically describes “a picnic basket having at least one apple” as well as “a picnic basket having apples”; the picnic basket further may contain one or more other items beside an apple. In contrast, reference to “a picnic basket having a single apple” describes “a picnic basket having only one apple”; the picnic basket further may contain one or more other items beside an apple. In contrast, “a picnic basket consisting of an apple” has only a single item contained therein, i.e., one apple; the picnic basket contains no other item.

[0053] When used herein to join a list of items, “or” denotes “at least one of the items” but does not exclude a plurality of items of the list. Thus, reference to “a picnic basket having cheese or crackers” describes “a picnic basket having cheese without crackers”, “a picnic basket having crackers without cheese”, and “a picnic basket having both cheese and crackers”; the picnic basket further may contain one or more other items beside cheese and crackers.

[0054] When used herein to join a list of items, “and” denotes “all of the items of the list”. Thus, reference to “a picnic basket having cheese and crackers” describes “a picnic basket having cheese, wherein the picnic basket further has crackers”, as well as describes “a picnic basket having crackers, wherein the picnic basket further has cheese”; the picnic basket further may contain one or more other items beside cheese and crackers.

[0055] The phrase “at least one” followed by a list of items joined by “and” denotes an item of the list but does not require every item of the list. Thus, “at least one of an apple and an orange” encompasses the following mutually exclusive scenarios: there is an apple but no orange; there is an orange but no apple; and there is both an apple and an orange. In these scenarios if there is an apple, there may be more than one apple, and if there is an orange, there may be more than one orange. Moreover, the phrase “one or more” followed by a list of items joined by “and” is the equivalent of “at least one” followed by the list of items joined by “and”.

[0056] Referring now to the drawings, one or more preferred embodiments of the invention are next described. The following description of one or more preferred embodiments is merely exemplary in nature and is in no way intended to limit the invention, its implementations, or uses.

[0057] Turning now to FIG. 1, a perspective view of a preferred liquid dispensing apparatus **100** in accordance with one or more aspects and features of the invention is illustrated. Furthermore, FIG. 2 is a top plan view of the dispensing apparatus **100**; FIG. 3 is a bottom plan view of the dispensing apparatus **100**; FIG. 4 is an elevational view of a first side of the dispensing apparatus **100**; FIG. 5 is an elevational view of a rear of the dispensing apparatus **100**; FIG. 6 is an elevational view of a second side of the dispensing apparatus **100**; and FIG. 7 is an elevational view of a front side of the dispensing apparatus **100**. Exploded views of the dispensing apparatus **100** are illustrated in FIG. 8, which is an elevational view of the front side, and in FIG. 9, which is a perspective view thereof.

[0058] As seen in these figures, the dispensing apparatus **100** comprises a container **102** with a lid **104** that is retained to the container **102** by a tether **106**. The container **102** preferably holds a volume to be dispensed of up to 3 milliliters and is graduated, i.e., marked with units of measurement, by for example units of milliliters or half milliliters (not shown). The container **102** may be transparent, translucent, or opaque.

[0059] The container **102** includes a downwardly extending wall portion **103** that define a bottom opening **112** through which a liquid held in the container **102** is dispensed. The wall portion **103** defining the bottom opening of the container **102** is perhaps best seen in FIG. 14, which is a cross-sectional view of just the container **102**. Dispensing of the fluid from the container **102** is mechanically controlled by an actuator **108**, as described below.

[0060] The container **102** further includes downwardly extending tabs **105**.

[0061] The lid **104** snap-fits onto a rim of the container **102** in covering relation to a mouth **101** of the container **102** so as to seal the top of the container **102**. Alternatively, the lid **104** may include threads that mate with threads on the container **102** for screwing of the lid **104** onto the container

**102.**

[0062] The tether **106** is attached to the lid **104** at a distal end of the tether **106** and is attached to the container **102** at a proximal end of the tether **106**. The tether may attach to the lid in any conventional manner or the tether may be integrally formed with the lid in a manufacturing process. The tether includes a band portion **107** at a proximal end of the tether **106** by which the tether **106** is attached to the container **102**. The band portion **107** is shown as being integrally manufactured with the tether **106** but may alternatively be two pieces connected together. The band portion **107** wraps around a midportion of the container **102** and may be permanently attached to the container **102** or removably attached in a frictional fit on the midportion of the container **102**.

[0063] With reference to FIGS. **8**, **9**, **12**, **13**, and FIG. **15**, the dispensing apparatus **100** further includes a valve **110** that controls dispensing of a liquid held in the container **102** through the bottom opening **112**. A detailed view of the valve **110** is provided in FIGS. **12** and **13**; FIG. **12** is a perspective view looking downwardly of the valve **110**, and FIG. **13** is a perspective view looking upwardly of the valve **110**. FIG. **15** is a cross-sectional view of the dispensing apparatus **100**.

[0064] An O-ring **114** seals a head **111** of the valve **110** and the container **102** in a liquid-tight manner for precluding leaking through the bottom opening **112** when the valve **110** is in a closed position. The head **111** of the valve **110** is located at a proximal end of the valve **110**, and the O-ring **114** is received within a channel **120** defined between the head **111** and shoulder **122**; the valve **110** includes four shoulders **122** arranged equidistant around a longitudinal axis **119** of the valve **110** for retaining the O-ring **114** adjacent the head **111**. The valve **110** further includes alignment ribs **124**; the valve **110** includes four ribs **124** arranged equidistant around the longitudinal axis **119** of the valve **110**.

[0065] A distal end of the valve **110** is configured for attachment of the actuator **108**, whereby the valve **110** is mechanically actuated by the actuator **108**. Specifically, the distal end of the valve **110** includes a bulbous portion **128**. The actuator **108** clutches onto the distal end of the valve **110** and is retained there by the bulbous portion **128**, as described below.

[0066] A spring **116** extends between the actuator **108** and the container **102** and is tensioned to bias the actuator **108** in a downward direction away from the container **102** and, consequently, thereby biases the valve **110** into the closed position sealing off the liquid in the container from the bottom opening **112** of the container **102**.

[0067] A detailed view of the actuator **108** is provided in FIGS. **10** and **11**; FIG. **10** is a perspective view of a top of the actuator **108**, and FIG. **11** is a top plan view of the actuator **108**. The actuator comprises a downwardly extending portion **134** defining a funnel and an annular portion **132**. On an inside of the downwardly extending portion **134**, the actuator **108** comprises a plurality of radially extending fingers **138** that extend toward an axis of the actuator **139**. The fingers **138** collectively define an area between the ends thereof that is dimensioned to receive therethrough the distal end of the valve **110** and, specifically, the bulbous portion **128**.

[0068] In passing the bulbous portion **128** through the area, the portion **128** engages the ends of the fingers **138** and the bulbous portion **128**, the fingers **138**, or both flex to a sufficient extent so as to allow the bulbous portion **128** to pass by the fingers **138** with minor force and without damaging either. The actuator **108** thereby snaps or pops onto the distal end of the valve **110** and is retained thereon. The portion of the valve **110** to which the fingers **138** come to engage preferably are shaped and dimensioned to receive and retain the fingers, as illustrated in FIG. **16** for example. This fixes the actuator **108** and to the valve **110** relative to axial movement along axis **119**; the actuator **108** and valve **110** are in fixed disposition relative to each other when moving toward and away from the container **102**.

[0069] Moreover, the actuator **108** while retained on the distal end of the valve is nonetheless rotatable about the axis **119** and axis **139**. Fluid passageways **140** also are defined between the fingers **138**, as perhaps best illustrated in FIG. **11**, whereby a liquid may flow through the downwardly extending portion **134** and around the bulbous portion **128** even while the actuator **108**

is attached on the distal end of the valve **110**.

[0070] The annular portion **134** is located proximate and underlies the bottom of the container **102**. The dispensing apparatus **100** is configured such that the actuator **108** is rotatable with the tabs **105** riding up inclined surfaces **142** to detents **144** formed in the annular portion **132** in which detents **144** the ends of the tabs **105** are received and retained. Furthermore, when the ends of the tabs **105** are received and retained in the detents **144**, the valve **110** is biased by the spring in the closed position. This serves to lock the valve in the closed position.

[0071] To open the valve **110** for dispensing of fluid in the container **102**, the actuator **108** is moved away from the container **102** such that the ends of the tabs **105** are withdrawn from the detents **144**, the actuator **108** then is rotated such that the tabs align with the openings **136** formed in the annular portion **134**, and the actuator **108** is moved toward the container **102** in opposition to the spring biasing. In moving the actuator **108** toward the container **102**, the tabs pass through the openings **136**. Moreover, because the actuator is mounted to the distal end of the valve **110**, such movement extends the head **111** of the valve **110** into the containment space of the container **102** thereby unsealing the bottom opening **112** and enabling fluid to flow from the container **102** through the bottom opening **112**.

[0072] FIG. **14** is a top plan view of the container **102**. As illustrated in FIG. **14**, the container **102** defines alignment ribs **148** on an inside of the wall portion **103**. The alignment ribs **124** on the valve **110** and the alignment ribs **148** complement each other such that the distal end and mid portion of the valve **110** passes through the bottom opening **112** in the container **102** and is retained therein against rotation about the axis **119** of the valve when the dispensing apparatus **100** is in the assembled state. Preferably there is little room or space between the alignment ribs **103,148** for a rotation-free fit.

[0073] FIG. **15** is a cross-sectional view of the container **102** of the dispensing apparatus **100**.

[0074] FIG. **16** is a cross-sectional view of the dispensing apparatus **100**. FIG. **16** perhaps best illustrates a recess **113** that is formed in the lid **104**, wherein the recess **113** is shaped and dimensioned to receive in frictional fit therein the funnel-shaped, downwardly extending wall portion **134** of the actuator **108**. This enables the container **102** to be placed and maintained in an upright position on a table surface without using one's hand to maintain the container **102**; in this respect, it is free standing. Both hands thus can be used for pouring of a liquid into the container **102**.

[0075] Use of the dispensing apparatus **100** to add a liquid from the container to a second liquid in a bottle **150** is collectively illustrated in FIGS. **17**, **18**, and **19**. It is contemplated that the bottle **150** also could be—and hereby additionally represents—a container in the form of a can.

[0076] As illustrated in FIG. **17**, the second liquid has a liquid level at **152** such that there is sufficient capacity remaining in the bottle **150** to add the liquid from the container of the dispensing apparatus **100**. The dispensing apparatus is unlocked (if locked) by rotating the actuator such that the openings in the annular portion align with the locking tabs extending downwardly from the container. The apparatus then is positioned with the funnel-shaped, downwardly extending wall portion of the actuator extending into the mouth and neck of the bottle **150**, as illustrated in FIG. **18**.

[0077] As illustrated in FIG. **18**, the annular portion of the actuator abuts the rim of the bottom **150** but has yet to be displaced toward the container of the apparatus. As such, no liquid has yet been dispensed from the apparatus **100** into the bottle. Further pressing of the container downwardly (depressing the container relative to the actuator and bottle) results in displacement of the actuator toward the container, counter to the biasing of the spring of the apparatus **100**. This unseats the head of the valve, resulting in fluid flow around the valve head and through the fluid passageways of the actuator, and dispensing into the interior of the bottle **150** for mixing with the liquid already in the bottle **150** and raising the fill level, as shown in FIG. **18**.

[0078] FIGS. **20**, **21**, and **22** are perspective views of a working prototype of a dispensing



apparatus in accordance with one or more aspects and features of the invention. The dispensing apparatus is illustrated in FIG. 20 in a sealed and locked condition suitable for storing and carrying liquid in the container for later use. FIG. 21 illustrates a top of the dispensing apparatus including recess formed in the lid. The recess of the lid is configured to receive the funnel-shaped, downwardly extending wall portion of the actuator for handsfree standing of the apparatus, which is illustrated in FIG. 22.

[0079] Of course, the liquid in the container can also be dispensed by manually pressing the actuator toward the container to unseat the valve. The liquid in the container can also be poured from the container rather than dispensed through the bottom opening, if desired.

[0080] In view of the foregoing, it will be appreciated that the “means for dispensing a liquid” comprises the spring-biased valve and may further include the actuator; the “means for positioning the apparatus for filling” comprises the funnel-shaped, downwardly extending portion thereof and the lid thereof having the recess within which the funnel-shaped, downwardly extending portion is positioned in frictional fit when the lid is placed on a surface, whereby the apparatus is free standing; and the “means for locking the apparatus” comprises the spring-biased tabs and detents.

[0081] Based on the foregoing description, it will be readily understood by those persons skilled in the art that the invention has broad utility and application. Many embodiments and adaptations of the invention other than those specifically described herein, as well as many variations, modifications, and equivalent arrangements, will be apparent from or reasonably suggested by the invention and the foregoing descriptions thereof, without departing from the substance or scope of the invention.

[0082] Accordingly, while the invention has been described herein in detail in relation to one or more preferred embodiments, it is to be understood that this disclosure is only illustrative and exemplary of the invention and is made merely for the purpose of providing a full and enabling disclosure of the invention. The foregoing disclosure is not intended to be construed to limit the invention or otherwise exclude any such other embodiments, adaptations, variations, modifications or equivalent arrangements, the invention being limited only by the claims appended hereto and the equivalents thereof.

## Claims

1. A method of using a liquid dispensing apparatus for adding a liquid from the apparatus to a second liquid in a bottle, comprising the steps of: (a) filling the liquid dispensing apparatus; (b) positioning the liquid dispensing apparatus such that a funnel-shaped, downwardly extending portion thereof is received through a mouth of the bottle; and (c) actuating a valve of the apparatus such that the liquid is dispensed from the apparatus into the bottle through the funnel-shaped portion; (d) wherein the apparatus comprises a lid and wherein filling the liquid dispenser comprises positioning in frictional fit the funnel-shaped portion within a recess of the lid with the lid placed on a surface, whereby the liquid dispenser is free standing.
2. The method of claim 1, wherein actuating the valve of the apparatus comprising depressing a container of the apparatus toward a portion of the apparatus that abuts a rim of the bottle.
3. The method of claim 1, further comprising, after performing said step (a), covering a container of the apparatus with a lid and storing or transporting the apparatus prior to performing said steps (b) and (c).
4. The method of claim 3, wherein the step of storing or transporting the apparatus comprises placing the apparatus in a bag, purse, or backpack.
5. A method of using a liquid dispensing apparatus for adding a liquid from the apparatus to a second liquid in a bottle, comprising the steps of: (a) filling the liquid dispensing apparatus; (b) positioning the liquid dispensing apparatus such that a funnel-shaped, downwardly extending portion thereof is received through a mouth of the bottle; and (c) actuating a valve of the apparatus

such that the liquid is dispensed from the apparatus into the bottle through the funnel-shaped portion; (d) wherein the method further comprises unlocking the liquid dispensing apparatus to enable actuating of the valve; and (e) wherein unlocking the liquid dispensing apparatus comprises rotating an actuator such that openings defined in an annular portion of the actuator align with locking tabs that extend downwardly from a bottom of the container.

**6.** The method of claim 5, wherein actuating the valve of the apparatus comprising depressing a container of the apparatus toward a portion of the apparatus that abuts a rim of the bottle.

**7.** The method of claim 5, further comprising, after performing said step (a), covering a container of the apparatus with a lid and storing or transporting the apparatus prior to performing said steps (b) and (c).

**8.** The method of claim 7, wherein the step of storing or transporting the apparatus comprises placing the apparatus in a bag, purse, or backpack.

---