

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281043

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

HU; Fu-Ming et al.

METHOD AND APPARATUS FOR MONITORING COLLECTION OF PHYSIOLOGICAL PATIENT DATA

Abstract

A method and apparatus for monitoring collection of subject condition data is provided. The method includes receiving a value of a parameter of subject condition data and a value of a sample time, for each of a plurality of sample times. The method also includes storing the subject condition data in a data structure including a first field for holding data indicating a current sample time and a second field for holding data indicating the value of the parameter. The method also includes determining a time gap defined by a duration between the current sample time and a most recent sample time and determining whether the time gap exceeds a time gap threshold and causing an apparatus to perform remedial action. A method for presenting the subject condition data on a display is also provided.

Inventors: HU; Fu-Ming (Ellicott City, MD), STANSBURY; Lynn G. (Seattle, WA), MACKENZIE; Colin F. (Pasadena, MD), SCALEA; Thomas M. (Baltimore, MD), STEIN; Deborah M. (Owings Mills, MD), YANG; Shiming (Halethorpe, MD)

Applicant: University of Maryland, Baltimore (Baltimore, MD)

Family ID: 64691583

Appl. No.: 19/217250

Filed: May 23, 2025

Related U.S. Application Data

parent US continuation 18295373 20230404 parent-grant-document US 12343109 child US 19217250

parent US division 17676657 20220221 parent-grant-document US 11647904 child US 18295373

parent US division 15976409 20180510 parent-grant-document US 11291369 child US 17676657

us-provisional-application US 62504891 20170511

Publication Classification

Int. Cl.: **A61B5/00** (20060101); **A61B5/01** (20060101); **A61B5/0205** (20060101); **A61B5/024** (20060101); **A61B5/11** (20060101); **A61B5/1455** (20060101); **G16H10/40** (20180101); **G16H10/60** (20180101)

U.S. Cl.:

CPC **A61B5/0022** (20130101); **A61B5/0006** (20130101); **A61B5/0008** (20130101); **A61B5/02055** (20130101); **A61B5/1113** (20130101); **G16H10/40** (20180101); **G16H10/60** (20180101); A61B5/01 (20130101); A61B5/02405 (20130101); A61B5/1455 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/295,373, filed Apr. 4, 2023, which is a divisional of U.S. application Ser. No. 17/676,657, filed Feb. 21, 2022, which claims benefit of U.S. application Ser. No. 15/976,409 filed May 10, 2018, which claims the benefit of provisional application 62/504,891, filed May 11, 2017, the entire contents of which are incorporated herein.

BACKGROUND

[0003] Automated electronic patient monitoring and data collection systems are used to collect real time physiological data over a plurality of sample times from physiological data monitors associated with units in a facility. Multiple servers receive the physiological data from the physiological data monitors. In the event that one of the servers does not record physiological data at a sample time, the system assesses whether another of the servers recorded physiological data at the sample time. If none of the servers record physiological data at the sample time, the system classifies the sample time as a time gap in the collection of physiological data. Collection performance of these systems is assessed based on a collection rate defined as a percentage of the sample times where physiological data is recorded.

SUMMARY

[0004] It is here recognized that conventional automated electronic patient monitoring and data collection systems are deficient, since they merely assess whether there is a time gap in the collection of physiological data at each sample time and do not take remedial action to diagnose and resolve the time gap. Consequently, the collection rate of conventional systems is limited. Collection rates in conventional systems range between 28% and 40% when using a single server and approximately 79% when multiple servers are connected redundantly, e.g. if one server does not record data, a backup server is relied upon to provide the recorded data. An advantage of the monitoring and data collection system described herein is that, in an experimental embodiment, the collection rate significantly improved to a range between 87% and 95% when using a single server and to 99.88% when multiple servers are connected redundantly.

[0005] In a first set of embodiments, a method is provided for monitoring collection of subject condition data. The method includes receiving a value of a parameter of subject condition data and a value of a sample time at each of a plurality of sample times from one or more servers. The value of the parameter and the value of the sample time is received on the one or more servers from a plurality of subject condition data monitors associated with a respective plurality of units in a facility. The method further includes storing the subject condition data from each unit in a data structure for a current sample time. The data structure includes a first field for holding data

indicating the current sample time. The data structure also includes a second field for holding data indicating a value of the parameter of subject condition data. The method further includes determining a time gap defined by a duration between the current sample time and a most recent sample time. The method further includes determining whether the time gap for each unit exceeds one or more time gap thresholds. The method further includes causing an apparatus to perform a remedial action based on the determining step.

[0006] In a second set of embodiments, non-transitory computer-readable medium is provided for storing a sequence of instructions and a data structure including two or more records, where each record includes two or more fields. Execution of the one or more sequences of instructions by one or more processors causes the one or more processors to perform one or more steps of the above method.

[0007] In a third set of embodiments, an apparatus is provided for monitoring collection of subject condition data. The apparatus includes a processor, a memory including one or more sequences of instructions and a data structure including two or more records and where each record includes two or more fields. The memory and the sequence of instructions are configured to, with the processor, cause the apparatus to perform one or more steps of the above method.

[0008] In a fourth set of embodiments, a method is provided for displaying subject condition data relating to monitoring a plurality of subjects in a respective plurality of units of a facility, where the plurality of units are divided into one or more groups of the facility. The method includes receiving a value of a parameter of subject condition data and a value of a sample time at each of a plurality of sample times from a plurality of subject condition data monitors associated with the respective plurality of units. The method further includes presenting a first indicator in each of a first plurality of active areas in a group region of a display, where each active area in the group region corresponds to a respective group of the facility. In response to a selection of a particular active area of the group region, the method further includes presenting a representation based on the value of the parameter of subject condition data in each of a second plurality of active areas in a unit region of the display, where each active area in the unit region corresponds to a respective unit within the group corresponding to the particular active area of the group region.

[0009] In a fifth set of embodiments, a method is provided for displaying subject condition data relating to monitoring a plurality of subjects in a respective plurality of units. The method includes receiving a value of a parameter of subject condition data and a value of a sample time at each of a plurality of sample times from a plurality of subject condition data monitors associated with the respective plurality of units. The method further includes presenting a first indicator in each of a first plurality of active areas in a thumbnail region of a display, where each active area in the thumbnail region corresponds to a respective unit. The method further includes presenting a trace of the value of the parameter of subject condition data over a time window encompassed by the plurality sample times in each of a second plurality of active areas of a trace region of the display. Each active area in the trace region corresponds to a respective parameter. The method further includes presenting a bar that indicates an occurrence of the value of the parameter over the time window in each of a third plurality of active areas of a bar region of the display. Each active area in the bar region corresponds to a respective parameter. The method further includes presenting points in an index plot over the time window in at least one active area in an index region of the display. Each active area in the index region corresponds to a respective index plot, where the points are based on a value of a first parameter of subject condition data and a value of a second parameter of subject condition data.

[0010] Still other aspects, features, and advantages are readily apparent from the following detailed description, simply by illustrating a number of particular embodiments and implementations, including the best mode contemplated for carrying out the invention. Other embodiments are also capable of other and different features and advantages, and its several details can be modified in various obvious respects, all without departing from the spirit and scope of the invention.

Accordingly, the drawings and description are to be regarded as illustrative in nature, and not as restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Embodiments are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings in which like reference numerals refer to similar elements and in which:

[0012] FIG. 1A is a block diagram that illustrates an example system for monitoring collection of physiological data, according to an embodiment;

[0013] FIG. 1B is a block diagram that illustrates an example system for monitoring collection of physiological data, according to an embodiment;

[0014] FIG. 1C is a block diagram that illustrates an example system for monitoring collection of physiological data, according to an embodiment;

[0015] FIG. 2 is a block diagram that illustrates an example data structure used to store physiological patient data, according to an embodiment;

[0016] FIG. 3A is an image that illustrates an example of a block of active areas on the display of FIG. 1A, according to an embodiment;

[0017] FIG. 3B is an image that illustrates an example of a region of the block of FIG. 3A, according to an embodiment;

[0018] FIG. 3C is an image that illustrates an example of a different region of the block of FIG. 3A, according to an embodiment;

[0019] FIG. 4A is a graph that illustrates a first example collection gap pattern of physiological data at the plurality of servers from the plurality of physiological data monitors of FIG. 1B, according to an embodiment;

[0020] FIG. 4B is a graph that illustrates a second example collection gap pattern of physiological data at the plurality of servers from the plurality of physiological data monitors of FIG. 1B, according to an embodiment;

[0021] FIG. 4C is a graph that illustrates a third example collection gap pattern of physiological data at the plurality of servers from the plurality of physiological data monitors of FIG. 1B, according to an embodiment;

[0022] FIG. 5A is a block diagram that illustrates an example of a group view for displaying physiological patient data, according to an embodiment;

[0023] FIG. 5B is a block diagram that illustrates an example of a unit view for displaying physiological patient data, according to an embodiment;

[0024] FIG. 5C is a block diagram that illustrates an example of a trace region of the unit view of FIG. 5B, according to an embodiment;

[0025] FIG. 5D is a block diagram that illustrates an example of a bar region of the unit view of FIG. 5B, according to an embodiment;

[0026] FIG. 5E is a block diagram that illustrates an example of an active area of the group view of FIG. 5A, according to an embodiment;

[0027] FIG. 6A is an image that illustrates an example of a trace of the trace region of FIG. 5B, according to an embodiment;

[0028] FIG. 6B is an image that illustrates an example of a bar of the bar region of FIG. 5B, according to an embodiment;

[0029] FIG. 6C is an image that illustrates an example of an index plot of the index region of FIG. 5B, according to an embodiment;

[0030] FIG. 6D is an image that illustrates an example of a trace of a value of a waveform

parameter of physiological patient data, according to an embodiment;

[0031] FIG. 7A is a flow diagram that illustrates an example of a method for monitoring collection of physiological data, according to an embodiment;

[0032] FIG. 7B is a flow diagram that illustrates an example of a method for displaying a group view of physiological data collected from a plurality of bed units divided into groups in a medical facility, according to an embodiment;

[0033] FIG. 7C is a flow diagram that illustrates an example of a method for displaying a unit view of physiological data collected from a plurality of bed units in a medical facility, according to an embodiment;

[0034] FIG. 8 is a block diagram that illustrates a computer system upon which an embodiment of the invention may be implemented;

[0035] FIG. 9 is a block diagram that illustrates a chip set upon which an embodiment of the invention may be implemented; and

[0036] FIG. 10 is a block diagram that illustrates a mobile terminal upon which an embodiment of the invention may be implemented.

DETAILED DESCRIPTION

[0037] A method and apparatus are described for monitoring collection of physiological data. Additionally, a method is described for presenting physiological data on a display. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that the present invention may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring the present invention.

[0038] Notwithstanding that the numerical ranges and parameters setting forth the broad scope are approximations, the numerical values set forth in specific non-limiting examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements at the time of this writing. Furthermore, unless otherwise clear from the context, a numerical value presented herein has an implied precision given by the least significant digit. Thus a value 1.1 implies a value from 1.05 to 1.15. The term “about” is used to indicate a broader range centered on the given value, and unless otherwise clear from the context implies a broader range around the least significant digit, such as “about 1.1” implies a range from 1.0 to 1.2. If the least significant digit is unclear, then the term “about” implies a factor of two, e.g., “about X” implies a value in the range from $0.5\times$ to $2\times$, for example, about 100 implies a value in a range from 50 to 200. Moreover, all ranges disclosed herein are to be understood to encompass any and all sub-ranges subsumed therein. For example, a range of “less than 10” can include any and all sub-ranges between (and including) the minimum value of zero and the maximum value of 10, that is, any and all sub-ranges having a minimum value of equal to or greater than zero and a maximum value of equal to or less than 10, e.g., 1 to 4.

[0039] Some embodiments of the invention are described below in the context of the collection of physiological data from a plurality of physiological data monitors associated with a respective plurality of bed units in a medical facility, such as a hospital with one or more vital signs monitors available for each bed. Other embodiments of the invention are described below in the context of the display of the collected physiological patient data. However, the invention is not limited to these contexts. In various embodiments, the medical facility is a hospital, a mobile medical unit, such as a helicopter, plane, boat, train, or ambulance and the monitoring equipment includes devices for generating electrocardiograms (EKGs), electroencephalograms (EEGs) and other indicators on the state or condition of a patient. In some embodiments, the monitors provide other indicators of the state of other kinds of subjects, such as various equipment. For example, in various embodiments the subject condition data indicates the voltage at multiple power generators,

or the central processor unit usage of various processors, or the rotation rate of various engines. As used herein the term “subject condition” refers to the conditions or state or function of a subject, including physiological data, like vital signs, for a patient of a medical facility. Furthermore, the term “unit” refers to a known location where a monitor is connected to a subject, such as a bed in a medical facility.

1. Overview for a Medical Facility

[0040] FIG. 1A is a block diagram that illustrates an example system **100** for monitoring collection of physiological data, according to an embodiment. The system **100** includes a plurality of subject condition data monitors **104a**, **104b** that are assigned to a respective plurality of units **102a**, **102b** in a facility, such as physiological monitors for bed units in a medical facility, as assumed for purposes of illustration in the following. In some embodiments, the system **100** excludes the bed units **102a**, **102b**. Although FIG. 1A depicts two bed units **102**, in some embodiments the system **100** includes more than two bed units **102** that are divided into more than one group within the medical facility. For example, the groups include a trauma resuscitation unit (TRU), an operating room (OR) and a neural trauma critical care (NTCC), as further discussed below. In some embodiments, the medical facility is a hospital. In other embodiments, the medical facility is any location where healthcare is provided including clinics, doctor's offices, urgent care centers, residential treatment centers, or geriatric care facilities.

[0041] At each of a plurality of sample times, the physiological data monitors **104a**, **104b** measure a value of a parameter of physiological patient data and transmit the measured value and a value of the sample time to a plurality of servers **105a**, **105b**. In some embodiments, the physiological data monitors **104a**, **104b**, the servers **105a**, **105b** and a controller are connected through a local network **180**. In some embodiments, the parameter of physiological patient data includes but is not limited to electrocardiogramatoplethysmographic (PPG), carbon dioxide (CO₂), arterial blood pressure (ABP), intracranial pressure (ICP), heart rate (HR), respiratory rate (RR), temperature, oxygen saturation (SP02) and end-tidal CO₂ (EtCO₂). Although FIG. 1A depicts two servers **105**, in some embodiments the system **100** includes one server **105** or more than two servers **105**. The controller **106** maintains a data structure for each server, such as data structure **120a** for data reported by server **105a** and data structure **120b** for data reported by server **105b**.

[0042] At each sample time, the measured value of the parameter of physiological patient data and the value of the sample time is transmitted from each server **105a**, **105b** to a controller **106**. FIG. 2 is a block diagram that illustrates an example of a data structure **200** used to store physiological patient data, according to an embodiment. The data structure **200** resides as one of the data structures **120a** or **120b**, described above, on a computer-readable medium, such as a memory of the controller **106**. In some embodiments, multiple data structures **200** are provided in the memory of the controller **106**, where a respective data structure **200** is used to store physiological patient data from a respective server **105**. The data structure **200** includes multiple records **202**, where a respective record **202** is used to store the physiological patient data at a respective sample time. In an example embodiment, the physiological patient data at a first sample time is stored in a first record **202a** and the physiological patient data at a second sample time is stored in a second record **202b**.

[0043] Each record **202** includes multiple fields including a first field **204** for holding data indicating a value of the sample times for each bed unit **102** when a recorded value of the parameter of physiological patient data was received from the server for the physiological data monitor **104** associated with each bed unit **102**. Each record **202** also includes a second field **206** for holding data indicating the value of the parameter of physiological patient data received from the server for the physiological data monitor **104** associated with each bed unit **102**. In some embodiments, each record **202** also includes a third field **208** for holding data indicating the parameter of physiological patient data received from the server for physiological data monitor **104** associated with each bed unit **102**.

[0044] Although processes, equipment, and data structures are depicted in FIG. 1A and FIG. 1B and FIG. 1C as integral blocks in a particular arrangement for purposes of illustration, in other embodiments one or more processes or data structures, or portions thereof, are arranged in a different manner, on the same or different hosts, in one or more databases, or are omitted, or one or more different processes or data structures are included on the same or different hosts.

[0045] Although data structures, messages and fields are depicted in FIG. 2, as integral blocks in a particular order for purposes of illustration, in other embodiments, one or more data structures or messages or fields, or portions thereof, are arranged in a different order, in the same or different number of data structures or databases in one or more hosts or messages, or are omitted, or one or more additional fields are included, or the data structures and messages are changed in some combination of ways.

[0046] In other embodiments, each bed unit **102** has a unique identifier. At each sample time, the physiological data monitor **104** associated with each bed unit **102** transmits the unique identifier to the server **105** which subsequently transmits the unique identifier to the controller **106**. In this embodiment, each record **202** also includes a fourth field **210** for holding data indicating the identifier for each bed unit **102**.

[0047] In other embodiments, each bed unit **102** has an admission status that indicates whether a patient is admitted (A) or discharged (D) from the bed unit **102**. In some embodiments, the admission status is changed by medical staff (e.g. nurse) using a manual switch when the patient is admitted or discharged. At each sample time, the physiological data monitor **104** associated with each bed unit **102** transmits the admission status to the server **105** which subsequently transmits the admission status to the controller **106**. In this embodiment, each record **202** also includes a fifth field **212** for holding data indicating the admission status for each bed unit **102**.

[0048] As illustrated in FIG. 1A, the controller **106** is configured to monitor the collection of physiological data and perform remedial action to diagnose and resolve detected gaps in the collection of physiological data and is connected to a display device **108**, or other device, to present some or all the data in the one or more data structures, or otherwise remediate the situation detected. The controller **106** includes a monitor of monitor module **107** to perform one or more steps of a method described below with reference to FIG. 7A. In various embodiments, the controller **106** comprises one or more general purpose computer systems, as depicted in FIG. 8 or one or more chip sets as depicted in FIG. 9 or one or more mobile terminals as depicted in FIG. 10, and instructions to cause the computer or chip set or mobile terminal to perform one or more steps of a method described below with reference to FIG. 7A.

[0049] In some embodiments, for a current sample time, the module **107** determines a time gap defined by a duration between the current sample time and a most recent sample time. In one embodiment, the current sample time and the most recent sample time are retrieved from the first field **204** data of the data structure **202**. In other embodiments, the time gap is stored in one of the fields (e.g. first field **204**) of the data structure **202**. In these embodiments, for the current sample time, the module **107** determines whether the time gap is greater than one or more time gap thresholds. The module **107** then causes the controller **106** to perform remedial action based on whether the time gap exceeds the one or more time gap thresholds. In some embodiments, the remedial action includes sending a communication to a person responsible for maintenance of the system, e.g., via email or text to a technician. In some embodiments, the remedial action involves transmitting a signal to the display **108** to present a plurality of indicators on the display **108** for each of the plurality of bed units **102**. Each indicator provides a status of the collection of physiological data from the respective bed unit **102**. In some embodiments, the indicator is color-coded based on whether the time gap for each bed unit **102** is greater than the one or more time gap thresholds. In some embodiments, the one or more time gap thresholds include a first time gap threshold (e.g. 5 minutes) and a second time gap threshold (e.g. 4 hours) that is greater than the first time gap threshold. In an embodiment, the color-coded indicator is a first colored indicator (e.g.

green), if the time gap for the bed unit **102** is less than the first time gap threshold. In another embodiment, the color-coded indicator is a second colored indicator (e.g. yellow), if the time gap for the bed unit **102** is greater than the first time gap threshold but less than the second time gap threshold. In another embodiment, the color-coded indicator is a third colored indicator (e.g. red), if the time gap for the bed unit **102** is greater than the second time gap threshold. In one embodiment, a value of the first time gap threshold is small enough to achieve a relatively fast response (e.g. presenting the second colored indicator on the display **108**) to an issue with the collection of physiological data. In another embodiment, the value of the first time gap threshold is large enough to avoid oversensitive response to insignificant network delays. In an example embodiment, the value of the first time gap threshold is in a range from about 2 minutes to about 10 minutes. In another example embodiment, the value of the second time gap threshold is in a range from about 1 hour to about 12 hours. In some embodiments, the values of the first time gap threshold and the second time gap threshold are adjustable.

[0050] FIG. **3A** through FIG. **3C** and FIG. **5A** through FIG. **5E** are diagrams of user interfaces utilized in the processes described herein, according to various embodiments. For example, FIG. **3A** is an image that illustrates an example of a block **300** of active areas **304** on the display **108** of FIG. **1A**, according to an embodiment. The screen includes one or more active areas **304** that allow a user to input data to operate on data. As is well known, an active area is a portion of a display to which a user can point using a pointing device (such as a cursor and cursor movement device, or a touch screen) to cause an action to be initiated by the device that includes the display. Well known forms of active areas are standalone buttons, radio buttons, check lists, pull down menus, scrolling lists, and text boxes, among others. Although areas, active areas, windows and tool bars are depicted in FIG. **3A** through FIG. **3C** and FIG. **5A** through FIG. **5E** as integral blocks in a particular arrangement on particular screens for purposes of illustration, in other embodiments, one or more screens, windows or active areas, or portions thereof, are arranged in a different order, are of different types, or one or more are omitted, or additional areas are included or the user interfaces are changed in some combination of ways.

[0051] As depicted in FIG. **3A**, in some embodiments, each active area **304** presents a color-coded indicator associated with a respective bed unit **102**. In some embodiments, the block **300** is specific to the physiological data provided by one server **105** and thus multiple blocks **300** can be generated based on the physiological data provided by the multiple servers **105**. In one embodiment, the block **300** is a rectangular array of active areas **304**. In another embodiment, the block **300** includes vertical columns or horizontal rows that are assigned to groups of bed units **102** within the medical facility. FIG. **3B** is an image that illustrates an example of a region **302a** of the block **300** of FIG. **3A**, according to an embodiment. In an embodiment, a first active area **304a** presents a green indicator and thus the bed unit **102** associated with the first active area **304a** has a time gap at the current sample time that is less than the first time gap threshold. In an embodiment, a second active area **304b** presents a red indicator and thus the bed unit **102** associated with the second active area **304b** has a time gap at the current sample time that is greater than the second time gap threshold. In other embodiments, the indicators presented in the active areas **304** include the unique identifier of the bed unit **102** (e.g. TOR5) indicated by the fourth field **210** data. In an example embodiment, the active areas **304** of the block **300** correspond to bed units **102** in a trauma resuscitation unit (TRU), an operating room (OR), a neurotrauma critical care unit (NTCC) and/or a multi-trauma critical care (MTCC) unit. In still other embodiments, the indicator presented in the active area **304a** includes the value of the parameter of physiological patient data (e.g., **88**) indicated by the second field **206** data. In still other embodiments, the indicator presented in the active area **304a** includes the admission status (e.g., A) indicated by the fifth field **212** data. In still other embodiments, the indicator presented in the active area **304b** includes the time gap (e.g., 6 h 51 m) calculated from the first field **204** data. In an example embodiment, the time gap is included in red and yellow indicators and the admission status and value of the parameter of physiological patient data are

included in green indicators. In some embodiments, the block **300** only depicts active areas **304** where the time gap exceeds one of the first or second time gap thresholds (e.g. the block **300** only displays active areas **304** corresponding to bed units **102** with abnormal collection status based on yellow or red indicators). An advantage of this embodiment is that the block **300** can effectively monitor a greater number of bed units **102** since only those bed units **102** with abnormal collection statuses are displayed. In other embodiments, where the number of active areas **304** is less than a number of bed units **102** being monitored (e.g. the number of bed units **102** in a medical facility or a group within the medical facility), the display toggles between a first block **300** and a second block **300** (or more than two blocks **300**) so that all of the bed units **102** are displayed over the two or more blocks **300** and where the toggle time between the blocks **300** is less than an incremental time when the physiological patient data is updated.

[0052] FIG. **3C** is an image that illustrates an example of a region **302b** of the block **300** of FIG. **3A**, according to an embodiment. In this embodiment, an active area **304c** within the region **302b** presents a color-coded indicator based on the parameter of physiological patient data (e.g. intracranial pressure, ICP) indicated by the third field **208** data. In another embodiment, the color-coded indicator is based on the value of the parameter of physiological patient data (e.g., heart rate, HR>120) indicated by the second field **206** data. In some embodiments, the color-coded indicator is other than a green indicator, a yellow indicator or a red indicator (e.g. pink color indicator).

[0053] In some embodiments, the user can view the values of the parameter of physiological patient data associated with a particular bed unit **102**. By an action of a pointing device the user selects a particular active area **304** associated with the particular bed unit **102**. In one embodiment, the display **108** is a touchscreen and the user touches the particular active area **304**. In response to this user action, the display **108** transmits a signal to the controller **106**, wherein the signal identifies the particular bed unit **102**. In some embodiments, a graphical user interface (GUI) module **109** of the controller **106** then transmits a signal to the display **108** including second field **206** data that indicate values of the parameter of physiological patient data from the particular bed unit **102**. In an example embodiment, a trace plot **600** (FIG. **6A**) is presented on the display **108** including the trace **608** of values of the parameter of physiological patient data from the particular bed unit **102**. In another example embodiment, a unit view **550** (FIG. **5B**) is presented on the display **108** of the particular bed unit **102**.

[0054] FIG. **1B** is a block diagram that illustrates an example system **150** for monitoring collection of physiological data, according to an embodiment. The system **150** of FIG. **1B** is similar to the system **100** of FIG. **1A**, with the exception that the system **150** includes three servers **105a**, **105b**, **105c** and a network **152** of more than two physiological data monitors **104**. In some embodiments, messages from the servers **105a**, **105b**, **105c** to the controller **106**, represented by curved lines in FIG. **1B**, travel through the same or similar network as the local network **180** of FIG. **1A**. Additionally, in some embodiments, the system **150** includes multiple screens that can be alternatively presented on a single display, or presented simultaneously on three different displays **108a**, **108b**, **108c**, which screens are used to perform distinct functions of the system **150**. In one embodiment, the display **108a** is used to present a screen comprising the block **300** of active areas **304**. In another embodiment, the display **108b** is used to present a screen comprising an interactive graphical user interface (GUI) with displayed physiological data. In another embodiment, the display **108c** is used to present a screen configured to diagnose a gap in the collection of physiological data from one or more bed units **102**. In an example embodiment, the display **108c** screen is used to diagnose an instance when the time gap exceeds the one or more time gap thresholds. In some embodiments, the single display **108** is used and thus the features of each screen described above for display **108a**, **108b**, **108c** are presented on the single display **108**. Additionally, the system **150** includes a workstation **154** that can be located at the medical facility or remote from the medical facility. In one embodiment, the workstation **154** is a medical workstation configured for medical personnel (e.g. nurses) and is located at the medical facility. In another embodiment, the

workstation **154** is configured for information technology (IT) personnel that are responsible for maintaining the connectivity of the system **150**.

[0055] FIG. **1C** is a block diagram that illustrates an example system **150'** for monitoring collection of physiological data, according to an embodiment. The system **150'** of FIG. **1C** is similar to the system **150** of FIG. **1B** with the exception that the system **150'** includes three waveform generators **156a**, **156b**, **156c** that generate a value of a waveform parameter of physiological patient data including but not limited to electrocardiogram and photoplethysmographic (PPG). In some embodiments, the waveform generator **156a** and data monitor **104a** are associated with the same bed unit **104a**, the waveform generator **156b** and data monitor **104b** are associated with the same bed unit **104b** and the waveform generator **156c** and data monitor **104c** are associated with the same bed unit **104c**. In these embodiments, the data monitors **104** measure a value of a parameter of physiological patient data other than the waveform parameter of physiological patient data. In an embodiment, the system **150'** features a triple modular redundancy architecture which permits fast switch over time and high system availability. In one embodiment, one server **105c** is selected as a principle or “backbone” server. If the selected backbone server **105c** fails, values from a second server **105a** or **105b** will fill in. If the selected backbone server **105c** and a second server **105a** fail, values from the third server **105b** fill in.

[0056] FIG. **4A** is a graph that illustrates an example of a collection gap pattern **400a** of physiological data at the plurality of servers **105a**, **105b**, **105c** from the plurality of physiological data monitors **104** of FIG. **1B**, according to an embodiment. Such a pattern can be presented on a screen for diagnosing gap patterns. The horizontal axis **402** represents time in arbitrary units. The vertical axis **404** represents distinct bed units **102** using the unique identifier. For each bed unit (e.g. TRU01, TRU02, etc), three data streams **406**, **408**, **410** represent recorded values of the parameter of physiological patient data received over time at the respective three servers **105a**, **105b**, **105c** and reported to the controller **106**. Grey bands indicate times when data is received from a server **105** but the physiological parameter value is absent, e.g., indicates a null value for the physiological parameter. This can occur when the monitor is in communication with the server **105**, but the subject is not connected to the monitor, e.g., has been taken to a radiology laboratory. The three different shades of grey indicate the three different servers of FIG. **1B**. A time gap **412** in the data stream **410a** for a first bed unit **102** (e.g. TRU04) indicates that no records were received by the server **105c** over the gap **412**. In some embodiments, the time gap **412** exceeds one or more time gap thresholds. FIG. **4A** depicts that the time gap **412** is present in the data stream **410** received at the third server **105c** for every bed unit. In some embodiments, the module **107** automatically determines that the time gap **412**, e.g., indicated by the first field **204** data for every bed unit **102** received from the server **105c** exceeds the time gap threshold and consequently determines that the server **105c** is offline. In this embodiment, the module **107** causes the controller **106** to perform a remedial action to resolve the time gap **412** and bring the server **105c** back online. In one embodiment, the remedial action involves automatically transmitting an alert including an indication that the server **105c** is offline. In an example embodiment, the alert is a communication message (e.g. email or text or both) to the workstation **154** that communicates to personnel at the workstation **154** that the server **105c** is offline. In response to receiving the alert, personnel at the workstation **154** respond to the time gap **412**, such as by rebooting the server **105c**. In other embodiments, the remedial action involves automatically transmitting a signal to the server **105c** to automatically reboot the server **105c**. In other embodiments, a user observing the collection gap pattern **400a** on the display **108** (or display **108c**) visually determines that the server **105c** is offline and subsequently transmits a communication message (e.g. email or text or both) to the workstation **154** to request that personnel at the workstation **154** bring the server **105c** back online. In other embodiments, the communication message is an auditory alert message delivered to the workstation **154**.

[0057] In some embodiments, the determination that the server **105c** is offline gleaned from the

collection gap pattern **400a** of FIG. 4A can be similarly derived from the block **300** of FIG. 3A. In some embodiments, when the server **105c** is offline, every active area **304** of the block **300** includes an indicator that the time gap exceeds the one or more time gap thresholds. In an example embodiment, when the server **105c** is offline, every active area **304** of the block **300** includes a yellow indicator (e.g. if the time gap >5 minutes but <4 hours) or a red indicator (e.g. if the time gap is >4 hours).

[0058] FIG. 4A depicts non-null values **414** of the parameter of physiological patient data (e.g. HR) within each respective data stream **406**, **408**, **410**. In some embodiments, non-null values **414** over a time period indicate a presence of a patient in the bed unit over that time period. Consequently, in some embodiments, the module **107** classifies a risk of loss of data collection for each time gap **412** based on whether the time gap **412** coincides with non-null values **414**. In some embodiments, the time gap **412** in the data stream **410b** from the TRU03 bed unit **102** (e.g. patient is present) may be classified as higher risk loss of data collection than the time gap **412** in the data stream **410a** from TRU04 bed unit **102** (e.g. patient may not be present). This visual feature of the collection gap pattern **400a** advantageously provides the user with information regarding potential data collection loss of each time gaps **412**. For example, on unit TRU01, no patient is connected to a monitor until the last portion of the time period, while, in unit TRU02 and TRU03, each patient is intermittently connected to a monitor, as agreed by all functioning servers. Similarly, no patient is connected to a monitor at unit TRU04 during the entire time interval depicted.

[0059] FIG. 4B is a graph that illustrates an example of a collection gap pattern **400b** of physiological data at the plurality of servers **105a**, **105b**, **105c** from the plurality of physiological data monitors **104** of FIG. 1B, according to an embodiment. In some embodiments, the module **107** stores physiological patient data (e.g. data stream **406**) from the server **105a** in a first data structure **200**, stores physiological patient data (e.g. data stream **408**) from the server **105b** in a second data structure **200**, and stores physiological patient data (e.g. data stream **410**) from the server **105c** in a third data structure **200**. The horizontal axis **402** represents time in arbitrary units. The vertical axis **404** represents the distinct bed units **102** using the unique identifier. A time gap **416** in the data stream **406b** from the server **105a** associated with a first bed unit **102** (e.g. TRU03) indicates that no record was received by the server **105a** over the time gap **416** from unit TRU03 only. In some embodiments, the time gap **416** exceeds the one or more time gap thresholds.

[0060] As depicted in FIG. 4B, no time gap is present in the data stream **406a** from the server **105a** associated with a second bed unit **102** (e.g. TRU04). Additionally, as depicted in FIG. 4B, no time gap is present in the data stream **408b** from the server **105b** associated with the first bed unit **102** (e.g. TRU03). Consequently, the time gap **416** is attributable to a disconnection between the first server **105a** and the physiological data monitor **104** associated with the first bed unit **102** (e.g. TRU03).

[0061] In some embodiments, the module **107** automatically determines that the time gap **416**, e.g. calculated from first field **204** data of the first data structure associated with the first bed unit **102** is greater than the at least one time gap threshold. Additionally, the module **107** automatically determines that time gaps calculated from the first field **204** data of the first data structure associated with the second bed unit **102** (e.g. data stream **406a**) do not include a time gap exceeding the time gap threshold. Additionally, the module **107** automatically determines that time gaps calculated from the first field **204** data of the second data structure associated with the first bed unit **102** (e.g. data stream **408b**) do not include a time gap exceeding the time gap threshold. Consequently, the module **107** automatically determines that there is a disconnection between the first server **105a** and the physiological data monitor **104** associated with the first bed unit **102** (e.g. TRU03).

[0062] The module **107** then causes the controller **106** to perform a remedial action to respond to the time gap **416**. In one embodiment, the remedial action involves automatically transmitting an alert including an indication that there is a disconnection between the first server **105a** and the

physiological data monitor **104** associated with the first bed unit **102**. In an example embodiment, the alert is a communication message (e.g. email or text or both) to personnel at the workstation **154**. In response to receiving the alert, personnel at the workstation **154** respond to the time gap **416**, by reconnecting the first server **105a** and the physiological data monitor **104** associated with the first bed unit **102**. In other embodiments, a user observing the collection gap pattern **400b** on the display **108** (or display **108c**) visually determines that the time gap **416** is attributable to a disconnection between the first server **105a** and the physiological data monitor **104** associated with the first bed unit **102** (e.g. TRU03). In this embodiment, the user subsequently transmits a communication message (e.g. email or text or both) to personnel at the workstation **154** to respond to the time gap **416** and reconnect the first server **105a** and physiological data monitor **104**. [0063] FIG. **4B** depicts non-null values **414** of the parameter of physiological patient data (e.g. HR) that can be used to classify the time gap **416** in a similar manner as in the collection gap pattern **400a**.

[0064] In some embodiments, the determination of a disconnection between the first server **105a** and the physiological data monitor **104** associated with the first bed unit **102** gleaned from the collection gap pattern **400b** of FIG. **4B** can be similarly derived from the block **300** of FIG. **3A**. In some embodiments, this disconnection is recognized when the block **300** associated with the server **105a** includes a first active area **304b** (e.g. TRU03 bed unit) indicating that the time gap exceeds the time gap threshold and a second active area **304a** (e.g. TRU04) that does not indicate that the time gap exceeds the time gap threshold. In an example embodiment, the disconnection is recognized when the first active area **304b** includes a yellow indicator or red indicator and the second active area **304a** includes a green indicator.

[0065] FIG. **4C** is a graph that illustrates an example of a collection gap pattern **400c** of physiological data at the plurality of servers **105a**, **105b**, **105c** from the plurality of physiological data monitors **104** of FIG. **1B**, according to an embodiment. The horizontal axis **402** represents time in arbitrary units. The vertical axis **404** represents the distinct bed units **102** using the unique identifier. A time gap **418** in the data streams **406c**, **408c**, **410c** from the respective servers **105a**, **105b**, **105c** associated with a first bed unit **102** (e.g. TRU02) indicates that no records were received from the first bed unit **102** over the time gap **418**. In some embodiments, the time gap **418** exceeds the one or more time gap thresholds. As depicted in FIG. **4C**, the time gap **418** is present in the data streams **406c**, **408c**, **410c** of each server **105a**, **105b**, **105c** associated with the first bed unit **102** (e.g. TRU02) and no time gap is present in the data streams **406b**, **408b**, **410b** of each server **105a**, **105b**, **105c** associated with a second bed unit **102** (e.g. TRU03). Consequently, the time gap **418** is attributable to a disconnection between every server **105a**, **105b**, **105c** and the physiological data monitor **104** associated with the first bed unit **102** (e.g. TRU02).

[0066] In some embodiments, the module **107** automatically determines that the time gap **418**, i.e. calculated from first field **204** data of the first data structure, second data structure and third data structure associated with the first bed unit **102** (e.g. TRU02) is greater than the at least one time gap threshold. Additionally, the module **107** automatically determines that time gaps calculated from the first field **204** data of the first data structure, second data structure and third data structure associated with the second bed unit **102** (e.g. TRU03) do not include a time gap exceeding the time gap threshold. Consequently, the module **107** automatically determines that there is a disconnection between every server **105a**, **105b**, **105c** and the physiological data monitor **104** associated with the first bed unit **102** (e.g. TRU02). The module **107** then causes the controller **106** to perform a remedial action to resolve the time gap **418**.

[0067] In one embodiment, the remedial action involves automatically transmitting an alert including an indication that there is a disconnection between each server **105a**, **105b**, **105c** and the physiological data monitor **104** associated with the first bed unit **102**. In an example embodiment, the alert is a communication message (e.g. email or text or both) to personnel at the workstation **154**. In response to receiving the alert, the personnel respond to the time gap **418**, by reconnecting

the servers **105a**, **105b**, **105c** and the physiological data monitor **104** associated with the first bed unit **102**. In other embodiments, a user observing the collection gap pattern **400c** on the display **108** (or display **108c**) visually determines that the time gap **418** is attributable to a disconnection between every server **105a**, **105b**, **105c** and the physiological data monitor **104** associated with the first bed unit **102** (e.g. TRU02). In this embodiment, the user subsequently transmits a communication message (e.g. email or text or both) to personnel at the workstation **154** to respond to the time gap **418** and reconnect each server **105a**, **105b**, **105c** and physiological data monitor **104**. FIG. 4C depicts non-zero values **414** of the parameter of physiological patient data (e.g. HR) that can be used to classify the time gap **418** in a similar manner as in the collection gap pattern **400a**.

[0068] In some embodiments, the determination of a disconnection between every server **105a**, **105b**, **105c** and the physiological data monitor **104** associated with the first bed unit **102** gleaned from the collection gap pattern **400c** of FIG. 4C can be similarly derived from the block **300** of FIG. 3A. In some embodiments, this disconnection is recognized when the multiple blocks **300** associated with each of the servers **105a**, **105b**, **105c** includes a first common active area **304b** (e.g. TRU02 bed unit) indicating that the time gap exceeds the time gap threshold and a second common active area **304a** (e.g. TRU03) that does not indicate that the time gap exceeds the time gap threshold. In an example embodiment, the first common active area **304b** includes a yellow indicator or red indicator and the second common active area **304a** includes a green indicator.

[0069] In an example embodiment, Table 1 below depicts a diagnosis for various collection gap patterns, including the collection gap patterns of FIGS. 4A-4C.

TABLE-US-00001 TABLE 1 Failure type MoMs indicator BedMaster 1. Individual bed unit Random cells in yellow/red software configuration error 2. BedMaster database error A block of cells in yellow/red; BedMaster server is online 3. BedMaster service down A block of cells in yellow/red; BedMaster service stopped BedMaster 1. BedMaster server down A block of cells in yellow/red; hardware BedMaster server is offline Network 1. BedMaster server Random cells in yellow/red connection failure

[0070] In another example embodiment, the monitor of monitor module **107** features software in a high level programming language (e.g. Matlab® R2014a, Mathworks, Boston MA) that preprocesses the physiological parameter data so that it is aligned in the time domain in the collection gap patterns depicted in FIGS. 4A-4C.

[0071] Although steps are depicted in FIGS. 7A-7C, as integral steps in a particular order for purposes of illustration, in other embodiments, one or more steps, or portions thereof, are performed in a different order, or overlapping in time, in series or in parallel, or are omitted, or one or more additional steps are added, or the method is changed in some combination of ways.

[0072] FIG. 7A is a flow diagram that illustrates an example of a method **700** for monitoring collection of physiological data, according to an embodiment. In step **702**, the value of the parameter of physiological patient data and the value of the sample time is received at the controller **106** from each server **105a**, **105b**. In one embodiment, step **702** is performed at each sample time. In an example embodiment, the sample times occur every 1 minute. In some embodiments, two servers **105a**, **105b** (FIG. 1A) are employed during step **702**. In other embodiments, one server **105** or more than two servers (e.g. FIG. 1B) are employed during step **702**. In some embodiments, at each sample time, the servers **105a**, **105b** each receive the value of the parameter of physiological patient data and the value of the sample time from each of the plurality of physiological data monitors **104** associated with the plurality of bed units **102**.

[0073] In step **704**, data is stored in the first field **204** of the data structure **200** that indicates the value of the sample time when the value of the parameter of physiological patient data is received in step **702**. In some embodiments, step **704** is performed at a current sample time and the value of the current sample time is stored in the first field **204**. Additionally, in step **704**, data is stored in the second field **206** that indicates the value of the parameter of physiological patient data received in

step **702**. Where values for more than one parameter of physiological patient data is received in step **702**, second field **206** data is stored that indicates these values in step **704**. In some embodiments, step **704** is performed at the current sample time and the value of the parameter of physiological patient data received at the current sample time is stored in the second field **206**. If no value is reported by the monitor for a particular physiological parameter, a null value is stored in the field. The field is recorded to indicate that a record was received from the server.

[0074] In step **705** a time gap is defined as the duration between the current sample time and a most recent sample time when a recorded value of the parameter of physiological patient data was received at step **702**. In some embodiments, in step **705**, the current sample time and the most recent sample time are retrieved from the first field **204**. In other embodiments, in step **704** the time gap is stored in one of the fields (e.g. first field **204**) of the data structure **200** and step **705** is omitted.

[0075] In step **706**, a determination is made at the current sample time regarding the time gap determined in step **705**. In one embodiment, in step **706**, a determination is made whether the time gap calculated by the first field **204** data exceeds one or more time gap thresholds stored in a memory of the controller **106**. In an example embodiment depicted in FIG. 3A, the time gap threshold is the first time gap threshold (e.g. 5 minutes). In another example embodiment, the time gap threshold is the second time gap threshold (e.g. 4 hours) that is longer than the first time gap threshold. In some embodiments, in step **706**, the determination further includes a determination of a cause of the time gap exceeding the one or more time gap thresholds. In an example embodiment, in step **706**, the determination is made whether the time gap exceeding the time gap threshold is attributable to one of the servers **105** being offline (FIG. 4A). In another example embodiment, in step **706**, the determination is made whether the time gap exceeding the time gap threshold is attributable to a disconnection between one of the servers **105** and the physiological data monitor **104** associated with one of the bed units **102** (FIG. 4B). In another example embodiment, in step **706**, the determination is made whether the time gap exceeding the time gap threshold is attributable to a disconnection between every server **105** and the physiological data monitor **104** associated with one of the bed units **102** (FIG. 4C). If the determination in step **706** is negative, then the method **700** proceeds back to step **702**. If the determination in step **706** is positive, then the method **700** proceeds to step **708**.

[0076] In step **708**, an alert is generated that the time gap exceeds one or more time gap thresholds. In one embodiment, the alert is generated by presenting the block **300** of active areas **304** on the display **108**, where the color-coded indicator within each active area **304** is based on the determination of step **706**. In other embodiments, the alert is generating by transmitting a communication message (e.g. email or text or both) to personnel at the workstation **154** to respond to the time gap. In an example embodiment, the communication message identifies the one or more bed units **102** where the time gap exceeds the time gap threshold. In another example embodiment, where the determination in step **706** includes a determination of the cause of the time gap exceeding the time gap threshold, the communication message identifies the determined cause (e.g. server **105** is offline, physiological data monitor **104** is disconnected from server **105**, etc.).

[0077] In step **710**, remedial action is initiated based on the generated alert of step **708**. In one embodiment, the remedial action includes responding to the time gap that exceeds the one or more time gap thresholds. In one embodiment, where the communication message from step **708** identifies one or more bed units **102** where the time gap exceeds the time gap threshold, the remedial action involves checking the status of the physiological data monitors **104** associated with the one or more bed units **102** to ensure the physiological data monitors **104** are functional. In other embodiments, the remedial action involves checking that the one or more servers **105** are online and rebooting any servers **105** that are identified as offline. In one embodiment, where the communication message from step **708** identifies that the cause of the time gap exceeding the time gap threshold is that one or more servers **105** is offline, the remedial action involves verifying that

the one or more servers **105** are offline and rebooting the one or more servers **105**. In yet another embodiment, where the communication message from step **708** identifies that the cause of the time gap exceeding the time gap threshold is a disconnection between one or more servers **105** and a physiological data monitor **104** of one of the bed units **102**, the remedial action involves checking the connection between the one or more servers **105** and the physiological data monitor **104** and reconnecting the one or more servers **105** with the physiological data monitor **104**. After performing the remedial action in step **710**, the method **700** proceeds back to step **702**. In step **706**, the determination of whether the time gap exceeds the time gap threshold is repeated, in order to verify whether the remedial action in step **710** was effective in eliminating the time gap.

[0078] As illustrated in FIG. **1A**, the controller **106** is connected to the display **108**, to present the physiological patient data. In some embodiments, the display **108** is the same as the display **108** used to present the indicators for each bed unit **102** (e.g. the block **300** of active areas **304**) for monitoring collection of the physiological patient data. In other embodiments, the controller generates a separate screen that is presented on the same or a separate display, e.g., display **108b** (FIG. **1B**) to present the physiological patient data, where the separate screen is configured for viewing by medical professionals to determine the state or care, or both, of a patient in one or more of the bed units. In some embodiments, it is advantageous for the screen to be presented on the display **108b** that is separate from the display **108a** used to present the indicators for each bed unit **102** to monitor the collection of physiological patient data.

[0079] In some embodiments, the controller **106** receives the value of the parameter of physiological patient data and the value of the sample time from the servers **105a**, **105b**. In other embodiments, the servers **105a**, **105b** are omitted and the controller **106** receives the value of the parameter of physiological patient data and the value of the sample time from the physiological data monitors **104**. The controller **106** includes a graphical user interface (GUI) module **109** to perform one or more steps of a method described below with reference to FIG. **7B** or a method described below with reference to FIG. **7C**. In various embodiments, the controller **106** comprises one or more general purpose computer systems, as depicted in FIG. **8** or one or more chip sets as depicted in FIG. **9**, and instructions to cause the computer or chip set to perform one or more steps of a method described below with reference to FIG. **7B** or FIG. **7C**. In some embodiments a screen is generated for presentation on a display to present physiological patient data related to monitoring a plurality of patients in a respective plurality of bed units **102** of a medical facility. In some embodiments, the plurality of bed units **102** are divided into one or more groups or clinical divisions of the medical facility. In one embodiment, the groups include a trauma resuscitation unit (TRU), an operating room (OR), and a neural trauma critical care (NTCC).

[0080] FIG. **5A** is a block diagram that illustrates an example of a group view **500** for displaying physiological data of patients in a single group of the medical facility, according to an embodiment. In one embodiment, the group view **500** is a screen that includes an indicator in a plurality of active areas **504a**, **504b** in a group region **502**. In some embodiments, each active area **504** corresponds to a respective group in the medical facility. In some embodiments, the indicator in each active area **504** is an acronym of the name of the group (e.g. TRU for trauma resuscitation unit). In other embodiments the indicator is a thumbnail image or icon representing the group. In other embodiments, multiple active areas **504** correspond to a respective group in the medical facility. Although FIG. **5A** depicts five active areas **504**, the group region **502** is not limited to five active areas **504** and can include more or less active areas **504** in order to match the number of groups in the medical facility.

[0081] The group view **500** further includes a plurality of active areas **506a**, **506b**, **506c**, **506d** in a unit region **505**, where each active area **506** corresponds to a respective bed unit **102** in a particular group associated with a particular active area **504a** in the group region **502**. In one embodiment, in response to a selection by a single or other action of a pointing device within the particular active area **504a**, the value of the parameter of physiological patient data for each bed unit **102** in the

particular group is displayed in a respective active area **506**. In some embodiments, in response to the selection of the particular active area **504a**, a representation of the value of the parameter of physiological patient data is presented in the respective active area **506**. In one embodiment, the representation is a trace **608** (FIG. **6A**) of the value of the parameter of physiological patient data along a time axis. In another embodiment, the representation is a bar **656** (FIG. **6B**) that indicates an occurrence of the value of the parameter of physiological patient data along a time axis. In an example embodiment, a first color (e.g. green) of the trace or bar indicates that the value of the parameter is below a first threshold value and a second color (e.g. yellow, red) of the trace or bar indicates that the value of the parameter is above a second threshold value. In one example embodiment, the first threshold value is the same as the second threshold value. In another example embodiment, the first threshold value is not the same as the second threshold value and a third color (e.g. yellow) of the trace or bar indicates that the value of the parameter is above the first threshold value and below the second threshold value. In an example embodiment, the display **108** is a touchscreen and the single action of selecting the particular active area **504a** is touching the particular active area **504a**.

[0082] In some embodiments, the unit region **505** includes a fixed number of active areas **506**. In these embodiments, where the number of bed units **102** in the single group exceeds the fixed number of active areas **506**, multiple active areas **504** in the group region **502** are used to designate a single group. In an example embodiment, the indicator in the multiple areas **504** include an acronym for the group and an alpha or numeric character or other indicator, such as color or hatching, to represent a subgroup within the single group (e.g. TRU-A and TRU-B). Although FIG. **5A** depicts that the unit region **505** includes a specific fixed number (e.g., four) active areas **506**, the unit region **505** is not limited to this fixed number of active areas and can feature less or more fixed number of active areas **506**. Additionally, in other embodiments, the unit region **505** includes an automatically or manually adjustable number of active areas **506**, where a size of each active area **506** changes based on the number of active areas **506** (e.g., larger active area **506** for a smaller number of active areas **506** and a smaller active area **506** for a larger number of active areas **506**).

[0083] FIG. **5E** is a block diagram that illustrates an example of the active area **506** of the group view **500** of FIG. **5A**, according to an embodiment. In one embodiment, the active area **506** includes a trace region **556** where one or more traces of the values of the parameter of physiological patient data is plotted against time. FIG. **5C** is a block diagram that illustrates an example of the trace region **556** of FIG. **5E**, according to an embodiment. In one embodiment, the trace region **556** includes a plurality of active areas **557a**, **557b**, where each active area **557** corresponds to a respective parameter of physiological patient data. In an example embodiment, where there is a limited number of active areas **557a**, **557b**, parameters of physiological patient data with higher priority are displayed first and parameters of physiological patient data with lower priority are displayed if active areas **557a**, **557b** remain after the higher priority parameters are displayed. In an example embodiment, a trace plot of the values of a first parameter of physiological patient data against time is presented in the first active area **557a** and a trace plot of the values of a second parameter of physiological patient data against time is presented in the second active area **557b**. FIG. **6A** is an image that illustrates an example of a trace plot **600** of the trace region **556** of FIG. **5C**, according to an embodiment. The horizontal axis **602** indicates time in units of (hour:minutes) spanning a 24 hour range from 12:00 PM to 12:00 PM. In other embodiments, the range of the horizontal axis **602** can be selected. In an example embodiment, the range can be selected from a minimum value of about 1 minute to a maximum value based on the plurality of sample times for the stored physiological patient data. The vertical axis **604** indicates the parameter of physiological patient data in relevant units (e.g., beats per minute for heartrate). The trace plot **600** includes a trace **608** of the values of the parameter of physiological patient data over a time window **606** encompassing at least some of the plurality of sample times that the controller **106** receives the values of the parameter of physiological patient data. In an example

embodiment, the time window **606** is about 24 hours. In some embodiments, a color of the trace **608** changes from a first color to a second color when the value of the parameter of physiological patient data exceeds each of one or more threshold values **609**. In an example embodiment, the color of the trace **600** changes from green to yellow at a first threshold value **609a** and from yellow to red when the value **608** of the parameter exceeds a second threshold value **609b**. That is the trace has one color at values below each threshold value and a different color at values above the threshold value. In an example embodiment, where the parameter of physiological patient data is heart rate, the first threshold value **609a** is 100 beats per minute and the second threshold value **609b** is approximately 120 beats per minute. In some embodiments, not only is the trace given and the color appropriate for the value, but areas below the trace and above the first threshold value **609a** are filled with the corresponding color, as depicted in FIG. 6A.

[0084] One notable advantage of the group view **500** is that a user simultaneously views the traces **600** of each patient in a particular group by viewing the active areas **506a**, **506b**, **506c**, **506d** and prioritizes which patients require more time and attention. In an example embodiment, if the traces **600** in active areas **506a**, **506b** are red colored, whereas the traces **600** in the active areas **506c**, **506d** are green colored, the user can decide to spend more time with the patients associated with active areas **506a**, **506b**. This improves the efficiency of physicians and medical staff in the medical facility and improves the quality of care provided to patients that require more time and attention. Because these are active areas, in some embodiments, by selecting the active area corresponding to one unit with a pointing device, an expanded view of a single unit is presented on the display; and, the presentation of other units are reduced, as described below with reference to FIG. 5B.

[0085] In some embodiments the values plotted in a trace are the values of an “index” which is an indication of a particular condition of the subject that is a function of two or more physiological parameters. In some example embodiments, the index value is a ratio of a value of a first parameter of physiological patient data to a value of a second parameter of physiological patient data. In an example embodiment, the trace **608** indicates an index value that is of a shock index (SI) that is a ratio of a value of heart rate (HR) to a value of systolic blood pressure (SBP). In another example embodiment, the index value is a value of a brain trauma index (BTI) that is a ratio of a value of intracranial blood pressure (ICP) to a value of cerebral perfusion pressure (CPP).

[0086] In another embodiment, the active area **506** of FIG. 5E includes a bar region **558** where a one dimensional bar plot that indicates a time history of range of the value of the parameter of physiological patient data is displayed as a bar with color that can change along the time axis. FIG. 5D is a block diagram that illustrates an example of the bar region **558** of FIG. 5E, according to an embodiment. In one embodiment, the bar region **558** includes a plurality of active areas **559a**, **559b**, where each active area **559** corresponds to a respective parameter of physiological patient data. In an example embodiment, a bar plot of the value range of a first parameter of physiological patient data is displayed in the first active area **559a** and a bar plot of the value range of a second parameter of physiological patient data is displayed in the second active area **559b**. FIG. 6B is an image that illustrates an example of a bar plot **650** of the bar region **558** of FIG. 5D, according to an embodiment. The horizontal axis **602** is time in units of (hour:minutes) spanning a 24 hour range from 12:00 PM to 12:00 PM. In other embodiments, the range of the horizontal axis **602** can be selected. In an example embodiment, the range can be selected from a minimum value of about 1 minute to a maximum value based on the plurality of sample times for the stored physiological patient data. As a one dimensional plot, there is no vertical axis. The bar plot **650** includes a bar **656** that is colored based on the value range of the parameter of physiological patient data over the time window **606**. In some embodiments, a color of the bar **656** indicates the value range such that a first color indicates that the range of the value of the parameter of physiological patient data is in a first range (e.g. less than a first threshold value), a second color indicates that the range of the value of the parameter of physiological patient data is in a second range (e.g. greater than the first

threshold value but less than a second threshold value) and a third color indicates that the range of the value of the parameter of physiological patient data is in a third range (e.g. greater than the second threshold value). In an example embodiment, the first color is green, the second color is yellow and the third color is red and the first and second thresholds correspond to those used in the trace plot **600** of FIG. **6A**. An advantage of the bar plot is that more different physiological parameters can be presented in the same area of the display device because there is no vertical axis. Thus more parameters can be presented per unit in the group. Only one or a few traces can be plotted or only the one or few traces that exceed a first or second threshold are plotted in the trace plot region.

[0087] In some embodiments, the value range is a range of a ratio of a value of a first parameter of physiological patient data to a value of a second parameter of physiological patient data. In an example embodiment, the value range is a range of the shock index (SI) or of the brain trauma index (BTI).

[0088] Returning to FIG. **5A**, in some embodiments, a plurality of active areas **510a**, **510b** are displayed in a time interval region **508** of the group view **500**. In one embodiment, an indicator is displayed in each active area **510**, where the indicator is a time interval value. In some embodiments, upon selecting a particular active area **510a** by a single action of a pointing device, the interval of the time window **606** of the trace plots **600** in the trace region **556** and the bar plots **650** in the bar region **558** is adjusted based on the time interval value in the particular active area **510a**. In one embodiment, the time interval value of the active areas **510** include one or more of 1 hour, 2 hours, 4 hours, 8 hours, 12 hours, 24 hours, 48 hours and 72 hours.

[0089] In some embodiments, the group view **500** includes a particular arrangement where the group region **502** is presented on a left side of the display **108**, the time region **508** is presented in a bottom portion of the display and the unit region **505** is presented to a right side of the group region **502** and above the time region **508**. However, this is merely one example arrangement and other embodiments of the group view **500** can feature different rearrangements of the group region **502**, time region **108** and unit region **505**.

[0090] FIG. **7B** is a flow diagram that illustrates an example of a method **720** for displaying the group view **500** of physiological data collected from the plurality of bed units **102** divided into groups in a medical facility, according to an embodiment. In step **722**, the value of the parameter of physiological patient data and the value of the sample time is received at the controller **106**. In some embodiments, the value of the parameter of physiological patient data and the value of the sample time is received at the controller **106** from each server **105**. In other embodiments, the value of the parameter of physiological patient data and the value of the sample time is received from the plurality of physiological data monitors **104** associated with the plurality of bed units **102** divided into the one or more groups of the medical facility without use of the server or the controller.

[0091] In step **724**, indicators in the active areas **504** of the group region **502** are presented, where each active area **504** corresponds to a respective group within the medical facility. In some embodiments, where a fixed number of active areas **506** are provided in the unit region **505** and the number of bed units **102** within a particular group exceeds the fixed number, multiple active areas **504** correspond to the respective group within the medical facility.

[0092] In step **726**, data is received based on a selection of a particular active area **504a** of the group region **502**. In an embodiment, the particular active area **504a** of the group region **502** is selected by a single or other action of a pointing device. In one embodiment, the display **108** is a touchscreen and the single action of the pointing device involves touching the particular active area **504a**. In an example embodiment, the particular active area **504a** is selected in order to monitor the values of the parameter of physiological patient data of bed units **102** in the group corresponding to the particular active area **504a**. In an embodiment, in step **726**, the controller **106** receives a signal from the display **108** based on the selection of the particular active area **504a** of the group region **502**.

[0093] In step **728**, a representation based on the value of the parameter of physiological patient data is displayed in the active areas **506** of the unit region **505**, where each active area **506** corresponds to a respective bed unit **102** within the group that corresponds to the particular active area **504a** selected in step **726**. In some embodiments, in step **728**, the trace plot **600** of the trace **608** of the parameter values against time of the physiological patient data is displayed in the trace region **556** of the active area **506**. In an example embodiment, in step **728**, multiple trace plots **600** are displayed in multiple active areas **557a**, **557b** of the trace region **556**, where each trace plot **600** in each active area **557** corresponds to a respective parameter of physiological patient data.

[0094] In some embodiments, in step **728**, the bar plot **650** of the parameter of the physiological patient data is displayed in the bar region **558** of the active area **506**. In an example embodiment, in step **728**, multiple bar plots **650** are displayed in multiple active areas **559a**, **559b** of the bar region **558**, where each bar plot **650** in each active area **559** corresponds to a respective parameter of physiological patient data.

[0095] In one embodiment, in response to a selection by a single or other action of a pointing device within a particular unit active area **506a** in the group view **500**, the value of the physiological patient data for the bed unit **102** corresponding to the particular active area **506a** is displayed in a different screen called unit view **550**. FIG. 5B is a block diagram that illustrates an example of the unit view **550** for displaying physiological patient data, according to an embodiment. In one embodiment, the unit view **550** includes an indicator in a plurality of active areas **554a**, **554b** in a thumbnail region **552**. In some embodiments, each active area **554** corresponds to a respective bed unit **102** within the group corresponding to the selected active area **504a** in the group view **500**. In some embodiments, the indicator in each active area **554** is a thumbnail image of the traces and bars presented in the active area **506** of the unit region **505** corresponding to the respective bed unit **102**.

[0096] The unit view **550** further includes the trace region **556** with the plurality of active areas **557** (FIG. 5C), where each active area **557** corresponds to a respective parameter of physiological patient data. In an embodiment, the trace plot **600** of the trace **608** of the parameter of physiological patient data is displayed in the active area **557** of the trace region **556**, where the physiological patient data corresponds to the bed unit **102** associated with the particular active area **506a** selected in the group view **500**.

[0097] Additionally, the unit view **550** includes the bar region **558** with the plurality of active areas **559** (FIG. 5D), where each active area **559** corresponds to a respective parameter of physiological patient data. In an embodiment, the bar plot **650** of the bar of colored or cross-hatched value ranges of the parameter of physiological patient data is displayed in each active area **559** of the bar region **558**, where the physiological patient data corresponds to the bed unit **102** associated with the particular active area **506a** selected in the group view **500**.

[0098] In other embodiments, in response to a selection by a single or other action of a pointing device within a particular active area **554a** in the thumbnail region **552**, the value of the physiological patient data for the bed unit **102** corresponding to the particular active area **554a** is displayed in the unit view **550**.

[0099] In one embodiment, the unit view **550** further includes one or more active areas **562a**, **562b** in an index region **560**. In one embodiment, a scatter index plot rather than a time series is presented in each active area **562**. In a scatter plot, data points are plotted based on a value of a first parameter of physiological patient data on one axis and a value of a second parameter of physiological patient data on the perpendicular axis. In an example embodiment, the index plot is a shock index (SI) plot where the first parameter of physiological patient data is heart rate (HR) and the second parameter of physiological patient data is systolic blood pressure (SBP). In another example embodiment, the index plot is a brain trauma index (BTI) plot, where the first parameter of physiological patient data is intracranial blood pressure (ICP) and the second parameter of physiological patient data is cerebral perfusion pressure (CPP). FIG. 6C is an image that illustrates

an example of an index plot **670** of the index region **560** of FIG. **5B**, according to an embodiment. The horizontal axis **672** is a first parameter of physiological patient data (e.g. heartrate) in units of the parameter (e.g. beats per minute) in a range from about 80 beats per minute to about 138 beats per minute. The vertical axis **674** is a second parameter of physiological patient data (e.g. systolic blood pressure, SBP) in units of the parameter (e.g. millimeters of Mercury). In some embodiments, a range of the second parameter of physiological patient data is dynamically determined by minimum and maximum values acquired over the time window **606**. In some embodiments, the index plot **670** includes data points **682** that have coordinates (x, y) where x is a value of the first parameter of physiological patient data along the horizontal axis **672** and y is a value of the second parameter of physiological patient data along the vertical axis **674**. In some embodiments, the index plot **670** includes a color coded time axis **676** such that a sample time of each data point **682** can be color coded according to the color coded time axis **676**. The time window **606** defines the range of the coded time axis **676**. In an example embodiment, the time window **606** is about 24 hours. In one embodiment, the coded time axis **676** is a color coded time axis and each data point **682** is color coded based on the respective sample time of each data point **682** and the color coded time axis **676**. In an example embodiment, the color coded time axis **676** is a color spectrum that extends from a red color to designate more recent sample times to a blue color to indicate earlier sample times. In this example embodiment, the data points **682** during recent sample times are color coded red whereas the data points **682** during previous sample times are color coded blue. FIG. **6C** depicts lines that correlate color coded portions of the time axis **676** and respective data points **682** of the plot **670**.

[0100] As illustrated in FIG. **6C**, in one embodiment the index plot **670** includes one or more vertical intercept lines **678** that intersect the horizontal axis **672** to indicate one or more respective threshold values of the first parameter of physiological patient data. In another embodiment, the index plot **670** includes one or more horizontal intercept lines **680** that intersect the vertical axis **674** to indicate one or more respective threshold values of the second parameter of physiological patient data. The vertical intercept lines **678** and horizontal intercept lines **680** advantageously allow the user to determine whether data points **682** are within a region of the plot **670** defined by the intercept lines **678**, **680**. In an example embodiment, where the index plot **670** is a shock index (SI) plot, the intercept lines **678**, **680** allow the user to determine whether the data points **682** are within a region of concern **673** defined by a vertical intercept line **678** and horizontal intercept line **680**. In another example embodiment, the color coded points **682** based on the time axis **676** advantageously permit the user to determine whether the points **682** are trending toward the region of concern **673**.

[0101] As illustrated in FIG. **5B**, in one embodiment the unit view **550** further includes a plurality of active areas **570a**, **570b** in an action region **568**. In an embodiment, an action indicator is displayed in each active area **570a**, **570b**. In one embodiment, in response to selection of the active area **570a** by a single or other action of a pointing device, an image file of the unit view **550** is generated and stored in a memory of the controller **106**. In one embodiment, the image file of the unit view **550** represents an image of the thumbnail region **552**, the trace region **556**, the bar region **558** and the index region **560** at the time that the active area **570a** is selected. In an example embodiment, the action indicator in the active area **570a** is “snapshot”.

[0102] In one embodiment, in response to selection of the active area **570b** by a single or other action of a pointing device, the value of a waveform parameter of physiological patient data is displayed over a secondary time window **606'** that is less than the time window **606**. In some embodiments, the value of the waveform parameter of physiological patient data is provided to the server **105** by the waveform generators **156a**, **156b**, **156c**. This option is useful for traces that are better viewed on a much expanded time axis, such as an EKG. FIG. **6D** is an image that illustrates an example trace plot **600'** of a trace **608'** of values of a waveform parameter of physiological patient data, according to an embodiment. In this embodiment, the parameter of physiological

patient data is an EKG waveform parameter of physiological patient data. In an embodiment, the value of the waveform parameter of physiological patient data is displayed in one of the active areas **557** of the trace region **556**. In an example embodiment, the waveform parameter of physiological patient data is an electrocardiogram or a photoplethysmographic (PPG). In another example embodiment, the secondary time window **606'** is less than 1 hour. In another example embodiment, the secondary time window **606'** is less than 10 minutes.

[0103] In some embodiments, the time window **606** of the traces **600** in the trace region **556**, the bars **650** in the bar region **558** and the index plot **670** in the index region **560** can be adjusted. In one embodiment, the time window **606** is adjusted by selecting an active area **566a**, **566b** in a time interval region **564** of the unit view **550**, where each active area **566** includes a time interval value. Upon selecting a particular active area **566a**, the time window **606** is adjusted based on the time interval value within the particular active area **566a**. In one embodiment, the time interval value of the active areas **566** include one or more of 1 hour, 2 hours, 4 hours, 8 hours, 12 hours, 24 hours, 48 hours and 72 hours. In another embodiment, the time window **606** is adjusted by manually selecting a secondary time window within the time window **606** by a single action of a pointing device. In response to this manual selection of the secondary window within the time window **606**, the trace plots **600** in the trace region **556**, bar plots **650** in the bar region **558** and index plot **670** in the index region **560** are displayed over the secondary time window.

[0104] In some embodiments, highlighting one or more areas (e.g. moving cursor to one or more areas with the pointing device **816** such as a mouse) along one or more of the trace **600**, the bar plot **650** and/or the index plot **670**, generates an output on the display of a value of the respective trace/bar plot/index plot and/or a value of the time associated with the highlighted trace/bar plot/index plot value. In one embodiment, highlighting the one or more areas further displays a vertical line along the trace/bar plot/index plot at the respective time value.

[0105] In some embodiments, the unit view **550** further includes a home region **572** with an active area **574**. In one embodiment, an indicator is displayed in the active area **574**. In an example embodiment, the indicator is a home symbol. Upon selecting the active area **574** by a single or other action of a pointing device, the display **108** switches from the unit view **550** of FIG. 5B to the group view **500** of FIG. 5A.

[0106] FIG. 7C is a flow diagram that illustrates an example of a method **730** for displaying the unit view **550** of physiological data collected from the plurality of bed units **102** in a medical facility, according to an embodiment. In step **732**, the value of the parameter of physiological patient data and the value of the sample time is received at the controller **106** from the plurality of physiological data monitors **104**. In some embodiments, in step **732**, the value of the parameter of physiological patient data and the value of the sample time is received at the controller **106** from the servers **105**, which in turn received the data from the plurality of physiological data monitors **104**.

[0107] In step **734**, an indicator is displayed in the active areas **554** of the thumbnail region **552** of the unit view **550**, where each active area **554** corresponds to a respective bed unit **102**. In some embodiments, each active area **554** corresponds to a respective bed unit **102** in the group associated with the selected active area **504** in the group region **502** of the group view **500**. In some embodiments, the indicator in each active area **554** is the active area **506** of the unit region **505** corresponding to the respective bed unit **102**.

[0108] In step **736**, the trace plot **600** including the trace **608** of the value of the parameter of the physiological patient data is displayed in the active areas **557** of the trace region **556**, where each active area **557** corresponds to a respective parameter of physiological patient data. In some embodiments, in step **736**, the trace **600** is a value of an index parameter based on a function, such as a ratio, of a value of a first parameter of physiological patient data and a value of a second parameter of physiological patient data.

[0109] In step **738**, the bar plot **650** including that the bar **656** that indicates a range of the value of

the parameter of the physiological patient data is displayed in the active areas **559** of the bar region **558**, where each active area **559** corresponds to a respective parameter of physiological patient data. In some embodiments, in step **738**, the bar **656** color indicates a value range of an index parameter based on a ratio of a value of a first parameter of physiological patient data to a value of a second parameter of physiological patient data.

[0110] In step **740**, one or more scatter index plots **670** are displayed in the active areas **562** of the index region **560**, where each active area **562** corresponds to a respective index plot **670** of a respective index parameter of physiological patient data. In an embodiment, the index parameter is shock index (SI) or brain trauma index (BTI). Data points **682** of the index plot **670** are presented, where each data point **682** is based on a value of a first parameter of physiological patient data and a value of a second parameter of physiological patient data. In some embodiments, the data points **682** of the index plot **670** have (x, y) coordinates, where x is the value of the first parameter of physiological patient data and y is the value of the second parameter of physiological patient data.

[0111] In some embodiments, based on the physiological patient data received at the controller **106**, any predictive algorithm known in the art could be used to make a prediction regarding future physiological patient data or recommend treatment of the patient. In an example embodiment, such a prediction or recommendation could be presented on the screen view presented on any display **108**. An example of such a predictive algorithm is disclosed in Provisional Application No. 62/334,750 filed on May 11, 2016 and with a common assignee with the present invention.

2. Example Embodiments

[0112] In one embodiment, the system **100**, **150** is utilized and/or the method **700**, **720**, **730** is practiced in a military medical transport facility, such as a military medical transport vehicle. Conventional military medical transport vehicles routinely feature limited medical staff and thus involve limited access to patients and equipment instability (e.g. data monitors **104** and servers **105**) in a noisy and moving environment. Additionally, conventional military medical transport vehicles do not feature remote monitoring of current values of the parameter of physiological patient data from the data monitors **104**. The implementation of the system **100**, **150** and/or the method **700**, **720**, **730** in military medical transport vehicles addresses these issues by permitting the limited medical staff to monitor more patients in a shorter amount of time and/or to quickly detect and remedy any equipment instability.

[0113] In one embodiment, the controller **106** of the system **100**, **150** is an Intel i5 1.9 GHZ CPU with 16 GB memory and running on Windows 7 operating system. In an example embodiment, 16 units **102** are provided at the medical facility and 16 data monitors **104** are provided at each unit **102** to provide values for 16 parameters of physiological patient data. In this example embodiment, where the data monitors **104** provide parameter values at each minute, the controller **106** receives about 0.37 million data points over a 24 hour period. In an embodiment, such daily amounts of data can be displayed in real-time or near real-time (e.g. <1 second or <0.5 seconds or <250 milliseconds) in the block **300** and/or the gap collection pattern **400** and/or the group view **500** and/or the unit view **550**. Table 2 below depicts that the update time of the block **300** and/or pattern **400** and/or group view **500** and/or unit view **550** is on the order of hundreds of milliseconds (e.g. <500 milliseconds) for physiological patient data that is updated each minute.

TABLE-US-00002 TABLE 2 Self Total Function 15319.5 ms 15319.5 ms (idle) 196.4 ms 34.57% 196.4 ms 34.57% (program) 118.3 ms 20.82% 229.2 ms 40.33 drawUnitData 10.14.1.23/:269 30.6 ms 5.39% 70.8 ms 12.45% drawOneData 10.14.1.23/:1029 29.6 ms 5.20% 107.7 ms 18.96% \$.ajax.success 10.14.1.23/:1553 26.4 ms 4.65% 193.3 ms 34.01% \$.ajax.success 10.14.1.23/:1573 23.2 ms 4.09% 23.2 ms 4.09% lineTo 15.8 ms 2.79% 15.8 ms 2.79% (anonymous function) 14.8 ms 2.60% 166.9 ms 29.37% drawSideGroupData 10.14.1.23/:1424 14.8 ms 2.60% 14.8 ms 2.60% (garbage collector) 11.6 ms 2.04% 11.6 ms 2.04% parseDataTime 10.14.1.23/:224 6.3 ms 1.12% 6.3 ms 1.12% fillText 5.3 ms 0.93% 19.0 ms 3.35% drawDataOverView 10.14.1.23/:729 5.3 ms 0.93% 5.3 ms 0.93% fillRect 4.2 ms 0.74% 4.2 ms 0.74% measureText

[0114] In an embodiment, the system and method discussed herein has the capacity to deliver a remote patient monitoring platform refined and customized for use in the medical transport setting. In one embodiment, the system and method discussed herein provides both remote and on-board clinicians with the capability to simultaneously monitor dynamic physiologic changes in multiple patients. This offers the ability to identify critically worsening patients quickly and more effectively as both current and trend data can be clearly displayed. This technology allows for integration with clinical decision support tailored to the individual patient, providing unprecedented help in the austere battlefield environment. Traumatic brain injuries are common in the military population and reliable remote monitoring allows specialists to aid in the critical early hours of treatment of these complex injuries.

[0115] In an embodiment, the system and method discussed herein is practiced in a medical facility including 94 bed units **102** with 94 data monitors **104** (e.g. GE-Marquette Solar 7000/8000®, General Electric, Fairfield CT). In one embodiment, the 94 data monitors **104** are networked to provide collection of real time physiological patient data including 13 data monitors **104** in a trauma resuscitation unit (TRU); 9 data monitors **104** in an operating room (OR); 12 data monitors **104** in a post-anesthesia care unit (PACU) and 60 data monitors **104** in an intensive care unit (ICU). In an example embodiment, each data monitor **104** collects real-time 240 Hz waveforms (e.g. ECG, PPG, CO2, ABP, ICP) and 0.5 Hz trend data (e.g. HR, RR, SpO2, CO2, ICP) which are broadcasted via UDP (User Datagram Protocol) through secure intranet to a dedicated server **105c** (e.g. Bedmaster® with Excel Medical Electronics, Jupiter Florida). In the example embodiment, about 20 million data points per unit **102** are generated each day or roughly 30 terabits per year of data. During a twelve month study from February 2013 to January 2014, a total of 8719 adult patients stayed in the medical facility for an average stay of 3.8 days. In an example embodiment, collection rates from each individual server **105** were in a range from between 27.79% and 40.49% prior to implementing the system **100, 150**. In an example embodiment, after implementation of the triple redundant server system (e.g. servers **105** connected in the triple redundant arrangement) but before the implementation of the system **100, 150** the data collection rate improved to about 79.13%. In an example embodiment, the missing collection rate (gap) was about 20.87% and was mostly due to collection gaps of greater than 4 hours (e.g. 18.02% or 1.62 times per bed per month) and collection gaps of between 5 minutes and 4 hours (e.g. 0.13% or 0.6 times per bed per month). In an example embodiment, reasons for collection gaps included individual collection server failure, software instability, individual bed setting consistency and/or clinical engineering servicing of patient monitors. In an example embodiment, in a 6 month period after implementation of the system **100, 150**, the single server collection rate improved to a range between 87.05% and 95.54% and the triple redundant system achieved 99.88% total collection rate. Table 3 below depicts the server collection rates for the individual and combined server arrangements before and after implementation of the system **100, 150** (“pre-MoMs”, “post-MoMs”).

TABLE-US-00003	TABLE 3	Server 1	Server 2	Server 3	Server 3	Server 1	collected	collected
		collected	contributed	contributed	Combined	Pre-MoMs	40.5%	27.8%
		36.3%	25.4%	26.0%	79.1%			
		Post-MoMs	95.4%	95.5%	87.1%	4.2%	0.2%	99.9%

3. Hardware Overview

[0116] FIG. **8** is a block diagram that illustrates a computer system **800** upon which an embodiment of the invention may be implemented. Computer system **800** includes a communication mechanism such as a bus **810** for passing information between other internal and external components of the computer system **800**. Information is represented as physical signals of a measurable phenomenon, typically electric voltages, but including, in other embodiments, such phenomena as magnetic, electromagnetic, pressure, chemical, molecular atomic and quantum interactions. For example, north and south magnetic fields, or a zero and non-zero electric voltage, represent two states (0, 1) of a binary digit (bit).). Other phenomena can represent digits of a higher base. A superposition of multiple simultaneous quantum states before measurement represents a quantum bit (qubit). A

sequence of one or more digits constitutes digital data that is used to represent a number or code for a character. In some embodiments, information called analog data is represented by a near continuum of measurable values within a particular range. Computer system **800**, or a portion thereof, constitutes a means for performing one or more steps of one or more methods described herein.

[0117] A sequence of binary digits constitutes digital data that is used to represent a number or code for a character. A bus **810** includes many parallel conductors of information so that information is transferred quickly among devices coupled to the bus **810**. One or more processors **802** for processing information are coupled with the bus **810**. A processor **802** performs a set of operations on information. The set of operations include bringing information in from the bus **810** and placing information on the bus **810**. The set of operations also typically include comparing two or more units of information, shifting positions of units of information, and combining two or more units of information, such as by addition or multiplication. A sequence of operations to be executed by the processor **802** constitutes computer instructions.

[0118] Computer system **800** also includes a memory **804** coupled to bus **810**. The memory **804**, such as a random access memory (RAM) or other dynamic storage device, stores information including computer instructions. Dynamic memory allows information stored therein to be changed by the computer system **800**. RAM allows a unit of information stored at a location called a memory address to be stored and retrieved independently of information at neighboring addresses. The memory **804** is also used by the processor **802** to store temporary values during execution of computer instructions. The computer system **800** also includes a read only memory (ROM) **806** or other static storage device coupled to the bus **810** for storing static information, including instructions, that is not changed by the computer system **800**. Also coupled to bus **810** is a non-volatile (persistent) storage device **808**, such as a magnetic disk or optical disk, for storing information, including instructions, that persists even when the computer system **800** is turned off or otherwise loses power.

[0119] Information, including instructions, is provided to the bus **810** for use by the processor from an external input device **812**, such as a keyboard containing alphanumeric keys operated by a human user, or a sensor. A sensor detects conditions in its vicinity and transforms those detections into signals compatible with the signals used to represent information in computer system **800**. Other external devices coupled to bus **810**, used primarily for interacting with humans, include a display device **814**, such as a cathode ray tube (CRT) or a liquid crystal display (LCD), for presenting images, and a pointing device **816**, such as a mouse or a trackball or cursor direction keys, for controlling a position of a small cursor image presented on the display **814** and issuing commands associated with graphical elements presented on the display **814**.

[0120] In the illustrated embodiment, special purpose hardware, such as an application specific integrated circuit (IC) **820**, is coupled to bus **810**. The special purpose hardware is configured to perform operations not performed by processor **802** quickly enough for special purposes. Examples of application specific ICs include graphics accelerator cards for generating images for display **814**, cryptographic boards for encrypting and decrypting messages sent over a network, speech recognition, and interfaces to special external devices, such as robotic arms and medical scanning equipment that repeatedly perform some complex sequence of operations that are more efficiently implemented in hardware.

[0121] Computer system **800** also includes one or more instances of a communications interface **870** coupled to bus **810**. Communication interface **870** provides a two-way communication coupling to a variety of external devices that operate with their own processors, such as printers, scanners and external disks. In general the coupling is with a network link **878** that is connected to a local network **880** to which a variety of external devices with their own processors are connected. For example, communication interface **870** may be a parallel port or a serial port or a universal serial bus (USB) port on a personal computer. In some embodiments, communications interface

870 is an integrated services digital network (ISDN) card or a digital subscriber line (DSL) card or a telephone modem that provides an information communication connection to a corresponding type of telephone line. In some embodiments, a communication interface **870** is a cable modem that converts signals on bus **810** into signals for a communication connection over a coaxial cable or into optical signals for a communication connection over a fiber optic cable. As another example, communications interface **870** may be a local area network (LAN) card to provide a data communication connection to a compatible LAN, such as Ethernet. Wireless links may also be implemented. Carrier waves, such as acoustic waves and electromagnetic waves, including radio, optical and infrared waves travel through space without wires or cables. Signals include man-made variations in amplitude, frequency, phase, polarization or other physical properties of carrier waves. For wireless links, the communications interface **870** sends and receives electrical, acoustic or electromagnetic signals, including infrared and optical signals, that carry information streams, such as digital data.

[0122] The term computer-readable medium is used herein to refer to any medium that participates in providing information to processor **802**, including instructions for execution. Such a medium may take many forms, including, but not limited to, non-volatile media, volatile media and transmission media. Non-volatile media include, for example, optical or magnetic disks, such as storage device **808**. Volatile media include, for example, dynamic memory **804**. Transmission media include, for example, coaxial cables, copper wire, fiber optic cables, and waves that travel through space without wires or cables, such as acoustic waves and electromagnetic waves, including radio, optical and infrared waves. The term computer-readable storage medium is used herein to refer to any medium that participates in providing information to processor **802**, except for transmission media.

[0123] Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, a hard disk, a magnetic tape, or any other magnetic medium, a compact disk ROM (CD-ROM), a digital video disk (DVD) or any other optical medium, punch cards, paper tape, or any other physical medium with patterns of holes, a RAM, a programmable ROM (PROM), an erasable PROM (EPROM), a FLASH-EPROM, or any other memory chip or cartridge, a carrier wave, or any other medium from which a computer can read. The term non-transitory computer-readable storage medium is used herein to refer to any medium that participates in providing information to processor **802**, except for carrier waves and other signals.

[0124] Logic encoded in one or more tangible media includes one or both of processor instructions on a computer-readable storage media and special purpose hardware, such as ASIC ***820**.

[0125] Network link **878** typically provides information communication through one or more networks to other devices that use or process the information. For example, network link **878** may provide a connection through local network **880** to a host computer **882** or to equipment **884** operated by an Internet Service Provider (ISP). ISP equipment **884** in turn provides data communication services through the public, world-wide packet-switching communication network of networks now commonly referred to as the Internet **890**. A computer called a server **892** connected to the Internet provides a service in response to information received over the Internet. For example, server **892** provides information representing video data for presentation at display **814**.

[0126] The invention is related to the use of computer system **800** for implementing the techniques described herein. According to one embodiment of the invention, those techniques are performed by computer system **800** in response to processor **802** executing one or more sequences of one or more instructions contained in memory **804**. Such instructions, also called software and program code, may be read into memory **804** from another computer-readable medium such as storage device **808**. Execution of the sequences of instructions contained in memory **804** causes processor **802** to perform the method steps described herein. In alternative embodiments, hardware, such as application specific integrated circuit **820**, may be used in place of or in combination with software

to implement the invention. Thus, embodiments of the invention are not limited to any specific combination of hardware and software.

[0127] The signals transmitted over network link **878** and other networks through communications interface **870**, carry information to and from computer system **800**. Computer system **800** can send and receive information, including program code, through the networks **880**, **890** among others, through network link **878** and communications interface **870**. In an example using the Internet **890**, a server **892** transmits program code for a particular application, requested by a message sent from computer **800**, through Internet **890**, ISP equipment **884**, local network **880** and communications interface **870**. The received code may be executed by processor **802** as it is received, or may be stored in storage device **808** or other non-volatile storage for later execution, or both. In this manner, computer system **800** may obtain application program code in the form of a signal on a carrier wave.

[0128] Various forms of computer readable media may be involved in carrying one or more sequence of instructions or data or both to processor **802** for execution. For example, instructions and data may initially be carried on a magnetic disk of a remote computer such as host **882**. The remote computer loads the instructions and data into its dynamic memory and sends the instructions and data over a telephone line using a modem. A modem local to the computer system **800** receives the instructions and data on a telephone line and uses an infra-red transmitter to convert the instructions and data to a signal on an infra-red a carrier wave serving as the network link **878**. An infrared detector serving as communications interface **870** receives the instructions and data carried in the infrared signal and places information representing the instructions and data onto bus **810**. Bus **810** carries the information to memory **804** from which processor **802** retrieves and executes the instructions using some of the data sent with the instructions. The instructions and data received in memory **804** may optionally be stored on storage device **808**, either before or after execution by the processor **802**.

[0129] FIG. **9** illustrates a chip set **900** upon which an embodiment of the invention may be implemented. Chip set **900** is programmed to perform one or more steps of a method described herein and includes, for instance, the processor and memory components described with respect to FIG. ***8** incorporated in one or more physical packages (e.g., chips). By way of example, a physical package includes an arrangement of one or more materials, components, and/or wires on a structural assembly (e.g., a baseboard) to provide one or more characteristics such as physical strength, conservation of size, and/or limitation of electrical interaction. It is contemplated that in certain embodiments the chip set can be implemented in a single chip. Chip set **900**, or a portion thereof, constitutes a means for performing one or more steps of a method described herein.

[0130] In one embodiment, the chip set **900** includes a communication mechanism such as a bus **901** for passing information among the components of the chip set **900**. A processor **903** has connectivity to the bus **901** to execute instructions and process information stored in, for example, a memory **905**. The processor **903** may include one or more processing cores with each core configured to perform independently. A multi-core processor enables multiprocessing within a single physical package. Examples of a multi-core processor include two, four, eight, or greater numbers of processing cores. Alternatively or in addition, the processor **903** may include one or more microprocessors configured in tandem via the bus **901** to enable independent execution of instructions, pipelining, and multithreading. The processor **903** may also be accompanied with one or more specialized components to perform certain processing functions and tasks such as one or more digital signal processors (DSP) **907**, or one or more application-specific integrated circuits (ASIC) **909**. A DSP **907** typically is configured to process real-world signals (e.g., sound) in real time independently of the processor **903**. Similarly, an ASIC **909** can be configured to performed specialized functions not easily performed by a general purposed processor. Other specialized components to aid in performing the inventive functions described herein include one or more field programmable gate arrays (FPGA) (not shown), one or more controllers (not shown), or one or

more other special-purpose computer chips.

[0131] The processor **903** and accompanying components have connectivity to the memory **905** via the bus **901**. The memory **905** includes both dynamic memory (e.g., RAM, magnetic disk, writable optical disk, etc.) and static memory (e.g., ROM, CD-ROM, etc.) for storing executable instructions that when executed perform one or more steps of a method described herein. The memory **905** also stores the data associated with or generated by the execution of one or more steps of the methods described herein.

[0132] FIG. **10** is a diagram of exemplary components of a mobile terminal **1000** (e.g., cell phone handset) for communications, which is capable of operating in the system of FIG. **2C**, according to one embodiment. In some embodiments, mobile terminal **1001**, or a portion thereof, constitutes a means for performing one or more steps described herein. Generally, a radio receiver is often defined in terms of front-end and back-end characteristics. The front-end of the receiver encompasses all of the Radio Frequency (RF) circuitry whereas the back-end encompasses all of the base-band processing circuitry. As used in this application, the term “circuitry” refers to both: (1) hardware-only implementations (such as implementations in only analog and/or digital circuitry), and (2) to combinations of circuitry and software (and/or firmware) (such as, if applicable to the particular context, to a combination of processor(s), including digital signal processor(s), software, and memory(ies) that work together to cause an apparatus, such as a mobile phone or server, to perform various functions). This definition of “circuitry” applies to all uses of this term in this application, including in any claims. As a further example, as used in this application and if applicable to the particular context, the term “circuitry” would also cover an implementation of merely a processor (or multiple processors) and its (or their) accompanying software/or firmware. The term “circuitry” would also cover if applicable to the particular context, for example, a baseband integrated circuit or applications processor integrated circuit in a mobile phone or a similar integrated circuit in a cellular network device or other network devices.

[0133] Pertinent internal components of the telephone include a Main Control Unit (MCU) **1003**, a Digital Signal Processor (DSP) **1005**, and a receiver/transmitter unit including a microphone gain control unit and a speaker gain control unit. A main display unit **1007** provides a display to the user in support of various applications and mobile terminal functions that perform or support the steps as described herein. The display **1007** includes display circuitry configured to display at least a portion of a user interface of the mobile terminal (e.g., mobile telephone). Additionally, the display **1007** and display circuitry are configured to facilitate user control of at least some functions of the mobile terminal. An audio function circuitry **1009** includes a microphone **1011** and microphone amplifier that amplifies the speech signal output from the microphone **1011**. The amplified speech signal output from the microphone **1011** is fed to a coder/decoder (CODEC) **1013**.

[0134] A radio section **1015** amplifies power and converts frequency in order to communicate with a base station, which is included in a mobile communication system, via antenna **1017**. The power amplifier (PA) **1019** and the transmitter/modulation circuitry are operationally responsive to the MCU **1003**, with an output from the PA **1019** coupled to the duplexer **1021** or circulator or antenna switch, as known in the art. The PA **1019** also couples to a battery interface and power control unit **1020**.

[0135] In use, a user of mobile terminal **1001** speaks into the microphone **1011** and his or her voice along with any detected background noise is converted into an analog voltage. The analog voltage is then converted into a digital signal through the Analog to Digital Converter (ADC) **1023**. The control unit **1003** routes the digital signal into the DSP **1005** for processing therein, such as speech encoding, channel encoding, encrypting, and interleaving. In one embodiment, the processed voice signals are encoded, by units not separately shown, using a cellular transmission protocol such as enhanced data rates for global evolution (EDGE), general packet radio service (GPRS), global system for mobile communications (GSM), Internet protocol multimedia subsystem (IMS), universal mobile telecommunications system (UMTS), etc., as well as any other suitable wireless

medium, e.g., microwave access (WiMAX), Long Term Evolution (LTE) networks, code division multiple access (CDMA), wideband code division multiple access (WCDMA), wireless fidelity (WiFi), satellite, and the like, or any combination thereof.

[0136] The encoded signals are then routed to an equalizer **1025** for compensation of any frequency-dependent impairments that occur during transmission through the air such as phase and amplitude distortion. After equalizing the bit stream, the modulator **1027** combines the signal with a RF signal generated in the RF interface **1029**. The modulator **1027** generates a sine wave by way of frequency or phase modulation. In order to prepare the signal for transmission, an up-converter **1031** combines the sine wave output from the modulator **1027** with another sine wave generated by a synthesizer **1033** to achieve the desired frequency of transmission. The signal is then sent through a PA **1019** to increase the signal to an appropriate power level. In practical systems, the PA **1019** acts as a variable gain amplifier whose gain is controlled by the DSP **1005** from information received from a network base station. The signal is then filtered within the duplexer **1021** and optionally sent to an antenna coupler **1035** to match impedances to provide maximum power transfer. Finally, the signal is transmitted via antenna **1017** to a local base station. An automatic gain control (AGC) can be supplied to control the gain of the final stages of the receiver. The signals may be forwarded from there to a remote telephone which may be another cellular telephone, any other mobile phone or a land-line connected to a Public Switched Telephone Network (PSTN), or other telephony networks.

[0137] Voice signals transmitted to the mobile terminal **1001** are received via antenna **1017** and immediately amplified by a low noise amplifier (LNA) **1037**. A down-converter **1039** lowers the carrier frequency while the demodulator **1041** strips away the RF leaving only a digital bit stream. The signal then goes through the equalizer **1025** and is processed by the DSP **1005**. A Digital to Analog Converter (DAC) **1043** converts the signal and the resulting output is transmitted to the user through the speaker **1045**, all under control of a Main Control Unit (MCU) **1003** which can be implemented as a Central Processing Unit (CPU) (not shown).

[0138] The MCU **1003** receives various signals including input signals from the keyboard **1047**. The keyboard **1047** and/or the MCU **1003** in combination with other user input components (e.g., the microphone **1011**) comprise a user interface circuitry for managing user input. The MCU **1003** runs a user interface software to facilitate user control of at least some functions of the mobile terminal **1001** as described herein. The MCU **1003** also delivers a display command and a switch command to the display **1007** and to the speech output switching controller, respectively. Further, the MCU **1003** exchanges information with the DSP **1005** and can access an optionally incorporated SIM card **1049** and a memory **1051**. In addition, the MCU **1003** executes various control functions required of the terminal. The DSP **1005** may, depending upon the implementation, perform any of a variety of conventional digital processing functions on the voice signals. Additionally, DSP **1005** determines the background noise level of the local environment from the signals detected by microphone **1011** and sets the gain of microphone **1011** to a level selected to compensate for the natural tendency of the user of the mobile terminal **1001**.

[0139] The CODEC **1013** includes the ADC **1023** and DAC **1043**. The memory **1051** stores various data including call incoming tone data and is capable of storing other data including music data received via, e.g., the global Internet. The software module could reside in RAM memory, flash memory, registers, or any other form of writable storage medium known in the art. The memory device **1051** may be, but not limited to, a single memory, CD, DVD, ROM, RAM, EEPROM, optical storage, magnetic disk storage, flash memory storage, or any other non-volatile storage medium capable of storing digital data.

[0140] An optionally incorporated SIM card **1049** carries, for instance, important information, such as the cellular phone number, the carrier supplying service, subscription details, and security information. The SIM card **1049** serves primarily to identify the mobile terminal **1001** on a radio network. The card **1049** also contains a memory for storing a personal telephone number registry,

text messages, and user specific mobile terminal settings.

[0141] In some embodiments, the mobile terminal **1001** includes a digital camera comprising an array of optical detectors, such as charge coupled device (CCD) array **1065**. The output of the array is image data that is transferred to the MCU for further processing or storage in the memory **1051** or both. In the illustrated embodiment, the light impinges on the optical array through a lens **1063**, such as a pin-hole lens or a material lens made of an optical grade glass or plastic material. In the illustrated embodiment, the mobile terminal **1001** includes a light source **1061**, such as a LED to illuminate a subject for capture by the optical array, e.g., CCD **1065**. The light source is powered by the battery interface and power control module **1020** and controlled by the MCU **1003** based on instructions stored or loaded into the MCU **1003**.

[0142] In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense. Throughout this specification and the claims, unless the context requires otherwise, the word “comprise” and its variations, such as “comprises” and “comprising,” will be understood to imply the inclusion of a stated item, element or step or group of items, elements or steps but not the exclusion of any other item, element or step or group of items, elements or steps. Furthermore, the indefinite article “a” or “an” is meant to indicate one or more of the item, element or step modified by the article. As used herein, unless otherwise clear from the context, a value is “about” another value if it is within a factor of two (twice or half) of the other value. While example ranges are given, unless otherwise clear from the context, any contained ranges are also intended in various embodiments. Thus, a range from 0 to 10 includes the range 1 to 4 in some embodiments.

Claims

1. A method for displaying subject condition data relating to monitoring a plurality of patients in a respective plurality of units, the method comprising: for each of a plurality of sample times, receiving, on a processor, a value of at least one parameter of subject condition data and a value of each sample time from a plurality of subject condition data monitors associated with the respective plurality of units; and presenting, on the display, a trace of the value of the at least one parameter over a time window encompassed by the plurality of sample times increments in each of a first plurality of active areas of a trace region, each active area in the trace region corresponding to a respective parameter.
2. The method of claim 1, further comprising: presenting, on the display, a first indicator in each of a second plurality of active areas in a thumbnail region, each active area in the thumbnail region corresponding to a respective unit.
3. The method of claim 1, further comprising: presenting, on the display, a bar that indicates an occurrence of the value of the parameter over the time window in each of a third plurality of active areas of a bar region, each active area in the bar region corresponding to a respective parameter.
4. The method of claim 1, further comprising: presenting, on the display, points in an index plot over the time window in at least one active area in an index region, each active area in the index region corresponding to a respective index plot and wherein the points in the index plot are based on a value of a first parameter of subject condition data and a value of a second parameter of subject condition data.
5. The method of claim 1, further comprising: presenting, on the display, a bar that indicates an occurrence of the value of the parameter over the time window in each of a third plurality of active areas of a bar region, each active area in the bar region corresponding to a respective parameter; and presenting, on the display, points in an index plot over the time window in at least one active area in an index region, each active area in the index region corresponding to a respective index

plot and wherein the points in the index plot are based on a value of a first parameter of subject condition data and a value of a second parameter of subject condition data.

6. The method of claim 1, further comprising: presenting a second indicator in each of a fourth plurality of active areas in a time region, each active area in the time region corresponding to one of a plurality of time interval values; in response to a selection of a particular active area of the time region, adjusting a value of the time window based on the time interval value of the particular active area of the time region.

7. The method of claim 5, wherein the index region is in a right portion of the display and the trace and bar regions are presented to the left of the index region.

8. The method of claim 5, further comprising presenting, on the display, an action indicator in each of a fifth plurality of active areas in an action region, at least one active area in the action region corresponding to a respective action taken, wherein the method further comprises at least one of; in response to a selection of a first active area of the action region, generating an image file that represents an image of at least one of the trace region, the bar region and the index region and storing the image file in a memory of the processor; and in response to a selection of a second active area of the action region, presenting the value of the parameter of subject condition data over a secondary time window that is less than the time window, wherein the parameter of subject condition data is a waveform parameter of subject condition data.

9. The method of claim 4, wherein the points are color coded based on the sample time of each value of the first parameter and second parameter over the time window.

10. The method of claim 1, wherein the parameter of subject condition data includes at least one of heart rate (HR), systolic blood pressure (SBP), intracranial pressure (ICP), respiratory rate (RR), temperature, oxygen saturation (SP02), cerebral perfusion pressure (CPP).

11. The method of claim 4, wherein the points in the index plot are based on a ratio of the value of the first parameter of subject condition data to the value of the second parameter of subject condition data.

12. The method of claim 11, wherein the points in the index plot are at least one of: a value of a shock index that is a ratio of a value of heart rate (HR) to a value of systolic blood pressure (SBP); and a value of a brain trauma index that is a ratio of a value of intracranial blood pressure (ICP) to a value of cerebral perfusion pressure (CPP).

13. The method of claim 4, wherein the step of presenting the points in the index plot further comprises presenting at least one vertical intercept line that intersects a horizontal axis of the index plot to indicate at least one threshold value of the first parameter of subject condition data along the horizontal axis and presenting at least one horizontal intercept line that intersects a vertical axis to indicate at least one threshold value of the second parameter of subject condition data along the vertical axis.

14. The method of claim 8, wherein the waveform parameter of subject condition data is at least one of electrocardiogram and photoplethysmographic (PPG) and wherein the secondary time window is less than 1 hour.

15. The method of claim 5, wherein in response to a selection of a secondary time window within the time window: the step of presenting the trace of the value of the parameter is performed over the secondary time window in the at least one active area in the trace region; the step of presenting the bar that indicates the occurrence of the value of the parameter is performed over the secondary time window in the at least one active area in the bar region; and the step of presenting the points in the index plot is performed over the secondary time window.

16. The method of claim 5, wherein in response to a selection of an active area in a home region, presenting, on the display, a third indicator in each of a third plurality of active areas in a group region, at least one active area in the group region corresponding to a respective one of a groups of the facility; in response to a selection of a particular active area of the group region, presenting, on the display, a representation based on the value of the at least one parameter of subject condition

data in each of a fourth plurality of active areas in a unit region, each active area in the unit region corresponding to a respective unit within the group corresponding to the particular active area of the group region.

17. A method for displaying subject condition data relating to monitoring a plurality of patients in a respective plurality of units, the method comprising: for each of a plurality of sample times, receiving, on a processor, a value of at least one parameter of subject condition data and a value of each sample time from a plurality of subject condition data monitors associated with the respective plurality of units; presenting, on the display, a trace of the value of the at least one parameter over a time window encompassed by the plurality of sample times increments in each of a first plurality of active areas of a trace region, each active area in the trace region corresponding to a respective parameter; presenting, on the display, a bar that indicates an occurrence of the value of the parameter over the time window in each of a second plurality of active areas of a bar region, each active area in the bar region corresponding to a respective parameter; and presenting, on the display, points in an index plot over the time window in at least one active area in an index region, each active area in the index region corresponding to a respective index plot and wherein the points in the index plot are based on a value of a first parameter of subject condition data and a value of a second parameter of subject condition data.

18. The method of claim 17, further comprising: presenting an indicator in each of a third plurality of active areas in a time region, each active area in the time region corresponding to one of a plurality of time interval values; in response to a selection of a particular active area of the time region, adjusting a value of the time window based on the time interval value of the particular active area of the time region.

19. The method of claim 17, further comprising presenting, on the display, an indicator in each of a third plurality of active areas in a thumbnail region, each active area in the thumbnail region corresponding to a respective unit; and wherein the thumbnail region is presented in a left portion of the display, the index region is in a right portion of the display and the trace and bar regions are between the thumbnail region and index region.

20. The method of claim 17, further comprising presenting, on the display, an action indicator in each of a fifth plurality of active areas in an action region, at least one active area in the action region corresponding to a respective action taken, wherein the method further comprises at least one of; in response to a selection of a first active area of the action region, generating an image file that represents an image of at least one of the trace region, the bar region and the index region and storing the image file in a memory of the processor; and in response to a selection of a second active area of the action region, presenting the value of the parameter of subject condition data over a secondary time window that is less than the time window, wherein the parameter of subject condition data is a waveform parameter of subject condition data.
