

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284126

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

MISAWA; Atsushi

DISPLAY CONTROL DEVICE, DISPLAY CONTROL METHOD, AND DISPLAY CONTROL PROGRAM

Abstract

A display control device of a wearable device including a monitor, the display control device including: a memory; and at least one processor that is coupled to or incorporates the memory, and that is configured to: acquire an image to be displayed on the monitor; acquire a first operation instruction that is input through operation of an operation unit of an imaging apparatus in order to change a display magnification of the image and that is input through a magnification changing operation performed at the imaging apparatus, the imaging apparatus being a separate body from the wearable device; and change the display magnification of the image in accordance with the first operation instruction.

Inventors: MISAWA; Atsushi (Saitama, JP)

Applicant: FUJIFILM Corporation (Tokyo, JP)

Family ID: 81382408

Assignee: FUJIFILM Corporation (Tokyo, JP)

Appl. No.: 19/217890

Filed: May 23, 2025

Foreign Application Priority Data

JP	2020-179750	Oct. 27, 2020
----	-------------	---------------

Related U.S. Application Data

parent US continuation 18653781 20240502 parent-grant-document US 12332440 child US 19217890

parent US continuation 18306422 20230425 parent-grant-document US 12007563 child US

Publication Classification

Int. Cl.: G02B27/01 (20060101); G06F3/0485 (20220101); G06F3/0488 (20220101)

U.S. Cl.:

CPC G02B27/017 (20130101); G02B27/0101 (20130101); G06F3/0485 (20130101);
G06F3/0488 (20130101); G02B2027/014 (20130101); G06F2203/04806 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/653,781, filed on May 2, 2024, which is a continuation application of U.S. application Ser. No. 18/306,422, filed on Apr. 25, 2023, now U.S. Pat. No. 12,007,563, issued Jun. 11, 2024, which is a continuation application of International Application No. PCT/JP2021/036534, filed on Oct. 4, 2021, which are incorporated herein by reference in their entireties. Further, this application claims priority from Japanese Patent Application No. 2020-179750, filed on Oct. 27, 2020, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

Technical Field

[0002] The disclosed technology relates to a display control device, a display control method, and a non-transitory storage medium storing a display control program.

Related Art

[0003] In recent years, a wearable monitor such as a head mounted display (HMD) has been developed as a monitor to be mounted on a head part of a user. Furthermore, so-called smart glasses and the like that display information in front of eyes using a small liquid crystal display (LCD) projector unlike the HMD in the related art, and that are smaller and lighter than the HMD in the related art and are approximately in the same size or slightly larger than glasses in terms of appearance have emerged. The smart glasses can display a display image of a monitor in a superimposed manner on transmitted light or in a part of a field of view. These types of wearable monitors are considered to be the mainstream in the future. Such wearable monitors are an example of a wearable device including a monitor. A display control device that can scroll an image in a case of displaying a captured image obtained using an imaging apparatus on the monitor of the wearable device has been suggested (for example, refer to WO2014/185146A). In WO2014/185146A, scrolling an image displayed on a monitor of a wearable device in accordance with an inclination of a smartphone is disclosed.

SUMMARY

[0004] The disclosed technology provides a display control device, a display control method, and a non-transitory storage medium storing a display control program that improve usability.

[0005] A display control device according to an aspect of the present disclosure is a display control device of a wearable device including a monitor, the display control device comprising at least one processor, and a memory that is incorporated in or connected to the processor, in which the processor is configured to execute image acquisition processing of acquiring an image to be displayed on the monitor, first operation instruction acquisition processing of acquiring a first

operation instruction that is input through operation of an operation unit of an imaging apparatus which is a separate body from the wearable device, in order to change a display magnification of the image and that is input through a magnification changing operation in the imaging apparatus, and display control processing of changing the display magnification of the image in accordance with the first operation instruction.

[0006] The magnification changing operation may be a zoom magnification changing operation performed in a case of imaging using the imaging apparatus.

[0007] In addition, the processor may be configured to control an amount of change in the display magnification of the image in accordance with an amount of change in magnification with respect to an operation amount of the magnification changing operation in the display control processing.

[0008] In addition, the processor may be configured to further execute second operation instruction acquisition processing of acquiring, as a second operation instruction, a change in a posture of the imaging apparatus detected by a posture detection unit that detects the posture of the imaging apparatus, and scroll the image in accordance with the second operation instruction in the display control processing.

[0009] In addition, in a case where the imaging apparatus includes a touch panel functioning as the operation unit, and the magnification changing operation in a case of imaging of the imaging apparatus is a swipe operation within a first region in the touch panel, the processor may be configured to detect, as an operation of changing the display magnification of the image, a swipe operation within a second region that includes the first region and that is wider than the first region in the touch panel.

[0010] In addition, the processor may be configured to detect, as the magnification changing operation, a swipe operation of an arc shape of which a radius is greater than or equal to 3 cm and less than or equal to 8 cm in the touch panel.

[0011] In addition, the image may be an image captured by the imaging apparatus.

[0012] In addition, the processor may be mounted in the wearable device, and the processor may be configured to acquire the image from an external server in the image acquisition processing, and acquire the first operation instruction, which is input through the operation of the operation unit of the imaging apparatus, through the server in the first operation instruction acquisition processing.

[0013] In addition, the processor may be mounted in the wearable device, and the processor may be configured to acquire the image from an external server in the image acquisition processing, and acquire the first operation instruction, which is input through the operation of the operation unit of the imaging apparatus, directly from the imaging apparatus in the first operation instruction acquisition processing.

[0014] In addition, the image may include information about a tilt angle that is an inclination angle of the imaging apparatus with respect to a horizontal direction in capturing the image, and the processor may be configured to change an initial position of a center position in a case of changing the display magnification of the image based on the tilt angle in the display control processing.

[0015] In addition, the image may include information about a roll angle that is a rotation angle of the imaging apparatus about an optical axis with respect to a horizontal direction in capturing the image, and the processor may be configured to correct the image with respect to the horizontal direction based on the roll angle in the display control processing.

[0016] In addition, the image may include magnification changing operation-related information related to an amount of change in magnification with respect to an operation amount of the magnification changing operation in a case of imaging in the imaging apparatus that has captured the image, and the processor may be configured to match the amount of change in the magnification with respect to the operation amount of the magnification changing operation in imaging to an amount of change in magnification with respect to an operation amount in a case of changing the display magnification of the image, based on the magnification changing operation-related information in the display control processing.

[0017] In addition, the image may include angle-of-view information related to an angle of view of the imaging apparatus in capturing the image, and the processor may be configured to correct a scroll amount in a case of scrolling the image in accordance with the second operation instruction based on the angle-of-view information in the display control processing.

[0018] A display control method according to another aspect of the present disclosure is a display control method of a wearable device including a monitor, the display control method comprising an image acquisition processing step of acquiring an image to be displayed on the monitor, a first operation instruction acquisition processing step of acquiring a first operation instruction that is input through operation of an operation unit of an imaging apparatus which is a separate body from the wearable device, in order to change a display magnification of the image and that is input through a magnification changing operation in the imaging apparatus, and a display control processing step of changing the display magnification of the image in accordance with the first operation instruction.

[0019] A non-transitory storage medium according to still another aspect of the present disclosure stores a program for executing display control processing by a wearable device including a monitor, the display control processing including: acquiring an image to be displayed on the monitor, acquiring a first operation instruction that is input through operation of an operation unit of an imaging apparatus which is a separate body from the wearable device, in order to change a display magnification of the image and that is input through a magnification changing operation in the imaging apparatus, and changing the display magnification of the image in accordance with the first operation instruction.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] FIG. 1 is a schematic configuration diagram of an image display system including a display control device according to a first embodiment.

[0021] FIG. 2 is a block diagram illustrating a hardware configuration of a smartphone.

[0022] FIG. 3 is a functional block diagram of the smartphone.

[0023] FIG. 4 is an external view of smart glasses.

[0024] FIG. 5 is a diagram for describing a field of view of a user seen through the smart glasses.

[0025] FIG. 6 is a block diagram illustrating a hardware configuration of the smart glasses.

[0026] FIG. 7 is a diagram illustrating a state of the user in image capturing.

[0027] FIG. 8 is a flowchart for describing processing in the image capturing in the first embodiment.

[0028] FIG. 9 is a diagram illustrating an example of an imaging screen displayed on a touch panel.

[0029] FIG. 10 is a diagram illustrating a state of the user in image display.

[0030] FIG. 11 is a flowchart for describing processing in the image display in the first embodiment.

[0031] FIG. 12 is a diagram illustrating an example of a display screen displayed on the touch panel.

[0032] FIG. 13 is a graph showing a relationship between a swipe amount and a magnification in a zoom magnification changing operation and in a display magnification changing operation.

[0033] FIG. 14 is a diagram for describing a swipe operation on the display screen.

[0034] FIG. 15 is a diagram illustrating a state where an image displayed on the smart glasses is enlarged from an initial display state.

[0035] FIG. 16 is a diagram illustrating a state where the image displayed on the smart glasses is scrolled rightward from the state illustrated in FIG. 15.

[0036] FIG. 17 is a diagram illustrating a state where the image displayed on the smart glasses is

scrolled upward from the state illustrated in FIG. 15.

[0037] FIG. 18 is a schematic configuration diagram of an image display system including a display control device according to a second embodiment.

[0038] FIG. 19 is a flowchart for describing processing in image display in the second embodiment.

[0039] FIG. 20 is a flowchart for describing processing in image display in a third embodiment.

[0040] FIG. 21 is a diagram for describing a structure of an image file in a fourth embodiment.

[0041] FIG. 22 is a diagram for describing a tilt angle according to an embodiment of the disclosed technology.

[0042] FIG. 23 is a diagram for describing an initial position of a center position in a case of changing a display magnification.

[0043] FIG. 24 is a graph showing a relationship between the tilt angle and an amount of change in the center position on a Y axis.

[0044] FIG. 25 is a diagram for describing a structure of an image file in a fifth embodiment.

[0045] FIG. 26 is a diagram for describing a roll angle according to the embodiment of the disclosed technology.

[0046] FIG. 27 is a diagram illustrating an image captured in a state where the smartphone is inclined.

[0047] FIG. 28 is a diagram illustrating a state where the image captured in a state where the smartphone is inclined is corrected.

[0048] FIG. 29 is a diagram for describing a structure of an image file in a sixth embodiment.

[0049] FIG. 30 is a graph showing a relationship between the swipe amount and the magnification in the touch panel.

[0050] FIG. 31 is a diagram illustrating an example of the display screen displayed on the touch panel.

[0051] FIG. 32 is an external view in which the smartphone on which a smartphone cover is mounted is seen from the front.

[0052] FIG. 33 is an external view in which the smartphone on which the smartphone cover is mounted is seen from the rear.

[0053] FIG. 34 is a diagram for describing a structure of an image file in a seventh embodiment.

[0054] FIG. 35 is a graph showing a relationship between a rotation amount of a zoom ring or of a ring-type controller and the magnification.

[0055] FIG. 36 is a diagram for describing a structure of an image file in an eighth embodiment.

[0056] FIG. 37 is a diagram for describing a relationship between an angle of view and an inclination angle of the smartphone.

[0057] FIG. 38 is a diagram illustrating an example of an image displayed on the smart glasses in imaging.

DETAILED DESCRIPTION

First Embodiment

[0058] Hereinafter, embodiments of the present disclosure will be described with reference to the drawings. FIG. 1 is a schematic configuration diagram of an image display system including a display control device according to a first embodiment of the present disclosure. An image display system 1 illustrated in FIG. 1 comprises a smartphone 10 and smart glasses 50. The smart glasses 50 are caused to function as an external display of the smartphone 10 so that an image displayable on the smartphone 10 can be displayed on the smart glasses 50. In the image display system 1, as will be illustrated below, changing of a display magnification and scrolling of an image displayed on the smart glasses 50 can be performed by operating the smartphone 10.

[0059] As illustrated in FIG. 1, in the image display system 1, the smartphone 10 and the smart glasses 50 are wirelessly connected as an example. The smartphone 10 is an example of an imaging apparatus according to an embodiment of the disclosed technology. The smart glasses 50 are a

glasses-type wearable computer and are a so-called wearable monitor. The wearable monitor is an example of a wearable device that is mounted on a body of a user U and that includes a monitor on which an image is displayed within a field of view of the user U.

[0060] As is well known, the smartphone **10** is a portable terminal that functions as a mobile computer and as a mobile phone. The smartphone **10** comprises a housing **11** of a flat plate shape. A touch panel **24** is disposed on one surface of the housing **11**. An imaging lens **26a** is disposed on a surface **11b** of the housing **11** on an opposite side to the surface on which the touch panel **24** is disposed. In the following description, for convenience, in the housing **11** of the smartphone **10**, the surface on which the touch panel **24** is disposed will be described as a front surface **11a** (refer to FIG. **8**), and the surface on which the imaging lens **26a** is disposed will be described as the rear surface **11b**.

[0061] As illustrated in FIG. **2**, the smartphone **10** includes a central processing unit (CPU) **21**, a memory **22**, a storage **23**, the touch panel **24**, a communication unit **25**, an imaging unit **26**, and a posture detection unit **27**. Each configuration is mutually communicably connected through a bus **28**.

[0062] The CPU **21** integrally controls each part of the smartphone **10** by executing a control program or the like. The memory **22** is a work memory and is composed of, for example, a random access memory (RAM). The CPU **21** reads out the control program into the memory **22** from the storage **23** and executes the control program using the memory **22** as a work region. The CPU **21** controls each configuration and performs various types of processing in accordance with the control program.

[0063] The CPU **21** is an example of a processor according to the embodiment of the disclosed technology. The memory **22** is an example of a memory according to the embodiment of the disclosed technology. The smartphone **10** comprising the CPU **21** and the memory **22** also functions as a display control device according to the embodiment of the disclosed technology.

[0064] The storage **23** stores various programs including the control program including an operating system, an application program, and the like and various types of data including image data. The storage **23** is composed of, for example, a non-volatile memory such as a flash memory. In the present embodiment, the storage **23** stores a display control program PG as one of the various programs.

[0065] The touch panel **24** has a function as a display unit that displays various images, and a function as an operation unit that receives a touch input operation.

[0066] The communication unit **25** is an interface for communication of the smartphone **10** with the smart glasses **50** and with other apparatuses and, for example, uses standards such as Wi-Fi (registered trademark) and Bluetooth (registered trademark).

[0067] The imaging unit **26** comprises the imaging lens **26a** and an imaging element and the like, not illustrated. The imaging unit **26** acquires image data of a subject by imaging the subject.

[0068] The posture detection unit **27** detects a posture of the smartphone **10** and, for example, uses a gyro sensor.

[0069] As illustrated in FIG. **3**, the CPU **21** functions as an image acquisition processing unit **21a**, an operation instruction acquisition processing unit **21b**, and a display control processing unit **21c** by executing the display control program PG stored in the storage **23**.

[0070] The image acquisition processing unit **21a** executes image acquisition processing of acquiring an image to be displayed on the smart glasses **50**.

[0071] The operation instruction acquisition processing unit **21b** executes first operation instruction acquisition processing of acquiring a first operation instruction that is input through operation of the operation unit of the smartphone **10** which is a separate body from the smart glasses **50**, in order to change a display magnification of the image and that is input through a magnification changing operation in the smartphone **10**. As an example, the first operation instruction is the same operation as a zoom magnification changing operation in a case of imaging using the smartphone

10 and is a swipe operation in the touch panel **24**.

[0072] In addition, the operation instruction acquisition processing unit **21b** executes second operation instruction acquisition processing of acquiring, as a second operation instruction, a change in the posture of the smartphone **10**, that is, a change in direction of the imaging lens **26a** of the smartphone **10**, detected by the posture detection unit **27** that detects the posture of the smartphone **10**.

[0073] The display control processing unit **21c** executes processing of changing the display magnification of the image displayed on the smart glasses **50** in accordance with the first operation instruction. In addition, the display control processing unit **21c** executes processing of scrolling the image displayed on the smart glasses **50** in accordance with the second operation instruction.

[0074] As illustrated in FIG. **4**, the smart glasses **50** are a glasses-type wearable monitor and comprise a frame **51**, a lens **52** that is disposed in front of eyes and that has a size covering both eyes, and a display unit **64** disposed at a position corresponding to the right eye in the lens **52**. As an example, the display unit **64** is a retinal projection-type display unit that displays an image IM in a part of a field of view of the right eye as illustrated in FIG. **5** by directly projecting display light of the image to a retina. FIG. **5** schematically illustrates a state where the image IM is captured in the field of view of the user U wearing the smart glasses **50**. For the user U, the image IM looks as if the image IM is projected to the lens **52**.

[0075] As illustrated in FIG. **6**, the smart glasses **50** include a CPU **61**, a memory **62**, a storage **63**, the display unit **64**, and a communication unit **65**. Each configuration is mutually communicably connected through a bus **66**.

[0076] The CPU **61** controls each part of the smart glasses **50** by executing a control program or the like. The memory **62** is a work memory and is composed of, for example, a RAM. The storage **63** stores various programs and various types of data. The storage **63** is composed of, for example, a flash memory. The CPU **61** reads out the control program into the memory **62** from the storage **63** and executes the control program using the memory **62** as a work region. The CPU **61** controls each configuration and performs various types of processing in accordance with the control program.

[0077] The display unit **64** displays the image in a part of the field of view of the user U by projecting the display light of the image to pupils of the user U and comprises an image display element, a projection lens, and the like, not illustrated. A resolution of the image display element is, for example, **640** dots in a lateral direction and **360** dots in a vertical direction.

[0078] The communication unit **65** is an interface for communication of the smart glasses **50** with the smartphone **10** and with other apparatuses and, for example, uses standards such as Wi-Fi (registered trademark) and Bluetooth (registered trademark).

Flow of Processing

[0079] First, a flow of processing in a case where the user U captures an image using the smartphone **10** will be described. As illustrated in FIG. **7**, in a case of capturing the image, as an example, the user U performs imaging using only the smartphone **10** without wearing the smart glasses **50**.

[0080] FIG. **8** is a flowchart for describing the processing in a case of capturing the image using the smartphone **10**.

[0081] In a case where an instruction such as a start instruction of a camera to set an image capturing mode is input from the user U, the CPU **21** of the smartphone **10** transitions to an image capturing mode (step SP1).

[0082] In a case where a transition is made to the image capturing mode, the CPU **21** displays an imaging screen IP (refer to FIG. **9**) on the touch panel **24** (step SP2). As illustrated in FIG. **9**, the imaging screen IP includes a zoom magnification input unit **30** that is a graphical user interface (GUI) for adjusting a zoom magnification, a shutter button **31**, and a live view display unit **32**. The image IM to be captured is displayed as a live view on the live view display unit **32**. In FIG. **9**, the

image IM is illustrated outside a field of the live view display unit **32** in order to avoid complication of illustration. However, in actuality, the image IM is displayed within the live view display unit **32**, and the image IM and the zoom magnification input unit **30** are displayed in a superimposed manner.

[0083] The zoom magnification input unit **30** comprises, for example, a magnification display unit **30a** that displays the current zoom magnification, and a magnification designation line **30b** for designating the zoom magnification from a wide angle end to a telephoto end. The zoom magnification is displayed based on a focal length at the wide angle end as a reference. That is, the zoom magnification at the wide angle end is the reference and thus, is a magnification of 1. The zoom magnification at the telephoto end is a magnification of 5 as an example. The magnification designation line **30b** is a curved line of an arc shape. One end (a lower end in FIG. 9) of the magnification designation line **30b** is the zoom magnification at the wide angle end and is set to a magnification of 1 in the present example. The other end (an upper end in FIG. 9) of the magnification designation line **30b** is the zoom magnification at the telephoto end and is set to a magnification of 5 in the present example. In the magnification designation line **30b**, the zoom magnification in an intermediate portion is set to a magnification of 1 to a magnification of 5 in accordance with a distance from the one end. In the present example, the magnification display unit **30a** has a circular shape and approximately has a size that surrounds a number indicating the zoom magnification such as a magnification of 1 and a magnification of 5.

[0084] A display position of the magnification display unit **30a** of a circular shape is fixed. On the other hand, the magnification designation line **30b** moves along a path of an arc shape with respect to the magnification display unit **30a** via the swipe operation of the user U. Numbers indicating the zoom magnification such as a magnification of 1 ($\times 1.0$) and a magnification of 5 ($\times 5.0$) displayed in both end parts of the magnification designation line **30b** are movable together with the magnification designation line **30b**. Moving the magnification designation line **30b** via the swipe operation of the user U changes an intersection position of the magnification designation line **30b** with respect to the magnification display unit **30a**. The zoom magnification corresponding to the intersection position in the magnification designation line **30b** is displayed within the magnification display unit **30a** of a circular shape. In FIG. 9, a state where a magnification of 2.5 ($\times 2.5$) is displayed within the magnification display unit **30a** is illustrated. Accordingly, the zoom magnification corresponding to the intersection position of the magnification designation line **30b** with respect to the magnification display unit **30a** is input.

[0085] A zoom magnification input region **24a** is a region including the magnification display unit **30a** and the magnification designation line **30b** and is set to have an arc shape along the magnification designation line **30b** that is a curved line of an arc shape. The zoom magnification input region **24a** indicates a movement range in which a finger of the user U operating the zoom magnification input unit **30** moves. The zoom magnification input region **24a** is a first region according to the embodiment of the disclosed technology.

[0086] The CPU **21** detects, as the zoom magnification changing operation performed in a case of imaging using the smartphone **10**, the swipe operation of moving the magnification designation line **30b** within the zoom magnification input region **24a** in the touch panel **24**. In a case where the zoom magnification changing operation is detected, the CPU **21** changes the zoom magnification of the imaging lens **26a** or the zoom magnification of an electronic zoom. The image IM being displayed on the live view display unit **32** is zoomed in accordance with the change in the zoom magnification. That is, as the zoom magnification approaches the telephoto end, the subject within the image IM is enlarged, but an angle of view is narrowed. As the zoom magnification approaches the wide angle end, the subject within the image IM is reduced, but the angle of view is widened.

[0087] In addition, in the smartphone **10**, an optical axis direction Z of the imaging lens **26a** provided on the rear surface **11b** of the housing **11** is an imaging direction of the image. The user U adjusts the imaging direction by moving the smartphone **10** to adjust the direction of the imaging

lens **26a** of the smartphone **10**.

[0088] The user **U** adjusts the imaging direction and the zoom magnification and, in a case where the user **U** is ready to perform imaging, touches the shutter button **31**. In a case where an operation of touching the shutter button **31** is detected (step **SP3**), the CPU **21** performs imaging by controlling the imaging unit **26** (step **SP4**) and acquires the image data (step **SP5**). The CPU **21** stores the image data acquired by the imaging unit **26** in the storage **23** and ends the processing.

[0089] Next, a flow of processing in a case where the user checks the image in the image display system **1** will be described. As illustrated in FIG. **10**, in a case where the user **U** checks the image **IM** via the smart glasses **50**, the user **U** wears the smart glasses **50**.

[0090] FIG. **11** is a flowchart for describing processing in a case of image display in the image display system **1**.

[0091] In a case where an instruction to set an image display mode is input from the user **U**, the CPU **21** of the smartphone **10** transitions to the image display mode (step **SP11**).

[0092] In a case where a transition is made to the image display mode, the CPU **21** acquires information about a resolution of the display unit **64** of the smart glasses **50** connected to the smartphone **10** (step **SP12**). For example, the information about the resolution of the display unit **64** is stored in the storage **23** together with model information of the smart glasses **50** in setting in a case of wirelessly connecting the smart glasses **50** to the smartphone **10**. In a case where a transition is made to the image display mode, the CPU **21** acquires the information about the resolution of the display unit **64** by reading out the information from the storage **23**.

[0093] In a case where the image to be displayed is designated by the user **U** from images captured by the smartphone **10**, the CPU **21** executes the image acquisition processing of acquiring the image from the storage **23** (step **SP13**). Here, a case of displaying the image **IM** of a landscape in which a person is captured as illustrated in FIG. **9** and the like will be described as an example. A resolution of the image **IM** captured by the smartphone **10** is 4096 dots in the lateral direction and 3072 dots in the vertical direction as an example.

[0094] In the present example, the resolution of the display unit **64** of the smart glasses **50** is lower than the resolution of the image **IM**. Thus, the CPU **21** adjusts the resolution of the image **IM** in accordance with the resolution of the display unit **64** of the smart glasses **50**. Adjustment of the resolution of the image **IM** is equivalent to adjustment of an image size. In an initial state, the image **IM** has a size in which the entire image **IM** falls within the entire screen of the display unit **64**. The CPU **21** adjusts the image **IM** to the image size of the initial state and displays the image **IM** on the smart glasses **50** (step **SP14**).

[0095] Next, as illustrated in FIG. **12**, the CPU **21** of the smartphone **10** displays a display screen **IV** on the touch panel **24** for a state where the first operation instruction for changing the display magnification of the image **IM** displayed on the smart glasses **50** and the second operation instruction for scrolling the image **IM** are received from the user **U** (step **SP15**). The display screen **IV** is an operation screen displayed on the touch panel **24** in a case of displaying the image **IM** on the smart glasses **50**.

[0096] In the present example, an example in which the image **IM** is not displayed on the display screen **IV** of the smartphone **10**, and in which the image **IM** is displayed on only the smart glasses **50** will be described. In a case of displaying the image **IM** on the smart glasses **50**, the image **IM** may also be displayed on the display screen **IV**.

[0097] In a case where the first operation instruction for changing the display magnification of the image **IM** or the second operation instruction for scrolling the image **IM** is input through the display screen **IV** (a Yes determination in step **SP16**), the CPU **21** acquires the input operation instruction. Step **SP16** is an example of operation instruction acquisition processing of acquiring the first operation instruction or the second operation instruction. Next, the CPU **21** executes display control processing of changing of the display magnification and scrolling of the image **IM** in accordance with the acquired operation instruction, generates the image **IM** of which a display

aspect is changed, and displays the image IM on the smart glasses **50** (step SP18).

[0098] The processing of changing of the display magnification and scrolling of the image IM (steps SP16 to SP18) is repeated until an instruction to end the image display is input from the user U.

[0099] After checking of the image IM ends, the user U inputs the instruction to end the image display into the smartphone **10**. For example, the input of the instruction to end the image display is provided by a physical button, not illustrated, provided in the smartphone **10** or by a return button, not illustrated, in the touch panel **24**. In a case where the instruction to end the image display is input (a Yes determination in step SP19), the CPU **21** stops displaying the image IM and ends the processing.

[0100] In addition, in a state where the display screen IV is displayed (step SP15), and then, none of the operation instructions for changing of the display magnification and scrolling of the image IM is input (a No determination in step SP16), in a case where the instruction to end the image display is input (a Yes determination in step SP19), the CPU **21** stops displaying the image IM in the initial state and ends the processing.

[0101] Here, processing in changing of the display magnification and processing in scrolling of the image IM will be individually described in detail.

[0102] First, changing of the display magnification of the image IM will be described. As illustrated in FIG. **12**, the zoom magnification input unit **30** is displayed on the display screen IV. In the image display mode, the zoom magnification input unit **30** is displayed as an operation unit for changing the display magnification of the image IM. For example, the zoom magnification input unit **30** is displayed at almost the same position as the imaging screen IP. Accordingly, the magnification changing operation for changing the display magnification can be performed by the same operation as the zoom magnification changing operation performed in a case of imaging.

[0103] A magnification input region **24b** is a region in which an input of the magnification changing operation for changing the display magnification is received. The magnification input region **24b** is set to have a rectangular shape wider than the zoom magnification input region **24a**. The magnification input region **24b** is a second region according to the embodiment of the disclosed technology.

[0104] The CPU **21** detects, as the magnification changing operation for changing the display magnification, the swipe operation of moving the magnification designation line **30b** within the magnification input region **24b** in the touch panel **24**. At this point, in a case where a finger is brought into contact with a position separated from the magnification designation line **30b** within the magnification input region **24b**, the CPU **21** handles the finger as being in contact with the closest position in the magnification designation line **30b** from the contact position of the finger and detects the swipe operation with respect to the magnification designation line **30b** as the magnification changing operation.

[0105] FIG. **13** is a graph showing a relationship between a swipe amount (that is, an operation amount) and a magnification in the magnification changing operation. A state where a lower limit value of the magnification shown on the magnification designation line **30b** of the zoom magnification input unit **30** is superimposed on the magnification display unit **30a** is set as a reference position (that is, a swipe amount of 0), and a relationship between the swipe amount from the reference position and an amount of change in the zoom magnification is shown in a graph R1. In the zoom magnification input unit **30**, as described above, the reference position indicates the zoom magnification (a magnification of 1) at the wide angle end in the image capturing mode. On the other hand, in the image display mode, the reference position indicates that the display magnification of the image IM is the same magnification (a magnification of 1). Display at the same magnification (a magnification of 1) is a state where the entire image IM of the initial state matching the resolution of the touch panel **24** is displayed on the smart glasses **50** as illustrated in FIG. **5**.

[0106] In the graph **R1**, the magnification changes in proportion to the swipe amount. In the image capturing mode, in a case where the swipe operation is performed, the CPU **21** determines the zoom magnification corresponding to the swipe amount from the relationship shown in the graph **R1**. As the swipe amount is increased, the zoom magnification is increased. In the image display mode, in a case where the swipe operation is performed, the CPU **21** determines the display magnification corresponding to the swipe amount from the relationship shown in the graph **R1**. As the swipe amount is increased, the display magnification is increased. As the display magnification is increased, the image **IM** is displayed in an enlarged manner. The relationship between the operation amount and the magnification shown in the graph **RI** is used for both of changing of the zoom magnification in the image capturing mode and changing of the display magnification in the image display mode. Thus, in a case where the swipe operation of the same swipe amount as the swipe operation in the image capturing mode is performed in the image display mode, the CPU **21** changes the display magnification of the image **IM** by the same amount as the amount of change in the zoom magnification in the image capturing mode.

[0107] As illustrated in FIG. **14**, the swipe operation for changing the magnification in the image display mode is the swipe operation of an arc shape and is the same as the zoom magnification changing operation in the image capturing mode. The CPU **21** detects the swipe operation of an arc shape as the magnification changing operation. For example, the swipe operation of an arc shape in the touch panel **24** is the swipe operation of an arc shape of which a radius is greater than or equal to 3 cm and less than or equal to 8 cm. This swipe operation has a shape and a range in which the operation can be comfortably performed in a case where the user **U** holds the smartphone **10** in a hand and performs the swipe operation with a thumb.

[0108] In a case where the swipe operation is input within the magnification input region **24b** (refer to step **SP16** in FIG. **11**), the CPU **21** acquires the swipe operation as the first operation instruction.

[0109] The CPU **21** executes the display control processing of changing the display magnification of the image **IM** displayed on the smart glasses **50** in accordance with the zoom magnification changing operation which is the first operation instruction (refer to step **SP17** in FIG. **11**). At this point, the CPU **21** controls an amount of change in the display magnification of the image **IM** in accordance with the amount of change in the magnification with respect to the operation amount of the zoom magnification changing operation.

[0110] In addition, as an example, a center position in a case of changing the display magnification of the image **IM** is a center position of the image **IM** currently displayed on the smart glasses **50**. As illustrated in FIG. **15**, in the initial state, the center position of the entire image **IM** is an initial position **C0** of the center position in a case of changing the display magnification. That is, in a case of enlarging the image **IM** in accordance with the display magnification, the image **IM** is enlarged with respect to the initial position **C0** as a center. A region **DA** indicates a region displayed on the smart glasses **50** in a case where the image **IM** is enlarged with respect to the initial position **C0** as a center.

[0111] The center position can be changed from the initial position **C0**. For example, the center position may be designatable by causing the user **U** to touch any position in the image **IM**. Accordingly, the image **IM** can be enlarged with respect to a region of interest for the user **U** in the image **IM** as a center.

[0112] Next, scrolling of the image **IM** will be described. In a state where the entire image **IM** is not displayed on the smart glasses **50** because of a change in the display magnification of the image **IM**, the image **IM** can be scrolled. For example, as illustrated in FIG. **15**, in a case where the region **DA** that is a part of the image **IM** is displayed, the region **DA** displayed within the image **IM** can be changed by scrolling the image **IM**.

[0113] For scrolling, the user **U** designates a scroll direction by moving the smartphone **10** as in the case of imaging to adjust the direction of the imaging lens **26a** of the smartphone **10**. For example, in a case where the image **IM** is to be scrolled rightward, the direction of the imaging lens **26a** of

the smartphone **10** is inclined rightward from a reference direction. In addition, in a case where the image IM is to be scrolled upward, the direction of the imaging lens **26a** of the smartphone **10** is inclined upward from the reference direction.

[0114] Regarding the reference direction, for example, the reference direction in a left-right direction is set to the direction of the imaging lens **26a** of the smartphone **10** when a transition is made to the image display mode in step SP11 illustrated in FIG. **11**. In addition, for example, the reference direction in an up-down direction is set to a direction in which the direction of the imaging lens **26a** of the smartphone **10** is the horizontal direction.

[0115] The CPU **21** constantly monitors the posture of the smartphone **10** detected by the posture detection unit **27** and acquires a change in the posture of the smartphone **10** as the second operation instruction (refer to step SP16 in FIG. **11**).

[0116] The CPU **21** executes the display control processing of scrolling the image IM displayed on the smart glasses **50** in accordance with the second operation instruction (step SP17).

[0117] For example, in a case where rightward inclination of the direction of the imaging lens **26a** of the smartphone **10** from the reference direction is detected, the CPU **21**, as illustrated in FIG. **16**, scrolls the image IM rightward from the state illustrated in FIG. **15**. Accordingly, the region DA displayed on the smart glasses **50** in the image IM is changed to a right side portion within the image IM. In addition, in a case where the direction of the imaging lens **26a** of the smartphone **10** is inclined upward from the reference direction, the CPU **21**, as illustrated in FIG. **17**, scrolls the image IM upward from the state illustrated in FIG. **15**. Accordingly, the region DA displayed on the smart glasses **50** in the image IM is changed to an upper side within the image IM.

Action and Effect

[0118] The CPU **21** (corresponds to the processor) of the smartphone **10** (corresponds to the imaging apparatus and the display control device) in the present embodiment executes the image acquisition processing of acquiring the image to be displayed on the smart glasses **50** (corresponds to the wearable monitor), the first operation instruction acquisition processing of acquiring the first operation instruction that is input through the operation of the operation unit of the smartphone **10** which is a separate body from the smart glasses **50**, in order to change the display magnification of the image and that is input through the magnification changing operation in the smartphone **10**, and the display control processing of changing the display magnification of the image in accordance with the first operation instruction.

[0119] Accordingly, since the user U can change the display magnification of the image displayed on the smart glasses **50** by performing the magnification changing operation in the smartphone **10**, the display control device having high usability can be provided.

[0120] Generally, the display resolution of the wearable monitor such as the smart glasses **50** is lower than the resolution of the image acquired by the imaging apparatus such as the smartphone **10**. Thus, an operation frequency of an operation of displaying the image in an enlarged manner by changing the display magnification of the image in order to check noise and the like of the image in detail in the wearable monitor is high.

[0121] According to the disclosed technology, the display magnification changing operation of the image having a high operation frequency can be performed with the same sense of operation as the zoom magnification changing operation performed in a case of imaging as in the present example. Thus, even in a state where wearing the wearable monitor such as the smart glasses **50** blocks a part of the field of view, the user U can easily perform the magnification changing operation. This is because enlarging and reducing of the displayed image are common in both of changing of the zoom magnification in imaging and changing of the display magnification in image display, and the user U is considered to be familiar with the zoom magnification changing operation in the imaging apparatus such as the smartphone **10**. Accordingly, the display control device having good operability and high usability for the user can be provided.

[0122] In the present example, an example in which the magnification changing operation in the

imaging apparatus is the zoom magnification changing operation in imaging of the smartphone **10** which is an example of the imaging apparatus, and in which the display magnification of the image of the wearable monitor is changed by the same operation as the zoom magnification changing operation is described. However, the disclosed technology is not limited thereto. Changing of the zoom magnification is an example, and the magnification changing operation according to the embodiment of the present invention can also be applied to, for example, changing of a magnification of an extender lens of a TV lens. The magnification changing operation in the imaging apparatus may be the display magnification changing operation of changing the display magnification of the image in a case of displaying the image on the smartphone **10** which is an example of the imaging apparatus. That is, the display magnification of the image of the wearable monitor may be changed by the same operation as the display magnification changing operation of the image in the imaging apparatus.

[0123] In addition, in the display control processing, the CPU **21** controls the amount of change in the display magnification of the image IM in accordance with the amount of change in the magnification with respect to the operation amount of the magnification changing operation. Such an aspect enables the display magnification of the image displayed on the smart glasses **50** to be changed with the same sense of operation as the magnification changing operation in the smartphone **10** and thus, is preferable.

[0124] In addition, the CPU **21** further executes the second operation instruction acquisition processing of acquiring a change in the posture of the smartphone **10** detected by the posture detection unit **27**, which detects the posture of the smartphone **10**, as the second operation instruction and scrolls the image in accordance with the second operation instruction in the display control processing. Such an aspect enables a scroll operation to be performed with the same sense as inclining the smartphone **10** toward a desired subject in a case of imaging.

[0125] In addition, the smartphone **10** comprises the touch panel **24**. In a case where the zoom magnification changing operation in a case of imaging of the smartphone **10** is the swipe operation within the zoom magnification input region **24a** in the touch panel, the CPU **21** detects, as an operation of changing the display magnification of the image, the swipe operation within the magnification input region **24b** that includes the zoom magnification input region **24a** and that is wider than the zoom magnification input region **24a** in the touch panel **24**. Such an aspect enables the swipe operation to be detected even in a case where a position of the finger of the swipe operation is separated from the magnification designation line **35b** because the user U performs the display magnification changing operation without seeing the touch panel **24**. Thus, the display control device of higher usability is implemented.

[0126] In addition, the CPU **21** detects the swipe operation of an arc shape of which a radius R is greater than or equal to 3 cm and less than or equal to 8 cm in the touch panel **24** as the display magnification changing operation. The swipe operation of an arc shape of which the radius R is greater than or equal to 3 cm and less than or equal to 8 cm has a shape in which the swipe operation can be comfortably performed in a case where the user U holds the smartphone **10** in a hand and performs the swipe operation with a thumb. Such an aspect can provide the display control device of higher usability. In a case where the radius R of the swipe operation of an arc shape is below 3 cm, the operation has to be performed by extremely bending the thumb. Thus, it is difficult to perform the swipe operation. In addition, in a case where the radius R of the swipe operation of an arc shape is above 8 cm, a case where the radius R cannot be reached even by fully stretching the thumb occurs. Thus, it is difficult to perform the swipe operation.

[0127] In addition, the image IM displayed on the smart glasses **50** is the image captured by the smartphone **10**. That is, capturing of the image IM and changing of the display magnification in a case of displaying the image IM can be performed by the same smartphone **10**. Thus, the display control device of high usability is implemented.

Second Embodiment

[0128] Next, a second embodiment of the present disclosure will be described. In an image display system **2** according to the second embodiment, an apparatus that functions as the display control device is not the smartphone **10** and is changed to the smart glasses **50** unlike in the first embodiment. That is, as will be described later, the smart glasses **50** execute the image acquisition processing, the first operation instruction acquisition processing, and the display control processing. In addition, in the second embodiment, the image to be displayed on the smart glasses **50** is not acquired from the smartphone **10** and is changed to be acquired from an external server **70** unlike in the first embodiment.

[0129] Hardware configurations of the smartphone **10** and the smart glasses **50** are the same as in the first embodiment. Thus, duplicate content of the first embodiment will not be described. FIG. **18** is a schematic configuration diagram of an image display system including a display control device according to the second embodiment.

[0130] As illustrated in FIG. **18**, the image display system **2** comprises the smartphone **10** and the smart glasses **50**. The CPU **61** of the smart glasses **50** is an example of the processor according to the embodiment of the disclosed technology. In addition, the memory **62** is an example of the memory according to the embodiment of the disclosed technology. The smart glasses **50** comprising the CPU **61** and the memory **62** also function as the display control device according to the embodiment of the disclosed technology. The CPU **61** of the smart glasses **50** acquires the image to be displayed on the smart glasses **50** from the external server **70**.

[0131] The smartphone **10** and the smart glasses **50** are wirelessly directly connected. The smartphone **10** and the server **70** are wirelessly connected through a network **71**. In the same manner, the smart glasses **50** and the server **70** are wirelessly connected through the network **71**.

Flow of Processing

[0132] Next, processing performed in the present embodiment will be described. FIG. **19** is a flowchart for describing processing in image display in the image display system **2**.

[0133] In a case where the instruction to set the image display mode is input from the user **U**, the CPU **21** of the smartphone **10** transitions to the image display mode (step SP21).

[0134] In a case where the image to be displayed is designated by the user **U** from images stored in the server **70**, the CPU **21** transmits image designation information indicating the designated image to the server **70** (step SP22).

[0135] In a case where the image designation information is received from the smartphone **10** (step SS21), the server **70** transmits the designated image to the smart glasses **50** (step SS22).

[0136] The CPU **61** of the smart glasses **50** executes the image acquisition processing of acquiring the image **IM** to be displayed on the display unit **64** by receiving the image from the server **70** (step SG21). Next, the CPU **61** adjusts the resolution of the acquired image in accordance with the resolution of the display unit **64** of the smart glasses **50**. In the initial state, the image has a size in which the entire image falls within the entire screen of the display unit **64**. The CPU **61** adjusts a size of the image **IM** to the image size of the initial state and displays the image **IM** on the display unit **64** (step SG22).

[0137] Next, in step SP23, the CPU **21** of the smartphone **10** displays the display screen **IV** illustrated in FIG. **12** on the touch panel **24** for a state where the instructions to change the display magnification and to scroll the image displayed on the smart glasses **50** are received from the user **U**.

[0138] In a case where the first operation instruction for changing the display magnification of the image or the second operation instruction for scrolling the image **IM** is input (a Yes determination in step SP24), the CPU **21** transmits the operation instruction to the server **70** (step SP25).

[0139] In a case where any of the first operation instruction and the second operation instruction is received from the smartphone **10** (step SS23), the server **70** transmits the operation instruction to the smart glasses **50** (step SS24).

[0140] The CPU **61** of the smart glasses **50** executes the operation instruction acquisition

processing of acquiring the operation instruction as an instruction to change the display aspect by receiving the operation instruction from the server **70** (step SG23). Next, the CPU **61** executes the display control processing of changing the display magnification or of scrolling the image IM in accordance with the operation instruction and displays the image IM of which the display aspect is changed by changing of the display magnification or by scrolling on the display unit **64** (step SG24).

[0141] In the smartphone **10**, the processing of changing the display magnification and of scrolling the image is repeated until the instruction to end the image display is input from the user U (steps SP24 to SP26). The smart glasses **50** and the server **70** also repeat the processing illustrated in FIG. **19** in accordance with the processing of the smartphone **10**.

[0142] After checking of the image ends, the user U inputs the instruction to end the image display into the smartphone **10**. For example, the input of the instruction to end the image display is provided by the physical button, not illustrated, provided in the smartphone **10** or by the return button, not illustrated, in the touch panel **24**. In a case where the instruction to end the image display is input (a Yes determination in step SP26), the CPU **21** of the smartphone **10** transmits a display ending instruction to the server **70** (step SP27) and ends the processing.

[0143] In a case where the display ending instruction is received from the smartphone **10** (step SS25), the server **70** transmits the display ending instruction to the smart glasses **50** (step SS26).

[0144] In a case where the display ending instruction is received from the server **70**, the CPU **61** of the smart glasses **50** ends the display of the image on the display unit **64** (step SG25).

Action and Effect

[0145] In the present embodiment, the smart glasses **50** which are an example of the wearable monitor according to the embodiment of the disclosed technology also functions as the display control device according to the embodiment of the disclosed technology. In addition, the CPU **61** of the smart glasses **50** acquires the image IM from the external server **70** in the image acquisition processing and acquires the first operation instruction and the second operation instruction through the server **70** in the operation instruction acquisition processing.

[0146] Such an aspect enables images other than the image captured by the smartphone **10** to be acquired from the server **70** and displayed on the smart glasses **50**.

[0147] In addition, in a case of displaying the image IM on the smart glasses **50**, all pieces of data acquired by the smart glasses **50** are acquired from the server **70**. Thus, in a case of displaying the image, the smart glasses **50** do not need to communicate with the smartphone **10** and may communicate with only the server **70**. Accordingly, a load of communication processing with respect to the smartphone **10** can be reduced.

Third Embodiment

[0148] Next, a third embodiment of the present disclosure will be described. An image display system according to the third embodiment is different from the second embodiment in that the CPU **61** of the smart glasses **50** directly acquires the first operation instruction and the second operation instruction in the display control processing and the display ending instruction in a case of ending the image display, from the smartphone **10** without passing through the server **70** (refer to steps SP35 and SP37 and steps SG33 and SG35). Hardware configurations of the smartphone **10** and the smart glasses **50** are the same as in the second embodiment and thus, will not be described.

Flow of Processing

[0149] Next, processing performed in the present embodiment will be described. FIG. **20** is a flowchart for describing processing in image display in the image display system of the present embodiment.

[0150] In a case where the instruction to set the image display mode is input from the user U, the CPU **21** of the smartphone **10** transitions to the image display mode (step SP31).

[0151] In a case where the image to be displayed is designated by the user U from the images stored in the server **70**, the CPU **21** transmits the image designation information indicating the

designated image to the server **70** (step SP32).

[0152] In a case where the image designation information is received from the smartphone **10** (step SS31), the server **70** transmits the designated image to the smart glasses **50** (step SS32).

[0153] In a case where the image is received from the server **70**, the CPU **61** of the smart glasses **50** executes the image acquisition processing of acquiring the image as the image to be displayed on the display unit **64** (step SG31). Next, the CPU **61** adjusts the resolution of the acquired image in accordance with the resolution of the display unit **64** of the smart glasses **50**. In the initial state, the image has a size in which the entire image falls within the entire screen of the display unit **64**. The CPU **61** adjusts the image to the image size of the initial state and displays the image on the display unit **64** (step SG32).

[0154] Next, in step SP33, the CPU **21** of the smartphone **10** displays the display screen IV illustrated in FIG. **12** on the touch panel **24** for a state where the instructions to change the display magnification and to scroll the image displayed on the smart glasses **50** are received from the user U (step SP33).

[0155] In a case where the first operation instruction for changing the display magnification of the image or the second operation instruction for scrolling the image IM is input (a Yes determination in step SP34), the CPU **21** transmits the operation instruction to the smart glasses **50** (step SP35).

[0156] The CPU **61** of the smart glasses **50** executes the operation instruction acquisition processing of acquiring the operation instruction as an instruction to change the display aspect by directly receiving the operation instruction from the smartphone **10** (step SG33). Next, the CPU **61** executes the display control processing of changing the display magnification or of scrolling the image IM in accordance with the operation instruction and displays the image of which the display aspect is changed by changing of the display magnification or by scrolling on the display unit **64** (step SP34).

[0157] In the smartphone **10**, the processing of changing the display magnification and of scrolling the image is repeated until the instruction to end the image display is input from the user U (steps SP34 to SP36). The smart glasses **50** and the server **70** also repeat the processing illustrated in FIG. **20** in accordance with the processing of the smartphone **10**.

[0158] After checking of the image ends, the user U inputs the instruction to end the image display into the smartphone **10**. For example, the input of the instruction to end the image display is provided by the physical button, not illustrated, provided in the smartphone **10** or by the return button, not illustrated, in the touch panel **24**. In a case where the instruction to end the image display is input (a Yes determination in step SP36), the CPU **21** of the smartphone **10** transmits the display ending instruction to the smart glasses **50** (step SP37) and ends the processing.

[0159] In a case where the display ending instruction is directly received from the smartphone **10**, the CPU **61** of the smart glasses **50** ends the display of the image on the display unit **64** (step SG35).

Action and Effect

[0160] In the present embodiment, the smart glasses **50** which are an example of the wearable monitor according to the embodiment of the disclosed technology also functions as the display control device according to the embodiment of the disclosed technology. In addition, the CPU **61** of the smart glasses **50** acquires the image from the external server **70** in the image acquisition processing and directly acquires the first operation instruction and the second operation instruction from the smartphone **10** in the operation instruction acquisition processing.

[0161] Such an aspect enables images other than the image captured by the smartphone **10** to be acquired from the server **70** and displayed on the smart glasses **50**.

[0162] In addition, the smart glasses **50** directly acquire the first operation instruction and the second operation instruction for performing the display control processing such as changing of the display magnification and scrolling of the image from the smartphone **10** without passing through the server **70**. Thus, a time lag (a time lag caused by communication delay) from the input of the

operation instruction into the smartphone **10** by the user U to the changing of the display aspect can be reduced, compared to a case where the first operation instruction and the second operation instruction are acquired through the server **70**.

Fourth Embodiment

[0163] Next, a fourth embodiment of the present disclosure will be described. An image display system according to the fourth embodiment is different from the first embodiment in that the initial position **C0** of the center position in a case of changing the display magnification of the image is changed in the display control processing in the CPU **21** of the smartphone **10**. In the present embodiment, hardware configurations of the smartphone **10** and the smart glasses **50** are the same as in the first embodiment and thus, will not be described.

[0164] As illustrated in FIG. **21**, an image file **F1** of the image **IM** handled in the present embodiment has accessory information data **D2** in addition to image data **D1**. The accessory information data **D2** includes, in addition to information such as a capturing date and time of the image and a capturing location of the image, information **D2a** about a tilt angle that is an inclination angle of the smartphone **10** with respect to the horizontal direction in capturing the image.

[0165] As illustrated in FIG. **22**, in the embodiment of the disclosed technology, a tilt angle θ_{tilt} is specifically an angle between the optical axis direction **Z** (synonymous with the imaging direction) of the imaging lens **26a** of the smartphone **10** and a horizontal direction **H**. The tilt angle θ_{tilt} is 0° in a case where the optical axis direction **Z** is directed in the horizontal direction **H**, a positive angle in a case where the optical axis direction **Z** is directed upward from the horizontal direction **H**, and a negative angle in a case where the optical axis direction **Z** is directed downward from the horizontal direction **H**.

[0166] FIG. **23** is a diagram for describing the initial position **C0** of the center position in a case of changing the display magnification in the image **IM**. In FIG. **23**, a coordinate of the image **IM** in an **X** direction (that is, the lateral direction in FIG. **23**) is denoted by **X**, and a coordinate of the image **IM** in a **Y** direction (that is, the vertical direction in FIG. **23**) is denoted by **Y**. Regarding the two-dimensional coordinates (**X**, **Y**) of the image **IM**, lower left coordinates are set as an origin (0, 0), and upper right coordinates are set as an apex (100, 100). In addition, both of the **X** coordinate and the **Y** coordinate show values obtained by normalizing the maximum value of the number of pixels of the image **IM** to **100**.

[0167] In the first embodiment, coordinates of the initial position **C0** of the center position in a case of changing the display magnification of the image are (50, 50) which is a coordinate position of the center position of the image **IM**. Meanwhile, in the present embodiment, the CPU **21** of the smartphone **10** changes the coordinate position of the initial position **C0** of the center position in a case of changing the display magnification of the image from the default coordinate position (50, 50) based on the information **D2a** about the tilt angle included in the image file **F1**.

[0168] Regarding changing of the initial position **C0** of the center position in a case of changing the display magnification of the image, the coordinate position (50, 50) of the initial position **C0** of the center position is not changed from the default position in a case where the tilt angle θ_{tilt} is 0 as illustrated in FIG. **24** as an example. In addition, in a case where the tilt angle θ_{tilt} is positive, an amount of change in the center position on a **Y** axis is linearly changed from 0 to 50 with respect to the tilt angle θ_{tilt} greater than 0° and less than or equal to 45° . In a case where the tilt angle θ_{tilt} is above 45° , the amount of change in the center position on the **Y** axis is 50.

[0169] In addition, in a case where the tilt angle θ_{tilt} is negative, the amount of change in the center position on the **Y** axis is linearly changed from 0 to -50 with respect to the tilt angle θ_{tilt} greater than or equal to -45° and less than 0° . In a case where the tilt angle θ_{tilt} is below -45° , the amount of change in the center position on the **Y** axis is -50 . That is, in a case where the tilt angle is positive, the initial position **C0** of the center position in a case of changing the display magnification of the image **IM** is in an upper part within the image **IM**. In a case where the tilt

angle is negative, the initial position **C0** of the center position in a case of changing the display magnification of the image **IM** is in a lower part within the image **IM**. As an example, in a case where the tilt angle θ_{tilt} is 22.5° , the coordinates of the initial position of a center position **C0a** after change are changed to (50, 75) as illustrated in FIG. 23.

[0170] In the present embodiment, the image file **F1** of the image **IM** includes, in addition to the image data **D1**, the information **D2a** about the tilt angle which is the inclination angle of the smartphone **10** with respect to the horizontal direction in capturing the image **IM**, as the accessory information data **D2**. In this case, the CPU **21** of the smartphone **10** changes the initial position **C0** of the center position in a case of changing the display magnification of the image **IM**, in the display control processing based on the information **D2a** about the tilt angle.

[0171] For example, in a case of capturing a landscape photo at a distance, in a case where the direction of the imaging lens **26a** of the smartphone **10** is directed upward, a region closer to the sky is captured. In this state, in a case where the zoom magnification changing operation is performed, the zoom magnification is changed with respect to the sky as a center.

[0172] In the aspect of the present embodiment, even with the image **IM** that has already been captured, the initial position **C0** of the center position in a case of changing the display magnification of the image **IM** is changed to an upper part of the image **IM** in a case where the tilt angle in imaging is positive, that is, in a case where the image **IM** is captured in a state where the optical axis direction **Z** of the imaging apparatus is directed upward. Thus, in a case of image display, the user **U** can feel the sense of zoom changing in a case of imaging in a pseudo manner.

Fifth Embodiment

[0173] Next, a fifth embodiment of the present disclosure will be described. An image display system according to the fifth embodiment is different from the first embodiment in that the image **IM** is corrected to be in the horizontal direction in a case of displaying the image **IM** on the smart glasses **50**. In the present embodiment, hardware configurations of the smartphone **10** and the smart glasses **50** are the same as in the first embodiment and thus, will not be described.

[0174] As illustrated in FIG. 25, an image file **F2** of the image **IM** handled in the present embodiment has the accessory information data **D2** in addition to the image data **D1**. The accessory information data **D2** includes, in addition to the information such as the capturing date and time of the image and the capturing location of the image, information **D2b** about a roll angle that is a rotation angle of the smartphone **10** about the optical axis direction **Z** (synonymous with the imaging direction) with respect to the horizontal direction in capturing the image.

[0175] As illustrated in FIG. 26, in the embodiment of the disclosed technology, a roll angle θ_{roll} is specifically an angle between a lateral direction **HP** of the smartphone **10** in imaging and the horizontal direction **H**. In imaging of the smartphone **10**, changing an angle of the housing **11** of the smartphone **10** with respect to the horizontal direction **H** can switch between capturing of a vertically long image and capturing of a laterally long image. In either case, a direction of the smartphone **10** corresponding to the lateral direction (longitudinal direction) of the image **IM** is the lateral direction **HP**.

[0176] In a case where the imaging direction of the smartphone **10** is set to a rear side of the page of FIG. 26, the roll angle θ_{roll} is a positive angle in a case where a right end of the smartphone **10** is above the horizontal direction **H** with respect to the optical axis direction **Z** as a center in FIG. 26, that is, in a state where the smartphone **10** is rotated counterclockwise. In addition, the roll angle θ_{roll} is a negative angle in a case where the right end of the smartphone **10** is below the horizontal direction **H** with respect to the optical axis direction **Z** as a center in FIG. 26 (FIG. 26 illustrates this state), that is, in a case where the smartphone **10** is rotated clockwise.

[0177] FIG. 26 illustrates a state where a laterally long image is captured by the smartphone **10**. In this state, a longitudinal direction of the housing **11** of the smartphone **10** is the lateral direction **HP** of the smartphone **10**. In addition, in FIG. 26, a state where the roll angle θ_{roll} of the smartphone **10** in capturing the image is negative is illustrated. In a case where the image is captured in this

state, a horizontal direction HI of the subject in the image IM is in a state of being rotated counterclockwise about a center CI of the image IM as an axis as illustrated in FIG. 27.

[0178] In a case of displaying the image on the smart glasses 50, the CPU 21 of the smartphone 10 corrects the image IM with respect to the horizontal direction. As the correction in the horizontal direction, for example, the entire image IM may be rotated by the same angle as the roll angle θ_{roll} about the center CI of the image IM as an axis. At this point, a direction in which the image IM is rotated counterclockwise corresponds to a positive angle. In addition, a direction in which the image IM is rotated clockwise corresponds to a negative angle.

[0179] As illustrated in FIG. 27 as an example, in a case of the image IM captured in a state where the roll angle θ_{roll} is -20° , the horizontal direction HI of the subject in the image IM is in a state of being rotated counterclockwise by 20° about the center CI of the image IM as an axis. Thus, as illustrated in FIG. 28, by rotating the entire image IM by -20° , which is the same angle as the roll angle θ_{roll} , about the center CI of the image IM as an axis, the horizontal direction HI of the subject in the image IM can be matched to the left-right direction of the image IM.

[0180] Such an aspect enables the horizontal direction of the subject to match the left-right direction of the image IM even in a case where the image is captured in an inclined state. Thus, an image that does not make the user U feel unnatural can be displayed on the smart glasses 50.

Sixth Embodiment

[0181] Next, a sixth embodiment of the present disclosure will be described. An image display system according to the sixth embodiment is a configuration for matching the amount of change in the magnification with respect to the operation amount of the magnification changing operation in a case of imaging to the amount of change in the magnification with respect to the operation amount in a case of changing the display magnification of the image, particularly in a case where an imaging apparatus that has performed imaging is different from an imaging apparatus for inputting the operation instruction such as the magnification changing operation and scrolling of the image.

[0182] In the present embodiment, content of the display control processing in the CPU 21 of the smartphone 10 is different from the first embodiment. In the present embodiment, hardware configurations of the smartphone 10 and the smart glasses 50 are the same as in the first embodiment and thus, will not be described.

[0183] As illustrated in FIG. 29, an image file F3 of the image handled in the present embodiment has the accessory information data D2 in addition to the image data D1. The accessory information data D2 includes, in addition to the information such as the capturing date and time of the image and the capturing location of the image, magnification changing operation-related information D2c related to the amount of change in the magnification with respect to the operation amount of the magnification changing operation in a case of imaging in the imaging apparatus that has captured the image. In the present embodiment, a case where information about the maximum zoom magnification of a smartphone that has captured the image is recorded for the magnification changing operation-related information D2c will be described as an example.

[0184] Images stored in the storage 23 of the smartphone 10 of the image display system are not necessarily limited to images captured by the smartphone 10. In a case where the maximum zoom magnification of the smartphone that has captured the image is different from the maximum zoom magnification of the smartphone 10, the sense of operation in the zoom magnification changing operation is different between the smartphone that has captured the image, and the smartphone 10.

[0185] In such a case, the CPU 21 of the smartphone 10 acquires, as the magnification changing operation-related information D2c, the information about the maximum zoom magnification of the smartphone that has captured the image, from the accessory information data D2 of the image file F3 of the image to be displayed.

[0186] FIG. 30 is a graph showing a relationship between the swipe amount (that is, the operation amount) and the magnification in the zoom magnification changing operation. Here, a case where the maximum zoom magnification of the smartphone 10 is a magnification of 5, and where the

maximum zoom magnification of the smartphone that has captured the image is a magnification of 10 will be described as an example.

[0187] A state where a lower limit value of the magnification designation line **30b** of the zoom magnification input unit **30** in the smartphone **10** is superimposed on the magnification display unit **30a** is set as a reference position (that is, a swipe amount of 0), and a relationship between the swipe amount from the reference position and the amount of change in the magnification is shown in the graph **R1**. In addition, a state where a lower limit value of a magnification designation line of a zoom magnification input unit in the smartphone that has captured the image is superimposed on a magnification display unit is set as a reference position (that is, a swipe amount of 0), and a relationship between the swipe amount from the reference position and the amount of change in the magnification is shown in a graph **R2**.

[0188] As described above, the maximum zoom magnification of the smartphone that has captured the image is a magnification of 10, and the maximum zoom magnification of the smartphone **10** is a magnification of 5. Thus, even in a case where operations of the same operation amount are performed in the zoom magnification changing operation, the amounts of change in the zoom magnification do not match.

[0189] Thus, the CPU **21** of the smartphone **10** performs processing of matching the amount of change in the zoom magnification with respect to the operation amount of the zoom magnification changing operation in the smartphone that has captured the image, to the amount of change in the zoom magnification with respect to the operation amount of the zoom magnification changing operation in the smartphone **10**, based on the information about the maximum zoom magnification of the smartphone that has captured the image. Specifically, as shown in a graph **R1a** in FIG. **30**, the display magnification at one end of the magnification designation line **30b** is set to a magnification of 1. The display magnification at the other end of the magnification designation line **30b** is set to a magnification of 10 which is the same as the maximum zoom magnification of the smartphone that has captured the image. The display magnification in the intermediate portion is set to a magnification of 1 to a magnification of 10 in accordance with the distance from the one end.

[0190] In addition, as illustrated in FIG. **31**, even in the zoom magnification input unit **30**, the display magnification at one end of the magnification designation line **30b** is set to a magnification of 1. The display magnification at the other end of the magnification designation line **30b** is set to a magnification of 10. The display magnification in the intermediate portion is set to a magnification of 1 to a magnification of 10 in accordance with the distance from the one end.

[0191] Such an aspect enables the sense of operation in the zoom magnification changing operation to be the same between the smartphone that has captured the image, and the smartphone **10** in a case where the maximum zoom magnification of the smartphone that has captured the image is different from the maximum zoom magnification of the smartphone **10**.

[0192] In a case where a size of a touch panel of the smartphone that has captured the image is different from a size of the touch panel **24** of the smartphone **10**, the sense of operation in the zoom magnification changing operation is not exactly the same between the smartphone that has captured the image, and the smartphone **10**.

[0193] In addition, in a case where a GUI in the zoom magnification changing operation of the smartphone that has captured the image is different from a GUI in the zoom magnification changing operation of the smartphone **10**, the sense of operation in the zoom magnification changing operation is not exactly the same between the smartphone that has captured the image, and the smartphone **10**.

[0194] However, even in these cases, the aspect of the present embodiment can make the sense of operation in the zoom magnification changing operation in the smartphone **10** approach the sense of operation of the smartphone that has captured the image.

Seventh Embodiment

[0195] Next, a seventh embodiment of the present disclosure will be described. An image display system according to the seventh embodiment is a configuration for matching the amount of change in the magnification with respect to the operation amount of the magnification changing operation in a case of imaging to the amount of change in the magnification with respect to the operation amount in a case of changing the display magnification of the image, particularly in a case where an imaging apparatus that has performed imaging is different from an imaging apparatus for inputting the operation instruction such as the magnification changing operation and scrolling of the image.

[0196] In the present embodiment, an interface of the zoom magnification changing operation in the smartphone **10** is different from the sixth embodiment. In addition, content of the display control processing in the CPU **21** of the smartphone **10** is different. In the present embodiment, hardware configurations of a body of the smartphone **10** and the smart glasses **50** are the same as in the first embodiment and thus, will not be described.

[0197] As illustrated in FIG. **32** and FIG. **33**, in the present embodiment, the smartphone **10** is combined with a smartphone cover **15**.

[0198] The smartphone cover **15** comprises a cover unit **16** and a ring-type controller **18**. The cover unit **16** engages with the smartphone **10**. In the cover unit **16**, an opening **17** for exposing the imaging lens **26a** of the smartphone **10** in a case where the smartphone **10** is engaged is formed. In addition, the ring-type controller **18** is attached to a rear surface **16b** of the cover unit **16** in a rotatable manner with respect to the cover unit **16**.

[0199] The ring-type controller **18** is rotatable with respect to the cover unit **16** like a zoom ring of a general digital camera and functions as an interface for the zoom magnification changing operation and for the display magnification changing operation in the smartphone **10**. A detection unit, not illustrated, that detects a rotation direction and a rotation angle of the ring-type controller **18** is comprised inside the ring-type controller **18**. Signals indicating the rotation direction and the rotation angle of the ring-type controller **18** detected by the detection unit are transmitted to the smartphone **10** by a communication unit, not illustrated. The communication unit uses standards such as Bluetooth (registered trademark).

[0200] As illustrated in FIG. **34**, an image file **F4** of the image handled in the present embodiment has the accessory information data **D2** in addition to the image data **D1**. The accessory information data **D2** includes, in addition to the information such as the capturing date and time of the image and the capturing location of the image, magnification changing operation-related information **D2d** related to the amount of change in the magnification with respect to the operation amount of the magnification changing operation in a case of imaging in the imaging apparatus that has captured the image. In the present embodiment, a case where information about an amount of change in the magnification with respect to an amount of change in a rotation angle of a zoom ring of a digital camera that has captured the image, and information about the maximum zoom magnification of the digital camera are recorded for the magnification changing operation-related information **D2d** will be described as an example.

[0201] Images stored in the storage **23** of the smartphone **10** of the image display system are not necessarily limited to images captured by the smartphone **10**. In a case where the imaging apparatus that has captured the image is a digital camera, the sense of operation in the zoom magnification changing operation is different between the digital camera and the smartphone **10**.

[0202] Generally, in the digital camera, the zoom magnification changing operation is performed by rotating the zoom ring. However, in the smartphone **10**, the zoom magnification changing operation is performed by the swipe operation on the touch panel **24**.

[0203] The smartphone cover **15** is a cover for performing the zoom magnification changing operation in the smartphone **10** with the same sense of operation as the digital camera.

[0204] In a case where mounting of the smartphone cover **15** on the smartphone **10** is sensed, the CPU **21** of the smartphone **10** causes the ring-type controller **18** of the smartphone cover **15** to

function as an interface for the zoom magnification changing operation in the smartphone **10**.

[0205] As a method of sensing the mounting of the smartphone cover **15** on the smartphone **10** in the CPU **21** of the smartphone **10**, for example, establishment of communication between the communication unit **25** of the smartphone **10** and the communication unit of the ring-type controller **18** may be detected.

[0206] In addition, the CPU **21** of the smartphone **10** acquires, as the magnification changing operation-related information D2*d*, the information about the amount of change in the magnification with respect to the amount of change in the rotation angle of the zoom ring of the digital camera that has captured the image, and the information about the maximum zoom magnification of the digital camera from the accessory information data D2 of the image file F4 of the image to be displayed.

[0207] FIG. **35** is a graph showing a relationship between a rotation amount (that is, an operation amount) of the zoom ring or of the ring-type controller **18** and the magnification in the zoom magnification changing operation. Here, a case where the zoom magnification is increased by a magnification of 1 each time the ring-type controller **18** is rotated clockwise by 90°, and where the maximum zoom magnification is a magnification of 5 for the smartphone **10** will be described as an example. In addition, a case where the zoom magnification is increased by a magnification of 1 each time the zoom ring is rotated clockwise by 40°, and where the maximum zoom magnification is a magnification of 10 for the digital camera that has captured the image will be described.

[0208] A relationship between the rotation amount (that is, the operation amount) of the ring-type controller **18** from a reference position (that is, a rotation amount of 0) and the amount of change in the zoom magnification in the smartphone **10** is shown in a graph R10. In addition, a position of a lower limit of the magnification of the zoom ring in the digital camera that has captured the image is set as a reference position (that is, a rotation amount of 0), and a relationship between the rotation amount (that is, the operation amount) from the reference position and the amount of change in the zoom magnification is shown in a graph R20.

[0209] The ring-type controller **18** rotates endlessly and can freely rotate any number of rotations in the same direction. Thus, the reference position of the ring-type controller **18** may be, for example, a position of the ring-type controller **18** when the image in an initial display state is displayed on the display unit **64**.

[0210] As described above, the amount of change in the magnification with respect to the amount of change in the rotation angle of the zoom ring of the digital camera that has captured the image is different from that of the ring-type controller **18** mounted on the smartphone **10**. In addition, the maximum zoom magnification of the digital camera that has captured the image is different from that of the smartphone **10**. Thus, even in a case where operations of the same operation amount are performed in the zoom magnification changing operation, the amounts of change in the zoom magnification do not match.

[0211] Thus, the CPU **21** of the smartphone **10** performs processing of matching the amount of change in the zoom magnification with respect to the operation amount of the zoom magnification changing operation in the digital camera that has captured the image to the amount of change in the zoom magnification with respect to the operation amount of the zoom magnification changing operation in the smartphone **10**, based on the information about the amount of change in the magnification with respect to the amount of change in the rotation angle of the zoom ring of the digital camera that has captured the image, and on the information about the maximum zoom magnification of the digital camera. Specifically, as shown in a graph R10*a* in FIG. **30**, the zoom magnification is set to be increased by a magnification of 1 each time an operation input of the ring-type controller **18** mounted on the smartphone **10** is clockwise rotation by 40°. In addition, the maximum zoom magnification is set to a magnification of 10.

[0212] Such an aspect can make the sense of operation in the zoom magnification changing operation in the smartphone **10** approach the sense of operation of the digital camera that has

captured the image.

Eighth Embodiment

[0213] Next, an eighth embodiment of the present disclosure will be described. An image display system according to the eighth embodiment is different from the first embodiment in that a scroll amount in a case of scrolling the image in accordance with the second operation instruction is corrected in the display control processing in the CPU **21** of the smartphone **10**. In the present embodiment, hardware configurations of the smartphone **10** and the smart glasses **50** are the same as in the first embodiment and thus, will not be described.

[0214] As illustrated in FIG. **36**, an image file F5 of the image IM handled in the present embodiment has the accessory information data D2 in addition to the image data D1. The accessory information data D2 includes, in addition to the information such as the capturing date and time of the image and the capturing location of the image, angle-of-view information D2e related to an angle of view of the smartphone **10** in capturing the image.

[0215] The angle-of-view information D2e may be information with which the angle of view of the smartphone **10** in imaging can be specified. The angle-of-view information D2e may be information about the angle of view or may be information about the zoom magnification corresponding to the angle of view. In a case of acquiring the information about the zoom magnification, information about the angle of view corresponding to the zoom magnification may be separately acquired. Here, the angle-of-view information D2e is an angle of view of an imaging region as an example.

[0216] As illustrated in FIG. **37**, an angle of view θ_{avw} of the smartphone **10** at the wide angle end (that is, the zoom magnification is a magnification of 1) in capturing the image is greater by a factor of 5 than an angle of view θ_{avt} at the telephoto end (that is, the zoom magnification is a magnification of 5). In addition, as the angle of view in capturing the image is increased, an inclination angle of the smartphone **10** necessary for changing the direction of the imaging lens **26a** from one end to the other end of an imaging range is increased. As in the above example, in a case where the angle of view is increased by a factor of 5, the inclination angle of the smartphone **10** necessary for changing the direction of the imaging lens **26a** from one end to the other end of the imaging range is increased by a factor of 5.

[0217] In a case of executing the display control processing of scrolling the image displayed on the display unit **64** of the smart glasses **50** in accordance with the second operation instruction, the CPU **21** of the smartphone **10** corrects the scroll amount of the image based on the angle-of-view information D2e in imaging.

[0218] Specifically, the scroll amount of the image is corrected such that the inclination angle of the smartphone **10** necessary for scrolling from one end to the other end of the image in a case of displaying the image matches the inclination angle of the smartphone **10** necessary for changing the direction of the imaging lens **26a** from one end to the other end of the imaging range in a case of capturing the image.

[0219] Such an aspect can reproduce, in a case of scrolling the image, a sense similar to a change in the imaging region in a case where the smartphone **10** is inclined in a case of capturing the image.

Modification Example

[0220] While the present disclosure is described above based on preferred embodiments, embodiments to which the present disclosure can be applied are not limited to the above embodiments.

[0221] For example, while a case where the user U performs imaging using only the smartphone **10** without wearing the smart glasses **50** in a case of capturing the image is described in the embodiments, the user U may perform imaging in a state of wearing the smart glasses **50** in a case of capturing the image. In this case, as illustrated in FIG. **38**, setting information in imaging of the smartphone **10** may be additionally displayed in an image IX displayed in a part of the field of view of the right eye. Regarding content to be displayed in the image IX, a live view of the smartphone

10 may be displayed in addition to the setting information in imaging. The live view of the smartphone **10** and the setting information may be displayed in a superimposed manner.

[0222] In addition, the smart glasses **50** are not limited to the display of the image in a part of the field of view of the right eye. The image may be displayed in a part of a field of view of a left eye, a part of the fields of view of both eyes, or the entire fields of view of both eyes.

[0223] In addition, the wearable monitor according to the embodiment of the disclosed technology is not limited to the smart glasses and may be other display devices such as a HMD.

[0224] In addition, the imaging apparatus according to the embodiment of the disclosed technology is not limited to the smartphone and may be a digital camera having the same functions as the smartphone **10**.

[0225] In addition, processing executed by causing the CPU **21** and the CPU **61** to read software (program) in each embodiment may be executed by various processors other than the CPU. Examples of the processors in this case include a programmable logic device (PLD) such as a field-programmable gate array (FPGA) of which a circuit configuration can be changed after manufacture, and a dedicated electric circuit such as an application specific integrated circuit (ASIC) that is a processor having a circuit configuration dedicatedly designed to execute specific processing. In addition, each processing may be executed by one of the various processors or may be executed by a combination of two or more processors of the same type or different types (for example, a plurality of FPGAs and a combination of a CPU and a FPGA). In addition, a hardware structure of the various processors is more specifically an electric circuit in which circuit elements such as semiconductor elements are combined.

[0226] In addition, while an aspect of storing (installing) the display control program in the storage **23** or in the storage **63** in advance is described in each embodiment, the disclosed technology is not limited thereto. The program may be provided in the form of a recording on a recording medium such as a compact disk read only memory (CD-ROM), a digital versatile disk read only memory (DVD-ROM), and a universal serial bus (USB) memory. In addition, the program may be in the form of a download from an external apparatus through a network.

[0227] In addition, the term ROM is a broad concept including a flash memory, an erasable programmable read only memory (EPROM), an electrically erasable programmable read only memory (EEPROM), and the like that are rewritable-type ROMs.

[0228] In addition, in the first to fifth embodiments, the CPU is provided to be integrated inside the wearable device or is provided to be integrated in the smartphone. However, the CPU may be provided on a network connected to the wearable device or to the smartphone, in an operating unit connected to a network, or in a cloud computing unit connected to a network.

[0229] In a case where the CPU is provided on a network or in an apparatus connected to a network, it is desirable that the network is managed by a cloud system, and the CPU connected to the network operates as a CPU virtually incorporated in the wearable device or in the smartphone through the network using cloud computing technology.

[0230] A case where changing of the display magnification or scrolling is necessary because of a difference between the resolution of the captured image and the resolution of the display image is described in each embodiment. In addition to this, there is also a case where changing of the display magnification or scrolling is necessary because of a difference in aspect ratio in panoramic imaging or the like, or a case where changing of the display magnification or scrolling is necessary because of a difference between a resolution of an image generated by interpolating processing, rendering, or the like instead of the resolution of the captured image, and the resolution of the display image. Even in these cases, the same effects as in the embodiments are obtained.

[0231] While the wearable monitor that is an example of the wearable device comprising the monitor does not comprise a camera in the embodiments, the wearable monitor may further comprise a camera and be able to perform imaging alone without being combined with the imaging apparatus. In this case, it is preferable that imaging by the camera on the imaging apparatus side

can also be performed in a case where the wearable monitor is combined with the imaging apparatus.

[0232] The above described contents and illustrated contents are detailed descriptions for parts according to the embodiment of the disclosed technology and are merely an example of the disclosed technology. For example, description related to the above configurations, functions, actions, and effects is description related to an example of configurations, functions, actions, and effects of the parts according to the embodiment of the disclosed technology. Thus, of course, unnecessary parts may be removed, new elements may be added, or parts may be replaced in the above described contents and the illustrated contents without departing from the gist of the disclosed technology. In addition, particularly, description related to common technical knowledge or the like that does not need to be described in terms of embodying the disclosed technology is omitted in the above described contents and the illustrated contents in order to avoid complication and to facilitate understanding of the parts according to the embodiment of the disclosed technology.

[0233] All documents, patent applications, and technical standards disclosed in the present specification are incorporated in the present specification by reference to the same extent as in a case where each of the documents, patent applications, technical standards are specifically and individually indicated to be incorporated by reference.

Claims

1. A display control device of a wearable device including a monitor, the display control device comprising: a memory; and at least one processor that is coupled to or incorporates the memory, and that is configured to: acquire an image to be displayed on the monitor; acquire a first operation instruction that is input through operation of an operation unit, including a graphical user interface, of a display apparatus in order to change a display magnification of the image and that is input through a magnification changing operation performed at the display apparatus, the display apparatus being a separate body from the wearable device; and change the display magnification of the image in accordance with the first operation instruction, wherein the image includes magnification changing operation-related information related to an amount of change in magnification with respect to an operation amount of the magnification changing operation performed during an imaging of the image, and the processor is further configured to match the amount of change in the magnification with respect to the operation amount of the magnification changing operation performed in the imaging, to an amount of change in magnification with respect to an operation amount when changing the display magnification of the image, based on the magnification changing operation-related information.
2. The display control device according to claim 1, wherein the magnification changing operation is based on a zoom magnification changing operation performed during the imaging of the image.
3. The display control device according to claim 1, wherein the at least one processor is configured to control an amount of change in the display magnification of the image in accordance with an amount of change in magnification with respect to an operation amount of the magnification changing operation.
4. A display control device of a wearable device including a monitor, the display control device comprising: a memory; and at least one processor that is coupled to or incorporates the memory, and that is configured to: acquire an image to be displayed on the monitor; acquire a first operation instruction that is input through operation of an operation unit of an display apparatus in order to change a display magnification of the image and that is input through a magnification changing operation performed at the display apparatus, the display apparatus being a separate body from the wearable device; change the display magnification of the image in accordance with the first operation instruction; acquire, as a second operation instruction, a change in a posture of the

display apparatus detected by a posture detection unit that detects the posture of the display apparatus; and scroll the image in accordance with the second operation instruction, wherein the image includes angle-of-view information related to an angle of view when capturing the image, and the at least one processor is further configured to correct a scroll amount when scrolling the image in accordance with the second operation instruction based on the angle-of-view information.

5. The display control device according to claim 1, wherein the at least one processor is mounted in the wearable device, and the at least one processor is configured to: acquire the image from an external server; and acquire, through the server, the first operation instruction, which is input through the operation of the operation unit of the display apparatus.

6. The display control device according to claim 1, wherein the at least one processor is mounted in the wearable device, and the at least one processor is configured to: acquire the image from an external server; and acquire, directly from the display apparatus, the first operation instruction, which is input through the operation of the operation unit of the display apparatus.

7. The display control device according to claim 1, wherein the image is captured by an imaging apparatus that is a separate apparatus from the display apparatus.

8. The display control device according to claim 7, wherein the image includes information about a tilt angle that is an inclination angle of the imaging apparatus with respect to a horizontal direction in capturing the image, and the at least one processor is configured to change an initial position of a center position in a case of changing the display magnification of the image based on the tilt angle.

9. The display control device according to claim 7, wherein the image includes information about a roll angle that is a rotation angle of the imaging apparatus about an optical axis with respect to a horizontal direction in capturing the image, and the at least one processor is configured to correct the image with respect to the horizontal direction based on the roll angle.

10. A display control method of a wearable device including a monitor, the display control method comprising: acquiring an image to be displayed on the monitor; acquiring a first operation instruction that is input through operation of an operation unit, including a graphical user interface, of a display apparatus in order to change a display magnification of the image and that is input through a magnification changing operation performed at the display apparatus, the display apparatus being a separate body from the wearable device; and changing the display magnification of the image in accordance with the first operation instruction, wherein the image includes magnification changing operation-related information related to an amount of change in magnification with respect to an operation amount of the magnification changing operation performed during an imaging of the image, and the display control method further comprises matching the amount of change in the magnification with respect to the operation amount of the magnification changing operation performed in the imaging, to an amount of change in magnification with respect to an operation amount when changing the display magnification of the image, based on the magnification changing operation-related information.

11. A non-transitory storage medium storing a program for executing display control processing by a wearable device including a monitor, the display control processing comprising: acquiring an image to be displayed on the monitor; acquiring a first operation instruction that is input through operation of an operation unit including a graphical user interface, of a display apparatus in order to change a display magnification of the image and that is input through a magnification changing operation performed at the display apparatus, the display apparatus being a separate body from the wearable device; and changing the display magnification of the image in accordance with the first operation instruction, wherein the image includes magnification changing operation-related information related to an amount of change in magnification with respect to an operation amount of the magnification changing operation performed during an imaging of the image, and the display control method further comprises matching the amount of change in the magnification with respect to the operation amount of the magnification changing operation performed in the imaging, to an amount of change in magnification with respect to an operation amount when changing the display

- magnification of the image, based on the magnification changing operation-related information.
- 12.** The display control device according to claim 4, wherein the operation unit of the display apparatus includes a graphical user interface.
- 13.** The display control device according claim 4, wherein the posture of the display apparatus includes an inclination of the display apparatus.
-