

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284620

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

NATH; Suman K. et al.

GENERATING FAULT CONDITIONS USING A FAULT-ENABLED SOFTWARE DEVELOPMENT KIT

Abstract

Systems and methods are provided for automatically generating a fault-enabled software development kit (SDK) to test an application. The generating includes determining one or more faults based on codes associated with the SDK and a frequency of occurrences of faults while executing the SDK. A fault injector automatically injects the determined faults in select layers of code in the SDK and generates fault configuration data associated with the automatically injected faults in the SDK. The fault configuration data describes faults that have been injected in the fault-enabled SDK to test an application. The fault-enabled SDK tests the application without needs for modifying the application code for testing purposes. The fault-enabled SDK further provides types of faults that may be common in using the SDK without requiring application developers to have detailed understanding of internals of the SDK to test the application with simulated faults.

Inventors: NATH; Suman K. (Redmond, WA), SHROSBREE; Peter C. (Redmond, WA), FAISAL; Fazle Elahi (Bothell, WA), LEESATAPORNWONGSA; Tanakorn (Redmond, WA)

Applicant: Microsoft Technology Licensing, LLC (Redmond, WA)

Family ID: 1000008626894

Assignee: Microsoft Technology Licensing, LLC (Redmond, WA)

Appl. No.: 19/219444

Filed: May 27, 2025

Related U.S. Application Data

parent US continuation 18428778 20240131 parent-grant-document US 12346245 child US 19219444

Publication Classification

Int. Cl.: **G06F11/3668** (20250101); **G06F11/30** (20060101)

U.S. Cl.:

CPC **G06F11/3688** (20130101); **G06F11/3075** (20130101); **G06F11/3692** (20130101); **G06F11/3696** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/428,778, filed on Jan. 31, 2024, which is a continuation of U.S. patent application Ser. No. 17/342,094, filed on Jun. 8, 2021, now U.S. Pat. No. 11,921,622, the disclosures of all are hereby incorporated by reference in their entirety.

BACKGROUND

[0002] As use of cloud services become popular, interactions among application programs using layers of software transmitting data across networks become commonplace. Resilience of an application therefore becomes an issue, especially since many factors may cause various types of faults that can affect execution of an application. For example, a network disconnect may occur at any time; authentication errors may occur; a sudden spike in workload by a central processing unit (CPU); and, in some cases software in the layers outside the application may error by time-outs after waiting for allocation of resources. Many of the faults occur not necessarily because of executing the application but because of a failure in another program application or some hardware in a system infrastructure.

[0003] Testing the application for its resilience against a variety of types of faults has become important. The testing is very complex. The application needs to sustain from occurrences of faults that occur in various places in the system and on the network. Testing faults often includes creating or simulating faults that the application encounters while executing. Some developers inject faults in the application program code when the developers are knowledgeable about behavior of the faults. As systems become more complex, in use of cloud services for example, complete understanding of faults over the network and/or in cloud servers by application developers becomes difficult. In practice, application developers may be unaware of internals of all the layers of libraries in a computer, underlying infrastructure across the network, and inside the cloud. The application developers need to minimize their need to develop separate application programs for testing and for production use. Furthermore, testing application programs by generating or simulating faults that affect the only the application without affecting other software in the system has become difficult because of the use of shared resources in the system. Accordingly, application developers need ways to simulate faults to test the application program code. Thus, developing a technology that better meets these needs while minimizing trade-offs would be desirable.

[0004] It is with respect to these and other general considerations that the aspects disclosed herein have been made. Also, although relatively specific problems may be discussed, it should be understood that the examples should not be limited to solving the specific problems identified in the background or elsewhere in this disclosure.

SUMMARY

[0005] According to the present disclosure, incorporating a set of predetermined types of faults within a software development kit (SDK), which enables applications to access a remote service, resolves the above and other issues. The present disclosure relates to generating a fault-enabled SDK for testing an application. In particular, a fault-enabled SDK generator automatically generates a fault-enabled SDK based on a received SDK. The fault-enabled SDK generator determines faults based on public methods or application programming interface (API) of the received SDK and automatically injecting faults into the received SDK code. The fault-enabled SDK generator creates fault configuration data, which lists a variety of faults that the fault-enabled SDK can simulate. Developers and testers of client applications configure types of faults the fault-enabled SDK generates.

[0006] The fault-enabled SDK generator further receives a log of errors and/or faults that have occurred in the received SDK. By ranking the faults based on a frequency of occurrence and severity of the faults to the application, the fault-enabled SDK generator determines which faults to inject for generating a fault-enabled SDK.

[0007] The fault-enabled SDK simulates faulty conditions for application programs and helps testing the application programs by enabling the developers and testers of the application programs to specify which faults to generate.

[0008] This Summary is provided to introduce a selection of concepts in a simplified form, which is further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter. Additional aspects, features, and/or advantages of examples will be set forth in part in the following description and, in part, will be apparent from the description, or may be learned by practice of the disclosure.

Description

BRIEF DESCRIPTIONS OF THE DRAWINGS

[0009] Non-limiting and non-exhaustive examples are described with reference to the following figures.

[0010] FIG. 1 illustrates an overview of an example system for generating a failure in an SDK for testing an application in accordance to aspects of the present disclosure.

[0011] FIG. 2 illustrates an overview of an example system for generating a failure in an SDK for testing an application in accordance with aspects of the present disclosure.

[0012] FIG. 3A illustrates an example of a fault configuration data in accordance with aspects of the present disclosure.

[0013] FIG. 3B illustrates an overview of an example of a fault log in accordance with aspects of the present disclosure.

[0014] FIG. 4 illustrates an overview of an example system with a transport layer of an SDK for generating a failure in accordance with aspects of the present disclosure.

[0015] FIG. 5 illustrates an example of a method for generating a failure for testing an application in accordance with aspects of the present disclosure.

[0016] FIG. 6 illustrates an example of a method for generating a fault-enabled SDK and fault configuration data in accordance with aspects of the present disclosure.

[0017] FIG. 7 is a block diagram illustrating example physical components of a computing device with which aspects of the disclosure may be practiced.

[0018] FIG. 8A is a simplified diagram of a mobile computing device with which aspects of the present disclosure may be practiced.

[0019] FIG. 8B is another simplified block diagram of a mobile computing device with which aspects of the present disclosure may be practiced.

DETAILED DESCRIPTION

[0020] Various aspects of the disclosure are described more fully below with reference to the accompanying drawings, which from a part hereof, and which show specific example aspects. However, different aspects of the disclosure may be implemented in many different ways and should not be construed as limited to the aspects set forth herein; rather, these aspects are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the aspects to those skilled in the art. Aspects may be practiced as methods, systems, or devices. Accordingly, aspects may take the form of a hardware implementation, an entirely software implementation or an implementation combining software and hardware aspects.

[0021] As applications interact with services across the network (e.g., cloud services), maintaining resilience of an application has become an issue because testing becomes complex. Many faults (or failures) may occur outside the control of the application. Application developers often do not know with accuracy all the types of faults that the application needs to expect and to process in a graceful and effectual manner.

[0022] To test the application, application developers typically had two traditional approaches. First is to inject fault conditions within the application program code to simulate the faults in underlying systems and validate handling of the faults. For example, an application developer code a dummy function or object to that returns an error in response to the calling of the function or the object by other parts of the application. This application-level approach was often convenient for the application developers because the application developers had a control over the program code in the application. On the other hand, modifying and injecting code that is not necessarily for production use in the application is prone to more quality issues in the application.

[0023] Second is to generate faults in underlying system by physically causing a failure. For example, the application developers may disconnect a network cable from a computer that executes the application to cause a network disconnect failure. The approach of generating a fault in the underlying infrastructure becomes an issue when the tester needs to generate the fault in a controlled manner where the fault affects the application but without affecting other programs that are concurrently running in the system. For example, disconnecting the network (i.e., unplugging a network cable) may cause a fault that is catastrophic to the client application server. Furthermore, disconnecting the network may cause an issue to become too complex to isolate the application that is being tested.

[0024] As discussed in more detail below, the present disclosure relates to an SDK that generates a failure for testing an application. In particular, the SDK generates a failure of a command execution as requested by the application through an application programming interface (API) according to a failure configuration data. In aspects, the SDK includes a transport layer, which communicates with a server through a network, and mimics a failure by returning an error status and code to the application.

[0025] FIG. 1 illustrates an overview of an example system **100** for generating a failure using an SDK for testing an application in accordance with aspects of the present disclosure. System **100** represents a system for testing an application using an SDK that generates a failure. System **100** includes a client device **102**, an application server **110**, a cloud server **130**, a fault-enabled SDK generator **140**, and a network **160**. The client device **102** communicates with the application server **110**. The application server **110** includes a client application **112** and a software development kit **114** (SDK). The client application **112** executes as an application on the client device **102**. In aspects, the client device **102** includes an interactive browser **104** for providing an interactive user interface on a browser. The one or more sets of instructions in the application server **110** may provide an interactive user interface through the interactive browser **104**. A cloud server **130** provides a cloud service to the client application **112** for a user using the client device **102**. The network **160** provides network connectivity among the client device **102**, the application server **110**, and the cloud server **130**. The fault-enabled SDK **114** includes an application programming

interface **116** (API), a transport layer **118**, a network layer **120**, a fault log store **122**, and a fault configuration data store **124**. The fault-enabled SDK **114** provides an interface of commands to the client application **112** to use a cloud service (e.g., storing and reading data from a cloud storage service). The API **116** includes a set of commands and/or public methods for the client application **112**. The API **116** interfaces the transport layer **118** in the fault-enabled SDK **114**. The transport layer **118** processes one or more cloud commands that the client application **112** requests and returns a result of the requested commands. The transport layer **118** in turn issues a command to the network layer **120**. The network layer **120** transmits a command received from the transport layer **118** to a network layer **136** of the cloud server **130**. The fault log store **122** stores a collection of failures in processing commands. For example, information about a failure may include a timestamp, a type of a failure, a requesting application, and a cloud server.

[0026] In aspects, the fault log includes faults as described by documentations associated with an SDK, bug reports, execution traces, and the like. For example, SDK documents may be parsed to identify faults according to the technical specifications and APIs.

[0027] The fault configuration data store **124** stores fault configuration data. The fault configuration data includes entries of faults, describing types of faults and locations in the SDK to generate faults to test the client application **112**. For example, an entry of the fault configuration data may indicate a fault corresponding to an authentication error in the transport layer **118** as a result of transmitting a GET command to read data from an object in a cloud storage. The fault-enabled SDK **114**, when enabled to generate a simulated fault, generates the authentication error in the network layer **118** when the client application **112** invokes a public method of the API **116** to read data from an object from a cloud storage.

[0028] The cloud server **130** performs requests associated with a cloud service. The cloud server **130** includes a cloud server application **132**, a transport layer **134**, and a network layer **136**. In aspects, the cloud server application **132** includes a cloud storage service application. For example, the cloud storage service provides a storage space to store data for the client application **112**. The network layer **136** of the cloud server **106** receives a request from the network layer **120** of the fault-enabled SDK **114** associated with the client application **112** in the application server **110**. Using an example of the cloud storage service as an example, the cloud server **130** may provide a cloud storage service to the client application **112**. A command for performing the cloud storage service may include but not limited to reading, writing, modifying, and deleting data in the cloud storage.

[0029] In the normal course of processing requests without a fault, the client application **112** uses the API **116** of the fault-enabled SDK **114** in the application server **110** to place a request to process data in the cloud (e.g., storing data in the cloud storage). The API **116** may include a command to process data in the cloud storage as specified by the client application. The API **116** in turn instructs the transport layer **118** to transmit the request to the cloud server application **132** in the cloud server **130**. The transport layer **118** then instructs the network layer **120** of the fault-enabled SDK **114** to transmit a cloud storage command with parameters as specified by the client application **112** via the API **116** over the network **160** to the network layer **136** of the cloud server **130**.

[0030] In aspects, the network layer **120** establishes a network connection with the network layer **136** of the cloud server **106** over the network **160**. The network layer **120** transmits the cloud storage command with data associated with the command to the network layer **136** of the cloud server **106**.

[0031] The network layer **136** in the cloud server **130** then receives the command and data associated with the command. The network layer **136** provides the command and the data to the transport layer **134**, which in turn provides them to the cloud server application **132**. The cloud server application **132**, upon receiving the command and the data, performs the command (e.g., stores the data in the cloud storage). The cloud server application **132** provides a result of performing the command to the transport layer **134**. The transport layer **134** instructs the network

layer **136** to transmit the result status of performing the command accordingly. The network layer **136** of the cloud server **130** transmits the result status to the network layer **120** on the application server **110**.

[0032] In aspects, the network layer **120** in the fault-enabled SDK **114** of the application server **110** receives the result status of performing the command in the cloud service. The network layer **120** sends the result status to the transport layer **118**. The transport layer **118** processes the result status and provides the result status to the API. The API **116** returns a result of the API command to the client application **112**. In aspects, the network layer **120** or other parts of the SDK or underlying systems may store the result status in a fault log store **122**. For example, the network layer **120** may store a result in the fault log store **122** when the result includes an error in performing the cloud request.

[0033] Protocols for the communications between the network layer **120** of the fault-enabled SDK **114** and the network layer **136** of the cloud server **130** may be in various forms. For example, the protocol may be based on REST (or RESTful) API (i.e., REST stands for Representative State Transfer), a protocol used for web services.

[0034] In aspects, the fault-enabled SDK **114** generates a failure while performing a command from the client application **112** for testing the client application **112**. The fault-enabled SDK **114** may generate the failure in the API **116**, the transport layer **118**, and in the network layer **120**. In aspect, the transport layer **118** may generate or simulate a fault by replacing otherwise a varying result of a command to the transport layer with a fixed fault (e.g., an HTTP authentication error). In another aspect, the network layer **120** may generate a failure associated with network connectivity regardless of the actual status of the network **160**. When the network layer **120** uses the REST API for interacting with the cloud server **130**, the network layer **120** may return an error to the transport layer **118** as if the network layer **120** received a **401** error (e.g., a network authentication error) from the network layer **136** of the cloud server **130**.

[0035] The fault-enabled SDK **114**, enabled to generate a fault in response to API calls from the client application **112**, enables testing the client application **112** in a controlled manner. The fault-enabled SDK **114** may contain the simulated fault within the fault-enabled SDK **114**. The contained faults may eliminate causing failures in other applications and programs in the application server **110**. Furthermore, the ability of the fault-enabled SDK **114** generating the failures removes the needs for the application developers to modify the program codes of the client application **112** because the client application **112** uses the fault-enabled SDK **114** for testing in the same way that the client application **112** uses the fault-enabled SDK **114** in the production environment. The disclosed technology may provide the fault-enabled SDK **114** in two versions: a production version without an ability to generate failures and a test version with the ability to generate failures. In some other aspect, the fault-enabled SDK **114** may include a flag that switches functionality of the fault-enabled SDK **114** between the production mode and the test mode. The fault-enabled SDK **114** in the test mode may generate failures for testing the client application **112**. The fault-enabled SDK **114** in the production mode does not cause the failure for testing.

[0036] In aspects, the fault-enabled SDK **114** determines a set of failures to generate in response to commands based on a frequency of failures that occur in actual user of the cloud services. The network layer **120** may log failures in the fault log store **122** when the network layer **120** receives an error (e.g., the HTTP 401 Unauthorized client error in the REST API) from the cloud server **130**. The network layer **120** analyzes the failures in the fault log store **122** and determines a set of failures that have occurred more often than a predetermined threshold. The network layer **120** stores information associated with the set of failures to generate (and/or simulate) in the fault configuration data store **124**.

[0037] The fault configuration data store **124** includes a set of faults and settings of whether to generate respective failures for testing the client application **112**. For example, the fault configuration data may specify whether to generate a failure that results from the **401** error from

the cloud server **130**.

[0038] The fault-enabled SDK generator **140** generates a fault-enabled SDK based on a given SDK. The fault-enabled SDK generator **140** includes an SDK receiver **142**, a fault determiner **144**, a fault injector **146**, a fault configuration data generator **148**, and a fault-enabled SDK transmitter **150**. The SDK receiver **142** receives an SDK (and/or a library code). The fault-enabled SDK generator **140** generates a fault-enabled SDK (e.g., the fault-enabled SDK **114**) based on the received SDK.

[0039] The fault determiner **144** determines one or more faults to generate (and/or simulate) in the received SDK. In aspects, the fault determiner **144** analyzes code in the received SDK to identify commands and public methods that are available as API **116** to the client application **112** to use. The fault determiner **144** further determines faults associated with respective public methods of the API **116** either by analyzing the binary code of the received SDK or information (e.g., a documentation) associated with the received SDK. In some other aspects, the fault determiner **144** retrieves a fault log from the fault log store **122** of the received SDK. Based on the fault log, the fault determiner **144** determines one or more faults that occur at a frequency that is higher than a predetermined threshold. In aspects, the fault determiner **144** determines a part (e.g., the API **116**, the transport layer **118**, and the network layer **120**) of the received SDK to generate the one more faults.

[0040] The fault injector **146** injects code that generates the determined faults in the received SDK. In aspects, the fault injector **146** may inject code in the transport layer **118** of the received SDK by replacing a normal result received from the network layer **120** with an error code associated with the determined fault. In some other aspects, the fault injector **146** injects code that causes a fault in the network layer **120** of the received SDK; the network layer **120** returns an authentication error without transmitting a request to the cloud server **130** over the network **160**. The fault injector **146** generates a fault-enabled SDK (e.g., the fault-enabled SDK **114**).

[0041] Traditional systems generate faults within a system infrastructure (e.g., physical network connectivity and electric power for the servers and routers) by causing actual faults. The infrastructure-level fault injection is a real failure. However, the faults tend to be coarse and not finely tunable/controllable by the application tester. Additionally or alternatively, the traditional system may create mock/fake failures by modifying the application or the API code without terminating external network and/or services. The fault injections at the API-level and at the application-level may provide a detailed control over faults but require detailed knowledge about internals of APIs and SDKs by the application tester to test the application with faults in a meaningful manner.

[0042] The fault configuration data generator **148** generates fault configuration data according to the injected faults in the received SDK. The fault configuration data is associated with the received SDK. The fault configuration data store **124** for the received SDK stores the fault configuration data for the received SDK. The fault configuration data include information associated with availability of respective faults, which may be enabled to be generated (and/or simulated) by the received SDK.

[0043] The fault-enabled SDK transmitter **150** transmits the received SDK with injected faults and the fault configuration data. In aspects, the fault-enabled SDK transmitter **150** transmits the received SDK to the application server **110** to test the client application **112**.

[0044] As will be appreciated, the various methods, devices, applications, features, etc., described with respect to FIG. **1** are not intended to limit the system **100** to being performed by the particular applications and features described. Accordingly, additional controller configurations may be used to practice the methods and systems herein and/or features and applications described may be excluded without departing from the methods and systems disclosed herein.

[0045] In traditional testing of client applications, controlled fault injections at the SDK-level have not been available to testers of client applications because SDKs tend to be black boxes to the

developers and testers of client applications. Details of faults that may be result from internal errors of the SDK have been opaque to the client applications. For example, varying frequencies of respective faults raised by the traditional SDKs may be unknown to the developers and testers of client applications. Testing a client application, which uses a remote service (e.g., a cloud service), includes testing various faults that occur remotely. The faults may be raised not by the local client device but by application servers and cloud servers over the network. The disclosed technology provides a structure and a method to automatically generate: 1) a combination of a fault-enabled SDK, and 2) a fault configuration data for the fault-enabled SDK. The combination enables the developers and testers of client applications to control types of faults to simulate and test the client applications without modifying the code for the client applications.

[0046] FIG. 2 illustrates an example system that generates a fault using a fault-enabled SDK for testing an application in accordance with aspects of the present disclosure. The system **200** includes an application **202**, a fault-enabled SDK **204**, and a remote server **220**. The application **202** connects to the fault-enabled SDK **204**. The fault-enabled SDK **204** communicates with the remote server **220**.

[0047] The fault-enabled SDK **204** includes a fault mode switch **212**. The fault mode switch **212** switches a mode of the fault-enabled SDK **204** between a production mode and a fault mode. In aspects, application developers and testers may change settings of the fault mode switch **212** by modifying the fault configuration data (e.g., in the fault configuration data store **124** as shown in FIG. 1).

[0048] In the production mode (e.g., the fault mode switch **212** is OFF), the fault-enabled SDK **204** receives commands from the application **202** through the API **206** and transmits the command to the remote server **220** for performing the command. The fault-enabled SDK **204** returns a result of performing the command to the application **202**. In aspects, the transport layer **210** sends a GET command of the REST API to the remote server **220**. The remote server **220** (e.g., a cloud storage server) receives the request for reading data from a cloud storage, performs the request, and transmits data from the cloud storage and status to the transport layer **210** of the fault-enabled SDK **204**. The transport layer **210** sends the status to the network layer **208**. The network layer **208** returns the result to the API **206**. Accordingly, the API **206** returns the result to the application **202**.

[0049] In the fault test mode, the fault-enabled SDK **204** generates a fault as if the request to the remote server **220** has failed and returned an error (e.g., HTTP Status Code: **401** {"status": **401**, "message": "Authentication Error Opening Storage"}). In aspects, the transport layer **210** of the fault-enabled SDK **204** generates the fault (e.g., the **401** error) according to the fault configuration data. The transport layer **210** returns the fault to the network layer **208**. The network layer **208** processes the error and further returns a result of executing a command to the API **206**. In some other aspects, the network layer **208** generates (and/or simulates) the fault when the fault configuration data specifies the network layer **208** for generating the fault. The API **206** processes the erroneous status from the network layer **208** and returns the error to the application **202**.

[0050] As will be appreciated, the various methods, devices, applications, features, etc., described with respect to FIG. 2 are not intended to limit the system **200** to being performed by the particular applications and features described. Accordingly, additional controller configurations may be used to practice the methods and systems herein and/or features and applications described may be excluded without departing from the methods and systems disclosed herein.

[0051] FIG. 3A illustrates an example of fault configuration data according to aspects of the present disclosure. The example **300A** illustrates exemplar configurations for generating a various types of faults in response to commands received from the client application. In aspects, the fault configuration data **302** includes command name **304**, layer **306**, fault mode **308**, and a fault description **310**. The command name **304** indicates a name of command for which to generate a fault. The layer **306** indicates a software layer (e.g., an API, a network layer, and a transport layer) in the SDK to generate faults. The fault mode **308** indicates a mode that determines whether to

generate a fault. The fault mode **308** “OFF” indicates that the SDK does not generate a fault for testing the application. The fault mode **308** “ON” indicates that the SDK generates faults for testing the application. The fault description **310** indicates a type of fault that the SDK generates. For example, a command name may be “Read Object” processed by a network layer, and its fault mode is currently “OFF.” In another example, the transport layer generates a fault in the Get Object command for reading data from a cloud storage by returning the **401** error (i.e., authentication error) to the network layer to process the artificially generated fault. The transport layer does not actually communicate over the network with the cloud server but generates the fault by returning the **401** error.

[0052] FIG. **3B** illustrates an example of a fault log according to aspects of the present disclosure. The example **300B** illustrates an exemplar fault log. The log includes records of faults that the SDK has encountered. A fault log **342** includes timestamp **344**, command **346**, fault status **348**, and target server **350**. In aspects, the fault log **342** records faults that the transport layer has encountered in communicating with the cloud server.

[0053] For example, a fault may include a Get command (e.g., a Get request in the REST API for a cloud storage service) with a timestamp “202105100810” with a fault error code 401, in interactions with a cloud server “Cloud_Storage-001.” Another fault may indicate a fault error code 401 in response to issuing a Copy command to the cloud server “Cloud_Storage-001.”

[0054] FIG. **4** is an example of a method for generating a fault-enabled SDK in accordance with aspects of the present disclosure. A general order of the operations for the method **400** is shown in FIG. **4**. Generally, the method **400** begins with start operation **402** and ends with end operation **418**. The method **400** may include more or fewer steps or may arrange the order of the steps differently than those shown in FIG. **4**. The method **400** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Further, the method **400** can be performed by gates or circuits associated with a processor, an ASIC, an FPGA, a SOC or other hardware device. Hereinafter, the method **400** shall be explained with reference to the systems, components, devices, modules, software, data structures, data characteristic representations, signaling diagrams, methods, etc., described in conjunction with FIGS. **1**, **2**, **3A**, **3B**, **5**, **6**, **7**, and **8A-B**.

[0055] Following start operation **402**, the method **400** begins with receive operation **404**, which receives code associated with a software development kit (SDK). In aspects, the SDK may include a binary code of the SDK for production use.

[0056] Identify operation **406** identifies API associated with the SDK code by analyzing the SDK code. In aspects, the API represents a set of public functions or method of objects, which a client application uses. The API provides functions of the SDK (e.g., a cloud storage service) to the client application.

[0057] Determine operation **408** determines a set of faults (and/or failures) and error codes associated with the faults as supported by the identified API. In aspects, the determine operation **408** receives (or retrieves) a fault log associated with use of the SDK. For example, the fault log may include timestamps, an identifier of an API that processed the error, and types of the error. The determine operation **408** may identify faults that have occurred more often than a predetermined frequency threshold. In aspects, the determine operation **408** may determine a subset of faults to generate based on a frequency of respective faults. In aspects, the determine operation **408** determines and stores faults in the fault log based on information from SDK documentations (e.g., specifications for the API and the SDK).

[0058] Generate operation **410** generates fault configuration data. In aspects, the fault configuration data includes a list of faults that a fault-enabled SDK generates. The fault configuration data further includes indications of whether the fault-enabled SDK generates respective faults for respective API.

[0059] Inject operation **412** injects a set of code that generate faults in the SDK. For example, the

inject operation **412** injects codes that simulates a fault. The fault may indicate a network disconnect. The code may return a network timeout error to a command that attempts establishing a connection with a remote server. In some other aspects, the inject operation **412** injects an authentication error (e.g., an HTTP return code 401 for an authentication fault) in processing a command that includes an authentication of a client at a remote server. In aspects, the inject operation **412** may be termed as instrumentation of the SDK to generate a fault-enabled SDK. In some other aspects, the inject operation **412** injects faults in the SDK based on the fault configuration data. For example, when the fault configuration data instructs generating a fault indicating a user authentication in a read data command, the inject operation **412** injects and enables code that generates a user authentication error.

[0060] Generate operation **414** generates a fault-enabled SDK. The fault enabled SDK includes a set of code that generates faults as specified by the fault configuration data. Additionally or alternatively, the generate operation **414** generates an updated SDK that includes the additional code that generate faults.

[0061] Release operation **416** releases the fault-enabled SDK to a client application for use. In aspects, the fault-enabled SDK may be distinct from the SDK for production use. In aspects, method **400** may end with end operation **418**. In aspects, the method **400** may automatically generate the fault-enabled SDK based on the received SDK.

[0062] As should be appreciated, operations **402-418** are described for purposes of illustrating the present methods and systems and are not intended to limit the disclosure to a particular sequence of steps, e.g., steps may be performed in different order, additional steps may be performed, and disclosed steps may be excluded without departing from the present disclosure.

[0063] FIG. 5 is an example of a method for generating a fault in a fault-enabled SDK in accordance with aspects of the present disclosure. A general order of the operations for the method **500** is shown in FIG. 5. Generally, the method **500** begins with start operation **502** and ends with end operation **530**. The method **500** may include more or fewer steps or may arrange the order of the steps differently than those shown in FIG. 5. The method **500** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Further, the method **500** can be performed by gates or circuits associated with a processor, an ASIC, an FPGA, a SOC or other hardware device. Hereinafter, the method **500** shall be explained with reference to the systems, components, devices, modules, software, data structures, data characteristic representations, signaling diagrams, methods, etc., described in conjunction with FIGS. 1, 2, 3A, 3B, 4, 6, 7, and 8A-B.

[0064] Following start operation **502**, the method **500** begins with receive operation **504**, which receives an API call from an application. For example, the application may use a cloud storage service by invoking a public method of an API associated with an SDK. The SDK may be associated with a cloud storage service. The API call may include a command to read data from a cloud storage, for example. In aspects, the SDK includes an ON/OFF switch that sets the SDK between a production mode and a fault-enabled (test) mode.

[0065] When the fault test mode is NO **506** (that is, the production mode), the method **500** proceeds to transmit operation **508**. The transmit operation **508** transmits the command to the cloud server for processing the command. Receive operation **510** receives a response with a result of the command from the cloud server.

[0066] Additionally or alternatively, when the receive operation **510** receives a fault (or failure in processing the client request), store operation **512** stores the command and the fault result in a fault log store (e.g., the fault log store **122** as shown in FIG. 1). The fault log includes a list of faults, which occurred in processing requests from the application.

[0067] When the fault test mode is YES **514**, the method **500** proceeds to receive operation **516**, which receives the fault configuration data (e.g., the fault configuration data store **124** as shown in FIG. 1). In aspects, the fault configuration data specifies which faults to enable in the fault test

mode of the SDK. For example, the fault configuration data may specify generating an authentication fault (e.g., HTTP status **401**) while processing a GET data command in the REST API to access the cloud server for reading data from a cloud storage.

[0068] Determine operation **518** determines a fault to generate as a result of the API call. For example, the SDK determines the transport layer to generate an authentication error (e.g., HTTP status **401**) while processing a GET data command in the REST API to access the cloud server. In aspects, the determine operation **518** determines the fault to generate based on the fault configuration data. Accordingly, the transport layer of the SDK generates the error and returns the API call accordingly. In aspects, the SDK is a fault-enabled SDK where the fault-enabled SDK generator previously injected code for generating the fault to test the application.

[0069] A decision operation **520** decides whether the fault needs an interaction with a server. For example, a timeout fault may need the API command operation to be propagated to the server and wait for a timeout error from the server by fault injection. When the fault needs a server interaction **524**, transmit operation **526** transmits the API command to the server for processing. In aspects, the method **500** waits for a return from the server to continue to a transmit operation **528**. When the fault does not need the server interaction **522**, the method **500** proceeds to the transmit operation **528**.

[0070] Transmit operation **528** transmits a result of the API call to the application. For example, when the SDK has its fault test mode ON, the SDK returns an error based on its transport layer generating a fault (e.g., the HTTP status **401**) as specified by the fault configuration data. The method **500** ends with the end operation **530**.

[0071] As should be appreciated, operations **502-530** are described for purposes of illustrating the present methods and systems and are not intended to limit the disclosure to a particular sequence of steps, e.g., steps may be performed in different order, additional steps may be performed, and disclosed steps may be excluded without departing from the present disclosure.

[0072] FIG. **6** is an example of a method for automatically generating a fault-enabled SDK that generates faults in accordance with aspects of the present disclosure. A general order of the operations for the method **600** is shown in FIG. **6**. Generally, the method **600** begins with start operation **602** and ends with end operation **614**. The method **600** may include more or fewer steps or may arrange the order of the steps differently than those shown in FIG. **6**. The method **600** can be executed as a set of computer-executable instructions executed by a computer system and encoded or stored on a computer readable medium. Further, the method **600** can be performed by gates or circuits associated with a processor, an ASIC, an FPGA, a SOC or other hardware device. Hereinafter, the method **600** shall be explained with reference to the systems, components, devices, modules, software, data structures, data characteristic representations, signaling diagrams, methods, etc., described in conjunction with FIGS. **1**, **2**, **3A**, **3B**, **4**, **5**, **7**, and **8A-B**.

[0073] Following start operation **602**, the method **600** begins with receive operation **604**, which receives fault data from a fault log store (e.g., the fault log store **122** in FIG. **1**). In aspects, the fault data includes time, an identifier of software parts (e.g., the transport layer of the SDK), a description of a command request to the remote server, and a result that indicates a fault). In aspects, the faults in the fault log may originate from sources that is not limited to faults that actually occur in use of the API commands. Additionally or alternatively, the faults in the fault log may originate from documentations associated with the SDK and the API (e.g., API specifications). For example, the receive operation **604** may parse the documentations and extract information associated with faults and store information about the faults in the fault log in the fault log store **122**.

[0074] Determine operation **606** determines one more faults that frequently occur based on the fault history data.

[0075] Generate operation **608** generates code that simulates the fault. For example, the determine operation **606** determines that fault history data includes the authentication error (the **401** error) in

the GET command of a cloud storage service more often than a predetermined threshold. In aspects, the fault log store stores faults that occur in use of a REST API through which the transport layer of the SDK transmits requests for processing data at a cloud service in a remote cloud server. Parameters and a syntax used by the REST API are based on HTTP and XML-based data in a text format. Accordingly, injecting faults includes adding the simulated fault in the code of the transport layer and replace the normal version of the transport layer with the fault-enabled transport layer. Code associated with other layers (e.g., API and the network layer) remain the same.

[0076] Generate operation **610** generates the fault configuration data based on the injected faults in the SDK. In aspects, the generate operation **610** generates a fault-enabled SDK. The fault-enabled SDK may be a combination of the injected faults in the SDK, and the fault configuration data that configures (e.g., fault test mode ON/OFF) the injected faults for the SDK.

[0077] Transmit operation **612** transmits the fault-enabled SDK for use to test applications. In aspects, the transmit operation **612** transmits the fault-enabled SDK to an application server for testing client applications that use the fault-enabled SDK. In aspects, the method **600** may end with end operation **614**.

[0078] As should be appreciated, operations **602-614** are described for purposes of illustrating the present methods and systems and are not intended to limit the disclosure to a particular sequence of steps, e.g., steps may be performed in different order, additional steps may be performed, and disclosed steps may be excluded without departing from the present disclosure.

[0079] FIG. 7 is a block diagram illustrating physical components (e.g., hardware) of a computing device **700** with which aspects of the disclosure may be practiced. The computing device components described below may be suitable for the computing devices described above. In a basic configuration, the computing device **700** may include at least one processing unit **702** and a system memory **704**. Depending on the configuration and type of computing device, the system memory **704** may comprise, but is not limited to, volatile storage (e.g., random access memory), non-volatile storage (e.g., read-only memory), flash memory, or any combination of such memories. The system memory **704** may include an operating system **705** and one or more program tools **706** suitable for performing the various aspects disclosed herein such. The operating system **705**, for example, may be suitable for controlling the operation of the computing device **700**. Furthermore, aspects of the disclosure may be practiced in conjunction with a graphics library, other operating systems, or any other application program and is not limited to any particular application or system. This basic configuration is illustrated in FIG. 7 by those components within a dashed line **708**. The computing device **700** may have additional features or functionality. For example, the computing device **700** may also include additional data storage devices (removable and/or non-removable) such as, for example, magnetic disks, optical disks, or tape. Such additional storage is illustrated in FIG. 7 by a removable storage device **709** and a non-removable storage device **710**.

[0080] As stated above, a number of program tools and data files may be stored in the system memory **704**. While executing on the at least one processing unit **702**, the program tools **706** (e.g., an application **720**) may perform processes including, but not limited to, the aspects, as described herein. The application **720** includes an SDK receiver **722**, a fault determiner **724**, a fault injector **726**, a fault configuration data updater **728**, and a fault-enabled SDK transmitter **730**, as described in more detail with regard to FIG. 1. Other program tools that may be used in accordance with aspects of the present disclosure may include electronic mail and contacts applications, word processing applications, spreadsheet applications, database applications, slide presentation applications, drawing or computer-aided application programs, etc.

[0081] Furthermore, aspects of the disclosure may be practiced in an electrical circuit comprising discrete electronic elements, packaged or integrated electronic chips containing logic gates, a circuit utilizing a microprocessor, or on a single chip containing electronic elements or microprocessors. For example, aspects of the disclosure may be practiced via a system-on-a-chip (SOC) where each or many of the components illustrated in FIG. 7 may be integrated onto a single

integrated circuit. Such an SOC device may include one or more processing units, graphics units, communications units, system virtualization units and various application functionality all of which are integrated (or “burned”) onto the chip substrate as a single integrated circuit. When operating via an SOC, the functionality, described herein, with respect to the capability of client to switch protocols may be operated via application-specific logic integrated with other components of the computing device **700** on the single integrated circuit (chip). Aspects of the disclosure may also be practiced using other technologies capable of performing logical operations such as, for example, AND, OR, and NOT, including but not limited to mechanical, optical, fluidic, and quantum technologies. In addition, aspects of the disclosure may be practiced within a general purpose computer or in any other circuits or systems.

[0082] The computing device **700** may also have one or more input device(s) **712**, such as a keyboard, a mouse, a pen, a sound or voice input device, a touch or swipe input device, etc. The output device(s) **714** such as a display, speakers, a printer, etc. may also be included. The aforementioned devices are examples and others may be used. The computing device **700** may include one or more communication connections **716** allowing communications with other computing devices **750**. Examples of suitable communication connections **716** include, but are not limited to, radio frequency (RF) transmitter, receiver, and/or transceiver circuitry; universal serial bus (USB), parallel, and/or serial ports.

[0083] The term computer readable media as used herein may include computer storage media. Computer storage media may include volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, or program tools. The system memory **704**, the removable storage device **709**, and the non-removable storage device **710** are all computer storage media examples (e.g., memory storage). Computer storage media may include RAM, ROM, electrically erasable read-only memory (EEPROM), flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other article of manufacture which can be used to store information and which can be accessed by the computing device **700**. Any such computer storage media may be part of the computing device **700**. Computer storage media does not include a carrier wave or other propagated or modulated data signal.

[0084] Communication media may be embodied by computer readable instructions, data structures, program tools, or other data in a modulated data signal, such as a carrier wave or other transport mechanism, and includes any information delivery media. The term “modulated data signal” may describe a signal that has one or more characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media may include wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, radio frequency (RF), infrared, and other wireless media.

[0085] FIGS. **8A** and **8B** illustrate a computing device or mobile computing device **800**, for example, a mobile telephone, a smart phone, wearable computer (such as a smart watch), a tablet computer, a laptop computer, and the like, with which aspects of the disclosure may be practiced. In some aspects, the client utilized by a user (e.g., user of client device **102** in FIG. **1**) may be a mobile computing device. With reference to FIG. **8A**, one aspect of a mobile computing device **800** for implementing the aspects is illustrated. In a basic configuration, the mobile computing device **800** is a handheld computer having both input elements and output elements. The mobile computing device **800** typically includes a display **805** and one or more input buttons **810** that allow the user to enter information into the mobile computing device **800**. The display **805** of the mobile computing device **800** may also function as an input device (e.g., a touch screen display). If included as an optional input element, a side input element **815** allows further user input. The side input element **815** may be a rotary switch, a button, or any other type of manual input element. In alternative aspects, mobile computing device **800** may incorporate more or less input elements. For

example, the display **805** may not be a touch screen in some aspects. In yet another alternative aspect, the mobile computing device **800** is a portable phone system, such as a cellular phone. The mobile computing device **800** may also include an optional keypad **835**. Optional keypad **835** may be a physical keypad or a “soft” keypad generated on the touch screen display. In various aspects, the output elements include the display **805** for showing a graphical user interface (GUI), a visual indicator **820** (e.g., a light emitting diode), and/or an audio transducer **825** (e.g., a speaker). In some aspects, the mobile computing device **800** incorporates a vibration transducer for providing the user with tactile feedback. In yet another aspect, the mobile computing device **800** incorporates input and/or output ports, such as an audio input (e.g., a microphone jack), an audio output (e.g., a headphone jack), and a video output (e.g., a HDMI port) for sending signals to or receiving signals from an external device.

[0086] FIG. **8B** is a block diagram illustrating the architecture of one aspect of computing device, a server (e.g., an application server **110** and a fault-enabled SDK generator **140**, and a cloud server **130** in FIG. **1**), a mobile computing device, etc. That is, the mobile computing device **800** can incorporate a system **802** (e.g., a system architecture) to implement some aspects. The system **802** can implemented as a “smart phone” capable of running one or more applications (e.g., browser, e-mail, calendaring, contact managers, messaging clients, games, and media clients/players). In some aspects, the system **802** is integrated as a computing device, such as an integrated digital assistant (PDA) and wireless phone.

[0087] One or more application programs **866** may be loaded into the memory **862** and run on or in association with the operating system **864**. Examples of the application programs include phone dialer programs, e-mail programs, information management (PIM) programs, word processing programs, spreadsheet programs, Internet browser programs, messaging programs, and so forth. The system **802** also includes a non-volatile storage area **868** within the memory **862**. The non-volatile storage area **868** may be used to store persistent information that should not be lost if the system **802** is powered down. The application programs **866** may use and store information in the non-volatile storage area **868**, such as e-mail or other messages used by an e-mail application, and the like. A synchronization application (not shown) also resides on the system **802** and is programmed to interact with a corresponding synchronization application resident on a host computer to keep the information stored in the non-volatile storage area **868** synchronized with corresponding information stored at the host computer. As should be appreciated, other applications may be loaded into the memory **862** and run on the mobile computing device **800** described herein.

[0088] The system **802** has a power supply **870**, which may be implemented as one or more batteries. The power supply **870** might further include an external power source, such as an AC adapter or a powered docking cradle that supplements or recharges the batteries.

[0089] The system **802** may also include a radio interface layer **872** that performs the function of transmitting and receiving radio frequency communications. The radio interface layer **872** facilitates wireless connectivity between the system **802** and the “outside world,” via a communications carrier or service provider. Transmissions to and from the radio interface layer **872** are conducted under control of the operating system **864**. In other words, communications received by the radio interface layer **872** may be disseminated to the application programs **866** via the operating system **864**, and vice versa.

[0090] The visual indicator **820** (e.g., LED) may be used to provide visual notifications, and/or an audio interface **874** may be used for producing audible notifications via the audio transducer **825**. In the illustrated configuration, the visual indicator **820** is a light emitting diode (LED) and the audio transducer **825** is a speaker. These devices may be directly coupled to the power supply **870** so that when activated, they remain on for a duration dictated by the notification mechanism even though the processor **860** and other components might shut down for conserving battery power. The LED may be programmed to remain on indefinitely until the user takes action to indicate the powered-on status of the device. The audio interface **874** is used to provide audible signals to and

receive audible signals from the user. For example, in addition to being coupled to the audio transducer **825**, the audio interface **874** may also be coupled to a microphone to receive audible input, such as to facilitate a telephone conversation. In accordance with aspects of the present disclosure, the microphone may also serve as an audio sensor to facilitate control of notifications, as will be described below. The system **802** may further include a video interface **876** that enables an operation of an on-board camera **830** to record still images, video stream, and the like.

[0091] A mobile computing device **800** implementing the system **802** may have additional features or functionality. For example, the mobile computing device **800** may also include additional data storage devices (removable and/or non-removable) such as, magnetic disks, optical disks, or tape. Such additional storage is illustrated in FIG. **8B** by the non-volatile storage area **868**.

[0092] Data/information generated or captured by the mobile computing device **800** and stored via the system **802** may be stored locally on the mobile computing device **800**, as described above, or the data may be stored on any number of storage media that may be accessed by the device via the radio interface layer **872** or via a wired connection between the mobile computing device **800** and a separate computing device associated with the mobile computing device **800**, for example, a server computer in a distributed computing network, such as the Internet. As should be appreciated such data/information may be accessed via the mobile computing device **800** via the radio interface layer **872** or via a distributed computing network. Similarly, such data/information may be readily transferred between computing devices for storage and use according to well-known data/information transfer and storage means, including electronic mail and collaborative data/information sharing systems.

[0093] The description and illustration of one or more aspects provided in this application are not intended to limit or restrict the scope of the disclosure as claimed in any way. The aspects, examples, and details provided in this application are considered sufficient to convey possession and enable others to make and use the best mode of claimed disclosure. The claimed disclosure should not be construed as being limited to any aspect, for example, or detail provided in this application. Regardless of whether shown and described in combination or separately, the various features (both structural and methodological) are intended to be selectively included or omitted to produce an embodiment with a particular set of features. Having been provided with the description and illustration of the present application, one skilled in the art may envision variations, modifications, and alternate aspects falling within the spirit of the broader aspects of the general inventive concept embodied in this application that do not depart from the broader scope of the claimed disclosure.

[0094] The present disclosure relates to systems and methods for generating a fault-enabled SDK according to at least the examples provided in the sections below. As will be understood from the foregoing disclosure, one aspect of the technology relates to a computer-implemented method of automatically generating a fault-enabled software development kit (SDK). The method comprises retrieving a fault log associated with an SDK; determining, based on the retrieved fault log and a predetermined threshold of a frequency of fault occurrence, a fault to inject in the SDK; automatically injecting the fault in the SDK to generate the fault-enabled SDK to test a client application; generating a fault configuration data; and transmitting the fault-enabled SDK and the fault configuration data. The method further comprises ranking, based on the frequency of fault occurrence, faults in the fault log; and determining the fault to inject in the SDK, wherein the fault is the highest ranked fault in the ranked faults in the fault log. The SDK includes: an application programming interface (API), a network layer, and a transport layer, wherein the API interfaces a client application, wherein the transport layer transmits a request for processing data to a remote server using a Representative State Transfer (REST) API, and wherein the transport layer includes the automatically injected fault as a status of the request using the REST API. The SDK includes a fault test switch, and the method further comprises receiving an API call from the client application; and generating, based on the fault test switch, the fault associated with the received

API call to test the client application. The SDK corresponds to cloud service, and wherein the REST API includes a cloud service API. The fault configuration data includes at least one of an identifier of a fault, a location of the fault in the SDK, an indicator indicating whether to generate the fault, and one or more parameters associated with the fault. The fault-enabled SDK is distinct from the SDK. The computer-implemented method of claim 4, the method further comprises generating, by the fault-enabled SDK based on a status of the fault test switch, the fault according to the fault configuration data; and providing the fault in response to the received API call from the client application.

[0095] Another aspect of the technology relates to a system for automatically generating a fault-enabled SDK. The system comprises a processor; and a memory storing computer-executable instructions that when executed by the processor cause the system to determine, based on the retrieved fault log and a predetermined threshold of a frequency of fault occurrence, a fault to inject in the SDK; automatically inject the fault in the SDK to generate the fault-enabled SDK to test a client application; generate a fault configuration data; and transmit the fault-enabled SDK and the fault configuration data. The computer-executable instructions further cause the system to rank, based on the frequency of fault occurrence, faults in the fault log; and determine the fault to inject in the SDK, wherein the fault is the highest ranked fault in the ranked faults in the fault log. The SDK includes an application programming interface (API), a network layer, and a transport layer, wherein the API interfaces a client application, wherein the transport layer transmits a request for processing data to a remote server using a Representative State Transfer (REST) API, and wherein the transport layer includes the automatically injected fault as a status of the request using the REST API. The SDK includes a fault test switch, and the computer-executable instructions further cause the system to receive an API call from the client application; and generate, based on the fault test switch, the fault associated with the received API call to test the client application. The SDK corresponds to cloud service, and wherein the REST API includes a cloud service API. The fault configuration data includes at least one of an identifier of a fault, a location of the fault in the SDK, an indicator indicating whether to generate the fault, and one or more parameters associated with the fault. The fault-enabled SDK is distinct from the SDK.

[0096] In still further aspects, the technology relates to a computer-readable non-transitory recording medium storing computer-executable instructions. The computer-executable instructions when executed further causing the system to determine, based on the retrieved fault event log and a predetermined threshold of a frequency of fault occurrence, a fault to inject in the SDK; automatically inject the fault in the SDK to generate the fault-enabled SDK to test a client application; generate a fault configuration data; and transmit the fault-enabled SDK and the fault configuration data. The computer-executable instructions when executed further causing the system to: rank, based on the frequency of fault occurrence, faults in the fault event log; and determine the fault to inject in the SDK, wherein the fault is the highest ranked fault in the ranked faults in the fault event log. The SDK includes an application programming interface (API), a network layer, and a transport layer, wherein the API interfaces a client application, wherein the transport layer transmits a request for processing data to a remote server using a Representative State Transfer (REST) API, and wherein the transport layer includes the automatically injected fault as a status of the request using the REST API. The SDK includes a fault test switch, and the method further comprises receiving an API call from the client application; and generating, based on the fault test switch, the fault associated with the received API call to test the client application.

[0097] Any of the one or more above aspects in combination with any other of the one or more aspect. Any of the one or more aspects as described herein.

Claims

1-20. (canceled)

21. A computer-implemented method of automatically generating a fault-enabled software development kit (SDK), the method comprising: receiving an SDK and a fault log corresponding to the SDK, the fault log comprising records of a plurality of faults; selecting a fault from the plurality of faults; automatically generating the fault-enabled SDK by injecting the selected fault into the SDK; and outputting the fault-enabled SDK.

22. The computer-implemented method of claim 21, wherein the fault log comprises a timestamp corresponding to when the fault occurred.

23. The computer-implemented method of claim 21, wherein the fault log comprises a command that caused the fault.

24. The computer-implemented method of claim 23, wherein the fault log comprises an indication of a target server for the command.

25. The computer-implemented method of claim 21, further comprising: ranking the plurality of faults, based on the records, wherein the selecting a fault from the plurality of faults is based on the ranking.

26. The computer-implemented method of claim 21, wherein: the SDK includes a transport layer, the transport layer transmits a request for processing data to a remote server using a Representative State Transfer (REST) API, and the transport layer includes the selected fault as a status of the request using the REST API.

27. The computer-implemented method of claim 21, further comprising: causing the fault-enabled SDK to be executed; and receiving an indication of an error caused by the fault-enabled SDK being executed, wherein the error corresponds to the selected fault injected into the SDK.

28. A system for automatically generating a fault-enabled software development kit (SDK), the system comprising: at least one processor; and a memory storing instructions that, when executed by the at least one processor, cause the system to perform a set of operations comprising: receiving an SDK and a fault log corresponding to the SDK, the fault log comprising records of a plurality of faults; selecting a fault from the plurality of faults; automatically generating the fault-enabled SDK by injecting the selected fault into the SDK; and outputting the fault-enabled SDK.

29. The system of claim 28, wherein the fault log comprises a timestamp corresponding to when the fault occurred.

30. The system of claim 29, wherein the fault log further comprises a command that caused the fault.

31. The system of claim 30, wherein the fault log further comprises an indication of a target server for the command.

32. The system of claim 28, wherein the set of operations further comprises: ranking the plurality of faults, based on the records, wherein the selecting a fault from the plurality of faults is based on the ranking.

33. The system of claim 28, wherein: the SDK includes a transport layer, the transport layer transmits a request for processing data to a remote server using a Representative State Transfer (REST) API, and the transport layer includes the selected fault as a status of the request using the REST API.

34. The system of claim 28, wherein the set of operations further comprises: causing the fault-enabled SDK to be executed; and receiving an indication of an error caused by the fault-enabled SDK being executed, wherein the error corresponds to the selected fault injected into the SDK.

35. A non-transitory computer-readable storage medium comprising instructions that when executed by a processor cause a computer system to perform a set of operations comprising: receiving an SDK and a fault log corresponding to the SDK, the fault log comprising records of a plurality of faults; selecting a fault from the plurality of faults; automatically generating the fault-enabled SDK by injecting the selected fault into the SDK; and outputting the fault-enabled SDK.

- 36.** The non-transitory computer-readable storage medium of claim 35, wherein the fault log comprises a timestamp corresponding to when the fault occurred.
- 37.** The non-transitory computer-readable storage medium of claim 35, wherein the fault log further comprises a command that caused the fault and an indication of a target server for the command.
- 38.** The non-transitory computer-readable storage medium of claim 35, wherein the set of operations further comprises: ranking the plurality of faults, based on the records, wherein the selecting a fault from the plurality of faults is based on the ranking.
- 39.** The non-transitory computer-readable storage medium of claim 35, wherein: the SDK includes a transport layer, the transport layer transmits a request for processing data to a remote server using a Representative State Transfer (REST) API, and the transport layer includes the selected fault as a status of the request using the REST API.
- 40.** The non-transitory computer-readable storage medium of claim 39, wherein the set of operations further comprises: causing the fault-enabled SDK to be executed; and receiving an indication of an error caused by the fault-enabled SDK being executed, wherein the error corresponds to the selected fault injected into the SDK.
-