

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386868
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Mathison; Mark P.

Identifying missing nodes within a graphically represented family

Abstract

Embodiments use a visual cue to identify a record with missing information among a plurality of hierarchical records. Each record includes a parent field and an associated records field. An entry in the parent field identifies a parent record of a given record. An entry in the associated records field identifies records that are associated with the record based on a criterion or one or more predetermined criteria. For a selected record, a first group of records are identified based on the parent field of the selected record. The entries in the associated records field of the selected record are then compared to the first group of records. A missing record missing an entry in the associated records field is identified among the first group of records. When the first record and the first group of hierarchical records are graphically represented on a target output medium, the missing record is represented using a visual cue.

Inventors:	Mathison; Mark P. (Walnut Creek, CA)
Applicant:	Kilpatrick Townsend & Stockton LLP (Atlanta, GA)
Family ID:	69227532
Assignee:	Kilpatrick Townsend & Stockton LLP (Atlanta, GA)
Appl. No.:	18/460294
Filed:	September 01, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230409613 A1	Dec. 21, 2023

Related U.S. Application Data

continuation parent-doc US 17842670 20220616 US 11822585 child-doc US 18460294
continuation parent-doc US 16054836 20180803 US 11392627 20220719 child-doc US 17842670

Publication Classification

Int. Cl.: **G06F16/31** (20190101); **G06F7/32** (20060101); **G06F16/34** (20250101); **G06F16/901** (20190101); **G06F16/9038** (20190101); **G06F16/93** (20190101)

U.S. Cl.:

CPC **G06F16/328** (20190101); **G06F7/32** (20130101); **G06F16/322** (20190101); **G06F16/34** (20190101); **G06F16/9024** (20190101); **G06F16/9038** (20190101); **G06F16/93** (20190101);

Field of Classification Search

CPC: G06F (16/328); G06F (7/32); G06F (16/322); G06F (16/34); G06F (16/9024); G06F (16/9038); G06F (16/93)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7657547	12/2009	Huitema	N/A	N/A
9002859	12/2014	Ward	N/A	N/A
10116861	12/2017	Graham et al.	N/A	N/A
11222050	12/2021	Mathison	N/A	N/A
11226996	12/2021	Mathison et al.	N/A	N/A
11392627	12/2021	Mathison	N/A	N/A
11960512	12/2023	Mathison et al.	N/A	N/A
2003/0050925	12/2002	Moskovich et al.	N/A	N/A
2003/0120655	12/2002	Ohwada et al.	N/A	N/A
2003/0227487	12/2002	Hugh	N/A	N/A
2005/0114302	12/2004	Lee et al.	N/A	N/A
2005/0182773	12/2004	Feinsmith	N/A	N/A
2006/0259857	12/2005	Atkins	N/A	N/A
2007/0240203	12/2006	Beck	N/A	N/A
2012/0072470	12/2011	Joseph	N/A	N/A
2013/0086070	12/2012	Lundberg	N/A	N/A
2013/0117648	12/2012	Boutin	N/A	N/A
2014/0032557	12/2013	Bayliss	N/A	N/A
2015/0074612	12/2014	Antipa	N/A	N/A
2015/0248502	12/2014	Rath et al.	N/A	N/A
2015/0278273	12/2014	Wigington et al.	N/A	N/A
2015/0293959	12/2014	Jackson, Jr.	N/A	N/A
2017/0242921	12/2016	Rota	N/A	N/A
2018/0113887	12/2017	Le et al.	N/A	N/A
2018/0260085	12/2017	Whitelaw et al.	N/A	N/A
2018/0307737	12/2017	Xie et al.	N/A	N/A
2020/0042638	12/2019	Mathison	N/A	N/A
2020/0042639	12/2019	Mathison et al.	N/A	N/A
2020/0042640	12/2019	Mathison	N/A	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 17/540,077 , “Corrected Notice of Allowability”, Jan. 31, 2024, 3 pages. cited by applicant
U.S. Appl. No. 17/540,077 , “Notice of Allowance”, Jan. 24, 2024, 17 pages. cited by applicant
U.S. Appl. No. 18/460,483 , “Non-Final Office Action”, Mar. 26, 2024, 33 pages. cited by applicant
U.S. Appl. No. 17/540,077 , “Non-Final Office Action”, Aug. 31, 2023, 21 pages. cited by applicant
U.S. Appl. No. 18/460,483 , “Notice of Allowance”, Sep. 20, 2024, 15 pages. cited by applicant
U.S. Appl. No. 18/604,803 , “Non-Final Office Action”, Oct. 10, 2024, 34 pages. cited by applicant
U.S. Appl. No. 17/533,839 , “Corrected Notice of Allowability”, Oct. 16, 2023, 2 pages. cited by applicant
U.S. Appl. No. 17/842,670 , “Corrected Notice of Allowability”, Oct. 13, 2023, 2 pages. cited by applicant
U.S. Appl. No. 16/054,822 , “Final Office Action”, Dec. 9, 2020, 20 pages. cited by applicant
U.S. Appl. No. 16/054,822 , “Non-Final Office Action”, Jun. 24, 2020, 26 pages. cited by applicant
U.S. Appl. No. 16/054,822 , “Notice of Allowance”, Aug. 25, 2021, 14 pages. cited by applicant
U.S. Appl. No. 16/054,829 , “Final Office Action”, Dec. 11, 2020, 19 pages. cited by applicant
U.S. Appl. No. 16/054,829 , “Non-Final Office Action”, Jun. 24, 2020, 26 pages. cited by applicant
U.S. Appl. No. 16/054,829 , “Notice of Allowance”, Sep. 1, 2021, 14 pages. cited by applicant
U.S. Appl. No. 16/054,836 , “Final Office Action”, Nov. 4, 2020, 21 pages. cited by applicant
U.S. Appl. No. 16/054,836 , “Non-Final Office Action”, Mar. 19, 2020, 16 pages. cited by applicant
U.S. Appl. No. 16/054,836 , “Non-Final Office Action”, Dec. 6, 2021, 27 pages. cited by applicant
U.S. Appl. No. 16/054,836 , “Notice of Allowance”, Mar. 18, 2022, 7 pages. cited by applicant
U.S. Appl. No. 17/533,839 , “Non-Final Office Action”, Dec. 27, 2022, 30 pages. cited by applicant
U.S. Appl. No. 17/533,839 , “Notice of Allowance”, May 11, 2023, 15 pages. cited by applicant
U.S. Appl. No. 17/540,077 , “Final Office Action”, May 15, 2023, 28 pages. cited by applicant
U.S. Appl. No. 17/540,077 , “Non-Final Office Action”, Dec. 22, 2022, 30 pages. cited by applicant
U.S. Appl. No. 17/842,670 , “Non-Final Office Action”, Feb. 15, 2023, 9 pages. cited by applicant
U.S. Appl. No. 17/842,670 , “Notice of Allowance”, Jun. 2, 2023, 5 pages. cited by applicant
Walker II , “A Node-Positioning Algorithm for General Trees”, Software—Practice & Experience, Sep. 1989, 32 pages. cited by applicant
U.S. Appl. No. 18/604,803 , Notice of Allowance, Mailed On Apr. 28, 2025, 8 pages. cited by applicant

Primary Examiner: Phillips, III; Albert M

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/842,670, entitled IDENTIFYING MISSING NODES WITHIN A GRAPHICALLY REPRESENTED FAMILY filed Jun. 16, 2022, which is a continuation of U.S. patent application Ser. No. 16/054,836, entitled IDENTIFYING MISSING NODES WITHIN A GRAPHICALLY REPRESENTED FAMILY filed Aug. 3, 2018, now U.S. Pat. No. 11,392,627 issued Jul. 19, 2022, the disclosures of which are incorporated herein by reference for all purposes.

BACKGROUND

(1) A plurality of hierarchical records may be graphically represented using a graphical tree. graphical trees are a common method of visually representing a hierarchically-organized structure. Each node in the graphical tree may represent a given record among a plurality of hierarchical records, each connection between the nodes may represent a hierarchical relationship between the connected nodes. The graphical tree representations are expected to convey the hierarchical relationship information while conserving a visual aesthetic.

(2) The generation of a graphical tree begins with identifying all nodes and determining the placement (e.g. position) of each node on the display or output page. Previously, many graphical trees have been generated by a human graphic designer. Advancements in computer science resulted in developing node-positioning algorithms that calculate the x and y (e.g. x-y) coordinates for every node of the graphical tree. A rendering routine can then use these coordinates to render the graphical tree. A conventional node-positioning algorithm has a first constraint to generate a drawing that is aesthetically pleasing, and a second constraint to conserve space on the display or output page. Each of these two constraints can be handled straightforwardly by itself, but taking them together poses challenges especially as the number of nodes of the graphical tree increases.

(3) Many conventional computer-generated graphical trees contains irregularities (e.g. failing to correctly position interior nodes). In addition, conventional tree-generating algorithms fail to address all design requirements of a graphical tree (e.g. a child node having multiple parent nodes, relative rendering of two hierarchical families that are affiliated with each other).

(4) Embodiments of the present invention may solve these problems and other problems, individually and collectively.

BRIEF SUMMARY

(5) Embodiments provide methods, systems and mediums for providing a plurality of hierarchical records at a storage device, wherein each current record in the plurality of hierarchical records includes a parent field and an associated records field, an entry in the parent field identifies a parent record of the current record, wherein the parent record is higher in hierarchy than the current record, an entry in the associated records field identifies one or more records that are associated with the current record based on one or more predetermined criteria; receiving a selection of a first record among the plurality of hierarchical records; identifying a first group of hierarchical records among the plurality of hierarchical records based on the parent field of the first record; comparing the entries in the associated records field of the first record to the first group of hierarchical records; identifying a missing record among the first group of hierarchical records that does not have an entry in the associated records field; and graphically representing the first record and the first group of hierarchical records on a target output medium, wherein the missing record is represented using a visual cue such that the missing record is visually set apart from the first record and the first group of hierarchical records.

(6) These and other embodiments are described in further detail below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an exemplary graphical tree including nodes representing a set of hierarchical records, in accordance with embodiments of the present application.

(2) FIG. 2 illustrates an exemplary graphical representation of three sets of affiliated hierarchical records represented by three separate graphical trees, in accordance with embodiments of the present application.

(3) FIG. 3A illustrates an exemplary graphical tree rendered on a first target output medium having a first set of dimensions, in accordance with embodiments of the present application.

- (4) FIG. 3B illustrates the exemplary graphical tree of FIG. 3A rendered on a second target output medium having a second, smaller set of dimensions, in accordance with embodiments of the present application.
- (5) FIG. 4A illustrates an exemplary phantom parent (apex) node for rendering a graphical tree representing two sets of hierarchical records that are affiliated with each other, in accordance with embodiments of the present application.
- (6) FIG. 4B illustrates the graphical tree of FIG. 4A where the exemplary phantom parent (apex) node is removed, in accordance with embodiments of the present application.
- (7) FIG. 4C illustrates a flowchart of steps for generating a graphical tree representing two sets of hierarchical records that are affiliated with each other using a phantom parent (apex) node in the graphical tree, in accordance with embodiments of the present application.
- (8) FIG. 5A illustrates a first exemplary graphical tree including a node having more than one parent node, in accordance with embodiments of the present application.
- (9) FIG. 5B illustrates a second exemplary graphical tree including a node having more than one parent node, in accordance with embodiments of the present application.
- (10) FIG. 5C illustrates a flowchart of steps for generating a graphical tree including a node representing a hierarchical record in a graphical tree to have more than one parent node, in accordance with embodiments of the present application.
- (11) FIG. 6A illustrates a graphical tree representing a family of hierarchical records where one of the nodes is visually identified as including missing associated records information, in accordance with embodiments of the present application.
- (12) FIG. 6B illustrates a flowchart of steps for generating a graphical tree representing a family of hierarchical records where one of the nodes is visually identified as including missing associated records information, in accordance with embodiments of the present application.
- (13) FIG. 7 illustrates exemplary subsystems or components for implementing various participants and elements shown in FIGS. 1-6, in accordance with embodiments of the present application.

DETAILED DESCRIPTION

- (14) Embodiments provide methods and systems for generating graphical representation(s) of a plurality of hierarchical records. An exemplary graphical representation (also referred as “a tree” or “a graphical tree”) includes at least one parent, and hierarchical connections from the parent to its children. A given node in the graphical tree (e.g. a given record among the plurality of hierarchical records) may have more than one parent. There is no restriction on the number of children each node may have, as there is no restriction on the number of parents a given node may have. That is, a given node can have m parents (where m is 0 or more), and each node can have n children (where n is 0 or more). According to various embodiments, if a node has exactly one child, the child may be positioned directly below its parent node on a target output medium (e.g. a digital display, a paper).
- (15) In some embodiments, a record with missing information may be identified and graphically illustrated among a plurality of hierarchical records stored, for example, at a database. A graphical tree may be rendered, displayed or otherwise provided on a target output medium (e.g. a display device, paper). Each current record in the plurality of hierarchical records may include a parent field, and an entry in the parent field may identify a parent record of the current record. By definition, the parent record is higher in hierarchy than the current record. Each current record in the plurality of hierarchical records may also include an associated records field, and an entry in the associated records field may identify one or more records that are associated with the current record based on a predetermined criteria. According to various embodiments, the predetermined criteria may be ancestry (e.g. the current record is a child record, parent record, sibling record of the associated records) or any other criteria that may be set by a user.
- (16) Embodiments may select or receive a selection of a first record among the plurality of hierarchical records. A first group of hierarchical records may be identified among the plurality of

hierarchical records based on the parent field of the first record. The entries in the associated records field of the first record are then compared to the first group of hierarchical records. As a result of comparing, embodiments may identify a missing record among the first group of hierarchical records that does not have an entry in the associated records field. When the first record and the first group of hierarchical records are graphically represented on a target output medium using, for example, a graphical tree, the missing record may be represented using a visual cue such that the missing record is visually set apart from the first record and the first group of hierarchical records. Each shape on the graphical tree represents a unique record among the plurality of hierarchical records.

(17) The generation of graphical trees according to various embodiments may adhere to a set of predetermined rules. The set of rules may include one or more of the following rules: 1. Nodes at the same level of the graphical tree should lie along a straight line, and the straight lines defining the levels should be parallel. 2. A parent should be centered over its offspring. 3. A graphical tree and its minor image should produce drawings that are reflections of one another. 4. A subtree should be drawn the same way regardless of where it occurs in the graphical tree. 5. Small subtrees should not appear arbitrarily positioned among larger subtrees.

Accordingly, small, interior subtrees should be spaced out evenly among larger subtrees (where the larger subtrees are adjacent at one or more levels); and small subtrees at the far left or far right should be adjacent to larger subtrees.

(18) According to various embodiments, subtrees may be built as rigid units. That is, when a node is moved on the graphical tree, all of its descendants (if it has any) are also moved along with the node. The entire subtree is treated as a rigid unit. The graphical tree may be positioned by building the graphical tree up recursively from the leaves (representing children nodes) toward the root (representing the parent node(s)). Embodiments may use two fields for the positioning of each node: a preliminary x-coordinate, and a modifier field. According to various embodiments, a preliminary x-coordinate and a modifier may be assigned to each node, and a final x-coordinate for a given node may be determined by summing the preliminary x-coordinate of the node with the modifier fields of all of ancestors of the node (i.e. all nodes that are higher in the hierarchy than the node). The modifier field associated with the parent (apex) node (i.e. the root of the entire graphical tree) of the graphical tree may be used in determining the final position of all of the descendent nodes (i.e. all nodes that are lower in the hierarchy than the parent node) of the graphical tree.

(19) Sibling nodes (i.e. nodes at the same hierarchical level) may be separated from one another by at least a predefined minimal distance, and adjacent subtrees are separated by at least a predefined subtree separation. Subtrees of a node may be formed independently and placed as close together as the predefined separation values allow.

(20) For a given node, the subtrees are positioned one-by-one, moving, for example, from left to right. A new subtree is placed to the left of an existing neighbor (sibling) subtree while aligning the top node, and moved apart until no two points are touching. Initially the roots of the two neighboring subtrees are separated by the sibling separation value. Then, at the next lower level, the roots are pushed apart until the subtree separation value is established between the adjacent subtrees at the lower level. When this process is complete for all of the offsprings of a node, the node is centered over its leftmost and rightmost offspring.

(21) Embodiments produce graphical trees having evenly distributed, proportional spacing among subtrees. When moving a large subtree to the right, the distance it is moved is also apportioned to smaller, interior subtrees. The moving of these subtrees is accomplished by adding the proportional values to the preliminary x-coordinate and modifier fields of the roots of the small interior subtrees. For example, if three small subtrees are bunched at the left because a new large subtree has been positioned to the right, the first small subtree is shifted right proportionally to the gap (e.g. by $\frac{1}{4}$ of the gap), the second small subtree is shifted right proportionally to the gap (e.g. by $\frac{1}{2}$ of the gap), and the third small subtree is shifted right proportionally to the gap (e.g. by $\frac{3}{4}$ of the gap). The

second graphical tree traversal determines the final x-coordinate for each node. The second graphical tree traversal starts at the apex node of the graphical tree, summing each node's x-coordinate value with the combined sum of the modifier fields of its ancestors. The second graphical tree traversal also adds a value that guarantees centering of the display with respect to the position of the apex node of the drawing. A final graphical tree is thereby generated. These features are discussed in "A Node-Positioning Algorithm for General Trees" TR89-034, September, 1989 by John Q. Walker II, which is incorporated herein by reference.

(22) Referring now to FIG. 1, a graphical tree **100** will be described next. The graphical tree **100** may be generated to illustrate a first set of hierarchical records among a plurality of hierarchical records stored at a storage device (e.g. a database stored at a server memory). In some embodiments, the database may store a list of records and a hierarchical relationship among the plurality of hierarchical records. When a subset (including a portion or all) of the hierarchical records are graphically represented using the graphical tree **100**, each node in the graphical tree **100** represents a unique hierarchical record stored in the database. According to various embodiments, each node may be rendered on a target output medium using a graphical shape (e.g. an icon). The graphical shape may also include alphanumeric characters, symbols and/or graphics to illustrate information associated with the corresponding hierarchical record. For example, the graphical icon may include a record ID assigned to the hierarchical record.

(23) Embodiments may embed a link to a corresponding database entry from the node incorporated in the graphical tree **100**. For example, in the graphical tree **100** illustrated in FIG. 1, node **108** represents a unique record stored as a database entry on the database. The node **108** may be graphically selectable/activatable. Selecting and/or activating node **108** by, for example, clicking on the node **108** using a pointing device such a mouse, a stylus pen for touch-screens or user fingertips, the database entry associated with the unique record represented by node **108** may be retrieved from the database, and (optionally) displayed to the user.

(24) Each record in the plurality of hierarchical records may include a parent field. An entry in the parent field identifies a parent record of that record. The parent record is higher in hierarchy than the record. No entry in the parent field may indicate that the record does not have a parent. According to some embodiments, the first set of hierarchical records may be inter-related in a predetermined manner. For example, the first set of hierarchical records may belong to a family of hierarchical records where the first set of hierarchical records includes a parent record and off-springs of the parent record. For example, a record without a parent record may itself be the first record in a given family of hierarchical records. In some embodiments, the first set of hierarchical records may include more than one parent records, which will be discussed below in greater detail in connection with FIGS. 3A-3B.

(25) The graphical tree **100** illustrated in FIG. 1 includes a parent level (e.g. a first hierarchical level) **102**, a first off-spring level (e.g. a second hierarchical level) **104** and a lower second off-spring level (e.g. a third hierarchical level) **106**. The third hierarchical level is lower in hierarchy than the second hierarchical level, which is lower in hierarchy than the first hierarchical level. The exemplary graphical tree **100** includes one parent node **112** at the parent level **102**. The parent node **112** may represent a parent record among the first set of hierarchical records (e.g. among a first family of hierarchical records). The first off-spring level **104** includes four nodes **114**, **116**, **118**, **120** which are off-springs of the parent node **112**. The nodes **114**, **116**, **118**, **120** may each represent a child record of the parent record represented by parent node **112**. The nodes **114**, **116**, **118**, **120** may be referred as sibling nodes. The second off-spring level **106** includes two nodes **122**, **124** which are off-springs of nodes **114** and **120**, respectively. The node **122** represents a child record of the hierarchical record represented by node **114**. The node **124** represents a child record of the hierarchical record represented by node **120**.

(26) According to various embodiments, visual cues may be added to the graphical tree to illustrate various types of information associated with the hierarchical records. For example, an expired or

otherwise closed record may be illustrated using a first color, a record where an action needs to be taken by a predetermined deadline may be illustrated with a second color, etc. In some embodiments, an initial record may have been created in the database, however there may still be outstanding actions that need to be taken in connection with the initial record to transform the initial record to a formal, actual record in the database. Such an initial record may be illustrated using a graphical node having broken lines (such as node **232** in FIG. 2).

(27) Various embodiments may illustrate two or more sets of hierarchical records as affiliated records (e.g. a first set of records is affiliated with a second set of records). As used herein, affiliated records may refer to a relationship among records that are related to each other by a criteria other than ancestry. That is, when a first set of hierarchical records is affiliated with a second set of hierarchical records, no record in the first set of hierarchical records is a parent of any record in the second set of hierarchical records, and no record in the second set of hierarchical records is a parent of any record in the first set of hierarchical records.

(28) FIG. 2 illustrates an exemplary graphical representation **200** of three sets of affiliate hierarchical records. The first set of hierarchical records represented by a first graphical tree **210** includes a parent record represented by a first node **212** and a child record represented by a second node **214**. The second set of hierarchical records represented by a second graphical tree **220** includes a parent record represented by a third node **222**, a first child record (represented by a fourth node **224**) of the parent record, and a child record (represented by a fifth node **226**) of the first child record. The third set of hierarchical records represented by a third graphical tree **230** includes an initial record represented by a sixth node **232**. As described above, the initial record is created in the database. However, when there are outstanding actions that need to be taken in connection with the initial record to transform the initial record to a formal, actual, record in the database, the initial record is illustrated using a graphical node having broken lines (e.g. sixth node **232**).

(29) As provided above, according to some embodiments, a set of hierarchical records may be referred as a family of records. For example, in FIG. 2, a first family of records may be illustrated with the first graphical tree **210**, a second family of records may be illustrated with the first graphical tree **220**, and a third family of records may be illustrated with the first graphical tree **230**. The first, second and third families may belong to a same group (e.g. the families may be managed and/or owned by a single entity). Accordingly, the ability to display these families together using a single graphical representation **200** may allow for conveying information about these families simultaneously. For example, the ability to display these families together using a single graphical representation **200** may enable the owner/manager entity of these families to get an overview of a current status of these related families of records.

(30) According to various embodiments, generating a graphical tree includes identifying nodes representing the individual hierarchical records and determining an x-y coordinate on a target output medium for each of the plurality of hierarchical records. The target output medium may include a digital screen (e.g. a computer screen, a mobile device screen, a tablet screen) or a paper. The x-y coordinate for each node may be determined following the algorithm described above such that the nodes are evenly spaced on the target output medium. In some embodiments, a user may wish to switch the display medium after the graphical tree is generated. For example, the graphical tree may be rendered on a first digital screen having a first set of dimensions. The user may then wish to display the same graphical tree on a second, smaller digital screen having a second set of dimensions smaller than the first set of dimensions. Alternatively, the user may wish to display the graphical tree that is currently displayed on a first window on the first digital screen, to a second, larger window on the first digital screen. Embodiments are able to re-render the graphical tree based on the dimensions of the new target output medium such that the initial rendering and the subsequent rendering of the graphical representations may have a similar layout, resized according to the requirements of the target output medium.

(31) As illustrated in FIG. 3A, a first graphical tree **300** may be rendered on a first, larger target output medium. The x-y coordinate for each node of the first graphical tree **300** may be determined based on the dimensions of the first target output medium. The contents **302** of each node of the first graphical tree **300** may include a first set of information represented using one or more of alphanumerical characters, symbols and/or graphics. The first graphical tree **300** may represent a first set of hierarchical records.

(32) The same set of hierarchical records may be represented on a second, smaller target output medium using the second graphical tree **350**. As shown in FIG. 3B, the second graphical tree **350** has a similar overall shape as the first graphical tree **300**. Since the second graphical tree **350** is rendered on a smaller target output medium, the contents **352** of each node of the second graphical tree **350** may include a second set of information that is less than the first set of information. The second set of information may also be represented using one or more of alphanumerical characters, symbols and/or graphics. As such, the position (x-y coordinates) for a given record among the plurality of hierarchical records on a first target output medium having a first set of dimensions is different than the position (x-y coordinates) for the given record on a second target output medium having a second, different set of dimensions.

(33) Phantom Parent/Apex Node

(34) When generating a graphical tree representing two sets of hierarchical records that are affiliated with each other, embodiments allow for aligning the nodes at a given level in both sets of hierarchical records. This is accomplished by using a phantom parent (apex) node in the graphical tree.

(35) As shown in FIG. 4A, a first set of hierarchical records **400** and the second set of hierarchical records **450** are illustrated using a graphical tree **440**. The first set of hierarchical records **400** are stored on the database as being affiliated with the second set of hierarchical records **450**. As provided above, affiliate or affiliated records refer to a relationship among records that are related to each other by a criteria other than ancestry. That is, no record in the first set of hierarchical records **400** is a parent of any record in the second set of hierarchical records **450**, and no record in the second set of hierarchical records **450** is a parent of any record in the first set of hierarchical records **400**. The graphical tree **440** illustrated in FIG. 4A includes three hierarchical levels: a first hierarchical level **410**, a second hierarchical level **412** and a third hierarchical level **414**.

(36) The first set of hierarchical records **400** includes a first node **402** at the first hierarchical level **410**. The first node **402** is the parent (apex) node representing the parent record in the first set of hierarchical records **400**. Accordingly, the parent field of the hierarchical record represented by the first node **402** does not have an entry in its parent field. The second set of hierarchical records **450** includes a second node **452** at the first hierarchical level **410**. The second node **452** is the parent (apex) node representing the parent record in the second set of hierarchical records **452**.

Accordingly, the parent field of the hierarchical record represented by the first node **452** does not have an entry in its parent field. As shown in FIG. 4A, the first node **402** and the second node **452** (i.e. the parent node of the first set of hierarchical records **400** and the parent node of the second set of hierarchical records **450**) are aligned on the graphical tree **440**. Similarly, the first set of hierarchical records **400** includes a third node **404** at the second hierarchical level **412**. The third node **404** is the child (descendent) node of the parent node **402** representing the parent record of the first set of hierarchical records **400**. The second set of hierarchical records **450** includes a fourth node **454** at the second hierarchical level **412**. The fourth node **454** is the child (descendent) node of the parent node **452** representing the parent record of the second set of hierarchical records **450**. As shown in FIG. 4A, the third node **404** and the fourth node **454** are aligned on the graphical tree **440**. In addition, the second set of hierarchical records **450** includes a fifth node **456** at the third hierarchical level **414**. The fifth node **456** is the child (descendent) node of the child node **454** of the second set of hierarchical records **450**. As shown in FIG. 4A, since there are no corresponding entries at the third level **414** in the first set of graphical records, only fifth node **456** is displayed at

the third level **414**.

(37) The alignment of nodes in a given hierarchical level of affiliate sets of records is accomplished by using a phantom parent (apex) node **420** that acts as a pseudo apex for both the first set of hierarchical records **400** and the second set of hierarchical records **450**. Accordingly, the phantom parent (apex) node **420** becomes the pseudo-parent node of the parent node **402** of the first set of hierarchical records **400** and the pseudo-parent node of the parent node **452** of the second set of hierarchical records **450**.

(38) FIG. **4C** illustrates a flowchart **460** of steps for generating a graphical tree representing two sets of hierarchical records that are affiliated with each other using a phantom parent (apex) node in the graphical tree. Given a plurality of hierarchical records stored at a database, a phantom apex record is added to the plurality of hierarchical records at a step **S462**. That is, an entry for the phantom apex record is generated in the database. As provided above, initially, the parent field of both the hierarchical record represented by the parent node **402** and the hierarchical record represented by the parent node **452** did not contain any entries. The nodes **402** and **452** are identified at step **S464**, and the parent fields of these records are modified to insert an entry identifying the phantom parent (apex) record at step **S466**. Then, a position for the each of the nodes **402** and **404** is determined based on the phantom parent (apex) record at step **S468**.

Similarly, a position for each of the nodes **452**, **454** and **456** is determined based on at least the phantom parent (apex) record at step **S470**. The graphical tree **442** representing the two affiliated sets of graphical records is thereby generated.

(39) Once the positions of all nodes are determined, all references to the phantom apex record are deleted from all of the parent fields, and the phantom apex record is removed from the plurality of hierarchical records at step **S472**. The phantom parent (apex) node **420** illustrated in FIG. **4A** is shown for illustrative purposes only. According to various embodiments, the phantom parent (apex) node **420** is not added to the graphical tree representing the affiliate sets of graphical records. That is, as shown in FIG. **4B**, the phantom parent (apex) node **420** is not a part of the graphical tree **442**. According to various embodiments, a fixed distance may be added or subtracted from each of the positions in order to move a graphical representation of the plurality of hierarchical records over where the phantom apex node **420** would have been rendered, such that the nodes at the first hierarchical level **410** (e.g. nodes **402** and **452** at FIG. **4A**) will be aligned with each other, and centered below the phantom apex node **420**.

(40) At step **S474**, the graphical tree **442** is rendered on the target output medium by rendering a shape representing a unique record at each determined position for the plurality of hierarchical records. The shapes are then visually connecting (e.g. by using a line) based on entries in the parent fields. As shown in FIG. **4B**, the first set of hierarchical records **400** and the second set of hierarchical records **450** are rendered as sibling groups of hierarchical records.

(41) Graphically Representing Multiple Parents Claims

(42) Embodiments further allow a node representing a hierarchical record in a graphical tree to have more than one parent node. In some embodiments, a child record among the plurality of hierarchical records may have one or more parent fields identifying a first parent record and a second parent record of the child record.

(43) Referring to FIG. **5A**, the graphical tree **500** illustrates an exemplary child record represented by a child node **502** that has a first parent record represented by a first parent node **504** and a second parent record represented by a second parent node **506**. When determining the positions of respective nodes **502**, **504**, **506** on the target output medium, a first position (i.e. x-y coordinate) for the child node **502** and a second position for the first parent node **504** may be determined without considering the second parent node **506**. The first parent node **504** (e.g. the second position) is provided at a first, higher hierarchical level **510** and the child node **502** provided at a second, lower hierarchical level **512** on the target output medium.

(44) At a subsequent step, a third position for the second parent node **506** may be determined at a

same hierarchical level (i.e. the first, higher hierarchical level **510**) as the first parent node **504**. Embodiments then render a first shape (e.g. child node **502**) at the first position, a second shape (e.g. first parent node **504**) at the second position and a third shape (e.g. second parent node **506**) at the third position. The first shape is then visually connected with the second shape and the third shape to form the graphical tree **500** that graphically illustrates the plurality of hierarchical records on the target output medium.

(45) According to various embodiments, visually connecting the shapes may include drawing a first line **505** between the first shape and the second shape, and drawing a second line **507** between the first shape and the third shape, without visually connecting the second shape and the third shape. As illustrated in FIG. 5A, the first parent node **504** is rendered at a sibling level of the second parent node **506** such that the first parent record is represented as a sibling of the second parent record.

(46) According to various embodiments, the child record that has more than one parent records may be lower in a hierarchical level than that is illustrated in FIG. 5A. For example, FIG. 5B illustrates a graphical tree **540** having three hierarchical levels: a first hierarchical level **580**, a second hierarchical level **582** lower than the first hierarchical level **580**, and a third hierarchical level **584** lower than the second hierarchical level **582**. The child record having multiple parents may be provided at the lower third hierarchical level **584**. The graphical tree **540** may include a parent node **542** having three children nodes **544**, **546**, **548**. The child node **544** may have two child nodes **550**, **552**. The child node **550**, as well as the child node **552** may also have the node **548** as their parent. Accordingly, the child node **550** may have node **544** as a first parent node and node **548** as a second parent node. Similarly, the child node **552** may have node **544** as a first parent node and node **548** as a second parent node.

(47) FIG. 5C illustrates a flowchart **560** of steps for generating a graphical tree including a node representing a hierarchical record in a graphical tree to have more than one parent nodes. At step **S562**, embodiments may access a database storing a plurality of hierarchical records. At step **S564**, embodiments may identify a child record having one or more parent fields identifying multiple parent records, e.g. a first parent record, and a second parent record. At step **S566**, a first position for a first node representing the child record and a second position for a second node representing the first parent are determined without considering the second parent record. At step **S568**, a third position is determined for a third node representing the second parent record is determined to be at a same level as the position of the second node representing the first parent. At step **S570**, embodiments render a first shape, a second shape and a third shape at the first position, the second position and the third position, respectively. The first shape illustrates the first node, the second shape illustrates the second node and the third shape illustrates the third node. At step **S572**, the first shape is visually connected with the second shape and the third shape (without connecting the second shape with the third shape) to generate a graphical tree representing the plurality of hierarchical records including a node having more than one parent nodes on a target output medium.

(48) Compare Related Matters Claims

(49) According to various embodiments, a first set of records among the plurality of hierarchical records may be associated with each other. According to various embodiments, the term “associated records” may refer to a set of records where a given record in the set is related to other records in the same set by any type of relation including but not limited to a relationship defined when the records are generated, an association defined by a user, or ancestry (i.e. the given record is a parent, a descendent or a sibling of each of the other records in the same set).

(50) If records in a given set of records are related to each other only by ancestry, that given set of records may be referred as a family of hierarchical records. Accordingly, all records in the same family must identify all remaining records of the same family as their associated records. As provided above, relationship by ancestry is an example of association among records. To ensure

this cross-relation, embodiments review associated records to identify if one of the records in the family fails identify a given record in the same family as an associated record. For example, if a family includes 5 records (e.g. records A, B, C, D and E), each record (e.g. record A) must identify the remaining 4 records (e.g. records B, C, D and E) as associated records. If one of records (e.g. record B) identifies less than 4 records (e.g. records A, C, D) as associated records, that record (e.g. record B) will be visually identified in the graphical tree representing the family of 5 records.

(51) FIG. 6A shows a graphical tree **600** representing a family of hierarchical records where one of the nodes is visually identified as including missing associated record information. According to various embodiments, a plurality of hierarchical records may be stored at a database. That is, each record may have a database entry providing details about the record. A given database entry may have a parent field and an associated records field for a given record. An entry in the parent field identifies a parent record of the given record. An entry in the associated records field identifies one or more records that are associated with the given record.

(52) For example, in the graphical tree **600** shown in FIG. 6A, the node **604** may correspond to a first record. The first record may include a reference to a parent record represented by node **602** in the parent field, and references to records represented by nodes **606**, **608**, **610**, **612**, **614** in the associated records field. Embodiments may ensure for each one of the records represented by nodes **602**, **604**, **606**, **608**, **610**, **612** and **614** lists the records represented by the remaining of the nodes in the family in their associated records fields. This may be accomplished by traversing the database away from and toward the selected record (e.g. record represented by node **604**) to determine a first list of all records that are close or distant relatives (e.g. records represented by nodes **606**, **608**, **610**, **612**, **614**) of the selected record. According to various embodiments, the first list may be determined based on one or more of the parent field of the selected record, the parent fields of all the records of the family, or associated records fields of all the records of the family.

(53) Embodiments may then determine a second list of records based on the associated records field of the selected record. When the first list and the second list are compared against each other, a missing record (e.g. identified by node **614**) may be identified if the missing record appears in the first list but not in the second list. The node representing the missing record (e.g. node **614**) may be visually identified on the graphical tree **600**. For example the node **614** may be displayed using a predetermined color, a shape that is different than the remainder of the nodes of the same graphical tree, a textured line, shading, highlighting, etc.

(54) FIG. 6B illustrates a flowchart **660** of steps for generating a graphical tree representing a family of hierarchical records where one of the nodes is visually identified as including missing associated records information. At step **S662**, embodiments may access a database storing a plurality of hierarchical records. At step **S664**, embodiments may select (or receive a selection of) a first record among the plurality of hierarchical records. At step **S666**, embodiments identify a first group of hierarchical records among the plurality of hierarchical records based on at least the parent field of the first record. At step **S668**, entries in the associated records field of the first record are compared to the first group of hierarchical records. At step **S670**, a missing record is identified among the first group of hierarchical records that does not have an entry in the associated records field of the first record. At step **S672**, embodiments graphically represent the first record and the first group of hierarchical records on a target output medium where the missing record is visually set apart from the first record and the first group of hierarchical records.

(55) Once the missing record is identified and visually represented to a user, the user may then provide input to correct the records stored on the database. For example, the user may provide an input to update the missing record into the associated records field of the selected record. Some embodiments may further receive an input to update the missing record into the associated records field of the first record at step **S674** and update the associated records field of the first record with the missing record at step **S676**.

(56) Caching Parent & Child Data

(57) Various embodiments may identify parent record(s) and child record(s) in a given family of records, and may cache this information on a local storage device such that a graphical tree representing the family may be quickly and efficiently rendered on the local device. For example, when a user interacting with the embodiments requests the generation of a graphical tree to represent a first set of hierarchical records, embodiments may access a remote database storing a plurality of hierarchical records to identify, for each record, every child record for a selected record using the parent fields from different records in the database. Embodiments may then store, for each record, every child record in one or more child fields of the selected record on a local database. Similarly, the parent fields for each record are also stored on the local database. Each record in the plurality of records may be associated with a family such that each family is defined by all records that are close or distant relatives of each other in the database (e.g. each family includes records that are related to each other by ancestry). When a user interacting with the local device selects a record, embodiments may render a graphical tree representing the family of the selected record using the stored parent and child fields from the local database.

(58) The various embodiments discussed above may be used to illustrate patent application records. For example, the database may store a plurality of patent application records. As used herein, a patent application or a patent application record may include, but is not limited to, domestic patent applications, domestic patents, foreign patent applications and foreign patents. The visual cues discussed above may be used to illustrate whether a patent application is allowed, pending or expired. The nodes or graphical shapes used to illustrate a corresponding patent application may also display information such as the application number, a docket number, and/or a filing country of the corresponding patent application. A set of patent applications may form a family as they may be inter-related by ancestry. In certain cases, a first non-provisional patent application may claim priority to more than one provisional patent application. Therefore, the first non-provisional patent application may have the more than one provisional patent application as its parent records. In some embodiments two patent families may be affiliated. For example, a first patent family and a second patent family may be directed to similar subject matter without claiming priority to each other. These two affiliated patent families may be graphically illustrated next to each other. In addition, these two affiliated patent families may be listed among the related records fields of each other. In some embodiments, a first patent application in a family may list other patent applications in the same family in associated records field of the first patent application. Embodiments may identify a second patent application in the same family that does not list at least one of the remaining members of the family in an associated records field of the second patent application. The identified second patent application with missing information may be visually identified (e.g. using a different color, a different border) on the graphical tree.

(59) The various participants and elements shown in FIGS. 1-6 may operate one or more computer apparatuses (e.g., a server computer) to facilitate the functions described herein. Any of the elements in FIGS. 1-6 may use any suitable number of subsystems to facilitate the functions described herein. Examples of such subsystems or components are shown in FIG. 7.

(60) FIG. 7 shows a block diagram of a system 700 comprising a number of components according to some embodiments of the invention. The system comprises a computer device 702 in communication with a records database 704. The records database 704 may store a plurality of records and data associated with each one of the plurality of records. According to various embodiments, the records database 704 may be at a remote location compared to the computer device 702. The exemplary computer device 702 may comprise, but is not limited to, a processor 702A, an output element 702C, an input element 702D, a computer readable medium 702E, a local memory 702F, and a network interface 702G.

(61) The output element 702C may comprise any suitable devices that may output data. Examples of output elements 702C may include display screens, speakers, data transmission devices, printing devices, etc. The input element 702D may include any suitable device capable of inputting data

into the computer device **702**. Examples of input devices include mouse, keyboard, stylus pens, buttons, touchscreens, touch pads, microphones, etc. The local memory **702F** may store data saved thereon. For example, the local memory may store the cached parent/child data information described above. The network interface **702G** may include an interface that can allow the access device **702** to communicate with external computers or databases, such as the records database **704**. (62) The computer readable medium **702E** may comprise code, executable by the processor **702A**, to implement a method comprising: providing a plurality of hierarchical records at a storage device, wherein each current record in the plurality of hierarchical records includes a parent field and an associated records field, an entry in the parent field identifies a parent record of the current record, wherein the parent record is higher in hierarchy than the current record, an entry in the associated records field identifies one or more records that are associated with the current record based on one or more pre-determined criteria; receiving a selection of a first record among the plurality of hierarchical records; identifying a first group of hierarchical records among the plurality of hierarchical records based on the parent field of the first record; comparing the entries in the associated records field of the first record to the first group of hierarchical records; identifying a missing record among the first group of hierarchical records that does not have an entry in the associated records field; and graphically representing the first record and the first group of hierarchical records on a target output medium, wherein the missing record is represented using a visual cue such that the missing record is visually set apart from the first record and the first group of hierarchical records.

(63) Specific details regarding some of the above-described aspects are provided below. The specific details of the specific aspects may be combined in any suitable manner without departing from the spirit and scope of embodiments of the invention.

(64) Storage media and computer readable media for containing code, or portions of code, may include any appropriate media known or used in the art, including storage media and communication media, such as but not limited to volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage and/or transmission of information such as computer readable instructions, data structures, program modules, or other data, including RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disk (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, data signals, data transmissions, or any other medium which may be used to store or transmit the desired information and which may be accessed by the computer. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art may appreciate other ways and/or methods to implement the various embodiments.

(65) It may be understood that the present invention as described above may be implemented in the form of control logic using computer software in a modular or integrated manner. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art may know and appreciate other ways and/or methods to implement the present invention using hardware and a combination of hardware and software

(66) Any of the software components or functions described in this application, may be implemented as software code to be executed by a processor using any suitable computer language such as, for example, Java, C++ or Perl using, for example, conventional or object-oriented techniques. The software code may be stored as a series of instructions, or commands on a computer readable medium, such as a random access memory (RAM), a read only memory (ROM), a magnetic medium such as a hard-drive or a floppy disk, or an optical medium such as a CD-ROM. Any such computer readable medium may reside on or within a single computational apparatus, and may be present on or within different computational apparatuses within a system or processing server computer.

(67) The above description is illustrative and is not restrictive. Many variations of the invention may become apparent to those skilled in the art upon review of the disclosure. The scope of the

invention may, therefore, be determined not with reference to the above description, but instead may be determined with reference to the pending claims along with their full scope or equivalents. (68) One or more features from any embodiment may be combined with one or more features of any other embodiment without departing from the scope of the invention. (69) A recitation of “a”, “an” or “the” is intended to mean “one or more” unless specifically indicated to the contrary.

Claims

1. A method for graphically identifying a missing record among a plurality of hierarchical records, the method comprising: providing, by a computer device, a plurality of hierarchical records at a storage device, wherein each record in the plurality of hierarchical records is associated with a parent record and one or more associated records, wherein the parent record is higher in hierarchy than the record receiving, by the computer device, a user request identifying a first record among the plurality of hierarchical records; identifying, by the computer device, a first group of hierarchical records at the storage device among the plurality of hierarchical records based on at least the parent record of the first record; comparing, by the computer device, the associated records of the first record to each record among the first group of hierarchical records; identifying, by the computer device, a missing record among the first group of hierarchical records that does not appear as an entry among the associated records of the first record; generating, by the computer device, a graphical representation including the first record and the first group of hierarchical records on a target output medium, wherein the missing record is represented on the graphical representation using a visual cue such that the missing record is visually set apart from the first record and the first group of hierarchical records on the graphical representation; updating, by the computer system, the associated records of the first record to include the missing record.
2. The method of claim 1, wherein generating the graphical representation further comprises: determining, by the computer device, a position for each of the plurality of hierarchical records; rendering, by the computer device, a shape at each determined position, wherein each shape represents a unique record among the plurality of hierarchical records; and visually connecting, by the computer device, the shapes based on entries in parent fields of the hierarchical records thereby graphically illustrating the plurality of hierarchical records on the target output medium.
3. The method of claim 2, wherein determining a position for each of the plurality of hierarchical records includes: determining, by the computer device, an x-y coordinate on the target output medium for each of the plurality of hierarchical records.
4. The method of claim 2, wherein the position for a given record among the plurality of hierarchical records on a first target output medium having a first set of dimensions is different than the position for the given record on a second target output medium having a second set of dimensions, wherein the first target output medium has a different size than the second target output medium.
5. The method of claim 1, wherein the target output medium includes a digital display or a sheet of paper.
6. The method of claim 1, wherein the plurality of hierarchical records are graphically illustrated using a graphical tree.
7. The method of claim 1, wherein updating the associated records further comprises: updating, by the computer device, the graphical representation to remove the visual cue.
8. A system comprising: a processor and a non-transitory computer-readable medium coupled to the processor, the non-transitory computer-readable medium comprising instructions that, when executed by the processor, cause the processor to: provide a plurality of hierarchical records at a storage device, wherein each record in the plurality of hierarchical records is associated with a parent record and one or more associated records, wherein the parent record is higher in hierarchy

than the record; receive a user request identifying a first record among the plurality of hierarchical records; identify a first group of hierarchical records at the storage device among the plurality of hierarchical records based on at least the parent record of the first record; compare the associated records of the first record to each record among the first group of hierarchical records; identify a missing record among the first group of hierarchical records that does not appear among the associated records of the first record; generate a graphical representation including the first record and the first group of hierarchical records on a target output medium, wherein the missing record is represented on the graphical representation using a visual cue such that the missing record is visually set apart from the first record and the first group of hierarchical records on the graphical representation; update the associated records of the first record to include the missing record.

9. The system of claim 8, wherein generating the graphical representation further comprises instructions that, when executed by the processor, cause the processor to: determine a position for each of the plurality of hierarchical records; render a shape at each determined position, wherein each shape represents a unique record among the plurality of hierarchical records; and visually connect the shapes based on entries in parent fields of the hierarchical records thereby graphically illustrating the plurality of hierarchical records on the target output medium.

10. The system of claim 9, wherein determining a position for each of the plurality of hierarchical records includes instructions that, when executed by the processor, cause the processor to: determine an x-y coordinate on the target output medium for each of the plurality of hierarchical records.

11. The system of claim 9, wherein the position for a given record among the plurality of hierarchical records on a first target output medium having a first set of dimensions is different than the position for the given record on a second target output medium having a second set of dimensions, wherein the first target output medium has a different size than the second target output medium.

12. The system of claim 8, wherein the target output medium includes a digital display or a sheet of paper.

13. The system of claim 8, wherein the plurality of hierarchical records are graphically illustrated using a graphical tree.

14. The system of claim 8, wherein the instructions, when executed by the processor, further cause the processor to: update the graphical representation to remove the visual cue.

15. A non-transitory computer-readable medium storing instructions that, when executed by a processor, cause the processor to: provide a plurality of hierarchical records at a storage device, wherein each record in the plurality of hierarchical records is associated with a parent record and one or more associated records, wherein the parent record is higher in hierarchy than the record; receive a user request identifying a first record among the plurality of hierarchical records; identify a first group of hierarchical records at the storage device among the plurality of hierarchical records based on at least the parent record of the first record; compare the associated records of the first record to each record among the first group of hierarchical records; identify a missing record among the first group of hierarchical records that does not appear among the associated records of the first record; generate a graphical representation including the first record and the first group of hierarchical records on a target output medium, wherein the missing record is represented on the graphical representation using a visual cue such that the missing record is visually set apart from the first record and the first group of hierarchical records on the graphical representation; update the associated record of the first record to include the missing record.

16. The non-transitory computer-readable medium of claim 15, wherein generating the graphical representation further comprises instructions that, when executed by the processor, cause the processor to: determine a position for each of the plurality of hierarchical records; render a shape at each determined position, wherein each shape represents a unique record among the plurality of hierarchical records; and visually connect the shapes based on entries in parent fields of the

hierarchical records thereby graphically illustrating the plurality of hierarchical records on the target output medium.

17. The non-transitory computer-readable medium of claim 16, wherein determining a position for each of the plurality of hierarchical records includes instructions that, when executed by the processor, cause the processor to: determine an x-y coordinate on the target output medium for each of the plurality of hierarchical records.

18. The non-transitory computer-readable medium of claim 16, wherein the position for a given record among the plurality of hierarchical records on a first target output medium having a first set of dimensions is different than the position for the given record on a second target output medium having a second set of dimensions, wherein the first target output medium has a different size than the second target output medium.

19. The non-transitory computer-readable medium of claim 15, wherein the target output medium includes a digital display or a sheet of paper.

20. The non-transitory computer-readable medium of claim 15, wherein the plurality of hierarchical records are graphically illustrated using a graphical tree.
