

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397941
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Oumi; Syou et al.

Drug supply apparatus

Abstract

A drug supply apparatus of the present disclosure includes a drug supply unit configured to supply a drug to a drug delivery position; a downstream conveying unit configured to convey a strip-shaped first drug packaging paper, folded in half in advance along its longitudinal direction and configured to receive a drug at the drug delivery position; and an upstream conveying unit configured to convey a strip-shaped second drug packaging paper, folded in half in advance along its longitudinal direction. In the apparatus, the upstream conveying unit conveys the second drug packaging paper toward the first drug packaging paper in such a way that the downstream end part of the second drug packaging paper holds in its inside the upstream end part of the first drug packaging paper, and the ridge line of the second drug packaging paper overlaps the ridge line of the first drug packaging paper.

Inventors: Oumi; Syou (Ehime, JP), Shibata; Shiyouji (Ehime, JP), Ueta; Toshiaki (Tokushima, JP)

Applicant: PHC Holdings Corporation (Tokyo, JP)

Family ID: 1000008782236

Assignee: PHC HOLDINGS CORPORATION (Tokyo, JP)

Appl. No.: 18/615822

Filed: March 25, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240228086 A1	Jul. 11, 2024

Foreign Application Priority Data

JP	2021-159495	Sep. 29, 2021
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/JP2022/035521 20220922 PENDING child-doc US 18615822

Publication Classification

Int. Cl.: **B65B9/087** (20120101); **A61J3/00** (20060101); **B65B9/02** (20060101); **B65B41/16** (20060101); **B65B51/16** (20060101)

U.S. Cl.:

CPC **B65B9/087** (20130101); **A61J3/00** (20130101); **B65B9/02** (20130101); **B65B41/16** (20130101); **B65B51/16** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2017/0301087	12/2016	Yuyama	N/A	A61J 1/03

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
59-016805	12/1983	JP	N/A
2010023999	12/2009	JP	B65H 19/1852
5577526	12/2013	JP	N/A

OTHER PUBLICATIONS

Machine Translation of JP-2010023999-A (Year: 2025). cited by examiner
International Search Report dated Nov. 22, 2022 issued in International Patent Application No. PCT/JP2022/035521, with English translation. cited by applicant
Extended European Search Report dated Apr. 14, 2025 issued in the corresponding European Patent Application No. 1 22876073.2. cited by applicant

Primary Examiner: Martin; Veronica

Attorney, Agent or Firm: Rimon P.C.

Background/Summary

CROSS-REFERENCE OF RELATED APPLICATIONS (1) This is a Continuation of International Application No. PCT/JP2022/035521, filed on Sep. 22, 2022, which claims priority to Japanese Patent Application No. 2021-159495, filed on Sep. 29, 2021, the entire disclosures each of which are hereby incorporated by reference.

TECHNICAL FIELD

(1) The present disclosure relates to a drug supply apparatus.

BACKGROUND ART

(2) Patent Literature (hereinafter, referred to as PTL) 1 discloses a packaging paper connecting apparatus that connects the terminal end of packaging paper, which has been folded in half in advance along the longitudinal direction thereof and is used to package a drug, to the starting end of new packaging paper. An operator manually overlaps the terminal end of the packaging paper to be replaced and the starting end of the new packaging paper, and places the overlapped portions at a predetermined position. As the operator connects the overlapped portions to each other, the terminal end of the packaging paper to be replaced and the starting end of the new packaging paper are connected.

CITATION LIST

Patent Literature

(3) PTL 1

(4) Japanese Patent No. 5577526

SUMMARY OF INVENTION

Technical Problem

(5) In the packaging paper connecting apparatus of PTL 1, an operator manually replaces packaging paper. On the other hand, automation of packaging paper replacement is being promoted for the purpose of increasing the efficiency of the work for the packaging paper replacement. During the replacement of packaging paper, when new packaging paper is automatically conveyed, the leading edge of new packaging paper may be caught by a guide that guides the new packaging paper, for example. In such a case, folds are generated in the new packaging paper, and thus the new packaging paper cannot be smoothly conveyed.

(6) An object of the present disclosure is to smoothly convey packaging paper during the replacement of packaging paper in a drug supply apparatus.

Solution to Problem

(7) A drug supply apparatus of the present disclosure includes the following: a drug supply unit configured to supply a drug to a drug delivery position; a downstream conveying unit configured to convey a first drug packaging paper that is strip shaped and folded in half in advance along a longitudinal direction of the first drug packaging paper, in which the first drug packaging paper is configured to receive a drug at the drug delivery position; and an upstream conveying unit configured to convey a second drug packaging paper that is strip shaped and folded in half in advance along a longitudinal direction of the second drug packaging paper, in which the upstream conveying unit conveys the second drug packaging paper toward the first drug packaging paper in such a way that a downstream end part of the second drug packaging paper holds, in an inside of the downstream end part, an upstream end part of the first drug packaging paper, and a ridge line of the second drug packaging paper overlaps a ridge line of the first drug packaging paper.

Advantageous Effects of Invention

(8) A drug supply apparatus of the present disclosure is capable of smoothly conveying packaging paper during the replacement of packaging paper.

Description

BRIEF DESCRIPTION OF DRAWING

(1) FIG. 1 is a perspective view of a drug supply apparatus according to an embodiment of the present disclosure;

(2) FIG. 2 is a longitudinal cross-sectional view of the drug supply apparatus;

(3) FIG. 3 schematically illustrates a portion of a conveying part;

- (4) FIG. 4 is a partially enlarged view of FIG. 3;
- (5) FIG. 5 illustrates the side and a periphery of first drug packaging paper in FIG. 4;
- (6) FIG. 6 illustrates a state in which the first drug packaging paper has been cut;
- (7) FIG. 7 illustrates a state immediately before second drug packaging paper is conveyed;
- (8) FIG. 8 illustrates the side and a periphery of the first drug packaging paper in FIG. 7;
- (9) FIG. 9 is a longitudinal cross-sectional view of a guide member and a periphery thereof;
- (10) FIG. 10 illustrates a state in which the second drug packaging paper is conveyed and overlaps the first drug packaging paper;
- (11) FIG. 11 illustrates a variation of a pair of rollers; and
- (12) FIG. 12 illustrates a variation of the pair of rollers.

DESCRIPTION OF EMBODIMENTS

- (13) Hereinafter, at least one embodiment of the drug supply apparatus of the present disclosure will be described with reference to the drawings. In the following description, the side where operation part **11** is disposed is referred to as the front of drug supply apparatus **1**, and the opposite side is referred to as the back of drug supply apparatus **1** as indicated by the arrows in FIG. 1. In addition, the left and right sides of drug supply apparatus **1** when viewed from the front thereof are referred to as the left and right of drug supply apparatus **1**, respectively. The side away from the surface on which drug supply apparatus **1** is installed is referred to as the top of drug supply apparatus **1** (upward or above the apparatus), and the opposite side is referred to as the bottom of drug supply apparatus **1** (downward or below the apparatus).
- (14) FIG. 1 is a perspective view of exemplary drug supply apparatus **1**. Drug supply apparatus **1** includes first floor part **10** and second floor part **20**.
- (15) First floor part **10** includes operation part **11** and take-out part **12**. In addition, first floor part **10** includes an input part (not illustrated).
- (16) Operation part **11** is a device to be operated by an operator, and includes, for example, a display, operation buttons, and the like. Various information is input to drug supply apparatus **1** as the operator operates operation part **11**.
- (17) A drug (herein, a drug may be more than one drug) packaged in drug supply apparatus **1** is taken out from take-out part **12**. Take-out part **12** includes an opening, and the operator takes out the drug from the opening.
- (18) The input part is an input device receiving various information input from an external device. The input part is connected to, for example, a personal computer, and receives input from the personal computer, for example, information on a prescription issued at a medical institution.
- (19) As illustrated in FIG. 2, drug supply apparatus **1** includes drug supply unit **13**, packaging unit **14**, and control part (not illustrated) which performs overall control of drug supply apparatus **1**. Drug supply unit **13** is configured to supply a drug to drug delivery position Pr. Drug supply unit **13** includes a plurality of shelves **13a** and hopper **13b**.
- (20) The plurality of shelves **13a** are each configured to store the plurality of cassettes C in the second floor part. Drug supply apparatus **1** includes 20 shelves **13a**. The plurality of shelves **13a** are arranged in five stages in the up-down direction and in four rows in the left-right direction. The number and arrangement of shelves **13a** provided in second floor part **20** are not limited to those of the present embodiment, and the number of stages in the up-down direction and/or the number of rows in the left-right direction may be more or less than those described above.
- (21) A plurality of cassettes C are stored in each shelf **13a** so as to be arranged on shelf **13a** along the front and rear direction on both sides of shelf **13a** in the left-right direction. Each cassette C stores a plurality of drugs. Each cassette C is configured to discharge one tablet of a drug at a time.
- (22) The drug discharged from cassette C falls through passage W and is led to first floor part **10**. Passage W is provided so as to penetrate each shelf **13a** in the up-down direction.
- (23) Hopper **13b** is configured to receive the drug led to first floor part **10**, and lead the received drug through outlet **13c** to drug delivery position Pr in packaging unit **14**. Outlet **13c** is provided

approximately at the center of hopper **13b**.

(24) Packaging unit **14** is configured to package the drug led out from hopper **13b**. Packaging unit **14** includes conveying part **30**, printer **15**, and sealing device **16**.

(25) Conveying part **30** is configured to convey strip-shaped packaging paper for packaging a drug. Details of conveying part **30** will be described below.

(26) Printer **15** is a printing machine for printing, for example, the patient's name, the name of the drug to be supplied in packaging paper conveyed by conveying part **30**, the date and time of administration, and the like on the surface of the packaging paper.

(27) Sealing device **16** is for sealing the packaging paper in which a drug is wrapped.

(28) The packaging paper in which the drug is enclosed is cut, for example, with predetermined timing and is conveyed toward take-out part **12** with the conveyance direction thereof changed by conveying part **30**.

(29) In the following, conveying part **30** will be described. As illustrated in FIG. 3, conveying part **30** includes packaging paper holding part **31**, upstream conveying unit **32**, downstream conveying unit **33**, holding member **34**, and guide member **35**. The broken line arrow in FIG. 3 indicates conveyance direction **D1** of first drug packaging paper **PP1**.

(30) Packaging paper holding part **31** includes first packaging paper holding part **31a** and second packaging paper holding part **31b**. First packaging paper holding part **31a** rotatably holds roll **M1**, which is a package of strip-shaped first drug packaging paper **PP1** having been folded in half in advance along the longitudinal direction of first drug packaging paper **PP1**. Second packaging paper holding part **31b** rotatably holds roll **M2**, which is a package of strip-shaped second drug packaging paper **PP2** having been folded in half in advance along the longitudinal direction of second drug packaging paper **PP2**. The packages of first drug packaging paper **PP1** and second drug packaging paper **PP2** may be first drug packaging paper **PP1** in folds and second drug packaging paper **PP2** in folds.

(31) First packaging paper holding part **31a** and second packaging paper holding part **31b** can be exchanged for each other. That is, first packaging paper holding part **31a** can hold roll **M2**, and second packaging paper holding part **31b** can hold roll **M1**. In this case, a pair of rollers **32b** described below nip (i.e., hold the drug packaging paper between the rollers) and convey second drug packaging paper **PP2**, and another pair of rollers **32d** guide first drug packaging paper **PP1** without nipping the drug packaging paper.

(32) Upstream conveying unit **32** includes upstream guide member **32a**, a pair of rollers **32b**, another upstream guide member **32c**, the other pair of rollers **32d**, and moving member **32e**.

(33) Upstream guide member **32a** is configured to guide along conveyance direction **D1** first drug packaging paper **PP1** fed out from first packaging paper holding part **31a**. Upstream guide member **32a** is a plate-shaped member sandwiched by first drug packaging paper **PP1**. As illustrated in FIGS. 4 and 5, which are an enlarged view and a side view of upstream conveying unit **32** and holding member **34** and the peripheries thereof, upstream guide member **32a** is disposed in such a way that the side surface thereof coinciding with ridge line **R1** of first drug packaging paper **PP1** is along conveyance direction **D1**.

(34) The pair of rollers **32b** guide first drug packaging paper **PP1** without nipping the drug packaging paper. The pair of rollers **32b** are disposed on the upstream side of first drug packaging paper **PP1** from upstream guide member **32a**. The pair of rollers **32b** each have a cylindrical shape. The pair of rollers **32b** include driving roller **32b1** and driven roller **32b2**.

(35) Driving roller **32b1** is configured to be rotated by a drive device (not illustrated) such as a motor. Driving roller **32b1** is disposed in such a way that the rotational axis thereof is parallel to the plate surface of upstream guide member **32a** and orthogonal to conveyance direction **D1** of first drug packaging paper **PP1**. In addition, driving roller **32b1** contacts the side surface of first drug packaging paper **PP1**, thereby having a function of changing conveyance direction **D1** (see FIG. 3).

(36) In addition, driving roller **32b1** is configured to move toward driven roller **32b2** to be located

at conveying position Pm1, or to move away from driven roller 32b2 to be located at non-conveying position Pm2. When driving roller 32b1 is located at conveying position Pm1, the pair of rollers 32b can hold first drug packaging paper PP1 or second drug packaging paper PP2 located between the rollers and convey the drug packaging paper toward the downstream side.

(37) Driven roller 32b2 is disposed with the rotational axis thereof inclined. That is, driven roller 32b2 is disposed in such a way that one end part of driven roller 32b2 (on the opened side of first drug packaging paper PP1) is located on the downstream side of first drug packaging paper PP1 from the other end part of driven roller 32b2 (on the ridge line R1 side of first drug packaging paper PP1). In addition, driven roller 32b2 contacts the side surface of first drug packaging paper PP1, thereby having a function of changing conveyance direction D1 (see FIG. 3).

(38) Returning to FIG. 3, the description will be continued. The other upstream guide member 32c is a plate-shaped member sandwiched by the downstream end part of second drug packaging paper PP2 fed out from second packaging paper holding part 31b. The other upstream guide member 32c is disposed in such a way that the plate surface thereof is parallel to the plate surface of upstream guide member 32a, and the side surface thereof coinciding with ridge line R2 of second drug packaging paper PP2 is located on the same plane as the side surface of upstream guide member 32a coinciding with ridge line R1. The plate thickness of the other upstream guide member 32c is approximately the same as the plate thickness of upstream guide member 32a. As will be described below, at the time of replacing first drug packaging paper PP1 with second drug packaging paper PP2, the other upstream guide member 32c guides second drug packaging paper PP2.

(39) The other pair of rollers 32d are disposed on the upstream side of second drug packaging paper PP2 from the other upstream guide member 32c. The other pair of rollers 32d are stationary with the downstream end part of second drug packaging paper PP2 located between the rollers. As will be described below, at the time of replacing first drug packaging paper PP1 with second drug packaging paper PP2, the other pair of rollers 32d nip and convey second drug packaging paper PP2.

(40) The other pair of rollers 32d each have a cylindrical shape. The other pair of rollers 32d include driving roller 32d1 and driven roller 32d2.

(41) Driving roller 32d1 is configured to be rotated by a drive device (not illustrated) such as a motor. Driving roller 32d1 is disposed in such a way that the rotational axis thereof is parallel to the plate surface of the other upstream guide member 32c and orthogonal to conveyance direction D1 of first drug packaging paper PP1.

(42) In addition, driving roller 32d1 is configured to move toward driven roller 32d2 to be located at conveying position Pm1, or to move away from driven roller 32d2 to be located at non-conveying position Pm2. When driving roller 32d1 is located at conveying position Pm1, the other pair of rollers 32d can nip first drug packaging paper PP1 or second drug packaging paper PP2 located between the rollers and convey the drug packaging paper toward the downstream side.

(43) Driven roller 32d2 is disposed with the rotational axis thereof inclined. That is, driven roller 32d2 is disposed in such a way that one end part of driven roller 32d2 (on the opened side of second drug packaging paper PP2) is located on the downstream side of second drug packaging paper PP2 from the other end part of driven roller 32d2 (on the ridge line R2 side of second drug packaging paper PP2). In addition, driven roller 32d2 contacts the side surface of second drug packaging paper PP2, thereby having a function of changing the conveyance direction of second drug packaging paper PP2.

(44) Moving member 32e is configured to be able to move upstream guide member 32a, the pair of rollers 32b, the other upstream guide member 32c, and the other pair of rollers 32d, at the time of replacing first drug packaging paper PP1 with second drug packaging paper PP2. At the time of replacing first drug packaging paper PP1 with second drug packaging paper PP2, the other upstream guide member 32c moves to the position where upstream guide member 32a has been located before upstream guide member 32a is moved, and the other pair of rollers 32d moves to the

position where the pair of rollers **32b** have been located before the pair of rollers **32b** are moved.

(45) Downstream conveying unit **33** is configured to convey first drug packaging paper PP1 guided by upstream conveying unit **32** to printer **15** and sealing device **16**. Downstream conveying unit **33** conveys first drug packaging paper PP1 in such a way that first drug packaging paper PP1 receives a drug at drug delivery position Pr.

(46) Downstream conveying unit **33** includes a pair of downstream rollers **33a** that nip and convey first drug packaging paper PP1, a plurality of rollers **33b** that change conveyance direction D1 of first drug packaging paper PP1, and downstream guide member **33c**.

(47) Downstream guide member **33c** is a plate-shaped member sandwiched by first drug packaging paper PP1, and configured to guide first drug packaging paper PP1 to drug delivery position Pr. Downstream guide member **33c** is disposed in such a way that the plate surface thereof is orthogonal to the horizontal direction. First drug packaging paper PP1 hold, in its inside, downstream guide member **33c** with the opened side of the drug packaging paper facing upward (herein, “in its inside” does not necessarily mean that a component is completely in the inside of another component). First drug packaging paper PP1 is opened upward by being guided by downstream guide member **33c**, and receives a drug led out from hopper **13b** at drug delivery position Pr.

(48) Holding member **34** is disposed between upstream conveying unit **32** and downstream conveying unit **33**. Holding member **34** does not hold first drug packaging paper PP1 when conveying part **30** is conveying first drug packaging paper PP1. Holding member **34** holds first drug packaging paper PP1 between the members thereof when first drug packaging paper PP1 is to be replaced with second drug packaging paper PP2, as described below. Holding member **34** is composed of a pair of plate members **34a** and **34b**. The pair of plate members **34a** and **34b** are disposed in such a way that the plate surfaces of the members are parallel to the plate surface of upstream guide member **32a**. As illustrated in FIG. 4, first plate member **34a** and second plate member **34b** are configured to be located at holding position Ps1 where the members hold first drug packaging paper PP1 therebetween or at a non-holding position Ps2 where the members does not hold first drug packaging paper PP1 therebetween.

(49) Guide member **35** is disposed between holding member **34** and upstream conveying unit **32**, as illustrated in FIGS. 3 to 5, and configured to guide second drug packaging paper PP2 when first drug packaging paper PP1 is to be replaced with second drug packaging paper PP2, as described below. Guide member **35** is a plate-shaped member. The plate thickness of guide member **35** is substantially the same as the plate thicknesses of upstream guide member **32a** and the other upstream guide member **32c**.

(50) During the conveyance of first drug packaging paper PP1 by upstream conveying unit **32** and downstream conveying unit **33**, guide member **35** is located at non-guide position Pg2—a position where the guide member does not contact first drug packaging paper PP1, as illustrated in FIG. 5. As illustrated in FIG. 8 (which will be referred to later), at the time of replacing first drug packaging paper PP1 with second drug packaging paper PP2, guide member **35** is located at guide position Pg1—a position where the guide member can guide second drug packaging paper PP2. That is, guide member **35** is configured to be movable between guide position Pg1 and non-guide position Pg2. Guide member **35** includes inclined part **35a** and recessed part **35b**.

(51) Inclined part **35a** is a side portion of guide member **35**, and ridge line R2 of second drug packaging paper PP2 overlaps the side portion at the time of guiding second drug packaging paper PP2 by guide member **35**. Inclined part **35a** extends in a direction substantially parallel to ridge line R2 of second drug packaging paper PP2 guided by guide member **35**. Specifically, inclined part **35a** has a shape such that the inclined part is inclined from the opened side toward the ridge line R2 side of second drug packaging paper PP2 as the inclined part approaches the downstream side from the upstream side of second drug packaging paper PP2. Inclined part **35a** has a flat shape. Inclined part **35a** may have a triangular cross section or an arcuate cross section.

(52) Recessed part **35b** is a portion recessed approximately along conveyance direction **D1** from the side portion (downstream in conveyance direction **D1**) of guide member **35**.

(53) In the following, the operation of drug supply apparatus **1** when first drug packaging paper **PP1** is to be replaced with second drug packaging paper **PP2** will be described.

(54) As illustrated FIGS. **3** to **5**, when conveying part **30** is conveying first drug packaging paper **PP1**, driving roller **32b1** is located at the non-conveying position **Pm2**, first plate member **34a** of holding member **34** is located at the non-holding position **Ps2**, and guide member **35** is located at non-guide position **Pg2**. In addition, upstream guide member **32a** guides first drug packaging paper **PP1** while upstream guide member **32a** is sandwiched by first drug packaging paper **PP1**.

(55) For replacing the first drug packaging paper **PP1** with second drug packaging paper **PP2**, the operator inputs into operation part **11** an instruction to replace the packaging paper. Accordingly, the control part stops the operation of drug supply unit **13** and also stops the operation of the pair of downstream rollers **33a**.

(56) Subsequently, the control part moves first plate member **34a** to holding position **Ps1**. As a result, holding member **34** holds first drug packaging paper **PP1** between the members thereof. The operator then cuts first drug packaging paper **PP1** on the downstream side from holding member **34**, as illustrated in FIG. **6**. At this time, the operator cuts first drug packaging paper **PP1** in such a way that the downstream end of first drug packaging paper **PP1** to be formed by the cutting is located between holding member **34** and guide member **35** located at guide position **Pg1**. The cutting of first drug packaging paper **PP1** may be performed automatically. That is, the following configuration is also possible: conveying part **30** includes a blade for cutting first drug packaging paper **PP1**, and this blade automatically cuts first drug packaging paper **PP1** when the above-described instruction is input to operation part **11**.

(57) Further, the control part moves driving roller **32d1** of the other pair of rollers **32d** so that the other pair of rollers **32d** hold the downstream end part of second drug packaging paper **PP2** therebetween. In this state, the control part activates moving member **32e** to move upstream guide member **32a**, the pair of rollers **32b**, the other upstream guide member **32c**, and the other pair of rollers **32d**. Due to this movement, the other upstream guide member **32c** is located at the position where upstream guide member **32a** was located, and the other pair of rollers **32d** are located at the position where the pair of rollers **32b** were located. FIG. **7** illustrates the state at this time.

(58) At this time, the operator attaches adhesive tape **T** to the downstream end part of second drug packaging paper **PP2** so as to protrude from the downstream end of the drug packaging paper as illustrated in FIGS. **7** and **8**. Adhesive tapes **T** are attached to both outer surfaces of second drug packaging paper **PP2**, which is folded in half. Adhesive tape **T** may be attached to second drug packaging paper **PP2** in advance before moving member **32e** is activated, that is, in a state illustrated in FIG. **3**.

(59) Subsequently, the operator inputs into operation part **11** information to start conveying second drug packaging paper **PP2**. The control part accordingly moves guide member **35** to guide position **Pg1** as illustrated in FIG. **8**. The other pair of rollers **32d** hold second drug packaging paper **PP2** therebetween. Subsequently, the control part rotates driving roller **32d1** to convey second drug packaging paper **PP2**.

(60) As illustrated in FIG. **8**, driven roller **32d2** is disposed in such a way that one end part of driven roller **32d2** (on the opened side of second drug packaging paper **PP2**) is located on the downstream side of second drug packaging paper **PP2** from the other end part of driven roller **32d2** (on the ridge line **R2** side of second drug packaging paper **PP2**) as described above. Therefore, the other pair of rollers **32d** convey second drug packaging paper **PP2** in a direction inclined with respect to conveyance direction **D1** of first drug packaging paper **PP1**.

(61) Specifically, the other pair of rollers **32d** convey second drug packaging paper **PP2** in such a way that the opened side of the downstream end part of second drug packaging paper **PP2** approaches the ridge line **R1** side of the upstream end part of first drug packaging paper **PP1**. When

second drug packaging paper PP2 is conveyed to guide member 35, second drug packaging paper PP2 is guided by guide member 35. Describing with reference to the state illustrated in FIG. 8, guide member 35 guides second drug packaging paper PP2 in such a way that as second drug packaging paper PP2 moves leftward, the left end of second drug packaging paper PP2 moves upward.

(62) That is, second drug packaging paper PP2 is guided by inclined part 35a of guide member 35 in such a way that as the downstream end part of second drug packaging paper PP2 approaches the upstream end part of first drug packaging paper PP1, the opened side of the downstream end part of second drug packaging paper PP2 approaches the ridge line R1 side of the upstream end part of first drug packaging paper PP1. In other words, the direction in which inclined part 35a guides second drug packaging paper PP2 is approximately the same as the direction in which the other pair of rollers 32d convey second drug packaging paper PP2. Therefore, second drug packaging paper PP2 is smoothly conveyed and guided without being caught by inclined part 35a. In addition, guide member 35 includes recessed part 35b, thereby reducing contact of adhesive tape T with guide member 35.

(63) As second drug packaging paper PP2 is conveyed and guided as described above, when second drug packaging paper PP2 is conveyed to the downstream end part of first drug packaging paper PP1, ridge line R2 of second drug packaging paper PP2 is located above ridge line R1 of first drug packaging paper PP1. As illustrated in FIG. 9, a longitudinal cross-sectional view of guide member 35 and a periphery thereof, second drug packaging paper PP2 is wider than the plate thickness of guide member 35. The downstream end part of second drug packaging paper PP2 thus holds, in its inside, the upstream end part of first drug packaging paper PP1, and ridge line R2 of second drug packaging paper PP2 overlaps ridge line R1 of first drug packaging paper PP1, as illustrated in FIG. 10. Second drug packaging paper PP2 is thus smoothly conveyed and guided without the downstream end part of second drug packaging paper PP2 bumping into the upstream end part of first drug packaging paper PP1.

(64) At this time, first drug packaging paper PP1 is held by holding member 34 between the members thereof. Therefore, even when the moving second drug packaging paper PP2 or the moving adhesive tape T comes into contact with first drug packaging paper PP1, first drug packaging paper PP1 can stay at a predetermined position without shifting to the downstream side.

(65) That is, upstream conveying unit 32 conveys second drug packaging paper PP2 in such a way that the opened side of the downstream end part of second drug packaging paper PP2 approaches the ridge line R1 side of the upstream end part of first drug packaging paper PP1. In addition, upstream conveying unit 32 conveys second drug packaging paper PP2 toward first drug packaging paper PP1 in such a way that the downstream end part of second drug packaging paper PP2 holds, in its inside, the upstream end part of first drug packaging paper PP1, and ridge line R2 of second drug packaging paper PP2 overlaps ridge line R1 of first drug packaging paper PP1. Therefore, during the replacement of packaging paper, second drug packaging paper PP2 is smoothly conveyed to overlap first drug packaging paper PP1 while preventing the generation of folds in first drug packaging paper PP1 and second drug packaging paper PP2.

(66) The control part stops the operation of the pair of rollers 32b in response to the downstream end part of second drug packaging paper PP2 overlapping the upstream end part of first drug packaging paper PP1. The control part detects that the downstream end part of second drug packaging paper PP2 overlaps the upstream end part of first drug packaging paper PP1 based on a detection signal from a position sensor (for example, an infrared sensor) detecting the position of second drug packaging paper PP2.

(67) Subsequently, the operator manually attaches adhesive tape T to first drug packaging paper PP1, for example. As a result, second drug packaging paper PP2 is connected to first drug packaging paper PP1. The operator then inputs information indicating that second drug packaging paper PP2 is connected to first drug packaging paper PP1 into the operation part. The control part

accordingly positions first plate member **34a** at non-holding position **Ps2**, guide member **35** at non-guide position **Pg2**, and driving roller **32b1** at non-conveying position **Pm2**.

(68) Further, when first drug packaging paper **PP1** is conveyed by the pair of downstream rollers **33a** due to the operation by the control part, second drug packaging paper **PP2** connected to first drug packaging paper **PP1** is also conveyed. When first drug packaging paper **PP1** is consumed, the packaging paper conveyed by conveying part **30** is switched to second drug packaging paper **PP2**. In addition, the downstream end part of second drug packaging paper **PP2** holds, in its inside, the upstream end part of first drug packaging paper **PP1**; therefore, the upstream end part of second drug packaging paper **PP2** is not caught by downstream guide member **33c**. Therefore, switching to second drug packaging paper **PP2** is performed smoothly.

(69) The present disclosure is not limited to the embodiment described above. Various variations derived from the present embodiment are also included within the scope of the present disclosure, as long as those variations do not depart from the spirit of the present disclosure.

(70) For example, in the pairs of rollers **32b** and rollers **32d**, not only driven rollers **32b2** and **32d2** but also driving rollers **32b1** and **32d1** may be disposed to be inclined in the same manner as driven rollers **32b2** and **32d2**. In place of disposing driven rollers **32b2** and **32d2** so as to be inclined, driving rollers **32b1** and **32d1** may be disposed to be inclined.

(71) As illustrated in FIG. **11**, the following configuration is also possible: the circumferential side surface of driven roller **132d2** is tapered surface **TS** in which the circumferential length on the opened side of second drug packaging paper **PP2** is longer than the circumferential length on the ridge line **R2** side of second drug packaging paper **PP2**. Driven roller **132d2** is disposed in such a way that the rotational axis thereof is orthogonal to conveyance direction **D1** of first drug packaging paper **PP1**, and tapered surface **TS** is in line contact with the side surface of second drug packaging paper **PP2**. Due to this tapered surface **TS**, second drug packaging paper **PP2** is conveyed in such a way that the opened side of the downstream end part of second drug packaging paper **PP2** approaches the ridge line **R1** side of the upstream end part of first drug packaging paper **PP1**. At least one of the circumferential side surfaces of driven roller **32b2** and driving rollers **32b1** and **32d1** may be tapered surface **TS**.

(72) In addition, as illustrated in FIG. **12**, driven roller **32d2** including tapered surface **TS** may be disposed in such a way that one end part of driven roller **32d2** (on the opened side of second drug packaging paper **PP2**) is located on the downstream side of second drug packaging paper **PP2** from the other end part of driven roller **32d2** (on the ridge line **R2** side of second drug packaging paper **PP2**). Regarding the at least one of driven roller **32b2** and driving rollers **32b1** and **32d1** including tapered surface **TS**, the roller may be disposed in such a way that one end part of the roller (on the opened side of second drug packaging paper **PP2**) is located on the downstream side of second drug packaging paper **PP2** from the other end part of the roller (on the ridge line **R2** side of second drug packaging paper **PP2**).

(73) In addition, conveying part **30** does not need to include second packaging paper holding part **31b**, the other upstream guide member **32c**, the other pair of rollers **32d**, and moving member **32e**. In this case, at the time of replacing first drug packaging paper **PP1** with second drug packaging paper **PP2**, the operator cuts first drug packaging paper **PP1** as described above while holding member **34** holds first drug packaging paper **PP1** between the members thereof, and driving roller **32b1** is located at non-conveying position **Pm2**.

(74) The operator then removes first drug packaging paper **PP1** from first packaging paper holding part **31a** and attaches roll **M2** of second drug packaging paper **PP2** to first packaging paper holding part **31a**. The operator further disposes the downstream end part of second drug packaging paper **PP2** at upstream guide member **32a**, and attaches adhesive tape **T** to the downstream end part of second drug packaging paper **PP2**, as described above.

(75) Subsequently, the operator inputs into operation part **11** information to start conveying second drug packaging paper **PP2**. In response, the control part moves guide member **35** to guide position

Pg1 and positions driving roller **32b1** at conveying position Pm1. The control part further rotates driving roller **32b1** to convey second drug packaging paper PP2. As a result, second drug packaging paper PP2 is conveyed and guided as described above and connected to first drug packaging paper PP1.

(76) This application is entitled to and claims the benefit of Japanese Patent Application No. 2021-159495 filed on Sep. 29, 2021, the disclosure of which including the specification, drawings, and abstract is incorporated herein by reference in its entirety.

INDUSTRIAL APPLICABILITY

(77) The present disclosure is widely available for drug supply apparatuses.

REFERENCE SIGNS LIST

(78) **1** Drug supply apparatus **13** Drug supply unit **30** Conveying part **31** Packaging paper holding part **32** Upstream conveying unit **32a** Upstream guide member **32b** Pair of rollers **32c** Another upstream guide member **32d** Another pair of rollers **32e** Moving member **33** Downstream conveying unit **33c** Downstream guide member **35** Guide member **35a** Inclined part PP1 First drug packaging paper PP2 Second drug packaging paper Pr Drug delivery position R1 Ridge line of first drug packaging paper R2 Ridge line of second drug packaging paper TS Tapered surface

Claims

1. A drug supply apparatus, comprising: a drug supply unit configured to supply a drug to a drug delivery position; a downstream conveying unit configured to convey a first drug packaging paper that is strip shaped and folded in half in advance along a longitudinal direction of the first drug packaging paper, wherein the first drug packaging paper is configured to receive a drug at the drug delivery position; and an upstream conveying unit configured to convey a second drug packaging paper that is strip shaped and folded in half in advance along a longitudinal direction of the second drug packaging paper, wherein: the downstream conveying unit includes a pair of downstream rollers, the upstream conveying unit includes a first upstream guide member, a second upstream guide member, a first pair of rollers, a second pair of rollers, and a moving member, the upstream conveying unit conveys the second drug packaging paper toward the first drug packaging paper in such a way that a downstream end part of the second drug packaging paper holds, in an inside of the downstream end part, an upstream end part of the first drug packaging paper, and a ridge line of the second drug packaging paper overlaps a ridge line of the first drug packaging paper.
2. The drug supply apparatus according to claim 1, wherein the upstream conveying unit conveys the second drug packaging paper in such a way that an opened side of the downstream end part of the second drug packaging paper approaches a ridge line side of the upstream end part of the first drug packaging paper.
3. The drug supply apparatus according to claim 1, wherein the second pair of rollers of the upstream conveying unit is configured to nip and convey the second drug packaging paper.
4. The drug supply apparatus according to claim 3, wherein at least one roller of the second pair of rollers is disposed in such a way that one end part of the at least one roller is located on a downstream side of the second drug packaging paper from another end part of the at least one roller, the one end part being on an opened side of the second drug packaging paper, the other end part being on a ridge line side of the second drug packaging paper.
5. The drug supply apparatus according to claim 3, wherein a circumferential side surface of at least one roller of the second pair of rollers is a tapered surface with a circumferential length on an opened side of the second drug packaging paper longer than a circumferential length on a ridge line side of the second drug packaging paper.
6. The drug supply apparatus according to claim 1, further comprising: a guide member configured to guide the second drug packaging paper while the guide member is sandwiched by the second drug packaging paper, wherein the guide member has a shape allowing the guide member to guide

the second drug packaging paper in such a way that as the downstream end part of the second drug packaging paper approaches the upstream end part of the first drug packaging paper, an opened side of the downstream end part of the second drug packaging paper approaches a ridge line side of the upstream end part of the first drug packaging paper.

7. The drug supply apparatus according to claim 6, wherein the guide member includes an inclined part extending in a direction substantially parallel to the ridge line of the second drug packaging paper guided by the guide member.

8. The drug supply apparatus according to claim 6, wherein the guide member is plate shaped.
