

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283456

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Munneke; Kendall Jay

SECONDARY SUMP PUMP SHELF SYSTEM

Abstract

A sump pump system and shelf system for storing a second sump pump is disclosed. The sump pump system may have a sump pump basin, first sump pump, first discharge pipe, a shelf system, a second sump pump stored on the shelf system, and second discharge pipe is disclosed/Shelf system has a shelf secured to the first discharge pipe and a support member of the shelf system raises shelf above at least a portion of the first sump pump. The shelf is secured to the first discharge pipe and placed on the support member. The shelf provides a stabilizing surface for the second sump pump above the first sump pump while maintaining a compact sump pump system. The shelf is shaped to align with a curve of the sump pump basin and to be able to be placed over one or more components of the first sump pump.

Inventors: Munneke; Kendall Jay (Rock Valley, IA)

Applicant: Munneke; Kendall Jay (Rock Valley, IA)

Family ID: 96948725

Appl. No.: 19/069678

Filed: March 04, 2025

Related U.S. Application Data

us-provisional-application US 63562811 20240308

Publication Classification

Int. Cl.: F04B23/02 (20060101); F04B23/04 (20060101); F04B53/04 (20060101)

U.S. Cl.:

CPC F04B23/028 (20130101); F04B23/021 (20130101); F04B23/04 (20130101); F04B53/04

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION [0001] This application claims priority to provisional application Ser. No. 63/562,811 filed Mar. 8, 2024, and titled “SECONDARY SUMP PUMP SHELF SYSTEM” which is hereby incorporated by reference in its entirety.

FIELD OF THE DISCLOSURE

[0002] This disclosure relates generally to sump pump systems. More specifically and without limitation, this disclosure relates to a shelf for storing and stabilizing a second or back up sump pump.

OVERVIEW OF THE DISCLOSURE

[0003] In sump pump systems, the system may have a secondary or back up sump pump placed within a sump pump. It can be difficult to place the secondary sump pump within the sump pump basin without altering the pumping or the secondary sump pump is unstable after installation within the sump pump basin. In addition, the sump pump may not be placed high enough above the first sump pump to function as a backup pump.

[0004] As such, for all these reasons existing sump pump systems are too difficult to set up, they are too time consuming to set up and they are too easy to improperly set up.

[0005] Therefore, for all the reasons stated above, and the reasons stated below, there is a need in the art for a sump pump system that improves upon the state of the art.

[0006] Another object of the disclosure is to provide a sump pump system that provides improved functionality over prior art systems.

[0007] Yet another object of the disclosure is to provide a sump pump system that provides improved features over prior art systems.

[0008] Another object of the disclosure is to provide a sump pump system that is relatively inexpensive.

[0009] Yet another object of the disclosure is to provide a sump pump system that is easy to use.

Another object of the disclosure is to provide a sump pump system that is intuitive to use. Yet another object of the disclosure is to provide a sump pump system that is strong and robust.

[0010] Another object of the disclosure is to provide a sump pump system that can be used in many applications.

[0011] Yet another object of the disclosure is to provide a sump pump system that improves efficiencies.

[0012] Another object of the disclosure is to provide a sump pump system that provides unique functionality.

[0013] Yet another object of the disclosure is to provide a sump pump system that is fast to use and fast to set up.

[0014] Another object of the disclosure is to provide a sump pump system that is safe to use.

[0015] Yet another object of the disclosure is to provide a sump pump system that saves time.

[0016] Another object of the disclosure is to provide a sump pump system that is compact size.

[0017] Yet another object of the disclosure is to provide a sump pump system that has a long and useful life.

[0018] Another object of the disclosure is to provide a sump pump system that is high quality.

[0019] These and other objects, features, or advantages of the disclosure will become apparent from the specification, figures, and claims.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0020] FIG. 1 is a perspective view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side, forward end, rearward end, opposing sides, drainage openings, connection member openings, and support connection member opening.

[0021] FIG. 2 is a perspective view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side, forward end, rearward end, opposing sides, drainage openings, connection member, connection member wall, and support connection member opening.

[0022] FIG. 3 is a perspective view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side, forward end, rearward end, opposing sides, drainage openings, connection member, connection member wall, and support connection member opening.

[0023] FIG. 4 is a perspective view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the bottom side, forward end, rearward end, opposing sides, drainage openings, connection member openings, cells, cell walls, support connection member opening, and the curve of the bottom side.

[0024] FIG. 5 is a perspective view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the bottom side, forward end, rearward end, opposing sides, drainage openings, connection member, connection member wall, cells, cell walls, support connection member opening, and the curve of the bottom side.

[0025] FIG. 6 is a front view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the forward end of the shelf assembly, the connection member openings, the connection member, the top portion of the shelf assembly, the middle portion of the shelf assembly, the bottom portion of the shelf assembly, the height of the shelf assembly, the width of the top portion of the shelf assembly, a width of the middle portion of the shelf assembly, the width of the bottom portion of the shelf, and the curve of the bottom side of the shelf assembly.

[0026] FIG. 7 is a front view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the forward end of the shelf assembly, the connection member the connection member wall, the connection member, the top portion of the shelf assembly, the middle portion of the shelf assembly, the bottom portion of the shelf assembly, the height of the shelf assembly, the width of the top portion of the shelf assembly, a width of the middle portion of the shelf assembly, the width of the bottom portion of the shelf, and the curve of the bottom side of the shelf assembly.

[0027] FIG. 8 is a right side view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward end of the shelf assembly, the forward end of the shelf assembly, a height of the rearward end of the shelf assembly, the lip, the support connection member, the sides of the support connection member, a bottom of the support connection member, a width of the bottom opening of the support connection member, the curve of the bottom side of the shelf assembly, and the cell walls.

[0028] FIG. 9 is a right side view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward end of the shelf assembly, the forward end of the shelf assembly, a height of the rearward end of the shelf assembly, the lip, the support connection member, connection member wall, the curve of the bottom side of the shelf assembly, and the cell walls.

[0029] FIG. 10 is a back view view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward

end of the shelf assembly, the cell walls, the connection member, the cells, and the lip.

[0030] FIG. **11** is a back view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward end of the shelf assembly, the cell walls, the support connection member, the connection member wall, the cells, and the lip.

[0031] FIG. **12** is a left view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward end of the shelf assembly, the forward end of the shelf assembly, the lip, the support connection member, and the curve of the bottom side of the shelf assembly.

[0032] FIG. **13** is a left view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward end of the shelf assembly, the forward end of the shelf assembly, the lip, the support connection member, connection member wall, and the curve of the bottom side of the shelf assembly.

[0033] FIG. **14** is a bottom view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the bottom side of the shelf assembly, the rearward side of the support assembly, the forward end of the shelf assembly, the shelf recesses, the connection member, support connection member opening, the bottom of the support connection member opening, the support connection member, the cell walls, the cells, and the drainage openings.

[0034] FIG. **15** is a bottom view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the bottom side of the shelf assembly, the rearward side of the support assembly, the forward end of the shelf assembly, the connection member, support connection member opening, the bottom of the support connection member opening, the support connection member, the cell walls, the cells, and the drainage openings.

[0035] FIG. **16** is a bottom view of the shelf assembly of the sump pump system in accordance with one or more arrangements, the view showing the bottom side of the shelf assembly, the rearward side of the support assembly, the forward end of the shelf assembly, the connection member, support connection member opening, the bottom of the support connection member opening, the support connection member, the cell walls, the cells, and the drainage openings.

[0036] FIG. **17** is a top view of the shelf assembly of the sump pump system, in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward end of the shelf assembly, the forward end of the shelf assembly, the drainage openings, the connection member, the opposing sides of the shelf assembly, the support connection member opening, a top of the support connection member, and the shelf recesses.

[0037] FIG. **18** is a top view of the shelf assembly of the sump pump system, in accordance with one or more arrangements, the view showing the top side of the shelf assembly, the rearward end of the shelf assembly, the forward end of the shelf assembly, the drainage openings, the connection member, the opposing sides of the shelf assembly, the support connection member opening, a top of the support connection member and the connection member wall.

[0038] FIG. **19** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the first sump pump, the second sump pump, the floats, the discharge pipes, the sump pump shelf system, and the support member.

[0039] FIG. **20** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the first sump pump, the second sump pump, the floats, the float connection members, the discharge connection member, the discharge pipes, the sump pump shelf system, and the support member.

[0040] FIG. **21** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the first sump pump, the second sump pump, the floats, the float connection members, the discharge connection member, the discharge pipes, the sump pump shelf system, and the support member.

[0041] FIG. **22** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the first sump pump, the second sump pump, the floats, the float connection members, the discharge connection member, the discharge pipes, the sump pump shelf system, and the support member.

[0042] FIG. **23** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the first sump pump, the discharge pipe, the discharge connection member, the power supply, the top side of the first sump pump, the middle side of the first sump pump and the bottom of the first sump pump, the sump pump shelf system, and the support member.

[0043] FIG. **24** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the first sump pump, the discharge pipe, the float, the sump pump shelf system, the shelf connection member, the securing members, and the support member.

[0044] FIG. **25** is a photograph of the sump pump shelf system, in accordance with one or more arrangements, the view showing the shelf assembly, the connection member, the connection recess, the forward end, the rearward end, the drainage openings, the support connection member, the lip and the support member.

[0045] FIG. **26** is a photograph of the shelf assembly, in accordance with one or more arrangements, the view showing the connection member, the connection recess, the forward end, the rearward end, the opposing sides of the shelf assembly, the securing members, and the shelf recesses.

[0046] FIG. **27** is a photograph of the shelf assembly, in accordance with one or more arrangements, the view showing the connection member, the connection recess, the forward end, the rearward end, the opposing sides of the shelf assembly, the securing members, and the shelf recesses.

[0047] FIG. **28** is a photograph of the shelf assembly, in accordance with one or more arrangements, the view showing the connection member, the securing members, the connection member openings, the forward end, and the drainage openings.

[0048] FIG. **29** is a photograph of the sump pump shelf system, in accordance with one or more arrangements, the view showing the shelf assembly, the connection member, the connection recess, the forward end, the rearward end, the lip, and the support member.

[0049] FIG. **30** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the basin, the first sump pump, the discharge pipe, the discharge connection member, the power supplies, the sump pump shelf system, the second sump pump, the securing member, the connection member wall, and the support member.

[0050] FIG. **31** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the basin, the first sump pump, the discharge pipe, the discharge connection member, the power supplies, the sump pump shelf system, the second sump pump, the float and the support member.

[0051] FIG. **32** is a photograph of the sump pump system, in accordance with one or more arrangements, the view showing the basin, the first sump pump shelf system, the securing member, the connection member wall, the float and the support member.

SUMMARY OF THE DISCLOSURE

[0052] In one or more arrangements, a sump pump system is presented having a first sump pump having a first discharge pipe, a second sump pump placed above the first sump pump on a shelf operably connected to the first discharge pipe. The shelf is configured to secure to the first discharge pipe and hold the second sump pump above at least a portion of the first sump pump. In one or more arrangements, the shelf has a connection recess configured to fit around an exterior of the first discharge pipe and a connection member secures the shelf to the first discharge pipe. In one or more arrangements the shape of the shelf facilitates the placement of the first sump pump around or over components of the first sump pump allowing for a compact sump pump system

while stabilizing the second sump pump.

DETAILED DESCRIPTION OF THE DISCLOSURE

[0053] In the following detailed description of the embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the disclosure may be practiced. The embodiments of the present disclosure described below are not intended to be exhaustive or to limit the disclosure to the precise forms in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may appreciate and understand the principles and practices of the present disclosure. It will be understood by those skilled in the art that various changes in form and details may be made without departing from the principles and scope of the invention. It is intended to cover various modifications and similar arrangements and procedures, and the scope of the appended claims therefore should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements and procedures. For instance, although aspects and features may be illustrated in or described with reference to certain figures or embodiments, it will be appreciated that features from one figure or embodiment may be combined with features of another figure or embodiment even though the combination is not explicitly shown or explicitly described as a combination. In the depicted embodiments, like reference numbers refer to like elements throughout the various drawings.

[0054] It should be understood that any advantages and/or improvements discussed herein may not be provided by various disclosed embodiments, or implementations thereof. The contemplated embodiments are not so limited and should not be interpreted as being restricted to embodiments which provide such advantages or improvements. Similarly, it should be understood that various embodiments may not address all or any objects of the disclosure or objects of the invention that may be described herein. The contemplated embodiments are not so limited and should not be interpreted as being restricted to embodiments which address such objects of the disclosure or invention. Furthermore, although some disclosed embodiments may be described relative to specific materials, embodiments are not limited to the specific materials or apparatuses but only to their specific characteristics and capabilities and other materials and apparatuses can be substituted as is well understood by those skilled in the art in view of the present disclosure.

[0055] It is to be understood that the terms such as “left, right, top, bottom, front, back, side, height, length, width, upper, lower, interior, exterior, inner, outer, and the like as may be used herein, merely describe points of reference and do not limit the present invention to any particular orientation or configuration.

[0056] As used herein, the term “or” includes one or more of the associated listed items, such that “A or B” means “either A or B.” As used herein, the term “and” includes all combinations of one or more of the associated listed items, such that “A and B” means “A as well as B.” The use of “and/or” includes all combinations of one or more of the associated listed items, such that “A and/or B” includes “A but not B,” “B but not A,” and “A as well as B,” unless it is clearly indicated that only a single item, subgroup of items, or all items are present. The use of “etc.” is defined as “et cetera” and indicates the inclusion of all other elements belonging to the same group of the preceding items, in any “and/or” combination(s).

[0057] As used herein, the singular forms “a,” “an,” and “the” are intended to include both the singular and plural forms, unless the language explicitly indicates otherwise. Indefinite articles like “a” and “an” introduce or refer to any modified term, both previously-introduced and not, while definite articles like “the” refer to a same previously-introduced term; as such, it is understood that “a” or “an” modify items that are permitted to be previously-introduced or new, while definite articles modify an item that is the same as immediately previously presented. It will be further understood that the terms “comprises,” “comprising,” “includes,” and/or “including,” when used herein, specify the presence of stated features, characteristics, steps, operations, elements, and/or components, but do not themselves preclude the presence or addition of one or more other features,

characteristics, steps, operations, elements, components, and/or groups thereof, unless expressly indicated otherwise. For example, if an embodiment of a system is described as comprising an article, it is understood the system is not limited to a single instance of the article unless expressly indicated otherwise, even if elsewhere another embodiment of the system is described as comprising a plurality of articles.

[0058] It will be understood that when an element is referred to as being “connected,” “coupled,” “mated,” “attached,” “fixed,” etc. to another element, it can be directly connected to the other element, and/or intervening elements may be present. In contrast, when an element is referred to as being “directly connected,” “directly coupled,” “directly engaged” etc. to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” “engaged” versus “directly engaged,” etc.). Similarly, a term such as “operatively”, such as when used as “operatively connected” or “operatively engaged” is to be interpreted as connected or engaged, respectively, in any manner that facilitates operation, which may include being directly connected, indirectly connected, electronically connected, wirelessly connected or connected by any other manner, method or means that facilitates desired operation. Similarly, a term such as “communicatively connected” includes all variations of information exchange and routing between two electronic devices, including intermediary devices, networks, etc., connected wirelessly or not. Similarly, “connected” or other similar language particularly for electronic components is intended to mean connected by any means, either directly or indirectly, wired and/or wirelessly, such that electricity and/or information may be transmitted between the components.

[0059] It will be understood that, although the ordinal terms “first,” “second,” etc. may be used herein to describe various elements, these elements should not be limited to any order by these terms unless specifically stated as such. These terms are used only to distinguish one element from another; where there are “second” or higher ordinals, there merely must be a number of elements, without necessarily any difference or other relationship. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of example embodiments or methods.

[0060] Similarly, the structures and operations discussed herein may occur out of the order described and/or noted in the figures. For example, two operations and/or figures shown in succession may in fact be executed concurrently or may sometimes be executed in the reverse order, depending upon the functionality/acts involved. Similarly, individual operations within example methods described below may be executed repetitively, individually, or sequentially, to provide looping or other series of operations aside from single operations described below. It should be presumed that any embodiment or method having features and functionality described below, in any workable combination, falls within the scope of example embodiments.

[0061] As used herein, various disclosed embodiments may be primarily described in the context of a sump pump system or a shelf system. However, the embodiments are not so limited. It is appreciated that the embodiments may be adapted for use in various other applications, which may be improved by the disclosed structures, arrangements and/or methods. The system is merely shown and described as being used in the context of a sump pump system or a sump pump shelf system for ease of description and as one of countless examples.

System 10:

[0062] With reference to the figures, a sump pump system **10** (or simply system **10**) is presented. The sump pump system **10** is formed of any suitable size, shape and design and is configured to facilitate placement and stabilization of a second sump pump above a first sump pump in various configurations. In the arrangement shown, as one example, system **10** includes among other components a sump pump basin **12**, a first sump pump **40** (or simply sump pump **40**), a first discharge pipe **56** (or simply discharge pipe **56**), a second sump pump **80** (or simply sump pump

80), and a sump pump shelf system **110** (or simply shelf system **110**).

Sump Pump Basin **12** (Not Shown)

[0063] With reference to the figures, the sump pump basin **12** is formed of any suitable size, shape, and design and is configured to move water from the inside of a structure to the outside of a structure. For ease of explanation the sump pump basin **12** is a constructed pit below a main surface in the interior of the structure and configured to hold one or more sump pumps such as first sump pump **40** and/or second sump pump **80**. However, the arrangements are not so limited. Rather it is understood that in some various arrangements, system **10** may be positioned where first sump pump **40** is in an interior **14** of the basin while second sump pump **80** is on the outside of the basin.

[0064] In one or more arrangements, as one example, sump pump basin **12** has an interior **14**, a top side **16**, a bottom side **18**, a cover **20** (not shown), a lip **22**, a drainage pipe **26** (not shown), an opening for the drainage pipe, and a warning system **30** (not shown) for the drainage pipe.

[0065] In one or more arrangements, as one example, the interior of sump pump basin **12** may be circular or curved **24** to direct discharge flow and to obtain a more compact sump pump system **10**. However, the interior of sump pump basin **12** may be any suitable size, shape, and design.

[0066] In one or more arrangements, bottom side **18** may be flat to facilitate the placement of first sump pump **40** at the bottom of sump pump basin **12** to collect excess water entering sump pump basin **12** from drainage pipe **26**. The shape or surface of bottom side **18** may be any suitable size, shape, and design, configured to collect water and facilitate placement of first sump pump **40**.

[0067] In one or more arrangements, drainage pipe **26** may enter sump pump basin **12** through opening **28** (not shown) to direct water into sump pump basin **12**. The opening **28** and drainage pipe **26** may be circular shaped to better facilitate the flow of water through drainage pipe **26** and into sump pump basin **12**. Opening **28** may be placed above first sump pump **40**, at the same level as sump pump **40** or below sump pump **40**. For example, opening **28** may be placed to align with a middle portion **44** of sump pump **40**, a top side **42** of sump pump **40**, or a bottom side **46** of sump pump **40** to facilitate water entering sump pump basin **12** through drainage pipe **26**. The placement of first sump pump **40**, drainage pipe **26**, and opening **28** may be any suitable size, shape, and design to facilitate water entering sump pump basin **12** through drainage pipe **26** and pumped out by at least first sump pump **40**.

[0068] In one or more arrangements, a top side **16** of sump pump basin **12** prevents moisture, odor, or radon gas from escaping sump pump basin **12**. In the arrangement, top side **16** may have a cover **20** to prevent moisture, odor, and radon gas from escaping sump pump basin **12**. Cover **20** may be sealed to sump pump basin **12**. In some other arrangements cover **20** may be removable from sump pump basin **12** to allow access to interior **14** and system **10** components. Top side **16** may have a lip **22** shaped to match the shape of interior **14**, for example, lip **22** may be shaped to align with curve **24** of interior **14** to maintain a compact system **10** and allow cover **20** to fit to sump pump basin **12**. Top side **16**, cover **20** and lip **22** may be any suitable size, shape, and design to facilitate closing system **10** to prevent moisture, odor or gas from escaping sump pump basin **12**.

[0069] In one or more arrangements, sump pump basin **12** may have a warning system **30** (not shown) to alert a user of system **10** that water in interior **14** has reached a certain level or is escaping system **10**. For example, warning system **30** may alert a user if the water level has reached a top side **42** of sump pump **40** or a bottom **86** of sump pump **80**. Warning system **30** may be any suitable size, shape, and design to alert the user that water has reached a certain level or is escaping the system.

[0070] However, the arrangements and components are not so limited. Rather it is contemplated that in some various arrangements, sump pump basin **12** or its components may have alternative shapes, sizes or designs.

First Sump Pump **40**

[0071] With reference to the figures, first sump pump **40** or sump pump **40** is formed of any suitable size, shape, and design and is configured to pump water from interior **14** to through a first

discharge pipe **56** or discharge pipe **56** to the outside of a structure. Sump pump **40** may have various components including but not limited to a power supply **62**, a sump pump stand **64** (not shown), a check valve **60** (not shown), a float **52**, and a discharge pipe **56** to facilitate the pumping of water from sump pump basin **12** to an exterior of a structure. In some arrangements, sump pump **40** may be a submersible pump wherein at least a portion of sump pump **40** may be submersed in water before float **52** activates sump pump **40**. Sump pump **40** may have a top side **42** opposing a bottom side **46** and a middle **44** between the top side **42** and bottom side **46**. However, the arrangements are not so limited. Rather it is understood that in some various arrangements, sump pump **40** may not have a sump pump stand **64** and instead a bottom surface **46** of sump pump **40** is on bottom side **18** of sump pump basin **12**.

[0072] In one or more arrangements, as is shown for example, sump pump **40** is operably connected to a discharge pipe **56** to facilitate the discharge or expulsion of water or other liquids from sump pump basin **12** to an exterior of a structure to prevent an interior of the structure from flooding. Discharge pipe **56** may be operably connected to sump pump **40** through a discharge connection member **48**. In one or more arrangements, for example, discharge pipe **56** may be circular to facilitate the discharge of water from sump pump basin **12**. Discharge pipe **56** may be operably connected to a bottom side **46** of sump pump **40**. In one or more arrangements, discharge pipe **56** may have an exterior **58** which is exposed to water or other liquid in sump pump basin **12**. Discharge pipe **56** may be any suitable size, shape, and design to expel water, liquid, or other material from sump pump basin **12**.

[0073] In one or more arrangements as is shown, float **52** is operably connected to sump pump **40** to detect a water level in sump pump basin **12** or activate sump pump **40** when water or other liquid has reached a certain level in sump pump basin **12**. In one or more arrangements, float **52** may have a float connection member **50**, which attaches to sump pump float connection member **54** to connect float **52** to sump pump **40**. In one or more arrangements, when float **52** is lifted to a certain level, sump pump **40** activates or starts pumping water through discharge pipe **56** to an exterior of the structure. In the arrangement shown, as one example, float **52** is a tether float switch. However, in some other arrangements, float **52** may be a piggyback float switch, vertical float switch and electrical float switch or any other float switch that will detect a water level in sump pump **40**. Float **52**, Float connection member **50**, and sump pump float connection member **54** may be any suitable size, shape, and design to detect water levels sump pump basin **12**.

[0074] In one or more arrangements, for example, discharge pipe **56** may have a check valve **60** (not shown) to facilitate the flow of water through discharge pipe **56**. Check valve **60** may be any size shape and design to facilitate the flow of water through discharge pipe **56**.

[0075] In one or more arrangements, as is shown for example, sump pump **40** has a power supply **62** to power sump pump **40**. Power supply **62** may be any size shape and design to facilitate the flow of water through discharge pipe **56**.

[0076] In one or more arrangements, for example, bottom side **46** has support members **164** to create space between sump pump **40** and bottom side **18** of the sump pump basin **12** to prevent sump pump **40** from clogging. Additionally, or alternatively, in one or more arrangements, a sump pump stand **64** may be used to prevent sump pump **40** from clogging. Sump pump stand **64** may have a top side **66**, a bottom side **68**, and an edge **70**. Bottom side **18** of sump pump **40** may be placed on top side **66** of the sump pump stand **64** and bottom side **68** of sump pump stand **64** may be placed on bottom side **18** to prevent sump pump **40** from clogging. Sump pump stand **64** may be any size shape and design to facilitate the flow of water through discharge pipe **56**.

Second Sump Pump **80**

[0077] With reference to the figures, second sump pump **80** or sump pump **80** is formed of any suitable size, shape, and design and is configured to pump water from interior **14** to through a second discharge pipe **96** or discharge pipe **96** to the outside of a structure. Sump pump **80** may have various components including but not limited to a power supply **100** (not shown), a check

valve **98** (not shown), a float **92**, and a discharge pipe **96** to facilitate the pumping of water from sump pump basin **12** to an exterior of a structure. In some arrangements, sump pump **80** is a secondary sump pump to facilitate the pumping of water out of sump pump basin **12** when sump pump **40** fails or is having a hard time keeping the water below a certain level. In some arrangements, sump pump **80** may be a submersible pump wherein at least a portion of sump pump **40** may be submersed in water before float **92** activates sump pump **80**. Sump pump **80** may have a top side **82** opposing a bottom side **86** and a middle **84** between the top side **82** and bottom side **86**. However, the arrangements are not so limited. Rather it is understood that in some various arrangements, sump pump **80** may be placed above sump pump basin **12** and float **92** is in interior **14** of sump pump basin **12** to facilitate a more compact system **10**.

[0078] In one or more arrangements, as is shown for example, sump pump **80** is operably connected to a discharge pipe **96** to facilitate the discharge or expulsion of water or other liquids from sump pump basin **12** to an exterior of a structure to prevent an interior of the structure from flooding. Discharge pipe **96** may be operably connected to sump pump **80** through a discharge connection member **88**. In one or more arrangements, for example, discharge pipe **96** may be circular to facilitate the discharge of water from sump pump basin **12**. Discharge pipe **96** may be operably connected to a bottom side **86** of sump pump **80**. Discharge pipe **96** may be any suitable size, shape, and design to expel water, liquid, or other material from sump pump basin **12**.

[0079] In one or more arrangements, as is shown, float **92** is operably connected to sump pump **80** to detect a water level in sump pump basin **12** or activate sump pump **80** when water or other liquid has reached a certain level in sump pump basin **12**. In one or more arrangements, float **92** may have a float connection member **90** which attaches to sump pump float connection member **94** to connect float **92** to sump pump **80**. In one or more arrangements, when float **92** is lifted to a certain level, sump pump **80** activates or starts pumping water through discharge pipe **96** to an exterior of the structure. In the arrangement shown, as one example, float **92** is a tether float switch. However, in some arrangements, float **92** may be a piggyback float switch, vertical float switch and electrical float switch or any other float switch that will detect a water level in sump pump **80**. Float **92**, Float connection member **90**, and sump pump float connection member **94** may be any suitable size, shape, and design to detect water levels sump pump basin **12**.

[0080] In one or more arrangements, for example, discharge pipe **96** may have a check valve **98** (not shown) to facilitate the flow of water through discharge pipe **96**. Check valve **98** may be any size shape and design to facilitate the flow of water through discharge pipe **96**.

[0081] In one or more arrangements, as is shown for example, sump pump **80** has a power supply **100** to power sump pump **80**. Power supply **100** may be any size shape and design to facilitate the flow of water through discharge pipe **96**.

Shelf System **110**

[0082] With reference to the figures, shelf system **110** is formed of any suitable size, shape, and design and is configured to stabilize and hold sump pump **80** above sump pump **40** or at least a portion of sump pump **40**. In one or more arrangements, shelf system **110** may have various components including but not limited to a shelf assembly **112** (or simply shelf **112**), a connection member **144**, and a support member **164** to hold and store sump pump **80** in interior **14** of sump pump basin **12** above at least a portion of sump pump **40**. However, the arrangements are not so limited. Rather it is understood that in some various arrangements, shelf system **110** may be used to store and stabilize sump pump **80** to help maintain a compact system **10**.

Shelf **112**:

[0083] In one or more arrangements, as is shown for example, shelf **112** has a top side **114** configured to facilitate storage and positioning of sump pump **80**. Bottom side **86** rests on top side **114** providing stabilization of sump pump **80**. Top side **114** may have one or more drainage openings **116** to facilitate draining of water from shelf **112** toward bottom side **18** of sump pump basin **12**. In one or more arrangements, top side **114** may be a flat surface to level sump pump **80**.

Top side **114** and drainage openings **116** may be any suitable size, shape, and design to store and stabilize sump pump **80** or to drain water from top side **114**.

[0084] In one or more arrangements, as is shown for example, shelf **112** has a bottom side **118** to facilitate the connection between shelf **112** and support member **164**. Bottom side **118** may have cells **120**, or hollow cells **120** separated by cell walls to increase the strength and weight limit of shelf **112**. Bottom side **118** may have a support connection member **124** to attach shelf **112** to support member **164**. Support connection member **124** may be any suitable size, shape, and design and is configured to operably connect shelf **112** to support member **164**.

[0085] In the arrangement shown, for example, support connection member **124** may be circular and sized to fit around a shape of support member **164**, where support connection member **124** rests on a top of support member **164** and sides **176** of support connection member **124** prevent support member **164** from moving. However, the arrangements are not so limited. Rather, it is contemplated that various additional or alternative methods and or means of connecting shelf **112** to support member **164**. The side of support connection member **124** may have a height **126**. The height **126** may allow a user to measure the distance between the shelf **112** and a bottom surface such as the bottom side **18** of sump pump basin **12**. The support connection member may have an opening **162** to facilitate a user's ability to stick a measuring unit through the support connection member **164** to the support member **164** or through the support member **164** or a user may measure a water level of the sump pump basin by sticking a measuring tape through opening **162**. Opening **162** may be on side **176** of support connection member **124** or at the top of support connection member **178** and visible on top side **114** of shelf **112**. Opening **162** may run the entire height **126** of support connection member **124**. A top **168** of opening **162** may have a first width **170** and a bottom **172** of opening may have a second width **174**. The first width **170** may be smaller than the second width **174**, where the second width is large enough to facilitate encompassing the support member but the first width is small enough that the support member does not slide through the support connection member **124**. Bottom side **118**, cells **120**, cell walls **122**, support connection member, and opening **162** may be any suitable size, shape, and design to facilitate the attachment of shelf **112** to support member **164**. In addition, bottom side **118**, cells **120**, cell walls **122**, support connection member, and opening **162** may be any suitable size, shape, and design to facilitate measuring a water level of sump pump basin **12**.

[0086] In one or more arrangements, as is shown for example, shelf **112** has a forward end **128** to secure shelf **112** to discharge pipe **56** to stabilize and store sump pump **80**. The shape of the forward end **128** may allow placement of the shelf **112** around sump pump **80** while maintaining a compact system **10** without replumbing system **10**. Forward end **128** may have a top portion **130** with a first width **132**, a middle portion **134** with a second width **136**, and a bottom portion **138** with a third width **140**. In some other arrangements, forward end may have top portion **130** with a first width **132** and a bottom portion **138** with a second width **140**. The first width **132** may be greater than the second width **136**, which in turn may be greater than the third width **140**, this tapering of forward end **128** facilitates the placement of shelf **112** around discharge pipe **56** and/or around sump pump **40** or other components of system **10**. In addition, the tapering may allow shelf **112** to be placed above sump pump **40** or different components of sump pump **40** such as float **52**. The top portion **130**, middle portion **134**, and bottom portion **138** may be any suitable size, shape, and design to facilitate placement of the shelf **112** around the first sump pump **40**.

[0087] In one or more arrangements, as is shown for example, forward end **128** has a connection recess **142** configured to wrap around at least part of exterior **58** of discharge pipe **56** to secure shelf **112** to discharge pipe **56**. Connection recess **142** may have a cylindrical shape to match the shape of exterior **58** of discharge pipe **56**. Connection recess **142** may run a height **150** of forward end **128** or run along a middle of shelf **112** or a middle portion of forward end **128**. In one or more arrangements, as is shown, connection recess **142** fits around a portion of exterior **58**. However, in some other arrangements, connection recess **142** may fit around more or less of exterior **58**. In one

or more arrangements, connection recess **142** may be configured to surround exterior **58** for the height **150** of forward end **128**. In one or more arrangements, connection member **144** is configured to secure connection recess **142** to exterior **58** of discharge pipe **56**. The connection member **144** may secure shelf **112** to discharge pipe **56** by securing members **148** attached to connection openings **146**.

[0088] In one or more arrangements, for example, connection member **144** may be a clamp, such as a hose clamp, screw clamp, or a band clamp. Forward end **128** may have a connection wall **188** extending upwards from top portion **130** of forward end **128**. Connection wall **188** is configured to facilitate securing the shelf **112** to the first discharge pipe **56** using the connection member **144**. The connection wall **188** may have a width **192** that extends partially around the first discharge pipe **56** or fully around the first discharge pipe **56**. Connection wall **188** may have height **190**. Height **190** of connection wall **188** may be the same height of the securing member **144** or it may be higher or lower. Securing members **148** are configured to secure the hose clamp around the discharge pipe **56** and the connection member wall **188**. Securing members may be nuts, bolts, screws, shaped to slide into connection openings **146**, or any other design, shape, method, or suitable size to facilitate securing shelf **112** to discharge pipe **56**. In one or more arrangements the securing members **148** may be configured to allow a user to tighten or loosen the connection member **144**, thereby allowing shelf **112** to be raised, lowered, placed around discharge pipe **56**, or removed from discharge pipe **56**.

[0089] In one or more arrangements, for example, the connection member **144** may be a band placed around the portion of exterior **58** that is not covered by connection recess **142** and secured to connection openings **146** by securing members **148**. Securing members **148** may be nuts, bolts, screws, shaped to slide into connection openings **146**, or any other design, shape, method, or suitable size to facilitate securing shelf **112** to discharge pipe **56**. Connection openings **146** may be any design, shape, method, or suitable size configured to receive securing members **148**. Connection member **144** may be any suitable size, shape, and design and is configured to operably connect shelf **112** to discharge pipe **56**.

[0090] In one or more arrangements, as is shown for example, forward end **128** may have one or more recesses **166** configured to fit shelf **112** around one or more components of sump pump **40**. For example, the plurality of recesses **166** may be curved **184** to fit around an exterior of sump pump **40**. In addition, recess **166** may allow shelf **112** to be placed above sump pump **40** or different components of sump pump **40** such as float **52** or around float **52**. In one or more arrangements, for example, forward end **128** has two recesses **166** symmetrical to each other, each on one side of connection recess **142**. The shape of recesses **166** may aid in placement of shelf **112** around discharge pipe **56**. Recesses **166** may be any suitable size, shape, and design and is configured to operably connect shelf **112** to discharge pipe **56** or place the shelf above or around one or more components of system **10**. In one or more arrangements shelf **112** may not have recesses **166**, and have convex sides or straight sides to place shelf **112** place the shelf above or around one or more components of system **10**.

[0091] In one or more arrangements, as is shown, shelf **112** has a rearward end **152** to facilitate placement of shelf **112** in system **10**. The rearward end may oppose the forward end **128**. In one or more arrangements, rearward end **152** has a curve **156** to facilitate alignment of shelf **112** with one or more components of system **10**. For example, curve **156** may match curve **24** of basin **12** and facilitate alignment of shelf **112** to be adjacent to interior **14** of sump pump basin **12** to maintain a compact system **10**. In one or more arrangements, rearward end has a lip **158** having a height **154** to facilitate alignment of shelf **112** with one or more components of system **10** such as interior **14** of sump pump basin **12**. Height **154** may be less than height **150** of forward end **128** creating a tapering **186** or curve of the bottom side **118** of shelf **112** from forward end **128** to rearward end **152**. This tapering **186** facilitates or is configured to help aid in placement of shelf **112** above one or more components of sump pump **40**. The rearward end **152** may be any suitable size, shape, and

design and is configured to operably connect shelf **112** to discharge pipe **56** or place the shelf above or around one or more components of system **10**.

[0092] In one or more arrangements shelf system **110** has opposing sides **160** shaped to facilitate placement of shelf **112** along interior **14** of sump pump basin **12**. Opposing sides **160** may be any suitable size, shape, and design and is configured to operably connect shelf **112** to discharge pipe **56** or place the shelf **112** above, around, or in alignment with one or more components of system **10**.

[0093] In one or more arrangements shelf system **110** has one or more support members **164** configured to support shelf **112**. In one or more arrangements, as is shown, support member **164** is operably connected to shelf **112** through support connection member **124** securing a top **182** (not shown) of support member **164** to shelf **112** to stabilize shelf and sump pump **80**. A bottom **180** of support member **164** is configured to rest or is adjacent to bottom side **18** of sump pump basin **12**. In one of more arrangements, support member **164** has a length configured to place shelf **112** above at least a portion of sump pump **40** or other components of system **10**. Support member **164** may be any suitable size, shape, and design to support shelf **112** and place the shelf **112** above or around one or more components of system **10**.

System **10** Assembly:

[0094] System **10** Assembly is formed of any suitable size, shape and design and is configured to facilitate pumping water from a sump pump basin **12** and supporting a secondary sump pump **80** while maintaining a compact system **10**. In the arrangement shown, as one example, sump pump system **10** includes a sump pump basin **12** where first sump pump **40** and second sump pump **80** are stored in an interior, among other components. First discharge pipe **56** is operatively connected to first sump pump **40** and moves toward a top of the sump pump basin. Bottom side **180** of support member **164** is placed on bottom side **18** of sump pump basin **12** at top of support member shelf **112** is placed on top of support member **164** through connection member **144**. Shelf **112** is secured to first discharge pipe **56** through a connection recess **142**. A connection member **144** facilitates securing first discharge pipe **56** to shelf **112**. Connection member **144** and connection recess **142** may surround exterior **58** of first discharge pipe **56**. Connection member **144** may be secured to shelf **112** through securing members **148**. Shelf **112** may be placed above at least a portion of sump pump **40** so sump pump **80** only activates if sump pump **40** fails or is unable to maintain the water level. Sump pump **80** is placed on top of shelf **112**. Shelf **112** provides a stabilizing surface for sump pump **80**. However, the arrangements are not meant to be limited. Rather, system **10** may have various arrangements and one or more components may be altered or not present in various arrangements.

[0095] In one or more arrangements, system **10** and shelf system **110** and/or any components of system **10** and shelf system **110** are formed by any material having suitable durability and strength for pumping water out of sump pump basin **12**. Shelf system **110** and or any components of shelf system **110** are formed by any material having suitable durability and strength for storing and stabilizing sump pump **80** above at least a portion of sump pump **40**.

In Operation:

[0096] In one or more arrangements, sump pump **40** is provided and placed at a bottom **18** of sump pump basin **12**. First discharge pipe **56** is operably connected to sump pump **40** through discharge connection member **48**. Support member **164** is provided and a bottom **180** of support member **164** is placed at a bottom **18** of sump pump basin **12**. Support member **164** may be set vertically up right. Shelf **112** is placed on top **182** of support member **164** and is operably connected to support member **164** through support connection member **124**. A connection member **144** is provided to secure shelf **112** to first discharge pipe **56** utilizing connection recess **142**. Sump pump **80** is placed on shelf **112** after shelf **112** is secured to first discharge pipe **56**.

[0097] In one or more arrangements, water enters sump pump basin **12** through drainage pipe **26** (not shown) and begins to fill sump pump basin **12**. Once the water level reaches a certain

threshold float **52** detects the water level and activates sump pump **40** through float connection member **50** and sump pump float connection member **54**. Sump pump **80** is not activated yet as sump pump **80** is placed above at least a portion of sump pump **40** on shelf **112**. Sump pump **40** discharges water through discharge pipe **56**. The water level may continue to rise as sump pump **40** fails or can't maintain the water level due to the amount of water entering sump pump basin **12**. Shelf **112** is placed at a certain level above sump pump **40**, the level may be determined by a height of support member **164**, allowing sump pump **80** to act as a secondary sump pump or back up sump pump. Shelf **112** stabilizes sump pump **80** so the pump is not displaced as water levels rise. As the water levels rise above at least a portion of sump pump **40** and reaches float **92**, float **92** detects the water level and activates sump pump **80** through float connector **90** and sump pump float connector **94**. Sump pump **80** discharges water through second discharge pipe **96**.

[0098] This example of operation is not meant to be limited. Rather, system **10** may operate in various ways to facilitate the discharge of water from sump pump basin **12**.

[0099] From the above discussion it will be appreciated that the sump pump system and related method of use, presented herein, improves upon the state of the art.

[0100] Specifically, the sump pump system presented: provides improved functionality over prior art systems; provides improved features over prior art systems; is relatively inexpensive; is easy to use; is intuitive to use; is strong and robust; can be used in many applications; provides unique functionality; is fast to use and fast to set-up; is safe to use; saves time; has a compact size; is adjustable, has a long useful life; is high quality; and/or improves efficiencies, among countless other advantages and improvements.

[0101] It will be appreciated by those skilled in the art that other various modifications could be made to the device without parting from the spirit and scope of this disclosure. All such modifications and changes fall within the scope of the claims and are intended to be covered thereby.

SELECT REFERENCE NUMBERS

[0102] **10**—Sump Pump System [0103] **12**—Sump Pump Basin [0104] **14**—Interior (Sump Pump Basin) [0105] **16**—Top Side (Sump Pump Basin) [0106] **18**—Bottom Side (Sump Pump Basin) [0107] **20**—Cover (Sump Pump Basin) [0108] **22**—Lip (Sump Pump Basin) [0109] **24**—Curve (Interior of Sump Pump Basin) [0110] **26**—Drainage Pipe [0111] **28**—Opening (Drainage Pipe) [0112] **30**—Warning System [0113] **40**—First Sump Pump [0114] **42**—Top Side (First Sump Pump) [0115] **44**—Middle (First Sump Pump) [0116] **46**—Bottom Side (First Sump Pump) [0117] **48**—Discharge Connection Member (First Sump Pump) [0118] **50**—Float Connection Member (First Sump Pump) [0119] **52**—Float (First Sump Pump) [0120] **54**—Sump Pump Float Connection Member (First Sump Pump) [0121] **56**—Discharge Pipe (First Sump Pump) [0122] **58**—Exterior (First Discharge Pipe) [0123] **60**—Check Valve (Discharge Pipe First Sump Pump) [0124] **62**—Power Supply (First Sump Pump) [0125] **64**—Sump Pump Stand [0126] **66**—Top Side (First Sump Pump Stand) [0127] **68**—Bottom Side (First Sump Pump Stand) [0128] **70**—Edge (First Sump Pump Stand) [0129] **80**—Second Sump Pump [0130] **82**—Top Side (Second Sump Pump) [0131] **84**—Middle (Second Sump Pump) [0132] **86**—Bottom Side (Second Sump Pump) [0133] **88**—Discharge Connection Member (Second Sump Pump) [0134] **90**—Float Connection Member (Second Sump Pump) [0135] **92**—Float (Second Sump Pump) [0136] **94**—Sump Pump Float Connection Member (Second Sump Pump) [0137] **96**—Discharge Pipe (Second Sump Pump) [0138] **98**—Check Valve (Discharge Pipe Second Sump Pump) [0139] **100**—Power Supply (Second Sump Pump) [0140] **110**—Sump Pump Shelf System/Shelf System [0141] **112**—Shelf [0142] **114**—Top Side (Shelf) [0143] **116**—Openings (Top Side Shelf Drainage) [0144] **118**—Bottom Side (Shelf) [0145] **120**—Cells (Bottom Side Shelf) [0146] **122**—Cell Walls (Bottom Side Shelf) [0147] **124**—Support Connection Member (Bottom Side Shelf) [0148] **126**—Height (Support Connection Member) [0149] **128**—Forward End (Shelf) [0150] **130**—Top Portion (Forward End Shelf) [0151] **132**—Width (Top Portion Forward End Shelf) [0152] **134**—Middle

Portion (Forward End Shelf) [0153] **136**—Width (Middle Portion Forward End Shelf) [0154] **138**
 —Bottom Portion (Forward End Shelf) [0155] **140**—Width (Bottom Portion Forward End Shelf)
 [0156] **142**—Connection Recess (Forward End Shelf) [0157] **144**—Connection Member (Forward
 End Shelf) [0158] **146**—Connection Openings (Forward End Shelf) [0159] **148**—Securing
 Members (Connection Member Forward Shelf) [0160] **150**—Height (Forward End Shelf) [0161]
152—Rearward End (Shelf) [0162] **154**—Height (Rearward End Shelf) [0163] **156**—Curve
 (Rearward End Shelf) [0164] **158**—Lip (Rearward End Shelf) [0165] **160**—Opposing Sides (Shelf)
 [0166] **162**—Opening (Measurement Shelf/Support Connection Member Opening/Top Side Shelf)
 [0167] **164**—Support Member [0168] **166**—Recess (Shelf) [0169] **168**—Top Of Opening
 (Measurement Shelf) [0170] **170**—Width Of Top of Opening (Measurement Shelf) [0171] **172**—
 Bottom Of Opening (Measurement Shelf) [0172] **174**—Width Of Bottom of Opening
 (Measurement Shelf) [0173] **176**—Sides Of Support Connection Member [0174] **178**—Top Of
 Support Connection Member [0175] **180**—Bottom Of Support Member [0176] **182**—Top Of
 Support Member [0177] **184**—Curve of Forward Side (Shelf) [0178] **186**—Curve of Bottom Side
 (Shelf) [0179] **188**—Connection wall [0180] **190**—Height of connection wall [0181] **192**—Width
 of connection wall

Claims

1. A sump pump system comprising: a sump pump basin; a first sump pump; a first discharge pipe operatively connected to the first sump pump; a second sump pump; a second discharge pipe operatively connected to the second sump pump; and a shelf system comprising a shelf having a top side opposing a bottom side; wherein the top side of the shelf is configured to support the second sump pump; wherein a shape of the shelf is configured to facilitate placement of the shelf adjacent to the first discharge pipe.
2. The system of claim 1, further comprising: a support member; wherein the bottom side of the shelf comprises a support connection member to facilitate the connection of the shelf to the support member.
3. The system of claim 1, wherein the shelf comprises a connection recess configured to receive the first discharge pipe.
4. The system of claim 1, the shelf further comprising: a connection recess configured to receive the first discharge pipe; a connection member configured to secure the shelf to the first discharge pipe in the connection recess; a plurality of connection openings configured to secure the connection member to the shelf.
5. The system of claim 1, the shelf further comprising: a forward end having a first height; and a rearward end having a second height; wherein the forward end comprises a connection recess configured to secure the shelf to the first discharge pipe; wherein the first height is greater than the second height.
6. The system of the claim 1, wherein the shelf comprises a rearward end, wherein a lip of the rearward end is shaped to align with a lip of the sump pump basin.
7. A sump pump system comprising: a sump pump basin having a hollow interior; a first sump pump housed within the hollow interior of the sump pump basin; a second sump pump having a bottom side and housed within an interior of the sump pump basin; and a shelf system configured to store the second sump pump, the shelf system further comprising: a shelf having a top side configured to hold the second sump pump; wherein the shelf facilitates placement of the second pump above the first sump pump.
8. The system claim 7, further comprising: a support member having a top opposing a bottom, wherein the bottom of the support member is adjacent to a bottom of the sump basin.
9. The system of claim 7, further comprising: a support member having a top opposing a bottom, wherein the bottom of the support member is adjacent to a bottom of the sump basin; wherein the

shelf further comprises a support connection member on a bottom side of the shelf; wherein the support connection member facilitates securing the support member to the shelf.

10. The system of claim 7, the shelf further comprising: a forward end having a plurality of recesses; and a rear end; wherein the rear end has a curved lip, wherein the curved lip is adjacent to a surface of the interior of the sump pump basin.

11. The system of claim 7, the shelf further comprising: a forward end having a plurality of recesses; and a rear end; wherein the forward end has a top portion having a first width, a middle portion having a second width, and a bottom portion having a third width; wherein the first width is greater than the third width.

12. The system of claim 7, further comprising: a first discharge pipe operatively connected to the first sump pump; wherein the shelf system further comprises a connection member; wherein the shelf further comprises a forward end having a stand recess and a plurality of connection member recesses; wherein the connection member secures the first discharge pipe within the stand recess of the shelf using the plurality of connection member recesses.

13. A shelf system, the system comprising: a shelf having a top side and a bottom side; the shelf further comprising: a rearward end; a forward end having a plurality of recesses, wherein at least one of the plurality of recesses is configured to facilitate placement of the shelf adjacent to a first sump pump; a top side having a plurality of openings to facilitate liquid draining from the top side of the shelf, wherein the top side is configured to support a second sump pump; and a bottom side having a support connection member to facilitate securing the shelf to a support member; the support member having a top side, wherein the top side secures the support member to the support connection member, wherein the support member is configured to stabilize the shelf; wherein the shelf is configured to support a second sump pump; wherein the support member is configured to stabilize the shelf above at least a middle portion of the first sump pump.

14. The system of claim 13, wherein the rearward end is curved and where in the curve is aligned to fit with an interior of a sump pump basin.

15. The system of claim 13, wherein the forward end comprises a connection recess configured to secure the shelf to a first discharge pipe of the first sump pump.

16. The system of claim 13, wherein the shelf further comprises: a connection recess configured to receive a first discharge pipe; a connection member configured to secure the shelf to the first discharge pipe in the connection recess; a securing member configured to tighten the connection member.

17. The system of claim 13 wherein the bottom side has a plurality of hollow cells.

18. The system of claim 13 wherein the forward end has a top portion having a first width, and a bottom portion having a second width, and wherein the first width is greater than the second width.

19. The system of claim 13, wherein the forward end has a first height and the rearward end has a second height and wherein the first height is greater than the second height.
