

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275525

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Cook; Todd Michael

DEVICE FOR CONNECTING A LURE TO FISHING LINE

Abstract

A device for connecting a lure to a fishing line, the device includes a main shaft having a line attachment end and a lure holding end. A line holding element is provided at the line attachment end and a lure holding loop is provided at the lure holding end. The device further includes various other components to improve lure retention without impairing lure movement. These other components include one or more from the group of a retaining loop, three or more resistance points, a zigzag structure and a reverse direction terminating segment.

Inventors: Cook; Todd Michael (Painted Post, NY)

Applicant: Cook; Todd Michael (Painted Post, NY)

Family ID: 67540782

Appl. No.: 19/183813

Filed: April 19, 2025

Related U.S. Application Data

parent US continuation 16269697 20190207 parent-grant-document US 12279604 child US 19183813

us-provisional-application US 62628343 20180209

Publication Classification

Int. Cl.: A01K91/04 (20060101)

U.S. Cl.:

CPC A01K91/04 (20130101);

Background/Summary

RELATED APPLICATIONS [0001] This patent application is a continuation of copending U.S. Nonprovisional patent application Ser. No. 16/269,697, filed Feb. 7, 2019 that claims the benefit of priority of U.S. Provisional Patent Application No. 62/628,343, filed on Feb. 9, 2018, each of which is incorporated by reference herein in its entirety. This patent application is also related to U.S. Design patent application Ser. No. 29/636,568, filed on Feb. 9, 2018, U.S. Design patent application Ser. No. 29/817,889, filed Dec. 5, 2021, and U.S. Design patent application Ser. No. 29/997,285, filed Apr. 7, 2025, each of which is incorporated by reference herein in its entirety.

FIELD

[0002] The present invention generally relates to a device for connecting fishing line to a lure. More specifically, the invention relates to a device with multiple resistance points that prevent the lure from disconnecting and if the lure does pass one or more of the resistance points the lure can still move freely with a natural lure action.

BACKGROUND

[0003] Numerous devices exist for attaching a lure to a fishing line. These devices try to provide for a strong connection, ease of attachment, unhindered natural lure movement and minimizing the possibility of detachment of the lure. Two main classes of lure attachment devices exist; open and closing fishing snaps (U.S. Pat. Nos. 2,109,967, 5,781,972, 4,234,998, 5,042,191 and US D430,261) and wind-on fishing devices (US 2006/0265939 and US D536,763). While the goal of these devices is to maximize all of the attributes listed above usually only one or two of the attributes are achieved for any device.

[0004] For example, snaps that open and close have several drawbacks. These devices tend to weaken over time and have a propensity to unexpectedly open. Open and closing snaps usually have a single point of resistance along the main bracing arm, where if this point of resistance fails (i.e., it opens), then the lure or fish may be lost. Open and closing snaps can be hard on the fingers, especially in cold weather. Small versions can be tedious and dexterously challenging. Cross-locking mechanisms can be especially dexterously challenging because the larger latching hook or bent hook extremity can often end up accidentally closing on the inside of the smaller latching hook or bent hook extremity. This can be very difficult to reopen. Cross-locking mechanisms lack closed wire twists at their endpoint and as a result are weaker where the fishing line attaches. Cross-locking mechanisms also do not lend themselves to an extended leader or single wire with a snap built-in because of the necessity to interlock the two ends of the snap; this therefore requires a separate component for leader implementation. Open and closing fishing snaps with two half loops, such as U.S. Pat. No. 5,042,191, offer a single point of tension that exists at the bottom of the half loops. Lures can work their way through these two half loops without any visual indication of a problem. These same snaps with their two overlapped half loops also often negatively affect fishing lure action because the overlapping portions double the necessary space (two overlapping pieces of wire vs. a single piece of wire) needed for the snap to move freely against the lure eyelet.

[0005] Similarly, wind-on devices also have several drawbacks. Wind-on fishing snaps possess a design whereby a permanent latching hook or bent hook extremity large enough to wind on a lure suffers from an opening gap forming over time as the metal loses its strength and springiness which keeps the gap closes. Some wind-on devices have multiple coils running parallel to one another around a central body portion (US D536,763). In larger sizes, the coils tend to be far enough apart such that they provide an easy pathway for a lure to start working its way back out which affects the lure action. In smaller sizes, the multiple coils are all but destroyed when trying to wind on lures of even moderate size.

[0006] The present invention aims to eliminate many of the short comings of prior devices and

provide the desired combination of a strong connection, ease of attachment, multiple resistance points, natural lure action and accommodate an extended leader.

SUMMARY

[0007] In one implementation, the present disclosure is directed to a device for connecting a lure to a fishing line. The device comprises a main shaft having a line attachment end and a lure holding end. A line holding element is provided at the line attachment end. A lure holding loop is provided at the lure holding end. The device further comprises a retaining loop continuing from the lure holding loop and substantially perpendicular to the main shaft. The retaining loop generates two points of resistance (three resistance points when considering that one is used twice) and the perpendicular orientation to the main shaft inhibits movement along the main shaft.

[0008] In another implementation, the present disclosure is directed to a device for connecting a lure to a fishing line. The device comprises a main shaft having a line attachment end and a lure holding end. A line holding element is provided at the line attachment end. A lure holding loop is provided at the lure holding end, the lure holding loop having a lure holding loop extension that extends towards the line attachment end, the lure holding loop extension creating three or more resistance points for the lure to inhibit the lure from disengaging from the device.

[0009] In yet another implementation, the present disclosure is directed to a device for connecting a lure to a fishing line. The device comprises a main shaft having a line attachment end and a lure holding end. A line holding element is provided at the line attachment end. A lure holding loop is provided at the lure holding end, the lure holding loop extends towards the line attachment end to form a zigzag structure that provides retaining areas for the lure.

[0010] In still yet another implementation, the present disclosure is directed to a device for connecting a lure to a fishing line. The device comprises a main shaft having a line attachment end and a lure holding end. A line holding element is provided at the line attachment end. A lure holding loop is provided at the lure holding end. The device further comprises an arced section crossing the main shaft. The arced section bends away from the line holding end. The arced section has a curved region connecting a terminating segment and a zag segment. The terminating segment is longer than the zag segment to prevent manual unraveling of the device.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0011] For the purposes of illustrating the invention, the drawings show aspects of one or more embodiments of the invention. However, it should be understood that the present invention is not limited to the precise arrangements and instrumentalities shown in the drawings, wherein:

[0012] FIG. 1 is a perspective view of one exemplary embodiment of the device for connecting a lure to a fishing line;

[0013] FIG. 2a is left-side elevational view of the device in FIG. 2b;

[0014] FIG. 2b is a front elevational view of the device in FIG. 1;

[0015] FIG. 2c is a right-side elevational view of the device in FIG. 2b;

[0016] FIG. 2d is a top plan view of the device in FIG. 2b;

[0017] FIG. 2e is a back elevational view of the device in FIG. 2b;

[0018] FIG. 2f is a bottom plan view of the device in FIG. 2b;

[0019] FIG. 3a is a perspective view of the device in FIG. 1 with the main shaft highlighted;

[0020] FIG. 3b is a perspective view of the device in FIG. 1 with various parts of the lure holding loop highlighted;

[0021] FIG. 3c is a perspective view of the device in FIG. 1 with the retaining loop highlighted;

[0022] FIG. 3d is a perspective view of the device in FIG. 1 with the bracing section highlighted;

[0023] FIG. 3e is a perspective view of the device in FIG. 1 with various parts of the arced section

highlighted;

[0024] FIG. **3f** is a perspective view of the device in FIG. **1** with the zigzag structure highlighted;

[0025] FIG. **3g** is a perspective view of the device in FIG. **1** with the folded end highlighted;

[0026] FIG. **3h** is a perspective view of the device in FIG. **1** with the line holding element highlighted;

[0027] FIG. **3i** is a perspective view of the device in FIG. **1** with the resistance points highlighted;

[0028] FIG. **3j** is a perspective view of the device in FIG. **1** indicating a secondary retaining region;

[0029] FIG. **3k** is a perspective view of the device in FIG. **1** indicating a tertiary retaining region;

[0030] FIG. **3l** is a perspective view of the device in FIG. **1** indicating a quaternary retaining region; and

[0031] FIG. **4** is a front elevational view of the device in FIG. **1** including a solid metal leader.

DETAILED DESCRIPTION

[0032] Device **20** (a.k.a. Prevent Snap™) for connecting lure **22** to fishing line **24** is illustrated in FIGS. **1-4**. Lure **22** has a lure attachment element **25** that may be a front eyelet, split ring or other element allowing attachment of the lure. Various views of device **20** are shown in FIGS. **2a-2b**.

Device **20** is made of wire having a wire thickness. Device **20** comprises a main shaft **26**, FIG. **3a**. Main shaft **26** has a line attachment end **28** and a lure holding end **30**. Main shaft **26** provides the main structural strength for device **20**. Main shaft **26** defines a central axis for device **20**, device axis X.

[0033] Lure holding loop **32** (a.k.a. primary retaining region) extends from lure holding end **30**, FIG. **3b**. In a preferred embodiment lure holding loop **32** is an elongated loop with a loop bottom **34**. Lure holding loop **32** is symmetric relative to axis X. Lure holding loop **32** has loop sides **36** that angle outward from axis X. Loop sides **36** widen from loop bottom **34** and then narrow towards main shaft **26**, the widening from loop bottom **34** (loop widening angle $\theta_{sub.1}$) is at a lesser loop-side angle than the narrowing at main shaft **26** (loop narrowing angle $\theta_{sub.2}$). The loop widening angle $\theta_{sub.1}$ is less than the loop narrowing angle $\theta_{sub.2}$. The wire has an angled bend **23** in both loop sides **36**. The symmetry and angling of loop sides **36** acts to keep lure **22** centered relative to axis X, located near loop bottom **34** and provides for optimal performance of the lure when in use in water. Although lure holding loop **32** is shown as an elongated symmetric loop, the lure holding loop could take on different shapes that do not deviate from the scope of the invention. However, with these different lure holding loop shapes the lure may move differently. Lure holding loop **32** has a lure holding loop extension **33** that extends towards the line attachment end **28**. Lure holding loop extension **33** includes additional components that create strength, multiple resistance points that prevent the lure from disconnecting and if the lure does pass one or more of the resistance points the lure can still move freely as a natural lure. Each resistance point is a narrowing of space between two parts of the wire where that space is narrower than the wire thickness. Holding loop extension **33** may be a subset of the elements shown within the bracket.

[0034] Extending from holding lure loop **32** is a retaining loop **38** that crosses back onto itself. FIG. **3c**. Retaining loop **38** is located near lure holding end **28** of main shaft **26**. The function of retaining loop **38** is to keep lure **22** from riding back up main shaft **26** and disconnecting itself from device **20** during casting or when a fish is attached to the lure. Retaining loop **38** performs this function by first creating two resistance points (one used twice), FIG. **3i**. Each resistance point provides enough tension so as to limit or preclude lure movement through the resistance point without manual assistance. Each resistance point is separated by open spaces (a, k, a, retaining regions) that allow the lure to move freely. For example, secondary retaining region S, FIG. **3j**, is the region bounded by resistance points A and B and includes most of retaining loop **38**. Tertiary retaining region T, FIG. **3k**, is the region bounded by resistance points C and D and includes portions of main shaft **26**, bracing section **40** and lure holding loop **32**. Quaternary retaining region Q, FIG. **3l**, is the region bounded by resistance points D and E and includes portions of main shaft **26**, bracing section **40** and arced section **44**. Free movement of the lure improves chances that the

lure will perform as intended during each cast. Resistance point A (fourth resistance point) is generated where retaining loop **38** gets close to or touches main shaft **26**. Resistance point A provides resistance to the lure moving out of lure holding loop **32**. Resistance points B/C (third and fifth resistance points) is generated where retaining loop **38** crosses back onto itself. Resistance point B/C provides resistance twice when attaching a lure and twice when taking a lure off because the lure goes through that point two times. Further enhancing the retaining properties of retaining loop **38** is the orientation of the retaining loop perpendicular to device axis X. This perpendicular orientation requires lure **22** to move around device axis X and not along the length of device **20** and therefore helps to limit the lure from detaching from device **20**.

[0035] The next part of device **20** is bracing section **40**, FIG. **3d**. Bracing section **40** (a.k.a. zig segment) extends from retaining loop **38** towards line holding element **42**. Bracing section **40** is substantially parallel to main shaft **26** and crosses the main shaft to create resistance point D (second resistance point), FIG. **3i**. The section of device **20** between resistance points B/C and D provides a secondary retaining region for the lure, where lure **22** can still move relatively freely with appropriate action to still entice fish with a natural lure action if for some reason the lure moves past resistance points A, B and C during the retrieve.

[0036] Bracing section **40** terminates in arced section **44**, FIG. **3e**. Arced section **44** includes a zag segment **46**, entry bend **48** and terminating segment **50**. Zag segment **46** and terminating segment **50** are two parallel arced sides of arced section **44**, the zag segment and terminating segment connected by entry bend **48**. Together bracing section **40** and zag segment **46** create a zigzag structure **52** across main shaft **26**, FIG. **3f**. Zigzag structure **52** consists of a straight elongated middle section with two shorter angled end sections. Zigzag structure **52** provides strength, resistance points and additional holding regions for device **20**. Arced section **44** crosses main shaft **26** at the same position on opposing sides of main shaft **26** creating resistance point E (first resistance point), FIG. **3i**. Arced section **44** bends away from both sides of main shaft **26**. The side of arced section **44** with the entry point **21** is longer than the side of the arced section which is on the opposite side of main shaft **26**. Resistance point E is the last of five resistance points that help to secure lure **22** to device **20**. Arced section **44** preferably terminates with a folded end **54**, FIG. **3g**. Arced section **44** provides (via folded end **54**) the entry point for the lure and is bent away from line attachment end **28** to assist in allowing device **20** to slide more easily through weeds and allowing a lure retrieval device to more easily slide over the snap. Folded end **54** is bent away from the line attachment end **28** to further assist in allowing the device to slide more easily through weeds versus being bent sideways, thus doubling the width of the segment. Folded end **54** also hides the sharp edge from directly facing a user's fingers or clothing. Arced section **44** bends away from the line attachment end **28**. Terminating segment **50** is longer than zag segment **46**; this structure helps to mechanically limit the unraveling of device **20**.

[0037] Line holding element **42** extends from line attachment end **28**, FIG. **3h**. In a preferred embodiment line holding element **42** is a closed wire twist. Line holding element **42** could be any line holding element from the group consisting of an eyelet, loop and closed wire twist. Device **20** may be further modified by adding a solid wire leader **60** extending from main shaft **26** to line holding element **42** as shown in FIG. **4**. Device **20** has a snap length **62** defined as a length inclusive from loop bottom **34** to the entry point at folded end **54**. Solid wire leader **60** is the only piece of wire between the line attachment element and all remaining elements. Solid wire leader **60** has a solid wire leader length **64** greater than snap length **62**. A solid wire leader **60** is often preferred when fishing for game fish that are armed with sharp teeth and/or for casting certain types of lures that require a side-to-side action such as “jerkbaits” or “glidebaits”. The stiffer leader allows the angler to more easily impart the sharp action needed to work such baits. Such lures can often times end up side-by-side with the leader or line due to the side-to-side action. If a fish with sharp teeth strikes, the fish can often times cut straight through the line.

[0038] Device **20** is first used by attaching fishing line **24** to line holding element **42**. Fishing line

24 may be attached using any of numerous knots that are well known in the art. Lure attachment clement is first slipped over folded end 54 and along arced section 44 where the lure encounters first resistance point E. Once pushed past the first resistance point E, lure 22 continues onward past zag segment 46 and onto bracing section 40 where lure encounters second resistance point D. Once pushed past the second resistance point D, lure 22 continues onward to retaining loop 38 where the lure encounters third resistance point B, C (for the first time) where the retaining loop crosses back onto itself. Once pushed past the third resistance point B, C, lure 22 continues along retaining loop 38 until the lure reaches the fourth resistance point A where retaining loop 38 crosses main shaft 26. Once pushed past the fourth resistance point A, lure 22 continues along retaining loop 38 until the lure encounters the fifth resistance point B, C (for the second time) where retaining loop crosses lure holding loop 32. Once pushed past the fifth resistance point B, C, the lure enters lure holding loop 32.

[0039] One should also consider that, over time, the constant opening and closing of snaps with open and closing mechanisms weakens them. This is where the Prevent Snap's additional holding regions are of significant value as they provide for only the gradual distortion of the device's form when adding and removing lures over time.

[0040] Device 20 has many benefits over prior art devices. First, there is no opening and closing of the device when putting on and taking off a lure. Other devices that are based on opening and closing weaken over time with no apparent notification that they have weakened. Also, smaller opening and closing styled snaps can be dexterously challenging and larger size snaps can be hard on the user's fingers. The Prevent Snap, having no tight curl at its entry, in most instances, allows the snap to be easily fed through an eyelet without the need of a split ring. To the contrary locking-styled, open-close snaps, having a tight curl at entry that may require a split ring be added in order to accommodate attaching. Second, the use of multiple points of contact (up to five in the current device) is of great benefit. When only a single point of contact is used, if that single point is stressed to failure, there is no back up and lures are more likely to come off. Third, perpendicular retaining loop 38 provides a point of contact which does not allow a lure to work past without great difficulty. Fourth, the bends running parallel to the main shaft that create zig-zag structure 52 ensure that a lure will continue to track correctly whereas perpendicular curls in other prior art devices force a lure sideways. Fifth, device 20 will not unwind or open without significant effort beyond fishing and line strength. Sixth, arced section 44 of device 20 is angled away from line attachment end 28 in an effort to allow weeds and, potentially, lure retrievers to slide more easily over the front of the device. If instead the front of device 20 (arced section 44) were angled towards line attachment end 28, the front would provide a fairly sizeable gap wherein weeds could collect and where a lure retriever could potentially catch. Seventh, the lure holding loop which holds the lure is offset from the main shaft such that when aggressively working a lure, the devices own structure will not repeatedly guide said lure, with force, directly into a point of contact. Eighth, in low light conditions, it is easier to wind a lure on by feel vs. attempting to open and close a different style of snap. Smaller sizes are more accommodating for similar reasons: less dexterously challenging. Ninth, the sharp end point (folded end 54) is tucked away. Tenth, prior art cross-locking snaps which employ a dual open close structure that overlap, while stronger than some embodiments of open and closing snaps, suffer from some of the same problems. The prevent snap is structurally appropriate for a built-in leader version of a snap while the cross-locking designs are not. Eleventh, non-opening and closing snaps, which employ a single half curl and single point of contact, will develop a space in that single point of contact over time which then allows a lure to work its way free. Twelfth, overlapping curls in the form of an open-close snap, due to the singular point of contact; provide a way for a lure to work free. The Prevent Snap, lacking the overlapping curls does not double the thickness of the wire; this double thickness of the wire can be problematic when connecting a lure directly to an eyelet (i.e. no split ring). Thirteenth, the Prevent Snap has multiple points of contact and therefore does not allow a lure to easily work its way free. By

contrast, snaps with multiple curls but no points of contact allow a lure to start working its way back out where the lure usually gets stuck, ruining the intended action of the lure. Smaller versions of the Prevent Snap can accommodate eyelets and split rings of moderate size, or larger, while multiple curl snaps are also usually all but destroyed when winding on a lure with a moderate sized eyelet or split ring. Fourteenth, the Prevent Snap has points of contact which are not on the same parallel as the main shaft making it more difficult for a lure to work free while other multiple curling snaps that do have points of contact that are on the same parallel as the main shaft, are not as effective. Fifteenth, the Prevent Snap, having greater space in between the curls, the main shaft and points of contact, also allow greater mobility between the curls which aids in allowing the lure to continue to work as expected.

[0041] While several embodiments of the invention, together with modifications thereof, have been described in detail herein and illustrated in the accompanying drawings, it will be evident that various further modifications are possible without departing from the scope of the invention. The scope of the claims should not be limited by the preferred embodiments set forth in the examples. but should be given the broadest interpretation consistent with the description as a whole.

Claims

1. (canceled)
2. (canceled)
3. (canceled)
4. (canceled)
5. (canceled)
6. (canceled)
7. (canceled)
8. (canceled)
9. (canceled)
10. (canceled)
11. (canceled)
12. (canceled)
13. (canceled)
14. (canceled)
15. (canceled)
16. (canceled)
17. (canceled)
18. (canceled)
19. (canceled)
20. (canceled)
21. (canceled)
22. (canceled)
23. (canceled)
24. (canceled)
25. (canceled)
26. (canceled)

27. A monolithic device for connecting a lure, comprising: a main device axis comprising a solid wire leader and a main shaft, the main shaft extending from the solid wire leader along the main device axis; a line attachment end configured at one end of the solid wire leader; a lure holding end configured at one end of the main shaft; a lure holding loop at the lure holding end; an entry point configured between the solid wire leader and the main shaft; and wherein the solid wire leader comprises a first length and the main shaft comprises a second length; wherein the first length of

the solid wire leader is greater than the second length of the main shaft.

28. The monolithic device of claim **1**, further comprising a line holding element at the line attachment end, wherein the line holding element comprises a closed wire twist.

29. The monolithic device of claim **1**, further comprising a first resistance point.

30. The monolithic device of claim **3**, wherein the first resistance point is created at the entry point configured between the solid wire leader and the main shaft.

31. The monolithic device of claim **3**, further comprising a second resistance point.

32. The monolithic device of claim **5**, wherein the second resistance point is created at the lure holding loop.

33. The monolithic device of claim **1**, wherein the first length of the solid wire leader is at least about twice the second length of the main shaft.

34. A monolithic device for connecting a lure, comprising: a main device axis comprising a solid wire leader and a main shaft, the main shaft extending from the solid wire leader along the main device axis; a lure holding loop; an entry point; an arced section extending from the entry point; and wherein the arced section crosses the main shaft to create a first resistance point.

35. The monolithic device of claim **8**, further comprising a line holding element at the main shaft.

36. The monolithic device of claim **8**, wherein the arced section bends away from the main shaft on both sides of the main shaft.

37. The monolithic device of claim **8**, wherein the solid wire leader comprises a first length and the main shaft comprises a second length; wherein the first length of the solid wire leader is greater than the second length of the main shaft.

38. The monolithic device of claim **11**, wherein the first length of the solid wire leader is about twice the second length of the main shaft.

39. The monolithic device of claim **8**, further comprising a second resistance point.

40. A monolithic device for connecting a lure, comprising: a main device axis comprising a solid wire leader and a main shaft, the main shaft extending from the solid wire leader along the main device axis; a line holding element configured at one end of the solid wire leader; a lure holding loop configured at one end of the main shaft; an entry point; an arced section extending from the entry point; and wherein the side of the arced section with the entry point is longer than the side of the arced section which is on the opposite side of the main shaft.

41. The monolithic device of claim **14**, wherein the arced section crossing the main shaft creates a first resistance point.

42. The monolithic device of claim **14**, wherein the arced section bends away from both sides of the main shaft.

43. The monolithic device of claim **14**, wherein the solid wire leader comprises a first length and the main shaft comprises a second length; wherein the first length of the solid wire leader is greater than the second length of the main shaft

44. The monolithic device of claim **17**, wherein the first length of the solid wire leader is at about twice the second length of the main shaft.

45. The monolithic device of claim **14**, further comprising a second resistance point.
