

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277671

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Rasmusson; Robert Earl et al.

RENDERING A SITUATIONAL-AWARENESS VIEW IN AN AUTONOMOUS-VEHICLE ENVIRONMENT

Abstract

In one embodiment, a method includes receiving autonomous-vehicle sensor data from a sensor array of an autonomous vehicle. The autonomous-vehicle sensor data indicates an object in an external environment of the autonomous vehicle. The method further includes determining a confidence score for a classification of the object. The method further includes determining an object graphic with a level of detail to visually represent the object. The level of detail of the object graphic is based on the confidence score. The method further includes providing for display a visual representation the object graphic.

Inventors: Rasmusson; Robert Earl (San Francisco, CA), Matthiesen; Taggart (Kentfield, CA), Dehner; Craig (San Francisco, CA), Dong; Linda (San Francisco, CA), Yoo; Frank Taehyun (San Carlos, CA), van Schaardenburg; Karina (San Francisco, CA), Tighe; John (San Francisco, CA), Vitelli; Matt (San Francisco, CA), Guo; Jisi (San Francisco, CA), Guerron; Eli (San Francisco, CA)

Applicant: Lyft, Inc. (San Francisco, CA)

Family ID: 62107714

Appl. No.: 19/047267

Filed: February 06, 2025

Related U.S. Application Data

parent US continuation 17244838 20210429 parent-grant-document US 12235120 child US 19047267

parent US continuation 15812636 20171114 parent-grant-document US 11010615 child US 17244838

us-provisional-application US 62422025 20161114

Publication Classification

Int. Cl.: **G01C21/36** (20060101); **B60W60/00** (20200101); **B62D15/02** (20060101); **G05D1/00** (20240101); **G05D1/221** (20240101); **G05D1/224** (20240101); **G05D1/225** (20240101); **G05D1/227** (20240101); **G05D1/246** (20240101); **G05D1/249** (20240101); **G05D1/646** (20240101); **G05D101/10** (20240101); **G06F18/24** (20230101); **G06T7/20** (20170101); **G06V20/56** (20220101)

U.S. Cl.:

CPC **G01C21/3638** (20130101); **B60W60/00253** (20200201); **B60W60/0027** (20200201); **B62D15/0285** (20130101); **G01C21/365** (20130101); **G05D1/221** (20240101); **G05D1/2247** (20240101); **G05D1/225** (20240101); **G05D1/227** (20240101); **G05D1/246** (20240101); **G05D1/249** (20240101); **G05D1/646** (20240101); **G06F18/24** (20230101); **G06T7/20** (20130101); **G06V20/56** (20220101); **B60W2420/403** (20130101); **B60W2420/408** (20240101); **B60W2554/00** (20200201); **B60W2555/20** (20200201); **B60W2556/10** (20200201); **G05D101/10** (20240101); **G06T2207/30252** (20130101); **G06T2207/30256** (20130101); **G06T2207/30261** (20130101)

Background/Summary

PRIORITY [0001] This application is a continuation under 35 U.S.C. § 120 of U.S. patent application Ser. No. 17/244,838, filed 29 Apr. 2021, which is a continuation under 35 U.S.C. § 120 of U.S. patent application Ser. No. 15/812,636, filed 14 Nov. 2017, now U.S. Pat. No. 11,010,615 which claims the benefit, under 35 U.S.C. § 119 (e), of U.S. Provisional Patent Application No. 62/422,025, filed 14 Nov. 2016, which is hereby incorporated by reference in its entirety and for all purposes.

BACKGROUND

[0002] A dynamic transportation matching system may enable users (or requestors) to request rides from autonomous vehicles. A user may request a ride through the dynamic transportation matching system with a ride-service application on a mobile device of the user. The dynamic transportation matching system may, according to one or more privacy settings designated by a user, store user information (such as for example user preferences, pick-up or drop-off locations, payment information, or other suitable information) associated with the user.

[0003] Traditionally, transportation services have been provided by a human operating vehicle, such as taxis and ride sharing services. Improvements to computer technology have led to increasing efforts to automate these services using autonomous vehicles that do not require a human operator. However, riders are accustomed to traveling with a human driver that can see the road and avoid objects in the car's path. In an autonomous vehicle, a rider may not understand that the autonomous vehicle perceives the environment around it, including objects and obstacles in the road. This may cause the rider to become anxious or fearful during a ride in an autonomous vehicle.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 illustrates an example network environment associated with a dynamic transportation

matching system.

[0005] FIG. 2 illustrates an example driving environment of an example autonomous vehicle.

[0006] FIG. 3 illustrates an example user interface (UI) for displaying a real-time situational-awareness view associated with a ride in an autonomous vehicle associated with a dynamic transportation matching system.

[0007] FIG. 4 illustrates an example UI for a beginning of a ride in an autonomous vehicle associated with a dynamic transportation matching system.

[0008] FIG. 5 illustrates another example UI for a beginning of a ride in an autonomous vehicle associated with a dynamic transportation matching system.

[0009] FIG. 6 illustrates an example UI on an example autonomous-vehicle UI device.

[0010] FIG. 7 illustrates another example UI on an example autonomous-vehicle UI device.

[0011] FIG. 8 illustrates another example UI on an example autonomous-vehicle UI device.

[0012] FIGS. 9A-9D illustrate an example detail-rendering progression as an object moves closer to the autonomous vehicle.

[0013] FIG. 10 illustrates an example UI for an end of a ride in an autonomous vehicle associated with a dynamic transportation matching system.

[0014] FIG. 11 illustrates an example graphical interface for presenting an example warning to a passenger at the end of an autonomous ride.

[0015] FIG. 12 illustrates an example method for providing a situational-awareness view for a ride in an autonomous vehicle associated with a dynamic transportation matching system.

[0016] FIG. 13 illustrates an example method for determining an opacity or transparency for an object graphic.

[0017] FIG. 14 illustrates an example method for determining an overlay graphic based on third-party data.

[0018] FIG. 15 illustrates an example computer system.

DESCRIPTION OF EXAMPLE EMBODIMENTS

[0019] Riding in an autonomous vehicle can be disconcerting for some passengers. For example, a lack of understanding of what the autonomous vehicle perceives around it may cause a user to become anxious or scared. Moreover, the lack of control and general unawareness of how the autonomous vehicle is operating may inhibit users from using a dynamic transportation matching system that provides rides using autonomous vehicles. To reduce this fear or uneasiness and promote adoption rates, the dynamic transportation matching system may provide a situational-awareness view during a ride that is displayed on a computing device inside the autonomous vehicle. The situational-awareness view may be a display of the objects and roads that the autonomous vehicle perceives. The user may look at the situational-awareness view and feel comfortable that the autonomous vehicle is aware of all the objects in the external environment up to a threshold distance. This way, the user may not be as anxious about collisions or other accidents.

[0020] The situational-awareness view may be displayed on a computing device (e.g., tablet) in or integrated into the autonomous vehicle. Such a device may be referred to as an autonomous-vehicle UI device, where appropriate. In addition or as alternative, the situational-awareness view may be displayed on a mobile computing device of the user (e.g., a smartphone). The situational-awareness view may be generated based on autonomous-vehicle sensor data generated by sensors of the autonomous vehicle. In particular embodiments, the situational-awareness view may be generated based on map data and other third-party data (e.g., weather data, customer review data). The situational-awareness view may display a graphical representation of at least some of the external environment surrounding the autonomous vehicle. In particular embodiments, the situational-awareness view may include (1) one or more road graphics representing roads that the autonomous vehicle drives on, (2) one or more object graphics that represent objects (e.g., cars, people, buildings, traffic signs) in the external environment and within range of the sensors of the

autonomous vehicle, and (3) one or more overlay graphics that provide additional information associated with the autonomous vehicle, the user, the ride the user is currently taking, or any other suitable information. Examples of overlay graphics include a trip progress bar that informs a user how far into the current ride they are, a route indicator, a speedometer, an autonomous drive indicator, or any other suitable graphic. Further, the situational-awareness view provides an intuitive and interactive interface for users to understand the environment surrounding the autonomous vehicle, the world as the autonomous-vehicle understands it, and to interface and interact with the autonomous vehicle to ensure a successful ride.

[0021] U.S. patent application Ser. No. 15/812,645, entitled “Identifying Objects for Display in a Situational-Awareness View of an Autonomous-Vehicle Environment” and filed 14 Nov. 2017 and U.S. patent application Ser. No. 15/812,749, entitled “Evaluating and Presenting Pick-Up and Drop-Off Locations in a situational Awareness View of an Autonomous Vehicle” and filed 14 Nov. 2017, are both related to subject matter similar to the subject matter disclosed herein. Both applications are hereby incorporated by reference in their entirety and for all purposes.

[0022] FIG. 1 illustrates an example network environment **100** associated with a dynamic transportation matching system. Network environment **100** includes a user **101**, a user device **130** of a user, a dynamic transportation matching system **160**, an autonomous vehicle **140**, and one or more third-party system **170** connected to each other by a network **110**. Although FIG. 1 illustrates a particular arrangement of user **101**, user device **130**, dynamic transportation matching system **160**, autonomous vehicle **140**, third-party system **170**, and network **110**, this disclosure contemplates any suitable arrangement of user **101**, user device **130**, dynamic transportation matching system **160**, autonomous vehicle **140**, third-party system **170**, and network **110**. As an example and not by way of limitation, two or more of user device **130**, dynamic transportation matching system **160**, autonomous vehicle **140**, and third-party system **170** may be connected to each other directly, bypassing network **110**. As another example, two or more of user device **130**, dynamic transportation matching system **160**, autonomous vehicle **140**, and third-party system **170** may be physically or logically co-located with each other in whole or in part. Moreover, although FIG. 1 illustrates a particular number of users **101**, user devices **130**, dynamic transportation matching systems **160**, autonomous vehicles **140**, third-party systems **170**, and networks **110**, this disclosure contemplates any suitable number of users **101**, user devices **130**, dynamic transportation matching systems **160**, autonomous vehicles **140**, third-party systems **170**, and networks **110**. As an example and not by way of limitation, network environment **100** may include multiple users **101**, user devices **130**, dynamic transportation matching systems **160**, autonomous-vehicles **140**, third-party systems **170**, and networks **110**.

[0023] In particular embodiments, dynamic transportation matching system **160** may include one or more servers. Each server may be a unitary server or a distributed server spanning multiple computers or multiple datacenters. The servers may be of various types, such as, for example and without limitation, web server, news server, mail server, message server, advertising server, file server, application server, exchange server, database server, proxy server, another server suitable for performing functions or processes described herein, or any combination thereof. In particular embodiments, each server may include hardware, software, or embedded logic components or a combination of two or more such components for carrying out the appropriate functionalities implemented or supported by the server. In particular embodiments, dynamic transportation matching system **160** may include one or more data stores. The data stores may be used to store various types of information, such as ride information, rider information, or any other suitable type of information. In particular embodiments, the information stored in the data stores may be organized according to specific data structures. In particular embodiments, each data store may be a relational, columnar, correlation, or other suitable database. Although this disclosure describes or illustrates particular types of databases, this disclosure contemplates any suitable types of databases. Particular embodiments may provide interfaces that enable a user device **130**, a dynamic

transportation matching system **160**, autonomous-vehicle system **140**, or a third-party system **170** to manage, retrieve, modify, add, or delete, the information stored in data store **164**.

[0024] In particular embodiments, user device **130** may be a mobile computing device such as a smartphone, tablet computer, or laptop computer. User device **130** may include functionality for determining its location, direction, or orientation, such as a GPS receiver, compass, gyroscope, or accelerometer. Such a device may also include functionality for wireless communication, such as BLUETOOTH communication, near-field communication (NFC), or infrared (IR) communication or communication with a wireless local area networks (WLANs) or cellular-telephone network. Such a device may also include one or more cameras, scanners, touchscreens, microphones, or speakers. Mobile computing devices may also execute software applications, such as games, web browsers, or ride-service applications. With ride-service applications, users may connect to a dynamic transportation matching system to request rides to travel from one location to another.

[0025] In particular embodiments, autonomous vehicle **140** may be equipped with an array of sensors **144**, a navigation system **146**, and an autonomous-vehicle UI device **148**. Autonomous vehicle **140** may be in the full control of dynamic transportation matching system **160**, or it may be owned by a third party (e.g. a person or other entity). If owned by a third party, the third party may lend the autonomous vehicle for limited amounts of time to dynamic transportation matching system **160** for the purpose of providing rides to users. While the autonomous vehicle is being operated by dynamic transportation matching system **160**, the autonomous vehicle may share data (e.g. sensor data, navigation data) with dynamic transportation matching system **160**. Autonomous-vehicle sensor data may be captured by any suitable sensor arrangement, such as a Light Detection and Ranging (LiDAR) sensor array of multiple LiDAR transceivers that are configured to rotate 360° around the autonomous vehicle. In particular embodiments, LiDAR transmitting signals may be steered by use of a gated light valve, which may be a MEMs device that directs a light beam using the principle of light diffraction. Such a device may not use a gimbaled mirror to steer light beams in 360° around the autonomous vehicle. Rather, the gated light valve may direct the light beam into one of several optical fibers, which may be arranged such that the light beam may be directed to many discrete positions around the autonomous vehicle. Thus, data may be captured in 360° around the autonomous vehicle, but no rotating parts may be necessary.

[0026] In particular embodiments, the autonomous-vehicle sensor data may represent a three-dimensional schema of the external environment of the autonomous vehicle. As an example and not by way of limitation, the three-dimensional schema may represent the external environment including objects such as other cars and pedestrians up to a maximum range of the sensor arrangement (e.g., 100 meters). In particular embodiments, at least some of the autonomous-vehicle sensor data may be labeled (e.g., as labeled point sets) to include references to objects that are within a threshold distance from the autonomous vehicle. Although sensors **144** appear in a particular location on autonomous vehicle **140** in FIG. 1, sensors **144** may be located in any suitable location in or on autonomous vehicle **140**. Example locations for sensors include the front and rear bumpers, the doors, the front windshield, on the side paneling, or any other suitable location. In particular embodiments, navigation system **146** may be any suitable autonomous navigation system, such as a navigation system based at least in part on a Global Positioning System (GPS) module, inertial measurement unit (IMU), LiDAR sensors, optical cameras, radio frequency (RF) transceivers, or any other suitable data gathering mechanism. Navigation system **146** may use map data and autonomous-vehicle sensor data to guide the autonomous vehicle to its destinations without colliding into other objects. Although navigation system **146** appears in a particular location on autonomous vehicle **140** in FIG. 1, navigation system **146** may be located in any suitable location in or on autonomous vehicle **140**. Example locations for navigation system **146** include inside the cabin of autonomous vehicle **140**, near the engine/battery, near the front seats, rear seats, or in any other suitable location. Although this disclosure describes a particular autonomous vehicle having a particular set of features (e.g. sensors, navigation system, dynamic

transportation matching system computing device), this disclosure contemplates any suitable autonomous vehicle having any suitable set of features.

[0027] In particular embodiments, autonomous-vehicle UI device **148** may be a tablet or other suitable device installed by dynamic transportation matching system **160** to allow the user to interact with the autonomous vehicle **140**, dynamic transportation matching system **160**, other users **101**, or a third-party **170**. In particular embodiments, installation of autonomous-vehicle UI device **148** may be accomplished by placing the device **148** inside autonomous vehicle **140**. Although a single autonomous-vehicle UI device **148** is illustrated in a particular location in autonomous vehicle **140** of FIG. **1**, autonomous vehicle **140** may include several autonomous-vehicle UI devices **148** in several different locations within the vehicle. As an example and not by way of limitation, autonomous vehicle **140** may include four autonomous-vehicle UI devices **148** located in the following places: one in front of the front-left passenger seat (e.g. driver's seat in traditional U.S. automobiles), one in front of the front-right passenger seat, one in front of each of the rear-left and rear-right passenger seats. In particular embodiments, autonomous-vehicle UI device **148** may be detachable from any component of autonomous vehicle **140**. This may allow users to handle autonomous-vehicle UI device **148** in a manner consistent with other tablet computing devices. As an example and not by way of limitation, a user may move autonomous-vehicle UI device **148** to any location in the cabin of autonomous vehicle **140**, may hold device **148** in their lap, or handle device **148** in any other suitable manner.

[0028] In particular embodiments, autonomous-vehicle UI device **148** may be a computing device that has an application installed on it that communicates with dynamic transportation matching system **160**. In particular embodiments, user device **130** may have the application installed on it that communicates with dynamic transportation matching system **160**. In particular embodiments, autonomous-vehicle UI device **148** may include a display screen that is configured to display a situational-awareness view of a current environment of autonomous vehicle **140**. In particular embodiments, the situational-awareness view may be presented by a projector that projects the situational-awareness view onto one or more surfaces in the autonomous vehicle **140**. Surfaces may include a front windshield or side windows. The projection may operate similarly to a heads-up display, where the images are perceived as holograms. A situational-awareness view may be a representation of an environment of the autonomous vehicle that is updated in real time. In a situational-awareness view, graphical representations of objects that exist in the external environment of the autonomous vehicle may be displayed on the display screen of autonomous-vehicle UI device **148**. As an example and not by way of limitation, autonomous vehicle **140** may be driving along a city street. Autonomous vehicle **140** may approach a traffic signal that changes from green, to yellow, to red. After the light changes to red, several pedestrians may cross the street in front of autonomous vehicle **140**. Autonomous-vehicle UI device **148** may display a situational-awareness view that includes graphical representations of the traffic signal, the pedestrians, and any other objects (e.g. cars, street signs) within a threshold proximity of sensors **144** (e.g. 100 meters). The graphical representations of various data derived from various sources may be referred to herein as road graphics, object graphics, and overlay graphics.

[0029] Object graphics may be graphical representations of objects within a threshold distance of the autonomous vehicle **140**. Road graphics may be graphical representations of the roads on which autonomous vehicle **140** navigates. Overlay graphics may be graphical or textual representations of information related to the user, a current ride, or autonomous vehicle **140** (e.g., a route indicator, destination address). These graphics may help a passenger understand the autonomous-vehicle sensor data being gathered by sensors **144**. This may allow the passenger to see the vehicle-sensor data in a way that is understandable, intuitive, or user-friendly. To render the situational-awareness view, one or more computing devices associated with autonomous vehicle **140** may use autonomous-vehicle sensor data. If the user wishes to use their own user device **130** within the autonomous vehicle, the user device may display the situational-awareness view as it is received

from another computing device associated with the autonomous vehicle **140** via a wired or wireless connection.

[0030] In particular embodiments, the computing device may incorporate other data in addition to the autonomous-vehicle sensor data to render the situational-awareness view. The other data may include map data, historical data, data accessed from third-parties, or any other suitable type of data. Historical data may include previous identifications and classifications of objects along a particular route. When providing rides to users **101**, dynamic transportation matching system **160** may store the identified and classified objects along a route. As an example and not by way of limitation, the computing device may access information related to rides traveling from San Francisco International Airport (SFO) to Palo Alto, California. This information may include the objects that have been identified and classified in previous rides by autonomous vehicles from SFO to Palo Alto. The computing device may load at least some of the object graphics that correspond to previously identified and classified objects along the route from SFO to Palo Alto. As the autonomous vehicle **140** navigates along the route, the computing device may provide instructions to display the object graphics in the situational-awareness view. As an example and not by limitation, the route from SFO to Palo Alto may proceed along Highway **101**. The computing device may access the GPS coordinates of the billboards along Highway **101**. As the autonomous vehicle **140** passes GPS locations corresponding to the billboards, the computing device may send instructions to display object graphics representing the billboards. The same process may be performed for buildings. This may save significant computing resources because the computing device may not need to process and analyze as much received autonomous-vehicle sensor data in real time. Computing resources can be devoted to identifying and classifying moving objects on the road rather than stationary objects like billboards and buildings

[0031] In particular embodiments, the other data may include data from third-party systems **170**. Data obtained from third-party systems **170** may be displayed as an overlay graphic in the situational-awareness view. As an example and not by way of limitation, the computing devices may incorporate weather data from a third-party weather online resource to render the current weather in the situational-awareness view (e.g. if it is raining outside, autonomous-vehicle UI device **148** may display the representation of the environment as also raining). In this case, the rendering of the rain may be thought of as an overlay graphic. Overlay graphics are discussed in further detail herein. As another example and not by way of limitation, the computing devices may incorporate information related to nearby businesses and attractions from third-party applications such as YELP, GOOGLE MAPS, or other map-based databases. Continuing with this example, during a ride, autonomous vehicle **140** may drive on Webster Street in San Francisco, California. The situational-awareness view may display buildings as object graphics. These object graphics may correspond to actual buildings in the external environment of autonomous vehicle **140**. One of the object graphics displayed in the situational-awareness view may be a building that represents the restaurant ABC Ramen. The situational-awareness view may include the name of the restaurant as an overlay graphic that overlays the object graphic representing the building where ABC Ramen is located. In particular embodiments, additional information related to the restaurant may be displayed. Alternatively, the additional information may be displayed if the user interacts with the object graphic (e.g., by tapping on it or by using voice commands). The additional information may include hours of operation, current wait time, customer reviews, a menu, a web resource (e.g., a link to the restaurant's website or to a third-party reservations application such as OPEN TABLE), customer reviews, a phone number, or any other suitable information. Example overlay graphics are illustrated in FIG. 7, as elements **710**. Processing of autonomous-vehicle sensor data may comprise any suitable processing, including recognizing objects from autonomous-vehicle sensor data, rendering graphics using autonomous-vehicle sensor data for display on a display screen of autonomous-vehicle UI device **148**, recognizing potential safety risks, or any other suitable analysis.

[0032] In particular embodiments, autonomous-vehicle UI device **148** may have an interactive touchscreen display and one or more other input/output (I/O) interfaces (e.g. a microphone). The display of autonomous-vehicle UI device **148** may be operable to receive rider input via a touchscreen in the form of taps on the touchscreen or via a microphone in the form of voice commands. Users of the ride service may interface with autonomous-vehicle **140** by interfacing with autonomous-vehicle UI device **148** to obtain information (e.g. ETA, ride length, current location, nearby attractions), input commands to the autonomous vehicle (e.g. set a new destination, end the current ride, pick up another passenger, view information related to nearby attractions, view payment information), or perform any other suitable interaction. In particular embodiments, instead of using ride-service computing system **148** to view and interact with autonomous vehicle **140** or dynamic transportation matching system **160**, the user may use their own user device **130**. In particular embodiments, the situational-awareness view may be displayed on user device **130** as it is received from a computing device associated with autonomous vehicle **140** via a wired or wireless transmission such as Bluetooth or Wi-Fi.

[0033] Dynamic transportation matching system **160** may be accessed by the other components of network environment **100** either directly or via network **110**. In particular embodiments, dynamic transportation matching system **160** may include an authorization server (or other suitable component(s)) that allows users **101** to opt in to or opt out of having their actions logged by dynamic transportation matching system **160** or shared with other systems (e.g. third-party systems **170**), for example, by setting appropriate privacy settings. A privacy setting of a user may determine what information associated with the user may be logged, how information associated with the user may be logged, when information associated with the user may be logged, who may log information associated with the user, whom information associated with the user may be shared with, and for what purposes information associated with the user may be logged or shared.

Authorization servers may be used to enforce one or more privacy settings of the users of dynamic transportation matching system **160** through blocking, data hashing, anonymization, or other suitable techniques as appropriate. In particular embodiments, third-party system **170** may be a network-addressable computing system that can host GPS maps, customer reviews, weather information, or any other suitable type of information. Third-party system **170** may generate, store, receive, and send relevant data, such as, for example, map data, customer review data from a customer review website (e.g. YELP), weather data, or any other suitable type of data. Third-party system **170** may be accessed by the other components of network environment **100** either directly or via network **110**. In particular embodiments, one or more users **101** may use one or more user devices **130** to access, send data to, and receive data from dynamic transportation matching system **160** or third-party system **170**. User device **130** may access dynamic transportation matching system **160** or third-party system **170** directly, via network **110**, or via a third-party system. As an example and not by way of limitation, user device **130** may access third-party system **170** via dynamic transportation matching system **160**. User device **130** may be any suitable computing device, such as, for example, a personal computer, a laptop computer, a cellular telephone, a smartphone, a tablet computer, or an augmented/virtual reality device.

[0034] This disclosure contemplates any suitable network **110**. As an example and not by way of limitation, one or more portions of network **110** may include an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a cellular telephone network, or a combination of two or more of these. Network **110** may include one or more networks **110**.

[0035] Links **150** may connect user device **130**, dynamic transportation matching system **160**, and third-party system **170** to communication network **110** or to each other. This disclosure contemplates any suitable links **150**. In particular embodiments, one or more links **150** include one

or more wireline (such as for example Digital Subscriber Line (DSL) or Data Over Cable Service Interface Specification (DOCSIS)), wireless (such as for example Wi-Fi or Worldwide Interoperability for Microwave Access (WiMAX)), or optical (such as for example Synchronous Optical Network (SONET) or Synchronous Digital Hierarchy (SDH)) links. In particular embodiments, one or more links **150** each include an ad hoc network, an intranet, an extranet, a VPN, a LAN, a WLAN, a WAN, a WWAN, a MAN, a portion of the Internet, a portion of the PSTN, a cellular technology-based network, a satellite communications technology-based network, another link **150**, or a combination of two or more such links **150**. Links **150** need not necessarily be the same throughout network environment **100**. One or more first links **150** may differ in one or more respects from one or more second links **150**.

[0036] FIG. **2** illustrates an example driving environment of an example autonomous vehicle **140**. In particular embodiments, a computing device associated with autonomous vehicle **140** or dynamic transportation matching system **160** may receive autonomous-vehicle sensor data that represents an external environment within a threshold distance of autonomous vehicle **140**. In particular embodiments, the computing device may be autonomous-vehicle UI device **148**, may be navigation system **146**, or may be another suitable computing device or combination of computing devices associated with autonomous vehicle **140**. The autonomous-vehicle sensor data may be collected via sensors arranged on the outside or the inside of autonomous vehicle **140**. The autonomous-vehicle sensor data may enable autonomous vehicle **140** to identify objects in the surrounding external environment, such as vehicles **210**. The autonomous-vehicle sensor data may further enable autonomous vehicle **140** to identify the road upon which it is driving, lanes in the road, or any other suitable object.

[0037] As an example and not by way of limitation, the sensors on autonomous vehicle **140** may be LiDAR sensors. LiDAR systems may measure how far away a physical surface in a 3D space is from the emitting device, as well as the direction to that surface, which allows for the creation of a full 3D model of the world around the sensor. The basic method of operation of a LiDAR system may be to transmit a beam of light, and then measure the returning signal when the light reflects off of an object. The time that the reflected signal takes to come back to the LiDAR module may provide a direct measurement of the distance to the object. Additional information about the object, like its velocity or material composition, may also be determined by measuring certain properties of the reflected signal, such as for example the induced Doppler shift. Finally, by steering or directing this transmitted light, many different points of an environment may be measured to create a full 3D model. The LiDAR sensors may transmit laser beams **230A** and **230B** in multiple directions around autonomous vehicle **140** within a distance **240**, which may be the range of the sensors. As an example and not by way of limitation, the LiDAR sensors may transmit laser beams in any direction in a reference coordinate system having an x-direction **220A** and a y-direction **220B**. In particular embodiments, the reference coordinate system may also have a z-direction (not shown). Differences in laser return times and wavelengths may then be used to obtain coordinate information associated with the external environment of autonomous vehicle **140**. In particular embodiments, the coordinate information may comprise distance information. The coordinate information may include a list of coordinate points (e.g. x, y, z coordinates) that represent locations where a LiDAR laser hit the surface of an object. In particular embodiments, based on the coordinate information, a three-dimensional representation may be generated for use by autonomous vehicle **140**. In particular embodiments, the coordinate points may also comprise a time component *t* which may represent the time that a LiDAR beam was transmitted from the transceivers, hit an object, or was received by the transceivers. Autonomous vehicle **140** may use the time component of the coordinate points to determine a real-time three-dimensional representation of its external environment. In particular embodiments, autonomous vehicle **140** may combine the autonomous-vehicle sensor data with other types of data to detect roadways, buildings, traffic signs, and other objects. The other types of data may include data acquired from

third parties. Examples of other types of data acquired from third parties include map data, traffic data, weather data, ratings data (e.g. from YELP or another third-party ratings entity) or any other suitable type of data.

[0038] In particular embodiments, the computing device associated with autonomous vehicle **140** may access map data. The map data may be associated with the external environment of autonomous vehicle **140**. Map data may provide information about street names and street locations. The map data may be generated by a third-party (e.g. GOOGLE, DEEPMAP) and may be accessed by the computing device via an application program interface (API). Alternatively, the map data may be generated by dynamic transportation matching system **160**. The map data may be stored by the computing device prior to a given ride. This may enable faster processing by the computing device because there may not be a need to access a third-party system **170** during a given ride. Autonomous vehicle **140** (e.g. via navigation system **146**) may use the map data to determine one or more routes to navigate from an origin to a destination. In particular embodiments, the map data may comprise traffic data. The traffic data may indicate which routes have more or less traffic. Generally, more traffic may result in slower routes, so it may be desirable for autonomous vehicle **140** to take routes that have less traffic. In particular embodiments, the map data may be highly precise, offering data that is accurate to within 5-10 centimeters. This may mean that the map data may provide highly accurate road dimensions, so that if the autonomous-vehicle sensor data does not provide information for the location of the side of a road (e.g., where the curb or roadside is located), this information may be retrieved from the map data. The computing device may combine this data with GPS data of autonomous vehicle **140** to determine a location of the autonomous vehicle **140** with respect to the side of the road. The computing device may thus render a more accurately located road graphic that represents a curb or roadside.

[0039] In particular embodiments, the computing device associated with autonomous vehicle **140** (e.g., autonomous-vehicle UI device **148** or another suitable computing device) may determine a first view (e.g., situational-awareness view) based on the autonomous-vehicle sensor data. In particular embodiments, determining the situational awareness view may involve receiving a list of coordinate points as the autonomous-vehicle sensor data. These coordinate points may correspond to locations where a LiDAR laser hit the surface of an object in the external environment. Each point may have an x, y, and z component. The computing device may process the list of coordinate points and generate the situational-awareness view accordingly. As it is processing the list of coordinate points, the computing device may identify objects, classify each identified object, and assign each identified object a confidence score that represents the likelihood that the identified object has been correctly classified. As an example and not by way of limitation, the computing device may process the list of points and identify an object that is 50 meters away. Based on the locations of the coordinate points, the computing device may classify the object as a car.

[0040] In particular embodiments, the computing device may assign a confidence score to the classification. Continuing with the above example, the computing device may assign the classification of the car a confidence score of 0.65, based on the likelihood that the object is actually a car and not some other object such as a dumpster. The confidence score may be determined and assigned based on a variety of factors including the distance from autonomous vehicle **140** to the identified object, the noise in the data, how similar the identified object looks to a different class of object (e.g., a particular model of car may resemble a trash receptacle from far away). Noisy data may come from bad weather, a dirty sensor, etc., how much the identified object is moving in a non-linear path, or any other suitable source. In particular embodiments, the confidence score may be determined by comparing received sensor data to a pre-determined pattern that corresponds to the classification, and then determining the difference between the pre-determined pattern and the received sensor data. The received sensor data may include a subset of data points that correspond to an object. The subset of data points may be a labeled point set that was generated by another entity (e.g., sensor array **144**), or may be a particular subset of data points

in the received autonomous-vehicle sensor data. The subset of data points may be coordinate points with x, y, and z components. The subset may match a stored pattern for a particular object. Based on how closely the subset in the received data matches the stored pattern, the computing device may classify the object and assign it a confidence score using the methods described herein. As an example and not by way of limitation, the computing device may receive data that includes a subset of data points corresponding to an object. The subset may match a stored pattern for a cyclist. The computing device may normalize the two sets of data (e.g., the subset and the stored pattern) so that a difference may be calculated. For example, the bottom leftmost point on each of the subset and the stored pattern may be assigned the coordinate point (0, 0, 0). The computing device may then determine a difference between the stored pattern and the subset of data points using any suitable method, such as, for example determining the Euclidean distance between corresponding points in each set of data and averaging over all the points of data. Based on this difference, the computing device may assign the classification a confidence score. For example, if the classification is a cyclist and the average Euclidean distance is relatively small as compared with the distances between other classifications (e.g., car, pedestrian, dog), the computing device may assign the cyclist classification a relatively high confidence score.

[0041] In particular embodiments, the confidence score may be determined by a machine-learning model. The machine-learning model may predict the likelihood that the classification is correct. It may take as input the classification of the identified object along with the autonomous-vehicle sensor data, map data, third-party data (e.g., weather data), historical data, or any other suitable data. The machine-learning model may output the likelihood that the classification is correct expressed as a confidence score for the given input classification. The machine-learning model may be trained with training data. The training data may include a set of training examples. Each training example may include an input object and a desired output value. The input object may be a vector whose vector-elements correspond to the classification, various aspects of the autonomous-vehicle sensor data, historical data, and third-party data. The desired output value may be a “1” or a “0,” depending on whether the classification is correct or not. Once the machine-learning model is trained, it may begin predicting the likelihood that a particular classification is correct given one or more other input data sets (e.g., autonomous-vehicle sensor data, map data, third-party data).

[0042] In particular embodiments, the computing device may receive additional data from sensor array **144** as autonomous vehicle **140** moves closer to the identified object. The computing device may process the additional data and adjust the confidence score based on the additional data. In particular embodiments, as the confidence score for a particular identified object increases, the corresponding object graphic may be rendered in greater detail. In particular embodiments, as the confidence score increases, the corresponding object graphic may be rendered with more opacity. As an example and not by way of limitation, if the confidence score is 0.50 that an identified object is a car, the corresponding object graphic may be rendered as 50% transparent. If the confidence score moves up to 75% that the identified object is a car, the corresponding object graphic may be rendered as 25% transparent. In particular embodiments, the level of opacity/transparency may be based on the distance the identified object is from autonomous vehicle **140**. As an example and not by way of limitation, an identified object that is farther away may be rendered as an object graphic that is more transparent than an object graphic corresponding to a closer identified object.

[0043] In particular embodiments, the autonomous-vehicle sensor data may comprise one or more labeled point sets corresponding to objects in the external environment of autonomous vehicle **140**. In this scenario, instead of receiving raw data points with x, y, and z components, the autonomous-vehicle sensor data may already be classified when it is received by the computing device. The data may come in “point sets,” each point set corresponding to an identified object. Each point set may also be received with a confidence score. The rendering of the object graphic based on the classification and confidence score may function similar to the rendering of identified objects based on raw data, as discussed above.

[0044] FIG. 3 illustrates an example user interface (UI) **300** for displaying a real-time situational-awareness view associated with an autonomous ride. UI **300** may include a graphic representation of at least some of the autonomous-vehicle sensor data, map data, and third-party data (e.g., weather data). UI **300** may be displayed on the autonomous-vehicle UI device **148** or may be displayed on user device **130**. UI **300** may display a situational-awareness view that includes one or more road graphics, one or more object graphics, and one or more overlay graphics. These graphics may help a passenger understand the autonomous-vehicle sensor data being gathered by sensors **144**. This may allow the passenger to see the vehicle-sensor data in a way that is understandable, intuitive, or user-friendly. This may assuage the passenger's fears about riding in a car that does not have a human driver. These fears are a problem for many riders because their fears or anxiety deters them from taking rides in autonomous vehicles. One way to alleviate these fears is to provide the situational-awareness view, an example of which is shown in the graphical interface **300**.

[0045] In particular embodiments, the object graphics may represent an object within a threshold distance of the autonomous vehicle as detected at least in part by one or more of the sensors on sensor array **144** of the autonomous vehicle. The threshold distance may be determined based on the range **240** of sensor array **144**, or may be determined by dynamic transportation matching system **160**. As an example and not by way of limitation, the range of sensor array **144** may be 100 meters. However, rendering an object graphic for every detected object within 100 meters of autonomous vehicle **140** may place a high burden on the processing power of the computing device and may also overwhelm the user. Therefore, it may be desirable to render only those object graphics that correspond to objects closer to autonomous vehicle **140** than the range of the sensor array **144**. This distance may be 40 meters, 60 meters, 30 meters, or any other suitable distance. In particular embodiments, sensor array **144** may detect an object (e.g., a car) that is at the range of the sensors (e.g., 100 meters), and generate autonomous-vehicle sensor data for the computing device (e.g., autonomous-vehicle UI device **148** or other suitable computing device). Detecting an object prior to rendering its corresponding object graphic may be done so that the computing device may take advantage of lead time between the point in time when sensor array **144** detects the object and the point in time when the corresponding object graphic is rendered in the situational-awareness view. This lead time may be used to render the object graphic. This may save processing power and enable rendering of more detailed object graphics. Examples of object graphics include graphics associated with stationary objects **320** (e.g. parked cars, traffic signs or signals, mailboxes), graphics associated with moving objects **330**, **310** (e.g. moving cars, bicyclists, pedestrians, runners), a graphic associated with autonomous vehicle **140** (e.g., as shown by element **140** in FIG. 3), or any other suitable graphic associated with objects that may come into the range of sensors **144** of autonomous vehicle **140**. In particular embodiments, some objects may be partially rendered when displayed on the display screen. Partial rendering of an object may include rendering the object as semi-transparent, as discussed herein, or rendering the edges of the object that are closest to the autonomous vehicle in greater detail or opacity than the other edges.

[0046] In particular embodiments, the computing device may determine that an identified object is moving and may provide instructions to render an object graphic that has an indication that the corresponding object is moving. The process for such a determination may function as follows. The computing device may detect that an object is within a threshold distance from autonomous vehicle **140**. The detection may be based on a first received set of autonomous-vehicle sensor data. The received set of data may include a subset of data points that correspond to the nearby object. Based on the subset of data points, the computing device may additionally determine the distance between the object and autonomous vehicle **140**. In particular embodiments, the subset of data points may be a labeled point set that was generated by another entity (e.g., sensor array **144**), or may be a particular subset of data points in received coordinate points with x, y, and z components. The subset may match a stored pattern for a particular object. Based on how closely the subset in the

received data matches the stored pattern, the computing device may classify the object and assign it a confidence score using the methods described herein. As an example and not by way of limitation, the computing device may receive data that includes a subset of data points corresponding to an object. The subset may match a stored pattern for a cyclist. The computing device may classify the object as a cyclist and assign it a confidence score. After a brief time period (e.g., a fraction of a second), the computing device may receive a second set of autonomous-vehicle sensor data. The second data set may contain a subset whose pattern is substantially the same as the subset in the first received data set. Thus, the computing device may determine that the object is the same as that in the first data packet (e.g., a cyclist).

[0047] However, the distance between the cyclist and autonomous vehicle **140** may have changed, even after controlling for the motion of autonomous vehicle **140**. This may be an indication that the identified object is moving. Because the cyclist is moving, an object graphic representing the cyclist (e.g., object graphic **310**) may include a graphical indication that the cyclist is moving. This graphical indication may be any suitable indication, such as bounding box **311**, rendering the object graphic in a different color, rendering a star, diamond, or other graphic over the object graphic, rendering the object graphic in thicker lines than stationary objects, or any other suitable indication. Each of these graphical indications may indicate to the user that the autonomous vehicle is aware of the object and its motion as well as its surrounding space.

[0048] In particular embodiments, user interface **300** may be a situational-awareness view that includes one or more road graphics. A road graphic may represent a road on which autonomous vehicle **140** may drive. Examples of road graphics include graphics associated with any roads and intersections that are within range of the sensor array **144** of autonomous vehicle **140**, street markings **380** (e.g., lane indicators), curbs, or any other suitable graphic associated with the roads on which autonomous vehicle **140** drives. A road graphic may be rendered in the situational awareness view farther away than the object graphics are rendered. This may be because a user may wish to see any given road graphic as far “into” the situational-awareness view as possible. This may result in the road graphic being displayed and then one or more object graphics being rendered and appearing on the road graphic as autonomous vehicle **140** navigates down a road. In particular embodiments, more than one road graphics may be included in the situational-awareness view. As an example and not by way of limitation, autonomous vehicle **140** may approach an intersection, and the situational-awareness view may include both a road object corresponding to the road that autonomous vehicle **140** is driving on as well as a road object corresponding to the road that autonomous vehicle **140** is approaching. As another example and not by way of limitation, the situational-awareness view may provide a top-down view instead of a behind-the-vehicle view that is illustrated in FIG. 3. The top-down view may be enabled when the user selects the map toggle interface element **370**. The top-down view may allow the user to zoom out by pinching an appropriate area or tapping an appropriate icon to view several road graphics corresponding to the road that autonomous vehicle **140** is driving on as well as several nearby roads.

[0049] In particular embodiments, graphical interface **300** may display a situational-awareness view that includes one or more overlay graphics. An overlay graphic may provide particular information associated with one or more aspects of autonomous vehicle **140**, user **101**, the ride user **101** is currently taking, object graphics, road graphics, a current route of autonomous vehicle **140**, or any other suitable information. Examples of overlay graphics include route indicator **350** (which may display the current route for the current ride), destination indicator interface element **360** (which may display information about the destination such as miles remaining until destination is reached, or estimated time of arrival), and map toggle interface element **370** (which may display an alternate situational-awareness view that is a top-down view instead of a behind-the-vehicle view as illustrated by FIG. 3). Other examples of overlay graphics that are not illustrated in FIG. 3 but are nevertheless contemplated by this disclosure include information related to detected objects

corresponding to object graphics (e.g., distance from the detected object to autonomous vehicle **140**, the speed of the detected object), a music playlist of user **101**, information related to detected roads corresponding to road graphics (e.g., an indication of the amount of traffic congestion on that road, an indication of road construction on that road, the speed limit of that road), or any other suitable information.

[0050] As an example and not by way of limitation, the computing device may incorporate information related to nearby businesses and attractions from third-party applications such as YELP, GOOGLE MAPS, or other map-based databases. Continuing with this example, during a ride, autonomous vehicle **140** may drive on Webster Street in San Francisco, California. The situational-awareness view may display buildings as object graphics. These object graphics may correspond to actual buildings in the external environment of autonomous vehicle **140**. One of the object graphics displayed in the situational-awareness view may be a building that represents the restaurant ABC Ramen. The situational-awareness view may include the name of the restaurant as an overlay graphic that overlays the object graphic representing the building where ABC Ramen is located. In other words, the name of the restaurant may cover part of the object graphic representing the building corresponding to ABC Ramen. In particular embodiments, additional information related to the restaurant may be displayed. In particular embodiments, additional information may be displayed if the user interacts with the object graphic (e.g., by tapping on it or by using voice commands). The additional information may include hours of operation, current wait time, customer reviews, a menu, a web resource (e.g., a link to the restaurant's website or to a third-party reservations application such as OPEN TABLE), a phone number, or any other suitable information. Although this disclosure describes rendering overlay graphics in a particular manner, this disclosure contemplates rendering overlay graphics in any suitable manner.

[0051] In particular embodiments, the computing device may determine route indicator **350** based on map data, sensor data, and route-guidance data. The autonomous-vehicle sensor data may only indicate projected points (called waypoints) that are 60 meters to 100 meters ahead of autonomous vehicle **140**. Based on a curve associated with the upcoming waypoints, the computing device may need to infer the route that autonomous vehicle **140** will take and provide instructions to render route indicator **350** that is based on the inferred route. As an example and not by way of limitation, the upcoming waypoints may show that autonomous vehicle **140** may curve to the left. The computing device may need to determine whether this leftward curve is a left-hand turn on a particular road, or if the road autonomous vehicle **140** is currently driving on merely curves to the left. To make this determination, the computing device may determine the angle of the curve, analyze map data and autonomous-vehicle sensor data. If the map data shows the road curving but no other roads intersecting with the road autonomous vehicle **140** is driving on, the computing device may infer that autonomous vehicle **140** may continue to drive on the same road as the road curves to the left. On the other hand, if the waypoints show a 90° curve to the left, the computing device may infer that autonomous vehicle **140** is turning left on a particular street. The computing device may access a list of potential street names from a third-party system and infer the street name that autonomous vehicle **140** may turn on. This determination may additionally be made on the upcoming waypoints and the autonomous-vehicle sensor data in addition to the map data.

[0052] In particular embodiments, at least some of the object graphics, the road graphics, and the overlay graphics may be interactive. As an example and not by way of limitation, if the user taps on the graphical rendering of autonomous vehicle **140**, information related to autonomous vehicle **140** may be displayed, such as the make, model, year, the battery or fuel level, the number of miles driven that day, week, month, or during the lifetime of autonomous vehicle **140**, or any other suitable information. As another example and not by way of limitation, if the user taps on map toggle interface element **370**, a larger-sized map may be displayed on the display screen. The user may then be able to interact with the map in any suitable manner. As another example and not by way of limitation, if the user taps on destination indicator interface element **360**, information about

the destination may be displayed, such as miles remaining until destination is reached, or estimated time of arrival. The user may be able to set a new destination, see information related to the destination, or view any other suitable information.

[0053] In particular embodiments, every element in graphical interface **300** may be interactive. As an example and not by way of limitation, if the user taps on a rendering of a building **340**, data related to that particular building may be displayed, as discussed above. If the building is a restaurant, the computing device may access third-party data related to the restaurant and display the information, as discussed above. As another example and not by way of limitation, if the user taps on a rendering of a pedestrian, the graphical interface may display limited information related to the pedestrian, such as the pedestrian's current distance from autonomous vehicle **140** and current velocity. Although this disclosure describes providing a particular graphical interface in a particular manner, this disclosure contemplates providing any suitable graphical interface in any suitable manner.

[0054] FIG. **4** illustrates an example UI for a beginning of a ride in an autonomous vehicle. UI **400** may be presented to the passenger upon entrance into the autonomous vehicle **140**. UI **400** may be displayed on autonomous-vehicle UI device **148**, user device **130**, or any other suitable display. UI **400** may provide instructions and information **410** regarding the ride, destination, rider, vehicle, or any other suitable information. UI **400** may include interactive element **420** to allow the passenger to begin the ride. UI **400** may also include a reference vehicle **140A** that represents the autonomous vehicle **140** that the passenger is sitting in.

[0055] UI **400** may also include object graphics **430**. The object graphics **430** may represent physical objects that are within a threshold distance of autonomous vehicle **140**. As an example and not by way of limitation, object graphics **430** may represent cars driving along the same road as autonomous vehicle **140**. Object graphics **430** may be displayed in the graphical interface **400** to help the passengers understand that the autonomous vehicle **140** is aware of its surroundings. This may help a user feel more at ease knowing that the autonomous vehicle **140** knows of nearby objects. The object graphics **430** may additionally include near-edge indications **431**. Near-edge indications may be a graphical indication that the autonomous vehicle **140** is aware of the nearest edges of the identified objects. For example, the near-edge indications **431** may be rendered as emboldened lines that represent the near edges of the object. Near-edge indications may be rendered and displayed in any suitable situational-awareness view and not just in the context of FIG. **4**. The object classification, size, and shape may be inferred based on sensor data while the near-edge indications may correlate to the sensor data received from the sensor array **144**.

Rendering objects with near-edge indications may further assuage a user's anxiety over riding in an autonomous vehicle because near-edge indications may help the user understand that the autonomous vehicle is aware of the closest edges of nearby objects.

[0056] FIG. **5** illustrates another example UI for a beginning of a ride in an autonomous vehicle associated with a dynamic transportation matching system. UI **500** shows further instructions and information **510** such as a direction to fasten a seatbelt. Additionally, UI **500** may include feedback to the user regarding where they may find their seatbelt. Object graphics **530** may indicate to the user that autonomous vehicle **140** is aware of nearby objects. Once the user has fastened their seatbelt, they may tap interactive element **520** to begin the ride. Alternatively, the autonomous vehicle **140** may automatically detect a seatbelt fastening and may begin the ride without further input from the user.

[0057] FIG. **6** illustrates an example UI on an example autonomous-vehicle UI device. Once a ride has begun, the user may handle the autonomous-vehicle UI device **148** by holding it and moving it in any direction the user desires. As discussed herein, the autonomous-vehicle UI device **148** may determine its orientation (e.g., North, South, East, West) as well as its tilt. This may allow the autonomous-vehicle UI device **148** to display a situational-awareness view **600** that corresponds to the external environment that is in front of the device **148**. As an example and not by limitation, the

external environment in front of the autonomous-vehicle UI device **148** may include road **630A**, cars **610A**, buildings **620A**, and clouds **640A**, as well as trees (not numbered) or any other suitable object. Corresponding road graphics **630B**, object graphics (e.g., car **610B**, building **620B**, cloud **640B**) may be displayed in a situational-awareness view on a display screen of autonomous-vehicle UI device **148**. Note that in particular embodiments, cloud **640B** may not directly correspond with cloud **640A**. Rather, the computing device may access third party weather data and determine that the weather may be partly cloudy. In response, the computing device may provide instructions to render a partly cloudy sky in the situational-awareness view on autonomous-vehicle UI device **148**. In particular embodiments, although it may be possible to render a high definition representation that closely matches the actual external environment, the situational-awareness view may not include all the details that exist in the actual external environment due to limitations in processing speed, granularity of sensor data, and/or design considerations. For example, the situational-awareness view may not display license plate numbers, leaves on trees, cracks in the sidewalk, some design features of cars or buildings, people's faces, and other such details in order to save processing resources for other tasks, because such details are not captured by the sensor data, and/or because the system is designed to show an abstraction of the environment instead of an exact replication of the environment depending on the specific features.

[0058] FIGS. **7** and **8** illustrate another example UI on an example autonomous-vehicle UI device. In particular embodiments, UI **700** and UI **800** may include an overlay graphic which may be an autonomous-drive indicator **720** and **820**. Autonomous drive indicator **720** and **820** may indicate when autonomous vehicle **140** is operating in an autonomous-drive mode and when autonomous vehicle **140** is being operated by a human driver. In particular embodiments, autonomous vehicle **140** may have a “safety driver,” which is a human who may or may not drive autonomous vehicle **140**. The autonomous-drive indicator **720** and **820** may display certain information based on the state of autonomous vehicle **140**. Autonomous vehicle **140** may have at least three states: (i) the safety driver is operating the vehicle (illustrated in FIG. **8**); (ii) the vehicle is being self-driven (illustrated in FIG. **7**); and (iii) the vehicle is being self-driven above a certain speed (not illustrated). In state (i), the autonomous drive indicator **820** may include the safety driver's face **821** as well as textual information stating, for example, “Sandra is driving” to indicate that the vehicle is being operated by a human. In state (ii), the safety driver's face may be replaced by a different icon **721** that indicates that the vehicle is being self-driven. The icon may be anything that would indicate self-driving, such as a green steering wheel, a green circle, text that says that say “Autonomous Driving Activated,” or any other suitable indication. In state (iii), the autonomous drive indicator may include additional information such as the vehicle's speed and direction. These display icons may inform the user when the vehicle is being operated by a human and when it is being self-driven, so that the user may be aware of how autonomous vehicle **140** is being operated. UI **700** and UI **800** may include additional overlay graphics **710** and **810** that provide information about nearby business and attractions.

[0059] FIGS. **9A-9D** illustrate an example detail-rendering progression as an object moves closer to the autonomous vehicle. In particular embodiments, objects that are farther away from autonomous vehicle **140** may be displayed in less detail than objects that are closer to autonomous vehicle **140**. This may be to save processing resources for rendering objects in greater detail that are closer to the autonomous vehicle. The user is more likely to be interested in objects that are close to the vehicle, and thus the computing device may devote more resources to rendering object graphics in higher detail that correspond to objects that are close to the vehicle. Additionally, there may be insufficient sensor information to capture far away objects with the same level of detail as those objects that are closer to the autonomous vehicle. To illustrate this principle, FIG. **9A** illustrates an example rendering of a detected and classified object that is **100** meters away from autonomous vehicle **140**. FIG. **9B** illustrates an example rendering of a detected and classified object that is **75** meters away from autonomous vehicle **140**. FIG. **9C** illustrates an example

rendering of a detected and classified object that is 50 meters away from autonomous vehicle **140**. FIG. **9D** illustrates an example rendering of a detected and classified object that is 25 meters away from autonomous vehicle **140**. As can be seen by FIGS. **9A-9D**, as the vehicle moves closer to the autonomous vehicle, its corresponding object graphic is displayed in greater detail. Although the distances used here are specific distances, this disclosure contemplates any suitable distance to render the object graphic in greater detail. For example, the distance corresponding to FIG. **9A** may be 100 feet, the distance corresponding to FIG. **9B** may be 75 feet, and so on. Further, the distance intervals between detail levels need not be consistent. This disclosure contemplates any suitable distance for detected objects and any suitable level of detail for object graphics. In particular embodiments, the different levels of detail may be replaced with different levels of opacity. Thus, objects that are far away from autonomous vehicle **140** may be rendered with a lower level of opacity (e.g., a higher level of transparency). As objects move closer to the autonomous vehicle, they may be rendered with a higher level of opacity. In particular embodiments, the level of detail or level of opacity may depend on a confidence score of an object classification for a detected object instead of the distance between the detected object and the autonomous vehicle. This is discussed with reference to FIG. **12** below. Changing the opacity may be a way to let the user know that the autonomous vehicle **140** is aware of the objects and their proximity to the autonomous vehicle.

[0060] In particular embodiments, once the level of detail has been determined, the computing device (e.g., autonomous-vehicle UI device or other suitable computing device or combination thereof) may apply the level of detail by applying a particular surface treatment to the object graphic. The particular surface treatment may be selected by the computing device based on the determined level of detail, as discussed herein. The surface treatment may be any suitable surface treatment, including applying a point mesh to the object graphic. A point mesh may be a technique used to render the object graphic wherein only a particular number of points of the object graphic are rendered. As an example and not by way of limitation, the point mesh for a low level of detail may specify that every one in five points of the object graphic are to be rendered. As the level of detail increases, the number of points of the object graphic to be rendered also increases. Thus, a relatively high level of detail may correspond to an object graphic that has four out of every five points on the object graphic rendered. For the points that are not rendered, the computing device may provide instructions to make the unrendered points at least somewhat translucent.

[0061] In particular embodiments, the situational-awareness view may have 360° display capabilities. This may mean that a passenger (e.g., user **101** or another rider in autonomous vehicle **160**) may handle autonomous-vehicle UI device **148** like a normal tablet and position it in any direction they desire. As the passenger moves autonomous-vehicle UI device **148** in different directions, the situational-awareness view may update to show a representation of the portion of the external environment that is directly in front of autonomous-vehicle UI device **148**. As an example and not by way of limitation, if autonomous vehicle **140** is driving south along Pacific Coast Highway in Huntington Beach, California, the passenger may handle autonomous-vehicle UI device **148** and position it straight ahead. In this case, the situational awareness view may include a road graphic that represents Pacific Coast Highway, and one or more other object graphics that represent cars, pedestrians, or buildings. If the passenger points the autonomous-vehicle UI device **148** to their left, the situational awareness view may include several object graphics that represent buildings (e.g., Jill's Skimboard Shop on First Street, ABC Bagels), pedestrians, cars, or any other suitable objects. If the passenger points the autonomous-vehicle UI device **148** to their right, the situational-awareness view may include object graphics that represent objects that are located to the west of Pacific Coast Highway, such as a pier, a lifeguard house, a restaurant, and the Pacific Ocean.

[0062] The 360° capability may have the effect that the autonomous-vehicle UI device **148** has a camera that is capturing the external environment and rendering the situational-awareness view via

the camera. In reality, sensor array **144** may be capturing the external environment and sending it to the autonomous-vehicle UI device **148** via a wired or wireless connection. The autonomous-vehicle UI device (or, in particular embodiments, the user's personal device) may determine its orientation by accessing real-time data generated by one or more internal sensors along with other data. Orientation may include both the direction the device is pointing (e.g., North, South, East, West) as well as the tilt of the device relative to the horizon (e.g., pointing down toward the ground, or up toward the sky). The direction the device is pointing may be determined by magnetic field sensors. Magnetic field sensors may determine the direction of Magnetic North. The device may combine the magnetic field data with GPS data to determine the direction of True North. The magnetic field sensors may return multi-dimensional arrays of sensor values. For example, the geomagnetic field sensor may provide geomagnetic field strength values for each of the three coordinate axes (e.g., (x, y, z) axes) at regular intervals. The three coordinate axes may remain fixed in relation to the device. Based on the geomagnetic field strength values for each coordinate axis, the device may determine which direction it is pointing. From the user's perspective, the x-axis may point to the right and left of the device, the y-axis may point up and down, and the z-axis may point out of and into the screen of the device. As an example and not by way of limitation, the geomagnetic field strength values may be measured at a given time as (0, 0, 1), which may mean that all of the magnetic force on the device is occurring in the positive Z direction. This may mean that the device is pointed due South with no tilt. As another example, the geomagnetic field strength values may be measured at a given time as (1, 0, 0), which may mean that all of the magnetic force on the device is occurring in the positive Y direction. This may mean that the device is pointed due West with no tilt.

[0063] The degree of tilt on the device may be determined from the magnetic field values alone, from gravity sensors, from the accelerometer, or from a combination of the three. Using magnetic field sensors, if the device is tilted downward slightly, there may be some magnetic force in the y-direction. As an example, if the device is oriented northward and also tilted downward, the geomagnetic field strength values may be measured as (0, 0.2, -0.8). The Z value may be negative because forces going into the screen may have negative Z values. The Y value may be 0.2 because there may be a magnetic force occurring in the positive Y direction, which may be toward the top of the computing device. As another example, if the device is oriented northward and also tilted upward, the geometric field strength values may be measured as (0, -0.2, -0.8). Additionally, the device may use gravity sensors to determine how much gravity force is occurring in each direction. As an example, if the device is pointed straight ahead in any of the X or Z directions, the gravity force may be entirely in the Y direction. Accelerometers may determine the angle at which the device is pointed (e.g., up at the sky, straight ahead, down toward the ground) as well as whether the device is oriented in landscape or portrait.

[0064] Once the orientation of the device is determined, a field of view may be determined that approximates what a user would expect to see on the display screen as they point the device in a given direction. The field of view may encompass parameters for the edges of the situational-awareness view. The field of view may be updated based on the orientation of the device. Based on the determined field of view, a corresponding situational-awareness view may be rendered for display on the display screen. To determine the corresponding situational-awareness view, the computing device may map the field of view parameters to a set of coordinate points associated with the autonomous-vehicle sensor data. The set of coordinate points may represent a particular area of the external environment and include data related to identified objects and identified roads. The computing device may provide instructions to render a situational-awareness view based on the set of coordinate points.

[0065] In particular embodiments, the situational-awareness view may be sent to a user device **130** of the user **101** or another passenger in autonomous vehicle **140**. The functionality may be similar to that of the 360° view in autonomous-vehicle UI device **148**, but may be displayed on a display

screen of user device **130** instead.

[0066] FIG. **10** illustrates an example graphical interface **1000** for presenting graphical representations of objects after an autonomous ride. When a ride ends, the autonomous-vehicle UI device **148** may display graphical user interface **1000**. Graphical user interface **1000** may include information and instructions **1010**, an object graphic **140A** that corresponds to autonomous vehicle **140**, as well as object graphics **1030** that correspond to detected objects in the external environment. The user may use object graphics **1030** for safety reasons. For example, the user may monitor the graphical interface to determine when it is safe to open a door to exit the vehicle.

[0067] In particular embodiments, after user **101** has completed a ride in autonomous vehicle **140** using ride-service system **160**, dynamic transportation matching system **160** may provide a post-ride video of particular situational-awareness and other camera views that were generated during the ride. Dynamic transportation matching system **160** may send the post-ride video to user **101**. User **101** may then share the post-ride video with friends via, e.g., social media. The post-ride video may include video and audio clips in addition to the situational-awareness views.

Alternatively, the user **101** may have a preconfigured setting that authorizes dynamic transportation matching system **160** to post to an online social media page on their behalf. By sharing the video on social media, more people may become aware of dynamic transportation matching system **160** and the availability of autonomous rides using dynamic transportation matching system **160**. This way potential users may familiarize themselves with dynamic transportation matching system **160** and autonomous vehicles before actually using the service.

[0068] FIG. **11** illustrates an example graphical interface for presenting an example warning to a passenger at the end of an autonomous ride. In particular embodiments, the autonomous-vehicle UI device may present one or more alerts on the display screen that displays the situational-awareness view. The computing device may access autonomous-vehicle sensor data that contains an indication that an object is approaching an alert zone associated with autonomous vehicle **140**. The computing device may make this determination by analyzing the autonomous-vehicle sensor data, determining a current path of the object (e.g., cyclist), and extrapolating the current path to estimate a near-term future path of the object. The near-term future path of the object may be a path that the computing device predicts the object to take in the immediate future, such as the next five or ten seconds. If the near-term future path of the object crosses an alert zone of the autonomous vehicle **140**, the computing device may provide instructions to issue an alert. An alert zone may be an area immediately surrounding the autonomous vehicle within a threshold distance. The threshold distance may be the distance that a door swings open plus a buffer distance (e.g., two or three feet). If a cyclist is inside or will soon enter the alert zone, opening a door of the autonomous vehicle may result in a collision with the cyclist. In addition to informational text **1110**, the autonomous-vehicle UI device may provide instructions to present a warning **1120** along with instructions **1130**. As an example and not by way of limitation, the warning **1120** may state: "Warning: Cyclist Approaching." The instructions **1130** may state: "Do not exit the vehicle until the cyclist has passed."

[0069] FIG. **12** illustrates an example method **1200** for providing a situational-awareness view associated with an autonomous ride. The method may begin at step **1210**, where a computing device associated with a dynamic transportation matching system (e.g., autonomous-vehicle UI device **148** or other suitable computing device) may receive autonomous-vehicle sensor data from a sensor array of an autonomous vehicle. The autonomous-vehicle sensor data may indicate an object in an external environment of the autonomous vehicle. At step **1220**, the computing device may determine a confidence score for a classification of the object. At step **1230**, the computing device may determine an object graphic with a level of detail to visually represent the object. The level of detail of the object graphic may be based on the confidence score. At step **1240**, the computing device may provide for display a visual representation of the object graphic.

[0070] FIG. **13** illustrates an example method **1300** for determining the opacity/transparency with

which to render an object graphic. In particular embodiments, as the confidence score for a particular identified object increases, the corresponding object graphic may be rendered in greater detail. In particular embodiments, as the confidence score increases, the corresponding object graphic may be rendered with more opacity. At step **1310**, the computing device may receive autonomous-vehicle sensor data. The data may be raw or may be organized into labeled point sets, as discussed previously. At step **1320**, the computing device may determine whether the data contains an object. If it is determined that the data does not contain an object, the process may return to step **1310**. If it is determined that the data contains an object, the process may proceed to step **1330**, where the computing device may classify the object. At step **1340**, the computing device may determine a confidence score for the classification, as discussed previously.

[0071] In particular embodiments, the data may be received as labeled point sets with confidence scores. The labeled point sets and corresponding confidence scores may be generated by another system such as sensor array **144** and sent to the computing device after they are generated. Sensor array **144** may be manufactured and maintained by a third-party entity **170**. In this scenario, steps **1310** through **1340** may be skipped and the method may begin at step **1350**, where the computing device may determine whether the confidence score for a given classified object falls into one of a plurality of windows. Although four windows are illustrated in FIG. **13** (e.g., $CS < A$, $CS < B$, $CS < C$, $CS \geq C$, where CS is “confidence score” and A, B, and C are particular threshold confidence scores), any number of windows is contemplated by this disclosure. Depending on which window the confidence score falls into, at step **1360**, the computing device may render the object graphic with a different level of transparency. In this example method, the transparency is inversely based on the confidence score. As the confidence score increases, the object graphic is rendered with less transparency. As an example and not by way of limitation, let $A=0.25$, $B=0.50$, and $C=0.75$. Thus, a classified object with a confidence score of 0.24 would be represented by an object graphic with a transparency of $T=1-0.25=0.75$. A classified object with a confidence score of 0.26 may fall into window B, so the transparency of the corresponding object graphic may be $T=1-0.50=0.50$.

[0072] FIG. **14** illustrates an example method **1400** for determining an overlay graphic from third-party data. An overlay graphic may provide particular information associated with one or more aspects of autonomous vehicle **140**, user **101**, the ride user **101** is currently taking, object graphics, road graphics, a current route of autonomous vehicle **140**, or any other suitable information. Examples of overlay graphics include route indicator **350**, destination indicator interface element **360**, and map toggle interface element **370**. Other examples of overlay graphics that are not illustrated in FIG. **3** but nevertheless contemplated by this disclosure include information related to detected objects corresponding to object graphics, a music playlist of user **101**, information related to detected roads corresponding to road graphics, or any other suitable information. As an example and not by way of limitation, the computing devices may incorporate information related to nearby businesses and attractions from third-party applications such as YELP, GOOGLE MAPS, or other map-based databases. At step **1410**, the computing device may determine the orientation of the autonomous-vehicle UI device **148**, or alternatively, the user device **130** if the situational-awareness view is being displayed there. In particular embodiments the computing device may be the autonomous-vehicle UI device **148** or may be another computing device associated with autonomous vehicle **140**. At step **1420**, the computing device may determine whether the autonomous-vehicle UI device **148** is pointed at a building. If yes, the process may proceed to step **1430**. If no, the process may proceed to step **1440**. At step **1430**, the computing device may access third party data to retrieve information that is relevant to the building that the autonomous-vehicle UI device **148** is pointed towards. As an example and not by way of limitation, the computing device may access GOOGLE map data to determine the address, phone number, hours of operation, and any other suitable information. At step **1450**, the computing device may determine if any relevant information is available. If yes, the computing device may proceed to step **1480** and send instructions to render the third-party data as an overlay graphic. As an example and not by way of

limitation, YELP data may be displayed as an overlay graphic over an object graphic representing a particular restaurant. This data may include an average customer rating, hours of operation, an interactive option to book a table at the restaurant, or any other suitable information. If no relevant third-party information is available, the computing device may not render any overlay graphic, and may return to step **1410**. Although this method discusses the steps with respect to an autonomous-vehicle UI device **148**, this disclosure contemplates method **1300** being performed with respect to a user device **130**, as discussed herein.

[0073] Returning to the decision at step **1420**, if the autonomous-vehicle UI device is not pointed at a building, the computing device may determine if the autonomous-vehicle UI device is pointed at another object. If no, the process may return to step **1410**. If yes, the process may determine if the object is moving. As an example and not by way of limitation, the object may be a pedestrian that is crossing the street in front of autonomous vehicle **140**. If the object is moving, the computing device may proceed to step **1470** and send instructions to render a graphical indication that the object is moving. As an example and not by way of limitation, the graphical indication may be a bounding box **311** that surrounds the moving object graphic, or a diamond or star that appears to float above the object graphic. As another example and not by way of limitation, the graphical indication may be a change of color of the moving object graphic (e.g., from yellow to red). In particular embodiments, the color of the object graphic may be based on the velocity of the object the object graphic represents. As an example and not by way of limitation, object graphics corresponding to objects moving slower than 25 mph may be rendered as yellow, object graphics corresponding to objects moving between 26 and 50 mph may be rendered as orange, and object graphics corresponding to objects moving faster than 51 mph may be rendered as red. As another example and not by way of limitation, the color of object graphics may be related to the speed limit on the road upon which the objects are traveling. For example, if the speed limit on a particular road is 35 mph, object graphics corresponding to objects traveling less than 36 miles per hour may be rendered as green, and object graphics corresponding to objects traveling greater than 35 miles per hour may be rendered as red.

[0074] In particular embodiments, if the object is not moving, the computing device may proceed to step **1430** and attempt to access third party data relevant to the identified object. As an example and not by way of limitation, the object may be a mailbox and the third-party information may be mail pickup times. The process may proceed from step **1430** as discussed previously.

[0075] Particular embodiments may repeat one or more steps of the method of FIGS. **12-14**, where appropriate. Although this disclosure describes and illustrates particular steps of the method of FIGS. **12-14** as occurring in a particular order, this disclosure contemplates any suitable steps of the method of FIGS. **12-14** occurring in any suitable order. Moreover, although this disclosure describes and illustrates an example method for determining an overlay graphic from third-party data including the particular steps of the method of FIGS. **12-14**, this disclosure contemplates any suitable method for determining an overlay graphic from third-party data including any suitable steps, which may include all, some, or none of the steps of the method of FIGS. **12-14**, where appropriate. Furthermore, although this disclosure describes and illustrates particular components, devices, or systems carrying out particular steps of the method of FIGS. **12-14**, this disclosure contemplates any suitable combination of any suitable components, devices, or systems carrying out any suitable steps of the method of FIGS. **12-14**.

[0076] FIG. **15** illustrates an example computer system **1500**. In particular embodiments, one or more computer systems **1500** perform one or more steps of one or more methods described or illustrated herein. In particular embodiments, one or more computer systems **1500** provide functionality described or illustrated herein. In particular embodiments, software running on one or more computer systems **1500** performs one or more steps of one or more methods described or illustrated herein or provides functionality described or illustrated herein. Particular embodiments include one or more portions of one or more computer systems **1500**. Herein, reference to a

computer system may encompass a computing device, and vice versa, where appropriate. Moreover, reference to a computer system may encompass one or more computer systems, where appropriate.

[0077] This disclosure contemplates any suitable number of computer systems **1500**. This disclosure contemplates computer system **1500** taking any suitable physical form. As example and not by way of limitation, computer system **1500** may be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) (such as, for example, a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, an interactive kiosk, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, a tablet computer system, an augmented/virtual reality device, or a combination of two or more of these. Where appropriate, computer system **1500** may include one or more computer systems **1500**; be unitary or distributed; span multiple locations; span multiple machines; span multiple data centers; or reside in a cloud, which may include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **1500** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein. As an example and not by way of limitation, one or more computer systems **1500** may perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. One or more computer systems **1500** may perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate.

[0078] In particular embodiments, computer system **1500** includes a processor **1502**, memory **1504**, storage **1506**, an input/output (I/O) interface **1508**, a communication interface **1510**, and a bus **1512**. Although this disclosure describes and illustrates a particular computer system having a particular number of particular components in a particular arrangement, this disclosure contemplates any suitable computer system having any suitable number of any suitable components in any suitable arrangement.

[0079] In particular embodiments, processor **1502** includes hardware for executing instructions, such as those making up a computer program. As an example and not by way of limitation, to execute instructions, processor **1502** may retrieve (or fetch) the instructions from an internal register, an internal cache, memory **1504**, or storage **1506**; decode and execute them; and then write one or more results to an internal register, an internal cache, memory **1504**, or storage **1506**. In particular embodiments, processor **1502** may include one or more internal caches for data, instructions, or addresses. This disclosure contemplates processor **1502** including any suitable number of any suitable internal caches, where appropriate. As an example and not by way of limitation, processor **1502** may include one or more instruction caches, one or more data caches, and one or more translation lookaside buffers (TLBs). Instructions in the instruction caches may be copies of instructions in memory **1504** or storage **1506**, and the instruction caches may speed up retrieval of those instructions by processor **1502**. Data in the data caches may be copies of data in memory **1504** or storage **1506** for instructions executing at processor **1502** to operate on; the results of previous instructions executed at processor **1502** for access by subsequent instructions executing at processor **1502** or for writing to memory **1504** or storage **1506**; or other suitable data. The data caches may speed up read or write operations by processor **1502**. The TLBs may speed up virtual-address translation for processor **1502**. In particular embodiments, processor **1502** may include one or more internal registers for data, instructions, or addresses. This disclosure contemplates processor **1502** including any suitable number of any suitable internal registers, where appropriate. Where appropriate, processor **1502** may include one or more arithmetic logic units (ALUs); be a multi-core processor; or include one or more processors **1502**. Although this disclosure describes and illustrates a particular processor, this disclosure contemplates any suitable processor.

[0080] In particular embodiments, memory **1504** includes main memory for storing instructions for processor **1502** to execute or data for processor **1502** to operate on. As an example and not by way

of limitation, computer system **1500** may load instructions from storage **1506** or another source (such as, for example, another computer system **1500**) to memory **1504**. Processor **1502** may then load the instructions from memory **1504** to an internal register or internal cache. To execute the instructions, processor **1502** may retrieve the instructions from the internal register or internal cache and decode them. During or after execution of the instructions, processor **1502** may write one or more results (which may be intermediate or final results) to the internal register or internal cache. Processor **1502** may then write one or more of those results to memory **1504**. In particular embodiments, processor **1502** executes only instructions in one or more internal registers or internal caches or in memory **1504** (as opposed to storage **1506** or elsewhere) and operates only on data in one or more internal registers or internal caches or in memory **1504** (as opposed to storage **1506** or elsewhere). One or more memory buses (which may each include an address bus and a data bus) may couple processor **1502** to memory **1504**. Bus **1512** may include one or more memory buses, as described in further detail below. In particular embodiments, one or more memory management units (MMUs) reside between processor **1502** and memory **1504** and facilitate accesses to memory **1504** requested by processor **1502**. In particular embodiments, memory **1504** includes random access memory (RAM). This RAM may be volatile memory, where appropriate. Where appropriate, this RAM may be dynamic RAM (DRAM) or static RAM (SRAM). Moreover, where appropriate, this RAM may be single-ported or multi-ported RAM. This disclosure contemplates any suitable RAM. Memory **1504** may include one or more memories **1504**, where appropriate. Although this disclosure describes and illustrates particular memory, this disclosure contemplates any suitable memory.

[0081] In particular embodiments, storage **1506** includes mass storage for data or instructions. As an example and not by way of limitation, storage **1506** may include a hard disk drive (HDD), a floppy disk drive, flash memory, an optical disc, a magneto-optical disc, magnetic tape, or a Universal Serial Bus (USB) drive or a combination of two or more of these. Storage **1506** may include removable or non-removable (or fixed) media, where appropriate. Storage **1506** may be internal or external to computer system **1500**, where appropriate. In particular embodiments, storage **1506** is non-volatile, solid-state memory. In particular embodiments, storage **1506** includes read-only memory (ROM). Where appropriate, this ROM may be mask-programmed ROM, programmable ROM (PROM), erasable PROM (EPROM), electrically erasable PROM (EEPROM), electrically alterable ROM (EAROM), or flash memory or a combination of two or more of these. This disclosure contemplates mass storage **1506** taking any suitable physical form. Storage **1506** may include one or more storage control units facilitating communication between processor **1502** and storage **1506**, where appropriate. Where appropriate, storage **1506** may include one or more storages **1506**. Although this disclosure describes and illustrates particular storage, this disclosure contemplates any suitable storage.

[0082] In particular embodiments, I/O interface **1508** includes hardware, software, or both, providing one or more interfaces for communication between computer system **1500** and one or more I/O devices. Computer system **1500** may include one or more of these I/O devices, where appropriate. One or more of these I/O devices may enable communication between a person and computer system **1500**. As an example and not by way of limitation, an I/O device may include a keyboard, keypad, microphone, monitor, mouse, printer, scanner, speaker, still camera, stylus, tablet, touch screen, trackball, video camera, another suitable I/O device or a combination of two or more of these. An I/O device may include one or more sensors. This disclosure contemplates any suitable I/O devices and any suitable I/O interfaces **1508** for them. Where appropriate, I/O interface **1508** may include one or more device or software drivers enabling processor **1502** to drive one or more of these I/O devices. I/O interface **1508** may include one or more I/O interfaces **1508**, where appropriate. Although this disclosure describes and illustrates a particular I/O interface, this disclosure contemplates any suitable I/O interface.

[0083] In particular embodiments, communication interface **1510** includes hardware, software, or

both providing one or more interfaces for communication (such as, for example, packet-based communication) between computer system **1500** and one or more other computer systems **1500** or one or more networks. As an example and not by way of limitation, communication interface **1510** may include a network interface controller (NIC) or network adapter for communicating with an Ethernet or other wire-based network or a wireless NIC (WNIC) or wireless adapter for communicating with a wireless network, such as a WI-FI network. This disclosure contemplates any suitable network and any suitable communication interface **1510** for it. As an example and not by way of limitation, computer system **1500** may communicate with an ad hoc network, a personal area network (PAN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), or one or more portions of the Internet or a combination of two or more of these. One or more portions of one or more of these networks may be wired or wireless. As an example, computer system **1500** may communicate with a wireless PAN (WPAN) (such as, for example, a Bluetooth WPAN), a WI-FI network, a WI-MAX network, a cellular telephone network (such as, for example, a Global System for Mobile Communications (GSM) network), or other suitable wireless network or a combination of two or more of these. Computer system **1500** may include any suitable communication interface **1510** for any of these networks, where appropriate. Communication interface **1510** may include one or more communication interfaces **1510**, where appropriate. Although this disclosure describes and illustrates a particular communication interface, this disclosure contemplates any suitable communication interface.

[0084] In particular embodiments, bus **1512** includes hardware, software, or both coupling components of computer system **1500** to each other. As an example and not by way of limitation, bus **1512** may include an Accelerated Graphics Port (AGP) or other graphics bus, an Enhanced Industry Standard Architecture (EISA) bus, a front-side bus (FSB), a HYPERTRANSPORT (HT) interconnect, an Industry Standard Architecture (ISA) bus, an INFINIBAND interconnect, a low-pin-count (LPC) bus, a memory bus, a Micro Channel Architecture (MCA) bus, a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCIe) bus, a serial advanced technology attachment (SATA) bus, a Video Electronics Standards Association local (VLB) bus, or another suitable bus or a combination of two or more of these. Bus **1512** may include one or more buses **1512**, where appropriate. Although this disclosure describes and illustrates a particular bus, this disclosure contemplates any suitable bus or interconnect.

[0085] Herein, a computer-readable non-transitory storage medium or media may include one or more semiconductor-based or other integrated circuits (ICs) (such as, for example, field-programmable gate arrays (FPGAs) or application-specific ICs (ASICs)), hard disk drives (HDDs), hybrid hard drives (HHDs), optical discs, optical disc drives (ODDs), magneto-optical discs, magneto-optical drives, floppy diskettes, floppy disk drives (FDDs), magnetic tapes, solid-state drives (SSDs), RAM-drives, SECURE DIGITAL cards or drives, any other suitable computer-readable non-transitory storage media, or any suitable combination of two or more of these, where appropriate. A computer-readable non-transitory storage medium may be volatile, non-volatile, or a combination of volatile and non-volatile, where appropriate.

[0086] Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

[0087] The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements,

feature, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Additionally, although this disclosure describes or illustrates particular embodiments as providing particular advantages, particular embodiments may provide none, some, or all of these advantages.

Claims

1. A method comprising, by one or more computing devices: receiving autonomous-vehicle sensor data from a sensor array of an autonomous vehicle, wherein the autonomous-vehicle sensor data indicates an object in an external environment of the autonomous vehicle; determining a confidence score for a classification of the object; determining an object graphic with a level of detail to visually represent the object, wherein the level of detail of the object graphic is based on the confidence score; and providing for display a visual representation of the object graphic.
