

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278029

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

POIESZ; Thomas et al.

SUBSTRATE HOLDER FOR USE IN A LITHOGRAPHIC APPARATUS

Abstract

A substrate holder, for a lithographic apparatus, having a main body, a plurality of support elements to support a substrate and a seal unit. The seal unit may include a first seal positioned outward of and surrounding the plurality of support elements. A position of a substrate contact region of an upper surface of the first seal may be arranged at a distance from the plurality of support elements sufficient enough such that during the loading/unloading of the substrate, a force applied to the first seal by the substrate is greater than a force applied to the plurality of support elements by the substrate. A profile of the contact region, in a cross section through the seal, may have a shape which is configured such that during the loading/unloading of the substrate, the substrate contacts the seal via at least two different points of the profile.

Inventors: POIESZ; Thomas (Veldhoven, NL), BALTIS; Coen Hubertus Matheus (Eindhoven, NL), SOETHOUDT; Abraham Alexander (Eindhoven, NL), AKBAS; Mehmet Ali (Cheshire, CT), VAN DEN BERG; Dennis (Eindhoven, NL), VANESCH; Wouter (Lummen, BE), TEUNISSEN; Marcel Maria Cornelius Franciscus (Grathem, NL)

Applicant: ASML NETHERLANDS B.V. (Veldhoven, NL); ASML HOLDING N.V. (Veldhoven, NL)

Family ID: 64316578

Assignee: ASML NETHERLANDS B.V. (Veldhoven, NL); ASML HOLDING N.V. (Veldhoven, NL)

Appl. No.: 19/210413

Filed: May 16, 2025

Foreign Application Priority Data

EP	17206912.2	Dec. 13, 2017
EP	18183119.9	Jul. 12, 2018

Related U.S. Application Data

parent US continuation 17870444 20220721 parent-grant-document US 12321104 child US 19210413
parent US continuation 16770464 20200605 parent-grant-document US 11448976 WO
continuation PCT/EP2018/082175 20181122 child US 17870444

Publication Classification

Int. Cl.: G03F7/00 (20060101); H01L21/687 (20060101)

U.S. Cl.:

CPC G03F7/70716 (20130101); H01L21/68735 (20130101); H01L21/6875 (20130101);
H01L21/68757 (20130101);

Background/Summary

[0001] This application is a continuation of pending U.S. patent application Ser. No. 17/870,444, which was filed on Jul. 21, 2022, now allowed, which is a continuation of U.S. patent application Ser. No. 16/770,464, which was filed on Jun. 5, 2020, now U.S. Pat. No. 11,448,976, which is the U.S. national phase entry of PCT/EP2018/082175, which was filed on Nov. 22, 2018, which claims the benefit of priority of European Patent Application No. 18183119.9, which was filed on Jul. 12, 2018, and of European Patent Application No. 17206912.2, which was filed on Dec. 13, 2017, each of which is incorporated herein in its entirety by reference.

FIELD

[0002] The present description relates to a substrate holder for use in a lithographic apparatus.

BACKGROUND

[0003] A lithographic apparatus is a machine constructed to apply a desired pattern onto a substrate. A lithographic apparatus can be used, for example, in the manufacture of integrated circuits (ICs). A lithographic apparatus may, for example, project a pattern (also often referred to as “design layout” or “design”) of a patterning device (e.g., a mask) onto a layer of radiation-sensitive material (resist) provided on a substrate (e.g., a wafer).

[0004] As semiconductor manufacturing processes continue to advance, the dimensions of circuit elements have continually been reduced while the amount of functional elements, such as transistors, per device has been steadily increasing over decades, following a trend commonly referred to as ‘Moore's law’. To keep up with Moore's law the semiconductor industry is chasing technologies that enable to create increasingly smaller features. To project a pattern on a substrate a lithographic apparatus may use electromagnetic radiation. The wavelength of this radiation determines the minimum size of features which are patterned on the substrate. Typical wavelengths currently in use are 365 nm (i-line), 248 nm, 193 nm and 13.5 nm. A lithographic apparatus, which uses extreme ultraviolet (EUV) radiation, having a wavelength within a range of 4 nm to 20 nm, for

example 6.7 nm or 13.5 nm, may be used to form smaller features on a substrate than a lithographic apparatus which uses, for example, radiation with a wavelength of 193 nm.

[0005] In an immersion lithographic apparatus an immersion liquid is interposed in a space between a projection system of the apparatus and a substrate. This immersion liquid can find its way past the edge of the substrate to an under surface of the substrate. This can be deleterious due to contamination of the under surface of the substrate resulting from this immersion liquid and/or due to thermal loads applied to the under surface of the substrate at positions close to the edge of the substrate, due to evaporation of the immersion liquid. A substrate holder which is configured to support the substrate can have features which reduce the quantity and/or distance the immersion liquid moves radially inwardly along the under surface of the substrate.

[0006] Generally, a substrate will be supported by the substrate holder whilst the substrate is being irradiated. The substrate holder may comprise specific portions, such as support elements, which contact the underneath of the substrate during use to support the substrate. After the substrate has been irradiated, it may be removed from the substrate holder. There may be specific steps which are carried out to unload the substrate from the substrate holder. The substrate may be deformed during the process of unloading the substrate. The deformity generally causes the centre of the substrate to rise up, away from the substrate holder and causes the substrate to cantilever down, towards the substrate holder over the outermost support beneath the substrate.

[0007] During the unloading process, the deformed substrate may contact and wear against different parts of the substrate holder which can lead to various problems. Firstly, the interaction between the support elements of the substrate holders and the underside of the substrate during unloading can lead to wear of the supporting elements. As the supporting elements are used to support the substrate to irradiate further layers, or to support further substrates, any wear of the support elements can lead to focusing and/or overlay issues. The wear of any of the supporting elements may mean that the substrate table needs to be replaced in due course. In other words, the wear of the supporting elements may limit the usable life of the substrate holder. Secondly, the underneath of the substrate tends to contact the features used to reduce the quantity and/or distance that the immerse liquid moves radially inward from an outer edge. This means that the substrate wears down said features and that the features scrape against the underneath of the substrate at an outer edge of the substrate. This can generate particles which contaminate the system and can lead to focusing and/or overlay issues.

SUMMARY

[0008] It is an object to provide a substrate holder which reduces the wear on support elements used to support the substrate and/or to reduce damage to an underside of the substrate which can contaminate the system.

[0009] In an embodiment, there is provided a substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: a main body having a main body surface; a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; a seal unit comprising a first seal member projecting from the main body surface, the first seal member having an upper surface and a second height less than the first height and being positioned radially outward of and surrounding the plurality of support elements, the upper surface having a contact region configured to contact the substrate during loading and/or unloading of the substrate; and wherein a position of the contact region is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the first seal member by the substrate is greater than a force applied to the plurality of support elements by the substrate

[0010] In an embodiment, there is provided a substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: a main body having a main body surface; a plurality of support elements projecting from the main body surface, wherein each

support element has a distal end surface configured to support the substrate and a first height; a seal unit comprising a first seal member projecting from the main body surface, the first seal member having a second height less than the first height and being positioned radially outward of and surrounding the plurality of support elements, at least one further member projecting from the main body surface and having an upper surface, the at least one further member being positioned radially outward of and surrounding the seal unit, the at least one further member comprising a coating forming the upper surface of the further member, the coating having a contact region configured to contact the substrate during loading and/or unloading of the substrate, wherein the coating is made of diamond-like carbon (e.g. a-CH), diamond, silicon carbide (e.g. SiSiC or SiC), boron nitride, or boron carbon nitride (BCN); and wherein a position of the contact region of the further member is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the further member by the substrate is greater than a force applied to the plurality of support elements by the substrate.

[0011] In an embodiment, there is provided a substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: a main body having a main body surface; a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; a seal unit comprising a first seal member projecting from the main body surface, the first seal member having an upper surface and a second height less than the first height and being positioned radially outward of the plurality of and surrounding the support elements, and the upper surface having a contact region configured to contact the substrate during loading and/or unloading of the substrate; and wherein a profile of the contact region, in a cross section through the first seal member in a radial direction, has a shape which is configured such that during the loading and/or unloading of the substrate, the substrate contacts the first seal member via at least two different points of the profile. In an embodiment, there is provided a lithographic apparatus comprising a substrate holder configured to support the substrate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Embodiments of the invention will now be described, by way of example only, with reference to the accompanying schematic drawings, in which:

[0013] FIG. 1 depicts a schematic overview of a lithographic apparatus;

[0014] FIGS. 2A and 2B depict, in cross section, two different versions of a fluid handling structure with different features illustrated on the left-hand side and the right-hand side, which may extend around the complete circumference;

[0015] FIG. 3A depicts, in cross section, a substrate holder according to the prior art and FIG. 3B depicts a close-up portion of FIG. 3A showing an outermost support element and a seal member;

[0016] FIG. 4 depicts, in cross section, an edge of a substrate holder according to an embodiment of the present invention;

[0017] FIG. 5 depicts, in cross section, an edge of a substrate holder according to an embodiment of the present invention;

[0018] FIGS. 6A and 6B depict, in cross section, an edge of a substrate holder according to an embodiment of the present invention;

[0019] FIGS. 7A-7G each depict, in cross section, a seal unit according to an embodiment of the present invention;

[0020] FIG. 8 depicts, in cross section, an edge of a substrate holder according to an embodiment of the present invention;

[0021] FIG. 9 depicts, in cross section, an edge of a substrate holder according to an embodiment

of the present invention; and

[0022] FIG. **10** depicts, in cross section, an edge of a substrate according to an embodiment of the present invention.

DETAILED DESCRIPTION

[0023] In the present document, the terms “radiation” and “beam” are used to encompass all types of electromagnetic radiation, including ultraviolet radiation (e.g. with a wavelength of 365, 248, 193, 157 or 126 nm).

The term “reticle”, “mask” or “patterning device” as employed in this text may be broadly interpreted as referring to a generic patterning device that can be used to endow an incoming radiation beam with a patterned cross-section, corresponding to a pattern that is to be created in a target portion of the substrate. The term “light valve” can also be used in this context. Besides the classic mask (transmissive or reflective, binary, phase-shifting, hybrid, etc.), examples of other such patterning devices include a programmable mirror array and a programmable LCD array.

[0024] FIG. **1** schematically depicts a lithographic apparatus. The lithographic apparatus includes an illumination system (also referred to as illuminator) IL configured to condition a radiation beam B (e.g., UV radiation or DUV radiation), a mask support (e.g., a mask table) MT constructed to support a patterning device (e.g., a mask) MA and connected to a first positioner PM configured to accurately position the patterning device MA in accordance with certain parameters, a substrate support (e.g., a wafer table) WT constructed to hold a substrate (e.g., a resist coated wafer) W and connected to a second positioner PW configured to accurately position the substrate support WT in accordance with certain parameters, and a projection system (e.g., a refractive projection lens system) PS configured to project a pattern imparted to the radiation beam B by patterning device MA onto a target portion C (e.g., comprising one or more dies) of the substrate W.

[0025] In operation, the illumination system IL receives the radiation beam B from a radiation source SO, e.g. via a beam delivery system BD. The illumination system IL may include various types of optical components, such as refractive, reflective, magnetic, electromagnetic, electrostatic, and/or other types of optical components, or any combination thereof, for directing, shaping, and/or controlling radiation. The illuminator IL may be used to condition the radiation beam B to have a desired spatial and angular intensity distribution in its cross section at a plane of the patterning device MA.

[0026] The term “projection system” PS used herein should be broadly interpreted as encompassing various types of projection system, including refractive, reflective, catadioptric, anamorphic, magnetic, electromagnetic and/or electrostatic optical systems, or any combination thereof, as appropriate for the exposure radiation being used, and/or for other factors such as the use of an immersion liquid or the use of a vacuum. Any use of the term “projection lens” herein may be considered as synonymous with the more general term “projection system” PS.

[0027] The lithographic apparatus may be of a type wherein at least a portion of the substrate may be covered by an immersion liquid having a relatively high refractive index, e.g., water, so as to fill a space **11** between the projection system PS and the substrate W-which is also referred to as immersion lithography. More information on immersion techniques is given in U.S. Pat. No. 6,952,253, which is incorporated herein by reference.

[0028] The lithographic apparatus may also be of a type having two or more substrate supports WT (also named “dual stage”). In such “multiple stage” machine, the substrate supports WT may be used in parallel, and/or steps in preparation of a subsequent exposure of the substrate W may be carried out on the substrate W located on one of the substrate support WT while another substrate W on the other substrate support WT is being used for exposing a pattern on the other substrate W.

[0029] In addition to the substrate support WT, the lithographic apparatus may comprise a measurement stage. The measurement stage is arranged to hold a sensor and/or a cleaning device. The sensor may be arranged to measure a property of the projection system PS or a property of the radiation beam B. The measurement stage may hold multiple sensors. The cleaning device may be

arranged to clean part of the lithographic apparatus, for example a part of the projection system PS or a part of a system that provides the immersion liquid. The measurement stage may move beneath the projection system PS when the substrate support WT is away from the projection system PS. [0030] In operation, the radiation beam B is incident on the patterning device, e.g. mask, MA which is held on the mask support MT, and is patterned by the pattern (design layout) present on patterning device MA. Having traversed the mask MA, the radiation beam B passes through the projection system PS, which focuses the beam onto a target portion C of the substrate W. With the aid of the second positioner PW and a position measurement system IF, the substrate support WT can be moved accurately, e.g., so as to position different target portions C in the path of the radiation beam B at a focused and aligned position. Similarly, the first positioner PM and possibly another position sensor (which is not explicitly depicted in FIG. 1) may be used to accurately position the patterning device MA with respect to the path of the radiation beam B. Patterning device MA and substrate W may be aligned using mask alignment marks M1, M2 and substrate alignment marks P1, P2. Although the substrate alignment marks P1, P2 as illustrated occupy dedicated target portions, they may be located in spaces between target portions. Substrate alignment marks P1, P2 are known as scribe-lane alignment marks when these are located between the target portions C.

[0031] To clarify embodiments of the invention, a Cartesian coordinate system is used. The Cartesian coordinate system has three axis, i.e., an x-axis, a y-axis and a z-axis. Each of the three axis is orthogonal to the other two axis. A rotation around the x-axis is referred to as an Rx-rotation. A rotation around the y-axis is referred to as an Ry-rotation. A rotation around about the z-axis is referred to as an Rz-rotation. The x-axis and the y-axis define a horizontal plane, whereas the z-axis is in a vertical direction. The Cartesian coordinate system is not limiting the invention and is used for clarification only. Instead, another coordinate system, such as a cylindrical coordinate system, may be used to clarify embodiments of the invention. The orientation of the Cartesian coordinate system may be different, for example, such that the z-axis has a component along the horizontal plane.

[0032] Immersion techniques have been introduced into lithographic systems to enable improved resolution of smaller features. In an immersion lithographic apparatus, a liquid layer of immersion liquid having a relatively high refractive index is interposed in a space 11 between a projection system of the apparatus (through which the patterned beam is projected towards the substrate W) and the substrate W. The immersion liquid covers at least the part of the substrate under a final element of the projection system PS. Thus, at least the portion of the substrate W undergoing exposure is immersed in the immersion liquid. The effect of the immersion liquid is to enable imaging of smaller features since the exposure radiation will have a shorter wavelength in the liquid than gas. (The effect of the immersion liquid may also be regarded as increasing the effective numerical aperture (NA) of the system and also increasing the depth of focus.)

[0033] In commercial immersion lithography, the immersion liquid is water. Typically the water is distilled water of high purity, such as Ultra-Pure Water (UPW) which is commonly used in semiconductor fabrication plants. In an immersion system, the UPW is often purified and it may undergo additional treatment steps before supply to the immersion space 11 as immersion liquid. Other liquids with a high refractive index can be used besides water can be used as the immersion liquid, for example: a hydrocarbon, such as a fluorohydrocarbon; and/or an aqueous solution. Further, other fluids besides liquid have been envisaged for use in immersion lithography.

[0034] In this specification, reference will be made in the description to localized immersion in which the immersion liquid is confined, in use, to the space 11 between the final element and a surface facing the final element. The facing surface is a surface of substrate W or a surface of the supporting stage (or substrate support WT) that is co-planar with the surface of the substrate W. (Please note that reference in the following text to surface of the substrate W also refers in addition or in the alternative to the surface of the substrate support WT, unless expressly stated otherwise;

and vice versa). A fluid handling structure **12** present between the projection system PS and the substrate support WT is used to confine the immersion liquid to the immersion space **11**. The space **11** filled by the immersion liquid is smaller in plan than the top surface of the substrate W and the space **11** remains substantially stationary relative to the projection system PS while the substrate W and substrate support WT move underneath.

[0035] Other immersion systems have been envisaged such as an unconfined immersion system (a so-called 'All Wet' immersion system) and a bath immersion system. In an unconfined immersion system, the immersion liquid covers more than the surface under the final element. The liquid outside the immersion space **11** is present as a thin liquid film. The liquid may cover the whole surface of the substrate W or even the substrate W and the substrate support WT co-planar with the substrate W. In a bath type system, the substrate W is fully immersed in a bath of immersion liquid.

[0036] The fluid handling structure **12** is a structure which supplies the immersion liquid to the immersion space **11**, removes the immersion liquid from the space **11** and thereby confines the immersion liquid to the immersion space **11**. It includes features which are a part of a fluid supply system. The arrangement disclosed in PCT patent application publication no. WO 99/49504 is an early fluid handling structure comprising pipes which either supply or recover the immersion liquid from the space **11** and which operate depending on the relative motion of the stage beneath the projection system PS. In more recent designs, the fluid handling structure extends along at least a part of a boundary of the space **11** between the final element of the projection system PS and the substrate support WT or substrate W, so as to in part define the space **11**.

[0037] The fluid handling structure **12** may have a selection of different functions. Each function may be derived from a corresponding feature that enables the fluid handling structure **12** to achieve that function. The fluid handling structure **12** may be referred to by a number of different terms, each referring to a function, such as barrier member, seal unit, fluid supply system fluid removal system, liquid confinement structure, etc.

[0038] As a barrier member, the fluid handling structure **12** is a barrier to the flow of the immersion liquid from the space **11**. As a liquid confinement structure, the structure confines the immersion liquid to the space **11**. As a seal unit, sealing features of the fluid handling structure form a seal to confine the immersion liquid to the space **11**. The sealing features may include an additional gas flow from an opening in the surface of a seal member of the seal unit, such as a gas knife.

[0039] In an embodiment the fluid handling structure **12** may supply immersion fluid and therefore be a fluid supply system.

[0040] In an embodiment the fluid handling structure **12** may at least partly confine immersion fluid and thereby be a fluid confinement system.

[0041] In an embodiment the fluid handling structure **12** may provide a barrier to immersion fluid and thereby be a barrier member, such as a fluid confinement structure.

[0042] In an embodiment the fluid handling structure **12** may create or use a flow of gas, for example to help in controlling the flow and/or the position of the immersion fluid.

[0043] The flow of gas may form a seal to confine the immersion fluid so the fluid handling structure **12** may be referred to as a seal unit; such a seal unit may be a fluid confinement structure.

[0044] In an embodiment, immersion liquid is used as the immersion fluid. In that case the fluid handling structure **12** may be a liquid handling system. In reference to the aforementioned description, reference in this paragraph to a feature defined with respect to fluid may be understood to include a feature defined with respect to liquid.

[0045] A lithographic apparatus has a projection system PS. During exposure of a substrate W, the projection system PS projects a beam of patterned radiation onto the substrate W. To reach the substrate W, the path of the radiation beam B passes from the projection system PS through the immersion liquid confined by the fluid handling structure **12** between the projection system PS and the substrate W. The projection system PS has a lens element, the last in the path of the beam, which is in contact with the immersion liquid. This lens element which is in contact with the

immersion liquid may be referred to as ‘the last lens element’ or “the final element”. The final element is at least partly surrounded by the fluid handling structure **12**. The fluid handling structure **12** may confine the immersion liquid under the final element and above the facing surface. [0046] FIGS. **2A** and **2B** show different features which may be present in variations of fluid handling structure **12**. The designs may share some of the same features as FIGS. **2A** and **2B** unless described differently. The features described herein may be selected individually or in combination as shown or as required.

[0047] FIG. **2A** shows a fluid handling structure **12** around the bottom surface of a final element **100**. The final element **100** has an inverted frusto-conical shape. The frusto-conical shape having a planar bottom surface and a conical surface. The frusto-conical shape protrudes from a planar surface and having a bottom planar surface. The bottom planar surface is the optically active portion of the bottom surface of the final element **100**, through which the radiation beam B may pass. The final element **100** may have a coating **30**. The fluid handling structure **12** surrounds at least part of the frusto-conical shape. The fluid handling structure **12** has an inner-surface which faces towards the conical surface of the frusto-conical shape. The inner-surface and the conical surface have complementary shape. A top surface of the fluid handling structure **12** is substantially planar. The fluid handling structure **12** may fit around the frusto-conical shape of the final element **100**. A bottom surface of the fluid handling structure **12** is substantially planar and in use the bottom surface may be parallel with the facing surface of the substrate support WT and/or substrate W. The distance between the bottom surface and the facing surface may be in the range of 30 to 500 micrometers, desirably in the range of 80 to 200 micrometers.

[0048] The fluid handling structure **12** extends closer to the facing surface of the substrate W and substrate support WT than the final element **100**. A space **11** is therefore defined between the inner surface of the fluid handling structure **12**, the planar surface of the frusto-conical portion and the facing surface. During use, the space **11** is filled with immersion liquid. The immersion liquid fills at least part of a buffer space between the complementary surfaces between the final element **100** and the fluid handling structure **12**, in an embodiment at least part of the space between the complementary inner-surface and the conical surface.

[0049] The immersion liquid is supplied to the space **11** through an opening formed in a surface of the fluid handling structure **12**. The immersion liquid may be supplied through a supply opening **20** in the inner-surface of the fluid handling structure **12**. Alternatively or additionally, the immersion liquid is supplied from an under supply opening **23** formed in the undersurface of the fluid handling structure **12**. The under supply opening **23** may surround the path of the radiation beam B and it may be formed of a series of openings in an array. The immersion liquid is supplied to fill the space **11** so that flow through the space **11** under the projection system PS is laminar. The supply of the immersion liquid from the under supply opening **23** under the fluid handling structure **12** additionally prevents the ingress of bubbles into the space **11**. This supply of the immersion liquid functions as a liquid seal.

[0050] The immersion liquid may be recovered from a recovery opening **21** formed in the inner-surface. The recovery of the immersion liquid through the recovery opening **21** may be by application of an under pressure; the recovery through the recovery opening **21** as a consequence of the velocity of the immersion liquid flow through the space **11**; or the recovery may be as a consequence of both. The recovery opening **21** may be located on the opposite side of the supply opening **20**, when viewed in plan. Additionally or alternatively, the immersion liquid may be recovered through an overflow opening **24** located on the top surface of the fluid handling structure **12**. In an embodiment, the supply and recovery openings **20**, **21** can have their function swapped (i.e. the flow direction of liquid is reversed). This allows the direction of flow to be changed depending upon the relative motion of the fluid handling structure **12** and substrate W.

[0051] Additionally or alternatively, immersion liquid may be recovered from under the fluid handling structure **12** through a recovery opening **25** formed in its bottom surface. The recovery

opening **25** may serve to hold (or ‘pin’) a meniscus **33** of the immersion liquid to the fluid handling structure **12**. The meniscus **33** forms between the fluid handling structure **12** and the facing surface and it serves as border between the liquid space and the gaseous external environment. The recovery opening **25** may be a porous plate which may recover the immersion liquid in a single phase flow. The recovery opening in the bottom surface may be a series of pinning openings **32** through which the immersion liquid is recovered. The pinning openings **32** may recover the immersion liquid in a two phase flow.

[0052] Optionally radially outward, with respect to the inner-surface of the fluid handling structure **12**, is a gas knife opening **26**. Gas may be supplied through the gas knife opening **26** at elevated speed to assist liquid confinement of the immersion liquid in the space **11**. The supplied gas may be humidified and it may contain substantially carbon dioxide. Radially outward of the gas knife opening **26** is a gas recovery opening **28** for recovering the gas supplied through the gas knife opening **26**. Further openings, for example open to atmosphere or to a gas source, may be present in the bottom surface of the fluid handling structure **12**. For example, further openings may be present between gas knife opening **26** and gas recovery opening **28** and/or between pinning openings **32** and gas knife opening **26**.

[0053] Features shown in FIG. 2B which are common to FIG. 2A share the same reference numbers. The fluid handling structure **12** has an inner surface which complements the conical surface of the frusto-conical shape. The undersurface of the fluid handling structure **12** is closer to the facing surface than the bottom planar surface of the frusto-conical shape.

[0054] Immersion liquid is supplied to the space **11** through supply openings **34** formed in the inner surface of the fluid handling structure **12**. The supply openings **34** are located towards the bottom of the inner surface, perhaps below the bottom surface of the frusto-conical shape. The supply openings **34** are located around the inner surface, spaced apart around the path of the radiation beam B.

[0055] Immersion liquid is recovered from the space **11** through recovery openings **25** in the undersurface of the fluid handling structure **12**. As the facing surface moves under the fluid handling structure **12**, the meniscus **33** may migrate over the surface of the recovery opening **25** in the same direction as the movement of the facing surface. The recovery openings **25** may be formed of a porous member. The immersion liquid may be recovered in single phase. In an embodiment the immersion liquid is recovered in a two phase flow. The two phase flow is received in a chamber **35** within the fluid handling structure **12** where it is separated into liquid and gas. The liquid and gas are recovered through separate channels **36**, **38** from the chamber **35**.

[0056] An inner periphery **39** of the undersurface of fluid handling structure **12** extends into the space **11** away from the inner surface to form a plate **40**. The inner periphery **39** forms a small aperture which may be sized to match the shape and size of the radiation beam B. The plate **40** may serve to isolate the immersion liquid at either side of it. The supplied immersion liquid flows inwards towards the aperture, through the inner aperture and then under the plate **40** radially outwardly towards the surrounding the recovery openings **25**.

[0057] In an embodiment the fluid handling structure **12** may be in two parts as shown on the right hand side of FIG. 2B: an inner part **12a** and an outer part **12b**. The inner part **12a** and the outer part **12b** may move relatively to each other, in a plane parallel to facing surface. The inner part **12a** may have the supply openings **34** and it may have the overflow recovery **24**. The outer part **12b** may have the plate **40** and the recovery opening **25**. The inner part **12a** may have an intermediate recovery **42** for recovering the immersion liquid which flows between the inner part **12a** and the outer part **12b**.

[0058] In the examples of FIGS. 2A and 2B, at least one of the various recovery openings (e.g. recovery opening **21** in FIG. 2A, overflow recovery **24** in both FIGS. 2A and 2B, recovery opening **25** in both FIGS. 2A and 2B, pinning openings **32** in FIG. 2A, and channels **36**, **38** in FIG. 2B) and/or supply openings (e.g. supply opening **20** in FIG. 2A, under supply opening **23** in FIG. 2A,

and supply openings **34** in FIG. 2B) can be used to control the amount of immersion liquid in the space **11**. The location of the meniscus **33** and the location of a meniscus **22**, which is similar to meniscus **33** except it is formed between the another part of the fluid handling system **12** and the final element **100**, will vary depending on the amount of immersion liquid in the space **11**.

[0059] The substrate support WT may comprise a substrate holder **200** which is configured to support the substrate W. FIG. 3A illustrates, in cross section, substrate holder **200** and an associated substrate W which is being supported by the substrate holder **200**. The substrate holder **200** comprises a main body **201** having a main body surface **202**. In use, the main body surface **202** faces an under surface of the substrate W, i.e. a lower surface of the substrate W which faces the substrate holder **200**.

[0060] In a central region of the main body surface **202**, a plurality of support elements **210** project from the main body surface **202**. Each support elements **210** has a distal end surface **211** (shown in FIG. 3B) configured to support the substrate W. For example, during irradiation of the substrate W, the support elements **210** may be configured to contact the under surface of the substrate W. The support elements **210** are arranged relative to one another in a pattern, in plan. The pattern is such as to support the substrate W and to reduce any bowing of the substrate W towards the main body surface **202** to an acceptable amount.

[0061] The area in plan of each support element **210** is relatively small compared to the area, in plan, of the substrate W. Therefore, the support elements **210** contact only a small area of the under surface of the substrate W. This reduces the opportunity for contamination to be transferred from the substrate holder **200** to the substrate W.

[0062] A pressure differential across the substrate W is established. For example, the space between the main body **201** of the substrate holder **200** and the substrate W is connected to an under pressure that is lower than a higher pressure above the substrate W. The pressure difference gives rise to a force holding the substrate W to the substrate holder **200** when in use, e.g. when the substrate W is irradiated. In other words, the substrate holder **200** has means for clamping the substrate W to the substrate holder **200**.

[0063] In an immersion lithographic apparatus, liquid will, at least at certain times during exposure of the substrate W, be present adjacent to an edge of the substrate W. Due to the under pressure between the main body **201** of the substrate holder **200** and the under surface of the substrate W, this liquid will be drawn in around the edge of the substrate W and under the substrate W. In order to reduce occurrence of liquid being in contact with the under surface of the substrate W and especially at the area where the support elements **210** are in contact with the substrate W, a seal unit comprising at least one member projecting from the main body surface **202** of the main body **201** can be provided. Overall, the liquid between the substrate W and the main body surface **202** radially inward past the seal unit. The seal unit may comprise a first seal member and a second seal member. The first seal member may be radially outwards of and surrounding the second seal member. The first seal member may be used to reduce the pressure in a region between the first seal member and the second seal member. The second seal member may be configured to restrict or prevent the passage of liquid radially inwards of the second seal member. The first seal member may also at least partially restrict passage of liquid radially inward of the first seal member. The seal unit may be configured to restrict passage of the liquid around substantially the entire circumference of the seal unit, i.e. around the whole substrate W. In other words, the amount of liquid at a position radially outward of the seal unit is restricted or prevented from moving radially inward to a position radially inwards of the seal unit due to the presence of the seal unit. This means that the presence of the seal unit reduces the amount of liquid at a position radially inwards of the seal unit compared to if the seal unit is not provided. The liquid may be prevented from simply going around the seal unit.

[0064] The seal unit may be part of a seal mechanism, for example a seal formed near or around the radially outer edge of the substrate W. The seal unit may comprise further components used to

restrict passage of liquid radially inward.

[0065] One purpose of the seal unit is to limit the flow of gas (which may undesirably be humid) radially inward towards the support element **210**. This enables the under pressure to be generated around the support elements **210** which is necessary for clamping the substrate W to the substrate holder **200**. It is advantageous to allow some flow of gas over the seal unit so that when the under pressure source which generates the under pressure around the support elements **210** is switched off, the substrate W can quickly be removed from the substrate holder **200**. If the gas flow is too low past the seal unit, then the time taken for the pressure around the support elements **210** to equalize with the pressure above the substrate W, thereby releasing the substrate W, is too high. The substrate holder **200** may be configured to generate an over pressure beneath the under surface of the substrate W so that the substrate W can be more quickly removed.

[0066] The seal unit may comprise at least one seal member. The seal member may comprise a first seal member **220** and a second seal member **240**. The first seal member **220** is shown in FIGS. 3A and 3B. The second seal member **240** will be described below in further detail. The first seal member **220** may be configured to restrict the flow of gas/fluid radially inwards of the first seal member **220**. The seal unit may comprise only the first seal member **220**, for example, in a dry lithographic system.

[0067] The first seal member **220** has an upper surface **221** which is a distal end of the first seal member **220**. Thus, the upper surface **221** is situated away from the point of contact between the first seal member **220** and the main body surface **202** (even if the first seal member **220** and the main body **201** are integral with one another). The upper surface **221** is configured, in use, to form a gap between the upper surface **221** and the under surface of the substrate W. That is, the upper surface **221** is configured to be somewhat closer to the main body surface **202** than the distal end surface **211** of the support elements **210**. This is advantageous because this arrangement allows gas to be drawn in over the first seal member **220** (under the substrate W) just before the substrate W removal whilst allowing restriction of the passage of liquid in the same direction. This is achieved without contacting a large area of the under surface of the substrate W which would lead deleteriously to transfer of contamination from the first seal member **220** to the substrate W. This would also make removal of the substrate W from the substrate holder **200** more problematic.

[0068] As can be seen in FIGS. 3A and 3B, the most radially outward of the plurality of supporting elements **210** is somewhat distant from the edge of the substrate W. In the absence of any other feature supporting the substrate W radially outward of the most radially outward support elements **210**, bending of the edge of the substrate W downwards may occur, in particular, during unloading of the substrate W. This is due to the under pressure underneath the substrate W compared to above the substrate W.

[0069] In use, an under pressure in a central region of the substrate holder **200** between the main body surface **202** and the substrate W can be provided. This under pressure is the reason why the substrate W may be clamped to the substrate holder **200** during use. This clamping under pressure may have a lower magnitude (i.e. a less severe vacuum) than the under pressure at a region radially outward of the support elements **210**.

[0070] During unloading of the substrate W, the pressure can be controlled between the main body surface **202** and the substrate W to allow unloading of the substrate W. The unloading of the substrate W may include steps of increasing the pressure between the main body surface **202** and the substrate W. This is indicated by the upward arrows in FIG. 3A. For example, when the substrate W is to be unloaded, the vacuum under the substrate W can be removed by injecting high pressure air under the substrate W. Thus, the unloading of the substrate W includes at least one release step, for example, increasing the pressure between the main body **201** and the under surface of the substrate W. An advantage of creating an over pressure under the substrate W during unloading is that any fluid between the substrate W and the main body surface **202** will be pushed radially outward. However, this generally leads to an over pressure under the center of the substrate

W and an under pressure around the edge of the substrate W. Thus, the substrate W may deform and bulge up in the middle of the substrate W and cantilever downwards at the edge of the substrate W.

[0071] FIGS. 3A and 3B are indicative of the prior art and show that whilst the substrate W is bulging up in the middle, the sides of the substrate W will scrape over the radially outermost support element **210** and the first seal member **220**. As shown in the close up in FIG. 3B, there is interaction between the distal end surface **211** of the radially outermost support element **210** and the substrate W, and also between the upper surface **221** of the first seal member **220** and the substrate W. As indicated above, this can have deleterious effects on the system.

[0072] The scraping of the substrate W over the distal end surface **211** of the support element **210** applies a force to the support element **210**. Any interaction between the substrate W and one of the support elements **210** can lead to wear on the support element **210**. This is an issue because it can alter the exact height of the support elements **210**. If the height of the support elements **210** is changed, this can lead to focusing and/or overlay issues when irradiating further substrates W and/or further layers of the same substrate W. If the support elements **210** become too damaged, it may be necessary to replace the substrate holder **200**. Therefore, preventing damage of the support element **210** provides more stable long term performance of the substrate holder **200**.

[0073] Interaction between the substrate W and the first seal member **220** occurs as the underside of the substrate W scrapes over an edge of the first seal member **220**, i.e. in known systems, the under surface of the substrate W contacts the first seal member **220** via a single point contact (in cross-section) during unloading. This leads to high stress points on the under surface of the substrate W and causes scratches on the under surface of the substrate W. The scratches can generate particles of substrate W, or even first seal member **220**, which contaminate the system. The particles are generally close to the edge of the substrate W and could therefore end up on top of the substrate W. Additionally, the interaction may lead to wear of the first seal member **220** in an undesirable manner, i.e. in a way which affects the capability of the first seal member **220** (and thus the seal unit as a whole) to function as desired. Thus, it is desirable to reduce interaction between the first seal member **220** and the substrate W in a way which might affect the ability of the first seal member **220** to control the pressure between the first seal member **220** and the second seal member **240** and/or to control inward movement of liquid past the first seal member **220**.

Therefore, preventing damage of the first seal member **220** in certain areas used to provide the seal provides more stable long term performance of the substrate holder **200**.

[0074] Wear is deleterious because it can result in contamination of the substrate W as well as a change in the clamping characteristics of the substrate holder **200** and thereby deformation of the substrate W. The presence of liquid between the support elements **210** and the substrate W underside can also lead to wear (if the substrate holder **200** is a ceramic), and possibly friction variation. Deformation of the substrate W can lead to imaging errors (e.g. overlay errors and/or focusing errors), as can contamination. The presence of liquid on the underside of the substrate W is generally deleterious because this can result in thermal stability issues of the substrate W or difficulties when the liquid droplets are lost during unloading of the substrate W.

[0075] Similar issues may arise during loading of the substrate W on the substrate holder **200**. Thus, during loading, the substrate W may be deformed in some way which leads to the scraping of the substrate W against the substrate holder **200** as described above. Additionally or alternatively, during loading of a substrate W in a dry lithographic apparatus, the substrate W may be tilted during loading and this may cause the edge of the substrate W to contact the edge of the support elements **210** causing wear.

[0076] As will be described below, the substrate holder **200** of an embodiment of the present invention alleviates some of these difficulties due to the location and shape of the first seal member **220** which is configured to interact with the substrate W during unloading (or loading) of the substrate W and whilst still providing a mechanism as part of the seal unit, e.g. by restricting

passage of fluid/gas radially inward of the first seal member **220**. The unloading step can otherwise be referred to as a release step and thus, the term release can be interchanged in the parts of the description below relating to unloading of the substrate W.

[0077] In an embodiment, a substrate holder **200** as described in FIGS. **3A** and **3B** is provided. However, the first seal member **220** is configured to address some of the above described issues. The differences between an embodiment of the present invention and at least the first seal member **220** described above in relation to FIGS. **3A** and **3B** will be described in detail below.

[0078] In further detail, an embodiment provides a substrate holder **200** for use in lithographic apparatus and configured to support a substrate W. The substrate holder **200** comprises a main body **201** having a main body surface **202**. The substrate holder **200** also comprises a plurality of support elements **210** projecting from the main body surface **202**, wherein each support elements **210** has a distal end surface **211** configured to support the substrate W. The support elements **210** may have a first height. The substrate holder **200** further comprises a seal unit. The seal unit may be configured to restrict the passage of liquid between the substrate W and the main body surface **202** radially inward past the seal unit. The seal unit may comprise a first seal member **220** projecting from the main body surface **202** and having an upper surface **221**. The first seal member **220** may have a second height, the second height being less than the first height. Thus, the support elements **210** may be taller than the first seal member **220**. Similarly, the support elements **210** may be taller than the second seal member **240** (if provided). The seal unit may comprise a second seal member **240** projecting from the main body surface **202**. The second seal member **240** may be positioned radially inwards of the first seal member **220**. The first seal member **220** may be positioned radially outward of and surrounding the plurality of support elements **210**. The second seal member **240** is optional and may be particularly useful for immersion systems in order to prevent passage of liquid radially inwards.

[0079] The first seal member **220** and the second seal member **240** may together be configured to restrict or prevent liquid and gas from passing radially inwards of the seal unit. The first seal member **220** may be configured to create a low pressure region between the first seal member **220** and the second seal member **240**. Thus, the pressure of a space between the first seal member **220** and the second seal member **240**, i.e., seal area, may be lower than the pressure surrounding the seal unit. The low pressure region between the first seal member **220** and the second seal member **240** reduces the amount of liquid moving radially inwards of the space between the first seal member **220** and the second seal member **240**.

[0080] The first seal member **220** may be configured to provide a pressure drop radially inwards of the first seal member **220** relative to the pressure in a region radially outwards of the seal unit. For example, the first seal member **220** may be used primarily to create a pressure drop from ambient to approximately -500 mbar and, thus, to create a vacuum to clamp the substrate W. The second seal member **240** may be used to maintain a pressure difference of approximately 25 mbar between the seal area and the inner portion of the substrate holder **200**, which may be at -475 mbar for example. This small pressure difference may result in a body of water (capillary) in a small gap between the second seal member **240** and the substrate W. The main function of second seal member **240** may be the restriction of water moving further inwards. The second seal member **240** may be configured to reduce or prevent liquid from passing radially inwards of the seal unit.

[0081] The cross-sectional area of the first seal member **220** in plan, may be very much greater than that of the support elements **210**. The relatively large area, in plan, of the first seal member **220** results in a greater resistance to the passage of the liquid between the substrate W and the main body surface **202** radially inward past the first seal member **220**. The cross-sectional shape of the first seal member **220** in plan may be circular, or more specifically ring-shaped or annular shaped. Thus, the first seal member **220** may have an annular shape.

[0082] The cross-sectional area of the second seal member **240** in plan, may be very much greater than that of the support elements **210**. The relatively large area, in plan, of the second seal member

240 results in a greater resistance to the passage of the liquid between the substrate **W** and the main body surface **202** radially inward past the second seal member **240**. The first seal member **220** and the second seal member **240** may have similar or the same cross-sectional areas. The cross-sectional shape of the second seal member **240** in plan may be circular, or more specifically ring-shaped or annular shaped. Thus, the second seal member **240** may have an annular shape.

[0083] The first seal member **220** may surround the plurality of support elements **210**. Thus, the first seal member **220** may be substantially around the whole circumference of the plurality of the support elements **210**. In other words, the first seal member **220** may enclose the plurality of support elements **210**, for example, when viewed in plan. The first seal member **220** may be a continuous (though not necessarily uniform in cross-section) barrier surrounding the support elements **210**. Alternatively, the first seal member **220** may be formed of a plurality of segments. The plurality of segments may form substantially all of an annular ring. In other words, the first seal member **220** may be formed by multiple separate segments which substantially form an annular ring. In the segmented annular ring, there may be multiple seal member portions with a gap between each neighboring seal member portion. The gap between neighboring seal member portions may be the same length or shorter than the length of either or both of the neighboring portions. The distance between each seal member portion may be the same as, or less than, the width of one or both of the neighboring seal member portions. At least one of the gaps between neighboring seal member portions, i.e. the spacing between neighboring portions, may be in the order of tens or hundreds of microns. At least one of the gaps between neighboring seal member portions may be as narrow as approximately 10 microns. At least one of the gaps may be between 0.5-5 mm. Some or all of the gaps may have these dimensions. Providing small gaps may be advantageous is that any contamination, for example from interaction between the first seal member **220** and the underside of the substrate **W** can be caught in the gaps whilst still providing a relatively large contact area on the first seal member **220**.

[0084] The second seal member **240** may be positioned radially inward of the first seal member **220**. The second seal member **240** may be radially outward of some or all of the plurality of support elements **210**. Some of the plurality of support elements **210** may be provided radially outward of the second seal member **240**. Thus, some of the plurality of support elements **210** may be provided between the first seal member **220** and the second seal member **240**. This is described in further detail in relation to FIG. **10** below.

[0085] The second seal member **240** may surround at least some, if not most, of the plurality of support elements **210**. Thus, the second seal member **240** may be substantially around the whole circumference of at least some, if not most, of the plurality of the support elements **210**. In other words, the second seal member **240** may enclose at least some, if not most, of the plurality of support elements **210**, for example, when viewed in plan. The second seal member **240** may be a continuous (though not necessarily uniform in cross-section) barrier surrounding the support elements **210**. Alternatively, the second seal member **240** may be formed of a plurality of segments. The plurality of segments may form substantially all of an annular ring. In other words, the second seal member **240** may be formed by multiple separate segments which substantially form an annular ring. In the segmented annular ring, there may be multiple seal member portions with a gap between each neighboring seal member portion. The gap between neighboring seal member portions may be the same length or shorter than the length of either or both of the neighboring portions. The distance between each seal member portion may be the same as, or less than, the width of one or both of the neighboring seal member portions. At least one of the gaps between neighboring seal member portions, i.e. the spacing between neighboring portions, may be in the order of tens or hundreds of microns. At least one of the gaps between neighboring seal member portions may be as narrow as approximately 10 microns. At least one of the gaps may be between 0.5-5 mm. Some or all of the gaps may have these dimensions. Providing small gaps may be advantageous is that any contamination, for example from interaction between the first seal

member **220** and the underside of the substrate **W** can be caught in the gaps.

[0086] The upper surface **221** of the first seal member **220** has contact region **222** configured to contact the substrate **W** during unloading of the substrate **W**. The upper surface **221** of the first seal member **220** is configured so that it does not contact the substrate **W** when the substrate **W** is being irradiated, i.e. the first seal member **220** is not used to support the substrate **W** during irradiation. The contact region **222** is configured so that it does not contact the substrate **W** when the substrate **W** is being irradiated, i.e. the contact region **222** is not used to support the substrate **W** during irradiation. The contact region **222** may be configured to only contact the substrate **W** during the unloading of the substrate **W**. In previously known systems, it was not intended that the upper surface of any seal member provided would contact the substrate **W** during unloading (or loading) of the substrate **W**. Furthermore, in previously known systems, there may not have been any contact between the seal member and the substrate during loading or unloading, thus all the wear may have occurred on the support elements **210**.

[0087] In an embodiment, a position of the contact region **222** may be arranged at a distance from the plurality of support elements **210** sufficient enough such that during the unloading of the substrate **W**, a force applied to the first seal member **220** by the substrate **W** is greater than a force applied to the plurality of support elements **210** by the substrate **W**. This means that during unloading of the substrate **W**, wear of the support elements **210** is less than wear of the first seal member **220**. This means wear of the support elements **210** can be reduced compared to wear of the first seal member **220** when releasing a substrate using the configuration shown in FIGS. **3A** and **3B**. Ideally, the first seal member **220** may be the main feature in contact with the substrate **W** during unloading, i.e. ideally, at certain points during unloading, the substrate **W** is only in contact with the contact region **222** and not the supporting elements **210**.

[0088] In other words, the point and/or region of the first seal member **220** which is configured to contact the substrate **W** during unloading of the substrate **W** is far enough away from the support element **210** that the wear on the radially outermost support element **210** is less than the wear on the first seal member **220**. For example, if the first seal member **220** is formed with a uniform cross-section around the circumference, e.g. as shown in FIG. **4**, the cross-section shows a single point contact, but this will be provided around the circumference of the first seal member **220** and the contact region **222** will be provided by the area around the entire first seal member **220**.

[0089] The contact region **222** may simply be the region of the first seal member **220** configured to contact the substrate **W** at some point during the unload process. This will generally be a known, defined area. For example, in FIG. **4**, the contact region **222** is shown as the radially outermost point on the upper surface **221** of the first seal member **220**. The contact region **222** may be positioned point between the upper surface **221** of the first seal member **220** and a radially outer edge **223** of the first seal member **220**. In other words, the contact region **222** may provide a region between the upper surface **221** and the radially outer edge **223**. Thus, the contact region **222** may form a connection between the upper surface **221** and the radially outer edge **223**. This may be a point at which the upper surface **221** and the radially outer edge **223** would otherwise meet, as in FIG. **4**. Alternatively, the contact region **222** may be an area between these two surfaces, for example, as in FIG. **6A**. There may be a change in gradient between the upper surface **221** and the contact region **222**. There may be a change in gradient between the surface of the radially outer edge **223** and the contact region **222**.

[0090] The contact region **222** may not be uniform around the first seal member **220** and may be configured to provide an increased contact area in certain positions where it is known that particle contamination is greater.

[0091] It is known that the first seal member **220** should be provided within a certain distance of the radially outermost support element **210** in order to maintain the desired pressure between the substrate **W** and the main body **201**. Thus, an embodiment of the present invention teaches away from this by providing a certain distance between contact region **222** and the radially outer edge of

the most radially outer support element **210** whilst still maintaining the required pressure.

[0092] The position of the contact region **222** relative to the support elements **210** may be controlled in various different ways. For example, as shown in FIG. 4, the main dimensions relate to the distance between a radially outer edge **212** of distal end surface **211** of the radially outermost support elements **210** and an outer upper edge of the upper surface **221** of the first seal member **220**. The dimensions relate to these specific parts of the support element **210** and the first seal member **220** because these are the parts of these components which will come into contact with the under surface of the substrate W during unloading of the substrate W.

[0093] The distance may be defined by a distance D in the radial direction. The distance may be additionally or alternatively defined by the distance y between the distal end surface **211** of the support element **210** and the upper surface **221** of the first seal member **220**. Both of these distances will affect how the substrate W interacts with each of these components during unloading.

[0094] In this example, the contact region **222** is shown as an edge contact point in the cross section. Thus, in this embodiment, the contact region **222** is formed by the same contact point around the circumference of the first seal member **220**. This contact region **222** would be the same in FIG. 4 as in the examples shown in FIGS. 3A and 3B. However, the position of the contact region **222** in an embodiment with respect to the support element **210** would be different to the relative position of the contact region of the prior art, and would be configured to reduce the wear of the support element **210** during unloading of the substrate W.

[0095] In an embodiment the radial distance D from a radially outer edge **212** of the distal end surface **211** to the contact region **222** is greater than 1,000 microns, and preferably greater than 1,500 microns. This means that the contact region **222** can be far enough away from the support element **210** to reduce contact between the support elements **210** and the substrate W during loading and/or unloading. Additionally or alternatively, the difference in height between radially outermost support element **210** and the first seal member **220**, shown by y in FIG. 4, is between approximately 2 microns and 8 microns. The difference in height between the radially outermost support element **210** and the first seal member **220** is the distance between the distal end surface **211** and the upper surface **221** of the first seal member **220** in a y direction, wherein the y direction is orthogonal to a plane including the radial direction. Having a difference in height can also reduce contact between the support elements **210** and the substrate W during loading and/or unloading.

[0096] Providing the contact region **222** at such a distance means that during loading and/or unloading of the substrate, the substrate W will have greater interaction with the first seal member **220** rather than the radially outermost support elements **210**. Effectively, this means that the first seal member **220** is used as a sacrificial wear area. This can lead to significant reduction in the wear of the outermost support elements **210**. The distance between the radially outer edge **212** and the contact region **222** can be optimized in the radial direction and/or the y direction to minimize friction between the outermost support elements **210** and the substrate W during loading and/or unloading the substrate W. The optimum values for the distance D and the distance y may vary depending on the substrate holder **200** and/or the substrate W and/or the applications being applied to the substrate W.

[0097] The length x of the first seal member **220** in a radial direction may be greater than 300 microns, or preferably, greater than 500 microns. This may be beneficial because the contact region **222** of the first seal member **220** may be gradually worn down by the interaction between the substrate W and the first seal member **220** during unloading. If the first seal member **220** is long enough in the radial direction (i.e. x), the wear of the first seal member **220** will be less likely to affect the capability of the first seal member **220** to carry out the function of restricting the passage of liquid radially inward of the first seal member **220**. Thus, providing the first seal member **220** of sufficient length, e.g. greater than 300 microns, or preferably greater than 500 microns may mean that the first seal member **220** is configured to better control liquid at the edge of the substrate

holder **200** for a longer period of time than known seal members because the first seal member **220** of an embodiment would not be worn down by the interaction with the substrate W in the same way.

[0098] Optionally, the substrate holder **200** may comprise a coating. The coating may be used to cover at least a portion of the substrate holder **200**. For example, as described below, the coating may form part of the first seal member **220** and/or part of the at least one of the plurality of support elements **210**. The coating may be made of diamond-like carbon (DLC, e.g. a-CH), diamond, silicon carbide (e.g. SiSiC or SiC), boron nitride (BN) or boron carbon nitride (BCN). The coating may be substantially or entirely made from these materials and/or any derivatives of these materials. These materials may be particularly beneficial due to the combination of hardness and Young's modulus. Thus, these materials may have a desired level of toughness (hardness/Young's modulus).

[0099] The coating may be a thin layer e.g. having a thickness as described below. The coating may be used to cover the surface of various portions of the substrate holder **200**. The coating may be substantially uniform over any one portion of the substrate holder **200** comprising the coating. For example, the coating may be provided as a layer of substantially uniform thickness over the first seal member **220** and/or the at least one plurality of supporting elements **210**. For example, the thickness of the coating may vary by less than 50% of the thickness of the coating in the thickest part of the coating in any one portion. Preferably, the thickness varies by less than or equal to 30%, or more preferably by less than or equal to 20%.

[0100] The coating may be beneficial in reducing the wear of the substrate holder **200** and/or the scratching of the substrate W on any parts of the substrate holder **200** which come into contact with the substrate, for example, during loading or unloading of the substrate W. The coating may be advantageous in improving the wear resistance of the feature which is coated. This can prevent the feature which has the coating from wearing out.

[0101] The coating may be a thin layer. More specifically, the coating may have a thickness between approximately 0.2 μm and 2 μm . Preferably, the thickness of the coating is between approximately 0.2 μm to 1.5 μm . Preferably, the thickness of the coating is between approximately 0.2 μm to 1 μm . More generally, preferably the thickness is less than or equal to 2 μm , or preferably less than or equal to 1.5 μm , or preferably less than or equal to 1 μm . The thickness referred to here may be the average thickness over a specific portion of the substrate holder **200**.

[0102] As shown in FIG. 5, the at least one of the plurality of support elements **210** may comprise a coating **214**. The coating **214** may have the characteristics described above. As shown in FIG. 5, the coating **214** may form the distal end surface **211** of the at least one of the plurality of support elements **210**. In other words, the coating **214** may be provided on a distal end of a protrusion forming the at least one of the plurality of support elements **210**. The coating **214** may provide a layer of protection on the distal end of the at least one of the plurality of support elements **210**. As shown in FIG. 5, the coating **214** may be provided on a single one of the plurality of support elements **210**, or multiple of the plurality of support elements **210**, optionally, all of the plurality of support elements **210**.

[0103] The coating **214** of at least one of the plurality of support elements **210** may otherwise be referred to as a support member coating. As already described, the coating **214** may reduce wear of the at least one support element **210**. It is beneficial to reduce wear of the at least one support element **210** because this can increase the usable life of the substrate holder **200** so that it can be used to process more substrates.

[0104] Additionally, as shown in FIG. 5, the first seal member **220** may comprise a coating **224**. The coating **224** may have the characteristics described above. As shown in FIG. 5, the coating **224** may form the upper surface **221** of the first seal member **220**. In other words, the coating **224** may be provided on a distal end of a protrusion forming the first seal member **220**. The coating **224** may provide a layer of protection on the end of the first seal member **220**. When the coating **224** is

provided on the first seal member **220**, the contact region **222** of the first seal member **220** may be on the coating **224**. The coating **224** on the first seal member **220** may otherwise be referred to as a seal member coating.

[0105] The coating **224** may reduce wear of the first seal member **220**. It is beneficial to reduce wear of the first seal member **220** because this means that the first seal member **220** may continue to function as a seal more efficiently for a larger number of substrates **W** being processed than if no coating is provided. Additionally, if the first seal member **220** is worn down, then the substrate **W** may contact the at least one support element **210** during loading and unloading, which may reduce the useful life of the substrate holder **200**. Thus, it is beneficial to prevent wear of the first seal member **220** to protect the at least one support element **210** for as long as possible/for processing of as many substrates as possible.

[0106] As shown in FIG. 5, the coating **214** may be provided on the at least one of the plurality of support elements **210** and the coating **224** on the first seal member **220**. However, it is not necessary to provide multiple portions of the substrate holder **200** with a coating. Thus, for example, a coating may only be provided on one or the other, i.e. either the first seal member **220**, or at least one of the plurality of support elements **210**.

[0107] Although the above features may reduce the wear on the outermost support element **210**, this could be improved by changing the shape of the contact region **222**. Additionally or alternatively to the above features, the contact region **222** of the first seal member **220** may be provided with a specific geometry. For example, a profile of the contact region **222**, in a cross section through the first seal member **220** in a radial direction, may have a shape which is configured such that during the unloading of the substrate **W**, the substrate **W** contacts the seal first member **220** via at least two different points of the profile. An example of the contact region **222** which is configured such that the substrate **W** contacts the first seal member **220** via at least two different points during unloading is shown in FIG. 6A.

[0108] The profile of the contact region **222** being shaped in such a way means that either the substrate **W** comes into contact with an area rather than a single point in the cross section through the first seal member **220** (as was shown in FIGS. 3A, 3B and 4). Additionally or alternatively, the substrate **W** may interact with the contact region **222** via various different points, for example the contact point may change during unloading of the substrate **W**, as will be described in some of the examples below.

[0109] Having the substrate **W** contact the first seal member **220** via at least two different points on the profile is beneficial because the local stresses on the first seal member **220** can be reduced. This is because there is an increased area of contact between the substrate **W** and the first seal member **220** and/or force from the substrate **W** is applied to different points of the first seal member **220** during the loading and/or unloading process. Although different geometries may be provided, the different geometries provide a contact between the substrate **W** and the first seal member **220** at multiple points which spreads the force and reduces the local stresses. Thus, this reduces the forces acting on the underneath side of the substrate **W**. In turn, this reduces the formation of scratches on the under surface of the substrate **W** which might produce particles which contaminate the system. Thus, providing such a contact region **222** can be beneficial in reducing contamination.

[0110] Various different geometries of the profile may be provided. For example the profile may be linear from the upper surface **221** of the first seal member **220** to the radially outer edge **223** of the first seal member **220**. This is shown in FIG. 6A, in which the contact region **222** is formed by a sloped portion having an angle θ . In other words, the first seal member **220** may have a chamfered edge forming the contact region **222**. The linear profile from the upper surface **221** of the first seal member **220** to the radially outer edge **223** of the first seal member **220** may be at a negative gradient between approximately 0.15 microns per millimeter to 3 microns per millimeter relative to the upper surface **221** of the first seal member **220**.

[0111] As with the first seal member **220** depicted in FIG. 4, the distance between the contact

region **222** and the support element **210** may be defined by a distance **D** in the radial direction shown in FIG. **6A**. The distance may additionally or alternatively be defined by the distance **y1** between the distal end surface **211** of the support element **210** and the upper surface **221** of the first seal member **220**. This may be the same as the distance **y** referred to in FIG. **4** and described above. Both of these distances will affect how the substrate **W** interacts with each of these components during unloading.

[0112] The distance **x1** may be within the range defined above for **x**. The distance **x** is the full length of the first seal member **220**. Additionally or alternatively, the distance **x2** may be within the range defined above for **x**. The distance **x2** is the length of the upper surface **221** of the first seal member **220** in the radial direction. In other words, the distance **x2** is the length of the first seal member **220** minus the length of the contact region **222** in the radial direction. It may be beneficial for **x2** to be above a certain value. The upper surface **221** provides the function of restricting gas/fluid radially inwards of the first seal member **220** and/or providing a low pressure region between the first seal member **220** and the second seal member **240** and/or providing a pressure drop radially inwards of the first seal member **220**. Therefore, the part of the upper surface **211** (having length **x2**) should be long enough such that the first seal member **220** can provide this function.

[0113] As described above, the coating **224** may be provided on the upper surface of the first seal member **220**. As shown in FIG. **6B**, the coating **224** may only be provided on the contact region **222**, where it may have the greatest effect. Thus, the coating **224** may be formed as part of the first seal member **220** and may form the contact region **222** as described above and below.

[0114] In an embodiment, the profile may comprise multiple linear portions from an upper surface **221** of the first seal member **220** to a radially outer edge **223** of the first seal member **220**. This is shown in FIGS. **7A**, **7B** and **7C**. In an embodiment, the shape of the profile may be curved from an upper surface **221** of the first seal member **220** to a radially outer edge **223** of the first seal member **220**. This is shown in FIGS. **7D**, **7E** and **7F**. Additionally or alternatively, the outer edge of the first seal member **220** may be rounded. This could be a rounded chamfer on an outer edge which forms the contact region **222**. The shape of the profile may be part of an ellipse or circle. For example, the shape of the profile may be part of the elliptical circle as depicted in FIG. **7D**. The shape of the profile may be essentially step-shaped as shown in FIGS. **7F** and **7G**. Any of the shapes which provide multiple contact points will decrease local stress on the substrate **W** compared to a single point contact in cross-section. The substrate **W** may contact the contact region **222** via a line contact, e.g. when the edge is curved, there is more than a single point in contact between the substrate **W** and the first seal member **220** such that a line of contact would be seen in the cross-section. The shapes with multiple discrete contact points, rather than a line contact will generally have a smaller overall contact area and will wear faster. The shapes shown in FIGS. **7A-7G** are examples of shapes which may be particularly advantageous with specific substrates and/or systems and/or substrate unload settings/sequences. Some of these shapes may have improved manufacturability and/or may have improved effects on properties of used substrates **W**, such as reducing warpage of the substrates **W**.

[0115] It is beneficial to make the surface of the contact region **222** as smooth as possible. This reduces local stresses on the under surface of the substrate **W**. Thus, the contact region **222** may be configured to reduce frictional forces between the substrate **W** and the first seal member **220** when they interact. For example, the contact region **222** may be polished.

[0116] The various different profiles shown in FIGS. **6A** and **7A-7G** mean that the contact region **222** can provide an area of contact between the substrate **W** and the first seal member **220**. This is beneficial because it distributes to force applied to the first seal member **220** and the substrate **W** and means that local stresses are reduced to reduce or prevent the formation of scratches on an under surface of the substrate **W**, i.e. to reduce or prevent damage to the under surface of the substrate **W**. The area of contact can be provided by multiple discrete contact points or the line

contact in cross-section.

[0117] Although not depicted in the various different profiles shown in FIGS. 7A-7G, any of seal members having these profiles may have a coating **224** as described above.

[0118] The first seal member **220** being configured to surround and be positioned radially outward of the plurality of support elements **210** means that all of the support elements **210** are radially inward of the first seal member **220** in plan. Thus, the first seal member **220** can form an outermost point of contact with the under surface of the substrate W during loading and/or unloading. This allows the wear on the support elements **210** to be reduced as described above. The first seal member **220** may surround the support elements **210** as a discrete member around all of the support elements **210** in plan, for example, the first seal member **220** may be circular in plan. The first seal member **220** may not have a uniform cross-section and therefore, the shape of the first seal member **220** as shown in FIG. 4-6, 7A-7G, **8** or **9** may vary. The first seal member **220** may optionally have gaps, such that the first seal member **220** may be provided by multiple discrete members around all of the support elements **210**.

[0119] Due to the liquid near this part of the system, it is possible that the space between the under surface of the substrate W and the main body **201** of the substrate holder **200** may have a humid atmosphere. The disadvantage of a humid atmosphere is the possibility of oxidation of the support elements **210**. Oxidation of the support elements **210** is deleterious as this reduces the achievable flatness of the substrate W supported by the support elements **210**. The substrate holder **200** may comprise at least one extraction opening **230** formed in the main body **201** for the extraction of fluid into the main body **201** from between the main body surface **202** and the substrate W. The at least one extraction opening **230** may be part of the seal mechanism. Extraction openings **230** can be provided as described below to help avoid having a humid atmosphere between the main body surface **202** and the substrate W.

[0120] The at least one extraction opening **230** may be arranged radially inward and adjacent to the first seal member **220**. Thus, there may not be any other features, such as support elements **210**, between the at least one extraction opening **230** and the first seal member **220**. The extraction opening **230** may be connected to an under pressure source. Thereby any liquid which reaches the extraction opening **230** may be extracted through the main body **201**. This means that the liquid is restricted from entering further into the space between the main body surface **202** and the substrate W. The extraction opening **230** can also extract gas, for example when there is no liquid present to be extracted. A mixture of liquid and gas can be extracted through the extraction opening **230**. The at least one extraction opening **230** may be used to help provide the pressure drop and/or low pressure region described above.

[0121] The at least one extraction opening **230** may be formed by several openings. The extraction openings **230** may be spaced apart from one another all the way round the first seal member **220**. The extraction opening **230** may be discreet openings in the main body surface **202**. Alternatively, the extraction opening **230** may be a groove formed in the main body surface **202**. Alternatively, the groove may be formed in the main body surface **202** of the extraction openings **230** may emerge from the main body **202** at the bottom of the groove. The groove may be segmented with one or more openings in each segment. The segments may be seen as a plurality of recesses.

[0122] By connecting the at least one extraction opening **230** to an under pressure, liquid which does find its way to the edge of the substrate W can be removed through the extraction openings **230**. Once the edge of the substrate W is no longer covered in liquid, the under surface of the substrate W is dried as the liquid is removed.

[0123] As described above, the substrate holder **200** may additionally comprise the second seal member **240**. Although FIGS. 4, 5, 6A, 6B, **8** and **9** depict the second seal member **240**, this member is optional and may not be provided with the first seal member **220**. The second seal member **240** may be positioned radially inward of the at least one extraction opening **230** (if provided). The second seal member **240** may be positioned radially outward of the support

elements **210**. The second seal member **240** may be configured to surround the at least one support element **210**. Thus, all of the support elements **210** may be radially inward of the second seal member **240**. Alternatively, at least one of the support elements **210** may be radially outward of the second seal member **240**. In other words, the second seal member **240** may be radially inwards of one or more support elements **210**. For example, at least the radially outermost support element **210** may be positioned between the first seal member **220** and the second seal member **240**. The at least the radially outermost support element **210** may be arranged alternately with the at least one extraction opening **230** in a line surrounding the second seal member **240**.

[0124] Additionally or alternatively to the embodiments described above, the substrate holder **200** may comprise at least one further member **250**. The further member **250** may have a contact region **252** configured to contact the substrate W during loading or unloading of the substrate W. The contact region **252** of the further member **250** may be similar to, and have similar characteristics as described above for the contact region **222** of the first seal member **220**. The further member **250** may be provided in addition to the seal unit/first seal member **220** described above. In this embodiment, both the first seal member **220** and the further member **250** may be configured to contact the substrate W during loading and unloading of the substrate W. The further member **250** may have a third height, the third height being less than the first height. In other words, the support element **210** may be taller than the further member **250**.

[0125] The at least one further member **250** may be referred to below as the further member **250**, but it will be understood that references to the further member may also include multiple further members. Thus, the further member **250** may be formed by multiple separate portions or protrusions.

[0126] The further member **250** may provide a similar supporting function to the first seal member **220** described above. Thus, the further member **250** may be configured to contact the substrate W during loading and/or unloading of the substrate W. By adding a further member **250** radially outwards of the at least one support element **210**, damage to the at least one supporting elements **210** can be reduced or prevented. The further member **250** may act as a sacrificial burl/region.

[0127] In further detail, the substrate holder **200** may comprise the further member **250** projecting from the main body surface **202** and having an upper surface **251**. The at least one further member **250** may be positioned radially outward of and surrounding the first seal member **220**. The upper surface **251** of the further member **250** may have a contact region **252** configured to contact the substrate W during loading and/or unloading of the substrate W. A position of the contact region **252** of the further member **250** is arranged at a distance from the plurality of support elements **210** sufficient enough such that during the loading and/or unloading of the substrate W, a force applied to the further member **250** by the substrate W is greater than a force applied to the plurality of support elements **210** by the substrate W.

[0128] The further member **250** may comprise a coating **254** as described above. Thus, the coating may be formed of diamond-like carbon (DLC, e.g. a-CH), diamond, silicon carbide (e.g. SiSiC or SiC), boron nitride (BN) or boron carbon nitride (BCN). The coating **254** may form the upper surface **251** of the further member **250** and the contact region **252** of the further member **250** may be on the coating **254**. The coating **254** may have other characteristics, such as thickness, etc. as described above in relation to the seal member coating **224** and/or the support member coating **214**. The coating **254** of the further member **250** may otherwise be referred to as the further member coating.

[0129] The coating **254** is shown in FIG. 8. However, the further member **250** could be provided in combination with the first seal member **220**, as described above, without the coating **254**. The coating **254** of the further member **250** may only be provided on the contact region **252** of the further member **250**.

[0130] In another embodiment, the substrate holder **200** may comprise an alternative seal member **260** and a further member **250**. The alternative seal member **260** may replace the first seal member

220 described above. In this embodiment, only the further member **250** may have a contact region **252** configured to contact the substrate **W** during loading and/or unloading of the substrate **W**. In other words, in this embodiment, the alternative seal member **260** is not configured to contact the substrate **W** during loading and/or unloading of the substrate **W** as in the above described embodiments. For example, the alternative seal member **260** may be positioned such that it does not contact the substrate **W** during loading or unloading, e.g. the alternative seal member **260** may be too far radially inwards to contact the substrate **W** during loading and/or unloading. The alternative seal member **260** may thus provide a seal, e.g. by reducing or affecting gas/fluid flow as described above in relation to the first seal member **220**, but does not contact the substrate **W** during loading and/or unloading as is done by the first seal member **220**.

[0131] In further detail, the substrate holder **200** comprises a main body **201**, a plurality of support elements **210**, a seal unit and at least one further member **250**. The main body **201** has a main body surface **202**. The plurality of support elements **210** project from the main body surface **202**. Each support element **210** may have a distal end surface **211** configured to support the substrate **W** and a first height. The seal unit may be configured to restrict the passage of liquid and/or gas between the substrate **W** and the main body surface **202** radially inwards past the seal unit. The seal unit may comprise a first seal member **220** projecting from the main body surface **202**. The first seal member **220** may have a second height less than the first height. The first seal member **220** may be positioned radially outwards of and surrounding the plurality of support elements **210**. The at least one further member **250** projects from the main body surface **202** and has an upper surface **251**. The at least one further member **250** may be positioned radially outward of and surrounding plurality of support elements **210**. Additionally, the at least one further member **250** may be positioned radially outward of and surrounding the seal unit. The at least one further member **250** may comprise a coating **254** forming the upper surface **251** of the further member **250**. The coating **254** may have a contact region **252** configured to contact the substrate **W** during loading and/or unloading of the substrate **W**. The coating **254** may be made of diamond-like carbon (DLC, e.g. a-CH), diamond, silicon carbide (e.g. SiSiC or SiC), boron nitride (BN) or boron carbon nitride (BCN). A position of the contact region **252** of the further member **250** may be arranged at a distance from the plurality of support elements **210** sufficient enough such that during the loading and/or unloading of the substrate **W**, a force applied to the further member **250** by the substrate **W** is greater than a force applied to the plurality of support elements **210** by the substrate **W**.

[0132] In this embodiment, the seal unit may comprise an alternative seal member **260** as described above. The alternative seal member **260** may project from the main body surface **202**. The alternative seal member **260** may be radially outwards of the plurality of supports elements **210**. The alternative seal member **260** may be surrounding the plurality of support elements **210**. The alternative seal member **260** may function in the same way as the first seal member **220** described above. However, in this embodiment, the alternative seal member **260** may be configured such that it does not generally contact the substrate **W** during loading and/or unloading. The seal unit may comprise a second seal member **240** as described above. Thus, the second seal member **240** may project from the main body surface and may be positioned radially inwards of the alternative seal member **260**.

[0133] In either of the embodiments comprising the further member **250** may have similar characteristics to the first seal member **220** described above. For example, the further member **250** may have a contact region having a profile as described above in relation to the first seal member **220** in accordance with FIGS. 6A, 6B and 7A-7G. In further detail, the profile of the contact region **252** of the further member **250**, in a cross-section through the further member **250** in a radial direction, may have a shape which is configured such that during the loading and/or unloading of the substrate **W**, the substrate **W** contacts the further member **250** via at least two different points of the profile. The further member **250** may comprise a coating **254** only on the contact region **252** having the profile, as described for the first seal member **220** as shown in FIG. 6B.

[0134] The further member **250** may be provided in the shape of a continuous ring. In other words, the further member **250** may be circular in plan, or more specifically ring-shaped or annular shaped. Thus, the further member **250** may have an annular shape. The further member **250** may comprise a plurality of segments and may optionally be a segmented ring. In the segmented ring, there may be multiple further member portions with a gap between each neighboring further member portion. The further member portions may be referred to as radial spokes. The gap between neighboring further member portions may be the same length or shorter than the length of either or both of the neighboring portions. In other words, the distance between each further member portion may be the same as, or less than, the width of one or both of the neighboring further member portions. At least one of the gaps between neighboring further member portions, i.e. the spacing between neighboring portions, may be in the order of tens or hundreds of microns. At least one of the gaps between neighboring further member portions may be as narrow as approximately 10 microns. At least one of the gaps may be between 0.5-5 mm. Some or all of the gaps may have these dimensions. Providing small gaps may be advantageous is that any contamination, for example from interaction between the further member **250** and the underside of the substrate **W** can be caught in the gaps whilst still providing a relatively large contact area.

[0135] The further member **250** may be provided by a row of multiple individual burls or protrusions which are spaced to form a ring shape in plan. In other words, the further member **250** may comprise a plurality of further support elements. For example, the individual burls or protrusions may have a diameter of approximately 100-1000 microns. The distance from the middle of one burl or protrusion to the middle of a neighboring burl or protrusion may be approximately 1-3 mm. The upper surface **251** of the further member **250** may be slightly rounded or polished as described in relation to the first seal member **220** above, to reduce wear of the further member **250**.

[0136] The further member **250** may have a height (the third height) which is less than the height of the at least one support element **210**. This means that the further member **250** can take the load during the loading and unloading of the substrate **W**. However, during use, such as during exposure of the substrate **W**, the further member **250** may not be in contact with the substrate **W**. The distance between the further member **250** and the at least one support element **210** may be optimized as described above in FIG. 4 for the first seal member **220**.

[0137] The position of the contact region **252** of the further member **250** relative to the support elements **210** may be controlled in various different ways. For example, as shown in FIG. 9, the main dimensions relate to the distance between a radially outer edge **212** of distal end surface **211** of the radially outermost support elements **210** and an outer upper edge of the upper surface **251** of the further member **250**. The dimensions relate to these specific parts of the support element **210** and the further member **250** because these are the parts of these components which will come into contact with the under surface of the substrate **W** during loading and/or unloading of the substrate **W**.

[0138] The distance may be defined by a distance **D** in the radial direction. The distance may be additionally or alternatively defined by the distance **y** between the distal end surface **211** of the support element **210** and the upper surface **251** of the further member **250**. Both of these distances will affect how the substrate **W** interacts with each of these components during loading and/or unloading.

[0139] In this example, the contact region **252** is shown as an edge contact point in the cross section. Thus, in this embodiment, the contact region **252** is formed by the same contact point around the circumference of the further member **250**. This contact region **252** may be similar to the contact region for the first seal member **220** shown in FIG. 4. The position of the contact region **252** with respect to the support element **210** is configured to reduce the wear of the support element **210** during unloading of the substrate **W**.

[0140] In an embodiment the radial distance **D** from a radially outer edge **212** of the distal end

surface **211** to the contact region **252** is greater than 1,000 microns, and preferably greater than 1,500 microns. The radial distance **D** is preferably between approximately 1000-3000 microns, i.e. 1-3 mm. This means that the contact region **252** can be far enough away from the support element **210** to reduce contact between the support elements **210** and the substrate **W** during loading and/or unloading. Additionally or alternatively, the difference in height between radially outermost support element **210** and the further member **250**, shown by **y** in FIG. 9, is between approximately 0.5 microns and 5 microns. Preferably, the difference in height is greater than or equal to 3 microns to reduce the likelihood of the further member **250** contacting the underside of the substrate **W** during exposure of the substrate **W**. The difference in height between the radially outermost support element **210** and the further member **250** is the distance between the distal end surface **211** and the upper surface **251** of the further member **250** in a **y** direction, wherein the **y** direction is orthogonal to a plane including the radial direction. Having a difference in height can also reduce contact between the support elements **210** and the substrate **W** during loading and/or unloading.

[0141] Providing the contact region **252** at such a distance means that during loading and/or unloading of the substrate **W**, the substrate **W** will have greater interaction with the further member **250** rather than the radially outermost support elements **210**. Effectively, this means that the further member **250** is used as a sacrificial wear area. This can lead to significant reduction in the wear of the outermost support elements **210**. The distance between the radially outer edge **212** and the contact region **252** can be optimized in the radial direction and/or the **y** direction to minimize friction between the outermost support elements **210** and the substrate **W** during loading and/or unloading the substrate **W**. The optimum values for the distance **D** and the distance **y** may vary depending on the substrate holder **200** and/or the substrate **W** and/or the applications being applied to the substrate **W**.

[0142] As indicated above, the substrate holder **200** may comprise at least one support element **210** between the first seal member **220** and the second seal member **240**. This is shown in FIG. 10. Thus, the outermost support element **210** may be provided adjacent to the first seal member **220** and the second seal member **240**. Therefore, the second seal member **240** may only surround some, but not all, of the support elements **210**.

[0143] In this instance, as with the first seal member **220** depicted in FIG. 4, the distance between the contact region **222** and the support element **210** may be defined by a distance **D** in the radial direction shown in FIG. 10. This may be the same value/range as the distance **D** referred to in FIG. 4 and described above. The distance may additionally or alternatively be defined by the distance **y** between the distal end surface **211** of the support element **210** and the upper surface **221** of the first seal member **220**. This may be the same value/range as the distance **y** referred to in FIG. 4 and described above. The distance **x** is the full length of the first seal member **220**. This may be the same values/range as the distance **x** referred to in FIG. 4 and described above. All of these distances will affect how the substrate **W** interacts with each of these components during unloading.

[0144] Multiple support elements **210** may be provided between the first seal member **220** and the second seal member **240**. Optionally, at least one extraction opening **230** may also be provided. For example, support elements **210** and extraction openings **230** may be alternated in the space between the first seal member **220** and the second seal member **240**. In other words, FIG. 10 shows a cross section through part of the substrate holder **200** through an outermost support element **210** between the first seal member **220** and second seal member **240**, however, at a different radial position, a similar cross section may show an extraction opening **230** between the first seal member **220** and the second seal member **240** as in FIG. 4.

[0145] At least one outermost support element **210** may also be provided in a similar position in other embodiments. For example, the outermost support element **210** may be provided between the first seal member **220** and the second seal member **240** when a further member **250** is provided as in FIG. 8 or between the alternative seal member **260** and the second seal member **240** in FIG. 9.

These members may comprise a contact region **222**, **252** and/or a coating **254** as described in any of the embodiments or variations described above.

[0146] As described above the substrate holder **200** may be configured to control the pressure between the main body **201** and the substrate W when the substrate W is being unloaded. This may be done in various ways and any known method/system may be used. An embodiment of the present invention may comprise a lithographic apparatus as described in any of the above examples of variations. The lithographic apparatus may comprise a substrate holder **200** configured to support the substrate according to any of the described embodiments or variations.

[0147] Although specific reference may be made in this text to the use of a lithographic apparatus in the manufacture of ICs, it should be understood that the lithographic apparatus described herein may have other applications. Possible other applications include the manufacture of integrated optical systems, guidance and detection patterns for magnetic domain memories, flat-panel displays, liquid-crystal displays (LCDs), thin-film magnetic heads, etc.

[0148] Although specific reference may be made in this text to embodiments of the invention in the context of a lithographic apparatus, embodiments of the invention may be used in other apparatus. Embodiments of the invention may form part of a mask inspection apparatus, a metrology apparatus, or any apparatus that measures or processes an object such as a wafer (or other substrate) or mask (or other patterning device). These apparatus may be generally referred to as lithographic tools. Such a lithographic tool may use vacuum conditions or ambient (non-vacuum) conditions.

[0149] Although specific reference may have been made above to the use of embodiments of the invention in the context of optical lithography, it will be appreciated that the invention, where the context allows, is not limited to optical lithography and may be used in other applications, for example imprint lithography.

[0150] The drawings are intended to illustrate the various features described above. The drawings are not to scale. The relative widths and heights of different features may vary with respect to other features. For example, the further member **250** is shown to be narrower than the first seal member **220** and the second seal member **240**. However, the further member **250** may be the same width (i.e. same length in the x direction), or may be wider (i.e. have a larger length in the x direction).

[0151] Embodiments are provided according to the following clauses:

1. A substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: [0152] a main body having a main body surface; [0153] a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; [0154] a seal unit comprising a first seal member projecting from the main body surface, the first seal member having an upper surface and a second height less than the first height and being positioned radially outward of and surrounding the plurality of support elements, the upper surface having a contact region configured to contact the substrate during loading and/or unloading of the substrate; and [0155] wherein a position of the contact region is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the first seal member by the substrate is greater than a force applied to the plurality of support elements by the substrate.

2. The substrate holder of clause 1, wherein the contact region is positioned adjacent to a radially outer edge of the first seal member and the radial distance from a radially outer edge of the distal end surface to the contact region is greater than 1,000 microns and preferably, greater than 1,500 microns, and/or wherein the length of the first seal member in a radial direction is greater than 300 microns, and preferably, greater than 500 microns.

3. The substrate holder of clause 1 or clause 2, wherein a profile of the contact region, in a cross section through the first seal member in a radial direction, has a shape which is configured such that during the loading and/or unloading of the substrate, the substrate contacts the first seal

member via at least two different points of the profile, and/or the substrate holder further comprising at least one further member projecting from the main body surface and having an upper surface, the at least one further member being positioned radially outward of and surrounding the seal unit, the upper surface of the further member having a contact region configured to contact the substrate during loading and/or unloading of the substrate, wherein a position of the contact region of the further member is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the further member by the substrate is greater than a force applied to the plurality of support elements by the substrate.

4. The substrate holder of any of clauses 1-3, wherein the plurality of support elements, the first seal member, or both comprise a coating made of diamond-like carbon, diamond, silicon carbide, boron nitride or boron carbon nitride, and the coating forms the distal end surface of the plurality of support elements and/or forms the upper surface of the first seal member, and the contact region of the first seal member is on the coating, and/or the at least one further member comprising a coating made of diamond-like carbon, diamond, silicon carbide, boron nitride or boron carbon nitride, wherein the coating forms the upper surface of the further member and the contact region of the further member is on the coating of the further member.

5. A substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: [0156] a main body having a main body surface; [0157] a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; [0158] a seal unit comprising a first seal member projecting from the main body surface, the first seal member having a second height less than the first height and being positioned radially outward of and surrounding the plurality of support elements, at least one further member projecting from the main body surface and having an upper surface, the at least one further member being positioned radially outward of and surrounding the seal unit, the at least one further member comprising a coating forming the upper surface of the further member, the coating having a contact region configured to contact the substrate during loading and/or unloading of the substrate, wherein the coating is made of diamond-like carbon, diamond, silicon carbide, boron nitride or boron carbon nitride; and [0159] wherein a position of the contact region of the further member is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the further member by the substrate is greater than a force applied to the plurality of support elements by the substrate.

6. The substrate holder of clause 4 or clause 5, wherein a profile of the contact region of the further member, in a cross section through the further member in a radial direction, has a shape which is configured such that during the loading and/or unloading of the substrate, the substrate contacts the further member via at least two different points of the profile.

7. The substrate holder of any of clauses 4-6, wherein the further member has a third height less than the first height, and/or wherein the further member has an annular shape and comprises a plurality of segments, and/or wherein the further member comprises a plurality of further support elements.

8. A substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: [0160] a main body having a main body surface; [0161] a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; [0162] a seal unit comprising a first seal member projecting from the main body surface, the first seal member having an upper surface and a second height less than the first height and being positioned radially outward of the plurality of and surrounding the support elements, and the upper surface having a contact region configured to contact the substrate during loading and/or unloading of the substrate; and [0163] wherein a profile of the contact region, in a cross section through the first seal member in a radial

- direction, has a shape which is configured such that during the loading and/or unloading of the substrate, the substrate contacts the first seal member via at least two different points of the profile.
9. The substrate holder of clause 3, clause 6 or clause 8, wherein the shape of the profile is linear from the upper surface of the first seal member to a radially outer edge of the first seal member, and/or wherein the shape of the profile comprises multiple linear portions from an upper surface of the first seal member to a radially outer edge of the first seal member, and/or wherein the shape of the profile is substantially step-shaped, and/or wherein the shape of the profile is curved from an upper surface of the first seal member to a radially outer edge of the first seal member.
10. The substrate holder of clause 9, wherein the linear profile from the upper surface of the first seal member to the radially outer edge of the first seal member is at a negative gradient between approximately 0.15 microns/mm to 3 microns/mm relative to the upper surface of the first seal member.
11. The substrate holder of clause 9, wherein the shape of the profile is part of an ellipse or circle.
12. The substrate holder of any of clauses 1-11, wherein the seal unit comprises a second seal member projecting from the main body surface and positioned radially inward of the first seal member, the second member configured to restrict the passage of liquid between the substrate and the main body surface radially inward past the second seal member, and/or wherein the first seal member is configured to provide a pressure drop radially inward of the first seal member relative to the pressure in a region radially outward of the seal unit.
13. The substrate holder of clause 12, wherein the first seal member is configured to provide a low pressure region between the first seal member and the second seal member.
14. The substrate holder of any of clauses 1-13, further comprising at least one extraction opening formed in the main body for the extraction of fluid into the main body from between the main body surface and the substrate, the at least one extraction opening being arranged radially inward of and adjacent to the first seal member, and/or wherein the substrate holder is configured to control the pressure between the main body and the substrate when the substrate is being loaded and/or unloaded.
15. A lithographic apparatus comprising the substrate holder configured to support the substrate according to any of clauses 1-14.

[0164] While specific embodiments of the invention have been described above, it will be appreciated that the invention may be practiced otherwise than as described. The descriptions above are intended to be illustrative, not limiting. Thus it will be apparent to one skilled in the art that modifications may be made to the invention as described without departing from the scope of the claims set out below.

Claims

1. A substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: a main body having a main body surface; a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; a seal unit comprising a first seal member projecting from the main body surface, the first seal member having an upper surface and a second height less than the first height and being positioned radially outward of and surrounding the plurality of support elements, the upper surface having a contact region configured to contact the substrate during loading and/or unloading of the substrate; and wherein a position of the contact region is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the first seal member by the substrate is greater than a force applied to the plurality of support elements by the substrate.
2. The substrate holder of claim 1, wherein the contact region is positioned adjacent to a radially outer edge of the first seal member and the radial distance from a radially outer edge of the distal

end surface to the contact region is greater than 1,000 microns and preferably, greater than 1,500 microns, and/or wherein the length of the first seal member in a radial direction is greater than 300 microns, and preferably, greater than 500 microns.

3. The substrate holder of claim 1, wherein a profile of the contact region, in a cross section through the first seal member in a radial direction, has a shape which is configured such that during the loading and/or unloading of the substrate, the substrate contacts the first seal member via at least two different points of the profile, and/or the substrate holder further comprising at least one further member projecting from the main body surface and having an upper surface, the at least one further member being positioned radially outward of and surrounding the seal unit, the upper surface of the further member having a contact region configured to contact the substrate during loading and/or unloading of the substrate, wherein a position of the contact region of the further member is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the further member by the substrate is greater than a force applied to the plurality of support elements by the substrate.

4. The substrate holder of claim 1, wherein the plurality of support elements, the first seal member, or both comprise a coating made of diamond-like carbon, diamond, silicon carbide, boron nitride or boron carbon nitride, and the coating forms the distal end surface of the plurality of support elements and/or forms the upper surface of the first seal member, and the contact region of the first seal member is on the coating, and/or the at least one further member comprising a coating made of diamond-like carbon, diamond, silicon carbide, boron nitride or boron carbon nitride, wherein the coating forms the upper surface of the further member and the contact region of the further member is on the coating of the further member.

5. A substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: a main body having a main body surface; a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; a seal unit comprising a first seal member projecting from the main body surface, the first seal member having a second height less than the first height and being positioned radially outward of and surrounding the plurality of support elements, at least one further member projecting from the main body surface and having an upper surface, the at least one further member being positioned radially outward of and surrounding the seal unit, the at least one further member comprising a coating forming the upper surface of the further member, the coating having a contact region configured to contact the substrate during loading and/or unloading of the substrate, wherein the coating is made of diamond-like carbon, diamond, silicon carbide, boron nitride or boron carbon nitride; and wherein a position of the contact region of the further member is arranged at a distance from the plurality of support elements sufficient enough such that during the loading and/or unloading of the substrate, a force applied to the further member by the substrate is greater than a force applied to the plurality of support elements by the substrate.

6. The substrate holder of claim 4, wherein a profile of the contact region of the further member, in a cross section through the further member in a radial direction, has a shape which is configured such that during the loading and/or unloading of the substrate, the substrate contacts the further member via at least two different points of the profile.

7. The substrate holder of claim 4, wherein the further member has a third height less than the first height, and/or wherein the further member has an annular shape and comprises a plurality of segments, and/or wherein the further member comprises a plurality of further support elements.

8. A substrate holder for use in a lithographic apparatus and configured to support a substrate, the substrate holder comprising: a main body having a main body surface; a plurality of support elements projecting from the main body surface, wherein each support element has a distal end surface configured to support the substrate and a first height; a seal unit comprising a first seal member projecting from the main body surface, the first seal member having an upper surface and

a second height less than the first height and being positioned radially outward of the plurality of and surrounding the support elements, and the upper surface having a contact region configured to contact the substrate during loading and/or unloading of the substrate; and wherein a profile of the contact region, in a cross section through the first seal member in a radial direction, has a shape which is configured such that during the loading and/or unloading of the substrate, the substrate contacts the first seal member via at least two different points of the profile.

9. The substrate holder of claim 3, wherein the shape of the profile is linear from the upper surface of the first seal member to a radially outer edge of the first seal member, and/or wherein the shape of the profile comprises multiple linear portions from an upper surface of the first seal member to a radially outer edge of the first seal member, and/or wherein the shape of the profile is substantially step-shaped, and/or wherein the shape of the profile is curved from an upper surface of the first seal member to a radially outer edge of the first seal member.

10. The substrate holder of claim 9, wherein the linear profile from the upper surface of the first seal member to the radially outer edge of the first seal member is at a negative gradient between approximately 0.15 microns/mm to 3 microns/mm relative to the upper surface of the first seal member.

11. The substrate holder of claim 9, wherein the shape of the profile is part of an ellipse or circle.

12. The substrate holder of claim 1, wherein the seal unit comprises a second seal member projecting from the main body surface and positioned radially inward of the first seal member, the second member configured to restrict the passage of liquid between the substrate and the main body surface radially inward past the second seal member, and/or wherein the first seal member is configured to provide a pressure drop radially inward of the first seal member relative to the pressure in a region radially outward of the seal unit.

13. The substrate holder of claim 12, wherein the first seal member is configured to provide a low pressure region between the first seal member and the second seal member.

14. The substrate holder of claim 1, further comprising at least one extraction opening formed in the main body for the extraction of fluid into the main body from between the main body surface and the substrate, the at least one extraction opening being arranged radially inward of and adjacent to the first seal member, and/or wherein the substrate holder is configured to control the pressure between the main body and the substrate when the substrate is being loaded and/or unloaded.

15. A lithographic apparatus comprising the substrate holder configured to support the substrate according to claim 1.
