

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279859

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Park; Kyungmin et al.

Packet Duplication Control

Abstract

Wireless communications are described. A central unit control plane (CU-CP) node of a base station may activate and/or deactivate packet duplication based on status information from self-monitoring, from a distributed unit (DU), from a wireless device, and/or from a central unit user plane (CU-UP) node. The CU-UP node and/or the DU may activate and/or deactivate packet duplication based on status information from self-monitoring, from each other, from the wireless device, and/or from the CU-CP node. The CU-UP node and/or the DU, after activating and/or deactivating packet duplication, may report the activation and/or deactivation to the CU-CP node.

Inventors: Park; Kyungmin (Vienna, VA), Dinan; Esmael Hejazi (McLean, VA), Jeon; Hyongsuk (Centreville, VA), Zhou; Hua (Vienna, VA), Babaei; Alireza (Fairfax, VA), Cirik; Ali Cagatay (Chantilly, VA)

Applicant: Comcast Cable Communications. LLC (Philadelphia, PA)

Family ID: 66542028

Appl. No.: 19/191453

Filed: April 28, 2025

Related U.S. Application Data

parent US continuation 18440302 20240213 parent-grant-document US 12316465 child US 19191453

parent US continuation 17572211 20220110 parent-grant-document US 11943066 child US 18440302

parent US continuation 16409260 20190510 parent-grant-document US 11258549 child US 17572211

us-provisional-application US 62669927 20180510

Publication Classification

Int. Cl.: **H04L1/1867** (20230101); **H04L5/00** (20060101); **H04W24/08** (20090101); **H04W76/11** (20180101); **H04W76/12** (20180101); **H04W76/27** (20180101); **H04W80/02** (20090101); **H04W80/08** (20090101)

U.S. Cl.:

CPC **H04L1/189** (20130101); **H04L5/0098** (20130101); **H04W24/08** (20130101); **H04W76/11** (20180201); **H04W76/12** (20180201); **H04W76/27** (20180201); **H04W80/02** (20130101); **H04W80/08** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of and claims priority to U.S. patent application Ser. No. 18/440,302, filed Feb. 13, 2024, which is a continuation of U.S. patent application Ser. No. 17/572,211, filed Jan. 10, 2022 (now U.S. Pat. No. 11,943,066), which is a continuation of U.S. patent application Ser. No. 16/409,260, filed May 10, 2019 (now U.S. Pat. No. 11,258,549), which claims the benefit of U.S. Provisional Application No. 62/669,927, filed May 10, 2018, each of which is hereby incorporated by reference in its entirety.

BACKGROUND

[0002] A wireless device may be configured to receive original and duplicated data packets. Packet duplication may increase reliability of data transmission by sending original packets via a first path and duplicated packets via a different second path. In some conditions, however, packet duplication may result in inefficient resource allocation and/or may decrease communication reliability.

SUMMARY

[0003] The following summary presents a simplified summary of certain features. The summary is not an extensive overview and is not intended to identify key or critical elements.

[0004] Activating and/or deactivating packet duplication, for communications to or from a wireless device, are described. Packet duplication may be activated and/or deactivated by a network node having status information for operations that may be affected by, and/or that may have an effect on, packet duplication. The status information may be obtained from other network nodes, and/or may originate from the network node controlling activation and/or deactivation of packet duplication. A network node controlling activation and/or deactivation of packet duplication may send one or more messages to other nodes indicating such activation and/or deactivation. For a functionally-split base station comprising a central unit control plane (CU-CP) node, a central unit user plane (CU-UP) node, and a distributed unit (DU), the CU-CP node may, for example, activate and/or deactivate packet duplication based on status information from self-monitoring, from the DU, from a wireless device, and/or from the CU-UP node. The CU-UP node may activate and/or deactivate packet duplication, for example, based on status information from the CU-CP node, from the DU, from the wireless device, and/or from self-monitoring. The CU-UP node may send one or more messages to the CU-CP node and/or the DU indicating such activation or deactivation. The DU may activate and/or deactivate packet duplication, for example, based on status information from the CU-CP node, from the CU-UP node, from the wireless device, and/or from self-monitoring. The DU node may send one or more messages to the CU-CP node indicating such activation or

deactivation.

[0005] These and other features and advantages are described in greater detail below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Some features are shown by way of example, and not by limitation, in the accompanying drawings. In the drawings, like numerals reference similar elements.

[0007] FIG. 1 shows an example radio access network (RAN) architecture.

[0008] FIG. 2A shows an example user plane protocol stack.

[0009] FIG. 2B shows an example control plane protocol stack.

[0010] FIG. 3 shows an example wireless device and two base stations.

[0011] FIG. 4A, FIG. 4B, FIG. 4C, and FIG. 4D show examples of uplink and downlink signal transmission.

[0012] FIG. 5A shows an example uplink channel mapping and example uplink physical signals.

[0013] FIG. 5B shows an example downlink channel mapping and example downlink physical signals.

[0014] FIG. 6 shows an example transmission time and/or reception time for a carrier.

[0015] FIG. 7A and FIG. 7B show example sets of orthogonal frequency division multiplexing (OFDM) subcarriers.

[0016] FIG. 8 shows example OFDM radio resources.

[0017] FIG. 9A shows an example channel state information reference signal (CSI-RS) and/or synchronization signal (SS) block transmission in a multi-beam system.

[0018] FIG. 9B shows an example downlink beam management procedure.

[0019] FIG. 10 shows an example of configured bandwidth parts (BWPs).

[0020] FIG. 11A and FIG. 11B show examples of multi connectivity.

[0021] FIG. 12 shows an example of a random access procedure.

[0022] FIG. 13 shows example medium access control (MAC) entities.

[0023] FIG. 14 shows an example RAN architecture.

[0024] FIG. 15 shows example radio resource control (RRC) states.

[0025] FIG. 16A shows an example duplication activation/deactivation Media Access Control (MAC) Control Element (CE).

[0026] FIG. 16B shows example values for a Logical Channel Identifier (LCID) field.

[0027] FIG. 17 shows example nodes that may be associated with PDCP packet duplication.

[0028] FIG. 18 shows an example initial context setup request message.

[0029] FIG. 19 shows an example method for PDCP packet duplication configuration, activation, and/or deactivation.

[0030] FIG. 20 shows an example bearer context setup request message.

[0031] FIG. 21 shows an example method for PDCP packet duplication configuration, activation, and/or deactivation.

[0032] FIG. 22 shows an example method for PDCP packet duplication configuration, activation, and/or deactivation.

[0033] FIG. 23 shows examples of communications among one or more elements.

[0034] FIGS. 24, 25, and 26 show examples of PDCP packet activation and/or deactivation and/or of related communications.

[0035] FIG. 27 shows an example method for activating and/or deactivating packet duplication.

[0036] FIG. 28 shows an example method for activating and/or deactivating packet duplication.

[0037] FIG. 29 shows an example method for activating and/or deactivating packet duplication.

[0038] FIG. 30 shows an example method for operating a wireless device.

[0039] FIG. 31 shows example elements of a computing device that may be used to implement any of the various devices described herein.

DETAILED DESCRIPTION

[0040] The accompanying drawings and descriptions provide examples. It is to be understood that the examples shown in the drawings and/or described are non-exclusive and that there are other examples of how features shown and described may be practiced.

[0041] Examples are provided for operation of wireless communication systems which may be used in the technical field of multicarrier communication systems. More particularly, the technology described herein may, for example, relate to wireless communication systems in multicarrier communication systems.

[0042] The following acronyms are used throughout the drawings and/or descriptions, and are provided below for convenience although other acronyms may be introduced in the detailed description: [0043] 3GPP 3rd Generation Partnership Project [0044] 5GC 5G Core Network [0045] ACK Acknowledgement [0046] AMF Access and Mobility Management Function [0047] ARQ Automatic Repeat Request [0048] AS Access Stratum [0049] ASIC Application-Specific Integrated Circuit [0050] BA Bandwidth Adaptation [0051] BCCH Broadcast Control Channel [0052] BCH Broadcast Channel [0053] BPSK Binary Phase Shift Keying [0054] BWP Bandwidth Part [0055] CA Carrier Aggregation [0056] CC Component Carrier [0057] CCCH Common Control CHannel [0058] CDMA Code Division Multiple Access [0059] CN Core Network [0060] CP Cyclic Prefix [0061] CP-OFDM Cyclic Prefix-Orthogonal Frequency Division Multiplex [0062] C-RNTI Cell-Radio Network Temporary Identifier [0063] CS Configured Scheduling [0064] CSI Channel State Information [0065] CSI-RS Channel State Information-Reference Signal [0066] CQI Channel Quality Indicator [0067] CSS Common Search Space [0068] CU Central Unit [0069] DC Dual Connectivity [0070] DCCH Dedicated Control Channel [0071] DCI Downlink Control Information [0072] DL Downlink [0073] DL-SCH Downlink Shared CHannel [0074] DM-RS DeModulation Reference Signal [0075] DRB Data Radio Bearer [0076] DRX Discontinuous Reception [0077] DTCH Dedicated Traffic Channel [0078] DU Distributed Unit [0079] EPC Evolved Packet Core [0080] E-UTRA Evolved UMTS Terrestrial Radio Access [0081] E-UTRAN Evolved-Universal Terrestrial Radio Access Network [0082] FDD Frequency Division Duplex [0083] FPGA Field Programmable Gate Arrays [0084] F1-C F1-Control plane [0085] F1-U F1-User plane [0086] gNB next generation Node B [0087] HARQ Hybrid Automatic Repeat reQuest [0088] HDL Hardware Description Languages [0089] IE Information Element [0090] IP Internet Protocol [0091] LCID Logical Channel Identifier [0092] LTE Long Term Evolution [0093] MAC Media Access Control [0094] MCG Master Cell Group [0095] MCS Modulation and Coding Scheme [0096] MeNB Master evolved Node B [0097] MIB Master Information Block [0098] MME Mobility Management Entity [0099] MN Master Node [0100] NACK Negative Acknowledgement [0101] NAS Non-Access Stratum [0102] NG CP Next Generation Control Plane [0103] NGC Next Generation Core [0104] NG-C NG-Control plane [0105] ng-eNB next generation evolved Node B [0106] NG-U NG-User plane [0107] NR New Radio [0108] NR MAC New Radio MAC [0109] NR PDCP New Radio PDCP [0110] NR PHY New Radio PHYsical [0111] NR RLC New Radio RLC [0112] NR RRC New Radio RRC [0113] NSSAI Network Slice Selection Assistance Information [0114] O&M Operation and Maintenance [0115] OFDM Orthogonal Frequency Division Multiplexing [0116] PBCH Physical Broadcast CHannel [0117] PCC Primary Component Carrier [0118] PCCH Paging Control CHannel [0119] PCell Primary Cell [0120] PCH Paging CHannel [0121] PDCCH Physical Downlink Control CHannel [0122] PDCP Packet Data Convergence Protocol [0123] PDSCH Physical Downlink Shared CHannel [0124] PDU Protocol Data Unit [0125] PHICH Physical HARQ Indicator CHannel [0126] PHY PHYsical [0127] PLMN Public Land Mobile Network [0128] PMI Precoding Matrix Indicator [0129] PRACH Physical Random Access CHannel [0130] PRB Physical Resource Block [0131] PSCell Primary Secondary Cell [0132] PSS Primary Synchronization Signal [0133] pTAG primary Timing Advance Group

[0134] PT-RS Phase Tracking Reference Signal [0135] PUSCH Physical Uplink Control CHannel [0136] PUSCH Physical Uplink Shared CHannel [0137] QAM Quadrature Amplitude Modulation [0138] QFI Quality of Service Indicator [0139] QoS Quality of Service [0140] QPSK Quadrature Phase Shift Keying [0141] RA Random Access [0142] RACH Random Access CHannel [0143] RAN Radio Access Network [0144] RAT Radio Access Technology [0145] RA-RNTI Random Access-Radio Network Temporary Identifier [0146] RB Resource Blocks [0147] RBG Resource Block Groups [0148] RI Rank indicator [0149] RLC Radio Link Control [0150] RRC Radio Resource Control [0151] RS Reference Signal [0152] RSRP Reference Signal Received Power [0153] SCC Secondary Component Carrier [0154] SCell Secondary Cell [0155] SCG Secondary Cell Group [0156] SC-FDMA Single Carrier-Frequency Division Multiple Access [0157] SDAP Service Data Adaptation Protocol [0158] SDU Service Data Unit [0159] SeNB Secondary evolved Node B [0160] SFN System Frame Number [0161] S-GW Serving GateWay [0162] SI System Information [0163] SIB System Information Block [0164] SMF Session Management Function [0165] SN Secondary Node [0166] SpCell Special Cell [0167] SRB Signaling Radio Bearer [0168] SRS Sounding Reference Signal [0169] SS Synchronization Signal [0170] SSS Secondary Synchronization Signal [0171] sTAG secondary Timing Advance Group [0172] TA Timing Advance [0173] TAG Timing Advance Group [0174] TAI Tracking Area Identifier [0175] TAT Time Alignment Timer [0176] TB Transport Block [0177] TC-RNTI Temporary Cell-Radio Network Temporary Identifier [0178] TDD Time Division Duplex [0179] TDMA Time Division Multiple Access [0180] TTI Transmission Time Interval [0181] UCI Uplink Control Information [0182] UE User Equipment [0183] UL Uplink [0184] UL-SCH Uplink Shared CHannel [0185] UPF User Plane Function [0186] UPGW User Plane Gateway [0187] VHDL VHSIC Hardware Description Language [0188] Xn-C Xn-Control plane [0189] Xn-U Xn-User plane [0190] Examples described herein may be implemented using various physical layer modulation and transmission mechanisms. Example transmission mechanisms may include, but are not limited to: Code Division Multiple Access (CDMA), Orthogonal Frequency Division Multiple Access (OFDMA), Time Division Multiple Access (TDMA), Wavelet technologies, and/or the like. Hybrid transmission mechanisms such as TDMA/CDMA, and/or OFDM/CDMA may be used. Various modulation schemes may be used for signal transmission in the physical layer. Examples of modulation schemes include, but are not limited to: phase, amplitude, code, a combination of these, and/or the like. An example radio transmission method may implement Quadrature Amplitude Modulation (QAM) using Binary Phase Shift Keying (BPSK), Quadrature Phase Shift Keying (QPSK), 16-QAM, 64-QAM, 256-QAM, and/or the like. Physical radio transmission may be enhanced by dynamically or semi-dynamically changing the modulation and coding scheme, for example, depending on transmission requirements and/or radio conditions.

[0191] FIG. 1 shows an example Radio Access Network (RAN) architecture. A RAN node may comprise a next generation Node B (gNB) (e.g., **120A**, **120B**) providing New Radio (NR) user plane and control plane protocol terminations towards a first wireless device (e.g., **110A**). A RAN node may comprise a base station such as a next generation evolved Node B (ng-eNB) (e.g., **120C**, **120D**), providing Evolved UMTS Terrestrial Radio Access (E-UTRA) user plane and control plane protocol terminations towards a second wireless device (e.g., **110B**). A first wireless device **110A** may communicate with a base station, such as a gNB **120A**, over a Uu interface. A second wireless device **110B** may communicate with a base station, such as an ng-eNB **120D**, over a Uu interface. The wireless devices **110A** and/or **110B** may be structurally similar to wireless devices shown in and/or described in connection with other drawing figures. The Node B **120A**, the Node B **120B**, the Node B **120C**, and/or the Node B **120D** may be structurally similar to Nodes B and/or base stations shown in and/or described in connection with other drawing figures.

[0192] A base station, such as a gNB (e.g., **120A**, **120B**, etc.) and/or an ng-eNB (e.g., **120C**, **120D**, etc.) may host functions such as radio resource management and scheduling, IP header compression, encryption and integrity protection of data, selection of Access and Mobility

Management Function (AMF) at wireless device (e.g., User Equipment (UE)) attachment, routing of user plane and control plane data, connection setup and release, scheduling and transmission of paging messages (e.g., originated from the AMF), scheduling and transmission of system broadcast information (e.g., originated from the AMF or Operation and Maintenance (O&M)), measurement and measurement reporting configuration, transport level packet marking in the uplink, session management, support of network slicing, Quality of Service (QoS) flow management and mapping to data radio bearers, support of wireless devices in an inactive state (e.g., RRC_INACTIVE state), distribution function for Non-Access Stratum (NAS) messages, RAN sharing, dual connectivity, and/or tight interworking between NR and E-UTRA.

[0193] One or more first base stations (e.g., gNBs **120A** and **120B**) and/or one or more second base stations (e.g., ng-eNBs **120C** and **120D**) may be interconnected with each other via Xn interface. A first base station (e.g., gNB **120A**, **120B**, etc.) or a second base station (e.g., ng-eNB **120C**, **120D**, etc.) may be connected via NG interfaces to a network, such as a 5G Core Network (5GC). A 5GC may comprise one or more AMF/User Plan Function (UPF) functions (e.g., **130A** and/or **130B**). A base station (e.g., a gNB and/or an ng-eNB) may be connected to a UPF via an NG-User plane (NG-U) interface. The NG-U interface may provide delivery (e.g., non-guaranteed delivery) of user plane Protocol Data Units (PDUs) between a RAN node and the UPF. A base station (e.g., a gNB and/or an ng-eNB) may be connected to an AMF via an NG-Control plane (NG-C) interface. The NG-C interface may provide functions such as NG interface management, wireless device (e.g., UE) context management, wireless device (e.g., UE) mobility management, transport of NAS messages, paging, PDU session management, configuration transfer, and/or warning message transmission.

[0194] A UPF may host functions such as anchor point for intra-/inter-Radio Access Technology (RAT) mobility (e.g., if applicable), external PDU session point of interconnect to data network, packet routing and forwarding, packet inspection and user plane part of policy rule enforcement, traffic usage reporting, uplink classifier to support routing traffic flows to a data network, branching point to support multi-homed PDU session, quality of service (QoS) handling for user plane, packet filtering, gating, Uplink (UL)/Downlink (DL) rate enforcement, uplink traffic verification (e.g., Service Data Flow (SDF) to QoS flow mapping), downlink packet buffering, and/or downlink data notification triggering.

[0195] An AMF may host functions such as NAS signaling termination, NAS signaling security, Access Stratum (AS) security control, inter Core Network (CN) node signaling (e.g., for mobility between 3rd Generation Partnership Project (3GPP) access networks), idle mode wireless device reachability (e.g., control and execution of paging retransmission), registration area management, support of intra-system and inter-system mobility, access authentication, access authorization including check of roaming rights, mobility management control (e.g., subscription and/or policies), support of network slicing, and/or Session Management Function (SMF) selection.

[0196] FIG. 2A shows an example user plane protocol stack. A Service Data Adaptation Protocol (SDAP) (e.g., **211** and **221**), Packet Data Convergence Protocol (PDCP) (e.g., **212** and **222**), Radio Link Control (RLC) (e.g., **213** and **223**), and Media Access Control (MAC) (e.g., **214** and **224**) sublayers, and a Physical (PHY) (e.g., **215** and **225**) layer, may be terminated in a wireless device (e.g., **110**) and in a base station (e.g., **120**) on a network side. A PHY layer may provide transport services to higher layers (e.g., MAC, RRC, etc.). Services and/or functions of a MAC sublayer may comprise mapping between logical channels and transport channels, multiplexing and/or demultiplexing of MAC Service Data Units (SDUs) belonging to the same or different logical channels into and/or from Transport Blocks (TBs) delivered to and/or from the PHY layer, scheduling information reporting, error correction through Hybrid Automatic Repeat request (HARQ) (e.g., one HARQ entity per carrier for Carrier Aggregation (CA)), priority handling between wireless devices such as by using dynamic scheduling, priority handling between logical channels of a wireless device such as by using logical channel prioritization, and/or padding. A

MAC entity may support one or multiple numerologies and/or transmission timings. Mapping restrictions in a logical channel prioritization may control which numerology and/or transmission timing a logical channel may use. An RLC sublayer may support transparent mode (TM), unacknowledged mode (UM), and/or acknowledged mode (AM) transmission modes. The RLC configuration may be per logical channel with no dependency on numerologies and/or Transmission Time Interval (TTI) durations. Automatic Repeat Request (ARQ) may operate on any of the numerologies and/or TTI durations with which the logical channel is configured. Services and functions of the PDCP layer for the user plane may comprise, for example, sequence numbering, header compression and decompression, transfer of user data, reordering and duplicate detection, PDCP PDU routing (e.g., such as for split bearers), retransmission of PDCP SDUs, ciphering, deciphering and integrity protection, PDCP SDU discard, PDCP re-establishment and data recovery for RLC AM, and/or duplication of PDCP PDUs. Services and/or functions of SDAP may comprise, for example, mapping between a QoS flow and a data radio bearer. Services and/or functions of SDAP may comprise mapping a Quality of Service Indicator (QFI) in DL and UL packets. A protocol entity of SDAP may be configured for an individual PDU session.

[0197] FIG. 2B shows an example control plane protocol stack. A PDCP (e.g., 233 and 242), RLC (e.g., 234 and 243), and MAC (e.g., 235 and 244) sublayers, and a PHY (e.g., 236 and 245) layer, may be terminated in a wireless device (e.g., 110), and in a base station (e.g., 120) on a network side, and perform service and/or functions described above. RRC (e.g., 232 and 241) may be terminated in a wireless device and a base station on a network side. Services and/or functions of RRC may comprise broadcast of system information related to AS and/or NAS; paging (e.g., initiated by a 5GC or a RAN); establishment, maintenance, and/or release of an RRC connection between the wireless device and RAN; security functions such as key management, establishment, configuration, maintenance, and/or release of Signaling Radio Bearers (SRBs) and Data Radio Bearers (DRBs); mobility functions; QoS management functions; wireless device measurement reporting and control of the reporting; detection of and recovery from radio link failure; and/or NAS message transfer to/from NAS from/to a wireless device. NAS control protocol (e.g., 231 and 251) may be terminated in the wireless device and AMF (e.g., 130) on a network side. NAS control protocol may perform functions such as authentication, mobility management between a wireless device and an AMF (e.g., for 3GPP access and non-3GPP access), and/or session management between a wireless device and an SMF (e.g., for 3GPP access and non-3GPP access).

[0198] A base station may configure a plurality of logical channels for a wireless device. A logical channel of the plurality of logical channels may correspond to a radio bearer. The radio bearer may be associated with a QoS requirement. A base station may configure a logical channel to be mapped to one or more TTIs and/or numerologies in a plurality of TTIs and/or numerologies. The wireless device may receive Downlink Control Information (DCI) via a Physical Downlink Control CHannel (PDCCH) indicating an uplink grant. The uplink grant may be for a first TTI and/or a first numerology and may indicate uplink resources for transmission of a transport block. The base station may configure each logical channel in the plurality of logical channels with one or more parameters to be used by a logical channel prioritization procedure at the MAC layer of the wireless device. The one or more parameters may comprise, for example, priority, prioritized bit rate, etc. A logical channel in the plurality of logical channels may correspond to one or more buffers comprising data associated with the logical channel. The logical channel prioritization procedure may allocate the uplink resources to one or more first logical channels in the plurality of logical channels and/or to one or more MAC Control Elements (CEs). The one or more first logical channels may be mapped to the first TTI and/or the first numerology. The MAC layer at the wireless device may multiplex one or more MAC CEs and/or one or more MAC SDUs (e.g., logical channel) in a MAC PDU (e.g., transport block). The MAC PDU may comprise a MAC header comprising a plurality of MAC sub-headers. A MAC sub-header in the plurality of MAC sub-headers may correspond to a MAC CE or a MAC SUD (e.g., logical channel) in the one or

more MAC CEs and/or in the one or more MAC SDUs. A MAC CE and/or a logical channel may be configured with a Logical Channel Identifier (LCID). An LCID for a logical channel and/or a MAC CE may be fixed and/or pre-configured. An LCID for a logical channel and/or MAC CE may be configured for the wireless device by the base station. The MAC sub-header corresponding to a MAC CE and/or a MAC SDU may comprise an LCID associated with the MAC CE and/or the MAC SDU.

[0199] A base station may activate, deactivate, and/or impact one or more processes (e.g., set values of one or more parameters of the one or more processes or start and/or stop one or more timers of the one or more processes) at the wireless device, for example, by using one or more MAC commands. The one or more MAC commands may comprise one or more MAC control elements. The one or more processes may comprise activation and/or deactivation of PDCP packet duplication for one or more radio bearers. The base station may send (e.g., transmit) a MAC CE comprising one or more fields. The values of the fields may indicate activation and/or deactivation of PDCP duplication for the one or more radio bearers. The one or more processes may comprise Channel State Information (CSI) transmission for one or more cells. The base station may send (e.g., transmit) one or more MAC CEs indicating activation and/or deactivation of the CSI transmission on the one or more cells. The one or more processes may comprise activation and/or deactivation of one or more secondary cells. The base station may send (e.g., transmit) a MA CE indicating activation and/or deactivation of one or more secondary cells. The base station may send (e.g., transmit) one or more MAC CEs indicating starting and/or stopping of one or more Discontinuous Reception (DRX) timers at the wireless device. The base station may send (e.g., transmit) one or more MAC CEs indicating one or more timing advance values for one or more Timing Advance Groups (TAGs).

[0200] FIG. 3 shows an example of base stations (base station 1, 120A, and base station 2, 120B) and a wireless device 110. The wireless device 110 may comprise a UE or any other wireless device. The base station (e.g., 120A, 120B) may comprise a Node B, eNB, gNB, ng-eNB, or any other base station. A wireless device and/or a base station may perform one or more functions of a relay node. The base station 1, 120A, may comprise at least one communication interface 320A (e.g., a wireless modem, an antenna, a wired modem, and/or the like), at least one processor 321A, and at least one set of program code instructions 323A that may be stored in non-transitory memory 322A and executable by the at least one processor 321A. The base station 2, 120B, may comprise at least one communication interface 320B, at least one processor 321B, and at least one set of program code instructions 323B that may be stored in non-transitory memory 322B and executable by the at least one processor 321B.

[0201] A base station may comprise any number of sectors, for example: 1, 2, 3, 4, or 6 sectors. A base station may comprise any number of cells, for example, ranging from 1 to 50 cells or more. A cell may be categorized, for example, as a primary cell or secondary cell. At Radio Resource Control (RRC) connection establishment, re-establishment, handover, etc., a serving cell may provide NAS (non-access stratum) mobility information (e.g., Tracking Area Identifier (TAI)). At RRC connection re-establishment and/or handover, a serving cell may provide security input. This serving cell may be referred to as the Primary Cell (PCell). In the downlink, a carrier corresponding to the PCell may be a DL Primary Component Carrier (PCC). In the uplink, a carrier may be an UL PCC. Secondary Cells (SCells) may be configured to form together with a PCell a set of serving cells, for example, depending on wireless device capabilities. In a downlink, a carrier corresponding to an SCell may be a downlink secondary component carrier (DL SCC). In an uplink, a carrier may be an uplink secondary component carrier (UL SCC). An SCell may or may not have an uplink carrier.

[0202] A cell, comprising a downlink carrier and optionally an uplink carrier, may be assigned a physical cell ID and/or a cell index. A carrier (downlink and/or uplink) may belong to one cell. The cell ID and/or cell index may identify the downlink carrier and/or uplink carrier of the cell (e.g.,

depending on the context it is used). A cell ID may be equally referred to as a carrier ID, and a cell index may be referred to as a carrier index. A physical cell ID and/or a cell index may be assigned to a cell. A cell ID may be determined using a synchronization signal transmitted via a downlink carrier. A cell index may be determined using RRC messages. A first physical cell ID for a first downlink carrier may indicate that the first physical cell ID is for a cell comprising the first downlink carrier. The same concept may be used, for example, with carrier activation and/or deactivation (e.g., secondary cell activation and/or deactivation). A first carrier that is activated may indicate that a cell comprising the first carrier is activated.

[0203] A base station may send (e.g., transmit) to a wireless device one or more messages (e.g., RRC messages) comprising a plurality of configuration parameters for one or more cells. One or more cells may comprise at least one primary cell and at least one secondary cell. An RRC message may be broadcasted and/or unicasted to the wireless device. Configuration parameters may comprise common parameters and dedicated parameters.

[0204] Services and/or functions of an RRC sublayer may comprise at least one of: broadcast of system information related to AS and/or NAS; paging initiated by a 5GC and/or an NG-RAN; establishment, maintenance, and/or release of an RRC connection between a wireless device and an NG-RAN, which may comprise at least one of addition, modification, and/or release of carrier aggregation; and/or addition, modification, and/or release of dual connectivity in NR or between E-UTRA and NR. Services and/or functions of an RRC sublayer may comprise at least one of security functions comprising key management; establishment, configuration, maintenance, and/or release of Signaling Radio Bearers (SRBs) and/or Data Radio Bearers (DRBs); mobility functions which may comprise at least one of a handover (e.g., intra NR mobility or inter-RAT mobility) and/or a context transfer; and/or a wireless device cell selection and/or reselection and/or control of cell selection and reselection. Services and/or functions of an RRC sublayer may comprise at least one of QoS management functions; a wireless device measurement configuration/reporting; detection of and/or recovery from radio link failure; and/or NAS message transfer to and/or from a core network entity (e.g., AMF, Mobility Management Entity (MME)) from and/or to the wireless device.

[0205] An RRC sublayer may support an RRC_Idle state, an RRC_Inactive state, and/or an RRC_Connected state for a wireless device. In an RRC_Idle state, a wireless device may perform at least one of: Public Land Mobile Network (PLMN) selection; receiving broadcasted system information; cell selection and/or re-selection; monitoring and/or receiving a paging for mobile terminated data initiated by 5GC; paging for mobile terminated data area managed by 5GC; and/or DRX for CN paging configured via NAS. In an RRC_Inactive state, a wireless device may perform at least one of: receiving broadcasted system information; cell selection and/or re-selection; monitoring and/or receiving a RAN and/or CN paging initiated by an NG-RAN and/or a 5GC; RAN-based notification area (RNA) managed by an NG-RAN; and/or DRX for a RAN and/or CN paging configured by NG-RAN/NAS. In an RRC_Idle state of a wireless device, a base station (e.g., NG-RAN) may keep a 5GC-NG-RAN connection (e.g., both C/U-planes) for the wireless device; and/or store a wireless device AS context for the wireless device. In an RRC_Connected state of a wireless device, a base station (e.g., NG-RAN) may perform at least one of: establishment of 5GC-NG-RAN connection (both C/U-planes) for the wireless device; storing a UE AS context for the wireless device; send (e.g., transmit) and/or receive of unicast data to and/or from the wireless device; and/or network-controlled mobility based on measurement results received from the wireless device. In an RRC_Connected state of a wireless device, an NG-RAN may know a cell to which the wireless device belongs.

[0206] System information (SI) may be divided into minimum SI and other SI. The minimum SI may be periodically broadcast. The minimum SI may comprise basic information required for initial access and/or information for acquiring any other SI broadcast periodically and/or provisioned on-demand (e.g., scheduling information). The other SI may either be broadcast,

and/or be provisioned in a dedicated manner, such as either triggered by a network and/or upon request from a wireless device. A minimum SI may be transmitted via two different downlink channels using different messages (e.g., MasterInformationBlock and SystemInformationBlockType1). Another SI may be transmitted via SystemInformationBlockType2. For a wireless device in an RRC_Connected state, dedicated RRC signaling may be used for the request and delivery of the other SI. For the wireless device in the RRC_Idle state and/or in the RRC_Inactive state, the request may trigger a random-access procedure.

[0207] A wireless device may report its radio access capability information, which may be static. A base station may request one or more indications of capabilities for a wireless device to report based on band information. A temporary capability restriction request may be sent by the wireless device (e.g., if allowed by a network) to signal the limited availability of some capabilities (e.g., due to hardware sharing, interference, and/or overheating) to the base station. The base station may confirm or reject the request. The temporary capability restriction may be transparent to 5GC (e.g., static capabilities may be stored in 5GC).

[0208] A wireless device may have an RRC connection with a network, for example, if CA is configured. At RRC connection establishment, re-establishment, and/or handover procedures, a serving cell may provide NAS mobility information. At RRC connection re-establishment and/or handover, a serving cell may provide a security input. This serving cell may be referred to as the PCell. SCells may be configured to form together with the PCell a set of serving cells, for example, depending on the capabilities of the wireless device. The configured set of serving cells for the wireless device may comprise a PCell and one or more SCells.

[0209] The reconfiguration, addition, and/or removal of SCells may be performed by RRC messaging. At intra-NR handover, RRC may add, remove, and/or reconfigure SCells for usage with the target PCell. Dedicated RRC signaling may be used (e.g., if adding a new SCell) to send all required system information of the SCell (e.g., if in connected mode, wireless devices may not acquire broadcasted system information directly from the SCells).

[0210] The purpose of an RRC connection reconfiguration procedure may be to modify an RRC connection, (e.g., to establish, modify, and/or release RBs; to perform handover; to setup, modify, and/or release measurements, for example, to add, modify, and/or release SCells and cell groups). NAS dedicated information may be transferred from the network to the wireless device, for example, as part of the RRC connection reconfiguration procedure. The RRCConnectionReconfiguration message may be a command to modify an RRC connection. One or more RRC messages may convey information for measurement configuration, mobility control, and/or radio resource configuration (e.g., RBs, MAC main configuration, and/or physical channel configuration), which may comprise any associated dedicated NAS information and/or security configuration. The wireless device may perform an SCell release, for example, if the received RRC Connection Reconfiguration message includes the sCellToReleaseList. The wireless device may perform SCell additions or modification, for example, if the received RRC Connection Reconfiguration message includes the sCellToAddModList.

[0211] An RRC connection establishment, reestablishment, and/or resume procedure may be to establish, reestablish, and/or resume an RRC connection, respectively. An RRC connection establishment procedure may comprise SRB1 establishment. The RRC connection establishment procedure may be used to transfer the initial NAS dedicated information and/or message from a wireless device to an E-UTRAN. The RRCConnectionReestablishment message may be used to re-establish SRB1.

[0212] A measurement report procedure may be used to transfer measurement results from a wireless device to an NG-RAN. The wireless device may initiate a measurement report procedure, for example, after successful security activation. A measurement report message may be used to send (e.g., transmit) measurement results.

[0213] The wireless device **110** may comprise at least one communication interface **310** (e.g., a wireless modem, an antenna, and/or the like), at least one processor **314**, and at least one set of program code instructions **316** that may be stored in non-transitory memory **315** and executable by the at least one processor **314**. The wireless device **110** may further comprise at least one of at least one speaker and/or microphone **311**, at least one keypad **312**, at least one display and/or touchpad **313**, at least one power source **317**, at least one global positioning system (GPS) chipset **318**, and/or other peripherals **319**.

[0214] The processor **314** of the wireless device **110**, the processor **321A** of the base station **1 120A**, and/or the processor **321B** of the base station **2 120B** may comprise at least one of a general-purpose processor, a digital signal processor (DSP), a controller, a microcontroller, an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) and/or other programmable logic device, discrete gate and/or transistor logic, discrete hardware components, and/or the like. The processor **314** of the wireless device **110**, the processor **321A** in base station **1 120A**, and/or the processor **321B** in base station **2 120B** may perform at least one of signal coding and/or processing, data processing, power control, input/output processing, and/or any other functionality that may enable the wireless device **110**, the base station **1 120A** and/or the base station **2 120B** to operate in a wireless environment.

[0215] The processor **314** of the wireless device **110** may be connected to and/or in communication with the speaker and/or microphone **311**, the keypad **312**, and/or the display and/or touchpad **313**. The processor **314** may receive user input data from and/or provide user output data to the speaker and/or microphone **311**, the keypad **312**, and/or the display and/or touchpad **313**. The processor **314** in the wireless device **110** may receive power from the power source **317** and/or may be configured to distribute the power to the other components in the wireless device **110**. The power source **317** may comprise at least one of one or more dry cell batteries, solar cells, fuel cells, and/or the like. The processor **314** may be connected to the GPS chipset **318**. The GPS chipset **318** may be configured to provide geographic location information of the wireless device **110**.

[0216] The processor **314** of the wireless device **110** may further be connected to and/or in communication with other peripherals **319**, which may comprise one or more software and/or hardware modules that may provide additional features and/or functionalities. For example, the peripherals **319** may comprise at least one of an accelerometer, a satellite transceiver, a digital camera, a universal serial bus (USB) port, a hands-free headset, a frequency modulated (FM) radio unit, a media player, an Internet browser, and/or the like.

[0217] The communication interface **320A** of the base station **1, 120A**, and/or the communication interface **320B** of the base station **2, 120B**, may be configured to communicate with the communication interface **310** of the wireless device **110**, for example, via a wireless link **330A** and/or via a wireless link **330B**, respectively. The communication interface **320A** of the base station **1, 120A**, may communicate with the communication interface **320B** of the base station **2** and/or other RAN and/or core network nodes.

[0218] The wireless link **330A** and/or the wireless link **330B** may comprise at least one of a bi-directional link and/or a directional link. The communication interface **310** of the wireless device **110** may be configured to communicate with the communication interface **320A** of the base station **1 120A** and/or with the communication interface **320B** of the base station **2 120B**. The base station **1 120A** and the wireless device **110**, and/or the base station **2 120B** and the wireless device **110**, may be configured to send and receive transport blocks, for example, via the wireless link **330A** and/or via the wireless link **330B**, respectively. The wireless link **330A** and/or the wireless link **330B** may use at least one frequency carrier. Transceiver(s) may be used. A transceiver may be a device that comprises both a transmitter and a receiver. Transceivers may be used in devices such as wireless devices, base stations, relay nodes, computing devices, and/or the like. Radio technology may be implemented in the communication interface **310, 320A**, and/or **320B**, and the wireless link **330A** and/or **330B**. The radio technology may comprise one or more elements shown

in FIG. 4A, FIG. 4B, FIG. 4C, FIG. 4D, FIG. 6, FIG. 7A, FIG. 7B, FIG. 8, and associated text, described below.

[0219] Other nodes in a wireless network (e.g., AMF, UPF, SMF, etc.) may comprise one or more communication interfaces, one or more processors, and memory storing instructions. A node (e.g., wireless device, base station, AMF, SMF, UPF, servers, switches, antennas, and/or the like) may comprise one or more processors, and memory storing instructions that when executed by the one or more processors causes the node to perform certain processes and/or functions. Single-carrier and/or multi-carrier communication operation may be performed. A non-transitory tangible computer readable media may comprise instructions executable by one or more processors to cause operation of single-carrier and/or multi-carrier communications. An article of manufacture may comprise a non-transitory tangible computer readable machine-accessible medium having instructions encoded thereon for enabling programmable hardware to cause a node to enable operation of single-carrier and/or multi-carrier communications. The node may include processors, memory, interfaces, and/or the like.

[0220] An interface may comprise at least one of a hardware interface, a firmware interface, a software interface, and/or a combination thereof. The hardware interface may comprise connectors, wires, and/or electronic devices such as drivers, amplifiers, and/or the like. The software interface may comprise code stored in a memory device to implement protocol(s), protocol layers, communication drivers, device drivers, combinations thereof, and/or the like. The firmware interface may comprise a combination of embedded hardware and/or code stored in (and/or in communication with) a memory device to implement connections, electronic device operations, protocol(s), protocol layers, communication drivers, device drivers, hardware operations, combinations thereof, and/or the like.

[0221] A communication network may comprise the wireless device **110**, the base station **1**, **120A**, the base station **2**, **120B**, and/or any other device. The communication network may comprise any number and/or type of devices, such as, for example, computing devices, wireless devices, mobile devices, handsets, tablets, laptops, internet of things (IoT) devices, hotspots, cellular repeaters, computing devices, and/or, more generally, user equipment (e.g., UE). Although one or more of the above types of devices may be referenced herein (e.g., UE, wireless device, computing device, etc.), it should be understood that any device herein may comprise any one or more of the above types of devices or similar devices. The communication network, and any other network referenced herein, may comprise an LTE network, a 5G network, or any other network for wireless communications. Apparatuses, systems, and/or methods described herein may generally be described as implemented on one or more devices (e.g., wireless device, base station, eNB, gNB, computing device, etc.), in one or more networks, but it will be understood that one or more features and steps may be implemented on any device and/or in any network. As used throughout, the term “base station” may comprise one or more of: a base station, a node, a Node B, a gNB, an eNB, an ng-eNB, a relay node (e.g., an integrated access and backhaul (IAB) node), a donor node (e.g., a donor eNB, a donor gNB, etc.), an access point (e.g., a WiFi access point), a computing device, a device capable of wirelessly communicating, or any other device capable of sending and/or receiving signals. As used throughout, the term “wireless device” may comprise one or more of: a UE, a handset, a mobile device, a computing device, a node, a device capable of wirelessly communicating, or any other device capable of sending and/or receiving signals. Any reference to one or more of these terms/devices also considers use of any other term/device mentioned above.

[0222] FIG. 4A, FIG. 4B, FIG. 4C and FIG. 4D show examples of uplink and downlink signal transmission. FIG. 4A shows an example uplink transmitter for at least one physical channel. A baseband signal representing a physical uplink shared channel may perform one or more functions. The one or more functions may comprise at least one of: scrambling (e.g., by Scrambling); modulation of scrambled bits to generate complex-valued symbols (e.g., by a Modulation mapper); mapping of the complex-valued modulation symbols onto one or several transmission layers (e.g.,

by a Layer mapper); transform precoding to generate complex-valued symbols (e.g., by a Transform precoder); precoding of the complex-valued symbols (e.g., by a Precoder); mapping of precoded complex-valued symbols to resource elements (e.g., by a Resource element mapper); generation of complex-valued time-domain Single Carrier-Frequency Division Multiple Access (SC-FDMA) or CP-OFDM signal for an antenna port (e.g., by a signal gen.); and/or the like. A SC-FDMA signal for uplink transmission may be generated, for example, if transform precoding is enabled. A CP-OFDM signal for uplink transmission may be generated by FIG. 4A, for example, if transform precoding is not enabled. These functions are shown as examples and other mechanisms may be implemented.

[0223] FIG. 4B shows an example of modulation and up-conversion to the carrier frequency of a complex-valued SC-FDMA or CP-OFDM baseband signal for an antenna port and/or for the complex-valued Physical Random Access CHannel (PRACH) baseband signal. Filtering may be performed prior to transmission.

[0224] FIG. 4C shows an example of downlink transmissions. The baseband signal representing a downlink physical channel may perform one or more functions. The one or more functions may comprise: scrambling of coded bits in a codeword to be transmitted on a physical channel (e.g., by Scrambling); modulation of scrambled bits to generate complex-valued modulation symbols (e.g., by a Modulation mapper); mapping of the complex-valued modulation symbols onto one or several transmission layers (e.g., by a Layer mapper); precoding of the complex-valued modulation symbols on a layer for transmission on the antenna ports (e.g., by Precoding); mapping of complex-valued modulation symbols for an antenna port to resource elements (e.g., by a Resource element mapper); generation of complex-valued time-domain OFDM signal for an antenna port (e.g., by an OFDM signal gen.); and/or the like. These functions are shown as examples and other mechanisms may be implemented.

[0225] A base station may send (e.g., transmit) a first symbol and a second symbol on an antenna port, to a wireless device. The wireless device may infer the channel (e.g., fading gain, multipath delay, etc.) for conveying the second symbol on the antenna port, from the channel for conveying the first symbol on the antenna port. A first antenna port and a second antenna port may be quasi co-located, for example, if one or more large-scale properties of the channel over which a first symbol on the first antenna port is conveyed may be inferred from the channel over which a second symbol on a second antenna port is conveyed. The one or more large-scale properties may comprise at least one of: delay spread; Doppler spread; Doppler shift; average gain; average delay; and/or spatial receiving (Rx) parameters.

[0226] FIG. 4D shows an example modulation and up-conversion to the carrier frequency of the complex-valued OFDM baseband signal for an antenna port. Filtering may be performed prior to transmission.

[0227] FIG. 5A shows example uplink channel mapping and example uplink physical signals. A physical layer may provide one or more information transfer services to a MAC and/or one or more higher layers. The physical layer may provide the one or more information transfer services to the MAC via one or more transport channels. An information transfer service may indicate how and/or with what characteristics data is transferred over the radio interface.

[0228] Uplink transport channels may comprise an Uplink-Shared CHannel (UL-SCH) **501** and/or a Random Access CHannel (RACH) **502**. A wireless device may send (e.g., transmit) one or more uplink DM-RSs **506** to a base station for channel estimation, for example, for coherent demodulation of one or more uplink physical channels (e.g., PUSCH **503** and/or PUCCH **504**). The wireless device may send (e.g., transmit) to a base station at least one uplink DM-RS **506** with PUSCH **503** and/or PUCCH **504**, wherein the at least one uplink DM-RS **506** may be spanning a same frequency range as a corresponding physical channel. The base station may configure the wireless device with one or more uplink DM-RS configurations. At least one DM-RS configuration may support a front-loaded DM-RS pattern. A front-loaded DM-RS may be mapped over one or

more OFDM symbols (e.g., 1 or 2 adjacent OFDM symbols). One or more additional uplink DM-RS may be configured to send (e.g., transmit) at one or more symbols of a PUSCH and/or PUCCH. The base station may semi-statically configure the wireless device with a maximum number of front-loaded DM-RS symbols for PUSCH and/or PUCCH. The wireless device may schedule a single-symbol DM-RS and/or double symbol DM-RS based on a maximum number of front-loaded DM-RS symbols, wherein the base station may configure the wireless device with one or more additional uplink DM-RS for PUSCH and/or PUCCH. A new radio network may support, for example, at least for CP-OFDM, a common DM-RS structure for DL and UL, wherein a DM-RS location, DM-RS pattern, and/or scrambling sequence may be same or different.

[0229] Whether or not an uplink PT-RS **507** is present may depend on an RRC configuration. A presence of the uplink PT-RS may be wireless device-specifically configured. A presence and/or a pattern of the uplink PT-RS **507** in a scheduled resource may be wireless device-specifically configured by a combination of RRC signaling and/or association with one or more parameters used for other purposes (e.g., Modulation and Coding Scheme (MCS)) which may be indicated by DCI. If configured, a dynamic presence of uplink PT-RS **507** may be associated with one or more DCI parameters comprising at least a MCS. A radio network may support a plurality of uplink PT-RS densities defined in time/frequency domain. If present, a frequency domain density may be associated with at least one configuration of a scheduled bandwidth. A wireless device may assume a same precoding for a DMRS port and a PT-RS port. A number of PT-RS ports may be less than a number of DM-RS ports in a scheduled resource. The uplink PT-RS **507** may be confined in the scheduled time/frequency duration for a wireless device.

[0230] A wireless device may send (e.g., transmit) an SRS **508** to a base station for channel state estimation, for example, to support uplink channel dependent scheduling and/or link adaptation. The SRS **508** sent (e.g., transmitted) by the wireless device may allow for the base station to estimate an uplink channel state at one or more different frequencies. A base station scheduler may use an uplink channel state to assign one or more resource blocks of a certain quality (e.g., above a quality threshold) for an uplink PUSCH transmission from the wireless device. The base station may semi-statically configure the wireless device with one or more SRS resource sets. For an SRS resource set, the base station may configure the wireless device with one or more SRS resources. An SRS resource set applicability may be configured by a higher layer (e.g., RRC) parameter. An SRS resource in each of one or more SRS resource sets may be sent (e.g., transmitted) at a time instant, for example, if a higher layer parameter indicates beam management. The wireless device may send (e.g., transmit) one or more SRS resources in different SRS resource sets simultaneously. A new radio network may support aperiodic, periodic, and/or semi-persistent SRS transmissions. The wireless device may send (e.g., transmit) SRS resources, for example, based on one or more trigger types. The one or more trigger types may comprise higher layer signaling (e.g., RRC) and/or one or more DCI formats (e.g., at least one DCI format may be used for a wireless device to select at least one of one or more configured SRS resource sets). An SRS trigger type 0 may refer to an SRS triggered based on a higher layer signaling. An SRS trigger type 1 may refer to an SRS triggered based on one or more DCI formats. The wireless device may be configured to send (e.g., transmit) the SRS **508** after a transmission of PUSCH **503** and corresponding uplink DM-RS **506**, for example, if PUSCH **503** and the SRS **508** are transmitted in a same slot.

[0231] A base station may semi-statically configure a wireless device with one or more SRS configuration parameters indicating at least one of following: an SRS resource configuration identifier, a number of SRS ports, time domain behavior of SRS resource configuration (e.g., an indication of periodic, semi-persistent, or aperiodic SRS), slot (mini-slot, and/or subframe) level periodicity and/or offset for a periodic and/or aperiodic SRS resource, a number of OFDM symbols in a SRS resource, starting OFDM symbol of a SRS resource, an SRS bandwidth, a frequency hopping bandwidth, a cyclic shift, and/or an SRS sequence ID.

[0232] FIG. 5B shows an example downlink channel mapping and downlink physical signals.

Downlink transport channels may comprise a Downlink-Shared CHannel (DL-SCH) **511**, a Paging CHannel (PCH) **512**, and/or a Broadcast CHannel (BCH) **513**. A transport channel may be mapped to one or more corresponding physical channels. A UL-SCH **501** may be mapped to a Physical Uplink Shared CHannel (PUSCH) **503**. A RACH **502** may be mapped to a PRACH **505**. A DL-SCH **511** and a PCH **512** may be mapped to a Physical Downlink Shared CHannel (PDSCH) **514**. A BCH **513** may be mapped to a Physical Broadcast CHannel (PBCH) **516**.

[0233] A radio network may comprise one or more downlink and/or uplink transport channels. The radio network may comprise one or more physical channels without a corresponding transport channel. The one or more physical channels may be used for an Uplink Control Information (UCI) **509** and/or a Downlink Control Information (DCI) **517**. A Physical Uplink Control CHannel (PUCCH) **504** may carry UCI **509** from a wireless device to a base station. A Physical Downlink Control CHannel (PDCCH) **515** may carry the DCI **517** from a base station to a wireless device. The radio network (e.g., NR) may support the UCI **509** multiplexing in the PUSCH **503**, for example, if the UCI **509** and the PUSCH **503** transmissions may coincide in a slot (e.g., at least in part). The UCI **509** may comprise at least one of a CSI, an Acknowledgement (ACK)/Negative Acknowledgement (NACK), and/or a scheduling request. The DCI **517** via the PDCCH **515** may indicate at least one of following: one or more downlink assignments and/or one or more uplink scheduling grants.

[0234] In uplink, a wireless device may send (e.g., transmit) one or more Reference Signals (RSs) to a base station. The one or more RSs may comprise at least one of a Demodulation-RS (DM-RS) **506**, a Phase Tracking-RS (PT-RS) **507**, and/or a Sounding RS (SRS) **508**. In downlink, a base station may send (e.g., transmit, unicast, multicast, and/or broadcast) one or more RSs to a wireless device. The one or more RSs may comprise at least one of a Primary Synchronization Signal (PSS)/Secondary Synchronization Signal (SSS) **521**, a CSI-RS **522**, a DM-RS **523**, and/or a PT-RS **524**.

[0235] In a time domain, an SS/PBCH block may comprise one or more OFDM symbols (e.g., 4 OFDM symbols numbered in increasing order from **0** to **3**) within the SS/PBCH block. An SS/PBCH block may comprise the PSS/SSS **521** and/or the PBCH **516**. In the frequency domain, an SS/PBCH block may comprise one or more contiguous subcarriers (e.g., **240** contiguous subcarriers with the subcarriers numbered in increasing order from **0** to **239**) within the SS/PBCH block. The PSS/SSS **521** may occupy, for example, 1 OFDM symbol and 127 subcarriers. The PBCH **516** may span across, for example, 3 OFDM symbols and 240 subcarriers. A wireless device may assume that one or more SS/PBCH blocks transmitted with a same block index may be quasi co-located, for example, with respect to Doppler spread, Doppler shift, average gain, average delay, and/or spatial Rx parameters. A wireless device may not assume quasi co-location for other SS/PBCH block transmissions. A periodicity of an SS/PBCH block may be configured by a radio network (e.g., by an RRC signaling). One or more time locations in which the SS/PBCH block may be sent may be determined by sub-carrier spacing. A wireless device may assume a band-specific sub-carrier spacing for an SS/PBCH block, for example, unless a radio network has configured the wireless device to assume a different sub-carrier spacing.

[0236] The downlink CSI-RS **522** may be used for a wireless device to acquire channel state information. A radio network may support periodic, aperiodic, and/or semi-persistent transmission of the downlink CSI-RS **522**. A base station may semi-statically configure and/or reconfigure a wireless device with periodic transmission of the downlink CSI-RS **522**. A configured CSI-RS resources may be activated and/or deactivated. For semi-persistent transmission, an activation and/or deactivation of a CSI-RS resource may be triggered dynamically. A CSI-RS configuration may comprise one or more parameters indicating at least a number of antenna ports. A base station may configure a wireless device with 32 ports, or any other number of ports. A base station may semi-statically configure a wireless device with one or more CSI-RS resource sets. One or more CSI-RS resources may be allocated from one or more CSI-RS resource sets to one or more wireless

devices. A base station may semi-statically configure one or more parameters indicating CSI-RS resource mapping, for example, time-domain location of one or more CSI-RS resources, a bandwidth of a CSI-RS resource, and/or a periodicity. A wireless device may be configured to use the same OFDM symbols for the downlink CSI-RS **522** and the Control Resource Set (CORESET), for example, if the downlink CSI-RS **522** and the CORESET are spatially quasi co-located and resource elements associated with the downlink CSI-RS **522** are the outside of PRBs configured for the CORESET. A wireless device may be configured to use the same OFDM symbols for downlink CSI-RS **522** and SSB/PBCH, for example, if the downlink CSI-RS **522** and SSB/PBCH are spatially quasi co-located and resource elements associated with the downlink CSI-RS **522** are outside of the PRBs configured for the SSB/PBCH.

[0237] A wireless device may send (e.g., transmit) one or more downlink DM-RSs **523** to a base station for channel estimation, for example, for coherent demodulation of one or more downlink physical channels (e.g., PDSCH **514**). A radio network may support one or more variable and/or configurable DM-RS patterns for data demodulation. At least one downlink DM-RS configuration may support a front-loaded DM-RS pattern. A front-loaded DM-RS may be mapped over one or more OFDM symbols (e.g., **1** or **2** adjacent OFDM symbols). A base station may semi-statically configure a wireless device with a maximum number of front-loaded DM-RS symbols for PDSCH **514**. A DM-RS configuration may support one or more DM-RS ports. A DM-RS configuration may support at least 8 orthogonal downlink DM-RS ports, for example, for single user-MIMO. ADM-RS configuration may support 12 orthogonal downlink DM-RS ports, for example, for multiuser-MIMO. A radio network may support, for example, at least for CP-OFDM, a common DM-RS structure for DL and UL, wherein a DM-RS location, DM-RS pattern, and/or scrambling sequence may be the same or different.

[0238] Whether or not the downlink PT-RS **524** is present may depend on an RRC configuration. A presence of the downlink PT-RS **524** may be wireless device-specifically configured. A presence and/or a pattern of the downlink PT-RS **524** in a scheduled resource may be wireless device-specifically configured, for example, by a combination of RRC signaling and/or an association with one or more parameters used for other purposes (e.g., MCS) which may be indicated by the DCI. If configured, a dynamic presence of the downlink PT-RS **524** may be associated with one or more DCI parameters comprising at least MCS. A radio network may support a plurality of PT-RS densities in a time/frequency domain. If present, a frequency domain density may be associated with at least one configuration of a scheduled bandwidth. A wireless device may assume the same precoding for a DM-RS port and a PT-RS port. A number of PT-RS ports may be less than a number of DM-RS ports in a scheduled resource. The downlink PT-RS **524** may be confined in the scheduled time/frequency duration for a wireless device.

[0239] FIG. **6** shows an example transmission time and reception time, as well as an example frame structure, for a carrier. A multicarrier OFDM communication system may include one or more carriers, for example, ranging from 1 to 32 carriers (such as for carrier aggregation) or ranging from 1 to 64 carriers (such as for dual connectivity). Different radio frame structures may be supported (e.g., for FDD and/or for TDD duplex mechanisms). FIG. **6** shows an example frame timing. Downlink and uplink transmissions may be organized into radio frames **601**. Radio frame duration may be 10 milliseconds (ms). A 10 ms radio frame **601** may be divided into ten equally sized subframes **602**, each with a 1 ms duration. Subframe(s) may comprise one or more slots (e.g., slots **603** and **605**) depending on subcarrier spacing and/or CP length. For example, a subframe with 15 kHz, 30 kHz, 60 kHz, 120 kHz, 240 kHz and 480 kHz subcarrier spacing may comprise one, two, four, eight, sixteen and thirty-two slots, respectively. In FIG. **6**, a subframe may be divided into two equally sized slots **603** with 0.5 ms duration. For example, 10 subframes may be available for downlink transmission and 10 subframes may be available for uplink transmissions in a 10 ms interval. Other subframe durations such as, for example, 0.5 ms, 1 ms, 2 ms, and 5 ms may be supported. Uplink and downlink transmissions may be separated in the frequency domain.

Slot(s) may include a plurality of OFDM symbols **604**. The number of OFDM symbols **604** in a slot **605** may depend on the cyclic prefix length. A slot may be 14 OFDM symbols for the same subcarrier spacing of up to 480 kHz with normal CP. A slot may be 12 OFDM symbols for the same subcarrier spacing of 60 kHz with extended CP. A slot may comprise downlink, uplink, and/or a downlink part and an uplink part, and/or alike.

[0240] FIG. 7A shows example sets of OFDM subcarriers. A base station may communicate with a wireless device using a carrier having an example channel bandwidth **700**. Arrow(s) in the example may depict a subcarrier in a multicarrier OFDM system. The OFDM system may use technology such as OFDM technology, SC-FDMA technology, and/or the like. An arrow **701** shows a subcarrier transmitting information symbols. A subcarrier spacing **702**, between two contiguous subcarriers in a carrier, may be any one of 15 kHz, 30 kHz, 60 kHz, 120 kHz, 240 kHz, or any other frequency. Different subcarrier spacing may correspond to different transmission numerologies. A transmission numerology may comprise at least: a numerology index; a value of subcarrier spacing; and/or a type of cyclic prefix (CP). A base station may send (e.g., transmit) to and/or receive from a wireless device via a number of subcarriers **703** in a carrier. A bandwidth occupied by a number of subcarriers **703** (e.g., transmission bandwidth) may be smaller than the channel bandwidth **700** of a carrier, for example, due to guard bands **704** and **705**. Guard bands **704** and **705** may be used to reduce interference to and from one or more neighbor carriers. A number of subcarriers (e.g., transmission bandwidth) in a carrier may depend on the channel bandwidth of the carrier and/or the subcarrier spacing. A transmission bandwidth, for a carrier with a 20 MHz channel bandwidth and a 15 kHz subcarrier spacing, may be in number of 1024 subcarriers.

[0241] A base station and a wireless device may communicate with multiple component carriers (CCs), for example, if configured with CA. Different component carriers may have different bandwidth and/or different subcarrier spacing, for example, if CA is supported. A base station may send (e.g., transmit) a first type of service to a wireless device via a first component carrier. The base station may send (e.g., transmit) a second type of service to the wireless device via a second component carrier. Different types of services may have different service requirements (e.g., data rate, latency, reliability), which may be suitable for transmission via different component carriers having different subcarrier spacing and/or different bandwidth.

[0242] FIG. 7B shows examples of component carriers. A first component carrier may comprise a first number of subcarriers **706** having a first subcarrier spacing **709**. A second component carrier may comprise a second number of subcarriers **707** having a second subcarrier spacing **710**. A third component carrier may comprise a third number of subcarriers **708** having a third subcarrier spacing **711**. Carriers in a multicarrier OFDM communication system may be contiguous carriers, non-contiguous carriers, or a combination of both contiguous and non-contiguous carriers.

[0243] FIG. 8 shows an example of OFDM radio resources. A carrier may have a transmission bandwidth **801**. A resource grid may be in a structure of frequency domain **802** and time domain **803**. A resource grid may comprise a first number of OFDM symbols in a subframe and a second number of resource blocks, starting from a common resource block indicated by higher-layer signaling (e.g., RRC signaling), for a transmission numerology and a carrier. In a resource grid, a resource element **805** may comprise a resource unit that may be identified by a subcarrier index and a symbol index. A subframe may comprise a first number of OFDM symbols **807** that may depend on a numerology associated with a carrier. A subframe may have 14 OFDM symbols for a carrier, for example, if a subcarrier spacing of a numerology of a carrier is 15 kHz. A subframe may have 28 OFDM symbols, for example, if a subcarrier spacing of a numerology is 30 kHz. A subframe may have 56 OFDM symbols, for example, if a subcarrier spacing of a numerology is 60 kHz. A subcarrier spacing of a numerology may comprise any other frequency. A second number of resource blocks comprised in a resource grid of a carrier may depend on a bandwidth and a numerology of the carrier.

[0244] A resource block **806** may comprise 12 subcarriers. Multiple resource blocks may be

grouped into a Resource Block Group (RBG) 804. A size of a RBG may depend on at least one of: a RRC message indicating a RBG size configuration; a size of a carrier bandwidth; and/or a size of a bandwidth part of a carrier. A carrier may comprise multiple bandwidth parts. A first bandwidth part of a carrier may have a different frequency location and/or a different bandwidth from a second bandwidth part of the carrier.

[0245] A base station may send (e.g., transmit), to a wireless device, a downlink control information comprising a downlink or uplink resource block assignment. A base station may send (e.g., transmit) to and/or receive from, a wireless device, data packets (e.g., transport blocks). The data packets may be scheduled on and transmitted via one or more resource blocks and one or more slots indicated by parameters in downlink control information and/or RRC message(s). A starting symbol relative to a first slot of the one or more slots may be indicated to the wireless device. A base station may send (e.g., transmit) to and/or receive from, a wireless device, data packets. The data packets may be scheduled for transmission on one or more RBGs and in one or more slots.

[0246] A base station may send (e.g., transmit), to a wireless device, downlink control information comprising a downlink assignment. The base station may send (e.g., transmit) the DCI via one or more PDCCHs. The downlink assignment may comprise parameters indicating at least one of a modulation and coding format; resource allocation; and/or HARQ information related to the DL-SCH. The resource allocation may comprise parameters of resource block allocation; and/or slot allocation. A base station may allocate (e.g., dynamically) resources to a wireless device, for example, via a Cell-Radio Network Temporary Identifier (C-RNTI) on one or more PDCCHs. The wireless device may monitor the one or more PDCCHs, for example, in order to find possible allocation if its downlink reception is enabled. The wireless device may receive one or more downlink data packets on one or more PDSCH scheduled by the one or more PDCCHs, for example, if the wireless device successfully detects the one or more PDCCHs.

[0247] A base station may allocate Configured Scheduling (CS) resources for down link transmission to a wireless device. The base station may send (e.g., transmit) one or more RRC messages indicating a periodicity of the CS grant. The base station may send (e.g., transmit) DCI via a PDCCH addressed to a Configured Scheduling-RNTI (CS-RNTI) activating the CS resources. The DCI may comprise parameters indicating that the downlink grant is a CS grant. The CS grant may be implicitly reused according to the periodicity defined by the one or more RRC messages. The CS grant may be implicitly reused, for example, until deactivated.

[0248] A base station may send (e.g., transmit), to a wireless device via one or more PDCCHs, downlink control information comprising an uplink grant. The uplink grant may comprise parameters indicating at least one of a modulation and coding format; a resource allocation; and/or HARQ information related to the UL-SCH. The resource allocation may comprise parameters of resource block allocation; and/or slot allocation. The base station may dynamically allocate resources to the wireless device via a C-RNTI on one or more PDCCHs. The wireless device may monitor the one or more PDCCHs, for example, in order to find possible resource allocation. The wireless device may send (e.g., transmit) one or more uplink data packets via one or more PUSCH scheduled by the one or more PDCCHs, for example, if the wireless device successfully detects the one or more PDCCHs.

[0249] The base station may allocate CS resources for uplink data transmission to a wireless device. The base station may transmit one or more RRC messages indicating a periodicity of the CS grant. The base station may send (e.g., transmit) DCI via a PDCCH addressed to a CS-RNTI to activate the CS resources. The DCI may comprise parameters indicating that the uplink grant is a CS grant. The CS grant may be implicitly reused according to the periodicity defined by the one or more RRC message, The CS grant may be implicitly reused, for example, until deactivated.

[0250] A base station may send (e.g., transmit) DCI and/or control signaling via a PDCCH. The DCI may comprise a format of a plurality of formats. The DCI may comprise downlink and/or uplink scheduling information (e.g., resource allocation information, HARQ related parameters,

MCS), request(s) for CSI (e.g., aperiodic CQI reports), request(s) for an SRS, uplink power control commands for one or more cells, one or more timing information (e.g., TB transmission/reception timing, HARQ feedback timing, etc.), and/or the like. The DCI may indicate an uplink grant comprising transmission parameters for one or more transport blocks. The DCI may indicate a downlink assignment indicating parameters for receiving one or more transport blocks. The DCI may be used by the base station to initiate a contention-free random access at the wireless device. The base station may send (e.g., transmit) DCI comprising a slot format indicator (SFI) indicating a slot format. The base station may send (e.g., transmit) DCI comprising a preemption indication indicating the PRB(s) and/or OFDM symbol(s) in which a wireless device may assume no transmission is intended for the wireless device. The base station may send (e.g., transmit) DCI for group power control of the PUCCH, the PUSCH, and/or an SRS. DCI may correspond to an RNTI. The wireless device may obtain an RNTI after or in response to completing the initial access (e.g., C-RNTI). The base station may configure an RNTI for the wireless (e.g., CS-RNTI, TPC-CS-RNTI, TPC-PUCCH-RNTI, TPC-PUSCH-RNTI, TPC-SRS-RNTI, etc.). The wireless device may determine (e.g., compute) an RNTI (e.g., the wireless device may determine the RA-RNTI based on resources used for transmission of a preamble). An RNTI may have a pre-configured value (e.g., P-RNTI or SI-RNTI). The wireless device may monitor a group common search space which may be used by the base station for sending (e.g., transmitting) DCIs that are intended for a group of wireless devices. A group common DCI may correspond to an RNTI which is commonly configured for a group of wireless devices. The wireless device may monitor a wireless device-specific search space. A wireless device specific DCI may correspond to an RNTI configured for the wireless device.

[0251] A communications system (e.g., an NR system) may support a single beam operation and/or a multi-beam operation. In a multi-beam operation, a base station may perform a downlink beam sweeping to provide coverage for common control channels and/or downlink SS blocks, which may comprise at least a PSS, a SSS, and/or PBCH. A wireless device may measure quality of a beam pair link using one or more RSs. One or more SS blocks, or one or more CSI-RS resources (e.g., which may be associated with a CSI-RS resource index (CRI)), and/or one or more DM-RSs of a PBCH, may be used as an RS for measuring a quality of a beam pair link. The quality of a beam pair link may be based on a reference signal received power (RSRP) value, a reference signal received quality (RSRQ) value, and/or a CSI value measured on RS resources. The base station may indicate whether an RS resource, used for measuring a beam pair link quality, is quasi-co-located (QCLed) with DM-RSs of a control channel. An RS resource and DM-RSs of a control channel may be called QCLed, for example, if channel characteristics from a transmission on an RS to a wireless device, and that from a transmission on a control channel to a wireless device, are similar or the same under a configured criterion. In a multi-beam operation, a wireless device may perform an uplink beam sweeping to access a cell.

[0252] A wireless device may be configured to monitor a PDCCH on one or more beam pair links simultaneously, for example, depending on a capability of the wireless device. This monitoring may increase robustness against beam pair link blocking. A base station may send (e.g., transmit) one or more messages to configure the wireless device to monitor the PDCCH on one or more beam pair links in different PDCCH OFDM symbols. A base station may send (e.g., transmit) higher layer signaling (e.g., RRC signaling) and/or a MAC CE comprising parameters related to the Rx beam setting of the wireless device for monitoring the PDCCH on one or more beam pair links. The base station may send (e.g., transmit) an indication of a spatial QCL assumption between an DL RS antenna port(s) (e.g., a cell-specific CSI-RS, a wireless device-specific CSI-RS, an SS block, and/or a PBCH with or without DM-RSs of the PBCH) and/or DL RS antenna port(s) for demodulation of a DL control channel. Signaling for beam indication for a PDCCH may comprise MAC CE signaling, RRC signaling, DCI signaling, and/or specification-transparent and/or implicit method, and/or any combination of signaling methods.

[0253] A base station may indicate spatial QCL parameters between DL RS antenna port(s) and DM-RS antenna port(s) of a DL data channel, for example, for reception of a unicast DL data channel. The base station may send (e.g., transmit) DCI (e.g., downlink grants) comprising information indicating the RS antenna port(s). The information may indicate RS antenna port(s) that may be QCLed with the DM-RS antenna port(s). A different set of DM-RS antenna port(s) for a DL data channel may be indicated as QCL with a different set of the RS antenna port(s).

[0254] FIG. 9A shows an example of beam sweeping in a DL channel. In an RRC_INACTIVE state or RRC_IDLE state, a wireless device may assume that SS blocks form an SS burst **940**, and an SS burst set **950**. The SS burst set **950** may have a given periodicity. A base station **120** may send (e.g., transmit) SS blocks in multiple beams, together forming a SS burst **940**, for example, in a multi-beam operation. One or more SS blocks may be sent (e.g., transmitted) on one beam. If multiple SS bursts **940** are transmitted with multiple beams, SS bursts together may form SS burst set **950**.

[0255] A wireless device may use CSI-RS for estimating a beam quality of a link between a wireless device and a base station, for example, in the multi beam operation. A beam may be associated with a CSI-RS. A wireless device may (e.g., based on a RSRP measurement on CSI-RS) report a beam index, which may be indicated in a CRI for downlink beam selection and/or associated with an RSRP value of a beam. A CSI-RS may be sent (e.g., transmitted) on a CSI-RS resource, which may comprise at least one of: one or more antenna ports and/or one or more time and/or frequency radio resources. A CSI-RS resource may be configured in a cell-specific way such as by common RRC signaling, or in a wireless device-specific way such as by dedicated RRC signaling and/or L1/L2 signaling. Multiple wireless devices covered by a cell may measure a cell-specific CSI-RS resource. A dedicated subset of wireless devices covered by a cell may measure a wireless device-specific CSI-RS resource.

[0256] A CSI-RS resource may be sent (e.g., transmitted) periodically, using aperiodic transmission, or using a multi-shot or semi-persistent transmission. In a periodic transmission in FIG. 9A, a base station **120** may send (e.g., transmit) configured CSI-RS resources **940** periodically using a configured periodicity in a time domain. In an aperiodic transmission, a configured CSI-RS resource may be sent (e.g., transmitted) in a dedicated time slot. In a multi-shot and/or semi-persistent transmission, a configured CSI-RS resource may be sent (e.g., transmitted) within a configured period. Beams used for CSI-RS transmission may have a different beam width than beams used for SS-blocks transmission.

[0257] FIG. 9B shows an example of a beam management procedure, such as in an example new radio network. The base station **120** and/or the wireless device **110** may perform a downlink L1/L2 beam management procedure. One or more of the following downlink L1/L2 beam management procedures may be performed within one or more wireless devices **110** and one or more base stations **120**. A P1 procedure **910** may be used to enable the wireless device **110** to measure one or more Transmission (Tx) beams associated with the base station **120**, for example, to support a selection of a first set of Tx beams associated with the base station **120** and a first set of Rx beam(s) associated with the wireless device **110**. A base station **120** may sweep a set of different Tx beams, for example, for beamforming at a base station **120** (such as shown in the top row, in a counter-clockwise direction). A wireless device **110** may sweep a set of different Rx beams, for example, for beamforming at a wireless device **110** (such as shown in the bottom row, in a clockwise direction). A P2 procedure **920** may be used to enable a wireless device **110** to measure one or more Tx beams associated with a base station **120**, for example, to possibly change a first set of Tx beams associated with a base station **120**. A P2 procedure **920** may be performed on a possibly smaller set of beams (e.g., for beam refinement) than in the P1 procedure **910**. A P2 procedure **920** may be a special example of a P1 procedure **910**. A P3 procedure **930** may be used to enable a wireless device **110** to measure at least one Tx beam associated with a base station **120**, for example, to change a first set of Rx beams associated with a wireless device **110**.

[0258] A wireless device **110** may send (e.g., transmit) one or more beam management reports to a base station **120**. In one or more beam management reports, a wireless device **110** may indicate one or more beam pair quality parameters comprising one or more of: a beam identification; an RSRP; a Precoding Matrix Indicator (PMI), Channel Quality Indicator (CQI), and/or Rank Indicator (RI) of a subset of configured beams. Based on one or more beam management reports, the base station **120** may send (e.g., transmit) to a wireless device **110** a signal indicating that one or more beam pair links are one or more serving beams. The base station **120** may send (e.g., transmit) the PDCCH and the PDSCH for a wireless device **110** using one or more serving beams.

[0259] A communications network (e.g., a new radio network) may support a Bandwidth Adaptation (BA). Receive and/or transmit bandwidths that may be configured for a wireless device using a BA may not be large. Receive and/or transmit bandwidth may not be as large as a bandwidth of a cell. Receive and/or transmit bandwidths may be adjustable. A wireless device may change receive and/or transmit bandwidths, for example, to reduce (e.g., shrink) the bandwidth(s) at (e.g., during) a period of low activity such as to save power. A wireless device may change a location of receive and/or transmit bandwidths in a frequency domain, for example, to increase scheduling flexibility. A wireless device may change a subcarrier spacing, for example, to allow different services.

[0260] A Bandwidth Part (BWP) may comprise a subset of a total cell bandwidth of a cell. A base station may configure a wireless device with one or more BWPs, for example, to achieve a BA. A base station may indicate, to a wireless device, which of the one or more (configured) BWPs is an active BWP.

[0261] FIG. **10** shows an example of BWP configurations. BWPs may be configured as follows: BWP1 (**1010** and **1050**) with a width of 40 MHz and subcarrier spacing of 15 kHz; BWP2 (**1020** and **1040**) with a width of 10 MHz and subcarrier spacing of 15 kHz; BWP3 **1030** with a width of 20 MHz and subcarrier spacing of 60 kHz. Any number of BWP configurations may comprise any other width and subcarrier spacing combination.

[0262] A wireless device, configured for operation in one or more BWPs of a cell, may be configured by one or more higher layers (e.g., RRC layer). The wireless device may be configured for a cell with: a set of one or more BWPs (e.g., at most four BWPs) for reception (e.g., a DL BWP set) in a DL bandwidth by at least one parameter DL-BWP; and a set of one or more BWPs (e.g., at most four BWPs) for transmissions (e.g., UL BWP set) in an UL bandwidth by at least one parameter UL-BWP.

[0263] A base station may configure a wireless device with one or more UL and DL BWP pairs, for example, to enable BA on the PCell. To enable BA on SCells (e.g., for CA), a base station may configure a wireless device at least with one or more DL BWPs (e.g., there may be none in an UL).

[0264] An initial active DL BWP may comprise at least one of a location and number of contiguous PRBs, a subcarrier spacing, or a cyclic prefix, for example, for a control resource set for at least one common search space. For operation on the PCell, one or more higher layer parameters may indicate at least one initial UL BWP for a random access procedure. If a wireless device is configured with a secondary carrier on a primary cell, the wireless device may be configured with an initial BWP for random access procedure on a secondary carrier.

[0265] A wireless device may expect that a center frequency for a DL BWP may be same as a center frequency for a UL BWP, for example, for unpaired spectrum operation. A base station may semi-statically configure a wireless device for a cell with one or more parameters, for example, for a DL BWP or an UL BWP in a set of one or more DL BWPs or one or more UL BWPs, respectively. The one or more parameters may indicate one or more of following: a subcarrier spacing; a cyclic prefix; a number of contiguous PRBs; an index in the set of one or more DL BWPs and/or one or more UL BWPs; a link between a DL BWP and an UL BWP from a set of configured DL BWPs and UL BWPs; DCI detection to a PDSCH reception timing; a PDSCH reception to a HARQ-ACK transmission timing value; DCI detection to a PUSCH transmission

timing value; and/or an offset of a first PRB of a DL bandwidth or an UL bandwidth, respectively, relative to a first PRB of a bandwidth.

[0266] For a DL BWP in a set of one or more DL BWPs on a PCell, a base station may configure a wireless device with one or more control resource sets for at least one type of common search space and/or one wireless device-specific search space. A base station may not configure a wireless device without a common search space on a PCell, or on a PSCell, in an active DL BWP. For an UL BWP in a set of one or more UL BWPs, a base station may configure a wireless device with one or more resource sets for one or more PUCCH transmissions.

[0267] DCI may comprise a BWP indicator field. The BWP indicator field value may indicate an active DL BWP, from a configured DL BWP set, for one or more DL receptions. The BWP indicator field value may indicate an active UL BWP, from a configured UL BWP set, for one or more UL transmissions.

[0268] For a PCell, a base station may semi-statically configure a wireless device with a default DL BWP among configured DL BWPs. If a wireless device is not provided a default DL BWP, a default BWP may be an initial active DL BWP.

[0269] A base station may configure a wireless device with a timer value for a PCell. A wireless device may start a timer (e.g., a BWP inactivity timer), for example, if a wireless device detects DCI indicating an active DL BWP, other than a default DL BWP, for a paired spectrum operation, and/or if a wireless device detects DCI indicating an active DL BWP or UL BWP, other than a default DL BWP or UL BWP, for an unpaired spectrum operation. The wireless device may increment the timer by an interval of a first value (e.g., the first value may be 1 millisecond, 0.5 milliseconds, or any other time duration), for example, if the wireless device does not detect DCI at (e.g., during) the interval for a paired spectrum operation or for an unpaired spectrum operation. The timer may expire at a time that the timer is equal to the timer value. A wireless device may switch to the default DL BWP from an active DL BWP, for example, if the timer expires.

[0270] A base station may semi-statically configure a wireless device with one or more BWPs. A wireless device may switch an active BWP from a first BWP to a second BWP, for example, after or in response to receiving DCI indicating the second BWP as an active BWP, and/or after or in response to an expiry of BWP inactivity timer (e.g., the second BWP may be a default BWP). FIG. 10 shows an example of three BWPs configured, BWP1 (1010 and 1050), BWP2 (1020 and 1040), and BWP3 (1030). BWP2 (1020 and 1040) may be a default BWP. BWP1 (1010) may be an initial active BWP. A wireless device may switch an active BWP from BWP1 1010 to BWP2 1020, for example, after or in response to an expiry of the BWP inactivity timer. A wireless device may switch an active BWP from BWP2 1020 to BWP3 1030, for example, after or in response to receiving DCI indicating BWP3 1030 as an active BWP. Switching an active BWP from BWP3 1030 to BWP2 1040 and/or from BWP2 1040 to BWP1 1050 may be after or in response to receiving DCI indicating an active BWP, and/or after or in response to an expiry of BWP inactivity timer.

[0271] Wireless device procedures on a secondary cell may be same as on a primary cell using the timer value for the secondary cell and the default DL BWP for the secondary cell, for example, if a wireless device is configured for a secondary cell with a default DL BWP among configured DL BWPs and a timer value. A wireless device may use an indicated DL BWP and an indicated UL BWP on a secondary cell as a respective first active DL BWP and first active UL BWP on a secondary cell or carrier, for example, if a base station configures a wireless device with a first active DL BWP and a first active UL BWP on a secondary cell or carrier.

[0272] FIG. 11A and FIG. 11B show packet flows using a multi connectivity (e.g., dual connectivity, multi connectivity, tight interworking, and/or the like). FIG. 11A shows an example of a protocol structure of a wireless device 110 (e.g., UE) with CA and/or multi connectivity. FIG. 11B shows an example of a protocol structure of multiple base stations with CA and/or multi connectivity. The multiple base stations may comprise a master node, MN 1130 (e.g., a master

node, a master base station, a master gNB, a master eNB, and/or the like) and a secondary node, SN **1150** (e.g., a secondary node, a secondary base station, a secondary gNB, a secondary eNB, and/or the like). A master node **1130** and a secondary node **1150** may co-work to communicate with a wireless device **110**.

[0273] If multi connectivity is configured for a wireless device **110**, the wireless device **110**, which may support multiple reception and/or transmission functions in an RRC connected state, may be configured to utilize radio resources provided by multiple schedulers of a multiple base stations. Multiple base stations may be inter-connected via a non-ideal or ideal backhaul (e.g., Xn interface, X2 interface, and/or the like). A base station involved in multi connectivity for a certain wireless device may perform at least one of two different roles: a base station may act as a master base station or act as a secondary base station. In multi connectivity, a wireless device may be connected to one master base station and one or more secondary base stations. A master base station (e.g., the MN **1130**) may provide a master cell group (MCG) comprising a primary cell and/or one or more secondary cells for a wireless device (e.g., the wireless device **110**). A secondary base station (e.g., the SN **1150**) may provide a secondary cell group (SCG) comprising a primary secondary cell (PSCell) and/or one or more secondary cells for a wireless device (e.g., the wireless device **110**).

[0274] In multi connectivity, a radio protocol architecture that a bearer uses may depend on how a bearer is setup. Three different types of bearer setup options may be supported: an MCG bearer, an SCG bearer, and/or a split bearer. A wireless device may receive and/or send (e.g., transmit) packets of an MCG bearer via one or more cells of the MCG. A wireless device may receive and/or send (e.g., transmit) packets of an SCG bearer via one or more cells of an SCG. Multi-connectivity may indicate having at least one bearer configured to use radio resources provided by the secondary base station. Multi-connectivity may or may not be configured and/or implemented.

[0275] A wireless device (e.g., wireless device **110**) may send (e.g., transmit) and/or receive: packets of an MCG bearer via an SDAP layer (e.g., SDAP **1110**), a PDCP layer (e.g., NR PDCP **1111**), an RLC layer (e.g., MN RLC **1114**), and a MAC layer (e.g., MN MAC **1118**); packets of a split bearer via an SDAP layer (e.g., SDAP **1110**), a PDCP layer (e.g., NR PDCP **1112**), one of a master or secondary RLC layer (e.g., MN RLC **1115**, SN RLC **1116**), and one of a master or secondary MAC layer (e.g., MN MAC **1118**, SN MAC **1119**); and/or packets of an SCG bearer via an SDAP layer (e.g., SDAP **1110**), a PDCP layer (e.g., NR PDCP **1113**), an RLC layer (e.g., SN RLC **1117**), and a MAC layer (e.g., MN MAC **1118**).

[0276] A master base station (e.g., MN **1130**) and/or a secondary base station (e.g., SN **1150**) may send (e.g., transmit) and/or receive: packets of an MCG bearer via a master or secondary node SDAP layer (e.g., SDAP **1120**, SDAP **1140**), a master or secondary node PDCP layer (e.g., NR PDCP **1121**, NR PDCP **1142**), a master node RLC layer (e.g., MN RLC **1124**, MN RLC **1125**), and a master node MAC layer (e.g., MN MAC **1128**); packets of an SCG bearer via a master or secondary node SDAP layer (e.g., SDAP **1120**, SDAP **1140**), a master or secondary node PDCP layer (e.g., NR PDCP **1122**, NR PDCP **1143**), a secondary node RLC layer (e.g., SN RLC **1146**, SN RLC **1147**), and a secondary node MAC layer (e.g., SN MAC **1148**); packets of a split bearer via a master or secondary node SDAP layer (e.g., SDAP **1120**, SDAP **1140**), a master or secondary node PDCP layer (e.g., NR PDCP **1123**, NR PDCP **1141**), a master or secondary node RLC layer (e.g., MN RLC **1126**, SN RLC **1144**, SN RLC **1145**, MN RLC **1127**), and a master or secondary node MAC layer (e.g., MN MAC **1128**, SN MAC **1148**).

[0277] In multi connectivity, a wireless device may configure multiple MAC entities, such as one MAC entity (e.g., MN MAC **1118**) for a master base station, and other MAC entities (e.g., SN MAC **1119**) for a secondary base station. In multi-connectivity, a configured set of serving cells for a wireless device may comprise two subsets: an MCG comprising serving cells of a master base station, and SCGs comprising serving cells of a secondary base station. For an SCG, one or more of following configurations may be used. At least one cell of an SCG may have a configured UL CC and at least one cell of a SCG, named as primary secondary cell (e.g., PSCell, PCell of SCG,

PCell), and may be configured with PUCCH resources. If an SCG is configured, there may be at least one SCG bearer or one split bearer. After or upon detection of a physical layer problem or a random access problem on a PSCell, or a number of NR RLC retransmissions has been reached associated with the SCG, or after or upon detection of an access problem on a PSCell associated with (e.g., during) a SCG addition or an SCG change: an RRC connection re-establishment procedure may not be triggered, UL transmissions towards cells of an SCG may be stopped, a master base station may be informed by a wireless device of a SCG failure type, a DL data transfer over a master base station may be maintained (e.g., for a split bearer). An NR RLC acknowledged mode (AM) bearer may be configured for a split bearer. A PCell and/or a PSCell may not be deactivated. A PSCell may be changed with a SCG change procedure (e.g., with security key change and a RACH procedure). A bearer type change between a split bearer and a SCG bearer, and/or simultaneous configuration of a SCG and a split bearer, may or may not be supported.

[0278] With respect to interactions between a master base station and a secondary base stations for multi-connectivity, one or more of the following may be used. A master base station and/or a secondary base station may maintain RRM measurement configurations of a wireless device. A master base station may determine (e.g., based on received measurement reports, traffic conditions, and/or bearer types) to request a secondary base station to provide additional resources (e.g., serving cells) for a wireless device. After or upon receiving a request from a master base station, a secondary base station may create and/or modify a container that may result in a configuration of additional serving cells for a wireless device (or decide that the secondary base station has no resource available to do so). For a wireless device capability coordination, a master base station may provide (e.g., all or a part of) an AS configuration and wireless device capabilities to a secondary base station. A master base station and a secondary base station may exchange information about a wireless device configuration such as by using RRC containers (e.g., inter-node messages) carried via Xn messages. A secondary base station may initiate a reconfiguration of the secondary base station existing serving cells (e.g., PUCCH towards the secondary base station). A secondary base station may decide which cell is a PSCell within a SCG. A master base station may or may not change content of RRC configurations provided by a secondary base station. A master base station may provide recent (and/or the latest) measurement results for SCG cell(s), for example, if an SCG addition and/or an SCG SCell addition occurs. A master base station and secondary base stations may receive information of SFN and/or subframe offset of each other from an OAM and/or via an Xn interface (e.g., for a purpose of DRX alignment and/or identification of a measurement gap). Dedicated RRC signaling may be used for sending required system information of a cell as for CA, for example, if adding a new SCG SCell, except for an SFN acquired from an MIB of a PSCell of a SCG.

[0279] FIG. 12 shows an example of a random access procedure. One or more events may trigger a random access procedure. For example, one or more events may be at least one of following: initial access from RRC_IDLE, RRC connection re-establishment procedure, handover, DL or UL data arrival in (e.g., during) a state of RRC_CONNECTED (e.g., if UL synchronization status is non-synchronized), transition from RRC_Inactive, and/or request for other system information. A PDCCH order, a MAC entity, and/or a beam failure indication may initiate a random access procedure.

[0280] A random access procedure may comprise or be one of at least a contention based random access procedure and/or a contention free random access procedure. A contention based random access procedure may comprise one or more Msg 1 1220 transmissions, one or more Msg2 1230 transmissions, one or more Msg3 1240 transmissions, and contention resolution 1250. A contention free random access procedure may comprise one or more Msg 1 1220 transmissions and one or more Msg2 1230 transmissions. One or more of Msg 1 1220, Msg 2 1230, Msg 3 1240, and/or contention resolution 1250 may be transmitted in the same step. A two-step random access procedure, for example, may comprise a first transmission (e.g., Msg A) and a second transmission

(e.g., Msg B). The first transmission (e.g., Msg A) may comprise transmitting, by a wireless device (e.g., wireless device **110**) to a base station (e.g., base station **120**), one or more messages indicating an equivalent and/or similar contents of Msg**1 1220** and Msg**3 1240** of a four-step random access procedure. The second transmission (e.g., Msg B) may comprise transmitting, by the base station (e.g., base station **120**) to a wireless device (e.g., wireless device **110**) after or in response to the first message, one or more messages indicating an equivalent and/or similar content of Msg**2 1230** and contention resolution **1250** of a four-step random access procedure.

[0281] A base station may send (e.g., transmit, unicast, multicast, broadcast, etc.), to a wireless device, a RACH configuration **1210** via one or more beams. The RACH configuration **1210** may comprise one or more parameters indicating at least one of following: an available set of PRACH resources for a transmission of a random access preamble, initial preamble power (e.g., random access preamble initial received target power), an RSRP threshold for a selection of a SS block and corresponding PRACH resource, a power-ramping factor (e.g., random access preamble power ramping step), a random access preamble index, a maximum number of preamble transmissions, preamble group A and group B, a threshold (e.g., message size) to determine the groups of random access preambles, a set of one or more random access preambles for a system information request and corresponding PRACH resource(s) (e.g., if any), a set of one or more random access preambles for a beam failure recovery (BFR) procedure and corresponding PRACH resource(s) (e.g., if any), a time window to monitor RA response(s), a time window to monitor response(s) on a BFR procedure, and/or a contention resolution timer.

[0282] The Msg**1 1220** may comprise one or more transmissions of a random access preamble. For a contention based random access procedure, a wireless device may select an SS block with an RSRP above the RSRP threshold. If random access preambles group B exists, a wireless device may select one or more random access preambles from a group A or a group B, for example, depending on a potential Msg**3 1240** size. If a random access preambles group B does not exist, a wireless device may select the one or more random access preambles from a group A. A wireless device may select a random access preamble index randomly (e.g., with equal probability or a normal distribution) from one or more random access preambles associated with a selected group. If a base station semi-statically configures a wireless device with an association between random access preambles and SS blocks, the wireless device may select a random access preamble index randomly with equal probability from one or more random access preambles associated with a selected SS block and a selected group.

[0283] A wireless device may initiate a contention free random access procedure, for example, based on a beam failure indication from a lower layer. A base station may semi-statically configure a wireless device with one or more contention free PRACH resources for a BFR procedure associated with at least one of SS blocks and/or CSI-RSs. A wireless device may select a random access preamble index corresponding to a selected SS block or a CSI-RS from a set of one or more random access preambles for a BFR procedure, for example, if at least one of the SS blocks with an RSRP above a first RSRP threshold amongst associated SS blocks is available, and/or if at least one of CSI-RSs with a RSRP above a second RSRP threshold amongst associated CSI-RSs is available.

[0284] A wireless device may receive, from a base station, a random access preamble index via PDCCH or RRC for a contention free random access procedure. The wireless device may select a random access preamble index, for example, if a base station does not configure a wireless device with at least one contention free PRACH resource associated with SS blocks or CSI-RS. The wireless device may select the at least one SS block and/or select a random access preamble corresponding to the at least one SS block, for example, if a base station configures the wireless device with one or more contention free PRACH resources associated with SS blocks and/or if at least one SS block with a RSRP above a first RSRP threshold amongst associated SS blocks is available. The wireless device may select the at least one CSI-RS and/or select a random access preamble corresponding to the at least one CSI-RS, for example, if a base station configures a

wireless device with one or more contention free PRACH resources associated with CSI-RSs and/or if at least one CSI-RS with a RSRP above a second RSRP threshold amongst the associated CSI-RSs is available.

[0285] A wireless device may perform one or more **Msg1 1220** transmissions, for example, by sending (e.g., transmitting) the selected random access preamble. The wireless device may determine a PRACH occasion from one or more PRACH occasions corresponding to a selected SS block, for example, if the wireless device selects an SS block and is configured with an association between one or more PRACH occasions and/or one or more SS blocks. The wireless device may determine a PRACH occasion from one or more PRACH occasions corresponding to a selected CSI-RS, for example, if the wireless device selects a CSI-RS and is configured with an association between one or more PRACH occasions and one or more CSI-RSs. The wireless device may send (e.g., transmit), to a base station, a selected random access preamble via a selected PRACH occasions. The wireless device may determine a transmit power for a transmission of a selected random access preamble at least based on an initial preamble power and a power-ramping factor. The wireless device may determine an RA-RNTI associated with a selected PRACH occasion in which a selected random access preamble is sent (e.g., transmitted). The wireless device may not determine an RA-RNTI for a BFR procedure. The wireless device may determine an RA-RNTI at least based on an index of a first OFDM symbol, an index of a first slot of a selected PRACH occasions, and/or an uplink carrier index for a transmission of **Msg1 1220**.

[0286] A wireless device may receive, from a base station, a random access response, **Msg 2 1230**. The wireless device may start a time window (e.g., ra-ResponseWindow) to monitor a random access response. For a BFR procedure, the base station may configure the wireless device with a different time window (e.g., bfr-ResponseWindow) to monitor response on a BFR procedure. The wireless device may start a time window (e.g., ra-ResponseWindow or bfr-ResponseWindow) at a start of a first PDCCH occasion, for example, after a fixed duration of one or more symbols from an end of a preamble transmission. If the wireless device sends (e.g., transmits) multiple preambles, the wireless device may start a time window at a start of a first PDCCH occasion after a fixed duration of one or more symbols from an end of a first preamble transmission. The wireless device may monitor a PDCCH of a cell for at least one random access response identified by a RA-RNTI, or for at least one response to a BFR procedure identified by a C-RNTI, at a time that a timer for a time window is running.

[0287] A wireless device may determine that a reception of random access response is successful, for example, if at least one random access response comprises a random access preamble identifier corresponding to a random access preamble sent (e.g., transmitted) by the wireless device. The wireless device may determine that the contention free random access procedure is successfully completed, for example, if a reception of a random access response is successful. The wireless device may determine that a contention free random access procedure is successfully complete, for example, if a contention free random access procedure is triggered for a BFR procedure and if a PDCCH transmission is addressed to a C-RNTI. The wireless device may determine that the random access procedure is successfully completed, and may indicate a reception of an acknowledgement for a system information request to upper layers, for example, if at least one random access response comprises a random access preamble identifier. The wireless device may stop sending (e.g., transmitting) remaining preambles (if any) after or in response to a successful reception of a corresponding random access response, for example, if the wireless device has signaled multiple preamble transmissions.

[0288] The wireless device may perform one or more **Msg 3 1240** transmissions, for example, after or in response to a successful reception of random access response (e.g., for a contention based random access procedure). The wireless device may adjust an uplink transmission timing, for example, based on a timing advanced command indicated by a random access response. The wireless device may send (e.g., transmit) one or more transport blocks, for example, based on an

uplink grant indicated by a random access response. Subcarrier spacing for PUSCH transmission for **Msg3 1240** may be provided by at least one higher layer (e.g., RRC) parameter. The wireless device may send (e.g., transmit) a random access preamble via a PRACH, and **Msg3 1240** via PUSCH, on the same cell. A base station may indicate an UL BWP for a PUSCH transmission of **Msg3 1240** via system information block. The wireless device may use HARQ for a retransmission of **Msg 3 1240**.

[0289] Multiple wireless devices may perform **Msg 1 1220**, for example, by sending (e.g., transmitting) the same preamble to a base station. The multiple wireless devices may receive, from the base station, the same random access response comprising an identity (e.g., TC-RNTI). Contention resolution (e.g., comprising the wireless device **110** receiving contention resolution **1250**) may be used to increase the likelihood that a wireless device does not incorrectly use an identity of another wireless device. The contention resolution **1250** may be based on, for example, a C-RNTI on a PDCCH, and/or a wireless device contention resolution identity on a DL-SCH. If a base station assigns a C-RNTI to a wireless device, the wireless device may perform contention resolution (e.g., comprising receiving contention resolution **1250**), for example, based on a reception of a PDCCH transmission that is addressed to the C-RNTI. The wireless device may determine that contention resolution is successful, and/or that a random access procedure is successfully completed, for example, after or in response to detecting a C-RNTI on a PDCCH. If a wireless device has no valid C-RNTI, a contention resolution may be addressed by using a TC-RNTI. If a MAC PDU is successfully decoded and a MAC PDU comprises a wireless device contention resolution identity MAC CE that matches or otherwise corresponds with the CCCH SDU sent (e.g., transmitted) in **Msg3 1240**, the wireless device may determine that the contention resolution (e.g., comprising contention resolution **1250**) is successful and/or the wireless device may determine that the random access procedure is successfully completed.

[0290] FIG. 13 shows an example structure for MAC entities. A wireless device may be configured to operate in a multi-connectivity mode. A wireless device in RRC_CONNECTED with multiple Rx/Tx may be configured to utilize radio resources provided by multiple schedulers that may be located in a plurality of base stations. The plurality of base stations may be connected via a non-ideal or ideal backhaul over the Xn interface. A base station in a plurality of base stations may act as a master base station or as a secondary base station. A wireless device may be connected to and/or in communication with, for example, one master base station and one or more secondary base stations. A wireless device may be configured with multiple MAC entities, for example, one MAC entity for a master base station, and one or more other MAC entities for secondary base station(s). A configured set of serving cells for a wireless device may comprise two subsets: an MCG comprising serving cells of a master base station, and one or more SCGs comprising serving cells of a secondary base station(s). FIG. 13 shows an example structure for MAC entities in which a MCG and a SCG are configured for a wireless device.

[0291] At least one cell in a SCG may have a configured UL CC. A cell of the at least one cell may comprise a PSCell or a PCell of a SCG, or a PCell. A PSCell may be configured with PUCCH resources. There may be at least one SCG bearer, or one split bearer, for a SCG that is configured. After or upon detection of a physical layer problem or a random access problem on a PSCell, after or upon reaching a number of RLC retransmissions associated with the SCG, and/or after or upon detection of an access problem on a PSCell associated with (e.g., during) a SCG addition or a SCG change: an RRC connection re-establishment procedure may not be triggered, UL transmissions towards cells of a SCG may be stopped, and/or a master base station may be informed by a wireless device of a SCG failure type and DL data transfer over a master base station may be maintained.

[0292] A MAC sublayer may provide services such as data transfer and radio resource allocation to upper layers (e.g., **1310** or **1320**). A MAC sublayer may comprise a plurality of MAC entities (e.g., **1350** and **1360**). A MAC sublayer may provide data transfer services on logical channels. To accommodate different kinds of data transfer services, multiple types of logical channels may be

defined. A logical channel may support transfer of a particular type of information. A logical channel type may be defined by what type of information (e.g., control or data) is transferred. BCCH, PCCH, CCCH and/or DCCH may be control channels, and DTCH may be a traffic channel. A first MAC entity (e.g., **1310**) may provide services on PCCH, BCCH, CCCH, DCCH, DTCH, and/or MAC control elements. A second MAC entity (e.g., **1320**) may provide services on BCCH, DCCH, DTCH, and/or MAC control elements.

[0293] A MAC sublayer may expect from a physical layer (e.g., **1330** or **1340**) services such as data transfer services, signaling of HARQ feedback, and/or signaling of scheduling request or measurements (e.g., CQI). In dual connectivity, two MAC entities may be configured for a wireless device: one for a MCG and one for a SCG. A MAC entity of a wireless device may handle a plurality of transport channels. A first MAC entity may handle first transport channels comprising a PCCH of a MCG, a first BCH of the MCG, one or more first DL-SCHs of the MCG, one or more first UL-SCHs of the MCG, and/or one or more first RACHs of the MCG. A second MAC entity may handle second transport channels comprising a second BCH of a SCG, one or more second DL-SCHs of the SCG, one or more second UL-SCHs of the SCG, and/or one or more second RACHs of the SCG.

[0294] If a MAC entity is configured with one or more SCells, there may be multiple DL-SCHs, multiple UL-SCHs, and/or multiple RACHs per MAC entity. There may be one DL-SCH and/or one UL-SCH on an SpCell. There may be one DL-SCH, zero or one UL-SCH, and/or zero or one RACH for an SCell. A DL-SCH may support receptions using different numerologies and/or TTI duration within a MAC entity. A UL-SCH may support transmissions using different numerologies and/or TTI duration within the MAC entity.

[0295] A MAC sublayer may support different functions. The MAC sublayer may control these functions with a control (e.g., Control **1355** and/or Control **1365**) element. Functions performed by a MAC entity may comprise one or more of: mapping between logical channels and transport channels (e.g., in uplink or downlink), multiplexing (e.g., (De-) Multiplexing **1352** and/or (De-) Multiplexing **1362**) of MAC SDUs from one or different logical channels onto transport blocks (TBs) to be delivered to the physical layer on transport channels (e.g., in uplink), demultiplexing (e.g., (De-) Multiplexing **1352** and/or (De-) Multiplexing **1362**) of MAC SDUs to one or different logical channels from transport blocks (TBs) delivered from the physical layer on transport channels (e.g., in downlink), scheduling information reporting (e.g., in uplink), error correction through HARQ in uplink and/or downlink (e.g., **1363**), and logical channel prioritization in uplink (e.g., Logical Channel Prioritization **1351** and/or Logical Channel Prioritization **1361**). A MAC entity may handle a random access process (e.g., Random Access Control **1354** and/or Random Access Control **1364**).

[0296] FIG. **14** shows an example of a RAN architecture comprising one or more base stations. A protocol stack (e.g., RRC, SDAP, PDCP, RLC, MAC, and/or PHY) may be supported at a node. A base station (e.g., gNB **120A** and/or **120B**) may comprise a base station central unit (CU) (e.g., gNB-CU **1420A** or **1420B**) and at least one base station distributed unit (DU) (e.g., gNB-DU **1430A**, **1430B**, **1430C**, and/or **1430D**), for example, if a functional split is configured. Upper protocol layers of a base station may be located in a base station CU, and lower layers of the base station may be located in the base station DUs. An F1 interface (e.g., CU-DU interface) connecting a base station CU and base station DUs may be an ideal or non-ideal backhaul. F1-C may provide a control plane connection over an F1 interface, and F1-U may provide a user plane connection over the F1 interface. An Xn interface may be configured between base station CUs.

[0297] A base station CU may comprise an RRC function, an SDAP layer, and/or a PDCP layer. Base station DUs may comprise an RLC layer, a MAC layer, and/or a PHY layer. Various functional split options between a base station CU and base station DUs may be possible, for example, by locating different combinations of upper protocol layers (e.g., RAN functions) in a base station CU and different combinations of lower protocol layers (e.g., RAN functions) in base

station DUs. A functional split may support flexibility to move protocol layers between a base station CU and base station DUs, for example, depending on service requirements and/or network environments.

[0298] Functional split options may be configured per base station, per base station CU, per base station DU, per wireless device, per bearer, per slice, and/or with other granularities. In a per base station CU split, a base station CU may have a fixed split option, and base station DUs may be configured to match a split option of a base station CU. In a per base station DU split, a base station DU may be configured with a different split option, and a base station CU may provide different split options for different base station DUs. In a per wireless device split, a base station (e.g., a base station CU and at least one base station DUs) may provide different split options for different wireless devices. In a per bearer split, different split options may be utilized for different bearers. In a per slice splice, different split options may be used for different slices.

[0299] FIG. 15 shows example RRC state transitions of a wireless device. A wireless device may be in at least one RRC state among an RRC connected state (e.g., RRC Connected **1530**, RRC_Connected, etc.), an RRC idle state (e.g., RRC_Idle **1510**, RRC_Idle, etc.), and/or an RRC inactive state (e.g., RRC_Inactive **1520**, RRC_Inactive, etc.). In an RRC connected state, a wireless device may have at least one RRC connection with at least one base station (e.g., gNB and/or eNB), which may have a context of the wireless device (e.g., UE context). A wireless device context (e.g., UE context) may comprise at least one of an access stratum context, one or more radio link configuration parameters, bearer (e.g., data radio bearer (DRB), signaling radio bearer (SRB), logical channel, QoS flow, PDU session, and/or the like) configuration information, security information, PHY/MAC/RLC/PDCP/SDAP layer configuration information, and/or the like configuration information for a wireless device. In an RRC idle state, a wireless device may not have an RRC connection with a base station, and a context of the wireless device may not be stored in a base station. In an RRC inactive state, a wireless device may not have an RRC connection with a base station. A context of a wireless device may be stored in a base station, which may comprise an anchor base station (e.g., a last serving base station).

[0300] A wireless device may transition an RRC state (e.g., UE RRC state) between an RRC idle state and an RRC connected state in both ways (e.g., connection release **1540** or connection establishment **1550**; and/or connection reestablishment) and/or between an RRC inactive state and an RRC connected state in both ways (e.g., connection inactivation **1570** or connection resume **1580**). A wireless device may transition its RRC state from an RRC inactive state to an RRC idle state (e.g., connection release **1560**).

[0301] An anchor base station may be a base station that may keep a context of a wireless device (e.g., UE context) at least at (e.g., during) a time period that the wireless device stays in a RAN notification area (RNA) of an anchor base station, and/or at (e.g., during) a time period that the wireless device stays in an RRC inactive state. An anchor base station may comprise a base station that a wireless device in an RRC inactive state was most recently connected to in a latest RRC connected state, and/or a base station in which a wireless device most recently performed an RNA update procedure. An RNA may comprise one or more cells operated by one or more base stations. A base station may belong to one or more RNAs. A cell may belong to one or more RNAs.

[0302] A wireless device may transition, in a base station, an RRC state (e.g., UE RRC state) from an RRC connected state to an RRC inactive state. The wireless device may receive RNA information from the base station. RNA information may comprise at least one of an RNA identifier, one or more cell identifiers of one or more cells of an RNA, a base station identifier, an IP address of the base station, an AS context identifier of the wireless device, a resume identifier, and/or the like.

[0303] An anchor base station may broadcast a message (e.g., RAN paging message) to base stations of an RNA to reach to a wireless device in an RRC inactive state. The base stations receiving the message from the anchor base station may broadcast and/or multicast another

message (e.g., paging message) to wireless devices in their coverage area, cell coverage area, and/or beam coverage area associated with the RNA via an air interface.

[0304] A wireless device may perform an RNA update (RNAU) procedure, for example, if the wireless device is in an RRC inactive state and moves into a new RNA. The RNAU procedure may comprise a random access procedure by the wireless device and/or a context retrieve procedure (e.g., UE context retrieve). A context retrieve procedure may comprise: receiving, by a base station from a wireless device, a random access preamble; and requesting and/or receiving (e.g., fetching), by a base station, a context of the wireless device (e.g., UE context) from an old anchor base station. The requesting and/or receiving (e.g., fetching) may comprise: sending a retrieve context request message (e.g., UE context request message) comprising a resume identifier to the old anchor base station and receiving a retrieve context response message comprising the context of the wireless device from the old anchor base station.

[0305] A wireless device in an RRC inactive state may select a cell to camp on based on at least a measurement result for one or more cells, a cell in which a wireless device may monitor an RNA paging message, and/or a core network paging message from a base station. A wireless device in an RRC inactive state may select a cell to perform a random access procedure to resume an RRC connection and/or to send (e.g., transmit) one or more packets to a base station (e.g., to a network). The wireless device may initiate a random access procedure to perform an RNA update procedure, for example, if a cell selected belongs to a different RNA from an RNA for the wireless device in an RRC inactive state. The wireless device may initiate a random access procedure to send (e.g., transmit) one or more packets to a base station of a cell that the wireless device selects, for example, if the wireless device is in an RRC inactive state and has one or more packets (e.g., in a buffer) to send (e.g., transmit) to a network. A random access procedure may be performed with two messages (e.g., 2-stage or 2-step random access) and/or four messages (e.g., 4-stage or 4-step random access) between the wireless device and the base station.

[0306] A base station receiving one or more uplink packets from a wireless device in an RRC inactive state may request and/or receive (e.g., fetch) a context of a wireless device (e.g., UE context), for example, by sending (e.g., transmitting) a retrieve context request message for the wireless device to an anchor base station of the wireless device based on at least one of an AS context identifier, an RNA identifier, a base station identifier, a resume identifier, and/or a cell identifier received from the wireless device. A base station may send (e.g., transmit) a path switch request for a wireless device to a core network entity (e.g., AMF, MME, and/or the like), for example, after or in response to requesting and/or receiving (e.g., fetching) a context. A core network entity may update a downlink tunnel endpoint identifier for one or more bearers established for the wireless device between a user plane core network entity (e.g., UPF, S-GW, and/or the like) and a RAN node (e.g., the base station), such as by changing a downlink tunnel endpoint identifier from an address of the anchor base station to an address of the base station).

[0307] A base station may communicate with a wireless device via a wireless network using one or more technologies, such as new radio technologies (e.g., NR, 5G, etc.). The one or more radio technologies may comprise at least one of: multiple technologies related to physical layer; multiple technologies related to medium access control layer; and/or multiple technologies related to radio resource control layer. Enhancing the one or more radio technologies may improve performance of a wireless network. System throughput, and/or data rate of transmission, may be increased. Battery consumption of a wireless device may be reduced. Latency of data transmission between a base station and a wireless device may be improved. Network coverage of a wireless network may be improved. Transmission efficiency of a wireless network may be improved.

[0308] A base station, for example, a base station CU, may initiate PDCP duplication (e.g., PDCP packet duplication) for a bearer for a wireless device. The bearer may be an SRB and/or a DRB. A base station CU may, for example, initiate PDCP duplication for the bearer to increase a transmission reliability by creating a diversity gain of multiple packet transmission paths for

packets (e.g., a first path for original packets and a second path for duplicated packets (e.g., duplicated versions of the original packets)). The bearer may, for example, be used for ultra-reliable low-latency communications (URLLC) services.

[0309] If duplication is configured for a bearer via an RRC layer, an additional RLC entity and/or an additional logical channel may be configured for the radio bearer to handle duplicated PDCP PDUs. PDCP packet duplication may comprise sending the same PDCP PDUs at least twice: once by the original RLC entity and a second time by the additional RLC entity. By allowing two independent transmission paths, packet duplication may increase reliability and may reduce latency by reducing packet retransmission delays. PDCP duplication may be beneficial for a variety of services such as, for example, URLLC services. Original PDCP PDUs and corresponding duplicate PDCP PDUs may be sent (e.g., transmitted) on different carriers. Two different logical channels may belong to a same MAC entity (e.g., if CA is used) and/or to different MAC entities (e.g., if DC is used). If CA is used, logical channel mapping restrictions may be used by a MAC entity to avoid a logical channel carrying the original PDCP PDUs and a logical channel carrying the corresponding PDCP PDUs being sent on the same carrier.

[0310] If PDCP packet duplication is configured and, for example, for uplink packet transmissions, packet duplication may be activated and/or de-activated per DRB (and/or SRB) by using a MAC control element (MAC CE). If CA is used, and if duplication is deactivated, logical channel mapping restrictions may be lifted. If DC is used, a wireless device (e.g., a UE) may apply MAC CE commands regardless of the origin(s) (e.g., a MCG and/or an SCG) of those MAC CEs.

[0311] If one or more DRBs are configured with PDCP packet duplication, a network may, for example, activate and deactivate the PDCP packet duplication for the configured DRB(s). Uplink PDCP packet duplication for the configured DRB(s) may be activated and deactivated based on sending, to a wireless device, a duplication activation/deactivation MAC CE. A MAC entity processing the duplication activation/deactivation MAC CE may be for a DRB configured with duplication. If a duplication activation/deactivation MAC CE is received activating the PDCP duplication of the DRB, for example, the MAC entity may indicate the activation of PDCP packet duplication of the DRB to upper layers and/or may apply the allowedServingCells parameter(s) (e.g., received in one or more configuration messages) to the logical channels of the DRB. If a duplication activation/deactivation MAC CE is received deactivating PDCP packet duplication for the DRB, the MAC entity may indicate the deactivation of PDCP packet duplication of the DRB to upper layers and/or may refrain from applying the allowedServingCells parameter(s) to the logical channels of the DRB.

[0312] FIG. 16A shows an example duplication activation/deactivation MAC CE. A duplication activation/deactivation MAC CE may have a fixed size. As shown in FIG. 16A, a duplication activation/deactivation MAC CE may comprise a single octet containing eight D-fields. D_i may indicate that the activation/deactivation status of PDCP packet duplication for DRB i , and i may be the ascending order of DRB IDs configured with packet duplication. The D_i field may be set to one to indicate that PDCP packet duplication of DRB i may be activated. The D_i field may be set to zero to indicate that PDCP packet duplication of DRB i may be deactivated.

[0313] FIG. 16B shows example values for a Logical Channel Identifier (LCID) field. A duplication activation/deactivation MAC CE may be part of a MAC PDU and may be indicated by a MAC PDU subheader with an LCID. The MAC subheader may comprise an LCID field identifying the logical channel instance of the corresponding MAC SDU, the type of the corresponding MAC CE, and/or padding for a DL-SCH. There may be one LCID field per MAC subheader. The LCID field size may be 6 bits. An LCID value for a subheader indicating a duplication activation/deactivation MAC CE may, for example, as shown in FIG. 16B, be 111000. An L (Length) field of the subheader may indicate the length of the corresponding MAC SDU or variable-sized MAC CE in bytes. There may be one L field per MAC subheader except for subheaders corresponding to fixed-sized MAC CEs or padding. The size of the L field may be

indicated by an F (Format) field indicating the size of the Length field. There may be one F field per MAC subheader except for subheaders corresponding to fixed-sized MAC CEs or padding. The size of the F field may be 1 bit. The value 0 may indicate 8 bits of the Length field. The value 1 may indicate 16 bits of the Length field. An R (Reserved bit) of the MAC subheader may be set to zero. The MAC subheader may be octet aligned.

[0314] If two UL General Packet Radio Service (GPRS) Tunneling Protocol (GTP) Tunnel Endpoint IEs are included in a UE CONTEXT SETUP REQUEST message for a DRB, a DU (e.g., a gNB-DU) may include two DL GTP Tunnel Endpoint IEs in a UE CONTEXT SETUP RESPONSE message. A CU (e.g., a gNB-CU) and/or a DU (e.g., gNB-DU) may use the UL GTP Tunnel Endpoint IEs and DL GTP Tunnel Endpoint IEs to support packet duplication for intra-DU (e.g., intra-gNB-DU) CA.

[0315] A base station may, for example, if PDCP packet duplication is configured for a bearer of a wireless device, activate or deactivate PDCP packet duplication. The base station may, for example, activate packet duplication for the bearer based on: one or more radio conditions, status of one or more resources, and/or one or more configuration policies. If a radio quality for a wireless device decreases (e.g., below a predetermined level and/or based on one or more measurements), a base station may activate PDCP packet duplication (e.g., for uplink and/or downlink PDCP packets) of a bearer. PDCP packet duplication may be used, for example, for high reliability and/or low latency services. A base station may deactivate PDCP packet duplication for a bearer if, for example, resources of a network (e.g., of the base station and/or of the wireless device) are determined insufficient to support PDCP packet duplication.

[0316] Functions of a base station may be separately performed by different network nodes. Functions of a base station may, for example, be performed by a base station CU and at least one base station DU. Functions of a base station CU may be further divided, for example, between a central unit user plane (CU-UP) node and central unit control plane (CU-CP) node. A CU-CP node may, for example, perform an RRC function. A CU-UP node may, for example, control upper layer user plane functions (e.g., one or more PDCP layer functions, and/or one or more SDAP layer functions). A DU may control lower layer functions (e.g., one or more physical layer functions, one or more MAC layer functions, and/or one or more RLC layer functions).

[0317] A CU-UP node controlling a PDCP layer may perform duplication of at least downlink PDCP packets if PDCP packet duplication is activated for a bearer and/or for a wireless device. A CU-UP node may activate PDCP packet duplication without status information for other network nodes (e.g., for a DU, a CU-CP node, and/or a wireless device) that control operations that may be affected by, and/or that may have an effect on, PDCP packet duplication. Without such status information, a CU-UP node may activate and/or maintain PDCP packet duplication during periods when packet duplication is undesirable. If a DU is in a high traffic load state, for example, there may be insufficient resources to support packet duplication. Use of packet duplication under such circumstances may lead to call dropping and/or other losses of service. If radio link quality is sufficiently good, packet duplication may provide little or no advantage (e.g., there may be little or no packet loss on a single bearer), and using resources for unnecessary packet duplication may reduce resources available for allocation to communications to or from other devices. A CU-UP node without status information from other nodes may also or alternatively deactivate PDCP packet duplication during periods (e.g., if a DU is not in a high traffic load state and/or if radio link quality is not good) packet duplication may be desirable.

[0318] Communication reliability and/or resource utilization efficiency may be adversely affected if status information is unavailable for determining packet duplication activation and/or deactivation. Without such information and/or signaling mechanisms facilitating coordination of operations (e.g., packet duplication activation/deactivation) among split base station nodes (e.g., a CU-CP node, a CU-UP node, and/or a DU) decreased reliability and inefficient resource utilization may increase call dropping rate, may increase packet transmission delay, and/or may otherwise

impact services requiring high reliability and/or low latency.

[0319] One or more of these problems may be avoided and/or reduced by improved PDCP packet duplication signaling. A CU-CP node may, for example, determine activation and/or deactivation of PDCP packet duplication based on radio channel quality and/or based on traffic load status of a DU and/or of a wireless device. Based on such a determination, the CU-CP node may send, to a CU-UP node, an activation/deactivation indication for PDCP packet duplication. The CU-UP node may activate and/or deactivate PDCP packet duplication based on the activation/deactivation indication received from CU-CP node, thereby facilitating activation and/or deactivation based on radio channel quality and/or traffic load status, and allowing increased resource utilization efficiency and/or increased packet transmission reliability.

[0320] A CU-UP node may also or alternatively determine activation and/or deactivation of PDCP packet duplication. The CU-UP node may determine such activation and/or deactivation based on status information received, for example, from a CU-CP node. Determining activation and/or deactivation based on such status information may facilitate activation and/or deactivation based on radio channel quality and/or traffic load status, and may allow increased resource utilization efficiency and/or increased packet transmission reliability. A CU-UP node that determines activation and/or deactivation may also or alternatively inform the CU-CP node of such determination, thereby allowing, for example, more efficient allocation of resources.

[0321] A DU may also or alternatively determine activation and/or deactivation of PDCP packet duplication. The DU may determine such activation and/or deactivation based on status information received, for example, from a CU-CP node and/or from a wireless device. Determining activation and/or deactivation based on such status information may facilitate activation and/or deactivation based on radio channel quality and/or traffic load status, and may allow increased resource utilization efficiency and/or increased packet transmission reliability. A DU that determines activation and/or deactivation may also or alternatively inform the CU-CP node of such determination, thereby allowing, for example more efficient allocation of resources.

[0322] FIG. 17 shows example nodes (e.g., an example CU-CP node, an example CU-UP node, an example DU, and an example wireless device) that may be associated with PDCP packet duplication. In FIG. 17 and in various other figures WD is used as an abbreviation for wireless device (e.g., UE). A base station may comprise a CU-CP node **1701**, a CU-UP node **1702**, and/or one or more DUs **1703**. The DU **1703** may communicate with a wireless device **1704** (e.g., a UE). The CU-CP node **1701** and the CU-UP node **1702** may, for example, be nodes of a CU such as the gNB-CU **1420A** or the gNB-CU **1420B** of FIG. 14. The DU(s) **1703** may, for example, be one or more of the gNB-DUs **1430A**, **1430B**, **1430C**, or **1430D** of FIG. 14. The wireless device **1704** may be one of the wireless devices described in connection with other figures described herein. The CU-CP node **1701** may comprise upper layer control plane functions (e.g., RRC functions). The CU-UP node **1702** may comprise upper layer user plane functions (e.g., SDAP functions and/or PDCP functions). The DU **1703** may comprise lower layer functions (e.g., RLC functions, MAC functions, and/or PHY functions). PDCP packets (e.g., PDCP PDUs and/or PDCP SDUs) may be sent (e.g., transmitted) via an interface (e.g., an F1 user plane interface (and/or an interface between the CU-CP node **1701** and the DU **1703**)) between the CU-UP node **1702** (and/or the CU-CP node **1701**) and the DU **1703**. As shown in FIG. 17 with large-dash broken lines, DL PDCP duplicate packets may be generated and sent, with original PDCP packets, by the CU-UP node **1702** to the DU **1703**, which may forward those original and duplicate packets to the wireless device **1704**. DL original and duplicate PDCP packets may also or alternatively be generated and sent (e.g., transmitted) by the CU-CP node **1701** to the DU **1703**, which may forward such packets to the wireless device **1704**. The wireless device **1704** may also or alternatively generate original and duplicate UL PDCP packets and send those packets to the DU **1703**, which may forward those UL packets to the CU-UP node **1702** (and/or to the CU-CP node **1701**).

[0323] The CU-CP node **1701** may send one or more messages to the CU-UP node **1702** to

configure, activate, and/or deactivate PDCP packet duplication. The CU-CP node **1701** may, for example send one or more messages to configure PDCP packet duplication for a bearer (e.g., by indicating a bearer, a logical channel, a QoS flow, and/or a PDU session) for the wireless device **1704**. That bearer may comprise a packet flow to provide one or more URLLCs, one or more vehicle communications, one or more emergency services communications, one or more drone control communications, one or more remote control communications, and/or one or more other services for the wireless device **1704**. The bearer may comprise at least one of an SRB or a DRB. [0324] FIG. **18** shows an example initial context setup request message. A bearer (e.g., for which PDCP packet duplication is being configured) may comprise one or more packet flows of a PDU session for the wireless device **1704**. The PDU session may be configured based on a context setup request message from a core network entity (e.g., an AMF and/or a MME) for the wireless device. The context setup request message may be an initial context setup request message (e.g., as shown in FIG. **18**) and/or a wireless device (e.g., UE) context modification request message. The CU-UP node **1702** may send one or more response messages to the CU-CP node **1701** based on receiving one or more messages to configure, activate, and/or deactivate PDCP packet duplication. [0325] As shown in FIG. **17** with small-dash broken lines, and as further described below, information (e.g., status information) may be communicated by the wireless device **1704** to the DU **1703** and/or the CU-CP node **1701**, and/or from the DU **1703** to the CU-CP node **1701**. The wireless device **1704** may, for example, send one or more CSI reports and/or SRSs to the DU **1703** and/or send (e.g., via the DU **1703**) RRC UE status information to the CU-CP **1701**. The DU **1703** may, for example, send DU and/or lower layer wireless device (e.g., UE) status information to the CU-CP node **1701**.

[0326] FIG. **19** shows an example method, for PDCP packet duplication configuration, activation, and/or deactivation, that may be performed by one or more of the CU-CP node **1701**, the CU-UP node **1702**, the DU **1703**, and/or the wireless devices **1704**, and/or by one or more other nodes. The CU-CP node **1701** may send (e.g., transmit), to the CU-UP node **1702**, one or more messages **1901** indicating a bearer configuration request for the wireless device **1704**. The bearer configuration request of the message(s) **1901** may be associated with at least a first bearer for which PDCP packet duplication is being configured. The first bearer may comprise a bearer configured for E-UTRAN and/or NG-RAN. The message(s) **1901** may comprise a bearer context setup request message (e.g., as shown in FIG. **20**), a bearer context modification request message, a bearer context modification confirm message, and/or other type(s) of message(s). The message(s) **1901** may comprise a PDCP configuration parameter indicating that PDCP packet duplication is configured for the first bearer. A PDCP-Config (e.g., an RRC information element (IE)) of the message(s) **1901** may, for example, comprise the PDCP configuration parameter. A pdcp-Duplication IE of a PDCP-Config **1E** (see, e.g., “PDCP Configuration” in FIG. **20**) may, for example, indicate ENUMERATED {true}, indicating that PDCP packet duplication is configured for the first bearer.

[0327] The message(s) **1901** may, for example, comprise an information element explicitly indicating activation or deactivation of uplink and/or downlink PDCP packet duplication of the first bearer (e.g., the bearer for which PDCP packet duplication is being configured). Also or alternatively, uplink and/or downlink PDCP packet duplication may be implicitly activated or deactivated via the message(s) **1901**. Implicit activation may occur, for example, if the CU-UP node **1702** is configured to determine, based on receiving one or more messages **1901** indicating that PDCP packet duplication is configured, that PDCP packet duplication is initially activated for uplink and/or downlink based on that initial configuration. Implicit deactivation may occur, for example, if the CU-UP node **1702** is configured to determine, based on receiving the message(s) **1901** indicating that PDCP packet duplication is configured, that PDCP packet duplication is initially deactivated for uplink and/or downlink based on that configuration.

[0328] The message(s) **1901** may, for example, comprise at least one of: a wireless device identifier

(e.g., a gNB-CU-CP UE E1AP ID, a gNB-CU-UP UE E1AP ID, an IMEI, and/or a TMSI) of the wireless device **1704**, a bearer identifier of the first bearer (e.g., the bearer for which PDCP packet duplication is being configured), one or more bearer identifiers of one or more other bearers requested to be setup, modified, and/or removed, one or more identifiers of one or more PDU sessions, and/or one or more identifiers of one or more QoS flows requested to be setup, modified, and/or removed. The message(s) **1901** may also or alternatively comprise, for example, one or more PDCP configuration information elements of the first bearer, QoS information (e.g., QCI, ARP, 5QI, session AMBR, and/or other information) of the first bearer and/or of other bearer(s), PDU session(s), and/or QoS flow(s) requested to be setup and/or modified, S1/NG uplink user plane transport layer information (e.g., a tunnel endpoint identifier, an IP address of an S-GW, and/or a UPF), and/or data forwarding information. The message(s) **1901** may also or alternatively comprise, for example, cell group information (e.g., an MCG and/or an SCG), a PDU session identifier of a PDU session associated with the first bearer, and/or one or more network slice identifiers (e.g., an NSSAI and/or a single-NSSAI (S-NSSAI)) of one or more network slices associated with the first bearer and/or with other bearer(s), with one or more PDU sessions, and/or with one or more QoS flows. The message(s) **1901** may also or alternatively comprise, for example, flow mapping information and/or other information.

[0329] The message(s) **1901** may, for example, comprise a first logical channel identifier of a first logical channel for PDCP packets of the first bearer (e.g., the bearer for which PDCP packet duplication is being configured) and/or a second logical channel identifier of a second logical channel for duplicated PDCP packets of the first bearer. The message(s) **1901** may, for example, comprise a DL tunnel endpoint identifier (TEID) of a first tunnel for PDCP packets of the first bearer and/or a second DL TEID of a second tunnel for duplicated PDCP packets of the first bearer. The first DL TEID and/or the second DL TEID may comprise addresses (e.g., IP addresses) of a DU (e.g., of the DU **1703**). The CU-UP node **1702** may send (e.g., transmit) PDCP packets (e.g., original PDCP packets) of the first bearer to the first DL TEID, and/or may (e.g., if PDCP packet duplication is activated) send (e.g., transmit) duplicated PDCP packets (e.g., duplicated versions of the original packets) of the first bearer to the second DL TEID. The CU-CP node **1701** may receive the first DL TEID and/or the second DL TEID from the DU (e.g., the DU **1703**). The first DL TEID and/or the second DL TEID may also or alternatively be sent (e.g., transmitted), from the CU-CP node **1701** to the CU-UP node **1702**, via another message different from the message(s) **1901**. The first DL TEID and/or the second DL TEID may, for example, be sent via one or more messages **1907** (described below), one or more messages **2103** (FIG. 21), one or more messages **2107** (FIG. 21), one or more messages **2205** (FIG. 22), and/or one or more messages **2209** (FIG. 22).

[0330] The CU-UP node **1702** may, for example, based on receiving the message(s) **1901**, configure a first packet flow (e.g., a tunnel, a logical channel, a bearer, a QoS flow, and/or a PDU session) for PDCP packets of the first bearer (e.g., the bearer for which PDCP packet duplication is being configured) and/or may configure a second packet flow (e.g., a tunnel, a logical channel, a bearer, a QoS flow, and/or a PDU session) for duplicated PDCP packets of the first bearer. The CU-UP node **1702** may, for example, based on receiving the message(s) **1901**, configure a first UL TEID of a first tunnel for PDCP packets (e.g., packets, PDCP PDUs and/or PDCP SDUs) of the first bearer and/or a second UL TEID of a second tunnel for duplicated PDCP packets (e.g., duplicated packets, PDCP PDUs, and/or PDCP SDUs) of the first bearer. The CU-UP node **1702** may, for example, based on the message(s) **1901** and/or on configuration performed based on the message(s) **1901**, send (e.g., transmit), to the CU-CP node **1701**, one or more messages **1902** indicating that the PDCP packet duplication of the first bearer has been set up (e.g., configured) by the CU-UP node **1702**. The message(s) **1902** may, for example, further indicate that a bearer configuration request (e.g., of the message(s) **1901**) for the wireless device **1704** is accepted (e.g., allowed and/or configured at the CU-UP node **1702**). The message(s) **1902** may comprise at least one of a bearer context setup response message, a bearer context modification response message, a

bearer context modification required message, and/or other type of message.

[0331] The message(s) **1902** may, for example, further comprise the first UL TEID of the first tunnel for PDCP packets of the first bearer and/or the second UL TEID of the second tunnel for duplicated PDCP packets of the first bearer for the wireless device. The DU **1703** may send (e.g., transmit) PDCP packets (e.g., original PDCP packets) of the first bearer to the first UL TEID, and/or may (e.g., if PDCP packet duplication is activated) send (e.g., transmit) duplicated PDCP packets of the first bearer to the second UL TEID. The DU **1703** may receive the first UL TEID and/or the second UL TEID from the CU-CP node **1701**. The first UL TEID and/or the second UL TEID may comprise addresses (e.g., IP addresses) of the CU-UP node **1702**. The first UL TEID and/or the second UL TEID, if present in the message(s) **1902**, may indicate that PDCP packet duplication for the first bearer is setup (e.g., configured) at the CU-UP node **1702**.

[0332] The message(s) **1902** may, for example, comprise at least one of: the wireless device identifier (e.g., a gNB-CU-CP UE E1AP ID, a gNB-CU-UP UE E1AP ID, a IMEI, and/or a TMSI) of the wireless device **1704**, the first bearer identifier of the first bearer (e.g., the bearer for which PDCP packet duplication is being configured), one or more bearer identifiers of one or more bearers for which setup or modification failed or succeeded, one or more identifiers of one or more PDU sessions and/or one or more QoS flows for which setup or modification failed or succeeded, and/or one or more failure causes for bearer(s), PDU session(s), and/or QoS flows for which setup or modification failed. The message(s) **1902** may also or alternatively comprise, for example, PDCP configuration result information of the first bearer and/or QoS information (e.g., QCI, ARP, 5QI, session AMBR, and/or other information) of one or more bearers, one or more PDU sessions, and/or one or more QoS flows to be setup and/or modified. The message(s) **1902** may also or alternatively comprise, for example, S1/NG downlink user plane transport layer information (e.g., a tunnel endpoint identifier and/or an IP address of the CU-UP node **1702**), uplink user plane transport parameters comprising user plane transport layer information and/or cell group identifiers, data forwarding information, cell group information (e.g., MCG and/or SCG), the PDU session identifier of the PDU session associated with the first bearer, the network slice identifier (e.g., an NSSAI and/or an S-NSSAI) of the network slice associated with the first bearer, one or more network slice identifiers of one or more network slices associated with the one or more other bearers, flow mapping information, and/or other information.

[0333] The CU-UP node **1702** may, for example, based on the CU-UP node **1702** status, determine to setup, modify, and/or fail one or more bearers, one or more PDU sessions, one or more QoS flows, and/or the PDCP duplication configuration of the first bearer requested by the CU-CP node **1701**. The status of the CU-UP node **1702** may, for example, comprise a network resource status, a processing resource status (e.g., CPU, RAM, bus, and/or other system capacity), an interface congestion status of NG, F1, and/or S1 interfaces, bearer priority information (e.g., a bearer QoS level and/or a network slice priority of the bearer), and/or other information. If, for example, the network resources of the CU-UP node **1702** are not sufficient to serve all requested elements (e.g., all bearers, PDU sessions, QoS flows, and/or PDCP duplication), the CU-UP node **1702** may determine to fail one or more of the requested elements and may indicate the determined failure to the CU-CP node **1701** via the message(s) **1902**.

[0334] The CU-CP node **1701** may, for example, send (e.g., transmit) one or more messages **1903** indicating a bearer configuration request for the first bearer (e.g., the bearer for which PDCP packet duplication is being configured) of the wireless device. The CU-CP node **1701** may send (e.g., transmit) the message(s) **1903** to the DU **1703** based on receiving the message(s) **1902** from the CU-UP node **1702**. Alternatively, the CU-CP node **1701** may send (e.g., transmit) message(s), similar to the message(s) **1903**, to the DU **1703** before receiving messages, similar to the message(s) **1902**, from the CU-UP node **1702**. Also or alternatively, the CU-CP node **1701** may send (e.g., transmit) messages, similar to the message(s) **1902**, to the DU **1703** before sending (e.g., transmitting) messages, similar to the message(s) **1901**, to the CU-UP node **1702**. The messages

1903, and/or other bearer configuration requests sent from the CU-CP node **1701** to the DU **1703**, may indicate that PDCP packet duplication is configured for the first bearer of the wireless device. The message(s) **1903** may comprise the first UL TEID of the first tunnel for PDCP packets of the first bearer and/or the second UL TEID of the second tunnel for duplicated PDCP packets of the first bearer for the wireless device. The first UL TEID and/or the second UL TEID may be received, by the CU-CP node **1701**, via the message(s) **1902** and/or via other message(s) from the CU-UP node **1702**. The DU **1703** may, for example, based on the first UL TEID and/or the second UL TEID for the first bearer, recognize that PDCP duplication is configured for the first bearer. The DU **1703** may, for example, based on the message(s) **1903**, send (e.g., transmit) PDCP packets (e.g., original PDCP packets) of the first bearer to the first UL TEID, and/or may (e.g., if packet duplication is activated) send (e.g., transmit) duplicated PDCP packets of the first bearer to the second UL TEID.

[0335] The message(s) **1903** may, for example, comprise at least one of a wireless device (e.g., UE) context setup request message, a wireless device (e.g., UE) context modification request message, a wireless device (e.g., UE) context modification confirm message, and/or another type of message. Also or alternatively, the message(s) **1903** may comprise at least one of: a wireless device identifier (e.g., a gNB-CU-UE F1AP ID, a gNB-DU UE F1AP ID, an IMEI, and/or a TMSI) of the wireless device **1704**, an SpCell identifier, one or more candidate SpCell identifiers of one or more candidate SpCells, CU-to-DU RRC information, DRX cycle information, a resource coordination transfer container, and/or one or more SCell (secondary cell) identifiers of one or more SCells to be setup. Also or alternatively, the message(s) **1903** may comprise one or more bearer identifiers of one or more bearers (e.g., DRB, SRB) to be setup, modified, and/or removed, may comprise one or more identifiers of one or more PDU sessions and/or one or more QoS flows requested to be setup, modified, and/or removed, may comprise one or more QoS information of the one or more bearers to be setup and/or modified, and/or may comprise one or more tunnel information associated with the one or more bearers to be setup and/or modified. Also or alternatively, the message(s) **1903** may comprise one or more network slice identifiers (e.g., an NSSAI, and/or an S-NSSAI) of one or more network slices associated with the first bearer, with one or more other bearers (e.g., other bearers indicated in the message(s) **1903** for setup, modification, and/or removal), with one or more PDU sessions (e.g., other PDU sessions indicated in the fourth message(s) **1903** for setup, modification, and/or removal), and/or with one or more QoS flows (e.g., QoS flows indicated in the message(s) **1903** for setup, modification, and/or removal), may comprise RLC mode information of one or more bearers, may comprise uplink configuration information of one or more bearers, and/or may comprise other information.

[0336] The DU **1703** may, for example, based on receiving the message(s) **1903**, configure a first packet flow (e.g., a tunnel, a logical channel, a bearer, a QoS flow, and/or a PDU session) for PDCP packets of the first bearer and/or may configure a second packet flow (e.g., a tunnel, a logical channel, a bearer, a QoS flow, and/or a PDU session) for duplicated PDCP packets of the first bearer. The DU **1703** may, for example, based on receiving the message(s) **1903**, configure a first DL TEID of a first tunnel for PDCP packets (e.g., packets, PDCP PDUs, and/or PDCP SDUs) of the first bearer and/or a second DL TEID of a second tunnel for duplicated PDCP packets (e.g., duplicated packets, PDCP PDUs, and/or PDCP SDUs) of the first bearer. The first DL TEID and/or the first UL TEID may, for example, be associated with the first tunnel for PDCP packets of the first bearer. The second DL TEID and/or the second UL TEID may, for example, be associated with the second tunnel for duplicated PDCP packets of the first bearer.

[0337] The DU **1703** may, for example, based on the message(s) **1903**, send (e.g., transmit), to the CU-CP node **1701**, one or more message(s) **1904** indicating that the PDCP packet duplication of the first bearer (e.g., the bearer for which PDCP packet duplication is being configured) is set up (e.g., configured). The message(s) **1904** may, for example, further indicate that one or more requests of the message(s) **1903** (or other bearer configuration request for the wireless device) are

accepted (e.g., allowed and/or configured at the DU **1703**). The message(s) **1904** may, for example, comprise at least one of a wireless device (e.g., UE) context setup response message, a wireless device (e.g., UE) context modification response message, a wireless device (e.g., UE) context modification required message, and/or another type of message. The message(s) **1904** may, for example, indicate that PDCP packet duplication for the first bearer is setup (e.g., configured) at the DU **1703**.

[0338] The message(s) **1904** may, for example, comprise the first DL TEID of the first tunnel for PDCP packets of the first bearer and/or the second DL TEID of the second tunnel for duplicated PDCP packets of the first bearer for the wireless device. The CU-UP node **1702** may, for example, send (e.g., transmit) downlink PDCP packets (e.g., original PDCP packets) of the first bearer to the first DL TEID, and/or may (e.g., if PDCP packet duplication is activated) send (e.g., transmit) duplicated downlink PDCP packets of the first bearer to the second DL TEID. The first DL TEID and/or the second DL TEID may comprise addresses (e.g., IP addresses) of the DU **1703**. The first DL TEID and/or the second DL TEID may, for example, be sent (e.g., transmitted) from the DU **1703** to the CU-CP node **1701** via one or more other messages different from the message(s) **1904**. The first DL TEID and/or the second DL TEID being present in the message(s) may, for example, indicate that PDCP packet duplication for the first bearer is setup (e.g., configured) at the DU **1703**.

[0339] Also or alternatively, the message(s) **1904** may comprise at least one of: the wireless device identifier (e.g., a gNB-CU UE F1AP ID, a gNB-DU UE F1AP ID, an IMEI, and/or a TMSI) of the wireless device **1704**, DU-to-CU RRC information, a resource coordination transfer container, and/or the bearer identifier of the first bearer (e.g., the bearer for which PDCP packet duplication is being configured). Also or alternatively, the message(s) **1904** may comprise one or more bearer identifiers of one or more other bearers (e.g., SRBs, DRBs) for which setup or modification failed or succeeded, one or more identifiers of one or more PDU sessions and/or of one or more QoS flows for which set or modification failed or succeeded, and/or one or more failure causes for one or more bearers, one or more PDU sessions, and/or the one or more QoS flows for which setup or modification failed. Also or alternatively, the message(s) **1904** may comprise QoS information (e.g., QCI, ARP, 5QI, session AMBR, and/or other information) of one or more bearers, or one or more PDU sessions, and/or of one or more QoS flows to be setup and/or modified, and/or may comprise downlink tunnel endpoint identifiers (e.g., IP addresses of the DU **1703**) of one or more tunnels associated with one or more bearers, one or more PDU sessions, and/or of one or more QoS flows to setup and/or modify. Also or alternatively, the message(s) **1904** may comprise cell group information (e.g., MCG and/or SCG), the PDU session identifier of the PDU session associated with the first bearer, the network slice identifier(s) (e.g., an NSSAI and/or an S-NSSAI) of the network slice associated with the first bearer and/or of one or more network slices associated with one or more other bearers, and/or flow mapping information.

[0340] The DU **1703** may, for example, based on the DU **1703** status, determine to setup, modify, and/or fail one or more bearers, one or more PDU sessions, one or more QoS flows, and/or the PDCP duplication configuration of the first bearer requested by the CU-CP node **1701**. The status of the DU **1703** may, for example, comprise a network resource status, a radio resource status, a processing resource status (e.g., CPU, RAM, bus, and/or other system capacity), an interface congestion status of F1 and/or Uu interfaces, bearer priority information (e.g., a bearer QoS level and/or a network slice priority of the bearer), and/or other information. If, for example, the network resources of the DU **1703** are not sufficient to serve all requested elements (e.g., all bearers, PDU sessions, QoS flows, and/or PDCP duplication), the DU **1703** may determine to fail one or more of the requested elements and may indicate the determined failure to the CU-CP node **1701** via the message(s) **1904**.

[0341] The CU-CP node **1701** may, for example, based on receiving the message(s) **1902** and/or the message(s) **1904**, send (e.g., transmit), to the wireless device **1704**, one or more messages **1905**. The message(s) **1905** may comprise an RRC message (e.g., an RRC connection reconfiguration

message) comprising a PDCP configuration parameter indicating that PDCP packet duplication is configured for the first bearer. The CU-CP node **1701** may send (e.g., transmit) the message(s) **1905** to the DU **1703** via an F1 interface message (e.g., a DL RRC message transfer message and/or a wireless device (e.g., UE) context modification request message), and the DU **1703** may forward the message(s) **1905** to the wireless device **1704**. A PDCP-Config (e.g., an RRC IE) of the message(s) **1905** may comprise the PDCP configuration parameter. A pdcp-Duplication IE of the PDCP-Config IE may indicate ENUMERATED {true}, indicating that PDCP packet duplication is configured for the first bearer. The message(s) **1905** may further comprise a bearer identifier of the first bearer, a first logical channel identifier of a first logical channel for duplicated PDCP packets of the first bearer, a second logical channel identifier of a second logical channel for (original) PDCP packets of the first bearer, one or more first cell identifiers of one or more first cells for duplicated PDCP packets of the first bearer, one or more second cell identifiers of one or more second cells for (original) PDCP packets of the first bearer, and/or other information.

[0342] The wireless device **1704** may, for example, based on the message(s) **1905**, send one or more messages **1906**. The message(s) **1906** may comprise an RRC message (e.g., an RRC connection reconfiguration complete message) indicating that the wireless device **1704** set up one or more configurations of the message(s) **1905** (e.g., the PDCP configuration parameter and/or PDCP duplication related configurations for the first bearer). The CU-CP node **1701** may receive the message(s) **1906** via the DU **1703** (e.g., via an F1 interface message, a UL RRC message transfer message, and/or a wireless device (e.g., UE) context modification required message). The DU **1703** may forward the message(s) **1906** from the wireless device **1704** to the CU-CP node **1701**. The CU-CP node **1701** may, for example, based on receiving the message(s) **1906**, send (e.g., transmit), to the DU **1703**, an RRC configuration confirmation message (e.g., wireless device (e.g., UE) context modification request message) indicating that RRC configurations for the wireless device **1704** (e.g., PDCP packet duplication configuration for the first bearer) are completed. The DU **1703** may (e.g., based on the RRC configuration confirmation message) send (e.g., transmit), to the wireless device **1704**, a MAC CE indicating activation and/or deactivation of (uplink) PDCP packet duplication for the first bearer.

[0343] The CU-UP node **1702** may receive the first DL TEID and/or the second DL TEID from the CU-CP node **1701** via one or more messages such as, for example, the message(s) **1901**, the message(s) **1907**, the message(s) **2103** (FIG. 21), the message(s) **2107** (FIG. 21), the message(s) **2205** (FIG. 22), and/or the message(s) **2209** (FIG. 22). The CU-CP node **1701** may send (e.g., transmit) such one or more messages to the CU-UP node **1702** based on receiving information (e.g., via the message(s) **1904** and/or other message(s)) from the DU **1703**. The CU-CP may send (e.g., transmit) such one or more messages to the CU-UP **1702** before receiving information (e.g., via the message(s) **1904** and/or other message(s)) from the DU **1703**. Such one or more messages may comprise at least one of a bearer context setup request message, a bearer context modification request message, a bearer context modification confirm message, and/or another type of message.

[0344] The CU-CP node **1701** may send one or more messages **1907** to the CU-UP node **1702**. The message(s) **1907** may activate PDCP packet duplication (e.g., if PDCP packet duplication was not explicitly or implicitly activated in connection with the message(s) **1901** and/or other message(s)) or may deactivate PDCP packet duplication (e.g., if PDCP packet duplication was explicitly or implicitly activated in connection with the message(s) **1901** and/or other message(s)). Also or alternatively, the CU-CP node **1701** may send one or more messages **1908** to the DU **1703**. The message(s) **1908** may similarly activate PDCP packet duplication (e.g., if PDCP packet duplication was not activated in connection with the message(s) **1904** and/or other message(s)) or may deactivate PDCP packet duplication (e.g., if PDCP packet duplication was activated in connection with the message(s) **1904** and/or other message(s)).

[0345] The CU-UP node **1702** may send one or more messages **1909** to the CU-CP node **1701**. The message(s) **1909** may indicate that the CU-UP node **1702** has determined to activate PDCP packet

duplication (e.g., if PDCP packet duplication was not explicitly or implicitly activated in connection with the message(s) **1901** and/or other message(s)) or may indicate that the CU-UP node **1702** has determined to deactivate PDCP packet duplication (e.g., if PDCP packet duplication was explicitly or implicitly activated in connection with the message(s) **1901** and/or other message(s)).

[0346] The DU **1703** may send one or more messages **1910** to the CU-CP node **1701** and/or may send one or more messages **1911** to the wireless device **1704**. The message(s) **1910** and/or the message(s) **1911** may indicate that the DU **1703** has determined to activate PDCP packet duplication (e.g., if PDCP packet duplication was not explicitly or implicitly activated in connection with the message(s) **1903** and/or other message(s)) or may indicate that the DU **1703** has determined to deactivate PDCP packet duplication (e.g., if PDCP packet duplication was explicitly or implicitly activated in connection with the message(s) **1903** and/or other message(s)).

[0347] FIG. **21** shows an example method, for PDCP packet duplication configuration, activation, and/or deactivation, that may be performed by one or more of the CU-CP node **1701**, the CU-UP node **1702**, the DU **1703**, and/or the wireless devices **1704**, and/or by one or more other nodes. The CU-CP node **1701** may send (e.g., transmit) one or more messages **2101**, to the DU **1703**, comprising a request for PDCP packet duplication configuration of a first bearer. The one or more messages **2101** may be similar to the message(s) **1903** of FIG. **19**, and/or one or more actions performed based on the message(s) **2101** may be similar to one or more actions performed based on the message(s) **1903**. The DU **1703** may send, to the CU-CP node **1701**, one or more messages **2102** comprising the first DL TEID and the second DL TEID for PDCP packet duplication of the first bearer. The one or more messages **2102** may be similar to the message(s) **1904** of FIG. **19**, and/or one or more actions performed based on the message(s) **2102** may be similar to one or more actions performed based on the message(s) **1904**. The CU-CP node **1701** may, for example, based on receiving the message(s) **2102**, send, to the CU-UP node **1702**, one or more messages **2103** (e.g., comprising the first DL TEID and the second DL TEID) indicating a request for PDCP packet duplication configuration for the first bearer. The one or more messages **2103** may be similar to the message(s) **1901** of FIG. **19**, and/or one or more actions performed based on the message(s) **2103** may be similar to one or more actions performed based on the message(s) **1901**. The CU-UP node **1702** may, for example, based on the message(s) **2103**, send, to the CU-CP node **1701**, one or more messages **2104** comprising the first UL TEID and the second UP TEID for PDCP packet duplication of the first bearer. The one or more messages **2104** may be similar to the message(s) **1902** of FIG. **19**, and/or one or more actions performed based on the message(s) **2104** may be similar to one or more actions performed based on the message(s) **1902**. The CU-CP node **1701** may, for example, based on the message(s) **2104**, send (e.g., transmit), to the DU **1703**, a message comprising the first UL TEID and the second UP TEID for PDCP packet duplication of the first bearer. The one or more messages **2105** may be similar to the message(s) **1905** of FIG. **19**, and/or one or more actions performed based on the message(s) **2105** may be similar to one or more actions performed based on the message(s) **1905**. The one or more messages **2106** may be similar to the message(s) **1906** of FIG. **19**, and/or one or more actions performed based on the message(s) **2106** may be similar to one or more actions performed based on the message(s) **1906**. The one or more messages **2107** may be similar to the message(s) **1907** of FIG. **19**, and/or one or more actions performed based on the message(s) **2107** may be similar to one or more actions performed based on the message(s) **1907**. The one or more messages **2108** may be similar to the message(s) **1908** of FIG. **19**, and/or one or more actions performed based on the message(s) **2108** may be similar to one or more actions performed based on the message(s) **1908**. The one or more messages **2109** may be similar to the message(s) **1909** of FIG. **19**, and/or one or more actions performed based on the message(s) **2109** may be similar to one or more actions performed based on the message(s) **1909**. The one or more messages **2110** may be similar to the message(s) **1910** of FIG. **19**, and/or one or more actions performed based on the message(s) **2110** may be similar to one or more actions

performed based on the message(s) **1910**. The one or more messages **2111** may be similar to the message(s) **1911** of FIG. **19**, and/or one or more actions performed based on the message(s) **2111** may be similar to one or more actions performed based on the message(s) **1911**.

[0348] FIG. **22** shows an example method, for PDCP packet duplication configuration, activation, and/or deactivation, that may be performed by one or more of the CU-CP node **1701**, the CU-UP node **1702**, the DU **1703**, and/or the wireless devices **1704**, and/or by one or more other nodes. The one or more messages **2201** may be similar to the message(s) **1901** of FIG. **19**, and/or one or more actions performed based on the message(s) **2201** may be similar to one or more actions performed based on the message(s) **1901**. The one or more messages **2202** may be similar to the message(s) **1902** of FIG. **19**, and/or one or more actions performed based on the message(s) **2202** may be similar to one or more actions performed based on the message(s) **1902**. The one or more messages **2203** may be similar to the message(s) **1903** of FIG. **19**, and/or one or more actions performed based on the message(s) **2203** may be similar to one or more actions performed based on the message(s) **1903**. The one or more messages **2204** may be similar to the message(s) **1904** of FIG. **19**, and/or one or more actions performed based on the message(s) **2204** may be similar to one or more actions performed based on the message(s) **1904**. The one or more messages **2207** may be similar to the message(s) **1905** of FIG. **19**, and/or one or more actions performed based on the message(s) **2207** may be similar to one or more actions performed based on the message(s) **1905**. The one or more messages **2208** may be similar to the message(s) **1906** of FIG. **19**, and/or one or more actions performed based on the message(s) **2208** may be similar to one or more actions performed based on the message(s) **1906**. The one or more messages **2209** may be similar to the message(s) **1907** of FIG. **19**, and/or one or more actions performed based on the message(s) **2209** may be similar to one or more actions performed based on the message(s) **1907**. The one or more messages **2210** may be similar to the message(s) **1908** of FIG. **19**, and/or one or more actions performed based on the message(s) **2210** may be similar to one or more actions performed based on the message(s) **1908**. The one or more messages **2211** may be similar to the message(s) **1909** of FIG. **19**, and/or one or more actions performed based on the message(s) **2211** may be similar to one or more actions performed based on the message(s) **1909**. The one or more messages **2212** may be similar to the message(s) **1910** of FIG. **19**, and/or one or more actions performed based on the message(s) **2212** may be similar to one or more actions performed based on the message(s) **1910**. The one or more messages **2213** may be similar to the message(s) **1911** of FIG. **19**, and/or one or more actions performed based on the message(s) **2213** may be similar to one or more actions performed based on the message(s) **1911**.

[0349] The CU-CP node **1701** may, for example, based on receiving the message(s) **2204**, send one or more messages **2205** to the CU-UP node **1702**. The message(s) **2204** may, for example, indicate DL TEIDs for original packets and/or duplicate packets. Also or alternatively, the message(s) **2204** may indicate acceptance and/or rejection for bearer configurations (e.g., for PDCP packet duplication). The message(s) **2205** may, for example, indicate a bearer context modification request. The message(s) **2205** may, for example, comprise a bearer context modification request message, a bearer context modification confirm message, and/or other type(s) of message(s). The CU-CP node **1701** may forward, to the CU-UP node **1702** via the message(s) **2205**, one or more DL TEIDs received via the message(s) **2204**. The CU-CP node **1701** may, for example, depending on acceptance and/or rejection from the DU **1703**, update configurations (e.g., for PDCP packet duplication) via the message(s) **2205**.

[0350] The CU-UP node **1702** may, for example, based on receiving the message(s) **2205**, apply and/or otherwise use DL TEIDs for downlink packet transmission for the bearer (e.g., for original and/or duplicate packets). The CU-UP node **1702** may update configurations based on the message(s) **2205**. If, for example, the DU **1703** rejects PDCP duplication configuration or setup of the bearer, the CU-UP node **1702** may remove/delete/reset configurations request via the message(s) **2201** (e.g., PDCP duplication configuration or bearer setup of the bearer). The CU-UP

node **1702** may, for example, based on receiving the message(s) **2205**, send one or more messages **2206** to the CU-CP node **1701**. The message(s) **2206** may, for example, indicate a bearer context modification request. The message(s) **2206** may, for example, comprise a bearer context modification request message, a bearer context modification confirm message, and/or other type(s) of message(s). The message(s) **2206** may indicate that the CU-UP node **1702** modified bearer configurations based on the message(s) **2205**. The message(s) **2206** may indicate acceptance or rejection of one or more (e.g., each of) configuration modifications communicated via the message(s) **2205**. The CU-CP node **1701** may, for example, based on receiving the message(s) **2206**, confirm that some or all network nodes (e.g., the CU-UP node **1702** and/or the DU **1703**) are configured to serve the wireless device **1704**.

[0351] The CU-CP node **1701** may send one or more RRC connection reconfiguration messages **2207**, to the wireless device **1704** via the DU **1703**, to configure the wireless device **1704** based on network node configurations. The wireless device **1704** may, based on the message(s) **2207**, send one or more RRC connection reconfiguration complete messages **2208** to the CU-CP node **1701** via the DU **1703**. If modification of the CU-UP node **1702** occurs after RRC (re)configuration (e.g., via the message(s) **1907** in FIG. **19**), the CU-CP node **1701** may complete the bearer modification procedure (e.g., based on the RRC (re)configuration).

[0352] FIG. **23** shows examples of communications (e.g., requests and/or reports of PDCP packet duplication activation and/or deactivation, status information) among the CU-CP node **1701**, the CU-UP node **1702**, the DU **1703**, and/or the wireless device **1704**. FIGS. **24**, **25**, and **26** show examples of PDCP packet activation and/or deactivation and/or of related communications. One or more communications shown in FIGS. **23** through **26** may be the same or similar as one or more communications shown in, and/or described in connection with, preceding figures, and/or may comprise, in whole or in part, one or more communications separate from communications shown in, and/or described in connection with, other figures. One or more communications shown in, and/or described in connection with, one or more of FIG. **17** or **21** through **26** (and/or other figures) may be the same or similar as (and/or may be combined with and/or otherwise used in combination with) one or more other communications shown in, and/or described in connection with, one or more of FIG. **17** or **21** through **26** (and/or other figures).

[0353] As shown in FIG. **23** (e.g., message(s) **2303**) and in FIG. **24** (e.g., as message(s) causing activation **2403**, deactivation **2402**, and/or activation **2401**), the CU-CP node **1701** may send (e.g., transmit), to the CU-UP node **1702**, one or more messages indicating an activation and/or a deactivation of PDCP packet duplication of a bearer of the wireless device **1704**. The activation and/or the deactivation may be based on the PDCP packet duplication configuration of the CU-UP node **1702** (e.g., indicated one or more messages causing activation **2401**). The activation and/or the deactivation may be based on PDCP packet duplication configuration of the CU-CP node **1701** (indicated, e.g., via one or more messages causing activation **2401**) and/or of the DU **1703** (e.g., indicated via one or more messages **2405**).

[0354] As shown in FIG. **23**, FIG. **25**, and/or FIG. **26**, the CU-UP node **1702** may determine to activate and/or deactivate PDCP packet duplication (e.g., UL PDCP packet duplication via UL tunnel endpoints **1** and **2** and/or DL PDCP packet duplication via DL tunnel endpoints **1** and **2**) for a bearer of the wireless device **1704**. The CU-UP node **1702** may make that determination, for example, based on status information (e.g., information **2313**) for the CU-UP node **1702** obtained by monitoring systems of the CU-UP node **1702**. Also or alternatively, the CU-UP node **1702** may determine to activate and/or deactivate PDCP packet duplication based on status information for the CU-CP node **1701** received from the CU-CP node **1701** (e.g., via one or more messages **2301**). Also or alternatively, the CU-UP node **1702** may determine to activate and/or deactivate PDCP packet duplication based on status information for the DU **1703** received from the CU-CP node **1701** (e.g., via message(s) **2301**). Status information for the DU **1703** in message(s) **2301** may comprise information from, and/or be otherwise based on, one or more messages **2309** received by

the CU-CP node **1701** from the DU **1703**. Also or alternatively, the CU-UP node **1702** may determine to activate and/or deactivate PDCP packet duplication based on RRC wireless device (e.g., UE) status information received from the CU-CP node **1701** (e.g., via message(s) **2301**). RRC wireless device (e.g., UE) status information in message(s) **2301** may comprise information from, and/or be otherwise based on, one or more messages **2308** received by the CU-CP node **1701** from the wireless device **1704** via the DU **1703**. Also or alternatively, the CU-UP node **1702** may determine to activate and/or deactivate PDCP packet duplication based on lower layer wireless device (e.g., UE) status information received from the CU-CP node **1701** (e.g., via message(s) **2301**). Lower layer wireless device (e.g., UE) status information in message(s) **2301** may comprise information from, and/or be otherwise based on, one or more messages **2310** received by the CU-CP node **1701** from the wireless device **1704** via the DU **1703**. Also or alternatively, the CU-UP node **1702** may determine to activate and/or deactivate PDCP packet duplication based on other information. The CU-CP node **1701** may send, via the DU **1703**, one or more messages **2606** to the wireless device **1704**. The message(s) **2606** may be sent, for example, prior to or concurrently with activation and/or deactivation of PDCP packet duplication. The message(s) **2606** may be sent after activation and/or deactivation of PDCP packet duplication (e.g., by the CU-UP **1702**). The message(s) **2606** may comprise RRC reconfiguration message(s) indicating that PDCP packet duplication has been configured and/or may comprise one or more PDCP packet duplication configuration parameters.

[0355] The CU-UP node **1702** may determine to activate uplink and/or downlink PDCP packet duplication for a bearer, if, for example, status information and/or other information indicates that corresponding resources are available to support PDCP packet duplication (e.g., if a resource utilization ratio is lower than a threshold value), and/or that radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if a radio quality is lower than a threshold value). The CU-UP node **1702** may determine to deactivate uplink and/or downlink PDCP packet duplication for a bearer, if, for example, status information and/or other information indicates that corresponding resources to support the PDCP duplication are or may be insufficient (e.g., if resource utilization ratio is higher than a threshold value), and/or that radio signaling quality is sufficiently good and/or reliable so as to indicate that benefit(s) from PDCP packet duplication may be minimal (e.g., if radio quality is higher than a threshold value). Status information may, for example, comprise one or more of: the status information for the CU-UP node **1702**, the status information for the CU-CP node **1701**, the status information for the DU **1703**, the RRC wireless device (e.g., UE) status information, and/or the lower layer wireless device (e.g., UE) status information.

[0356] The CU-UP node **1702** may send (e.g., transmit), to the CU-CP node **1701**, one or more CU-UP configuration update messages (e.g., one or more messages **2304** and/or one or more messages **2601**) indicating activation (e.g., activation **2602** and/or activation **2604**) of UL and/or DL PDCP packet duplication of a bearer. For example, the CU-UP node **1702** may send such one or more CU-UP configuration update messages based on and/or after determining activation of uplink and/or downlink PDCP packet duplication of a bearer. The CU-UP configuration update message may comprise at least one of a bearer context modification required message, a bearer context modification response message, a bearer context modification failure message, a bearer context setup response message, a bearer context setup failure message, a bearer context release complete message, a bearer context release request message, and/or another type of message. The CU-CP node **1701** may send (e.g., transmit), to the DU **1703**, one or more messages (e.g., one or more messages **2305** and/or one or more messages **2605**) indicating the activation of UL and/or DL PDCP packet duplication of a bearer. The CU-CP node **1701** may send such one or more messages indicating the activation of UL and/or DL PDCP packet duplication based on, for example, in response to, receiving the CU-UP configuration update message(s). The one or more messages indicating the activation of UL and/or DL PDCP packet duplication (e.g., the message(s) **2305**

and/or the message(s) **2605**) may comprise a wireless device (e.g., UE) context setup request message, a wireless device (e.g., UE) context modification request message, a wireless device (e.g., UE) context modification confirm message, and/or another type of message. For the activation of the UL PDCP packet duplication, the DU **1703** may send (e.g., transmit), to the wireless device **1704**, a MAC CE indicating activation of the UL PDCP packet duplication of the first bearer. The DU **1703** may send that MAC CE in one or more messages **2311**. The wireless device **1704** may send (e.g., transmit) UL duplicated PDCP packets (e.g., via a second logical channel) and original PDCP packets (e.g., via a first logical channel) to the CU-UP node **1702** via the DU **1703**. The wireless device **1704** may send UL duplicated PDCP packets and original PDCP packets to the CU-UP node **1702** based on, for example, in response to, receiving the MAC CE indicating activation of UL PDCP packet duplication. The UL original PDCP packets may be sent to a first UL TEID (e.g., the uplink tunnel endpoint **1** in FIG. 25) and the UL duplicated PDCP packets may be sent to a second UL TEID (e.g., the uplink tunnel endpoint **2** in FIG. 25). The wireless device **1704** may send (e.g., transmit) UL original PDCP packets via a group of cells and may send (e.g., transmit) the UL duplicated PDCP packets via a separate group of cells. If DL PDCP packet duplication is activated, the DU **1703** may forward DL duplicated PDCP packets (e.g., via the second logical channel) and original PDCP packets (e.g., via the first logical channel) from the CU-UP node **1702** to the wireless device **1704**. The DU **1703** may use a group of cells to send (e.g., transmit) DL original PDCP packets to the wireless device and a separate group of cells to send (e.g., transmit) DL duplicated PDCP packets to the wireless device.

[0357] The CU-UP node **1702** may discard duplicated UL PDCP packets of the bearer received from the DU **1703** and/or the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may discard duplicated UL PDCP packets of the bearer (e.g., received from the DU **1703** and/or the wireless device **1704**) based on, for example, in response to, determining activation of UL PDCP packet duplication of a bearer. That discarding may begin after indicating activation of PDCP packet duplication to the CU-CP node **1701** and/or after determining activation. The CU-UP node **1702** may send (e.g., transmit) original DL PDCP packets and duplicated DL PDCP packets of the bearer to the DU **1703** and/or to the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may send original DL PDCP packets and duplicated DL PDCP packets of the bearer (e.g., to the DU **1703** and/or to the wireless device **1704** via the DU **1703**) based on, for example, in response to (and/or after) determining activation of DL PDCP packet duplication of a bearer. The CU-UP node **1702** may, for example, send original PDCP packets to a first DL TEID (e.g., the downlink tunnel endpoint **1** in FIG. 25) and duplicated PDCP packets to a second DL TEID (e.g., the downlink tunnel endpoint **2** in FIG. 25).

[0358] The CU-UP node **1702** may send (e.g., transmit), to the CU-CP node **1701**, a CU-UP configuration update message (e.g., one or more of the messages **2303** and/or one or more of the messages **2601**) indicating the deactivation of UL and/or DL PDCP packet duplication of the bearer. The CU-UP node **1702** may send such a CU-UP configuration update message after determining deactivation of UL and/or DL PDCP packet duplication of a bearer (e.g., the deactivation **2603**). That CU-UP configuration update message indicating deactivation may be based on (e.g., in response to) determining deactivation UL and/or DL PDCP packet duplication and may comprise at least one of a bearer context modification required message, a bearer context modification response message, a bearer context modification failure message, a bearer context setup response message, a bearer context setup failure message, a bearer context release complete message, a bearer context release request message, and/or another type of message. The CU-CP node **1701** may send (e.g., transmit), to the DU **1703**, one or more messages **2305** (e.g., one or more wireless device (e.g., UE) context setup request messages, one or more wireless device (e.g., UE) context modification request messages, one or more wireless device (e.g., UE) context modification confirm messages, one or more wireless device (e.g., UE) context release command messages, and/or one or more other type messages) indicating the deactivation of the UL and/or DL

PDCP packet duplication of the bearer. The CU-CP node **1701** may send message(s) **2305** based on, for example, in response to, receiving a CU-UP configuration update message indicating deactivation. For deactivation of UL PDCP packet duplication, the DU **1703** may send (e.g., transmit), to the wireless device **1704**, a MAC CE indicating deactivation of the UL PDCP packet duplication of the bearer. The wireless device **1704** may (e.g., based on, for example, in response to, receiving that MAC CE indicating deactivation of UL PDCP packet duplication) stop sending (e.g., transmitting) UL duplicated PDCP packets (e.g., via the second logical channel) or may stop sending (e.g., transmitting) original UL PDCP packets (e.g., via the first logical channel) to the DU **1703** (e.g., to the CU-UP node **1702** via the DU **1703**). UL original PDCP packets may be sent (e.g., transmitted) via one or more of serving cells of the wireless device **1704**. If DL PDCP packet duplication is deactivated, the DU **1703** may forward one of duplicated DL PDCP packets (e.g., via the second logical channel) or original DL PDCP packets (e.g., via the first logical channel) from the CU-UP node **1702** to the wireless device **1704**. The DU **1703** may use one or more of serving cells of the wireless device **1704** to send (e.g., transmit) original DL PDCP packets to the wireless device **1704**.

[0359] The CU-UP node **1702** may process UL PDCP packets of the first bearer received from the DU **1703** and/or from the wireless device **1704** via the DU **1703**. That processing may occur after determining deactivation of UL PDCP packet duplication of the first bearer and/or after indicating deactivation to the CU-CP node **1701**. That processing may occur based on (for example, in response to) determining deactivation of UL PDCP packet duplication. If, for example, the CU-UP node **1702** is receiving duplicated PDCP packets, the CU-UP node **1702** may discard the duplicated PDCP packets. The CU-UP node **1702** may stop sending (e.g., transmitting) duplicated DL PDCP packets of the first bearer to the DU **1703** and/or to the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may stop sending those duplicated DL PDCP packets after determining deactivation of DL PDCP packet duplication of the first bearer. The CU-UP node **1702** may stop sending those duplicated DL PDCP packets based on, for example, in response to, determining deactivation of DL PDCP packet duplication. The DL original PDCP packets may be sent (e.g., transmitted) via one of the first logical channel (e.g., via the first tunnel and the first TEID) or the second logical channel (e.g., via the second tunnel and the second TEID).

[0360] As shown, for example, in FIG. 23, FIG. 24, and FIG. 25, the CU-CP node **1701** may determine activation or deactivation of PDCP packet duplication for a bearer of the wireless device **1704**. The CU-CP node **1701** may determine such activation or deactivation based on at least one of status information **2302** for the CU-UP node **1702** received from the CU-UP node **1702**, status information **2312** for the CU-CP node **1701** obtained by monitoring systems of the CU-CP node **1701**, status information **2309** of the DU **1703** received from the DU **1703**, RRC wireless device (e.g., UE) status information **2308** received from the wireless device **1704** via one or more RRC messages (e.g., from the wireless device **1704** via the DU **1703**), lower layer wireless device (e.g., UE) status information **2309** received from the DU **1703** (e.g., from the wireless device **1704** via the DU **1703**), and/or other information. The lower layer wireless device (e.g., UE) status information **2309** may comprise and/or be based on the wireless device (e.g., UE) status information **2310** sent from the wireless device **1704** to the DU **1703**.

[0361] The CU-CP node **1701** may determine to activate UL and/or DL PDCP packet duplication for a bearer, if, for example, status information and/or other information indicates that corresponding resources to support PDCP packet duplication are available (e.g., if a resource utilization ratio is lower than a threshold value) and/or that radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if a radio quality is lower than a threshold value). The CU-CP node **1701** may determine to deactivate UL and/or DL PDCP packet duplication for a bearer, if, for example, status information and/or other information indicates that corresponding resources to support PDCP packet duplication are or may be insufficient (e.g., if a resource utilization ratio is higher than a threshold value) and/or that radio

signaling quality is sufficiently good and/or reliable so as to indicate that benefit(s) from PDCP packet duplication may be minimal (e.g., if radio quality is higher than a threshold value). Status information may comprise one or more of: the CU-UP status information **2302**, the CU-CP status information **2312**, the DU status information **2309**, the RRC wireless device (e.g., UE) status information **2308**, and/or the lower layer wireless device (e.g., UE) status information **2309**.

[0362] The CU-CP node **1701** may send (e.g., transmit), to the CU-UP node **1702**, a CU-CP configuration update message indicating the activation of UL and/or DL PDCP packet duplication of the bearer. The CU-CP node **1701** may send that configuration update message after determining activation of UL and/or DL PDCP packet duplication of a bearer. The CU-CP node **1701** may send that configuration update message based on (e.g., in response to) determining activation of PDCP packet duplication of the bearer. The CU-CP configuration update message (e.g., one or more of the messages causing the activation **2403** or one or more of the messages causing the activation **2401**) may comprise at least one of a bearer context modification request message, a bearer context modification confirm message, a bearer context setup request message, a bearer context release command message, and/or another type of message. The CU-CP node **1701** may send one or more messages **2404** configuring the bearer for PDCP packet duplication.

[0363] The CU-UP node **1702** may discard duplicated UL PDCP packets of the first bearer received from the DU **1703** and/or from the wireless device **1704** (e.g., via the DU **1703**). The CU-UP node **1702** may discard those duplicated UL PDCP packets after receiving the CU-CP configuration update message indicating the activation of the UL PDCP packet duplication of the bearer. The CU-UP node **1702** may discard those duplicated UL PDCP packets based on (e.g., in response to) receiving the CU-CP configuration update message indicating the activation of the UL PDCP packet duplication of the bearer. The duplicated UL PDCP packets may be sent (e.g., by the wireless device **1704**, and/or by the wireless device **1704** via the DU **1703**) to a second UL TEID (e.g., the uplink tunnel endpoint **2**) and original UL PDCP packets may be sent to a first UL TEID (e.g., the uplink tunnel endpoint **1**). The CU-UP node may send (e.g., transmit) original DL PDCP packets and duplicated DL PDCP packets of the bearer to the DU **1703**. The CU-UP node **1702** may send original DL PDCP packets and duplicated DL PDCP packets after receiving the CU-CP configuration update message indicating the activation of the DL PDCP packet duplication of the bearer. The CU-UP node **1702** may send original DL PDCP packets and duplicated DL PDCP packets based on (e.g., in response to) receiving the CU-CP configuration update message indicating the activation of the DL PDCP packet duplication. The CU-UP node may send the original DL PDCP packets to a first DL TEID (e.g., the downlink tunnel endpoint **1**) and duplicated PDCP packets to a second DL TEID (e.g., the downlink tunnel endpoint **1**), and/or to the wireless device **1704** via the DU **1703**.

[0364] The CU-CP node **1701** may send (e.g., transmit), to the DU **1703**, a one or more CU-CP configuration update messages (e.g., one or more of the messages **2305** and or one or more of the messages **2405**). The one or more CU-CP configuration update messages sent to the DU **1703** may be sent after determining activation of UL and/or DL PDCP packet duplication of the bearer. The one or more CU-CP configuration update messages sent to the DU **1703** may be sent based on (e.g., in response to) determining UL and/or DL PDCP packet duplication, may comprise a wireless device (e.g., UE) context setup request message, a wireless device (e.g., UE) context modification request message, a wireless device (e.g., UE) context modification confirm message, and/or other type of message, and/or may indicate the activation of the UL and/or DL PDCP packet duplication of the bearer. For the activation of UL PDCP packet duplication, the DU **1703** may send (e.g., transmit), to the wireless device **1704**, a MAC CE indicating activation of UL PDCP packet duplication of the bearer. The wireless device **1704** may send (e.g., transmit) UL duplicated PDCP packets (e.g., via a second logical channel) and UL PDCP packets (e.g., via a first logical channel) to the DU **1703** and/or to the CU-UP node **1702** via the DU **1703**. The wireless device **1704** may send such UL duplicated PDCP packets and UL PDCP packets based on, for example, in response

to, receiving the MAC CE indicating activation of UL PDCP packet duplication. The UL PDCP packets may be sent via a group of cells and the UL duplicated PDCP packets may be sent via a separate group of cells. If DL PDCP packet duplication is activated, the DU **1703** may forward DL duplicated PDCP packets (e.g., via the second logical channel) and DL original PDCP packets (e.g., via the first logical channel) from the CU-UP node **1702** to the wireless device **1704**. The DU **1703** may use a group of cells to send (e.g., transmit) DL original PDCP packets to the wireless device **1704** and a separate group of cells to send (e.g., transmit) DL duplicated PDCP packets to the wireless device **1704**.

[0365] The CU-CP node **1701** may send (e.g., transmit), to the CU-UP node **1702**, a CU-CP configuration update message indicating the deactivation of UL and/or DL PDCP packet duplication of the bearer. The CU-CP node **1701** may send that configuration update message after determining deactivation of UL and/or DL PDCP packet duplication of a bearer. The CU-CP node **1701** may send that configuration update message based on (e.g., in response to) determining deactivation of PDCP packet duplication of the bearer. The CU-CP configuration update message (e.g., one or more of the messages causing the deactivation **2402**) may comprise at least one of a bearer context modification request message, a bearer context modification confirm message, a bearer context setup request message, a bearer context release command message, and/or another type of message. The CU-UP node **1702** may process UL PDCP packets of the bearer received from the DU **1703** and/or from the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may process those UL PDCP packets after receiving a CU-CP configuration update message indicating the deactivation of UL PDCP packet duplication of the bearer. The CU-UP node **1702** may process those UL PDCP packets based on (e.g., in response to) receiving the CU-CP configuration update message indicating the deactivation of UL PDCP packet duplication. The CU-UP may, for example, if receiving duplicated PDCP packets, discard the duplicated PDCP packets. The CU-UP node **1702** may stop sending (e.g., transmitting) duplicated DL PDCP packets of the bearer to the DU **1703** and/or to the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may stop sending the duplicated DL PDCP packets after receiving the CU-CP configuration update message indicating the deactivation of the DL PDCP packet duplication of the first bearer. The CU-UP node **1702** may stop sending the duplicated DL PDCP packets based on, for example, in response to receiving the CU-CP configuration update message indicating the deactivation of the DL PDCP packet duplication. The DL original PDCP packets may be transmitted via one of a first logical channel (e.g., via a first tunnel and/or a first TEID) or a second logical channel (e.g., via a second tunnel and/or a second TEID).

[0366] The CU-CP node **1701** may send (e.g., transmit), to the DU **1703**, one or more CU-CP configuration update messages. Those one or more CU-CP configuration update messages (e.g., one or more of the message(s) **2305** and/or **2405**) may be sent after determining deactivation of UL and/or DL PDCP packet duplication of a bearer. Those one or more CU-CP configuration update messages (e.g., one or more of the message(s) **2305** and/or **2405**) may be sent based on (e.g., in response to) determining deactivation of PDCP packet duplication, comprise a wireless device (e.g., UE) context setup request message, a wireless device (e.g., UE) context modification request message, a wireless device (e.g., UE) context modification confirm message, a wireless device (e.g., UE) context release command message, and/or another type of message, and may indicate the deactivation of the UL and/or DL PDCP packet duplication of the bearer. For the deactivation of UL PDCP packet duplication, the DU **1703** may send (e.g., transmit), to the wireless device **1704**, a MAC CE indicating deactivation of the UL PDCP packet duplication of the bearer. The wireless device **1704** may stop sending (e.g., transmitting) UL duplicated PDCP packets (e.g., via the second logical channel or the first logical channel) to the DU **1703** and/or to the CU-UP node **1702** via the DU **1703**. The wireless device **1704** may stop sending UL duplicated PDCP packets based on (e.g., in response to) receiving the MAC CE indicating the deactivation of the UL PDCP packet duplication. Alternatively, the wireless device **1704** may stop sending the original UL PDCP

packets to the DU **1703** and/or to the CU-UP node **1702** via the DU **1703**. The UL PDCP packets may be transmitted via one or more of serving cells of the wireless device **1704**. If DL PDCP packet duplication is deactivated, the DU **1703** may, for example, may forward one of duplicated DL PDCP packets (e.g., via the second logical channel) or original DL PDCP packets (e.g., via the first logical channel) from the CU-UP node **1702** to the wireless device **1704**. The DU **1703** may use one or more of serving cells of the wireless device **1704** to send (e.g., transmit) the original DL PDCP packets to the wireless device **1704**. The CU-CP node **1701** may send, via the DU **1703**, one or more messages **2406** to the wireless device **1704**. The message(s) **2406** may be sent, for example, prior to or concurrently with activation and/or deactivation of PDCP packet duplication. The message(s) **2406** may be sent after activation and/or deactivation of PDCP packet duplication (e.g., by the CU-CP **1701**). The message(s) **2406** may comprise RRC reconfiguration message(s) indicating that PDCP packet duplication has been configured and/or may comprise one or more PDCP packet duplication configuration parameters.

[0367] As shown, for example, in FIG. **23**, the DU **1703** may determine activation and/or deactivation of PDCP packet duplication for a bearer of the wireless device **1704**. The DU **1703** may determine such activation and/or deactivation based on at least one of CU-UP status information **2307** received from the CU-CP node **1701** (which information may, e.g., comprise and/or be based on CU-UP status information **2302** sent by the CU-UP node **1702** to the CU-CP node **1701**), CU-CP status information **2307** received from the CU-CP node **1701**, DU status information **2314** obtained by monitoring systems of the DU **1703**, RRC wireless device (e.g., UE) status information received from the CU-CP node **1701** (e.g., from the wireless device **1704** via the DU **1703** and/or via one or more RRC messages), lower layer wireless device (e.g., UE) status information **2310** received from the wireless device, and/or other information. If, for example the CU-UP status information and/or the CU-CP status information **2307**, the DU status information **2314**, the RRC wireless device (e.g., UE) status information, the lower layer wireless device (e.g., UE) status information **2310**, and/or other information indicates that corresponding resources to support PDCP packet duplication are available (e.g., if a resource utilization ratio is lower than a threshold value) and/or that radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if radio quality is lower than a threshold value), the DU **1703** may determine to activate UL and/or DL PDCP packet duplication for a bearer. If, for example, at least one of the CU-UP status information and/or the CU-CP status information **2307**, the DU status information **2314**, the RRC wireless device (e.g., UE) status information, the lower layer wireless device (e.g., UE) status information **2310**, and/or other information indicates that corresponding resources to support PDCP packet duplication are or may be insufficient (e.g., if a resource utilization ratio is higher than a threshold value) and/or that radio signaling quality is sufficiently good and/or reliable so as to indicate that benefit(s) from PDCP duplication may be minimal (e.g., if radio quality is higher than a threshold value), the DU **1703** may determine to deactivate UL and/or DL PDCP packet duplication for the bearer.

[0368] The DU **1703** may send (e.g., transmit), to the CU-CP node **1701**, one or more DU configuration update messages **2306** indicating activation of UL and/or DL PDCP packet duplication of the bearer. The DU **1703** may send the message(s) **2306** after determining activation of UL and/or DL PDCP packet duplication of the bearer. The DU **1703** may send the message(s) **2306** based on, for example, in response to, the determination to activate PDCP packet duplication. The DU configuration update message(s) **2306** may comprise at least one of a wireless device (e.g., UE) context setup response message, a wireless device (e.g., UE) context setup failure message, a wireless device (e.g., UE) context modification required message, a wireless device (e.g., UE) context modification response message, a wireless device (e.g., UE) context modification failure message, a wireless device (e.g., UE) context release request message, a wireless device (e.g., UE) context release complete message, and/or another type of message. The CU-CP node **1701** may send (e.g., transmit), to the CU-UP node **1702**, one or more messages (e.g., a bearer context

modification request message, a bearer context modification confirm message, a bearer context setup request message, a bearer context release command message, and/or another type of message) indicating the activation of UL and/or DL PDCP packet duplication of the bearer. The CU-CP node **1701** may send one or more messages indicating the activation of UL and/or DL PDCP packet duplication of the bearer based on, for example, in response to, receiving the DU configuration update message(s) **2306** indicating the activation of UL and/or DL PDCP packet duplication of the bearer. The CU-UP node **1702** may discard duplicated UL PDCP packets of the bearer received from the DU **1703** and/or from the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may discard those duplicated packets after receiving the message indicating the activation of UL PDCP packet duplication of the bearer. The CU-UP node **1702** may discard those duplicated packets based on, for example, in response to, receiving the message indicating the activation of UL PDCP packet duplication. The CU-UP node **1702** may send (e.g., transmit) original DL PDCP packets and duplicated DL PDCP packets of the bearer to the DU **1703** (e.g., send PDCP packets to a first DL TEID (e.g., the downlink tunnel endpoint **1**) and duplicated PDCP packets to a second DL TEID (e.g., the downlink tunnel endpoint **2**)) and/or to the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may send original DL PDCP packets and duplicated DL PDCP packets after receiving the message indicating the activation of DL PDCP packet duplication of the bearer. The CU-UP node **1702** may send original DL PDCP packets and duplicated DL PDCP packets based on, for example, in response to, receiving the message indicating the activation of DL PDCP packet duplication.

[0369] The DU **1703** may send (e.g., transmit), to the wireless device, a MAC CE (e.g., as shown at **2311** in FIG. **23**) indicating the activation of UL and/or DL PDCP packet duplication of the bearer. The DU **1703** may send that MAC CE after determining activation of UL and/or DL PDCP packet duplication of the bearer. The DU **1703** may send that MAC CE based on, for example, in response to, determining activation of UL and/or DL PDCP packet duplication. For activation of UL PDCP packet duplication, the DU **1703** may send (e.g., transmit), to the wireless device **1704**, a MAC CE indicating activation of UL PDCP packet duplication of the bearer. The wireless device **1704** may send (e.g., transmit) UL duplicated PDCP packets (e.g., via a second logical channel) and UL original PDCP packets (e.g., via a first logical channel) to the DU **1703** and/or to the CU-UP node **1702** via the DU **1703**. The wireless device **1704** may send such UL duplicated PDCP packets and UL original PDCP packets based on, for example, in response to, receiving the MAC CE indicating the activation of UL PDCP packet duplication. The UL original PDCP packets and the UL duplicated PDCP packets may respectively be sent (e.g., transmitted) via separate groups of cells. If DL PDCP packet duplication is activated, the DU **1703** may, for example, forward DL duplicated PDCP packets (e.g., via the second logical channel) and DL original PDCP packets (e.g., via the first logical channel) from the CU-UP node **1702** to the wireless device **1704**. The DU **1703** may use separate groups of cells to send DL original PDCP packets and DL duplicated PDCP packets to the wireless device **1704**.

[0370] The DU **1703** may send (e.g., transmit), to the CU-CP node **1701**, a DU configuration update message **2306** indicating the deactivation of UL and/or DL PDCP packet duplication of the bearer. The DU **1703** may send that DU configuration update message **2306** indicating the deactivation after determining deactivation of UL and/or DL PDCP packet duplication of a bearer. The DU **1703** may send that DU configuration update message **2306** indicating the deactivation based on, for example, in response to, determining the deactivation of UL and/or DL PDCP packet duplication. The DU configuration update message **2306** indicating the deactivation may comprise at least one of: a wireless device (e.g., UE) context setup response message, a wireless device (e.g., UE) context setup failure message, a wireless device (e.g., UE) context modification required message, a wireless device (e.g., UE) context modification response message, a wireless device (e.g., UE) context modification failure message, a wireless device (e.g., UE) context release request message, a wireless device (e.g., UE) context release complete message, and/or another type of

message. The CU-CP node **1701** may send (e.g., transmit), to the CU-UP node **1702**, one or more messages (e.g., a bearer context modification request message, a bearer context modification confirm message, a bearer context setup request message, a bearer context release command message, and/or another type of message) indicating the deactivation of the UL and/or DL PDCP packet duplication of the bearer. The CU-CP node **1701** may send such one or more messages indicating the deactivation of the UL and/or DL PDCP packet duplication of the bearer based on, for example, in response to, receiving the DU configuration update message indicating the deactivation of UL and/or DL PDCP packet duplication of the bearer. The CU-UP node **1702** may process UL PDCP packets of the bearer received from the DU **1703** and/or from the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may process those UL PDCP packets after receiving the message indicating the deactivation of the UL PDCP packet duplication of the bearer. The CU-UP node **1702** may process those UL PDCP packets based on, for example, in response to, receiving the message indicating the deactivation of the UL PDCP packet duplication. If receiving duplicated PDCP packets, the CU-UP node **1702** may, for example, discard the duplicated PDCP packets. The CU-UP node **1702** may stop sending (e.g., transmitting) duplicated DL PDCP packets of the bearer to the DU **1703** and/or to the wireless device **1704** via the DU **1703**. The CU-UP node **1702** may stop sending those duplicated DL PDCP packets after receiving the message indicating the deactivation of DL PDCP packet duplication of the bearer. The CU-UP node **1702** may stop sending those duplicated DL PDCP packets based on, for example, in response to, receiving the message indicating the deactivation of DL PDCP packet duplication. The CU-UP node **1702** may send (e.g., transmit) DL original PDCP packets via one of the first logical channel (e.g., via a first tunnel and/or a first TEID) or the second logical channel (e.g., via a second tunnel and/or a second TEID).

[0371] The DU **1703** may send (e.g., transmit), to the wireless device **1704**, a MAC CE (e.g., as shown at **2311** in FIG. **23**) indicating the deactivation of UL and/or DL PDCP packet duplication of the bearer. The DU **1703** may send that MAC CE after determining deactivation of UL and/or DL PDCP packet duplication of a bearer. The DU **1703** may send that MAC CE based on, for example, in response to, determining deactivation of UL and/or DL PDCP packet duplication. For deactivation of UL PDCP packet duplication, the DU **1703** may send (e.g., transmit), to the wireless device **1704**, a MAC CE indicating deactivation of UL PDCP packet duplication of the bearer. The wireless device **1704** may stop sending (e.g., transmitting) UL duplicated PDCP packets (e.g., via the second logical channel or the first logical channel) to the DU **1703** and/or to the CU-UP node **1702** via the DU **1703**. The wireless device **1704** may stop sending such UL duplicated PDCP packets based on, for example, in response to, receiving the MAC CE indicating the deactivation of UL PDCP packet duplication. Alternatively, the wireless device **1704** may stop sending the original UL PDCP packets to the DU **1703** and/or to the CU-UP node **1702** via the DU **1703**. The UL original PDCP packets may be sent (e.g., transmitted) via one or more of serving cells of the wireless device **1704**. If DL PDCP packet duplication is deactivated, the DU **1703** may, for example, forward one of duplicated DL PDCP packets (e.g., via the second logical channel) or original DL PDCP packets (e.g., via the first logical channel) from the CU-UP node **1702** to the wireless device **1704**. The DU **1703** may use one or more of serving cells of the wireless device **1704** to send (e.g., transmit) original DL PDCP packets to the wireless device **1704**.

[0372] CU-UP status information (e.g., the status information **2302** and/or the status information **2313** obtained by monitoring the CU-UP node **1702**) may, for example, comprise at least one of: a hardware load indicator, an NG interface load indicator (e.g., a load indicator for an interface between the CU-UP node **1702** and a core network entity), an F1 interface load indicator (e.g., load information for an interface between the CU-UP node **1702** and the DU **1703**), a composite available capacity group, and/or a network slice overload indicator of the CU-UP node **1702**. CU-CP status information (e.g., the status information **2312**) may, for example, comprise at least one of: a hardware load indicator, an NG interface load indicator (e.g., a load indicator for an interface

between the CU-CP node **1701** and a core network entity), an F1 interface load indicator (e.g., load information for an interface between the CU-CP node **1701** and the DU **1703**), a composite available capacity group, and/or a network slice overload indicator of the CU-CP node **1701**. [0373] DU status information (e.g., the status information **2314**) may, for example, comprise at least one of: a hardware load indicator, an F1 interface load indicator (e.g., load information for an interface between the CU-CP node **1701** or the CU-UP node **1702** and the DU **1703**), a radio resource status, a composite available capacity group, and/or a network slice overload indicator of the DU **1703**. DU status information may also or alternatively comprise UL radio signaling quality information of the wireless device **1704** (e.g., based on SRS, RSRQ, and/or RSRP). RRC wireless device (e.g., UE) status information may, for example, comprise at least one of: measurement results (e.g., RSRP and/or RSRQ of one or more serving cells), battery status information, a number of RLC retransmissions for UL transmission, UL transport block transmission failure rate, random access failure rate, configured resource (e.g., Type 1, grant free resource) access failure rate, UL PDCP delay information, and/or other information. Lower layer wireless device (e.g., UE) status information may, for example, comprise at least one of: a CQI report, information of RSRQ or RSRP of CSI-RS or SS, hybrid ARQ retransmission number information, buffer status report of one or more logical channels (e.g., associated with a bearer for which PDCP packet duplication is configured and/or activated), and/or other information.

[0374] A hardware load indicator may, for example, indicate hardware load information (e.g., load or other status of a CPU, memory, and/or a bus, and/or information) of corresponding node and/or one or more associated cells. A hardware load indicator may comprise hardware load information for each network slice of the one or more slices served via the corresponding node and/or a cell. Hardware load information may, for example, indicate a hardware load level status. Hardware load information may, for example, indicate a low load status, a medium load status, a high load status, and/or an overload status. Hardware load information may, for example, comprise one or more network slice identifiers of one or more overloaded network slices.

[0375] Hardware load information may, for example, indicate a hardware load share status of one or more associated cells and/or each network slice of one or more network slices. Hardware load information may, for example, indicate a hardware resource usage amount ratio (e.g., a hardware load share amount ratio) of one or more associated cells compared to a hardware resource usage amount of other cells and/or compared to a total hardware resource amount of a corresponding node. Hardware load information may, for example, indicate a hardware resource usage amount ratio (e.g., a hardware load share amount ratio) of each network slice of one or more network slices compared to a hardware resource usage amount of other network slices in a corresponding node and/or one or more associated cells. Hardware load information may, for example, indicate a hardware resource usage amount ratio (e.g., a hardware load share amount ratio) of each network slice of one or more network slices compared to a total hardware resource amount of a corresponding node and/or one or more associated cells.

[0376] An NG interface load indicator may, for example, indicate a load of an interface between a corresponding node (e.g., the CU-CP node **1701** and/or the CU-UP node **1702**) and a core network entity. An NG interface load indicator may comprise an NG interface load information for each network slice of one or more network slices. NG interface load information may, for example, indicate an NG interface load level status of a corresponding node and/or of each network slice of one or more network slices. NG interface load information may, for example, indicate a low load status, a medium load status, a high load status, and/or an overload status. NG interface load information may, for example, comprise one or more network slice identifiers of one or more overloaded network slices of a corresponding node.

[0377] NG interface load information may, for example, indicate an NG interface load share status of a corresponding node and/or each network slice of one or more network slices. NG interface load information may, for example, indicate an NG interface resource usage amount ratio (e.g., an

NG interface load share amount ratio) of each network slice of one or more network slices compared to an NG interface resource usage amount of other network slices. NG interface load information may, for example, indicate an NG interface resource usage amount ratio (e.g., an NG interface load share amount ratio) of each network slice of one or more network slices compared to a total NG interface resource amount of a corresponding node.

[0378] An F1 interface load indicator may, for example, indicate load information of an interface between a corresponding node (e.g., the CU-CP node **1701** and/or the CU-UP node **1702**) and the DU **1703**. An F1 interface load indicator may indicate F1 interface load information for one or more serving cells. An F1 interface load indicator may indicate F1 interface load information for each network slice of one or more network slices. F1 interface load information may, for example, indicate an F1 interface load level status of a corresponding node, and/or each network slice of one or more network slices. F1 interface load information may, for example, indicate a low load status, a medium load status, a high load status, and/or an overload status of a corresponding node, and/or each network slice of one or more network slices. F1 interface load information may, for example, comprise one or more network slice identifiers of one or more overloaded network slices. F1 interface load information may, for example, comprise one or more cell identifiers of one or more overloaded cells of the DU **1703**.

[0379] F1 interface load information may, for example, indicate an F1 interface load share status of each network slice of one or more network slices. F1 interface load information may, for example, indicate an F1 interface resource usage amount ratio (e.g., an F1 interface load share amount ratio) of each network slice of one or more network slices compared to an F1 interface resource usage amount of other network slices. F1 interface load information may, for example, indicate an F1 interface resource usage amount ratio (e.g., an F1 interface load share amount ratio) of each network slice of one or more first network slices compared to a total F1 interface resource amount of a corresponding node and/or one or more serving cells.

[0380] Radio resource status may, for example, comprise a physical layer resource block usage information for a downlink GBR, a downlink non-GBR, an uplink GBR, an uplink non-GBR, a total downlink, and/or a total uplink transmission associated with one or more serving cells and/or each network slice of one or more network slices. Radio resource status may, for example, comprise a physical layer resource block usage information for each network slice of one or more network slices. Physical layer resource block usage information may, for example, indicate a physical layer resource block usage level of one or more serving cells and/or each network slice of one or more network slices. Physical layer resource block usage information may, for example, indicate a low usage status, a medium usage status, a high usage status, and/or a full usage status of one or more serving cells and/or each network slice of one or more network slices. Physical layer resource block usage information may, for example, comprise one or more network slice identifiers of one or more overloaded network slices.

[0381] Physical layer resource block usage information may, for example, indicate a physical layer resource block usage status of one or more serving cells and/or each network slice of one or more network slices. Physical layer resource block usage status may, for example, be associated with a downlink GBR, a downlink non-GBR, an uplink GBR, an uplink non-GBR, a total downlink, and/or a total uplink transmission of one or more serving cells and/or each network slice of one or more network slices. Physical layer resource block usage information may, for example, indicate a physical layer resource block usage amount ratio of each network slice of one or more network slices compared to a physical layer resource block usage amount of other network slices. Physical layer resource block usage information may, for example, indicate a physical layer resource block usage amount ratio of each network slice of one or more network slices compared to a total physical layer resource block amount. Physical layer resource block usage information may, for example, indicate a physical layer resource block usage amount ratio of each network slice of one or more network slices compared to a physical layer resource block amount allowed for each

network slice.

[0382] A composite available capacity group may, for example, comprise a cell capacity class value and/or a capacity value for a DL and/or an UL associated with a corresponding node, one or more service cells, and/or each network slice of one or more network slices. A cell capacity class value may, for example, indicate a value classifying a cell capacity of one or more serving cells with regards to other cells. A cell capacity class value may, for example, indicate a value classifying a capacity for each network slice of one or more network slices with regards to other cells and/or other network slices. The capacity value may indicate an amount of resources, for one or more serving cells and/or each network slice of one or more network slices, that are available relative to a total resource for corresponding node, one or more serving cells, and/or each network slice of one or more network slices.

[0383] A network slice overload indicator may, for example, indicate whether each network slice of one or more network slices is overloaded. A network slice overload indicator may, for example, indicate a low load status, a medium load status, a high load status, and/or an overload status of each network slice of one or more network slices.

[0384] FIG. 27 shows an example method that may, for example, be performed by a CU-CP node (e.g., the CU-CP node 1701). Status information may be received in step 2701. The status information may, for example, comprise status information from self-monitoring (e.g., the status information 2312), status information (e.g., the status information 2302) for a CU-UP node (e.g., the CU-UP node 1702), status information (e.g., the status information 2309) for a DU (e.g., the DU 1703), RRC wireless device (e.g., UE) status information (e.g., the status information 2309) received from a wireless device (e.g., the wireless device 1704) via the DU, lower layer status information (e.g., the status information 2309) received from the DU and/or from the wireless device (e.g., the status information 2310), and/or other information.

[0385] In step 2702, a determination, regarding the availability of resources to support packet duplication, may be made. The determination may be based on one or more parts of the status information received in step 2701 and may comprise, for example, determining whether a resource utilization ratio satisfies (e.g., is lower than) a first threshold value. The first threshold value may be predetermined. The first threshold value for the method of FIG. 27 may be the same as, or different from, the first threshold value for the method of FIG. 28, and/or may be the same as, or different from, the first threshold value for the method of FIG. 29. If it is determined in step 2702 that resources to support packet duplication are not available (e.g., if the utilization ratio does not satisfy (e.g., is not lower than) the first threshold value), step 2706 (described below) may be performed. If it is determined in step 2702 that resources to support packet duplication are available (e.g., if the utilization ratio satisfies (e.g., is lower than) the first threshold value), step 2703 may be performed.

[0386] In step 2703, a determination, of whether radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication, may be made. The determination may be based on one or more parts of the status information received in step 2701 and may comprise, for example, determining if a radio quality satisfies (e.g., is lower than) a second threshold value. The second threshold value may be predetermined. The second threshold value for the method of FIG. 27 may be the same as, or different from, the second threshold value for the method of FIG. 28, and/or may be the same as, or different from, the second threshold value for the method of FIG. 29. If it is determined in step 2703 that radio signaling quality is not sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if the radio quality does not satisfy (e.g., is not lower than) the second threshold value), step 2705 may be performed. If it is determined in step 2703 that radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if the radio quality does satisfy (e.g., is lower than) the second threshold value), step 2704 may be performed.

[0387] In step 2704, a determination, of whether PDCP packet duplication is activated, may be

made. If PDCP packet duplication is activated, step **2701** may be repeated. If PDCP packet duplication is not activated, step **2705** may be performed. In step **2705**, activation of UL PDCP packet duplication and/or of DL PDCP packet duplication may be caused. An indication of UL and/or DL PDCP packet duplication activation may, as part of step **2705**, be sent to the CU-UP node and/or to the DU. The method may end. Alternatively, and as shown with a broken line, the method may begin again by repeating step **2701**.

[0388] If it is determined in step **2703** that radio signaling quality is not sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication, step **2706** may be performed. In step **2706**, a determination, of whether PDCP packet duplication is activated, may be made. If PDCP packet duplication is not activated, step **2701** may be repeated. If PDCP packet duplication is activated, step **2707** may be performed. In step **2707**, deactivation of UL and/or DL PDCP packet duplication for a bearer may be caused. An indication of UL and/or DL PDCP packet duplication deactivation may, as part of step **2707**, be sent to the CU-UP node and/or to the DU. The method may end. Alternatively, and as shown with a broken line, the method may begin again by repeating step **2701**.

[0389] FIG. **28** shows an example method that may, for example, be performed by a CU-UP node (e.g., the CU-UP node **1702**). Status information may be received in step **2801**. The status information may, for example, comprise status information from self-monitoring (e.g., the status information **2313**) and/or status information (e.g., the status information **2301**) for a CU-CP node (e.g., the CU-CP node **1701**), status information for a DU (e.g., the DU **1703**), RRC wireless device (e.g., UE) status information, lower layer wireless device (e.g., UE) status information, and/or other information.

[0390] In step **2802**, a determination, regarding the availability of resources to support packet duplication, may be made. The determination may be based on one or more parts of the status information received in step **2801** and may comprise, for example, determining whether a resource utilization ratio satisfies (e.g., is lower than) a first threshold value. The first threshold value may be predetermined. The first threshold value for the method of FIG. **28** may be the same as, or different from, the first threshold value for the method of FIG. **27**, and/or may be the same as, or different from, the first threshold value for the method of FIG. **29**. If it is determined in step **2802** that resources to support packet duplication are not available (e.g., if the utilization ratio does not satisfy (e.g., is not lower than) the first threshold value), step **2807** (described below) may be performed. If it is determined in step **2802** that resources to support packet duplication are available (e.g., if the utilization ratio satisfies (e.g., is lower than) the first threshold value), step **2803** may be performed.

[0391] In step **2803**, a determination, of whether radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication, may be made. The determination may be based on one or more parts of the status information received in step **2801** and may comprise, for example, determining if a radio quality satisfies (e.g., is lower than) a second threshold value. The second threshold value may be predetermined. The second threshold value for the method of FIG. **28** may be the same as, or different from, the second threshold value for the method of FIG. **27**, and/or may be the same as, or different from, the second threshold value for the method of FIG. **29**. If it is determined in step **2803** that radio signaling quality is not sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if the radio quality does not satisfy (e.g., is not lower than) the second threshold value), step **2807** may be performed. If it is determined in step **2803** that radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if the radio quality does satisfy (e.g., is lower than) the second threshold value), step **2804** may be performed.

[0392] In step **2804**, a determination, of whether PDCP packet duplication is activated, may be made. If PDCP packet duplication is activated, step **2801** may be repeated. If PDCP packet duplication is not activated, step **2805** may be performed. In step **2805**, activation of UL PDCP

packet duplication and/or of DL PDCP packet duplication may be caused. An indication of UL and/or DL PDCP packet duplication activation may, as part of step **2805**, be sent to the CU-CP node and/or to the DU.

[0393] In step **2806**, the start of sending of duplicated DL PDCP packets, and/or the start of discarding duplicated UL PDCP packets, may be caused. The method may end. Alternatively, and as shown with a broken line, the method may begin again by repeating step **2801**.

[0394] If it is determined in step **2803** that radio signaling quality is not sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication, step **2807** may be performed. In step **2807**, a determination, of whether PDCP packet duplication is activated, may be made. If PDCP packet duplication is not activated, step **2801** may be repeated. If PDCP packet duplication is activated, step **2808** may be performed. In step **2808**, deactivation of UL and/or DL PDCP packet duplication for a bearer may be caused. An indication of UL and/or DL PDCP packet duplication deactivation may, as part of step **2808**, be sent to the CU-CP node and/or to the DU.

[0395] In step **2809**, the cessation of sending duplicated DL PDCP packets may be caused. The method may end. Alternatively, and as shown with a broken line, the method may begin again by repeating step **2801**.

[0396] FIG. **29** shows an example method that may, for example, be performed by a DU (e.g., the DU **1703**). Status information may be received in step **2901**. The status information may, for example, comprise status information from self-monitoring (e.g., the status information **2314**), status information (e.g., the status information **2307**) for a CU-CP node (e.g., the CU-CP node **1701**) and/or a CU-UP node (e.g., the CU-UP node **1702**), RRC wireless device (e.g., UE) status information, lower layer wireless device (e.g., UE) status information, and/or other information.

[0397] In step **2902**, a determination, regarding the availability of resources to support packet duplication, may be made. The determination may be based on one or more parts of the status information received in step **2901** and may comprise, for example, determining whether a resource utilization ratio satisfies (e.g., is lower than) a first threshold value. The first threshold value may be predetermined. The first threshold value for the method of FIG. **29** may be the same as, or different from, the first threshold value for the method of FIG. **27**, and/or may be the same as, or different from, the first threshold value for the method of FIG. **28**. If it is determined in step **2902** that resources to support packet duplication are not available (e.g., if the utilization ratio does not satisfy (e.g., is not lower than) the first threshold value), step **2906** (described below) may be performed. If it is determined in step **2902** that resources to support packet duplication are available (e.g., if the utilization ratio satisfies (e.g., is lower than) the first threshold value), step **2903** may be performed.

[0398] In step **2903**, a determination, of whether radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication, may be made. The determination may be based on one or more parts of the status information received in step **2901** and may comprise, for example, determining if a radio quality satisfies (e.g., is lower than) a second threshold value. The second threshold value may be predetermined. The second threshold value for the method of FIG. **29** may be the same as, or different from, the second threshold value for the method of FIG. **27**, and/or may be the same as, or different from, the second threshold value for the method of FIG. **28**. If it is determined in step **2903** that radio signaling quality is not sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if the radio quality does not satisfy (e.g., is not lower than) the second threshold value), step **2906** may be performed. If it is determined in step **2903** that radio signaling quality is sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication (e.g., if the radio quality does satisfy (e.g., is lower than) the second threshold value), step **2904** may be performed.

[0399] In step **2904**, a determination, of whether PDCP packet duplication is activated, may be made. If PDCP packet duplication is activated, step **2901** may be repeated. If PDCP packet duplication is not activated, step **2905** may be performed. In step **2905**, activation of UL PDCP

packet duplication and/or of DL PDCP packet duplication may be caused. An indication of UL and/or DL PDCP packet duplication activation may, as part of step **2905**, be sent to the CU-CP node and/or to a wireless device (e.g., to the wireless device **1704**). The method may end. Alternatively, and as shown with a broken line, the method may begin again by repeating step **2901**.

[0400] If it is determined in step **2903** that radio signaling quality is not sufficiently poor and/or unstable so as to indicate a benefit from PDCP packet duplication, step **2906** may be performed. In step **2906**, a determination, of whether PDCP packet duplication is activated, may be made. If PDCP packet duplication is not activated, step **2901** may be repeated. If PDCP packet duplication is activated, step **2907** may be performed. In step **2907**, deactivation of UL and/or DL PDCP packet duplication for a bearer may be caused. An indication of UL and/or DL PDCP packet duplication deactivation may, as part of step **2907**, be sent to the CU-CP node and/or to the wireless device. The method may end. Alternatively, and as shown with a broken line, the method may begin again by repeating step **2901**.

[0401] FIG. **30** shows an example method that may, for example, be performed by a wireless device (e.g., the wireless device **1704**). In step **3001**, a MAC CE indicating activation or deactivation of UL PDCP packet duplication may be received. The MAC CE may be received, for example, from a DU (e.g., the DU **1703**). In step **3002**, a determination, of whether the MAC CE indicates activation of PDCP packet duplication or deactivation of PDCP packet duplication, may be made. If the MAC CE indicates activation of PDCP packet duplication, and as shown in step **3003**, the start of sending duplicated PDCP packets may be caused. If the MAC CE indicates deactivation of PDCP packet duplication, and as shown in step **3004**, cessation of sending duplicated PDCP packets may be caused.

[0402] PDCP packet duplication may be activated (e.g., caused to be activated) by one of the CU-CP **1701**, the CU-UP **1702**, or the DU **1703**, and may subsequently be deactivated (e.g., caused to be deactivated) by a different one of the CU-CP **1701**, the CU-UP **1702**, or the DU **1703**. PDCP packet duplication may be activated (e.g., caused to be activated) by one of the CU-CP **1701**, the CU-UP **1702**, or the DU **1703**, and at a different time may be activated (e.g., caused to be activated) by a different one of the CU-CP **1701**, the CU-UP **1702**, or the DU **1703**. PDCP packet duplication may be deactivated (e.g., caused to be deactivated) by one of the CU-CP **1701**, the CU-UP **1702**, or the DU **1703**, and at a different time may be deactivated (e.g., caused to be deactivated) by a different one of the CU-CP **1701**, the CU-UP **1702**, or the DU **1703**.

[0403] A CU-CP (e.g., a CU-CP node) may transmit, to a CU-UP (e.g., a CU-UP node), a first message indicating a first bearer configuration request for a wireless device. The first message may comprise a first bearer identifier of a first bearer and/or a PDCP configuration parameter indicating that PDCP packet duplication is configured for the first bearer. The CU-CP may receive, from the CU-UP, a second message indicating that the PDCP packet duplication of the first bearer is set up (e.g., configured). The CU-UP may send (e.g., transmit), to the CU-UP, a third message indicating a first activation or a first deactivation of the PDCP packet duplication of the first bearer. The second message may comprise UL tunnel information of the first bearer. The UL tunnel information may comprise a first UL TEID and/or a second UL TEID.

[0404] The CU-CP may send (e.g., transmit), to a DU and based on (e.g., in response to) receiving the second message, a fourth message indicating a second bearer configuration request for the first bearer of the wireless device. The fourth message may comprise the UL tunnel information of the first bearer. The CU-CP may receive, from the DU and based on (e.g., in response to) the fourth message, a fifth message comprising DL tunnel information of the first bearer. The DL tunnel information may comprise a first DL TEID and/or a second DL TEID. The CU-CP may send (e.g., transmit), to the CU-UP, a sixth message comprising the DL tunnel information for the first bearer. A first base station may comprise the CU-CP, the CU-UP, and/or the DU.

[0405] The DU may, for example, send (e.g., transmit), to the wireless device, a MAC CE

indicating a second activation or a second deactivation of the PDCP packet duplication. The second activation and the second deactivation may be associated with an UL PDCP packet duplication. The DU may receive, from the wireless device, duplicated PDCP packets of the first bearer if the MAC CE indicates the second activation. Based on (e.g., in response to) the third message: if the third message indicates the first activation, the CU-CP may transmit duplicated PDCP packets of the first bearer; and/or if the third message indicates the first deactivation, the CU-CP may stop transmitting duplicated PDCP packets of the first bearer. The CU-UP may, for example, discard duplicated PDCP packets of the first bearer received from the wireless device if the third message indicates the first activation. The first activation and/or the first deactivation may, for example, be associated with at least one of an UL PDCP packet duplication and/or a DL PDCP packet duplication.

[0406] The first message may, for example, further indicate and/or comprise an IE indicating a third activation or a third deactivation of the PDCP packet duplication. The third activation and the third deactivation may be associated with at least one of an UL PDCP packet duplication and/or a DL PDCP packet duplication. The CU-CP may, for example send (e.g., transmit), to the wireless device, an RRC message indicating that the PDCP packet duplication for the first bearer is configured. The wireless device may, for example, discard duplicated PDCP packets of the first bearer received from the CU-UP (and/or the DU) if the third message indicates the first activation. The first activation or the first deactivation may, for example, be based on at least one of: first status information received from a DU, the first status information comprising DU status information and/or lower layer wireless device status information; and/or second status information received from the wireless device, the second status information comprising RRC wireless device status information.

[0407] A CU-CP may, for example, send (e.g., transmit), to a CU-UP, a first message indicating a first bearer configuration request for a wireless device. The first message may comprise a first bearer identifier of a first bearer and/or a PDCP configuration parameter indicating that PDCP packet duplication is configured for the first bearer. The CU-CP may receive, from the CU-UP, a second message indicating that the PDCP packet duplication of the first bearer is set up (e.g., configured). The CU-CP may receive, from the CU-UP, a third message indicating a fourth activation or a fourth deactivation of the PDCP packet duplication of the first bearer. The CU-UP may initiate the fourth activation and the fourth deactivation. The fourth activation and the fourth deactivation may, for example, be associated with at least one of an UL PDCP packet duplication and/or a DL PDCP packet duplication.

[0408] Based on, for example, in response to, the third message: if the third message indicates the fourth activation, the CU-UP may transmit duplicated PDCP packets of the first bearer; and/or if the third message indicates the fourth deactivation, the CU-UP may stop transmitting duplicated PDCP packets of the first bearer. The CU-UP may, for example, discard duplicated PDCP packets of the first bearer received from the wireless device if the third message indicates the fourth activation. The wireless device may, for example, discard duplicated PDCP packets of the first bearer received from the CU-UP (and/or the DU) if the third message indicates the fourth activation.

[0409] The fourth activation or the fourth deactivation may be based on first status information received from a CU-CP. The first status information may comprise at least one of CU-CP status information, DU status information, RRC wireless device status information, and/or lower layer wireless device status information.

[0410] A method may comprise receiving, by a central unit user plane (CU-UP) node from a central unit control plane (CU-CP) node, one or more messages. The one or more messages may indicate: configuration of packet duplication for a bearer, and activation of the packet duplication. The method may comprise sending, by the CU-UP node and based on the one or more messages, packets for the bearer and duplicated versions of the packets. The one or more messages may comprise a configuration message indicating a bearer configuration request for a wireless device.

The sending may comprise sending the packets and the duplicated versions of the packets, via a distributed unit of a base station, to a wireless device. The one or more messages may comprise logical channel information, for the bearer, comprising: a first logical channel identifier of a first logical channel for the packets, and a second logical channel identifier of a second logical channel for the duplicated versions of the packets. The method may comprise after receiving the one or more messages, sending, by the CU-UP node to the CU-CP node, one or more second messages comprising uplink tunnel information, for the bearer, comprising: a first uplink tunnel endpoint identifier for a first tunnel for uplink packets of the bearer, and a second uplink tunnel endpoint identifier for a second tunnel for duplicated uplink packets. The method may comprise after sending the one or more second messages, receiving, from the CU-CP node, a configuration update message indicating downlink tunnel information for the bearer. The method may comprise receiving, by the CU-UP node from the CU-CP node, one or more messages indicating deactivation of the packet duplication; and based on the one or more messages indicating the deactivation, discontinuing the sending of the duplicated versions of the packets. The method may comprise based on status information associated with the CU-CP node, deactivating, by the CU-UP node, the packet duplication. The method may comprise based on status information associated with a distributed unit of a base station, deactivating, by the CU-UP node, the packet duplication. The method may comprise based on status information received by the CU-UP node, deactivating the packet duplication, wherein the status information may comprise indications of one or more of: a hardware load, a load of an N2 interface between the CU-UP node and a core network entity, a load of an F1 interface between the CU-UP node and a distributed unit of a base station, a composite available capacity group, or a network slice overload. The method may comprise deactivating, by the CU-UP node, the packet duplication; and sending, by the CU-UP node to the CU-CP node, one or more messages indicating the deactivation of the packet duplication. The method may comprise activating, by the CU-UP node and based on status information received by the CU-UP node, packet duplication, wherein the status information may comprise one or more of: status information associated with the CU-CP node, or status information associated with a distributed unit of a base station; and sending by the CU-UP node to the CU-CP node, one or more messages indicating the activation by the CU-UP node. The packet duplication may comprise packet data convergence protocol (PDCP) packet duplication.

[0411] A method may comprise receiving, by a central unit user plane (CU-UP) node from a central unit control plane (CU-CP) node, one or more messages indicating activation of packet duplication for a bearer. The method may comprise sending, by the CU-UP node and based on the one or more messages, packets for the bearer and duplicated versions of the packets. The method may comprise receiving, by the CU-UP node from the CU-CP node, one or more messages indicating deactivation of the packet duplication. The method may comprise based on the one or more messages indicating the deactivation, discontinuing the sending of the duplicated versions of the packets. The method may comprise determining, by the CU-UP node and based on status information received by the CU-UP node after a second activation of the packet duplication, to perform a second deactivation of the packet duplication, wherein the status information may comprise status information associated with one or more of the CU-CP node or a distributed unit (DU) of a base station. The method may comprise activating, by the CU-UP node, the packet duplication; and sending by the CU-UP node to the CU-CP node, one or more messages indicating the activation by the CU-UP node. The method may comprise based on additional status information received by the CU-UP node, activating, by the CU-UP node, packet duplication, wherein the additional status information may comprise one or more of: additional status information associated with the CU-CP node, or additional status information associated with a distributed unit (DU) of a base station.

[0412] A method may comprise based on status information received by a central unit user plane (CU-UP) node, activating, by the CU-UP node, packet duplication. The status information may comprise one or more of: status information associated with a central unit control plane (CU-CP)

node, or status information associated with a distributed unit (DU). The method may comprise sending, by the CU-UP node to the CU-CP node, one or more messages indicating the activation. The method may comprise based on the activation, sending, via the DU and to a wireless device, packets and duplicated versions of the packets. The status information may comprise indications of one or more of: a hardware load, a load of an N2 interface between the CU-UP node and a core network entity, a load of an F1 interface between the CU-UP node and the DU, a composite available capacity group, or a network slice overload. The method may comprise deactivating, by the CU-UP node, the packet duplication; and sending, by the CU-UP node to the CU-CP node, one or more messages indicating the deactivation of the packet duplication.

[0413] A method may comprise receiving, by a central unit user plane from a central unit control plane, a configuration message indicating a bearer configuration request for a wireless device. The configuration message may comprise: a bearer identifier of a bearer; a packet data convergence protocol (PDCP) duplication parameter indicating that PDCP packet duplication is configured for the bearer; and a duplication activation parameter indicating that the PDCP packet duplication is activated. The method may comprise transmitting, by the central unit user plane to the central unit control plane, a response message for the configuration message. The method may comprise transmitting, by the central unit user plane to the wireless device and based on the duplication activation parameter, packets for the bearer and duplicated packets of the packets. The configuration message may comprise logical channel information of the bearer, and the logical channel information may comprise: a first logical channel identifier of a first logical channel for packets of the bearer; and a second logical channel identifier of a second logical channel for duplication of the packets. The response message may comprise uplink tunnel information of the bearer, and the uplink tunnel information may comprise: a first uplink tunnel endpoint identifier for a first tunnel for uplink packets of the bearer; and a second uplink tunnel endpoint identifier for a second tunnel for duplication of the uplink packets. The method may comprise transmitting, by the central unit control plane to a distributed unit and in response to receiving the response message, a second configuration message indicating a second bearer configuration request for the bearer of the wireless device, the second configuration message comprising the uplink tunnel information of the bearer. The method may comprise receiving, by the central unit control plane from the distributed unit and in response to the message, a second response message comprising downlink tunnel information of the bearer, and the downlink tunnel information may comprise: a first downlink tunnel endpoint identifier for the first tunnel; and a second downlink tunnel endpoint identifier for the second tunnel. The method may comprise transmitting, by the central unit control plane to the central unit user plane, a configuration update message comprising the downlink tunnel information for the bearer. A base station may comprise: the central unit control plane; the central unit user plane; and the distributed unit. The method may comprise transmitting, by the distributed unit to the wireless device, a medium access control control element (MAC CE) indicating a second activation or a second deactivation of the PDCP packet duplication, wherein the second activation and the second deactivation are for an uplink PDCP packet duplication. The method may comprise receiving, by the distributed unit from the wireless device, duplicated PDCP packets of the bearer if the medium access control control element indicates the second activation. The method may comprise receiving, by the central unit user plane from the central unit control plane, a third configuration message comprising a duplication deactivation parameter indicating that the PDCP packet duplication is deactivated. The method may comprise stopping, by the central unit user plane, transmitting duplicated packets of packets for the bearer. The method may comprise receiving, by the central unit user plane from the central unit control plane, a fourth configuration message comprising a second duplication activation parameter indicating that the PDCP packet duplication is deactivated. The method may comprise transmitting, by the central unit user plane to the wireless device and based on the second duplication activation parameter, second packets for the bearer and second duplicated packets of the second packets. The method may comprise

receiving, by the central unit user plane from the wireless device, uplink packets for the bearer and uplink duplicated packets of the uplink packets. The method may comprise discarding, by the central unit user plane, at least one of the uplink packets or the uplink duplicated packets. The method may comprise discarding, by the wireless device, at least one of the packets for the bearer or the duplicated packets of the packets. The method may comprise transmitting, by the central unit control plane to the wireless device, a radio resource control message indicating that the PDCP packet duplication for the bearer is configured. The central unit control plane may determine the activation of the PDCP packet duplication based on at least one of: first status information received from a distributed unit (and the first status information may comprise at least one of: distributed unit status information; or lower layer wireless device status information of the wireless device); or second status information received from the wireless device (the second status information may comprise radio resource control wireless device status information). The distributed unit status information may comprise at least one of: a hardware load indicator; a F1 interface load indicator indicating load information of an interface between the central unit user plane and the distributed unit; a radio resource status information; a composite available capacity group; or a network slice overload indicator of the distributed unit. The lower layer wireless device status information may comprise at least one of: uplink radio signaling quality information; or downlink radio signaling quality information. The uplink radio signaling quality information may comprise at least one of: one or more sounding reference signals received from the wireless device; hybrid automatic repeat request (HARQ) retransmission number information; or buffer status information of one or more logical channels. The downlink radio signaling quality information may comprise a channel status information report received from the wireless device. The channel status information may comprise at least one of: a reference signal received power; or a reference signal received quality. The radio resource control wireless device status information comprises at least one of: a reference signal received power; a reference signal received quality; battery status information; a number of radio link control (RLC) retransmissions; a transport block transmission failure rate; a random access failure rate; a configured resource access failure rate; or PDCP delay information. The method may comprise determining, by the central unit user plane, deactivation of the PDCP packet duplication. The method may comprise stopping, by the central unit user plane and in response to determining the deactivation, transmitting duplicated packets of packets for the bearer. The determining the deactivation may be based on status information of the central unit control plane, the status information comprising at least one of: a hardware load; an N2 interface load of an N2 interface between the central unit user plane and a core network entity; an F1 interface load of an F1 interface between the central unit user plane and a distributed unit; a composite available capacity group; or a network slice overload. The method may comprise transmitting, by the central unit user plane to central unit control plane, a configuration update request message indicating the deactivation of the PDCP packet duplication.

[0414] A method may comprise sending, by a central unit control plane to a central unit user plane, a configuration message indicating a first bearer configuration request for a wireless device, and the configuration message may comprise: a bearer identifier of a bearer; and a packet data convergence protocol (PDCP) configuration parameter indicating that PDCP packet duplication is configured for the bearer. The method may comprise receiving, by the central unit control plane from a base station distributed unit, distributed unit status information. The method may comprise determining, by the central unit control plane, to activate the PDCP packet duplication based on the distributed unit status information. The method may comprise sending, by the central unit control plane to the central unit user plane, a configuration update message indicating activation of the PDCP packet duplication of the bearer.

[0415] A method may comprise determining, by a central unit control plane, to activate a packet data convergence protocol (PDCP) packet duplication for a bearer of a wireless device. The method may comprise sending, by a central unit control plane to a central unit user plane, a configuration

message indicating a bearer configuration request for the wireless device. The configuration message may comprise: a bearer identifier of a bearer; a PDCP duplication parameter indicating that PDCP packet duplication is configured for the bearer; and a duplication activation parameter indicating that the PDCP packet duplication is activated. The method may comprise receiving, by the central unit control plane from a base station distributed unit, a response message for the configuration message.

[0416] A method may comprise receiving, by a central unit control plane from a core network node, a context setup message requesting configuration of a session for a wireless device. The method may comprise determining, by the central unit control plane: to configure packet data convergence protocol (PDCP) packet duplication for a bearer of the session; and to activate the PDCP duplication based on distributed unit status information. The method may comprise sending, by a central unit control plane to a central unit user plane, a configuration message indicating a bearer configuration request for the wireless device. The configuration message may comprise: a bearer identifier of the bearer; and PDCP configuration parameters. The PDCP configuration parameters may indicate that: the PDCP packet duplication is configured for the bearer; and the PDCP packet duplication is activated for the bearer. The method may comprise receiving, by the central unit control plane from a base station distributed unit, a response message for the configuration message. The response message may indicate that the PDCP configuration parameters are configured.

[0417] A method may comprise transmitting, by a central unit control plane to a central unit user plane, a first message indicating a bearer configuration request for a wireless device. The first message may comprise: a bearer identifier of a bearer; and a packet data convergence protocol (PDCP) configuration parameter indicating that PDCP packet duplication is configured for the bearer. The method may comprise receiving, by the central unit control plane from the central unit user plane, a second message indicating that the PDCP packet duplication of the bearer is set up. The method may comprise receiving, by the central unit control plane from the central unit user plane, a third message indicating an activation or a deactivation of the PDCP packet duplication of the bearer. The activation and the deactivation may be initiated by the central unit user plane. The activation and the deactivation may be associated with at least one of: an uplink PDCP packet duplication; or a downlink PDCP packet duplication. The method may comprise, in response to the third message: if the third message indicates the activation, transmitting, by the central unit user plane, duplicated PDCP packets of the bearer; and if the third message indicates the deactivation, stopping, by the central unit user plane, transmitting duplicated PDCP packets of the bearer. The method may comprise discarding, by the central unit user plane, duplicated PDCP packets of the bearer received from the wireless device if the third message indicates the activation. The method may comprise discarding, by the wireless device, at least one of PDCP packets of the bearer or duplicated PDCP packets of the PDCP packets received from the central unit user plane. The activation or the deactivation may be based on at least one of status information received from a central unit control plane. The status information may comprise at least one of: central unit control plane status information; distributed unit status information; radio resource control wireless device status information; or lower layer wireless device status information.

[0418] FIG. 31 shows example elements of a computing device that may be used to implement any of the various devices described herein, including, e.g., the base station **120A** and/or **120B**, the wireless device **110** (e.g., **110A** and/or **110B**), or any other base station, wireless device, or computing device described herein. The computing device **3100** may include one or more processors **3101**, which may execute instructions stored in the random access memory (RAM) **3103**, the removable media **3104** (such as a Universal Serial Bus (USB) drive, compact disk (CD) or digital versatile disk (DVD), or floppy disk drive), or any other desired storage medium. Instructions may also be stored in an attached (or internal) hard drive **3105**. The computing device **3100** may also include a security processor (not shown), which may execute instructions of one or

more computer programs to monitor the processes executing on the processor **3101** and any process that requests access to any hardware and/or software components of the computing device **3100** (e.g., ROM **3102**, RAM **3103**, the removable media **3104**, the hard drive **3105**, the device controller **3107**, a network interface **3109**, a GPS **3111**, a Bluetooth interface **3112**, a WiFi interface **3113**, etc.). The computing device **3100** may include one or more output devices, such as the display **3106** (e.g., a screen, a display device, a monitor, a television, etc.), and may include one or more output device controllers **3107**, such as a video processor. There may also be one or more user input devices **3108**, such as a remote control, keyboard, mouse, touch screen, microphone, etc. The computing device **3100** may also include one or more network interfaces, such as a network interface **3109**, which may be a wired interface, a wireless interface, or a combination of the two. The network interface **3109** may provide an interface for the computing device **3100** to communicate with a network **3110** (e.g., a RAN, or any other network). The network interface **3109** may include a modem (e.g., a cable modem), and the external network **3110** may include communication links, an external network, an in-home network, a provider's wireless, coaxial, fiber, or hybrid fiber/coaxial distribution system (e.g., a DOCSIS network), or any other desired network. Additionally, the computing device **3100** may include a location-detecting device, such as a global positioning system (GPS) microprocessor **3111**, which may be configured to receive and process global positioning signals and determine, with possible assistance from an external server and antenna, a geographic position of the computing device **3100**.

[0419] The example in FIG. **31** may be a hardware configuration, although the components shown may be implemented as software as well. Modifications may be made to add, remove, combine, divide, etc. components of the computing device **3100** as desired. Additionally, the components may be implemented using basic computing devices and components, and the same components (e.g., processor **3101**, ROM storage **3102**, display **3106**, etc.) may be used to implement any of the other computing devices and components described herein. For example, the various components described herein may be implemented using computing devices having components such as a processor executing computer-executable instructions stored on a computer-readable medium, as shown in FIG. **31**. Some or all of the entities described herein may be software based, and may co-exist in a common physical platform (e.g., a requesting entity may be a separate software process and program from a dependent entity, both of which may be executed as software on a common computing device).

[0420] The disclosed mechanisms herein may be performed if certain criteria are met, for example, in a wireless device, a base station, a radio environment, a network, a combination of the above, and/or the like. Example criteria may be based on, for example, wireless device and/or network node configurations, traffic load, initial system set up, packet sizes, traffic characteristics, a combination of the above, and/or the like. If the one or more criteria are met, various examples may be used. It may be possible to implement examples that selectively implement disclosed protocols.

[0421] A base station may communicate with a mix of wireless devices. Wireless devices and/or base stations may support multiple technologies, and/or multiple releases of the same technology. Wireless devices may have some specific capability(ies) depending on wireless device category and/or capability(ies). A base station may comprise multiple sectors. A base station communicating with a plurality of wireless devices may refer to base station communicating with a subset of the total wireless devices in a coverage area. Wireless devices referred to herein may correspond to a plurality of wireless devices of a particular LTE or 5G release with a given capability and in a given sector of a base station. A plurality of wireless devices may refer to a selected plurality of wireless devices, and/or a subset of total wireless devices in a coverage area. Such devices may operate, function, and/or perform based on or according to drawings and/or descriptions herein, and/or the like. There may be a plurality of base stations or a plurality of wireless devices in a coverage area that may not comply with the disclosed methods, for example, because those wireless devices and/or base stations perform based on older releases of LTE or 5G technology.

[0422] One or more features described herein may be implemented in a computer-usable data and/or computer-executable instructions, such as in one or more program modules, executed by one or more computers or other devices. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types when executed by a processor in a computer or other data processing device. The computer executable instructions may be stored on one or more computer readable media such as a hard disk, optical disk, removable storage media, solid state memory, RAM, etc. The functionality of the program modules may be combined or distributed as desired. The functionality may be implemented in whole or in part in firmware or hardware equivalents such as integrated circuits, field programmable gate arrays (FPGA), and the like. Particular data structures may be used to more effectively implement one or more features described herein, and such data structures are contemplated within the scope of computer executable instructions and computer-usable data described herein.

[0423] Many of the elements in examples may be implemented as modules. A module may be an isolatable element that performs a defined function and has a defined interface to other elements. The modules may be implemented in hardware, software in combination with hardware, firmware, wetware (i.e., hardware with a biological element) or a combination thereof, all of which may be behaviorally equivalent. For example, modules may be implemented as a software routine written in a computer language configured to be executed by a hardware machine (such as C, C++, Fortran, Java, Basic, Matlab or the like) or a modeling/simulation program such as Simulink, Stateflow, GNU Octave, or LabVIEWMathScript. Additionally or alternatively, it may be possible to implement modules using physical hardware that incorporates discrete or programmable analog, digital and/or quantum hardware. Examples of programmable hardware may comprise: computers, microcontrollers, microprocessors, application-specific integrated circuits (ASICs); field programmable gate arrays (FPGAs); and complex programmable logic devices (CPLDs). Computers, microcontrollers, and microprocessors may be programmed using languages such as assembly, C, C++ or the like. FPGAs, ASICs, and CPLDs may be programmed using hardware description languages (HDL), such as VHSIC hardware description language (VHDL) or Verilog, which may configure connections between internal hardware modules with lesser functionality on a programmable device. The above-mentioned technologies may be used in combination to achieve the result of a functional module.

[0424] A non-transitory tangible computer readable media may comprise instructions executable by one or more processors configured to cause operations of multi-carrier communications described herein. An article of manufacture may comprise a non-transitory tangible computer readable machine-accessible medium having instructions encoded thereon for enabling programmable hardware to cause a device (e.g., a wireless device, wireless communicator, a wireless device, a base station, and the like) to allow operation of multi-carrier communications described herein. The device, or one or more devices such as in a system, may include one or more processors, memory, interfaces, and/or the like. Other examples may comprise communication networks comprising devices such as base stations, wireless devices or user equipment (wireless device), servers, switches, antennas, and/or the like. A network may comprise any wireless technology, including but not limited to, cellular, wireless, WiFi, 4G, 5G, any generation of 3GPP or other cellular standard or recommendation, wireless local area networks, wireless personal area networks, wireless ad hoc networks, wireless metropolitan area networks, wireless wide area networks, global area networks, space networks, and any other network using wireless communications. Any device (e.g., a wireless device, a base station, or any other device) or combination of devices may be used to perform any combination of one or more of steps described herein, including, for example, any complementary step or steps of one or more of the above steps.

[0425] Although examples are described above, features and/or steps of those examples may be combined, divided, omitted, rearranged, revised, and/or augmented in any desired manner. Various

alterations, modifications, and improvements will readily occur to those skilled in the art. Such alterations, modifications, and improvements are intended to be part of this description, though not expressly stated herein, and are intended to be within the spirit and scope of the descriptions herein. Accordingly, the foregoing description is by way of example only, and is not limiting.

Claims

1. A method comprising: receiving, by a central unit user plane (CU-UP) node from a central unit control plane (CU-CP) node, a message comprising: a first field indicating configuration of packet duplication, and a second field indicating an initial state of packet duplication; and activating or deactivating, by the CU-UP node based on the message, packet duplication of at least one packet.
2. The method of claim 1, wherein the message further comprises a bearer configuration request for a wireless device.
3. The method of claim 1, wherein the message further comprises logical channel information, for a bearer, comprising: a first logical channel identifier of a first logical channel for the at least one packet, and a second logical channel identifier of a second logical channel for at least one duplicated version of the at least one packet.
4. The method of claim 1, further comprising: after receiving the message, sending, by the CU-UP node to the CU-CP node, at least one second message comprising uplink tunnel information, for a bearer, comprising: a first uplink tunnel endpoint identifier for a first tunnel for at least one uplink packet, and a second uplink tunnel endpoint identifier for a second tunnel for at least one duplicated uplink packet.
5. The method of claim 1, wherein the configuration of packet duplication comprises configuration of packet data convergence protocol (PDCP) packet duplication.
6. The method of claim 1, wherein the initial state is one of activated or deactivated.
7. The method of claim 1, wherein the configuration of packet duplication is for a bearer associated with a wireless device.
8. The method of claim 1, further comprising: sending, by the CU-UP node, via at least one distributed unit (DU) node, to a wireless device, and based on the message, the at least one packet.
9. A central unit user plane (CU-UP) node comprising: one or more processors; and memory storing instructions that, when executed by the one or more processors, configure the CU-UP node to: receive, from a central unit control plane (CU-CP) node, a message comprising: a first field indicating configuration of packet duplication, and a second field indicating an initial state of packet duplication; and activate or deactivate, based on the message, packet duplication of at least one packet.
10. The CU-UP of claim 9, wherein the message further comprises a bearer configuration request for a wireless device.
11. The CU-UP of claim 9, wherein the message further comprises logical channel information, for a bearer, comprising: a first logical channel identifier of a first logical channel for the at least one packet, and a second logical channel identifier of a second logical channel for at least one duplicated version of the at least one packet.
12. The CU-UP of claim 9, wherein the instructions, when executed by the one or more processors, further configure the CU-UP node to: after receiving the message, send, to the CU-CP node, at least one second message comprising uplink tunnel information, for a bearer, comprising: a first uplink tunnel endpoint identifier for a first tunnel for at least one uplink packet, and a second uplink tunnel endpoint identifier for a second tunnel for at least one duplicated uplink packet.
13. The CU-UP of claim 9, wherein the configuration of packet duplication comprises configuration of packet data convergence protocol (PDCP) packet duplication.
14. The CU-UP of claim 9, wherein the initial state is one of activated or deactivated.
15. The CU-UP of claim 9, wherein the configuration of packet duplication is for a bearer

associated with a wireless device.

- 16.** The CU-UP of claim 9, further comprising: sending, by the CU-UP node, via at least one distributed unit (DU) node, to a wireless device, and based on the message, the at least one packet.
 - 17.** A non-transitory computer-readable medium storing instructions that, when executed, cause: receiving, by a central unit user plane (CU-UP) node from a central unit control plane (CU-CP) node, a message comprising: a first field indicating configuration of packet duplication, and a second field indicating an initial state of packet duplication; and activating or deactivating, by the CU-UP node based on the message, packet duplication of at least one packet.
 - 18.** The non-transitory computer-readable medium of claim 17, wherein the message further comprises a bearer configuration request for a wireless device.
 - 19.** The non-transitory computer-readable medium of claim 17, wherein the message further comprises logical channel information, for a bearer, comprising: a first logical channel identifier of a first logical channel for the at least one packet, and a second logical channel identifier of a second logical channel for at least one duplicated version of the at least one packet.
 - 20.** The non-transitory computer-readable medium of claim 17, wherein the instructions, when executed, further cause: after receiving the message, sending, by the CU-UP node to the CU-CP node, at least one second message comprising uplink tunnel information, for a bearer, comprising: a first uplink tunnel endpoint identifier for a first tunnel for at least one uplink packet, and a second uplink tunnel endpoint identifier for a second tunnel for at least one duplicated uplink packet.
 - 21.** The non-transitory computer-readable medium of claim 17, wherein the configuration of packet duplication comprises configuration of packet data convergence protocol (PDCP) packet duplication.
 - 22.** The non-transitory computer-readable medium of claim 17, wherein the initial state is one of activated or deactivated.
 - 23.** The non-transitory computer-readable medium of claim 17, wherein the configuration of packet duplication is for a bearer associated with a wireless device.
 - 24.** The non-transitory computer-readable medium of claim 17, wherein the instructions, when executed, further cause: sending, by the CU-UP node, via at least one distributed unit (DU) node, to a wireless device, and based on the message, the at least one packet.
-