

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397637
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Mori; Hideyuki et al.

Reaction force imparting device

Abstract

An actuator is provided in an actuator housing. A lever is provided in the actuator housing, rotates by driving force from the actuator, contacts an arm that rotates together with the pedal, and is capable of imparting a reaction force to the pedal against a driver's depression force. A fixing member is formed so that a pedal housing and the actuator housing are fixed apart from each other, and are attachable to a vehicle. A positioning portion determines a contact position between an arm and the lever and between a rotation axis of the pedal and a rotation axis of the lever.

Inventors: Mori; Hideyuki (Kariya, JP), Hariu; Tetsuo (Kariya, JP), Inagaki; Noriyuki (Kariya, JP), Iwata; Rika (Kariya, JP), Kinouchi; Soichi (Kariya, JP), Kita; Takuto (Kariya, JP)

Applicant: DENSO CORPORATION (Kariya, JP)

Family ID: 1000008782115

Assignee: DENSO CORPORATION (Kariya, JP)

Appl. No.: 18/535255

Filed: December 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240100945 A1	Mar. 28, 2024

Foreign Application Priority Data

JP	2021-172618	Oct. 21, 2021
----	-------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: B60K26/02 (20060101)

U.S. Cl.:

CPC B60K26/021 (20130101);

Field of Classification Search

CPC: B60K (26/021); G05G (1/38)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0096976	12/2011	Leone	74/513	G05G 1/30
2015/0360563	12/2014	Horiuchi et al.	N/A	N/A
2016/0250924	12/2015	Kouzuma	74/89	G05G 5/03
2019/0322172	12/2018	O Meachair	N/A	B60W 30/143

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2001310648	12/2000	JP	N/A

Primary Examiner: Yabut; Daniel D

Attorney, Agent or Firm: Nixon & Vanderhye P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of International Patent Application No. PCT/JP2022/039173 filed on Oct. 20, 2022, which designated the U.S. and based on and claims the benefits of priority of Japanese Patent Application No. 2021-172618 filed on Oct. 21, 2021. The entire disclosure of all of the above applications is incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to a reaction force imparting device.

BACKGROUND

(2) Conventionally, there has been known a reaction force imparting device that imparts a reaction force against a driver's depression force to a pedal of an accelerator device that includes a pedal that is depressed by a driver.

SUMMARY

(3) An object of the present disclosure is to provide a reaction force imparting device that improves the accuracy of the reaction force applied to the pedal of the accelerator device.

- (4) The present disclosure provides a reaction force imparting device capable of imparting a reaction force against a driver's depression force to a pedal of an accelerator device, which includes a pedal that is depressed by a driver and a pedal housing that rotatably supports the pedal. The reaction force imparting device includes an actuator housing, an actuator, a lever, a fixing member, and a positioning portion.
- (5) The actuator is provided in the actuator housing. The lever is provided in the actuator housing, rotates by driving force from the actuator, contacts the pedal or an arm that rotates together with the pedal, and is capable of imparting the reaction force to the pedal against the driver's depression force.
- (6) The fixing member is formed so that the pedal housing and the actuator housing are fixed apart from each other, and are attached to the vehicle. The positioning portion determines a contact position between the pedal or the arm and the lever between the rotation axis of the pedal and the rotation axis of the lever.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objects, features and advantages of the present disclosure will become more apparent from the following detailed description made with reference to the accompanying drawings. In the drawings:
- (2) FIG. 1 is a diagram showing a reaction force imparting device of a first embodiment and an accelerator device to which the same is applied;
- (3) FIG. 2 is a diagram showing FIG. 1 viewed in a direction of an arrow II;
- (4) FIG. 3 is a diagram showing a part of the reaction force imparting device of the first embodiment;
- (5) FIG. 4 is a diagram showing a reaction force imparting device of a second embodiment and an accelerator device to which the same is applied;
- (6) FIG. 5 is a diagram showing FIG. 4 viewed from a direction of an arrow V;
- (7) FIG. 6 is a diagram showing a part of the reaction force imparting device of a third embodiment;
- (8) FIG. 7 is a diagram showing a part of the reaction force imparting device of a fourth embodiment;
- (9) FIG. 8 is a diagram showing a part of the reaction force imparting device of a fifth embodiment;
- (10) FIG. 9 is a diagram showing a part of the reaction force imparting device of the fifth embodiment;
- (11) FIG. 10 is a diagram showing a part of the reaction force imparting device of a sixth embodiment;
- (12) FIG. 11 is a diagram showing a part of the reaction force imparting device of the sixth embodiment;
- (13) FIG. 12 is a diagram showing a part of the reaction force imparting device of a seventh embodiment;
- (14) FIG. 13 is a diagram showing a part of the reaction force imparting device of an eighth embodiment; and
- (15) FIG. 14 is a diagram showing a part of the reaction force imparting device according to a ninth embodiment.

DETAILED DESCRIPTION

- (16) In an assumable example, there has been known a reaction force imparting device that imparts a reaction force against a driver's depression force to a pedal of an accelerator device that includes a pedal that is depressed by a driver. For example, the reaction force imparting device includes a

lever that comes into contact with an arm that rotates together with a pedal of an accelerator device and can impart a reaction force to the pedal in response to a driver's depression force.

(17) In the reaction force imparting device, when a distance between a contact point between an arm and a lever and a rotation axis of the arm is defined as L1, and a distance between the contact point between the arm and the lever and a rotation axis of the lever is defined as L2, a reaction force, or torque, generated by the reaction force imparting device is transmitted to the pedal by a factor of a lever ratio L1/L2. Therefore, when the position of the contact point between the arm and the lever changes, the lever ratio changes, which may affect the reaction force applied to the pedal.

(18) By the way, the reaction force imparting device disclosed in Patent Document 1 is attached to a vehicle at a position a predetermined distance away from the accelerator device. That is, the reaction force imparting device and the accelerator device are each attached to different positions on the floor of the vehicle. Therefore, when an accuracy of the mounting positions of both is low, the contact point between the arm and the lever may deviate significantly, causing a change in the lever ratio, and there is a possibility that the reaction force generated from the reaction force imparting device deviates significantly from the target value.

(19) An object of the present disclosure is to provide a reaction force imparting device that improves the accuracy of the reaction force applied to the pedal of the accelerator device.

(20) The present disclosure provides a reaction force imparting device capable of imparting a reaction force against a driver's depression force to a pedal of an accelerator device, which includes a pedal that is depressed by a driver and a pedal housing that rotatably supports the pedal. The reaction force imparting device includes an actuator housing, an actuator, a lever, a fixing member, and a positioning portion.

(21) The actuator is provided in the actuator housing. The lever is provided in the actuator housing, rotates by driving force from the actuator, contacts the pedal or an arm that rotates together with the pedal, and is capable of imparting the reaction force to the pedal against the driver's depression force.

(22) The fixing member is formed so that the pedal housing and the actuator housing are fixed apart from each other, and are attached to the vehicle. The positioning portion determines a contact position between the pedal or the arm and the lever between the rotation axis of the pedal and the rotation axis of the lever.

(23) Therefore, it is possible to improve the accuracy of the attachment positions of the pedal housing and the actuator housing to the vehicle, and it is possible to suppress misalignment of the contact point, which is the contact position between the pedal or the arm and the lever. Thereby, changes in the lever ratio can be suppressed and the reaction force generated from the reaction force imparting device can be brought closer to a target value. Therefore, the accuracy of the reaction force imparted to the pedal of the accelerator device can be improved.

(24) Hereinafter, a reaction force imparting device according to a plurality of embodiments and an accelerator device to which the same is applied will be described based on the drawings.

Components that are substantially the same in the plurality of embodiments are denoted by the same reference numerals and will not be described.

First Embodiment

(25) A reaction force imparting device according to a first embodiment and an accelerator device to which the same is applied are shown in FIGS. 1 and 2.

(26) An accelerator device **100** is mounted on a vehicle **1** and is used to control a driving state of the vehicle **1** by detecting an accelerator opening degree corresponding to a rotation angle of a pedal **120** depressed by a driver. The accelerator device **100** employs an accelerator-by-wire system and is not mechanically connected to a throttle device of the vehicle **1**. The accelerator device **100** transmits information regarding the accelerator opening degree corresponding to the rotation angle of the pedal **120** to an electronic control unit (hereinafter referred to as "ECU"), not shown. The ECU controls the throttle device based on the accelerator opening degree transmitted from the

accelerator device **100**. Thereby, a running state of the vehicle **1** is controlled.

(27) A reaction force imparting device **10** is mounted on the vehicle **1** together with the accelerator device **100**, and can impart a reaction force F_2 to the pedal **120** of the accelerator device **100** in response to a driver's depression force F_1 . By imparting a reaction force to the pedal **120** of the accelerator device **100**, the reaction force imparting device **10** can provide a driver notification such as a danger notification or a fuel efficiency improvement notification to the driver. Further, the reaction force imparting device **10** can use the pedal **120** as a footrest by regulating the rotation of the pedal **120**.

(28) The accelerator device **100** includes a pedal housing **110**, a pedal **120**, and the like. The pedal housing **110** has a housing body **111** and a housing attachment portion **112**. The housing body **111** has a space inside that can accommodate components. The housing attachment portion **112** is formed integrally with the housing body **111** so as to protrude from the housing body **111**. In the present embodiment, for example, three housing attachment portions **112** are formed (see FIG. 2). The pedal housing **110** is attached to a floor panel **2** by fixing the housing attachment portion **112** to a fixing member **60** (described later) using, for example, an attachment bolt **3**, and fixing the fixing member **60** to the floor panel **2** of the vehicle **1**.

(29) In FIG. 1, an x-axis indicates a traveling direction of the vehicle **1**, a y-axis indicates a width direction of the vehicle, and a z-axis indicates a vertically upward direction. Hereinafter, unless otherwise specified, the shape or configuration of the accelerator device **100** and the reaction force imparting device **10** in a state where they are attached to the vehicle **1** will be described. For example, the term “upward” or “upper side” means the upward or upper side of the accelerator device **100** or the reaction force imparting device **10** in a state where it is attached to the vehicle **1**. Furthermore, in the present embodiment, the floor panel **2** has the wall surface **7** parallel to a yz plane. Here, “a state where it is attached to a vehicle” includes not only a state where it is directly attached to a vehicle but also a state where it is indirectly attached to a vehicle via other members (the same applies hereinafter).

(30) One end of the pedal **120** is rotatably supported by the housing body **111** of the pedal housing **110** so as to rotate around a rotation axis Ax_1 . The other end of the pedal **120A** is provided with a pad **121** that is depressed by the driver. Inside the housing body **111**, an opening degree sensor (not shown) for the accelerator is provided on the rotation axis Ax_1 . The accelerator opening degree sensor detects the accelerator opening degree corresponding to the rotation angle of the pedal **120** rotated by the driver's depression operation, and transmits the detected accelerator opening degree to the ECU. The rotation axis Ax_1 is set to be perpendicular to the z-axis and the x-axis, and parallel to the y-axis.

(31) A pedal biasing member (not shown) is provided inside the housing body **111** of the pedal housing **110**. The pedal **120** is biased in the accelerator closing direction by a pedal biasing member. The pedal housing **110** has a stopper that restricts rotation of the pedal **120** in an accelerator closing direction and a stopper that restricts rotation of the pedal **120** in an accelerator opening direction. The pedal **120** is rotatable within a range in which it contacts both stoppers. FIG. 1 shows a state in which the pedal **120** is in contact with a stopper in the accelerator closing direction, that is, a state in which the accelerator is fully closed.

(32) As shown in FIGS. 1 and 2, the reaction force imparting device **10** includes an actuator housing **20**, an actuator **30**, a lever **40**, the fixing member **60**, and a positioning portion **700**.

(33) The actuator **30** is provided in the actuator housing **20**. The lever **40** is provided in the actuator housing **20**, rotates by driving force from the actuator **30**, contacts an arm **50** that rotates together with the pedal **120**, and is capable of imparting the reaction force to the pedal **120** against the driver's depression force.

(34) More specifically, as shown in FIG. 3, the actuator housing **20** includes a housing main body **201**, a housing extension portion **211**, a housing extension portion **212**, a housing fastening portion **221**, a housing fastening portion **222**, a housing fastening portion **223**, etc. The housing main body

201 has a space formed therein for accommodating the actuator **30** and the like.

(35) The housing extension portion **211**, the housing extension portion **212**, the housing fastening portion **221**, the housing fastening portion **222**, and the housing fastening portion **223** are formed to protrude from an outer edge of the housing main body **201**. A fastening hole **220** is formed in the housing fastening portion **221**, the housing fastening portion **222**, and the housing fastening portion **223**.

(36) The actuator housing **20** is fixed to the fixing member **60** (described later) and is attached to the floor panel **2** by fixing the fixing member **60** to the wall surface **7** of the floor panel **2** of the vehicle **1**.

(37) The actuator **30** is, for example, an electric motor, and is housed within the housing main body **201** of the actuator housing **20**. The actuator **30** can output torque as a driving force when energized. The ECU can control power supply to the actuator **30** and control the operation of the actuator **30**. A speed reducer (not shown) consisting of a plurality of gears is provided within the housing main body **201**. The speed reducer can reduce the torque of the actuator **30** and output it.

(38) One end of the lever **40** is rotatably supported by the actuator housing **20** so as to rotate around the rotation axis Ax3. One end of the lever **40** is connected to the speed reducer within the housing main body **201**. The lever **40** rotates around the rotation axis Ax3 by the driving force from the actuator **30** output from the speed reducer.

(39) In the present embodiment, the arm **50** is provided on the accelerator device **100**. The arm **50** is formed into a bending rod shape and is attached to the pedal **120** so that one end thereof is fixed to the pedal **120**. This allows the arm **50** to rotate together with the pedal **120**. Therefore, the rotation axis Ax2 of the arm **50** coincides with the rotation axis Ax1 of the pedal **120**.

(40) The other end of the lever **40**, that is, the end opposite to the rotation axis Ax3, can come into contact with the other end of the arm **50**, that is, the end opposite to the pedal **120**. The lever **40** is rotated by the driving force from the actuator **30**, contacts the other end of the arm **50** that rotates together with the pedal **120**, and imparts the reaction force F2 to the arm **50** in response to the driver's depression force F1. Therefore, the reaction force F2 can be applied to the pedal **120** via the arm **50**.

(41) The fixing member **60** is formed so that the pedal housing **110** and the actuator housing **20** can be fixed apart from each other, and can be attached to the vehicle **1**. The positioning portion **700** determines a contact position Pt1 between the arm **50** and the lever **40** and between the rotation axis Ax1 of the pedal **120** and the rotation axis Ax3 of the lever **40**.

(42) More specifically, the fixing member **60** has a fixing member main body **61** and a fixing member wall portion **62**. The fixing member main body **61** is formed into a long plate shape. The fixing member wall portion **62** is formed to extend perpendicularly from the outer edge of the fixing member main body **61** in a plate shape. A housing corresponding hole **620** is formed in the fixing member wall portion **62**. The housing corresponding hole **620** has a shape corresponding to the shape of the housing main body **201** of the actuator housing **20**, and has a size such that a predetermined gap is formed between the housing corresponding hole **620** and the housing main body **201** when the housing main body **201** is inserted into the housing corresponding hole **620**.

(43) In the pedal housing **110**, a housing attachment portion **112** is fixed to the fixing member main body **61** of the fixing member **60** by, for example, the attachment bolt **3**. Furthermore, the actuator housing **20** is fixed to the fixing member wall portion **62** of the fixing member **60** in a state where the housing main body **201** is inserted into the housing corresponding hole **620**. The fixing member **60** is attached to the floor panel **2** by fixing the fixing member main body **61** to the floor panel **2** of the vehicle **1** using, for example, the attachment bolts **3** (see FIGS. **1** and **2**). In this way, the fixing member **60** is formed so that the pedal housing **110** and the actuator housing **20** can be fixed apart from each other, and can be attached to the vehicle **1**.

(44) In the present embodiment, the positioning portion **700** is provided with a plurality of position regulating parts **710** each consisting of a boss provided on either the actuator housing **20** or the

fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(45) The position regulating part **710** regulates a relative rotation of the boss with respect to the hole, or a relative movement of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and can regulate a relative position of the actuator housing **20** with respect to the fixing member **60** at any position.

(46) More specifically, the positioning portion **700** has two position regulating parts **710** and three fastening parts **720**. One of the two position regulating parts **710** includes a boss **81** and a hole **91**. The boss **81** is formed to protrude in a cylindrical shape from the housing extension portion **211** of the actuator housing **20** (see FIG. 3). The hole **91** is formed at a predetermined distance from the housing corresponding hole **620** so as to penetrate the fixing member wall portion **62** of the fixing member **60** in a circular manner (see FIG. 1). An inner diameter of the hole **91** is slightly larger than an outer diameter of the boss **81**. The hole **91** is formed into which the boss **81** can be inserted.

(47) The other of the two position regulating parts **710** includes a boss **82** and a hole **92**. The boss **82** is formed to protrude in a cylindrical shape from the housing extension portion **212** of the actuator housing **20** (see FIG. 3). The hole **92** is formed at a predetermined distance from the housing corresponding hole **620** so as to penetrate the fixing member wall portion **62** of the fixing member **60** in a rounded rectangular shape (see FIG. 1). Here, the term “rounded rectangular shape” means a figure consisting of two parallel lines of equal length and two semicircles (the same applies hereinafter). The hole **92** is formed such that a line along a longer side direction is inclined with respect to the yz plane. An inner diameter of the hole **92** in a lateral direction is slightly larger than an outer diameter of the boss **82**. The hole **92** is formed into which the boss **82** can be inserted.

(48) The fastening part **720** is, for example, a bolt. The bolt is formed in the fixing member wall portion **62** at a position corresponding to the fastening hole **220** of the actuator housing **20** when the housing main body **201** is inserted into the housing corresponding hole **620**. The fastening part **720** can fasten the actuator housing **20** and the fixing member **60** by passing through the bolt hole and screwing into the fastening hole **220** of the actuator housing **20**.

(49) FIG. 3 shows a state of the fixing member wall portion **62** and the actuator housing **20** when the boss **81** is inserted into the hole **91** and the boss **82** is inserted into the hole **92**. Although the hole **91** allows a relative rotation of the boss **81** with respect to the hole **91**, it restricts a relative movement in the radial direction of the boss **81** with respect to the hole **91**. On the other hand, although the hole **92** allows the relative rotation of the boss **82** with respect to the hole **92** and the relative movement of the boss **82** with respect to the hole **92** in a longer side direction of the hole **92**, it restricts the relative movement of the boss **82** with respect to the hole **92** in a shorter side direction of the hole **92**. That is, the position regulating part **710** regulates the relative movement of the bosses **81** and **82** with respect to the holes **91** and **92** in a direction perpendicular to the axes of the bosses **81** and **82**.

(50) In FIG. 3, the dashed arrows indicate the directions of relative movement and relative rotation of the bosses **81**, **82** with respect to the holes **91**, **92**, which are permitted by the position regulating part **710**. The dashed-dotted arrow indicates the direction of relative movement or relative rotation of the bosses **81** and **82** with respect to the holes **91** and **92**, which is regulated by the position regulating part **710**.

(51) As shown in FIG. 3, the holes **91** and **92** restrict a movement, that is, a translation movement, of the bosses **81** and **82** in the surface direction of the xz plane. Furthermore, the regulation directions by the position regulating part **710** have at least different directions and is not determined by the same rotatable center.

(52) In the reaction force imparting device **10** of the present embodiment, when a distance L1 between a contact point between the arm **50** and the lever **40**, that is, a contact position Pt1, and the rotation axis Ax2 of the arm **50** is defined as L1, and a distance between the contact point between

the arm **50** and the lever **40** and a rotation axis Ax3 of the lever **40** is defined as L2, the reaction force F2, or torque, generated by the reaction force imparting device **10** is transmitted to the pedal **120** by a factor of a lever ratio L1/L2.

(53) The present embodiment further includes a lock portion **41** that can restrict the rotation of the pedal **120** by restricting the rotation of the lever **40**.

(54) More specifically, the lock portion **41** is provided within the housing main body **201** of the actuator housing **20**. The lock portion **41** is operated by the ECU and can restrict the rotation of the lever **40**. With this configuration, for example, when the pedal **120** is in the accelerator fully closed position, the rotation of the lever **40** is restricted by the lock portion **41** while the lever **40** is in contact with the arm **50**, thereby making it possible to reliably use the pedal **120** as the footrest.

(55) As described above, in the present embodiment, the positioning portion **700** determines the contact position Pt1 between the arm **50** and the lever **40** between the rotation axis Ax1 of the pedal **120** and the rotation axis Ax3 of the lever **40**.

(56) Therefore, it is possible to improve the accuracy of the attachment positions of the pedal housing **110** and the actuator housing **20** to the vehicle **1**, and it is possible to suppress misalignment of the contact point Pt1, which is the contact position between the arm **50** and the lever **40**. Thereby, changes in the lever ratio can be suppressed and the reaction force F2 generated from the reaction force imparting device **10** can be brought closer to a target value. Therefore, the accuracy of the reaction force imparted to the pedal **120** of the accelerator device **100** can be improved.

(57) Furthermore, in the present embodiment, the positioning portion **700** is provided with a plurality of position regulating parts **710** each consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(58) The position regulating part **710** regulates a relative rotation of the boss with respect to the hole, or a relative movement of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and can regulate a relative position of the actuator housing **20** with respect to the fixing member **60** at any position.

(59) In the present embodiment, the positioning portion **700** has a plurality of position regulating parts **710** spaced apart by a predetermined distance, so that the contact position Pt1 between the arm **50** and the lever **40** can be determined more accurately. Therefore, the accuracy of the reaction force applied to the pedal **120** of the accelerator device **100** can be further improved.

(60) The present embodiment further includes a lock portion **41** that can restrict the rotation of the pedal **120** by restricting the rotation of the lever **40**. By regulating the rotation of the lever **40** with the lock portion **41** while the lever **40** is in contact with the arm **50**, the pedal **120** can be reliably used as a footrest. As a result, the reaction force imparting device **10** can have a function of reliably using the pedal **120** as the footrest in addition to the function of applying a reaction force to the pedal **120**, and can appropriately respond to requests for variations in the reaction force imparting device **10**.

Second Embodiment

(61) The reaction force imparting device and the accelerator device according to a second embodiment are shown in FIGS. 4 and 5. The second embodiment differs from the first embodiment in the configurations of the accelerator device **100** and the fixing member **60**, etc.

(62) In the present embodiment, the accelerator device **100** includes a pedal housing **130**, a pedal **140**, and the like. The pedal housing **130** has a housing body **131** and a housing attachment portion **132**. The housing body **131** is formed to be able to accommodate or install components. The housing attachment portion **132** is formed integrally with the housing body **131** so as to protrude from the housing body **131**. The pedal housing **130** is attached to the floor panel **2** by fixing the housing attachment portion **132** to the fixing member **60**, and fixing the fixing member **60** to the

floor panel **2** of the vehicle **1**.

(63) In the present embodiment, the floor panel **2** has the wall surface **7** parallel to the yz plane and a wall surface **8** inclined with respect to the wall surface **7**.

(64) The pedal **140** is rotatably supported by the housing body **131** of the pedal housing **130** so as to rotate around the rotation axis Ax1. The pedal **140** is provided with a substantially rectangular plate-shaped pad **141** that is depressed by the driver. The housing body **131** is provided with an opening degree sensor of the accelerator (not shown). The accelerator opening degree sensor detects the accelerator opening degree corresponding to the rotation angle of the pedal **140** rotated by the driver's depression operation, and transmits the detected accelerator opening degree to the ECU. The rotation axis Ax1 is set to be perpendicular to the z-axis and the x-axis, and parallel to the y-axis.

(65) A pedal biasing member (not shown) is provided inside the housing body **131** of the pedal housing **130**. The pedal **140** is biased in the accelerator closing direction by a pedal biasing member. The pedal housing **130** has a stopper that restricts rotation of the pedal **140** in an accelerator closing direction and a stopper that restricts rotation of the pedal **120** in an accelerator opening direction. The pedal **140** is rotatable within a range in which it contacts both stoppers. FIG. **4** shows a state in which the pedal **140** is in contact with a stopper in the accelerator closing direction, that is, a state in which the accelerator is fully closed.

(66) In the present embodiment, the fixing member main body **61** of the fixing member **60** is formed into a bent plate shape so as to correspond to the shapes of the wall surfaces **7** and **8** of the floor panel **2**. The configuration of the fixing member wall portion **62** and the configuration of the positioning portion **700** are the same as those in the first embodiment.

(67) In the pedal housing **130**, a housing attachment portion **132** is fixed to a lower part of a fixing member main body **61** of the fixing member **60**. Furthermore, like the first embodiment, the actuator housing **20** is fixed to the fixing member wall portion **62** of the fixing member **60** in a state where the housing main body **201** is inserted into the housing corresponding hole **620**. The fixing member **60** is attached to the wall surfaces **7** and **8** of the floor panel **2** by fixing the fixing member main body **61** to the floor panel **2** of the vehicle **1** using, for example, the attachment bolts **3** (see FIGS. **4** and **5**). In this way, the fixing member **60** is formed so that the pedal housing **130** and the actuator housing **20** can be fixed apart from each other, and can be attached to the vehicle **1**.

(68) In the present embodiment, the arm **50** is not provided in the accelerator device **100**. The end of the lever **40** on the side opposite to the rotation axis Ax3 can come into contact with the end of the pad **141** of the pedal **140** on the side opposite to the rotation axis Ax1. The lever **40** is rotated by the driving force from the actuator **30**, comes into contact with the pad **141** of the pedal **140**, and can impart the reaction force F2 to the pedal **140** in response to the depression force F1 by the driver.

(69) In the present embodiment, the positioning portion **700** determines a contact position Pt1 between the pedal **140** and the lever **40** between the rotation axis Ax1 of the pedal **140** and the rotation axis Ax3 of the lever **40**.

(70) As explained above, the present embodiment includes the positioning portion **700** similar to that of the first embodiment. Therefore, it is possible to improve the accuracy of the attachment positions of the pedal housing **130** and the actuator housing **20** to the vehicle **1**, and it is possible to suppress misalignment of the contact point Pt1, which is the contact position between the pedal **140** and the lever **40**. Therefore, like the first embodiment, the accuracy of the reaction force imparted to the pedal **140** of the accelerator device **100** can be improved.

Third Embodiment

(71) A part of the reaction force imparting device according to the third embodiment is shown in FIG. **6**. The third embodiment differs from the first embodiment in the configuration of a position regulating part **710**.

(72) In the present embodiment, the boss **82** is formed such that the cross-sectional shape taken

along a plane perpendicular to the axis of the boss **82** has a rounded rectangular shape. The boss **82** is formed such that a line along the longer side direction in a cross section of the boss **82** is inclined with respect to the yz plane. A line along the longer side direction of the hole **92** substantially coincides with a line along the longer side direction in the cross section of the boss **82**. The inner diameter of the hole **92** in the shorter side direction is slightly larger than the outer diameter in the shorter side direction in the cross section of the boss **82**. The inner diameter of the hole **92** in the longer side direction is larger than the outer diameter in the longer side direction in the cross section of the boss **82**. The hole **92** is formed into which the boss **82** can be inserted.

(73) FIG. **6** shows a state of the fixing member wall portion **62** and the actuator housing **20** when the boss **81** is inserted into the hole **91** and the boss **82** is inserted into the hole **92**. Although the hole **91** allows a relative rotation of the boss **81** with respect to the hole **91**, it restricts a relative movement in the radial direction of the boss **81** with respect to the hole **91**. On the other hand, although the hole **92** allows the relative movement of the hole **92** of the boss **82** with respect to the hole **92** in the longer side direction, it restricts the relative movement of the hole **92** of the boss **82** with respect to the hole **92** in the shorter side direction, and the relative rotation of the boss **82** with respect to the hole **92**. That is, the position regulating part **710** regulates the relative movement of the bosses **81** and **82** with respect to the holes **91** and **92** in the direction perpendicular to the axes of the bosses **81** and **82**, and the relative rotation of the boss **82** with respect to the hole **92**.

(74) In FIG. **6**, the dashed arrows indicate the directions of relative movement and relative rotation of the bosses **81**, **82** with respect to the holes **91**, **92**, which are permitted by the position regulating part **710**. The dashed-dotted arrow indicates the direction of relative movement or relative rotation of the bosses **81** and **82** with respect to the holes **91** and **92**, which is regulated by the position regulating part **710**.

(75) As shown in FIG. **6**, the holes **91** and **92** restrict a movement, that is, a translation movement, of the bosses **81** and **82** in the surface direction of the xz plane. Further, the hole **92** restricts the rotational position of the boss **82**. Furthermore, the regulation directions by the position regulating part **710** have at least different directions and is not determined by the same rotatable center.

Fourth Embodiment

(76) A part of the reaction force imparting device according to a fourth embodiment is shown in FIG. **7**. The fourth embodiment differs from the third embodiment in the configuration of a position regulating part **710**.

(77) In the present embodiment, the hole **91** is formed to penetrate the fixing member wall portion **62** of the fixing member **60** in the rounded rectangular shape. The hole **91** is formed such that a line along a longer side direction is parallel to the x-axis. The boss **81** is formed such that the cross-sectional shape taken along a plane perpendicular to the axis of the boss **81** has the rounded rectangular shape. The boss **81** is formed such that a line along the longer side direction of the cross section of the boss **81** is parallel to the x-axis. A line along the longer side direction of the hole **91** substantially coincides with a line along the longer side direction in the cross section of the boss **81**. The inner diameter of the hole **91** in the shorter side direction is slightly larger than the outer diameter in the shorter side direction in the cross section of the boss **81**. The inner diameter of the hole **91** in the longer side direction is larger than the outer diameter in the longer side direction in the cross section of the boss **81**. The hole **91** is formed into which the boss **81** can be inserted.

(78) The hole **92** is formed such that a line along the longer side direction is parallel to the z-axis. The boss **82** is formed such that a line along the longer side direction of the cross section of the boss **82** is parallel to the z-axis.

(79) FIG. **7** shows a state of the fixing member wall portion **62** and the actuator housing **20** when the boss **81** is inserted into the hole **91** and the boss **82** is inserted into the hole **92**. The hole **91** allows the relative movement of the boss **81** with respect to the hole **91** in the longer side direction of the hole **91**, but restricts the relative movement of the boss **81** with respect to the hole **91** in the shorter side direction of the hole **91** and the relative rotation of the boss **81** with respect to the hole

91. On the other hand, the hole 92 allows the relative movement of the boss 82 with respect to the hole 92 in the longer side direction of the hole 92, but restricts the relative movement of the boss 82 with respect to the hole 92 in the shorter side direction of the hole 92 and the relative rotation of the boss 82 with respect to the hole 92. That is, the position regulating part 710 regulates the relative movement of the bosses 81 and 82 with respect to the holes 91 and 92 in the direction perpendicular to the axes of the bosses 81 and 82, and the relative rotation of the bosses 81 and 82 with respect to the holes 91 and 92.

(80) In FIG. 7, the dashed arrows indicate the directions of relative movement and relative rotation of the bosses 81, 82 with respect to the holes 91, 92, which are permitted by the position regulating part 710. The dashed-dotted arrow indicates the direction of relative movement or relative rotation of the bosses 81 and 82 with respect to the holes 91 and 92, which is regulated by the position regulating part 710.

(81) As shown in FIG. 7, the holes 91 and 92 restrict a movement, that is, a translation movement, of the bosses 81 and 82 in the surface direction of the xz plane. Further, the holes 91 and 92 restricts the rotational position of the bosses 81 and 82. Furthermore, the regulation directions by the position regulating part 710 have at least different directions and is not determined by the same rotatable center.

Fifth Embodiment

(82) A part of the reaction force imparting device according to a fifth embodiment is shown in FIGS. 8 and 9. The fifth embodiment differs from the fourth embodiment in the configuration of the positioning portion 700.

(83) Furthermore, in the present embodiment, the positioning portion 700 is provided with one position regulating part 710 each consisting of a boss provided on either the actuator housing 20 or the fixing member 60 and a hole provided on the other of the actuator housing 20 or the fixing member 60 so that the boss can be inserted therein, and also has at least one fastening part 720 that fastens the actuator housing 20 and the fixing member 60.

(84) The position regulating part 710 regulates the relative rotation of the boss with respect to the hole and the relative movement of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and can regulate a relative position of the actuator housing 20 with respect to the fixing member 60 at any position.

(85) More specifically, the positioning portion 700 has one position regulating part 710 and three fastening parts 720. The position regulating part 710 includes a boss 81 and a hole 91. The boss 81 is formed to protrude from the housing extension portion 211 of the actuator housing 20.

(86) In the present embodiment, the hole 91 is formed to penetrate the fixing member wall portion 62 of the fixing member 60 in the rounded rectangular shape. The hole 91 is formed such that a line along a longer side direction is parallel to the x-axis. The boss 81 is formed such that the cross-sectional shape taken along a plane perpendicular to the axis of the boss 81 has the rounded rectangular shape. The boss 81 is formed such that a line along the longer side direction of the cross section of the boss 81 is parallel to the x-axis. A line along the longer side direction of the hole 91 substantially coincides with a line along the longer side direction in the cross section of the boss 81. The inner diameter of the hole 91 in the shorter side direction is slightly larger than the outer diameter in the shorter side direction in the cross section of the boss 81. The inner diameter of the hole 91 in the longer side direction is slightly larger than the outer diameter in the longer side direction in the cross section of the boss 81. The hole 91 is formed into which the boss 81 can be inserted.

(87) In the present embodiment, the actuator housing 20 does not have the housing extension portion 212.

(88) FIG. 9 shows the state of the fixing member wall portion 62 and the actuator housing 20 when the boss 81 is inserted into the hole 91. The hole 91 restricts the relative movement of the hole 91 of the boss 81 with respect to the hole 91 in the longer side direction, the relative movement of the

hole **91** of the boss **81** with respect to the hole **91** in the shorter side direction, and the relative movement of the boss **81** with respect to the hole **91**. That is, the position regulating part **710** restricts the relative movement of the boss **81** with respect to the hole **91** in the direction perpendicular to the axes of the boss **81**, and restricts the relative rotation of the boss **81** with respect to the hole **91**.

(89) As shown in FIG. **9**, the dashed-dotted arrow indicates the direction of relative movement or relative rotation of the boss **81** with respect to the hole **91**, which is regulated by the position regulating part **710**.

(90) As described above, in the present embodiment, the positioning portion **700** is provided with one position regulating part **710** each consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(91) The position regulating part **710** regulates the relative rotation of the boss with respect to the hole and the relative movement of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and can regulate a relative position of the actuator housing **20** with respect to the fixing member **60** at any position.

(92) In the present embodiment, the position of the reaction force imparting device **10** on the fixing member **60** can be determined with a relatively simple configuration, and the contact position Pt1 between the arm **50** and the lever **40** can be determined with high accuracy.

Sixth Embodiment

(93) A part of the reaction force imparting device according to a sixth embodiment is shown in FIGS. **10** and **11**. The sixth embodiment differs from the first embodiment in the configuration of the positioning portion **700**.

(94) In the present embodiment, the positioning portion **700** has at least one position adjustment part **730** each consisting of a boss provided on either the actuator housing **20** or the fixing member **60** or a hole provided on the other of the actuator housing **20** and the fixing member **60** so that the boss can be inserted therein, and has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(95) The position adjustment part **730** adjusts the relative rotational position of the boss with respect to the hole, or the relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss, and adjusts the relative position of the actuator housing **20** with respect to the fixing member **60**.

(96) More specifically, the positioning portion **700** has two position adjustment parts **730** and three fastening parts **720**. One of the two position adjustment parts **730** is made up of a boss **81** and a hole **91**. The boss **81** is formed to protrude in a cylindrical shape from the housing extension portion **211** of the actuator housing **20** (see FIG. **11**). The hole **91** is formed at a predetermined distance from the housing corresponding hole **620** so as to penetrate the fixing member wall portion **62** of the fixing member **60** in a circular manner (see FIG. **10**). An inner diameter of the hole **91** is slightly larger than an outer diameter of the boss **81**. The hole **91** is formed into which the boss **81** can be inserted.

(97) The other of the two position adjustment parts **730** is made up of a boss **82** and a hole **92**. The boss **82** is formed to protrude in a cylindrical shape from the housing extension portion **212** of the actuator housing **20** (see FIG. **11**). The hole **92** is formed at a predetermined distance from the housing corresponding hole **620** so as to penetrate the fixing member wall portion **62** of the fixing member **60** in an arc shape (see FIG. **10**). The hole **92** is formed so that the center of the arc along the hole **92** coincides with the center of the boss **81**. The size of the arc of the hole **92** in the radial direction is slightly larger than the outer diameter of the boss **82**. The hole **92** is formed into which the boss **82** can be inserted.

(98) FIG. **11** shows a state of the fixing member wall portion **62** and the actuator housing **20** when

the boss **81** is inserted into the hole **91** and the boss **82** is inserted into the hole **92**. Although the hole **91** allows a relative rotation of the boss **81** with respect to the hole **91**, it restricts a relative movement in the radial direction of the boss **81** with respect to the hole **91**. On the other hand, although the hole **92** allows the relative movement (rotation) of the boss **82** with respect to the hole **92** with the center of the boss **81** as the center of rotation and restricts the relative movement of the boss **82** with respect to the hole **92** in the radial direction of circular arc of the hole **92**. That is, the position adjustment part **730** is configured to be able to adjust the relative rotational positions of the bosses **81** and **82** with respect to the holes **91** and **92**. In the present embodiment, the relative position of the actuator housing **20** with respect to the fixing member **60** can be adjusted to any position by rotating the actuator housing **20** relative to the fixing member wall portion **62** with the center of the boss **81** as the rotation center.

(99) In FIG. **11**, the dashed arrows indicate the directions of relative movement and relative rotation of the bosses **81**, **82** with respect to the holes **91**, **92**, which are permitted by the position adjustment part **730**. The dashed-dotted arrow indicates the direction of relative movement or relative rotation of the bosses **81** and **82** with respect to the holes **91** and **92**, which is regulated by the position adjustment part **730**.

(100) As described above, in the present embodiment, the positioning portion **700** is provided with at least one position adjustment part **730** each consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(101) The position adjustment part **730** adjusts the relative rotational position of the boss with respect to the hole, or the relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss, and adjusts the relative position of the actuator housing **20** with respect to the fixing member **60**.

(102) In the present embodiment, the actuator housing **20** can be fixed to the fixing member **60** while adjusting the relative rotational position of the actuator housing **20** with respect to the fixing member **60**. Therefore, the contact position Pt1 between the arm **50** and the lever **40** can be determined with higher accuracy. Therefore, the accuracy of the reaction force applied to the pedal **120** of the accelerator device **100** can be further improved.

Seventh Embodiment

(103) A part of the reaction force imparting device according to a seventh embodiment is shown in FIG. **12**. The seventh embodiment differs from the sixth embodiment in the configuration of the positioning portion **700**.

(104) Furthermore, in the present embodiment, the positioning portion **700** is provided with one position adjustment part **730** consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(105) The position adjustment part **730** adjusts the relative rotational position of the boss with respect to the hole, or the relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss, and adjusts the relative position of the actuator housing **20** with respect to the fixing member **60**.

(106) More specifically, the positioning portion **700** has one position adjustment part **730** and three fastening parts **720**. The position adjustment part **730** includes a boss **82** and a hole **92**. The boss **82** is formed to protrude from the housing extension portion **212** of the actuator housing **20**.

(107) In the present embodiment, the hole **92** is formed to penetrate the fixing member wall portion **62** of the fixing member **60** in an arc shape. The hole **92** is formed so that the center of the arc along the hole **92** coincides with the rotation axis Ax3 of the lever **40**. The boss **82** is formed so that a cross-sectional shape taken along a plane perpendicular to the axis of the boss **82** is arcuate. The

size of the circular arc of the hole **92** in the radial direction is slightly larger than the size of the circular arc of the boss **82** in the radial direction. The size of the circular arc of the hole **92** in the circumferential direction is larger than the size of the circular arc of the boss **82** in the circumferential direction. The hole **92** is formed into which the boss **82** can be inserted.

(108) In the present embodiment, the actuator housing **20** does not have the housing extension portion **211**.

(109) FIG. **12** shows the state of the fixing member wall portion **62** and the actuator housing **20** when the boss **82** is inserted into the hole **92**. Although the hole **92** allows the relative movement (rotation) of the boss **82** with respect to the hole **92** around the rotation axis Ax3 of the lever **40**, the hole **92** restricts the relative movement of the boss **82** with respect to the hole **92** in the radial direction of the circular arc of the hole **92** and the relative rotation of the boss **82** with respect to the hole **92**. In the present embodiment, the relative position of the actuator housing **20** with respect to the fixing member **60** can be adjusted to any position by rotating the actuator housing **20** relative to the fixing member wall portion **62** with the rotation axis Ax3 of the lever **40** as the rotation center.

(110) In FIG. **12**, the dashed arrows indicate the directions of relative movement and relative rotation of the boss **82** with respect to the hole **92**, which are permitted by the position adjustment part **730**. The dashed-dotted arrow indicates the direction of relative movement or relative rotation of the boss **82** with respect to the holes **92**, which is regulated by the position adjustment part **730**.

(111) As described above, in the present embodiment, the positioning portion **700** is provided with one position adjustment part **730** consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(112) Therefore, like the sixth embodiment, the actuator housing **20** can be fixed to the fixing member **60** while adjusting the relative rotational position of the actuator housing **20** with respect to the fixing member **60**. Therefore, the accuracy of the reaction force applied to the pedal **120** of the accelerator device **100** can be further improved.

Eighth Embodiment

(113) A part of the reaction force imparting device according to an eighth embodiment is shown in FIG. **13**. The eighth embodiment differs from the seventh embodiment in the configuration of the positioning portion **700**.

(114) Furthermore, in the present embodiment, the positioning portion **700** is provided with one position adjustment part **730** consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(115) The position adjustment part **730** restricts the relative rotation of the boss with respect to the hole and adjusts the relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss and the relative position of the actuator housing **20** with respect to the fixing member **60**.

(116) More specifically, the positioning portion **700** has one position adjustment part **730** and three fastening parts **720**. The position adjustment part **730** includes a boss **81** and a hole **91**. The boss **81** is formed to protrude from the housing extension portion **211** of the actuator housing **20**.

(117) In the present embodiment, the hole **91** is formed to penetrate the fixing member wall portion **62** of the fixing member **60** in the rounded rectangular shape. The hole **91** is formed such that a line along a longer side direction is parallel to the x-axis. The boss **81** is formed such that the cross-sectional shape taken along a plane perpendicular to the axis of the boss **81** has the rounded rectangular shape. The boss **81** is formed such that a line along the longer side direction of the cross section of the boss **81** is parallel to the x-axis. A line along the longer side direction of the hole **91** substantially coincides with a line along the longer side direction in the cross section of the

boss **81**. The inner diameter of the hole **91** in the shorter side direction is slightly larger than the outer diameter in the shorter side direction in the cross section of the boss **81**. The inner diameter of the hole **91** in the longer side direction is larger than the outer diameter in the longer side direction in the cross section of the boss **81**. The hole **91** is formed into which the boss **81** can be inserted. (118) FIG. **13** shows the state of the fixing member wall portion **62** and the actuator housing **20** when the boss **81** is inserted into the hole **91**. The hole **91** allows the relative movement of the boss **81** with respect to the hole **91** in the longer side direction of the hole **91**, but restricts the relative movement of the boss **81** with respect to the hole **91** in the shorter side direction of the hole **91** and the relative rotation of the boss **81** with respect to the hole **91**. In the present embodiment, the relative position of the actuator housing **20** with respect to the fixing member **60** can be adjusted to any position by moving the actuator housing **20** relative to the fixing member wall portion **62** in the longer side direction of the hole **91**.

(119) In FIG. **13**, the dashed arrows indicate the directions of relative movement and relative rotation of the boss **81** with respect to the hole **91**, which are permitted by the position adjustment part **730**. The dashed-dotted arrow indicates the direction of relative movement or relative rotation of the boss **81** with respect to the holes **91**, which is regulated by the position adjustment part **730**.

(120) As described above, in the present embodiment, the positioning portion **700** is provided with one position adjustment part **730** consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(121) The position adjustment part **730** restricts the relative rotation of the boss with respect to the hole and adjusts the relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss and the relative position of the actuator housing **20** with respect to the fixing member **60**.

(122) In the present embodiment, the actuator housing **20** can be fixed to the fixing member **60** while adjusting the relative position of the actuator housing **20** with respect to the fixing member **60** with a relatively simple configuration. Therefore, the contact position Pt1 between the arm **50** and the lever **40** can be determined with higher accuracy. Therefore, the accuracy of the reaction force applied to the pedal **120** of the accelerator device **100** can be further improved.

Ninth Embodiment

(123) A part of the reaction force imparting device according to a ninth embodiment is shown in FIG. **14**. The ninth embodiment differs from the eighth embodiment in the configuration of the positioning portion **700**.

(124) Furthermore, in the present embodiment, the positioning portion **700** is provided with a plurality of position adjustment parts **730** each consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(125) The position adjustment part **730** adjusts the relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss, and adjusts the relative position of the actuator housing **20** with respect to the fixing member **60**.

(126) More specifically, the positioning portion **700** has two position adjustment parts **730** and three fastening parts **720**. One of the two position adjustment parts **730** is made up of a boss **81** and a hole **91**. The boss **81** is formed to protrude in a cylindrical shape from the housing extension portion **211** of the actuator housing **20**. The hole **91** is formed to penetrate the fixing member wall portion **62** of the fixing member **60** in the rounded rectangular shape. The hole **91** is formed such that a line along a longer side direction is parallel to the x-axis. An inner diameter of the hole **91** in a lateral direction is slightly larger than an outer diameter of the boss **81**. The hole **91** is formed into which the boss **81** can be inserted.

(127) The other of the two position adjustment parts **730** is made up of a boss **82** and a hole **92**. The boss **82** is formed to protrude in a cylindrical shape from the housing extension portion **212** of the actuator housing **20**. The hole **92** is formed to penetrate the fixing member wall portion **62** of the fixing member **60** in the rounded rectangular shape. The hole **92** is formed such that a line along a longer side direction is parallel to the x-axis. An inner diameter of the hole **92** in a lateral direction is slightly larger than an outer diameter of the boss **82**. The hole **92** is formed into which the boss **82** can be inserted.

(128) FIG. **14** shows a state of the fixing member wall portion **62** and the actuator housing **20** when the boss **81** is inserted into the hole **91** and the boss **82** is inserted into the hole **92**. The hole **91** allows the relative rotation of the boss **81** with respect to the hole **91** and the relative movement of the boss **81** with respect to the hole **91** in the longer side direction of the hole **91**, but restricts the relative movement of the boss **81** with respect to the hole **91** in the shorter side direction of the hole **91**. On the other hand, although the hole **92** allows the relative rotation of the boss **82** with respect to the hole **92** and the relative movement of the boss **82** with respect to the hole **92** in the longer side direction of the hole **92**, it restricts the relative movement of the boss **82** with respect to the hole **92** in a shorter side direction of the hole **92**. That is, the position adjustment part **730** is configured to be able to adjust the relative positions of the bosses **81** and **82** with respect to the holes **91** and **92** in a direction perpendicular to the axes of the bosses **81** and **82**. In the present embodiment, the relative position of the actuator housing **20** with respect to the fixing member **60** can be adjusted to any position by moving the actuator housing **20** relative to the fixing member wall portion **62** in the longer side direction of the holes **91** and **92**.

(129) As described above, in the present embodiment, the positioning portion **700** is provided with a plurality of position adjustment parts **730** each consisting of a boss provided on either the actuator housing **20** or the fixing member **60** and a hole provided on the other of the actuator housing **20** or the fixing member **60** so that the boss can be inserted therein, and also has at least one fastening part **720** that fastens the actuator housing **20** and the fixing member **60**.

(130) The position adjustment part **730** adjusts the relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss, and adjusts the relative position of the actuator housing **20** with respect to the fixing member **60**.

(131) In the present embodiment, the positioning portion **700** has a plurality of position adjustment parts **730** spaced apart by a predetermined distance, so that the contact position Pt1 between the arm **50** and the lever **40** can be determined more accurately. Therefore, the accuracy of the reaction force applied to the pedal **120** of the accelerator device **100** can be further improved.

Other Embodiments

(132) The plurality of embodiments described above may be implemented in combination unless there is a structural impediment factor. For example, the accelerator device of the second embodiment and the reaction force imparting device of the third to ninth embodiments may be combined.

(133) Furthermore, in the above-described embodiments, an example is shown in which the boss is provided in the actuator housing, which is either the actuator housing or the fixing member, and the hole is provided in the fixing member, which is the other of the actuator housing or the fixing member. On the other hand, in other embodiments, either the actuator housing or the fixing member may be provided with the boss, and the other of the actuator housing or the fixing member may be provided with the hole.

(134) In other embodiments, the positioning portions is not limited to having one or two position regulating parts, but may have three or more. Further, the positioning portion is not limited to having one or two position adjustment parts, but may have three or more.

(135) Moreover, in the above-described embodiments, an example was shown in which the reaction force imparting device includes the lock portion that can restrict the rotation of the pedal by restricting the rotation of the lever. On the other hand, in other embodiments, the reaction force

imparting device may not include the lock portion.

(136) In other embodiments, the wall surface of the floor panel of the vehicle to which the reaction force imparting device and the accelerator device are attached may not be formed parallel to the yz plane. That is, the wall surface of the floor panel may be formed at any angle with respect to the vehicle.

(137) Thus, the present disclosure is not limited to the above embodiments but can be implemented in various forms without departing from the scope thereof.

(138) The present disclosure has been described based on the embodiments. However, the present disclosure is not limited to the embodiments and structures. The present disclosure also encompasses various modifications and variations within the scope of equivalents. Furthermore, various combination and formation, and other combination and formation including one, more than one or less than one element may be made in the present disclosure.

Claims

1. An accelerator operation mechanism attached to a vehicle, comprising: an accelerator device including a pedal that is depressed by a driver and a pedal housing that rotatably supports the pedal; a reaction force imparting device configured to impart a reaction force to the pedal against a depression force of the driver; and a fixing member to which the accelerator device and the reaction force imparting device are fixed at a distance; wherein the reaction force imparting device includes: an actuator housing; an actuator provided in the actuator housing; a lever that is provided in the actuator housing, rotates by a driving force from the actuator, contacts the pedal or an arm rotating together with the pedal, and imparts the reaction force to the pedal against the depression force of the driver; and a positioning portion that determines a contact position between the pedal or the arm and the lever and between a rotation axis of the pedal and a rotation axis of the lever; the positioning portion is provided with a position regulating part that regulates a relative position of the actuator housing with respect to the fixing member and a fastening part that fastens the actuator housing and the fixing member, the position regulating part and the fastening part are located on the fixing member, the pedal housing is fixed to the fixing member by a mounting member, and the accelerator operation mechanism is attached to the vehicle by mounting the fixing member to the vehicle.

2. The accelerator operation mechanism according to claim 1, wherein the position regulating part consists of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and the position regulating part regulates a relative rotation of the boss with respect to the hole and a relative movement of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and regulates a relative position of the actuator housing with respect to the fixing member.

3. The accelerator operation mechanism according to claim 1, wherein the positioning portion is provided with a plurality of position regulating parts each consisting of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and each position regulating part regulates a relative rotation of the boss with respect to the hole or a relative movement of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and regulates a relative position of the actuator housing with respect to the fixing member.

4. The accelerator operation mechanism according to claim 1, wherein the positioning portion is provided with at least one position adjustment part each consisting of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and each position adjustment part adjusts a relative rotation position of the boss with respect to the hole or a relative position of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and adjusts a relative position

of the actuator housing with respect to the fixing member.

5. The accelerator operation mechanism according to claim 1, wherein the positioning portion is provided with one position adjustment part consisting of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and the position adjustment part restricts a relative rotation of the boss with respect to the hole and adjusts a relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss and a relative position of the actuator housing with respect to the fixing member.

6. The accelerator operation mechanism according to claim 1, wherein the positioning portion is provided with a plurality of position adjustment parts each consisting of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and at least one fastening part that fastens the actuator housing and the fixing member, and each position adjustment part adjusts a relative position of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and adjusts a relative position of the actuator housing with respect to the fixing member.

7. The accelerator operation mechanism according to claim 1, further comprising, a lock portion capable of regulating rotation of the pedal by regulating rotation of the lever.

8. A reaction force imparting device for imparting a reaction force against a depression force of a driver to a pedal of an accelerator device including the pedal to be depressed by the driver and a pedal housing rotatably supporting the pedal, the reaction force imparting device, comprising: an actuator housing; an actuator provided in the actuator housing; a lever that is provided in the actuator housing, rotates by a driving force from the actuator, contacts the pedal or an arm rotating together with the pedal, and imparts the reaction force to the pedal against the depression force of the driver; a fixing member that is formed to fix the pedal housing and the actuator housing apart from each other, and that is attachable to a vehicle; and a positioning portion that determines a contact position between the pedal or the arm and the lever and between a rotation axis of the pedal and a rotation axis of the lever; wherein the positioning portion is provided with at least one position adjustment part each consisting of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and at least one fastening part that fastens the actuator housing and the fixing member, and each position adjustment part adjusts a relative rotation position of the boss with respect to the hole or a relative position of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and adjusts a relative position of the actuator housing with respect to the fixing member.

9. A reaction force imparting device for imparting a reaction force against a depression force of a driver to a pedal of an accelerator device including the pedal to be depressed by the driver and a pedal housing rotatably supporting the pedal, the reaction force imparting device, comprising: an actuator housing; an actuator provided in the actuator housing; a lever that is provided in the actuator housing, rotates by a driving force from the actuator, contacts the pedal or an arm rotating together with the pedal, and imparts the reaction force to the pedal against the depression force of the driver; a fixing member that is formed to fix the pedal housing and the actuator housing apart from each other, and that is attachable to a vehicle; and a positioning portion that determines a contact position between the pedal or the arm and the lever and between a rotation axis of the pedal and a rotation axis of the lever; wherein the positioning portion is provided with one position adjustment part consisting of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and at least one fastening part that fastens the actuator housing and the fixing member, and the position adjustment part restricts a relative rotation of the boss with respect to the hole and adjusts a relative position of the boss with respect to the hole in the direction perpendicular to the axis of the boss and a relative position of the actuator housing with respect to

the fixing member.

10. A reaction force imparting device for imparting a reaction force against a depression force of a driver to a pedal of an accelerator device including the pedal to be depressed by the driver and a pedal housing rotatably supporting the pedal, the reaction force imparting device, comprising: an actuator housing; an actuator provided in the actuator housing; a lever that is provided in the actuator housing, rotates by a driving force from the actuator, contacts the pedal or an arm rotating together with the pedal, and imparts the reaction force to the pedal against the depression force of the driver; a fixing member that is formed to fix the pedal housing and the actuator housing apart from each other, and that is attachable to a vehicle; and a positioning portion that determines a contact position between the pedal or the arm and the lever and between a rotation axis of the pedal and a rotation axis of the lever; wherein the positioning portion is provided with a plurality of position adjustment parts each consisting of a boss provided on either the actuator housing or the fixing member and a hole provided on the other of the actuator housing or the fixing member so that the boss is inserted therein, and at least one fastening part that fastens the actuator housing and the fixing member, and each position adjustment part adjusts a relative position of the boss with respect to the hole in a direction perpendicular to an axis of the boss, and adjusts a relative position of the actuator housing with respect to the fixing member.
