

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397921
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Cazeaux; Laurent et al.

Internal fixed structure for an aircraft nacelle

Abstract

An internal fixed structure for a nacelle, comprising end panels, an intermediate panel in the form of a half-cylinder between the end panels, splice plates between the intermediate panel and each end panel, wherein each splice plate is made up of a skin with an inner face fastened to the panels and at least one indentation protruding with respect to an outer face, and a pad fastened to each fastening surface of an indentation, wherein each pad of the upper splice plate bears against a surface of an engine pylon, and wherein each pad of the lower splice plate bears against a pad of a lower splice plate of another internal fixed structure.

Inventors: Cazeaux; Laurent (Toulouse, FR), Caliman; Laurent (Toulouse, FR), Charton; Nicolas (Toulouse, FR)

Applicant: Airbus Operations SAS (Toulouse, FR)

Family ID: 1000008782174

Assignee: Airbus Operations SAS (Toulouse, FR)

Appl. No.: 18/643483

Filed: April 23, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240351697 A1	Oct. 24, 2024

Foreign Application Priority Data

FR	2304078	Apr. 24, 2023
----	---------	---------------

Publication Classification

Int. Cl.: B64D29/02 (20060101)

U.S. Cl.:

CPC B64D29/02 (20130101);

Field of Classification Search

CPC: B64D (29/00); B64D (29/02); B64D (29/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5101621	12/1991	Mutch	428/116	B64D 29/00
2015/0041059	12/2014	Olson	156/60	B32B 37/12
2015/0136875	12/2014	Lacko	239/265.19	F02K 1/827
2015/0143796	12/2014	Lacko	60/226.2	F02K 1/766

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019155015	12/2018	WO	N/A

OTHER PUBLICATIONS

French Search Report for corresponding French Patent Application No. 2304078 dated Oct. 10, 2023. cited by applicant

Primary Examiner: Abell; Tye William

Attorney, Agent or Firm: Greer, Burns & Crain, Ltd.

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS

(1) This application claims the benefit of French Patent Application Number 2304078 filed on Apr. 24, 2023, the entire disclosure of which is incorporated herein by way of reference.

FIELD OF THE INVENTION

(2) The present invention relates to an internal fixed structure for an aircraft nacelle, to a nacelle comprising two such structures, and to an aircraft comprising at least one such nacelle.

BACKGROUND OF THE INVENTION

(3) A nacelle of an aircraft engine is fastened to a structure of the aircraft wing by an engine pylon and the nacelle encloses the engine of the aircraft. The nacelle conventionally comprises two internal fixed structures (also called IFS) and two outer structures (also called OS).

(4) Each structure comprises a part forming a half-cylinder overall. The two internal structures are disposed facing one another so as to form a cylinder in which the engine is housed, and the two outer structures are disposed around the internal fixed structures. A secondary duct is thus formed between the internal fixed structures and the outer structures.

(5) An internal fixed structure is generally made up of an upper end panel, of an intermediate panel

and of a lower end panel. The end panels are planar overall, and the intermediate panel is in the form of a half-cylinder overall and is between the end panels. The end panels are fastened to the intermediate panel so as to form the internal fixed structure.

(6) FIG. 6 shows an example of an internal fixed structure **600** from the prior art at an upper junction **601** between the upper end panel **602** and the intermediate panel **604**. Each panel **602**, **604** takes the form of a sandwich panel successively comprising a resistive skin **606a**, a honeycomb structure **606b** and a structural skin **606c**.

(7) The internal fixed structure **600** also comprises, at the junction **601**, at least one shoe **610**, conventionally made of metal, which is fastened a posteriori to the panels **602** and **604**, for example with the aid of fasteners **612**. Each shoe **610** also bears a pad **614**. At the upper junction **601**, the two internal fixed structures **600** appear on either side of the engine pylon **608** and each pad **614** bears against a surface of the engine pylon **608**.

(8) At a lower junction between the lower end panel and the intermediate panel **604**, the two internal fixed structures **600** appear facing one another and each pad **614** of one internal fixed structure **600** bears against a pad of the other internal fixed structure **600**.

(9) Furthermore, due to the curvature at the junctions **601**, the internal fixed structure **600** comprises a honeycomb structure **607** which exhibits high flexibility properties in order to adapt to said curvature.

(10) Even if such an arrangement is satisfactory from a functional point of view, it is necessary to find a new arrangement, for example in order to eliminate the flexible honeycomb structure **607** which is relatively expensive.

SUMMARY OF THE INVENTION

(11) An object of the present invention is to propose an internal fixed structure for an aircraft nacelle, for which the shoes are incorporated directly into a splice plate fastened to the panels.

(12) To this end, what is proposed is an internal fixed structure for a nacelle of an aircraft comprising an engine pylon, said internal fixed structure comprising: an upper end panel, a lower end panel, an intermediate panel in the form of a half-cylinder and disposed between the upper end panel and the lower end panel, an upper splice plate between the upper end panel and the intermediate panel, a lower splice plate between the intermediate panel and the lower end panel, wherein each splice plate is made up of a skin with an inner face and an outer face, wherein the inner face is fastened to the intermediate panel and to the end panel considered, and wherein the skin comprises at least one indentation protruding with respect to the outer face, wherein each indentation has a fastening surface, and for each fastening surface, a pad fastened to said fastening surface, wherein each pad of the upper splice plate is intended to bear against a surface of the engine pylon, and wherein each pad of the lower splice plate is intended to bear against a pad of a lower splice plate of another internal fixed structure.

(13) With such an arrangement, it is no longer necessary to install a honeycomb structure with high flexibility properties, and a honeycomb structure with standard flexibility properties is sufficient.

(14) According to a particular embodiment, each panel is a sandwich panel successively comprising a resistive skin, a honeycomb structure and a structural skin, which are fastened to one another, wherein the inner face of each splice plate is fastened to the structural skins of the intermediate panel and of the end panel considered.

(15) According to a particular embodiment, each panel is a sandwich panel successively comprising a resistive skin, a honeycomb structure, a structural skin, which are fastened to one another, and a closure skin shaped so as to be fastened to the structural skin and to a edge of said panel, wherein the inner face of each splice plate is fastened to the closure skins of the intermediate panel and of the end panel considered.

(16) Advantageously, the internal fixed structure comprises a complementary skin fastened between the resistive skins of the intermediate panel and of the end panel considered, and the closure skins of the intermediate panel and of the end panel considered are common and thus form a single skin

placed against the complementary skin.

(17) Advantageously, the internal fixed structure comprises a complementary honeycomb structure fastened between the complementary skin and the closure skin/skins.

(18) Advantageously, a edge of the intermediate panel and a edge of a considered end panel are at a distance from one another, the considered splice plate comprises stiffeners or extruded elements or corrugations disposed against the inner face of the skin of said splice plate, and each stiffener or extruded element or corrugation is positioned between the edge of the intermediate panel and the edge of said end panel.

(19) Advantageously, each stiffener or extruded element or corrugation comprises a plate fastened to the skin of the splice plate.

(20) Advantageously, each stiffener or extruded element or corrugation comprises a wall that is rigidly connected to the plate and extends perpendicularly with respect to the plate.

(21) The invention also proposes a nacelle for an aircraft comprising an engine pylon, the nacelle comprising two internal fixed structures according to one of the preceding variants, wherein the two internal fixed structures face one another, in such a way that the intermediate panels form a cylinder, wherein each pad of the lower splice plate of one internal fixed structure bears against a pad of the lower splice plate of the other internal fixed structure.

(22) The invention also proposes an aircraft comprising an engine pylon and at least one nacelle according to the preceding variant, wherein each pad of the upper splice plate of an internal fixed structure bears against a surface of the engine pylon.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above-mentioned features of the invention, along with others, will become more clearly apparent upon reading the following description of one exemplary embodiment, said description being given with reference to the appended drawings, in which:

(2) FIG. 1 is a side view of an aircraft according to the invention,

(3) FIG. 2 is a schematic perspective representation of an internal fixed structure according to the invention,

(4) FIG. 3 is a perspective front view of a splice plate for the internal fixed structure according to the invention,

(5) FIG. 4 is a perspective top view of the splice plate in FIG. 3,

(6) FIG. 5 is a view in section of the internal fixed structure according to the invention along plane V in FIG. 2, and

(7) FIG. 6 is a view in section of an internal fixed structure of the prior art.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(8) FIG. 1 shows an aircraft **100** which comprises a fuselage **102** to either side of which is fastened a wing **104** beneath which at least one nacelle **106** is fastened via an engine pylon **108**. An engine is housed inside the nacelle **106**.

(9) In the following description, and by convention, X denotes the longitudinal axis of the nacelle **106** which is oriented positively in the direction of forward movement of the aircraft **100**, Y denotes the transverse axis which is horizontal when the aircraft **100** is on the ground, and Z denotes the vertical axis or vertical height when the aircraft **100** is on the ground, these three directions X, Y and Z being mutually orthogonal.

(10) In the following description, terms relating to a position are considered with reference to the direction of movement of the aircraft **100** when the turbomachine is in operation, indicated by the arrow F.

(11) FIG. 2 shows an internal fixed structure **200** according to the invention. As for the prior art, the

nacelle **106** comprises two internal fixed structures **200** (also called IFS) and two outer structures **202** (also called OS).

(12) Each structure **200**, **202** comprises a part forming a half-cylinder overall, and the two internal fixed structures **200** are disposed facing one another in such a way that the two half-cylinders combine to form a cylinder in which the engine **204** is housed. The two outer structures **202** are disposed around the internal fixed structures **200** in such a way as to form a secondary air duct **50** between the internal fixed structures **200** and the outer structures **202**.

(13) The internal fixed structure **200** is made up of an upper end panel **200a**, of an intermediate panel **200c** and of a lower end panel **200b**. The end panels **200a-b** are planar overall, and the intermediate panel **200c** forms a half-cylinder overall and is disposed and fastened between the end panels **200a-b** so as to form the internal fixed structure **200**. In position in the aircraft **100**, the upper end panel **200a** is disposed above the intermediate panel **200c** and the lower end panel **200b** is disposed below the intermediate panel **200c**. Thus, in the nacelle **106**, the two internal fixed structures **200** face one another, in such a way that the intermediate panels **200c** face one another so as to form the cylinder in which the engine **204** is housed.

(14) The internal fixed structure **200** has an upper junction **208a** between the upper end panel **200a** and the intermediate panel **200c** and a lower junction **208b** between the intermediate panel **200c** and the lower end panel **200b**. FIG. 5 shows the internal fixed structure **200** at the upper junction **208a**, but the arrangement is similar at the lower junction **208b**.

(15) According to the invention, at the upper junction **208a**, the internal fixed structure **200** comprises an upper splice plate **210a**, and at the lower junction **208b**, the internal fixed structure **200** comprises a lower splice plate **210b**. Each splice plate **210a-b** ensures the joining and the fastening between the intermediate panel **200c** and the end panel **200a-b** considered.

(16) FIGS. 3 and 4 show the upper splice plate **210a**, but the principle is identical for the lower splice plate **210b**. The splice plate **210a-b** is made up of a skin **312** having an inner face **312a** and an outer face **312b**, wherein the inner face **312a** is fastened to the intermediate panel **200c** and to the end panel **200a-b** considered. The edge of the intermediate panel **200c** and the edge of the end panel **200a-b** considered are at a distance from one another, and the splice plate **210a-b** thus bridges the space between said edges and holds them together.

(17) The skin **312** is thus shaped depending on the form of the internal fixed structure **200** and comprises one or more indentations **314**, wherein each indentation **314** protrudes with respect to the outer face **312b**. Each indentation **314** is therefore in one piece with the skin **312**, thus forming a single component. Each indentation **314** thus forms a boss on the side of the outer face **312b** and a recess on the side of the inner face **312a**.

(18) The fastening of the skin **312** is ensured by any suitable means, such as the installation of fasteners **504** such as blind bolts, adhesive bonding, etc.

(19) Each indentation **314** has a fastening surface **316** to which a pad **506** is fastened.

(20) At the upper junction **208a** and therefore the upper splice plate **210a**, the two internal fixed structures **200** appear on either side of the engine pylon **108** and each pad **506** of an upper splice plate **210a** bears against a surface of the engine pylon **108**. At the lower junction **208b** and therefore the lower splice plate **210b**, the two internal fixed structures **200** appear facing one another and each pad **506** of the lower splice plate **210b** of one internal fixed structure **200** bears against a pad **506** of the lower splice plate **210b** of the other internal fixed structure **200**.

(21) Thus, with such an arrangement, it is no longer necessary to install a flexible honeycomb structure, resulting in financial gain. The incorporation of the indentations into the splice plate makes it possible to obtain a single component which can be easily installed, instead of having several such components in the case of the prior art.

(22) Each splice plate **210a-b** can be produced from any suitable materials such as metal (aluminum alloys, steel), thermosetting or thermoplastic composite, and by any suitable methods such as by stamping, pressing, molding, machining or others.

(23) In the embodiment of the invention presented in FIG. 5, each panel **200a-c** takes the form of a sandwich panel successively comprising a resistive skin **500a**, a honeycomb structure **500b** and a structural skin **500c** which are fastened to one another.

(24) The structural skin **500c** and the honeycomb structure **500b** ensure the rigidity of the panel **200a-c** and ensure that forces passing through the panel **200a-c** are reacted.

(25) The resistive skin **500a** is pierced with holes which open out into the honeycomb structure **500b** in order to absorb acoustic waves. The resistive skin **500a** is disposed towards the secondary air duct **50** and the structural skin **500c** is oriented towards the engine **204**. The honeycomb structure **500b** is made up of open cells which extend between the resistive skin **500a** and the structural skin **500c**.

(26) In one embodiment of the invention that is not shown, the inner face **312a** of each splice plate **210a-b** is fastened to the structural skins **500c** of the intermediate panel **200c** and of the end panel **200a-b** considered.

(27) In the embodiment of the invention presented in FIG. 5, each panel **200a-c** also comprises a closure skin **502** which is shaped so as to be fastened to the structural skin **500c** of said panel **200a-c** and to the edge of said panel **200a-c** in order to close the honeycomb structure **500b**. In this embodiment of the invention, the inner face **312a** of each splice plate **210a-b** is fastened to the closure skins **502** of the intermediate panel **200c** and of the end panel **200a-b** considered.

(28) Furthermore, in the embodiment of the invention presented in FIG. 5, a complementary skin **501** is fastened between the resistive skins **500a** of the intermediate panel **200c** and of the end panel **200a-b**, forming the junction **208a-b** considered. The closure skins **502** of the intermediate panel **200c** and of the end panel **200a-b** considered are common and thus form a single skin which is placed against the complementary skin **501**.

(29) In the embodiment of the invention presented in FIG. 5, a complementary honeycomb structure **503** is fastened between the complementary skin **501** and the closure skin/skins **502**.

(30) To adjust the rigidity of the skin **312** of the splice plates **210a-b**, stiffeners **318** or extruded elements or corrugations are disposed against the inner face **312a**. In the case of stiffeners **318**, the latter are fastened to the inner face **312a**. Each stiffener **318** or extruded element or corrugation is positioned in the space between the edge of the intermediate panel **200c** and the edge of the end panel **200a-b** considered.

(31) In the embodiment of the invention presented in FIG. 5, each stiffener **318** is thus disposed between the skin **312** of the splice plate **210a-b** and the closure skin **502** between the intermediate panel **200c** and the end panel **200a-b**.

(32) According to the method implemented to produce the splice plate **210a-b**, each stiffener **318** is added by overmolding, mechanical connection, welding, etc.

(33) Each stiffener **318** or extruded element or corrugation in this case comprises a plate **318a** which is fastened to the skin **312** of the splice plate **210a-b** and is curved in this case.

(34) Depending on the constraints, each stiffener **318** or extruded element or corrugation may also comprise a wall **318b** that is rigidly connected to the plate **318a** and extends perpendicularly with respect to the plate **318a**.

(35) While at least one exemplary embodiment of the present invention(s) is disclosed herein, it should be understood that modifications, substitutions and alternatives may be apparent to one of ordinary skill in the art and can be made without departing from the scope of this disclosure. This disclosure is intended to cover any adaptations or variations of the exemplary embodiment(s). In addition, in this disclosure, the terms “comprise” or “comprising” do not exclude other elements or steps, the terms “a” or “one” do not exclude a plural number, and the term “or” means either or both. Furthermore, characteristics or steps which have been described may also be used in combination with other characteristics or steps and in any order unless the disclosure or context suggests otherwise. This disclosure hereby incorporates by reference the complete disclosure of any patent or application from which it claims benefit or priority.

Claims

1. An internal fixed structure for a nacelle of an aircraft comprising an engine pylon, said internal fixed structure comprising: an upper end panel, a lower end panel, an intermediate panel in a form of a half-cylinder and disposed between the upper end panel and the lower end panel, an upper splice plate between the upper end panel and the intermediate panel, a lower splice plate between the intermediate panel and the lower end panel, wherein each splice plate is made up of a skin with an inner face and an outer face, wherein the inner face is fastened to the intermediate panel and to the respective end panel, and wherein each skin comprises at least one indentation protruding with respect to the outer face, wherein each indentation has a fastening surface, and for each fastening surface, a pad fastened to said fastening surface, wherein each pad of the upper splice plate is configured to bear against a surface of the engine pylon, and wherein each pad of the lower splice plate is configured to bear against a pad of a lower splice plate of another internal fixed structure.
 2. The internal fixed structure according to claim 1, wherein each panel is a sandwich panel successively comprising a resistive skin, a honeycomb structure and a structural skin, which are fastened to one another, wherein the inner face of each splice plate is fastened to the structural skins of the intermediate panel and of the respective end panel.
 3. The internal fixed structure according to claim 1, wherein each panel is a sandwich panel successively comprising a resistive skin, a honeycomb structure, a structural skin, which are fastened to one another, and a closure skin shaped so as to be fastened to the structural skin and to an edge of said panel, wherein the inner face of each splice plate is fastened to the closure skins of the intermediate panel and of the respective end panel considered.
 4. The internal fixed structure according to claim 3, further comprising: a complementary skin fastened between the resistive skins of the intermediate panel and of the respective end panel, wherein the closure skins of the intermediate panel and of the respective end panel are common and form a single skin placed against the complementary skin.
 5. The internal fixed structure according to claim 4, further comprising: a complementary honeycomb structure fastened between the complementary skin and a closure skin.
 6. The internal fixed structure according to claim 1, wherein an edge of the intermediate panel and an edge of a respective end panel are at a distance from one another, wherein the respective splice plate comprises stiffeners or extruded elements or corrugations disposed against the inner face of the skin of the respective splice plate, and wherein the stiffener or extruded element or corrugation is positioned between the edge of the intermediate panel and the edge of said end panel.
 7. The internal fixed structure according to claim 6, wherein each stiffener or extruded element or corrugation comprises a plate fastened to the skin of the splice plate.
 8. The internal fixed structure according to claim 7, wherein each stiffener or extruded element or corrugation comprises a wall that is rigidly connected to the plate and extends perpendicularly with respect to the plate.
 9. A nacelle for an aircraft comprising: an engine pylon, and two internal fixed structures according to claim 1, wherein the two internal fixed structures face one another, in such a way that the intermediate panels form a cylinder, wherein each pad of the lower splice plate of one of the two internal fixed structures bears against a pad of the lower splice plate of the other of the two internal fixed structures.
 10. An aircraft comprising: an engine pylon and the nacelle according to claim 9, wherein each pad of the upper splice plate of the two internal fixed structures bears against a surface of the engine pylon.
-