

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                        |
|----------------------|------------------------|
| United States Patent | 12398652               |
| Kind Code            | B2                     |
| Date of Patent       | August 26, 2025        |
| Inventor(s)          | Trivedi; Deepak et al. |

---

### Seal assembly for a turbomachine

---

#### Abstract

This disclosure is directed to seal assemblies for a turbomachine. The seal assemblies include one or more paired rotors and stators and at least one interface between the rotors and the stators. The components of the stator may be axially and radially movable by vibrations and other mechanical interference. The stators comprise a sealing element, a seal housing, and a stator interface connected to the engine housing. In some examples, seal assembly includes a damping element to isolate one or more of the rotating components from vibrations mechanical interference that might misalign the rotating components from the stationary components while the turbomachine is operational. In some examples, the damping element is positioned between the seal housing and the stator interface. In other examples, the damping element is positioned between the stator interface and the engine housing.

---

**Inventors:** Trivedi; Deepak (Halfmoon, NY), Bidkar; Rahul Anil (Clifton Park, NY), Ertas; Bugra H. (Niskayuna, NY), Hardikar; Narendra Anand (Bangalore, IN), Ganiger; Ravindra Shankar (Bengaluru, IN)

**Applicant:** General Electric Company (Schenectady, NY)

**Family ID:** 1000008782143

**Assignee:** GENERAL ELECTRIC COMPANY (Evendale, OH)

**Appl. No.:** 18/751022

**Filed:** June 21, 2024

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240426222 A1          | Dec. 26, 2024           |

#### Foreign Application Priority Data

|    |              |               |
|----|--------------|---------------|
| IN | 202311041857 | Jun. 23, 2023 |
|----|--------------|---------------|

## Publication Classification

**Int. Cl.:** F01D11/02 (20060101); F01D11/00 (20060101); F01D25/04 (20060101)

**U.S. Cl.:**

**CPC** F01D11/025 (20130101); F01D11/003 (20130101); F01D25/04 (20130101); F05D2260/96 (20130101)

## Field of Classification Search

**CPC:** F01D (11/08); F01D (25/04); F01D (11/025); F01D (25/183); F01D (11/003); F05D (2260/96); F16J (15/3452); F16J (15/3464); F02C (7/28)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC          |
|--------------|-------------|---------------|----------|--------------|
| 3372939      | 12/1967     | Coulombe      | 277/916  | F16J 15/36   |
| 4916892      | 12/1989     | Pope          | N/A      | N/A          |
| 6311983      | 12/2000     | Burcham       | 415/113  | F16J 15/44   |
| 6601854      | 12/2002     | Auber         | 277/377  | F16J 15/3464 |
| 6676369      | 12/2003     | Brauer        | N/A      | N/A          |
| 6848689      | 12/2004     | Auber         | 277/377  | F16J 15/3464 |
| 7819405      | 12/2009     | Ohama         | 277/390  | F16J 15/3404 |
| 8490980      | 12/2012     | Wright et al. | N/A      | N/A          |
| 8714558      | 12/2013     | Berard        | 277/377  | F16J 15/363  |
| 9903218      | 12/2017     | Hafner et al. | N/A      | N/A          |
| 11028927     | 12/2020     | Lewis         | N/A      | N/A          |
| 11035253     | 12/2020     | Walker        | N/A      | F01D 11/005  |
| 11047481     | 12/2020     | Bidkar et al. | N/A      | N/A          |
| 11268477     | 12/2021     | O'Leary       | N/A      | N/A          |
| 2013/0147123 | 12/2012     | Davies        | 277/348  | F01D 25/183  |
| 2014/0159317 | 12/2013     | Jahn          | 277/411  | F16J 15/3468 |
| 2015/0184531 | 12/2014     | Baptista      | 415/230  | F16J 15/24   |
| 2023/0279781 | 12/2022     | Ganiger       | 277/412  | F16J 15/4476 |

### FOREIGN PATENT DOCUMENTS

| Patent No.     | Application Date | Country | CPC |
|----------------|------------------|---------|-----|
| 2233700        | 12/2009          | EP      | N/A |
| WO 2017/180682 | 12/2016          | WO      | N/A |

---

*Primary Examiner:* Brockman; Eldon T

*Attorney, Agent or Firm:* Venable LLP

---

## Background/Summary

## CROSS REFERENCE TO RELATED APPLICATION

(1) This application claims the benefit of India Patent Application No. 202311041857, filed Jun. 23, 2023. The prior application is incorporated herein by reference in its entirety.

## FIELD

(2) The present disclosure relates to turbomachine engine seals, mechanisms for controlling turbomachine engine seal gaps, and dampers for seal gap control mechanisms.

## BACKGROUND

(3) Turbomachines typically include a rotor assembly, a compressor, and a turbine. The rotor assembly may include a fan having an array of fan blades extending radially outwardly from a rotating shaft. The rotating shaft, which transfers power and rotary motion from the turbine to both the compressor and the rotor assembly, is supported longitudinally using a plurality of bearing assemblies. Known bearing assemblies include one or more rolling elements supported within a paired race. To maintain a rotor critical speed margin, the rotor assembly is typically supported on three bearing assemblies: one thrust bearing assembly and two roller bearing assemblies. The thrust bearing assembly supports the rotor shaft and minimizes axial and radial movement thereof, while the roller bearing assemblies support radial movement of the rotor shaft.

(4) Typically, these bearing assemblies are enclosed within a housing disposed radially around the bearing assembly. The housing forms a compartment or sump that holds a lubricant (e.g., oil) for lubricating the bearing. This lubricant may also lubricate gears and other seals. Gaps between the housing and the rotor shaft are necessary to permit rotation of the rotor shaft relative to the housing. The bearing sealing system usually includes two such gaps: one on the upstream end and another on the downstream end. In this respect, a seal disposed in each gap prevents the lubricant from escaping the compartment. Further, the air around the sump may generally be at a higher pressure than the sump to reduce the amount of lubricant that leaks from the sump. Further, one or more gaps and corresponding seals are generally positioned upstream and/or downstream of the sump to create the higher-pressure region surrounding the sump.

(5) In some turbomachine engines, the seals may be hydrodynamic or non-contacting seals. To avoid wear of the components of such seals when the turbomachine engines are operational, it is important that no unintentional contact between adjacent components occurs. To accomplish this, various seal gap control mechanisms exist to maintain a desired spacing between non-contacting portions of a non-contacting seal.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a schematic side view of an example turbomachine engine.

(2) FIG. 2 illustrates a schematic side view of a section of a turbomachine engine including an example of a seal assembly.

(3) FIG. 3A illustrates an enlarged view of the seal assembly depicted in FIG. 2.

(4) FIG. 3B illustrates a schematic side view of a section of a turbomachine engine including a contact seal assembly.

(5) FIG. 4 illustrates a hydrodynamic seal assembly according to one example.

(6) FIG. 5A illustrates a seal assembly according to another example, having a vibration damper disposed between a stator interface and a fixed housing.

(7) FIG. 5B illustrates the vibration damper of FIG. 5A disposed between the stator interface and the seal assembly in greater detail.

(8) FIG. 5C illustrates a coil portion of the vibration damper of FIG. 5A according to one example.

(9) FIG. 6 illustrates a stator of a seal assembly having a vibration damper according to another example.

- (10) FIG. 7 illustrates the vibration damper of FIG. 6 in greater detail.
- (11) FIG. 8A illustrates a portion of a seal assembly according to another example, having a vibration damper disposed between a stator interface and a fixed housing.
- (12) FIG. 8B illustrates the vibration damper of the seal assembly of FIG. 8A in greater detail.
- (13) FIG. 8C illustrates the vibration damper of the seal assembly of FIG. 8A in greater detail.
- (14) FIG. 8D illustrates a portion of the damper shown in FIGS. 8B and 8C.
- (15) FIG. 8E illustrates a portion of the damper shown in FIGS. 8B and 8C.
- (16) FIG. 9 illustrates a seal assembly according to another example, having a damper disposed between the stator interface and the sealing element, according to one example.
- (17) FIG. 10 illustrates the damper of FIG. 9 along a centerline axis.
- (18) FIG. 11 illustrates a seal assembly according to another example, having a damper between the stator interface and the sealing element, according to another example.
- (19) FIG. 12A illustrates a seal assembly according to another example, having a damper comprising one or more visco-elastomeric rods.
- (20) FIG. 12B illustrates a seal assembly according to another example, having a damper comprising an elastomeric ring according to one example.
- (21) FIG. 12C illustrates a seal assembly according to another example, having a damper comprising an elastomeric ring according to another example.
- (22) FIG. 13A illustrates a seal assembly according to another example, having a damper comprising a piston ring and piston.
- (23) FIG. 13B illustrates the piston ring component of FIG. 13A.
- (24) FIG. 14 illustrates a seal assembly according to another example, having a damper comprising an axial foil damper.

#### DETAILED DESCRIPTION

- (25) Reference now will be made in detail to preferred embodiments, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation, not limitation of the preferred embodiments. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the embodiments discussed without departing from the scope or spirit of disclosure. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that the present disclosure covers such modifications and variations as come within the scope of the appended claims and their equivalents.
- (26) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations.
- (27) The terms “forward” and “aft” refer to relative positions within a gas turbine engine or vehicle, and refer to the normal operational attitude of the gas turbine engine or vehicle. For example, with regard to a gas turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust.
- (28) As used herein, the terms “first” and “second” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.
- (29) The terms “upstream” and “downstream” refer to the relative direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.
- (30) The terms “coupled,” “fixed,” “attached to,” and the like refer to both direct coupling, fixing, or attaching, as well as indirect coupling, fixing, or attaching through one or more intermediate components or features, unless otherwise specified herein.
- (31) The singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise.

(32) Disclosed herein are examples of turbomachines and seal assemblies for use with turbomachines. The turbomachine may include a rotating shaft extending along a centerline axis and a fixed housing positioned exterior to the rotating shaft in a radial direction relative to the centerline axis. The seal assembly may include a sump housing at least partially defining a bearing compartment for holding a cooling lubricant. The seal assembly may further include a bearing supporting the rotating shaft. In addition, the seal assembly may also include a sump seal at least partially defining the bearing compartment. A pressurized housing of the seal assembly may be positioned exterior to the sump housing and define a pressurized compartment to at least partially enclose the sump housing. Further, a seal may be positioned between the rotating shaft and the pressurized housing to at least partially define the pressurized compartment to enclose the sump housing.

(33) In certain examples, a seal assembly including a self-lubricating lattice material may allow for a more efficient turbomachine. A self-lubricating lattice material disposed between the rotating portions of a seal assembly and the static portions of the seal assembly can reduce the wear of the various seal assembly components that are in rotating contact with one another when the turbomachine is in an operational condition. Additionally, the use of a self-lubricating lattice material can mitigate heat buildup along the operational seal interface. In some examples, the self-lubricating lattice can be permeated with a lubricant and/or a coolant. For example, a self-lubricating lattice material can be deposited between a rotating runner and a static sealing element so as to form a lubricant layer between the runner and the sealing element when the turbomachine engine is operational.

(34) It should be appreciated that, although the present subject matter will generally be described herein with reference to a gas turbine engine, the disclosed systems and methods may generally be used on bearings and/or seals within any suitable type of turbine engine, including aircraft-based turbine engines, land-based turbine engines, and/or steam turbine engines. Further, though the present subject matter is generally described in reference to a high-pressure spool of a turbine engine, it should also be appreciated that the disclosed system and method can be used on any spool within a turbine engine, (e.g., a low-pressure spool or an intermediate pressure spool).

(35) Referring now to the drawings, FIG. 1 illustrates a cross-sectional view of one example of a turbomachine 10, also referred to herein as turbomachine engine 10. More particularly, FIG. 1 depicts the turbomachine 10 configured as a gas turbine engine that may be utilized within an aircraft in accordance with aspects of the present subject matter. The gas turbine engine is shown having a longitudinal or centerline axis 12, also referred to herein as a centerline, extending therethrough for reference purposes. In general, the engine may include a core engine 14 and a fan section 16 positioned upstream thereof. The core engine 14 may generally include a substantially tubular external housing 18 that defines an annular inlet 20. In addition, the external housing 18 may further enclose and support a compressor section 23. For the example shown, the compressor section 23 includes a booster compressor 22 and a high-pressure compressor 24. The booster compressor 22 generally increases the pressure of the air (indicated by arrow 54) that enters the core engine 14 to a first pressure level. The high-pressure compressor 24, such as a multi-stage, axial-flow compressor, may then receive the pressurized air (indicated by arrow 58) from the booster compressor 22 and further increases the pressure of such air. The pressurized air exiting the high-pressure compressor 24 may then flow to a combustor 26 within which fuel is injected into the flow of pressurized air, with the resulting mixture being combusted within the combustor 26.

(36) For the example illustrated, the external housing 18 may further enclose and support a turbine section 29. Further, for the depicted example, the turbine section 29 includes a first, high-pressure turbine 28 and second, low-pressure turbine 32. For the illustrated examples, one or more of the compressors 22, 24 may be drivingly coupled to one or more of the turbines 28, 32 via a rotating shaft 31 extending along the centerline axis 12. For example, high energy combustion products 60 are directed from the combustor 26 along the hot gas path of the engine to the high-pressure turbine

**28** for driving the high-pressure compressor **24** via a first, high-pressure drive shaft **30**. Subsequently, the combustion products **60** may be directed to the low-pressure turbine **32** for driving the booster compressor **22** and fan section **16** via a second, low-pressure drive shaft **34** generally coaxial with high-pressure drive shaft **30**. After driving each of turbines **28** and **32**, the combustion products **60** may be expelled from the core engine **14** via an exhaust nozzle **36** to provide propulsive jet thrust. Further, the rotating shaft(s) **31** may be enclosed by a fixed housing **39** extending along the centerline axis **12** and positioned exterior to the rotating shaft **31** in a radial direction relative to the centerline axis **12**.

(37) Additionally, as shown in FIG. 1, the fan section **16** of the engine may generally include a rotatable, axial-flow fan rotor assembly **38** surrounded by an annular fan casing **40**. It should be appreciated by those of ordinary skill in the art that the fan casing **40** may be supported relative to the core engine **14** by a plurality of substantially radially-extending, circumferentially-spaced outlet guide vanes **42**. As such, the fan casing **40** may enclose the fan rotor assembly **38** and its corresponding fan blades **44**. Moreover, a downstream section **46** of the fan casing **40** may extend over an outer portion of the core engine **14** so as to define a secondary, or bypass, airflow conduit **48** providing additional propulsive jet thrust.

(38) It should be appreciated that, in several examples, the low-pressure drive shaft **34** may be directly coupled to the fan rotor assembly **38** to provide a direct-drive configuration. Alternatively, the low-pressure drive shaft **34** may be coupled to the fan rotor assembly **38** via a speed reduction device **37** (e.g., a reduction gear or gearbox or a transmission) to provide an indirect-drive or geared drive configuration. Such a speed reduction device(s) **37** may also be provided between any other suitable shafts and/or spools within the turbomachine engine **10** as desired or required.

(39) During operation of the turbomachine engine **10**, it should be appreciated that an initial airflow (indicated in FIG. 1 by arrow **50**) may enter the turbomachine engine **10** through an associated inlet **52** of the fan casing **40**. For the illustrated example, the airflow then passes through the fan blades **44** and splits into a first compressed airflow (indicated by arrow **54**) that moves through the bypass airflow conduit **48** and a second compressed airflow (indicated by arrow **56**) which enters the booster compressor **22**. In the depicted example, the pressure of the second compressed airflow **56** is then increased and enters the high-pressure compressor **24** (as indicated by arrow **58**). After mixing with fuel and being combusted within the combustor **26**, the combustion products **60** may exit the combustor **26** and flow through the high-pressure turbine **28**. Thereafter, for the shown example, the combustion products **60** flow through the low-pressure turbine **32** and exit the exhaust nozzle **36** to provide thrust for the engine.

(40) Turning now to FIG. 2, the turbomachine engine **10** (FIG. 1) can include a seal assembly **100**, positioned between stationary and rotating components of the turbomachine engine **10**. For example, the seal assembly **100** can be positioned between the stationary and rotating components of the high-pressure compressor **24** (FIG. 1) described above.

(41) The seal assembly **100** may generally isolate a sump housing **102** from the rest of the turbomachine engine **10**. As such, the seal assembly **100** includes the sump housing **102**. The sump housing **102** includes at least a portion of the rotating shaft **31** and the fixed housing **39**. For example, the fixed housing **39** may include various intermediary components or parts extending from the fixed housing **39** to form a portion of the sump housing **102**. Such intermediary components or parts may be coupled to the fixed housing **39** or formed integrally with the fixed housing **39**. Similarly, the rotating shaft **31** may also include various intermediary components extending from the rotating shaft **31** to form the sump housing **102**. Further, the sump housing **102** at least partially defines a compartment, more particularly, a bearing compartment **120** for holding a cooling lubricant (not shown). For instance, the sump housing **102** at least partially radially encloses the cooling lubricant and a bearing **118** (as described in more detail in relation to FIG. 3A). The cooling lubricant (e.g., oil) for lubricating the various components of the bearing **118** may circulate through the bearing compartment **120**. The seal assembly **100** may include one or more

sump seals **105** (as described in more detail in reference to FIGS. **3** and **4**) at least partially defining the bearing compartment **120** for holding the cooling lubricant.

(42) The seal assembly **100** further includes a pressurized housing **103** positioned exterior to the sump housing **102**. The pressurized housing **103** may at least partially enclose the sump housing **102**. For example, as illustrated, the pressurized housing **103** may be positioned both forward and aft relative to the centerline axis **12** of the turbomachine engine **10**. The pressurized housing **103** may include at least a portion of the rotating shaft **31** and the fixed housing **39** or intermediary components extending from the rotating shaft **31** and/or the fixed housing **39**. For example, the pressurized housing **103** may be formed at least partially by the high-pressure drive shaft **30** and the fixed housing **39** both forward and aft of the sump housing **102**.

(43) For the depicted example, the pressurized housing **103** defines a compartment, and more particularly, a pressurized compartment **124** to at least partially enclose the sump housing **102**. In the exemplary example, bleed air from the compressor section **23** (FIG. **1**), the turbine section **29** (FIG. **1**), and/or the fan section **16** (FIG. **1**) may pressurize the pressurized compartment **124** to a pressure relatively greater than the pressure of the bearing compartment **120**. As such, the pressurized compartment **124** may prevent or reduce the amount of any cooling lubricant leaking from the sump housing **102** across the sump seal **105**.

(44) Further, the seal assembly **100** may include one or more seals to further partially define the pressurized compartment **124** (such as the seal assemblies **200** and **300** as described in more detail in regard to FIGS. **4-10**). For instance, one or more sealing elements may be positioned between the rotating shaft **31** and the fixed housing **39**.

(45) Referring now to FIG. **3A**, a closer view of the sump housing **102** is illustrated according to aspects of the present disclosure. In the illustrated example, the seal assembly **100** includes the bearing **118**. The bearing **118** may be in contact with an exterior surface of the rotating shaft **31** and an interior surface of the fixed housing **39**. It should be recognized that the rotating shaft **31** may be the high-pressure drive shaft **30** or the low-pressure drive shaft **34** described in regard to FIG. **1** or any other rotating drive shaft of the turbomachine **10**. The bearing **118** may be positioned radially between the portion of the rotating shaft **31** and the portion of the fixed housing **39** that form the sump housing **102**. As such, the bearing **118** may be positioned within the sump housing **102**. The bearing **118** may support the rotating shaft **31** relative to various fixed components in the engine.

(46) In the depicted example, the bearing **118** may be a thrust bearing. That is, the bearing **118** may support the rotating shaft **31** from loads in the axial, or the axial and radial directions relative to the centerline axis **12**. For example, the bearing **118** may include an inner race **128** extending circumferentially around an outer surface of the rotating shaft **31**. In the shown example, an outer race **130** is disposed radially outward from the inner race **128** and mates with the fixed housing **39**, such as an interior surface of the sump housing **102**. The inner and outer races **128**, **130** may have a split race configuration. For the depicted example, the inner and outer race **128**, **130** may sandwich at least one ball bearing **132** therebetween. Preferably, the inner and outer races **128**, **130** sandwich at least three ball bearings **132** therebetween.

(47) In additional examples, the bearing **118** may be a radial bearing. That is, the bearing **118** may support the rotating shaft **31** from loads generally in the radial direction relative to the centerline axis **12**. In other examples, the inner race **128** and outer race **130** may sandwich at least one cylinder, cone, or other shaped element to form the bearing **118**.

(48) Still referring to FIG. **3A**, the seal assembly may include two sump seals **105**. Each of a first and a second sump seals **105** may be positioned between the rotating shaft **31** and the fixed housing **39** to at least partially define the bearing compartment **120** for housing the cooling lubricant and the bearing **118**. For example, the first sump seal **105** may be positioned forward of the bearing **118**, and the second sump seal **105** may be positioned aft of the bearing **118**. For the illustrated example, the first sump seal **105** may be a labyrinth seal **104**, and the second sump seal **105** may be a carbon seal **106**. Although, the two sump seals **105** may be any suitable type of seal, and, in other

examples, the sealing system may include further sump seals **105**, such as three or more. For example, in other examples, multiple labyrinth seals, carbon seals, and/or hydrodynamic seals may be utilized in the sump housing **102** in any arrangement.

(49) FIG. **3A** also more closely illustrates the labyrinth seal **104** and the carbon seal **106**. For the example depicted, the labyrinth seal **104** and the carbon seal **106** (such as a hydrodynamic seal) are non-contact seals, which do not require contact between the stationary and moving components when operating at high speed. Non-contact seals typically have a longer service life than contact seals. Still, in other examples, one or both of the sump seals **105** may be a contact seal. Each type of seal may operate in a different manner. For the depicted example, the labyrinth seal **104** includes an inner surface **136** (coupled to the rotating shaft **31**) and an outer surface **138** (coupled to the fixed housing **39**). For example, a tortuous path (not shown) extending between the inner surface **136** and the outer surface **138** prevents the cooling lubricant from escaping the sump housing **102**. For the exemplary example shown, the air pressure on an outer side of the labyrinth seal **104** (i.e., in the pressurized compartment **124**) is greater than the air pressure on the inner side of the labyrinth seal **104** (i.e., in the bearing compartment **120**). In this respect, the stationary and rotating components may be separated by an air film (sometimes called an air gap) during relative rotation therebetween.

(50) The carbon seal **106** may, in some examples, be a hydrodynamic or non-contacting seal with one or more hydrodynamic grooves **140** that are positioned between the stationary and rotating components, as illustrated in FIG. **3A**. In general, the hydrodynamic grooves **140** may act as a pump to create an air film between the non-contacting carbon seal **106** and the rotating shaft **31**. For example, as the rotating shaft **31** rotates, fluid shear may direct air in a radial gap **112** into the hydrodynamic groove(s) **140**. As air is directed into the hydrodynamic groove(s) **140**, the air may be compressed until it exits the hydrodynamic groove(s) **140** and forms the air film to separate the rotating shaft **31** and the non-contacting carbon seal **106**. The air film may define a radial gap **112** between the stationary and non-stationary components of the seal assembly **100**, as shown in FIG. **3A**. Thus, the rotating shaft **31** may ride on the air film instead of contacting an inner sealing surface **108**.

(51) In some examples, the carbon seal **106** is proximate to and in sealing engagement with a hairpin member **146** of the rotating shaft **31**. In this respect, the hairpin member **146** may contact the carbon seal **106** when the rotating shaft **31** is stationary or rotating at low speeds. Though it should be recognized that the carbon seal **106** may be in sealing engagement with any other part or component of the rotating shaft **31**. Nevertheless, for the illustrated hydrodynamic, carbon seal **106**, the carbon seal **106** lifts off of the rotating shaft **31** and/or the hairpin member **146** when the rotating shaft **31** rotates at sufficient speeds.

(52) Referring now to FIG. **3B**, a sump housing **102** of a seal assembly **100** is illustrated according to another aspect of the present disclosure. It should be noted that the description of the seal assembly **100** of FIG. **3A** applies to like parts of the seal assembly **100** of FIG. **3B** unless otherwise noted, and accordingly, like parts will be identified with like numerals.

(53) The sump housing **102** of FIG. **3B** particularly illustrates the sump housing **102** with three sump seals **105**. The sump housing **102** may generally be configured as the sump housing **102** of FIG. **3A**. For example, the sump housing **102** may include a portion of the rotating shaft **31**, a portion of the fixed housing **39**, and enclose the bearing **118**. Further, the sump seals **105** and the sump housing **102**, at least partially, define the bearing compartment **120**.

(54) In the example illustrated, one of the sump seals **105** is a contacting lip seal **107**. As such, the inner surface **136** and the outer surface **138** may be in contact in order to seal the sump housing **102**. The illustrated example further includes a carbon seal **106** configured as a contacting carbon seal. As such, the carbon seal **106** includes a carbon element **150** in sealing engagement with the rotating shaft **31**. For the example depicted, the carbon element **150** may engage the hairpin member **146** of the rotating shaft **31**. Additionally, the carbon seal **106** may include a windback **152**

that reduces the amount of the cooling lubricant that reaches the carbon element **150**. Further, one of the sump seals **105** may be an open gap seal **110**. For instance, the pressure on an outer side **154** (such as the pressurized compartment **124**) may be greater than the pressure of the bearing compartment **120** and thus reduce the leakage of cooling lubricant through the open gap seal **110**. In further examples, one of the sump seals **105** may be a brush seal. In such examples, the brush seal may contain a plurality of bristles (such as carbon bristles) in sealing engagement between the rotating shaft **31** and the fixed housing **39**.

(55) Another example seal assembly **200** that may be used with the turbomachine engine **10** discussed above is illustrated in FIG. **4**. It should be noted that the description of the seal assembly **100** of FIGS. **2**, **3A**, and **3B** applies to like parts of the seal assembly **200** of FIG. **4** unless otherwise noted; and accordingly, like parts will be identified with like numerals.

(56) As shown in FIG. **4**, the seal assembly **200** can be a face seal positioned between the components of the rotating shaft **31** and the components of the fixed housing **39** and can comprise a runner **202** disposed circumferentially around and coupled to the rotating shaft **31**, such that the runner **202** and the rotating shaft rotate in tandem. The seal assembly **200** can also comprise a sealing element **204** coupled to a stationary member **206** of the fixed housing **39**.

(57) During the operation of a turbomachine engine **10** that includes the seal assembly **200**, the rotation of the shaft **31** causes the corresponding rotation of the runner **202** connected to the rotating shaft **31**. The runner **202** contacts the sealing element **204** along an interfacial zone **210**. The interfacial zone **210** can, in some examples, form a boundary between two chambers, such as the bearing compartment **120** and the pressurized compartment **124** described above, and illustrated in FIG. **3A**. Accordingly, the interfacial zone **210** can, in some examples, prevent the flow of fluids between the two chambers.

(58) In some examples, such as that illustrated in FIG. **4** the seal assembly **200** can be a hydrodynamic seal. In such examples, the sealing element **204** and/or the runner **202** can have hydrodynamic features such as hydrodynamic grooves **216**. The hydrodynamic grooves **216** function in substantially the same way as the hydrodynamic grooves in non-contacting carbon seal **106** described above to create an air cushion between the runner **202** and the sealing element **204**. As the rotating shaft **31** and the connected runner **202** rotate relative to the sealing element **204** and the fixed housing **39**, the air cushion prevents the sealing element **204** and the runner **202** from coming into contact, while preventing the flow of fluids such as lubricant between the two chambers separated by the seal, such as the bearing compartment **120** and the pressurized compartment **124**. It is to be understood that, in other examples, the seal assembly **200** can comprise a contact seal (such as those discussed above), wherein the interfacial zone **210** is defined by a region of contact between the sealing element **204** and the runner **202**.

(59) In some examples, the facial seal assemblies, such as that illustrated in FIG. **4**, can include sealing elements (such as sealing element **204** as previously discussed) coupled to the fixed housing **39** by a gap controlling mechanism (such as a damper or spring disposed between the sealing element **204** and the fixed housing **39**). In such examples, the position of the sealing element relative to the runner can be adjusted during the operation of the turbomachine engine **10**, according to forces imparted by other components of the seal assembly, or external engine conditions such as physical shocks and/or turbulence. However, in some cases, the positioning of the components of the seal assembly, and particularly the sealing element may be too sensitive to rapid variations in the forces and/or operational conditions affecting the turbomachine engine **10**. This can cause axial misplacement of the sealing element, which may result in undesirable contact between the sealing element and the runner, or abrasion of the sealing element and/or the runner. The sealing element can also become radially misaligned with the runner (i.e., the center of gravity of the sealing element can come out of radial alignment with the center of gravity of the runner). When the sealing element becomes radially misaligned, the forces controlling the gap between the sealing element and the runner can also come out of alignment, which cause a reduction in the

effectiveness of the seal and/or can cause the sealing element to impinge on the runner.

(60) Accordingly, there is a need for seal assemblies with improved damping for the sealing element, capable of reducing and/or dampening the movement of the sealing element relative to the runner and/or relative to the fixed housing **39** in response to changes in operational and/or environmental conditions of the turbomachine engine **10**.

(61) In some examples, the movement of the sealing element relative to the runner can be dampened by isolation or dampening the portions of the seal assembly, sometimes called the stator, extending between the sealing element and the fixed housing **39**.

(62) FIG. 5A shows an example seal assembly **300**, suitable for use with turbomachine engines previously discussed (such as turbomachine engine **10**), with additional damping elements to control the axial “A” and radial “R” position of various components of the seal assembly **300**. As shown in FIG. 5A, the seal assembly **300** can comprise a runner **302** statically coupled to the rotating shaft **31** and a sealing element **304** axially spaced apart from the runner **302** and movably coupled to the fixed housing **39**. The region of contact between the runner **302** and the sealing element **304** (or in the case of a hydrodynamic seal, the gap between the runner **302** and the sealing element **304**) can define a seal interface **306**.

(63) With continued reference to FIG. 5A, the sealing element **304** can be statically coupled to a seal housing **308**. The seal assembly **300** can also include a spring chamber **310** defined by the seal housing **308** and a stator interface **312**, which in turn is statically coupled to a fixed housing **39**. A spring element **314** can be disposed in the spring chamber **310** and configured to allow the seal housing **308** and the stator interface **312** to move axially relative to one another. Thus, the seal housing is movably connected to the fixed housing, through the spring element. In turn, this allows the contact force (in the case of a contact seal assembly) or the seal gap (in the case of a non-contacting seal assembly) between the runner **302** and the sealing element **304** to be adjusted during the operation of the turbomachine engine **10**. For convenience, the portion of the seal assembly **300** comprising the sealing element **304**, the seal housing **308**, the spring chamber **310**, the spring element **314**, and the stator interface **312** can be collectively referred to as a stator assembly **316**.

(64) The seal assembly **300** can also include a radial damper **318** and an axial damper **320** disposed between and in mutual contact with the stator interface **312** and the fixed housing **39**. As best shown in FIG. 5B, the radial damper **318** can be disposed in a first notch **322a** formed in a radial face **324** of the stator interface **312**, such that the radial damper **318** extends around the circumference of the stator interface **312** and is positioned in a radial gap **336** positioned between the stator interface **312** and a portion of the fixed housing **39**. Similarly, as best shown in FIG. 5B, the axial damper **320** can be disposed in a second notch **322b**, formed in an axial face **328** of the stator interface **312**, such that the axial damper **320** extends circumferentially around the rotating shaft **31** and is positioned in an axial gap **338** located between the stator interface **312** and a portion of the fixed housing **39**.

(65) The radial damper **318** and the axial damper **320** are illustrated in greater detail in FIG. 5C. As shown in FIG. 5C, the dampers **318**, **320** can each have an annular body comprising an inner coil **332** and an outer sheath **334** disposed outside of and extending at least partially around the inner coil **332**.

(66) In some examples, the inner coil **332** can comprise a plurality of deformable rings, and the outer sheath **334** can comprise a flexible material such as an elastomer, a ceramic or glass-fiber rope, or a metallic structure. The arrangement of the outer sheath **334** and the inner coil **332** can be such that the inner coil **332** can deform within the outer sheath **334**, while the outer sheath **334** remains in contact with both the stator interface **312** and the fixed housing **39**. In this way, forces that might otherwise be communicated between the fixed housing **39** and the stator interface **312** are absorbed or mitigated by the dampers **318**, **320**.

(67) In a neutral or equilibrium condition, the center of gravity of the stator assembly **316** can be

axially aligned with the center of gravity of the runner **302** (that is, both centers of gravity can lie on the centerline axis **12** of the turbomachine engine **10**). However, during the operation of the turbomachine engine **10**, forces exerted on the sealing element **304** can cause the displacement of the stator assembly **316** such that the center of gravity of the stator assembly **316** comes out of axial alignment with the center of gravity of the runner **302** (i.e., moves off the centerline axis **12** of the turbomachine engine **10**).

(68) More particularly, and with reference back to FIG. 5A, in the case of a non-contacting seal assembly, the hydrodynamic pressures caused by the air film along the seal interface **306** can exert an axial force on the sealing element **304**, directed towards the stator interface **312**. In the case of a contacting seal assembly, the contact between the sealing element **304** and the runner **302** can exert an axial force on the sealing element **304** directed towards the stator interface **312**. In both cases, external forces on the turbomachine engine **10**, such as operational vibrations, external physical shocks, and turbulence can displace the sealing element **304**, the seal housing **308**, and the stator interface **312**.

(69) Such displacement of the sealing element **304** and the seal housing **308** can comprise both an axial component and a radial component. In the case of radial displacement of the stator interface **312**, the stator interface **312** can move relative to the fixed housing **39**, such that the stator interface **312** moves closer to the fixed housing **39** at some points along the circumference of the radial gap **336** and further away from the fixed housing **39** at others. As the stator interface **312** moves relative to the fixed housing **39**, the radial damper **318** can deform to absorb and/or resist the forces which would tend to move the stator interface **312**, and therefore the seal housing **308** and the sealing element **304**, out of radial alignment with the runner **302**.

(70) In the case of axial displacement of the stator interface **312**, the stator interface **312** can move axially to the fixed housing **39**, such that the stator interface **312** moves closer to or further apart from the fixed housing **39** at some points along the circumference of the axial gap **338** and further away from the fixed housing **39** at others. As the stator interface **312** moves relative to the fixed housing **39**, the axial damper **320** can deform to absorb and/or resist the forces which would tend to move the stator interface **312**, and therefore the seal housing **308** and the sealing element **304**, out of axial alignment with the runner **302**.

(71) Additionally, the radial damper **318** and the axial damper **320** isolate the stator interface **312**, the seal housing **308**, and the sealing element **304** from the fixed housing **39**. In this way, vibrations in the fixed housing **39**, such as those caused by the rotational motion of the various rotating components of the turbomachine engine **10**, can be reduced and/or slowed by the radial damper **318** and the axial damper **320**. Because the radial damper **318** and the axial damper **320** are flexible and configured to absorb forces communicated between the stator interface **312** and the fixed housing **39**, the position of the components of the seal assembly **300** relative to one another may be maintained despite operational vibrations of the turbomachine engine **10** (FIG. 1).

(72) In another example, the seal assembly **300** can include a stator comprising a radial foil damper configured to absorb radial and axial displacement of the stator components. This stator can be included in lieu of the stator assembly **316** described above in relation to the seal assembly **300** and illustrated in FIGS. 5A-5C.

(73) Turning now to FIG. 6, a stator assembly **400** according to another example can comprise a sealing element **402** statically coupled to a seal housing **404**. The stator assembly **400** also comprises a spring chamber **406** defined by the seal housing **404** and a stator interface **408**, which in turn is statically coupled to a fixed housing **39**. A spring element **410** can be disposed in the spring chamber **406** and configured to allow the seal housing **404** and the stator interface **408** to move axially relative to one another, which in turn allows the contact force (in the case of a contact seal assembly) or the seal gap (in the case of a non-contacting seal assembly) between a runner (such as the runner **302** of FIG. 5A) and the sealing element **402** to be adjusted during the operation of the turbomachine engine **10**.

(74) The stator interface **408** can, as shown in FIG. 6, comprise a first axial face portion **412** and a second axial face portion **414** separated by a loop member **416**. The first axial face portion **412** can form one axial face of the spring chamber **406**, receiving a first end portion **410a** of the spring element **410**. The second axial face portion **414** can be coupled to the fixed housing **39**. The loop member **416** extending between the first axial face portion **412** and the second axial face portion **414** can define an annular gap **418** between the axial face portions **412**, **414**. As shown in FIG. 6, the stator interface **408** can thus have a horseshoe shaped or substantially horseshoe shaped cross section, with the first axial face portion **412** on one end of the horseshoe shape and the second axial face portion **414** on the other end of the horseshoe shape.

(75) The stator interface **408** can, in such examples, be formed of a relatively thin material, and subject to vibrational forces and turbulence when the turbomachine engine **10** (FIG. 1) is in an operational state. As the stator assembly **400** is subjected to axial and/or radial displacement, as described in greater detail above, either from the forces generated in the sealing gap (i.e., hydrodynamic forces in the case of a hydrodynamic seal assembly, or contact forces in the case of a contact seal assembly), the first axial face portion **412** and the second axial face portion **414**, and thus the stator assembly **400** and the fixed housing **39**, can move relative to one another.

(76) More particularly, when an axial force moves the sealing element **402** and/or the seal housing **404**, such as might occur from fluctuations in forces in the seal gap, as described above in an axial direction, the stator interface **408** can deflect with the first axial face portion **412** moving axially relative to the second axial face portion **414**. Likewise, when an axial force, such as from turbulent flight conditions, acts on the fixed housing **39**, the second axial face portion **414** can move relative to the first axial face portion **412**.

(77) Similarly, when a radial force moves the sealing element **402** and/or the seal housing **404**, the first axial face portion **412** of the stator interface **408** can move radially closer to or further apart from the second axial face portion **414**, by narrowing or widening a mouth **420** of the annular gap **418**. Likewise, radial force to the fixed housing **39** can cause the second axial face portion **414** to move relative to the first axial face portion **412** in the same way.

(78) To reduce and/or absorb the relative movement of the axial face portions **412**, **414**, and thus maintain alignment in the radial “R” direction and the axial “A” direction of the seal assembly, the stator assembly **400** can also include a radial foil damper **422**. Shown in greater detail in FIG. 7, the radial foil damper **422** can comprise an outer sheath **424** and an inner sheath **426**. A corrugated foil **428** can be disposed between the outer sheath **424** and the inner sheath **426** of the radial foil damper **422**. The corrugated foil **428** can attach at a first end portion **430** to the outer sheath **424** and at a second end portion **432** to the inner sheath **426**. The radial foil damper **422** can be configured such that the outer sheath **424** and the inner sheath **426** of the radial foil damper **422** can be configured to move axially relative to one another. As the outer sheath **424** and the inner sheath **426** of the radial foil damper **422** move axially relative to each other, the first end portion **430** of the corrugated foil **428** can move along with the outer sheath **424** and the second end portion **432** of the corrugated foil **428** can move along with the inner sheath **426** of the foil damper. The corrugated foil **428** elastically deforms or axially moves to accommodate the relative axial motion of the outer sheath **424** and the inner sheath **426**, and the force required to cause this elastic deformation or axial motion of the corrugated foil **428** resists the forces moving the outer sheath **424** and the inner sheath **426**.

(79) As shown in FIG. 6, the radial foil damper **422** can be positioned between the first axial face portion **412** and the second axial face portion **414** of the stator interface **408**. Thus, the outer sheath **424** will be in contact with a radially outer portion **434** of the loop member **416** and the inner sheath **426** in contact with a radially inner portion **436** of the loop member **416**.

(80) When the first axial face portion **412** and the second axial face portion **414** move axially relative to one another in response to forces on the fixed housing **39** and/or the sealing element **402**, the radially outer portion **434** and the radially inner portion **436** of the loop member **416** also

move axially relative to each other. This causes the outer sheath **424** to move with the radially outer portion **434** of the loop member **416** and the inner sheath **426** to move with the radially inner portion **436** of the loop member **416**. In turn, this causes the radial foil damper **422** to absorb axial forces acting on the first axial face portion **412** and the second axial face portion **414** of the stator interface **408**.

(81) When the first axial face portion **412** and the second axial face portion **414** move radially relative to one another in response to forces on the fixed housing **39** and/or the sealing element **402**, the radially outer portion **434** and the radially inner portion **436** of the loop member **416** move closer together or further apart. This causes the outer sheath **424** and the inner sheath **426** of the radial foil damper **422** press closer together or pull further apart, which elastically deforms the corrugated foil **428**, absorbing radial forces and/or displacement acting on the stator interface **408**.

(82) In another example, a seal assembly can include a stator comprising an axial foil damper configured to absorb radial and axial displacement of the stator components. This stator can be included in lieu of the stator assembly **316** (FIG. 5A) or the stator assembly **400** (FIG. 6) described above.

(83) Turning now to FIG. 8A, a stator **500** according to one example can comprise a sealing element **502** fixedly coupled to a seal housing **504**. The seal housing **504** comprises an annular lip **506** spaced axially apart from sealing element **502** and defining a groove **508**. As shown in FIG. 8D, the annular lip **506** comprises a plurality of slots **510** circumferentially spaced apart from one another and retaining tabs **512** positioned between the plurality of slots **510**.

(84) Returning to FIG. 8A, the groove **508** receives an axial foil damper **514**, which extends between the seal housing **504** and the fixed housing **39**. As best shown in FIG. 8E, the axial foil damper **514** comprises an annular body **516** with an arched cross section. The axial foil damper **514** further comprises a plurality of outer tabs **518** and inner tabs **520**. The outer tabs **518** are each received in a corresponding slot **510** (FIG. 8D) in the annular lip **506** (FIG. 8A) of the seal housing **504** (FIG. 8A), allowing the axial foil damper **514** to be securely slotted into the groove **508** (FIG. 8A) by inserting the outer tabs **518** into the corresponding slots **510** (FIG. 8D) and then rotating the axial foil damper **514** relative to the seal housing **504** to secure the outer tabs **518** beneath the retaining tabs **512** (FIG. 8D).

(85) As best shown in FIG. 8E, the inner tabs **520** extend radially inwards from the annular body **516** and are separated by a plurality of notches **522**. The inner tabs **520** each have an inwardly disposed end portion **524** and a cusp **526** formed between the junction of each inner tab **520** with the annular body **516** of the axial foil damper **514**. The plurality of cusps **526** form an annular ridge **528** that extends axially away from the seal housing **504** to contact the fixed housing **39**, as shown in FIG. 8A. Because the inner tabs **520** are not connected to one another, each inner tab **520** may deflect axially independently of the other inner tabs **520**, allowing for the inner tabs **520** to absorb axial deflection, such as by engine vibration or displacement to the fixed housing **39** or the sealing element **502**, as shown in FIG. 8A, and as discussed above in relation to the stator assemblies **316** (FIG. 5A) and **400** (FIG. 6). This controls the relative axial positions of the fixed housing **39**, the sealing element **502**, and the runner (such as the runner **302** discussed above in relation to the seal assembly **300** of FIG. 5A).

(86) Returning to FIG. 8D, the seal housing **504** can also comprise a plurality of circumferential tabs **530**, disposed around the outer circumference of the seal housing **504**. Two adjacent circumferential tabs **530** can, together, define a plurality of circumferential slots **532** extending around the seal housing **504**.

(87) As shown in FIG. 8B, the circumferential slots **532** can each receive a corresponding corrugated foil element **534**. The corrugated foil elements **534** can comprise a plurality of peaks **536** and valleys **538**, and can extend radially between the seal housing **504** and the fixed housing **39** with the peaks **536** in contact with the fixed housing **39** and the valleys **538** in contact with the seal housing **504**, as best shown in FIG. 8C. Because the circumferential slots **532** extend around

the full circumference of the stator **500**, they can respond to radial displacement of the stator **500** (FIG. **8A**) in any direction. More particularly, when the seal housing **504** or the fixed housing **39** experiences radial forces as described above, the peaks **536** and the valleys **538** of the corrugated foil elements **534** are pressed closer to each other at some point around the circumference of the seal housing **504**. Thus, the corrugated foil elements **534** can absorb the radial deflection of the seal housing **504** and/or the fixed housing **39** relative to each other and control the radial alignment of the sealing element **502** relative to a runner, such as the runner **302** described above in relation to the seal assembly **300** of FIG. **5A**.

(88) In some examples, the stator **500** can also include a secondary seal **540** disposed radially outwards of the annular lip **506**. As shown in FIG. **8A**, the secondary seal **540** can extend over the annular lip **506** and to the axial foil damper **514**. A portion of the secondary seal **540** may rest against the axial foil damper **514** to create a contact region **542** between the secondary seal **540** and the axial foil damper **514**. Because the secondary seal **540** rests against, but is not connected to, the axial foil damper **514**, any movement of the axial foil damper **514** in the radial “R” and/or axial “A” direction will cause movement of the axial foil damper **514** relative to the secondary seal **540** along the contact region **542**. This causes friction between the axial foil damper **514** and the secondary seal **540**, which resists and therefore dampens the motion of the axial foil damper **514**, further controlling the radial and axial alignment of the sealing element **502** relative to a runner, such as the runner **302** described above in relation to the seal assembly **300** of FIG. **5A**. The secondary seal **540** may also form a seal between the axial foil damper **514**, and the bearing compartment **120** (FIG. **2**), providing an additional barrier to prevent lubricant from leaking past the stator (that is, the rotationally static portions of the seal assembly) into other engine compartments, such as the pressurized compartment **124** (FIG. **2**). The secondary seal **540** is typically an elastomeric or otherwise soft and flexible material and may be selected for a combination of friction and sealing properties.

(89) In some examples, the movement of the sealing element relative to the runner can be dampened by isolating or dampening the housing of the sealing element to minimize its motion relative to the other portions of the stator.

(90) FIGS. **9-11** show an example seal assembly **600** with an isolated or dampened seal housing **608**. As shown in FIG. **9**, the seal assembly **600** comprises a runner **602**, fixedly coupled to the rotating shaft **31** and configured to rotate with the rotating shaft **31** when the turbomachine (such as turbomachine engine **10** of FIG. **1**) is in an operational state. The seal assembly **600** also includes a sealing element **604**, axially spaced apart from the runner **602** and forming a seal interface **606** therebetween.

(91) The sealing element **604** is also statically coupled to the seal housing **608**, which together with a stator interface **610** defines a spring chamber **612**. A spring element **614** can be disposed in the spring chamber **612**, axially spacing the seal housing **608** away from the stator interface **610** and allowing the position of the sealing element **604** relative to the stator interface **610** and/or the runner **602** in a way substantially similar to that described in relation to seal assembly **300** of FIG. **5A**.

(92) As shown in FIG. **9**, the seal assembly **600** also includes one or more damping arms **616** extending between the stator interface **610** and the seal housing **608** and positioned radially outwards from the seal housing **608**. The damping arms **616** can comprise an axially extending member **618** and a radially extending tongue **620**. The radially extending tongue **620** of each damping arm **616** can extend into a corresponding groove **622** formed in the outer circumference of the seal housing **608**.

(93) The grooves **622** in the outer circumference of the seal housing **608** can be sized so that the tongue **620** of the corresponding damping arm **616** frictionally engages an inner wall portion **624** of the groove **622**. In this way, when the engine fixed housing **39** and/or the sealing element **604** experience an axial shock or displacement, the tongue **620** of each damping arm **616** slides axially

within the groove **622**, and friction between the tongue **620** and the inner wall portion **624** of the groove **622** resists the axial displacement of the sealing element **604** and/or the seal housing **608** relative to the runner **602** and the fixed housing **39**, thereby controlling the relative positioning between the sealing element **604** and the runner **602**.

(94) As shown in FIG. **10**, the seal assembly **600** can comprise a plurality of damping arms **616** spaced circumferentially apart from one another around the seal housing **608** and a corresponding plurality of grooves **622**, arranged such that the plurality of grooves **622** and damping arms **616** forms a plurality of paired grooves **622** and damping arms **616**. Each paired groove **622** and damping arm **616** can thus have a tongue **620** extending into each groove **622** and engaging the inner wall portion **624** of the groove **622**. It is to be appreciated that, while FIG. **10** shows a seal assembly **600** having 12 pairs of damping arms **616** and grooves **622**, the seal assembly **600** can comprise a different number of pairs of damping arms **616** and grooves **622**, depending on the size of the sealing element **604** and other factors such as the operational resonant frequency of the turbomachine. In some examples, the seal assembly **600** can comprise 2-16 pairs of damping arms **616** and grooves **622**, such as 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, or 16 pairs of damping arms **616** and grooves **622**.

(95) Because the number of tongues **620** and corresponding grooves **622** can be varied as previously described, and because each tongue **620** and corresponding groove **622** will variably contact one another, the seal assembly **600** may be resistant to harmonic forcing, which can drive the seal housing **608** into resonance. Resonant behavior potentially leads to large amplitude oscillations of the seal structure which increases the probability of failure due to either rubbing between the rotor and the seal face, rubbing of various interfaces within the seal, increased fatigue loading on the seal, or any combination thereof.

(96) In some examples, as illustrated in FIG. **11**, the damping arms **616** can further comprise a first member **626** and a second member **628** disposed radially outwards from the first member **626**, separated by an elastomeric layer **630** that is simultaneously in contact with the first member **626** and the second member **628**. The elastomeric layer **630** can further absorb radial and axial vibrations caused by displacement or shock to the seal assembly **600** and/or the fixed housing **39**, and further control the relative positioning between the sealing element **604** and the runner **602**. The elastomeric layer **630** can comprise any suitable vibration damping material, including, for example, silicone rubber, Kalrez®, or any combination thereof.

(97) FIGS. **12A-12C** show another example seal assembly **700** comprising a seal housing **708** spaced apart from the fixed portions of the stator by one or more elastomeric elements. As shown in FIGS. **12A-12C**, the seal assembly **700** comprises a runner **702**, statically coupled to and configured to rotate along with the rotating shaft **31**. The seal assembly **700** also includes a sealing element **704** axially spaced apart from the runner **702**, forming a seal interface **706** between the sealing element **704** and the runner **702**.

(98) The sealing element **704** is also statically coupled to the seal housing **708**, which together with a stator interface **710** defines a spring chamber **712**. A spring element **714** can be disposed in the spring chamber **712**, axially spacing the seal housing **708** away from the stator interface **710** and allowing the position of the sealing element **704** relative to the stator interface **710** and/or the runner **702** in a way substantially similar to that described in relation to the seal assemblies **300** and **600**.

(99) With continued reference to FIGS. **12A-12C**, a damper housing **716** can be statically coupled to and extend axially from the stator interface **710**. As shown, the damper housing **716** can extend alongside and radially outwards from the seal housing **708**, such that a radial gap **718** is defined between the damper housing **716** and the seal housing **708**.

(100) One or more damping elements can be placed in the radial gap **718** between the damper housing **716** and the seal housing elements. In one particular example, the damping elements can comprise one or more visco-elastic rods **720** extending between the seal housing **708** and the damper

housing **716**, as illustrated in FIG. **12A**. In some examples, such as that illustrated in FIG. **12A**, the plurality of viso-elastic rods **720** can be axially spaced apart from one another to form a row of viso-elastic rods **720** in the radial gap **718**. The seal assembly **700** can thus include a plurality of rows of viso-elastic rods **720**, each row of viso-elastic rods **720** spaced circumferentially apart from the adjacent rows of viso-elastic rods **720** such that the plurality of viso-elastic rods **720** is disposed throughout the entire circumference of the radial gap **718**.

(101) In some such examples, the rows of viso-elastic rods **720** (or other dissipative rods) can be axially aligned or substantially axially aligned with the adjacent rows of viso-elastic rods **720**, such that the viso-elastic rods **720** of each row of viso-elastic rods **720** occupies the same axial position as the corresponding elastomeric rods of the adjacent rows of viso-elastic rods **720**, separated only by the circumferential spacing between them. In other such examples, certain rows of viso-elastic rods **720** can be axially offset relative to one another, such that the viso-elastic rods **720** of each row occupy a different axial position than the corresponding viso-elastic rods **720** of the adjacent rows of viso-elastic rods **720**.

(102) It is to be appreciated that, while FIG. **12A** shows a seal assembly **700** with a row of viso-elastic rods **720** having three viso-elastic rods **720**, it is to be understood that, in some examples, the row of viso-elastic rods **720** can comprise a different number of viso-elastic rods **720**, such as 2, 4, 5, or 6 elastomeric rods circumferentially aligned with and axially spaced apart from one another. It is also to be appreciated that, in some examples, in lieu of rows of each row of viso-elastic rods **720**, a single elastomeric rod can be placed at each circumferential spacing around the seal housing **708**.

(103) When the seal housing **708** moves in the radial “R” direction relative to the damper housing **716** (and therefore relative to the fixed housing **39**), it can only do so by compressing at least some of the viso-elastic rods **720** disposed along the side of the seal housing **708** moving radially towards the damper housing **716** as the radial gap **718** narrows. In such a case, the force needed to compress the viso-elastic rods **720** to accommodate the movement of the seal housing **708** relative to the damper housing **716** is absorbed and the motion of the seal housing **708** relative to the damper housing **716** is reduced. Thus, the viso-elastic rods **720** absorb vibration and reduce misalignment of the sealing element **704** and the runner **702**.

(104) When the seal housing **708** moves in the axial “A” direction relative to the damper housing **716** (and therefore relative to the fixed housing **39**), it can only do so by shearing at least some of the viso-elastic rods **720** in an axial direction, because the viso-elastic rods **720** are in contact with the seal housing **708** at one end and the damper housing **716** on the other end. In such a case, the force needed to shear the viso-elastic rods **720** in the axial direction to accommodate the movement of the seal housing **708** relative to the damper housing **716** is absorbed and the motion of the seal housing **708** relative to the damper housing **716** is reduced. Thus, the viso-elastic rods **720** absorb vibration and reduce misalignment of the sealing element **704** and the runner **702**.

(105) When the seal housing **708** moves circumferentially (that is, when it rotates) relative to the damper housing **716** (and therefore relative to the fixed housing **39**), it can only do so by shearing at least some of the viso-elastic rods **720** in a circumferential direction, because the viso-elastic rods **720** are in contact with the seal housing **708** at one end and the damper housing **716** on the other end. In such a case, the force needed to shear the viso-elastic rods **720** in the circumferential direction to accommodate the movement of the seal housing **708** relative to the damper housing **716** is absorbed and the motion of the seal housing **708** relative to the damper housing **716** is reduced. Thus, the viso-elastic rods **720** absorb vibration and reduce misalignment of the sealing element **704** and the runner **702**.

(106) In another example, illustrated in FIGS. **12B** and **12C**, the damping element disposed in the radial gap **718** between the seal housing **708** and the damper housing **716** can be an elastomeric ring **722**. The elastomeric ring **722** can function in the same or substantially the same way as the viso-elastic rods **720** (FIG. **12A**) described above, except for the differences described below.

(107) As shown in FIGS. 12B and 12C, the elastomeric ring 722 can extend between the seal housing 708 and the damper housing 716 and extend circumferentially around the seal housing 708. The elastomeric ring 722 can sit within a groove 724 that extends circumferentially around the radial gap 718. The groove 724 can be formed by a first annular ridge 726a and a second annular ridge 726b axially spaced apart from the first annular ridge 726a. The annular ridges 726a, 726b can in some examples, such as that illustrated in FIG. 12B, extend radially outwards from the seal housing 708. In other examples, such as that illustrated in FIG. 12C, the annular ridges 726a, 726b can extend radially inwards from the damper housing 716.

(108) The elastomeric ring 722 is thus bound in either axial direction by the annular ridges 726a, 726b, and is in simultaneous contact with the seal housing 708 and the damper housing 716. Therefore, when the seal housing 708 moves in the radial “R” direction relative to the damper housing 716 (and therefore to the fixed housing 39), at least some portion of the elastomeric ring 722 must radially compress to accommodate the relative movement of the seal housing 708 and the damper housing 716. Likewise, when the seal housing 708 moves in the axial “A” direction or circumferentially relative to the damper housing 716 (and therefore to the fixed housing 39), at least some portion of the elastomeric ring 722 must shear to accommodate the relative movement of the seal housing 708 and the damper housing 716. As described above regarding the visco-elastic rods 720 shown in FIG. 12A, this reduces the movement of the seal housing 708 relative to the damper housing 716, and thus absorbs vibration and reduces misalignment of the sealing element 704 and the runner 702.

(109) The visco-elastic rods 720 and/or the elastomeric rings 722 described above and shown in FIGS. 12A-12C can comprise any elastomeric material of sufficient stiffness and temperature resistance. In some examples, the elastomeric rods 720 and/or the elastomeric rings 722 can comprise silicone rubber or Kalrez®, but it is to be understood that any elastomeric material with a suitable combination of physical and thermal properties could be used instead.

(110) For each example having an elastomeric dampening element disposed between the seal housing 708 and a damper housing 716 extending from the stator interface 710, the addition of the elastomeric damping element further provides radial support for the seal housing 708 and can thus help reduce sag or tilt of the seal housing 708 relative to the stator interface 710.

(111) While the examples illustrated in FIGS. 12A-12C show the elastomeric damping element disposed on the side of the seal assembly 700 that is open to the bearing compartment 120, it is also to be understood that, in other examples, the elastomeric damping element (and the damper housing 716) can be placed on the side of the seal assembly 700 that is open to the pressurized compartment 124.

(112) FIGS. 13A and 13B show another example seal assembly 800 comprising a seal housing spaced apart from the fixed portions of the stator with one or more piston elements disposed therebetween. As shown in FIG. 14A, the seal assembly 800 comprises a runner 802, statically coupled to and configured to rotate along with the rotating shaft 31. The seal assembly 800 also includes a sealing element 804 axially spaced apart from the runner 802, forming a seal interface 806 between the sealing element 804 and the runner 802.

(113) The sealing element 804 is also statically coupled to a seal housing 808, which together with a stator interface 810 defines a spring chamber 812. A spring element 814 can be disposed in the spring chamber 812, axially spacing the seal housing 808 away from the stator interface 810 and allowing the position of the sealing element 804 relative to the stator interface 810 and/or the runner 802 in a way substantially similar to that described in relation to the seal assemblies 300, 600, and 700 of FIG. 5A, FIG. 10 and FIGS. 12A-12C, respectively.

(114) The seal assembly 800 can also comprise a piston ring 815 disposed radially outwards of and circumferentially around the seal housing 808. The piston ring 815 can comprise two projections 816 that extend radially outwards from the seal housing 808 to define one or more grooves 818. While FIG. 13A shows an example piston ring 815 with projections 816 extending radially

outwards from the seal housing **808**, forming one groove **818** between them, it is to be appreciated that, in other examples, the piston ring **815** could comprise a greater number of projections **816**, such as 3, 4, 5, 6, 7, or 8 projections, defining a greater number of grooves **818** between them, such as 2, 3, 4, 5, 6, or 7 grooves.

(115) With continued reference to FIG. **13A**, a piston housing **820** can be statically coupled to and extend axially from the stator interface **810**. As shown in FIG. **13A**, the piston housing **820** can extend alongside and radially outwards from the seal housing **808**, such that a radial gap **822** is defined between the piston housing **820** and the seal housing **808**. A piston element **824** extends radially inwards from the piston housing **820** and is received by a corresponding groove **818**. The piston element **824** having an interference fit on the inner diameter of the piston housing **820**. It should also be noted that piston element **824** can extend radially inward in an integral circumferential groove **818** created in the seal housing **808**. While FIG. **13A** shows a seal assembly **800** having a single groove **818** to receive a single piston element **824**, it is to be appreciated that, in examples having a greater number of grooves **818**, a correspondingly greater number of piston elements **824** can extend radially inwards from the piston housing **820**, forming a row of piston elements **824**.

(116) The piston element **824** is tightly sized to fit within the groove **818**, while contacting the axial walls of the groove **818**. Thus, when the seal housing **808** moves in the radial “R” direction relative to the stator interface **810** (and thus relative to the fixed housing **39**), the outer periphery of the piston element **824** slides along the walls of the groove **818**. The friction between the piston element **824** and the groove **818** resists the movement of the seal housing **808** relative to the stator interface **810**. This reduces the movement of the seal housing **808**, and thus absorbs vibration and reduces misalignment of the sealing element **804** and the runner **802**.

(117) Because the piston element **824** is bounded in both axial directions by the piston ring **815**, any axial motion of the seal housing **808** relative to the stator interface **810** (and thus relative to the fixed housing **39**) is resisted by the contact between the piston element **824** and the piston ring **815**. This reduces the movement of the seal housing **808**, and thus absorbs vibration and reduces misalignment of the sealing element **804** and the runner **802**.

(118) FIG. **14** shows another example seal assembly **900** comprising a seal housing **908** spaced apart from the fixed portions of a stator interface **910** with a radial foil damper positioned between the seal housing **908** and the stator interface **910**. As shown in FIG. **14**, the seal assembly **900** comprises a runner **902**, statically coupled to and configured to rotate along with the rotating shaft **31**. The seal assembly **900** also includes a sealing element **904** axially spaced apart from the runner **902**, forming a seal interface **906** between the sealing element **904** and the runner **902**.

(119) The sealing element **904** is also statically coupled to a seal housing **908**, which together with a stator interface **910** defines a spring chamber **912**. A spring element **914** can be disposed in the spring chamber **912**, axially spacing the seal housing **908** away from the stator interface **910** and allowing the position of the sealing element **904** to change relative to the stator interface **910** and/or the runner **902** in a way substantially similar to that described in relation to the seal assemblies **300**, **600**, **700** and **800** of FIG. **5A**, FIG. **10**, FIGS. **13A-13C**, and FIG. **14A**, respectively.

(120) With continued reference to FIG. **14** a damper housing **916** can be statically coupled to and extend axially from the stator interface **910**. The damper housing **916** can extend alongside and radially outwards from the seal housing **908**, such that a radial gap **918** is defined between the damper housing **916** and the seal housing **908**. A radial foil damper, such as the radial foil damper **422** described in greater detail above and illustrated in FIG. **7**, can be positioned between the seal housing **908** and the damper housing **916**. As shown in FIG. **15**, the radial foil damper **422** can be positioned such that the outer sheath **424** is in contact with the damper housing **916** and the inner sheath **426** is in contact with the seal housing **908**.

(121) When the seal housing **908** moves in the axial “A” direction relative to the damper housing **916** (and therefore relative to the fixed housing **39**), the inner sheath **426** moves with the seal

housing **908** while the outer sheath **424** remains stationary relative to the damper housing **916**. This causes the inner sheath **426** of the radial foil damper **422** to move relative to the outer sheath **424**, in turn causing the corrugated foil **428** to move in shear between the inner sheath **426** and the outer sheath **424**. This provides resistance to the axial motion of the seal housing **908** relative to the damper housing **916**, and reduces the movement of the seal housing **908**, thus absorbing axial vibration and reducing misalignment of the sealing element **904** and the runner **902**.

(122) When the seal housing **908** moves in the radial “R” direction relative to the damper housing **916** (and thus relative to the engine housing **39**), at least a portion of the seal housing **908** and the damper housing **916** move closer together. This causes at least a portion of the outer sheath **424** and the inner sheath **426** of the radial foil damper **422** to press closer together, which in turn requires the elastic deformation of the corrugated foil **428**. This resists and reduces the movement of the seal housing **908** relative to the damper housing **916**, and reduces the movement of the seal housing **908**, thus absorbing axial vibration and reducing misalignment of the sealing element **904** and the runner **902**.

(123) In the various examples described above, the seal housing can be isolated from vibrations and/or dislocations arising from various operational conditions affecting the turbomachine engine. This ameliorates sources of axial and/or radial misalignment between the sealing element and the runner, and in turn reduces the occurrence of undesired impingement between the sealing element and the runner, improves seal performance, and reduces seal wear. It will be appreciated that the various examples described above can be used individually, or in any combination with one another.

(124) In view of the many possible embodiments to which the principles of the disclosed invention may be applied, it should be recognized that the illustrated embodiments are only preferred examples of the invention and should not be taken as limiting the scope of the invention. Rather, the scope of the disclosure is defined by the following claims.

(125) Further aspects of the disclosure are provided by the subject matter of the following clauses:

(126) A seal assembly for a turbomachine, the turbomachine including a rotating shaft extending along a centerline axis and a fixed housing positioned exterior to the rotating shaft in a radial direction relative to the centerline axis, the seal assembly comprising a runner statically coupled to the rotating shaft, a seal housing positioned radially outwards of the rotating shaft, a sealing element axially spaced apart from the runner and statically coupled to the seal housing, and a damper disposed between the seal housing and the fixed housing, wherein the seal housing is located between the sealing element and the fixed housing, and is movably connected to the fixed housing, wherein the seal housing is axially and radially movable relative to the runner and the fixed housing, and wherein the vibration is resistant to movement of the seal housing relative to the runner in an axial direction and radial a direction.

(127) The seal assembly of any preceding clause, wherein a stator interface is disposed between the seal housing and the fixed housing, is axially spaced apart from the seal housing, and is coupled to the fixed housing.

(128) The seal assembly of any preceding clause, wherein the damper comprises a coil damper disposed radially between the stator interface and the fixed housing, the coil damper comprising an annular inner coil partially enclosed by an outer sheath.

(129) The seal assembly of any preceding clause, wherein the damper comprises a coil damper disposed axially between the stator interface and the fixed housing, the coil damper comprising an annular inner coil partially enclosed by an outer sheath.

(130) The seal assembly of any preceding clause, wherein the damper is a radial foil damper, disposed radially between a portion of the stator interface and the fixed housing, the radial foil damper comprising an outer sheath, an inner sheath, and a corrugated foil extending between the outer sheath and the inner sheath.

(131) The seal assembly of any preceding clause, wherein the stator interface comprises a loop

member having a radially outer portion and a radially inner portion, and an axially extending gap between the first radial section and the second radial section, and wherein the radial foil damper is positioned within the axially extending gap.

(132) The seal assembly of any preceding clause, wherein the damper is an axial foil damper, disposed radially between the seal housing and the fixed housing, the axial foil damper comprising an annular body with an axially-extending ridge and a plurality of flexible tabs extending radially inwards from the annular body.

(133) The seal assembly of any preceding clause, wherein the seal housing comprises an annular ridge defining an annular slot positioned between the sealing element and the fixed housing, wherein the annular body of the axial foil damper further comprises a plurality of tabs extending radially outwards from the annular body, and wherein the tabs extending radially outwards from the annular body of the axial foil damper are received by the annular slot of the seal housing.

(134) The seal assembly of any preceding clause, further comprising a secondary seal disposed radially outwards of the annular ridge, extending over the annular ridge and contacting the annular body of the axial foil damper.

(135) The seal assembly of any preceding clause, further comprising one or more radial foil dampers disposed radially outwards of the seal housing and in mutual contact with the seal housing and the fixed housing.

(136) The seal assembly of any preceding clause, wherein the damper comprises an elastomeric ring disposed between the seal housing and the fixed housing.

(137) The seal assembly of any preceding clause, wherein the damper comprises one or more visco-elastic rods extending radially between the seal housing and the fixed housing.

(138) The seal assembly of any preceding clause, wherein the one or more visco-elastic rods comprise a row of visco-elastic rods spaced apart axially from each other between the seal housing and the fixed housing.

(139) The seal assembly of any preceding clause, wherein the damper further comprises one or more additional rows of visco-elastic rods spaced apart axially from each other between the seal housing and the fixed housing, and wherein the rows of visco-elastic rods are spaced apart circumferentially.

(140) A turbomachine comprising a rotating shaft extending along a centerline axis, a fixed housing positioned radially exterior to the rotating shaft relative to the centerline axis and a seal assembly comprising a runner coupled to the rotating shaft, a sealing element coupled to a seal housing, and a stator interface statically connected to the fixed housing and positioned axially between the seal housing and the fixed housing, a damper disposed between the seal housing and the stator interface; wherein the stator interface comprises a damper arm and the damper arm extends axially alongside and radially outside of the seal housing, wherein the seal housing is axially and radially movable relative to the runner and the fixed housing, and wherein the vibration is resistant to movement of the seal housing relative to the runner in an axial direction and a radial direction.

(141) The turbomachine of any preceding clause, wherein the damper comprises one or more visco-elastic rods, wherein the damper extends axially from the stator interface and is positioned radially outwards from the seal housing, and wherein the visco-elastic rods extend radially between the damper arm and the seal housing.

(142) The turbomachine of any preceding clause, wherein the one or more visco-elastic rods comprise a row of visco-elastic rods spaced apart axially from each other between the damper arm and the seal housing.

(143) The turbomachine of any preceding clause, wherein the damper further comprises one or more additional rows of visco-elastic rods spaced apart axially from each other between the damper arm and the seal housing, and wherein the rows of visco-elastic rods are spaced apart circumferentially.

(144) The turbomachine of any preceding clause, wherein the damper comprises an elastomeric

ring disposed between the damper arm and the seal housing.

(145) The turbomachine of any preceding clause, wherein the elastomeric ring sits within a circumferentially extending groove that bounds the elastomeric ring in both axial directions.

(146) The turbomachine of any preceding clause, wherein the turbomachine further comprises a piston ring disposed radially outwards of and circumferentially around the seal housing, and wherein the damper comprises a piston element extending radially inwards from the damper arm, and wherein the piston ring has a corresponding radially extending groove that receives the piston.

(147) The turbomachine of any preceding clause, wherein the damper comprises one or more tongues extending radially inwards from the damper arm and the seal housing comprises one or more axially extending grooves that receive the one or more tongues.

(148) The turbomachine of any preceding clause, wherein the damper comprises a plurality of tongues circumferentially spaced apart from each other, and the seal housing comprises a corresponding number of axially extending grooves that receive the plurality of tongues.

(149) The turbomachine of any preceding clause, wherein the damper arm comprises an axially extending first member, an axially extending second member disposed radially outwards of the first rigid layer, a gap between the first rigid layer and the second rigid layer, and an elastomeric layer deposited in the gap.

## Claims

1. A seal assembly for a turbomachine, the turbomachine including a rotating shaft extending along a centerline axis and a fixed housing positioned exterior to the rotating shaft in a radial direction relative to the centerline axis, the seal assembly comprising: a runner statically coupled to the rotating shaft; a seal housing positioned radially outwards of the rotating shaft; a sealing element axially spaced apart from the runner and statically coupled to the seal housing; and a damper disposed between the seal housing and the fixed housing, wherein the seal housing is located between the sealing element and the fixed housing, the seal housing is movably connected to the fixed housing, and the seal housing is axially and radially movable relative to the runner and the fixed housing, wherein the damper is resistant to movement of the seal housing relative to the runner in an axial direction and radial a direction, and wherein a stator interface is disposed between the seal housing and the fixed housing, the stator interface being axially spaced apart from the seal housing and coupled to the fixed housing.

2. The seal assembly of claim 1, wherein the damper comprises a coil damper disposed radially between the stator interface and the fixed housing, the coil damper comprising an annular inner coil partially enclosed by an outer sheath.

3. The seal assembly of claim 1, wherein the damper comprises a coil damper disposed axially between the stator interface and the fixed housing, the coil damper comprising an annular inner coil partially enclosed by an outer sheath.

4. The seal assembly of claim 1, wherein the damper is a radial foil damper, disposed radially between a portion of the stator interface and the fixed housing, the radial foil damper comprising an outer sheath, an inner sheath, and a corrugated foil extending between the outer sheath and the inner sheath.

5. The seal assembly of claim 4, wherein the stator interface comprises a loop member having a radially outer portion and a radially inner portion, and an axially extending gap between the radially outer portion and the radially inner portion, and wherein the radial foil damper is positioned within the axially extending gap.

6. A seal assembly for a turbomachine, the turbomachine including a rotating shaft extending along a centerline axis and a fixed housing positioned exterior to the rotating shaft in a radial direction relative to the centerline axis, the seal assembly comprising: a runner statically coupled to the rotating shaft; a seal housing positioned radially outwards of the rotating shaft; a sealing element

axially spaced apart from the runner and statically coupled to the seal housing; and a damper disposed between the seal housing and the fixed housing, wherein the seal housing is located between the sealing element and the fixed housing, the seal housing is movably connected to the fixed housing, and the seal housing is axially and radially movable relative to the runner and the fixed housing, wherein the damper is resistant to movement of the seal housing relative to the runner in an axial direction and radial a direction, and wherein the damper is an axial foil damper disposed radially between the seal housing and the fixed housing, the axial foil damper comprising an annular body with an axially-extending ridge and a plurality of flexible tabs extending radially inwards from the annular body.

7. The seal assembly of claim 6, wherein the seal housing comprises an annular ridge defining an annular slot positioned between the sealing element and the fixed housing, wherein the annular body of the axial foil damper further comprises a plurality of tabs extending radially outwards from the annular body, and wherein the tabs extending radially outwards from the annular body of the axial foil damper are received by the annular slot of the seal housing.

8. The seal assembly of claim 7, further comprising a secondary seal disposed radially outwards of the annular ridge, extending over the annular ridge and contacting the annular body of the axial foil damper.

9. The seal assembly of claim 6, further comprising one or more radial foil dampers disposed radially outwards of the seal housing and in mutual contact with the seal housing and the fixed housing.

10. A turbomachine comprising: a rotating shaft extending along a centerline axis, a fixed housing positioned radially exterior to the rotating shaft relative to the centerline axis; a seal assembly comprising a runner coupled to the rotating shaft, a sealing element coupled to a seal housing, and a stator interface statically connected to the fixed housing and positioned axially between the seal housing and the fixed housing; and a damper disposed between the seal housing and the stator interface, wherein the stator interface comprises a damper arm and the damper arm extends axially alongside and radially outside of the seal housing, wherein the seal housing is axially and radially movable relative to the runner and the fixed housing, and wherein the damper is resistant to movement of the seal housing relative to the runner in an axial direction and a radial direction.

11. The turbomachine of claim 10, wherein the damper comprises one or more viso-elastic rods, wherein the damper extends axially from the stator interface and is positioned radially outwards from the seal housing, and wherein the viso-elastic rods extend radially between the damper arm and the seal housing.

12. The turbomachine of claim 11, wherein the one or more viso-elastic rods comprise a row of viso-elastic rods spaced apart axially from each other between the damper arm and the seal housing.

13. The turbomachine of claim 12, wherein the damper further comprises one or more additional rows of viso-elastic rods spaced apart axially from each other between the damper arm and the seal housing, and wherein the rows of viso-elastic rods are spaced apart circumferentially.

14. The turbomachine of claim 10, wherein the damper comprises an elastomeric ring disposed between the damper arm and the seal housing.

15. The turbomachine of claim 14, wherein the elastomeric ring sits within a circumferentially extending groove that bounds the elastomeric ring in both axial directions.

16. The turbomachine of claim 10, wherein the turbomachine further comprises a piston ring disposed radially outwards of and circumferentially around the seal housing, and wherein the damper comprises a piston element extending radially inwards from the damper arm, and wherein the piston ring has a corresponding radially extending groove that receives the piston.

17. The turbomachine of claim 10, wherein the damper comprises one or more tongues extending radially inwards from the damper arm and the seal housing comprises one or more axially extending grooves that receive the one or more tongues.

18. The turbomachine of claim 17, wherein the damper comprises a plurality of tongues circumferentially spaced apart from each other, and the seal housing comprises a corresponding number of axially extending grooves that receive the plurality of tongues.

19. The turbomachine of claim 10, wherein the damper arm comprises an axially extending first member, an axially extending second member disposed radially outwards of the axially extending first member, a gap between the axially extending first member and the axially extending second member, and an elastomeric layer deposited in the gap.

---