

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400328
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Wang; Hsiang-Chen et al.

Method for deleting redundant images of endoscope

Abstract

The present application related to a method for deleting redundant images of an endoscope. Firstly, a host receives an input image datum from an endoscopy, hereby, capturing a plurality of corresponded input images from the input image data. Next, a plurality of dimension reduction data are obtained to operate with at least one adjacent dimension reduction datum, and then, a plurality of root mean squared error values are obtained to compare with an error threshold value. Hereby, at least one image unarrived the error threshold value are deleted to obtain a plurality of screened images. Thus, redundant images in the input image data of the endoscopy will be deleted to prevent from performing an image analysis of same images or approximated images.

Inventors: Wang; Hsiang-Chen (Chiayi, TW), Tsao; Yu-Ming (Chiayi County, TW), Mukundan; Arvind (Chiayi County, TW)

Applicant: NATIONAL CHUNG CHENG UNIVERSITY (Chiayi County, TW)

Family ID: 1000008782134

Assignee: National Chung Cheng University (Chiayi County, TW)

Appl. No.: 18/350140

Filed: July 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240386548 A1	Nov. 21, 2024

Foreign Application Priority Data

TW	112118548	May. 18, 2023
----	-----------	---------------

Publication Classification

Int. Cl.: G06K9/00 (20220101); G06T3/40 (20060101); G06T7/00 (20170101); G06V10/44 (20220101); G06V10/56 (20220101); G06V10/74 (20220101)

U.S. Cl.:

CPC G06T7/0012 (20130101); G06T3/40 (20130101); G06V10/44 (20220101); G06V10/56 (20220101); G06V10/761 (20220101); G06T2207/10036 (20130101); G06T2207/10068 (20130101)

Field of Classification Search

CPC: G06K (9/00); G06T (7/00); H04N (23/843)

USPC: 382/100; 382/103; 382/106; 382/128-132; 382/154; 382/158; 382/172; 382/181; 382/199; 382/219; 382/224; 382/254; 382/285-291; 382/305; 382/321; 600/111; 600/332; 348/E9.005; 378/4; 378/21

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0307116	12/2011	Lansel	348/E9.005	H04N 23/843
2015/0374210	12/2014	Durr	600/111	A61B 1/000096
2016/0299170	12/2015	Ito	N/A	G02B 23/26
2024/0212811	12/2023	Vogler	N/A	G06N 3/0455
2024/0386548	12/2023	Wang	N/A	G06T 7/0012
2025/0184584	12/2024	Liang	N/A	G01J 3/2823

OTHER PUBLICATIONS

De-redundancy in wireless capsule endoscopy video sequences using correspondence matching and motion analysis Libin Lan1,2,3 · Chunxiao Ye2,3 · Chao Liao2,3 · Chengliang Wang2,3 · Xin Feng1 (Year: 2024). cited by examiner

Primary Examiner: Azarian; Seyed H

Attorney, Agent or Firm: Rosenberg, Klein & Lee

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to a method for image processing, especially to a method for deleting redundant images of endoscopes.

BACKGROUND OF THE INVENTION

(2) Most of medical techniques for disease diagnosis available now depend on a single type of indicator or a piece of information such as body temperature, blood pressure, and body scan images. For example, in order to detect serious diseases such as cancer, the most common medical device used now is image-based equipment including X-ray, computer tomography (CT) scan, nuclear magnetic resonance (NMR) imaging, etc. Various combinations of these techniques are

useful in disease diagnosis in some degrees. Yet early detection of the serious diseases is not so accurate, reliable, effective and economical when the above equipment is used alone. Moreover, most of the devices are invasive and having larger volume such as those using X-ray, CT, and NMR imaging techniques. Thus endoscopes have been developed for observation of lesions on digestive organs or gastrointestinal tract.

(3) The endoscope is a medical instrument able to enter human body through many different ways and used to observe the inside of the body. The endoscopes have been used widely in a variety of medical applications and have significant impact on the field because the endoscope can be inserted into body cavities unable to be observed directly and capturing images therein. An endoscopy is an examination procedure using the endoscope. Some specially designed endoscopes such as cystoscope, gastroscope, colonoscope, bronchoscope, laparoscope, and arthroscopy are used to perform surgical procedures besides imaging capture. For example, esophagus is a tubular organ which connects the pharynx to the stomach for sending food ingested through the mouth to the stomach. The normal esophageal mucosa includes multiple layers of squamous epithelial cells with thickness of 200-500 μm . The multiple layers consist of epithelium (EP), lamina propria mucosae (LPM), muscularis mucosae (MM), submucosa (SM), and muscularis propria (MP) from top to bottom. A gastrointestinal endoscope is inserted toward the stomach to observe esophagus and deal with lesions on the esophagus.

(4) Furthermore, detection of esophageal diseases at early stage is not easy. Besides nearly no symptoms, a part of people with subtle changes such as a bit change in colors of the tissue are unable to be identified even using endoscopic examination. Thus a large amount of patients with early-stage esophageal lesions are unable to be diagnosed and thus the treatment is delayed. In order to detect lesions which are not easy to spot, several techniques including Lugol chromoendoscopy, narrow band image (NBI), and magnifying endoscopy have been developed.

(5) However, images captured during each time of the endoscopic examination, often over seventy-five thousand images, and this a huge amount of data is produced. Even the resolution of 640×480 pixels is used to avoid too much data in image files, computation of large amount of data is still a problem while using the endoscopic examination for image recognition.

(6) In order to solve the above problem, the present invention provides a method for deleting redundant images of endoscopes. A host retrieves a plurality of input images from input image data. Then a plurality of corresponding dimensionality reduction feature data is obtained after dimensionality reduction. Next the respective dimensionality reduction feature data is compared with at least one adjacent dimensionality reduction feature data to get a plurality of root-mean-square error (RMSE) values. Then the plurality of RMSE values are compared with an error threshold value to obtain an error comparison result. Later images with the RMSE values not reaching the error threshold value are removed according to the error comparison result to get a plurality of screened images. Lastly the corresponding input images of the input image data are retained according to the screened images. Thereby the problem of huge amount of data needs to be processed during image recognition can be solved.

SUMMARY

(7) Therefore, it is a primary object of the present invention to provide a method for deleting redundant images of endoscopes in which a plurality of dimensionality reduction feature data is obtained by a host executing dimensionality reduction on a plurality of input images. Then the host compares the respective dimensionality reduction feature data with at least one adjacent dimensionality reduction feature data to get a plurality of root-mean-square error (RMSE) values. Next the RMSE values are compared with an error threshold value to obtain a plurality of screened images. Then the input images are modified according to the screened images and redundant images of input image data are removed so as to avoid the issue of huge amount of data obtained during image recognition.

(8) In order to achieve the above object, a method for deleting redundant images of endoscopes

includes a plurality of steps. First a host obtains an input image data of an endoscope. Then the host retrieves a plurality of input images from the input image data and runs certain steps to get a plurality of dimensionality reduction feature data. The input images are converted into a plurality of hyperspectral images according to a hyperspectral reference data. Then a principal component analysis (PCA) is executed to generate a plurality of dimensionality reduced images according to the hyperspectral images. Next an image analysis is performed on the dimensionality reduced images to get a plurality of dimensionality reduction feature data. After getting the dimensionality reduction feature data, the host performs an error calculation between each of the dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data and at least one of the adjacent dimensionality reduced feature data to get a plurality of root-mean-square error (RMSE) values. Then the host compares the plurality of RMSE values with an error threshold value to obtain an error comparison result. Later the host deletes at least one of the dimensionality reduced images corresponding to at least one of the RMSE values not reaching the error threshold value according to the error comparison result to get a plurality of screened images. Lastly the host modifies the input image data according to the screened images. Thereby redundant images in the input image data can be removed automatically and the problem of huge amount of data which needs to be processed during image recognition can be solved.

(9) Preferably, the input image data is a static image data or a dynamic image data.

(10) Preferably, in the step of retrieving a plurality of input images from the input image data, the host retrieves at least a part of image data from the input image data and converts the image data into frames to get the input images.

(11) Preferably, the hyperspectral reference data is corresponding to the endoscope.

(12) Preferably, in the step of executing a principal component analysis (PCA) to generate a plurality of dimensionality reduced images according to the hyperspectral images, the host converts the hyperspectral images into a plurality of gray-scale images and reduces resolution to generate the plurality of dimensionality reduced images.

(13) Preferably, in the step of performing an image analysis on the dimensionality reduced images to get a plurality of dimensionality reduction feature data, the host performs a feature extraction according to a plurality of feature points and an analysis vector of the dimensionality reduced images to get the corresponding dimensionality reduced feature data according to the dimensionality reduced images.

(14) Preferably, in the step of getting a plurality of root-mean-square error (RMSE) values by comparing each of the dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data with at least one of the adjacent dimensionality reduced feature data to get a plurality of RMSE values, the host compares the respective dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data with at least the previous one adjacent dimensionality reduced feature data to get the plurality of RMSE values.

(15) Preferably, in the step of getting a plurality of root-mean-square error (RMSE) values by comparing each of the dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data with at least one of the adjacent dimensionality reduced feature data to get a plurality of RMSE values, the host compares the respective dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data with at least the previous one and the next one adjacent dimensionality reduced feature data to get the plurality of root-mean-square error (RMSE) values.

(16) Preferably, in the step of comparing the plurality of RMSE values with an error threshold value to obtain an error comparison result, the host reads the error threshold value stored in a storage unit or receives the error threshold value input by an input device.

(17) Preferably, in the step of modifying the input image data according to the screened images, according to an order of the screened images corresponding to the input images, the host retains a part of the input images in the input image data and deletes the rest of the input images.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a flow chart showing steps of a method for deleting redundant images of endoscopes of a first embodiment according to the present invention;
- (2) FIG. 2A-2H are schematic drawings showing a part of steps of the first embodiment according to the present invention;
- (3) FIG. 3 is a schematic drawing showing how root-mean-square error (RMSE) values are obtained of the first embodiment according to the present invention;
- (4) FIG. 4 is a schematic drawing showing how root-mean-square error (RMSE) values are obtained of a second embodiment according to the present invention;
- (5) FIG. 5 is a schematic drawing a system of a third embodiment according to the present invention;
- (6) FIG. 6 is a schematic drawing a system of a fourth embodiment according to the present invention;
- (7) FIG. 7 is a curve chart showing the third embodiment and the fourth embodiment after removal of redundant images by an embodiment according to the present invention.

DETAILED DESCRIPTION

- (8) In order to make the structure and characteristics as well as the effectiveness of the present application to be further understood and recognized, the detailed description of the present application is provided as follows along with embodiments and accompanying figures.
- (9) The input image data of the endoscopes needs a huge amount of computation and this further leads to difficulty in image processing and recognition. Thus a method for deleting redundant images of endoscopes is provided by the present invention to solve the problem.
- (10) Features of a method for deleting redundant images of endoscopes according to the present invention together with a system used in combination with the method are further provided in the following embodiments.
- (11) Refer to FIG. 1, a method for deleting redundant images of endoscopes according to the present invention has the following steps. Step S10: obtaining input image data of an endoscope; Step S12: retrieving input images from the input image data; Step S14: converting the input images into hyperspectral images according to hyperspectral reference data; Step S16: performing a principal component analysis (PCA) to generate a plurality of dimensionality reduced images according to the hyperspectral images; Step S18: performing an image analysis on the dimensionality reduced images to get dimensionality reduction feature data; Step S20: performing error calculation between each of the dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data and at least one of the adjacent dimensionality reduced feature data to get root-mean-square error (RMSE) values; Step S22: comparing the RMSE values with an error threshold value and deleting the dimensionality reduced images with the RMSE values not reaching the error threshold value to get screened images; Step S24: modifying the input image data according to the screened images.
- (12) Refer to FIG. 2A-2H, a detection system 1 which is used in combination with the method for deleting redundant images of endoscopes according to the present invention includes a host 10 and an endoscope 20. In this embodiment, the host 10 is a main computer which consists of a processing unit 12, a memory 14, and a storage unit 16. But the host 10 is not limited to the main computer. It can also be a server, a laptop computer, a tablet computer, or an electronic with basic

arithmetic and logic operation. A database **30** is built in the storage unit **16**, but not limited. The storage unit **16** can be an external storage unit and that means the database **30** is arranged outside the host **10**. The host **10** executes a de-redundancy program P by the processing unit **12**. The endoscope **20** is a device used to detect organs and tissues in human bodies such as cystoscope, gastroscope, colonoscope, bronchoscope, and laparoscope.

(13) As shown in FIG. 2A, in the step **S10**, the host **10** is used to read an input image data **202** captured by the endoscope **20**. The input image data **202** is a static image data or a dynamic image data. The input image data **202** can be a white light image stored in the database **30**. In this embodiment, the endoscope **20** gets corresponding white light images by OLYMPUS EVIS LUCERA CV-260 SL endoscopy system. Refer to FIG. 2A, in the step **S12**, the host **10** further retrieves a plurality of input images **204** from the input image data **202**. The host **10** retrieves at least a part of image data from the input image data **202** and converts the image data into frames to get the input images **204**. In this embodiment, the input images **204** are the white light images captured by the endoscope **20**.

(14) As shown in FIG. 2B, the host **10** runs the step **S14**. The host **10** reads a hyperspectral reference data REF from the database **30** according to the input image data **202** and then converts the input images **204** into hyperspectral images **206**. That means Visible Hyperspectral Algorithm (VIS-HAS) is used to compute the input images **204** captured by the endoscope **20** for getting the hyperspectral images **206** being converted from general color space (color space of the captured image) to XYZ color space (CIE 1931 XYZ Color space) such as from sRGB to XYZ color space. The hyperspectral imaging information in the present invention is corresponding to visible wavelengths of visible Hyperspectral Algorithm and 24 Color Checkers (X-Rite Classic). For example, the 24 color checkers includes white, black, four neutral grays, blue, green, red, yellow, magenta, cyan, orange, purplish blue, moderate red, purple, yellow green, orange yellow, dark skin, light skin, blue sky, foliage, blue flower, and bluish green. The hyperspectral reference data REF is corresponding to the above input image data **202** captured by the endoscope and composed of a plurality of color matching functions (CMF) corresponding to the 24 Color Checkers, a correction matrix and a conversion matrix.

(15) For hyperspectral conversion, first the input image data **202** is converted into the XYZ color space to get spectral value of the XYZ color space [XYZ Spectrum]. Use correction matrix C in the following equation (5) to perform correction of endoscopic images. For example, nonlinear response and dark current of the endoscope, inaccurate color separation and color shift of filters (such as white balance) need to be corrected. Thereby the spectral value of the XYZ color space [XYZ Spectrum] is corrected. The corrected X, Y, and Z values [XYZCorrect] are obtained. For example, the average error value of [XYZCorrect] and [XYZSpectrum] in the white light images is 1.40.

(16) As shown in FIG. 2C, the host **10** runs the step **S16**. Carry out principal component analysis (PCA) **102** on the hyperspectral images **206** obtained in the step **S14** for simplifying image values and removing the image values with lower changes. Then perform simplification according to corresponding eigen vectors of the hyperspectral images **206** to generate a plurality of dimensionality reduced images **208**. For example, the following equation (1) is the PCA equation.

$$(17) \quad y_i = a_{j1}(x_{1i} - \bar{x}_1) + a_{j2}(x_{2i} - \bar{x}_2) + \dots + a_{jn}(x_{ni} - \bar{x}_n) \quad \text{equation}(1)$$

(18) x_{1i} to x_{ni} represent spectrum intensity value of the first to the nth wavelength;  represent expected value of the spectrum (average spectrum intensity) of the first to the nth wavelength; a_{j1} to a_{jn} represent eigen vector coefficient of a covariance matrix giving the covariance of the spectrum. For example, PCA **102** is used for dimensionality reduction of high dimensional spectral information and only the first three dimensions are obtained to reduce computational complexity. Generally, color images are converted into gray-scale images which are decolorized so that computational complexity is further

reduced. At the same time, the host **10** can further reduce resolution of the images. For example, a corresponding resolution of the hyperspectral images **206** can be reduced from 640×480 pixels to 128×128 pixels by using the PCA **102**. Or the resolution can be reduced with certain magnification such as one half so that the corresponding resolution of the hyperspectral images **206** is reduced from 640×480 pixels to 320×240 pixels to get the dimensionality reduced images **208**.

(19) As shown in FIG. 2D, the host **10** runs the step **S18**, perform an image analysis and computing **104** on the dimensionality reduced images **208** for feature extraction of feature points in the dimensionality reduced images **208**. Then a plurality of dimensionality reduced feature data **210** is extracted and obtained according to the dimensionality reduced images **208**. For example, the host **10** uses an analysis vector C to analyze the dimensionality reduced images **208** and then get the dimensionality reduced feature data **210**.

(20) As shown in FIG. 2E, in the step **S20**, the processing unit **12** of the host **10** executes the de-redundancy program P and makes comparison of the dimensionality reduced feature data **210** corresponding to the input image **204**. In this embodiment, each of the dimensionality reduced feature data **210** is compared with one of the adjacent dimensionality reduced feature data to get a plurality of root-mean-square error (RMSE) values **212**. As shown in FIG. 3, the dimensionality reduced feature data **210** includes a first feature data **2101**, a second feature data **2102**, a third feature data **2103** . . . , and a Nth feature data **210N**. The host **10** compares the first feature data **2101** with the second feature data **2102** to get a first RMSE value **2121**. The host **10** compares the second feature data **2102** with the third feature data **2103** to get a second RMSE value **2122**. The host **10** compares the third feature data **2103** with the fourth feature data **2104** to get a third RMSE value **2123**. Thereby the N-1th feature data **210** (N-1) and the Nth feature data **210N** are compared to get a N-1th RMSE value **212** (N-1). The first RMSE value **2121** is root-mean-square error (RMSE) between the first feature data **2101** and the second feature data **2102**. The second RMSE value **2122** is root-mean-square error (RMSE) between the second feature data **2102** and the third feature data **2103**. The third RMSE value **2123** is root-mean-square error (RMSE) between the third feature data **2103** and the fourth feature data **2104**. The N-1th RMSE value **212** (N-1) is root-mean-square error (RMSE) between the N-1th feature data **210** (N-1) and the Nth feature data **210N**.

(21) The RMSE obtained by comparison of the dimensionality reduced feature data is calculated by the following equation (2).

$$(22) \quad RMSE = \frac{\sqrt{\begin{aligned} &.Math_{n=1}^{\infty} (((redA(x_n, y_n)) - (redB(x_n, y_n)))^2) + \\ &.Math_{n=1}^{\infty} (((blueA(x_n, y_n)) - (blueB(x_n, y_n)))^2) + \\ &.Math_{n=1}^{\infty} (((greenA(x_n, y_n)) - (greenB(x_n, y_n)))^2) \end{aligned}}}{3 \times x_n \times y_n} \quad \text{equation(2)}$$

(23) In the step **S22**, as shown in FIG. 2F, the host **10** reads an error threshold value TH from the database **30** and then compares the RMSE values **212** obtained in the above step **S20** with the error threshold value TH to get an error comparison result **214**. For example, the first RMSE value **2121**, the second RMSE value **2122**, the third RMSE value **2123**, the fourth RMSE value, and the fifth RMSE value of the RMSE values **212** are respectively 1, 1, 2, 3, and 4 and corresponding to the second dimensionality reduction feature data, the third dimensionality reduction feature data, the fourth dimensionality reduction feature data, the fifth dimensionality reduction feature data, and the sixth dimensionality reduction feature data. Since the error threshold value TH is 3, the second to the fourth dimensionality reduction feature data are marked as the dimensionality reduction feature data not reaching the error threshold value TH and this is used as the error comparison result **214**.

(24) Refer to FIG. 2G, the host **10** deletes dimensionality reduced images **208** corresponding to the RMSE values **212** not reaching the error threshold value TH according to the error comparison result **214** obtained in the step **S22** so as to generate a plurality of screened images **216** whose number is smaller than the number of the input images **204** or the number of the dimensionality

reduced images **208**. For example, the error comparison result **214** in the step **S22** is that the second to the fourth dimensionality reduction feature data are marked as the dimensionality reduction feature data not reaching the error threshold value TH. Thereby the host **10** deletes the dimensionality reduced images **208** corresponding to the second to the fourth dimensionality reduction feature data to generate the corresponding screened images **216**.

(25) In the step **S24**, as shown in FIG. **2H**, the de-redundancy program P modifies the input image data **202** according to the screened images **216** generated in the step **S24**. According to an order the screened images **216** correspond to the input images **204**, the de-redundancy program P retains a part of the input images **204** in the input image data **202** and deletes the rest of the input images **204**. That means the input images **204** corresponding to the screened images **216** are categorized into a group of target images TA by the de-redundancy program P while the input images **204** without corresponding to the screened images **216** are categorized into a group of non-target images NTA and then the NTA is deleted. For example, the screened images **216** are corresponding to the first to the fifth input images of the input image data **202** and the de-redundancy program P marks the first to the fifth input images of the input image data **202** as the target images TA while the rest of the input images **204** of the input image data **202** are labelled as the non-target images NTA. Thereby the non-target images NTA are removed from the input image data **202** by the de-redundancy program P. Therefore, redundant images of the input image data **202** are deleted.

(26) The above comparison of the RMSE values is only an embodiment of the present invention, not intended to limit the present invention. As shown in FIG. **4**, computation of RMSE values of a second embodiment of the present invention is provided. The dimensionality reduced feature data **210** includes a first feature data **2101**, a second feature data **2102**, a third feature data **2103** . . . , and a (N+1)th feature data **210** (N+1). The host **10** compares the first feature data **2101** and the second feature data **2102** with the third feature data **2103** to get a first root-mean-square error (RMSE) value **2121**. The host **10** compares the second feature data **2102** and the third feature data **2103** to the fourth feature data **2104** to get a second root-mean-square error (RMSE) value **2122**. The host **10** compares the third feature data **2103** and the fourth feature data **2104** to the fifth feature data **2105** to get a third root-mean-square error (RMSE) value **2123**. Thereby the N-1th feature data **210** (N-1), the Nth feature data **210N**, and the (N+1)th feature data **210** (N+1) are compared to get a N-1th RMSE value **212** (N-1). The first RMSE value **2121** is root-mean-square error (RMSE) among the first feature data **2101**, the second feature data **2102**, and the third feature data **2103**. The second RMSE value **2122** is root-mean-square error (RMSE) among the second feature data **2102**, the third feature data **2103**, and the fourth feature data **2104**. The third RMSE value **2123** is root-mean-square error (RMSE) among the third feature data **2103**, the fourth feature data **2104**, and the fifth feature data **2105**. Thereby the N-1th RMSE value **212** (N-1) is root-mean-square error (RMSE) among the N-1th feature data **210** (N-1), the Nth feature data **210N**, and the (N+1)th feature data **210** (N+1). More dimensionality reduced feature data **210** is computed in a similar way to get the corresponding RMSE values.

(27) The following embodiment shows actual operation conditions.

(28) As shown in FIG. **5**, in a third embodiment, a first endoscope **300** of InsightEyes EGD System sold by Insight Medical Solutions Inc. provides a first input image data **302** to a workstation **400** in which a processing unit **402** is mounted. The processing unit **402** not only runs a de-redundancy program P and reads a hyperspectral reference data REF from a database **430**, but also converts a plurality of first input images **304** of the first input image data **302** into a plurality of first hyperspectral images **306** according to the hyperspectral reference data REF. Then principal component analysis (PCA) **102** is performed to simplify the plurality of the first hyperspectral images **306** into a plurality of first dimensionality reduced images **308**. Next the processing unit **402** performs an image analysis and computing **104** to get a plurality of first dimensionality reduced feature data **310** according to a plurality of feature points in the first dimensionality reduced images **308**. Then the processing unit **402** executes the de-redundancy program P to get a

plurality of first root-mean-square error (RMSE) values **312** corresponding to the first dimensionality reduced feature data **310** by comparing each of the first dimensionality reduced feature data **310** with at least one adjacent first dimensionality reduced feature data **310**. The processing unit **402** executes the de-redundancy program P to get a first error comparison result **314** by comparison of the first RMSE values **312** with a threshold value TH. The processing unit **402** continues to run the de-redundancy program P to remove images not reaching the threshold value TH from the first dimensionality reduced images **308** according to the first error comparison result **314** and get a plurality of first screened images **316**. Later the host **10** modifies the first input image data **302** according to the first screened images **316**. That means redundant images in the first input image data **302** are deleted.

(29) As shown in FIG. 6, in a fourth embodiment, a second endoscope **500** of Olympus CV-290 system provides a second input image data **502** to a workstation **400**. A processing unit **402** of the workstation **400** not only reads a hyperspectral reference data REF from a database **430**, but also converts a plurality of second input images **504** of the second input image data **502** into a plurality of second hyperspectral images **506** according to the hyperspectral reference data REF. Then principal component analysis (PCA) **102** is executed to simplify the plurality of the second hyperspectral images **506** into a plurality of second dimensionality reduced images **508**. Next the processing unit **402** performs an image analysis and computing **104** to get a plurality of second dimensionality reduced feature data **510** according to a plurality of feature points in the second dimensionality reduced images **508**. Then the processing unit **402** executes a de-redundancy program P to get a plurality of second root-mean-square error (RMSE) values **512** corresponding to the second dimensionality reduced feature data **510** by comparing the respective second dimensionality reduced feature data **510** with at least one adjacent second dimensionality reduced feature data **510**. The processing unit **402** executes the de-redundancy program P to get a second error comparison result **514** by comparison of the second RMSE values **512** with a threshold value TH. The processing unit **402** continues to run the de-redundancy program P to remove images not reaching the threshold value TH according to the second error comparison result **514** and get a plurality of second screened images **516**. Later the host **10** modifies the second input image data **502** according to the second screened images **516**. That means redundant images in the second input image data **502** are deleted.

(30) Refer to FIG. 7, a curve chart of the number of images of the first input image data **302** of the third embodiment and the second input image data **502** of the fourth embodiment after removal of redundant images by the present invention versus error threshold value is provided. The solid-line curve represents the number of the first input images **304** left after removal of the redundant images from the first input image data **302** while the dashed-line curve represents the number of the second input images **504** left after removal of the redundant images from the second input image data **502**. An initial number of the first input images **304** of the third embodiment and an initial number of the second input images **504** of the fourth embodiment are set as 1000 pieces of images. By the de-redundancy program P with the error threshold value TH of 0-10, the number of the images in both the first input image data **302** and the second input image data **502** changes. The change is linear when the error threshold value TH is 4-8. While the error threshold value TH is larger than 8, the number of the images approaches 1. That means only the first piece of the first input images **304** and the first piece of the second input images **504** are left. When the error threshold value TH is smaller than 4, the curve showing the change of the number of the images gets flatter.

(31) In summary, the method for deleting redundant images of endoscopes according to the present invention includes a plurality of steps. First obtaining an input image data of an endoscope by a host. Then converting input images of the input image data into hyperspectral images and performing dimensionality reduction (such as PCA) on the hyperspectral images to get dimensionality reduced images. Next analyzing the dimensionality reduced images to get dimensionality reduction feature data. Then getting error values by comparing the respective

dimensionality reduction feature data with the adjacent one. Next comparing the error values with an error threshold value to get an error comparison result. Then deleting the dimensionality reduced images not reaching the error threshold value according to the error comparison result to get screened images. Lastly the input image data is modified by using the order of the screened images corresponding to the input images and redundant images of the input image data are removed. Therefore, the problem of large amount of data needs to be dealt with during image processing can be solved.

(32) Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details, and representative devices shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalent.

Claims

1. A method for deleting redundant images of endoscopes comprising the steps of: obtaining an input image data of an endoscope by a host; retrieving a plurality of input images from the input image data by the host; converting the input images into a plurality of hyperspectral images according to a hyperspectral reference data by the host; performing a principal component analysis (PCA) on the hyperspectral images by the host to generate a plurality of dimensionality reduced images; performing an image analysis and computing according to the dimensionality reduced images to get dimensionality reduction feature data by the host; performing an error calculation between each of the dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data and at least one of the adjacent dimensionality reduced feature data to get a plurality of root-mean-square error (RMSE) values by the host; comparing the RMSE values with an error threshold value and deleting the dimensionality reduced images with the RMSE values not reaching the error threshold value to get a plurality of screened images by the host; and modifying the input image data according to the screened images by the host, wherein in the step of performing a principal component analysis (PCA) on the hyperspectral images by the host to generate a plurality of dimensionality reduced images, the host converts the hyperspectral images into a plurality of gray-scale images and reduces resolution to generate the plurality of dimensionality reduced images.
2. The method as claimed in claim 1, wherein the input image data is a static image data or a dynamic image data.
3. The method as claimed in claim 1, wherein in the step of retrieving a plurality of input images from the input image data by the host, the host retrieves at least a part of image data from the input image data and converts the image data into frames to get the input images.
4. The method as claimed in claim 1, wherein the hyperspectral reference data is corresponding to the endoscope.
5. The method as claimed in claim 1, wherein in the step of performing an image analysis and computing according to the dimensionality reduced images to get dimensionality reduction feature data by the host, the host performs a feature extraction according to a plurality of feature points and an analysis vector of the dimensionality reduced images to get the corresponding dimensionality reduced feature data according to the dimensionality reduced images.
6. The method as claimed in claim 1, wherein in the step of performing an error calculation between each of the dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data and at least one of the adjacent dimensionality reduced feature data to get a plurality of RMSE values by the host, the host compares the respective dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data with at least

the previous one adjacent dimensionality reduced feature data to get the plurality of RMSE values correspondingly.

7. The method as claimed in claim 1, wherein in the step of performing an error calculation between each of the dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data and at least one of the adjacent dimensionality reduced feature data to get a plurality of RMSE values by the host, the host compares the respective dimensionality reduction feature data ranging from the second dimensionality reduction feature data to the last dimensionality reduction feature data with at least the previous one and the next one adjacent dimensionality reduced feature data to get the plurality of RMSE values.

8. The method as claimed in claim 1, wherein in the step of comparing the RMSE values with an error threshold value and deleting the dimensionality reduced images with the RMSE values not reaching the error threshold value to get a plurality of screened images by the host, the host reads the error threshold value stored in a storage unit or receives the error threshold value input by an input device.

9. The method as claimed in claim 1, wherein in the step of modifying the input image data according to the screened images by the host, the host keeps a part of the input images in the input image data and deletes the rest of the input images according to an order the screened images correspond to the input images.
