

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400398
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Vizeu Oliveira; Lana et al.

Generating and/or displaying virtual interactions with virtual objects

Abstract

Systems and techniques are described herein for displaying one or more virtual objects. For instance, a method for displaying one or more virtual objects is provided. The method may include obtaining hand-pose data indicative of a pose of a hand; obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data.

Inventors: Vizeu Oliveira; Lana (Bordeaux, FR), Gaidon; Laurent Ghislain (Peujard, FR), Rivalland; Ludovic (Cenon, FR), Aubree; Lois Corentin (Bordeaux, FR)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 1000008782096

Assignee: QUALCOMM Incorporated (San Diego, CA)

Appl. No.: 18/301849

Filed: April 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240346751 A1	Oct. 17, 2024

Publication Classification

Int. Cl.: G06T17/00 (20060101); G06F3/01 (20060101); G06T7/62 (20170101); G06T7/70 (20170101); G06T13/40 (20110101); G06V10/74 (20220101); G06V40/10 (20220101)

U.S. Cl.:

CPC **G06T17/00** (20130101); **G06F3/017** (20130101); **G06T7/62** (20170101); **G06T7/70** (20170101); **G06T13/40** (20130101); **G06V10/761** (20220101); **G06V40/11** (20220101); G06T2207/30196 (20130101)

Field of Classification Search

CPC: G06T (17/00); G06F (3/017); G06V (40/11); G06V (20/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0216060	12/2010	Weising	345/419	A63F 13/00
2013/0307875	12/2012	Anderson	345/633	A63F 13/92
2018/0165864	12/2017	Jin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3183633	12/2016	EP	N/A
2020155139	12/2019	JP	N/A

OTHER PUBLICATIONS

Dewez D., et al., “Do You Need Another Hand? Investigating Dual Body Representations During Anisomorphic 3D Manipulation”, IEEE Transactions on Visualization and Computer Graphics, IEEE, USA, vol. 28, No. 5, May 2022, pp. 2047-2057, Feb. 15, 2022, XP011905506, figures 1-9 p. 2047, left-hand col., line 1—p. 2050, left-hand col. line 18. cited by applicant

International Search Report and Written Opinion—PCT/US2024/018561—ISA/EPO—Jun. 17, 2024. cited by applicant

Prachyabrued M., et al., “Visual Feedback for Virtual Grasping”, 2014 IEEE Symposium on 3D User Interfaces (3DUI) , IEEE, Mar. 29, 2014, pp. 19-26, XP032586723, figures 1-6 p. 20, right-hand col. line 39—p. 23, right-hand col. line 27. cited by applicant

Zhang L., et al., “Using the Visuo-Haptic Illusion to Perceive and Manipulate Different Virtual Objects in Augmented Reality”, IEEE Access, IEEE, USA, vol. 9, Oct. 19, 2021, pp. 143782-143794, XP011884637, Figures 1-11 abstract, p. 143782, left-hand col. line 1—p. 143788, left-hand col. line 3. cited by applicant

Primary Examiner: Martello; Edward

Attorney, Agent or Firm: Polsinelli LLP / QUALCOMM Incorporated

Background/Summary

TECHNICAL FIELD

(1) The present disclosure generally relates to virtual interactions with virtual objects. For example, aspects of the present disclosure include systems and techniques for generating and/or displaying virtual interactions between virtual hands and virtual objects.

BACKGROUND

- (2) An extended reality (XR) (e.g., virtual reality (VR), augmented reality (AR), and/or mixed reality (MR)) system can provide a user with a virtual experience by displaying virtual content to the user). The virtual content may include a completely virtual environment (made up entirely of virtual content). Alternatively, the virtual content may provide the user with an augmented or mixed reality experience by displaying virtual content alongside with, and/or overlaid onto, a user's field of view of a real-world environment (e.g., using a see-through or pass-through XR system).
- (3) Some XR systems can facilitate interaction with XR environments. For instance, a user can use the XR system or device to interact with virtual objects in the virtual environment. In some examples, a user may play games using virtual objects (e.g., a virtual steering wheel, virtual balls, virtual sports equipment, etc.), virtually interact with other users (e.g., in a social setting, in a virtual meeting, etc.), virtually shop for items (e.g., goods, services, property, etc.), and/or experience other services in a virtual environment.

SUMMARY

(4) The following presents a simplified summary relating to one or more aspects disclosed herein. Thus, the following summary should not be considered an extensive overview relating to all contemplated aspects, nor should the following summary be considered to identify key or critical elements relating to all contemplated aspects or to delineate the scope associated with any particular aspect. Accordingly, the following summary presents certain concepts relating to one or more aspects relating to the mechanisms disclosed herein in a simplified form to precede the detailed description presented below.

(5) Systems and techniques are described for displaying one or more virtual objects. According to at least one example, a method is provided for displaying one or more virtual objects. The method includes: obtaining hand-pose data indicative of a pose of a hand; obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data. In some cases, a gesture of the virtual hand may be different from a gesture of the hand.

(6) In another example, an apparatus for displaying one or more virtual objects is provided that includes at least one memory and at least one processor (e.g., configured in circuitry) coupled to the at least one memory. The at least one processor configured to: obtain hand-pose data indicative of a pose of a hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data. In some cases, a gesture of the virtual hand may be different from a gesture of the hand.

(7) In another example, a non-transitory computer-readable medium is provided that has stored thereon instructions that, when executed by one or more processors, cause the one or more processors to: obtain hand-pose data indicative of a pose of a hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data. In some cases, a gesture of the virtual hand may be different from a gesture of the hand.

(8) In another example, an apparatus for displaying one or more virtual objects is provided. The apparatus includes: means for obtaining hand-pose data indicative of a pose of a hand; means for obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and means for displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data. In some cases, a gesture of the virtual hand may be different from a gesture of the hand.

(9) Systems and techniques are described for displaying one or more virtual objects. According to at least one example, a method is provided for displaying one or more virtual objects. The method includes: obtaining hand-pose data indicative of a pose of a hand; obtaining virtual-object data

indicative of a virtual object with which the hand is virtually interacting; and displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein a position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data.

(10) In another example, an apparatus for displaying one or more virtual objects is provided that includes at least one memory and at least one processor (e.g., configured in circuitry) coupled to the at least one memory. The at least one processor configured to: obtain hand-pose data indicative of a pose of a hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein a position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data.

(11) In another example, a non-transitory computer-readable medium is provided that has stored thereon instructions that, when executed by one or more processors, cause the one or more processors to: obtain hand-pose data indicative of a pose of a hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein a position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data.

(12) In another example, an apparatus for displaying one or more virtual objects is provided. The apparatus includes: means for obtaining hand-pose data indicative of a pose of a hand; means for obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and means for displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein a position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data.

(13) In some aspects, one or more of the apparatuses described herein is, can be part of, or can include a mobile device (e.g., a mobile telephone or so-called “smart phone”, a tablet computer, or other type of mobile device), an extended reality device (e.g., a virtual reality (VR) device, an augmented reality (AR) device, or a mixed reality (MR) device), a vehicle (or a computing device or system of a vehicle), a smart or connected device (e.g., an Internet-of-Things (IoT) device), a wearable device, a personal computer, a laptop computer, a video server, a television (e.g., a network-connected television), a robotics device or system, or other device. In some aspects, each apparatus can include an image sensor (e.g., a camera) or multiple image sensors (e.g., multiple cameras) for capturing one or more images. In some aspects, each apparatus can include one or more displays for displaying one or more images, notifications, and/or other displayable data. In some aspects, each apparatus can include one or more speakers, one or more light-emitting devices, and/or one or more microphones. In some aspects, each apparatus can include one or more sensors. In some cases, the one or more sensors can be used for determining a location of the apparatuses, a state of the apparatuses (e.g., a tracking state, an operating state, a temperature, a humidity level, and/or other state), and/or for other purposes.

(14) This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended to be used in isolation to determine the scope of the claimed subject matter. The subject matter should be understood by reference to appropriate portions of the entire specification of this patent, any or all drawings, and each claim.

(15) The foregoing, together with other features and aspects, will become more apparent upon referring to the following specification, claims, and accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Illustrative examples of the present application are described in detail below with reference to the following figures:
- (2) FIG. 1 is a diagram illustrating an example of an extended reality (XR) system, according to aspects of the disclosure;
- (3) FIG. 2 is a diagram illustrating an architecture of an example extended reality (XR) system, in accordance with some aspects of the disclosure;
- (4) FIG. 3 is a block diagram illustrating an example system for generating and/or displaying virtual interactions, according to various aspects of the present disclosure;
- (5) FIG. 4 is a diagram illustrating an example scenario including displaying virtual interactions, according to various aspects of the present disclosure;
- (6) FIG. 5 is a diagram illustrating another example scenario including displaying virtual interactions, according to various aspects of the present disclosure;
- (7) FIG. 6 is a diagram illustrating yet another example scenario including displaying virtual interactions, according to various aspects of the present disclosure;
- (8) FIG. 7 is a diagram illustrating yet another example scenario including displaying virtual interactions, according to various aspects of the present disclosure;
- (9) FIG. 8 is a diagram illustrating yet another example scenario including displaying virtual interactions, according to various aspects of the present disclosure;
- (10) FIG. 9 is a diagram illustrating yet another example scenario including displaying virtual interactions, according to various aspects of the present disclosure;
- (11) FIG. 10 is a diagram illustrating yet another example scenario including displaying virtual interactions, according to various aspects of the present disclosure;
- (12) FIG. 11 is a flow diagram illustrating an example of a process for displaying virtual interactions between virtual hands and virtual objects, in accordance with aspects of the present disclosure;
- (13) FIG. 12 is a flow diagram illustrating another example of a process for displaying virtual interactions between virtual hands and virtual objects, in accordance with aspects of the present disclosure; and
- (14) FIG. 13 illustrates an example computing-device architecture of an example computing device which can implement the various techniques described herein.

DETAILED DESCRIPTION

(15) Certain aspects of this disclosure are provided below. Some of these aspects may be applied independently and some of them may be applied in combination as would be apparent to those of skill in the art. In the following description, for the purposes of explanation, specific details are set forth in order to provide a thorough understanding of aspects of the application. However, it will be apparent that various aspects may be practiced without these specific details. The figures and description are not intended to be restrictive.

(16) The ensuing description provides example aspects only, and is not intended to limit the scope, applicability, or configuration of the disclosure. Rather, the ensuing description of the exemplary aspects will provide those skilled in the art with an enabling description for implementing an exemplary aspect. It should be understood that various changes may be made in the function and arrangement of elements without departing from the spirit and scope of the application as set forth in the appended claims.

(17) The terms “exemplary” and/or “example” are used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” and/or “example” is not necessarily to be construed as preferred or advantageous over other aspects. Likewise, the term “aspects of the disclosure” does not require that all aspects of the disclosure include the discussed feature, advantage or mode of operation.

(18) As mentioned above, extended reality (XR) (e.g., virtual reality (VR), augmented reality (AR), and/or mixed reality (MR)) system can allow a user to interact with virtual objects. For example, an XR system may include a camera that may capture images (or video) of hands of a user. The XR system may track positions of the hands (e.g., through successive images) and/or detect gestures of the hands. The XR system may take the positions and the gestures as inputs and determine desired user interactions based on the position and gestures. For example the user may reach toward a virtual object and make a pinching gesture. The XR system may interpret the reach and the pinching gestures as the user intending to grab the virtual object. In some cases, the XR system may display virtual hands grabbing the virtual object (e.g., to give the user an impression that they are holding the virtual object).

(19) However, in some cases, a user's gesture may not match the virtual object. For example, a user may observe a virtual object as small (e.g., based on the object being distant from the user). To grab the virtual object, the user may reach with fingers to pinch the virtual object (e.g., based on the object appearing as small in the user's field of view). If the virtual object has a handle to be grasped by a hand, for example, the pinch may not match the virtual object. The mismatch between the pinch and the virtual object may detract from the virtual experience by making the virtual experience appear less real. As another example, a virtual object may simulate a heavy object. A user, not lifting an actual object, may initiate an interaction by reaching out to grab the virtual object and quickly moving the virtual object. The virtual object moving quickly, unaffected by inertia and/or gravity, may detract from the virtual experience by making the virtual experience appear less real.

(20) Systems, apparatuses, methods (also referred to as processes), and computer-readable media (collectively referred to herein as “systems and techniques”) are described herein for generating and/or displaying virtual interactions with virtual objects. For instance, the systems and techniques described herein may obtain hand-pose data (e.g., from a hand tracker) indicative of a pose of a hand. The hand-pose data may include position information indicative of a position of the hand and gesture information indicative of a gesture of the hand (e.g., a pinch, a grab, etc.). The systems and techniques may obtain virtual-object data (e.g., from a virtual-content generator) indicative of a virtual object with which the hand is virtually interacting or initiating a virtual interaction. The systems and techniques may generate for display, and/or display, a virtual hand interacting with the virtual object. The virtual hand may exhibit a position and a gesture. One or both of the position of the virtual hand or the gesture of the virtual hand may be based on the virtual-object data. In some cases, one or both of the position of the virtual hand and/or the gesture of the virtual hand may not correspond to the position of the hand or the gesture of the hand respectively.

(21) As a first example, the gesture of the virtual hands may be based on the virtual-object data. For example, if a user reaches a hand to pinch a virtual steering wheel, a virtual hand may be displayed grasping the steering wheel based on an interaction pose of the steering wheel. In the present disclosure, the term “interaction pose” may refer to a virtual interaction that matches the virtual object. For example, the interaction pose of a virtual steering wheel may indicate that the virtual steering wheel is to be grasped by one or two virtual hands, with virtual palms facing away from the user. The position of the virtual hands may be based on the position of the hands of the user (e.g., such that as the user moves their hands, the virtual hands move to match the position of the user's hands).

(22) As a second example, the position of the virtual hands may be based on the virtual-object data. For example, if a user reaches to grab a virtual bowling ball, then quickly moves their hand upward, a virtual hand may be displayed grabbing the virtual bowling ball. The virtual hand and the virtual bowling ball may then move more slowly than the real hand to move upward (e.g., simulating inertia and/or gravity based on a simulated weight of the virtual bowling ball).

(23) By displaying virtual interactions based on characteristics of virtual objects, systems and techniques may improve users' virtual experiences. For example, by displaying a virtual hand that

virtually interacts with a virtual object in a way that matches the virtual object, the virtual interaction with the virtual object may appear to be more real to a user than if the virtual hand were displayed exhibiting a gesture that does not match the virtual object. As another example, by displaying the movement of a virtual hand and virtual object in a way that simulates weight of the virtual object, the virtual object appear to be more real to the user than if the virtual object were to move around without any simulated weight.

(24) Various aspects of the application will be described with respect to the figures below.

(25) FIG. 1 is a diagram illustrating an example of an extended reality (XR) system **100**, according to aspects of the disclosure. As shown, XR system **100** includes an XR device **102**, a companion device **104**, and a communication link **106** between XR device **102** and companion device **104**. In some cases, XR device **102** may generally implement display, image-capture, and/or view-tracking aspects of extended reality, including virtual reality (VR), augmented reality (AR), mixed reality (MR), etc. In some cases, companion device **104** may generally implement computing aspects of extended reality. For example, XR device **102** may capture images of an environment of a user **108** and provide the images to companion device **104** (e.g., via communication link **106**). Companion device **104** may render virtual content (e.g., related to the captured images of the environment) and provide the virtual content to XR device **102** (e.g., via communication link **106**). XR device **102** may display the virtual content to a user **108** (e.g., within a field of view **110** of user **108**). In other cases, XR device **102** and companion device **104** may be included in the same device, or XR device **102** and companion device **104** may be directly connected.

(26) Generally, XR device **102** may display virtual content to be viewed by a user **108** in field of view **110**. In some examples, XR device **102** may include a transparent surface (e.g., optical glass) such that virtual objects may be displayed on (e.g., by being projected onto) the transparent surface to overlay virtual content on real-world objects viewed through the transparent surface (e.g., in a see-through configuration). In some cases, XR device **102** may include a camera and may display both real-world objects (e.g., as frames or images captured by the camera) and virtual objects overlaid on the displayed real-world objects (e.g., in a pass-through configuration). In various examples, XR device **102** may include aspects of a virtual reality headset, smart glasses, a live feed video camera, a GPU, one or more sensors (e.g., such as one or more inertial measurement units (IMUs), image sensors, microphones, etc.), one or more output devices (e.g., such as speakers, display, smart glass, etc.), etc.

(27) Companion device **104** may render the virtual content to be displayed by XR device **102**. In some examples, companion device **104** may be, or may include, a smartphone, laptop, tablet computer, personal computer, gaming system, a server computer or server device (e.g., an edge or cloud-based server, a personal computer acting as a server device, or a mobile device acting as a server device), any other computing device and/or a combination thereof.

(28) In some cases, communication link **106** may be a wireless connection according to any suitable wireless protocol, such as, for example, Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.15, or Bluetooth®. In some cases, communication link **106** may be a direct wireless connection between XR device **102** and companion device **104**. In other cases, communication link **106** may be through one or more intermediary devices, such as, for example, routers or switches and/or across a network. In other cases (e.g., cases in which XR device **102** and companion device **104** are included in the same device, or XR device **102** and companion device **104** are directly connected) communication link **106** may be a wired connection (e.g., through a bus or printed circuit board).

(29) FIG. 2 is a diagram illustrating an architecture of an example extended reality (XR) system **200**, in accordance with some aspects of the disclosure. XR system **200** may execute XR applications and implement XR operations.

(30) In this illustrative example, XR system **200** includes one or more image sensors **202**, an accelerometer **204**, a gyroscope **206**, storage **208**, an input device **210**, a display **212**, Compute

components **214**, an XR engine **224**, an image processing engine **226**, a rendering engine **228**, and a communications engine **230**. It should be noted that the components **202-230** shown in FIG. 2 are non-limiting examples provided for illustrative and explanation purposes, and other examples may include more, fewer, or different components than those shown in FIG. 2. For example, in some cases, XR system **200** may include one or more other sensors (e.g., one or more inertial measurement units (IMUs), radars, light detection and ranging (LIDAR) sensors, radio detection and ranging (RADAR) sensors, sound detection and ranging (SODAR) sensors, sound navigation and ranging (SONAR) sensors, audio sensors, etc.), one or more display devices, one or more other processing engines, one or more other hardware components, and/or one or more other software and/or hardware components that are not shown in FIG. 2. While various components of XR system **200**, such as image sensor **202**, may be referenced in the singular form herein, it should be understood that XR system **200** may include multiple of any component discussed herein (e.g., multiple image sensors **202**).

(31) Display **212** may be, or may include, a glass, a screen, a lens, a projector, and/or other display mechanism that, in some cases, allows a user to see the real-world environment and also allows XR content to be overlaid, overlapped, blended with, or otherwise displayed thereon. In other cases, display **212** may be a display that doesn't allow the user to see the real-world environment (e.g., a display filling most, or all, of a field of view of the user). Display **212** may include separate portions (e.g., one for each eye) for stereoscopic viewing.

(32) XR system **200** may include, or may be in communication with, (wired or wirelessly) an input device **210**. Input device **210** may include any suitable input device, such as a touchscreen, a pen or other pointer device, a keyboard, a mouse, a button or key, a microphone for receiving voice commands, a gesture input device for receiving gesture commands, a video game controller, a steering wheel, a joystick, a set of buttons, a trackball, a remote control, any other input device discussed herein, or any combination thereof. In some cases, image sensor **202** may capture images (e.g., images of hands of a user) that may be processed for interpreting gesture commands.

(33) XR system **200** may also communicate with one or more other electronic devices (wired or wirelessly). For example, communications engine **230** may be configured to manage connections and communicate with one or more electronic devices. In some cases, communications engine **230** may correspond to communication interface **1326** of FIG. 13.

(34) In some implementations, image sensors **202**, accelerometer **204**, gyroscope **206**, storage **208**, display **212**, compute components **214**, XR engine **224**, image processing engine **226**, and rendering engine **228** may be part of the same computing device. For example, in some cases, image sensors **202**, accelerometer **204**, gyroscope **206**, storage **208**, display **212**, compute components **214**, XR engine **224**, image processing engine **226**, and rendering engine **228** may be integrated into an HMD, extended reality glasses, smartphone, laptop, tablet computer, gaming system, and/or any other computing device. However, in some implementations, image sensors **202**, accelerometer **204**, gyroscope **206**, storage **208**, display **212**, compute components **214**, XR engine **224**, image processing engine **226**, and rendering engine **228** may be part of two or more separate computing devices. For instance, in some cases, some of the components **202-230** may be part of, or implemented by, one computing device and the remaining components may be part of, or implemented by, one or more other computing devices. For example, such as in a split perception XR system, XR system **200** may include a first device (e.g., an HMD), including display **212**, image sensor **202**, accelerometer **204**, gyroscope **206**, and/or one or more compute components **214**. XR system **200** may also include a second device including additional compute components **214** (e.g., implementing XR engine **224**, image processing engine **226**, rendering engine **228**, and/or communications engine **230**). In such an example, the second device may generate virtual content based on information or data (e.g., images, sensor data such as measurements from accelerometer **204** and gyroscope **206**) and may provide the virtual content to the first device for display at the first device. The second device may be, or may include, a smartphone, laptop, tablet

computer, personal computer, gaming system, a server computer or server device (e.g., an edge or cloud-based server, a personal computer acting as a server device, or a mobile device acting as a server device), any other computing device and/or a combination thereof.

(35) Storage **208** may be any storage device(s) for storing data. Moreover, storage **208** may store data from any of the components of XR system **200**. For example, storage **208** may store data from image sensor **202** (e.g., image or video data), data from accelerometer **204** (e.g., measurements), data from gyroscope **206** (e.g., measurements), data from compute components **214** (e.g., processing parameters, preferences, virtual content, rendering content, scene maps, tracking and localization data, object detection data, privacy data, XR application data, face recognition data, occlusion data, etc.), data from XR engine **224**, data from image processing engine **226**, and/or data from rendering engine **228** (e.g., output frames). In some examples, storage **208** may include a buffer for storing frames for processing by compute components **214**.

(36) Compute components **214** may be, or may include, a central processing unit (CPU) **216**, a graphics processing unit (GPU) **218**, a digital signal processor (DSP) **220**, an image signal processor (ISP) **222**, and/or other processor (e.g., a neural processing unit (NPU) implementing one or more trained neural networks). Compute components **214** may perform various operations such as image enhancement, computer vision, graphics rendering, extended reality operations (e.g., tracking, localization, pose estimation, mapping, content anchoring, content rendering, predicting, etc.), image and/or video processing, sensor processing, recognition (e.g., text recognition, facial recognition, object recognition, feature recognition, tracking or pattern recognition, scene recognition, occlusion detection, etc.), trained machine-learning operations, filtering, and/or any of the various operations described herein. In some examples, compute components **214** may implement (e.g., control, operate, etc.) XR engine **224**, image processing engine **226**, and rendering engine **228**. In other examples, compute components **214** may also implement one or more other processing engines.

(37) Image sensor **202** may include any image and/or video sensors or capturing devices. In some examples, image sensor **202** may be part of a multiple-camera assembly, such as a dual-camera assembly. Image sensor **202** may capture image and/or video content (e.g., raw image and/or video data), which may then be processed by compute components **214**, XR engine **224**, image processing engine **226**, and/or rendering engine **228** as described herein.

(38) In some examples, image sensor **202** may capture image data and may generate images (also referred to as frames) based on the image data and/or may provide the image data or frames to XR engine **224**, image processing engine **226**, and/or rendering engine **228** for processing. An image or frame may include a video frame of a video sequence or a still image. An image or frame may include a pixel array representing a scene. For example, an image may be a red-green-blue (RGB) image having red, green, and blue color components per pixel; a luma, chroma-red, chroma-blue (YCbCr) image having a luma component and two chroma (color) components (chroma-red and chroma-blue) per pixel; or any other suitable type of color or monochrome image.

(39) In some cases, image sensor **202** (and/or other camera of XR system **200**) may be configured to also capture depth information. For example, in some implementations, image sensor **202** (and/or other camera) may include an RGB-depth (RGB-D) camera. In some cases, XR system **200** may include one or more depth sensors (not shown) that are separate from image sensor **202** (and/or other camera) and that may capture depth information. For instance, such a depth sensor may obtain depth information independently from image sensor **202**. In some examples, a depth sensor may be physically installed in the same general location or position as image sensor **202**, but may operate at a different frequency or frame rate from image sensor **202**. In some examples, a depth sensor may take the form of a light source that may project a structured or textured light pattern, which may include one or more narrow bands of light, onto one or more objects in a scene. Depth information may then be obtained by exploiting geometrical distortions of the projected pattern caused by the surface shape of the object. In one example, depth information may be

obtained from stereo sensors such as a combination of an infra-red structured light projector and an infra-red camera registered to a camera (e.g., an RGB camera).

(40) XR system **200** may also include other sensors in its one or more sensors. The one or more sensors may include one or more accelerometers (e.g., accelerometer **204**), one or more gyroscopes (e.g., gyroscope **206**), and/or other sensors. The one or more sensors may provide velocity, orientation, and/or other position-related information to compute components **214**. For example, accelerometer **204** may detect acceleration by XR system **200** and may generate acceleration measurements based on the detected acceleration. In some cases, accelerometer **204** may provide one or more translational vectors (e.g., up/down, left/right, forward/back) that may be used for determining a position or pose of XR system **200**. Gyroscope **206** may detect and measure the orientation and angular velocity of XR system **200**. For example, gyroscope **206** may be used to measure the pitch, roll, and yaw of XR system **200**. In some cases, gyroscope **206** may provide one or more rotational vectors (e.g., pitch, yaw, roll). In some examples, image sensor **202** and/or XR engine **224** may use measurements obtained by accelerometer **204** (e.g., one or more translational vectors) and/or gyroscope **206** (e.g., one or more rotational vectors) to calculate the pose of XR system **200**. As previously noted, in other examples, XR system **200** may also include other sensors, such as an inertial measurement unit (IMU), a magnetometer, a gaze and/or eye tracking sensor, a machine vision sensor, a smart scene sensor, a speech recognition sensor, an impact sensor, a shock sensor, a position sensor, a tilt sensor, etc.

(41) As noted above, in some cases, the one or more sensors may include at least one IMU. An IMU is an electronic device that measures the specific force, angular rate, and/or the orientation of XR system **200**, using a combination of one or more accelerometers, one or more gyroscopes, and/or one or more magnetometers. In some examples, the one or more sensors may output measured information associated with the capture of an image captured by image sensor **202** (and/or other camera of XR system **200**) and/or depth information obtained using one or more depth sensors of XR system **200**.

(42) The output of one or more sensors (e.g., accelerometer **204**, gyroscope **206**, one or more IMUs, and/or other sensors) can be used by XR engine **224** to determine a pose of XR system **200** (also referred to as the head pose) and/or the pose of image sensor **202** (or other camera of XR system **200**). In some cases, the pose of XR system **200** and the pose of image sensor **202** (or other camera) can be the same. The pose of image sensor **202** refers to the position and orientation of image sensor **202** relative to a frame of reference (e.g., with respect to a field of view **110** of FIG. **1**). In some implementations, the camera pose can be determined for 6-Degrees Of Freedom (6DoF), which refers to three translational components (e.g., which can be given by X (horizontal), Y (vertical), and Z (depth) coordinates relative to a frame of reference, such as the image plane) and three angular components (e.g. roll, pitch, and yaw relative to the same frame of reference). In some implementations, the camera pose can be determined for 3-Degrees Of Freedom (3DoF), which refers to the three angular components (e.g. roll, pitch, and yaw).

(43) In some cases, a device tracker (not shown) can use the measurements from the one or more sensors and image data from image sensor **202** to track a pose (e.g., a 6DoF pose) of XR system **200**. For example, the device tracker can fuse visual data (e.g., using a visual tracking solution) from the image data with inertial data from the measurements to determine a position and motion of XR system **200** relative to the physical world (e.g., the scene) and a map of the physical world. As described below, in some examples, when tracking the pose of XR system **200**, the device tracker can generate a three-dimensional (3D) map of the scene (e.g., the real world) and/or generate updates for a 3D map of the scene. The 3D map updates can include, for example and without limitation, new or updated features and/or feature or landmark points associated with the scene and/or the 3D map of the scene, localization updates identifying or updating a position of XR system **200** within the scene and the 3D map of the scene, etc. The 3D map can provide a digital representation of a scene in the real/physical world. In some examples, the 3D map can anchor

position-based objects and/or content to real-world coordinates and/or objects. XR system **200** can use a mapped scene (e.g., a scene in the physical world represented by, and/or associated with, a 3D map) to merge the physical and virtual worlds and/or merge virtual content or objects with the physical environment.

(44) In some aspects, the pose of image sensor **202** and/or XR system **200** as a whole can be determined and/or tracked by compute components **214** using a visual tracking solution based on images captured by image sensor **202** (and/or other camera of XR system **200**). For instance, in some examples, compute components **214** can perform tracking using computer vision-based tracking, model-based tracking, and/or simultaneous localization and mapping (SLAM) techniques. For instance, compute components **214** can perform SLAM or can be in communication (wired or wireless) with a SLAM system (not shown). SLAM refers to a class of techniques where a map of an environment (e.g., a map of an environment being modeled by XR system **200**) is created while simultaneously tracking the pose of a camera (e.g., image sensor **202**) and/or XR system **200** relative to that map. The map can be referred to as a SLAM map, and can be three-dimensional (3D). The SLAM techniques can be performed using color or grayscale image data captured by image sensor **202** (and/or other camera of XR system **200**), and can be used to generate estimates of 6DoF pose measurements of image sensor **202** and/or XR system **200**. Such a SLAM technique configured to perform 6DoF tracking can be referred to as 6DoF SLAM. In some cases, the output of the one or more sensors (e.g., accelerometer **204**, gyroscope **206**, one or more IMUs, and/or other sensors) can be used to estimate, correct, and/or otherwise adjust the estimated pose.

(45) FIG. 3 is a block diagram illustrating an example system **300** for generating and/or displaying virtual interactions, according to various aspects of the present disclosure. System **300** includes a rendering engine **302**, which may, in general, obtain hand-pose data **304** and virtual-object data **306** and generate virtual-hand-pose data **308** based on hand-pose data **304** and/or virtual-object data **306**. System **300** (and more specifically rendering engine **302**) may be implemented in XR system **100** of FIG. 1 (e.g., at companion device **104**) and/or in XR system **200** of FIG. 2 (e.g., at or any or all of compute components **214**, XR engine **224**, image processing engine **226**, and/or rendering engine **228**).

(46) Hand-pose data **304** may be, or may include, information regarding one or more hands of one or more users. Hand-pose data **304** may include position information indicative of a position of the one or more hands. The position information may be relative to an XR system including rendering engine **302** or relative to a 3D map of the real world. The position information may include position information for one or more points of the one or more hands. For example, the position information may include a position of each of five respective fingertips of a hand, a position for each of five respective knuckles of the hand, a position of one or more points of a palm of hand, etc.

(47) Additionally, hand-pose data **304** may include gesture information. The gesture information may include an interpretation of the position information. For example, a gesture of a hand based on the positions of one or more points of the hand. Examples of gestures include pinching, grabbing with a palm away from the user, grabbing with a palm toward the user, pointing, releasing a grasp, etc. Rendering engine **302**, or other elements of system **300**, may take gestures as input (e.g., as an instruction or intention of a user). For example, system **300** may take a pinch, or a grab, as an indication that the user wishes to interact with a virtual object.

(48) Hand-pose data **304** may be obtained by a hand tracker. For example, system **300** may include a hand tracker. Alternatively, system **300** may receive hand-pose data **304** from a hand tracker. The hand tracker may be a machine-learning model trained to infer gestures based on images of hands. The hand tracker may obtain one or more images of the hand and determine, based on the one or more images of the hand, the hand-pose data.

(49) Virtual-object data **306** may be, or may include, data regarding a virtual object. Virtual-object data **306** may include a position of the virtual object. The position of the virtual object may be relative to the XR system including rendering engine **302** or relative to a 3D map of the real world.

Additionally, virtual-object data **306** may include data indicative of characteristics of the virtual object, the characteristics including: a size of the virtual object, a shape of the virtual object, a weight of the virtual object, a distance between the hand and the virtual object, an interaction pose of the virtual object, any combination thereof, and/or other property of the virtual object.

(50) Virtual-object data **306** may be received by rendering engine **302** from another element of system **300** (e.g., XR engine **224** of FIG. 2) as illustrated in system **300**. Alternatively, virtual-object data **306** may be generated by rendering engine **302**.

(51) Rendering engine **302** may generate virtual-hand-pose data **308** based on hand-pose data **304** and/or virtual-object data **306**. For example, rendering engine **302** may determine that the hand of hand-pose data **304** is virtually interacting with (or initiating a virtual interaction with) the virtual object of virtual-object data **306** (e.g., based on a relationship between the position of the hand and the position of the virtual object and the gesture of the hand). For instance, rendering engine **302** may determine that a user is initiating a virtual interaction with a virtual object based on the user reaching a hand toward the position of the virtual object, and initiating a pinch or grab gesture.

(52) After determining a virtual interaction between the hand and the virtual object, rendering engine **302** may generate virtual-hand-pose data **308**. Virtual-hand-pose data **308** may be data for displaying a virtual hand interacting with the virtual object. Virtual-hand-pose data **308** may include a position of the virtual hand and a gesture of the virtual hand. The position of the virtual hand may be relative to the XR system including rendering engine **302** or relative to a 3D map of the real world. Virtual-hand-pose data **308** may be provided to a display (e.g., of XR device **102** of FIG. 1 or display **212** of FIG. 2). The display may display the virtual hand interacting with the virtual object.

(53) The position and/or gesture of the virtual hand may, or may not, correspond to the position and/or gesture of the hand of hand-pose data **304**. For example, the position and/or gesture of the virtual hand may be based on virtual-object data **306** and hand-pose data **304** and may, or may not, correspond the position and/or gesture of the hand of hand-pose data **304**. FIG. 4 through FIG. 10 include displayed virtual hands, displayed virtual objects, and real-world hands illustrating examples of virtual hands being displayed based on virtual-object data **306** and hand-pose data **304**.

(54) By displaying a virtual hand (of virtual-hand-pose data **308**), system **300** may display a virtual interaction with a virtual object that matches the virtual object, without the virtual hand corresponding to the position and/or gesture of the hand of the user. For example, system **300** may display a virtual hand grabbing a virtual steering wheel even though the hand of the user is pinching. As another example, system **300** may display virtual hands that are slow to lift a virtual object that has a weight associated with it even though the hand of the user moves freely and quickly (e.g., the virtual hands and virtual object may simulate inertia of the virtual object). The match between the virtual hand gesture and the virtual object may make the virtual object to appear to be more real to the user.

(55) Additionally, according to some aspects, rendering engine **302** may generate shadow virtual-hand-pose data **310** for display. Shadow virtual-hand-pose data **310** may be data for displaying a shadow virtual hand. Shadow virtual-hand-pose data **310** may include position information of a shadow virtual hand and gesture information of a shadow virtual hand. The position of the shadow virtual hand may be relative to the XR system including rendering engine **302** or relative to a 3D map of the real world. Shadow virtual-hand-pose data **310** may be provided to a display (e.g., of XR device **102** of FIG. 1 or display **212** of FIG. 2). The shadow virtual hand may be displayed as translucent (e.g., shadow virtual-hand-pose data **310** may indicate that shadow virtual-hand-pose data **310** is translucent).

(56) The position and/or gesture of shadow virtual-hand-pose data **310** may correspond to the position and/or gesture of the hand of the user. For example, the user may reach out and perform a pinch indicating that the user intends to virtually pick up a virtual object. The virtual object may have an interaction pose and a weight associated with it. According to a virtual experience, virtual

hands may be slow to lift the virtual object and the virtual hands may grasp the object according to the interaction pose rather than according to the pinch of the user's hand. The shadow virtual hands may correspond to the user's hands and may maintain the pinch and move without being affected by the weight associated with the virtual object. FIG. 9 and FIG. 10 include displayed virtual hands, displayed virtual objects, displayed shadow virtual hands, and real-world hands illustrating examples of virtual hands being displayed based on virtual-object data 306 and hand-pose data 304 and shadow virtual hands being displayed based on hand-pose data 304.

(57) By displaying a shadow virtual hand (of shadow virtual-hand-pose data 310), the position and/or gesture of the shadow virtual hand corresponding to the position and/or gesture of the user's hand, system 300 may be displaying an indication of the position and/or gesture of the user's hand. The user's hand may not be visible to the user because the display may occlude the user's view of the user's hand.

(58) By displaying a virtual hand and a shadow virtual hand, system 300 may be displaying differences between the user's hand and the virtual hand. Such displayed differences may be a part of a virtual experience. For example, the position of a shadow virtual hand being different from the position of a virtual hand may indicate to the user that the user's hand has passed through a virtual boundary (e.g., a virtual wall or a virtual object). As another example, a gesture of the shadow virtual hand being different than a gesture of the virtual hand may indicate that the user's hand gesture doesn't match the virtual object (e.g., based on an interaction pose of the virtual object). As another example, a position of the shadow virtual hand being different from a position of the virtual hand may indicate to the user that the virtual hand is encountering resistance (e.g., based on a virtual object).

(59) FIG. 4 is a diagram illustrating an example scenario 400 including displaying virtual interactions, according to various aspects of the present disclosure. In scenario 400, a display 402 displays a virtual hand 408 interacting with a virtual object 406. The position and/or gesture of virtual hand 408 is based on characteristics of virtual object 406 and on a position and/or gesture of a hand 404. Display 402 may be part of an XR system (e.g., XR system 100 of FIG. 1 or XR system 200 of FIG. 2).

(60) In scenario 400, the position of virtual hand 408 may correspond to the position of hand 404. For example, a hand tracker of the XR system may determine position data of hand 404. A rendering engine (e.g., rendering engine 302 of FIG. 3) of the XR system may render virtual hand 408 with a position that corresponds (e.g., within a field of view 110 of FIG. 1) with the position of hand 404. As hand 404 moves, the hand tracker may track hand 404 and update the position of hand 404. The rendering engine may update the position of virtual hand 408 to correspond with the updated position of hand 404.

(61) Additionally, in scenario 400, the gesture of virtual hand 408 may be based on characteristics of virtual object 406 and may, or may not, correspond to the gesture of hand 404. According to the example of scenario 400, virtual object 406 have an interaction pose, for example, a grasp, with the palm facing toward the user. The XR system may interpret the pinch gesture of hand 404 as an intent to grab and/or hold virtual object 406. The XR system may initiate and maintain the grab and/or hold interaction allowing the user to virtually interact with virtual object 406. However, the rendering engine may display virtual hand 408 interacting with virtual object 406 according to the interaction pose of virtual object 406 and not according to the gesture of hand 404. Displaying virtual hand 408 interacting with virtual object 406 according to the interaction pose of virtual object 406 rather than the gesture of hand 404 may cause virtual object 406 and virtual hand 408 (and/or the interaction therebetween) to appear to be more real to the user.

(62) FIG. 5 is a diagram illustrating an example scenario 500 including displaying virtual interactions, according to various aspects of the present disclosure. In scenario 500, a display 502 displays two virtual hands 508 interacting with a virtual object 506. The positions and/or gestures of virtual hands 508 are based on characteristics of virtual object 506 and on positions and/or

gestures of hands **504**. Display **502** may be part of an XR system (e.g., XR system **100** of FIG. **1** or XR system **200** of FIG. **2**).

(63) In scenario **500**, the respective positions of virtual hands **508** may correspond to the respective positions of hands **504**. For example, a hand tracker of the XR system may determine position data of hands **504**. A rendering engine (e.g., rendering engine **302** of FIG. **3**) of the XR system may render virtual hands **508** with respective positions that corresponds (e.g., within a field of view **110** of FIG. **1**) with the respective positions of hands **504**. As hands **504** move, the hand tracker may track hands **504** and update the respective positions of hands **504**. The rendering engine may update the respective positions of virtual hands **508** to correspond with the updated respective positions of hands **504**.

(64) Additionally, in scenario **500**, the respective gestures of virtual hands **508** may be based on characteristics of virtual object **506** and may, or may not, correspond to the respective gestures of hands **504**. In the example of scenario **500**, virtual object **506** have an interaction pose, for example, a grasp, with the palms facing away from the user. The XR system may interpret the pinch gestures of hands **504** as an intent to grab and/or hold virtual object **506**. The XR system may initiate and maintain the grab and/or hold interaction allowing the user to virtually interact with virtual object **506**. However, a rendering engine of the XR system may display virtual hands **508** interacting with virtual object **506** according to the interaction pose of virtual object **506** and not according to the gestures of hands **504**. Displaying virtual hands **508** interacting with virtual object **506** according to the interaction pose of virtual object **506** rather than the gestures of hands **504** may cause virtual object **506** and virtual hands **508** (and/or the interaction therebetween) to appear to be more real to the user.

(65) FIG. **6** is a diagram illustrating an example scenario **600** including displaying virtual interactions, according to various aspects of the present disclosure. In scenario **600**, a display **602** displays two virtual hands **608** interacting with a virtual object **606**. The positions and/or gestures of virtual hands **608** are based on characteristics of virtual object **606** and on positions and/or gestures of hands **604**. Display **602** may be part of an XR system (e.g., XR system **100** of FIG. **1** or XR system **200** of FIG. **2**).

(66) In scenario **600**, the respective positions of virtual hands **608** may correspond to the respective positions of hands **604**. For example, a hand tracker of the XR system may determine position data of hands **604**. A rendering engine (e.g., rendering engine **302** of FIG. **3**) of the XR system may render virtual hands **608** with respective positions that corresponds (e.g., within a field of view **110** of FIG. **1**) with the respective positions of hands **604**. As hands **604** move, the hand tracker may track hands **604** and update the respective positions of hands **604**. The rendering engine may update the respective positions of virtual hands **608** to correspond with the updated respective positions of hands **604**.

(67) Additionally in scenario **600**, the respective gestures of virtual hands **608** may be based on characteristics of virtual object **606** and may, or may not, correspond to the respective gestures of hands **604**. According to the example of scenario **600**, virtual object **606** have an interaction pose, for example, a grasp, with the palms facing toward the user. An XR system may interpret the pinch gestures of hands **604** as an intent to grab and/or hold virtual object **606**. The XR system may initiate and maintain the grab and/or hold interaction allowing the user to virtually interact with virtual object **606**. However, a rendering engine of the XR system may display virtual hands **608** interacting with virtual object **606** according to the interaction pose of virtual object **606** and not according to the gestures of hands **604**. Displaying virtual hands **608** interacting with virtual object **606** according to the interaction pose of virtual object **606** rather than the gestures of hands **604** may cause virtual object **606** and virtual hands **608** (and/or the interaction therebetween) to appear to be more real to the user.

(68) Notably, the respective gestures of hands **504** of FIG. **5** may be the same as the respective gestures of hands **604** of FIG. **6**. Further, one or more characteristics of virtual object **506** of FIG. **5**

and one or more characteristics of virtual object **606** of FIG. **6** may be the same. For example, virtual object **506** and virtual object **606** may have the same shape and/or size. However, an interaction pose of virtual object **506** may differ from an interaction pose of virtual object **606**. Because the interaction pose of virtual object **506** differs from the interaction pose of virtual object **606**, the gesture of virtual hands **508** differs from the gesture of virtual hands **608**.

(69) FIG. **7** is a diagram illustrating an example scenario **700** including displaying virtual interactions, according to various aspects of the present disclosure. In scenario **700**, a display **702** displays a virtual hand **708** interacting with a virtual object **706**. The position and/or gesture of virtual hand **708** is based on characteristics of virtual object **706** and on a position and/or gesture of a hand **704**. Display **702** may be part of an XR system (e.g., XR system **100** of FIG. **1** or XR system **200** of FIG. **2**).

(70) In scenario **700**, the position of virtual hand **708** may be delayed relative to the position of hand **704** based on characteristics of virtual object **706**. In the present disclosure, the term “delayed relative to,” and like terms, may refer to a delayed correspondence between positions (e.g., the position of the virtual hand corresponding to a prior position of the hand). For example, a hand tracker of the XR system may determine position data of hand **704**, including one or more positions of hand **704** at one or more corresponding times. A rendering engine (e.g., rendering engine **302** of FIG. **3**) of the XR system may render virtual hand **708** with a position that corresponds (e.g., within a field of view **110** of FIG. **1**) with a prior position of hand **704**. For example, the hand tracker may determine that at a first time, hand **704** is at a first position, at a second time, hand **704** is at a second position, at a third time, hand **704** is at a third position, and at a fourth time, hand **704** is at a fourth position, etc. At the third time, display **702** may display virtual hand **708** at a position of display **702** that corresponds to the first position. At the fourth time, display **702** may display virtual hand **708** at a position of display **702** that corresponds to the second position. At a fifth time, display **702** may display virtual hand **708** at a position of display **702** that corresponds to the third position, etc.

(71) The fact that virtual hand **708** is displayed is delayed relative to hand **704**, and an amount of the delay (e.g., a duration of time between when hand **704** is at a location and when virtual hand **708** is displayed at the corresponding location of display **702**), may be based on characteristics of virtual object **706**. For example, the amount of delay may be based on a resistance of virtual object **706** to acceleration or to movement. For example, virtual object **706** may be associated with a weight and gravity and/or inertia may be simulated in when displaying movements of virtual object **706**. For example, hand **704** may move quickly to one side. Virtual hand **708**, interacting with virtual object **706** which has a weight associated with it, may move initially more slowly to the side. Additionally, in some cases, if hand **704** suddenly stops, virtual hand **708**, carried by simulated inertia, may continue to move to the side before stopping. Additionally, or alternatively, upward movements of virtual object **706** may be more affected by delay than lateral or downward movements of virtual object **706** (e.g., based on simulated effects gravity on virtual object **706**). Displaying virtual hand **708** interacting with virtual object **706** according to the characteristics of virtual object **706** rather than corresponding in time to the movements of hand **704** may cause virtual object **706** and virtual hand **708** (and/or the interaction therebetween) to appear to be more real to the user.

(72) The gesture of virtual hand **708** may, or may not, be based on characteristics of virtual object **706**. In some cases, virtual object **706** have an interaction pose, for example, a two-finger-plus-thumb grip of a bowling ball. The XR system may interpret the pinch gesture of hand **704** as an intent to grab and/or hold virtual object **706**. The XR system may initiate and maintain the grab and/or hold interaction allowing the user to virtually interact with virtual object **706**. However, the rendering engine may display virtual hand **708** interacting with virtual object **706** according to the interaction pose of virtual object **706** and not according to the gesture of hand **704**. Displaying virtual hand **708** interacting with virtual object **706** according to the interaction pose of virtual

object **706** rather than the gesture of hand **704** may cause virtual object **706** and virtual hand **708** (and/or the interaction therebetween) to appear to be more real to the user.

(73) FIG. **8** is a diagram illustrating an example scenario **800** including displaying virtual interactions, according to various aspects of the present disclosure. In scenario **800**, a display **802** displays two virtual hands **808** interacting with a virtual object **806**. The positions and/or gestures of virtual hands **808** are based on characteristics of virtual object **806** and on positions and/or gestures of hands **804**. Display **802** may be part of an XR system (e.g., XR system **100** of FIG. **1** or XR system **200** of FIG. **2**).

(74) In scenario **800**, the respective position of virtual hands **808** may be delayed relative to the respective positions of hands **804** based on characteristics of virtual object **806**. For example, a hand tracker of the XR system may determine position data of hands **804**, including one or more positions of hands **804** at one or more corresponding times. A rendering engine (e.g., rendering engine **302** of FIG. **3**) of the XR system may render virtual hands **808** with respective positions that corresponds (e.g., within a field of view **110** of FIG. **1**) with respective prior positions of hands **804**.

(75) The fact that virtual hands **808** are displayed delayed relative to hands **804**, and an amount of the delay, may be based on characteristics of virtual object **806**. For example, virtual object **806** may have a characteristics indicating that virtual object **806** is resistant to movement (e.g., rotation) or can no faster than a given speed. In such cases, virtual object **806**, and virtual hands **808** interacting with virtual object **806** may be displayed moving more slowly than, or delayed relative to, hands **804**. Displaying virtual hands **808** interacting with virtual object **806** according to the characteristics of virtual object **806** rather than corresponding in time to the movements of hands **804** may cause virtual object **806** and virtual hands **808** (and/or the interaction therebetween) to appear to be more real to the user.

(76) The respective gestures of virtual hands **808** may, or may not, be based on characteristics of virtual object **806**. In some cases, virtual object **806** have an interaction pose, for example, a grasp with palms facing toward the user. The XR system may interpret the pinch gestures of hands **804** as an intent to grab and/or hold virtual object **806**. The XR system may initiate and maintain the grab and/or hold interaction allowing the user to virtually interact with virtual object **806**. However, the rendering engine may display virtual hands **808** interacting with virtual object **806** according to the interaction pose of virtual object **806** and not according to the gestures of hands **804**. Displaying virtual hands **808** interacting with virtual object **806** according to the interaction pose of virtual object **806** rather than the gestures of hands **804** may cause virtual object **806** and virtual hands **808** (and/or the interaction therebetween) to appear to be more real to the user.

(77) FIG. **9** is a diagram illustrating an example scenario **900** including displaying virtual interactions, according to various aspects of the present disclosure. In scenario **900**, a display **902** displays a virtual hand **908** interacting with a virtual object **906**. The position and/or gesture of virtual hand **908** is based on characteristics of virtual object **906** and on a position and/or gesture of a hand **904**. Display **902** may be part of an XR system (e.g., XR system **100** of FIG. **1** or XR system **200** of FIG. **2**).

(78) In scenario **900**, the position of virtual hand **908** may be delayed relative to the position of hand **904** based on characteristics of virtual object **906**. For example, a hand tracker of the XR system may determine position data of hand **904**, including one or more positions of hand **904** at one or more corresponding times. A rendering engine (e.g., rendering engine **302** of FIG. **3**) of the XR system may render virtual hand **908** with a position that corresponds (e.g., within a field of view **110** of FIG. **1**) with a prior position of hand **904**.

(79) The gesture of virtual hand **908** may, or may not, be based on characteristics of virtual object **906**. In some cases, virtual object **906** have an interaction pose, for example, a two-finger-plus-thumb grip of a bowling ball. The XR system may interpret the pinch gesture of hand **904** as an intent to grab and/or hold virtual object **906**. The XR system may initiate and maintain the grab

and/or hold interaction allowing the user to virtually interact with virtual object **906**. However, the rendering engine may display virtual hand **908** interacting with virtual object **906** according to the interaction pose of virtual object **906** and not according to the gesture of hand **904**.

(80) In scenario **900**, display **902** may display a shadow virtual hand **910**. The position and/or gesture of shadow virtual hand **910** may correspond to the position and/or gesture of hand **904**. Display **902** may display shadow virtual hand **910** as translucent. As an example, the hand tracker, having determined position data of hand **904**, may provide the position data to the XR engine. The XR engine may render shadow virtual hand **910** as a representation (e.g., a translucent representation) of hand **904**. The XR engine may provide data representative of shadow virtual hand **910** to display **902** and display **902** may display shadow virtual hand **910**.

(81) Displaying shadow virtual hand **910** to a user may indicate to the user the position of hand **904**. In some case, the user may be unable to see hand **904** based on display **902** occluding a view of the user. Further, displaying shadow virtual hand **910** and virtual hand **908** to the user may indicate to the user a difference between the position of hand **904** and virtual hand **908** (e.g., based on characteristics of virtual object **906**). Such an indication may provide a visual cue regarding the characteristics of virtual object **906**, which may cause virtual object **906** and virtual hand **908** (and/or the interaction therebetween) to appear to be more real to the user. Additionally or alternatively, displaying shadow virtual hand **910** and virtual hand **908** to a user may indicate to the user that their gesture does not match the interaction pose of virtual object **906**. Such an interaction may serve as a suggestion for the user to change their gesture to match the interaction pose of virtual object **906**, which may (e.g., through proprioception) cause virtual object **906** and virtual hand **908** (and/or the interaction therebetween) to appear or feel more real to the user.

(82) FIG. **10** is a diagram illustrating an example scenario **1000** including displaying virtual interactions, according to various aspects of the present disclosure. In scenario **1000**, a display **1002** displays a virtual hand **1008** interacting with a virtual object **1006**. The position and/or gesture of virtual hand **1008** is based on characteristics of virtual object **1006** and on a position and/or gesture of a hand **1004**. Display **1002** may be part of an XR system (e.g., XR system **100** of FIG. **1** or XR system **200** of FIG. **2**).

(83) In scenario **1000**, the position of virtual hand **1008** may correspond to the position of hand **1004**. For example, a hand tracker of the XR system may determine position data of hand **1004**. A rendering engine (e.g., rendering engine **302** of FIG. **3**) of the XR system may render virtual hand **1008** with a position that corresponds (e.g., within a field of view **110** of FIG. **1**) with the position of hand **1004**. As hand **1004** moves, the hand tracker may track hand **1004** and update the position of hand **1004**. The rendering engine may update the position of virtual hand **1008** to correspond with the updated position of hand **1004**.

(84) Additionally, in scenario **1000**, the gesture of virtual hand **1008** may be based on characteristics of virtual object **1006** and may, or may not, correspond to the gesture of hand **1004**. In the example of scenario **1000**, virtual object **1006** have an interaction pose, for example, a grasp, with the palm facing toward the user. The XR system may interpret the pinch gesture of hand **1004** as an intent to grab and/or hold virtual object **1006**. The XR system may initiate and maintain the grab and/or hold interaction allowing the user to virtually interact with virtual object **1006**. However, the rendering engine may display virtual hand **1008** interacting with virtual object **1006** according to the interaction pose of virtual object **1006** and not according to the gesture of hand **1004**. Displaying virtual hand **1008** interacting with virtual object **1006** according to the interaction pose of virtual object **1006** rather than the gesture of hand **1004** may cause virtual object **1006** and virtual hand **1008** (and/or the interaction therebetween) to appear to be more real to the user.

(85) In scenario **1000**, display **1002** may display a shadow virtual hand **1010**. The position and/or gesture of shadow virtual hand **1010** may correspond to the position and/or gesture of hand **1004**. Display **1002** may display shadow virtual hand **1010** as translucent. As an example, the hand tracker, having determined position data of hand **1004**, may provide the position data to the XR

engine. The XR engine may render shadow virtual hand **1010** as a representation (e.g., a translucent representation) of hand **1004**. The XR engine may provide data representative of shadow virtual hand **1010** to display **1002** and display **1002** may display shadow virtual hand **1010**. Displaying shadow virtual hand **1010** and virtual hand **1008** to a user may indicate to the user that their gesture does not match the interaction pose of virtual object **1006**. Such an interaction may serve as a suggestion for the user to change their gesture to match the interaction pose of virtual object **1006**, which may (e.g., through proprioception) cause virtual object **1006** and virtual hand **1008** (and/or the interaction therebetween) to appear or feel more real to the user.

(86) FIG. **11** is a flow diagram illustrating a process **1100** for displaying virtual interactions between virtual hands and virtual objects, in accordance with aspects of the present disclosure. One or more operations of process **1100** may be performed by a computing device (or apparatus) or a component (e.g., a chipset, codec, etc.) of the computing device. The computing device may be a mobile device (e.g., a mobile phone), a network-connected wearable such as a watch, an extended reality (XR) device such as a virtual reality (VR) device or augmented reality (AR) device, a vehicle or component or system of a vehicle, or other type of computing device. The one or more operations of process **1100** may be implemented as software components that are executed and run on one or more processors.

(87) At block **1102**, a computing device (or one or more components thereof) may obtain hand-pose data indicative of a pose of a hand. For example, rendering engine **302** of FIG. **3** may obtain hand-pose data **304** of FIG. **3**.

(88) In some aspects, the computing device (or one or more components thereof) may obtain one or more images of the hand; and determine, based on the one or more images of the hand, the hand-pose data, the hand-pose data comprising a position of the hand and a gesture of the hand. For example, the computing device (or one or more components thereof) may capture images of hand **404** of FIG. **4** and determine a position and/or gesture of hand **404** based on the captured images.

(89) At block **1104**, the computing device (or one or more components thereof) may obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting. For example, rendering engine **302** may obtain virtual-object data **306** of FIG. **3**.

(90) In some aspects, the virtual-object data is based on characteristics of the virtual object; and the characteristics of the virtual object include one or more of: a size of the virtual object, a shape of the virtual object, a weight of the virtual object, a distance between the hand and the virtual object, or an interaction pose of the virtual object.

(91) In some aspects, the pose of the hand may include a position of the hand and a gesture of the hand. The virtual-object data may include a position of the virtual object. The computing device (or one or more components thereof) may determine that the hand is virtually interacting with the virtual object based on a relationship between the position of the hand and the position of the virtual object and the gesture of the hand. For example, the computing device (or one or more components thereof) may determine that hand **404** is virtually interacting with virtual object **406** based on a position of hand **404** and a position of virtual object **406**.

(92) At block **1106**, the computing device (or one or more components thereof) may display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data. For example, rendering engine **302** may render virtual-hand-pose data **308** of FIG. **3** for displaying a virtual hand. For example, rendering engine **302** may render virtual-hand-pose data **308** which may be displayed by display **402** of FIG. **4**. Virtual-hand-pose data **308** may include data to render virtual hand **408** of FIG. **4**.

(93) In some aspects, a gesture of the virtual hand may be different from a gesture of the hand. For example, a gesture of hand **404** of FIG. **4** may differ from a gesture of virtual hand **408**. In some aspects, the gesture of the virtual hand may be based on an interaction pose of the virtual object indicated by the virtual-object data. For example, the gesture (e.g., grab) of virtual hand **408** may be based on an interaction pose of virtual object **406**.

(94) In some aspects, the pose of the hand may include a position of the hand and the gesture of the hand. The virtual-hand pose may include a position of the virtual hand and the gesture of the virtual hand. The position of the virtual hand may correspond to the position of the hand and the gesture of the virtual hand is based on the virtual-object data. For example, the position of virtual hand **408** may correspond to the position of hand **404** and the gesture of virtual hand **408** may be based on virtual object **406** of FIG. 4.

(95) In some aspects, the hand-pose data comprises first hand-pose data and the gesture of the hand comprises a first gesture; the pose of the hand comprises a first pose of the hand comprising the first gesture of the hand; the virtual-object data comprises first virtual-object data; the virtual object comprises a first virtual object; the virtual-hand pose comprises a first virtual hand pose; and the computing device (or one or more components thereof) may: obtain second hand-pose data indicative of a second pose of the hand, the second pose of the hand comprising a second gesture of the hand that is the same as the first gesture of the hand; obtain second virtual-object data indicative of a second virtual object with which the hand is virtually interacting, the second virtual-object data being different than the first virtual-object data; and display the virtual hand interacting with the second virtual object, the virtual hand exhibiting a second virtual-hand pose, the second virtual-hand pose different from the first virtual hand pose based on the second virtual-object data being different than the first virtual-object data. For example, the gesture of virtual hands **508** of FIG. 5 may differ from the gesture of virtual hands **608** of FIG. 6 based on virtual object **506** of FIG. 5 being different from virtual object **606** of FIG. 6 (e.g., virtual object **506** and virtual object **606** may have different interaction poses).

(96) In some aspects, the pose of the hand comprises a position of the hand; the virtual-hand pose comprises a position of the virtual hand; and the position of the virtual hand is delayed relative to the position of the hand based on the virtual-object data. For example, the position of virtual hand **708** of FIG. 7 may be delayed relative to the position of hand **704** of FIG. 7. In some aspects, the position of the virtual hand may be delayed relative to the position of the hand based on a weight of the virtual object indicated by the virtual-object data. For example, the position of virtual hand **708** may be delayed relative to hand **704** based on a weight of virtual object **706**. In some aspects, the computing device (or one or more components thereof) may display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand. For example, a position of shadow virtual hand **910** of FIG. 9 may correspond to a position of hand **904** of FIG. 9.

(97) In some aspects, the computing device (or one or more components thereof) may display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose corresponding to the pose of the hand. For example, the position of shadow virtual hand **910** of FIG. 9 may correspond to the position of hand **904** of FIG. 9. In some aspects, the computing device (or one or more components thereof) may display the shadow virtual hand as translucent. For example, shadow virtual hand **910** may be displayed as translucent.

(98) In some aspects, the computing device (or one or more components thereof) may display a shadow virtual hand exhibiting a shadow-virtual-hand pose. The shadow-virtual-hand pose may include a position of the shadow virtual hand and a gesture of the shadow virtual hand. The position of the shadow virtual hand may correspond to the position of the hand and the gesture of the shadow virtual hand may correspond to the gesture of the hand. For example, the position of shadow virtual hand **910** of FIG. 9 may correspond to the position of hand **904** of FIG. 9 and the gesture of shadow virtual hand **910** may correspond to the gesture of hand **904**.

(99) FIG. 12 is a flow diagram illustrating a process **1200** for displaying virtual interactions between virtual hands and virtual objects, in accordance with aspects of the present disclosure. One or more operations of process **1200** may be performed by a computing device (or apparatus) or a component (e.g., a chipset, codec, etc.) of the computing device. The computing device may be a

mobile device (e.g., a mobile phone), a network-connected wearable such as a watch, an extended reality (XR) device such as a virtual reality (VR) device or augmented reality (AR) device, a vehicle or component or system of a vehicle, or other type of computing device. The one or more operations of process **1200** may be implemented as software components that are executed and run on one or more processors.

(100) At block **1202**, a computing device (or one or more components thereof) may obtain hand-pose data indicative of a pose of a hand. For example, rendering engine **302** of FIG. **3** may obtain hand-pose data **304** of FIG. **3**.

(101) At block **1204**, the computing device (or one or more components thereof) may obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting. For example, rendering engine **302** may obtain virtual-object data **306** of FIG. **3**.

(102) At block **1206**, the computing device (or one or more components thereof) may display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein a position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data.

(103) For example, rendering engine **302** may render virtual-hand-pose data **308** of FIG. **3** for displaying a virtual hand. For example, rendering engine **302** may render virtual-hand-pose data **308** which may be displayed by display **702** of FIG. **7**. Virtual-hand-pose data **308** may include data to render virtual hand **708** of FIG. **7**. The position of virtual hand **708** of FIG. **7** may be delayed relative to the position of hand **704** of FIG. **7**.

(104) In some examples, the methods described herein (e.g., process **1100** of FIG. **11**, process **1200** of FIG. **12** and/or other methods described herein) can be performed, in whole or in part, by a computing device or apparatus. In one example, one or more of the methods can be performed by XR system **100** of FIG. **1**, XR device **102** of FIG. **1**, companion device **104** of FIG. **1**, XR system **200** of FIG. **2**, compute components **214** of FIG. **2**, display **212** of FIG. **2**, system **300** of FIG. **3**, rendering engine **302** of FIG. **3**, or by another system or device. In another example, one or more of the methods can be performed, in whole or in part, by the computing-device architecture **1300** shown in FIG. **13**. For instance, a computing device with the computing-device architecture **1300** shown in FIG. **13** can include, or be included in, the components of XR system **100** of FIG. **1**, XR device **102** of FIG. **1**, companion device **104** of FIG. **1**, XR system **200** of FIG. **2**, compute components **214** of FIG. **2**, display **212** of FIG. **2**, system **300** of FIG. **3**, rendering engine **302** of FIG. **3**, and can implement the operations of process **1100**, process **1200**, and/or other process described herein.

(105) The computing device can include any suitable device, such as a vehicle or a computing device of a vehicle, a mobile device (e.g., a mobile phone), a desktop computing device, a tablet computing device, a wearable device (e.g., a VR headset, an AR headset, AR glasses, a network-connected watch or smartwatch, or other wearable device), a server computer, a robotic device, a television, and/or any other computing device with the resource capabilities to perform the processes described herein, including, process **1100**, process **1200**, and/or other process described herein. In some cases, the computing device or apparatus can include various components, such as one or more input devices, one or more output devices, one or more processors, one or more microprocessors, one or more microcomputers, one or more cameras, one or more sensors, and/or other component(s) that are configured to carry out the steps of processes described herein. In some examples, the computing device can include a display, a network interface configured to communicate and/or receive the data, any combination thereof, and/or other component(s). The network interface can be configured to communicate and/or receive Internet Protocol (IP) based data or other type of data.

(106) The components of the computing device can be implemented in circuitry. For example, the components can include and/or can be implemented using electronic circuits or other electronic hardware, which can include one or more programmable electronic circuits (e.g., microprocessors,

graphics processing units (GPUs), digital signal processors (DSPs), central processing units (CPUs), and/or other suitable electronic circuits), and/or can include and/or be implemented using computer software, firmware, or any combination thereof, to perform the various operations described herein.

(107) Process **1100**, process **1200**, and/or other process described herein are illustrated as logical flow diagrams, the operation of which represents a sequence of operations that can be implemented in hardware, computer instructions, or a combination thereof. In the context of computer instructions, the operations represent computer-executable instructions stored on one or more computer-readable storage media that, when executed by one or more processors, perform the recited operations. Generally, computer-executable instructions include routines, programs, objects, components, data structures, and the like that perform particular functions or implement particular data types. The order in which the operations are described is not intended to be construed as a limitation, and any number of the described operations can be combined in any order and/or in parallel to implement the processes.

(108) Additionally, process **1100**, process **1200**, and/or other process described herein can be performed under the control of one or more computer systems configured with executable instructions and can be implemented as code (e.g., executable instructions, one or more computer programs, or one or more applications) executing collectively on one or more processors, by hardware, or combinations thereof. As noted above, the code can be stored on a computer-readable or machine-readable storage medium, for example, in the form of a computer program comprising a plurality of instructions executable by one or more processors. The computer-readable or machine-readable storage medium can be non-transitory.

(109) FIG. **13** illustrates an example computing-device architecture **1300** of an example computing device which can implement the various techniques described herein. In some examples, the computing device can include a mobile device, a wearable device, an extended reality device (e.g., a virtual reality (VR) device, an augmented reality (AR) device, or a mixed reality (MR) device), a personal computer, a laptop computer, a video server, a vehicle (or computing device of a vehicle), or other device. For example, the computing-device architecture **1300** may include, implement, or be included in any or all of XR system **100** of FIG. **1**, XR device **102** of FIG. **1**, companion device **104** of FIG. **1**, XR system **200** of FIG. **2**, compute components **214** of FIG. **2**, display **212** of FIG. **2**, system **300** of FIG. **3**, rendering engine **302** of FIG. **3**.

(110) The components of computing-device architecture **1300** are shown in electrical communication with each other using connection **1312**, such as a bus. The example computing-device architecture **1300** includes a processing unit (CPU or processor) **1302** and computing device connection **1312** that couples various computing device components including computing device memory **1310**, such as read only memory (ROM) **1308** and random-access memory (RAM) **1306**, to processor **1302**.

(111) Computing-device architecture **1300** can include a cache of high-speed memory connected directly with, in close proximity to, or integrated as part of processor **1302**. Computing-device architecture **1300** can copy data from memory **1310** and/or the storage device **1314** to cache **1304** for quick access by processor **1302**. In this way, the cache can provide a performance boost that avoids processor **1302** delays while waiting for data. These and other modules can control or be configured to control processor **1302** to perform various actions. Other computing device memory **1310** may be available for use as well. Memory **1310** can include multiple different types of memory with different performance characteristics. Processor **1302** can include any general-purpose processor and a hardware or software service, such as service 1 **1316**, service 2 **1318**, and service 3 **1320** stored in storage device **1314**, configured to control processor **1302** as well as a special-purpose processor where software instructions are incorporated into the processor design. Processor **1302** may be a self-contained system, containing multiple cores or processors, a bus, memory controller, cache, etc. A multi-core processor may be symmetric or asymmetric.

(112) To enable user interaction with the computing-device architecture **1300**, input device **1322** can represent any number of input mechanisms, such as a microphone for speech, a touch-sensitive screen for gesture or graphical input, keyboard, mouse, motion input, speech and so forth. Output device **1324** can also be one or more of a number of output mechanisms known to those of skill in the art, such as a display, projector, television, speaker device, etc. In some instances, multimodal computing devices can enable a user to provide multiple types of input to communicate with computing-device architecture **1300**. Communication interface **1326** can generally govern and manage the user input and computing device output. There is no restriction on operating on any particular hardware arrangement and therefore the basic features here may easily be substituted for improved hardware or firmware arrangements as they are developed.

(113) Storage device **1314** is a non-volatile memory and can be a hard disk or other types of computer readable media which can store data that are accessible by a computer, such as magnetic cassettes, flash memory cards, solid state memory devices, digital versatile disks, cartridges, random-access memories (RAMs) **1306**, read only memory (ROM) **1308**, and hybrids thereof. Storage device **1314** can include services **1316**, **1318**, and **1320** for controlling processor **1302**. Other hardware or software modules are contemplated. Storage device **1314** can be connected to the computing device connection **1312**. In one aspect, a hardware module that performs a particular function can include the software component stored in a computer-readable medium in connection with the necessary hardware components, such as processor **1302**, connection **1312**, output device **1324**, and so forth, to carry out the function.

(114) The term “substantially,” in reference to a given parameter, property, or condition, may refer to a degree that one of ordinary skill in the art would understand that the given parameter, property, or condition is met with a small degree of variance, such as, for example, within acceptable manufacturing tolerances. By way of example, depending on the particular parameter, property, or condition that is substantially met, the parameter, property, or condition may be at least 90% met, at least 95% met, or even at least 99% met.

(115) Aspects of the present disclosure are applicable to any suitable electronic device (such as security systems, smartphones, tablets, laptop computers, vehicles, drones, or other devices) including or coupled to one or more active depth sensing systems. While described below with respect to a device having or coupled to one light projector, aspects of the present disclosure are applicable to devices having any number of light projectors, and are therefore not limited to specific devices.

(116) The term “device” is not limited to one or a specific number of physical objects (such as one smartphone, one controller, one processing system and so on). As used herein, a device may be any electronic device with one or more parts that may implement at least some portions of this disclosure. While the below description and examples use the term “device” to describe various aspects of this disclosure, the term “device” is not limited to a specific configuration, type, or number of objects. Additionally, the term “system” is not limited to multiple components or specific aspects. For example, a system may be implemented on one or more printed circuit boards or other substrates, and may have movable or static components. While the below description and examples use the term “system” to describe various aspects of this disclosure, the term “system” is not limited to a specific configuration, type, or number of objects.

(117) Specific details are provided in the description above to provide a thorough understanding of the aspects and examples provided herein. However, it will be understood by one of ordinary skill in the art that the aspects may be practiced without these specific details. For clarity of explanation, in some instances the present technology may be presented as including individual functional blocks including functional blocks including devices, device components, steps or routines in a method embodied in software, or combinations of hardware and software. Additional components may be used other than those shown in the figures and/or described herein. For example, circuits, systems, networks, processes, and other components may be shown as components in block

diagram form in order not to obscure the aspects in unnecessary detail. In other instances, well-known circuits, processes, algorithms, structures, and techniques may be shown without unnecessary detail in order to avoid obscuring the aspects.

(118) Individual aspects may be described above as a process or method which is depicted as a flowchart, a flow diagram, a data flow diagram, a structure diagram, or a block diagram. Although a flowchart may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process is terminated when its operations are completed but could have additional steps not included in a figure. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, etc. When a process corresponds to a function, its termination can correspond to a return of the function to the calling function or the main function.

(119) Processes and methods according to the above-described examples can be implemented using computer-executable instructions that are stored or otherwise available from computer-readable media. Such instructions can include, for example, instructions and data which cause or otherwise configure a general-purpose computer, special purpose computer, or a processing device to perform a certain function or group of functions. Portions of computer resources used can be accessible over a network. The computer executable instructions may be, for example, binaries, intermediate format instructions such as assembly language, firmware, source code, etc.

(120) The term “computer-readable medium” includes, but is not limited to, portable or non-portable storage devices, optical storage devices, and various other mediums capable of storing, containing, or carrying instruction(s) and/or data. A computer-readable medium may include a non-transitory medium in which data can be stored and that does not include carrier waves and/or transitory electronic signals propagating wirelessly or over wired connections. Examples of a non-transitory medium may include, but are not limited to, a magnetic disk or tape, optical storage media such as flash memory, memory or memory devices, magnetic or optical disks, flash memory, USB devices provided with non-volatile memory, networked storage devices, compact disk (CD) or digital versatile disk (DVD), any suitable combination thereof, among others. A computer-readable medium may have stored thereon code and/or machine-executable instructions that may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a class, or any combination of instructions, data structures, or program statements. A code segment may be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, or memory contents. Information, arguments, parameters, data, etc. may be passed, forwarded, or transmitted via any suitable means including memory sharing, message passing, token passing, network transmission, or the like.

(121) In some aspects the computer-readable storage devices, mediums, and memories can include a cable or wireless signal containing a bit stream and the like. However, when mentioned, non-transitory computer-readable storage media expressly exclude media such as energy, carrier signals, electromagnetic waves, and signals per se.

(122) Devices implementing processes and methods according to these disclosures can include hardware, software, firmware, middleware, microcode, hardware description languages, or any combination thereof, and can take any of a variety of form factors. When implemented in software, firmware, middleware, or microcode, the program code or code segments to perform the necessary tasks (e.g., a computer-program product) may be stored in a computer-readable or machine-readable medium. A processor(s) may perform the necessary tasks. Typical examples of form factors include laptops, smart phones, mobile phones, tablet devices or other small form factor personal computers, personal digital assistants, rackmount devices, standalone devices, and so on. Functionality described herein also can be embodied in peripherals or add-in cards. Such functionality can also be implemented on a circuit board among different chips or different processes executing in a single device, by way of further example.

(123) The instructions, media for conveying such instructions, computing resources for executing

them, and other structures for supporting such computing resources are example means for providing the functions described in the disclosure.

(124) In the foregoing description, aspects of the application are described with reference to specific aspects thereof, but those skilled in the art will recognize that the application is not limited thereto. Thus, while illustrative aspects of the application have been described in detail herein, it is to be understood that the inventive concepts may be otherwise variously embodied and employed, and that the appended claims are intended to be construed to include such variations, except as limited by the prior art. Various features and aspects of the above-described application may be used individually or jointly. Further, aspects can be utilized in any number of environments and applications beyond those described herein without departing from the broader spirit and scope of the specification. The specification and drawings are, accordingly, to be regarded as illustrative rather than restrictive. For the purposes of illustration, methods were described in a particular order. It should be appreciated that in alternate aspects, the methods may be performed in a different order than that described.

(125) One of ordinary skill will appreciate that the less than (“<”) and greater than (“>”) symbols or terminology used herein can be replaced with less than or equal to (“≤”) and greater than or equal to (“≥”) symbols, respectively, without departing from the scope of this description.

(126) Where components are described as being “configured to” perform certain operations, such configuration can be accomplished, for example, by designing electronic circuits or other hardware to perform the operation, by programming programmable electronic circuits (e.g., microprocessors, or other suitable electronic circuits) to perform the operation, or any combination thereof.

(127) The phrase “coupled to” refers to any component that is physically connected to another component either directly or indirectly, and/or any component that is in communication with another component (e.g., connected to the other component over a wired or wireless connection, and/or other suitable communication interface) either directly or indirectly.

(128) Claim language or other language reciting “at least one of” a set and/or “one or more” of a set indicates that one member of the set or multiple members of the set (in any combination) satisfy the claim. For example, claim language reciting “at least one of A and B” or “at least one of A or B” means A, B, or A and B. In another example, claim language reciting “at least one of A, B, and C” or “at least one of A, B, or C” means A, B, C, or A and B, or A and C, or B and C, or A and B and C. The language “at least one of” a set and/or “one or more” of a set does not limit the set to the items listed in the set. For example, claim language reciting “at least one of A and B” or “at least one of A or B” can mean A, B, or A and B, and can additionally include items not listed in the set of A and B.

(129) The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the aspects disclosed herein may be implemented as electronic hardware, computer software, firmware, or combinations thereof. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present application.

(130) The techniques described herein may also be implemented in electronic hardware, computer software, firmware, or any combination thereof. Such techniques may be implemented in any of a variety of devices such as general-purposes computers, wireless communication device handsets, or integrated circuit devices having multiple uses including application in wireless communication device handsets and other devices. Any features described as modules or components may be implemented together in an integrated logic device or separately as discrete but interoperable logic devices. If implemented in software, the techniques may be realized at least in part by a computer-

readable data storage medium including program code including instructions that, when executed, performs one or more of the methods described above. The computer-readable data storage medium may form part of a computer program product, which may include packaging materials. The computer-readable medium may include memory or data storage media, such as random-access memory (RAM) such as synchronous dynamic random-access memory (SDRAM), read-only memory (ROM), non-volatile random-access memory (NVRAM), electrically erasable programmable read-only memory (EEPROM), FLASH memory, magnetic or optical data storage media, and the like. The techniques additionally, or alternatively, may be realized at least in part by a computer-readable communication medium that carries or communicates program code in the form of instructions or data structures and that can be accessed, read, and/or executed by a computer, such as propagated signals or waves.

(131) The program code may be executed by a processor, which may include one or more processors, such as one or more digital signal processors (DSPs), general-purpose microprocessors, an application specific integrated circuits (ASICs), field programmable logic arrays (FPGAs), or other equivalent integrated or discrete logic circuitry. Such a processor may be configured to perform any of the techniques described in this disclosure. A general-purpose processor may be a microprocessor; but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration). Accordingly, the term “processor,” as used herein may refer to any of the foregoing structure, any combination of the foregoing structure, or any other structure or apparatus suitable for implementation of the techniques described herein.

(132) Illustrative aspects of the disclosure include:

(133) Aspect 1. An apparatus for displaying one or more virtual objects, the apparatus comprising: at least one memory; and at least one processor coupled to the at least one memory and configured to: obtain hand-pose data indicative of a pose of a hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data.

(134) Aspect 2. The apparatus of aspect 1, wherein a gesture of the virtual hand is different from a gesture of the hand.

(135) Aspect 3. The apparatus of any one of aspects 1 or 2, wherein: the pose of the hand comprises a position of the hand and the gesture of the hand; the virtual-hand pose comprises a position of the virtual hand and the gesture of the virtual hand; the position of the virtual hand corresponds to the position of the hand; and the gesture of the virtual hand is based on the virtual-object data.

(136) Aspect 4. The apparatus of aspect 3, wherein the at least one processor is further configured to display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand and a gesture of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand and the gesture of the shadow virtual hand corresponding to the gesture of the hand.

(137) Aspect 5. The apparatus of any one of aspects 1 to 4, wherein the gesture of the virtual hand is based on an interaction pose of the virtual object indicated by the virtual-object data.

(138) Aspect 6. The apparatus of any one of aspects 1 to 5, wherein: the hand-pose data comprises first hand-pose data and the gesture of the hand comprises a first gesture; the pose of the hand comprises a first pose of the hand comprising the first gesture of the hand; the virtual-object data comprises first virtual-object data; the virtual object comprises a first virtual object; the virtual-hand pose comprises a first virtual hand pose; and the at least one processor is further configured to: obtain second hand-pose data indicative of a second pose of the hand, the second pose of the hand comprising a second gesture of the hand that is the same as the first gesture of the hand;

obtain second virtual-object data indicative of a second virtual object with which the hand is virtually interacting, the second virtual-object data being different than the first virtual-object data; and display the virtual hand interacting with the second virtual object, the virtual hand exhibiting a second virtual-hand pose, the second virtual-hand pose different from the first virtual hand pose based on the second virtual-object data being different than the first virtual-object data.

(139) Aspect 7. The apparatus of any one of aspects 1 to 6, wherein: the pose of the hand comprises a position of the hand; the virtual-hand pose comprises a position of the virtual hand; and the position of the virtual hand is delayed relative to the position of the hand based on the virtual-object data.

(140) Aspect 8. The apparatus of aspect 7, wherein the position of the virtual hand is delayed relative to the position of the hand based on a weight of the virtual object indicated by the virtual-object data.

(141) Aspect 9. The apparatus of any one of aspects 7 or 8, wherein the at least one processor is further configured to display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand.

(142) Aspect 10. The apparatus of any one of aspects 1 to 9, wherein the virtual-hand pose is different from the pose of the hand.

(143) Aspect 11. The apparatus of any one of aspects 1 to 10, wherein: the virtual-object data is based on characteristics of the virtual object; and the characteristics of the virtual object include one or more of: a size of the virtual object, a shape of the virtual object, a weight of the virtual object, a distance between the hand and the virtual object, or an interaction pose of the virtual object.

(144) Aspect 12. The apparatus of any one of aspects 1 to 11, wherein the at least one processor is further configured to display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose corresponding to the pose of the hand.

(145) Aspect 13. The apparatus of aspect 12, wherein to display the shadow virtual hand the at least one processor is further configured to display the shadow virtual hand as translucent.

(146) Aspect 14. The apparatus of any one of aspects 1 to 13, wherein the at least one processor is further configured to: obtain one or more images of the hand; and determine, based on the one or more images of the hand, the hand-pose data, the hand-pose data comprising a position of the hand and a gesture of the hand.

(147) Aspect 15. The apparatus of any one of aspects 1 to 14, wherein: the pose of the hand comprises a position of the hand and a gesture of the hand; the virtual-object data comprises a position of the virtual object; and the at least one processor is further configured to determine that the hand is virtually interacting with the virtual object based on a relationship between the position of the hand and the position of the virtual object and the gesture of the hand.

(148) Aspect 16. An apparatus for displaying one or more virtual objects, the apparatus comprising: at least one memory; and at least one processor coupled to the at least one memory and configured to: obtain hand-pose data indicative of a pose of a hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein a position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data.

(149) Aspect 17. A method for displaying one or more virtual objects, the method comprising: obtaining hand-pose data indicative of a pose of a hand; obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data.

(150) Aspect 18. The method of aspect 17, wherein a gesture of the virtual hand is different from a

gesture of the hand.

(151) Aspect 19. The method of any one of aspects 17 or 18, wherein: the pose of the hand comprises a position of the hand and the gesture of the hand; the virtual-hand pose comprises a position of the virtual hand and the gesture of the virtual hand; the position of the virtual hand corresponds to the position of the hand; and the gesture of the virtual hand is based on the virtual-object data.

(152) Aspect 20. The method of aspect 19, further comprising displaying a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand and a gesture of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand and the gesture of the shadow virtual hand corresponding to the gesture of the hand.

(153) Aspect 21. The method of any one of aspects 17 to 20, wherein the gesture of the virtual hand is based on an interaction pose of the virtual object indicated by the virtual-object data.

(154) Aspect 22. The method of any one of aspects 17 to 21, wherein: the hand-pose data comprises first hand-pose data and the gesture of the hand comprises a first gesture; the pose of the hand comprises a first pose of the hand comprising the first gesture of the hand; the virtual-object data comprises first virtual-object data; the virtual object comprises a first virtual object; the virtual-hand pose comprises a first virtual hand pose; and the method further comprises: obtaining second hand-pose data indicative of a second pose of the hand, the second pose of the hand comprising a second gesture of the hand that is the same as the first gesture of the hand; obtaining second virtual-object data indicative of a second virtual object with which the hand is virtually interacting, the second virtual-object data being different than the first virtual-object data; and displaying the virtual hand interacting with the second virtual object, the virtual hand exhibiting a second virtual-hand pose, the second virtual-hand pose different from the first virtual hand pose based on the second virtual-object data being different than the first virtual-object data.

(155) Aspect 23. The method of any one of aspects 17 to 22, wherein: the pose of the hand comprises a position of the hand; the virtual-hand pose comprises a position of the virtual hand; and the position of the virtual hand is delayed relative to the position of the hand based on the virtual-object data.

(156) Aspect 24. The method of aspect 23, wherein the position of the virtual hand is delayed relative to the position of the hand based on a weight of the virtual object indicated by the virtual-object data.

(157) Aspect 25. The method of any one of aspects 23 or 24, further comprising displaying a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand.

(158) Aspect 26. The method of any one of aspects 17 to 25, wherein the virtual-hand pose is different from the pose of the hand.

(159) Aspect 27. The method of any one of aspects 17 to 26, wherein: the virtual-object data is based on characteristics of the virtual object; and the characteristics of the virtual object include one or more of: a size of the virtual object, a shape of the virtual object, a weight of the virtual object, a distance between the hand and the virtual object, or an interaction pose of the virtual object.

(160) Aspect 28. The method of any one of aspects 17 to 27, further comprising displaying a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose corresponding to the pose of the hand.

(161) Aspect 29. The method of any one of aspects 17 to 28, wherein displaying the shadow virtual hand comprises displaying the shadow virtual hand as translucent.

(162) Aspect 30. The method of any one of aspects 17 to 29, further comprising: obtaining one or more images of the hand; and determining, based on the one or more images of the hand, the hand-

pose data, the hand-pose data comprising a position of the hand and a gesture of the hand.

(163) Aspect 31. The method of any one of aspects 17 to 30, wherein: the pose of the hand comprises a position of the hand and a gesture of the hand; the virtual-object data comprises a position of the virtual object; and the method further comprises determining that the hand is virtually interacting with the virtual object based on a relationship between the position of the hand and the position of the virtual object and the gesture of the hand.

(164) Aspect 32. A method for displaying one or more virtual objects, the method comprising: obtaining hand-pose data indicative of a pose of a hand; obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein a position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data.

(165) Aspect 33. A non-transitory computer-readable storage medium having stored thereon instructions that, when executed by at least one processor, cause the at least one processor to perform operations according to any of aspects 17 to 32.

(166) Aspect 34. An apparatus for providing virtual content for display, the apparatus comprising one or more means for perform operations according to any of aspects 17 to 32.

Claims

1. An apparatus for displaying one or more virtual objects, the apparatus comprising: at least one memory; and at least one processor coupled to the at least one memory and configured to: obtain hand-pose data indicative of a pose of a hand, wherein the pose of the hand comprises a position of the hand and a gesture of the hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein the virtual-hand pose comprises a position of the virtual hand and a gesture of the virtual hand, wherein the position of the virtual hand corresponds to the position of the hand, wherein the gesture of the virtual hand is based on the virtual-object data, and wherein the gesture of the virtual hand is different from the gesture of the hand.
2. The apparatus of claim 1, wherein the at least one processor is further configured to display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand and a gesture of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand and the gesture of the shadow virtual hand corresponding to the gesture of the hand.
3. The apparatus of claim 1, wherein the gesture of the virtual hand is based on an interaction pose of the virtual object indicated by the virtual-object data.
4. The apparatus of claim 1, wherein: the hand-pose data comprises first hand-pose data and the gesture of the hand comprises a first gesture; the pose of the hand comprises a first pose of the hand comprising the first gesture of the hand; the virtual-object data comprises first virtual-object data; the virtual object comprises a first virtual object; the virtual-hand pose comprises a first virtual hand pose; and the at least one processor is further configured to: obtain second hand-pose data indicative of a second pose of the hand, the second pose of the hand comprising a second gesture of the hand that is the same as the first gesture of the hand; obtain second virtual-object data indicative of a second virtual object with which the hand is virtually interacting, the second virtual-object data being different than the first virtual-object data; and display the virtual hand interacting with the second virtual object, the virtual hand exhibiting a second virtual-hand pose, the second virtual-hand pose different from the first virtual hand pose based on the second virtual-object data being different than the first virtual-object data.
5. The apparatus of claim 1, wherein: the pose of the hand comprises a position of the hand; the

virtual-hand pose comprises a position of the virtual hand; and the position of the virtual hand is delayed relative to the position of the hand based on the virtual-object data.

6. The apparatus of claim 5, wherein the position of the virtual hand is delayed relative to the position of the hand based on a weight of the virtual object indicated by the virtual-object data.

7. The apparatus of claim 5, wherein the at least one processor is further configured to display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand.

8. The apparatus of claim 1, wherein the virtual-hand pose is different from the pose of the hand.

9. The apparatus of claim 1, wherein: the virtual-object data is based on characteristics of the virtual object; and the characteristics of the virtual object include one or more of: a size of the virtual object, a shape of the virtual object, a weight of the virtual object, a distance between the hand and the virtual object, or an interaction pose of the virtual object.

10. The apparatus of claim 1, wherein the at least one processor is further configured to display a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose corresponding to the pose of the hand.

11. The apparatus of claim 10, wherein to display the shadow virtual hand the at least one processor is further configured to display the shadow virtual hand as translucent.

12. The apparatus of claim 1, wherein the at least one processor is further configured to: obtain one or more images of the hand; and determine, based on the one or more images of the hand, the hand-pose data, the hand-pose data comprising a position of the hand and a gesture of the hand.

13. The apparatus of claim 1, wherein: the pose of the hand comprises a position of the hand and a gesture of the hand; the virtual-object data comprises a position of the virtual object; and the at least one processor is further configured to determine that the hand is virtually interacting with the virtual object based on a relationship between the position of the hand and the position of the virtual object and the gesture of the hand.

14. An apparatus for displaying one or more virtual objects, the apparatus comprising: at least one memory; and at least one processor coupled to the at least one memory and configured to: obtain hand-pose data indicative of a pose of a hand, wherein the pose of the hand comprises a position of the hand and a gesture of the hand; obtain virtual-object data indicative of a virtual object with which the hand is virtually interacting; and display a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein the virtual-hand pose comprises a position of the virtual hand and a gesture of the virtual hand, wherein the position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data, wherein the gesture of the virtual hand is based on the virtual-object data, and wherein the gesture of the virtual hand is different from the gesture of the hand.

15. A method for displaying one or more virtual objects, the method comprising: obtaining hand-pose data indicative of a pose of a hand, wherein the pose of the hand comprises a position of the hand and a gesture of the hand; obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein the virtual-hand pose comprises a position of the virtual hand and a gesture of the virtual hand, wherein the position of the virtual hand corresponds to the position of the hand, wherein the gesture of the virtual hand is based on the virtual-object data, and wherein the gesture of the virtual hand is different from the gesture of the hand.

16. The method of claim 15, further comprising displaying a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand and a gesture of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand and the gesture of the shadow virtual hand corresponding to the gesture of the hand.

17. The method of claim 15, wherein the gesture of the virtual hand is based on an interaction pose of the virtual object indicated by the virtual-object data.
18. The method of claim 15, wherein: the hand-pose data comprises first hand-pose data and the gesture of the hand comprises a first gesture; the pose of the hand comprises a first pose of the hand comprising the first gesture of the hand; the virtual-object data comprises first virtual-object data; the virtual object comprises a first virtual object; the virtual-hand pose comprises a first virtual hand pose; and the method further comprises: obtaining second hand-pose data indicative of a second pose of the hand, the second pose of the hand comprising a second gesture of the hand that is the same as the first gesture of the hand; obtaining second virtual-object data indicative of a second virtual object with which the hand is virtually interacting, the second virtual-object data being different than the first virtual-object data; and displaying the virtual hand interacting with the second virtual object, the virtual hand exhibiting a second virtual-hand pose, the second virtual-hand pose different from the first virtual hand pose based on the second virtual-object data being different than the first virtual-object data.
19. The method of claim 15, wherein: the pose of the hand comprises a position of the hand; the virtual-hand pose comprises a position of the virtual hand; and the position of the virtual hand is delayed relative to the position of the hand based on the virtual-object data.
20. The method of claim 19, wherein the position of the virtual hand is delayed relative to the position of the hand based on a weight of the virtual object indicated by the virtual-object data.
21. The method of claim 19, further comprising displaying a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose comprising a position of the shadow virtual hand, the position of the shadow virtual hand corresponding to the position of the hand.
22. The method of claim 15, wherein the virtual-hand pose is different from the pose of the hand.
23. The method of claim 15, wherein: the virtual-object data is based on characteristics of the virtual object; and the characteristics of the virtual object include one or more of: a size of the virtual object, a shape of the virtual object, a weight of the virtual object, a distance between the hand and the virtual object, or an interaction pose of the virtual object.
24. The method of claim 15, further comprising displaying a shadow virtual hand exhibiting a shadow-virtual-hand pose, the shadow-virtual-hand pose corresponding to the pose of the hand.
25. The method of claim 24, wherein displaying the shadow virtual hand comprises displaying the shadow virtual hand as translucent.
26. A method for displaying one or more virtual objects, the method comprising: obtaining hand-pose data indicative of a pose of a hand, wherein the pose of the hand comprises a position of the hand and a gesture of the hand; obtaining virtual-object data indicative of a virtual object with which the hand is virtually interacting; and displaying a virtual hand interacting with the virtual object, the virtual hand exhibiting a virtual-hand pose based on the pose of the hand and the virtual-object data, wherein the virtual-hand pose comprises a position of the virtual hand and a gesture of the virtual hand, wherein the position of the virtual hand is delayed relative to a position of the hand based on the virtual-object data, wherein the gesture of the virtual hand is based on the virtual-object data, and wherein the gesture of the virtual hand is different from the gesture of the hand.
-