

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401726
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Mall; Mohamed et al.

Systems and methods for automatic user profile switching

Abstract

Aspects of the present disclosure include systems and methods for profile switching by the computing device. In an example, a computing device may include a memory storing instructions and a processor communicatively coupled with the memory and configured to execute the instructions. The processor may receive a request to initiate a new instance of a website. The processor may also determine a domain name of the website in response to the request. The processor may also determine a first user profile from a plurality of user profiles that corresponds to the domain name based on profile information corresponding to one or more of profile history data, profile favorites data, or administrative settings data. The processor may also launch the new instance of the website in a browser according to the first user profile.

Inventors: Mall; Mohamed (Sydney, AU), Andrew; Felix Gerard Torquil Ifor (Seattle, WA)

Applicant: Microsoft Technology Licensing, LLC (Redmond, WA)

Family ID: 1000008782104

Assignee: Microsoft Technology Licensing, LLC (Redmond, WA)

Appl. No.: 18/509651

Filed: November 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240089332 A1	Mar. 14, 2024

Related U.S. Application Data

continuation parent-doc US 17554914 20211217 US 11863634 child-doc US 18509651
continuation parent-doc US 16682932 20191113 US 11206315 20211221 child-doc US 17554914

Publication Classification

Int. Cl.: **G06F15/16** (20060101); **G06F16/955** (20190101); **H04L41/0859** (20220101);
H04L61/3015 (20220101); **H04L61/4511** (20220101); **H04L67/306** (20220101)

U.S. Cl.:

CPC **H04L67/306** (20130101); **G06F16/9558** (20190101); **G06F16/9562** (20190101);
H04L41/0859 (20130101); **H04L61/3025** (20130101); **H04L61/4511** (20220501);

Field of Classification Search

CPC: H04L (67/306); H04L (61/4511); H04L (41/0859); H04L (61/3025); G06F (16/9558);
G06F (16/9562)

USPC: 709/203

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11206315	12/2020	Mall	N/A	H04L 61/3025
2014/0244784	12/2013	Jaskiewicz	709/217	H04L 67/306
2017/0344384	12/2016	Wadley	N/A	G06F 9/451
2020/0320218	12/2019	Buehler	N/A	H04W 12/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101681459	12/2009	CN	N/A
106164919	12/2015	CN	N/A

OTHER PUBLICATIONS

First Office Action Received for Chinese Application No. 202080078728, mailed on Jun. 7, 2024, 12 pages (English Translation Provided). cited by applicant

“HTTP cookie—Wikipedia,” Retrieved from the Internet URL:

https://web.archive.org/web/20181202134913/https://en.wikipedia.org/wiki/HTTP_cookie,
retrieved on Apr. 17, 2024, 20 Pages. cited by applicant

Summons to attend oral proceedings pursuant to Rule 115(1) EPC, received for European Application No. 20807620.8, mailed on Mar. 27, 2024, 07 pages. cited by applicant

Office Action Received for Chinese Application No. 202080078728.X, mailed on Dec. 5, 2024, 4 pages (English Translation Provided). cited by applicant

Communication pursuant to 94(3) Received for European Application No. 20807620.8, mailed on Dec. 12, 2023, 5 pages. cited by applicant

Decision to refuse a European patent application to Article 97(2) Received for European Application No. 20807620.8, mailed on Feb. 4, 2025, 04 Pages. cited by applicant

Primary Examiner: Chou; Alan S

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation of U.S. application Ser. No. 17/554,914 filed Dec. 17, 2021, which is a Continuation of U.S. application Ser. No. 16/682,932, filed Nov. 13, 2019, now Issued U.S. Pat. No. 11,206,315 and which applications are incorporated herein by reference. To the extent appropriate, a claim of priority is made to each of the above-disclosed applications.

BACKGROUND

(1) The present disclosure relates to computing devices, and more particularly, to systems and methods for automatic profile switching by a computing device.

(2) A user profile may provide a custom experience for a user on a domain or website based on stored settings such as browsing settings, bookmarks, or saved passwords. For example, when a user visits a website, the website may request for user profile information (e.g., username and password). Once the user profile information is entered, the browser may save the user profile information and the website may store browsing information (e.g., cookies) related to the user profile information. In this example, the website may remember products viewed by the user to provide recommendations to the user during the current visit or on a next visit to the website. Typically, a user visits a website without providing any user profile information or a browser automatically provides the website with user profile information entered during a previous visit to the website. However, in some situations, the browser may provide the website with the user profile information but the user may prefer to use an alternative user profile associated with the website.

(3) Accordingly, there is a need in the art for improvements to user profile switching.

SUMMARY

(4) The following presents a simplified summary of one or more implementations of the present disclosure in order to provide a basic understanding of such implementations. This summary is not an extensive overview of all contemplated implementations, and is intended to neither identify key or critical elements of all implementations nor delineate the scope of any or all implementations. Its sole purpose is to present some concepts of one or more implementations of the present disclosure in a simplified form as a prelude to the more detailed description that is presented later.

(5) In an aspect, a computing device including a memory storing instructions for profile switching by the computing device and a processor communicatively coupled with the memory, is disclosed. The processor may be configured to execute the instructions to receive a request to initiate a new instance of a website. determine a domain name of the website in response to the request. The processor may also be configured to execute the instructions to determine a first user profile from a plurality of user profiles that corresponds to the domain name based on user profile information corresponding to one or more of profile history data, profile favorites data, or administrative settings data. The processor may also be configured to execute the instructions to launch the new instance of the website in a browser according to the first user profile.

(6) In another aspect, a method for profile switching by a computing device is disclosed. The method may include receiving a request to initiate a new instance of a website. The method may also include determining a domain name of the website in response to the request. The method may also include determining a first user profile of a plurality of user profiles corresponds to the domain name based on user profile information corresponding to one or more of profile history data, profile favorites data, or administrative settings data. The method may also include launching the new instance of the website in a browser according to the first user profile.

(7) In another aspect, a computer-readable medium storing instructions executable by a processor is disclosed. The computer-readable medium may include instructions to receive a request to initiate a

new instance of a website. The computer-readable medium may also include instructions to determine a domain name of the website in response to the request. The computer-readable medium may also include instructions to determine a first user profile of a plurality of user profiles corresponds to the domain name based on user profile information corresponding to one or more of profile history data, profile favorites data, or administrative settings data. The computer-readable medium may also include instructions to launch the new instance of the website in a browser according to the first user profile.

(8) Additional advantages and novel features relating to implementations of the present disclosure will be set forth in part in the description that follows, and in part will become more apparent to those skilled in the art upon examination of the following or upon learning by practice thereof.

Description

DESCRIPTION OF THE FIGURES

(1) In the drawings:

(2) FIG. 1 is a conceptual view of an example user interface of a computing device, according to aspects of the present disclosure;

(3) FIG. 2 is a conceptual view of an example computing device, according to aspects of the present disclosure;

(4) FIG. 3 is another conceptual view of an example user interface of a computing device, according to aspects of the present disclosure;

(5) FIG. 4 is a flowchart of an example method for profile switching by the computing device of FIG. 2, according to aspects of the present disclosure; and

(6) FIG. 5 is a block diagram of additional components of the example computing device of FIG. 2, according to aspects of the present disclosure.

DETAILED DESCRIPTION

(7) The present disclosure provides systems and methods for automatic user profile switching by a computing device. In an example, the systems and methods disclosed herein may allow a computing device to switch user profiles based on user profile information including one or more of user preferences, past use of a user profile, favorite settings, domain name, subdomain, query parameters of a uniform resource locator (URL), or administrative settings.

(8) For example, a browser may support multiple user profiles such as @microsoft.com or @outlook.com. When a user visits a website (e.g., an online shopping site) for a personal reason, the user may want to use the user profile under @outlook.com, and when the user visits a website (e.g., sharepoint.microsoft.com) for a business reason, the user may want to use the user profile under @microsoft.com. In another example, when a user clicks on a link sent in an email, a browser may launch but the browser does not know which account or user profile the user would like to use. If the URL associated with the link relates to work, a work related user profile would be ideal, and if the URL is social, a personal related user profile would be ideal. According to aspects of the present disclosure, the browser may switch user profiles based on the user profile information. Further, when the user switches user profiles manually, the browser may be configured to prompt the user to provide an indication of whether the switch is a permanent switch, and record the indication accordingly.

(9) Turning now to the figures, examples of systems and methods for automatic user profile switching by a computing device are depicted. It is to be understood that aspects of the figures may not be drawn to scale and are instead drawn for illustrative purposes.

(10) Referring to FIG. 1, a conceptual view of an example user interface **100** of a computing device is depicted. Examples of the computing device may include a cellular phone, a smart phone, a laptop, a personal digital assistant (PDA), a multimedia device, a video device, a digital audio

player (e.g., MP3 player), a camera, a game console, a tablet, a smart device, a wearable device, a large or small kitchen appliance, IoT devices, or any other similar functioning device that is capable of displaying the user interface **100**.

(11) As shown, the user interface **100** may display a first application **110** (e.g., email application) for interaction with a user. In an example, content **112** of the first application **110** may display a link **114** for the user to access a website (e.g., www.businesssite.com). In response to the link **114** being selected by the user, the user interface **100** may transition to a browser **120** to display content **124** of a website **122** corresponding to the link **114**.

(12) In some situations, the browser **120** may determine whether the website **122** was accessed under a first user profile **126** (e.g. Profile 1) at a previous visit to the website **122**, and reuses the first user profile from the previous visit to the website **122**. In other words, a profile manager for the browser **120** typically retains user profile information which includes the website **122** and credentials (e.g., username and password) associated with (or used during) the last visit to the website **122**. However, in some examples, the user may want the website **122** to be displayed under a different user profile (e.g., Profile 2) than the last used user profile to visit the website **122**.

(13) Aspects of the present disclosure describe a profile manager for the browser **120** which allows the browser **120** to switch user profiles based on one or more of a password list, user profile history, an administrative settings, or a profile favorites setting. In some examples, the profile manager of the browser **120** may further use domain name, subdomain name, and or query parameters in determining which user profile to use.

(14) Referring to FIG. 2, a conceptual view of an example computing device **200** for profile switching is depicted. In an aspect, the computing device **200** may include a profile manager **210** configured to manage a plurality of user profiles **222** and to select a user profile from the plurality of user profiles **222** to launch a website in the browser **120**.

(15) In an aspect, the profile manager **210** may communicate with an originating application **204** to receive a request (e.g., link **114**) to access a website (e.g., website **122**) and may provide information to the browser **120** for the website to be launched under a selected user profile based on user profile information **220**. In an example, the originating application **204** may be any application installed on the computing device **200** (e.g., first application **110** or browser **120**) or any online application (e.g., online email application) accessed by the computing device **200**.

(16) In an example, the profile manager **210** may include a URL component manager **212** configured to receive the request from the originating application **204** and determine URL component data **240** corresponding to a URL associated with the request. For example, the URL component manager **212** may determine the URL component data **240** by parsing a domain name, a subdomain name, a path, and/or a query parameter from a URL (e.g., www.businesssite.com) associated with the request.

(17) In an aspect, the profile manager **210** may also include a profile determiner **214** configured to determine a first user profile from a plurality of user profiles **222** that corresponds to the domain name based on the user profile information **220**. In an example, the profile determiner **214** may receive the user profile information **220** from a memory **216**.

(18) In an aspect, the user profile information **220** may include user profiles **222**, credential data **224**, profile history data **226**, profile favorites data **228**, or administrative (admin) settings data **230**. In an example, the user profiles **222** may include data indicating user profiles such as profile names or profile identifiers that correspond to websites.

(19) In an example, the credential data **224** may include data indicating credentialing information corresponding to the user profiles **222** and used to accessed websites. For example, the credential data **224** may include usernames and/or passwords corresponding to the user profiles **222** and the websites.

(20) In an example, the profile history data **226** may include data indicating historical access information of the user profiles **222** in accessing the websites. For example, the profile history data

226 may include a number of visits the user profiles **222** have made to websites, a duration of these visits to the websites, and/or a schedule (e.g., time of day, day of week) of these visits to the websites.

(21) In an example, the profile favorites data **228** may include data indicating favorite settings (e.g., as indicated by the user) corresponding to user profiles **222** and the websites. For example, the profile favorites data **228** may indicate user profiles which users have selected to be used when accessing corresponding websites.

(22) The administrative settings data **230** may include data indicating settings (or restrictions) corresponding to the user profiles **222** and the websites. In some examples, the administrative settings data **230** may allow or restrict a website from being launched under a user profile such as restrictions to personal profiles to a business intranet website.

(23) In an example, to determine a first user profile, the profile determiner **214** may review the user profile information **220** and URL component data **240** and determine one or more user profiles **222** that correspond to a domain name of the URL of the request. When a single user profile is determined to correspond to the domain name of the URL of the request, the profile determiner **214** may determine whether to open the URL under the single user profile **222** based on the user profile information **220**. For example, the profile determiner **214** may verify that the administrative settings data **230** allows the single user profile **222** to be used when launching the website.

(24) When multiple user profiles **222** correspond to a domain name of the URL of the request, the profile determiner **214** may determine which one of the multiple user profiles **222** to provide to the browser **120** to launch the website. In an example, the profile determiner **214** may look to the profile history data **226**, the profile favorites data **228**, and the administrative settings data **230** to determine whether one user profile **222** should be selected over another user profile **222**. For example, the data of the user profile information **220** may be weighted such that some of the data is weighted over other data. In some examples, the user profile information **220** may be weighted based on a descending sequential order of weight such as the administrative settings data **230** may have a greater weight than the profile favorites data **228**, which may have a greater weight than the profile history data **226**.

(25) Further, the profile determiner **214** may look to the URL component data **240** to further determine one of the multiple user profiles **222** to provide to the browser **120**. For example, the URL component data **240** may be compared to the credential data **224**, the profile history data **226**, the profile favorites data **228**, and/or the administrative settings data **230** to determine whether the URL component data **240** (e.g., subdomain name or query parameters) indicates which user profile **222** of the multiple user profiles **222** to provide to the browser **120**.

(26) Once a user profile **222** has been determined (or selected), the profile determiner **214** may send the determined user profile **222** to the browser **120** to launch the website under the determined user profile **222**. In an example, if a current browser window is open, the browser **120** may use the current browser window to launch the website under the determined user profile **222**. In another example, if there are more than one browser windows open, the browser **120** may use the most recently used browser window to launch the website under the determined user profile **222**. In another example, if there is no browser window open, the browser **120** may open a new browser window and use the new browser window to launch the website under the determined user profile **222**.

(27) Referring to FIG. 3, another conceptual view of the example user interface **100** is depicted. In this example, the browser **120** may have transitioned to a website **322** under a first profile (e.g., Profile 1) received from the profile manager **210** based on the user profile information **220**. However, there may be multiple user profiles **326** that correspond to the website **322**. Accordingly, the user may select a second profile (e.g., Profile 2) as the user profile for the website **322**.

(28) In response to manually changing to the second profile, content **324** of the website **322** may reflect the change in user profiles. For example, the content **324** for the website **322** may display

couches, as shown by FIG. 3, based on the second profile (e.g., Profile 2) having been selected, whereas the content **324** may display types of furniture different than couches based on the first profile (e.g., Profile 1).

(29) Further in response to manually changing to the second profile, a profile favorites settings window **340** may display in the user interface **100**. The profile favorites settings window **340** may include content **342** that provide the user with one or more selections **344** to select whether the second profile (i.e., user selected profile) should be designated as permanent profile switch (e.g., “favorite” profile) for a next visit to the website **322**. The user may select the one or more selections **344** and save (e.g., by selecting save button **346**) the selection **344** as profile favorites data **228**.

(30) Referring to FIG. 4, an example method **400** for profile switching by a computing device is depicted. In an example, the method **400** may be performed by the computing device **200** of FIG. 2 and one or more components of the computing device **200**, as described herein (see e.g., FIGS. 2 and 5). Examples of the operations of the method **400** may be described in relation to FIGS. 1-3 and 5.

(31) At **402**, the method **400** may include receiving a request to initiate a new instance of a website. For example, the computing device **200** and/or one or more components (e.g., processor **502**, profile manager **210**, and/or URL component manager **212**) of the computing device **200** may receive a request to initiate a new instance of the website **122**. In an example, the request may be received from the originating application **204**. Examples of the originating application **204** may be any application installed on the computing device **200** (e.g., first application **110** or browser **120**) or any online application (e.g., online email application) accessed by the computing device **200**. In an example, the request may include a URL (e.g., URL **114**) of the website (e.g., website **122**).

(32) At **404**, the method **400** may include determining a domain name of the website in response to the request. For example, the computing device **200** and/or one or more components (e.g., processor **502**, profile manager **210**, and/or URL component manager **212**) of the computing device **200** may determine a domain name of the website **122** in response to the request. For example, the URL component manager **212** may parse the components of the URL from the request to determine the domain name of the website.

(33) At **406**, the method **400** may include determining a first user profile from a plurality of user profiles that corresponds to the domain name based on user profile information. For example, the computing device **200** and/or one or more components (e.g., processor **502**, profile manager **210**, and/or profile determiner **214**) of the computing device **200** may determine a first user profile from the plurality of user profiles **222** that corresponds to the domain name based on the user profile information corresponding to one or more of the credential data **224**, the profile history data **226**, the profile favorites data **228**, or the administrative settings data **230**.

(34) In some examples, the method **400** may also include comparing the user profile information with the domain name, and determine whether the user profile information corresponding to the first user profile corresponds to the domain name. For example, the computing device **200** and/or one or more components (e.g., processor **502**, profile manager **210**, and/or profile determiner **214**) of the computing device **200** may, to determine the first user profile, compare the user profile information **220** with the domain name, and determine whether the user profile information **220** corresponding to the first user profile corresponds to the domain name.

(35) In some examples, the method **400** may also include determining multiple user profiles of the plurality of user profiles correspond to the domain name, wherein the multiple user profiles include the first user profile, and selecting the first user profile from the multiple user profiles based on the user profile information corresponding to one or more of a subdomain name or query parameters of a URL. For example, the computing device **200** and/or one or more components (e.g., processor **502**, profile manager **210**, and/or profile determiner **214**) of the computing device **200** may, to determine the first user profile, compare the user profile information **220** with URL component

data **240**.

(36) At **408**, the method **400** may include launching the new instance of the website in a browser according to the first user profile. For example, the computing device **200** and/or one or more components (e.g., processor **502**, profile manager **210**, and/or profile determiner **214**) of the computing device **200** may launch the new instance of the website **122** in the browser **120** according to the first user profile. In an example, the profile manager **210** may send information for the browser **120** to launch the website **122** under the first user profile.

(37) Referring now to FIG. 5, illustrated is an example of components of the computing device **200** in accordance with an implementation, including additional component details as described herein. In one example, the computing device **200** may include a processor **502** for carrying out processing functions associated with one or more of the components and the functions described herein. The processor **502** may include a single processor or a multiple set of processors or multi-core processors. Moreover, the processor **502** may be implemented as an integrated processing system and/or a distributed processing system. In an implementation, for example, the processor **502** may include the profile manager **210**, the profile determiner **214**, and/or the URL component manager **212**.

(38) In an example, the computing device **200** may include memory **216** for storing instructions executable by the processor **502** for carrying out the functions described herein. Further, the memory **216** may store the user profile information **220** including the user profiles **222**, the credential data **224**, the profile history data **226**, the profile favorites data **228**, or the administrative settings data **230**, as described herein.

(39) The computing device **200** may include a communications component **506** that provides for establishing and maintaining communications with one or more devices utilizing hardware, software, and services, as described herein. The communications component **506** may carry communications between components on the computing device **200**, as well as between the computing device **200** and external devices and devices located across a communications network and/or devices serially or locally connected to the computing device **200**. For example, the communications component **506** may include one or more buses, and may further include transmit chain components and receive chain components associated with a transmitter and receiver, respectively, operable for interfacing with external devices. In an example, the communications component **506** may communicate with other devices using one or more technologies such as, but not limited to, WiFi, Bluetooth, infrared, or any other technology configured to receive a signal with which the computing device **200** may use for profile switching.

(40) Computing device **200** may also include a user interface component **508** operable to receive inputs from a user and/or a sensor of the computing device **200** and further operable to generate outputs for presentation (e.g., user interface **100**) to the user. The user interface component **508** may include one or more input devices **520** including but not limited to a keyboard, a number pad, a mouse, a display (e.g., touch-sensitive), a digitizer, a navigation key, a function key, a voice recognition component, any other mechanism capable of receiving an input from a user or sensor, or any combination thereof. Further, the user interface component **508** may include one or more output devices **530**, including but not limited to the display, a speaker, a haptic feedback mechanism, a printer, any other mechanism capable of presenting an output to a user, or any combination thereof. In an example, the output device **530** (e.g., display) may present the user interface **100**.

(41) As used in this application, the terms “component,” “system” and the like are intended to include a computer-related entity, such as but not limited to hardware, firmware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a computer device and the computer device can be a component. One or more

components can reside within a process and/or thread of execution and a component may be localized on one computer and/or distributed between two or more computers. In addition, these components can execute from various computer readable media having various data structures stored thereon. The components may communicate by way of local and/or remote processes such as in accordance with a signal having one or more data packets, such as data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems by way of the signal.

(42) Moreover, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise, or clear from the context, the phrase “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, the phrase “X employs A or B” is satisfied by any of the following instances: X employs A; X employs B; or X employs both A and B. In addition, the articles “a” and “an” as used in this application and the appended claims should generally be construed to mean “one or more” unless specified otherwise or clear from the context to be directed to a singular form.

(43) Various implementations or features may have been presented in terms of systems that may include a number of devices, components, modules, and the like. It is to be understood and appreciated that the various systems may include additional devices, components, modules, etc. and/or may not include all of the devices, components, modules etc. discussed in connection with the figures. A combination of these approaches may also be used.

(44) The various illustrative logics, logical blocks, and actions of methods described in connection with the embodiments disclosed herein may be implemented or performed with a specially-programmed one of a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computer devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Additionally, at least one processor may comprise one or more components operable to perform one or more of the steps and/or actions described above.

(45) Further, the steps and/or actions of a method or procedure described in connection with the implementations disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, a hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium may be coupled to the processor, such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. Further, in some implementations, the processor and the storage medium may reside in an ASIC. Additionally, the ASIC may reside in a user terminal. In the alternative, the processor and the storage medium may reside as discrete components in a user terminal. Additionally, in some implementations, the steps and/or actions of a method or procedure may reside as one or any combination or set of codes and/or instructions on a machine readable medium and/or computer readable medium, including non-transitory computer readable medium, which may be incorporated into a computer program product.

(46) In one or more implementations, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored or transmitted as one or more instructions or code on a computer-readable medium. Computer-readable media includes both computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A

storage medium may be any available media that can be accessed by a computer. By way of example, and not limitation, such computer-readable media can comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired program code in the form of instructions or data structures and that can be accessed by a computer. Disk and disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs usually reproduce data optically with lasers. Combinations of the above should also be included within the scope of computer-readable media.

(47) While implementations of the present disclosure have been described in connection with examples thereof, it will be understood by those skilled in the art that variations and modifications of the implementations described above may be made without departing from the scope hereof. Other implementations will be apparent to those skilled in the art from a consideration of the specification or from a practice in accordance with examples disclosed herein.

Claims

1. A computing device, comprising: a memory storing instructions for profile switching by the computing device; a processor communicatively coupled with the memory and configured to execute the instructions to: receive a request to initiate a new instance of a website; determine a domain name of the website in response to the request; determine a first user profile from a plurality of user profiles that each corresponds to a single user for accessing the website, wherein the user profiles among the plurality of user profiles are different from each other, wherein determining the first user profile is based on user profile information corresponding to one or more of profile history data, profile favorites data, or administrative settings data; and launch the new instance of the website in a browser according to the first user profile.
2. The computing device of claim 1, wherein the processor is further configured to execute the instructions to: compare the user profile information with the domain name; and determine whether the user profile information corresponding to the first user profile corresponds to the domain name of a uniform resource locator (URL).
3. The computing device of claim 1, wherein the profile history data includes historical access information of user profiles used to access the website.
4. The computing device of claim 1, wherein the administrative settings data indicates one or more instructions to launch the new instance of the website based on group administrative information corresponding to a group of users.
5. The computing device of claim 1, wherein the profile favorites data indicates one or more instructions to launch the new instance of the website based on user preference information.
6. The computing device of claim 1, wherein the request to initiate the new instance of the website is received from a first application different than the browser.
7. The computing device of claim 1, wherein the user profile information further corresponds to credential data.
8. A method for profile switching by a computing device, comprising: receiving a request to initiate a new instance of a website that has been launched in a browser according to a first user profile of a plurality of user profiles, each user profile corresponding to a single user for accessing the website, wherein the user profiles among the plurality of user profiles are different from each other; determining a second user profile of a plurality of user profiles, wherein determining the second user profile is based on user profile information corresponding to one or more of profile history data, profile favorites data, or administrative settings data; and launching the new instance of the website in the browser according to the second user profile.
9. The method of claim 8, wherein determining the first user profile of the plurality of user profiles

comprises: comparing the user profile information with the domain name; and determining whether the user profile information corresponding to the first user profile corresponds to the domain name of a uniform resource locator (URL).

10. The method of claim 8, wherein the profile history data includes historical access information of user profiles used to access the website.
11. The method of claim 8, wherein the administrative settings data indicates one or more instructions to launch the new instance of the website based on group administrative information corresponding to a group of users.
12. The method of claim 8, wherein the profile favorites data indicates one or more instructions to launch the new instance of the website based on user preference information.
13. The method of claim 8, wherein the request to initiate the new instance of the website is received from a first application different than the browser.
14. The method of claim 8, wherein the user profile information further corresponding to credential data.
15. A computer-readable medium storing instructions executable by a processor, comprising: instructions to receive a request to initiate a new instance of a website; instructions to determine a domain name of the website in response to the request; instructions to determine a first user profile of a plurality of user profiles that each corresponds to a single user for accessing the website, wherein the user profiles among the plurality of user profiles are different from each other, wherein determining the first user profile is based on user profile information corresponding to one or more of profile history data, profile favorites data, or administrative settings data; and instructions to launch the new instance of the website in a browser according to the first user profile.
16. The computer-readable medium of claim 15, further comprising: instructions to compare the user profile information with the domain name; and instructions to determine whether the user profile information corresponding to the first user profile corresponds to the domain name of a uniform resource locator (URL).
17. The computer-readable medium of claim 15, wherein the profile history data includes historical access information of user profiles used to access the website.
18. The computer-readable medium of claim 15, wherein the administrative settings data indicates one or more instructions to launch the new instance of the website based on group administrative information corresponding to a group of users.
19. The computer-readable medium of claim 15, wherein the profile favorites data indicates one or more instructions to launch the new instance of the website based on user preference information.
20. The computer-readable medium of claim 15, wherein the request to initiate the new instance of the website is received from a first application different than the browser.
