

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402281
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Xiao; Yongwang et al.

Heat dissipation assembly for a terminal device

Abstract

Embodiments of this application provide a terminal device, including a middle frame, a heat source device, a first heat dissipation assembly, and a second heat dissipation assembly, where the first heat dissipation assembly is disposed on one side of the middle frame, the heat source device and the second heat dissipation assembly are disposed on the other side of the middle frame, and at least one of the first heat dissipation assembly and the second heat dissipation assembly is a graphene heat dissipation assembly.

Inventors: Xiao; Yongwang (Shanghai, CN), Jin; Linfang (Dongguan, CN), Li; Hualin (Shanghai, CN), Xu; Naixiang (Shanghai, CN), Wang; Guoping (Shenzhen, CN)

Applicant: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 1000008782101

Assignee: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Appl. No.: 18/505673

Filed: November 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240081026 A1	Mar. 07, 2024

Foreign Application Priority Data

CN	201811205613.3	Oct. 15, 2018
CN	201811609350.2	Dec. 27, 2018

Related U.S. Application Data

Publication Classification

Int. Cl.: **H05K7/20** (20060101); **G06F1/20** (20060101); **H04M1/02** (20060101)

U.S. Cl.:

CPC **H05K7/20336** (20130101); **G06F1/203** (20130101); **H05K7/20481** (20130101);
H04M1/026 (20130101)

Field of Classification Search

CPC: H05K (7/20472-20481); H05K (7/20509); H05K (7/20963); H05K (7/2099); H05K
(7/20336); H05K (1/0203); G06F (1/203)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8202765	12/2011	Casey et al.	N/A	N/A
9233850	12/2015	Jang et al.	N/A	N/A
9360905	12/2015	Zhamu et al.	N/A	N/A
9431319	12/2015	Olsen et al.	N/A	N/A
10437299	12/2018	Wang	N/A	H05K 7/205
2011/0247795	12/2010	Horng	N/A	N/A
2014/0240926	12/2013	Choi	N/A	N/A
2015/0271950	12/2014	Hagiwara et al.	N/A	N/A
2016/0007504	12/2015	Wu	N/A	N/A
2016/0282914	12/2015	Saito	N/A	N/A
2017/0238442	12/2016	Zhang	N/A	N/A
2017/0315598	12/2016	Voth et al.	N/A	N/A
2018/0035528	12/2017	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103235436	12/2012	CN	N/A
203233631	12/2012	CN	N/A
203882256	12/2013	CN	N/A
104869184	12/2014	CN	N/A
104882613	12/2014	CN	N/A
204633838	12/2014	CN	N/A
105228413	12/2015	CN	N/A
205546375	12/2015	CN	N/A
205681514	12/2015	CN	N/A
106304817	12/2016	CN	N/A
106790797	12/2016	CN	N/A
206181696	12/2016	CN	N/A

107168464	12/2016	CN	N/A
107249283	12/2016	CN	N/A
107249285	12/2016	CN	N/A
107509365	12/2016	CN	N/A
107592386	12/2017	CN	N/A
107660099	12/2017	CN	N/A
206962867	12/2017	CN	N/A
207219261	12/2017	CN	N/A
207368170	12/2017	CN	N/A
108513519	12/2017	CN	N/A
207817623	12/2017	CN	N/A
108617082	12/2017	CN	N/A
20150024664	12/2014	KR	N/A

Primary Examiner: Pape; Zachary

Attorney, Agent or Firm: Slater Matsil, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/284,381, filed on Apr. 9, 2021, which is a national stage of International Application No. PCT/CN2019/107624, filed on Sep. 25, 2019, which claims priority to Chinese Patent Application No. 201811205613.3, filed on Oct. 15, 2018 and Chinese Patent Application No. 201811609350.2, filed on Dec. 27, 2018. All of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) This application relates to the field of electronic technologies, and in particular, to a terminal device.

BACKGROUND

(2) Currently, a processing module (for example, a processor) with high computing performance is disposed in many terminal devices (for example, a mobile phone and a tablet computer), and a large amount of heat is generated in a working process of the processing module.

(3) The heat generated by the processing module affects performance of the processing module and another component in an electronic device, and causes poor user experience. In the prior art, a plurality of layers of graphite sheets are usually disposed in the electronic device, and the heat generated by the processing module is dissipated by the plurality of layers of graphite sheets. Usually, a double-sided tape is used for bonding between the plurality of layers of graphite sheets. Because of poor heat conductivity of the double-sided tape, heat conductivity of the plurality of layers of graphite sheets is poor. Consequently, a heat dissipation effect of the plurality of layers of graphite sheets on the terminal device is poor.

SUMMARY

(4) This application provides a terminal device, to improve heat dissipation efficiency of the terminal device.

(5) Embodiments of this application provide a terminal device, including a middle frame, a heat source device, a first heat dissipation assembly, and a second heat dissipation assembly, where the first heat dissipation assembly is disposed on one side of the middle frame, the heat source device and the second heat dissipation assembly are disposed on the other side of the middle frame, and at

least one of the first heat dissipation assembly and the second heat dissipation assembly is a graphene heat dissipation assembly.

(6) Because the terminal device includes at least one graphene heat dissipation assembly and the graphene heat dissipation assembly has relatively good heat transfer performance, the graphene heat dissipation assembly may quickly transfer heat generated by the heat source device, to improve heat dissipation efficiency of the terminal device. In this way, the heat may be more evenly distributed in the terminal device. Because a thickness of the graphene heat dissipation assembly is relatively small, the first heat dissipation assembly or the second heat dissipation assembly occupies relatively little space in the terminal device, so that a thickness of the terminal device is relatively small.

(7) In a possible implementation, a projection of the heat source device on the middle frame and a projection of the first heat dissipation assembly on the middle frame have an overlapping part.

(8) In a possible implementation, the projection of the heat source device on the middle frame is located in a projection of the first heat dissipation assembly on the middle frame.

(9) In an actual application process, after the heat source device generates the heat, the heat source device quickly transfers the heat to an area (briefly referred to as a first area below) that is in the middle frame and that faces the heat source device. When the projection of the heat source device on the middle frame and the projection of the first heat dissipation assembly on the middle frame have the overlapping part, a part or all of the first area further faces the first heat dissipation assembly, so that heat in the first area is quickly transferred to the first heat dissipation assembly, to further improve heat dissipation efficiency.

(10) In a possible implementation, the projection of the heat source device on the middle frame and a projection of the second heat dissipation assembly on the middle frame have an overlapping part.

(11) In a possible implementation, the projection of the heat source device on the middle frame is located in the projection of the second heat dissipation assembly on the middle frame.

(12) In an actual application process, after the heat source device generates the heat, when the projection of the heat source device on the middle frame and the projection of the second heat dissipation assembly on the middle frame have the overlapping part, the heat generated by the heat source device may be quickly transferred to the second heat dissipation assembly, to improve heat dissipation efficiency.

(13) In a possible implementation, the graphene heat dissipation assembly is a single-layer graphene sheet. Because a thickness of the single-layer graphene sheet is relatively small, the first heat dissipation assembly or the second heat dissipation assembly occupies relatively little space in the terminal device, so that the thickness of the terminal device is relatively small.

(14) In a possible implementation, at least one of the following heat conductive materials is composited in the single-layer graphene sheet: copper and carbon fiber.

(15) In a possible implementation, an avoidance hole is disposed on the graphene heat dissipation assembly. In this way, it is convenient to install internal components of the terminal device.

(16) In a possible implementation, the terminal device further includes a liquid cooling pipe, and the liquid cooling pipe is attached to the middle frame. The liquid cooling pipe may quickly transfer the heat, to improve heat dissipation efficiency. Further, temperature distribution in the terminal device may be more even through temperature transfer of the liquid cooling pipe.

(17) In a possible implementation, a projection of the liquid cooling pipe on the middle frame and the projection of the heat source device on the middle frame have an overlapping part.

(18) In an actual application process, after the heat source device generates the heat, the heat source device quickly transfers the heat to an area (briefly referred to as a first area below) that is in the middle frame and that faces the heat source device. When the projection of the liquid cooling pipe on the middle frame and the projection of the heat source device on the middle frame have the overlapping part, a part or all of the first area further faces the liquid cooling pipe, so that heat in the first area is quickly transferred to the liquid cooling pipe, to further improve heat dissipation

efficiency.

(19) In a possible implementation, the projection of the liquid cooling pipe on the middle frame is located in the projection of the first heat dissipation assembly on the middle frame.

(20) When the projection of the liquid cooling pipe on the middle frame is located in the projection of the first heat dissipation assembly on the middle frame, the liquid cooling pipe may quickly transfer the heat to the first heat dissipation assembly, so that the first heat dissipation assembly may quickly dissipate the heat, to improve heat dissipation efficiency.

(21) In a possible implementation, the liquid cooling pipe is disposed on a side, of the middle frame, facing the first heat dissipation assembly, and the liquid cooling pipe is further attached to the first heat dissipation assembly.

(22) The liquid cooling pipe is attached to the first heat dissipation assembly, so that the liquid cooling pipe can quickly transfer the heat to the first heat dissipation assembly, to improve heat dissipation efficiency.

(23) In a possible implementation, the liquid cooling pipe is disposed on a side, of the middle frame, facing the second heat dissipation assembly.

(24) In a possible implementation, the liquid cooling pipe includes any one of an ultra-thin heat pipe, an ultra-thin vapor chamber, or a loop heat pipe.

(25) In a possible implementation, the liquid cooling pipe is accommodated in a groove that matches a shape of the liquid cooling pipe and that is disposed on the middle frame. In this way, a contact area between the liquid cooling pipe and the middle frame can be increased, so that the liquid cooling pipe quickly transfers the heat to the middle frame, and the liquid cooling pipe can be fastened more firmly.

(26) In a possible implementation, a part of the liquid cooling pipe is close to the heat source device, and the other part of the liquid cooling pipe is far away from the heat source device. The part, of the liquid cooling pipe, close to the heat source device is less than the other part, of the liquid cooling pipe, far away from the heat source device.

(27) In a possible implementation, a thickness of the first heat dissipation assembly is different from a thickness of the second heat dissipation assembly.

(28) In a possible implementation, a thickness of the first heat dissipation assembly or the second heat dissipation assembly is 42 micrometers. Because the thickness of the first heat dissipation assembly or the second heat dissipation assembly is relatively small, the first heat dissipation assembly or the second heat dissipation assembly occupies relatively little space in the terminal device, so that the thickness of the terminal device is relatively small.

(29) In a possible implementation, the terminal device further includes a display screen, and the display screen is disposed on the middle frame.

(30) In a possible implementation, the display screen covers the first heat dissipation assembly.

(31) In a possible implementation, the terminal device further includes a housing. The housing is disposed on the middle frame, and the housing covers the second heat dissipation assembly. The housing may protect the terminal device.

(32) In a possible implementation, the display screen covers the first heat dissipation assembly and the second heat dissipation assembly.

(33) In a possible implementation, two sides of the heat source device are wrapped with a metal shielding can. The metal shielding can may reduce electromagnetic interference of another component to the heat source device.

(34) The embodiments of this application provide the terminal device, including the middle frame, the heat source device, the first heat dissipation assembly, and the second heat dissipation assembly, where the first heat dissipation assembly is disposed on one side of the middle frame, the heat source device and the second heat dissipation assembly are disposed on the other side of the middle frame, and at least one of the first heat dissipation assembly and the second heat dissipation assembly is the graphene heat dissipation assembly. Because the terminal device includes at least

one graphene heat dissipation assembly and the graphene heat dissipation assembly has relatively good heat transfer performance, the graphene heat dissipation assembly may quickly transfer the heat generated by the heat source device, to improve heat dissipation efficiency of the terminal device. In this way, the heat may be more evenly distributed in the terminal device. Because the thickness of the graphene heat dissipation assembly is relatively small, the first heat dissipation assembly or the second heat dissipation assembly occupies relatively little space in the terminal device, so that the thickness of the terminal device is relatively small.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a structure of a terminal device according to an embodiment of this application;
- (2) FIG. 2A is a schematic diagram of a projection according to an embodiment of this application;
- (3) FIG. 2B is a schematic diagram of another projection according to an embodiment of this application;
- (4) FIG. 3 is a schematic diagram of a structure of another terminal device according to an embodiment of this application;
- (5) FIG. 4 is a schematic diagram of a structure of still another terminal device according to an embodiment of this application;
- (6) FIG. 5 is a schematic diagram of a structure of yet another terminal device according to an embodiment of this application; and
- (7) FIG. 6 is a schematic diagram of a structure of still yet another terminal device according to an embodiment of this application.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

- (8) The following describes the embodiments of this application with reference to the accompanying drawings in the embodiments of this application.
- (9) From understanding of a person skilled in the art, graphite is an allotrope of an element carbon, and the graphite has good electrical and heat conductivity. Common graphite is formed by stacking layers of planar carbon atoms that are arranged in a honeycomb shape order, and interlayer force of the graphite is relatively weak. Therefore, layers of the graphite are likely to be stripped from each other, and thin graphite sheets are formed.
- (10) When the graphite sheet is stripped into a single layer, the single layer with only one carbon atom thickness is graphene. A research shows that the graphene has super high heat conductivity. In an ideal condition, the heat conductivity of the graphene is up to 5300 W/m.K, which is more than 10 times that of copper.
- (11) An embodiment of this application provides a terminal device that dissipates heat by using graphene. The terminal device may be a mobile phone, a tablet computer, an e-reader, a notebook computer, a vehicle-mounted device, a wearable device, or the like. A graphene heat dissipation assembly is disposed in the terminal device. Because the graphene heat dissipation assembly has relatively good heat transfer performance, the graphene heat dissipation assembly may quickly transfer heat generated by a heat source device, to improve heat dissipation efficiency of the terminal device. In this way, the heat may be more evenly distributed in the terminal device. Because a thickness of the graphene heat dissipation assembly is relatively small, a first heat dissipation assembly or a second heat dissipation assembly occupies relatively little space in the terminal device, so that a thickness of the terminal device is relatively small.
- (12) The following describes in detail a structure of the terminal device shown in this application by using specific embodiments. It should be noted that the following several embodiments may exist separately, or may be combined with each other. Same or similar content is not repeatedly

described in different embodiments.

(13) FIG. 1 is a schematic diagram of a structure of a terminal device according to an embodiment of this application. Referring to FIG. 1, the terminal device may include a middle frame **11**, a heat source device **12**, a first heat dissipation assembly **13**, and a second heat dissipation assembly **14**. The first heat dissipation assembly **13** is disposed on one side of the middle frame **11**, and the heat source device **12** and the second heat dissipation assembly **14** are disposed on the other side of the middle frame **11**. At least one of the first heat dissipation assembly **13** and the second heat dissipation assembly **14** is a graphene heat dissipation assembly.

(14) The middle frame **11** may be a framework structure of the terminal device, and some or all other components of the terminal device may be directly or indirectly disposed on the middle frame **11**, to form the terminal device.

(15) Optionally, the middle frame **11** may be disposed inside the terminal device, and an edge of the middle frame **11** may be designed as a part of a housing of the terminal device. When the edge of the middle frame **11** is used as the housing of the terminal device, a function of protecting the terminal device may be implemented.

(16) Optionally, the middle frame **11** may have a planar structure or a structure similar to a planar structure. Therefore, two side faces of the middle frame **11** may be visually distinguished. The two side faces may be referred to as a front face and a rear face of the middle frame **11**, or the two side faces may be referred to as a side face and another side face of the middle frame **11**. Inside the middle frame **11**, a part of the middle frame **11** may be hollowed out based on a requirement, to dispose other components in the terminal device.

(17) Optionally, a part or all of the middle frame **11** may be made of a metal material or an alloy material (for example, an aluminum alloy). Certainly, the middle frame **11** may alternatively be made of another material. This is not specifically limited in this embodiment of this application.

(18) In this embodiment of this application, the heat source device **12** is a device that radiates relatively much heat in the terminal device.

(19) In an actual application process, heat radiated by a component is usually positively correlated with power consumption of the component. More power consumption of the component indicates more heat radiated by the component. Correspondingly, the heat source device **12** in this application may be a device whose power consumption exceeds M % of overall power consumption in the terminal device, and M may be 30, 40, or the like.

(20) Optionally, the heat source device **12** may include a processor, a processor device integrating processing and storage functions, a power supply component (for example, a battery), and the like. Certainly, the heat source device **12** may alternatively be another device. This is not specifically limited in this embodiment of this application.

(21) Optionally, the first heat dissipation assembly **13** and the second heat dissipation assembly **14** may be graphene heat dissipation assemblies. Alternatively, the first heat dissipation assembly **13** is the graphene heat dissipation assembly, and the second heat dissipation assembly **14** is a multi-layer graphite heat dissipation assembly. Alternatively, the first heat dissipation assembly **13** is a multi-layer graphite heat dissipation assembly, and the second heat dissipation assembly **14** is the graphene heat dissipation assembly.

(22) Optionally, the graphene heat dissipation assembly may be of a sheet structure.

(23) Optionally, a thickness of the first heat dissipation assembly **13** is different from a thickness of the second heat dissipation assembly **14**.

(24) Optionally, the thickness of the first heat dissipation assembly **13** or the second heat dissipation assembly **14** is greater than or equal to 40 micrometers. Optionally, the thickness of the first heat dissipation assembly **13** or the second heat dissipation assembly **14** is 42 micrometers.

(25) In an actual application process, an avoidance hole may be disposed on the graphene heat dissipation assembly based on an actual requirement, to facilitate installation of another component in the terminal device. Optionally, the first heat dissipation assembly **13** or the second heat

dissipation assembly **14** may be bent arbitrarily based on a space requirement inside the terminal device.

(26) Optionally, the graphene heat dissipation assembly may be a single-layer graphene sheet. At least one of the following heat conductive materials may be further composited in the single-layer graphene sheet: copper and carbon fiber. Certainly, in an actual application process, another heat conductive material may be further composited in the single-layer graphene sheet.

(27) In this embodiment of this application, one side of the middle frame **11** is opposite to the other side of the middle frame **11**. Optionally, one side of the middle frame **11** may be the front face of the middle frame **11**, and the other side of the middle frame **11** may be the rear face of the middle frame **11**.

(28) Optionally, The heat source device **12** is partially or completely attached to the middle frame **11**. For example, the heat source device **12** may be fastened to the middle frame **11**. Alternatively, the heat source device **12** may be disposed on another component (for example, a circuit board), and the another component is disposed on the middle frame **11**, so that the heat source device **12** is partially or completely attached to the middle frame **11**.

(29) Optionally, the heat source device **12** is disposed between the middle frame **11** and the second heat dissipation assembly **14**. The heat source device **12** may be partially or completely attached to the second heat dissipation assembly **14**.

(30) Optionally, the first heat dissipation assembly **13** may be partially or completely attached to the middle frame **11**.

(31) The following describes a heat dissipation process of the terminal device shown in the embodiment in FIG. **1**.

(32) In a running process of the terminal device, the heat source device **12** of the terminal device generates heat, and the heat generated by the heat source device **12** dissipates along each radius of a sphere by using the heat source device **12** as a sphere center. Because a distance between the middle frame **11** and the heat source device **12** is relatively short, the heat generated by the heat source device **12** may be quickly transferred to a part (for example, a part attached to the heat source device **12**) that is in the middle frame **11** and that is relatively close to the heat source device **12**. The middle frame **11** transfers the received heat inside the middle frame **11**. In addition, the middle frame **11** further transfers the heat to the first heat dissipation assembly **13**. After the first heat dissipation assembly **13** receives the heat transferred by the middle frame **11**, the first heat dissipation assembly **13** transfers the received heat inside the first heat dissipation assembly **13**. In addition, the first heat dissipation assembly **13** further transfers the heat to the middle frame **11** or another component (such as a display screen or a housing). When the heat is transferred inside a component (the middle frame **11** or the first heat dissipation assembly **13**), the heat is transferred from a high-temperature part of the component to a low-temperature part of the component. When the heat is transferred between the first heat dissipation assembly and the middle frame **11**, the first heat dissipation assembly **13** may transfer the heat to the middle frame **11**, and the middle frame **11** may also transfer the heat to the first heat dissipation assembly **13**.

(33) The heat generated by the heat source device **12** may be further transferred to the second heat dissipation assembly **14**. When the second heat dissipation assembly **14** receives the heat transferred by the heat source device **12**, the second heat dissipation assembly **14** transfers the received heat inside the second heat dissipation assembly **14**. In addition, the second heat dissipation assembly **14** further transfers the heat to the middle frame **11** or another component (such as the display screen or the housing). Optionally, when the heat is transferred between the second heat dissipation assembly and the middle frame **11**, the second heat dissipation assembly **14** may transfer the heat to the middle frame **11**, and the middle frame **11** may also transfer the heat to the second heat dissipation assembly **14**.

(34) According to the middle frame **11**, the heat source device **12**, the first heat dissipation assembly **13**, and the second heat dissipation assembly **14** of the terminal device provided in this

embodiment of this application, the first heat dissipation assembly **13** is disposed on one side of the middle frame **11**, and the heat source device **12** and the second heat dissipation assembly **14** are disposed on the other side of the middle frame **11**. At least one of the first heat dissipation assembly **13** and the second heat dissipation assembly **14** is the graphene heat dissipation assembly. Because the terminal device includes at least one graphene heat dissipation assembly and the graphene heat dissipation assembly has relatively good heat transfer performance, the graphene heat dissipation assembly may quickly transfer the heat generated by the heat source device **12**, to improve heat dissipation efficiency of the terminal device. In this way, the heat may be more evenly distributed in the terminal device. Because a thickness of the graphene heat dissipation assembly is relatively small, the first heat dissipation assembly **13** or the second heat dissipation assembly **14** occupies relatively little space in the terminal device, so that a thickness of the terminal device is relatively small.

(35) Based on any one of the foregoing embodiments, optionally, a projection of the heat source device **12** on the middle frame **11** and a projection of the first heat dissipation assembly **13** on the middle frame **11** have an overlapping part.

(36) The following describes in detail the projection of the heat source device **12** on the middle frame **11** and the projection of the first heat dissipation assembly **13** on the middle frame **11** with reference to FIG. 2A and FIG. 2B.

(37) FIG. 2A is a schematic diagram of a projection according to an embodiment of this application. FIG. 2B is a schematic diagram of another projection according to an embodiment of this application.

(38) Referring to FIG. 2A, the projection of the first heat dissipation assembly on the middle frame **11** is **A1**, and the projection of the heat source device **12** on the middle frame **11** is **A2**. A part of the projection **A2** of the heat source device **12** on the middle frame **11** overlaps a part of the projection **A1** of the first heat dissipation assembly **13** on the middle frame **11**.

(39) Referring to FIG. 2B, the projection of the first heat dissipation assembly on the middle frame **11** is **B1**, and the projection of the heat source device **12** on the middle frame **11** is **B2**. The projection **B2** of the heat source device **12** on the middle frame **11** is located in the projection **B1** of the first heat dissipation assembly **13** on the middle frame **11**.

(40) In an actual application process, after the heat source device **12** generates the heat, the heat source device **12** quickly transfers the heat to an area (briefly referred to as a first area below) that is in the middle frame **11** and that faces the heat source device **12**. When the projection of the heat source device **12** on the middle frame **11** and the projection of the first heat dissipation assembly **13** on the middle frame **11** have an overlapping part, a part or all of the first area further faces the first heat dissipation assembly **13**, so that heat in the first area is quickly transferred to the first heat dissipation assembly, to further improve heat dissipation efficiency.

(41) Based on any one of the foregoing embodiments, optionally, the projection of the heat source device **12** on the middle frame **11** and the projection of the second heat dissipation assembly **14** on the middle frame **11** have an overlapping part.

(42) Optionally, the projection of the heat source device **12** on the middle frame **11** is located in the projection of the second heat dissipation assembly **14** on the middle frame **11**.

(43) It should be noted that for the projection of the heat source device **12** on the middle frame **11** and the projection of the second heat dissipation assembly **14** on the middle frame **11**, refer to FIG. 2A and FIG. 2B. Details are not described herein again.

(44) In an actual application process, after the heat source device **12** generates the heat, when the projection of the heat source device **12** on the middle frame **11** and the projection of the second heat dissipation assembly **14** on the middle frame **11** have the overlapping part, the heat generated by the heat source device **12** may be quickly transferred to the second heat dissipation assembly **14**, to improve heat dissipation efficiency.

(45) Based on any one of the foregoing embodiments, optionally, to improve heat dissipation

efficiency and make temperature distribution in the terminal device more even, the liquid cooling pipe **15** may be further disposed in the terminal device.

(46) Optionally, the liquid cooling pipe **15** includes any one of an ultra-thin heat pipe, an ultra-thin vapor chamber, or a loop heat pipe.

(47) Optionally, the liquid cooling pipe **15** may be attached to the middle frame **11**.

(48) Optionally, the liquid cooling pipe **15** may be attached to the middle frame **11** through adhesive bonding, welding, or the like.

(49) For example, an opening groove that matches a shape of the liquid cooling pipe **15** may be disposed on the middle frame **11**, and the liquid cooling pipe **15** is disposed in the opening groove. The opening groove may be a groove.

(50) Optionally, the liquid cooling pipe **15** may be disposed on one side of the middle frame **11**, or may be disposed on the other side of the middle frame **11**. The following describes, with reference to FIG. 3 and FIG. 4, a structure of a terminal device on which the liquid cooling pipe **15** is disposed.

(51) FIG. 3 is a schematic diagram of a structure of another terminal device according to an embodiment of this application. FIG. 4 is a schematic diagram of a structure of still another terminal device according to an embodiment of this application.

(52) Referring to FIG. 3, a liquid cooling pipe **15** is disposed on a side, of a middle frame **11**, facing a first heat dissipation assembly **13**. Optionally, the liquid cooling pipe **15** may further be attached to the first heat dissipation assembly **13**.

(53) The following describes a heat dissipation process of the terminal device shown in the embodiment in FIG. 3.

(54) In a running process of the terminal device, a heat source device **12** of the terminal device generates heat, and the heat source device **12** first transfers the heat to a part that is in the middle frame **11** and that is relatively close to the heat source device **12** (for example, a part attached to the heat source device **12**). The middle frame **11** transfers the received heat inside the middle frame **11**. In addition, the middle frame **11** further transfers the heat to one end of the first heat dissipation assembly **13** and one end of the liquid cooling pipe **15**. After one end of the liquid cooling pipe **15** receives the heat, the liquid cooling pipe **15** may quickly transfer the heat to the entire liquid cooling pipe **15**, so that temperature is relatively evenly distributed in the entire liquid cooling pipe **15**. Because the liquid cooling pipe **15** is attached to the middle frame **11**, the liquid cooling pipe **15** may transfer the heat to a part that is in the middle frame **11** and that is attached to the liquid cooling pipe **15**, and the heat is transferred from the part to another part of the middle frame **11**, so that temperature of all parts in the terminal is relatively even. In addition, the liquid cooling pipe **15** further transfers the heat to the first heat dissipation assembly **13**. After the first heat dissipation assembly **13** receives the heat transferred by the middle frame **11** and/or the liquid cooling pipe **15**, the first heat dissipation assembly **13** transfers the received heat inside the first heat dissipation assembly **13**. In addition, the first heat dissipation assembly **13** further transfers the heat to the middle frame **11** or another component (such as a display screen or a housing). When the heat is transferred inside a component (the middle frame **11**, the first heat dissipation assembly **13**, or the liquid cooling pipe **15**), the heat is transferred from a high-temperature part of the component to a low-temperature part of the component. When the heat is transferred among the first heat dissipation assembly, the middle frame **11**, and the liquid cooling pipe **15**, the heat may be transferred among the three.

(55) The heat generated by the heat source device **12** may be further transferred to a second heat dissipation assembly **14**. When the second heat dissipation assembly **14** receives the heat transferred by the heat source device **12**, the second heat dissipation assembly **14** transfers the received heat inside the second heat dissipation assembly **14**. In addition, the second heat dissipation assembly **14** further transfers the heat to the middle frame **11** or another component (such as the display screen or the housing). Optionally, when the heat is transferred between the

second heat dissipation assembly and the middle frame **11**, the second heat dissipation assembly **14** may transfer the heat to the middle frame **11**, and the middle frame **11** may also transfer the heat to the second heat dissipation assembly **14**.

(56) Optionally, a projection of the liquid cooling pipe **15** on the middle frame **11** and a projection of the heat source device **12** on the middle frame **11** have an overlapping part.

(57) In an actual application process, after the heat source device **12** generates the heat, the heat source device **12** quickly transfers the heat to an area (briefly referred to as a first area below) that is in the middle frame **11** and that faces the heat source device **12**. When the projection of the liquid cooling pipe **15** on the middle frame **11** and the projection of the heat source device **12** on the middle frame **11** have an overlapping part, a part or all of the first area further faces the liquid cooling pipe **15**, so that heat in the first area is quickly transferred to the liquid cooling pipe **15**, to further improve heat dissipation efficiency.

(58) Optionally, the projection of the liquid cooling pipe **15** on the middle frame **11** is located in the projection of the first heat dissipation assembly **13** on the middle frame **11**. In other words, a length and a width of a first graphene sheet in a horizontal direction are greater than a length and a width of the liquid cooling pipe **15**.

(59) When the projection of the liquid cooling pipe **15** on the middle frame **11** is located in the projection of the first heat dissipation assembly **13** on the middle frame **11**, the liquid cooling pipe **15** may quickly transfer the heat to the first heat dissipation assembly **13**, so that the first heat dissipation assembly **13** may quickly dissipate the heat, to improve heat dissipation efficiency.

(60) Optionally, a part of the liquid cooling pipe **15** is close to the heat source device **12**, and the other part of the liquid cooling pipe **15** is far away from the heat source device **12**. The part, of the liquid cooling pipe **15**, close to the heat source device **12** is less than the other part, of the liquid cooling pipe **15**, far away from the heat source device **12**.

(61) For example, referring to FIG. 3, the part, of the liquid cooling pipe **15**, close to the heat source device **12** may be an upper part of the liquid cooling pipe **15**, and the other part, of the liquid cooling pipe **15**, far away from the heat source device **12** may be a lower part of the liquid cooling pipe **15**.

(62) For example, the part, of the liquid cooling pipe **15**, close to the heat source device **12** may be a one-third upper part of the liquid cooling pipe **15**, and the other part, of the liquid cooling pipe **15**, far away from the heat source device **12** may be a two-third lower part of the liquid cooling pipe **15**.

(63) Referring to FIG. 4, the liquid cooling pipe **15** is disposed on a side, of the middle frame **11**, facing the second heat dissipation assembly **14**.

(64) The following describes a heat dissipation process of the terminal device shown in the embodiment in FIG. 4.

(65) In a running process of the terminal device, a heat source device **12** of the terminal device generates heat, and the heat source device **12** first transfers the heat to a part that is in the middle frame **11** and that is relatively close to the heat source device **12** (for example, a part attached to the heat source device **12**). Optionally, if one end of the heat source device **12** is attached to one end of the liquid cooling pipe **15**, the heat source device **12** may further transfer the heat to one end of the liquid cooling pipe **15**. The middle frame **11** transfers the received heat inside the middle frame **11**. In addition, the middle frame **11** further transfers the heat to one end of the first heat dissipation assembly **13** and one end of the liquid cooling pipe **15**. After one end of the liquid cooling pipe **15** receives the heat, the liquid cooling pipe **15** may quickly transfer the heat to the entire liquid cooling pipe **15**, so that temperature is relatively evenly distributed in the entire liquid cooling pipe **15**. Because the liquid cooling pipe **15** is attached to the middle frame **11**, the liquid cooling pipe **15** may transfer the heat to a part that is in the middle frame **11** and that is attached to the liquid cooling pipe **15**, and the heat is transferred from the part to another part of the middle frame **11**, so that temperature is relatively evenly distributed in the middle frame **11**. The middle frame **11** may

further transfer heat of each part to the first heat dissipation assembly **13**. After the first heat dissipation assembly **13** receives the heat transferred by the middle frame **11**, the first heat dissipation assembly **13** transfers the received heat inside the first heat dissipation assembly **13**. In addition, the first heat dissipation assembly **13** further transfers the heat to the middle frame **11** or another component (such as a display screen or a housing). When the heat is transferred inside a component (the middle frame **11**, the first heat dissipation assembly **13**, or the liquid cooling pipe **15**), the heat is transferred from a high-temperature part of the component to a low-temperature part of the component. When the heat is transferred between the first heat dissipation assembly and the middle frame **11**, the first heat dissipation assembly **13** may transfer the heat to the middle frame **11**, and the middle frame **11** may also transfer the heat to the first heat dissipation assembly **13**.

(66) The heat generated by the heat source device **12** may be further transferred to a second heat dissipation assembly **14**. In addition, heat in the liquid cooling pipe **15** and the middle frame **11** may also be transferred to the second heat dissipation assembly **14**. After the second heat dissipation assembly **14** receives the heat, the second heat dissipation assembly **14** transfers the received heat inside the second heat dissipation assembly **14**. In addition, the second heat dissipation assembly **14** further transfers the heat to the middle frame **11**, the liquid cooling pipe **15**, or another component (such as the display screen or the housing). When the heat is transferred among the second heat dissipation assembly, the middle frame **11**, and the liquid cooling pipe **15**, the heat may be transferred among the three.

(67) Based on any one of the foregoing embodiments, optionally, the terminal device further includes a display screen, and the display screen is disposed on the middle frame **11**.

(68) Optionally, the display screen covers the first heat dissipation assembly **13**. The terminal device further includes a housing. The housing is disposed on the middle frame **11**, and the housing covers the second heat dissipation assembly **14**.

(69) Optionally, the display screen covers the first heat dissipation assembly **13** and the second heat dissipation assembly **14**.

(70) Based on any one of the foregoing embodiments, optionally, two sides of the heat source device **12** are wrapped with a metal shielding can. For example, the metal shielding can may be made of a copper alloy.

(71) The metal shielding can may protect the heat source device **12**. For example, the metal shielding can may reduce electromagnetic interference to the heat source device **12**.

(72) Based on any one of the foregoing embodiments, the following describes a structure of the terminal device in detail with reference to FIG. 5 and FIG. 6.

(73) FIG. 5 is a schematic diagram of a structure of yet another terminal device according to an embodiment of this application. FIG. 6 is a schematic diagram of a structure of still yet another terminal device according to an embodiment of this application.

(74) Referring to FIG. 5, the terminal device includes a display screen **16**, a first heat dissipation assembly **13**, a liquid cooling pipe **15**, a middle frame **11**, a printed circuit board (Printed Circuit Board, PCB) **19**, a heat source device **12**, a metal shielding can **18**, a second heat dissipation assembly **14**, and a rear housing **17**.

(75) A groove is disposed on a front face (one side) of the middle frame **11**, and a shape of the groove is consistent with a shape of the liquid cooling pipe **15**. The liquid cooling pipe **15** is disposed in the groove. The first heat dissipation assembly **13** is disposed on a front face of the middle frame **11**, the liquid cooling pipe **15** is disposed between the first heat dissipation assembly **13** and the middle frame **11**, and the first heat dissipation assembly **13** covers the liquid cooling pipe **15**. The display screen **16** is disposed on the front face of the middle frame **11**, the first heat dissipation assembly **13** is disposed between the middle frame **11** and the display screen **16**, and the display screen **16** covers the first heat dissipation assembly **13**.

(76) The PCB board **19** is disposed on a rear face (another side) of the middle frame **11**, the heat source device **12** is disposed on the PCB board **19**, and the heat source device **12** may be a device

such as a processor. The metal shielding can **18** is disposed on each of two sides of the PCB board **19**. The second heat dissipation assembly **14** is disposed on the rear face of the middle frame **11**, and an avoidance hole is disposed on the second heat dissipation assembly **14**, to facilitate installation of devices on the PCB board **19**. The rear housing **17** is disposed on the rear face of the middle frame **11**, the second heat dissipation assembly **14** is disposed between the middle frame **11** and the rear housing **17**, and the rear housing **17** covers the second heat dissipation assembly **14**. Optionally, a battery may be disposed on a lower side of the PCB board **19**.

(77) Optionally, the PCB board **19** may also be referred to as a printed wiring board. The circuit board may be a hard board, a flexible circuit board, or a combination thereof. The circuit board is a single-layer circuit board or a multi-layer circuit board. A wiring and a pad pattern are usually disposed on the circuit board, to dispose an electronic element on the circuit board.

(78) In an actual application process, when the terminal device runs, the heat source device **12** generates heat, and the heat is transferred to the middle frame **11**. Along the front face of the middle frame **11**, the middle frame **11** transfers the heat to the liquid cooling pipe **15** and the first heat dissipation assembly **13**. The first heat dissipation assembly **13** may further transfer the heat to the display screen **16**, and the display screen **16** dissipates the heat to air. Along the rear face of the middle frame **11**, the middle frame **11** and/or the heat source device **12** transfer/transfers the heat to the second heat dissipation assembly **14**, the second heat dissipation assembly **14** transfers the heat to the rear housing **17**, and the rear housing **17** dissipates the heat to the air. In the foregoing process, at least one of the first heat dissipation assembly **13** and the second heat dissipation assembly **14** is a graphene heat dissipation assembly. Because the graphene heat dissipation assembly and the liquid cooling pipe **15** have relatively good heat transfer performance, the graphene heat dissipation assembly and the liquid cooling pipe **15** may quickly transfer the heat generated by the heat source device **12**, to improve heat dissipation efficiency of the terminal device. In this way, the heat can be more evenly distributed in the terminal device.

(79) It should be noted that, for a heat transfer direction, reference may be made to directions indicated by arrows in FIG. 5.

(80) Referring to FIG. 6, the terminal device includes a display screen **16**, a first heat dissipation assembly **13**, a middle frame **11**, a liquid cooling pipe **15**, a PCB board **19**, a heat source device **12**, a second heat dissipation assembly **14**, and a rear housing **17**.

(81) The first heat dissipation assembly **13** and the display screen **16** are disposed on a front face (one side) of the middle frame **11**, the first heat dissipation assembly **13** is disposed between the display screen **16** and the middle frame **11**, and the display screen **16** covers the middle frame **11**.

(82) A groove is disposed on a rear face (another side) of the middle frame **11**, and a shape of the groove is consistent with a shape of the liquid cooling pipe **15**. The liquid cooling pipe **15** is disposed in the groove. The PCB board **19** is disposed on the rear face of the middle frame **11**, the liquid cooling pipe **15** is disposed between the middle frame **11** and the PCB board **19**, and the PCB board **19** covers the liquid cooling pipe **15**. The second heat dissipation assembly **14** is disposed on the rear face of the middle frame **11**, the PCB board **19** is disposed between the middle frame **11** and the second heat dissipation assembly **14**, and an avoidance hole is disposed on the second heat dissipation assembly **14**, to facilitate installation of devices on the PCB board **19**. The rear housing **17** is disposed on the rear face of the middle frame **11**, the second heat dissipation assembly **14** is disposed between the rear housing **17** and the middle frame **11**, and the rear housing **17** covers the second heat dissipation assembly **14**. Optionally, a battery may be further disposed on a side in a width direction of the PCB board **19**.

(83) In an actual application process, when the terminal device runs, the heat source device **12** generates heat, and the heat is transferred to the middle frame **11**. Along the front face of the middle frame **11**, the middle frame **11** transfers the heat to the first heat dissipation assembly **13**. The first heat dissipation assembly **13** may further transfer the heat to the display screen **16**, and the display screen **16** dissipates the heat to air. Along the rear face of the middle frame **11**, the heat source

device **12** may transfer the heat to the liquid cooling pipe **15** and the second heat dissipation assembly **14**, the second heat dissipation assembly **14** transfers the heat to the rear housing **17**, and the rear housing **17** dissipates the heat to the air. In the foregoing process, at least one of the first heat dissipation assembly **13** and the second heat dissipation assembly **14** is a graphene heat dissipation assembly. Because the graphene heat dissipation assembly and the liquid cooling pipe **15** have relatively good heat transfer performance, the graphene heat dissipation assembly and the liquid cooling pipe **15** may quickly transfer the heat generated by the heat source device **12**, to improve heat dissipation efficiency of the terminal device. In this way, the heat can be more evenly distributed in the terminal device.

(84) In this embodiment of this application, the terminal device may be of a cuboid structure, or may be of a sliding structure, for example, including a fastening part and a sliding part. Alternatively, the terminal device is of a foldable structure, for example, including a fastening part and a foldable part. In this case, a whole including the middle frame **11**, the first heat dissipation assembly **13**, the second heat dissipation assembly **14**, the heat source device **12**, the circuit board, and the like may be disposed in a part of the terminal device, or separately disposed in a plurality of parts. This is not limited.

(85) According to the terminal device in the embodiments of the present invention, by using a combination of the first heat dissipation assembly **13**, the second heat dissipation assembly **14**, and the liquid cooling pipe **15**, the heat of the heat source device **12** may be quickly transferred along a height direction of the terminal device through the liquid cooling pipe **15**, and then dissipates in a horizontal direction through the middle frame **11**, the first heat dissipation assembly **13**, and the second heat dissipation assembly **14**, so that the heat is more evenly distributed in the terminal device, and a temperature rising speed is reduced. The terminal device provides better user experience in scenarios with high power consumption, such as games.

(86) It should be noted that in this specification, that “at least one of the first heat dissipation assembly and the second heat dissipation assembly is a graphene heat dissipation assembly” includes that the first heat dissipation assembly is the graphene heat dissipation assembly, or that the second heat dissipation assembly is the graphene heat dissipation assembly, or that the first heat dissipation assembly and the second heat dissipation assembly are graphene heat dissipation assemblies.

(87) It should be noted that “first” and “second” in this specification are merely used for differentiation, and do not limit a sequence.

(88) It should be noted that the “graphite film” mentioned in this specification may also be referred to as a graphite heat conductive sheet, a graphite heat dissipation film, or a heat conductive graphite sheet.

(89) The foregoing descriptions are merely specific implementations of the present invention, but are not intended to limit the protection scope of the present invention. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in this application shall fall within the protection scope of the present invention. When no conflict occurs, the implementations of the present invention and the features in the implementations may be mutually combined. Therefore, the protection scope of the present invention shall be subject to the protection scope of the claims.

Claims

1. A terminal device, comprising: a middle frame, comprising a metal material or an alloy material; a printed circuit board (PCB); a heat source device disposed on the PCB; a first graphene heat dissipation assembly disposed on a first side of the middle frame; a second graphene heat dissipation assembly, wherein the heat source device, the PCB, and the second graphene heat dissipation assembly are disposed on a second side of the middle frame; and a liquid cooling pipe

attached to the middle frame, wherein a projection of the liquid cooling pipe on the middle frame and a projection of the heat source device on the middle frame have an overlapping part, and the projection of the liquid cooling pipe on the middle frame is located in a projection of the first graphene heat dissipation assembly on the middle frame, and the liquid cooling pipe is disposed between the first graphene heat dissipation assembly and the middle frame.

2. The terminal device according to claim 1, wherein the projection of the heat source device on the middle frame and the projection of the first graphene heat dissipation assembly on the middle frame have an overlapping part.
3. The terminal device according to claim 1, wherein the projection of the heat source device on the middle frame is located in the projection of the first graphene heat dissipation assembly on the middle frame.
4. The terminal device according to claim 1, wherein the projection of the heat source device on the middle frame and a projection of the second graphene heat dissipation assembly on the middle frame have an overlapping part.
5. The terminal device according to claim 1, wherein the projection of the heat source device on the middle frame is located in the projection of the second graphene heat dissipation assembly on the middle frame.
6. The terminal device according to claim 1, wherein each graphene heat dissipation assembly of the first graphene heat dissipation assembly and the second graphene heat dissipation assembly comprises an avoidance hole.
7. The terminal device according to claim 1, wherein the liquid cooling pipe faces the first graphene heat dissipation assembly on the middle frame, and the liquid cooling pipe is further attached to the first graphene heat dissipation assembly.
8. The terminal device according to claim 1, wherein the liquid cooling pipe comprises any one of an ultra-thin heat pipe, an ultra-thin vapor chamber, or a loop heat pipe.
9. The terminal device according to claim 1, wherein the liquid cooling pipe is accommodated in an opening groove that is comprised in the middle frame, and a shape of the opening groove matches a shape of the liquid cooling pipe.
10. The terminal device according to claim 1, wherein a first part of the liquid cooling pipe is closest to the heat source device, and a second part of the liquid cooling pipe is farthest from the heat source device, and wherein the first part of the liquid cooling pipe is smaller than the second part of the liquid cooling pipe.
11. The terminal device according to claim 1, wherein a thickness of the first graphene heat dissipation assembly is different from a thickness of the second graphene heat dissipation assembly.
12. The terminal device according to claim 1, wherein a thickness of the first graphene heat dissipation assembly or the second graphene heat dissipation assembly is 42 micrometers.
13. The terminal device according to claim 1, wherein the terminal device further comprises a display screen, and the display screen is disposed on the middle frame.
14. The terminal device according to claim 13, wherein the display screen covers the first graphene heat dissipation assembly.
15. The terminal device according to claim 14, wherein the terminal device further comprises a housing, the housing is disposed on the middle frame, and the housing covers the second graphene heat dissipation assembly.
16. The terminal device according to claim 13, wherein the display screen covers the first graphene heat dissipation assembly and the second graphene heat dissipation assembly.
17. The terminal device according to claim 1, wherein two sides of the heat source device are wrapped with a metal shielding can.
18. A terminal device, comprising: a middle frame, wherein the middle frame comprises a metal material or an alloy material; a printed circuit board (PCB); a heat source device, wherein the heat source device is disposed on the PCB; a display screen; a first graphene heat dissipation assembly

disposed on a first side of the middle frame; a second graphene heat dissipation assembly, wherein the heat source device, the PCB, and the second graphene heat dissipation assembly are disposed on a second side of the middle frame; and a liquid cooling pipe attached to the middle frame, wherein a projection of the liquid cooling pipe on the middle frame and a projection of the heat source device on the middle frame have an overlapping part, and the projection of the liquid cooling pipe on the middle frame is located in a projection of the first graphene heat dissipation assembly on the middle frame, wherein the liquid cooling pipe is disposed between the first graphene heat dissipation assembly and the middle frame; and wherein the display screen covers the first graphene heat dissipation assembly.
