

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404942
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hurst; Justin Lee et al.

Plunger or piston with hardened insert

Abstract

A valve assembly including: a hardened insert coupled with a hardened insert carrier; and a valve body coupled with a valve insert, wherein, in a closed configuration of the valve assembly, the valve body contacts a primary sealing surface of the hardened insert and the valve insert contacts an initial sealing surface of a hardened insert carrier to prevent fluid flow through the valve assembly, and, in an open configuration of the valve assembly, the valve body does not contact the primary sealing surface of the hardened insert and the valve insert does not contact the initial sealing surface of the hardened insert carrier to allow fluid flow through the valve assembly, wherein the hardened insert carrier comprises a reciprocating element, a replaceable valve carrier (RVC), or a pump fluid end body.

Inventors: Hurst; Justin Lee (Healdton, OK), Gillispie; Aric Martin (Duncan, OK), Olis; James Alan (Duncan, OK)

Applicant: Halliburton Energy Services, Inc. (Houston, TX)

Family ID: 77272634

Assignee: Halliburton Energy Services, Inc. (Houston, TX)

Appl. No.: 16/791474

Filed: February 14, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210254735 A1	Aug. 19, 2021

Publication Classification

Int. Cl.: F16K25/00 (20060101); E21B43/26 (20060101); F16K3/24 (20060101); E21B21/10 (20060101)

U.S. Cl.:

CPC **F16K25/005** (20130101); **E21B43/2607** (20200501); **F16K3/243** (20130101);
E21B21/106 (20130101)

Field of Classification Search

CPC: F16K (25/005); F16K (3/243); E21B (21/106); E21B (43/2607)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1662725	12/1927	Toney, Jr.	N/A	N/A
2673519	12/1953	Halliburton	N/A	N/A
2678006	12/1953	Gray	N/A	N/A
3005412	12/1960	Camp	N/A	N/A
3229640	12/1965	Williams	N/A	N/A
3301197	12/1966	Dodson et al.	N/A	N/A
3380247	12/1967	Colmerauer	N/A	N/A
3887305	12/1974	Ito	N/A	N/A
4478561	12/1983	Elliston	N/A	N/A
4770206	12/1987	Sjoberg	N/A	N/A
5061159	12/1990	Pryor	N/A	N/A
8360751	12/2012	Duncan	N/A	N/A
8590614	12/2012	Surjaatmadja et al.	N/A	N/A
9435454	12/2015	Blume	N/A	N/A
2005/0126638	12/2004	Gilbert	N/A	N/A
2006/0249703	12/2005	Gilbert et al.	N/A	N/A
2009/0246051	12/2008	Kim	N/A	N/A
2012/0279721	12/2011	Surjaatmadja	166/105	F04B 53/10
2014/0127036	12/2013	Buckley et al.	N/A	N/A
2014/0127058	12/2013	Buckley	417/415	F04B 39/10
2014/0127062	12/2013	Buckley et al.	N/A	N/A
2014/0322050	12/2013	Marette	417/437	F04B 49/22
2014/0356201	12/2013	Blume	N/A	N/A
2015/0144826	12/2014	Bayyouk	251/359	F16K 25/005
2016/0131131	12/2015	Weaver et al.	N/A	N/A
2016/0281699	12/2015	Gnessin et al.	N/A	N/A
2016/0319805	12/2015	Dille	N/A	N/A
2018/0073653	12/2017	Bayyouk et al.	N/A	N/A
2018/0313456	12/2017	Bayyouk et al.	N/A	N/A
2019/0011051	12/2018	Yeung	N/A	N/A
2019/0040966	12/2018	Myers et al.	N/A	N/A
2019/0063427	12/2018	Nowell	N/A	F16K 1/427
2019/0120389	12/2018	Foster	N/A	F16K 1/443
2019/0145391	12/2018	Davids	417/2	F04B 49/20
2019/0368619	12/2018	Barnett	N/A	F04B 53/1032
2019/0376508	12/2018	Wagner et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
257522	12/1947	CH	N/A
19808724	12/1997	DE	N/A
0580196	12/1993	EP	N/A
1103722	12/2000	EP	N/A
2383470	12/2010	EP	N/A
120622	12/1917	GB	N/A
450645	12/1935	GB	N/A
672173	12/1951	GB	N/A
1226014	12/1970	GB	N/A
1262826	12/1971	GB	N/A
63001012	12/1987	JP	N/A
2002037217	12/2001	JP	N/A
2004257283	12/2003	JP	N/A
4121804	12/2007	JP	N/A
2009131747	12/2008	JP	N/A
5107651	12/2011	JP	N/A
2020040010	12/2019	JP	N/A
2019191276	12/2018	WO	N/A

OTHER PUBLICATIONS

Surjaatmadja, Jim Basuki et al., Fling Receipt, Specification and Drawings for U.S. Appl. No. 16/436,356, filed Jun. 10, 2019, titled “Multi-Material Frac Valve Poppet,” 78 pages. cited by applicant

Hurst, Justin Lee et al., Filing Receipt, Specification and Drawings for U.S. Appl. No. 16/791,479, filed Feb. 14, 2020, titled “Pump Valve Assembly,” 91 pages. cited by applicant

Hurst, Justin Lee et al., “Filing Receipt, Specification and Drawings for U.S. Appl. No. 16/411,910, filed May 14, 2019, titled” Valve Assembly for a Fluid End with Limited Access, 75 pages. cited by applicant

Hurst, Justin Lee et al., Filing Receipt, Specification and Drawings for U.S. Appl. No. 16/411,898, filed May 14, 2019, titled “Pump Valve Seat with Supplemental Retention,” 72 pages. cited by applicant

Foreign Communication from Related Application—International Search Report and Written Opinion of the International Searching Authority, International Application No. PCT/US2020/022043, dated Jul. 3, 2020, 13 pages. cited by applicant

Office Action (33 pages), U.S. Appl. No. 16/791,479, dated Mar. 26, 2021. cited by applicant

Kiani, Mahdi et al., “Numerical Modeling and Analytical Investigation of Autofrettage Process on the Fluid End Module of Fracture Pumps,” Journal of Pressure Vessel Technology, Aug. 2018, pp. 0414031-0414037, vol. 140, ASME. cited by applicant

“Pump Catalog,” Cat Pumps, Inc., 2014, 24 pages. cited by applicant

Furuta, Katsunori et al., “ Study of the In-Line Pump System for Diesel Engines to Meet Future Emission Regulations,” SAE International Congress and Exposition, Feb. 1998, pp. 125-136, Society of Automotive Engineers, Inc. cited by applicant

“550 Series: High Pressure, High Flow Water Jetting,” Gardner Denver Water Jetting Systems, Inc., 2009, 4 pages. cited by applicant

Houghton, J.E. et al., “Improved Pump Run Time Using Snow Auto-Rotating Plunger (SARP) Pump,” SPE Western Regional Meeting, May 1998, SPE46217, 6 pages, Society of Petroleum

Engineers, Inc. cited by applicant

“Improved Double Acting Pump,” Scientific American, 1867, pp. 248, vol. 17, No. 16, American Periodicals. cited by applicant

Langewis, Jr., C et al., “Practical Hydraulics of Positive Displacement Pumps for High-Pressure Waterflood Installations,” Journal of Petroleum Technology, Feb. 1971, pp. 173-179, SPE-AIME/Continental Oil Co. cited by applicant

Petzold, Martin et al., “Visualization and Analysis of the Multiphase Flow in an Electromagnetically Driven Dosing Pump,” ASME/BATH Symposium on Fluid Power & Motion Control, Oct. 2013, FPMC2013-4433, 6 pages, ASME. cited by applicant

Romer, M. C. et al., “Field Trial of a Novel Self-Reciprocating Hydraulic Pump for Deliquification,” SPE Production & Operations, 2017, 12 pages, Society of Petroleum Engineers. cited by applicant

Foreign Communication from Related Application—International Search Report and Written Opinion of the International Searching Authority, International Application No.

PCT/US2020/018718, dated Oct. 30, 2020, 14 pages. cited by applicant

Foreign Communication from Related Application—International Search Report and Written Opinion of the International Searching Authority, International Application No.

PCT/US2020/018719, dated Nov. 3, 2020, 13 pages. cited by applicant

Primary Examiner: Tietjen; Marina A

Attorney, Agent or Firm: Conley Rose, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) Not applicable.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(2) Not applicable.

TECHNICAL FIELD

(3) The present disclosure relates generally to a method and apparatus for supplying pressurized fluids. More particularly, the present disclosure relates to methods and reciprocating devices for pumping fluids into a wellbore.

BACKGROUND

(4) High-pressure pumps having reciprocating elements such as plungers or pistons are commonly employed in oil and gas production fields for operations such as drilling and well servicing. For instance, one or more reciprocating pumps may be employed to pump fluids into a wellbore in conjunction with activities including fracturing, acidizing, remediation, cementing, and other stimulation or servicing activities. Due to the harsh conditions associated with such activities, many considerations are generally taken into account when designing a pump for use in oil and gas operations. One design consideration may concern lifetime and reliability of pump fluid end components, as reciprocating pumps used in wellbore operations, for example, often encounter high cyclical pressures and various other conditions that can render pump components susceptible to wear and result in a need for servicing and maintenance of the pump.

(5) Accordingly, it is desirable to provide a pump fluid end that enhances a life of components therein, such as a valve assembly, whereby maintenance can be minimized and/or simplified.

Description

BRIEF SUMMARY OF THE DRAWINGS

- (1) For a more complete understanding of this disclosure, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts.
- (2) FIG. 1 is an elevational view of a reciprocating pump, according to embodiments of this disclosure.
- (3) FIG. 2A is a cut-away illustration of an exemplary reciprocating pump comprising a cross-bore pump fluid end, according to embodiments of the present disclosure.
- (4) FIG. 2B is a cut-away illustration of an exemplary reciprocating pump comprising a cross-bore pump fluid end, according to other embodiments of the present disclosure.
- (5) FIG. 3 is a cut-away illustration of an exemplary reciprocating pump comprising a concentric bore pump fluid end, according to embodiments of the present disclosure.
- (6) FIG. 4 is cut-away illustration of a pump power end of a pump, according to embodiments of the present disclosure.
- (7) FIG. 5 is a schematic of a valve assembly, according to embodiments of the present disclosure, in which the hardened insert carrier comprises the reciprocating element.
- (8) FIG. 6A is a schematic of another valve assembly, according to embodiments of the present disclosure, in which the hardened insert carrier comprises the replaceable valve carrier (RVC).
- (9) FIG. 6B is a schematic of a pump fluid end comprising the valve assembly of FIG. 6A.
- (10) FIG. 7A is a schematic of another valve assembly, according to embodiments of the present disclosure, in which the hardened insert carrier comprises the pump fluid end body.
- (11) FIG. 7B is a schematic of a pump fluid end comprising the valve assembly of FIG. 7A.
- (12) FIG. 8 is a schematic of another valve assembly, according to embodiments of the present disclosure.
- (13) FIG. 9A is a schematic of another valve assembly, according to embodiments of the present disclosure, in which the hardened insert carrier comprises the reciprocating element.
- (14) FIG. 9B is a schematic of another valve assembly, according to embodiments of the present disclosure, in which the hardened insert carrier comprises the reciprocating element.
- (15) FIG. 9C is a schematic of another valve assembly, according to embodiments of the present disclosure, in which the hardened insert carrier comprises the replaceable valve carrier (RVC).
- (16) FIG. 9D is a schematic of another valve assembly, according to embodiments of the present disclosure, in which the hardened insert carrier comprises the pump fluid end body.
- (17) FIG. 10 is a schematic representation of an embodiment of a wellbore servicing system, according to embodiments of this disclosure.

DETAILED DESCRIPTION

- (18) It should be understood at the outset that although an illustrative implementation of one or more embodiments are provided below, the disclosed systems and/or methods may be implemented using any number of techniques, whether currently known or in existence. The disclosure should in no way be limited to the illustrative implementations, drawings, and techniques illustrated below, including the exemplary designs and implementations illustrated and described herein, but may be modified within the scope of the appended claims along with their full scope of equivalents.
- (19) Disclosed herein is a reciprocating apparatus for pumping pressurized fluid. In embodiments, the reciprocating apparatus comprises a pump fluid end containing a valve assembly. The valve assembly of this disclosure comprises: a hardened insert coupled with a hardened insert carrier; and a valve body coupled with a valve insert, wherein, in a closed configuration of the valve assembly, the valve body contacts a primary sealing surface of the hardened insert and the valve insert contacts an initial sealing surface of the hardened insert carrier to prevent fluid flow through the

valve assembly, and, in an open configuration of the valve assembly, the valve body does not contact the primary sealing surface of the hardened insert and the valve insert does not contact the initial sealing surface of the hardened insert carrier to allow fluid flow through the valve assembly. The valve body and the hardened insert carrier are coaxially aligned along a central axis of the valve assembly. In embodiments, the reciprocating apparatus is a high-pressure pump configured to operate at a pressure greater than or equal to about 3,000 psi and/or in a well servicing operation and environment. Utilization of a valve assembly of this disclosure as a suction valve assembly and/or utilization of a valve assembly of this disclosure as a discharge valve assembly of a pump can increase a life and/or reduce a cost relative to a conventional valve assembly, thus reducing maintenance cost and downtime for maintenance of the pump.

(20) A reciprocating apparatus of this disclosure may comprise any suitable pump operable to pump fluid. Non-limiting examples of suitable pumps include, but are not limited to, piston pumps, plunger pumps, and the like. In embodiments, the pump is a rotary- or reciprocating-type pump such as a positive displacement pump operable to displace pressurized fluid. The pump comprises a pump power end, a pump fluid end, and an integration section whereby a reciprocating element (e.g., a plunger) can be mechanically connected with the pump power end such that the reciprocating element can be reciprocated within a reciprocating element bore of the pump fluid end. FIG. 1 is an elevational view (e.g., side view) of a pump 10 (e.g., a reciprocating pump) according to an exemplary embodiment, the reciprocating pump comprising a pump power end 12, a pump fluid end 22, and an integration section 11. As illustrated in FIG. 1, pump fluid end has a front S1 opposite a back S2 along a first or x-axis, a top S3 opposite a bottom S4 along a second or y-axis, wherein the y-axis is in the same plane as and perpendicular to the x-axis, and a left side and a right side along a z-axis, wherein the z-axis is along a plane perpendicular to the plane of the x-axis and the y-axis. Accordingly, toward the top of pump fluid end 22 (and pump 10) is along the y-axis toward top S3, toward the bottom of pump fluid end 22 (and pump 10) is along the y-axis toward bottom S4, toward the front of pump fluid end 22 (and pump 10) is along the x-axis toward front S1, and toward the back of pump fluid end 22 (and pump 10) is along the x-axis away from front S1.

(21) The pump fluid end 22 is integrated with the pump power end 12 via the integration section 11, such that pump power end 12 is operable to reciprocate the reciprocating element 18 within a reciprocating element bore 24 (FIGS. 2-3) of the pump fluid end 22. The reciprocating element bore 24 is at least partially defined by a cylinder wall 26. As described further hereinbelow with reference to FIGS. 2A-2B and FIG. 3, pump fluid end 22 can be a multi-bore pump fluid end (also referred to herein as a cross-bore pump fluid end) 22 or, alternatively, an in-line or “concentric” bore pump fluid end. As utilized herein, multi-bore pump fluid ends can comprise “T-bore” pump fluid ends, “X-bore” (e.g., cross shaped bore) pump fluid ends, or “Y-bore” pump fluid ends. FIG. 2A is a schematic showing a cross-bore pump fluid end 22 engaged with a reciprocating element 18, wherein the cross-bore pump fluid end 22 comprises a cross-bore 25 that makes a cross shape (+) relative to reciprocating element bore 24. FIG. 2B is a schematic showing a cross-bore pump fluid end 22 engaged with a reciprocating element 18, wherein the cross bore pump fluid end 22 comprises a tee-bore 25 that makes a “T” shape relative to reciprocating element bore 24. FIG. 3 is a schematic showing a concentric bore pump fluid end 22 engaged with a reciprocating element 18. As discussed further below, the pump 10 includes at least one fluid inlet 38 for receiving fluid from a fluid source, e.g., a suction line, suction header, storage or mix tank, blender, discharge from a boost pump such as a centrifugal pump, etc. The pump 10 also includes at least one discharge outlet 54 for discharging fluid to a discharge source, e.g., a flowmeter, pressure monitoring and control system, distribution header, discharge line, wellhead, discharge manifold pipe, and the like.

(22) The pump 10 may comprise any suitable pump power end 12 for enabling the pump 10 to perform pumping operations (e.g., pumping a wellbore servicing fluid downhole). Similarly, the pump 10 may include any suitable housing 14 for containing and/or supporting the pump power

end **12** and components thereof. The housing **14** may comprise various combinations of inlets, outlets, channels, and the like for circulating and/or transferring fluid. Additionally, the housing **14** may include connections to other components and/or systems, such as, but not limited to, pipes, tanks, drive mechanisms, etc. Furthermore, the housing **14** may be configured with cover plates or entryways for permitting access to the pump power end **12** and/or other pump components. As such, the pump **10** may be inspected to determine whether parts need to be repaired or replaced. The pump power end may also be hydraulically driven, whether it is a non-intensifying or an intensifying system.

(23) Those versed in the art will understand that the pump power end **12** may include various components commonly employed in pumps. Pump power end **12** can be any suitable pump known in the art and with the help of this disclosure to be operable to reciprocate reciprocating element **18** in reciprocating element bore **24**. For example, without limitation, pump power end **12** can be operable via and comprise a crank and slider mechanism, a powered hydraulic/pneumatic/steam cylinder mechanism or various electric, mechanical or electro-mechanical drives. FIG. **4** provides a cutaway illustration of an exemplary pump **10** of this disclosure, showing an exemplary pump power end **12**, integrated via integration section **11** with a pump fluid end **22**, wherein the pump power end **12** is operable to reciprocate the reciprocating element **18** within a reciprocating element bore **24** of the pump fluid end **22**. Briefly, for example, the pump power end **12** may include a rotatable crankshaft **16** attached to at least one reciprocating element **18** (e.g., a plunger or piston) by way of a crank arm/connecting rod **20**. Additionally, an engine (e.g., a diesel engine), motor, or other suitable power source may be operatively connected to the crankshaft **16** (e.g., through a transmission and drive shaft) and operable to actuate rotation thereof. In operation, rotation of the crankshaft **16** induces translational movement of the crank arm/connecting rod **20**, thereby causing the reciprocating element **18** to extend and retract along a flow path, which may generally be defined by a central axis **17** within a reciprocating element bore **24** (sometimes referred to herein for brevity as a “reciprocating element bore **24**” or simply a “bore **24**”, and not wishing to be limited to a particular reciprocating element **18**). Pump **10** of FIG. **1** is typically mounted on a movable structure such as a semi-tractor trailer or skid, and the moveable structure may contain additional components, such as a motor or engine (e.g., a diesel engine), that provides power (e.g., mechanical motion) to the pump power end **12** (e.g., a crankcase comprising crankshaft **16** and related connecting rods **20**).

(24) Of course, numerous other components associated with the pump power end **12** of the pump **10** may be similarly employed, and therefore, fall within the purview of the present disclosure. Furthermore, since the construction and operation of components associated with pumps of the sort depicted in FIG. **1** are well known and understood, discussion of the pump **10** will herein be limited to the extent necessary for enabling a proper understanding of the disclosed embodiments.

(25) As noted hereinabove, the pump **10** comprises a pump fluid end **22** attached to the pump power end **12**. Various embodiments of the pump fluid end **22** are described in detail below in connection with other drawings, for example FIGS. **2A-2B** and FIG. **3**. Generally, the pump fluid end **22** comprises at least one fluid inlet **38** for receiving fluid, and at least one discharge outlet **54** through which fluid flows out of the discharge chamber **53**. The pump fluid end **22** also comprises at least one valve assembly for controlling the receipt and output of fluid. For example, the pump fluid end **22** can comprise a suction valve assembly **56** and a discharge valve assembly **72**.

According to this disclosure, at least one of the suction valve assembly **56** and the discharge valve assembly **72** is provided by a valve assembly, as described hereinbelow with reference to FIG. **5**, FIG. **6A**, FIG. **6B**, FIG. **7A**, FIG. **7B**, FIG. **8**, FIG. **9A**, FIG. **9B**, FIG. **9C**, and/or FIG. **9D**. The pump fluid end **22** may include any suitable component(s) and/or structure(s) for containing and/or supporting the reciprocating element **18** and providing a cylinder wall **26** at least partially defining a reciprocating element bore **24** along which the pump power end can reciprocate the reciprocating element during operation of the pump.

(26) In embodiments, the pump fluid end **22** may comprise a cylinder wall **26** at least partially defining a bore **24** through which the reciprocating element **18** may extend and retract. Additionally, the bore **24** may be in fluid communication with a discharge chamber **53** formed within the pump fluid end **22**. Such a discharge chamber **53**, for example, may be configured as a pressurized discharge chamber **53** having a discharge outlet **54** through which fluid is discharged by the reciprocating element **18**. Thus, the reciprocating element **18** may be movably disposed within the reciprocating element bore **24**, which may provide a fluid flow path into and/or out of the pump chamber. During operation of the pump **10**, the reciprocating element **18** may be configured to reciprocate along a path (e.g., along central axis **17** within bore **24** and/or pump chamber **28**, which corresponds to reciprocal movement parallel to the x-axis of FIG. **1**) to transfer a supply of fluid to the pump chamber **28** and/or discharge fluid from the pump chamber **28**.

(27) In operation, the reciprocating element **18** extends and retracts along a flow path to alternate between providing forward strokes (also referred to as discharge strokes and correlating to movement in a positive direction parallel to the x-axis of FIG. **1**, indicated by arrow **117**) and return strokes (also referred to as suction strokes and correlating to movement in a negative direction parallel to the x-axis of FIG. **1**, indicated by arrow **116**), respectively. During a forward stroke, the reciprocating element **18** extends away from the pump power end **12** and toward the pump fluid end **22**. Before the forward stroke begins, the reciprocating element **18** is in a fully retracted position (also referred to as bottom dead center (BDC) with reference to the crankshaft **16**), in which case the suction valve assembly **56** can be in a closed configuration having allowed fluid to flow into the (e.g., high pressure) pump chamber **28**. (As utilized here, “high pressure” indicates possible subjection to high pressure during discharge.) When discharge valve assembly **72** is in a closed configuration (e.g., under the influence of a closing mechanism, such as a spring), the high pressure in a discharge pipe or manifold containing discharge outlet **54** prevents fluid flow into discharge chamber **53** and causes pressure in the pump chamber **28** to accumulate upon stroking of the reciprocating element **18**. When the reciprocating element **18** begins the forward stroke, the pressure builds inside the pump chamber **28** and acts as an opening force that results in positioning of the discharge valve assembly **72** in an open configuration, while a closing force (e.g., via a closing mechanism, such as a spring and/or pressure increase inside pump chamber **28**) urges the suction valve assembly **56** into a closed configuration. When utilized in connection with a valve assembly, ‘open’ and ‘closed’ refer, respectively, to a configuration in which fluid can flow through the valve assembly (e.g., can pass between a valve body (e.g., a movable poppet) and a hardened insert carrier or a valve seat thereof) and a configuration in which fluid cannot flow through the valve assembly (e.g., cannot pass between a valve body (e.g., a movable poppet) and a hardened insert carrier or a valve seat thereof). As the reciprocating element **18** extends forward, fluid within the pump chamber **28** is discharged through the discharge outlet **54**.

(28) During a return stroke, the reciprocating element **18** reciprocates or retracts away from the pump fluid end **22** and towards the pump power end **12** of the pump **10**. Before the return stroke begins, the reciprocating element **18** is in a fully extended position (also referred to as top dead center (TDC) with reference to the crankshaft **16**), in which case the discharge valve assembly **72** can be in a closed configuration having allowed fluid to flow out of the pump chamber **28** and the suction valve assembly **56** is in a closed configuration. When the reciprocating element **18** begins and retracts towards the pump power end **12**, the discharge valve assembly **72** assumes a closed configuration, while the suction valve assembly **56** opens. As the reciprocating element **18** moves away from the discharge valve **72** during a return stroke, fluid flows through the suction valve assembly **56** and into the pump chamber **28**.

(29) With reference to the embodiments of FIG. **2A**, which is a schematic showing a cross-bore pump fluid end **22** engaged with a reciprocating element **18**, cross-bore pump fluid end **22** comprises a cross-bore fluid end body **8**, a cross-bore pump chamber **28**, a suction valve assembly **56**, and a discharge valve assembly **72**. In this cross-bore configuration, suction valve assembly **56**

and discharge valve assembly 72 are located in a bore or channel 25 (also referred to herein as a cross bore 25) of pump chamber 28, wherein bore 25 has a central axis 27 that is parallel to the y-axis of FIG. 1 and is perpendicular to bore 24 in which reciprocating element 18 reciprocates during operation. Suction valve assembly 56 and discharge valve assembly 72 are operable to direct fluid flow within the pump 10. When reciprocating element 18 retracts, or moves along central axis 17 in a direction away from the pump chamber 28 and the pump fluid end 22 and toward the pump power end 12 (as indicated by arrow 116), a suction valve of the suction valve assembly 56 opens (e.g., either under natural flow or other biasing means), and a discharge valve of discharge valve assembly 72 will be closed, whereby fluid enters pump chamber 28 via fluid inlet 38. When the reciprocating element 18 reverses direction, due to the action of the pump power end 12, the reciprocating element 18 reverses direction along central axis 17, now moving in a direction toward the pump chamber 28 and pump fluid end 22 and away from pump power end 12 (as indicated by arrow 117), and the discharge valve of discharge valve assembly 72 is open and the suction valve of suction valve assembly 56 is closed (e.g., again either due to fluid flow and/or other biasing means of valve control), such that fluid is pumped out of pump chamber 28 via discharge outlet 54.

(30) With reference to the embodiment of FIG. 2B, which is a schematic showing a T-bore pump fluid end 22 engaged with a reciprocating element 18, T-bore pump fluid end 22 comprises a T-bore fluid end body 8, a T-shaped pump chamber 28, a suction valve assembly 56, and a discharge valve assembly 72. In this T-bore configuration of FIG. 2B, suction valve assembly 56 is coupled with front end 60 of reciprocating element 18 and discharge valve assembly 72 is positioned in bore 25 that makes a tee with reciprocating element bore 24, i.e., central axis 17 of reciprocating element bore 24 is also the central axis of suction pump assembly 56 and perpendicular to a central axis 27 of discharge valve assembly 72 (i.e., central axis 27 is parallel to the y-axis of FIG. 1 and is perpendicular to bore 24 in which reciprocating element 18 reciprocates during operation). Suction valve assembly 56 and discharge valve assembly 72 are operable to direct fluid flow within the pump 10. When reciprocating element 18 retracts, or moves along central axis 17 in a direction away from the pump chamber 28 and the pump fluid end 22 and toward the pump power end 12 (as indicated by arrow 116), a suction valve of the suction valve assembly 56 opens (e.g., either under natural flow or other biasing means), and a discharge valve of discharge valve assembly 72 will be closed, whereby fluid enters pump chamber 28 via fluid inlet 38. When the reciprocating element 18 reverses direction, due to the action of the pump power end 12, the reciprocating element 18 reverses direction along central axis 17, now moving in a direction toward the pump chamber 28 and pump fluid end 22 and away from pump power end 12 (as indicated by arrow 117), and the discharge valve of discharge valve assembly 72 is open and the suction valve of suction valve assembly 56 is closed (e.g., again either due to fluid flow and/or other biasing means of valve control), such that fluid is pumped out of pump chamber 28 via discharge outlet 54.

(31) With reference to the embodiment of FIG. 3, which is a schematic showing a concentric pump fluid end 22 engaged with a reciprocating element 18, concentric bore pump fluid end 22 comprises a concentric bore fluid end body 8, a concentric pump chamber 28, a suction valve assembly 56, and a discharge valve assembly 72. In this concentric bore configuration, suction valve assembly 56 and discharge valve assembly 72 are positioned in-line (also referred to as coaxial) with reciprocating element bore 24, i.e., central axis 17 of reciprocating element bore 24 is also the central axis of suction pump assembly 56 and discharge valve assembly 72). Suction valve assembly 56 and discharge valve assembly 72 are operable to direct fluid flow within the pump 10. In some concentric bore fluid end designs, fluid flows within a hollow reciprocating element (e.g., a hollow plunger) 18. In some such embodiments, the reciprocating element bore 24 of such a concentric bore fluid end design can be defined by a high pressure cylinder 26 providing a high pressure chamber and a low pressure cylinder (not depicted in the embodiment of FIG. 3) providing a low pressure chamber toward tail end 62 of reciprocating element 18, whereby fluid

from fluid inlet **38** enters reciprocating element **18**. When reciprocating element **18** retracts, or moves along central axis **17** in a direction away from the pump chamber **28** and pump fluid end **22** and toward pump power end **12** (as indicated by arrow **116**), a suction valve of the suction valve assembly **56** opens (e.g., either under natural flow and/or other biasing means), and a discharge valve of discharge valve assembly **72** will be closed, whereby fluid enters pump chamber **28** via a fluid inlet **38**. For a concentric bore pump fluid end **22** design, the fluid inlet can be configured to introduce fluid into pump chamber **28** via a reciprocating element **18** that is hollow and/or via a low pressure chamber as described above. When the reciprocating element **18** reverses direction, due to the action of the pump power end **12**, the reciprocating element **18** reverses direction along central axis **17**, now moving in a direction toward the pump chamber **28** and pump fluid end **22** and away from pump power end **12** (as indicated by arrow **117**), and the discharge valve of discharge valve assembly **72** is open and the suction valve of suction valve assembly **56** is closed (e.g., again either due to fluid flow and/or other biasing means of valve control), such that fluid is pumped out of pump chamber **28** via discharge chamber **53** and discharge outlet **54**.

(32) A pump **10** of this disclosure can comprise one or more access ports. For example, with reference to the cross-bore fluid end body **8** embodiments of FIG. 2A and FIG. 2B, a front access port **50A** can be located on a front **S1** of the pump fluid end **22** opposite a back **S2** of the pump fluid end **22**, wherein the back **S2** of the pump fluid end is proximal the pump power end **12**, upon integration therewith via integration section **11**. A top access port **50B** can be located on a top **S3** of the pump fluid end **22** opposite a bottom **S4** of the pump fluid end **22**, wherein the top **S1** of the pump fluid end **22** is above central axis **17** and the bottom **S4** of the pump fluid end **22** is below central axis **17**. With reference to the concentric fluid end body **8** embodiment of FIG. 3, a front access port **50A** can be located on a front **S1** of the pump fluid end **22** opposite a back **S2** of the pump fluid end **22**, wherein the back **S2** of the pump fluid end is proximal the pump power end **12**, upon integration therewith via integration section **11**. Locations described as front **S1**, back **S2**, top **S3**, and bottom **S4** are further described with reference to the x-y-z coordinate system shown in FIG. 1 and further can be relative to a surface (e.g., a trailer bed, the ground, a platform, etc.) upon which the pump **10** is located, a bottom **S4** of the pump fluid end being proximal the surface (e.g., trailer bed) upon which the pump **10** is located. Generally, due to size and positioning of pump **10**, the front **S1** and top **S3** of the pump fluid end **22** are more easily accessible than a back **S2** or bottom **S4** thereof. In a similar manner, a front of pump **10** is distal the pump power end **12** and a back of the pump **10** is distal the pump fluid end **22**. The integration section **11** can be positioned in a space between the pump fluid end **22** and the pump power end **12**, and can be safeguarded (e.g., from personnel) via a cover **15**.

(33) In embodiments, a pump fluid end **22** and pump **10** of this disclosure comprise at least one access port located on a side of the discharge valve assembly **72** opposite the suction valve assembly **56**. For example, in the cross-bore pump fluid end **22** embodiment of FIG. 2A, top access port **50B** is located on a side (e.g., top side) of discharge valve assembly **72** opposite suction valve assembly **56**, while in the concentric bore pump fluid end **22** embodiment of FIG. 3, front access port **50A** is located on a side (e.g., front side) of discharge valve assembly **72** opposite suction valve assembly **56**.

(34) In embodiments, one or more seals **29** (e.g., “o-ring” seals, packing seals, or the like), also referred to herein as ‘primary’ reciprocating element packing **29** (or “packing **29**”) may be arranged around the reciprocating element **18** to provide sealing between the outer walls of the reciprocating element **18** and the inner walls **26** defining at least a portion of the reciprocating element bore **24**. The inner walls **26** may be provided by fluid end body **8** or a sleeve within reciprocating element bore **24**, as described below. In some concentric bore fluid end designs, a second set of seals (also referred to herein as ‘secondary’ reciprocating element packing; not shown in the Figures) may be fixedly arranged around the reciprocating element **18** to provide sealing between the outer walls of the reciprocating element **18** and the inner walls of a low-pressure cylinder that defines the low

pressure chamber described hereinabove (e.g., wherein the secondary packing is farther back along the x-axis and delineates a back end of the low pressure chamber that extends from the primary packing **29** to the secondary packing). In embodiments, only a primary reciprocating element packing is utilized, as fluid enters tail end **62** of reciprocating element **18** without first contacting an outer peripheral wall thereof (i.e., no secondary reciprocating element packing is needed/utilized, because no low pressure chamber external to reciprocating element **18** is utilized). Skilled artisans will recognize that the seals may comprise any suitable type of seals, and the selection of seals may depend on various factors e.g., fluid, temperature, pressure, etc.

(35) While the foregoing discussion focused on a pump fluid end **22** comprising a single reciprocating element **18** disposed in a single reciprocating element bore **24**, it is to be understood that the pump fluid end **22** may include any suitable number of reciprocating elements. As discussed further below, for example, the pump **10** may comprise a plurality of reciprocating elements **18** and associated reciprocating element bores **24** arranged in parallel and spaced apart along the z-axis of FIG. **1** (or another arrangement such as a V block or radial arrangement). In such a multi-bore pump, each reciprocating element bore may be associated with a respective reciprocating element and crank arm, and a single common crankshaft may drive each of the plurality of reciprocating elements and crank arms. Alternatively, a multi-bore pump may include multiple crankshafts, such that each crankshaft may drive a corresponding reciprocating element. Furthermore, the pump **10** may be implemented as any suitable type of multi-bore pump. In a non-limiting example, the pump **10** may comprise a Triplex pump having three reciprocating elements **18** (e.g., plungers or pistons) and associated reciprocating element bores **24**, discharge valve assemblies **72** and suction valve assemblies **56**, or a Quintuplex pump having five reciprocating elements **18** and five associated reciprocating element bores **24**, discharge valve assemblies **72** and suction valve assemblies **56**.

(36) Reciprocating element bore **24** can have an inner diameter slightly greater than the outer diameter of the reciprocating element **18**, such that the reciprocating element **18** may sufficiently reciprocate within reciprocating element bore **24** (optionally, within a sleeve, as described hereinbelow). In embodiments, the fluid end body **8** of pump fluid end **22** has a pressure rating ranging from about 100 psi to about 3000 psi, or from about 2000 psi to about 10,000 psi, from about 5000 psi to about 30,000 psi, or from about 3000 psi to about 50,000 psi or greater. The fluid end body **8** of pump fluid end **22** may be cast, forged, machined, printed or formed from any suitable materials, e.g., steel, metal alloys, or the like. Those versed in the art will recognize that the type and condition of material(s) suitable for the fluid end body **8** may be selected based on various factors. In a wellbore servicing operation, for example, the selection of a material may depend on flow rates, pressure rates, wellbore service fluid types (e.g., particulate type and/or concentration present in particle laden fluids such as fracturing fluids or drilling fluids, or fluids comprising cryogenic/foams), etc. Moreover, the fluid end body **8** (e.g., cylinder wall **26** defining at least a portion of reciprocating element bore **24** and/or pump chamber **28**) may include protective coatings for preventing and/or resisting abrasion, erosion, and/or corrosion.

(37) In embodiments, the cylindrical shape (e.g., providing cylindrical wall(s) **26**) of the fluid end body **8** may be pre-stressed in an initial compression. Moreover, a high-pressure cylinder(s) providing the cylindrical shape (e.g., providing cylindrical wall(s) **26**) may comprise one or more sleeves (e.g., heat-shrinkable sleeves). Additionally or alternatively, the high-pressure cylinder(s) may comprise one or more composite overwraps and/or concentric sleeves (“over-sleeves”), such that an outer wrap/sleeve pre-loads an inner wrap/sleeve. The overwraps and/or over-sleeves may be non-metallic (e.g., fiber windings) and/or constructed from relatively lightweight materials. Overwraps and/or over-sleeves may be added to increase fatigue strength and overall reinforcement of the components.

(38) The cylinders and cylindrical-shaped components (e.g., providing cylindrical wall **26**) associated with the pump fluid end body **8** of pump fluid end **22** may be held in place within the

pump **10** using any appropriate technique. For example, components may be assembled and connected, e.g., bolted, welded, etc. Additionally or alternatively, cylinders may be press-fit (e.g., interference fit) into openings machined or cast into the pump fluid end **22** or other suitable portion of the pump **10**. Such openings may be configured to accept and rigidly hold cylinders (e.g., having cylinder wall(s) **26** at least partially defining reciprocating element bore **24**) in place so as to facilitate interaction of the reciprocating element **18** and other components associated with the pump **10**.

(39) In embodiments, the reciprocating element **18** comprises a plunger or a piston. While the reciprocating element **18** may be described herein with respect to embodiments comprising a plunger, it is to be understood that the reciprocating element **18** may comprise any suitable component for displacing fluid. In a non-limiting example, the reciprocating element **18** may be a piston. As those versed in the art will readily appreciate, a piston-type pump generally employs sealing elements (e.g., rings, packing, etc.) attached to the piston and movable therewith. In contrast, a plunger-type pump generally employs fixed or static seals (e.g., primary seal or packing **29**) through which the plunger moves during each stroke (e.g., suction stroke or discharge stroke).

(40) As skilled artisans will understand, the reciprocating element **18** may include any suitable size and/or shape for extending and retracting along a flow path within the pump fluid end **22**. For instance, reciprocating element **18** may comprise a generally cylindrical shape, and may be sized such that the reciprocating element **18** can sufficiently slide against or otherwise interact with the inner cylinder wall **26**. In embodiments, one or more additional components or mechanical linkages **48** (FIG. 4; e.g., clamps, adapters, extensions, etc.) may be used to couple the reciprocating element **18** to the pump power end **12** (e.g., to a pushrod **9**).

(41) In some embodiments (e.g., cross-bore pump fluid end **22** embodiments such as FIG. 2A), the reciprocating element may be substantially solid and/or impermeable (e.g., not hollow). In alternative embodiments (e.g., tee-bore pump fluid end **22** embodiment such as FIG. 2B and concentric bore pump fluid end **22** embodiment such as FIG. 3), the reciprocating element **18** comprises a peripheral wall defining a hollow body. Additionally (e.g., tee-bore pump fluid end **22** embodiments such as FIG. 2B and concentric bore pump fluid end **22** embodiments such as FIG. 3), a portion of the peripheral wall of reciprocating element **18** may be generally permeable or may include an input through which fluid may enter the hollow body and an output through which fluid may exit the hollow body. Furthermore, while the reciprocating element **18** may, in embodiments, define a substantially hollow interior and include a ported body, a base of the reciprocating element **18** proximal the pump power end **12**, when assembled, may be substantially solid and/or impermeable (e.g., a plunger having both a hollow portion and a solid portion).

(42) The reciprocating element **18** comprises a front or free end **60**. In embodiments comprising concentric bore pump fluid end designs **22** such as shown in FIG. 3, the reciprocating element **18** can contain or at least partially contain the suction valve assembly **56**. In one aspect, the suction valve assembly **56** is at least partially disposed within the reciprocating element **18** at or proximate to the front end **60** thereof. At an opposite or tail end **62** (also referred to as back end **62**) of the reciprocating element **18**, the reciprocating element **18** may include a base coupled to the pump power end **12** of the pump **10** (e.g., via crank arm **20**). In embodiments, the tail end **62** of the reciprocating element **18** is coupled to the pump power end **12** outside of pump fluid end **22**, e.g., within integration section **11**.

(43) As noted above, pump fluid end **22** contains a suction valve assembly **56**. Suction valve assembly **56** may alternately open or close to permit or prevent fluid flow. Skilled artisans will understand that the suction valve assembly **56** may be of any suitable type or configuration (e.g., gravity- or spring-biased, flow activated, etc.). Those versed in the art will understand that the suction valve assembly **56** may be disposed within the pump fluid end **22** at any suitable location therein. For instance, the suction valve assembly **56** may be disposed within the bore **25** below central axis **17** of the pump fluid end **22**, in cross-bore pump fluid end **22** designs such as FIG. 2A,

such that a suction valve body (e.g., a poppet assembly) of the suction valve assembly 56 moves toward central axis 17 when the suction valve assembly 56 opening and away from the central axis 17 when the suction valve assembly 56 is closing. The suction valve assembly 56 may be disposed within reciprocating element bore 24 and at least partially within reciprocating element 18 in tee-bore pump fluid end 22 designs such as FIG. 2B and concentric bore pump fluid end 22 designs such as FIG. 3, such that a suction valve body (e.g., a poppet assembly) of the suction valve assembly 56 moves away from the reciprocating element 18 when the suction valve assembly 56 approaches an open configuration (i.e., is opening) and toward reciprocating element 18 when the suction valve assembly 56 approaches a closed configuration (i.e., is closing).

(44) Pump 10 comprises a discharge valve assembly 72 for controlling the output of fluid through discharge chamber 53 and discharge outlet 54. Analogous to the suction valve assembly 56, the discharge valve assembly 72 may alternately open or close to permit or prevent fluid flow. Those versed in the art will understand that the discharge valve assembly 72 may be disposed within the pump chamber at any suitable location therein. For instance, the discharge valve assembly 72 may be disposed within the bore 25 proximal the top S3 of the pump fluid end 22, in cross-bore pump fluid end 22 designs such as FIG. 2A and tee-bore pump fluid end 22 designs such as FIG. 2B, such that a discharge valve body (e.g., a poppet assembly) of the discharge valve assembly 72 moves toward the discharge chamber 53 when the discharge valve assembly 72 approaches an open configuration and away from the discharge chamber 53 when the discharge valve assembly 72 approaches a closed configuration. The discharge valve assembly 72 may be disposed proximal the front S1 of bore 24 of the pump fluid end 22 (e.g., at least partially within discharge chamber 53 and/or pump chamber 28) in concentric bore pump fluid end 22 designs such as FIG. 3, such that a discharge valve body (e.g., poppet assembly) of the discharge valve assembly 72 moves toward the discharge chamber 53 when the discharge valve assembly 72 approaches an open configuration and away from the discharge chamber 53 when the discharge valve assembly 72 approaches a closed configuration. In addition, the discharge valve assembly 72 may be co-axially aligned with the suction valve assembly 56 (e.g., along central axis 17 in concentric bore pump fluid end 22 configurations such as FIG. 3 or along central axis 27 of bore 25 perpendicular to central axis 17 in cross-bore pump fluid end 22 configurations such as FIG. 2A and FIG. 2B). In concentric bore pump fluid end 22 configurations such as FIG. 3, the suction valve assembly 56 and the discharge valve assembly 72 may be coaxially aligned with the reciprocating element 18 (e.g., along central axis 17).

(45) Further, the suction valve assembly 56 and the discharge valve assembly 72 can comprise any suitable mechanism for opening and closing valves. For example, the suction valve assembly 56 and the discharge valve assembly 72 can comprise a suction valve spring and a discharge valve spring, respectively. Additionally, any suitable structure (e.g., valve assembly comprising sealing rings, stems, valve guides, poppets, etc.) and/or components may be employed for retaining the components of the suction valve assembly 56 and the components of the discharge valve assembly 72 within the pump fluid end 22. For example, the discharge valve assembly 72 and/or the suction valve assembly 56 can comprise a valve poppet, as described, for example, in U.S. patent application Ser. No. 16/436,356 filed Jun. 10, 2019 and entitled “Multi-Material Frac Valve Poppet”, the disclosure of which is hereby incorporated herein in its entirety for purposes not contrary to this disclosure. Although at least one of the suction valve assembly 56 or the discharge valve assembly 72 of this disclosure comprises a valve assembly 20 as described herein absent a valve seat, in embodiments, the suction valve assembly 56 or the discharge valve assembly 72 can comprise a conventional valve seat and a valve body. That is, the suction valve assembly can comprise a suction valve seat and a suction valve body, or the discharge valve assembly 72 can comprise a discharge valve seat and a discharge valve body. The suction valve body and the discharge valve body can be any known valve bodies, for example, movable valve poppets, and can be wing guided and/or stem guided, or a combination thereof.

(46) The fluid inlet **38** may be arranged within any suitable portion of the pump fluid end **22** and configured to supply fluid to the pump in any direction and/or angle. Moreover, the pump fluid end **22** may comprise and/or be coupled to any suitable conduit (e.g., pipe, tubing, or the like) through which a fluid source may supply fluid to the fluid inlet **38**. The pump **10** may comprise and/or be coupled to any suitable fluid source for supplying fluid to the pump via the fluid inlet **38**. In embodiments, the pump **10** may also comprise and/or be coupled to a pressure source such as a boost pump (e.g., a suction boost pump) fluidly connected to the pump **10** (e.g., via inlet **38**) and operable to increase or “boost” the pressure of fluid introduced to pump **10** via fluid inlet **38**. A boost pump may comprise any suitable type including, but not limited to, a centrifugal pump, a gear pump, a screw pump, a roller pump, a scroll pump, a piston/plunger pump, or any combination thereof. For instance, the pump **10** may comprise and/or be coupled to a boost pump known to operate efficiently in high-volume operations and/or may allow the pumping rate therefrom to be adjusted. Skilled artisans will readily appreciate that the amount of added pressure may depend and/or vary based on factors such as operating conditions, application requirements, etc. In one aspect, the boost pump may have an outlet pressure greater than or equal to about 70 psi, about 80 psi, or about 110 psi, providing fluid to the suction side of pump **10** at about said pressures. Additionally or alternatively, the boost pump may have a flow rate of greater than or equal to about 80 BPM, about 70 BPM, and/or about 50 BPM.

(47) As noted hereinabove, the pump **10** may be implemented as a multi-cylinder pump comprising multiple cylindrical reciprocating element bores **24** and corresponding components. In embodiments, the pump **10** is a Triplex pump in which the pump fluid end **22** comprises three reciprocating assemblies, each reciprocating assembly comprising a suction valve assembly **56**, a discharge valve assembly **72**, a pump chamber **28**, a fluid inlet **38**, a discharge outlet **54**, and a reciprocating element bore **24** within which a corresponding reciprocating element **18** reciprocates during operation of the pump **10** via connection therewith to a (e.g., common) pump power end **12**. In embodiments, the pump **10** is a Quintuplex pump in which the pump fluid end **22** comprises five reciprocating assemblies. In a non-limiting example, the pump **10** may be a Q-10™ Quintuplex Pump or an HT-400™ Triplex Pump, produced by Halliburton Energy Services, Inc.

(48) In embodiments, the pump fluid end **22** may comprise an external manifold (e.g., a suction header) for feeding fluid to the multiple reciprocating assemblies via any suitable inlet(s). Additionally or alternatively, the pump fluid end **22** may comprise separate conduits such as hoses fluidly connected to separate inlets for inputting fluid to each reciprocating assembly. Of course, numerous other variations may be similarly employed, and therefore, fall within the scope of the present disclosure.

(49) Those skilled in the art will understand that the reciprocating elements of each of the reciprocating assemblies may be operatively connected to the pump power end **12** of the pump **10** according to any suitable manner. For instance, separate connectors (e.g., cranks arms/connecting rods **20**, one or more additional components or mechanical linkages **48**, pushrods **9**, etc.) associated with the pump power end **12** may be coupled to each reciprocating element body or tail end **62**. The pump **10** may employ a common crankshaft (e.g., crankshaft **16**) or separate crankshafts to drive the multiple reciprocating elements.

(50) As previously discussed, the fluid inlet(s) **38** may receive a supply of fluid from any suitable fluid source, which may be configured to provide a constant fluid supply. Additionally or alternatively, the pressure of supplied fluid may be increased by adding pressure (e.g., boost pressure) as described previously. In embodiments, the fluid inlet(s) **38** receive a supply of pressurized fluid comprising a pressure ranging from about 30 psi to about 300 psi.

(51) Additionally or alternatively, the one or more discharge outlet(s) **54** may be fluidly connected to a common collection point such as a sump or distribution manifold, which may be configured to collect fluids flowing out of the fluid outlet(s) **54**, or another cylinder bank and/or one or more additional pumps.

(52) During pumping, the multiple reciprocating elements **18** will perform forward and returns strokes similarly, as described hereinabove. In embodiments, the multiple reciprocating elements **18** can be angularly offset to ensure that no two reciprocating elements are located at the same position along their respective stroke paths (i.e., the plungers are “out of phase”). For example, the reciprocating elements may be angularly distributed to have a certain offset (e.g., 120 degrees of separation in a Triplex pump) to minimize undesirable effects that may result from multiple reciprocating elements of a single pump simultaneously producing pressure pulses. The position of a reciprocating element is generally based on the number of degrees a pump crankshaft (e.g., crankshaft **16**) has rotated from a bottom dead center (BDC) position. The BDC position corresponds to the position of a fully retracted reciprocating element at zero velocity, e.g., just prior to a reciprocating element moving (i.e., in a direction indicated by arrow **117** in FIGS. 2A-2B and FIG. 3) forward in its cylinder. A top dead center position corresponds to the position of a fully extended reciprocating element at zero velocity, e.g., just prior to a reciprocating element moving backward (i.e., in a direction indicated by arrow **116** in FIGS. 2A-2B and FIG. 3) in its cylinder.

(53) As described above, each reciprocating element **18** is operable to draw in fluid during a suction (backward or return) stroke and discharge fluid during a discharge (forward) stroke. Skilled artisans will understand that the multiple reciprocating elements **18** may be angularly offset or phase-shifted to improve fluid intake for each reciprocating element **18**. For instance, a phase degree offset (at 360 degrees divided by the number of reciprocating elements) may be employed to ensure the multiple reciprocating elements **18** receive fluid and/or a certain quantity of fluid at all times of operation. In one implementation, the three reciprocating elements **18** of a Triplex pump may be phase-shifted by a 120-degree offset. Accordingly, when one reciprocating element **18** is at its maximum forward stroke position, a second reciprocating element **18** will be 60 degrees through its discharge stroke from BDC, and a third reciprocating element will be 120 degrees through its suction stroke from top dead center (TDC).

(54) Herein disclosed is a valve assembly comprising: a hardened insert; and a valve body coupled with a valve insert. The valve body coupled with the valve insert may be referred to herein simply as a “valve”. The hardened insert is coupled with or “carried” by a “hardened insert carrier.” According to this disclosure, the hardened insert carrier can comprise a reciprocating element **18**, a replaceable valve carrier **40** (FIG. 6A and FIG. 6B, described hereinbelow), or a pump fluid end body **8** of a pump fluid end **22**. In a closed configuration of the valve assembly, the valve body contacts a primary sealing surface of the hardened insert and the valve insert contacts an initial sealing surface of the hardened insert carrier to prevent fluid flow through the valve assembly, and, in an open configuration of the valve assembly, the valve body does not contact the primary sealing surface of the hardened insert and the valve insert does not contact the initial sealing surface of the hardened insert carrier to allow fluid flow through the valve assembly. As utilized herein, a “contact” or “sealing” surface is the surface that contacts the valve **3** (described with reference to FIGS. 5-8 hereinbelow) when the valve assembly **20** is in the closed configuration. The contact surface **30** includes the primary sealing surface **30A** of the hardened insert **2** that contacts a valve body sealing surface **30C**, when the valve assembly **20** is in the closed configuration, and the initial sealing surface **30B** of the hardened insert carrier **5** that contacts a valve insert sealing surface **30D** of the valve insert **3B**, when the valve assembly **20** is in the closed configuration. As detailed further hereinbelow, the contact surface of valve assembly **20** of this disclosure is not provided by a conventional valve seat that provides a contact surface between the valve and the valve seat.

(55) Use of the term “initial” in reference to “initial sealing surface” indicates that the initial sealing surface of the contact surface can contact the valve before the primary sealing surface contacts the valve during closing of the valve assembly. Similarly, use of the term “primary” in reference to the “primary sealing surface” indicates that the primary sealing surface of the contact surface provides the majority of the seal between the valve and the contact surface when the valve assembly is in the closed configuration (e.g., takes most of the impact between the valve and the

contact surface during operation of a pump comprising the valve assembly).

(56) For example, with reference now to FIG. 5, a valve assembly **20** according to embodiments of this disclosure comprises valve body **3A** coupled with valve insert **3B** (also referred to herein simply as “valve” **3**), and hardened insert **2** coupled with hardened insert carrier **5**. In the embodiment of FIG. 5, hardened insert carrier **5** is provided by reciprocating element **18**. Contact surface **30** comprises initial sealing surface **30B** of reciprocating element **18** and primary sealing surface **30A** of hardened insert **2**. During operation of the valve assembly **20**, valve body **3A** moves cyclically relative to the reciprocating element/hardened insert carrier **18/5** that is coupled with the hardened insert **2**. In the closed configuration of the valve assembly **20**, the valve body **3A** contacts the primary sealing surface **30A** of the hardened insert **2** and the valve insert **3B** contacts the initial sealing surface **30B** of the reciprocating element **18** to prevent fluid flow through the valve assembly **20**. In the open configuration of the valve assembly **20**, the valve body **3A** does not contact the primary sealing surface **30A** of the hardened insert **2** and the valve insert **3B** does not contact the initial sealing surface **30B** of the reciprocating element **18** to allow fluid flow through the valve assembly **20**.

(57) As noted above, in embodiments, the hardened insert carrier **5** comprises a replaceable valve carrier (RVC) **40**. For example, with reference now to FIG. 6A, a valve assembly **20** comprises valve **3** comprising valve body **3A** coupled with valve insert **3B**, and comprises hardened insert **2** coupled with hardened insert carrier **5**. In the embodiment of FIG. 6A, hardened insert carrier **5** is provided by RVC **40**. Contact surface **30** comprises initial sealing surface **30B** of RVC **40** and primary sealing surface **30A** of hardened insert **2**. During operation of the valve assembly **20**, valve body **3A** moves cyclically relative to the RVC/hardened insert carrier **40/5** that is coupled with the hardened insert **2**. In the closed configuration of the valve assembly **20**, the valve body **3A** contacts the primary sealing surface **30A** of the hardened insert **2** and the valve insert **3B** contacts the initial sealing surface **30B** of the RVC **40** to prevent fluid flow through the valve assembly **20**. In the open configuration of the valve assembly **20**, the valve body **3A** does not contact the primary sealing surface **30A** of the hardened insert **2** and the valve insert **3B** does not contact the initial sealing surface **30B** of the RVC **40** to allow fluid flow through the valve assembly **20**.

(58) In embodiments in which the hardened insert carrier **5** comprises a replaceable valve carrier (RVC) **40**, the RVC **40** is coupled with an inside surface of a pump fluid end body **8** of the pump fluid end **22**, and the hardened insert **2** is positioned about an inside surface **40A** of the RVC **40**. For example, as depicted in FIG. 6A, RVC **40** can be interference fit, press fit, threaded, glued, or a combination thereof within pump fluid end body **8**, such that an outside surface S.sub.o of the RVC **40** contacts an inside surface of the pump fluid end body **8**. As depicted in FIG. 6A and FIG. 6B, the initial sealing surface **30B** can comprise a portion of the inside surface S.sub.i of the RVC **40** that contacts the valve insert sealing surface **30C** during closing of the valve assembly **20** and/or when the valve assembly is in the closed configuration. The RVC **40** can be substantially larger in size than a conventional valve seat. For example, a surface area of the inside surface S.sub.i of the RVC **40** can be at least 5, 10, 15, 20, 25, 30, 35, 40, 45, 50% or more larger than the combined area of the initial sealing surface **30B** and the primary sealing surface **30A**.

(59) RVC **40** can be operable as a slip fit carrier sealed into the pump fluid end **22** using, for example, O-rings or similar seals. In the event of a valve **3** failure, cavitation, hardened sealing surface (i.e., primary sealing surface **30A**) failure, or the like that would otherwise damage a pump fluid end **22** absent RVC **40**, damage can be limited to the RVC **40**. In such an event, the RVC **40** can be removed and another RVC **40** inserted into the pump fluid end **22**. In this manner, RVC **40** can also serve as a sacrificial replacement for a high wear section of pump fluid end **22**, and be subjected to damage that would otherwise be inflicted on the (e.g., discharge portion of) the pump fluid end **22**.

(60) As noted above, in embodiments, the hardened insert carrier **5** comprises a pump fluid end body **8** of a pump fluid end **22** comprising the valve assembly **20**. For example, with reference now

to FIG. 7A, a valve assembly **20** comprises valve **3** comprising valve body **3A** coupled with valve insert **3B**, and comprises hardened insert **2** coupled with hardened insert carrier **5**. In the embodiment of FIG. 7A, hardened insert carrier **5** is provided by pump fluid end body **8**. Contact surface **30** comprises initial sealing surface **30B** of pump fluid end body **8** and primary sealing surface **30A** of hardened insert **2**. During operation of the valve assembly **20**, valve body **3A** moves cyclically relative to the contact surface **30** of the pump fluid end body **8** that is coupled with the hardened insert **2**. In the closed configuration of the valve assembly **20**, the valve body **3A** contacts the primary sealing surface **30A** of the hardened insert **2** and the valve insert **3B** contacts the initial sealing surface **30B** of the pump fluid end body **8** to prevent fluid flow through the valve assembly **20**. In the open configuration of the valve assembly **20**, the valve body **3A** does not contact the primary sealing surface **30A** of the hardened insert **2** and the valve insert **3B** does not contact the initial sealing surface **30B** of the pump fluid end body **8** to allow fluid flow through the valve assembly **20**.

(61) The hardened insert **2** can be generally cylindrical. The hardened insert **2** can be positioned within an inside surface of the hardened insert carrier **5**, in embodiments. In alternative embodiments, hardened insert **2** is radially positioned between an inside surface S.sub.i of the hardened insert carrier **5** and an outside surface S.sub.o thereof. In embodiments, such as depicted in FIG. 5, the hardened insert carrier **5** comprises a reciprocating element **18**, and the initial sealing surface **30B** is provided by a front surface **18A** of the reciprocating element **18**. In embodiments, such as depicted in FIG. 6A and FIG. 6B, the hardened insert carrier **5** comprises a replaceable valve carrier (RVC), and the initial sealing surface **30B** is provided by an inside surface **40A** of the replaceable valve carrier (RVC). In embodiments, such as depicted in FIG. 7A and FIG. 7B, the hardened insert carrier **5** comprises a pump fluid end body **8**, and the initial sealing surface **30B** is provided by an inside surface **8A** of the pump fluid end body **8**.

(62) The hardened insert **2** can be coupled with hardened insert carrier **5** by any suitable methods known to those of skill in the art. For example, hardened insert **2** can be bonded in place, retained with a secondary sealing surface such as an o-ring and pressed in, pressed in, or placed via a thermal shrink fit. According to some embodiments, the hardened insert **2** may be attached to steel or metal portions of the hardened insert carrier **5** in a number of ways. For example, the hardened insert **2** may be pressed, cast in place, shrunk via cold temperatures and put in place, friction welded, applied with a brazing solution, glued or bonded via some adhesive, chemically bonded, press fit, shrink fit, sintered, welded, or a combination thereof. In other examples, the hardened insert **2** is a coating applied by dipping or spraying. In embodiments, a tungsten carbide hardened insert **2** is secured by bonding, press-fitting, heating, cooling, shrinking, gluing, shrink-fitting, sintering, welding, or combinations thereof.

(63) As noted above, in operation, the hardened insert **2** operates to extend the life span of the valve assembly **20**, which is subject to corrosion, erosion, or pitting during operation caused by the valve body **3A** repetitively hitting the contact surface **30**. Hardened insert **2** can be formed of different shapes and sizes. The size, shape, and placement of the hardened insert **2** can depend on the operational environment. Hardened insert **2** can be sized, shaped, or placed based on areas of the valve assembly **20** that are subject to the most erosion or pitting. Likewise, variances in operational, ambient, or environmental temperatures, along with the operational forces applied to and/or otherwise acting on the hardened insert **2** (e.g., the tensile and compressive forces) may affect the size, shape or placement of the hardened insert **2**.

(64) With reference to FIG. 8, which is a schematic of a valve assembly **20** of this disclosure, hardened insert **2** can further comprise an extension E. The extension E extends a distance L1 in a direction perpendicular to the central axis **17A** of the valve assembly **20**. Extension E of hardened insert **2** extends farther toward central axis **17A** of valve assembly **20** than an inside surface of the hardened valve carrier **5** (e.g., inside surface **18B** of reciprocating element **18** when hardened insert carrier **5** comprises reciprocating element **18**, inside surface **40A** of RVC **40** when hardened insert

carrier 5 comprises RVC 40, or inside surface 8A of pump fluid end body 8 when hardened insert carrier 5 comprises pump fluid end body 8). The extension E of hardened insert 2 can be designed to retain another component of the valve assembly 20. For example, with reference to FIGS. 9A-9C, which are discussed further hereinbelow, an extension E of hardened insert 2 can be designed to retain valve spring 31, i.e., can serve as a seat for valve spring 31.

(65) In FIG. 5-FIG. 8, hardened insert 2 is positioned in a cavity 7 of the hardened insert carrier 5, the cavity 7 formed in the hardened insert carrier 5 by sidewalls 7a, 7b and 7c. In embodiments, the primary sealing surface 30A of the hardened insert 2 is flush with the initial sealing surface 30B of the hardened insert carrier 5. Alternatively, the primary contact surface 30A of hardened insert 2 is raised relative to the initial sealing surface 30B of the hardened insert carrier 5. According to embodiments and as noted above, hardened insert 2 may be bonded in place, although other means of installation can be employed.

(66) As noted hereinabove, an amount of hardened material (e.g., carbide) in the hardened insert 2 is less than an amount of hardened material (e.g., carbide) in a conventional valve seat in which the primary sealing surface 30A and the initial sealing surface 30B are provided by a valve seat made of the (e.g., same) hardened material (e.g., carbide). For example, in embodiments, an amount (e.g., a mass) of hardened material (e.g., carbide) in the hardened insert 2 is at least 40, 50, or 60% less than an amount (e.g., a mass) of the hardened material (e.g., carbide) in a conventional valve seat in which the primary sealing surface 30A and the initial sealing surface 30B are provided by a valve seat made of the hardened material (e.g., carbide).

(67) The primary sealing surface 30A provided by the hardened insert and the initial sealing surface 30B provided by the hardened insert carrier comprise disparate materials. A material of the primary sealing surface 30A has a greater hardness than a material of the initial sealing surface 30B. The hardness can be measured by the Vickers Hardness according to ASTM E92, the Rockwell or Vickers Hardness as measured by ASTM E18-19, and/or the Brinell Hardness as measured by ASTM E10-18. Reference to a “hardened” insert indicates that the hardened insert 2 is manufactured out of a “high-strength hardened material” (or simply a “hardened material”). Examples of high-strength hardened materials include, without limitation, zirconia, partially stabilized zirconia, tungsten carbide, tungsten carbide nickel, titanium, tungsten carbide cobalt, titanium carbide, silicon nitride, sialon, silicon, silicon nitride, ceramic, or other hardened material. Making a hardened insert 2 out of such materials enables the herein disclosed valve assembly 20 to protect against conventional corrosion, pitting, and other wear-and-tear caused by the valve body 3A repetitively impacting the hardened insert 2, while minimizing an amount of hardened material utilized to provide the contact surface 30. Placing hardened insert 2 where constant valve friction occurs (i.e., utilizing hardened insert 2 to provide the primary sealing surface 30A) can extend the life of the valve assembly, and by extension the life of a pump 10 (e.g., a frac pump), while minimizing an amount of the hardened material utilized to provide the contact surface 30 (e.g., primary sealing surface 30A plus initial sealing surface 30B). As opposed to a conventional valve assembly comprising a valve seat, in which the entire contact surface (i.e., the contact surface between the valve body and the valve seat and the contact surface between the valve insert and the valve seat) are provided by a hardened material, a primary sealing surface 30A of the contact surface 30 of the valve assembly 20 of this disclosure is provided by hardened insert 2, while the initial sealing surface 30B of the contact surface 30 of the valve assembly 20 of this disclosure is provided by a material having a reduced hardness relative to a hardness of the hardened insert 2.

(68) The primary sealing surface 30A provided by the hardened insert 2 can comprise carbide. For example, in such embodiments, the hardened insert 2 can comprise a carbide ring. The carbide can comprise tungsten carbide. The hardness of the tungsten carbide may range from about 620-1076 HV, with reference to the Vickers hardness number. The initial sealing surface 30B provided by the hardened insert carrier 5, which has a hardness less than the hardness of the primary sealing surface 30A, can comprise any suitable material having the noted hardness. For example and without

limitation, the initial sealing surface **30B** can comprise carburized steel. The initial sealing surface **30B** can comprise the same or a different material from the remainder of the hardened insert carrier **5**. For example, a reciprocating element (e.g., plunger or piston) **18**, RVC **40**, or pump fluid end body **8** can comprise steel, and the initial sealing surface **30B** thereof can comprise carburized steel.

(69) The steel of the hardened insert carrier **5** (and/or valve body **3A**) may include, for example, stainless steel, low-carbon steel (e.g., with less than 0.3% carbon); medium-carbon steel (e.g., 0.3-0.6% carbon); high-carbon steel (e.g., more than 0.6% carbon); alloy steels, (e.g., manganese, silicon, nickel, titanium, copper, chromium, aluminum, and the like) or any other type of steel and/or metal.

(70) The valve **3** can be any suitable valve known in the art. For example, as noted hereinabove valve **3** can comprise a movable valve poppet, and can be wing guided and/or stem guided, or a combination thereof. For example, in embodiments, valve **3** comprises a valve poppet, as described, for example, in U.S. patent application Ser. No. 16/436,356 filed Jun. 10, 2019, which is entitled "Multi-Material Frac Valve Poppet", the disclosure of which is hereby incorporated herein in its entirety for purposes not contrary to this disclosure. In such applications, the valve seat of the valve poppet assembly is replaced with the contact surface **30**, as described herein.

(71) Valve assembly **20** comprises valve body **3A** coupled with valve insert **3B**. Valve body **3A** can be generally cylindrical. Valve body **3A** comprises a first side **35** opposite (e.g., axially distal from) a second side **36**. The first side **35** of valve body **3A** comprises the valve body sealing surface **30C** that contacts the primary sealing surface **30A** of the hardened insert **2** when the valve assembly **20** is in a (e.g., normally) closed position. Second side **36** of valve body **3A** can comprise a head **37** that extends radially along a side **6** of valve insert **3B** that is axially distal valve insert sealing surface **30D**. Head **37** can be perpendicular to central axis **17A** of valve assembly **20**. As depicted in FIG. 5-FIG. 8, an outer circumference of valve body **3A** can align with an outer circumference of valve insert **3B**. As noted hereinbelow with reference to FIG. 9B, the second side **36** of valve body **3A** can comprise a coupler actuating feature **58**.

(72) Valve body **3A** can comprise a metal. By way of non-limiting examples, the valve body can comprise carbide or steel. As described above for the hardened insert carrier **5**, the steel can include, for example, stainless steel, low-carbon steel (e.g., with less than 0.3% carbon); medium-carbon steel (e.g., 0.3-0.6% carbon); high-carbon steel (e.g., more than 0.6% carbon); alloy steels, (e.g., manganese, silicon, nickel, titanium, copper, chromium, aluminum, and the like) or any other type of steel and/or metal.

(73) Valve insert **3B** can be generally cylindrical. Without limitation, valve insert **3B** can comprise, for example, an elastomeric ring positioned on an outer circumference of valve body **3A**. As depicted in FIGS. 5, 6A-6B and FIGS. 7A-7B, and 8, valve insert **3B** can have an L-shaped cross-section with a lip **44** extending into a circumferential groove **55** of valve body **3A**. Other shapes and coupling arrangements of valve body **3A** and valve insert **3B** are within the scope of this disclosure. Valve insert **3B** can be press fit, interference fit, or otherwise positioned into groove **55** of valve body **3A** for coupling therewith. For example, in embodiments, valve insert **3B** can be molded in place in the valve body **3A**. In other embodiments, the valve insert **3B** is preformed and then attached to the valve body **3A**.

(74) Generally, valve insert **3B** comprise a material, such as an elastomer, that can deform about particulates being pumped by a pump comprising the valve assembly **20** during formation of the primary seal provided by contact of the primary sealing surface **30A** and valve body contact surface **30C**. Valve insert **3B** is designed to provide an initial seal via contact of the valve insert sealing surface **30D** and the initial sealing surface of the hardened insert carrier **5** during closing of the valve assembly **20**. As depicted in FIGS. 5, 6A, 7A, and 8, initial sealing surface **30B** can extend a radial distance **D** from an outer circumference of valve **3** (e.g., from outer circumference of valve insert **3B** and/or valve body **3A**) when valve assembly is in the closed configuration, such that,

when valve assembly **20** is closing, an initial contact of valve **3** with initial sealing surface **30B** provides for enough pressure to completely close valve assembly **20**. That is, when in the closed configuration, the initial sealing surface **30B** provided by the hardened insert carrier **5** can extend radially beyond the outer circumference of valve **3**. In this manner, valve **3** can slide into position to assume the closed configuration. Thus, contact surface **30** can be longer than a length of valve body sealing surface **30C** and valve insert sealing surface **30D**, such that, in a closed configuration only a portion of initial sealing surface **30B** contacts valve insert sealing surface **30D**, as depicted in FIG. 5-FIG. 9D.

(75) According to some examples, valve insert **3B** is composed of one or more materials such as, for example, a deformable thermoplastic material, a urethane material, a fiber-reinforced material, carbon, glass, cotton, wire fibers, cloth, and/or any combination thereof. In other embodiments, valve insert **3B** comprises a cloth, which is disposed in a thermoplastic material. The cloth can include carbon, glass, wire, cotton fibers, and/or any combination thereof. In embodiments, valve insert **3B** comprises a fiber-reinforced material, which can prevent or at least reduce delamination. In embodiments, the valve insert **3B** has a hardness of 95 A durometer or greater, or a hardness of 69 D durometer or greater based on the Rockwell Hardness scale. In embodiments, the valve body **3A** is harder and more rigid than the valve insert **3B**.

(76) Although valve insert **3B** is depicted as coupled with valve body **3A**, in embodiments, valve insert **3B** is a sealing insert as described in U.S. patent application Ser. No. 16/791,479, entitled “Pump Valve Assembly”, which is being filed concurrently herewith and the disclosure of which is hereby incorporated herein in its entirety for purposes not contrary to this disclosure. In such embodiments, valve insert **3B** can be coupled with hardened insert carrier **5**, rather than with valve body **3A**.

(77) Valve **3** can comprise additional components. For example, as depicted in FIG. 9A and FIG. 9B, which are schematics of a valve assembly **20** as described with reference to FIG. 5 in which hardened insert carrier **5** comprises reciprocating element **18**, FIG. 9C, which is a schematic of a valve assembly **20** as described with reference to FIGS. 6A-6B in which hardened insert carrier **5** comprises RVC **40**, and FIG. 9D, which is a schematic of a valve assembly **20** as described with reference to FIG. 7A-7B in which hardened insert carrier **5** comprises pump fluid end body **8**, valve assembly **20** can further comprise a spring **31** operable as a biasing component, and a valve guide **32** operable to maintain alignment of valve **3** within housing **65** (e.g., reciprocating element bore **24**, chamber **28**, or bore **25**) of pump fluid end **22**.

(78) As noted hereinabove and depicted in FIG. 9A, FIG. 9B, and FIG. 9C, hardened insert **2** can serve as a seating surface for valve spring **31**, and/or valve spring **31** can be disposed about valve guide **32**. Alternatively, as depicted in FIG. 9D, valve spring **31** can be positioned on an opposite side of valve **3** from valve guide **32** and seated on another component of pump fluid end **22**.

(79) As noted hereinabove, valve **3** can further comprise a valve guide **32**. In embodiments, valve guide can be coupled with the valve body **3A** via a valve stem **103** and configured to align the valve body **3A** within the valve assembly **20**. Such a valve guide is described, for example, in U.S. patent application Ser. No. 16/411,910 filed May 14, 2019, which is entitled “Valve Assembly for a Fluid End with Limited Access”, the disclosure of which is hereby incorporated herein in its entirety for purposes not contrary to this disclosure. For example, as depicted in FIG. 9B, valve assembly **20** can further comprise a valve guide **32** comprising a plurality of wings or fins **42**. When assembled, each of the plurality of wings **42** is aligned with one of a plurality of grooves **34** of an inside surface of a housing **65** (e.g., an inside surface **18B** of a reciprocating element **18** in FIG. 9B), such that, during operation, the plurality of wings **42** can slide along the plurality of grooves **34**, and rotation of the valve guide **32** about central axis **17A** of valve assembly **20** is restricted. In an embodiment, a number of grooves **34** is equal to a number of wings **42**. In alternative embodiments, a valve assembly **20** comprises a greater or lesser number of grooves **34** than wings **42**. In embodiments, valve assembly **20** comprises three grooves **34** and three wings **42**,

spaced at 120 degrees to form a 360 degree circumference. The plurality of circumferentially-spaced wings **42** angularly extending from the valve body **3A** to slidably engage the inside surface of the housing **65**. In FIG. 5-FIG. 8, the valve body **3A** is engaged and otherwise biased by a spring **31**, which biases the valve body **3A** to a closed position, to prevent fluid flow. Other examples do not include springs.

(80) Valve guide **32** can comprise a coupler **39**. Valve guide **32** can be coupled to or decoupled from a first side **35** of the valve body **3A** via the coupler **39** by actuating the coupler actuating feature **58** of valve body **3A** on a second side **36** of the valve body **3A**. Coupler **39** can comprise a threaded portion of the valve guide **32**, which engages complimentary threads located in a threaded hole or recess **33** located on the first side **35** of the valve body **3A**. Alternatively, coupler **39** can comprise a twist lock coupler **39**. Valve guide **32** can further comprise a valve guide end **41** distal the coupler **39**. When the valve guide **32** is coupled to the valve body **3A** via the coupler **39**, the valve guide end **41** of the valve guide **32** distal the coupler **39** extends a greater radial distance from the central axis of the valve body **3A** (which, upon assembly, is coincident with (also referred to as coaxial with) the central axis **17A** of valve assembly **20**) than the plurality of wings **42**. As depicted in FIG. 9B, the valve guide end **41** of the valve guide **32** distal the coupler **39** extends radially a distance **E2** from central axis **17A**, which is a greater radial distance from the central axis **17A** than a distance **E1** from central axis **17A** that wings **40** radially extend. When valve assembly **20** is in an assembled configuration, valve body **3A** is coupled to valve guide **32** via coupler **39**, the plurality of wings **42** of the valve guide **32** are aligned with the plurality of grooves **34**, and a valve spring **31** is positioned in an annular space **45** extending an axial distance **D2** between housing **65** and valve guide end **41** of valve guide **32** distal coupler **39** (e.g., the wings **42** of the valve guide **32** are positioned inside coil or helical valve spring **31**, typically a compression coil spring). Valve guide **32** (e.g., valve guide end **41**) can rest on shoulder **46** of seat housing **65**, with at least a portion of corresponding portion **46A** of valve guide end **41** corresponding to shoulder **46** contacting shoulder **46**.

(81) The contact surface **30**, the primary sealing surface **30A**, the initial sealing surface **30B**, the valve body sealing surface **30C**, the valve insert sealing surface **30D**, or a combination thereof can be frusto-conical or frusto-spherical in shape. Although depicted as frusto-conical in the embodiments of FIG. 5, FIG. 6A, FIG. 6B, FIG. 7, FIG. 7B, and FIG. 8, other shapes are possible and within the scope of this disclosure. Hardened insert **2**, valve **3** (i.e., valve body **3A** and/or valve insert **3B**), hardened insert carrier **5**, or a combination thereof can thus have alternative shapes from those depicted in the Figures.

(82) The valve assembly **20** can be horizontally positioned such that central axis **17A** of the valve assembly **20** is horizontal, or vertically positioned such that the central axis **17A** of the valve assembly **20** is vertical.

(83) Also disclosed herein is a pump fluid end **22** comprising: a reciprocating element **18** at least partially within a reciprocating element bore **24** of the pump fluid end **22**, wherein the reciprocating element bore **24** extends into the pump fluid end **22** from an end (e.g., back end **S2**) of the pump fluid end **22** and has a central axis **17**; a suction valve assembly **56**; and a discharge valve assembly **72**. According to this disclosure, the suction valve assembly **56**, the discharge valve assembly **72**, or both the suction valve assembly **56** and the discharge valve assembly **72** comprise a valve assembly **20** comprising a hardened insert **2**, and a valve **3** comprising a valve body **3A** coupled with a valve insert **3B**, wherein, in a closed configuration of the valve assembly **20**, the valve body **3A** contacts a primary sealing surface **30A** of the hardened insert **2** and the valve insert **2** contacts an initial sealing surface **30B** of a hardened insert carrier **5** to prevent fluid flow through the valve assembly **20**, and, in an open configuration of the valve assembly **20**, the valve body **3A** does not contact the primary sealing surface **30A** of the hardened insert **2** and the valve insert **3B** does not contact the initial sealing surface **30B** of the hardened insert carrier **5** to allow fluid flow through the valve assembly **20**.

(84) The pump fluid end 22 can be a concentric bore pump fluid end 22 (e.g., a concentric bore pump fluid end 22, as described hereinabove with reference to FIG. 3) or a cross bore (e.g., an x-bore pump fluid end 22, as described hereinabove with reference to FIG. 2A or a T-bore pump fluid end 22, as described with reference to FIG. 2B) pump fluid end 22.

(85) As described with reference to FIG. 3, the pump fluid end 22 can be a concentric bore pump fluid end 22. As depicted in FIG. 5, in some such embodiments, the suction valve assembly 56 comprises the valve assembly 20 of this disclosure comprising the hardened insert 2 and the valve 3 comprising the valve body 3A coupled with the valve insert 3B, wherein the hardened insert 2 is coupled with a front end 60 of the reciprocating element about an inside surface 18B thereof, and wherein the initial sealing surface 30B is provided by a front surface 18A of the reciprocating element 18. In such embodiments, the discharge valve assembly 72 may or may not be a valve assembly 20 as described herein.

(86) In embodiments, the pump fluid end 22 is a concentric bore pump fluid end 22, as described with reference to FIG. 3, the discharge valve assembly 72 comprises the valve assembly 20 of this disclosure comprising the hardened insert 2 and the valve 3 comprising the valve body 3A coupled with the valve insert 3B, and the hardened insert carrier 5 comprises an RVC 40 or the pump fluid end body 8. In such embodiments, the suction valve assembly 56 may or may not be a valve assembly 20 as described herein.

(87) In embodiments, the pump fluid end is a cross-bore pump fluid end 22, and the discharge valve assembly 72, the suction valve assembly 56, or both the discharge valve assembly 72 and the suction valve assembly 56 comprise a valve assembly 20 of this disclosure, wherein the hardened insert carrier 5 comprises an RVC 40 or the pump fluid end body 8 of the pump fluid end 22. In some such cross-bore pump fluid end 22 embodiments, the pump fluid end 22 is a tee-bore pump fluid end 22, as described hereinabove with reference to FIG. 2B, the discharge valve assembly 72 comprises a valve assembly 20 of this disclosure, and the hardened insert carrier 5 of the valve assembly 20/discharge valve assembly 72 comprises the RVC 40 or pump fluid end body 8. In such embodiments, the suction valve assembly 56 may or may not be a valve assembly 20 as disclosed herein. In some such cross-bore pump fluid end 22 embodiments, the pump fluid end 22 is a tee-bore pump fluid end 22, as described hereinabove with reference to FIG. 2B, the suction valve assembly 56 comprises a valve assembly 20 of this disclosure, and the hardened insert carrier 5 of the valve assembly 20/suction valve assembly 56 comprises the reciprocating element 18. In such embodiments, the discharge valve assembly 72 may or may not be a valve assembly 20 as disclosed herein.

(88) In some cross-bore pump fluid end 22 embodiments, the pump fluid end 22 is an x-bore pump fluid end 22, as described hereinabove with reference to FIG. 2A, the discharge valve assembly 72 comprises a valve assembly 20 of this disclosure, and the hardened insert carrier 5 of the valve assembly 20/discharge valve assembly 72 comprises the RVC 40 or pump fluid end body 8. In such embodiments, the suction valve assembly 56 may or may not be a valve assembly 20 as disclosed herein. In other such cross-bore pump fluid end 22 embodiments, the pump fluid end 22 is an x-bore pump fluid end 22, as described hereinabove with reference to FIG. 2A, the suction valve assembly 56 comprises a valve assembly 20 of this disclosure, and the hardened insert carrier 5 of the valve assembly 20/suction valve assembly 56 comprises an RVC 40 or the pump fluid end body 8. In such embodiments, the discharge valve assembly 72 may or may not be a valve assembly 20 as disclosed herein.

(89) For example, FIG. 6B depicts the valve assembly 20 of FIG. 6A as a discharge valve assembly 72 in a cross-bore pump fluid end 22, and FIG. 7B depicts the valve assembly 20 of FIG. 7A as a discharge valve assembly 72 in a cross-bore pump fluid end 22.

(90) Also disclosed herein is a pump 10 comprising a pump fluid end 22 of this disclosure comprising the valve assembly 20 as described herein. The pump of this disclosure comprises a pump power end 12 (e.g., as described with reference to FIG. 3, hereinabove) and the pump fluid

end **22** comprising the valve assembly **20** of this disclosure. The pump power end **12** is operable to reciprocate reciprocating element **18** within reciprocating element bore **24** of the pump fluid end **22**. As described hereinabove, the pump fluid end **22** comprises: the reciprocating element **18** at least partially within reciprocating element bore **24** of the pump fluid end **22**, wherein the reciprocating element bore **24** extends into pump fluid end **22** from an end (e.g., back end **S2**) of pump fluid end **22** and has a central axis **17**, a suction valve assembly **56**, a discharge valve assembly **72**. The suction valve assembly **56**, the discharge valve assembly **72**, or both the suction valve assembly **56** and the discharge valve assembly **72** comprise a valve assembly **20** comprising hardened insert **2** and valve **3** comprising valve body **3A** coupled with valve insert **3B**, wherein, in a closed configuration of the valve assembly **20**, the valve body **3A** contacts primary sealing surface **30A** of hardened insert **2** and valve insert **3B** contacts initial sealing surface **30B** of hardened insert carrier **5** to prevent fluid flow through the valve assembly **20**, and, in an open configuration of the valve assembly **20**, valve body **3A** does not contact primary sealing surface **30A** of the hardened insert **2** and valve insert **30B** does not contact the initial sealing surface **30B** of the hardened insert carrier **5** to allow fluid flow through the valve assembly **20**.

(91) A pump **10** of this disclosure can be a multiplex pump comprising a plurality of reciprocating assemblies (e.g., reciprocating elements **18**, and a corresponding plurality of reciprocating element bores **24**, suction valve assemblies **56**, and discharge valve assemblies **72**). The plurality can comprise any number such as, for example, 2, 3, 4, 5, 6, 7, or more. For example, in embodiments, pump **10** is a triplex pump, wherein the plurality comprises three. In alternative embodiments, pump **10** comprises a Quintuplex pump, wherein the plurality comprises five.

(92) Also disclosed herein are a method of servicing a wellbore and a wellbore servicing system **200** comprising a pump of this disclosure. An embodiment of a wellbore servicing system **200** and a method of servicing a wellbore via the wellbore servicing system **200** will now be described with reference to FIG. **10**, which is a schematic representation of an embodiment of a wellbore servicing system **200**, according to embodiments of this disclosure.

(93) A method of servicing a wellbore **224** according to this disclosure comprises: fluidly coupling a pump **10** to a source of a wellbore servicing fluid and to the wellbore **224**; and communicating wellbore servicing fluid into a formation in fluid communication with the wellbore **224** via the pump **10**.

(94) As detailed further hereinabove, the pump **10** of this disclosure comprises a pump fluid end **12** and a pump power end **22**. The pump power end **12** is operable to reciprocate reciprocating element **18** within reciprocating element bore **24** of pump fluid end **22**. The pump fluid end **22** comprises: reciprocating element **18** at least partially within reciprocating element bore **24** of the pump fluid end **22**, wherein the reciprocating element bore **24** extends into pump fluid end **22** from an end (e.g., back end **S2**) of pump fluid end **22** and has a central axis **17**; a suction valve assembly **56**; and a discharge valve assembly **72**. The suction valve assembly **56**, the discharge valve assembly **72**, or both the suction valve assembly **56** and the discharge valve assembly **72** comprise a valve assembly **20** of this disclosure comprising hardened insert **2** and valve **3** comprising valve body **3A** coupled with valve insert **3B**, wherein, in a closed configuration of valve assembly **20**, valve body **3A** contacts primary sealing surface **30A** of hardened insert **2** and valve insert **3B** contacts initial sealing surface **30B** of hardened insert carrier **5** to prevent fluid flow through the valve assembly **20**, and, in an open configuration of valve assembly **20**, valve body **3A** does not contact the primary sealing surface **30A** of the hardened insert **2** and valve insert **3B** does not contact the initial sealing surface **30B** of hardened insert carrier **5** to allow fluid flow through the valve assembly **20**; and wherein the pump power end **12** is operable to reciprocate the reciprocating element **18** within the reciprocating element bore **24** of the pump fluid end **22**.

(95) It will be appreciated that the wellbore servicing system **200** disclosed herein can be used for any purpose. In embodiments, the wellbore servicing system **200** may be used to service a wellbore **224** that penetrates a subterranean formation by pumping a wellbore servicing fluid into the

wellbore and/or subterranean formation. As used herein, a “wellbore servicing fluid” or “servicing fluid” refers to a fluid used to drill, complete, work over, fracture, repair, or in any way prepare a well bore for the recovery of materials residing in a subterranean formation penetrated by the well bore. It is to be understood that “subterranean formation” encompasses both areas below exposed earth and areas below earth covered by water such as ocean or fresh water. Examples of servicing fluids suitable for use as the wellbore servicing fluid, the another wellbore servicing fluid, or both include, but are not limited to, cementitious fluids (e.g., cement slurries), drilling fluids or muds, spacer fluids, fracturing fluids or completion fluids, and gravel pack fluids, remedial fluids, perforating fluids, diverter fluids, sealants, drilling fluids, completion fluids, gelation fluids, polymeric fluids, aqueous fluids, oleaginous fluids, etc.

(96) In embodiments, the wellbore servicing system **200** comprises one or more pumps **10** operable to perform oilfield and/or well servicing operations. Such operations may include, but are not limited to, drilling operations, fracturing operations, perforating operations, fluid loss operations, primary cementing operations, secondary or remedial cementing operations, or any combination of operations thereof. Although a wellbore servicing system is illustrated, skilled artisans will readily appreciate that the pump **10** disclosed herein may be employed in any suitable operation.

(97) In embodiments, the wellbore servicing system **200** may be a system such as a fracturing spread for fracturing wells in a hydrocarbon-containing reservoir. In fracturing operations, wellbore servicing fluids, such as particle laden fluids, are pumped at high-pressure into a wellbore. The particle laden fluids may then be introduced into a portion of a subterranean formation at a sufficient pressure and velocity to cut a casing and/or create perforation tunnels and fractures within the subterranean formation. Proppants, such as grains of sand, are mixed with the wellbore servicing fluid to keep the fractures open so that hydrocarbons may be produced from the subterranean formation and flow into the wellbore. Hydraulic fracturing may desirably create high-conductivity fluid communication between the wellbore and the subterranean formation.

(98) The wellbore servicing system **200** comprises a blender **202** that is coupled to a wellbore services manifold trailer **204** via flowline **206**. As used herein, the term “wellbore services manifold trailer” includes a truck and/or trailer comprising one or more manifolds for receiving, organizing, and/or distributing wellbore servicing fluids during wellbore servicing operations. In this embodiment, the wellbore services manifold trailer **204** is coupled to six positive displacement pumps (e.g., such as pump **10** that may be mounted to a trailer and transported to the wellsite via a semi-tractor) via outlet flowlines **208** and inlet flowlines **210**. In alternative embodiments, however, there may be more or less pumps used in a wellbore servicing operation. Outlet flowlines **208** are outlet lines from the wellbore services manifold trailer **204** that supply fluid to the pumps **10**. Inlet flowlines **210** are inlet lines from the pumps **10** that supply fluid to the wellbore services manifold trailer **204**.

(99) The blender **202** mixes solid and fluid components to achieve a well-blended wellbore servicing fluid. As depicted, sand or proppant **212**, water **214**, and additives **216** are fed into the blender **202** via feedlines **218**, **220**, and **212**, respectively. The water **214** may be potable, non-potable, untreated, partially treated, or treated water. In embodiments, the water **214** may be produced water that has been extracted from the wellbore while producing hydrocarbons from the wellbore. The produced water may comprise dissolved and/or entrained organic materials, salts, minerals, paraffins, aromatics, resins, asphaltenes, and/or other natural or synthetic constituents that are displaced from a hydrocarbon formation during the production of the hydrocarbons. In embodiments, the water **214** may be flowback water that has previously been introduced into the wellbore during wellbore servicing operation. The flowback water may comprise some hydrocarbons, gelling agents, friction reducers, surfactants and/or remnants of wellbore servicing fluids previously introduced into the wellbore during wellbore servicing operations.

(100) The water **214** may further comprise local surface water contained in natural and/or manmade water features (such as ditches, ponds, rivers, lakes, oceans, etc.). Still further, the water

214 may comprise water stored in local or remote containers. The water **214** may be water that originated from near the wellbore and/or may be water that has been transported to an area near the wellbore from any distance. In some embodiments, the water **214** may comprise any combination of produced water, flowback water, local surface water, and/or container stored water. In some implementations, water may be substituted by nitrogen or carbon dioxide; some in a foaming condition.

(101) In embodiments, the blender **202** may be an Advanced Dry Polymer (ADP) blender and the additives **216** are dry blended and dry fed into the blender **202**. In alternative embodiments, however, additives may be pre-blended with water using other suitable blenders, such as, but not limited to, a GEL PRO blender, which is a commercially available preblender trailer from Halliburton Energy Services, Inc., to form a liquid gel concentrate that may be fed into the blender **202**. The mixing conditions of the blender **202**, including time period, agitation method, pressure, and temperature of the blender **202**, may be chosen by one of ordinary skill in the art with the aid of this disclosure to produce a homogeneous blend having a desirable composition, density, and viscosity. In alternative embodiments, however, sand or proppant, water, and additives may be premixed and/or stored in a storage tank before entering a wellbore services manifold trailer **204**.

(102) In embodiments, the pump(s) **10** (e.g., pump(s) **10** and/or maintained pump(s) **10**) pressurize the wellbore servicing fluid to a pressure suitable for delivery into a wellbore **224** or wellhead. For example, the pumps **10** may increase the pressure of the wellbore servicing fluid (e.g., the wellbore servicing fluid and/or the another wellbore servicing fluid) to a pressure of greater than or equal to about 3,000 psi, 5,000 psi, 10,000 psi, 20,000 psi, 30,000 psi, 40,000 psi, or 50,000 psi, or higher.

(103) From the pumps **10**, the wellbore servicing fluid may reenter the wellbore services manifold trailer **204** via inlet flowlines **210** and be combined so that the wellbore servicing fluid may have a total fluid flow rate that exits from the wellbore services manifold trailer **204** through flowline **226** to the flow connector wellbore **1128** of between about 1 BPM to about 200 BPM, alternatively from between about 50 BPM to about 150 BPM, alternatively about 100 BPM. In embodiments, each of one or more pumps **10** discharge wellbore servicing fluid at a fluid flow rate of between about 1 BPM to about 200 BPM, alternatively from between about 50 BPM to about 150 BPM, alternatively about 100 BPM. In embodiments, each of one or more pumps **10** discharge wellbore servicing fluid at a volumetric flow rate of greater than or equal to about 3, 10, or 20 barrels per minute (BPM), or in a range of from about 3 to about 20, from about 10 to about 20, or from about 5 to about 20 BPM.

(104) Persons of ordinary skill in the art with the aid of this disclosure will appreciate that the flowlines described herein are piping that are connected together for example via flanges, collars, welds, etc. These flowlines may include various configurations of pipe tees, elbows, and the like. These flowlines connect together the various wellbore servicing fluid process equipment described herein.

(105) Also disclosed herein are methods for servicing a wellbore (e.g., wellbore **224**). Without limitation, servicing the wellbore may include: positioning the wellbore servicing composition in the wellbore **224** (e.g., via one or more pumps **10** as described herein) to isolate the subterranean formation from a portion of the wellbore; to support a conduit in the wellbore; to plug a void or crack in the conduit; to plug a void or crack in a cement sheath disposed in an annulus of the wellbore; to plug a perforation; to plug an opening between the cement sheath and the conduit; to prevent the loss of aqueous or nonaqueous drilling fluids into loss circulation zones such as a void, vugular zone, or fracture; to plug a well for abandonment purposes; to divert treatment fluids; and/or to seal an annulus between the wellbore and an expandable pipe or pipe string. In other embodiments, the wellbore servicing systems and methods may be employed in well completion operations such as primary and secondary cementing operation to isolate the subterranean formation from a different portion of the wellbore.

(106) In embodiments, a wellbore servicing method may comprise transporting a positive

displacement pump (e.g., pump **10**) to a site for performing a servicing operation. Additionally or alternatively, one or more pumps may be situated on a suitable structural support. Non-limiting examples of a suitable structural support or supports include a trailer, truck, skid, barge or combinations thereof. In embodiments, a motor or other power source for a pump may be situated on a common structural support.

(107) In embodiments, a wellbore servicing method may comprise providing a source for a wellbore servicing fluid. As described above, the wellbore servicing fluid may comprise any suitable fluid or combinations of fluid as may be appropriate based upon the servicing operation being performed. Non-limiting examples of suitable wellbore servicing fluid include a fracturing fluid (e.g., a particle laden fluid, as described herein), a perforating fluid, a cementitious fluid, a sealant, a remedial fluid, a drilling fluid (e.g., mud), a spacer fluid, a gelation fluid, a polymeric fluid, an aqueous fluid, an oleaginous fluid, an emulsion, various other wellbore servicing fluid as will be appreciated by one of skill in the art with the aid of this disclosure, and combinations thereof. The wellbore servicing fluid may be prepared on-site (e.g., via the operation of one or more blenders) or, alternatively, transported to the site of the servicing operation.

(108) In embodiments, a wellbore servicing method may comprise fluidly coupling a pump **10** to the wellbore servicing fluid source. As such, wellbore servicing fluid may be drawn into and emitted from the pump **10**. Additionally or alternatively, a portion of a wellbore servicing fluid placed in a wellbore **224** may be recycled, i.e., mixed with the water stream obtained from a water source and treated in fluid treatment system. Furthermore, a wellbore servicing method may comprise conveying the wellbore servicing fluid from its source to the wellbore via the operation of the pump **10** disclosed herein.

(109) In alternative embodiments, the reciprocating apparatus may comprise a compressor. In embodiments, a compressor similar to the pump **10** may comprise at least one each of a cylinder, plunger, connecting rod, crankshaft, and housing, and may be coupled to a motor. In embodiments, such a compressor may be similar in form to a pump and may be configured to compress a compressible fluid (e.g., a gas) and thereby increase the pressure of the compressible fluid. For example, a compressor may be configured to direct the discharge therefrom to a chamber or vessel that collects the compressible fluid from the discharge of the compressor until a predetermined pressure is built up in the chamber. Generally, a pressure sensing device may be arranged and configured to monitor the pressure as it builds up in the chamber and to interact with the compressor when a predetermined pressure is reached. At that point, the compressor may either be shut off, or alternatively the discharge may be directed to another chamber for continued operation.

(110) In embodiments, a reciprocating apparatus comprises an internal combustion engine, hereinafter referred to as an engine. Such engines are also well known, and typically include at least one each of a plunger, cylinder, connecting rod, and crankshaft. The arrangement of these components is substantially the same in an engine and a pump (e.g. pump **10**). A reciprocating element **18** such as a plunger may be similarly arranged to move in reciprocating fashion within the cylinder. Skilled artisans will appreciate that operation of an engine may somewhat differ from that of a pump. In a pump, rotational power is generally applied to a crankshaft acting on the plunger via the connecting rod, whereas in an engine, rotational power generally results from a force (e.g., an internal combustion) exerted on or against the plunger, which acts against the crankshaft via the connecting rod.

(111) For example, in a typical 4-stroke engine, arbitrarily beginning with the exhaust stroke, the plunger is fully extended during the exhaust stroke, (e.g., minimizing the internal volume of the cylinder). The plunger may then be retracted by inertia or other forces of the engine componentry during the intake stroke. As the plunger retracts within the cylinder, the internal volume of cylinder increases, creating a low pressure within the cylinder into which an air/fuel mixture is drawn. When the plunger is fully retracted within the cylinder, the intake stroke is complete, and the cylinder is substantially filled with the air/fuel mixture. As the crankshaft continues to rotate, the

plunger may then be extended, during the compression stroke, into the cylinder compressing the air-fuel mixture within the cylinder to a higher pressure.

(112) A spark plug may be provided to ignite the fuel at a predetermined point in the compression stroke. This ignition increases the temperature and pressure within the cylinder substantially and rapidly. In a diesel engine, however, the spark plug may be omitted, as the heat of compression derived from the high compression ratios associated with diesel engines suffices to provide spontaneous combustion of the air-fuel mixture. In either case, the heat and pressure act forcibly against the plunger and cause it to retract back into the cylinder during the power cycle at a substantial force, which may then be exerted on the connecting rod, and thereby on to the crankshaft.

(113) Those of ordinary skill in the art will readily appreciate various benefits that may be realized by the present disclosure. Conventional pump assemblies comprising pump valve seats experience high erosion rates which require frequent replacement. Seat replacement is a time consuming and labor intensive process. A long life valve seat of hardened material which resists erosion, such as ceramic or carbide, can be utilized; however, this can be cost prohibitive due to the material quantity required to form the complete conventional valve seat. A valve assembly **20** of this disclosure comprises a hardened insert carrier **5** carrier for a hardened insert **2**, wherein the hardened insert **2** and the hardened insert carrier **5** provide the contact surface **30** that contacts the valve **3** (e.g., valve body **3A** and valve insert **3B**) when the valve assembly **20** is in the closed configuration. The herein disclosed valve assembly **20** thus obviates the need for a conventional valve seat. The hardened insert carrier **5** can serve as a housing (e.g., be an RVC **40**, as described hereinabove), can be integral to the fluid end **22** (e.g., can comprise the pump fluid end body **8**) or can serve another function (e.g., can be a plunger **18** or piston).

(114) By utilizing a hardened insert **2** coupled with a hardened insert carrier **5**, a material of the hardened insert **2** can be disparate from a material of the hardened insert carrier (i.e., a material of the initial contact surface **30B** provided by the hardened insert carrier **5** can be disparate from a material of the primary sealing surface **30A** provided by the hardened insert **2**). Accordingly, an amount of hardened material needed to provide sufficient sealing between the contact surface **30** and the valve **3** is greatly reduced relative to a conventional valve seat, in which the initial sealing surface and the primary sealing surface are provided by a valve seat. Utilizing a contact surface **30** provided with a hardened insert **2** that replaces or removes the need for a conventional valve seat thus allows for a reduction in an amount of hardened material needed to provide the sealing surface. The valve assembly **40** of this disclosure can thus increase a life of the valve assembly **20** relative to conventional valve assemblies and lower total component cost, thus providing decreased maintenance spend and decreased non-productive time on location. In embodiments, the hardened insert **2** can also serve as a retainer through added geometry (e.g., via extension or lip E, described hereinabove with reference to FIGS. **9A-9C**) for another component of the valve assembly **20**, such as a valve spring **31**.

(115) Additional Disclosure

(116) The following are non-limiting, specific embodiments in accordance with the present disclosure:

(117) In a first embodiment, a valve assembly comprises: a hardened insert coupled with a hardened insert carrier; and a valve body coupled with a valve insert, wherein, in a closed configuration of the valve assembly, the valve body contacts a primary sealing surface of the hardened insert and the valve insert contacts an initial sealing surface of a hardened insert carrier to prevent fluid flow through the valve assembly, and, in an open configuration of the valve assembly, the valve body does not contact the primary sealing surface of the hardened insert and the valve insert does not contact the initial sealing surface of the hardened insert carrier to allow fluid flow through the valve assembly, wherein the hardened insert carrier comprises a reciprocating element, a replaceable valve carrier (RVC), or a pump fluid end body.

- (118) A second embodiment can include the valve assembly of the first embodiment, wherein the primary sealing surface and the initial sealing surface comprise disparate materials.
- (119) A third embodiment can include the valve assembly of the second embodiment, wherein a material of the primary sealing surface has a greater hardness than a material of the initial sealing surface, wherein the hardness is measured by the Vickers Hardness according to ASTM E92, the Rockwell or Vickers Hardness as measured by ASTM E18-19, and/or the Brinell Hardness as measured by ASTM E10-18.
- (120) A fourth embodiment can include the valve assembly of the second or third embodiment, wherein the primary sealing surface comprises carbide, and the hardened insert comprises a carbide ring.
- (121) A fifth embodiment can include the valve assembly of the fourth embodiment, wherein the initial sealing surface comprises carburized steel.
- (122) A sixth embodiment can include the valve assembly of the fourth or fifth embodiment, wherein an amount of carbide in the hardened insert is at least 40, 50, or 60% less than an amount of carbide in a conventional valve seat wherein the primary sealing surface and the initial sealing surface are provided by a carbide valve seat.
- (123) A seventh embodiment can include the valve assembly of any one of the first to sixth embodiments, wherein the valve, the primary sealing surface, the initial sealing surface, or a combination thereof is frusto-conical or frusto-spherical in shape.
- (124) An eighth embodiment can include the valve assembly of any one of the first to seventh embodiments, wherein the hardened insert comprises an extension, wherein the extension extends a distance in a direction perpendicular to a central axis of the valve assembly, wherein the extension retains another component of the valve assembly.
- (125) A ninth embodiment can include the valve assembly of the eighth embodiment, wherein the another component of the valve assembly comprises a valve spring.
- (126) A tenth embodiment can include the valve assembly of any one of the first to ninth embodiments, wherein the initial sealing surface is provided by a front surface of the reciprocating element, a cylindrical inside surface of the replaceable valve carrier (RVC), or an inside surface of the pump fluid end body, respectively.
- (127) In an eleventh embodiment, a pump fluid end comprises: a reciprocating element at least partially within a reciprocating element bore of the pump fluid end, wherein the reciprocating element bore extends into the pump fluid end from an end of the pump fluid end and has a central axis; a suction valve assembly; and a discharge valve assembly, wherein the suction valve assembly, the discharge valve assembly, or both comprise a valve assembly comprising a hardened insert coupled with a hardened insert carrier, and a valve comprising a valve body coupled with a valve insert, wherein, in a closed configuration of the valve assembly, the valve body contacts a primary sealing surface of the hardened insert and the valve insert contacts an initial sealing surface of a hardened insert carrier to prevent fluid flow through the valve assembly, and, in an open configuration of the valve assembly, the valve body does not contact the primary sealing surface of the hardened insert and the valve insert does not contact the initial sealing surface of the hardened insert carrier to allow fluid flow through the valve assembly, and wherein the hardened insert carrier comprises a reciprocating element, a replaceable valve carrier (RVC), or a pump fluid end body.
- (128) A twelfth embodiment can include the pump fluid end of the eleventh embodiment, wherein the pump fluid end is a concentric bore pump fluid end, wherein the suction valve assembly comprises the valve assembly comprising the hardened insert coupled with the hardened insert carrier, and the valve comprising the valve body coupled with the valve insert, wherein the hardened insert carrier comprises the reciprocating element, wherein the hardened insert is coupled with a front end of the reciprocating element about an inside surface thereof, and wherein the initial sealing surface is provided by a front surface of the reciprocating element.

(129) A thirteenth embodiment can include the pump fluid end of the eleventh embodiment or twelfth embodiment, wherein a material of the reciprocating element is disparate from a material of the hardened insert.

(130) A fourteenth embodiment can include the pump fluid end of the eleventh embodiment, wherein the hardened insert carrier comprises the replaceable valve carrier (RVC), wherein the RVC is coupled with an inside surface of a pump fluid end body of the pump fluid end, wherein the hardened insert is positioned about a cylindrical inside surface of the RVC, and wherein the initial sealing surface comprises the cylindrical inside surface of the RVC.

(131) A fifteenth embodiment can include the pump fluid end of any one of the eleventh to fourteenth embodiments, wherein the pump fluid end is a concentric bore pump fluid end or a cross bore pump fluid end.

(132) A sixteenth embodiment can include the pump fluid end of the fourteenth embodiment, wherein a surface area of the inside surface of the RVC is at least 5, 10, or 15% larger than the combined area of the initial sealing surface and the primary sealing surface.

(133) A seventeenth embodiment can include the pump fluid end of any one of the fourteenth to sixteenth embodiments, wherein a material of the RVC is disparate from a material of the hardened insert.

(134) An eighteenth embodiment can include the pump fluid end of the eleventh embodiment, wherein the hardened insert carrier comprises the pump fluid end body of the pump fluid end, and wherein the hardened insert is disposed about an inside surface of the pump fluid end body of the pump fluid end.

(135) A nineteenth embodiment can include the pump fluid end of the eighteenth embodiment, wherein the pump fluid end is a concentric bore pump fluid end or a cross bore pump fluid end.

(136) A twentieth embodiment can include the pump fluid end of the eighteenth or nineteenth embodiments, wherein a material of the hardened insert is disparate from a material of the inside surface of the pump fluid end body.

(137) In a twenty first embodiment, a pump comprises the pump fluid end of any one of the eleventh to twentieth embodiments, and a pump power end, wherein the pump power end is operable to reciprocate the reciprocating element within the reciprocating element bore of the pump fluid end.

(138) In a twenty second embodiment, a method of servicing a wellbore comprises: fluidly coupling a pump to a source of a wellbore servicing fluid and to the wellbore; and communicating wellbore servicing fluid into a formation in fluid communication with the wellbore via the pump, wherein the pump comprises a pump fluid end and a pump power end, wherein the pump fluid end comprises: a reciprocating element at least partially within a reciprocating element bore of the pump fluid end, wherein the reciprocating element bore extends into the pump fluid end from an end of the pump fluid end and has a central axis; a suction valve assembly; and a discharge valve assembly, wherein the suction valve assembly, the discharge valve assembly, or both comprise a valve assembly comprising a hardened insert coupled with a hardened insert carrier, and a valve comprising a valve body coupled with a valve insert, wherein, in a closed configuration of the valve assembly, the valve body contacts a primary sealing surface of the hardened insert and the valve insert contacts an initial sealing surface of a hardened insert carrier to prevent fluid flow through the valve assembly, and, in an open configuration of the valve assembly, the valve body does not contact the primary sealing surface of the hardened insert and the valve insert does not contact the initial sealing surface of the hardened insert carrier to allow fluid flow through the valve assembly, and wherein the hardened insert carrier comprises the reciprocating element, a replaceable valve carrier (RVC), or a pump fluid end body; and wherein the pump power end is operable to reciprocate the reciprocating element within the reciprocating element bore of the pump fluid end.

(139) A twenty third embodiment can include the method of the twenty second embodiment,

wherein the wellbore servicing fluid comprises a fracturing fluid, a cementitious fluid, a remedial fluid, a perforating fluid, a sealant, a drilling fluid, a spacer fluid, a completion fluid, a gravel pack fluid, a diverter fluid, a gelation fluid, a polymeric fluid, an aqueous fluid, an oleaginous fluid, or a combination thereof.

(140) A twenty fourth embodiment can include the method of the twenty second or twenty third embodiments, wherein the pump operates during the pumping of the wellbore servicing fluid at a pressure of greater than or equal to about 3,000 psi, 5,000 psi, 10,000 psi, 20,000 psi, 30,000 psi, 40,000 psi, or 50,000 psi.

(141) A twenty fifth embodiment can include the method of any one of the twenty second to twenty fourth embodiments, wherein the pump operates during the pumping of the wellbore servicing fluid at a volumetric flow rate of greater than or equal to about 3, 10, or 20 barrels per minute (BPM), or in a range of from about 3 to about 20, from about 10 to about 20, or from about 5 to about 20 BPM.

(142) While embodiments have been shown and described, modifications thereof can be made by one skilled in the art without departing from the spirit and teachings of this disclosure. The embodiments described herein are exemplary only, and are not intended to be limiting. Many variations and modifications of the embodiments disclosed herein are possible and are within the scope of this disclosure. Where numerical ranges or limitations are expressly stated, such express ranges or limitations should be understood to include iterative ranges or limitations of like magnitude falling within the expressly stated ranges or limitations (e.g., from about 1 to about 10 includes, 2, 3, 4, etc.; greater than 0.10 includes 0.11, 0.12, 0.13, etc.). For example, whenever a numerical range with a lower limit, R_l , and an upper limit, R_u , is disclosed, any number falling within the range is specifically disclosed. In particular, the following numbers within the range are specifically disclosed: $R = R_l + k * (R_u - R_l)$, wherein k is a variable ranging from 1 percent to 100 percent with a 1 percent increment, i.e., k is 1 percent, 2 percent, 3 percent, 4 percent, 5 percent, . . . 50 percent, 51 percent, 52 percent, . . . , 95 percent, 96 percent, 97 percent, 98 percent, 99 percent, or 100 percent. Moreover, any numerical range defined by two R numbers as defined in the above is also specifically disclosed. Use of the term “optionally” with respect to any element of a claim is intended to mean that the subject element is required, or alternatively, is not required. Both alternatives are intended to be within the scope of the claim. Use of broader terms such as comprises, includes, having, etc. should be understood to provide support for narrower terms such as consisting of, consisting essentially of, comprised substantially of, etc.

(143) Accordingly, the scope of protection is not limited by the description set out above but is only limited by the claims which follow, that scope including all equivalents of the subject matter of the claims. Each and every claim is incorporated into the specification as an embodiment of the present disclosure. Thus, the claims are a further description and are an addition to the embodiments of the present disclosure. The discussion of a reference herein is not an admission that it is prior art, especially any reference that may have a publication date after the priority date of this application. The disclosures of all patents, patent applications, and publications cited herein are hereby incorporated by reference, to the extent that they provide exemplary, procedural, or other details supplementary to those set forth herein.

Claims

1. A valve assembly comprising: a hardened insert coupled with a hardened insert carrier; and a valve body coupled with a valve insert, wherein, in a closed configuration of the valve assembly, the valve body contacts a primary sealing surface of the hardened insert and the valve insert contacts an initial sealing surface of the hardened insert carrier to prevent fluid flow through the valve assembly, and, in an open configuration of the valve assembly, the valve body does not contact the primary sealing surface of the hardened insert and the valve insert does not contact the

initial sealing surface of the hardened insert carrier to allow fluid flow through the valve assembly, wherein the hardened insert carrier comprises a reciprocating element, a replaceable valve carrier (RVC), or a pump fluid end body, and wherein the hardened insert comprises an extension, wherein the extension extends a distance in a direction perpendicular to a central axis of the valve assembly, wherein the extension retains another component of the valve assembly.

2. A pump fluid end comprising: a reciprocating element at least partially within a reciprocating element bore of the pump fluid end, wherein the reciprocating element bore extends into the pump fluid end from an end of the pump fluid end and has a central axis; a suction valve assembly; and a discharge valve assembly, wherein the suction valve assembly, the discharge valve assembly, or both comprise the valve assembly of claim 1.

3. The pump fluid end of claim 2, wherein the pump fluid end is a concentric bore pump fluid end, wherein the suction valve assembly comprises the valve assembly comprising the hardened insert coupled with the reciprocating element.

4. The pump fluid end of claim 3, wherein a material of the reciprocating element is disparate from a material of the hardened insert.

5. A method of servicing a wellbore, the method comprising: fluidly coupling a pump to a source of a wellbore servicing fluid and to the wellbore; and communicating wellbore servicing fluid into a formation in fluid communication with the wellbore via the pump, wherein the pump comprises a pump fluid end and a pump power end, wherein the pump fluid end comprises the valve assembly of claim 1.

6. The method of claim 5, wherein the wellbore servicing fluid comprises a fracturing fluid, a cementitious fluid, a remedial fluid, a perforating fluid, a sealant, a drilling fluid, a spacer fluid, a completion fluid, a gravel pack fluid, a diverter fluid, a gelation fluid, a polymeric fluid, an aqueous fluid, an oleaginous fluid, or a combination thereof.

7. The method of claim 5, wherein the pump operates during the pumping of the wellbore servicing fluid at a pressure of greater than or equal to about 3,000 psi.

8. The valve assembly of claim 1, wherein the initial sealing surface is provided by a front surface of the reciprocating element, a cylindrical inside surface of the replaceable valve carrier (RVC), or an inside surface of the pump fluid end body, respectively.

9. The valve assembly of claim 1, wherein the primary sealing surface and the initial sealing surface comprise disparate materials.

10. The valve assembly of claim 9, wherein a material of the primary sealing surface has a greater hardness than a material of the initial sealing surface, wherein the hardness is measured by the Vickers Hardness according to ASTM E92, the Rockwell or Vickers Hardness as measured by ASTM E18-19, and/or the Brinell Hardness as measured by ASTM E10-18.

11. The valve assembly of claim 9, wherein the primary sealing surface comprises carbide, and the hardened insert comprises a carbide ring.

12. The valve assembly of claim 1, wherein the valve body, the primary sealing surface, the initial sealing surface, or a combination thereof is frusto-conical or frusto-spherical in shape.

13. The valve assembly of claim 1, wherein the another component of the valve assembly comprises a valve spring.
