

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406406
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Choi; Seunghwan

Electronic device for providing augmented reality mode, and operating method therefor

Abstract

An electronic device may include a camera module, a processor operably connected to the camera module, and a memory operably connected to the processor, wherein the memory may store one or more instructions for allowing, during the execution thereof, the processor to identify a first interaction for a first application being executed, form a first application object for outputting an execution screen of the first application according to the identification of the first interaction, output an augmented reality space on the basis of an actual space recognized through the camera module, and output the first application object in the augmented reality space.

Inventors:	Choi; Seunghwan (Suwon-si, KR)
Applicant:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Family ID:	77671833
Assignee:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Appl. No.:	17/940833
Filed:	September 08, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230005193 A1	Jan. 05, 2023

Foreign Application Priority Data

KR	10-2020-0029812	Mar. 10, 2020
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06T11/00** (20060101); **G06F3/01** (20060101); **G06F3/0484** (20220101); **G06F9/451** (20180101); **G06T19/20** (20110101); **G06V20/20** (20220101); **G06V40/20** (20220101)

U.S. Cl.:

CPC **G06T11/00** (20130101); **G06F3/01** (20130101); **G06F3/011** (20130101); **G06F3/0484** (20130101); **G06F9/451** (20180201); **G06T19/20** (20130101); **G06V20/20** (20220101); **G06V40/20** (20220101); G06T2200/24 (20130101); G06T2219/2016 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9754414	12/2016	Kim et al.	N/A	N/A
10681287	12/2019	Park et al.	N/A	N/A
11308653	12/2021	Yoon et al.	N/A	N/A
2009/0027334	12/2008	Foulk	345/157	G06F 3/04886
2010/0066698	12/2009	Seo	N/A	N/A
2012/0194541	12/2011	Kim et al.	N/A	N/A
2014/0152698	12/2013	Kim et al.	N/A	N/A
2014/0304612	12/2013	Collin	715/748	G06F 9/451
2017/0150139	12/2016	Lee	N/A	H04N 13/344
2017/0154188	12/2016	Meier	N/A	G06F 21/552
2019/0098227	12/2018	Park et al.	N/A	N/A
2019/0384460	12/2018	Harnisch	N/A	G06F 9/453
2020/0226835	12/2019	Farchy	N/A	G06F 3/0346
2020/0265613	12/2019	Yoon et al.	N/A	N/A
2020/0286449	12/2019	Yang	N/A	G02B 27/01

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2010-0032660	12/2009	KR	N/A
10-2012-0026702	12/2011	KR	N/A
10-2012-0087024	12/2011	KR	N/A
10-2014-0071086	12/2013	KR	N/A
10-2017-0090392	12/2016	KR	N/A
10-2017-0125618	12/2016	KR	N/A
10-1894573	12/2017	KR	N/A
10-2019-0035116	12/2018	KR	N/A
10-2019-0059629	12/2018	KR	N/A

10-2019-0106404	12/2018	KR	N/A
10-2085136	12/2019	KR	N/A

OTHER PUBLICATIONS

Jens Grubert, Matthias Heinisch, Aaron Quigley, Dieter Schmalstieg, “MultiFi: Multi-Fidelity Interaction with Displays on and Around the Body”, Apr. 18, 2015, CHI '15: Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems pp. 3933-3942. cited by examiner

Erwan Normand, Michael J. McGuffin, “Enlarging a Smartphone with AR to Create a Handheld VESAD (Virtually Extended Screen-Aligned Display)”, Jan. 17, 2019, IEEE, 2018 IEEE International Symposium on Mixed and Augmented Reality (ISMAR), pp. 123-133. cited by examiner

Marcos Serrano, Barrett Ens, Xing-Dong Yang, Pourang Irani, “Gluey: Developing a Head-Worn Display Interface to Unify the Interaction Experience in Distributed Display Environments”, Aug. 24, 2015, ACM, Proceedings of the 17th International Conference on Human-Computer Interaction with Mobile Devices and Services. cited by examiner

Xiang ‘Anthony’ Chen, Julia Schwarz, Chris Harrison, et al., “Around-Body Interaction: Sensing & Interaction Techniques for Proprioception-Enhanced Input with Mobile Devices”, Sep. 23, 2014, ACM, Proceedings of the 16th International Conference on Human-Computer Interaction with Mobile Devices and Services. cited by examiner

Korean Office Action dated Jan. 31, 2024 for JP Application No. 10-2020-0029812. cited by applicant

Primary Examiner: Bader; Robert

Attorney, Agent or Firm: NIXON & VANDERHYE P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation of International Application No. PCT/KR2021/002979 designating the United States, filed on Mar. 10, 2021, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2020-0029812 filed Mar. 10, 2020, the disclosures of which are hereby incorporated herein by reference for all purposes as if fully set forth herein.

FIELD

(1) Various embodiments relate to an electronic device that provides an augmented reality mode and an operation method thereof.

BACKGROUND

(2) Augmented reality (AR) as a field of virtual reality (VR) is a computer graphic technique that synthesizes a virtual object or information in an actual environment to make the virtual object or information look like an object existing in the original environment.

(3) An electronic device may provide a multitasking screen that facilitates switching between tasks, such as switching an application in use to another application. The multitasking screen may receive a selection input of a user by displaying at least one application and/or task being executed.

SUMMARY

(4) The disclosure is to provide an electronic device and/or an operation method thereof that enable intuitive application search and switching and/or simplify a content sharing process between applications by providing a multitasking screen using an augmented reality mode.

- (5) An electronic device according to an example embodiment may include a camera module including imaging circuitry and/or at least one lens, a processor operatively connected to the camera module, and a memory operatively coupled to the processor, and the memory stores instructions that, when executed, may cause the processor to identify a first interaction for a first application being executed, form a first app object of outputting an execution screen of the first application as the first interaction is identified, output an augmented reality space based on a real space recognized via the camera module, and output the first app object in the augmented reality space.
- (6) An operation method of an electronic device for providing an augmented reality mode according to an example embodiment may include identifying a first interaction for a first application being executed, forming a first app object of outputting an execution screen of the first application as the first interaction is identified, outputting an augmented reality space based on a real space recognized via the camera module, and outputting the first app object in the augmented reality space.
- (7) According to various example embodiments, the electronic device and/or the operation method thereof may enable the intuitive application search and switching and simplify the content sharing process between the applications by providing the multitasking screen using the augmented reality mode may be provided.
- (8) In addition, various effects directly or indirectly identified through the disclosure may be provided.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain example embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a block diagram of an electronic device in a network environment according to various example embodiments.
- (3) FIG. 2 is a flowchart showing operations of an electronic device according to an example embodiment.
- (4) FIG. 3 is a diagram showing operations of an electronic device according to an example embodiment in order.
- (5) FIG. 4 is a diagram showing operations of an electronic device according to an example embodiment in order.
- (6) FIG. 5 is a flowchart showing operations of an electronic device according to an example embodiment.
- (7) FIG. 6 is a diagram showing operations of an electronic device according to an example embodiment in order.
- (8) FIG. 7 is a diagram showing operations of an electronic device according to an example embodiment in order.
- (9) FIG. 8 is a flowchart showing operations of an electronic device according to an embodiment.
- (10) FIG. 9 is a diagram showing operations of an electronic device according to an example embodiment in order.
- (11) FIG. 10 is a diagram showing operations of an electronic device according to an example embodiment in order.
- (12) FIG. 11 is a flowchart showing operations of an electronic device according to an example embodiment.
- (13) FIG. 12 is a diagram showing operations of an electronic device according to an example

embodiment in order.

(14) FIG. 13 is a diagram showing operations of an electronic device subsequent to operations in FIG. 12 of the electronic device according to an example embodiment in order.

(15) FIG. 14 is a diagram showing operations of an electronic device according to an example embodiment in order.

(16) In connection with the description of the drawings, the same or similar reference numerals may be used for the same or similar components.

DETAILED DESCRIPTION

(17) Hereinafter, various embodiments of the disclosure will be described with reference to the accompanying drawings. However, this is not intended to limit the disclosure to specific embodiments, and it should be understood to include various modifications, equivalents, and/or alternatives of embodiments of the disclosure.

(18) Hereinafter, with reference to FIG. 1, a configuration of an electronic device according to an embodiment will be described.

(19) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input device **150**, a sound output device **155**, a display device **160**, an audio module **170**, a sensor module **176**, an interface **177**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one (e.g., the display device **160** or the camera module **180**) of the components may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components may be implemented as single integrated circuitry. For example, the sensor module **176** (e.g., a fingerprint sensor, an iris sensor, or an illuminance sensor) may be implemented as embedded in the display device **160** (e.g., a display).

(20) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may load a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), and an auxiliary processor **123** (e.g., a graphics processing unit (GPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. Additionally or alternatively, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(21) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display device **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication

processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**.

(22) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(23) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(24) The input device **150** may receive a command or data to be used by other component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input device **150** may include, for example, a microphone, a mouse, a keyboard, or a digital pen (e.g., a stylus pen).

(25) The sound output device **155** may output sound signals to the outside of the electronic device **101**. The sound output device **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record, and the receiver may be used for an incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(26) The display device **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display device **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display device **160** may include touch circuitry adapted to detect a touch, or sensor circuitry (e.g., a pressure sensor) adapted to measure the intensity of force incurred by the touch.

(27) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input device **150**, or output the sound via the sound output device **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(28) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(29) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(30) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(31) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(32) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal

processors, or flashes.

(33) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(34) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(35) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a cellular network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(36) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., PCB). According to an embodiment, the antenna module **197** may include a plurality of antennas. In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(37) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(38) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** and **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the

external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, or client-server computing technology may be used, for example.

(39) Hereinafter, with reference to FIG. **2**, an operation of an electronic device according to an embodiment will be described.

(40) FIG. **2** is a flowchart **200** showing operations of an electronic device according to an embodiment. The operations of the electronic device to be described below may be performed by a processor (e.g., the processor **120** in FIG. **1**) of the electronic device (e.g., the electronic device **101** in FIG. **1**).

(41) Referring to FIG. **2**, in operation **201**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may identify an interaction for fixing an application while the application (e.g., the application **146** in FIG. **1**) stored in a memory (e.g., the memory **130** in FIG. **1**) of the electronic device is being executed in an entire screen of the electronic device (e.g., while an execution screen of the application is being output with a first size).

(42) According to one embodiment, the fixing of the application may mean or cover terminating the entire screen of the application being executed and placing a reduced screen of the application being executed in an augmented reality space (e.g., outputting the execution screen of the application in the augmented reality space with a second size smaller than the first size). According to one embodiment, the fixing of the application may mean or cover terminating the entire screen of the application being executed and outputting a multitasking screen or an application switching screen for multitasking or switching to another application.

(43) According to one embodiment, the multitasking screen or the application switching screen may be implemented as an augmented reality space screen. According to one embodiment, the augmented reality space screen may include at least one icon for the multitasking and/or at least one reduced screen of the application, and the electronic device may execute a corresponding function when an input for selecting the icon or the reduced screen is received.

(44) According to one embodiment, the interaction for fixing the application may include an operation in which a user moves the electronic device to a specific location in a real space. According to one embodiment, the specific location may be a location on the real space corresponding to a location where the user wants to fix the application in the augmented reality space. According to one embodiment, the interaction for fixing the application may include at least one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, and drag of the entire screen of the application. According to one embodiment, the interaction for fixing the application may include at least one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag of the entire screen of the application after the user moves the electronic device to the specific location in the real space.

(45) In operation **202**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may determine the application currently being executed in the entire screen of the electronic device as the interaction for fixing the application is identified. According to one embodiment, the electronic device may start outputting the application that is determined to currently being executed in the entire screen of the electronic device to a virtual memory for the multitasking or the switching of the application as the interaction for fixing the application is

identified.

(46) In operation **203**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may form a first app object that outputs the execution screen of the application currently being executed in the entire screen of the electronic device as the interaction for fixing the application is identified. According to one embodiment, the first app object may be an object that may be disposed in the augmented reality space. According to one embodiment, the first app object may be an object of augmented reality that may output the reduced screen that is obtained by reducing the execution screen of the application. According to one embodiment, the electronic device may map the reduced screen obtained by reducing the execution screen of the application currently being executed to the first app object. According to one embodiment, as the execution screen of the application currently being executed in the entire screen of the electronic device is mapped to the first app object, the execution screen of the application may be output as it is.

(47) In operation **204**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may output the first app object that outputs the execution screen of the application in the augmented reality space. According to one embodiment, the electronic device may form the augmented reality space based on an external video recognized via a camera module (e.g., the camera module **180** in FIG. **1**), and may execute an augmented reality mode that reproduces the formed augmented reality space. According to one embodiment, the electronic device may execute the augmented reality mode while terminating the entire screen of the application, and may output the first app object in the augmented reality space.

(48) According to one embodiment, the electronic device may identify a location of the electronic device with a GPS and/or a compass of the electronic device at a time point at which the interaction for fixing the application of the user occurs, and may output the first app object at a location in the augmented reality space corresponding to identified coordinates of the electronic device.

Alternatively, according to one embodiment, the electronic device may record a relative location of the first app object based on the location of the electronic device in the augmented reality space, so that, even when the electronic device (the user holding the electronic device) moves from the real space to another region, the first app object may be output to correspond to the relative location in the augmented reality space reflecting the corresponding region.

(49) Hereinafter, with reference to FIG. **3**, operations of an electronic device according to an embodiment will be described. Each embodiment herein may be used in combination with any other embodiment herein.

(50) FIG. **3** is a diagram **300** showing operations of an electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. **1**) of the electronic device (e.g., the electronic device **101** in FIG. **1**). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(51) Referring to a first drawing **310** in FIG. **3**, the electronic device **101** (or the processor **120**) may output an execution screen of an application **311** in the entire screen of the electronic device **101**. The electronic device **101** may be located at an arbitrary location in a real space **312**.

(52) Referring to a second drawing **320** in FIG. **3**, the user possessing the electronic device **101** may move to a specific location in the real space **312** together with the electronic device **101**.

(53) Referring to a third drawing **330** in FIG. **3**, as the electronic device **101** moves to the specific location in the real space **312**, or as an input for fixing the application **311** is additionally received after the movement, the electronic device **101** may identify that an interaction for fixing the application **311** has occurred.

(54) According to one embodiment, the electronic device **101** may determine the application **311** currently being executed in the entire screen of the electronic device **101** as the interaction for fixing the application **311** is identified. In addition, according to one embodiment, the electronic device **101** may start outputting the application **311** that is currently being executed in the entire

screen of the electronic device **101** to the virtual memory for the multitasking or the switching of the application as the interaction for fixing application **311** is identified.

(55) According to one embodiment, the electronic device **101** may form a first app object **331** as the interaction for fixing the application **311** is identified. According to one embodiment, the electronic device **101** may map the execution screen of the application **311** currently being executed in the entire screen of the electronic device **101** to the formed first app object **331**.

(56) Referring to a fourth drawing **340** in FIG. 3, the electronic device **101** may output the first app object **331** mapped with the execution screen of the application in an augmented reality space **341**. The electronic device **101** may form the augmented reality space **341** based on the real space **312** recognized via the camera module (e.g., the camera module **180** in FIG. 1), and may output the first app object **331** at a location in the augmented reality space **341** corresponding to coordinates of the real space **312** of the electronic device **101**. The electronic device **101** may terminate the entire screen of the application while executing the augmented reality mode that reproduces the formed augmented reality space **341** and output a content of the augmented reality space **341** on a display device.

(57) According to one embodiment, the augmented reality space **341** may output not only the first app object **331**, but also a second app object **342** to which an execution screen of a second application is mapped, and a third app object **343** to which an execution screen of a third application is mapped.

(58) Referring to a fifth drawing **350** in FIG. 3, as the electronic device **101** moves in the real space, the content of the augmented reality space **341** corresponding to the location of the electronic device **101** is output on the display device (e.g., the display device **160** in FIG. 1), and the user may switch the applications by selecting one of the first app object **331**, the second app object **342**, and the third app object **343** on the content of the augmented reality space **341** output on the electronic device **101**. For example, when an input of selecting the second app object **342** is received from the user, the electronic device **101** may terminate the augmented reality mode and may execute the second application in the entire screen.

(59) Hereinafter, with reference to FIG. 4, operations of an electronic device according to an embodiment will be described.

(60) FIG. 4 is a diagram **400** showing operations of an electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. 1) of the electronic device (e.g., the electronic device **101** in FIG. 1). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(61) Referring to a first drawing **410** in FIG. 4, the electronic device **101** (or the processor **120**) may output an application **411** being executed in the entire screen of the electronic device **101**. The electronic device **101** may be located at an arbitrary location in a real space **431**. According to one embodiment, the real space **431** in which a table is located is assumed.

(62) Referring to a second drawing **420** in FIG. 4, the user possessing the electronic device **101** may move to a specific location in the real space **431** together with the electronic device **101**. According to one embodiment, it is assumed that the electronic device **101** has moved to a location near the table so that a distance to the table **431** is reduced.

(63) According to one embodiment, when the user moves to the specific location in the real space, the electronic device **101** may identify that an interaction for fixing the application **411** has occurred.

(64) Alternatively, according to one embodiment, as the user moves to a location in the real space corresponding to a location at which the application **411** is to be fixed in the virtual real space and an input (e.g., touch, tap, swipe, and the like) for fixing the application **411** is additionally input, the electronic device **101** may identify that the interaction for fixing the application **411** has occurred.

(65) Referring to a third drawing **430** in FIG. **4**, as it is identified that the interaction for fixing the application **411** has occurred, the electronic device **101** may form a first app object **433**, and map the execution screen of the application **411** being executed in the entire screen of the electronic device **101** to the formed first app object **433**. In addition, the electronic device **101** may form an augmented reality space **432** and output the first app object **433** in the formed augmented reality space **432**. According to one embodiment, the electronic device **101** may form the augmented reality space **432** based on the real space **431** recognized via the camera module (e.g., the camera module **180** in FIG. **1**), and, for example, the formed augmented reality space **432** may contain a table object corresponding to the table in the real space **431**. In addition, for example, when a location of the electronic device **101** was on the table in the real space **431** at a time point at which the interaction for fixing the application **411** has occurred, the electronic device **101** may output the first app object **433** on the table object in the augmented reality space **432**. The electronic device **101** may terminate the entire screen of the application **411** and execute the augmented reality mode to output the augmented reality space **432** on the display device (e.g., the display device **160** in FIG. **1**). The camera module **180** may include imaging circuitry and/or at least one lens.

(66) According to one embodiment, the augmented reality space **432** may include a second app object **434** to which the execution screen of the second application is mapped, a third app object **435** to which the execution screen of the third application is mapped, and a fourth app object **436** to which an execution screen of a fourth application is mapped, which are formed via a process similar to the process for forming the first app object **433**. According to one embodiment, the augmented reality mode may provide the application switching screen for switching the application being used to another application.

(67) Hereinafter, with reference to FIG. **5**, operations of an electronic device according to an embodiment will be described.

(68) FIG. **5** is a flowchart **500** showing operations of an electronic device according to an embodiment. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. **1**) of the electronic device (e.g., the electronic device **101** in FIG. **1**). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(69) Referring to FIG. **5**, in operation **501**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may identify the interaction for outputting the entire screen of the application (e.g., the application **146** in FIG. **1**) while executing the augmented reality mode.

(70) According to one embodiment, the interaction for outputting the entire screen of the application may be or include an input of selecting the app object in the augmented reality space. The input of selecting the app object according to an embodiment may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the app object.

(71) According to one embodiment, the interaction for outputting the entire screen of the application may be moving the electronic device to the specific location in the real space. Alternatively, according to one embodiment, the interaction for outputting the entire screen of the application may be moving the electronic device to the location in the real space corresponding to the location of the app object in the augmented reality space. According to one embodiment, the interaction for outputting the entire screen of the application may include both the movement of the electronic device and the input of selecting the app object in the augmented reality space.

(72) In operation **502**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may display the application corresponding to the selected app object in the entire screen of the display device (e.g., the display device **160** in FIG. **1**) of the electronic device.

(73) In operation **503**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may delete the selected app object and terminate the augmented reality mode.

(74) According to one embodiment, operation **502** and operation **503** may be performed

simultaneously.

(75) Hereinafter, with reference to FIG. 6, operations of an electronic device according to an embodiment will be described.

(76) FIG. 6 is a diagram 600 showing operations of an electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor 120 in FIG. 1) of the electronic device (e.g., the electronic device 101 in FIG. 1). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(77) Referring to a first drawing 610 in FIG. 6, the electronic device 101 (or the processor 120) may receive an input of selecting the app object 331 in the augmented reality space 341 displayed on the display device (e.g., the display device 160 in FIG. 1) of the electronic device. The electronic device 101 may be executing the augmented reality mode.

(78) According to one embodiment, the input of selecting the app object may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the app object.

(79) Referring to a second drawing 620 in FIG. 6, the electronic device 101 may move the app object 331 in the augmented reality space 341 to the location of the electronic device 101 in the augmented reality space 341 as the input of selecting the app object 331 is received.

(80) Referring to a third drawing 630 in FIG. 6, the electronic device 101 may output the application 311 corresponding to the selected app object 331 in the entire screen of the display device (e.g., the display device 160 in FIG. 1) of the electronic device. In addition, the electronic device 101 may delete the selected app object 331 and terminate the augmented reality mode. According to one embodiment, the electronic device 101 may not perform the operation of moving the app object 331 to the location of the electronic device 101 in the augmented reality space 341, which has been described via the second drawing 620 in FIG. 6, and perform the operation described via the third drawing 630 in FIG. 6.

(81) Hereinafter, with reference to FIG. 7, operations of an electronic device according to an embodiment will be described.

(82) FIG. 7 is a diagram 700 showing operations of an electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor 120 in FIG. 1) of the electronic device (e.g., the electronic device 101 in FIG. 1). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(83) Referring to a first drawing 710 in FIG. 7, the electronic device 101 (or the processor 120) may be executing the augmented reality mode that displays an augmented reality space 712. The augmented reality space 712 may contain a table object corresponding to a table located in a real space 711.

(84) According to one embodiment, the electronic device 101 may receive an input of selecting an app object 713 in the augmented reality space 712 that is output on the display device (e.g., the display device 160 in FIG. 1) of the electronic device. According to one embodiment, the input of selecting the app object 713 may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the app object 713.

(85) Referring to a second drawing 720 in FIG. 7, as the input of selecting the app object 713 is received, the electronic device 101 may output an application 720 corresponding to the selected app object 713 in the entire screen of the display device of the electronic device. In addition, the electronic device 101 may delete the selected app object 713 and terminate the augmented reality mode.

(86) Hereinafter, with reference to FIG. 8, operations of an electronic device according to an embodiment will be described.

(87) FIG. 8 is a flowchart **800** showing operations of an electronic device according to an embodiment. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. 1) of the electronic device (e.g., the electronic device **101** in FIG. 1). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(88) Referring to FIG. 8, in operation **801**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. 1) may identify an interaction for content sharing. According to one embodiment, the interaction for the content sharing may be an input of selecting a content to be shared in the first application. According to one embodiment, the content may include at least one of a document, a text, an image, and a video. According to one embodiment, the input of selecting the content to be shared may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the corresponding content.

(89) According to one embodiment, the interaction for the content sharing may be identified during the entire screen output of the first application, and may also be identified in the first app object for the first application output in the augmented reality space during the augmented reality mode execution. In FIG. 8, a description may be made assuming that the interaction for the content sharing is identified during the entire screen output of the application.

(90) In operation **802**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. 1) may store the selected content in a memory.

(91) In operation **803**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. 1) may form a shared object representing the selected content. According to one embodiment, the shared object may be or include an object that may be disposed in the augmented reality space. According to one embodiment, the shared object may be or include an object in the augmented reality that may output contents of the selected content.

(92) In operation **804**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. 1) may fix the first application being output in the entire screen in the augmented reality space and execute the augmented reality mode. According to one embodiment, fixing the first application in the augmented reality space may include outputting the first app object corresponding to the first application at the specific location in the augmented reality space and terminating the entire screen output of the first application. According to one embodiment, the operation of fixing the first application in the augmented reality space may be performed by the process of the flowchart **200** in FIG. 2.

(93) In operation **805**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. 1) may identify a movement interaction of the shared object during the execution of the augmented reality mode. According to one embodiment, the movement interaction of the shared object may mean an input of moving the shared object via operations such as touch, drag, swipe, press, and the like. According to one embodiment, the movement interaction of the shared object may be an operation of touching and dragging the shared object to drop the shared object on another app object.

(94) In operation **806**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. 1) may transmit a content corresponding to the shared object to the second application when the interaction of moving the shared object onto the second app object corresponding to the second application is received.

(95) Hereinafter, with reference to FIG. 9, operations of an electronic device according to an embodiment will be described.

(96) FIG. 9 is a diagram **900** showing operations of an electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. 1) of the electronic device (e.g., the electronic device **101** in FIG. 1). The same component as that in the above-described embodiment may be

referred to by the same reference number, and the description of the same content may be omitted. (97) Referring to a first drawing **910** in FIG. **9**, the electronic device **101** (or the processor **120**) may output a first application **911** stored in the memory (e.g., the memory **130** in FIG. **1**) of the electronic device **101** in the entire screen of the display device (e.g., the display device **160** in FIG. **1**) of the electronic device **101**. The electronic device **101** may identify an interaction of selecting a content **912** to be shared on an execution screen of the first application **911**.

(98) According to one embodiment, the content may contain at least one of a document, a text, an image, and a video displayed on the execution screen of the first application **911**.

(99) According to one embodiment, an input of selecting the content **912** to be shared may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the corresponding content.

(100) According to one embodiment, the electronic device **101** may store the selected content **912** in the memory.

(101) Referring to a second drawing **920** in FIG. **9**, the electronic device **101** may form a shared object **921** representing the selected content **912**. According to one embodiment, the shared object **921** may include an object that may be disposed in an augmented reality space **922**. According to one embodiment, the shared object **921** may output a content of the selected content **912**.

(102) According to one embodiment, the electronic device **101** may fix the first application **911** being output in the entire screen according to the flowchart **200** in FIG. **2** in the augmented reality space **922** and execute the augmented reality mode. According to one embodiment, fixing the first application **911** in the augmented reality space **922** may include outputting a first app object **924** corresponding to the first application **911** at a specific location in the augmented reality space **922** and terminating the entire screen output of the first application **911**. According to one embodiment, the augmented reality space **922** may contain a second app object **923** for the second application stored in the memory of the electronic device **101**.

(103) Referring to a third drawing **930** in FIG. **9**, the electronic device **101** may identify a movement interaction of the shared object **921** while executing the augmented reality mode. According to one embodiment, the movement interaction of the shared object **921** may include an input of moving the shared object **921** via operations such as touch, drag, swipe, press, and the like. According to one embodiment, the movement interaction of the shared object **921** may be an operation of touching and dragging the shared object **921** to drop the shared object **921** on another app object. According to one embodiment, the movement interaction of the shared object **921** may include the movement of the electronic device **101** itself.

(104) Referring to a fourth drawing **940** in FIG. **9**, as an interaction of moving the shared object **921** onto the second app object **923** corresponding to the second application and dropping the shared object **921** is received, the electronic device **101** may transmit information (e.g., copy of the content, reference information of the content (an URL of the content, an ID of the content, and the like)) corresponding to the content **912** corresponding to the shared object **921** to the second application.

(105) Hereinafter, with reference to FIG. **10**, operations of an electronic device according to an embodiment will be described.

(106) FIG. **10** is a diagram **1000** showing operations of an electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. **1**) of the electronic device (e.g., the electronic device **101** in FIG. **1**). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(107) Referring to a first drawing **1010** in FIG. **10**, the electronic device **101** (or the processor **120**) may output an augmented reality space **1011** by executing the augmented reality mode. According to one embodiment, the augmented reality space **1011** may contain a first app object **1012** and a second app object **1014**.

(108) According to one embodiment, the electronic device **101** may identify an interaction of selecting a content to be shared on the first app object **1012**. According to one embodiment, the content may include at least one of a document, a text, an image, and a video displayed on an execution screen of the first app object **1012**. According to one embodiment, the electronic device **101** may form a shared object **1013** that outputs a content of the selected content.

(109) Referring to a second drawing **1020** in FIG. **10**, the electronic device **101** may identify a movement interaction of the shared object **1013** while executing the augmented reality mode. According to one embodiment, the movement interaction of the shared object **1013** may be an operation of touching and dragging the shared object **1013** to drop the shared object **1013** on the second app object **1014**. According to one embodiment, as the interaction of moving the shared object **1013** onto the second app object **1014** corresponding to the second application and dropping the shared object **1013** is received, the electronic device **101** may transmit information (e.g., copy of the content, reference information of the content (an URL of the content, an ID of the content, and the like)) corresponding to a content corresponding to the shared object **1013** to the second application.

(110) Hereinafter, with reference to FIG. **11**, operations of an electronic device according to an embodiment will be described.

(111) FIG. **11** is a flowchart **1100** showing operations of an electronic device according to an embodiment. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. **1**) of the electronic device (e.g., the electronic device **101** in FIG. **1**). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted. Each “processor” herein includes processing circuitry.

(112) Referring to FIG. **11**, in operation **1101**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may identify the interaction for the content sharing. According to one embodiment, the interaction for the content sharing may be the input of selecting the content to be shared in the first application. According to one embodiment, the content may include at least one of the document, the text, the image, and the video. According to one embodiment, the input of selecting the content to be shared may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the corresponding content.

(113) According to one embodiment, the interaction for the content sharing may be identified during the entire screen output of the first application, and may be identified on the first app object for the first application output in the augmented reality space during the execution of the augmented reality mode. In FIG. **11**, a description may be made assuming that the interaction for the content sharing is identified during the entire screen output of the application.

(114) In operation **1102**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may store the selected content in the memory.

(115) In operation **1103**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may form the first shared object representing the content of the selected content. According to one embodiment, the shared object may include the object that may be disposed in the augmented reality space.

(116) In operation **1104**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may form an editing space object for providing a space for editing the content to be shared. According to one embodiment, the editing space object may include an object that may be disposed in the augmented reality space. According to one embodiment, the user may move the content onto the editing space object and edit the content on the editing space object.

(117) In operation **1105**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may fix the first application being output in the entire screen in the augmented reality space and execute the augmented reality mode. According to one embodiment, fixing the first

application in the augmented reality space may include outputting the first app object corresponding to the first application at the specific location in the augmented reality space and terminating the entire screen output of the first application. According to one embodiment, the operation of fixing the first application in the augmented reality space may be performed by the process of the flowchart **200** in FIG. **2**.

(118) In operation **1106**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may identify an input of moving the first shared object onto the editing space object while the augmented reality mode is being executed. According to one embodiment, the electronic device may identify an operation of touching and dragging the first shared object to drop the first shared object on the editing space object. According to one embodiment, as the input of moving the first shared object onto the editing space object is identified during the execution of the augmented reality mode, the electronic device may temporarily store a copy of the content corresponding to the first shared object in the editing space object. In addition, the electronic device may output the copy of the content stored in the editing space object on the editing space object so as to be edited by the user.

(119) In operation **1107**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may identify an input of the user of editing the copy of the content displayed on the editing space object. According to one embodiment, the editing may include copying, cutting, pasting, and/or pasting with another content of the content.

(120) In operation **1108**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may form a second shared object representing a content of the edited content. According to one embodiment, the electronic device may form the second shared object as an input, by the user, of selecting the edited content is received via touch, long press, tap, double tap, and the like.

(121) In operation **1109**, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may identify the movement interaction of the second shared object. According to one embodiment, the movement interaction of the shared object may include an input of moving the shared object via operations such as touch, drag, swipe, press, and the like. According to one embodiment, the movement interaction of the shared object may be the operation of touching and dragging the shared object to drop the shared object on another app object. According to one embodiment, the electronic device may identify an operation of touching and dragging the second shared object to drop the second shared object on the second app object corresponding to the second application.

(122) In operation **1110**, as the interaction of moving the second shared object onto the second app object corresponding to the second application is received, the electronic device (e.g., the electronic device **101** or the processor **120** in FIG. **1**) may transmit the edited content corresponding to the second shared object to the second application.

(123) Hereinafter, with reference to FIGS. **12** and **13**, operations of an electronic device according to an embodiment will be described.

(124) FIG. **12** is a diagram **1200** showing operations of an electronic device according to an embodiment in order. FIG. **13** is a diagram **1300** showing operations of an electronic device subsequent to operations in FIG. **12** of the electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. **1**) of the electronic device (e.g., the electronic device **101** in FIG. **1**). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(125) Referring to a first drawing **1210** in FIG. **12**, the electronic device **101** (or the processor **120**) may output a first application **1211** stored in the memory (e.g., the memory **130** in FIG. **1**) of the electronic device **101** in the entire screen of the display device (e.g., the display device **160** in FIG. **1**) of the electronic device **101**.

(126) According to one embodiment, the electronic device **101** may identify an interaction of

selecting a first content **1212** to be shared on the execution screen of the first application **1211**. According to one embodiment, the first content **1212** may contain at least one of a document, a text, an image, and a video displayed on the execution screen of the first application **1211**.

According to one embodiment, the input of selecting the first content **1212** to be shared may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the corresponding content. According to one embodiment, the electronic device **101** may store the selected content in the memory.

(127) Referring to a second drawing **220** in FIG. **12**, the electronic device **101** may form a first shared object **1222** representing the selected first content **1212**. According to one embodiment, the first shared object **1222** may include an object that may be disposed in an augmented reality space **1230**. According to one embodiment, the first shared object **1222** may output a content of the selected first content **1212**.

(128) According to one embodiment, the electronic device **101** may fix the first application **1211** being output in the entire screen according to the flowchart **200** in FIG. **2** in the augmented reality space **1230** and execute the augmented reality mode. According to one embodiment, fixing the first application **1211** in the augmented reality space **1230** may include outputting a first app object **1221** corresponding to the first application **1211** at a specific location in the augmented reality space **1230** and terminating the entire screen output of the first application **1211**. According to one embodiment, the augmented reality space **1230** may contain a second app object **1224** for the second application and a third app object **1227** for the third application stored in the memory of the electronic device **101**.

(129) According to one embodiment, the electronic device **101** may form an editing space object **1223** for providing a space for editing the content to be shared. According to one embodiment, the editing space object **1223** may include an object that may be disposed in the augmented reality space **1230**.

(130) According to one embodiment, the user may move the content on the editing space object **1223** and edit the content on the editing space object. According to one embodiment, as the input of moving the shared object onto the editing space object is identified during the execution of the augmented reality mode, the electronic device may temporarily store the copy of the content corresponding to the shared object in the editing space object. In addition, the electronic device may output the copy of the content stored in the editing space object on the editing space object so as to be edited by the user. According to one embodiment, the electronic device **101** may output a second copy **1226** of a second content **1225** of the second app object **1224** stored in the editing space object **1223** on the editing space object **1223**.

(131) Referring to a third drawing **1230** in FIG. **12**, the electronic device **101** may identify a movement interaction of the first shared object **1222** while the augmented reality mode is being executed. According to one embodiment, the movement interaction of the first shared object **1222** may include an input of moving the first shared object **1222** via operations such as touch, drag, swipe, press, and the like. According to one embodiment, the movement interaction of the first shared object **1222** may be an operation of touching and dragging the first shared object **1222** to drop the first shared object **1222** on the object **1224**. According to one embodiment, the movement interaction of the first shared object **1222** may include the movement of the electronic device **101** itself.

(132) Referring to a fourth drawing **1240** in FIG. **12**, as the interaction of moving and dropping the first shared object **1222** onto the editing space object **1223** is received, the electronic device **101** may transmit a first copy **1228** of the first content **1212** corresponding to the first shared object **1222** to the editing space object **1223**. According to one embodiment, as the input of moving the first shared object **1222** onto the editing space object **1223** is identified during the execution of the augmented reality mode, the electronic device **101** may temporarily store the first copy **1228** of the first content **1212** corresponding to the first shared object **1222** in the editing space object **1223**. In

addition, the electronic device **101** may output the first copy **1228** of the first content **1212** stored in the editing space object **1223** on the editing space object **1223** so as to be edited by the user.

(133) Referring to a fifth drawing **1310** in FIG. **13**, the electronic device **101** may form a second shared object **1311** representing a content of an edited content **1226**.

(134) According to one embodiment, the electronic device **101** may identify an input of the user of editing the first copy **1228** of the first content **1212** and the second copy **1226** of the second content **1225** displayed on the editing space object **1223**. According to one embodiment, the editing may include the copying, the cutting, the pasting, or the pasting with another content of the content. According to one embodiment, the electronic device **101** may connect the first copy **1228** of the first content **1212** and the second copy **1226** of the second content **1225** displayed on the editing space object **1223** to each other to form the edited content **1311**.

(135) According to one embodiment, as an input, by the user, of selecting the edited content **1311** via touch, long press, tap, double tap, and the like is received, the electronic device **101** may form the second shared object **1311** representing a content of the edited content **1311**.

(136) Referring to a sixth drawing **1320** in FIG. **13**, the electronic device **101** may identify a movement interaction of the second shared object **1311**. According to one embodiment, the movement interaction of the second shared object **1311** may be an operation of touching and dragging the second shared object **1311** to drop the second shared object **1311** on the third app object **1227** corresponding to the third application. According to one embodiment, the movement interaction of the second shared object **1311** may include the movement of the electronic device **101** itself.

(137) Referring to a seventh drawing **1330** in FIG. **13**, as the interaction of moving the second shared object **1311** onto the third app object **1227** corresponding to the third application is received, the electronic device **101** may transmit a copy **1332** of the edited content **1226** corresponding to the second shared object **1311** to the second application.

(138) Hereinafter, with reference to FIG. **14**, operations of an electronic device according to an embodiment will be described.

(139) FIG. **14** is a diagram **1400** showing operations of an electronic device according to an embodiment in order. Operations of the electronic device to be described below may be performed by the processor (e.g., the processor **120** in FIG. **1**) of the electronic device (e.g., the electronic device **101** in FIG. **1**). The same component as that in the above-described embodiment may be referred to by the same reference number, and the description of the same content may be omitted.

(140) Referring to a first drawing **1410** in FIG. **14**, the electronic device **101** (or the processor **120**) may execute the augmented reality mode to output an augmented reality space **1420** on the display device (e.g., the display device **160** in FIG. **1**) of the electronic device **101**. According to one embodiment, the augmented reality space **1420** may contain a first app object **1411** corresponding to the first application stored in the memory (e.g., the memory **130** in FIG. **1**) of the electronic device **101**, a second app object **1415** corresponding to the second application, a third app object **1432** corresponding to the third application, and a fourth app object **1435** corresponding to the fourth application. In addition, according to one embodiment, the augmented reality space **1420** may contain an editing space object **1413** for providing a space for editing the content.

(141) According to one embodiment, the electronic device **101** may identify an interaction of selecting a first content **1412** to be shared on the first app object **1411**. According to one embodiment, the content may include at least one of the document, the text, the image, and the video contained in the application. According to one embodiment, the input of selecting the content to be shared may be one of operations of touch, tap, double tap, triple tap, swipe, double swipe, pinch, spread, rotation, scroll, long press, short press, and drag for the corresponding content.

(142) According to one embodiment, the electronic device **101** may form a first shared object representing the selected first content **1412**, and may receive an input of moving the first shared object onto the editing space object **1413**. According to one embodiment, as the input of moving

the first shared object onto the editing space object **1413** is received, the electronic device **101** may store a first copy **1414** of the first content **1412** in the editing space object **1413**, and output the first copy **1414** on the editing space object **1413**.

(143) Referring to a second drawing **1420** in FIG. **14**, the electronic device **101** may identify an interaction of selecting a second content **1416** to be shared on the second app object **1415**.

According to one embodiment, the electronic device **101** may form a second shared object representing the selected second content **1416**, and receive an input of moving the second shared object onto the editing space object **1413**. According to one embodiment, as the input of moving the second shared object onto the editing space object **1413** is received, the electronic device **101** may store a second copy **1417** of the second content **1416** in the editing space object **1413**, and output the second copy **1417** on the editing space object **1413**.

(144) Referring to a third drawing **1430** in FIG. **14**, the electronic device **101** may identify an input of the user of editing the first copy **1414** and the second copy **1417** output on the editing space object **1413**. According to one embodiment, the editing may include the copying, the cutting, the pasting, or the pasting with another content of the content. According to one embodiment, as the input, by the user, of selecting the edited content via touch, long press, tap, double tap, and the like is received, the electronic device **101** may form a third shared object **1433** representing a content of the edited content.

(145) According to one embodiment, the electronic device **101** may identify an input of moving the third shared object **1433** onto the third app object **1432**. According to one embodiment, as the input of moving the third shared object **1433** onto the third app object **1432** is identified, the electronic device **101** may transmit the edited content corresponding to the third shared object **1433** to the third application.

(146) In FIG. **14**, the editing space object **1413** is shown in an arbitrary shape, but, according to one embodiment, the editing space object may be in a shape that reproduces an object existing in the real space. In addition, according to one embodiment, when a user of an electronic device other than the electronic device **101** recognizes the object existing in the real space with the camera module while executing the augmented reality mode, the user may access and download the first copy **1414** and the second copy **1417** stored in the editing space object.

(147) An electronic device according to an example embodiment includes a camera module, a processor operatively connected (directly or indirectly) to the camera module, and a memory operatively coupled to the processor, and the memory stores instructions that, when executed, cause the processor to identify a first interaction for a first application being executed, form a first app object of outputting an execution screen of the first application as the first interaction is identified, output an augmented reality space based on a real space recognized via the camera module, and output the first app object in the augmented reality space.

(148) According to an example embodiment, the instructions may cause the processor to output the first app object at a location in the augmented reality space corresponding to a location of the electronic device in the real space at a time point when the first interaction has occurred.

(149) According to an example embodiment, the first interaction may include an operation of moving the electronic device to a specific location in the real space.

(150) According to an example embodiment, an entire screen of the first application may be terminated before or at the same time when the augmented reality space is output, and the entire screen of the first application may be output as a second interaction of moving the electronic device to the location of the first app object is identified.

(151) According to an example embodiment, the instructions may cause the processor to form a first shared object representing a selected content as an input of selecting a content contained in the first application is received.

(152) According to an example embodiment, the instructions may cause the processor to transmit information corresponding to the selected content to the second application when a third interaction

of moving the first shared object to the second app object is received.

(153) According to an example embodiment, the instructions may cause the processor to form an editing space object for content editing in the augmented reality space.

(154) According to an example embodiment, the instructions may cause the processor to form a first shared object representing a selected content as an input of selecting a content contained in the first application is received, and store a copy of the selected content in the editing space object as a third interaction of moving the first shared object to the editing space object is received.

(155) According to an example embodiment, the instructions may cause the processor to identify an input of forming an edited content by editing the copy in the editing space object.

(156) According to an example embodiment, the instructions may cause the processor to form a second shared object representing the edited content as an input of selecting the edited content is received, and transmit the edited content to the second application as a fourth interaction of moving the second shared object to the second app object is received.

(157) An operation method of an electronic device for providing an augmented reality mode according to an example embodiment may include identifying a first interaction for a first application being executed, forming a first app object of outputting an execution screen of the first application as the first interaction is identified, outputting an augmented reality space based on a real space recognized via a camera module, and outputting the first app object in the augmented reality space.

(158) According to an example embodiment, the first app object may be output at a location in the augmented reality space corresponding to a location of the electronic device in the real space at a time point when the first interaction has occurred.

(159) According to an example embodiment, the first interaction may include an operation of moving the electronic device to a specific location in the real space.

(160) According to an example embodiment, an entire screen of the first application may be terminated before or at the same time when the augmented reality space is output, and the entire screen of the first application may be output as a second interaction of moving the electronic device to the location of the first app object in the augmented reality space is identified.

(161) According to an example embodiment, a first shared object representing a selected content may be formed as an input of selecting a content contained in the first application is received.

(162) According to an example embodiment, information corresponding to the selected content may be transmitted to the second application when a third interaction of moving the first shared object to the second app object is received.

(163) According to an example embodiment, an editing space object for content editing may be formed in the augmented reality space.

(164) According to an example embodiment, a first shared object representing a selected content may be formed as an input of selecting a content contained in the first application is received, and a copy of the selected content may be stored in the editing space object as a third interaction of moving the first shared object to the editing space object is received.

(165) According to an example embodiment, an input of forming an edited content by editing the copy in the editing space object may be identified.

(166) According to an example embodiment, a second shared object representing the edited content may be formed as an input of selecting the edited content is received, and the edited content may be transmitted to the second application as a fourth interaction of moving the second shared object to the second app object is received.

(167) An electronic device according to an example embodiment includes a camera module comprising imaging circuitry, a processor operatively connected to the camera module and a memory operatively coupled to the processor, wherein the memory stores instructions that, when executed, are configured to cause the processor to: identify a first interaction in a state of outputting an execution screen of a first application with a first size, control to output an augmented reality

space based on a real space recognized via the camera module as the first interaction is identified, control to output, in the augmented reality space, a first app object of outputting the execution screen of the first application with a second size smaller than the first size and a second app object of outputting an execution screen of a second application different from the first application with the second size and control to output the execution screen of the second application corresponding to the selected second app object as a screen with the first size in response to identification of a second interaction of selecting the second app object. According to an embodiment, the camera module comprises the imaging circuitry and/or a lens.

(168) According to an example embodiment, wherein the instructions are configured to cause the processor to control to output the first app object and the second app object at a location in the augmented reality space corresponding to a location of the electronic device in the real space at a time point when the first interaction has occurred.

(169) According to an example embodiment, wherein the first interaction includes an operation of moving the electronic device to a specific location in the real space.

(170) According to an example embodiment, wherein the instructions and/or processor are configured so that the first app object and the second app object are to be output after terminating the output of the execution screen of the first application with the first size before or at the same time the augmented reality space is output, wherein the instructions and/or processor are configured so that the execution screen of the second application is to be output with the first size as the second interaction of moving the electronic device to a location of the second app object in the augmented reality space is received.

(171) According to an example embodiment, wherein the instructions are configured to cause the processor to control to output the execution screen of the second application as the screen with the first size after terminating the output of the first app object and the second app object in response to the identification of the second interaction.

(172) According to an example embodiment, wherein the instructions are configured to cause the processor to: control to form a first shared object representing a selected content as an input of selecting a content contained in the first application is received and control to transmit information corresponding to the selected content to the second application based on a third interaction of moving the first shared object to the second app object received.

(173) According to an example embodiment, wherein the instructions are configured to cause the processor to: control to form an editing space object for content editing in the augmented reality space and store a copy of the selected content in the editing space object as a fourth interaction of moving the first shared object to the editing space object is received.

(174) According to an example embodiment, wherein the instructions are configured to cause the processor to: identify an input of forming an edited content at least by editing the copy in the editing space object, control to form a second shared object representing the edited content as an input of selecting the edited content is received and control to transmit the edited content to the second application as a fifth interaction of moving the second shared object to the second app object is received.

(175) An operation method of an electronic device for providing an augmented reality mode according to an example embodiment includes identifying a first interaction in a state of outputting an execution screen of a first application with a first size, outputting an augmented reality space based on a real space recognized via a camera module as the first interaction is identified, the camera module comprising imaging circuitry, outputting, in the augmented reality space, a first app object of outputting the execution screen of the first application with a second size smaller than the first size and a second app object of outputting an execution screen of a second application different from the first application with the second size and outputting the execution screen of the second application corresponding to the selected second app object as a screen with the first size in response to identification of a second interaction of selecting the second app object.

(176) According to an example embodiment, the operation method may further comprises, outputting the first app object and the second app object at a location in the augmented reality space corresponding to a location of the electronic device in the real space at a time point when the first interaction has occurred.

(177) According to an example embodiment, wherein the first interaction includes an operation of moving the electronic device to a specific location in the real space.

(178) According to an example embodiment, the operation method may further comprises, outputting the first app object and the second app object after terminating the output of the execution screen of the first application with the first size before or at the same time the augmented reality space is output and outputting the execution screen of the second application with the first size as the second interaction of moving the electronic device to a location of the second app object in the augmented reality space is received.

(179) According to an example embodiment, the operation method may further comprises, forming a first shared object representing a selected content as an input of selecting a content contained in the first application is received and transmitting information corresponding to the selected content to the second application when a third interaction of moving the first shared object to the second app object is received.

(180) According to an example embodiment, the operation method may further comprises, forming an editing space object for content editing in the augmented reality space and storing a copy of the selected content in the editing space object as a fourth interaction of moving the first shared object to the editing space object is received.

(181) According to an example embodiment, the operation method may further comprises, identifying an input of forming an edited content by editing the copy in the editing space object, forming a second shared object representing the edited content as an input of selecting the edited content is received and transmitting the edited content to the second application as a fifth interaction of moving the second shared object to the second app object is received.

(182) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(183) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B, or C”, “at least one of A, B, and C”, and “at least one of A, B, or C” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd”, or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with”, “coupled to”, “connected with”, or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via at least a third element.

(184) As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic”, “logic block”, “part”, or “circuitry”. A module may be a single integral component, or a minimum unit or part

thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(185) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(186) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(187) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. An electronic device comprising: a display; a camera comprising imaging circuitry; a processor operatively connected to the camera; and memory operatively coupled to the processor, wherein the memory stores instructions that, when executed, cause the electronic device to: in response to execution of a first application stored in the electronic device, control to output, through the display, a first execution screen of the first application with a first size; identify a first interaction in a state of outputting the first execution screen of the first application; control to output, through the display, an augmented reality space based on a real space recognized via the camera as the first interaction is identified; control to output a second app object with a second size smaller than the first size, at a location in the augmented reality space corresponding to a location in the real space where a previous interaction to fix the second app object occurred, wherein the second app object corresponds to a second application stored in the electronic device; and in response to identification of a second interaction of selecting the second app object output with the second size by moving

the electronic device to the location in the real space where the second app object is output, control to output, through the display, a second execution screen of the second application with the first size after terminating the output the augmented reality space.

2. The electronic device of claim 1, wherein the instructions cause the electronic device to control to output the second app object at the location in the augmented reality space corresponding to a location of the electronic device in the real space at a time point when the previous interaction has occurred.

3. The electronic device of claim 1, wherein the first interaction includes an operation of moving the electronic device to a specific location in the real space.

4. The electronic device of claim 1, wherein the instructions cause the electronic device to: control to output, in the augmented reality space, a first app object of outputting the first execution screen, with the second size, wherein the first app object corresponds to the first application; in response to identification of a third interaction of selecting a content contained in the first app object output with the second size, control to transmit information corresponding to the selected content to the second application.

5. The electronic device of claim 4, wherein the instructions cause the electronic device to: control to form an editing space object for content editing in the augmented reality space; and store a copy of the selected content in the editing space object as a fourth interaction of moving a first shared object to the editing space object is received.

6. The electronic device of claim 5, wherein the instructions cause the electronic device to: identify an input of forming an edited content at least by editing the copy in the editing space object; control to form a second shared object representing the edited content as an input of selecting the edited content is received; and control to transmit the edited content to the second application as a fifth interaction of moving the second shared object to the second app object is received.

7. An operation method of an electronic device for providing an augmented reality mode, the method comprising: in response to execution of a first application stored in the electronic device, outputting, through a display of the electronic device, a first execution screen of the first application with a first size; identifying a first interaction in a state of outputting the first execution screen of the first application; outputting, through the display, an augmented reality space based on a real space recognized via a camera as the first interaction is identified, the camera comprising imaging circuitry; outputting a second app object with a second size smaller than the first size, at a location in the augmented reality space corresponding to a location in the real space where a previous interaction to fix the second app object occurred, wherein the second app object corresponds to a second application stored in the electronic device; and in response to identification of a second interaction of selecting the second app object output with the second size by moving the electronic device to the location in the real space where the second app object is output, outputting, through the display, a second execution screen of the second application with the first size after terminating the output the augmented reality space.

8. The method of claim 7, further comprising: outputting the second app object at the location in the augmented reality space corresponding to a location of the electronic device in the real space at a time point when the previous interaction has occurred.

9. The method of claim 7, wherein the first interaction includes an operation of moving the electronic device to a specific location in the real space.

10. The method of claim 9, further comprising: outputting, in the augmented reality space, a first app object of outputting the first execution screen, with the second size, wherein the first app object corresponds to the first application; and in response to identification of a third interaction of selecting a content contained in the first app object output with the second size, transmitting information corresponding to the selected content to the second application.

11. The method of claim 10, further comprising: forming an editing space object for content editing in the augmented reality space; and storing a copy of the selected content in the editing space

object as a fourth interaction of moving a first shared object to the editing space object is received.

12. The method of claim 11, further comprising: identifying an input of forming an edited content by editing the copy in the editing space object; forming a second shared object representing the edited content as an input of selecting the edited content is received; and transmitting the edited content to the second application as a fifth interaction of moving the second shared object to the second app object is received.
