

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384016
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lu; Haiyan

Positioner

Abstract

A positioner includes a base, a marking component, and a first mounting component. The marking component includes a marking portion and a connecting portion connected with each other. The marking portion is configured to set a mark onto a mounting surface. The connecting portion is inserted into the base. The first mounting component is detachably connected to the connecting portion. An end of the first mounting component distal from the connecting portion is configured to connect to a mounting object. Each fastening structure on a back surface of the mounting object is fixedly connected to a hanging structure via the first mounting component. A plurality of matching marks are made onto the mounting surface through a plurality of positioners.

Inventors:	Lu; Haiyan (Shenzhen, CN)
Applicant:	Lu; Haiyan (Shenzhen, CN)
Family ID:	88977967
Appl. No.:	18/070592
Filed:	November 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230390916 A1	Dec. 07, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 29864516 20220601 US D982997 child-doc US 18070592

Publication Classification

Int. Cl.: **B25H7/04 (20060101)**

U.S. Cl.:

CPC **B25H7/045** (20130101);

Field of Classification Search

CPC: B25H (7/045)

USPC: 33/574; 33/644; 33/666

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
726086	12/1902	McAlpine	33/574	B25H 7/04
3403623	12/1967	Blackwood	101/368	B41K 1/36
4353759	12/1981	Stallings	156/289	B44C 7/00
4382337	12/1982	Bendick	33/574	A47G 1/205
4473957	12/1983	Faulkner	33/666	B25H 7/04
4512084	12/1984	Lieberman	33/574	A47G 1/205
5233760	12/1992	Patterson	33/376	G01C 9/28
5253421	12/1992	Landmark	33/760	B43L 9/04
5867917	12/1998	Karon	33/666	A47G 1/205
6574880	12/2002	Lombardo	33/666	B25H 7/04
6739065	12/2003	Hofmeister	33/666	A47G 1/205
7293925	12/2006	Sanseviero	401/98	B43K 23/08
7506450	12/2008	Spaulding	248/205.3	G01C 9/26
8869410	12/2013	Callahan	33/514	A61C 7/146
10149559	12/2017	Marks	N/A	A47G 1/205
10518403	12/2018	Weitsman	N/A	B25H 7/045
11291317	12/2021	Weitsman	N/A	B25H 7/045
12263572	12/2024	Conklin	N/A	B25H 7/04
2002/0095812	12/2001	Newman	33/613	B25H 7/04
2004/0216319	12/2003	Muchnik	33/666	B25H 7/045
2006/0196069	12/2005	Groepper	33/613	A47G 1/205
2007/0283588	12/2006	Gardner	33/666	F16B 15/02
2009/0193674	12/2008	Megahed	33/666	A47G 1/205
2014/0166834	12/2013	Kuroyanagi	248/231.91	F16M 13/02

Primary Examiner: Bennett; George B

Attorney, Agent or Firm: HOWARD M COHN and Associates, LLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a technical field of house and home, and in particular to a positioner.

BACKGROUND

(2) Generally, a home decor object, such as a hanging picture, a bathroom mirror, a lamp, a build block board, etc., is provided on its back surface with a fastening structure, such as a screw, a hanging hole, etc. The home decor object is only fixed to a mounting surface such as a wall surface by the fastening structure and a fastening component cooperated with the fastening structure.

(3) Some home decor objects, such as hanging pictures, are relatively large and hung with their back surfaces against the mounting surface. In order to fasten the home decor object, more than two fastening structures are typically disposed on the back surface of the home decor object. In a case where there are more than two fastening structures, it is cumbersome to position these fastening structures since they are disposed on the back surface of the home decor object. After a mounting position is determined on the mounting surface, a user generally needs to measure positions of the fastening structures with respect to the home decor object and a distance between the fastening structures; and then drill holes or attach fastening screws in the mounting surface such as the wall surface. The fastening structures on the back surface of the home decor object are symmetrically arranged at the same level. If there exists a deviation in the distance between the drilled holes, new holes need to be drilled, which influences the appearance of the wall surface. Or, if there exists a deviation in the horizontal heights of the two drilled holes, the home decor object is tilted after installation, thereby diminishing the beauty of the home decor object.

SUMMARY

(4) Embodiments of the present disclosure provide a positioner, which enables no deviation in a hanging structure cooperated with the mounting object, thereby keeping the mounting object straight with no tilt after installation.

(5) An embodiment of the present disclosure provides a positioner, including: a base, a marking component, and a first mounting component.

(6) The marking component includes a marking portion and a connecting portion connected with each other. The marking portion is configured to set a mark onto a mounting surface. The connecting portion is inserted into the base.

(7) The first mounting component is detachably connected to the connecting portion. An end of the first mounting component distal from the connecting portion is configured to connect to a mounting object.

(8) Optionally, a printing-dyeing structure is disposed on the marking portion, and the printing-dyeing structure is configured to print the mark onto the mounting surface.

(9) Optionally, a tip structure is disposed on the marking portion, and the tip structure is configured to drill a positioning hole in the mounting surface to form the mark.

(10) Optionally, the connecting portion is detachably connected to the base, and the connecting portion is configured to be limited to different positions of the base.

(11) Optionally, a thread is disposed on an outer surface of the connecting portion, a first threaded hole is defined on the base, and the connecting portion is threaded to the first threaded hole.

(12) Optionally, a second threaded hole is defined at an end of the connecting portion away from the marking portion, and the first mounting component is threaded to the second threaded hole.

(13) Optionally, the base includes a substrate, a first protruding portion and a second protruding portion. The first protruding portion and the second protruding portion are disposed on a same side of the substrate.

(14) The first protruding portion is of a hollow structure, the first threaded hole is defined in a middle of the first protruding portion, and a first opening corresponding to the first protruding portion is defined on the substrate.

(15) The second protruding portion is of a hollow structure, and a second mounting component is disposed in the second protruding portion. The second mounting component is different from the first mounting component.

(16) Optionally, the base further includes a third protruding portion. The third protruding portion

and the second protruding portion are disposed on a same side of the substrate. the third protruding portion is of a hollow structure, and a third mounting component is disposed in the third protruding portion. The third mounting component, the second mounting component and the first mounting component are different from one another.

(17) Optionally, the second protruding portion and the third protruding portion are disposed on two opposite sides of the first protruding portion. A second opening corresponding to the second protruding portion is defined on the substrate, and a third opening corresponding to the third protruding portion is defined on the substrate. The second mounting component is inserted into the second opening, and the third mounting component is inserted into the third opening.

(18) Optionally, the positioner further includes a cover. The cover covers the marking portion.

(19) In the embodiments of the present disclosure, the first mounting component is detachably connected to the connecting portion of the marking component, and the end of the first mounting component away from the connecting portion is connected to a mounting object (a home decor object such as a hanging picture, a bathroom mirror, a lamp, a building block board, etc.). At least two fastening structures such as hanging holes are disposed on the back surface of the mounting object, and each hanging hole is configured to be sleeved over one first mounting component. The marking component is configured to make a mark onto a mounting surface such as a wall surface. Each fastening structure on the back surface of the mounting object is installed with one positioner, and each positioner is configured to make one mark onto the mounting surface. Then, a hanging structure such as a drilled hanging hole or an attached fastening screw is disposed corresponding to each mark. Each fastening structure on the back surface of the mounting object may be fixedly connected to the hanging structure via the first mounting component. The mounting object is kept straight when hung on the mounting surface. A plurality of matching marks are made on the mounting surface by a plurality of positioners. Thus, a plurality of hanging structures determined according to the plurality of marks are at the same level. Besides, a spacing between the plurality of marks is an actual distance of the plurality of fastening structures on the back surface of the mounting object, and there is no deviation in the spacing between the plurality of marks.

(20) Thus, according to the positioner of the embodiments, the plurality of marks corresponding to the plurality of fastening structures on the back surface of the mounting object are at the same level, and the spacing between any two marks is equal to the spacing between the corresponding fastening structures. Correspondingly, after the hanging structure corresponding to each mark is disposed, the plurality of hanging structures are matched one-by-one to the plurality of fastening structures. There is no deviation in the hanging structures, which avoids the situation where the hanging structures need to be redispersed due to their deviation, thus having no influence on the mounting surface. After the mounting object is hung on the mounting surface through one-by-one connection between the plurality of first mounting components and the plurality of hanging structures, the plurality of hanging structures are at the same level, thereby keeping the mounting object straight with no tilt after installation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to more clearly illustrate technical solutions in embodiments of the present disclosure, a brief description of drawings required for describing the embodiments is given below. The drawings described below are merely some embodiments of the present disclosure. For those skilled in art, other drawings may be obtained without any creative thinking.

(2) For a more complete understanding of the present disclosure and its beneficial effects, the description is made hereinafter with reference to the accompanying drawings. In the following description, identical reference numerals indicate identical portions.

- (3) FIG. 1 is a structural schematic diagram of a positioner according to one embodiment of the present disclosure.
- (4) FIG. 2 is a structural schematic diagram of a marking component in the positioner as shown in FIG. 1.
- (5) FIG. 3 is a structural schematic diagram of the positioner and a mounting object according to one embodiment of the present disclosure.
- (6) FIG. 4 is a structural schematic diagram of the mounting object and a mounting surface according to one embodiment of the present disclosure.
- (7) FIG. 5 is a structural schematic diagram of a fastening structure of the mounting object as shown in FIG. 4.
- (8) FIG. 6 is another structural schematic diagram of the fastening structure of the mounting object as shown in FIG. 4.
- (9) FIG. 7 is another structural schematic diagram of the positioner according to one embodiment of the present disclosure.
- (10) FIG. 8 is a structural schematic diagram of the marking component in the positioner as shown in FIG. 7.
- (11) FIG. 9 is still another structural schematic diagram of the positioner according to one embodiment of the present disclosure.
- (12) FIG. 10 is an exploded schematic diagram of the positioner as shown in FIG. 9.
- (13) FIG. 11 is another exploded schematic diagram of the positioner as shown in FIG. 9.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (14) Technical solutions in embodiments of the present disclosure are clearly and completely described below with reference to accompanying drawings in the embodiments of the present disclosure. Obviously, the embodiments described herein are merely a portion of embodiments of the present disclosure, not all of them. Based on the embodiments of the present disclosure, all other embodiments obtained by those skilled in art without creative thinking fall within a scope of protection of the present disclosure.
- (15) The embodiments of the present disclosure provide a positioner. FIG. 1 is a schematic structural diagram of a positioner according to an embodiment of the present disclosure, and FIG. 2 is a schematic structural diagram of a marking component in the positioner as shown in FIG. 1. The positioner 10 includes a base 12, a marking component 14, and a first mounting component 16. The base 12 is configured as a load-bearing structure for the positioner 10. The marking component 14 includes a marking portion 142 and a connecting portion 144 connected to each other. FIG. 3 is a schematic structural diagram of a positioner and a mounting object according to an embodiment of the present disclosure. FIG. 4 is a schematic structural diagram of a mounting object and a mounting surface according to an embodiment of the present disclosure. The marking portion 142 is configured to set a mark onto a mounting surface 30, and the connecting portion 144 is inserted into the base 12. The first mounting component 16 is detachably connected to the connecting portion 144. An end of the first mounting component 16 away from the connecting portion 144 is configured to connect to a mounting object 20 (a home decor object such as a hanging picture, a bathroom mirror, a lamp, a building block board, etc.).
- (16) FIG. 5 is a structural schematic diagram of the fastening structure of the mounting object as shown in FIG. 4, and FIG. 6 is another structural schematic diagram of the fastening structure of the mounting object as shown in FIG. 4. At least two fastening structures 22 may be disposed on a back surface of the mounting object 20. The fastening structures 22 are defined with hanging holes 23, each of which is sleeved over one first mounting component 16. The marking component 14 is configured to make the mark onto the mounting surface 30 such as the wall surface. In this way, each fastening structure 22 on the back surface of the mounting object 20 is installed with one positioner 10, and each positioner 10 is configured to make one mark onto the mounting surface 30. Then, a hanging structure (not shown in the drawings), such as a drilled hanging hole or an

attached fastening screw, is disposed corresponding to each mark. Each fastening structure **22** on the back surface of the mounting object **20** may be fixedly connected to the hanging structure via the first mounting component **16**. The mounting object **20** is kept straight when hung on the mounting surface **30**. A plurality of matching marks may be set onto the mounting surface **30** using a plurality of positioners **10**. Thus, a plurality of hanging structures determined according to the plurality of marks are at the same level. In addition, a spacing between the plurality of marks is an actual distance of the plurality of fastening structures **22** on the back surface of the mounting object **20**. There is no deviation in the spacing between the plurality of marks.

(17) Thus, using the positioner **10** according to the embodiments, the plurality of marks corresponding to the plurality of fastening structures **22** on the back surface of the mounting object **20** are at the same level, and the spacing between any two marks is equal to the spacing between the corresponding fastening structures **22**. Correspondingly, after the hanging structure is disposed corresponding to each mark, the plurality of hanging structures are matched one-by-one to the plurality of fastening structures **22**. There is no deviation in the hanging structures, which avoids the situation where the hanging structures need to be redispersed due to their deviation, thus having no influence on the mounting surface **30**. After the mounting object **20** is hung on the mounting surface **30** through one-by-one connection between the plurality of hanging structures and the plurality of first mounting components **16**, the plurality of hanging structures are at the same level, thereby keeping the mounting object **20** straight with no tilt after installation.

(18) Optionally, a printing-dyeing structure **142a** is disposed at the marking portion **142**. The printing-dyeing structure **142a** is configured to print the mark onto the mounting surface. Exemplarily, the printing-dyeing structure **142a** of the marking portion **142** has a function similar to a seal. When an external thrust is applied to the printing-dyeing structure **142a** and presses it against the mounting surface, the printing-dyeing structure **142a** is configured to make the mark onto the mounting surface such as the wall surface. A material that is reused many times may be stored in the printing-dyeing structure **142a**, so that there is no need to replace the printing-dyeing structure **142a** or supplement the material for printing-dyeing each time, which is convenient to use. A shape of the mark may be set as required. For example, the mark may be a combination of one or more of a solid circle, a circular ring, a cross, and an X shape. Accordingly, the printing-dyeing structure **142a** having the corresponding shape is disposed, so as to print the mark. A color of the mark may be set as required. For example, the mark may be a combination of one or more of red, blue, green, black, purple, etc.

(19) FIG. 7 is another schematic structural diagram of a positioner according to an embodiment of the present disclosure, and FIG. 8 is a schematic structural diagram of a marking component in the positioner as shown in FIG. 7. Optionally, a tip structure **142b** may be disposed at the marking portion **142**. The tip structure **142b** is configured to drill a positioning hole in the mounting surface, so as to form the mark. Exemplarily, the tip structure **142b** of the marking portion **142** may have a conical structure or other structure with a tip. When an external thrust is applied to the tip structure **142b** and presses it against the mounting surface, the tip structure **142b** is configured to drill a positioning hole such as a round concave point in the mounting surface such as the wall surface, and the positioning hole forms the mark. There is no color but only one positioning hole left on the mounting surface. Subsequently, the positioning hole is processed to form the hanging structure such as the hanging hole that matches the fastening structure on the back surface of the mounting object.

(20) FIG. 9 is still another schematic structural diagram of a positioner according to an embodiment of the present disclosure. FIG. 10 is a schematic exploded diagram of the positioner as shown in FIG. 9. FIG. 11 is another schematic exploded diagram of the positioner as shown in FIG. 9. The positioner **10** further includes a cover **19**, which covers the marking portion **142** and plays a role of protecting the marking portion **142**. The cover **19** may cover only the marking portion **142**, or cover the marking portion **142** and the first protruding portion **124**. The cover **19** may be in

snap-fit with the marking portion **142**, so as to improve connection stability therebetween. In some embodiments, structures cooperated with each other may be disposed on the cover **19** and the marking portion **142**. For example, a magnetic component may be respectively disposed on the cover **19** and the marking portion **142**, so that magnetic connection is realized between the cover **19** and the marking portion **142** through two magnetic components.

(21) In some embodiments, a convex rib **1422** is disposed on an outer side of the marking portion **142**, and an opening groove **191** is defined on the cover **19** corresponding to the convex rib **1422**. The convex rib **1422** is disposed in the opening groove **191**, and the convex rib **1422** is in interference fit with the opening groove **191**. As such, the cover **19** is in snap-fit with the marking portion **142**, which strengthens connection strength between the cover **19** and the marking portion **142**, thereby solving the problem that the cover **19** easily falls off. Optionally, a quantity of convex ribs **1422** may be set as required. For example, two convex ribs **1422** are disposed on the outer side of the marking portion **142**, and are symmetrically arranged on two sides of the marking portion **142**. In addition, two opening grooves **191** are defined on the cover **19** corresponding to the two convex ribs **1422**. The two opening grooves **191** are in one-to-one correspondence with the two convex ribs **1422**. For another example, three convex ribs **1422** are disposed on the outer side of the marking portion **142**, and are evenly disposed around an outer periphery of the marking portion **142**. In addition, three opening grooves **191** are defined on the cover **19** corresponding to the three convex ribs **1422**. The three opening grooves **191** are in one-to-one correspondence with the three convex ribs **1422**.

(22) The convex rib **1422** may extend along an end of the marking portion **142** away from the connecting portion **144** toward the connecting portion **144**. The convex rib **1422** may extend to the connecting portion **144**. Alternatively, the convex rib **1422** may extend to a middle of the marking portion **142**, with a certain distance spaced apart from the connecting portion **144**. A length of the convex rib **1422** may be set as required, which is not limited herein.

(23) The connecting portion **144** is detachably connected to the base **12**, and the connecting portion **144** is configured to be limited to different positions of the base **12**. The connecting portion **144** may be separated from the base **12**, and it may also be disposed at different positions of the base **12**, so that a distance between the connecting portion **144** and the mounting object is adjustable. That is, a distance between the mounting object and the marking portion **142** is adjustable. In this way, the distance between the marking portion **142** and the mounting object is closer to the distance between the first mounting component **16** and the mounting object.

(24) Specifically, a thread is disposed on an outer surface of the connecting portion **144**, and a first threaded hole **121** is defined on the base **12**, so that the connecting portion **144** is threaded to the first threaded hole **121**. Through the threaded connection, the connection between the connecting portion **144** and the first threaded hole **121** of the base **12** is realized, and also a relative position between the connecting portion **144** and the base **12** is adjustable; that is, the distance between the connecting portion **144** and the mounting object is adjustable.

(25) Optionally, a second threaded hole **1461** is defined at an end of the connecting portion **144** away from the marking portion **142**, and the first mounting component **16** is threaded to the second threaded hole **1461**. The first mounting component **16** is threaded to the connecting portion **144**, so as to realize connection between the first mounting component **16** and the connecting portion **144**. The first mounting component **16** may be a screw or a nut. An end of the first mounting component **16** is in snap-fit with the fastening structure on the back surface of the mounting object, and the other end of the first mounting component **16** is in threaded connection with the connecting portion **144**, which may be understood as similar to installation in the hanging structure of the mounting surface.

(26) In some embodiments, the connecting portion **144** and the marking portion **142** may be an integral structure, or may be split structures. The connecting portion **144** and the marking portion **142** are fixedly connected, such as by threading, welding, snap-fit, bonding, etc.

(27) It is appreciated that second threaded holes **1461** of different sizes may be defined on the connecting portion **144** as required. In some other embodiments, a plurality of connecting portions **144** of different specifications may be disposed on the positioner **10** as required. Each time the positioner **10** is used, a connecting portion is selected from the connecting portion **144** of different specifications according to the fastening structure on the back surface of the mounting object. Second threaded holes **1461** of different sizes are defined on the connecting portions **144** of different specifications. The second threaded holes **1461** of different sizes correspond to first mounting components **16** of different specifications.

(28) The base **12** includes a substrate **122**, a first protruding portion **124** and a second protruding portion **126**. The first protruding portion **124** and the second protruding portion **126** are arranged on the same side of the substrate **122**. The first protruding portion **124** is of a hollow structure, and the first threaded hole **121** is defined in a middle of the first protruding portion **124**. A first opening corresponding to the first protruding portion **124** is defined on the substrate **122**. The second protruding portion **126** is of a hollow structure, and a second mounting component **17** is disposed in the second protruding portion **126**. The second mounting component **17** is different from the first mounting component **16**.

(29) The first protruding portion **124** is configured to accommodate the connecting portion **144**, and the second protruding portion **126** is configured to accommodate the second mounting component **17**. The second mounting component **17** and the first mounting component **16** are of different types. The second mounting component **17** may be adapted to a mounting object with other fastening structure, or may be adapted to a mounting object in other mounting mode.

(30) In some embodiments, the second mounting component **17** may be threaded into the second protruding portion **126**. In some other embodiments, the second mounting component **17** may be snapped in the second protruding portion **126**. For example, the second protruding portion **126** has a certain elasticity, an inner size of the second protruding portion **126** is slightly smaller than a size of the second mounting component **17**, and the second mounting component **17** is in interference fit with the second protruding portion **126**. As such, the second mounting component **17** may be determined from a wider selection range.

(31) In some embodiments, the base **12** further includes a third protruding portion **128**. The third protruding portion **128** and the second protruding portion **126** are arranged on the same side of the substrate **122**, which is convenient to arrange the three protruding portions. The third protruding portion **128** is of a hollow structure, and a third mounting component **18** is disposed in the third protruding portion **128**. The third mounting component **18**, the second mounting component **17** and the first mounting component **16** are different from one another. The third mounting component **18**, the second mounting component **17** and the first mounting component **16** may be of different types. The three mounting components may be adapted to mounting objects with three types of fastening structures, or may be adapted to mounting objects in three different mounting modes, thereby widening an application range of the positioner **10**.

(32) Exemplarily, in a case that the mounting object has been selected, and the fastening structure on the back surface of the mounting object has been disposed, one of three mounting components in the connecting portion **144**, the second protruding portion **126** and the third protruding portion **128** of the positioner **10** may be selected as the first mounting component **16** according to the fastening structure on the back surface of the mounting object. The selected first mounting component is connected to the connecting portion **144**, and is cooperated with the fastening structure, so as to realize positioning of the fastening structure corresponding to the mounting object on the mounting surface. For example, the first mounting component **16** as shown in FIG. 5 is cooperated with the fastening structure **22** as shown in FIG. 5. For another example, the first mounting component **16** as shown in FIG. 11 is cooperated with the fastening structure **22** as shown in FIG. 6.

(33) In some embodiments, the third mounting component **18** may be threaded into the third

protruding portion **128**. In some other embodiments, the third mounting component **18** may be snapped in the third protruding portion **128**. For example, the third protruding portion **128** has a certain elasticity, an inner size of the third protruding portion **128** is slightly smaller than a size of the third mounting component **18**, and the third mounting component **18** is in interference fit with the third protruding portion **128**. As such, the third mounting component **18** may be determined from a wider selection range.

(34) The second protruding portion **126** and the third protruding portion **128** are arranged on two opposite sides of the first protruding portion **124**, making the overall appearance more symmetrical and beautiful. A second opening corresponding to the second protruding portion **126** is defined on the substrate **122**, and a third opening corresponding to the third protruding portion **128** is defined on the substrate **122**. The second mounting component **17** is inserted into the second opening, and the third mounting component **18** is inserted into the third opening. The second opening of the second protruding portion **126** and the third opening of the third protruding portion **128** face the same side, namely the side where the mounting object is located, and also the same side as the arrangement direction of the first mounting component **16**, thereby being convenient to place the first mounting component **16**, the second mounting component **17** and the third mounting component **18**.

(35) It should be noted that, in some other embodiments, the opening of the second protruding portion **126** and the opening of the third protruding portion **128** may be defined at a side away from the mounting object. That is, no opening is defined on the base **12** corresponding to the second protruding portion **126** and the third protruding portion **128**. The second mounting component **17** and the third mounting component **18** are installed into the second protruding portion **126** and the third protruding portion **128** from a side away from the mounting object. In still other embodiments, the opening of the second protruding portion **126** and the opening of the third protruding portion **128** may be defined on different sides. For example, one is defined on a side facing the mounting object, and the other one is defined on a side away from the mounting object.

(36) The first protruding portion **124**, the second protruding portion **126** and the third protruding portion **128** may be arranged at intervals from one another, or may be arranged adjacent to one another. For example, the second protruding portion **126** and the third protruding portion **128** are arranged on two sides of the first protruding portion **124** and are both connected to the first protruding portion **124**, which enhances the structural strength of the second protruding portion **126** and the third protruding portion **128**, thereby preventing them from breaking easily. The first protruding portion **124**, the second protruding portion **126** and the third protruding portion **128** may be integrally formed with the substrate.

(37) The positioner provided in the embodiments of the present disclosure is detailed above. Herein, specific examples are used to explain the principle and implementation of the present disclosure. The foregoing embodiments are merely used to help understand the technical solution of the present disclosure and its core idea. In addition, for those skilled in the art, according to the idea of the present disclosure, there will be changes in the specific implementation and application. In summary, the content described herein should not be interpreted as a limitation on the present disclosure.

Claims

1. A positioner, comprising: a base; a marking component; and a first mounting component; wherein the marking component comprises a marking portion and a connecting portion, the marking portion is connected with the connecting portion, the marking portion is configured to set a mark onto a mounting surface, and the connecting portion is inserted into the base; and the first mounting component is detachably connected to the connecting portion, an end of the first mounting component distal from the connecting portion is configured to connect to a mounting

object.

2. The positioner according to claim 1, wherein a printing-dyeing structure is disposed on the marking portion, and the printing-dyeing structure is capable of printing the mark onto the mounting surface.
 3. The positioner according to claim 1, wherein a tip structure is disposed on the marking portion, and the tip structure is capable of drilling a positioning hole in the mounting surface to form the mark.
 4. The positioner according to claim 1, wherein the connecting portion is detachably connected to the base, and the connecting portion is capable of being limited to different positions of the base.
 5. The positioner according to claim 4, wherein a thread is disposed on an outer surface of the connecting portion, a first threaded hole is defined on the base, and the connecting portion is threaded to the first threaded hole.
 6. The positioner according to claim 5, wherein the base comprises: a substrate; a first protruding portion; and a second protruding portion; wherein the first protruding portion and the second protruding portion are disposed on a same side of the substrate; the first protruding portion is of a hollow structure, the first threaded hole is defined in a middle of the first protruding portion, and a first opening corresponding to the first protruding portion is defined on the substrate; the second protruding portion is of a hollow structure, and a second mounting component is disposed in the second protruding portion; and the second mounting component is different from the first mounting component.
 7. The positioner according to claim 6, wherein the base further comprises a third protruding portion; the third protruding portion and the second protruding portion are disposed on a same side of the substrate; the third protruding portion is of a hollow structure, and a third mounting component is disposed in the third protruding portion; and the third mounting component, the second mounting component and the first mounting component are different from one another.
 8. The positioner according to claim 7, wherein the second protruding portion and the third protruding portion are disposed on two opposite sides of the first protruding portion: a second opening corresponding to the second protruding portion is defined on the substrate, and a third opening corresponding to the third protruding portion is defined on the substrate; and the second mounting component is inserted into the second opening, and the third mounting component is inserted into the third opening.
 9. The positioner according to claim 4, wherein a second threaded hole is defined at an end of the connecting portion away from the marking portion, and the first mounting component is threaded to the second threaded hole.
 10. The positioner according to claim 1, wherein the positioner further comprises a cover; and the cover covers the marking portion.
-