

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384045
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Cai; Wayne et al.

Supplemental and targeted heating of vehicle body-in-white interior components/areas for paint ovens

Abstract

A heating system includes a conveying system configured to transport a plurality of vehicle body-in-whites (BIWs) sequentially through an oven room to cure paint applied in a paint room. A preheating system includes one or more robot arms. A heat source is connected to the one or more robot arms. A controller is configured to control the one or more robot arms based on a position of one of the vehicle BIWs on the conveying system and to position the heat source near or in direct contact with one or more inner components of the one of the vehicle BIWs to heat the one or more inner components prior to the one of the vehicle BIWs entering the oven room.

Inventors: Cai; Wayne (Troy, MI), Fan; Hua-Tzu (Troy, MI), Carlson; Blair E. (Ann Arbor, MI), Bracey; Jennifer Therese (Holly, MI), Baylis; Mark E. (Howell, MI), McLean; Kenneth W. (Commerce Township, MI), Bondy; Matthew (Windsor, CA), McLoughlin; Ian (Bloomfield Hills, MI)

Applicant: GM GLOBAL TECHNOLOGY OPERATIONS LLC (Detroit, MI)

Family ID: 88977974

Assignee: GM GLOBAL TECHNOLOGY OPERATIONS LLC (Detroit, MI)

Appl. No.: 17/832914

Filed: June 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230390938 A1	Dec. 07, 2023

Publication Classification

Int. Cl.: B25J11/00 (20060101); B62D65/00 (20060101); H05B6/10 (20060101)

U.S. Cl.:

CPC **B25J11/0075** (20130101); **B62D65/00** (20130101); **H05B6/10** (20130101);

Field of Classification Search

CPC: B25J (11/0075); B25J (11/00); B62D (65/00); B62D (25/04); H05B (6/10); H05B (2203/032); H05B (6/101); H05B (1/023)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5115758	12/1991	Suzuki	118/621	B05D 1/002
8287966	12/2011	Sundarraaj et al.	N/A	N/A
8317253	12/2011	Sachdev et al.	N/A	N/A
8327910	12/2011	Walker et al.	N/A	N/A
8361251	12/2012	Luo et al.	N/A	N/A
8454078	12/2012	Sachdev et al.	N/A	N/A
8708425	12/2013	Carlson et al.	N/A	N/A
8852359	12/2013	Walker et al.	N/A	N/A
8889226	12/2013	Walker et al.	N/A	N/A
8992696	12/2014	Walker et al.	N/A	N/A
9358608	12/2015	Carlson et al.	N/A	N/A
9555694	12/2016	O'Kane et al.	N/A	N/A
9771635	12/2016	Wang et al.	N/A	N/A
11359269	12/2021	Morales et al.	N/A	N/A
2003/0121906	12/2002	Abbott	219/543	H05B 3/12
2008/0099040	12/2007	Bahng	134/21	H01L 21/02057
2010/0227082	12/2009	Fan	427/532	B05D 3/0263
2011/0286880	12/2010	Luo et al.	N/A	N/A
2019/0136401	12/2018	Maddela	N/A	C25D 13/02
2021/0046643	12/2020	Kegasa	N/A	B25J 9/1666
2022/0039278	12/2021	Golm et al.	N/A	N/A
2023/0060932	12/2022	Willden	N/A	B29D 99/0003

OTHER PUBLICATIONS

U.S. Appl. No. 17/323,041, filed May 18, 2021, Bobel et al. cited by applicant

U.S. Appl. No. 17/388,799, filed Jul. 29, 2021, Bobel et al. cited by applicant

U.S. Appl. No. 17/500,641, filed Oct. 13, 2021, Bobel et al. cited by applicant

U.S. Appl. No. 17/679,254, filed Feb. 24, 2022, Sachdev et al. cited by applicant

U.S. Appl. No. 17/735,228, filed May 3, 2022, Morales et al. cited by applicant

Primary Examiner: Holly; Lee A

Background/Summary

INTRODUCTION

- (1) The information provided in this section is for the purpose of generally presenting the context of the disclosure. Work of the presently named inventors, to the extent it is described in this section, as well as aspects of the description that may not otherwise qualify as prior art at the time of filing, are neither expressly nor impliedly admitted as prior art against the present disclosure.
- (2) The present disclosure relates to painting of vehicles, and more particularly to supplemental and targeted heating of vehicle components during curing of a vehicle body-in-white (BIW) after painting.
- (3) During manufacturing, a vehicle body-in-white (BIW) is typically painted prior to assembly of other vehicle components such as powertrain, suspension, doors, interior, etc. After painting in a paint shop, the vehicle BIW passes through an oven to cure the paint and/or other structural adhesives that are used. During heating in the oven, outer panels of the vehicle BIW heat up much faster than inner panels of the vehicle BIW since the outer panels are directly exposed to a heat source of the oven. In other words, the outer panels shield the inner panels from the heat source. The temperature difference induces thermal stress and may cause outer panels to buckle as the vehicle BIW passes through the oven.

SUMMARY

- (4) A heating system includes a conveying system configured to transport a plurality of vehicle body-in-whites (BIWs) sequentially through an oven room to cure paint applied in a paint room. A preheating system includes one or more robot arms. A heat source is connected to the one or more robot arms. A controller is configured to control the one or more robot arms based on a position of one of the vehicle BIWs on the conveying system and to position the heat source near or in direct contact with one or more inner components of the one of the vehicle BIWs to heat the one or more inner components prior to the one of the vehicle BIWs entering the oven room.
- (5) In other features, the heat source comprises a contact heat source. The contact heat source comprises a resistive heater. The contact heat source comprises an array of resistive heaters. The heat source comprises a non-contact heat source. The non-contact heat source includes an inductive heater including a coil. The non-contact heat source includes an inductive heater including an array of coils. The non-contact heat source includes an infrared heater. The non-contact heat source includes a heated air source.
- (6) In other features, the controller is configured to position the heat source while the one of the vehicle BIWs is moved by the conveying system.
- (7) A heating system includes a conveying system configured to transport a plurality of vehicle body-in-whites (BIWs) sequentially through a paint room and an oven room to cure paint applied in the paint room. A supplemental heating system is arranged inside of the oven room and includes a heat source, a controller, and one or more arms connected to the heat source and configured to extend into one of the vehicle BIWs to heat one or more interior components of the one of the vehicle BIWs to reduce a temperature differential relative to an outer surface of the one of the vehicle BIWs while the one of the vehicle BIWs passes through the oven room.
- (8) In other features, the heat source comprises a non-contact heat source. The non-contact heat source includes an infrared heater. A mirror connected to at least one of the one or more arms to divert a portion of infrared light output by the infrared heater onto the one or more interior components.
- (9) In other features, the non-contact heat source includes a heated air source and wherein the one or more arms include internal fluid channels configured to direct heater air onto the one or more interior components of the one of the vehicle BIWs. A diffuser is connected to at least one of the one or more arms to divert a portion of heated air from the heated air source.
- (10) In other features, the one or more arms include a first arm, a second arm movably connected to the first arm, and an actuator configured to extend the second arm into an interior of the one of the

vehicle BIWs to direct the heat source at the one or more interior components of the one of the vehicle BIWs.

(11) In other features, the one or more arms further include a third arm that rotates relative to the second arm. A first fluid channel in the first arm, a second fluid channel in the second arm and a third fluid channel in the third arm, wherein the first fluid channel is in fluid communication with a source of heated air, the second fluid channel, and the third fluid channel.

(12) Further areas of applicability of the present disclosure will become apparent from the detailed description, the claims and the drawings. The detailed description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure will become more fully understood from the detailed description and the accompanying drawings, wherein:

(2) FIG. 1A is a functional block diagram of an example of a contact heater configured to preheat a component of a vehicle BIW prior passing through to the oven according to the present disclosure;

(3) FIG. 1B is a functional block diagram of an example of a robot for positioning the contact heater relative to the vehicle BIW prior passing through to the oven according to the present disclosure;

(4) FIG. 2A is a functional block diagram of an example of a non-contact heater configured to preheat a component of a vehicle BIW prior passing through to the oven according to the present disclosure;

(5) FIG. 2B is a functional block diagram of an example of a robot for positioning the non-contact heater relative to the vehicle BIW prior passing through to the oven according to the present disclosure;

(6) FIGS. 3A and 3B are drawings illustrating an example of a supplemental heating system arranged in the oven to direct hot air at an inner surface of a vehicle BIW according to the present disclosure;

(7) FIGS. 4A and 4B are drawings illustrating an example of a supplemental heating system deployed in the oven to direct infrared light at an inner surface of a vehicle BIW according to the present disclosure;

(8) FIG. 5 illustrates the heating system installed inside of the oven according to the present disclosure; and

(9) FIG. 6 is a functional block diagram of an example of a control system for the supplemental heating systems in FIGS. 3A to 5 according to the present disclosure;

(10) In the drawings, reference numbers may be reused to identify similar and/or identical elements.

DETAILED DESCRIPTION

(11) The present disclosure relates preheating or supplemental heating of inner components/areas of a vehicle BIW to prevent thermal-induced distortion of outer panels of the vehicle BIW during curing in the oven. As described above, the vehicle body-in-white (BIW) is typically painted in a paint shop prior to assembly of other vehicle components. After being painted in the paint shop, the vehicle BIW passes through the oven to cure the wet paint and/or other structural adhesives that are used.

(12) During heating in the oven, vehicle outer panels heat up much faster than vehicle inner panels since the outer panels are directly exposed to a heat source of the oven. In other words, the outer panels may shield the inner panels from the heat source. The temperature difference induces thermal stress and may cause outer panels to buckle as the vehicle BIW passes through the oven.

(13) Referring now to FIGS. 1A and 1B, systems and methods are shown for preheating selected portions of the vehicle BIW before the vehicle BIW enters the oven using contact heating to reduce heat distortion. In some examples, the contact heating includes resistive heating.

(14) In FIG. 1A, a portion **20** of a vehicle BIW is shown. Leads **24** and **28** from a resistive heater **22** are connected inner components/areas of the vehicle BIW and current is supplied between the leads **24** for a predetermined period. The path between the leads **24** has a non-zero resistance and the current flowing between the leads **24** heats the inner components/areas there between.

(15) In FIG. 1B, a conveying system **32** propels vehicle BIWs **34** through a paint room (not shown) and then through an oven **31** for curing of the paint and/or structural adhesives. A robot includes one or more robot arms **36** that positions N pairs of leads **24-1**, **24-2**, . . . , and **24-N** of the resistive heater **22** adjacent to the inner component/area of the vehicle BIW **34** to be preheated. As can be appreciated, a single robot arm can position a pair of leads, two or more separately controlled robots can position two or more leads, respectively, a single robot arm can position a fixture including multiple leads, and/or combinations thereof.

(16) A controller **30** is configured to coordinate movement of the one or more robot arms **36** (into position in the vehicle BIW and application of the current through the leads **24**) relative to the vehicle BIWs on the conveying system **32**. In other words, as the vehicle BIW **34** is moved on a conveying system, the one or more robot arms **36** extend into the vehicle BIW, position the leads **24** in contact with the vehicle BIW while it is moving, apply current for heating, and then retract. The process is repeated for the next vehicle BIW on the conveying system.

(17) Resistive heating is the most direct and efficient method of heating targeted workpieces, even if the workpieces are encapsulated. Resistive heating is highly efficient since only a few seconds of heating is needed. Little or no extra workspace is needed.

(18) Referring now to FIGS. 2A and 2B, a method for reducing heat distortion includes preheating selected portions of the vehicle BIW prior to heating in the oven using non-contact heating. While the foregoing example includes inductive heating, convective heating using hot air and/or infrared heating can also be used. In FIG. 2A, an inductive heater **111** includes a controller and power supply **112** and a conductor **114** with one or more coils **118**. The controller and power supply **112** outputs power through the one or more coils **118** that are arranged adjacent to a desired area on a body inner structure to be preheated. The one or more coils **118** generate a magnetic field that induces eddy currents in the vehicle BIW to cause heating of the selected portions of the vehicle BIW.

(19) In some examples, the one or more coils **118** include a single coil that heats a single portion of the vehicle BIW and/or is sequentially moved to multiple portions of the vehicle BIW. This arrangement is low-cost, relatively flexible, and supports low throughput. In some examples, the one or more coils **118** include an array of coils that are arranged by a fixture in one or more predetermined patterns corresponding one or more portions located inside of the vehicle BIW. In other examples, the one or more coils are arranged adjacent to different portions of the body inner structure to allow multiple components to be heated at the same time prior to entering the oven. This arrangement has a higher cost, is less flexible, and supports higher throughput.

(20) In FIG. 2B, the conveying system **32** carries the vehicle BIW **34** into the oven **31**. One or more robot arms **36** position one or more coils of the inductive heater **111** relative to the selected portion of the vehicle BIW **34** to be heated. In other words, as the vehicle BIW **34** is moved on a conveying system, the one or more robot arms **36** extend into the vehicle BIW, position the one or more coils **118** in contact with the vehicle BIW while it is moving, apply current for heating, and then retract. The process is repeated for the next vehicle BIW on the conveying system.

(21) Referring now to FIGS. 3A and 3B, a preheating system **200** is used to heat an inner surface **214** of a portion **210** of a vehicle BIW located inside of the oven using supplemental heating such as heated air. The outer surface **212** of the vehicle BIW is primarily heated by the oven. The preheating system **200** is mounted inside of the oven (such as on an oven wall **218**) and includes a

position adjuster **219**. In some examples, the position adjuster **219** includes an extendable arm **220** slidably received by a mounted arm **222**. In some examples, rollers **226** guide the extendable arm **220**. In some examples, the rollers **226** are rotated by a motor (not shown) to controllably move the extendable arm **220** inwardly and outwardly. In other examples, a linear actuator (not shown) such as cylinder or screw motor is used.

(22) An arm **238** is connected to an end of the extendable arm **220**. In some examples, the arm **238** is fixed relative to the extendible arm **220** and in other examples the arm rotates relative to an axis **234**. In some examples, a positioning motor **230** adjusts an angular position of the arm **238** relative to the extendable arm **220**. Heated air is supplied through fluid channels arranged inside of or outside of the mounted arm **222**, the extendable arm **220**, the arm **238** and an outlet **239** onto an inner surface of the vehicle BIW to be heated.

(23) In some examples, the heated air that is supplied is already generated by the oven and redirected. The heated air is supplied to a region behind the oven wall **218** of the oven and flows through fluid channels **241** in the mounted arm **222**, the extendable arm **220**, the arm **238** and the outlet **239** onto the inner surface of the vehicle BIW to be heated.

(24) In FIG. **3B**, a diffuser **260** can be used to redirect the hot air supplied from the outlet **239**. In some examples, the diffuser **260** is spaced from the outlet and connected by a supporting member **264** to the arm **238** and/or the extendable arm **220**. In some examples, a diffuser surface **266** is spaced from the outlet **239** and is used to redirect the heated air onto another portion of the vehicle BIW. The diffuser **260** can be used for more complex inner components/areas that may be oriented in a direction that is difficult to reach using the heater air directly from the outlet **239**. In some examples, the diffuser surface **266** can include an enclosed surface with open ends such as a curved tube or an open surface such as a shaped surface.

(25) Referring now to FIGS. **4A** and **4B**, a preheating system **300** is used to preheat an inner surface **214** of the portion **210** of a vehicle BIW using an infrared heating. The outer surface **212** is primarily heated by the oven. The preheating system **300** is mounted to the oven wall **218** and includes the position adjuster **219**. An infrared lamp **310** is connected to an end of the extendable arm **220**. The infrared lamp **310** is fixed to the extendable arm **220** or rotates relative to the extendable arm **220** about the axis **234**. In some examples, the positioning motor **230** adjusts the angular position of the infrared lamp **310** relative to the extendable arm **220**. The infrared lamp **310** is directed at the portion of the vehicle BIW to be heated.

(26) In FIG. **4B**, a mirror **322** or other reflective surface can be used to redirect the infrared light from the infrared lamp **310** to heat more complex inner components/areas that may be oriented in a direction that is difficult to reach using the infrared radiation directly from the infrared lamp **310**. In some examples, the mirror **322** is connected by a supporting member **320** to the arm **238** and/or the extendable arm **220**.

(27) Referring now to FIG. **5**, the vehicle BIWs move through an inner volume **404** of the oven **400** on a conveying system **410** and are heated by the oven to cure the paint and/or bonding adhesives. The conveying system **410** transports a vehicle BIW **412** through the inner volume **404** of the oven **400**. A supplemental heating system **418** includes a positioning system **420** that adjusts a position of a source of heat **424** relative to the vehicle BIW **412** that is moving. In some examples, the positioning system **420** includes a first positioner **430** that moves the output of the supplemental heater laterally into the volume and a second positioner **434** that moves the supplemental heater in a longitudinal direction parallel to the movement of the vehicle BIW on the conveying system **410** so that the supplement heating system **418** is moving in synchronization with the vehicle BIW **412**.

(28) Referring now to FIG. **6**, a controller **450** coordinates movement of the vehicle BIW relative to the supplemental heating system. The controller **450** coordinates movement relative to the position of the vehicle BIW and the inner components/areas thereof that need to be heated. The controller **450** determines the desired position of the supplemental heater relative to the vehicle BIW and controls the positioning system **420** in response thereto.

(29) In some examples, the positioning system **420** includes a first positioner **430** configured to extend and retract the arm. In some examples, the first positioner **430** includes rollers with motors configured to rotate in first and second directions to extend or retract the arm. In other examples, the first positioner **430** includes a cylinder that extends and retracts the arm using fluid such as liquid or gas, a screw motor or other linear actuator.

(30) A second positioner **434** is configured to move the supplemental heating system longitudinally approximately in sync with the vehicle BIW on the conveying system while supplemental heating is performed. After performing supplemental heating, the first positioner **430** retracts the arm and the second positioner **434** moves the supplemental heating system in a direction opposite to the conveying direction to align with the next vehicle BIW. When positioned relative to the next vehicle BIW, the first positioner **430** extends the arm and the second positioner **434** moves approximately in sync with the conveying system while supplemental heating is performed again.

(31) The foregoing description is merely illustrative in nature and is in no way intended to limit the disclosure, its application, or uses. The broad teachings of the disclosure can be implemented in a variety of forms. Therefore, while this disclosure includes particular examples, the true scope of the disclosure should not be so limited since other modifications will become apparent upon a study of the drawings, the specification, and the following claims. It should be understood that one or more steps within a method may be executed in different order (or concurrently) without altering the principles of the present disclosure. Further, although each of the embodiments is described above as having certain features, any one or more of those features described with respect to any embodiment of the disclosure can be implemented in and/or combined with features of any of the other embodiments, even if that combination is not explicitly described. In other words, the described embodiments are not mutually exclusive, and permutations of one or more embodiments with one another remain within the scope of this disclosure.

(32) Spatial and functional relationships between elements (for example, between modules, circuit elements, semiconductor layers, etc.) are described using various terms, including “connected,” “engaged,” “coupled,” “adjacent,” “next to,” “on top of,” “above,” “below,” and “disposed.” Unless explicitly described as being “direct,” when a relationship between first and second elements is described in the above disclosure, that relationship can be a direct relationship where no other intervening elements are present between the first and second elements but can also be an indirect relationship where one or more intervening elements are present (either spatially or functionally) between the first and second elements. As used herein, the phrase at least one of A, B, and C should be construed to mean a logical (A OR B OR C), using a non-exclusive logical OR, and should not be construed to mean “at least one of A, at least one of B, and at least one of C.”

(33) In the figures, the direction of an arrow, as indicated by the arrowhead, generally demonstrates the flow of information (such as data or instructions) that is of interest to the illustration. For example, when element A and element B exchange a variety of information but information transmitted from element A to element B is relevant to the illustration, the arrow may point from element A to element B. This unidirectional arrow does not imply that no other information is transmitted from element B to element A. Further, for information sent from element A to element B, element B may send requests for, or receipt acknowledgements of, the information to element A.

(34) In this application, including the definitions below, the term “module” or the term “controller” may be replaced with the term “circuit.” The term “module” may refer to, be part of, or include: an Application Specific Integrated Circuit (ASIC); a digital, analog, or mixed analog/digital discrete circuit; a digital, analog, or mixed analog/digital integrated circuit; a combinational logic circuit; a field programmable gate array (FPGA); a processor circuit (shared, dedicated, or group) that executes code; a memory circuit (shared, dedicated, or group) that stores code executed by the processor circuit; other suitable hardware components that provide the described functionality; or a combination of some or all of the above, such as in a system-on-chip.

(35) The module may include one or more interface circuits. In some examples, the interface

circuits may include wired or wireless interfaces that are connected to a local area network (LAN), the Internet, a wide area network (WAN), or combinations thereof. The functionality of any given module of the present disclosure may be distributed among multiple modules that are connected via interface circuits. For example, multiple modules may allow load balancing. In a further example, a server (also known as remote, or cloud) module may accomplish some functionality on behalf of a client module.

(36) The term code, as used above, may include software, firmware, and/or microcode, and may refer to programs, routines, functions, classes, data structures, and/or objects. The term shared processor circuit encompasses a single processor circuit that executes some or all code from multiple modules. The term group processor circuit encompasses a processor circuit that, in combination with additional processor circuits, executes some or all code from one or more modules. References to multiple processor circuits encompass multiple processor circuits on discrete dies, multiple processor circuits on a single die, multiple cores of a single processor circuit, multiple threads of a single processor circuit, or a combination of the above. The term shared memory circuit encompasses a single memory circuit that stores some or all code from multiple modules. The term group memory circuit encompasses a memory circuit that, in combination with additional memories, stores some or all code from one or more modules.

(37) The term memory circuit is a subset of the term computer-readable medium. The term computer-readable medium, as used herein, does not encompass transitory electrical or electromagnetic signals propagating through a medium (such as on a carrier wave); the term computer-readable medium may therefore be considered tangible and non-transitory. Non-limiting examples of a non-transitory, tangible computer-readable medium are nonvolatile memory circuits (such as a flash memory circuit, an erasable programmable read-only memory circuit, or a mask read-only memory circuit), volatile memory circuits (such as a static random access memory circuit or a dynamic random access memory circuit), magnetic storage media (such as an analog or digital magnetic tape or a hard disk drive), and optical storage media (such as a CD, a DVD, or a Blu-ray Disc).

(38) The apparatuses and methods described in this application may be partially or fully implemented by a special purpose computer created by configuring a general purpose computer to execute one or more particular functions embodied in computer programs. The functional blocks, flowchart components, and other elements described above serve as software specifications, which can be translated into the computer programs by the routine work of a skilled technician or programmer.

(39) The computer programs include processor-executable instructions that are stored on at least one non-transitory, tangible computer-readable medium. The computer programs may also include or rely on stored data. The computer programs may encompass a basic input/output system (BIOS) that interacts with hardware of the special purpose computer, device drivers that interact with particular devices of the special purpose computer, one or more operating systems, user applications, background services, background applications, etc.

(40) The computer programs may include: (i) descriptive text to be parsed, such as HTML (hypertext markup language), XML (extensible markup language), or JSON (JavaScript Object Notation) (ii) assembly code, (iii) object code generated from source code by a compiler, (iv) source code for execution by an interpreter, (v) source code for compilation and execution by a just-in-time compiler, etc. As examples only, source code may be written using syntax from languages including C, C++, C #, Objective-C, Swift, Haskell, Go, SQL, R, Lisp, Java®, Fortran, Perl, Pascal, Curl, OCaml, Javascript®, HTML5 (Hypertext Markup Language 5th revision), Ada, ASP (Active Server Pages), PHP (PHP: Hypertext Preprocessor), Scala, Eiffel, Smalltalk, Erlang, Ruby, Flash®, Visual Basic®, Lua, MATLAB, SIMULINK, and Python®.

Claims

1. A heating system, comprising: a conveying system configured to transport a plurality of vehicle body-in-whites (BIWs) sequentially through a paint room and an oven room to cure paint applied in the paint room; a supplemental heating system arranged inside of the oven room and including: a heat source; a controller; and one or more arms connected to the heat source and configured to extend into one of the vehicle BIWs to heat one or more interior components of the one of the vehicle BIWs to reduce a temperature differential relative to an outer surface of the one of the vehicle BIWs while the one of the vehicle BIWs passes through the oven room.
 2. The heating system of claim 1, wherein the one or more arms includes: a first arm; a second arm movably connected to the first arm; and an actuator configured to extend the second arm into an interior of the one of the vehicle BIWs to direct the heat source at the one or more interior components of the one of the vehicle BIWs.
 3. The heating system of claim 2, wherein the one or more arms further include a third arm that rotates relative to the second arm.
 4. The heating system of claim 3, further comprising a first fluid channel in the first arm, a second fluid channel in the second arm and a third fluid channel in the third arm.
 5. The heating system of claim 4, wherein the first fluid channel is in fluid communication with a source of heated air, the second fluid channel, and the third fluid channel.
 6. The heating system of claim 1, wherein the heat source comprises a non-contact heat source.
 7. The heating system of claim 6, wherein the non-contact heat source includes an infrared heater.
 8. The heating system of claim 7, further comprising a mirror connected to at least one of the one or more arms to divert a portion of infrared light output by the infrared heater onto the one or more interior components.
 9. The heating system of claim 6, wherein the non-contact heat source includes a heated air source and wherein the one or more arms include internal fluid channels configured to direct heater air onto the one or more interior components of the one of the vehicle BIWs.
 10. The heating system of claim 9, further comprising a diffuser connected to at least one of the one or more arms to divert a portion of heated air from the heated air source.
-